

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386193
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Park; Sang Ok et al.

Lens moving apparatus

Abstract

A lens moving apparatus includes a bobbin including a first coil disposed therearound, a first magnet disposed to face the first coil, a housing for supporting the first magnet, upper and lower elastic members each coupled to both the bobbin and the housing, a base disposed to be spaced apart from the housing by a predetermined distance, a second coil disposed to face the first magnet, a printed circuit board on which the second coil is mounted, a plurality of support members, which support the housing such that the housing is movable in second and/or third directions and which connect at least one of the upper and lower elastic members to the printed circuit board, and a conductive member for conductively connecting the upper and lower elastic members.

Inventors:	Park; Sang Ok (Seoul, KR), Min; Sang Jun (Seoul, KR)
Applicant:	LG Innotek Co., Ltd. (Seoul, KR)
Family ID:	54427612
Assignee:	LG INNOTEK CO., LTD. (Seoul, KR)
Appl. No.:	18/633619
Filed:	April 12, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240255771 A1	Aug. 01, 2024

Foreign Application Priority Data

KR	10-2014-0158683	Nov. 14, 2014
KR	10-2014-0158686	Nov. 14, 2014

Related U.S. Application Data

continuation parent-doc US 16941203 20200728 US 11982820 child-doc US 18633619
continuation parent-doc US 16029182 20180706 US 10761339 20200901 child-doc US 16941203
continuation parent-doc US 14942297 20151116 US 10042178 20180807 child-doc US 16029182

Publication Classification

Int. Cl.: **G02B27/64** (20060101); **G02B7/08** (20210101); **G03B5/02** (20210101); **G03B5/04** (20210101); **H01F7/20** (20060101); **H01F27/28** (20060101); **H01F27/32** (20060101)

U.S. Cl.:

CPC **G02B27/646** (20130101); **G02B7/08** (20130101); **G03B5/02** (20130101); **G03B5/04** (20130101); **H01F7/20** (20130101); **H01F27/2804** (20130101); **H01F27/325** (20130101);

Field of Classification Search

CPC: G02B (27/646); G02B (7/08); G02B (7/04); G02B (7/09); G02B (27/642); G02B (27/644); G03B (5/02); G03B (5/04); G03B (2205/0007); H01F (7/20); H01F (27/2804); H01F (27/325)

USPC: 359/557

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10761339	12/2019	Park et al.	N/A	N/A
2012/0229901	12/2011	Moriya et al.	N/A	N/A
2013/0050828	12/2012	Sato et al.	N/A	N/A
2013/0107068	12/2012	Kim et al.	N/A	N/A
2013/0107112	12/2012	Oh	N/A	N/A
2013/0136438	12/2012	Lee et al.	N/A	N/A
2014/0192260	12/2013	Oh	N/A	N/A
2014/0327965	12/2013	Chen	359/557	H04N 23/687
2015/0261067	12/2014	Jung et al.	N/A	N/A
2016/0109681	12/2015	Lam	N/A	N/A
2016/0109721	12/2015	Min et al.	N/A	N/A
2016/0209621	12/2015	Park et al.	N/A	N/A
2016/0223830	12/2015	Oh	N/A	N/A
2016/0341927	12/2015	Chen et al.	N/A	N/A
2017/0254979	12/2016	Bai	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101563836	12/2008	CN	N/A
102472944	12/2011	CN	N/A
102955324	12/2012	CN	N/A

103095974	12/2012	CN	N/A
203054325	12/2012	CN	N/A
203275847	12/2012	CN	N/A
104142553	12/2013	CN	N/A
204009314	12/2013	CN	N/A
2 921 892	12/2014	EP	N/A
61-502648	12/1985	JP	N/A
H07-73488	12/1994	JP	N/A
H09-230226	12/1996	JP	N/A
2001-305598	12/2000	JP	N/A
2002-063724	12/2001	JP	N/A
2010-134375	12/2009	JP	N/A
2011-65140	12/2010	JP	N/A
2011-203283	12/2010	JP	N/A
2012-197325	12/2011	JP	N/A
2013-24944	12/2012	JP	N/A
2013-120248	12/2012	JP	N/A
2013-210550	12/2012	JP	N/A
2014-126668	12/2013	JP	N/A
2014-219675	12/2013	JP	N/A
2016-20939	12/2015	JP	N/A
10-2012-0027751	12/2011	KR	N/A
10-2013-0050626	12/2012	KR	N/A
10-2014-0084971	12/2013	KR	N/A
2013-17654	12/2012	TW	N/A
WO-2013/027927	12/2012	WO	N/A

OTHER PUBLICATIONS

European Search Report dated Mar. 16, 2016, in European Application No. 15192898.3. cited by applicant

European Search Report dated Jul. 26, 2018 in European Application No. 18160094.1. cited by applicant

Notice of Allowance dated Feb. 2, 2021 in Chinese Application No. 201510785707.2, along with its English translation. cited by applicant

Office Action dated Jul. 8, 2021 in Japanese Application No. 2020-122127. cited by applicant

Office Action dated May 10, 2023 in European Application No. 18 160 094. cited by applicant

Primary Examiner: Duong; Henry

Attorney, Agent or Firm: Saliwanchik, Lloyd & Eisenschenk

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/941,203, filed Jul. 28, 2020; which is a continuation of U.S. patent application Ser. No. 16/029,182, filed Jul. 6, 2018, now U.S. Pat. No. 10,761,339, issued Sep. 1, 2020; which is a continuation of U.S. patent application Ser. No. 14/942,297, filed Nov. 16, 2015, now U.S. Pat. No. 10,042,178, issued Aug. 7, 2018; which claims priority to Korean Patent

TECHNICAL FIELD

(1) Embodiments relate to a lens moving apparatus.

BACKGROUND

- (2) It is difficult to adopt voice coil motor (VCM) technology, which is typically used in conventional camera modules, for use in an ultracompact camera module, which aims at achieving low power consumption, and thus research into the technology has been actively undertaken.
- (3) A camera module mounted in a small-sized electronic product, such as a smart phone, may be frequently subjected to shocks during use. In addition, the camera module may minutely shake due to the trembling of the user's hand while taking a photograph. Therefore, there is a high necessity for a technology capable of incorporating an optical image stabilizer into the camera module.
- (4) Various handshake correction technologies have been recently researched. In such handshake correction, there is the need to reduce the driving force required for handshake correction and to increase the durability of the lens moving apparatus and the camera module. Among such handshake correction technologies, there is a technology of correcting handshake by moving an optical module in the x-axis and y-axis directions, which define a plane perpendicular to the optical axis. The technology is required to accurately and rapidly move the optical system in the plane perpendicular to the optical axis for image correction.

BRIEF SUMMARY

- (5) Embodiments provide a lens moving apparatus, which is able to reduce driving force for handshake correction and to increase durability, and a camera module including the same.
- (6) Furthermore, embodiments provide a lens moving apparatus, which has a simplified structure and enables accurate and rapid handshake correction, and a camera module including the same.
- (7) In one embodiment, a lens moving apparatus includes a bobbin including a first coil, a first magnet disposed to face the first coil, a housing for supporting the first magnet, upper and lower elastic members each coupled to both the bobbin and the housing, a base disposed to be spaced apart from the housing, a second coil disposed to face the first magnet, a printed circuit board on which the second coil is mounted, a plurality of support members, which support the housing such that the housing is movable in second and/or third directions and which connect at least one of the upper and lower elastic members to the printed circuit board, and a conductive member for conductively connecting the upper and lower elastic members.
- (8) In another embodiment, a lens moving apparatus includes a housing, a bobbin disposed in the housing so as to move in a first direction, upper and lower elastic members each coupled to both the housing and the bobbin, a printed circuit board conductively connected to at least one of the upper and lower elastic members, and at least one support member, which supports the housing such that the housing is movable with respect to the base in second and/or third directions and which conductively connects at least one of the upper and lower elastic members to the printed circuit board, the at least one support member being integrated with two conductive wires.
- (9) In a further embodiment, a lens moving apparatus includes a housing, a bobbin disposed in the housing so as to move in a first direction, upper and lower elastic members each coupled to both the housing and the bobbin, a printed circuit board conductively connected to at least one of the upper and lower elastic members, and at least one support member, which supports the housing such that the housing is movable in second and/or third directions and which conductively connects at least one of the upper and lower elastic members to the printed circuit board, the at least one support member being integrated with at least two conductive wires, wherein the at least one support member includes an electrical insulating coating member, which sheathes the two conductive wires and which includes a projecting insulator protruding from an end thereof, the projecting insulator being positioned between the two conductive wires such that adjacent upper

elastic members are spaced apart from each other and are thus conductively isolated from each other.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Arrangements and embodiments may be described in detail with reference to the following drawings, in which like reference numerals refer to like elements and wherein:
- (2) FIG. 1 is a schematic perspective view showing a lens moving apparatus according to a first embodiment;
- (3) FIG. 2 is an exploded perspective view showing the lens moving apparatus according to the embodiment;
- (4) FIG. 3 is a perspective view showing a housing according to the embodiment, from which a cover member is removed;
- (5) FIG. 4 is an exploded perspective view of the lens moving apparatus according to the embodiment, which shows the bobbin, the first coil, the magnet, the first sensor and the sensor substrate;
- (6) FIG. 5A is a plan view showing the bobbin and the magnet shown in FIG. 4;
- (7) FIG. 5B is a perspective view showing another embodiment of the sensor substrate shown in FIG. 4;
- (8) FIG. 5C is a rear perspective view showing one embodiment of the first sensor and the sensor substrate shown in FIG. 4;
- (9) FIG. 6 is a top perspective view of the housing according to the embodiment;
- (10) FIG. 7 is a bottom exploded perspective view of the housing and the magnet according to the embodiment;
- (11) FIG. 8 is a cross-sectional view taken along line I-I' of FIG. 3;
- (12) FIG. 9 is a graph illustrating the accuracy of the first sensor as a function of the position of the first sensor;
- (13) FIG. 10 is a top perspective view of the bobbin, the housing, the upper elastic member, the first sensor, the sensor substrate and a plurality of support members, all of which are coupled to one another;
- (14) FIG. 11 is a bottom perspective view of the bobbin, the housing, the lower elastic member and the plurality of support members, all of which are coupled to one another;
- (15) FIG. 12 is a perspective of the upper elastic member, the lower elastic member, the support members, conductive members and the printed circuit board according to the embodiment, all of which are assembled to one another;
- (16) FIG. 13 is a front view showing the upper elastic member, the lower elastic member, the support members, the conductive member, the printed circuit board, the bobbin and the first coil according to the embodiment, all of which are assembled to one another;
- (17) FIG. 14 is an exploded perspective view of the base, the second coil and the printed circuit board;
- (18) FIG. 15 is a perspective view showing a lens moving apparatus according to a second embodiment of the present invention;
- (19) FIG. 16 is an exploded perspective view showing the lens moving apparatus according to the second embodiment;
- (20) FIG. 17 is a perspective view showing some of the components of the lens moving apparatus according to the second embodiment;
- (21) FIG. 18 is a perspective view of FIG. 17, from which the bobbin and the first coil are removed;

- (22) FIG. 19A is a perspective view of the area A of FIGS. 17 and 18;
- (23) FIG. 19B is a view showing the support member according to an embodiment of the present invention;
- (24) FIG. 19C is a view showing the support member according to another embodiment of the present invention;
- (25) FIG. 20A is a perspective view showing the area B of FIG. 18;
- (26) FIG. 20B is a view showing the support member according to another embodiment;
- (27) FIG. 21 is a plan view of FIG. 18;
- (28) FIGS. 22A and 22B are plan views showing the area A of FIG. 21; and
- (29) FIG. 23 is a plan view showing the area B of FIG. 21.

DETAILED DESCRIPTION

(30) Hereinafter, embodiments will be described with reference to the attached drawings. In the drawings, the same or similar elements are denoted by the same reference numerals even though they are depicted in different drawings. In the following description, a detailed description of known functions and configurations incorporated herein will be omitted when it may make the subject matter of the disclosure rather unclear. Those skilled in the art will appreciate that some features in the drawings are exaggerated, reduced, or simplified for ease in description, and drawings and elements thereof are not always shown in proportion.

(31) For reference, in the respective drawings, a rectangular coordinate system (x, y, z) may be used. In the drawings, the x-axis and the y-axis mean a plane perpendicular to an optical axis and, for convenience, an optical axis (z-axis) direction may be referred to as a first direction, an x-axis direction may be referred to as a second direction, and a y-axis direction may be referred to as a third direction.

(32) A handshake correction apparatus, which is applied to compact camera modules of mobile devices such as smart phones or tablet PCs, refers to an apparatus configured to inhibit the contour of an image captured when taking a still image from not being clearly formed due to vibrations caused by the trembling of the user's hand.

(33) In addition, an autofocus apparatus is configured to automatically focus the subject image on the surface of an image sensor. The handshake correction apparatus and the autofocus apparatus may be configured in various manners. The lens moving apparatus according to the embodiments may perform the handshake correction and/or autofocus operations in such a manner as to move an optical module, composed of a plurality of lenses, in a first direction perpendicular to the optical axis or in a plane defined by the second and third directions, which are perpendicular to the first direction.

(34) The second or third direction may include not only the x-axis direction or the y-axis direction but also a direction which is substantially close to the x-axis direction or the y-axis direction. In other words, in terms of driving in the embodiments, although a housing 140 may move in a direction parallel to the x-axis or the y-axis, the housing may move in a direction which is slightly inclined with respect to the x-axis or the y-axis in the state of being supported by a support member 220.

First Embodiment

(35) FIG. 1 is a schematic perspective view showing a lens moving apparatus according to a first embodiment. FIG. 2 is an exploded perspective view of the lens moving apparatus shown in FIG. 1.

(36) Referring to FIGS. 1 and 2, the lens moving apparatus according to the embodiment may include a first lens moving unit, a second lens moving unit, and a cover member 300. The first lens moving unit may serve as the above-mentioned autofocus apparatus. In other words, the first lens moving unit may serve to move a bobbin 110 in the first direction by virtue of the interaction between a magnet 130 and a first coil 120.

(37) The second lens moving unit may serve as the handshake correction apparatus. In other words,

the second lens moving unit may serve to move all or a portion of the first lens moving unit in the second and/or third directions by virtue of the interaction between the magnet **130** and the second coil **230**.

(38) The cover member **300** may be configured to have an approximate box shape so as to accommodate the first and second lens moving units therein.

(39) FIG. **3** is a perspective view showing the lens moving apparatus according to the embodiment, from which the cover member **300** shown in FIG. **1** is removed.

(40) The first lens moving unit may include the bobbin **110**, the first coil **120**, the magnet **130**, a housing **140**, an upper elastic member **150**, a lower elastic member **160**, a first sensor **170** and a sensor substrate **180**.

(41) FIG. **4** is an exploded perspective view of the lens moving apparatus according to the embodiment, which shows the bobbin **110**, the first coil **120**, the magnet **130** (**130-1**, **130-2**, **130-3** and **130-4**), the first sensor **170** and the sensor substrate **180**.

(42) FIG. **5A** is a plan view showing the bobbin **110** and the magnet **130** (**130-1**, **130-2**, **130-3** and **130-4**) shown in FIG. **4**. FIG. **5B** is a perspective view showing another embodiment of the sensor substrate **180** shown in FIG. **4**. FIG. **5C** is a rear perspective view showing one embodiment of the first sensor **170** and the sensor substrate **180** shown in FIG. **4**.

(43) Referring to the above-mentioned drawings, the bobbin **110** may be disposed in the internal space defined in the housing **140** so as to reciprocate in the first direction, which is the optical axis direction, or in a direction parallel to the first direction. As shown in FIG. **4**, the bobbin **110** may be provided therearound with the first coil **120** such that the first coil **120** and the magnet **130** interact with each other in an electromagnetic manner. To this end, the magnet **130** may be disposed around the bobbin **110** so as to face the first coil **120**.

(44) When the bobbin **110** performs the upward and/or downward movements in the first direction, which is the optical axis direction, or in a direction parallel to the first direction to fulfill the autofocus function, the bobbin **110** may be elastically supported by means of the upper and lower elastic members **150** and **160**. To this end, the upper and lower elastic members **150** and **160** may be coupled to the bobbin **110** and the housing **140**, as will be described later.

(45) Although not shown in the drawings, the lens moving apparatus may include a lens barrel (not shown), which is provided on the inner side surface (i.e. the inner surface) of the bobbin **110** and on which at least one lens is mounted. The lens barrel may be mounted on the inner surface of the bobbin **110** in various ways. For example, the lens barrel may be directly secured to the interior of the bobbin **110**, or a single lens may be integrally formed with the bobbin **110** without using the lens barrel. The lens mounted on the lens barrel may include a single lens, or may include two or more lenses, which constitute an optical system.

(46) According to another embodiment, although not shown in the drawings, the bobbin **110** may be provided on the inner circumferential surface thereof with a female threaded portion and on the outer circumferential surface thereof with a male threaded portion corresponding to the female threaded portion such that the lens barrel is coupled to the bobbin **110** by virtue of threaded engagement between the female and male threaded portions. However, the embodiments are not limited thereto.

(47) The bobbin **110** may include first and second protrusions **111** and **112**.

(48) The first protrusion **111** may include a guide portion **111a** and a first stopper **111b**. The guide portion **111a** may serve to guide the installation of the upper elastic member **150** at a predetermined position. For example, the guide portion **111a** may guide the passage of a first frame connector **153** of the upper elastic member **150**, as shown in FIG. **3**. To this end, according to the embodiment, a plurality of guide portions **111a** may protrude in the second and third directions, which are perpendicular to the first direction. The guide portions **111a** may be provided in a plane defined by the x axis and the y axis so as to be symmetrical about the center point of the bobbin **110**, as shown in the drawings, or may be provided so as to be asymmetrical about the center point of the bobbin

110 without interference with other components, unlike the embodiment shown in the drawings.

(49) The second protrusion **112** may include a plurality of second protrusions, which protrude in the second and third directions, which are perpendicular to the first direction. A first inner frame **151** of the upper elastic member **150**, which will be described later, may be mounted on the upper surfaces **112a** of the second protrusions **112**.

(50) FIG. **6** is a top perspective view of the housing **140** according to the embodiment. FIG. **7** is a bottom exploded perspective view of the housing **140** and the magnet **130** according to the embodiment.

(51) Referring to FIG. **6**, the housing **140** may include first mounting recesses **146**, which are formed at positions corresponding to those of the first and second protrusions **111** and **112**. When the bobbin **110** moves in the first direction, which is the optical axis direction, or in a direction parallel to the first direction for the autofocus function, the first stoppers **111b** of the first protrusions **111** and the second protrusions **112** serve to inhibit the bottom surface of the body of the bobbin **110** from directly colliding with the upper surfaces of a base **210** and a printed circuit board **250** even when the bobbin **110** moves beyond a predetermined range due to external impacts or the like. To this end, the first stoppers **111b** may protrude from the outer circumferential surface of the bobbin **110** in a radial direction, that is, in the second or third direction, so as to be longer than the guide portions **111a**, and the second protrusions **112** may also protrude in the lateral direction so as to be larger than the upper surfaces thereof on which the upper elastic member **150** is mounted.

(52) Referring to FIG. **6**, when the state in which the bottom surfaces of the first and second protrusions **111** and **112** are in contact with the bottom surfaces of the first mounting recesses **146** is set to be the initial position, the autofocus function may be controlled as in the unidirectional control of a conventional voice coil motor (VCM). Specifically, the autofocus function may be fulfilled in such a manner that the bobbin **110** is raised when current is supplied to the first coil **120** and is lowered when the supply of current is interrupted.

(53) However, when the state in which the bottom surfaces of the first and second protrusions **111** and **112** are spaced apart from the bottom surfaces of the first mounting recesses **146** by a predetermined distance is set to be the initial position, the autofocus function may be controlled in accordance with the direction of current, as in the bidirectional control of a conventional voice coil motor. Specifically, the autofocus function may be fulfilled by moving the bobbin **110** upward or downward. For example, the bobbin **110** may be moved upward upon the application of forward current and may be moved downward upon the application of reverse current.

(54) The housing **140** may include third protrusions **148**, which are provided at positions corresponding to spaces each having a first width $W1$, which are defined between the first and second protrusions **111** and **112**. The surfaces of the third protrusions **148** that face the bobbin **110** may have the same shape as the side surface of the bobbin **110**. At this point, the first width $W1$ between the first and second protrusions **111** and **112**, shown in FIG. **4**, and the second width $W2$ between the third protrusions **148**, shown in FIG. **6** may be set to have a predetermined tolerance therebetween. Accordingly, the displacement of the third protrusions **148** between the first and second protrusions **111** and **112** may be restricted. As a result, even if the bobbin **110** is subjected to a force tending to rotate the bobbin **110** about the optical axis rather than a force tending to move the bobbin **110** in the optical axis direction, it is possible to inhibit the rotation of the bobbin **110** by means of the third protrusions **148**.

(55) According to the embodiment, the first sensor **170** may be disposed, coupled or mounted on the bobbin **110**, and may thus be moved together with the bobbin **110**. The first sensor **170** may detect displacement of the bobbin **110** in the first direction, which is the optical axis direction, and may output the result of the detection as a feedback signal. By using the result of the detection which is obtained by detecting displacement of the bobbin **110** in the first direction or in a direction parallel to the first direction using the feedback signal, displacement of the bobbin **110** in the first

direction or a direction parallel to the first direction may be adjusted. The first sensor **170** may be disposed, coupled or mounted on the housing **140** in various manners, and may receive current in various fashions depending on the manner in which the first sensor **170** is disposed, coupled or mounted.

(56) According to one embodiment, the first sensor **170** may be coupled to the housing **140**, and an additional magnet (not shown), which faces the first sensor **170**, may be disposed on the bobbin **110**. The first sensor **170** may be disposed, coupled or mounted on side surfaces or corners of the first mounting recess **146** of the housing **140** shown in FIG. **6** (for example, the surface of the third protrusion **148**). In this case, by the magnetic force which is exerted on the magnet **130** from the additional sensor magnet, the bobbin **110**, which is moved in the first direction, that is, the optical axis direction, or a direction parallel to the first direction, may be tilted, and the accuracy of the feedback signal may be deteriorated. In consideration of this, another additional sensor magnet may be disposed, coupled or mounted on the bobbin **110** at a position at which the interaction between the first additional sensor magnet and the magnet **130** is minimized.

(57) According to another embodiment, the first sensor **170** may be directly disposed, coupled or mounted on the outer circumferential surface of the bobbin **110**. In this case, surface electrodes (not shown) may be provided on the outer circumferential surface of the bobbin **110**, and the first sensor **170** may receive current through the surface electrodes.

(58) According to a further embodiment, the first sensor **170** may be indirectly disposed, coupled or mounted on the bobbin **110**, as shown in the drawings. For example, the first sensor **170** may be disposed, coupled or mounted on the sensor substrate **180**, and the sensor substrate **180** may be coupled to the bobbin **110**. In other words, the first sensor **170** may be indirectly disposed, coupled or mounted on the bobbin **110** through the sensor substrate **180**.

(59) When the first sensor **170** is directly or indirectly disposed on the bobbin **110**, as in the other and further embodiments, the sensor magnet may be disposed independently from the magnet **130**, and the magnet **130** may be used as the sensor magnet.

(60) Hereinafter, although the case in which the first sensor **170** is indirectly disposed, coupled or mounted on the bobbin **110** through the sensor substrate **180** and the magnet **130** is used as the sensor magnet will be described, the embodiments are not limited thereto.

(61) Referring to FIGS. **4** and **5A**, the bobbin **110** may be provided on the outer side surface thereof with a support groove **114**, and the sensor substrate **180** may be fitted into the support groove **114** so as to be coupled to the bobbin **110**. Although the sensor substrate **180** may have, for example, a ring shape, as shown in the drawings, the embodiments are not limited as to the shape of the sensor substrate **180**. The support groove **114** may be defined between the outer circumferential surface of the bobbin **110** and the first and second protrusions **111** and **112**. At this point, the first sensor **170** may have a shape capable of being disposed, coupled or mounted on the sensor substrate **180**. As shown in FIGS. **4** and **5B**, the first sensor **170** may be disposed, coupled or mounted on, for example, an upper area **A1**, an intermediate area **A2** and a lower area **A3** of the outer surface of the sensor substrate **180** in various manners. The first sensor **170** may receive current from the outside through the circuit of the sensor substrate **180**. For example, a mounting hole **183** may be formed in the outer surface of the sensor substrate **180**, and the first sensor **170** may be disposed, coupled or mounted in the mounting hole **183**, as shown in FIG. **5B**. At least one surface of the mounting hole **183** may be configured to have an inclined surface (not shown) so as to allow more efficient injection of epoxy or the like for assembly of the first sensor **170**. Although additional epoxy or the like may not be injected into the mounting hole **183**, the epoxy or the like may be injected so as to increase the disposition stability, coupling force and/or mounting force of the first sensor **170**.

(62) Alternatively, the first sensor **170** may be attached to the outer surface of the sensor substrate **180** by means of an adhesive, such as epoxy or double-sided adhesive tape, as shown in FIG. **4**. As illustrated in FIG. **4**, the first sensor **170** may be disposed, coupled or mounted on the center of the sensor substrate **180**.

(63) The bobbin **110** may have a reception recess **116**, which is suitable for receiving the first sensor **170**, which is disposed, coupled or mounted on the sensor substrate **180**. The reception recess **116** may be formed between the first and second protrusions **111** and **112**.

(64) The sensor substrate **180** may include a body **182**, clastic member contacts **184-1**, **184-2**, **184-3** and **184-4**, and circuit patterns **L1**, **L2**, **L3** and **L4**.

(65) When the support groove **114**, which is defined between the outer surface of the bobbin **110** and the first and second protrusions **111** and **112**, has the same shape as the outer surface of the bobbin **110**, the body **182** of the sensor substrate **180** may have a shape capable of being securely fitted into the support groove **114**. Although the support groove **114** and the body **182** may have a circular cross-sectional shape, as shown in FIG. 3 to FIG. 5A, the embodiments are not limited thereto. According to another embodiment, the support groove **114** and the body **182** may have a polygonal cross-sectional shape.

(66) The body **182** of the sensor substrate **180** may include a first segment, on the outer surface of which the first sensor **170** is disposed, coupled or mounted, and a second segment, which contacts the first segment and extends therefrom. Although the sensor substrate **180** may have an opening in a region facing the first segment so as to be easily fitted into the support groove **114**, the embodiments are not limited to a sensor substrate **180** having any specific shape. The elastic member contacts **184-1**, **184-2**, **184-3** and **184-4** may protrude from the body **182** in the direction which allows the elastic member contacts **184-1**, **184-2**, **184-3** and **184-4** to contact the first frame **151**, for example, in the first direction, that is, the optical axis direction, or in a direction parallel to the first direction. The elastic member contacts **184-1**, **184-2**, **184-3** and **184-4** are the portions that are connected to the first inner frame **151** of the upper elastic member **150**, which will be described later.

(67) The circuit patterns **L1**, **L2**, **L3** and **L4** may be formed on the body **182**, and may conductively connect the first sensor **170** and the clastic member contacts **184-1**, **184-2**, **184-3** and **184-4**. For example, the first sensor **170** may be embodied as a Hall sensor, but may alternatively be embodied as any sensor as long as it is able to detect variation in magnetic force. If the first sensor **170** is embodied as a Hall sensor, the Hall sensor **170** may have a plurality of pins. For example, the plurality of pins may include a first pin and a second pin. Referring to FIG. 5C, the first pin may include, for example, a first of first pin **P11** and a second of first pin **P12**, which are respectively connected to the voltage and to ground, and the second pin may include a first of second pin **P21** and a second of second pin **P22**, which output the result of the detection. At this point, although the result of the detection, that is, the feedback signal which is output through the first of second pin **P21** and the second of second pin **P22**, may be of a current type, the embodiments are not limited as to the kind of feedback signal.

(68) The first of first, second of first, first of second and second of second pins **P11**, **P12**, **P21** and **P22** of the first sensor **170** may be conductively connected to the elastic member contacts **184-1**, **184-2**, **184-3** and **184-4** through the circuit patterns **L1**, **L2**, **L3** and **L4**, respectively. Referring to FIG. 5C, the first of first, second of first, first of second and second of second pins **P11**, **P12**, **P21** and **P22** may be connected to the fourth, third, second and first clastic member contacts **184-1**, **184-3**, **184-2** and **184-4** through the circuit patterns, that is, the first, second, third and fourth lines **L1**, **L2**, **L3** and **L4**, respectively. According to an embodiment, the first, second, third and fourth lines **L1**, **L2**, **L3** and **L4** may be constructed so as to be visible to the naked eye. According to another embodiment, the first, second, third and fourth lines **L1**, **L2**, **L3** and **L4** may be formed in the body **182** so as to be invisible to the naked eye.

(69) FIG. 8 is a cross-sectional view taken along line I-I' of FIG. 3.

(70) Referring to FIG. 8, the first sensor **170** may be disposed to face the magnet **130** such that the imaginary center horizontal line **172**, which extends through the center of the first sensor **170** in the optical axis direction and intersects the optical axis, is aligned with the upper end **131** of the magnet **130**.

(71) At this point, although the bobbin **110** may be moved upward and downward in the optical axis direction, that is, in the first direction or in a direction parallel to the first direction with respect to the reference point at which the imaginary center horizontal line **172** coincides with the upper end **131** of the magnet **130**, the embodiments are not limited thereto.

(72) FIG. **9** is a graph illustrating the accuracy of the first sensor **170** as a function of the position of the first sensor **170**, in which the horizontal axis represents the position of the first sensor **170** and the vertical axis represents the accuracy of the first sensor **170**.

(73) Referring to FIGS. **8** and **9**, it will be appreciated that the efficiency of sensing by the first sensor **170** is maximized when the imaginary center horizontal line **172** coincides with the upper end **131** of the magnet **130**.

(74) FIG. **10** is a top perspective view of the bobbin **110**, the housing **140**, the upper elastic member **150**, the first sensor **170**, the sensor substrate **180** and a plurality of support members **220**, all of which are coupled to one another.

(75) FIG. **11** is a bottom perspective view of the bobbin **110**, the housing **140**, the lower elastic member **160** and the plurality of support members **220**, all of which are coupled to one another.

(76) The first coil **120** may be wound around the outer circumferential surface of the bobbin **110** by a worker or a machine, and then both ends, that is, the starting line and the ending line of the first coil **120** may be respectively wound around a pair of winding protrusions **119** protruding from the bottom surface of the bobbin **110** in the first direction, and may be secured thereto. At this time, the position of the ending line of the first coil **120**, which is wound around the winding protrusion **119**, may vary depending on the worker. As illustrated in FIG. **11**, although the pair of winding protrusions **119** may be disposed at positions that are symmetrical about the center of the bobbin **110**, the embodiments are not limited thereto.

(77) As illustrated in FIG. **8**, the first coil **120** may be fitted and coupled in a coil groove **118**, which is formed in the outer circumferential surface of the bobbin **110**. As illustrated in FIG. **2**, although the first coil **120** may be embodied as a polygonal coil block, the embodiments are not limited thereto. According to another embodiment, the first coil **120** may be directly wound around the outer circumferential surface of the bobbin **110**, or may be wound through a coil ring (not shown). The coil ring may be coupled to the bobbin **110** in the same manner as the sensor substrate **180** fitted in the support groove **114**, and the first coil **120** may be wound around the coil ring rather than being wound or disposed around the bobbin **110**. In any case, the starting line and the ending line of the first coil **120** may be respectively wound around the pair of winding protrusions **119** and secured thereto, and other constructions are the same.

(78) As shown in FIG. **2**, the first coil **120** may be configured to have an approximately octagonal shape. This is because the outer circumferential surface of the bobbin **110**, which corresponds to the first coil **120**, has the octagonal shape, as illustrated in FIG. **5A**. At least four of the surfaces of the first coil **120** may be configured to be linear, and the corner surfaces connected between the four surfaces may also be configured to be linear. However, the embodiments are not limited thereto, and the surfaces may be configured to be rounded.

(79) The linear surfaces of the first coil **120** may be configured to correspond to the magnets **130**. The surfaces of the magnets **130**, which correspond to the surfaces of the first coil **120**, may have the same radius of curvature as the surfaces of the first coil **120**. Specifically, the surfaces of the magnets **130** may be linear when the surfaces of the coils **120** are linear, whereas the surfaces of the magnets **130** may be rounded when the surfaces of the coils **120** are rounded. However, even if the surfaces of the first coil **120** are rounded, the surfaces of the magnets **130** may be linear, and vice versa.

(80) The first coil **120**, which is intended to move the bobbin **110** in the first direction, which is parallel to the optical axis, or in a direction parallel to the first direction so as to fulfill the autofocus function, may generate electromagnetic force through the interaction between the magnets **130** and the first coil **120** upon the supply of current. The generated electromagnetic force

may move the bobbin **110** in the first direction or in a direction parallel to the first direction.

(81) The first coil **120** may be configured to correspond to the magnets **130**. In other words, if the magnets **130** are constructed to form a single magnet body and the entire inner surface of the magnet **130**, which faces the outer surface of the first coil **120**, has the same polarity, the outer surface of the first coil **120**, which corresponds to the inner surface of the magnet **130**, may have the same polarity.

(82) Alternatively, the magnet **130** may be divided into two or four magnets and thus the inner surface of the magnet **130**, which faces the outer surface of the first coil **120**, may also be divided into two or four surfaces, in which case the first coil **120** may also be divided into a number of coils that corresponds to the number of the divided magnets **130**.

(83) The magnet **130** may be disposed at a position corresponding to that of the first coil **120**. Referring to FIG. 8, the magnet **130** may be disposed to face the first coil **120** as well as the first sensor **170**. This is the case in which the magnet **130** is used as the magnet for the first sensor **170** without providing an additional magnet for the first sensor **170**, as in one embodiment. In this case, the magnet **130** may be received in a first side portion **141** of the housing **140**, as shown in FIG. 7. The magnet **130** may be configured to have an approximately cuboid shape corresponding to that of the first side portion **141** of the housing **140**, and the surface of the magnet **130** that faces the first coil **120** may be configured to have a curvature corresponding to that of the corresponding surface of the first coil **120**.

(84) The magnet **130** may be constituted by a single magnet body. Referring to FIG. 5A, which shows the embodiment, the magnet **130** may be oriented such that the inner surface of the magnet **130** that faces the first coil **120** serves as an S pole, whereas the outer surface of the magnet **130** serves as an N pole **134**. However, the embodiments are not limited thereto, and the inverted disposition is also possible.

(85) Two or more magnets **130** may be provided. According to the embodiment, four magnets **130** may be provided. As shown in FIG. 5A, the magnet **130** may be configured to have an approximately rectangular shape when viewed in a plan view. Alternatively, the magnet **130** may be configured to have a triangular shape or a rhombus shape.

(86) Although the surface of the magnet **130** that faces the first coil **120** may be linear, the embodiments are not limited thereto. If the corresponding surface of the first coil **120** is rounded, the magnet **130** may be rounded so as to have a curvature corresponding to that of the rounded surface of the first coil **120**. By virtue of this configuration, it is possible to maintain a constant distance between the magnet **130** and the first coil **120**. In the embodiment, the magnets **130** may be disposed one at each of the four first side portions **141** of the housing **140**. However, the embodiments are not limited thereto. In some designs, only one of the surface of the magnet **130** and the surface of the first coil **120** may be a flat surface, whereas the other surface may be a curved surface. Furthermore, both the mating surfaces of the first coil **120** and the magnet **130** may be curved surfaces. In this case, the mating faces of the first coil **120** and the magnet **130** may have the same curvature.

(87) When the magnets **130** have a rectangular shape when viewed in a plan view, as illustrated in FIG. 5A, a pair of magnets **130** among the plurality of magnets **130** may be oriented parallel to each other in the second direction, and the other pair of magnets **130** may be oriented parallel to each other in the third direction. By virtue of this configuration, it is possible to control the movement of the housing **140** for handshake correction.

(88) The housing **140** may have a polygonal shape when viewed in a plan view. Although the outer contour of the upper end of the housing **140** may have a square shape, as shown in FIG. 6, which shows the embodiment, the inner contour of the lower end of the housing **140** may have an octagonal shape, as shown in FIGS. 6 and 7. Accordingly, the housing **140** may include a plurality of side portions, for example, four first side portions **141** and four second side portions **142**.

(89) The first side portions **141** may be the portions on which the magnets **130** are mounted, and

the second side portions **142** may be the portions on which the support members **220** are mounted. The first side portions **141** may connect the second side portions **142** to each other, and may include flat surfaces having a predetermined depth.

(90) According to the embodiment, the first side portions **141** may be configured to have a surface area equal to or larger than that of the magnets **130**. Referring to FIG. 7, the magnets **130** may be held in magnet mounting portions **141a**, which are formed at lower portions of inner surfaces of the first side portions **141**. The magnet mounting portions **141a** may be embodied as recesses having a size corresponding to that of the magnets **130**, and may be disposed so as to face at least three surfaces, that is, opposite lateral side surfaces and the upper surface of the magnets **130**. The magnet mounting portions **141a** may have openings, which are provided in the bottom surfaces thereof and which face the second coil **230**, such that the bottom surfaces of the magnets **130** directly face the second coil **230**.

(91) Although the magnets **130** may be secured to the magnet mounting portions **141a** using an adhesive, an adhesive member such as a piece of double-sided adhesive tape may alternatively be used without limitation. Alternatively, the magnet mounting portions **141a** may be embodied as magnet mounting holes into which the magnets **130** are partially fitted or through which the magnets **130** are partially exposed, unlike the recessed structure shown in FIG. 7.

(92) The first side portions **141** may be disposed parallel to the side surfaces of the cover member **300**. The first side portions **141** may be configured to have a larger area than the second side portions **142**. The second side portions **142** may define passages through which the support members extend. Upper portions of the second side portions **142** may include first through holes **147**. The support members **220** may extend through the first through holes **147** and may be connected to the upper elastic member **150**.

(93) The housing **140** may further include second stoppers **144**. The second stoppers **144** may inhibit the upper surface of the housing **140** from directly colliding with the inner surface of the cover member **300** shown in FIG. 1.

(94) The housing **140** may further include a plurality of first upper support protrusions **143** formed on the second side portions **142**. The plurality of first upper support protrusions **143** may have a hemispherical shape, as shown in the drawings, or may have a circular cylindrical shape or a rectangular column shape. However, the embodiments are not limited as to the shape of the first upper support protrusions **143**.

(95) Referring to FIGS. 6 and 7, the housing **140** may be provided with first recesses **142a** formed in the side portions **142**. The first recesses **142a** are provided so as to provide paths, through which the support members **220** extend, as well as spaces which will be filled with a damping material. In other words, the first recesses **142a** may be filled with damping material. The damping material may be constituted by photo-curable resin. The damping material may be preferably constituted by ultraviolet-curable resin, and may be more preferably constituted by ultraviolet-curable silicone. The damping material may be a gel-type material.

(96) FIG. 12 is a perspective of the upper elastic member **150**, the lower elastic member **160**, the support members **220**, the conductive members **154** and the printed circuit board **250** according to the embodiment, all of which are assembled to one another.

(97) In this embodiment, the lower elastic member **160** may be constructed into a dual partitioning structure for applying power to the first coil **120**, and the upper elastic member **150** may be a four-segmented structure for outputting a feedback signal from the first sensor **170** and applying power to the first sensor **170**.

(98) In the embodiment, the first coil **120** may be conductively connected to the upper elastic member **150**, the lower elastic member **160** and the printed circuit board **250** so as to receive power from the printed circuit board **250**. The specific structure for implementing this is as follows.

(99) According to the embodiment, the upper elastic member **150** may include at least four upper elastic members, that is, first to fourth upper elastic members **150-1**, **150-2**, **150-3** and **150-4**. The

elastic member contacts **184-1**, **184-2**, **184-3** and **184-4**, which are connected to the first sensor **170**, may be connected to the plurality of support members **220** through the first to fourth upper elastic members **150-1**, **150-2**, **150-3** and **150-4**. Specifically, the first upper elastic member **150-1**, which is connected to the elastic member contact **184-4**, may be connected to a first support member **220-1**, that is, first of first and second of first support members **220-1a** and **220-1b**, and the second upper elastic member **150-2**, which is connected to the elastic member contact **184-3**, may be connected to a second support member **220-2**. Furthermore, the third upper elastic member **150-3**, which is connected to the elastic member contact **184-2**, may be connected to a third support member **220-3**, that is, first of third and second of third support members **220-3a** and **220-3b**, and the fourth upper elastic member **150-4**, which is connected to the elastic member contact **184-1**, may be connected to a fourth support member **220-4**.

(100) Each **150a** of the first and third upper elastic members **150-1** and **150-3** may include the first inner frame **151**, a first of first outer frame **152a** and the first frame connector **153**, and each **150b** of the second and fourth upper elastic members **150-2** and **150-4** may include the first inner frame **151**, a first of first outer frame **152b** and the first frame connector **153**. The first inner frame **151** may be coupled to the bobbin **110** and the associated elastic member contacts **184-1**, **184-2**, **184-3** and **184-4**. As shown in FIG. 4, when the upper surface **112a** of the second protrusion **112** is flat, the first inner frame **151** may be placed on the upper surface **112a**, and may be secured thereto by means of an adhesive member. According to another embodiment, when a support protrusion (not shown) is formed on the upper surface **112a**, unlike the one embodiment shown in FIG. 4, the support protrusion may be inserted into a first of second through hole **151a** formed in the first inner frame **151**, and may be secured thereto through thermal fusion or by means of an adhesive such as epoxy.

(101) The first of first outer frames **152a** and **152b** may be coupled to the housing **140**, and may be connected to the support members **220**. The first frame connector **153** may connect the first inner frame **151** and the first of first outer frame **152a** and **152b**. Although the first of first outer frame **152b** has a configuration in which the first of first outer frame **152a** is divided into two segments, the embodiments are not limited thereto. In other words, according to another embodiment, the first of first outer frame **152a** may also be divided into two segments in the same manner as the first of first outer frame **152b**.

(102) The first frame connector **153** may be bent at least one time to define a predetermined pattern. The upward and/or downward movement of the bobbin **110** in the first direction, parallel to the optical axis, may be flexibly supported by positional change and fine deformation of the first frame connector **153**.

(103) The plurality of first upper support protrusions **143** of the housing **140** may couple and secure the first of first outer frames **152a** and **152b** of the upper elastic member **150** to the housing **140**, as illustrated in FIG. 12. According to the embodiment, the first of first outer frames **152a** and **152b** may be provided with second of second through holes **157** at positions corresponding to the first upper support protrusions **143** of the first of first outer frames **152a** and **152b**. The upper support protrusions **143** and the second of second through holes **157** may be coupled to each other through thermal fusion or by means of an adhesive such as epoxy. In order to secure the plurality of first to fourth upper elastic members **150-1**, **150-2**, **150-3** and **150-4**, a sufficient number of first upper support protrusions **143** may be provided. Accordingly, it is possible to inhibit the first to fourth upper elastic members **150-1**, **150-2**, **150-3** and **150-4** and the housing **140** from being unreliably coupled to each other.

(104) The distance between the plurality of first upper support protrusions **143** may be appropriately set such that the first upper support protrusions do not interfere with peripheral components. Specifically, the first upper support protrusions **143** may be disposed at the corners of the housing **140** at regular intervals so as to be symmetrical about the center of the bobbin **110**, or may be disposed at irregular intervals so as to be symmetrical based on a specific imaginary line

extending through the center of the bobbin **110**.

(105) After the first inner frame **151** is coupled to the bobbin **110** and the first of first outer frames **152a** and **152b** are coupled to the housing **140**, conductive connecting members CP11, CP12, CP13 and CP14, made for example of solder, may be provided between the clastic member contacts **184-1**, **184-2**, **184-3** and **184-4** of the sensor substrate **180** and the first inner frame **151**, as shown in FIG. **10**, so as to enable power having different polarities to be applied to two pins P11 and P12, among the four pins P11, P12, P13 and P14 of the first sensor **170**, and to enable different feedback signals to be output from two other pins P21 and P22. In order to enable the application of power having different polarities and the output of different feedback signals in this way, the upper elastic member **150** may be divided into the first to fourth upper clastic members **150-1**, **150-2**, **150-3** and **150-4**.

(106) The first to fourth upper elastic members **150-1**, **150-2**, **150-3** and **150-4** are connected to the printed circuit board **250** through the support members **220**. Specifically, the first upper elastic member **150-1** may be connected to the printed circuit board **250** through at least one of the first of first support member **220-1a** and the second of first support member **220-1b**, and the second upper elastic member **150-2** may be connected to the printed circuit board **250** through the second support member **220-2**. Furthermore, the third upper elastic member **150-3** may be connected to the printed circuit board **250** through at least one of the first of third support member **220-3a** and the second of third support member **220-3b**, and the fourth upper elastic member **150-4** may be connected to the printed circuit board **250** through the fourth support member **220-4**. Accordingly, the first sensor **170** may receive power supplied from the printed circuit board **250** through the support members **220** and the upper elastic member **150**, or may output feedback signals and provide the feedback signals to the printed circuit board **250**. The lower elastic member **160** may include a first lower elastic member **160-1** and a second lower elastic member **160-2**, which are conductively isolated from each other. The first coil **120** may be connected to the plurality of support members **220** through the first and second lower elastic members **160-1** and **160-2**.

(107) Each of the first and second lower elastic members **160-1** and **160-2** may include at least one of the second inner frames **161-1** and **161-2**, at least one of the second outer frames **162-1** and **162-2**, and at least one of the second frame connectors **163-1** and **163-2**.

(108) The second inner frames **161-1** and **161-2** may be coupled to the bobbin **110**, and the second outer frames **162-1** and **162-2** may be coupled to the housing **140**. The first of second frame connector **163-1** may connect the second inner frame **161-1** and the second outer frame **162-1**, the second of second frame connector **163-2** may connect two second outer frames **162-1** and **162-2**, and the third of second frame connector **163-3** may connect the second inner frame **161-2** and the second outer frame **162-2**.

(109) The first lower elastic member **160-1** may further include a first coil frame **164-1**, and the second lower elastic member **160-2** may further include a second coil frame **164-2**. Referring to FIG. **11**, the first and second coil frames **164-1** and **164-2** may be connected to both ending lines of the first coil **120** through conductive connecting members, such as solder, at positions on the upper surface thereof which are disposed near the pair of winding protrusions **119**, around which the two ending lines of the first coil **120** are wound, whereby the first and second lower elastic members **160-1** and **160-2** may receive power having different polarities and may transmit the power to the first coil **120**. In order to enable the application of power having different polarities and transmission of the power to the first coil **120** in this way, the lower elastic member **160** may be divided into the first and second lower elastic members **160-1** and **160-2**.

(110) Each of the first and second lower elastic members **160-1** and **160-2** may further include a fourth of second frame connector **163-4**. The fourth of second frame connector **163-4** may connect the coil frame **164** and the second inner frame **161-2**.

(111) At least one of the first of second through fourth of second frame connectors **163-1**, **163-2**, **163-3** and **163-4** may be bent at least one time to define a predetermined pattern. Particularly, the

upward and/or downward movement of the bobbin **110** in the first direction, parallel to the optical axis, may be flexibly supported by positional change and fine deformation of the first of second frame connector **163-1** and the third of second frame connector **163-3**.

(112) According to one embodiment, each of the first and second lower elastic members **160-1** and **160-2** may further include a second protruding frame **165**. The second protruding frame **165** protrudes from the second of second frame connector **163-2**, to which the conductive member **154** is securely coupled. The upper elastic member **160** may further include fifth and sixth upper elastic members **150-5** and **150-6**, which are conductively isolated from each other.

(113) Each of the fifth and sixth upper elastic members **150-5** and **150-6** may further include a first protruding frame **155**, to which the conductive member **154** is securely coupled. The conductive member **154** may be connected to the second protruding frame **165**, and may be oriented such that the length direction thereof coincides with the first direction.

(114) The first and second protruding frames **155** and **165** may be disposed at positions corresponding to each other in the first direction such that two ends of the conductive member **154** are respectively coupled to the first and second protruding frames **155** and **165** and such that the length direction of the conductive member **154** coincides with the first direction.

(115) Each of the fifth and sixth upper elastic members **150-5** and **150-6** may be connected to the support member **220**. In other words, the fifth upper elastic member **150-5** may be connected to a fifth support member **220-5**, and the sixth upper elastic member **150-6** may be connected to a sixth support member **220-6**.

(116) The first and second lower elastic members **160-1** and **160-2** may be integrally formed with the respective second protruding frames **165**. In this way, the fifth and sixth upper elastic members **150-5** and **150-6** may be integrally formed with the respective first protruding frames **155**. The upper end of the conductive member **154** may be securely coupled to the first protruding frame **155**, and the lower end of the conductive member **154** may be securely coupled to the second protruding frame **165**.

(117) Here, the first and second protruding frames **155** and **165** and the conductive member **154** may be securely coupled to each other by means of soldering, a conductive adhesive or the like. In order to ensure the secure coupling between the first and second protruding frames **155** and **165** and the conductive member **154** and to facilitate the coupling work, each of the first and second protruding frames **155** and **165** may be provided with a hole or recess into which the conductive member **154** is fitted.

(118) In this way, each of the first and second lower elastic members **160-1** and **160-2** and each of the fifth and sixth upper elastic members **150-5** and **150-6** may be mechanically and electrically connected to each other via the conductive member **154**, which is oriented in the first direction.

(119) The conductive member **154** is preferably made of a flexible or elastic material such that the conductive member **154** flexes in a direction perpendicular to the length direction thereof when the bobbin **110** moves in the second and/or third directions.

(120) The lower ends of the plurality of support members **220** may be securely coupled to the printed circuit board **250**, or may be securely coupled to the second coil **230**. Accordingly, the lower ends of the plurality of support members **220** may be fixedly secured to the printed circuit board **150** or the second coil **230** even when the bobbin **110** moves in the second and/or third directions.

(121) According to still another embodiment, the housing **140** may further be provided with an insert or a metal attachment (not shown), unlike the embodiment shown in FIG. **12**. In this case, the second of first outer frame **158** and the second of second frame connector **163-2** may be connected to each other via the metal attachment. In this case, the first and second protruding frames **155** and **165** and the conductive member **154**, which are shown in FIG. **12**, may be omitted.

(122) The second of first outer frame **158** may further include the second of second through hole **157**, like the first of first outer frame **152b**. According to one embodiment, the first of first outer

frames **152a** and **152b** of the first to sixth upper elastic members **150-1**, **150-2**, **150-3**, **150-4**, **150-5** and **150-6** may be disposed to face each other in a diagonal direction, and the second of first outer frames **158** may be disposed to face each other in a diagonal direction. Specifically, the first of first outer frame **152a** of the first upper elastic member **150-1** and the first of first outer frame **152a** of the third upper elastic member **150-3** may be disposed to face each other in a diagonal direction. Furthermore, the first of first frame **152b** of the second upper elastic member **150-2** and the first of first outer frame **152b** of the fourth upper elastic member **150-4** may be disposed to face each other in a diagonal direction. In addition, the second of first outer frame **158** of the fifth upper elastic member **150-5** and the second of first outer frame **158** of the sixth upper elastic member **150-6** may be disposed to face each other in a diagonal direction.

(123) It will be appreciated that the first and second lower elastic members **160-1** and **160-2** receive power from the printed circuit board **250** through the fifth and sixth upper elastic members **150-5** and **150-6**, connected to the plurality of support members **220**, and through the conductive member **154** connecting the first and second lower elastic members **160-1** and **160-2** and the fifth and sixth upper elastic members **150-5** and **150-6**, and provide the power to the first coil **120**. Specifically, the first lower elastic member **160-1** may be connected to the printed circuit board **250** through the conductive member **154**, the sixth upper elastic member **160-6** and the sixth support member **220**, and the second lower elastic member **160-2** may be connected to the printed circuit board **250** through the conductive member **154**, the fifth upper elastic member **160-5** and the fifth support member **220-5**.

(124) Referring to FIG. **11**, the lower surface of the bobbin **110** may be provided with a plurality of first lower support protrusions **117** so as to couple or secure the second inner frames **161-1** and **161-2** of the lower elastic member **160** and the bobbin **110** to each other. The lower surface of the housing **140** may be provided with a plurality of second lower support protrusions **145** so as to couple or secure the second outer frames **162-1** and **162-2** of the lower elastic member **160** and the housing **140** to each other.

(125) The number of second lower support protrusions **145** may be greater than the number of first lower support protrusions **117**. This is because the second frame connector **163-2** of the lower elastic member **160** is longer than the first frame connector **163-1**.

(126) As described above, since the lower elastic member **160** is divided into two lower elastic members, the first and second lower support protrusions **117** and **145** are provided in a sufficient number equal to the number of the first upper support protrusions **143**, whereby it is possible to inhibit a gap which would otherwise be created when the lower elastic member **160** is separated. In the case where the lower elastic member **160** is constituted not by divided segments but by a single body, there is no necessity to provide a large number of first and second lower support protrusions **117** and **145** equal to the number of the first upper support protrusions **143**. This is because the lower elastic member **160** can be reliably coupled to the housing **140** by only a small number of first and second lower support protrusions **117** and **145**.

(127) However, when the lower elastic member **160** is divided into the first and second lower elastic members **160-1** and **160-2**, which are conductively isolated from each other, a sufficient number of first and second lower support protrusions **117** and **145** may be provided in order to hold the divided first and second lower elastic members **160-1** and **160-2**. Accordingly, it is possible to inhibit the first and second lower elastic members **160-1** and **160-2** and the housing **140** from being incompletely coupled to each other.

(128) As shown in FIG. **12**, according to the embodiment, the second inner frames **161-1** and **161-2** of the first and second lower elastic members **160-1** and **160-2** may be provided with third through holes **161a**, which are formed at positions corresponding to the first lower support protrusions **117** and have a shape corresponding to that of the first lower support protrusions **117**. The first lower support protrusions **117** and the third through holes **161a** may be coupled to each other through thermal fusion or by means of an adhesive such as epoxy.

(129) Furthermore, the second outer frames **162-1** and **162-2** of each of the first and second lower elastic members **160-1** and **160-2** may be provided with fourth through holes **162a**, which are formed at positions corresponding to the second lower support protrusions **145**. The second lower support protrusions **145** and the fourth through holes **162a** may be coupled to each other through thermal fusion or by means of an adhesive such as epoxy.

(130) The distance between the plurality of first lower support protrusions **117** and **145** may be appropriately set such that the first lower support protrusions do not interfere with peripheral components. Specifically, the first and second lower support protrusions **117** and **145** may be disposed at irregular intervals so as to be symmetrical about the center point of the bobbin **110**. Although the upper elastic member **150** and the lower elastic member **160** may be embodied as springs, the embodiments are not limited as to the material of the upper and lower elastic members **150** and **160**.

(131) The bobbin **110**, the housing **140** and the upper and lower elastic members **150** and **160** may be assembled to each other through thermal fusion and/or a bonding procedure using an adhesive. Here, the assembly may be performed in such a manner as to perform thermal fusion and then a bonding procedure using an adhesive depending on the assembly sequence.

(132) For example, when the bobbin **110** and the second inner frames **161-1** and **161-2** of the lower elastic member **160** are assembled to each other in the first sequence in the first assembly and then the housing **140** and the second outer frames **162-1** and **162-2** of the lower elastic member **160** are secondly assembled to each other in the second assembly, the first lower support protrusions **117** of the bobbin **110** may be coupled to the third through holes **161a** and the second lower support protrusions **145** of the housing **140** may be coupled to the fourth through holes **162a** through thermal fusion. When the first inner frame **151** of the upper elastic member **150** is first assembled in the third assembly, the elastic member contacts **184-1**, **184-2**, **184-3** and **184-4** of the sensor substrate **180** and the first inner frames **151** of the first to fourth upper elastic members **150-1**, **150-2**, **150-3** and **150-4** may be coupled to each other through thermal fusion. Thereafter, when the housing **140** and the first of first and second of first outer frames **152a**, **152b** and **158** of the upper elastic member **150** are coupled to each other in the fourth assembly, the second of second through holes **157** may be bonded to the first upper support protrusions **143** of the housing **140** through the application of an adhesive such as epoxy. However, this assembly sequence may be changed. In other words, the first to third assemblies may be performed through thermal fusion, and the fourth assembly may be performed through bonding. Although thermal fusion may involve deformation such as distortion, the bonding in the fourth assembly may compensate for such deformation.

(133) In the above embodiment, power may be supplied to the first sensor **170** through the two upper elastic members **160**, which are conductively isolated from each other, a feedback signal output from the first sensor **170** may be transmitted to the printed circuit board **250** through two other upper elastic members **150**, which are conductively isolated from each other, and power may be supplied to the first coil **120** through the two lower elastic members **160**, which are conductively isolated from each other. However, the embodiments are not limited thereto.

(134) According to another embodiment, the role of the plurality of upper elastic members **150** and that of the plurality of lower elastic members **160** may be swapped. Specifically, power may be supplied to the first coil **120** through the two upper elastic members **150**, which are conductively isolated from each other, power may be supplied to the first sensor **170** through two lower elastic members **160**, which are conductively isolated from each other, and a feedback signal output from the first sensor **170** may be transmitted to the printed circuit board **250** through two other lower elastic members **160**. Although not illustrated, this will be readily understood from the preceding drawings.

(135) Referring to FIGS. **3**, **6**, **7**, **10** and **11**, the outer side surface of the housing **140** may be provided with a plurality of third stoppers **149**. The third stoppers **149** are intended to inhibit the body of the housing **140** from colliding with the cover member **300** when the first lens moving unit

moves in the second and/or third directions in order to inhibit the side surface of the housing **140** from directly colliding with the inner surface of the cover member **300** upon the application of external impact. As shown in the drawings, although the third stoppers **149** are disposed two on each outer surface of the housing **140** with a constant interval therebetween, the embodiments are not limited as to the positions or number of the third stoppers **149**.

(136) Although not shown in the drawings, the housing **140** may further be provided at the lower surface thereof with fourth stoppers. The fourth stoppers may project from the lower surface of the housing **140**. The fourth stoppers may serve to inhibit the lower surface of the housing **140** from colliding with the base **210** and/or the printed circuit board **250**, which will be described later. In addition, the fourth stoppers may be maintained in the state of being spaced apart from the base **210** and/or the printed circuit board **250** by a predetermined distance when the fourth stoppers are in the initial position and are operating normally. By virtue of this construction, the housing **140** may be spaced apart downward from the base **210** and may be spaced apart upward from the cover member **300**, whereby the housing **140** may be maintained at a constant level in the optical axis direction without interference with other components. Accordingly, the housing **140** may move in the second and/or third directions.

(137) The first lens moving unit according to the embodiment may precisely control the movement of the bobbin **110** by detecting the position of the bobbin **110** in the optical axis direction, that is, the first direction or a direction parallel to the first direction. This may be achieved through feedback by providing information about the position, detected by the first sensor **170**, to the outside through the printed circuit board **250**.

(138) According to one embodiment, in order to move the bobbin **110** in the optical axis direction, that is, the first direction or a direction parallel to the first direction, a magnet (hereinafter referred to as the detecting magnet; not shown), which faces the first sensor **170**, may further be provided, in addition to the magnet **130** (hereinafter referred to as the autofocus magnet) that faces the first coil **120**. In this embodiment, the interaction between the autofocus magnet **130** and the first coil **120** may be obstructed by the detecting magnet. This is because a magnetic field may be generated by the detecting magnet. Accordingly, in order to inhibit the detecting magnet, which is separately provided, from interacting with the autofocus magnet **130** or in order to inhibit the bobbin **110** from being tilted but to allow the interaction between the detecting magnet and the autofocus magnet **130**, the first sensor **170** may be disposed to face the detecting magnet. In this case, the first sensor **170** may be disposed, coupled or mounted on the bobbin **110**, and the detecting magnet may be disposed, coupled or mounted on the housing **140**. Alternatively, the first sensor **170** may be disposed, coupled or mounted on the housing **140**, and the detecting magnet may be disposed, coupled or mounted on the bobbin **110**.

(139) According to another embodiment, in place of additional disposition of the detecting magnet, the autofocus magnet may be used as the detecting magnet in order to move the bobbin **110** in the optical axis direction, that is, the first direction or a direction parallel to the first direction. For example, in order for the autofocus magnet **130** to also serve as the detecting magnet, the first sensor **170** may not be disposed on the housing **140** but may be disposed, coupled or mounted on the bobbin **110** so as to be moved with the bobbin **110**. Accordingly, when both the autofocus magnet and the detecting magnet are present together, problems caused by the interaction between the two magnets may be fundamentally solved. For example, it is not necessary to provide a piece of magnetic field blocking metal (not shown) for minimizing the interaction between the autofocus magnet and the detecting magnet. In some cases, the first lens moving unit may further include various devices for improving the autofocus function, in addition to the first sensor **170**. In this case, the positions of the devices or the method or process of receiving power through the printed circuit board **250** and supplying feedback signals to the printed circuit board **250** may be identical to those of the first sensor **170**.

(140) Referring again to FIG. 2, the second lens moving unit, which serves as a handshake

correction lens moving unit, may include the first lens moving unit, the base **210**, the plurality of support members **220**, the second coil **230**, the second sensor **240**, and the printed circuit board **250**.

(141) Although the first lens moving unit may include the above-mentioned components, the above-mentioned components may be replaced with another optical system capable of fulfilling the autofocus function. Specifically, the first lens moving unit may be constituted by an optical module using a single lens moving actuator or a variable refractive index actuator, in place of using an autofocus actuator employing a voice coil motor. In other words, the first lens moving unit may adopt any optical actuator as long as it is capable of fulfilling an autofocus function. However, there is a need to install the magnet **130** at a position corresponding to the second coil **230**, which will be described later.

(142) FIG. **13** is a front view showing the upper elastic member **150**, the lower elastic member **160**, the support members **220**, the conductive member **154**, the printed circuit board **250**, the bobbin **110** and the first coil **120** according to the embodiment, all of which are assembled to one another.

(143) The conductive member **154** may be configured to have a shorter length than the support member **220**. Specifically, a first length **L1**, that is, the length of the conductive member **154**, which is the distance between the lower surface of the upper elastic member **150** and the upper surface of the lower elastic member **160**, may be shorter than a second length **L2**, that is, the length of the support member **220**, which is the distance between the lower surface of the upper elastic member **150** and the upper surface of the printed circuit board **250**.

(144) This is because the lower end of the conductive member **154** is securely coupled to the lower elastic member **160**, the lower end of the support member **220** is fitted or coupled to the printed circuit board and there is a certain distance between the lower elastic member **160** and the printed circuit board.

(145) The first length **L1** may be appropriately selected in consideration of case of assembly of the lens moving apparatus, the size of the bobbin **110**, or the like. Accordingly, the first length **L1** may be in a range of 0.1 mm to 1 mm, preferably in a range of 0.3 mm to 0.5 mm. In the embodiment, the upper elastic member **150** and the lower elastic member **160** are mechanically and electrically connected to each other via the conductive member **154** such that current from the printed circuit board **250** is applied to the lower elastic member **160**.

(146) When the lower elastic member **160** is directly connected to the support member **220**, the lower elastic member **160** is positioned near the lower end of the support member **220**, which is the portion that is secured to the printed circuit board **250** or the second coil **230**. When the bobbin **110** moves in the second and/or third directions, there is a need to provide a high driving force in order to bend the support member **220**, which is coupled to both the upper and lower elastic members **150** and **160**, in the second and/or third directions.

(147) However, since the support member **220** is coupled only to the upper elastic member **150** and the coupled portion is positioned at a relatively long distance from the lower end of the support member **220**, which is secured to the printed circuit board **250** or the second coil **230** in the embodiment, the support member **220** may be sufficiently bent in the second and/or third directions even by a remarkably low driving force, compared to the case in which the lower elastic member **160** is directly connected to the support member **220**.

(148) Accordingly, by virtue of the above construction, the embodiment has an advantage in that it is possible to reduce the driving force required to drive the bobbin **110** in the second and/or third directions.

(149) Consequently, the lens moving apparatus according to the embodiment has an effect of reducing a driving force required to move the bobbin **110** in the second and/or third directions by virtue of the above-described structure.

(150) Consequently, the lens moving apparatus according to the embodiment has an effect of performing handshake correction even using a low driving force. Furthermore, since excessive

driving force is not applied to the support member **220**, there is an effect of improving the durability of the lens moving apparatus including the support member **220**.

(151) FIG. **14** is an exploded perspective view of the base **210**, the second coil **230** and the printed circuit board **250**.

(152) As shown in FIGS. **2** and **14**, the base **210** of the second lens moving unit may have an approximately rectangular shape when viewed in a plan view. The base **210** may be provided with stepped portions **211**, to which an adhesive is applied when adhesively securing the cover member **300** to the base **210**, as illustrated in FIG. **14**. The stepped portion **211** may guide the cover member **300**, which is coupled on the base **210**, and may enable the cover member **300** to contact the base **210** in a surface-contact manner. The stepped portions **211** and the end of the cover member **300** may be adhesively secured to each other and may be sealed shut using an adhesive or the like.

(153) The base **210** may be disposed so as to be spaced apart from the first lens moving unit by a predetermined distance. The base **210** may be provided with a supporting portion **255**, which is positioned at the portion of the base **210** at which terminals **251** of the printed circuit board **250** are formed and which has a size corresponding to that portion of the base **210**. The supporting portion **255** may be configured to have a constant cross-sectional area without the stepped portion **211** so as to support a terminal pad **253** having the terminals **251**.

(154) The base **210** may have second recesses **212** formed in the corners thereof. When the cover member **300** includes projections formed at the corners thereof, the projections of the cover member **300** may be fitted into the second recesses **212**.

(155) The base **210** may be provided in the upper surface thereof with second mounting recesses **215-1** and **215-2** in which the second sensors **240** are disposed. According to the embodiment, two second mounting recesses **215-1** and **215-2** are provided, and the second sensors **240** are respectively disposed in the second mounting recesses **215-1** and **215-2**, whereby the second sensors **240** are able to detect the extent by which the housing **140** moves in the second and/or third directions. To this end, the two second mounting recesses **215-1** and **215-2** may be disposed such that the angle defined by two imaginary lines connecting the two second mounting recesses **215-1** and **215-2** and the center of the base **210** is 90°.

(156) Each of the second mounting recesses **215-1** and **215-2** may be provided on at least one surface thereof with an inclined surface (not shown) so as to allow epoxy or the like for the assembly of the second sensors **240** to be more easily injected through the inclined surface. The additional epoxy or the like may not be injected into the second mounting recesses **215-1** and **215-2**, or may be injected in order to secure the second sensors **240** in place. The second mounting recesses **215-1** and **215-2** may be disposed at or near the center of the second coil **230**. The center of the second coil **230** and the center of the second sensor **240** may coincide with each other. According to the embodiment, the second mounting recesses **215-1** and **215-2** may be formed near the sides of the base **210**.

(157) The cover member **300** may be provided with a groove in a position corresponding to the stepped portion **211** of the base **210** so as to allow the injection of an adhesive or the like through the groove. At this point, since the adhesive, which is injected through the groove, has a low viscosity, the adhesive can easily infiltrate between the stepped portion **211** and the end surface of the cover member **300**. The adhesive, which is applied to the groove, may fill the gap between the mating surfaces of the cover member **300** and the base **210** through the groove, and thus the cover member **300** may be sealingly coupled to the base **210**.

(158) The base **210** may further be provided on the lower surface thereof with a mounting seat (not shown) on which a filter is installed. The filter may be an infrared screening filter. However, the embodiments are not limited thereto, and the base **210** may be provided on the lower surface thereof with an additional sensor holder at which a filter is disposed. The base **210** may be provided on the lower surface thereof with a sensor substrate, on which an image sensor is mounted so as to constitute a camera module.

(159) The plurality of support members **220** may be disposed at the second side portions **142** of the housing **140**. As described above, when the housing **140** has, for example, a polygonal shape when viewed in a plan view, the housing **140** may have a plurality of second side portions **142**. If the interior of the lower end of the housing **140** has an octagonal shape, the plurality of support members **220** may be disposed at four second side portions **142**, among the eight side portions. For example, each of the four second side portions **142** may be provided with two support members **220**, and a total of eight support members **220** may thus be provided.

(160) Alternatively, among the four second side portions **142** of the housing **140**, each of two second side portions **142** may be provided with only one support member **220**, and each of the other two second side portions **142** may be provided with two support members **220**, with the result that a total of six support members **220** may be provided.

(161) As described above, the support members **220** may serve as the paths for transmitting the power required for the first sensor **170** and the first coil **120** and the paths for providing the printed circuit board **250** with the feedback signals output from the first sensor **170**.

(162) Furthermore, since the support members **220** serve to return the housing **140** to its usual position after the housing **140** has moved in the second and/or third directions in the first lens moving unit, when the same number of support members **220** are symmetrically disposed in the diagonal direction, the elastic coefficient may be balanced. Specifically, when the housing **140** moves in the second and/or third directions in the plane perpendicular to the optical axis direction, the support members **220** may be finely deformed in the direction in which the housing **140** moves or in the length direction of the support members **220**. Here, the term “length direction” may refer to the direction connecting the upper end and lower end of each wire of the support members **220**. Accordingly, the housing **140** can move only in the second and/or third directions, which are substantially perpendicular to the optical axis, with almost no displacement in the first direction, which is parallel to the optical axis, thus improving the accuracy of handshake correction. This may be obtained by the characteristic whereby the support members **220** are capable of being stretched.

(163) As shown in FIG. **12**, the four first to fourth support members **220-1**, **220-2**, **220-3** and **220-4**, each of which includes a pair of support members, are disposed two at each of four second side portions **142** among the eight side portions so as to support the housing **140** in the state of being spaced apart from the base **210** by a predetermined distance.

(164) The first to fourth support members **220-1**, **220-2**, **220-3** and **220-4** according to the embodiment may be respectively disposed at the second side portions **142** of the housing **140** so as to be symmetrical with one another. However, the embodiments are not limited thereto. In other words, the shape and number of the plurality of support members **220** may be set to be symmetrical to one another in the second and third directions, which are perpendicular to the first direction. In consideration of the above-mentioned elastic coefficient, the number of support members **220** may be eight.

(165) Although the support members **220** have been described as being embodied as suspension wires without a predetermined pattern in the above embodiment, the embodiments are not limited thereto. According to another embodiment, the support members **200** may be embodied as support plates having elastic deformation portions (not shown).

(166) Referring to FIG. **14**, the second coil **230** may include fifth through holes **230a**, which are formed through the corner regions of a circuit member **231**. The support members **220** may extend through the fifth through holes **230a** and may be connected to the printed circuit board **250**.

(167) The support member **220** may be fitted into the fifth through hole **230a**, and may be securely coupled to the second coil **230** by means of soldering, a conductive adhesive or the like. As described above, the support member **220** may be securely coupled to the printed circuit board **250**.

(168) The second coil **230** may be disposed to face the magnet **130** secured to the housing **140**. For example, the second coil **230** may be disposed outside the magnet **130**. Alternatively, the second coil **230** may be disposed under the magnet **130** so as to be spaced apart from the magnet **130** by a

predetermined distance.

(169) According to the embodiment, although the second coil **230** may include a total of four second coils, which are disposed at the four sides of the printed circuit board **250**, as shown in FIG. **14**, the embodiments are not limited thereto. Only two coils **230**, namely, a second coil for the second direction and a second coil for the third direction, may be provided, or four or more second coils **230** may also be provided. According to the embodiment, a circuit pattern may be formed on the printed circuit board **250** so as to have the shape of the second coil **230**, and an additional second coil **230** may be disposed on the printed circuit board **250**. However, the embodiments are not limited thereto, and only the second coil **230** may be disposed on the printed circuit board **250** without forming the circuit pattern having the shape of the second coil **230** on the printed circuit board **250**. Alternatively, the second coil **230**, which is constituted by winding a wire into a doughnut shape or which is constituted by a finely patterned coil, may be conductively connected to the printed circuit board **250**.

(170) The circuit member **231** including the second coil **230** may be mounted on the printed circuit board **250** disposed over the base **210**. However, the embodiments are not limited thereto, and the second coil **230** may be closely disposed on the base, or may be spaced apart from the base **210** by a predetermined distance. Furthermore, the second coil **230** may be formed on an additional substrate, and the substrate may be layered on the printed circuit board **250** and may be connected thereto.

(171) As described above, the housing **140** may be moved in the second and/or third directions by the interaction of the magnets **130**, which are disposed to face each other, and the second coil **230**, thus implementing handshake correction. To this end, the first to fourth support members **220** may support the housing **140** with respect to the base **210** such that the housing **140** can move in the second and/or third directions, which are perpendicular to the first direction.

(172) The second sensors **240** may detect displacement of the first lens moving unit with respect to the base **210** in the second and/or third directions, which are perpendicular to the optical axis. To this end, the second sensors **240** may be disposed at the center of the second coil **230** by a predetermined distance in the first direction, with the printed circuit board **250** disposed therebetween so as to detect movement of the housing **140**. In other words, the second sensors **240** are not directly connected to the second coil **230**, and the printed circuit board **250** may be provided on the upper surface thereof with the second coil **230** and on the lower surface thereof with the second sensors **240**. According to the embodiment, the second sensors **240**, the second coil **230** and the magnet **130** may be disposed on the same axis.

(173) The second sensors **240** may be embodied as Hall sensors, but may alternatively be embodied as any sensor as long as it is capable of detecting variation in magnetic force. As shown in FIG. **14**, two second sensors **240** may be disposed near the sides of the base **210** disposed under the printed circuit board **250**, and may be fitted in the second mounting recesses **215-1** and **215-2** formed in the base **210**.

(174) The printed circuit board **250** may include sixth through holes **250a1** and **250a2** through which the support members **220** extend. The support members **220** may extend through the sixth through holes **250a1** and **250a2** in the printed circuit board **250** and may be conductively connected to the associated circuit patterns, which may be disposed on the lower surface of the printed circuit board **250**, via soldering.

(175) The printed circuit board **250** may further include seventh through holes **250b**. The second upper support protrusions **217** of the base **210** and the seventh through holes **250b** may be coupled as shown in FIG. **14**, and may be secured to each other through thermal fusion or by means of an adhesive such as epoxy.

(176) The printed circuit board **250** may include a plurality of terminals **251**. The printed circuit board **250** may be provided with the bent terminal pad **253**. According to the embodiment, the one bent terminal pad **253** of the printed circuit board **250** may be provided with at least one terminal

251.

(177) According to the embodiment, the plurality of terminals **251** provided on the terminal pad **253** may receive external power, and may supply the power to the first and second coils **120** and **130** and the first and second sensors **170** and **240**. Furthermore, the plurality of terminals **251** may output the feedback signals, output from the first sensor **170**, to the outside. The number of terminals **251** provided on the terminal pad **252** may be increased or decreased depending on the kinds of components to be controlled.

(178) According to the embodiment, although the printed circuit board **250** may be embodied as an FPCB, the embodiments are not limited thereto. The terminals of the printed circuit board **250** may be directly formed on the base **210** through a process of forming a surface electrode. As described above, the printed circuit board **250** may supply power (or current) required for the first coil **120** and the first sensor **170**, and may receive the feedback signals from the first sensor **170** so as to adjust the displacement of the bobbin **110**.

(179) By virtue of the above-described construction, the respective autofocus and handshake correction operations of the first and second lens moving units may be realized by sharing the magnet **130**.

(180) In the lens moving apparatus according to the embodiments, the first sensor **170** may be disposed, coupled or mounted on the housing **140** or the bobbin **110**, and the autofocus magnet **130** may be shared as the detecting magnet, or the detecting magnet may be additionally disposed. If the autofocus magnet **130** is shared as the detecting magnet, or the detecting magnet is positioned so as not to interact with the autofocus magnet **130**, the detecting magnet does not affect the autofocus magnet **130**. Consequently, tilting of the bobbin **110** does not occur, and the accuracy of the feedback signal is improved. Furthermore, the number of components is not increased, and the weight of the housing **140** is reduced, thus improving responsiveness. Of course, the autofocus magnet and the handshake correction magnet may be independently constructed.

Second Embodiment

(181) FIG. **15** is a perspective view showing a lens moving apparatus according to a second embodiment of the present invention. FIG. **16** is an exploded perspective view showing the lens moving apparatus according to the second embodiment.

(182) As shown in FIGS. **15** and **16**, the lens moving apparatus according to this embodiment may include a movable unit. The movable unit may fulfill the functions of autofocus and handshake correction of a lens. The movable unit may include a bobbin **110**, a first coil **120**, a first magnet **130**, a housing **140**, an upper elastic member **150** and a lower elastic member **160**.

(183) The bobbin **110** may be provided in the housing **300**, and the first coil **120**, which is disposed inside the first magnet **130**, may be provided on the outer circumferential surface of the bobbin **110**. The bobbin **110** may be reciprocated in the first direction in the internal space of the housing **140** by electromagnetic interaction between the first magnet **130** and the first coil **120**. The first coil **120** is provided on the outer circumferential surface of the bobbin **110** so as to undergo electromagnetic interaction with the first magnet **130**.

(184) The bobbin **110** is moved in the first direction in the state of being elastically supported by the upper and lower elastic members **150** and **160**, thereby fulfilling the autofocus function.

(185) The bobbin **110** may include a lens barrel (not shown) in which at least one lens is mounted. The lens barrel may be coupled to the inside of the bobbin **110** in various manners. The autofocus function may be controlled by the direction of electric current, and may be fulfilled by moving the bobbin **110** in the first direction. For example, the bobbin **110** may move upward from its initial position upon the application of forward current, whereas the bobbin **110** may move downward from its initial position upon the application of reverse current. In addition, the distance that the bobbin **110** moves from its initial position in one direction may be increased or decreased by controlling the amount of current flowing in the corresponding direction.

(186) The bobbin **110** may be provided at upper and lower surfaces thereof with a plurality of

upper support protrusions and a plurality of lower support protrusions. The upper support protrusions may be configured to have a cylindrical shape or a polygonal column shape so as to secure the upper elastic member **150**. The lower support protrusions may be configured to have a cylindrical shape or a polygonal column shape so as to secure the lower elastic member **160**.

(187) The upper elastic member **150** may have through holes corresponding to the upper support protrusions, and the lower elastic member **160** may have through holes corresponding to the lower support protrusions. The respective support protrusions and the respective through holes may be securely coupled to each other by means of thermal fusion or an adhesive such as epoxy.

(188) The housing **140** may have a hollow column shape for supporting the first magnet **130**, and may be configured to have an approximately rectangular shape. The housing **140** may be provided at a lateral side thereof with the first magnet **130** and support members **220** coupled thereto. As in the first embodiment, the housing **140** may be provided on the inner surface thereof with the bobbin **110**, which is guided by the housing **140** and is moved in the first direction.

(189) The upper elastic member **150** and the lower elastic member **160** may each be coupled to both the housing **140** and the bobbin **110**, and may elastically support upward and/or downward movement of the bobbin **110** in the first direction. The upper and lower elastic members **150** and **160** may be constituted by a leaf spring.

(190) As shown in FIG. **16**, the upper elastic member **150** may include a plurality of upper elastic members, which are separated from each other. By virtue of this multiply-segmented structure, the respective segments of the upper elastic member **150** may receive current having different polarities or different powers. The lower elastic member **160** may also include a plurality of lower elastic members, which are separated from each other, and may be conductively connected to the upper elastic member **150**.

(191) The upper elastic member **150**, the lower elastic member **160**, the bobbin **110** and the housing **140** may be assembled to one another through thermal fusion and/or bonding using an adhesive or the like. Here, the assembly may be performed in such a manner as to perform thermal fusion first, followed by a bonding procedure using an adhesive, depending on the assembly sequence.

(192) The base **210**, which is configured to have an approximately rectangular shape, may be disposed under the bobbin **110**, and a printed circuit board **250** may be mounted on the base **210**. The regions of the base **210** that face terminal members **253** of the printed circuit board **250** may be provided with respective support recesses having a size corresponding to that of the terminal members **253**. The support recesses may be recessed from the outer circumferential surfaces of the base **210** by a predetermined depth such that the terminal members **253** do not protrude outward from the outer circumferential surface of the base **210** or such that the extent to which the terminal members **253** protrude can be controlled.

(193) The support members **220** are disposed on lateral sides of the housing **140** such that the upper sides of the support members **220** are coupled to the housing **140** and the lower sides of the support members **220** are coupled to the base **210**. The support members **220** may support the bobbin **110** and the housing **140** in such a manner as to allow the bobbin **110** and the housing **140** to move in the second and third directions, perpendicular to the first direction. The support members **220** may be conductively connected to the first coil **120**.

(194) Since the support members **220** according to the embodiment are disposed on the outer surfaces of the respective corners of the housing **140**, a total of four support members **220** may be disposed. The support members **220** may be conductively connected to the upper elastic member **150**. Specifically, the support members **220** may be conductively connected to regions around the through holes.

(195) Since the support members **220** are made of a different material from that of the upper elastic member **150**, the support members **220** may be conductively connected to the upper elastic member **150** by means of a conductive adhesive, solder or the like. Consequently, the upper elastic member **150** may apply current to the first coil **120** through the support members **220** conductively

connected thereto.

(196) Although the support members **220** are illustrated in FIG. **16** as being embodied as linear support members according to the embodiment, the support members **220** are not limited thereto. In other words, the support members **220** may be configured to have a plate shape or the like. Second coils **230** may move the housing **140** in the second and/or third directions to perform the handshake correction by virtue of electromagnetic interaction with the first magnets **130**. Accordingly, the first magnets **130** are required to be disposed at positions corresponding to the second coils **230**.

(197) The second coils **230** may be disposed so as to face the first magnets **130**, which are secured to the housing **140**. In one embodiment, the second coils **230** may be disposed outside the first magnets **130**, or may be disposed under the first magnets **130** so as to be spaced apart from the first magnets **130** by a predetermined distance.

(198) Although a total of four second coils **230** may be disposed one on each side of a circuit member **231** according to the embodiment, the disclosure is not limited thereto. Only two second coils **230**, that is, one second coil for movement in the second direction and one second coil for movement in the third direction, may be provided, or a total of more than four second coils **230** may be provided.

(199) In the embodiment, although circuit patterns having the shape of the second coils **230** are formed on the circuit member **231** and additional second coils are disposed on the circuit board **231**, the disclosure is not limited thereto. Alternatively, only additional second coils may be disposed on the circuit member **231**, without forming the circuit patterns having the shape of the second coils **230**.

(200) Furthermore, the second coils **230**, which have been prepared by winding wires into a doughnut shape or which have the shape of a finely patterned coil, may be conductively connected to the printed circuit board **250**.

(201) The circuit member **231** including the second coils **230** may be disposed on the upper surface of the printed circuit board **250**, which is positioned over the base **210**. However, the disclosure is not limited thereto, and the second coils **230** may be disposed on the base **210** in a state of being in close contact therewith, or may be spaced apart from the base **210** by a predetermined distance. In other examples, a substrate on which the second coils are formed may be layered on the printed circuit board **250** and connected thereto.

(202) The printed circuit board **250** may be conductively connected to at least one of the upper elastic member **150** and the lower elastic member **160**, and may be coupled to the upper surface of the base **210**. As shown in FIG. **16**, the printed circuit board **250** may have through holes formed at positions corresponding to the support members **220**, so as to allow the support members **220** to be fitted into the through holes.

(203) The printed circuit board **250** may be provided with the terminal members **253**, which are formed by bending portions of the printed circuit board **250**. Referring to FIG. **21**, the printed circuit board **250** according to the embodiment includes two bent terminal members **253**. Each terminal member **253** includes a plurality of terminals **251** for the application of external power to the terminal members **253**, whereby current is supplied to the first coil **120** and the second coils **230**. The number of terminals **251** provided on each terminal member **253** may be increased or decreased depending on the kinds of components to be controlled. Alternatively, the number of terminal members **253** provided on the printed circuit board may be one or three or more.

(204) A cover member **300**, which is configured to have an approximate box shape, may accommodate the movable unit, the second coil **230** and a portion of the printed circuit board **250**, and may be coupled to the base **210**. The cover member **300** may serve to protect the movable unit, the second coils **230**, the printed circuit board **250** and the like, accommodated therein, from damage, and may serve to inhibit an electromagnetic field, which is generated by the first magnets **130**, the first coil **120**, the second coils **230** and the like, from leaking outward, thereby

concentrating the electromagnetic field.

(205) FIG. 17 is a perspective view showing some of the components of the lens moving apparatus according to the second embodiment. FIG. 18 is a perspective view of FIG. 17, from which the bobbin 110 and the first coil 120 have been removed. As shown in FIGS. 17 and 18, each of the upper and lower elastic members 150 and 160 may be divided into multiple segments.

(206) For example, the upper elastic member 150 may include a first upper elastic member 150-1, a second upper elastic member 150-2, a third upper elastic member 150-3 and a fourth upper elastic member 150-4, which are separated from one another and are conductively connected to the printed circuit board 250.

(207) The upper elastic member 150 may further include a fifth upper elastic member 150-5 and a sixth upper elastic member 150-6, which are separated from each other and are conductively connected to the lower elastic member 160. Here, the respective upper elastic members 150 may be conductively isolated from one another so as to receive current having different polarities.

(208) The lower elastic member 160 may include a first lower elastic member 160-1 and a second lower elastic member 160-2, which are separated from each other. Here, the first lower elastic member 160-1 may be conductively connected to the sixth upper elastic member 150-6, and the second lower elastic member 160-2 may be conductively connected to the fifth upper elastic member 150-5.

(209) The upper elastic member 150 and the lower elastic member 160 may be conductively connected to each other via a conductive member 400. The conductive member 400 may include a first conductive member 400-1, which connects one of the fifth upper elastic member 150-5 and the sixth upper elastic member 150-6 and one of the first lower elastic member 160-1 and the second lower elastic member 160-2.

(210) The conductive member 400 may further include a second conductive member 400-2, which connects the other of the fifth upper elastic member 150-5 and the sixth upper elastic member 150-6 and the other of the first lower elastic member 160-1 and the second lower elastic member 160-2.

(211) As shown in FIGS. 17 and 18, by way of example, the first conductive member 400-1 conductively connects the sixth upper elastic member 150-6 and the first lower elastic member 160-1, and the second conductive member 400-2 conductively connects the fifth upper elastic member 150-5 and the second lower elastic member 160-2.

(212) Each of the fifth upper elastic member 150-5 and the sixth upper elastic member 150-6 may include a first protruding frame 155, which is connected to the conductive member 400. Each of the first lower elastic member 160-1 and the second lower elastic member 160-2 may include a second protruding frame 165, which is formed at a position corresponding to the first protruding frame 155 in the first direction and which is connected to the conductive member 400. The first protruding frame 155, the second protruding frame 165 and the conductive member 400 may be securely coupled to one another by means of soldering, a conductive adhesive or the like. In order to ensure secure coupling between the first and second protruding frames 155 and 165 and the conductive member 400 and to facilitate the coupling work, each of the first and second protruding frames 155 and 165 may be provided with a hole or recess into which the conductive member 400 is fitted.

(213) The conductive member 400 is preferably made of a flexible or elastic material such that the conductive member 400 flexes in the direction perpendicular to the length direction thereof when the bobbin 110 moves in the second and/or third directions.

(214) The support members 220 may support the housing 300 such that the housing 300 is able to move with respect to the base 210 in the second and/or third directions, and may conductively connect at least one of the upper and lower elastic members 150 and 160 and the printed circuit board 250. The support member 220 may be integrally formed with two conductive wires 221. The support member 220 may include a plurality of support members. The plurality of support members 220 may be symmetrically disposed in the second and third directions. The specific structure of the support member 220 will now be described below.

(215) FIG. 19A is a perspective view of the area A of FIGS. 17 and 18. FIG. 19B is a view showing the support member 220 according to an embodiment of the present invention. FIG. 19C is a view showing the support member 220 according to another embodiment of the present invention.

(216) The support member 220 may include a first support member 220-1, at which the two conductive wires 221 are connected to one of the first to fourth upper elastic members 150-1, 150-2, 150-3 and 150-4. As shown in FIG. 19A, the first support member 220-1 may be connected to, for example, the first upper elastic member 150-1 or the third upper elastic member 150-3, which is directly connected to the printed circuit board 250 in a conductive manner.

(217) Referring still to FIG. 19A, the first support member 220-1 may include an electrical insulation coating member 222 sheathing the two conductive wires 221, and the two conductive wires 221 may be conductively isolated from each other by means of the electrical insulation coating member 222.

(218) The coating member 222 serves to conductively isolate the two conductive wires 221 and serves as a damper. Accordingly, when the first support member 220-1 is bent in the second and/or third directions during a handshake correction operation, the coating member 222 may alleviate impacts to which the conductive wires 221 and the first support member 220-1 including the conductive wires 221 are subjected.

(219) As described above, the first support member 220-1 and the first upper elastic member 150-1 or the third upper elastic member 150-3 may be conductively connected to each other by means of a conductive adhesive, solder, or the like.

(220) Alternatively, the first support member 220-1 may be constructed such that the two conductive wires 221 are conductively shorted. This is because, when one end of the first support member 220-1 is connected to one of the upper elastic members 150, for example, the first upper elastic member 150-1 or the third upper elastic member 150-3 in the embodiment, there is no problem even if the two conductive wires 221 are conductively shorted.

(221) As shown in FIG. 19B, the first support member 220-1 may be constructed, for example, such that the two conductive wires 221 are twisted in the length direction thereof and are thus shorted.

(222) Since the first support member 220-1 serves to elastically support movement of the housing 300 and the bobbin 110 in the second and/or third directions, like the upper elastic member 150 or the lower elastic member 160, the first support member 220-1 may need to have elasticity.

(223) In this case, in consideration of performance and the operating characteristics of handshake correction of the lens moving apparatus, it is preferable to enable the elasticity of the first support member 220-1 to be controlled.

(224) Accordingly, in the case in which the first support member 220-1 contains the two conductive wires 221, which are twisted, the elasticity of the first support member 220-1 may be controlled in such a manner as to control the extent of twisting of the two conductive wires 221, that is, the number of turns by which the two conductive wires 221 are twisted about the longitudinal axis.

(225) Furthermore, it is possible to control the vibrational frequency in the second and/or third directions of the support member 220 during a handshake correction operation by controlling the elasticity of the first support member 220-1, and it is also possible to avoid mechanical resonance or reduce the maximum amplitude caused by the mechanical resonance by controlling the vibrational frequency.

(226) Furthermore, it is possible to control the rigidity of the first support member 220-1 by controlling the extent of twisting of the two conductive wires 221.

(227) Resistance of the conductive wires 221 is inversely proportional to the cross-sectional area thereof. Accordingly, when the two conductive wires 221 are conductively shorted, the total area of the conductive wires 221 is two times the area of a single wire, and the resistance of the conductive wires, which are shorted, decreases by half, compared to the resistance of conductive wires that are not shorted.

(228) By virtue of the halving of the resistance, the amount of current that is consumed to perform handshake correction may be reduced. In other words, the reduction of resistance enables the amount of current required to perform handshake correction to be increased.

(229) By virtue of the increased amount of current, the range of motion within which the support member **220** can move in the second and/or third directions for handshake correction may be increased. This is because the amount of current that flows through the support member **220** is proportional to the range of motion of the support member **220** in the second and/or third direction.

(230) As shown in FIG. **19C**, for example, the first support member **220-1** may be constructed such that the two conductive wires **221** are twisted in the length direction thereof so as to be shorted. The first support member **220-1** may include the electrical insulation coating member **222** sheathing the two conductive wires **221**.

(231) Accordingly, this embodiment may exhibit an effect which is obtained by the coating member **222** shown in FIG. **19A** and an effect which is obtained by the two conductive wires **221**, shown in FIG. **19B**, which are twisted in the length direction thereof so as to be shorted. FIG. **20A** is a perspective view showing the area B of FIG. **18**. FIG. **20B** is a view showing the support member **220** according to another embodiment.

(232) The support member **220** according to another embodiment may include a second support member **220-2** in which one of the two conductive wires **221** is connected to one of the first upper elastic member **150-1**, the second upper elastic member **150-2**, the third upper elastic member **150-3** and the fourth upper elastic member **150-4**, and the other of the two conductive wires **221** is connected to one of the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6**.

(233) As shown in FIGS. **20A** and **20B**, the second support member **220-2** may be constructed, for example, such that one of the two conductive wires **221** is connected to the second upper elastic member **150-2**, and the other of the two conductive wires **221** is connected to the fifth upper elastic member **150-5**. Here, the second upper elastic member **150-2** and the fifth upper elastic member **150-5** may be disposed in the state of being conductively isolated from each other.

(234) Furthermore, the second support member **220-2** may be constructed such that one of the two conductive wires **221** is connected to the fourth upper elastic member **150-4** and such that the other of the two conductive wires **221** is connected to the sixth upper elastic member **150-6**. Here, the fourth upper elastic member **150-4** and the sixth upper elastic member **150-6** may be disposed in the state of being conductively isolated from each other.

(235) The second support member **220-2** may include the electrical insulation coating member **222** sheathing the two conductive wires **221**, and the two conductive wires **221** may be conductively isolated from each other by means of the coating member **222**. One of the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6** may be separated from the other, and may be conductively connected to the other via the second support member **220-2**. Accordingly, there is a need to dispose the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6** such that one of the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6** is not in direct contact with the other. To this end, a projecting insulator **222a** may be provided at the upper end of the second support member **220-2** where the upper elastic members **150** are connected to the second support member **220-2**.

(236) As shown in FIG. **20B**, the projecting insulator **222a** may be formed by projecting a portion of the coating member **222** of one end of the second support member **220-2**, and may be disposed between the two conductive wires **221**. The projecting insulator **222a** may serve to space the upper elastic members **150** apart from each other so as to conductively isolate them from each other.

(237) When one of the two conductive wires **221** of the second support member **220-2** is connected to one of the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6**, and the other of the two conductive wires **221** is connected to the other of the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6**, the projecting insulator **222a** may be disposed between the adjacent fifth and sixth upper elastic members **150-5** and **150-6** so as to space the

adjacent fifth and sixth upper elastic members **150-5** and **150-6** apart from each other by a predetermined distance.

(238) By virtue of the projecting insulator **222a** having such a structure, the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6** are positioned close to each other in the state of being separated from each other, thereby inhibiting the occurrence of shorts between the fifth upper elastic member **150-5** and the sixth upper elastic member **150-6**.

(239) Like the coating member **222** of the first support member **220-1**, the coating member **222** of the second support member **220-2** may serve to conductively insulate the two conductive wires **221** from each other, and may serve as a damper. Accordingly, when the second support member **220-2** is bent in the second and/or third directions during a handshake correction operation, the coating member **222** may alleviate impacts to which the conductive wires **221** and the second support member **220-2** including the conductive wires **221** are subjected.

(240) Like the first support member, the second support member **220-2** may be conductively connected to the upper elastic member **150** by means of a conductive adhesive, solder or the like. FIG. **21** is a plan view of FIG. **18**. FIGS. **22A** and **22B** are plan views showing the area A of FIG. **21**. FIG. **23** is a plan view showing the area B of FIG. **21**.

(241) As shown in FIG. **21**, according to the embodiment, the first support member **220-1** may be connected to the first upper elastic member **150-1** or the third upper elastic member **150-3**. Accordingly, a total of two first support members **220-1** may be provided in the embodiment. According to the embodiment, one of the two conductive wires **221** of the second support member **220-2** may be connected to the second upper elastic member **150-2**, and the other of the two conductive wires **221** may be connected to the fifth upper elastic member **150-5**. One of the two conductive wires **221** of the second support member **220-2** may be connected to the fourth upper elastic member **150-4**, and the other of the two conductive wires **221** may be connected to the sixth upper elastic member **150-6**. Accordingly, a total of two second support members **220-2** may be provided in the embodiment.

(242) Ultimately, a total of four support members **220** including the two first support members **220-1** and the two second support members **220-2**, may be provided in the embodiment. As shown in FIG. **22A**, in one embodiment, the upper end of the first support member **220-1** may be conductively connected to one of the first upper elastic member **150-1** and the second upper elastic member **150-2**.

(243) Although the support member **220** is illustrated in FIG. **22A** as having an approximately elliptical cross-sectional shape, the embodiments are not limited thereto. The support member **220** may have various other cross-sectional shapes, such as a circular shape or a polygonal shape. As shown in FIG. **22B**, another embodiment of the first support member **220-1** may include the two conductive wires **221**, which are twisted, without the coating member **222**, as described above with reference to FIG. **19B**.

(244) In this embodiment, although the first support member **220-1** does not include the coating member **222**, the upper end of the first support member **220-1** may be connected to the first upper elastic member **150-1** or the second upper elastic member **150-2** via the two conductive wires **221**, as in the embodiment shown in FIG. **8**.

(245) As shown in FIG. **23**, in one embodiment, the second support member **220-2** may be connected at the upper end thereof to the second upper elastic member **150-2** and the fifth upper elastic member **150-5**. Here, one of the conductive wires contained in the second support member **220-2** may be connected to the second upper elastic member **150-2**, and the other of the conductive wires may be connected to the fifth upper elastic member **150-5**.

(246) The upper end of the second support member **220-2** may be connected to the fourth upper elastic member **150-4** and the sixth upper elastic member **150-6**. One of the conductive wires contained in the second support member **220-2** may be connected to the fourth upper elastic member **150-4**, and the other of the conductive wires may be connected to the sixth upper elastic

member **150-6**.

(247) As in the preceding embodiment, although the second support member **220-2** is illustrated in FIG. **23** as having an approximately elliptical cross-sectional shape, the embodiments are not limited thereto. The second support member **220-2** may have various other cross-sectional shapes, such as a circular shape or a polygonal shape.

(248) The projecting insulator **222a** may be disposed, for example, between the second upper elastic member **150-2** and the fifth upper elastic member **150-5**, or between the fourth upper elastic member **150-4** and the sixth upper elastic member **150-6** such that the adjacent upper elastic members are spaced apart from each other by a predetermined distance without contact therebetween, and are conductively isolated from each other.

(249) The coating member **222** sheathing the conductive wires **221** or the projecting insulator **222a** formed on the coating member **222** may be made of any material that is electrically insulative. For example, in consideration of case of manufacture, the cost of manufacturing the support member **220** and the like, the coating member **222** or the projecting insulator **222a** may be made of a polymer-based material.

(250) The lens moving apparatus according to this embodiment may be incorporated in devices in various fields, for example, a camera module. Such a camera module may be applied to mobile devices such as cellular phones.

(251) The camera module according to this embodiment may include the lens barrel coupled to the bobbin **110**, an image sensor (not shown), a printed circuit board **250**, and an optical system. The lens barrel may be constructed as described above, and the printed circuit board **250** may constitute the bottom surface of the camera module, starting from the area on which the image sensor is mounted.

(252) The optical system may include at least one lens for transmitting images to the image sensor. The optical system may be provided with an actuator module capable of fulfilling autofocus and handshake correction functions. The actuator module for fulfilling the autofocus function may be constructed in various fashions, but mainly adopts a voice coil unit motor. The lens moving apparatus according to this embodiment may serve as an actuator module for fulfilling both autofocus and handshake correction functions.

(253) The camera module may further include an infrared ray screening filter (not shown). The infrared ray screening filter serves to shield the image sensor from light in the infrared range. In this case, the base **210**, which is illustrated in FIG. **2**, may be provided with the infrared ray screening filter at a position corresponding to the image sensor, and the infrared ray screening filter may be coupled to the base **210** by means of a holder member (not shown). Furthermore, the base **210** may support the lower portion of the holder member.

(254) The base **210** may be provided with an additional terminal member for connection with the printed circuit board **250**, and the terminal member may be integrally formed using a surface electrode. The base **210** may serve as a sensor holder for protecting the image sensor. In this case, although the base **210** may be provided along the lateral side surface thereof with protrusions projecting downward, these are not essential components. Although not shown in the drawings, an additional sensor holder disposed under the base **210** may fulfill the function of the protrusions.

(255) Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

Claims

1. A lens moving apparatus, comprising: a base; a housing disposed on the base; a bobbin disposed in the housing so as to move in a first direction along an optical axis; a first coil disposed on the bobbin; a first magnet disposed to be opposite to the first coil; a first sensor disposed on the housing and comprising a plurality of pins; an upper elastic member coupled to the housing and an upper surface of the bobbin and comprising a first upper elastic member, a second upper elastic member, a third upper elastic member, and a fourth upper elastic member, which are spaced apart from one another; a lower elastic member coupled to the housing and a lower surface of the bobbin; a printed circuit board disposed between the base and the housing and conductively connected to at least one of the upper and lower elastic members; a second coil disposed to face the first magnet; a support member comprising at least one wire that supports the housing such that the housing is movable with respect to the base in second and/or third directions perpendicular to the first direction and conductively connecting at least one of the upper and lower elastic member to the printed circuit board; a plurality of circuit patterns conductively connected to the plurality of pins of the first sensor; and a plurality of elastic member contacts including a first elastic member contact conductively connected to the first upper elastic member, a second elastic member contact conductively connected to the second upper elastic member, a third elastic member contact conductively connected to the third upper elastic member, and a fourth elastic member contact conductively connected to the fourth upper elastic member, wherein the first sensor is disposed lower than the plurality of elastic member contacts.
2. The lens moving apparatus according to claim 1, wherein an outer circumferential surface of the bobbin faces to the first coil.
3. The lens moving apparatus according to claim 1, wherein an inner contour of a lower end of the housing has an octagonal shape.
4. The lens moving apparatus according to claim 1, wherein the housing includes four first side portions and four second side portions.
5. The lens moving apparatus according to claim 4, wherein the four second side portions are disposed on four corners of the housing, respectively.
6. The lens moving apparatus according to claim 4, wherein an upper portion of each of the second side portions comprises a respective first through hole, and wherein the support member extends through each first through hole and is connected to the upper elastic member.
7. The lens moving apparatus according to claim 6, wherein the housing comprises a first recess under at least one of the first through holes.
8. The lens moving apparatus according to claim 1, wherein the first coil has at least four surfaces that are configured to be linear and corner surfaces connected between the four surfaces that also are configured to be linear.
9. The lens moving apparatus according to claim 1, wherein the lower elastic member comprises first and second lower elastic members, which are spaced apart from each other.
10. The lens moving apparatus according to claim 9, wherein power is supplied to the first coil through the first and second lower elastic members.
11. The lens moving apparatus according to claim 1, wherein the support member comprises: a first support member electrically connecting the first upper elastic member to the printed circuit board; a second support member electrically connecting the second upper elastic member to the printed circuit board; a third support member electrically connecting the third upper elastic member to the printed circuit board; and a fourth support member electrically connecting the fourth upper elastic member to the printed circuit board.
12. The lens moving apparatus according to claim 11, wherein the first sensor is connected to the first to fourth support members through the first to fourth upper elastic members.

13. The lens moving apparatus according to claim 1, comprising: a second magnet disposed on the bobbin.

14. The lens moving apparatus according to claim 1, wherein the first upper elastic member comprises a first inner frame coupled to the bobbin, a first outer frame coupled to the housing, and a first frame connector connecting the first inner frame to the first outer frame, wherein the second upper elastic member comprises a second inner frame coupled to the bobbin, a second outer frame coupled to the housing, and a second frame connector connecting the second inner frame to the second outer frame, wherein the third upper elastic member comprises a third outer frame coupled to the housing, and wherein the fourth upper elastic member comprises a fourth outer frame coupled to the housing.

15. The lens moving apparatus according to claim 1, wherein the second coil is formed on the printed circuit board in a form of a circuit pattern.

16. The lens moving apparatus according to claim 1, wherein the second coil directly faces a bottom surface of the first magnet.

17. The lens moving apparatus according to claim 1, wherein the second coil is spaced apart from the first magnet by a predetermined distance.

18. A camera module, comprising: the lens moving apparatus of claim 1; a lens barrel coupled to the bobbin; a printed circuit board; and an image sensor disposed on the printed circuit board.

19. A phone, comprising: the camera module of claim 18; a controller configured to control a distance between the lens barrel and the image sensor.

20. A lens moving apparatus comprising: a base; a housing spaced apart from the base; a bobbin disposed in the housing so as to move in a first direction; a sensor disposed on the housing; upper and lower elastic members each coupled to the housing and the bobbin; a printed circuit board conductively connected to at least one of the upper and lower elastic members; a support member comprising at least one wire, which supports the housing such that the housing is movable with respect to the base in second and/or third directions and which conductively connects at least one of the upper and lower elastic members to the printed circuit board; a plurality of circuit patterns conductively connected to the sensor; and a plurality of elastic member contacts including a first elastic member contact conductively connected to the first upper elastic member, a second elastic member contact conductively connected to the second upper elastic member, a third elastic member contact conductively connected to the third upper elastic member, and a fourth elastic member contact conductively connected to the fourth upper elastic member, wherein the sensor is disposed lower than the plurality of elastic member contacts.
