



US012390849B2

(12) **United States Patent**
Davies et al.

(10) **Patent No.:** **US 12,390,849 B2**

(45) **Date of Patent:** ***Aug. 19, 2025**

(54) **EXPANSION TOOL**

(56) **References Cited**

(71) Applicant: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Peter J. Davies**, Milwaukee, WI (US);
Alex R. Kuhls, Brookfield, WI (US)

1,404,819 A 1/1922 Wiedeke
1,752,408 A 4/1930 Zein
(Continued)

(73) Assignee: **MILWAUKEE ELECTRIC TOOL CORPORATION**, Brookfield, WI (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CN 201346602 Y 11/2009
CN 204018564 U 12/2014
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **18/482,992**

International Search Report and Written Opinion for Application No. PCT/US2022/024077 dated Jul. 27, 2022 (8 pages).

(22) Filed: **Oct. 9, 2023**

(Continued)

(65) **Prior Publication Data**

Primary Examiner — Bobby Yeonjin Kim

US 2024/0033805 A1 Feb. 1, 2024

(74) *Attorney, Agent, or Firm* — Michael Best & Friedrich LLP

Related U.S. Application Data

(63) Continuation of application No. 17/716,773, filed on Apr. 8, 2022, now Pat. No. 11,779,990.

(Continued)

(51) **Int. Cl.**

B21D 39/20 (2006.01)

B21D 37/04 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B21D 39/20** (2013.01); **B21D 37/04** (2013.01); **B21D 37/18** (2013.01); **B25F 5/001** (2013.01)

(58) **Field of Classification Search**


CPC B21D 37/04; B21D 41/021; B21D 41/028; B21D 41/025; B21D 39/08; B25F 5/001; B29C 57/06; B29C 57/04; B29C 57/00

See application file for complete search history.

(57) **ABSTRACT**

An expansion tool includes a housing, a collar rotatably coupled to the housing, the collar including a plurality of slots, a plurality of jaws, each jaw having a projection received in a corresponding one of the plurality of slots such that the jaws are coupled for co-rotation with the collar, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position, and a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws. The mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and a rotation mechanism is configured to incrementally rotate the collar.

18 Claims, 10 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 63/303,732, filed on Jan. 27, 2022, provisional application No. 63/172,874, filed on Apr. 9, 2021.

(51) **Int. Cl.****B21D 37/18** (2006.01)**B25F 5/00** (2006.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

2,085,447 A 6/1937 Plaine
 2,725,918 A 12/1955 Deshler
 2,737,996 A 3/1956 Toth
 2,835,307 A 5/1958 Jorgensen
 2,999,529 A 9/1961 Wlodzimierz
 3,550,424 A 12/1970 Rast
 3,677,684 A 7/1972 Platz
 3,753,635 A 8/1973 Barnett
 3,857,666 A 12/1974 Barnett
 3,861,847 A 1/1975 Barnett
 3,888,102 A 6/1975 Nigido
 3,940,227 A 2/1976 Strasser
 3,947,950 A 4/1976 Adams
 4,034,591 A 7/1977 Rothenberger
 4,107,249 A 8/1978 Murai et al.
 4,144,735 A 3/1979 Rothenberger
 4,154,083 A 5/1979 Rothenberger
 4,397,173 A 8/1983 Eftefield et al.
 4,425,783 A 1/1984 Rast
 4,603,890 A 8/1986 Huppee
 4,733,551 A 3/1988 Bryant et al.
 4,735,078 A 4/1988 Wesebaum
 4,890,472 A 1/1990 Rothenberger
 5,046,349 A 9/1991 Velte
 5,090,226 A 2/1992 Takeoka et al.
 5,090,230 A 2/1992 Koskinen
 5,135,268 A 8/1992 McNaughton et al.
 5,243,845 A 9/1993 Velte
 5,261,709 A 11/1993 McNaughton et al.
 5,704,244 A 1/1998 Halasz et al.
 5,727,414 A 3/1998 Halasz et al.
 5,744,085 A 4/1998 Soberg
 5,879,033 A 3/1999 Hansel et al.
 5,943,891 A 8/1999 Takagi et al.
 6,199,915 B1 3/2001 Becker
 6,783,160 B2 8/2004 Rowley
 6,862,766 B2 3/2005 Geurts
 7,014,214 B2 3/2006 Kaneko
 7,065,995 B2 6/2006 Frenken
 7,128,560 B2 10/2006 Tandart
 7,325,436 B2 2/2008 Cheng
 7,490,499 B2 2/2009 Suzuki et al.
 7,516,990 B2 4/2009 Jamison et al.
 7,681,636 B2 3/2010 Roggeband et al.
 7,735,877 B2 6/2010 Ito et al.
 7,806,213 B2 10/2010 Inoue et al.
 7,922,475 B2 4/2011 Gueit
 8,302,448 B2 11/2012 Woelcken et al.
 8,303,295 B2 11/2012 Gueit
 8,371,409 B2 2/2013 Inoue et al.
 8,511,133 B1 8/2013 Chen
 8,517,715 B2* 8/2013 Thorson B29D 23/001
 425/467

8,534,711 B2 9/2013 Inoue et al.
 8,562,331 B2 10/2013 Schramm et al.
 8,763,439 B2 7/2014 Thorson et al.
 9,027,966 B2 5/2015 Altmann et al.
 9,089,889 B2 7/2015 Kohnen
 9,248,617 B2 2/2016 Lundquist et al.
 9,808,852 B2 11/2017 Frenken
 9,862,137 B2 1/2018 Dickert et al.
 9,914,260 B2 3/2018 Ellice

9,975,289 B2 5/2018 Li et al.
 9,993,961 B2 6/2018 Dickert et al.
 10,000,007 B2 6/2018 Dickert et al.
 10,195,783 B2 2/2019 Dickert et al.
 10,406,586 B2 9/2019 Frenken
 2005/0093298 A1 5/2005 Takayanagi
 2006/0201228 A1 9/2006 Rothenberger
 2007/0057393 A1 3/2007 Hartmann et al.
 2008/0122222 A1 5/2008 Sheppard
 2008/0160130 A1 7/2008 Gueit
 2010/0308503 A1* 12/2010 Schramm B29C 57/045
 264/312
 2011/0239674 A1 10/2011 Defilippi
 2013/0341831 A1 12/2013 Thorson et al.
 2018/0029286 A1* 2/2018 Li B21D 41/028
 2018/0128323 A1 5/2018 Carlson
 2019/0351605 A1 11/2019 Trickle
 2020/0094465 A1* 3/2020 Lindsey B29C 57/04
 2020/0261958 A1 8/2020 Davies
 2020/0261959 A1 8/2020 Wekwert et al.
 2021/0023767 A1 1/2021 Brochman
 2021/0254773 A1* 8/2021 Adelman B29C 57/04
 2022/0168793 A1 6/2022 Davies et al.


FOREIGN PATENT DOCUMENTS


CN 107838304 A 3/2018
 CN 207308769 U 5/2018
 DE 497609 C 5/1930
 DE 2800079 A1 7/1978
 DE 3439522 A1 8/1985
 DE 4003994 A1 8/1991
 DE 4005474 A1 9/1991
 DE 19730054 C1 3/1999
 DE 19924695 A1 11/2000
 DE 19963885 C1 5/2001
 DE 10063517 A1 7/2002
 DE 20301139 U1 6/2004
 DE 102005033482 A1 1/2007
 DE 102006015368 A1 10/2007
 DE 202008002265 U1 4/2008
 DE 202008002266 U1 4/2008
 DE 102007053518 A1 5/2009
 DE 102008061441 A1 7/2009
 DE 102008064320 A1 6/2010
 DE 102013208330 A1 11/2014
 EP 0234283 A1 9/1987
 EP 0397570 A1 11/1990
 EP 0462719 A2 12/1991
 EP 0567742 A2 11/1993
 EP 0718057 A2 6/1996
 EP 0878287 A1 11/1998
 EP 0967427 A2 12/1999
 EP 1118401 A1 7/2001
 EP 1278001 A2 1/2003
 EP 1930640 A1 6/2008
 EP 2090384 A2 8/2009
 EP 3520923 A1 8/2019
 FR 2451235 A1 10/1980
 FR 2645052 A1 10/1990
 GB 1485098 A 9/1977
 GB 1524149 A 9/1978
 WO 8800503 A1 1/1988
 WO 96020798 A1 7/1996
 WO 96040457 A2 12/1996
 WO 0189736 A1 11/2001


OTHER PUBLICATIONS


Partial Supplementary European Search Report for Application No. 22785554.1 dated Feb. 28, 2025 (15 pages).
 Extended European Search Report for Application No. 22785554.1 dated May 19, 2025 (12 pages).


* cited by examiner










**FIG. 3**


**FIG. 4**


**FIG. 5**











1

EXPANSION TOOL

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/716,773, filed Apr. 8, 2022, now U.S. Pat. No. 11,779,990, which claims priority to U.S. Provisional Patent Application No. 63/172,874, filed Apr. 9, 2021, and to U.S. Provisional Patent Application No. 63/303,732, filed Jan. 27, 2022, the entire contents of each of which are incorporated by reference herein.

FIELD

The present disclosure relates to pipe and tubing expansion tools. More particularly, the present disclosure relates to PEX (cross-linked polyethylene) expansion tools.

BACKGROUND

PEX tubing is commonly used in plumbing applications as a substitute for copper pipe. PEX tubing can be coupled to fittings in various ways. Crimp rings or clamp rings can be compressed onto the outside of PEX tubing over a fitting to couple the PEX tubing to the fitting. Alternatively, the PEX tube can be expanded, and the fitting inserted into the expanded end of the PEX tube. The PEX tube elastically recovers around the fitting to form a tight connection. Tools used to expand PEX tube for this purpose are referred to as PEX expansion tools.

SUMMARY

The present invention provides, in a first aspect, an expansion tool including a housing, a collar rotatably coupled to the housing, the collar including a plurality of slots, a plurality of jaws, each jaw having a projection received in a corresponding one of the plurality of slots such that the jaws are coupled for co-rotation with the collar, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position, and a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws. The mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and a rotation mechanism is configured to incrementally rotate the collar.

The present invention provides, in another aspect, an expansion tool including a housing, a motor supported in the housing, a plurality of jaws, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position, and a drive mechanism configured to convert rotational input from the motor into translational movement of the mandrel between the retracted position and the extended position. The drive mechanism is operable in a high speed configuration and a low speed configuration.

The present invention provides, in another aspect, an expansion tool including a housing, a collar rotatably coupled to the housing, a plurality of jaws coupled for co-rotation with the collar, a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the

2

jaws in response to movement of the mandrel to the extended position, and a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws. The mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and the cone includes means for containing grease to lubricate the inner surfaces of the plurality of jaws.

Other features and aspects of the invention will become apparent by consideration of the detailed description and accompanying drawings. Any feature(s) described herein in relation to one aspect or embodiment may be combined with any other feature(s) described herein in relation to any other aspect or embodiment as appropriate and applicable.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an expansion tool according to an embodiment of the present disclosure.

FIG. 2 is a cross-sectional view illustrating a drive assembly of the expansion tool of FIG. 1.

FIG. 3 is a perspective view of the expansion tool of FIG. 1, illustrating a shift actuator of the expansion tool.

FIG. 4 is a perspective view of the expansion tool of FIG. 1 with portions removed, illustrating the shift actuator.

FIG. 5 is a perspective view of a portion of the expansion tool of FIG. 1, illustrating a rotation collar.

FIG. 6A is a perspective view illustrating a first embodiment of a head for use with the expansion tool of FIG. 1.

FIG. 6B is a perspective view illustrating a second embodiment of a head for use with the expansion tool of FIG. 1.

FIG. 7 is an exploded view illustrating a portion of the expansion tool of FIG. 1 including the rotation collar and the head.

FIG. 8 is a cross-sectional view illustrating the head of FIG. 6B in a partially installed position on the expansion tool of FIG. 1.

FIG. 9 is a cross-sectional view illustrating the head of FIG. 6B in a fully installed position on the expansion tool of FIG. 1.

FIG. 10A is a cross-sectional view illustrating a third embodiment of a head for use with the expansion tool of FIG. 1.

FIG. 10B is a perspective view of an inner cone of the head of FIG. 10A.

FIG. 11A is a cross-sectional view illustrating a fourth embodiment of a head for use with the expansion tool of FIG. 1.

FIG. 11B is a perspective view of an inner cone of the head of FIG. 11A.

DETAILED DESCRIPTION

Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways.

FIG. 1 illustrates an expansion tool 10 usable to expand PEX tubing prior to inserting a fitting. The expansion tool 10 includes a housing 12 with a handle portion 14 configured to be gripped by a user during operation of the expansion tool 10. The illustrated housing 12 also includes a motor housing portion 18 positioned in front of the handle portion 14, and

a drive housing portion 22 positioned above the motor housing portion 18 and the handle portion 14. An actuator 26 (e.g., a trigger) for operating the expansion tool 10 is positioned on the handle portion 14. A motor 30 (e.g., a brushless DC electric motor) is supported within the motor housing portion 18, and a drive mechanism 34 is supported within the drive housing portion 22 (FIG. 2).

The illustrated expansion tool 10 includes a battery 46 (FIG. 1) configured to provide electrical power to the motor 30 (e.g., in response to depressing the actuator 26). The battery 46 is preferably a rechargeable battery pack with a plurality of lithium-based cells and is removably coupled to a battery receptacle 48 located at a base of the handle 14 (FIG. 1). In some embodiments, the battery 46 has a nominal output voltage of about 18 volts. In other embodiments, the battery 46 has a nominal output voltage of about 12 volts. In other embodiments, the battery 46 may have other nominal output voltages (e.g., 24 volts, 36 volts, 40 volts, etc.).

Referring to FIG. 2, the motor 30 includes a rotor or motor shaft 38 that rotates about a first axis or motor axis 42 to provide a rotational input to the drive mechanism 34. In the illustrated embodiment, the motor shaft 38 is rotationally supported by three bearings 43 spaced along the motor axis 42. The drive mechanism 34 converts the rotational input from the motor shaft 38 into a translational movement of a mandrel 50 along a second axis or mandrel axis 54. In the illustrated embodiment, the mandrel axis 54 is perpendicular to the motor axis 42, which contributes to a compact overall length of the expansion tool 10.

The illustrated drive mechanism 34 includes a first gear 58 coupled for co-rotation with the motor shaft 38 about the motor axis 42, a second gear 62 meshed with the first gear 58, and a third gear 66 meshed with the second gear 62. The drive mechanism 34 provides a speed reduction and torque increase from the motor shaft 38 to the third gear 66. For example, in the illustrated embodiment, the second gear 62 is larger in diameter and includes a greater number of teeth than the first gear 58, and the third gear 66 is larger in diameter and includes a greater number of teeth than the second gear 62.

With continued reference to FIG. 2, the third gear 66 is coupled for co-rotation with a shaft 70, such that the third gear 66 and the shaft 70 co-rotate together about a third axis or drive axis 74 that is parallel to the motor axis 42 and perpendicular to the mandrel axis 54. The shaft 70 provides a rotational input to a transmission 76, which in the illustrated embodiment is a multi-stage planetary transmission (e.g., a four-stage planetary transmission). In other embodiments, other types of transmissions 76 may be used. In the illustrated embodiment, the transmission 76 is shiftable to provide the expansion tool 10 with two different operating speeds.

More specifically, with reference to FIGS. 3-4, the expansion tool 10 includes a shifting assembly 1000 which may alternate between a high speed configuration or a low speed configuration. The illustrated shifting assembly 1000 includes an actuator 1002 positioned on the housing 12 of the expansion tool 10 and a shifting arm 1004 connected to the actuator 1002. The actuator 1002 is located on a rear side of the housing 12, above the handle portion 14 in the illustrated embodiment; however, the actuator 1002 may be located in other positions on the housing 12 in other embodiments.

The shifting arm 1004 is coupled to a movable ring gear 1008 (FIG. 2), which is part of an intermediate stage of the multi-stage planetary transmission 76. The shifting arm 1004 is pivotable to translate movement of the actuator 1002

into axial movement of the movable ring gear 1008. When the shifting assembly 1000 is in the low speed configuration, the movable ring gear 1008 engages a locking ring 1010, which prevents the ring gear 1008 from rotating. When the shifting assembly 1000 is in the high speed configuration, the movable ring gear 1008 disengages from the locking ring 1010, permitting free rotation of the ring gear 1008.

Referring to FIG. 4, the shifting assembly 1000 includes a shifting detector 1006 configured to detect when the shifting assembly 1000 is actuated between the high speed configuration and the low speed configuration. In the illustrated embodiment, the shifting detector 1006 includes a micro switch 1007 with a spring lever 1009 that extends into the path of the shifting arm 1004. The shifting arm 1004 engages the spring lever 1009 to close the micro switch 1007 when the shifting assembly 1000 is in the high speed configuration. When the shifting assembly 1000 is moved to the low speed configuration, the spring lever 1009 moves with the shifting arm 1004 to open the micro switch 1007. In other embodiments, the position of the micro switch 1007 may be varied such that the micro switch 1007 is closed when the shifting assembly 1000 is in the low speed configuration and opens when the shifting assembly 1000 is moved to the high speed configuration.

The shifting detector 1006 is electrically coupled to a controller 1010 (FIG. 1) of the expansion tool 10. The controller 1010 includes a plurality of electrical and electronic components that provide power, operational control, and protection to the components and modules within the controller 1010. In particular, the controller 1010 may include, among other things, an electronic processor (e.g., a programmable microprocessor, microcontroller, or similar device), non-transitory, machine-readable memory, an input/output interface, and the like. The components and modules of the controller 1010 may be mounted on a PCB supported within the housing 12. The electronic processor is communicatively coupled to the memory and configured to retrieve from memory and execute, among other things, instructions related to the control processes and methods described herein.

The shifting detector 1006 provides a signal to the controller 1010 of the expansion tool 10 to indicate if a shift is taking place. For example, the controller 1010 may determine that a shift from the low speed configuration to the high speed configuration is taking place if the micro switch 1007 changes state from its open position to its closed position. The controller 1010 may similarly determine that a shift from the high speed configuration to the low speed configuration is taking place if the micro switch 1007 changes state from its closed position to its open position. In other embodiments, the shifting detector 1006 may include other sensors capable of determining whether a shift is taking place. For example, in other embodiments, the shifting detector 1006 may include one or more optical sensors, magnetic sensors, position sensors, or the like capable of determining whether a shift is taking place by monitoring movement of the actuator 1002, ring gear 1008, and/or the shifting arm 1004.

In the illustrated embodiment, the expansion tool 10 includes a light source 1012 positioned on a front side of the housing 12 (FIG. 1). The light source 1012 may be configured to illuminate a workpiece during operation of the expansion tool 10. The light source 1012 may also be controlled by the controller 1010 to provide an operator with visual feedback associated with operation of the shifting assembly 1000.

5

In operation, the shifting assembly **1000** may be in either the high speed configuration or the low speed configuration. When the operator depresses the actuator **26** and energizes the motor **30**, the controller **1010** monitors the shifting detector **1006**. If the operator attempts to shift the shifting assembly **1000** between the high speed position and the low speed position by actuating the actuator **1002** while the motor **30** is energized, the shifting detector **1006** provides a signal to the controller **1010** indicating that a shift is occurring. In response to this signal, the controller **1010** automatically deenergizes the motor **30**. By deenergizing the motor **30**, the gears of the transmission **76** slow, and adverse impacts on the gears that may occur by shifting during operation are lessened. In some embodiments, the controller **1010** may also control the light source **1012** to produce a predetermined blinking pattern in order to communicate to the operator that the shut off was intentional. In other embodiments, other indicators, including but not limited to audible indicators, colored LEDs, LED/LCD displays, or the like may be used to alert the user to the intentional shut-off of the motor **30**. The operator can then resume operation by depressing the actuator **26** once more, thereby energizing the motor **30**.

With reference to FIG. 2, the illustrated transmission **76** includes an output member **78** (i.e., a carrier of the final stage of the planetary transmission **76**) coupled to a drive shaft **82** such that the drive shaft **82** co-rotates with the output member **78** about the drive axis **74**. A cam **86** is coupled for co-rotation with the drive shaft **82**. The cam **86** includes a contact surface **90** at its outer periphery. The contact surface **90** engages a follower or roller **94**, which in turn is coupled to the mandrel **50** via a pin **98** extending vertically through the mandrel **50**. The follower **94** is biased into engagement with the contact surface **90** of the cam **86** by a spring **102** acting on the mandrel **50**.

The contact surface **90** of the cam **86** has a variable radius such that rotation of the cam **86** moves the follower **94** to reciprocate the mandrel **50** along the mandrel axis **54**. The cam **86**, follower **94**, spring **102**, and mandrel **50** are supported within a frame **104**, which may be similar to the frame **627** described and illustrated in U.S. Patent Application Publication No. 2020/0261959, filed as application Ser. No. 16/795,742 on Feb. 20, 2020, in the name of Milwaukee Electric Tool Corporation, the entire content of which is incorporated herein by reference.

The mandrel **50** includes a conical outer surface **106** engageable with a head or working element **110** of the expansion tool **10** (FIG. 1). In the illustrated embodiment, the working element **110** includes a plurality of jaws **114**. The conical outer surface **106** of the mandrel **50** (FIG. 2) is engageable with interior sides of the jaws **114** as the mandrel **50** moves from a retracted position to an extended position along the mandrel axis **54**. This expands the jaws **114** radially outward from a closed position (illustrated in FIG. 1) to an expanded position. The jaws **114** may be biased toward the closed position (e.g., by an O-ring or toroidal spring surrounding the jaws **114**, by tension springs interconnecting adjacent jaws **114**, or by any other suitable arrangement), such that the jaws **114** return to the closed position when the mandrel **50** retracts along the mandrel axis **54**.

Referring to FIG. 1, each of the jaws **114** has an exterior side with a tapered portion **118** and a sizing portion **122**. When the working element **110** is in the closed position, adjacent jaws **114** abut one another such that the tapered portions **118** define a generally frustoconical shape. The sizing portions **122** collectively define a constant diameter or

6

maximum cross-sectional dimension when the jaws **114** are in the closed position, with the diameter being sized for proper expansion of PEX tubing of a desired nominal size. In other embodiments, the jaws **114** may be formed with other linear and/or non-linear profiles along the length of each jaw **114**. In some embodiments, the working element **110** may be removably coupled to the expansion tool **10** such that the jaws **114** may be interchanged with jaws having other sizes/geometries. For example, the working element **110** may be part of an expansion tool system including a plurality of interchangeable working elements, such as the expansion tool system **905** described and illustrated in U.S. Patent Application Publication No. 2020/0261959, which, as discussed above, is incorporated by reference.

The expansion tool **10** may include an automatic jaw rotation mechanism **200**, such as the automatic jaw rotation mechanism **200** described and illustrated in U.S. patent application Ser. No. 17/187,265, filed Feb. 26, 2021, in the name of Milwaukee Electric Tool Corporation, the entire content of which is incorporated herein by reference. The automatic jaw rotation mechanism **200** is configured to automatically rotate the jaws **114** of the working element **110** about the mandrel axis **54** during operation of the expansion tool **10**.

Referring to FIG. 5, in the illustrated embodiment, the automatic jaw rotation mechanism **200** includes a rotation collar **220** rotatably supported by the frame **104** adjacent a connection end **2000** of the frame **104**. The connection end **2000** includes a set of external threads **2002**. The rotation collar **220** includes a central bore **2004** which allows the mandrel **50** to pass through the rotation collar **220** and engage the jaws **114**. The rotation collar **220** includes an end face **2006** having a plurality of slots **2008** extending from the end face **2006** in an axial direction (i.e. a rearward direction). A plurality of teeth **2010** extends forwardly from the end face **2006**. The teeth **2010** are arranged such that each tooth **2010** is disposed between an adjacent pair of slots **2008**. The illustrated teeth **2010** are formed as truncated pyramids. In other embodiments, the teeth **2010** may be formed in other suitable shapes.

With reference to FIGS. 6A and 7, the working element **110** is removably coupled to the frame **104** by a retaining sleeve **2012**. The retaining sleeve **2012** includes an internal groove **2013** and a set of internal threads **2014**. Each of the jaws **114** includes a flange **2015** that is received within the internal groove **2013** of the retaining sleeve **2012**. The jaws **114** are rotatable relative to the retaining sleeve **2012**, as the flanges **2015** are slidable within the internal groove **2013**. The internal threads **2014** of the retaining sleeve **2012** cooperate with the external threads **2002** of the connection end **2000** to removably couple the retaining sleeve **2012** to the frame **104**.

Referring to FIG. 6A, each of the jaws **114** of the working element **110** includes a base surface **2016**, which faces rearward when the working element **110** is coupled to the expansion tool **10**. The base surface **2016** includes a projection or tab **2018** and two grooves **2022** located on either side of the tab **2018**, along the edges of the base surface **2016**. When the tabs **2018** are tapered outward in the rearward direction to match the profile of the conical outer surface **106** mandrel **50**.

As illustrated in FIGS. 8 and 9, when attaching the working element **110** to the expansion tool **10**, an operator positions the retaining sleeve **2012** adjacent the connection end **2000** of the frame. In order to couple the jaws **114** to the rotation collar **220**, the tabs **2018** of the jaws **114** must align with the slots **2008** formed in the end face **2006** of the

rotation collar **220**. As shown in FIG. 8, the jaws **114** can then be rotated relative to the retaining sleeve **2012** and the frame **104** until the tabs **2018** are aligned with the slots **2008**, at which point the retaining sleeve **2012** can be rotated relative to the frame **104** to begin threading the retaining sleeve **2012** on to the external threads **2002** of the connection end **2000**.

Continued rotation of the retaining sleeve **2012** in a tightening direction causes the tabs **2018** to travel further into the slots **2008**, thereby rotatably coupling the rotation collar **220** and the jaws **114**. Once the retaining sleeve **2012** is fully installed on the connection end **2000**, the teeth **2010** (FIG. 5) engage the grooves **2022** (FIG. 6A) to provide an additional torque-transmitting connection between the rotation collar **220** and the jaws **114**.

In operation, the jaws **114** (FIG. 1) of the expansion tool **10** are inserted into an end of a segment of PEX tubing to be expanded such that the tapered portions **118** abut an interior wall of the PEX tubing. The operator depresses the actuator **26**, which energizes the motor **30**.

Once energized, the motor **30** rotates the cam **86** via the drive mechanism **34** to perform cycles of axially extending and retracting the mandrel **50** along the mandrel axis **54** (FIG. 2), thereby expanding and contracting the jaws **114**. As the jaws **114** expand, the tapered portions **118** engage with the interior wall of the PEX tubing to gradually expand the PEX tubing. The expansion tool **10** continues the cycles of axially extending and retracting the mandrel **50**. The operator pushes the jaws **114** deeper into the PEX tubing with each successive expansion until the sizing portions **122** of the jaws **114** are fully inserted into the PEX tubing. This indicates to the operator that expansion is complete. The jaws **114** are withdrawn from the PEX tubing, and the operator inserts a fitting into the end of the PEX tubing. The interior of the PEX tubing then elastically recovers and secures the fitting in place.

The automatic rotation mechanism **200** operates to incrementally rotate the jaws **114** during each cycle of axially extending and retracting the mandrel **50**. The automatic rotation mechanism **200** incrementally rotates the rotation collar **220**. As the rotation collar **220** rotates, the slots **2008** engage the tabs **2018** and transfer the rotation to the jaws **114**. The engagement between the tabs **2018** and the slots **2008** ensure that rotation is transferred without any slippage. Additionally, the teeth **2010** engage the grooves **2022** to provide an additional torque-transmitting connection between the rotation collar **220** and the jaws **114**. The retaining sleeve **2012** remains stationary and retains the jaws **114** adjacent the connection end **2000** of the frame **104**.

The jaws **114** are preferably incrementally rotated during each retraction cycle by an angular displacement that is less than the angular spacing of the jaws **114**. For example, when the working element **110** includes six jaws, the jaws are spaced by sixty degrees, and the automatic rotation mechanism **200** is operable to rotate the jaws **114** by an angular displacement less than sixty degrees during each retraction cycle. In some embodiments, the jaws **114** are rotated by an angular displacement less than 45 degrees, and in some embodiments, the jaws **114** are rotated by an angular displacement less than 20 degrees.

By rotating the jaws **114** by an angular displacement that is less than the angular spacing of the jaws **114**, the jaws **114** smooth out any indentations that may be formed on the interior wall of the PEX tubing during expansion. This promotes a quality seal with the subsequently inserted fitting. Furthermore, by rotating the jaws **114** while the jaws **114** are retracting, friction between the jaws **114** and the

PEX tubing is reduced. In addition, rotating the jaws **114** simultaneously while the jaws **114** are retracting advantageously reduces the cycle time of the expansion tool **10**.

FIG. 6B illustrates a conventional working element **110a**, which may alternatively be coupled to the expansion tool **10**. The working element **110a** does not include the tabs **2018** and instead only includes the grooves **2020a** formed on the base surfaces **2016a** of the jaws **114a**. Because the rotation collar **220** includes the teeth **2010**, the teeth **2010** are received within the grooves **2020a** when the working element **110a** is coupled to the frame **104** to couple the jaws **114a** for co-rotation with the rotation collar **220**. Thus, the rotation collar **220** of the expansion tool **10** is advantageously backwards-compatible with conventional working elements, such as the working element **110a**.

FIGS. 10A and 11A illustrate additional embodiments of working elements **110b** and **110c** which may be coupled to the expansion tool **10** (e.g., by the retaining sleeve **2012**). In each case, the interior sides of jaws **114** define an interior cavity **126** in which an inner cone **130a** (FIG. 10A), **130b** (FIG. 10B) is disposed. The inner cone **130a**, **130b** defines an outer conical surface **134** that abuts and engages the interior sides of the jaws **114** and an inner bore **138** that extends at least partially along the length of the inner cone **130** along a conical axis **142**.

The inner cone **130a**, **130b** is engageable with the mandrel **50** and slidable along the mandrel axis **54** therewith. More specifically, the mandrel **50** engages the inner cone **130a**, **130b** with the mandrel **50** at least partially disposed in the inner bore **138** of the inner cone **130a**, **130b**. As the mandrel **50** engages the inner cone **130a**, **130b** and proceeds in a linear direction along the mandrel axis **54**, the inner cone **130a**, **130b** engages the interior sides of jaws **114** thereby transitioning the jaws from the closed position (e.g., shown in FIG. 9) to the expanded position (as shown in FIGS. 10A and 11A).

As shown in FIGS. 10B and 11B, the inner cone **130a**, **130b** may include features for distributing and/or retaining lubricant (such as grease, oil, or other appropriate material for reducing friction between surfaces moving relative to one another) at the interface of the outer conical surface **134** of the inner cone **130a**, **130b** and the interior sides of jaws **114**.

For example, as shown in FIG. 10B, the inner cone **130a** includes a plurality of bores **146** extending from the outer conical surface **134** to the inner bore **138** and fluidly communicating with the inner bore **138**, such that lubricant is allowed to move through the inner bore **138** at the engagement with the mandrel **50** to the outer conical surface **134** via bores **146**. Lubricant is thereby applied at the interface of the outer conical surface **134** and the interior sides of jaws **114**.

In another example, as shown in FIG. 11B, the inner cone **130b** includes a plurality of grooves **150** disposed on the outer conical surface **134** spaced along the conical axis **142** and extending circumferentially about the outer conical surface **134** and radially inward toward the inner bore **138**. Lubricant may be disposed in the grooves **150** whereby the interface of the outer conical surface **134** and the interior sides of jaws **114** is maintained in a lubricated state.

Various features and aspects of the present invention are set forth in the following claims.

What is claimed is:

1. An expansion tool, comprising:

a housing;

a collar rotatably coupled to the housing, the collar including a plurality of slots;

9

a plurality of jaws, each jaw having a projection received in a corresponding one of the plurality of slots such that the jaws are coupled for co-rotation with the collar; a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position; a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws, wherein the mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position; and a rotation mechanism configured to incrementally rotate the collar.

2. The expansion tool of claim 1, wherein the collar includes a front surface facing the jaws, and wherein the slots extend in a rearward direction from the front surface.

3. The expansion tool of claim 2, wherein the collar includes a plurality of teeth extending in a forward direction from the front surface.

4. The expansion tool of claim 3, wherein the plurality of jaws is removably coupled to the housing.

5. The expansion tool of claim 4, wherein the housing at least partially encloses a frame having a connection end, wherein the expansion tool further comprises a retaining sleeve surrounding the plurality of jaws, and wherein the plurality of jaws is configured to be coupled to the housing by coupling the retaining sleeve to the connection end of the frame.

6. The expansion tool of claim 4, wherein the plurality of jaws is a first plurality of jaws, and the first plurality of jaws is interchangeable with a second plurality of jaws.

7. The expansion tool of claim 6, wherein each jaw of the second plurality of jaws includes a recess formed in a rear surface of the jaw, and each recess is configured to receive a corresponding one of the plurality of teeth to couple the second plurality of jaws for co-rotation with the collar.

8. The expansion tool of claim 1, further comprising a drive mechanism including a motor and a rotatable cam, wherein rotation of the cam moves the mandrel between the retracted position and the extended position.

9. The expansion tool of claim 8, wherein the drive mechanism is operable in a high speed configuration and a low speed configuration, and wherein the expansion tool further comprises: a shifting assembly including an actuator operable to shift the drive mechanism between the high speed configuration and the low speed configuration; and a shifting detector configured to detect a shift between the high speed configuration and the low speed configuration.

10. The expansion tool of claim 1, wherein the cone includes a plurality of grooves containing grease to lubricate the inner surfaces of the plurality of jaws.

11. The expansion tool of claim 1, wherein the cone includes a plurality of bores extending from an outer conical surface to an inner bore, the plurality of bores defining fluid pathways to convey lubricant between the inner bore and an outer surface of the cone.

10

12. An expansion tool comprising:

a housing;

a motor supported in the housing;

a plurality of jaws;

a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position;

a drive mechanism configured to convert rotational input from the motor into translational movement of the mandrel between the retracted position and the extended position, the drive mechanism including a rotatable cam, wherein rotation of the cam moves the mandrel between the retracted position and the extended position, and wherein the drive mechanism is operable in a high speed configuration and a low speed configuration;

a shifting assembly including an actuator operable to shift the drive mechanism between the high speed configuration and the low speed configuration; and

a shifting detector configured to detect a shift between the high speed configuration and the low speed configuration.

13. The expansion tool of claim 12, wherein the shifting detector includes a micro switch.

14. The expansion tool of claim 13, wherein the shifting assembly includes a shifting arm engageable with the micro switch.

15. The expansion tool of claim 12, wherein the motor rotates the rotatable cam via the drive mechanism and a controller in communication with the shifting detector, wherein the controller is configured to deenergize the motor in response to the shifting detector detecting the shift.

16. The expansion tool of claim 15, further comprising an indicator, wherein the controller is configured to illuminate the indicator in response to the shifting detector detecting the shift.

17. The expansion tool of claim 12, wherein the drive mechanism includes a multi-stage planetary transmission, wherein the multi-stage planetary transmission includes a movable ring gear and a locking ring, wherein the movable ring gear is engaged with the locking ring in the low speed configuration, and wherein the movable ring gear is disengaged from the locking ring in the high speed configuration.

18. An expansion tool, comprising:

a housing;

a collar rotatably coupled to the housing;

a plurality of jaws coupled for co-rotation with the collar;

a mandrel moveable relative to the housing between a retracted position and an extended position, the mandrel engageable with the jaws to expand the jaws in response to movement of the mandrel to the extended position; and

a cone received within the plurality of jaws and engageable with inner surfaces of the plurality of jaws, wherein the mandrel is configured to engage the cone to move the cone with the mandrel to expand the jaws as the mandrel moves toward the extended position, and wherein the cone includes means for containing grease to lubricate the inner surfaces of the plurality of jaws.

* * * * *