

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250265070

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Fox; Harry et al.

---

### CLIENT CUSTOMIZED MULTIFUNCTION ROBOT

---

#### Abstract

A system for customizing a robot for client use, including a central server computer, a robotic operation control kit to control functionality of the robot, wherein the robotic operation control kit is stored on the central server to be downloaded by the robot to control general robot functionality that is not client specific, a client customizing application at the central server, which is accessible by a client to customize an application layer that is configured to be downloaded to the robot and cooperate with the robotic operation control kit to provide functionality of the robot; wherein the application layer controls client specific robot functionality.

---

**Inventors:** Fox; Harry (Jerusalem, IL), Zlotnikov; Boris (Tel Aviv, IL), Benjamin; Jacob (Maale Adumim, IL), Wulfsohn; Ronnie (Bat Ayin, IL), Topper; Betsalel (Jerusalem, IL), Gorelick; Andrew (Ashkelon, IL), Spiro; Efraim (Jerusalem, IL)

**Applicant:** XTEND AI Inc. (Middleburg, FL)

**Family ID:** 1000008576862

**Appl. No.:** 19/198211

**Filed:** May 05, 2025

#### Related U.S. Application Data

parent US continuation 18236002 20230821 parent-grant-document US 12293180 child US 19198211

us-provisional-application US 63523929 20230629

---

#### Publication Classification

**Int. Cl.:** G06F8/65 (20180101); G06V10/94 (20220101); G06V40/16 (20220101)

**U.S. Cl.:**

## Background/Summary

### FIELD OF THE DISCLOSURE

[0001] The present disclosure relates to robots and to robots that can operate offline and online.

### CROSS REFERENCE TO RELATED APPLICATIONS

[0002] Applicant claims priority and the benefit of U.S. non-provisional patent application Ser. No. 18/236,002, filed Aug. 21, 2023, which claims priority and the benefit of US provisional application 63/523,929, filed Jun. 29, 2023, the disclosure of which is incorporated herein by references.

### BACKGROUND OF THE DISCLOSURE

[0003] Robots in the modern day fall generally into two categories. The first is an unintelligent robot with hyper-specific functionality, usually on assembly lines. The second is an intelligent, general function, sometimes mobile, robot that may use intelligence derived from both artificial intelligence (such as Cloud Artificial Intelligence) or from the processing of operational algorithms such as facial and object recognition, audio recognition etc.

[0004] Intelligent robots are becoming more and more part of everyday life. Such robots are used (for example) for medical care support, as waiters in restaurant, for takeaway deliveries and other tasks.

[0005] The intelligent robots are typically controlled by a server which stores their data and functionality. The processing power needed to operate such robots typically requires large and costly processors and peripherals. In order to be controlled by the server and have access to data, resources and services, the robot is required to have some form of communication means with the server such as Bluetooth, Wi-Fi, Zigbee etc.

[0006] An intelligent online robot typically has access to a very large amount of data. With this data it can reliably pull operational data, or any other data, as needed. The server ensures keeping the data up to date. Without the online data, it is very difficult to have a robot with complex functionality operate. It may be appreciated that a robot may not always be in communication with its server during its use. For example, a power outage could cause a Wi-Fi connection to fail, leaving the robot offline. Alternatively, the robot may be out of range of communication with its server. Thus, in order for the robot to perform autonomously offline, it would therefore require the full functionality provided by the server to be stored locally on the robot requiring large and expensive processors and storage capabilities. This full functionality may also include the processing power to run heavy operational algorithms in order to support the intelligence it requires in order to make decisions to operate independently.

[0007] Typically, it is not practical nor cost effective to fit an entire server processing unit and storage onto an individual robot in order for it to have the full gamut of functionality available when offline.

[0008] To effect an offline robot, the processors are generally larger and more costly than the average processor of a similar robot that operates using a server, as an online robot can offload to the server much of the strenuous processing that would normally fall on the robot's processors. As the herein disclosed robot operates offline, that cannot be done. Accordingly, the processors of the robots in the current disclosure are much smaller than the average server processor, as you cannot fit an entire server processing unit onto each robot at any reasonable size or cost-effectiveness. Therefore, the processors are stronger than for the average online robot and weaker than the average server processor.

[0009] Application Ser. No. 18/149,183 filed Jan. 3, 2023 (published on Aug. 3, 2023 as US

2023/0244230) the disclosure of which is incorporated herein by reference discloses a robot system that is configured to function online and offline by downloading functional modules from the server. Preparation of the functional modules for each client places a heavy burden on the manufacturer in developing such a robot for a client.

[0010] Accordingly, there is a need in the industry and field for a device or system that can efficiently and effectively reduce the burden of preparation of a robot for a specific client by the manufacturer.

#### SUMMARY OF THE DISCLOSURE

[0011] To achieve these and other objects, the herein device can efficiently and effectively reduce the burden of preparation of a robot for a specific client by the manufacturer.

[0012] Therefore, to achieve these and other objects, the herein disclosed invention is a system for customizing a robot for client use, comprising: a central server computer; a robotic operation control kit to control functionality of the robot, wherein the robotic operation control kit is stored on the central server to be downloaded by the robot to control general robot functionality that is not client specific; and, a client customizing application at the central server, which is accessible by a client to customize an application layer that is configured to be downloaded to the robot and cooperate with the robotic operation control kit to provide functionality of the robot; wherein the application layer controls client specific robot functionality.

[0013] An aspect of an embodiment of the disclosure, relates to a system for customizing a robot. The system includes a central server, which is provided with a robotic operation control kit. The robotic operation control kit is downloaded to the robot to serve as an application for defining basic functionality of the robot that is independent of the client using the robot. The central server further comprises a customizing application that is accessible by a client to define an application layer, which is downloaded to the robot to cooperate with the robotic operation control kit by controlling client specific robot functionality.

[0014] The client may access the central server using a client server. The client server may access the central server to create the application layer and store the application layer at the central server or at the client server. Alternatively, the client server may download the customizing application from the central server to the client server and form the application layer locally at the client server.

[0015] The robot is configured to download the application layer from the central server or the client server respectively.

[0016] There is thus provided according to an embodiment of the disclosure, a system for customizing a robot for client use, comprising: [0017] A central server computer; [0018] A robotic operation control kit to control functionality of the robot, wherein the robotic operation control kit is stored on the central server to be downloaded by the robot to control general robot functionality that is not client specific; [0019] A client customizing application at the central server, which is accessible by a client to customize an application layer that is configured to be downloaded to the robot and cooperate with the robotic operation control kit to provide functionality of the robot; wherein the application layer controls client specific robot functionality.

[0020] In an embodiment of the disclosure, the system further comprises a client server that is configured to access the central server to customize the application layer and store the application layer at the central server; wherein the application layer is configured to be downloaded from the central server by the robot. Alternatively, the system further comprises a client server that is configured to access the central server to customize the application layer and store the application layer at the client server; wherein the application layer is configured to be downloaded from the client server by the robot. Further alternatively, the system further comprises a client server that is configured to access the central server to download the customization application to the client server, customize the application layer and store the application layer at the client server; wherein the application layer is configured to be downloaded from the client server by the robot.

[0021] In an embodiment of the disclosure, the robotic operation control kit controls access to

sensors and motors of the robot. Optionally, the application layer provides client data to the robotic operation control kit to enable performing client face recognition. In an embodiment of the disclosure, the robotic operation control kit communicates with sensors and motors of the robot via a communication broker that receives communications from the robotic operation control kit and provides them to the sensors and motors subject to availability. Optionally, the robotic operation control kit and application layer are configured to delegate processing processes to the central server when functioning online. In an embodiment of the disclosure, the robotic operation control kit is configured to receive upgrades from the central server. Optionally, the application layer is configured to receive upgrades from the client server.

[0022] There is further provided according to an embodiment of the disclosure, a method of customizing a robot, comprising: [0023] Storing a robotic operation control kit on a central server computer; wherein the robotic operation control kit is configured to control general robot functionality that is not client specific; [0024] Customizing an application layer by a client that has access to a client customizing application at the central server; wherein the application layer controls client specific robot functionality; [0025] Downloading the robotic operation control kit to the robot; [0026] Downloading the customized application layer; [0027] Wherein the application layer is configured to cooperate with the robotic operation control kit to provide functionality of the robot.

[0028] In an embodiment of the disclosure, a non-transitory computer readable storage medium comprises instruction that when executed by a computer are configured to perform the above method.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0029] The present disclosure will be understood and better appreciated from the following detailed description taken in conjunction with the drawings. Identical structures, elements or parts, which appear in more than one figure, are generally labeled with the same or similar number in all the figures in which they appear, wherein:

[0030] FIG. 1 is a schematic illustration of a system for preparing a client customized robot, according to an embodiment of the disclosure;

[0031] FIG. 2 is a schematic illustration of architecture of software of the system, according to an embodiment of the disclosure; and

[0032] FIG. 3 is a schematic illustration of a method of preparing a client customized robot, according to an embodiment of the disclosure.

### DETAILED DESCRIPTION

[0033] In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the invention. However, it will be understood by those skilled in the art that the present invention may be practiced without some of those specific details. In other instances, well-known methods, procedures, and components have not been described in detail so as not to obscure the present invention.

[0034] In a an embodiment, the Invention constitutes a system for customizing a robot for client use, comprising: a central server computer; a robotic operation control kit to control functionality of the robot, wherein the robotic operation control kit is stored on the central server to be downloaded by the robot to control general robot functionality that is not client specific; and, a client customizing application at the central server, which is accessible by a client to customize an application layer that is configured to be downloaded to the robot and cooperate with the robotic operation control kit to provide functionality of the robot; wherein the application layer controls client specific robot functionality.

[0035] FIG. 1 is a schematic illustration of a system **100** for preparing a client customized robot **120**, according to an embodiment of the disclosure. System **100** includes a central server **110** that is configured to provide robots **120** with a robotic operation control kit (ROCK) **122**. The robotic operation control kit **122** is a generic and raw robot functioning and managing portal or software development kit (SDK), which is configured to provide basic functionality of the robot **120** when offline or online. The robotic operation control kit **122** is configured to function in conjunction with an application layer **124** that is customized by robot clients optionally with a client server **130** according to their needs. The application layer **124** is a non-generic customizable or malleable front end and logical flow portal to handle the user experience (UX) and user interface (UI) of the robot. Accordingly, the robotic operation control kit **122** handles generic robot functionality and application layer **124** handles client specific robot functionality.

[0036] In an embodiment of the disclosure, the robotic operation control kit **122** is prepared, provided and updated by the robot manufacturer or designer on central server **110**. The robotic operation control kit **122** is generic for all robots **120** of a specific model and does not include client specific data, for example client specific algorithm modules, client policies and procedures, client information such as employee information, employee pictures (e.g., for face recognition), client location information (e.g., office maps) and other client relevant data. Optionally, application layer **124** is prepared, provided and updated by a client server **130** to provide the robot **120** with client specific data. This differentiation removes the burden of customizing the robot **120** to meet a clients needs from the robot manufacturer and allows a client to emphasize client specific functionality.

[0037] In an embodiment of the disclosure, central server **110** is a computer with a processor and memory, which includes the following elements: a communication interface **111**; a server frontend **112**; a server backend **113**; a server database **114**; and a client customizing application **115**.

[0038] The communication interface **111** is provided to communicate with robots **120** and client servers **130**.

[0039] The server frontend **112** is where user interaction occurs. The frontend serves as an interface for communicating with robots **120**, users, and client servers **130**.

[0040] The server backend **113** is where the technical processes occur. The backend serves to control and execute applications on the central server **110**.

[0041] The server database **114** is provided to store data such as a current robotic operation control kit **122** for providing to robots **120**.

[0042] The client customizing application **115** is configured to be accessed or downloaded to client servers **130** to customize an application layer **124**.

[0043] In an embodiment of the disclosure, client servers **130** are computers with a processor and memory, including the following elements: A communication interface **131**, a local database **134** and an application **135**.

[0044] The communication interface **131** serves to communicate with the central server **110** and with robots **120**.

[0045] The local database **134** serves to store application layer **124** and other client data.

[0046] The application **135** is configured to enable a client to access client customizing application **115** on central server **110** to customize a client specific application layer **124** for robot **120**. The application **135** may store the customized application in local database **134** to be provided to robot **120**. Alternatively or additionally, central server **110** may provide application **115** to the client server **130** to be stored and executed locally by the client to customize the application layer **124** for robot **120**.

[0047] In an embodiment of the disclosure, robot **120** includes a processor and memory configured to control and execute the following modules and elements of the robot **120**: a router **121**, a robotic operation control kit (Rock) **122**, a scripter **123**, an application layer **124**, a communication broker **125**, a local database **126** and features **127**.

[0048] The router **121** serves for communicating with central server **110** and client servers **130**.

[0049] The robotic operation control kit (Rock) **122** is provided by the central server **110** to control the basic functionality of the robot **120** when offline, for example interaction with sensors and motors of the robot **120**. Optionally, the robotic operation control kit **122** may also control basic functionality when online, for example to initiate queries from central server **110** and act on instructions from the central server **110**. For example the central server **110** may employ a large language module (LLM), which may be used to help the robot **120** to comprehend and respond to user communications. In some embodiments of the disclosure, the central server **110** may take control and provide the robot **120** with instructions to perform required tasks.

[0050] The application layer **124** is prepared by a client server **130** to provide client specific data and client specific functionality when offline; the application layer **124** may be stored at the client server **130** (e.g., in database **134**) or at the central server **110** (e.g., in server database **114**) to be provided to the robot to control offline functionality in conjunction with robotic operation control kit **122**. Optionally, application layer **124** may also support online functionality, for example communication with client server **130** regarding client specific issues or with central server **110** to access specific services provided by the central server **110**, for example an LLM.

[0051] The scripter **123** is responsible for managing the initial downloading and execution of the applications that comprise the robot's ability. The scripter is configured to initiate access to the central server **110** and the client server **130** and based on a unique ID of the robot identify, identify which robotic operation control kit **122** and which application layer **124** need to be downloaded by router **121** to initialize the robot **120** to serve the client that acquired the robot **120**.

[0052] The communication broker **125** or brokers configured to receive communications from the robotic operation control kit **122** and distribute the communications to the features of the robot **120** or vice versa, for example to provide instructions to motors and sensors of the robot or receive measurements from them. The communication broker **125** may use message queue telemetry transport (MQTT).

[0053] The local database **126** in the memory of the robot **120** is configured to store downloaded applications and data locally at the robot **120**.

[0054] The features **127** are the functions that the robot **120** activates during operation. The features are achieved using sensors, motors, gears, wheels and other software and hardware to perform the functions requested by the robotic operation control kit **122** and the application layer **124**. For example: image recognition, audio recognition, navigation, speech to text (STT), text to speech (TTS), natural language processing (NLP), optical symbol recognition (OSR), optical character recognition (OCR), identifying a person's vital signs (e.g., SpO2, heart rate breathing rate, pain diagrams, brain waves, pulse rate), and other functions.

[0055] FIG. 2 is a schematic illustration of architecture of the software of system **100**, according to an embodiment of the disclosure. In an embodiment of the disclosure, the application layer **124** is configured to communicate directly with the robotic operation control kit **122**, and the robotic operation control kit **122** is configured to communicate and activate the features **127**. Optionally, communication broker **125** serves as an intermedium between the robotic operation control kit **122** and the features **127**. Various features may act independently providing data simultaneously and communication broker **125** receives the data and provides it to the robotic operation control kit **122** when it is available to act on the data. Likewise the robotic operation control kit **122** may provide instructions to various features **127** (e.g., sensors) via communication broker **125**. Communication broker **125** may store the instructions in a buffer or queue and provide them to the features **127** when they are available to communicate. Likewise robotic operation control kit **122** may provide a single command that is to be delivered by the communication broker **125** to multiple sensors or motors.

[0056] In an embodiment of the disclosure, the robotic operation control kit **122** is provided from the central server **110** that represents the robot manufacturer. Optionally, the application layer **124**

is prepared by a client server **130** that represents a client that uses customizing application **115** to customize the use of the robotic operation control kit **122** of the robot **120** to meet the needs of the client. For example to identify specific people, perform specific tasks and understand specific phrases and terminology when offline, since the resources of the robot **120** are limited. When online the robot **120** may be able to use heavier resources, for example to use a large language model (LLM) by querying the central server **110** or the client server **130**.

[0057] In an embodiment of the disclosure, the robot is configured to function offline and online. When offline the basic functions of the robot are handled by the robotic operation control kit **122** and client specific functions are handled by the application layer **124**. When online the robotic operation control kit **122** and application layer **124** may access the central server **110** or client server **130** to enhance functionality of the robot, for example providing updates and more complex functions. Optionally, the central server **110** updates the robotic operation control kit **122** and the client server **130** updates the application layer **124** with client specific data and functions, for example the update process may include adding or removing client data in the robot **120** (e.g., when a new staff member joins, face recognition photos are required, when a user leaves specific data is no longer required for face recognition and face recognition photos can be deleted, remodeling of AI modules may be required, and maps and location names may be altered).

[0058] In an embodiment of the disclosure, when online the robotic operation control kit **122** and/or application layer **124** can delegate processing to a respective server (**110**, **130**) to provide functions that require processing power that exceeds the internal processing power of the robot **120** and/or internal storage capacity of the robot **120**.

[0059] In an embodiment of the disclosure, the robot **120** includes hardware and software to sense the environment and to enable performing various functions, which may include: [0060] i. Speech recognition; [0061] ii. Natural language processing; [0062] iii. Vision, image processing; object recognition, face recognition, OCR (optical character recognition), reading; [0063] iv. Ability to move, navigation; [0064] v. Ability to talk [0065] vi. User interface on the robot screen/face.

[0066] The role of the software is to manage the hardware to provide a 'world' whereby the robot **120** can function. The software fulfills the functional specification of any given robot **120**.

[0067] In an embodiment of the disclosure, the robotic operation control kit **122** includes software routines to perform the above functions. However, the robotic operation control kit **122** may be programed not to take actions unless instructed to do so by application layer **124**. The application layer **124** is programed to provide the robot with a role by invoking the functions of the robotic operation control kit **122** and performing high level tasks, for example to serve as a waiter in a restaurant, or a receptionist at a medical facility.

[0068] The sensors of the robot **120** may include cameras, accelerometers, magnetometers, tactile sensors, light sensors, GPS/GNSS, microphones, gyroscopes, and other sensors. The motors may include motors, gears and wheels to control motion of the robot **120**, for example move the robot's hands, feet, bend joints and the like.

[0069] In an embodiment of the disclosure, the robot **120** can serve as a clinic assistant robot, wherein the role of the robot **120** is to register patients, take vitals, escort the patient to an examination room, and assist a doctor during the examination. The robotic operation control kit **122** and application layer **124** manage all the components described above so that the robot can fulfill this functional specification. The robotic operation control kit **122** and application layer **124** create a closed and defined world for the robot to exist in.

[0070] In an embodiment of the disclosure, the robotic operation control kit **122** does not discriminate which sources to pull data from during its operation. Rather, this discrimination is handled by the application layer **124**. The robotic operation control kit **122** only discriminates based on data type and not the content of the data. The types are dictated between the application layer **124** and the robotic operation control kit **122** based on a contract. The contract includes the exact terms of which data will be stored and managed, who has access to what, what are the data

types, actions to take and responses to said actions, completion, cancel, abort, responses, etc. For example the data may include, location, face vectors, person, object, etc.

[0071] In an embodiment of the disclosure, “patients, doctors, and nurses” can all be 3 different sets of data under the category of “person”. If the application layer **124** tells the robotic operation control kit **122** to search for “patients” and “nurses” using facial recognition, it will search for anyone that falls under the “patients” and “nurses” sets within the “person” category. It does not distinguish between patients and nurses in its search but it will not include doctors.

[0072] Optionally, the robotic operation control kit **122** will blindly return the face data of any patient or nurse that it recognizes as well as the sub-category that that person falls into to the application Layer **124**. For the robotic operation control kit **122**, all face recognition is the same. It has no contextual awareness of why it needs to do face recognition or who it should be trying to recognize outside of the subsets “patients” and “nurses” of the “person” category. That is the responsibility of the application layer **124**.

[0073] The application layer **124** will use its higher-level logic to determine how to proceed with the information received from the robotic operation control kit **122**. For example, if the robot **120** is executing a flow in which it has different logic depending on if it recognizes a patient versus a nurse (like check-in) then the application layer **124** is responsible for providing the appropriate response for a patient (e.g., beginning the check-in workflow) versus a nurse (e.g., opening a nurse menu).

[0074] There are collections that are modifiable by both the robotic operation control kit **122** and the application layer **124** (in a database a collection is an ordered group of elements having the same datatype”). There may be collections in the database that are modifiable exclusively by the robotic operation control kit **122** or exclusively by the application layer **124**.

[0075] In an embodiment of the disclosure, separating between the robotic operation control kit **122** and the application layer **124** reduces manufacturer development time since the manufacturer does not deal with client specific data but rather with the general function of the robot **120**. Additionally, the separation enhances control by the client since the client defines client specific data and client specific robot behavior.

[0076] In an embodiment of the disclosure, the robotic operation control kit **122** and the application layer **124** communicate with each other via data abstraction, the robotic operation control kit **122** cares about data types and not data, and the application layer **124** cares about the data. Optionally, the communication is via a “contract” dictating the data types and protocols the robotic operation control kit **122** will respond to. The application layer **124** sends the robotic operation control kit **122** commands to perform basic functions like face recognition or listen for a voice command. In turn, the robotic operation control kit **122** sends a callback back when completing its function.

[0077] In an embodiment of the disclosure, the robotic operation control kit **122** communicates exclusively with the central server **110** and the application layer **124** communicates exclusively with the client server **130**. Alternatively, both communicate with the central server **110**. If the robot **120** only functions online the application layer **124** can be located at the central server **110** or client server **130**, however to function in offline mode the application layer **124** must be located on the robot **120**.

[0078] FIG. 3 is a schematic illustration of a method **300** of preparing a client customized robot **120**, according to an embodiment of the disclosure. Initially, the manufacturer prepares a general application for controlling the basic functionality of the robot **120**. The application is the robotic operation control kit (ROCK) **122** and is stored (**310**) at the central server **110**. The central server **110** also hosts a client customizing application **115** that is provided to customize (**320**) a client application-application layer **124** by the client. The application layer **124** is configured to cooperate with the robotic operation control kit **122** to define the functionality of the robot when in online mode (with access to the central server **110**) and when in offline mode, when the robot **120** must handle the environment independently.



[0079] In some embodiments of the disclosure, the client uses a client server **130** to access the customizing application **115** and customize the application layer **124**, for example the customizing application **115** may be provided as a web application. Optionally, the resulting application layer **124** may be stored at the central server **110** or at the client server **130** to be provided to the robot **120**. In some embodiments of the disclosure, the client server **130** may acquire/download the customizing application **115** from the central server **110** and prepare the application layer **124** locally.

[0080] The robot **120** is configured to access central server **110** and download (330) the current robotic operation control kit **122** to control functionality of the robot **120**. The robot **120** is further configured to access the central server **110** or the client server **130** to download (340) the client customized application layer **124**.

[0081] The robot then activates (350) the robotic operation control kit **122** in cooperation with the application layer **124** to control functionality of the robot when online and when offline.

Optionally, when offline the robot **120** operates independently and when online the robot may use more processing consuming processes via the central server **110**, for example LLM and ChatGPT.

[0082] In an embodiment of the disclosure, the robotic operation control kit **122** and/or application layer **124** may query the central server **110** (e.g., invoking an LLM) to receive instructions to handle a specific situation. Alternatively, or additionally, the central server **110** may cooperate with the robotic operation control kit **122** and/or application layer **124** to work in tandem. Further alternatively or additionally, the central server **110** may take control of the robot **120** providing the robot with instructions and responding to feedback.

[0083] In an embodiment of the disclosure, the robotic operations control kit **122** and/or application layer **124** can be backed up on a non-transitory memory device, for example a DVD, USB disk, external disk or other devices and can be provided physically to a robot **120** for installation and execution.

[0084] It should be appreciated that the above-described methods and apparatus may be varied in many ways, including omitting or adding elements or steps, changing the order of steps and the type of devices used. It should be appreciated that different features may be combined in different ways. In particular, not all the features shown above in a particular embodiment are necessary in every embodiment of the disclosure. Further combinations of the above features are also considered to be within the scope of some embodiments of the disclosure.

[0085] It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described hereinabove. Rather the scope of the present invention is defined only by the claims, which follow.

## Claims

1. A client customizable robot configured to receive operational information from at least one server comprising: at least one feature to enable performance of generic and client specific functions, at least one database, at least one sensor or motor, at least one processor, the at least one processor configured to: a robotic operation control kit to control performance of the generic functions; and, wherein the robotic operation control kit controls access to the at least one sensor or motor; wherein the robotic operation control kit is configured to communicate with an application layer, wherein the application layer controls performance of the client specific functions and provides a role to perform; wherein said communication between the robotic operation control kit and the application layer is managed by a contract, wherein the contract dictates data types and protocols between the robotic operation control kit and the application layer; and, a router configured to communicate with the at least one server, wherein the at least one server is configured to: execute a client customization application to enable a client to customize the application layer prior to downloading of the application layer to the robot, and, store and

- download the robotic operation control kit and the application layer to the robot, wherein the client customizable robot is configured to perform the at least one feature after downloading the robotic operation control kit and the application layer to the robot from the at least one server.
2. The client customizable robot of claim 1, wherein the at least one server further comprises a client server and a central server, wherein the client server is configured to access the central server to customize the application layer prior to downloading of the application layer to the robot and to store the application layer.
  3. The client customizable robot of claim 2, wherein the client server is further configured to: customize the application layer; and, download the application layer to the robot.
  4. The client customizable robot of claim 2, wherein the client server is further configured to: access the central server of the at least one server to download the client specific features; customize the application layer with the client specific features; store the application layer; and, download the application layer to the robot.
  5. The client customizable robot of claim 1, wherein the application layer provides client data to the robotic operation control kit to enable performing client face recognition.
  6. The client customizable robot of claim 1, wherein the robot further comprises a communication broker configured to: receive communications from the robotic operation control kit; and, distribute the communication to the at least one sensor or motor according to the availability of the at least one sensor or motor.
  7. The client customizable robot of claim 1, wherein the robotic operation control kit and the application layer are configured to delegate the processing of processes to the at least one server when the robot is in communication with the at least one server.
  8. The client customizable robot of claim 1, wherein the robotic operation control kit is configured to receive upgrades from the at least one server.
  9. The client customizable robot of claim 2, wherein the application layer is configured to receive upgrades from the client server.
  10. The client customizable robot of claim 1, wherein the robotic operation control kit is configured to access the at least one server to invoke a large language model (LLM).
  11. A method for customizing a client customized robot (“robot”) comprising at least one feature to enable performance of generic and client specific functions, the method comprising: receiving from a central server a robotic operation control kit, and receiving from a client server a customized application layer, wherein the robotic operation control kit controls performance of the generic functions and wherein the application layer controls performance of the client specific functions and provides a role to perform, wherein one of the central server or the client server comprises a client customization application to customize the application layer, dictating communication between the robotic operation control kit and application layer via a contract, wherein the contract dictates data types and protocols between the robotic operation control kit and the application layer, performing the at least one feature after receiving by the robot the robotic operation control kit from the central server and the application layer from the client server, wherein the robotic operation control kit is configured to operate at least one sensor or motor of the robot.
  12. The method of claim 11, further comprising allowing access to the client server to enable the client server to: download the customization application; customize the application layer; store the application layer; and download the application layer to the robot.
  13. The method of claim 11, wherein the application layer provides client data to the robotic operation control kit to enable performing client face recognition.
  14. The method of claim 11, wherein the robot comprises a communication broker configured to: receive communications from the robotic operation control kit; and, distribute the communication to the at least one sensors or motors of the robot according to availability of the at least one sensors or motors of the robot.
  15. The method of claim 11, wherein the robotic operation control kit and application layer are

configured to delegate processing processes to the central server when the robot is functioning online.

**16.** The method of claim 11, wherein the robotic operation control kit is configured to receive upgrades from the central server.

**17.** The method of claim 11, wherein the robotic operation control kit accesses the central server to invoke a large language model (LLM).

**18.** A non-transitory computer readable storage medium comprising instruction that when executed by a computer are configured to perform the method of claim 11.

---