

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12392527
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	ElSherbini; Abdelrahman I. et al.

---

### Ejector-enhanced heat recovery refrigeration system

---

#### Abstract

A refrigerated transport system comprises: an engine. A vapor compression system comprises: a compressor for compressing a flow of a refrigerant; a first heat exchanger along a refrigerant flowpath of the refrigerant; and a second heat exchanger along the refrigerant flowpath of the refrigerant. A heat recovery system has: a first heat exchanger for transferring heat from the engine to a heat recovery fluid along a heat recovery flowpath; and a second heat exchanger along the heat recovery flowpath. The heat recovery system second heat exchanger and the vapor compression system first heat exchanger are respective portions of a shared tube/fin package.

---

**Inventors:** ElSherbini; Abdelrahman I. (Windsor, CT), Verma; Parmesh (Manlius, NY), Cogswell; Frederick J. (Glastonbury, CT)

**Applicant:** Carrier Corporation (Palm Beach Gardens, FL)

**Family ID:** 1000008767851

**Assignee:** Carrier Corporation (Palm Beach Gardens, FL)

**Appl. No.:** 17/716397

**Filed:** April 08, 2022

#### Prior Publication Data

Document Identifier	Publication Date
US 20220227198 A1	Jul. 21, 2022

#### Related U.S. Application Data

continuation parent-doc US 16094345 US 11300327 WO PCT/US2017/029326 20170425 child-doc US 17716397  
us-provisional-application US 62331313 20160503

---

## Publication Classification

**Int. Cl.:** **F25B7/00** (20060101); **B60H1/00** (20060101); **B60H1/32** (20060101); **F25B1/06** (20060101); **F25B6/04** (20060101); **F25B27/02** (20060101); **F25B40/02** (20060101)

**U.S. Cl.:**

**CPC** **F25B7/00** (20130101); **F25B1/06** (20130101); **F25B6/04** (20130101); **F25B27/02** (20130101); **F25B40/02** (20130101); B60H1/00014 (20130101); B60H2001/3298 (20130101); Y02A30/274 (20180101)

## Field of Classification Search

**CPC:** B60H (2001/3298); F25B (7/00)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3922877	12/1974	Ophir et al.	N/A	N/A
4164850	12/1978	Lowi, Jr.	N/A	N/A
4918937	12/1989	Fineblum	N/A	N/A
5117648	12/1991	Kowalski et al.	N/A	N/A
5462113	12/1994	Wand	N/A	N/A
5477697	12/1994	Wharton et al.	N/A	N/A
5509272	12/1995	Hyde	62/196.3	F25B 39/04
5647221	12/1996	Garris, Jr.	N/A	N/A
6321552	12/2000	Frederiksen	N/A	N/A
6675609	12/2003	Takeuchi et al.	N/A	N/A
7703296	12/2009	Jang et al.	N/A	N/A
8628025	12/2013	Bucknell	N/A	N/A
9222372	12/2014	Benson	N/A	N/A
9657977	12/2016	Hinde et al.	N/A	N/A
9759454	12/2016	Choi et al.	N/A	N/A
9995509	12/2017	Cline	N/A	N/A
10047991	12/2017	Kim et al.	N/A	N/A
10094577	12/2017	Dennis	N/A	F24D 12/02
10101060	12/2017	Feng	N/A	F25B 41/20
10254015	12/2018	Punuru	N/A	F25B 5/02
11300327	12/2021	Elsherbini	N/A	F25B 6/04
11448427	12/2021	Liu	N/A	F25B 27/02
2004/0069012	12/2003	Inoue	N/A	N/A
2006/0266072	12/2005	Takeuchi et al.	N/A	N/A
2007/0101748	12/2006	Pham et al.	N/A	N/A
2010/0043475	12/2009	Taras et al.	N/A	N/A
2011/0030232	12/2010	May	N/A	N/A
2011/0162395	12/2010	Chakiachvili et al.	N/A	N/A
2011/0174015	12/2010	Nagano et al.	N/A	N/A
2011/0259039	12/2010	Ma et al.	N/A	N/A

2011/0289953	12/2010	Alston	N/A	N/A
2012/0111027	12/2011	Campbell et al.	N/A	N/A
2012/0116594	12/2011	Aidoun et al.	N/A	N/A
2014/0223933	12/2013	Steele et al.	N/A	N/A
2014/0260403	12/2013	Connell	N/A	N/A
2014/0345301	12/2013	Steele	N/A	N/A
2015/0052926	12/2014	Alston	N/A	N/A
2015/0321539	12/2014	Mohs et al.	N/A	N/A
2017/0182869	12/2016	Kujak et al.	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
2671914	12/2010	CA	N/A
201095301	12/2007	CN	N/A
101688695	12/2009	CN	N/A
101825372	12/2009	CN	N/A
102062456	12/2010	CN	N/A
203615641	12/2013	CN	N/A
204165272	12/2014	CN	N/A
105531130	12/2015	CN	N/A
2002174493	12/2001	JP	N/A
2007248022	12/2006	JP	N/A
2007255768	12/2006	JP	N/A
2011133123	12/2010	JP	N/A
2010/129801	12/2009	WO	N/A
2011/006251	12/2010	WO	N/A
2015065643	12/2014	WO	N/A

#### **OTHER PUBLICATIONS**

MSDS for R134a. cited by examiner

Chinese Office Action dated May 30, 2023 for Chinese Patent Application No. 202111570274.0. cited by applicant

International Search Report and Written Opinion dated Jul. 14, 2017 for PCT Patent Application No. PCT/US2017/029326. cited by applicant

Chinese Office Action dated May 28, 2020 for Chinese Patent Application No. 201780027529.4. cited by applicant

Chinese Office Action dated Dec. 31, 2020 for Chinese Patent Application No. 201780027529.4. cited by applicant

US Office Action dated Jan. 13, 2021 for U.S. Appl. No. 16/094,345. cited by applicant

R. Tiruselvan et al., "Double Tube Heat Exchanger with Novel Enhancement: Part I—Flow Development Length and Adiabatic Friction Factor", 2012, pp. 641-651, Springer, New York, New York. cited by applicant

DOW®, Safety Data Sheet Dowfrost HD 40 Heat Transfer Fluid, Dyed, Apr. 23, 2015. cited by applicant

EXIM Trading LLC, Material Safety Data Sheet, R-245fa, Aug. 30, 2011. cited by applicant

US Office Action dated Jun. 9, 2021 for U.S. Appl. No. 16/094,345. cited by applicant

US Office Action dated Sep. 16, 2021 for U.S. Appl. No. 16/094,345. cited by applicant

Chinese Office Action dated Jan. 19, 2023 for Chinese Patent Application No. 202111570274.0. cited by applicant

Chinese Decision on Rejection dated Aug. 24, 2023 for Chinese Patent Application No. cited by

applicant

European Office action dated Oct. 8, 2024 for European Patent Application No. 22164843.9. cited by applicant

---

*Primary Examiner:* Zerphey; Christopher R

*Attorney, Agent or Firm:* Bachman & LaPointe, P.C.

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation of U.S. patent application Ser. No. 16/094,345, filed Oct. 17, 2018, entitled “Ejector-Enhanced Heat Recovery Refrigeration System”, which is a 371 US national stage application of PCT/US17/29326, filed Apr. 25, 2017, which claims benefit of U.S. Patent Application No. 62/331,313, filed May 3, 2016, and entitled “Ejector-Enhanced Heat Recovery Refrigeration System, the disclosure of which applications are incorporated by reference herein in their entireties as if set forth at length.

### **BACKGROUND OF THE INVENTION**

(1) The invention relates to refrigeration. More particularly, the invention relates to heat recovery refrigeration systems such as refrigerated transport systems.

(2) A transport refrigeration system used to control an enclosed area, such as the box of a truck, trailer, intermodal container, or the like, functions by absorbing heat from the enclosed area and releasing heat outside of the box into the environment. A number of transport refrigeration units, including units currently sold by assignee, employ a reciprocating compressor to pressurize refrigerant to enable the removal of heat from the box.

(3) A number of systems power the vapor compression system via an internal combustion engine. Some systems directly couple the engine to the compressor to mechanically drive the compressor. Others electrically power the compressor via a generator. When an engine is present, a number of systems have been proposed to use heat recovery from the engine. Several recent systems include those of US Patent Application Publication No. 2012/0116594A1 of Aidoun et al., published May 10, 2012.

### **SUMMARY OF THE INVENTION**

(4) One aspect of the invention involves a refrigerated transport system comprising an engine. A vapor compression system comprises: a compressor for compressing a flow of a refrigerant; a first heat exchanger along a refrigerant flowpath of the refrigerant; and a second heat exchanger along the refrigerant flowpath of the refrigerant. A heat recovery system has: a first heat exchanger for transferring heat from the engine to a heat recovery fluid along a heat recovery flowpath; and a second heat exchanger along the heat recovery flowpath. The heat recovery system second heat exchanger and the vapor compression system first heat exchanger are respective portions of a shared tube/fin package.

(5) In one or more embodiments of any of the foregoing embodiments, a separate subcooler has respective legs along the vapor compression flowpath and the heat recovery flowpath and the heat recovery system second heat exchanger is a condenser.

(6) In one or more embodiments of any of the foregoing embodiments, there is no separate subcooler; and the heat recovery system second heat exchanger is an evaporator.

(7) In one or more embodiments of any of the foregoing embodiments, the heat recovery system further comprises: an ejector having a motive flow inlet, a secondary flow inlet, and an outlet; a pump; and a loop of the heat recovery flowpath passing through the pump to the heat recovery system first heat exchanger, through the motive flow inlet and from the outlet back to the pump.

- (8) In one or more embodiments of any of the foregoing embodiments, the heat recovery system first heat exchanger has a leg along a coolant flowpath of the engine.
- (9) In one or more embodiments of any of the foregoing embodiments, the refrigerated transport system further comprises: an engine radiator; and a valve along the coolant flowpath for apportioning a total coolant flow between the radiator and the heat recovery system first heat exchanger.
- (10) In one or more embodiments of any of the foregoing embodiments, the engine is coupled to the compressor to drive the compressor.
- (11) In one or more embodiments of any of the foregoing embodiments, the engine is coupled to the compressor to mechanically drive the compressor.
- (12) In one or more embodiments of any of the foregoing embodiments, the engine is mechanically coupled to an electrical generator and the electrical generator is electrically coupled to an electric motor of the compressor.
- (13) In one or more embodiments of any of the foregoing embodiments, the refrigerated transport system further comprises a refrigerated compartment in thermal communication with the vapor compression system second heat exchanger.
- (14) In one or more embodiments of any of the foregoing embodiments, the refrigerated transport is a truck or a trailer.
- (15) In one or more embodiments of any of the foregoing embodiments, the engine, vapor compression system, and heat recovery system are mounted along a front of the compartment.
- (16) In one or more embodiments of any of the foregoing embodiments, the vapor compression system refrigerant and the heat recovery fluid are different from each other.
- (17) In one or more embodiments of any of the foregoing embodiments, the refrigerant is less flammable, less toxic, and/or less harmful to the contents of the refrigerated compartment than the heat recovery fluid.
- (18) In one or more embodiments of any of the foregoing embodiments, a method for operating the refrigerated transport system comprises, in a first mode: running the engine to drive the compressor to compress the flow of refrigerant and drive the refrigerant along the refrigerant flowpath; transferring the heat from the engine to the heat recovery fluid along the heat recovery flowpath; and rejecting heat from the refrigerant in the vapor compression system first heat exchanger.
- (19) In one or more embodiments of any of the foregoing embodiments, heat is absorbed by the heat recovery fluid in the heat recovery system second heat exchanger.
- (20) In one or more embodiments of any of the foregoing embodiments, in the first mode heat is rejected by the heat recovery fluid in the heat recovery system second heat exchanger.
- (21) In one or more embodiments of any of the foregoing embodiments, a separate subcooler has respective legs along the vapor compression flowpath and the heat recovery flowpath. The method further comprises, in the first mode transferring heat from the refrigerant in the vapor compression system to the heat recovery fluid in the heat recovery system in the subcooler via a refrigerant-refrigerant heat exchange without airflow.
- (22) In one or more embodiments of any of the foregoing embodiments, the refrigerated transport system further comprises a radiator and the method further comprises, in the first mode using a valve to apportion engine coolant between the heat recovery system first heat exchanger and the radiator.
- (23) Another aspect of the invention involves a combined cooling heating and power (CCHP) system comprising: a heat source. A vapor compression system comprises: a compressor for compressing a flow of a refrigerant; a first heat exchanger along a refrigerant flowpath of the refrigerant; and a second heat exchanger along the refrigerant flowpath of the refrigerant. A heat recovery system has: a first heat exchanger for transferring heat from the heat source to a heat recovery fluid along a heat recovery flowpath; and a second heat exchanger along the heat recovery flowpath. The heat recovery system second heat exchanger and the vapor compression system first

heat exchanger are respective portions of a shared heat exchanger for rejecting heat to a heat transfer fluid. Further embodiments may variations be along the lines of the other embodiments discussed above and below.

(24) In one or more embodiments of any of the foregoing embodiments, the heat source comprises an engine and an electric generator is mechanically coupled to the engine to be driven by the engine.

(25) In one or more embodiments of any of the foregoing embodiments, the shared heat exchanger is a water-cooled condenser (WCC).

(26) In one or more embodiments of any of the foregoing embodiments, the water-cooled condenser is selected from the group consisting of: a shell and tube WCC; tube-in-tube water WCC; and a brazed plate WCC.

(27) Another aspect of the invention involves a system comprising a heat source. A vapor compression system comprises: a compressor for compressing a flow of a refrigerant; a first heat exchanger along a refrigerant flowpath of the refrigerant; and a second heat exchanger along the refrigerant flowpath of the refrigerant. A heat recovery system has: a first heat exchanger for transferring heat from the heat source to a heat recovery fluid along a heat recovery flowpath; and a second heat exchanger along the heat recovery flowpath. The heat recovery system second heat exchanger and the vapor compression system first heat exchanger are respective portions of a shared heat exchanger for rejecting heat to a heat transfer fluid and/or are in common (e.g., series or parallel) along a heat transfer fluid flowpath. Further embodiments may variations be along the lines of the other embodiments discussed above and below.

(28) The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic view of a refrigeration system of a refrigerated transport system.

(2) FIG. 2 is a schematic view of the refrigerated transport system.

(3) FIG. 3 is a schematic view of a second refrigeration system.

(4) FIG. 4 is a schematic view of a third refrigeration system.

(5) FIG. 5 is a schematic view of a fourth refrigeration system.

(6) FIG. 6 is a schematic view of a combined cooling heating and power (CCHP) system.

(7) FIG. 6A is a view of a shell and tube condenser of the CCHP system of FIG. 6.

(8) FIG. 7 is a schematic view of a second CCHP system.

(9) Like reference numbers and designations in the various drawings indicate like elements.

### DETAILED DESCRIPTION

(10) FIG. 2 shows a refrigerated transport unit (system) **20** in the form of a refrigerated trailer. The trailer may be pulled by a tractor **22**. The exemplary trailer includes a container/box **24** defining an interior/compartment **26**. An equipment housing **28** mounted to a front of the box **24** may contain an electric generator system including an engine **30** (e.g., diesel) and an electric generator **32** mechanically coupled to the engine to be driven thereby. A refrigeration system **34** may be electrically coupled to the generator **32** to receive electrical power.

(11) FIG. 1 shows further details of the exemplary refrigeration system **34**. The system **34** includes a control system **200**. The control system **200** may include: one or more user interface (e.g., input/output) devices **202**; processors **204**; memory **206**; storage **208**; and hardware interface devices **210** (e.g., ports).

(12) The system **34** further includes a compressor **40** having a suction (inlet) port **42** and a

discharge (outlet) port **44**. An exemplary compressor **40** is an electrically-powered reciprocating compressor having an integral electric motor **46**. The compressor **40** may be coupled to the control system **200** to regulate its operation and to the generator **32** via power lines **48** to receive power. The compressor is a portion of a vapor compression system **50** having a recirculating refrigerant flowpath or loop **52**. The exemplary refrigeration system **34** further comprises a heat recovery system **56** having a heat recovery flowpath or loop **58**.

(13) Along the refrigerant flowpath **52**, the vapor compression system **50** includes, in a downstream direction from the discharge port or outlet **44**, a heat exchanger **60**, a leg **62-1** of a subcooler **62**, an expansion device **64**, and a heat exchanger **66** before returning to the suction port **42**. In a normal operational mode, the heat exchanger **60** is a heat rejection heat exchanger (condenser or gas cooler) and the heat exchanger **66** is a heat absorption heat exchanger (evaporator). Both heat exchangers **60** and **66** may be refrigerant-air heat exchangers having respective fans **70** and **72** driving airflows **520** and **522** along air flowpaths across the heat exchangers. The heat exchanger **66** is in thermal communication with the box interior to cool the box in the normal cooling mode(s). The heat exchanger **60** is in thermal communication with an exterior of the box to reject heat to the airflow **520** in the normal cooling mode. Thus, the airflow **520** may be an external airflow and the airflow **522** may be an interior airflow.

(14) As is discussed further below, the subcooler **62** is a refrigerant-refrigerant heat exchanger wherein the leg **62-1** along the refrigerant flowpath **52** is in heat exchanger relation with a leg **62-2** along the heat recovery flowpath **58**. The heat recovery fluid flowing along the heat recovery flowpath may go through a phase change (e.g., as discussed below) and may otherwise be characterized as a refrigerant. However, for convenience of reference, it will be hereafter referred to as the heat recovery fluid. The heat recovery fluid and the refrigerant may, in some implementations, have identical compositions or may be different. In the latter situation, there will be no fluid communication between the two loops. In the former, there could be.

(15) The heat recovery system **56** includes a pump **80** having an inlet **82** and an outlet **84**. The pump is along a sub-loop or flowpath branch **86** of the heat recovery flowpath **58** which also includes the primary flowpath of an ejector **90**. The branch **86** may also provide a convenient location for a receiver (not shown; e.g., at the pump inlet). The ejector has a primary or motive flow inlet **92** at the inlet of a nozzle (e.g., a convergent-divergent nozzle) **94** and an outlet **96** at the downstream end of a diffuser **98**. The ejector further comprises a mixer **100** and a secondary or suction inlet port **102**. Sequentially along the loop **86** proceeding downstream from the pump **80** in a normal operational mode, flow passes through a leg **110-1** of a heat exchanger **110**, the ejector primary inlet **92**, the ejector outlet **96**, and a heat exchanger **112** before returning to the pump.

(16) A second sub-loop or flowpath branch **120** branches off from the loop **86** between the heat exchanger **112** and pump **80** and passes sequentially through an expansion device **122**, the heat recovery loop leg **62-2** of the subcooler **62**, and returns to the ejector secondary or suction port **102**. In normal heat recovery operation, the heat exchanger **110** is a generator heat exchanger transferring heat from the engine in a leg **110-2** to the leg **110-1** of the heat recovery loop. Similarly, the heat exchanger **112** is a heat rejection heat exchanger. The heat recovery loop leg **62-2** of the subcooler serves as an evaporator or heat absorption heat exchanger absorbing heat from the vapor compression system leg **62-1** of the subcooler.

(17) FIG. 1 further shows, associated with the engine **30**, a radiator **130** and a fan **132** (electric or mechanical) driving an airflow **524** across the radiator. For engine cooling, a coolant pump **134** (e.g., mechanical or electric) may drive fluid along a recirculating loop **136** outputting heated coolant from the engine and returning reduced temperature coolant. The coolant may be a conventional engine coolant such as a water and glycol mixture. In the exemplary implementation, a valve **140** allows selective communication of the coolant flow to the heat exchanger **110** and/or the radiator **130**. In this example, the valve **140** is a proportioning valve allowing a stepwise or continuous allocation of the coolant flow between the heat exchanger **110** and the radiator **130**. In

alternative embodiments, the valve is bi-static. For example, one configuration of a bi-static valve may alternatively deliver coolant to the heat exchanger **110** or radiator while not delivering to the other. Yet other bi-static situations involve having flow to both in at least one condition.

(18) In the exemplary implementation, the heat exchangers **60** and **112** are part of a single heat exchanger unit. In an exemplary implementation, the unit is a single bank of tubes and fins with the heat exchangers **60** and **112** representing separate groups of legs of the tubes but sharing fins and tube plates. In the exemplary illustrated implementation, the two heat exchangers **60** and **112** are in series along an air flowpath for the airflow **520**. In the exemplary embodiment in the normal cooling mode, the heat exchanger **112** is downstream of the heat exchanger **60** along the associated air flowpath. The integrated heat exchanger with series airflow may have advantages in terms of economizing on space, economizing on heat exchanger cost, and economizing on fan cost (e.g., by having a single fan servicing both). By having the heat exchanger **60** upstream along the air flowpath, it receives the coldest air in normal operation.

(19) A number of variations are possible. Plural of these variations may coexist. One group of variations involves having the compressor **40** mechanically powered by the engine **30** (e.g., directly driven or driven via a transmission) rather than electrically driven. This would eliminate the motor **46** and eliminate the generator **32** (although the engine may include a generator for powering the engine (e.g., providing spark, starting, and the like)).

(20) In other variations, the valve **140** may be eliminated so that all coolant passes in series through the heat exchanger **110** and the radiator **130** (e.g., FIG. 3).

(21) Other variations involve eliminating the radiator **130** (and its fan **132**) so that the coolant supply and return pass directly between the engine and the heat exchanger **110**. The radiator elimination may reduce cost and space consumed. The heat recovery loop takes heat from the engine coolant and the subcooler **62** and rejects it to air at the heat exchanger **112**. In order to protect the engine, the operation of this variation could be prioritized for engine heat rejection. For example this may involve running with the vapor compression system in a less-efficient state so as to consume more power (and thus require the engine to consume more fuel) than if the engine were rejecting heat via the omitted radiator.

(22) Other variations involve altering the cycles of the vapor compression system **50** and/or the heat recovery system **56**. The exemplary illustrated systems are relatively simple and many additional features could be added as are known in the art or yet developed. These, for example, include the use of economized vapor compression systems or ejector cycles in the vapor compression system.

(23) Further variations involve using engine exhaust heat in addition to or as an alternative to engine coolant for transferring heat to the heat recovery system in the heat exchanger **110**. These variations can increase the amount of heat and the temperature at heat exchanger **110**, leading to increased capacity and efficiency of the heat recovery loop.

(24) Yet further variations involve adding a feature such as a de-superheater linking the two loops in addition to the subcooler **62**. An exemplary de-superheater is a refrigerant-refrigerant heat exchanger having a leg along the vapor compression system upstream of the heat exchanger **60** and a leg along the heat recovery flowpath downstream of the subcooler. This may decrease the compressor work and increase the system efficiency.

(25) Yet further variations involve placing the heat exchangers **60** and **112** in parallel (e.g., FIG. 4) along air flowpaths rather than in series while still maintaining them as part of a single unit. In general, parallel flow increases thermodynamic efficiency because both heat exchangers are exposed to ambient inlet air (rather than one being exposed to air heated in the other). However, this may require increased space and potentially cost. In one group of examples, a single fan may pass flow across both in parallel, thus eliminating a fan and its cost. In other implementations, there may be separate fans **70-1**, **70-2**, which could provide better control separate flows **520-1**, **520-2**.

(26) Yet further variations involve effectively eliminating the subcooler **62** and replacing it with an



evaporator **63** in the heat recovery system (e.g., FIG. 5). The evaporator (heat rejection heat exchanger) may be placed in series with the heat exchanger **60** instead of placing the heat rejection heat exchanger **112** in series. In such implementations, the evaporator and the heat exchanger **60** may be the two sections of the integrated single unit. This would involve adding one net fan over the FIG. 1 embodiment with one fan **70-2** driving airflow **520-2** only across the heat exchanger **112** and another fan **70-1** driving airflow **520-1** in series across the added heat recovery system evaporator and the heat exchanger **60**. An exemplary airflow direction places the added evaporator upstream to precool the air (which then flows across the heat exchanger **60**) and thereby effectively provide interloop heat transfer from the vapor compression system to the heat recovery system.

(27) Other possible integrations involve yet further integrating heat exchangers and/or combining air flowpaths. One example modifies the FIG. 5 configuration by eliminating the fan **70-2** and integrating the heat exchanger **112** with heat exchangers **60** and **63** as sections of the integrated single unit (e.g., **112** could be immediately downstream of **60** along the flowpath **520-1** of FIG. 5).

(28) Further variations may involve stationary or fixed site installations. FIG. 6 shows an exemplary fixed site installation or system **320** embodied as a combined cooling, heating, and power (CCHP) system. Generally, like components to the system **20** are shown with like numerals even though the scale or form may ultimately be different in any particular implementation. The CCHP system **320** features refrigerant-water (generically including other liquids such as brine, glycols, other solutions, and the like)) heat exchangers in place of refrigerant-air heat exchangers. In addition to powering the compressor motor **46**, the generator **32** powers additional electric loads **322** of a building (e.g., beyond the loads of the system itself and, more broadly beyond heating ventilation and air conditioning (HVAC) loads). The vapor compression system evaporator **366** (legs **366-1** and **366-2** in heat exchange relation) cools a water flow **572** along a water flowpath (e.g., including along leg **366-2** and pumped via a pump **372** along a water line/conduit to/from cooling loads **371** such as air handling units, building cold water and the like). Condenser sections **360** and **412** along the two loops may be respective sections of a single refrigerant-water heater exchanger **600** (FIG. 6A). One example is a shell and tube heat exchanger. Another example is a brazed plate heat exchanger. Yet another example is a tube-in-tube heat exchanger. FIG. 6 shows a water flow **570** along a water flowpath (e.g., pumped via a pump **369** along a water line/conduit) from/to a cooling tower **650** through the unit **600**. The unit **600** has a water inlet **602** and a water outlet **604**. The exemplary unit **600** is a shell and tube heat exchanger having a shell with a cylindrical wall **610** and end caps **612** and **614**. Plates **616** and **618** define plena at respective end and are spanned by tube groups **620** and **622**. The first end plenum formed by the plate **616** and end cap **612** is subdivided by a plate **624** into respective inlet and outlet plena **630** and **632**. The second end plenum **634** defines a turn in the flowpath with the flowpath proceeding sequentially through the inlet **602** into the plenum **630**, through the tubes **620** to the plenum **634**, and then back through the tubes **622** to the plenum **632** and the outlet **604**.

(29) To cool the fluid of the two loops, the interior of the shell is further subdivided by a dividing plate **640** into chamber **642** and **644** which effectively form the condensers **360** and **412**, respectively. The chamber **642** has an inlet **646** and an outlet **648**. The chamber **644** has inlet **647** and an outlet **649**. Refrigerant from the compressor passes into the inlet **646** where it rejects heat to the sections of the tubes **622** and **620** within the chamber **642** before passing out the outlet **648** to go to the subcooler. Similarly, heat recovery fluid from the ejector passes through the inlet **647** and rejects heat to the water flowing in sections of the tubes **622** and **620** within the chamber **644** before exiting the outlet **649**.

(30) In yet further variations, instead of being an engine, the heat source **30** may be a fuel cell.

(31) Other variations may be along the lines noted above for the refrigerated transport system. For example, FIG. 7 shows a CCHP system **720** wherein the refrigerant-refrigerant subcooler is replaced with a refrigerant-water precooler **710** having a leg **710-2** along the cooling water flowpath rejecting heat to a leg **710-1** (acting as an evaporator) along the flowpath **58** upstream of

the ejector suction port. This further cools the cooling water from the tower to further cool the refrigerant and heat recovery fluid in the unit **600** (in a fashion similar to the unillustrated modification of FIG. 5 integrating the condenser **112** into the unit with **60** and **63**).

(32) In a variation on the FIG. 7 system, rather than having a single integrated unit **600**, there are physically separate WCC for the two loops, each with its own water supply and return from the tower. The precooler (leg **710-1** forming heat recovery loop evaporator) cools the water supply (along leg **710-2**) for the vapor compression system's WCC. Thus, the precooler (leg **710-2**) and the vapor compression system's WCC are in series along the heat transfer fluid flowpath (the cooling water flowpath for the vapor compression system's WCC).

(33) Thus, it is seen that one or more of several further shared features may exist between the loops of the various systems. A first area involves the physical integration of the heat exchangers of the vapor compression loop and heat recovery loop. Another area which may exist simultaneously with or alternatively to the first is the shared heat transfer fluid (air or water (generically including other liquids such as brine, glycols, other solutions, and the like)) whether in series or otherwise (e.g., the split series configuration of FIG. 6).

(34) Yet further variations on the foregoing systems involve the particular working fluids of the vapor compression system and heat recovery system. As mentioned above, they may be the same or different. In one possible area of differences, the refrigerant of the vapor compression system may be relatively non-flammable (and/or less toxic, and/or less harmful to the contents of the refrigerated compartment) when compared to the heat recovery fluid. For example, appropriate isolation allows only potential exposure/venting of the refrigerant into the box interior. The heat recovery fluid may be isolated from the box so as to not be able to accumulate in an enclosed space if there is a leak. Thus, one exemplary combination is a carbon dioxide-based refrigerant (e.g., R744) and a hydrocarbon heat transfer fluid (e.g., R290). An alternative pair is R452A/R245fa.

(35) The physical configuration of the system is merely illustrative and may schematically represent any of a number of existing or yet-developed constructions. The inventive methods described below may also be applicable to other constructions.

(36) The system may include various additional components including, receivers, filters, dryers, valves, sensors, and the like.

(37) One or more embodiments of the present invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the invention. For example, when applied in the reengineering of baseline system configuration or the remanufacturing of a baseline system, details of the baseline may influence or dictate details of the particular implementation. Accordingly, other embodiments are within the scope of the following claims.

## Claims

1. A refrigerated transport system comprising: a heat source; a vapor compression system comprising: a compressor for compressing a flow of a refrigerant; a first heat exchanger along a refrigerant flowpath of the refrigerant; and a second heat exchanger along the refrigerant flowpath of the refrigerant; a refrigerated compartment in thermal communication with the vapor compression system second heat exchanger; and a heat recovery system having: a first heat exchanger for transferring heat from the heat source to a heat recovery fluid along a heat recovery flowpath; and a second heat exchanger along the heat recovery flowpath, wherein: the heat recovery system second heat exchanger and the vapor compression system first heat exchanger are respective portions of a shared heat exchanger for rejecting heat to a heat transfer fluid; a separate subcooler has respective legs along the vapor compression flowpath and the heat recovery flowpath; and the heat recovery system first heat exchanger has respective legs along a coolant flowpath of the heat source and the heat recovery flowpath.

2. The refrigerated transport system of claim 1, wherein: the separate subcooler respective legs along the vapor compression flowpath and the heat recovery flowpath are in heat exchange relation with each other; and the heat recovery system second heat exchanger is a condenser.
  3. The refrigerated transport system of claim 1, wherein: the refrigerated transport system has a box forming the refrigerated compartment.
  4. The refrigerated transport system of claim 1, wherein the heat recovery system further comprises: an ejector having a motive flow inlet, a secondary flow inlet, and an outlet; a pump; and a loop of the heat recovery flowpath passing through the pump to the heat recovery system first heat exchanger, through the motive flow inlet and from the outlet back to the pump via the heat recovery system second heat exchanger.
  5. The refrigerated transport system of claim 1 further comprising: a radiator; and a valve along the coolant flowpath for apportioning a total coolant flow between the radiator and the heat recovery system first heat exchanger.
  6. The refrigerated transport system of claim 1, wherein: the heat recovery system second heat exchanger and the vapor compression system first heat exchanger are in common along a heat transfer fluid flowpath.
  7. The refrigerated transport system of claim 1 wherein the refrigerated compartment is within a truck or a trailer.
  8. The refrigerated transport system of claim 1 wherein said shared heat exchanger and is a tube/fin package.
  9. The refrigerated transport system of claim 1, wherein: the refrigerant and the heat recovery fluid are different from each other.
  10. The refrigerated transport system of claim 9, wherein the refrigerant is less flammable and/or less toxic than the heat recovery fluid.
  11. A method for operating the refrigerated transport system of claim 1, the method comprising, in a first mode: running the compressor to compress the flow of refrigerant and drive the refrigerant along the refrigerant flowpath; transferring the heat from the heat source to the heat recovery fluid along the heat recovery flowpath; and rejecting heat from the refrigerant in the vapor compression system first heat exchanger.
  12. The method of claim 11, further comprising, in the first mode: driving air as said heat transfer fluid wherein along a heat transfer fluid flowpath the vapor compression system first heat exchanger is upstream of the heat recovery system second heat exchanger.
  13. The method of claim 11, wherein, in the first mode: heat is rejected by the heat recovery fluid in the heat recovery system second heat exchanger.
  14. The method of claim 11, wherein: the method further comprises, in the first mode: transferring heat from the refrigerant in the vapor compression system to the heat recovery fluid in the heat recovery system in the subcooler via a refrigerant-refrigerant heat exchange without airflow.
  15. The method of claim 11, wherein the refrigerated transport system further comprises a radiator and the method further comprises, in the first mode: using a valve to apportion coolant between the heat recovery system first heat exchanger and the radiator.
  16. The method of claim 11, wherein: the refrigerated compartment is within a truck or a trailer.
  17. The method of claim 11, wherein: the heat transfer fluid is air; and the system has a fan for driving the air.
  18. The method of claim 11, wherein: the vapor compression system second heat exchanger is an evaporator in thermal communication with a load to cool the load in a cooling mode.
  19. The method of claim 11, wherein: the refrigerated transport system has a box forming the refrigerated compartment.
-