

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391143
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Shimizu; Tatsuya et al.

Vehicle

Abstract

A vehicle includes a power storage device, a gas supply unit, a vehicle side refrigerant connector, a vehicle side electric connector, and a gas supply pipe. The power storage device includes an electric connector, a refrigerant connector, and a ventilation path. A first connection portion where the vehicle side refrigerant connector and the refrigerant connector are connected to each other includes a first closed space and a second connection portion where the vehicle side electric connector and the electric connector are connected to each other includes a second closed space. The gas supply pipe is provided to supply gas to at least one of the first closed space and the second closed space. The ventilation path is provided to communicate with the gas supply pipe through at least one closed space and the ventilation path is provided with a flow detector.

Inventors: Shimizu; Tatsuya (Okazaki, JP), Shimazu; Katsuya (Toyota, JP), Kagami; Ayaka (Inazawa, JP), Kawashima; Mutsumi (Nisshin, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Family ID: 1000008764544

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Appl. No.: 18/512917

Filed: November 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240181922 A1	Jun. 06, 2024

Foreign Application Priority Data

JP	2022-194394	Dec. 05, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: **B60L53/80** (20190101); **B60L53/30** (20190101); **B60L58/18** (20190101); **B60L58/26** (20190101); **H01M10/42** (20060101); **H01M10/48** (20060101); **H01M10/613** (20140101); **H01M10/625** (20140101); **H01M10/6568** (20140101); **H01M50/249** (20210101); **H01M50/30** (20210101)

U.S. Cl.:

CPC **B60L53/80** (20190201); **B60L53/30** (20190201); **B60L58/18** (20190201); **B60L58/26** (20190201); **H01M10/4285** (20130101); **H01M10/48** (20130101); **H01M10/613** (20150401); **H01M10/625** (20150401); **H01M10/6568** (20150401); **H01M50/249** (20210101); **H01M50/30** (20210101); **B60L2250/16** (20130101); **H01M2220/20** (20130101)

Field of Classification Search

CPC: B60L (53/80); B60L (58/18); B60L (58/26); B60L (53/30); H01M (10/613); H01M (10/625); H01M (10/6568); H01M (50/249)

References Cited

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2020-058150	12/2019	JP	N/A

Primary Examiner: Refai; Ramsey

Attorney, Agent or Firm: Dinsmore & Shohl LLP

Background/Summary

(1) This nonprovisional application is based on Japanese Patent Application No. 2022-194394 filed on Dec. 5, 2022 with the Japan Patent Office, the entire contents of which are hereby incorporated by reference.

BACKGROUND

Field

(2) The present disclosure relates to a vehicle.

Description of the Background Art

(3) Conventionally, Japanese Patent Application Laid-Open No. 2020-58150 discloses a vehicle-mounted battery determination system in which it is possible to determine whether a battery mounted on a vehicle is a correct type of mounting battery.

(4) Specifically, a first control device having a first storage section for storing battery information is provided on the battery pack side. On the vehicle side, a second control device which is communicably provided with the first control device and which stores information of a battery to be mounted on the vehicle is provided.

(5) When the battery pack is mounted on the vehicle, the first control device and the second control

device determine whether the battery is a battery for mounting by comparing the information of the battery stored in the first storage unit with the information of the battery for mounting stored in the second storage unit.

SUMMARY

(6) In order to stabilize the vehicle's navigation, a battery pack (power storage device) mounted on the vehicle is replaced with another battery pack. As another battery pack, not only a battery pack in a new state but also a battery pack in which a battery pack once used is recharged may be used.

(7) In a battery pack mounted on a vehicle, a cooling device in which a refrigerant such as a coolant flows may be used in order to cool a battery disposed in a housing case. In this case, in order to connect a cooling circuit provided on the vehicle side to the cooling device, a vehicle side refrigerant connector is provided on the vehicle body side. A refrigerant connector connected to the vehicle side refrigerant connector is provided on the battery device side.

(8) Further, in order to connect the electric system on the vehicle side and the electric system on the battery side, a vehicle side electric connector is provided on the vehicle body side. An electric connector connected to the vehicle side electric connector is provided on the battery device side.

(9) When such a connector on the vehicle side and a connector on the battery device side are connected to each other, a connecting portion between the connector on the vehicle side and the connector on the battery device side is air-tightly or liquid-tightly sealed using a sealing member such as a packing.

(10) When the battery pack is replaced, a battery pack which is used once and charged again may be newly attached. In the case where the battery pack in which the sealing member has degraded due to vibration caused by traveling of the vehicle or long-term use is charged and attached to the vehicle, there is a concern that the connection between the connector on the vehicle side and the connector on the battery device side is not good.

(11) It is an object of the present disclosure to provide a vehicle capable of detecting a connection state between a connector on a vehicle side and a connector on a battery device side.

(12) A vehicle based on the present disclosure is a vehicle to which a power storage device is attached replaceably. The vehicle includes the power storage device, an auxiliary battery, a gas supply unit to which power is supplied from the auxiliary battery, a refrigerant circuit through which refrigerant flows, the refrigerant circuit including a vehicle side refrigerant connector provided as being connectable to the power storage device, a vehicle side electric connector provided as being connectable to the power storage device, and a gas supply pipe to which gas can flow from the gas supply unit, the gas supply pipe being connected to the gas supply unit.

(13) The power storage device includes an electric connector provided as being connectable to the vehicle side electric connector, a refrigerant connector provided as being connectable to the vehicle side refrigerant connector, and a ventilation path provided to communicate to the gas supply pipe. The vehicle side refrigerant connector and the refrigerant connector are connected to form a first connection portion that contains a first closed space. The vehicle side electric connector and the electric connector are connected to form a second connection portion that contains a second closed space. The gas supply pipe is provided to supply the gas into at least one hermetically closed space of the first closed space and the second closed space. The ventilation path is provided to communicate with the gas supply pipe through the at least one hermetically closed space. The ventilation path is provided with a flow detector that detects a flow state of the gas that flows through the ventilation path.

(14) According to the above configuration, the flow detector can detect the flow state of the gas that flows through the ventilation path that communicates with at least one of the first closed space and the second closed space formed by connection of the vehicle side connector and the power storage device side connector to each other. As a result, the connection state between the vehicle side connector and the power storage device side connector can be detected.

(15) The vehicle based on the present disclosure may further include a controller that controls an

operation of the gas supply unit with power from the auxiliary battery and a connection detector that detects connection of the vehicle side electric connector and the electric connector to each other. The power storage device may include a power storage module and a refrigerant flow path through which the refrigerant for cooling of the power storage module flows. The gas supply pipe may include a first supply pipe through which the gas can be supplied to the first closed space. The ventilation path may include a first path formed by the refrigerant flow path. In this case, when the connection detector detects connection of the electric connector and the vehicle side electric connector to each other, the controller may drive the gas supply unit to introduce the gas into the first closed space. The flow detector may include a first detector that detects a flow state of the gas that flows through the first path.

(16) According to the above configuration, when the power storage device mounted on the vehicle side is replaced with another power storage device, the connection state between the refrigerant connector on the power storage device side and the vehicle side refrigerant connector can be detected at the timing when the connection between the electric connector of another power storage device and the vehicle side electric connector is detected.

(17) In the vehicle based on the present disclosure, the first path may include a downstream refrigerant connection portion in which a first connector and a second connector are connected to each other, on a downstream side of the first connection portion in a flow direction of the refrigerant. The downstream refrigerant connection portion may contain a third closed space. The flow detector may include a first downstream detector provided in a portion of the first path located downstream of the third closed space, the first downstream detector detecting the flow state of the gas that flows through the first path.

(18) According to the above configuration, the connection state of the downstream refrigerant connection portion in which the first connector and the second connector are connected to each other on the downstream side of the first connection portion in the first path formed by the refrigerant flow path provided in the power storage device can also be detected.

(19) The vehicle based on the present disclosure may further include a controller that controls an operation of the gas supply unit with power from the auxiliary battery and a connection detector that detects connection of the vehicle side electric connector and the electric connector to each other. The power storage device may include a power storage module and an electric circuit that connects the power storage module and the electric connector to each other. The gas supply pipe may include a second supply pipe through which the gas can be supplied to the second closed space. The ventilation path may include a second path provided along the electric circuit. When the connection detector detects connection of the electric connector and the vehicle side electric connector to each other, the controller may drive the gas supply unit to introduce the gas into the second closed space. The flow detector may include a second detector that detects a flow state of the gas that flows through the second path.

(20) According to the above configuration, when the power storage device mounted on the vehicle side is replaced with another power storage device, the connection state between the electric connector on the power storage device side and the vehicle side electric connector can be detected at the timing when the connection between the electric connector of another power storage device and the vehicle side electric connector is detected.

(21) In the vehicle based on the present disclosure, the second path may include a downstream connector connection portion where a third connector and a fourth connector are connected to each other, on a side of the power storage module relative to the second connection portion. The downstream connector connection portion may contain a fourth closed space. The flow detector may include a second downstream detector provided in a portion of the second path located on a side of the power storage module relative to the fourth closed space, the second downstream detector detecting the flow state of the gas that flows through the second path.

(22) According to the above configuration, in the second path, the connection state of the

downstream connector connection portion where the third connector and the fourth connector are connected to each other on the side of the power storage module relative to the second connection portion can be detected.

(23) The vehicle based on the present disclosure may further include a display unit. A result of detection by the flow detector may be shown on the display unit.

(24) According to the above configuration, a user can know through the display unit, a result of detection by the flow detector.

(25) In the vehicle based on the present disclosure, an inspected power storage device inspected by an inspection device may be attached. The inspected power storage device is a power storage device in which the flow state of the gas that flows through the ventilation path is inspected in advance by the inspection device. The inspection device is provided as being connectable to the refrigerant connector and the electric connector, and the inspection device can supply gas to the ventilation path through at least one of closed spaces formed in respective connection portions while the inspection device is connected to the refrigerant connector and the electric connector.

(26) According to the above configuration, since the power storage device inspected in advance is attached to the vehicle, the connection state between the connector on the vehicle side and the connector on the power storage device side can more reliably be normal.

(27) In the vehicle based on the present disclosure, in attachment of the power storage device, a first mode of replacement of a power storage device inspected by an inspection device and a second mode of replacement of a power storage device not inspected by the inspection device may selectably be provided. The inspected power storage device is a power storage device in which the flow state of the gas that flows through the ventilation path is inspected in advance by the inspection device. The inspection device is provided as being connectable to the refrigerant connector and the electric connector and the inspection device can supply gas to the ventilation path through at least one of closed spaces formed in respective connection portions while the inspection device is connected to the refrigerant connector and the electric connector.

(28) According to the above configuration, a user can make selection between replacement of an inspected power storage device and replacement of an uninspected power storage device by selecting either the first mode or the second mode.

(29) The foregoing and other objects, features, aspects and advantages of the present disclosure will become more apparent from the following detailed description of the present disclosure when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram showing a configuration of a battery replacement apparatus according to an embodiment.
- (2) FIG. 2 is a diagram showing a configuration of a vehicle according to the embodiment.
- (3) FIG. 3 is a schematic cross-sectional view showing a first connection portion in which a vehicle side refrigerant connector and a battery side refrigerant connector according to the embodiment are connected.
- (4) FIG. 4 is a schematic cross-sectional view showing a second connection portion in which a vehicle side electric connector and a battery side electric connector according to the embodiment are connected.
- (5) FIG. 5 is a flowchart showing a battery replacement step of the battery replacement apparatus according to the embodiment.

DESCRIPTION OF THE EMBODIMENTS

- (6) Hereinafter, embodiments of the present disclosure will be described in detail with reference to

the drawings. In the following embodiments, the same or common portions are denoted by the same reference numerals, and description thereof will not be repeated.

(7) FIG. 1 is a diagram showing a configuration of a battery replacement apparatus according to a first embodiment. As shown in FIG. 1, a battery replacement apparatus **100** is an apparatus for replacing a battery (first power storage device) **400** attached to a vehicle **200** with another battery (second power storage device) **101**. The other battery **101** may be a new battery or a battery replaced from the vehicle **200** at another timing may be charged again.

(8) The battery replacement apparatus **100** includes a battery replacement station **100a** in which battery replacement is performed, and a storage box **100b** in which other batteries **101** are stored. The storage box **100b** is provided in parallel with the battery replacement station **100a**. The battery replacement apparatus **100** has a sub-floor area S.

(9) The battery replacement apparatus **100** includes a battery replacement mechanism **33**, a transport unit **36**, and an inspection device **500**. The battery replacement mechanism **33** is a mechanism for detaching the battery **400** from the vehicle **200** and attaching the other battery **101** to the vehicle **200**. The battery replacement mechanism **33** is provided in the storage box **100b** and the underfloor area S. The battery replacement mechanism **33** includes a battery mounting table **34** and an elevator **35**.

(10) The battery mounting table **34** moves the batteries **400** and **101** between the transport unit **36** and the vehicle **200**. The elevator **35** raises and lowers the vehicle **200** between a stop position where the vehicle stops at the battery replacement station **100a** and a predetermined height position. The transport unit **36** moves the batteries **101** and **400** between the temporary place **90** and the battery mounting table **34**. The transport unit **36** may be of a belt conveyor type, for example.

(11) The transport unit **36** conveys the battery **400**, which is detached from the vehicle **200** and mounted on the battery mounting table **34**, to the temporary place **90**. Specifically, the battery **400** is transferred from the battery mounting table **34** to the transport unit **36** in a state where the battery mounting table **34** on which the removed battery **400** is mounted is lowered to the same height position (position in the Z direction) as the transport unit **36**. The transfer of the battery **400** is performed by rotating a roller portion (not shown) of the battery mounting table **34**.

(12) Further, the transport unit **36** moves the other batteries **101** transported from the storage box **100b** to the temporary place **90** to the Y2 side and places the other batteries **101** on the battery mounting table **34**. At this time, the roller portion of the battery mounting table **34** rotates in a direction opposite to the above, whereby the battery **101** is transferred to the Y2 side on the battery mounting table **34**.

(13) The transfer of the batteries **101** and **400** between the temporary place **90** and the storage box **100b** is performed by another transfer device (not shown).

(14) The inspection device **500** is provided so as to be able to detect a state of a refrigerant connector **413** (see FIG. 2) and an electric connector **401** (see FIG. 2) to be described later of the battery **400** removed from the vehicle **200**. Specifically, the inspection device **500** includes an inspection refrigerant connector **513**, an inspection electric connector **501**, and an inspection gas supply unit **530**.

(15) The inspection refrigerant connector **513** is connected to the refrigerant connector **413**. The inspection electric connector **501** is connected to the electric connector **401**. The inspection gas supply unit **530** is provided so as to be able to supply a gas to a ventilation path **60** (see FIG. 2) described later through at least one of closed spaces formed in each of a connection portion between the inspection refrigerant connector **513** and the refrigerant connector **413** and a connection portion between the inspection electric connector **501** and the electric connector **401**.

(16) The inspection device **500** supplies a gas to the ventilation path **60**. The ventilation path **60** is provided with a flow detector **50** as described later. The state of the refrigerant connector **413** and the state of the electric connector **401** can be detected by detecting the flow state of the gas flowing

through the ventilation path **60** by the flow detector **50**. More specifically, it is possible to detect whether or not sealing members **418** and **408** (see FIGS. **3** and **4**) to be described later provided in the refrigerant connector **413** and the electric connector **401** are deteriorated. The detection result of the inspection device **500** is stored in a memory **12** described later. In the present embodiment, the inspection device **500** is provided to be able to inspect the battery **400** disposed in the temporary place **90**, but the inspection device **500** may be provided to be able to inspect the battery **101** stored in the storage box **100b**.

(17) The battery replacement apparatus **100** includes a control device **10** and a drive device **30**. The control device **10** includes a processor **11**, a memory **12**, and a communication unit **13**.

(18) The memory **12** stores, in addition to a program executed by the processor **11**, information (e.g., map, formula, and various parameters) used by the program. The processor **11** controls the operation of the drive device **30**. The drive device **30** includes the battery replacement mechanism **33**, the transport unit **36**, and the inspection device **500**.

(19) The communication unit **13** includes various communication I/Fs. The processor **11** controls the communication unit **13**. The communication unit **13** communicates with a DCM or the like of the vehicle **200**. The communication unit **13** and the vehicle **200** can perform bidirectional communication. The communication unit **13** may communicate with a mobile terminal or the like possessed by the user of the vehicle **200**. The communication unit **13** is an example of a vehicle information acquisition unit that acquires information from a vehicle.

(20) When the battery **400** is replaced, in a state where the vehicle **200** is stopped in the battery replacement station **100a**, the user performs an operation of instructing the start of the battery replacement operation in a navigation system (not shown) of the vehicle **200**. The communication unit **13** receives an instruction signal for starting a battery replacement operation from the vehicle **200**. The processor **11** starts the control of the battery replacement operation based on the reception of the instruction signal by the communication unit **13**.

(21) The vehicle **200** may be operated by the user operating the navigation system outside the battery replacement station **100a** to automatically stop at a predetermined position inside the battery replacement station **100a**. Further, the vehicle may be stopped at a predetermined position by the user driving the vehicle. Note that an operation unit for operating the navigation system is displayed on a display unit **280** of the vehicle.

(22) The vehicle **200** stops in the battery replacement station **100a** such that the front-rear direction is the X direction and the left-right direction is the Y direction.

(23) FIG. **2** is a diagram showing a configuration of a vehicle according to the embodiment. A vehicle **200** according to the embodiment will be described with reference to FIG. **2**.

(24) As shown in FIG. **2**, the vehicle **200** includes a PCU (Power Control Unit) **203**, a MG (Motor Generator) **205**, an auxiliary battery **206**, a DC/DC converter **207**, a vehicle side electric connector **201**, a vehicle side refrigerant connector **251**, a gas supply unit **300**, a gas supply pipe **310**, a refrigerant circuit **250**, and a connection detector **209**.

(25) When the battery **400** is replaced, the ignition power supply (not shown) is turned off in a state where the vehicle **200** is stopped in the battery replacement station **100a**, and the connection between the battery **400** and the PCU **203** is turned off. Thereby, the battery **400** is electrically disconnected from the PCU **203** and the MG **205**.

(26) In this state, an operation for instructing the start of the battery replacement operation is performed on the vehicle **200**, whereby the battery replacement apparatus **100** starts control of the battery replacement operation. Further, the lock between the vehicle side connector and the connector of the battery **400** is released based on the operation.

(27) After the ignition power supply is turned off, the power of the auxiliary battery **206** is supplied to the accessory such as the MG **205**, the DCM, and the gas supply unit **300** via the DC/DC converter **207** and the PCU **203**.

(28) The auxiliary battery **206** can supply electric power to the gas supply unit **300** even after the

ignition power supply is turned off. The gas supply unit **300** is, for example, a compressor.

(29) The gas supply pipe **310** is connected to the gas supply unit **300**. The gas supply pipe **310** is provided so that the gas from the gas supply unit **300** can flow. The gas supply pipe **310** is provided so as to be able to supply a gas to at least one of a first closed space **S1** and a second closed space **S2** described later. In the present embodiment, the gas supply pipe **310** is provided so as to be able to supply a gas to both the first closed space **S1** and the second closed space **S2**.

(30) The gas supply pipe **310** includes a first supply pipe **311** and a second supply pipe **312**. The first supply pipe **311** is provided so as to be able to supply a gas to the first closed space **S1**. The first supply pipe **311** is provided to connect the gas supply unit **300** and the first closed space **S1**.

(31) The second supply pipe **312** is provided so as to be able to supply a gas to the second closed space **S2**. The second supply pipe **312** is provided to connect the gas supply unit **300** and the second closed space **S2**.

(32) The refrigerant circuit **250** is provided so that the refrigerant flows. As the refrigerant, for example, a liquid such as water can be used. The refrigerant circuit **250** is provided with, for example, a storage tank for storing refrigerant, a pump, and the like. The pump can circulate the refrigerant in the refrigerant circuit **250**. The refrigerant circuit **250** is connected to a heat exchanger or the like.

(33) The connection detector **209** detects that the vehicle side electric connector **201** and the battery **400** side electric connector **401** are connected to each other. Specifically, the connection detector **209** detects a current flowing from the auxiliary battery **206** toward the battery **400** by connecting the vehicle side electric connector **201** and the electric connector **401** after the ignition power supply is turned off.

(34) The battery **400** includes a housing case **405**, a junction box **410**, a power storage module **420**, a cooling device **80**, an electric connector **401**, a first connector **81**, a second connector **82**, a third connector **411**, a fourth connector **412**, a fifth connector **421**, a sixth connector **422**, a flow detector **50**, and a ventilation path **60**.

(35) The housing case **405** has a substantially box shape. The housing case **405** houses therein the junction box **410**, the power storage module **420**, and the cooling device **80**. An electric connector **401** and a refrigerant connector **413** are provided on an outer surface of the housing case **405** so as to project to the outside.

(36) The power storage module **420** includes a plurality of power storage stacks in which power storage cells are arranged in a predetermined direction.

(37) The power storage cell is, for example, a secondary battery such as a nickel hydride battery or a lithium ion battery. The power storage cell may use either a liquid electrolyte or a solid electrolyte. The power storage cell may be a unit capacitor configured to be capable of storing electric power.

(38) The junction box **410** is disposed between the electric connector **401** and the power storage module **420**. The electric connector **401**, the junction box **410**, and the power storage module **420** are connected by an electric circuit **430**. The junction box **410** is provided with, for example, an electronic device for controlling the power storage module **420**.

(39) The cooling device **80** is provided so as to be able to cool the power storage module **420**. The cooling device **80** is disposed below the power storage module **420**, for example. The cooling device **80** is in thermal contact with the power storage module **420**. The cooling device **80** is connected to the refrigerant connector **413** through the refrigerant flow path **61**. The cooling device **80** is provided so that the refrigerant flows.

(40) The refrigerant connector **413** is connected to the vehicle side refrigerant connector **251**. The refrigerant connector **413** is detachably connected to the vehicle side refrigerant connector **251**. By connecting the refrigerant connector **413** to the vehicle side refrigerant connector **251**, the first connection portion **C1** having the first closed space **S1** therein is formed.

(41) By connecting the vehicle side refrigerant connector **251** and the refrigerant connector **413**, the

refrigerant for cooling the power storage module **420** flows through the refrigerant flow path **61**. The refrigerant flow path **61** includes a downstream refrigerant connection portion **C3** in which the first connector **81** and the second connector **82** are connected to the downstream side of the first connection portion **C1** in the flow direction of the refrigerant.

(42) The second connector **82** is provided in the cooling device **80**. The first connector **81** is provided at a downstream end of the refrigerant flow path **61** at a portion connecting the refrigerant connector **413** and the second connector **82**. The downstream refrigerant connection portion **C3** has a third closed space **S3** inside.

(43) The electric connector **401** is connected to the vehicle side electric connector **201**. The electric connector **401** is detachably connected to the vehicle side electric connector **201**. By connecting the electric connector **401** to the vehicle side electric connector **201**, the second connection portion **C2** having the second closed space **S2** is formed.

(44) The junction box **410** is provided with a fourth connector **412**. The electric circuit **430** includes a plurality of electric wires. The electric circuit **430** includes electrical wires connecting the electric connector **401** and the junction box **410**. An electric connector **401** is provided at one end of the electrical wiring, and a third connector **411** is provided at the other end of the electrical wiring.

(45) The electric circuit **430** includes a first downstream connector connection portion **C4** in which the third connector **411** and the fourth connector **412** are connected. The first downstream connector connection portion **C4** has a fourth closed space **S4** inside.

(46) The power storage module **420** is provided with a sixth connector **422**. The electric circuit **430** includes an electric wiring that connects the junction box **410** and the power storage module **420**. One end of the electrical wiring is connected to the junction box **410**. A fifth connector **421** is provided at the other end of the electrical wiring.

(47) The electric circuit **430** includes a second downstream connector connection portion **C5** in which the fifth connector **421** and the sixth connector **422** are connected. The second downstream connector connection portion **C5** has a fifth closed space **S5** inside.

(48) The ventilation path **60** is provided so as to be able to communicate with the gas supply pipe **310**. The ventilation path **60** is provided so as to be able to communicate with the gas supply pipe **310** via at least one closed space of the first closed space **S1** and the second closed space **S2**. Specifically, the ventilation path **60** includes a first path communicating with the first closed space **S1** and a second path **62** communicating with the second closed space **S2**.

(49) The first path is formed by a refrigerant flow path **61**. The first path is provided so as to pass through the third closed space **S3**. The second path **62** is provided along the electric circuit **430**. The second path **62** is provided so as to pass through the fourth closed space **S4** and the fifth closed space **S5**.

(50) The flow detector **50** is provided in the ventilation path **60**, and detects the flow state of the gas flowing through the ventilation path **60**. The flow detector **50** is provided, for example, so as to be able to detect the pressure of the gas. As the flow detector **50**, for example, a check valve can be adopted.

(51) The flow detector **50** includes a first detector **51**, a second detector **52**, a first downstream detector **53**, a second downstream detector **54**, and a third downstream detector **55**.

(52) The first detector **51** is provided in the first path (the refrigerant flow path **61**). More specifically, the first detector **51** is provided on the downstream side of the first closed space **S1** and on the upstream side of the third closed space **S3** in the refrigerant flow path **61**. The first detector **51** detects the flow state of the gas flowing in the first path on the downstream side of the first closed space **S1** and on the upstream side of the third closed space **S3**.

(53) By detecting the flow state of the gas by the first detector **51**, it is possible to confirm whether or not the connection state between the vehicle side refrigerant connector **251** and the refrigerant connector **413** is normal.

(54) The first downstream detector **53** is provided in the first path. More specifically, the first

downstream detector **53** is provided on the downstream side of the third closed space **S3** in the refrigerant flow path **61**. The first downstream detector **53** detects the flow state of the gas flowing in the first path on the downstream side of the third closed space **S3**.

(55) By detecting the flow state of the gas by the first downstream detector **53**, it is possible to confirm whether or not the connection state between the first connector **81** and the second connector **82** is normal.

(56) The second detector **52** is provided in the second path **62**. More specifically, the second detector **52** is disposed on the downstream side of the second closed space **S2** and on the upstream side of the fourth closed space **S4** in the second path **62**. The second detector **52** detects the flow state of the gas flowing through the second path **62** on the downstream side of the second closed space **S2** and on the upstream side of the fourth closed space **S4**.

(57) By detecting the flow state of the gas by the second detector **52**, it is possible to confirm whether or not the connection state between the vehicle side electric connector **201** and the electric connector **401** is normal.

(58) The second downstream detector **54** is provided in the second path **62**. More specifically, the second downstream detector **54** is provided on the downstream side of the fourth closed space **S4** and on the upstream side of the fifth closed space **S5** in the second path **62**. The second downstream detector **54** detects the flow state of the gas flowing through the second path **62** on the downstream side of the fourth closed space **S4** and on the upstream side of the fifth closed space **S5**.

(59) By detecting the flow state of the gas by the second downstream detector **54**, it is possible to confirm whether or not the connection state between the third connector **411** and the fourth connector **412** is normal.

(60) The third downstream detector **55** is provided in the second path **62**. More specifically, the third downstream detector **55** is provided on the downstream side of the fifth closed space **S5** in the second path **62**. The second downstream detector **54** detects the flow state of the gas flowing through the second path **62** on the downstream side of the fifth closed space **S5**.

(61) By detecting the flow state of the gas by the third downstream detector **55**, it is possible to confirm whether or not the connection state between the fifth connector **421** and the sixth connector **422** is normal.

(62) The detection results of the first detector **51**, the second detector **52**, the first downstream detector **53**, the second downstream detector **54**, and the third downstream detector **55** are displayed on the display unit **280**. When it is determined that the connection state of each connector is abnormal, the detection result of the detector determined to be abnormal may be displayed on the display unit **280**.

(63) FIG. **3** is a schematic cross-sectional view showing a first connection portion in which a vehicle side refrigerant connector and a battery side refrigerant connector according to the embodiment are connected. The details of the first connection portion **C1** will be described with reference to FIG. **3**. Since the configuration of the downstream refrigerant connection portion **C3** in which the first connector **81** and the second connector **82** are connected is substantially the same as the configuration of the first connection portion **C1**, the description thereof will be omitted.

(64) As shown in FIG. **3**, the vehicle side refrigerant connector **251** has a cylindrical shape. The first supply pipe **311** is provided so as to enter the interior of the vehicle side refrigerant connector **251**.

(65) The refrigerant connector **413** includes an outer cylindrical portion **415**, an inner cylindrical portion **416**, and a sealing member **418**. The outer cylindrical portion **415** is provided so as to surround the inner cylindrical portion **416**. The sealing member **418** is disposed between the inner cylindrical portion **416** and the outer cylindrical portion **415**. The sealing member **418** is fixed to the outer peripheral surface of the inner cylindrical portion **416** in a state in which the sealing member **418** is in close contact with the outer peripheral surface of the inner cylindrical portion

416.

(66) When the vehicle side refrigerant connector **251** and the refrigerant connector **413** are connected to each other, the distal end of the vehicle side refrigerant connector **251** enters between the outer cylindrical portion **415** and the inner cylindrical portion **416**. At this time, the inner peripheral surface of the tip is in close contact with the sealing member **418**, and a first closed space **S1** is formed in a portion surrounded by the inner peripheral surface of the tip, the outer peripheral surface of the inner cylindrical portion **416**, and the sealing member **418**.

(67) When a gas is introduced from the first supply pipe **311** into the first closed space **S1** and the sealing member **418** is not deteriorated, the gas passes through the interior of the refrigerant connector **413** (more specifically, the inner cylindrical portion **416**) as indicated by an arrow **AR1**.

(68) On the other hand, when the sealing member **418** is deteriorated, the gas is discharged to the outside through the gap between the outer cylindrical portion **415** and the tip of the vehicle side refrigerant connector **251**.

(69) Therefore, the connection state between the vehicle side refrigerant connector **251** and the refrigerant connector **413** can be detected by detecting the state (for example, pressure) of the gas flowing through the refrigerant flow path **61** by the first detector **51**.

(70) FIG. **4** is a schematic cross-sectional view showing a second connection portion in which a vehicle side electric connector and a battery side electric connector according to the embodiment are connected. The details of the second connection portion **C2** will be described with reference to FIG. **4**. The configuration of the first downstream connector connection portion **C4** in which the third connector **411** and the fourth connector **412** are connected and the configuration of the second downstream connector connection portion **C5** in which the fifth connector **421** and the sixth connector **422** are connected are substantially the same as those of the second connection portion **C2**, and thus the description thereof is omitted.

(71) As shown in FIG. **4**, the vehicle side electric connector **201** includes a cylindrical portion **205** provided at a distal end thereof and a terminal portion **201T** provided inside the cylindrical portion **205**. The second supply pipe **312** is provided to enter the interior of the vehicle side electric connector **201**.

(72) The electric connector **401** includes a terminal insertion portion **401C** into which the terminal portion **201T** is inserted, and a sealing member **408**. The sealing member **408** is fixed to the outer peripheral surface of the electric connector **401** in a state of being in close contact with the outer peripheral surface of the electric connector **401**. The electric connector **401** is provided with a part of the second path **62**.

(73) When the vehicle side electric connector **201** and the electric connector **401** are connected, the terminal portion **201T** is inserted into the terminal insertion portion **401C**. At this time, the inner peripheral surface of the cylindrical portion **205** is in close contact with the sealing member **408**, and the second closed space **S2** is formed in a portion surrounded by the inner peripheral surface of the cylindrical portion **205**, the outer peripheral surface positioned at the distal end side of the electric connector **401**, and the sealing member **408**.

(74) When a gas is introduced into the second closed space **S2** from the second supply pipe **312** and the sealing member **408** is not deteriorated, the gas passes through the inside of the second path **62** as indicated by an arrow **AR2**.

(75) On the other hand, when the sealing member **408** deteriorates, the gas is discharged to the outside through the gap between the cylindrical portion **205** and the distal end side of the electric connector **401**.

(76) Therefore, the state of the connection between the vehicle side electric connector **201** and the electric connector **401** can be detected by detecting the state of the gas flowing through the second path **62** by the second detector **52**.

(77) FIG. **5** is a flowchart showing a battery replacement step of the battery replacement apparatus according to the embodiment. Referring to FIG. **5**, the flow of battery replacement according to the

embodiment will be described.

(78) [Transmission of Vehicle Information and the Like:]

(79) First, in step **S21**, the vehicle **200** transmits information about the vehicle **200** and information about the battery **400** to the communication unit **13** of the battery replacement apparatus **100**. For example, when an operation of transmitting the above information is performed in a navigation system (not shown) of the vehicle **200**, the above information is transmitted to the communication unit **13**. The vehicle **200** transmits the above information before entering the battery replacement apparatus **100**. The above information may be transmitted after the vehicle **200** enters the battery replacement apparatus **100**.

(80) [Acquisition of Vehicle Information and the Like: Battery Replacement Apparatus]

(81) Next, in step **S11**, the communication unit **13** of the battery replacement apparatus **100** acquires information about the vehicle **200** and information about the battery **400** transmitted from the vehicle **200** in step **S21** by communication. The acquired information is stored in the memory **12** (see FIG. 1).

(82) [Entry of the Vehicle into the Battery Replacement Station:]

(83) When the vehicle information and the battery information are transmitted from the vehicle **200** to the communication unit **13** in step **S21**, the vehicle **200** enters the battery replacement station **100a** by automated driving or driving by a user in step **S22**.

(84) [Vehicle Stop in the Vehicle Stop Region:]

(85) Subsequently, in step **S23**, the vehicle **200** stops at a predetermined position in the battery replacement station **100a**.

(86) [Transmission of an Instruction Signal for a Battery Replacement Operation:]

(87) Next, in step **S24**, the vehicle **200** stopped in the battery replacement station **100a** transmits an instruction signal for starting the battery replacement operation to the communication unit **13**. After transmitting the instruction signal to the communication unit **13**, the vehicle **200** turns off the SMR (System Main Relay). At this time, communication between the vehicle **200** and the communication unit **13** is maintained by power supply from the auxiliary battery **206** (see FIG. 2).

(88) When the instruction signal for starting the battery replacement operation is transmitted to the communication unit **13**, the user may select the first mode or the second mode.

(89) When the first mode is selected, it is possible to replace the inspected battery **101** and the battery **400** in which the flow state of the gas flowing in the ventilation path **60** is previously detected by the inspection device **500**. That is, in the replacement operation, there is no abnormality in the sealing members **408** and **418**, and the battery **101** that can be normally connected to the vehicle **200** can be replaced. In this case, step **S16** described later may be omitted.

(90) When the second mode is selected, the battery **101** and the battery **400** which are not inspected by the inspection device **500** can be replaced. In this case, in step **S16**, it is confirmed whether or not the connection between the replaced battery **101** and the vehicle **200** is normal.

(91) When the first mode is selected, the replacement fee may be set higher than when the second mode is selected.

(92) [Receiving an Instruction Signal for a Battery Replacement Operation:]

(93) Next, in step **S12**, the communication unit **13** receives the instruction signal transmitted from the vehicle **200** in step **S24**. In step **S12**, after receiving the instruction signal, the processor **11** may transmit an instruction message or the like for turning off the ignition power supply to the user of the vehicle **200** through the communication unit **13**.

(94) [Removal of Battery: Battery Replacement Apparatus]

(95) Next, in step **S13**, the battery **400** is detached from the vehicle body **200a** of the vehicle **200**.

(96) Specifically, the elevator **35** lifts the vehicle **200** to a predetermined height position, and moves the battery mounting table **34** below the battery **400**. Subsequently, the locking of the battery **400** to the vehicle is released by the locking tool provided on the battery mounting table **34**. Thus, the battery **400** is detached from the vehicle. At this time, the connection between the vehicle

side refrigerant connector **251** and the refrigerant connector **413** and the connection between the vehicle side electric connector **201** and the electric connector **401** are also released.

(97) [Transport Battery to Storage: Battery Replacement Apparatus]

(98) Next, in step **S14**, the battery **400** removed from the vehicle body **200a** is conveyed to the storage box **100b**. Specifically, the battery mounting table **34** on which the battery **400** is mounted is lowered to the height position of the transport unit **36**.

(99) Subsequently, the battery **400** mounted on the battery mounting table **34** is transferred to the transport unit **36**. The battery **400** transferred to the transport unit **36** is transferred to the temporary place **90**. The battery **400** is stored in the storage box **100b** by another transfer device (not shown).

(100) [Checking the Connector of the Removed Battery: Battery Replacement Apparatus]

(101) Next, in step **S14A**, the states of the connector portions (the electric connector **401** and the refrigerant connector **413**) of the removed battery **400** are checked.

(102) Specifically, the inspection device **500** and the battery **400** are connected to each other, and a gas is supplied to the ventilation path **60**. At this time, the flow state of the gas flowing through the ventilation path **60** is detected by the flow detector **50**. Thereby, it is possible to confirm whether or not the sealing members **408** and **418** provided in the battery **400** are deteriorated.

(103) When the inspection device **500** is connected to the battery **400**, the inspection refrigerant connector **513** and the inspection electric connector **501** are connected to the refrigerant connector **413** and the electric connector **401**.

(104) Step **S14A** may be performed when the removed battery **400** is conveyed to the temporary place or may be performed after being conveyed to the storage box **100b**.

(105) [Other Battery Mounting: Battery Replacement Apparatus]

(106) Next, in step **S15**, another battery **101** is attached to the vehicle body **200a**. Specifically, by raising the elevator **35**, the vehicle **200** is held parallel to the horizontal direction at a predetermined height position.

(107) Subsequently, the battery mounting table **34** on which the battery **101** is mounted is raised, and the battery **101** is locked to the vehicle body **200a** using a locking tool. At this time, the vehicle side electric connector **201** and the electric connector **401**, and the vehicle side refrigerant connector **251** and the refrigerant connector **413** are connected to each other.

(108) [Confirmation of the Connected State of the Replaced Battery: Battery Replacement Apparatus]

(109) Next, in step **S16**, the connection state of the replaced battery **101** is confirmed. Specifically, in a state where the vehicle side electric connector **201** and the electric connector **401** and the vehicle side refrigerant connector **251** and the refrigerant connector **413** are connected to each other, the gas supply unit **300** is driven to introduce the gas into the ventilation path **60**.

(110) As described above, the flow state of the gas flowing through the ventilation path **60** is detected by the flow detector **50** to confirm the connection state between the vehicle **200** and the battery **101**.

(111) At this time, when it is confirmed that the connection state between the vehicle **200** and the battery **101** is normal (step **S17**; YES), step **S18** is performed. When it is confirmed that the connection state between the vehicle **200** and the battery **101** is abnormal (step **S17**; NO), the operation from step **S13** is repeated. When it is confirmed that the connection state is abnormal, a lamp for notifying an abnormality may be turned on or a mark for notifying an abnormality may be displayed on the display unit **280**.

(112) When the first mode is selected in step **S24** as described above, step **S16** may be omitted.

(113) [Notification of Completion of Battery Replacement Work: Battery Replacement Apparatus]

(114) Next, in step **S18**, the processor **11** notifies the vehicle **200** of the completion of the battery replacement operation through the communication unit **13**.

(115) [Receipt of the Battery Replacement Work Completion Notification: Vehicle]

(116) In step **S25**, the vehicle **200** receives the notification transmitted from the communication

unit **13** of the battery replacement apparatus **100** in step **S18**. Thus, the vehicle **200** is brought into a state in which the ignition power supply can be turned on. Thereafter, the process ends.

(117) Through the above steps, the battery replacement apparatus **100** can replace the battery **400** with a new battery **101**.

(118) Although the present disclosure has been described and illustrated in detail, it is clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the scope of the present disclosure being interpreted by the terms of the appended claims.

Claims

1. A vehicle to which a power storage device is attached replaceably, the vehicle comprising: the power storage device; an auxiliary battery; a gas supply unit to which power is supplied from the auxiliary battery; a refrigerant circuit through which refrigerant flows, the refrigerant circuit including a vehicle side refrigerant connector provided as being connectable to the power storage device; a vehicle side electric connector provided as being connectable to the power storage device; and a gas supply pipe to which gas can flow from the gas supply unit, the gas supply pipe being connected to the gas supply unit, wherein the power storage device includes an electric connector provided as being connectable to the vehicle side electric connector, a refrigerant connector provided as being connectable to the vehicle side refrigerant connector, and a ventilation path provided to communicate to the gas supply pipe, the vehicle side refrigerant connector and the refrigerant connector are connected to form a first connection portion that contains a first closed space, the vehicle side electric connector and the electric connector are connected to form a second connection portion that contains a second closed space, the gas supply pipe is provided to supply the gas into at least one closed space of the first closed space and the second closed space, the ventilation path is provided to communicate with the gas supply pipe through the at least one closed space, and the ventilation path is provided with a flow detector that detects a flow state of the gas that flows through the ventilation path.

2. The vehicle according to claim 1, further comprising: a controller that controls an operation of the gas supply unit with power from the auxiliary battery; and a connection detector that detects connection of the vehicle side electric connector and the electric connector to each other, wherein the power storage device includes a power storage module and a refrigerant flow path through which the refrigerant for cooling of the power storage module flows, the gas supply pipe includes a first supply pipe through which the gas can be supplied to the first closed space, the ventilation path includes a first path formed by the refrigerant flow path, when the connection detector detects connection of the electric connector and the vehicle side electric connector to each other, the controller drives the gas supply unit to introduce the gas into the first closed space, and the flow detector includes a first detector that detects a flow state of the gas that flows through the first path.

3. The vehicle according to claim 2, wherein the first path includes a downstream refrigerant connection portion in which a first connector and a second connector are connected to each other, on a downstream side of the first connection portion in a flow direction of the refrigerant, the downstream refrigerant connection portion contains a third closed space, and the flow detector includes a first downstream detector provided in a portion of the first path located downstream of the third closed space, the first downstream detector detecting the flow state of the gas that flows through the first path.

4. The vehicle according to claim 1, further comprising: a controller that controls an operation of the gas supply unit with power from the auxiliary battery; and a connection detector that detects connection of the vehicle side electric connector and the electric connector to each other, wherein the power storage device includes a power storage module and an electric circuit that connects the power storage module and the electric connector to each other, the gas supply pipe includes a

second supply pipe through which the gas can be supplied to the second closed space, the ventilation path includes a second path provided along the electric circuit, when the connection detector detects connection of the electric connector and the vehicle side electric connector to each other, the controller drives the gas supply unit to introduce the gas into the second closed space, and the flow detector includes a second detector that detects a flow state of the gas that flows through the second path.

5. The vehicle according to claim 4, wherein the electric circuit includes a downstream connector connection portion where a third connector and a fourth connector are connected to each other, on a side of the power storage module relative to the second connection portion, the downstream connector connection portion contains a fourth closed space, the second path is provided to pass through the fourth closed space, and the flow detector includes a second downstream detector provided in a portion of the second path located on a side of the power storage module relative to the fourth closed space, the second downstream detector detecting the flow state of the gas that flows through the second path.

6. The vehicle according to claim 1, further comprising a display unit, wherein a result of detection by the flow detector is shown on the display unit.

7. The vehicle according to claim 1, wherein an inspected power storage device inspected by an inspection device is attached, the inspected power storage device is a power storage device in which the flow state of the gas that flows through the ventilation path is inspected in advance by the inspection device, and the inspection device is provided as being connectable to the refrigerant connector and the electric connector, and the inspection device can supply gas to the ventilation path through at least one of closed spaces formed in respective connection portions while the inspection device is connected to the refrigerant connector and the electric connector.

8. The vehicle according to claim 1, wherein in attachment of the power storage device, a first mode of replacement of a power storage device inspected by an inspection device and a second mode of replacement of a power storage device not inspected by the inspection device are selectably provided, the inspected power storage device is a power storage device in which the flow state of the gas that flows through the ventilation path is inspected in advance by the inspection device, the inspection device is provided as being connectable to the refrigerant connector and the electric connector and the inspection device can supply gas to the ventilation path through at least one of closed spaces formed in respective connection portions while the inspection device is connected to the refrigerant connector and the electric connector.
