

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250266244

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

CHOI; Kyoungmi et al.

PLASMA LAYER DEPOSITION APPARATUS AND METHOD OF PREDICTING THICKNESS PROFILE OF LAYER

Abstract

A method of predicting a thickness profile of a layer includes providing a plasma layer deposition apparatus, loading a wafer on a substrate stage, where the wafer includes a first region having a first material and a second region having a second material, deriving an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus, determining a sheath voltage based on the equivalent circuit model, the sheath voltage corresponding to a voltage applied to a space adjacent to the wafer by a matcher current from an impedance matcher, and predicting a selectivity of the layer as a ratio between a first thickness of a first deposition portion on the first region and a second thickness of a second deposition portion on the second region based on a correlation between the determined sheath voltage and a pre-stored selectivity value.

Inventors: CHOI; Kyoungmi (Suwon-si, KR), OH; Youngjoon (Suwon-si, KR), LEE; Jaeeun (Suwon-si, KR), HONG; Taeki (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008490301

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 19/052723

Filed: February 13, 2025

Foreign Application Priority Data

KR

10-2024-0024338

Feb. 20, 2024

Publication Classification

Int. Cl.: H01J37/32 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is based on and claims priority to Korean Patent Application No. 10-2024-0024338, filed on Feb. 20, 2024, in the Korean Intellectual Property Office (KIPO), the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

[0002] Example embodiments of the disclosure relate to a plasma layer deposition apparatus and a method of predicting a thickness profile of a layer using the same, and more particularly, to a method of predicting a structure of a layer deposited on a silicon wafer.

[0003] In a layer deposition process, plasma enhanced chemical vapor deposition (PECVD) may be applied. In this case, it may be required to predict a structure of a deposited layer using a simulation in order to minimize trial and error. For example, it may be required to predict selectivity because the selectivity with respect to an underlying material is an important factor in order to decrease a feature scale of a semiconductor device and a resistance of a semiconductor device.

[0004] Information disclosed in this Background section has already been known to or derived by the inventors before or during the process of achieving the embodiments of the present application, or is technical information acquired in the process of achieving the embodiments. Therefore, it may contain information that does not form the prior art that is already known to the public.

SUMMARY

[0005] One or more example embodiments provide a plasma thin film deposition apparatus capable of predicting a selectivity of a thin film that will be formed by a deposition process, and a method of predicting a thin film by using the plasma thin film deposition apparatus.

[0006] Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

[0007] According to an aspect of an example embodiment, a method of predicting a thickness profile of a layer may include providing a plasma layer deposition apparatus, where the plasma layer deposition apparatus includes a substrate stage provided in a chamber, a lower electrode, an upper electrode, and a source power circuit including a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode, loading a wafer on the substrate stage, where the wafer includes a first region having a first material and a second region having a second material, deriving an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus, determining a sheath voltage based on the equivalent circuit model, the sheath voltage corresponding to a voltage applied to a space adjacent to the wafer by a matcher current from the impedance matcher, and predicting a selectivity of the layer as a ratio between a first thickness of a first deposition portion on the first region and a second thickness of a second deposition portion on the second region based on a correlation between the determined sheath voltage and a pre-stored selectivity value.

[0008] According to an aspect of an example embodiment, a method of predicting a thickness profile of a layer may include providing a plasma layer deposition apparatus, where the plasma layer deposition apparatus includes a chamber, a substrate stage provided in the chamber, a lower electrode, an upper electrode, a source power circuit including a high frequency generator and an impedance matcher configured to supply an RF power to the upper electrode, and an impedance

controller configured to control a current flowing to the lower electrode, loading a wafer on the substrate stage, deriving an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus, determining a sheath voltage based on the equivalent circuit model, the sheath voltage corresponding to a voltage applied to a space adjacent to the wafer by a matcher current from the impedance matcher, and predicting a selectivity as a ratio between thicknesses of each of plurality of deposition portions of the layer to be formed on the wafer based on a correlation between the determined sheath voltage and a pre-stored selectivity value.

[0009] According to an aspect of an example embodiment, a method of predicting a thickness profile of a layer may include providing a plasma layer deposition apparatus, where the plasma layer deposition apparatus includes a chamber including a plasma region where plasma is formed and a plurality of sheath regions surrounding the plasma region, a substrate stage in the chamber, a lower electrode, an upper electrode configured, and a source power circuit including a high frequency generator and an impedance matcher configured to supply an RF power to the upper electrode, loading a wafer on the substrate stage, where the wafer includes a first region having a first material and a second region having a second material, deriving an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus, determining a sheath voltage based on the equivalent circuit model, the sheath voltage corresponding to a voltage applied to a space adjacent to the wafer by a matcher current from the impedance matcher, and predicting a selectivity of the layer as a ratio between a first thickness of a first deposition portion to be formed on the first region and a second thickness of a second deposition portion to be formed on the second region based on the determined sheath voltage and a pre-stored selectivity value.

[0010] According to an aspect of an example embodiment, a plasma layer deposition apparatus may include a chamber including a process space and a gas supplier configured to supply a gas in the process space, a substrate stage in the chamber and configured to load a wafer, where the wafer includes a first region including a first material and a second region including a second material, a plasma control portion including a lower electrode provided in the substrate stage, an upper electrode provided on the chamber and configured to form a plasma between the lower electrode and the upper electrode, and a source power circuit including a high frequency generator and an impedance matcher configured to supply a radio frequency power to the upper electrode, and a simulation module configured to predict a selectivity of a layer deposited on the wafer, where the chamber includes a plasma region between the wafer and the upper electrode, and a plurality of sheath regions surrounding the plasma region, the simulation module is configured to derive an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus, and to predict the selectivity based on the equivalent circuit model, and the selectivity is a ratio between a first thickness of a first deposition portion on the first region and a second thickness of a second deposition portion on the second region.

[0011] According to example embodiments, in a method of predicting a thickness profile of a layer, a plasma layer deposition apparatus is provided, wherein the plasma layer deposition apparatus includes a substrate stage provided in a chamber and having a lower electrode, an upper electrode configured to form plasma between the upper electrode and the lower electrode, and a source power circuit having a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode. A wafer is loaded, wherein the wafer includes a first region having a first material and a second region having a second material. An equivalent circuit model is derived, wherein the equivalent circuit model corresponds to a plasma system including the high frequency generator and the impedance matcher. A sheath voltage based on the equivalent circuit model is determined, wherein the sheath voltage is applied to a space adjacent the loaded wafer by a matcher current from the impedance matcher. A selectivity of the layer as a ratio between a first thickness of a first deposition portion to be formed on the first region and a second thickness of the second deposition portion to be formed on the second region is predicted by using relation between the determined sheath voltage and the selectivity.

[0012] According to example embodiments, in a method of predicting a thickness profile of a layer, a plasma layer deposition apparatus is provided, wherein the plasma layer deposition apparatus includes a chamber, a substrate stage provided in the chamber and having a lower electrode, an upper electrode configured to form a plasma between the upper electrode and the lower electrode, and a source power circuit having a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode, and an impedance controller configured to controller a current flowing to the lower electrode. A wafer is loaded on the substrate stage. An equivalent circuit model is derived, wherein the equivalent circuit model corresponds to a plasma system including the high frequency generator, the impedance matcher, the chamber, and the impedance controller. A sheath voltage based on the equivalent circuit model is determined, wherein the sheath voltage is applied to a space adjacent the loaded wafer by a matcher current from the impedance matcher. A selectivity as a ratio between thicknesses of each of plurality of deposition portions of the layer to be formed on the wafer is predicted by using relation between the determined sheath voltage and the selectivity.

[0013] According to example embodiments, in a method of predicting a thickness profile of a layer, a plasma layer deposition apparatus is provided, wherein the plasma layer deposition apparatus includes a chamber including a plasma region where a plasma is formed and a plurality of sheath regions surrounding the plasma region, a substrate stage provided in the chamber and having a lower electrode, an upper electrode configured to form the plasma between the upper electrode and the lower electrode, and a source power circuit having a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode. A wafer is loaded on the substrate stage, wherein the wafer includes a first region having a first material and a second region having a second material. An equivalent circuit model is derived, wherein the equivalent circuit model corresponds to a plasma system including the high frequency generator, the impedance matcher, and the chamber. A sheath voltage based on the equivalent circuit model is determined, wherein the sheath voltage is applied to a space adjacent the loaded wafer by a matcher current from the impedance matcher. A selectivity of the layer as a ratio between a first thickness of a first deposition portion to be formed on the first region and a second thickness of the second deposition portion to be formed on the second region is predicted by using relation between the determined sheath voltage and the selectivity.

[0014] According to example embodiments, a plasma layer deposition apparatus includes a chamber including a process space and a gas supplier configured to supply a gas in the process chamber; a substrate stage provided in the chamber and configured to load a wafer, wherein the wafer includes a first region including a first material and a second region including a second material; a plasma control portion including a lower electrode provided in the substrate stage, an upper electrode provided on the chamber and configured to form a plasma between the lower electrode and the upper electrode, a source power circuit providing a high frequency generator and an impedance matcher configured to supply a radio frequency power to the upper electrode; and a controller including a simulation module configured to predict a selectivity of a layer deposited on the wafer, wherein the chamber includes a plasma region provided between the wafer and the upper electrode and a plurality of sheath regions surrounding the plasma region, wherein the simulation module of the controller is configured to derive an equivalent circuit model that is corresponds to a plasma system including the chamber, the substrate stage, the plasma control portion, the plasma region, the plurality of sheath regions, and the wafer and to predict the selectivity based on the equivalent circuit model, and wherein the selectivity is a ratio between a first thickness of a first deposition portion to be formed on the first region and a second thickness of the second deposition portion to be formed on the second region.

[0015] According to example embodiments, a plasma layer deposition apparatus may include a chamber, a substrate stage provided in the chamber and having a lower electrode, an upper electrode configured to form the plasma between the upper electrode and the lower electrode, and a

source power circuit having a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode. The chamber may include a plasma region where the plasma is formed and a plurality of sheath regions surrounding the plasma region. [0016] According to example embodiments, in a method of predicting a thickness profile of a layer, the plasma layer deposition apparatus may be provided. A wafer may be loaded on the substrate stage, wherein the wafer includes a first region having a first material and a second region having a second material. An equivalent circuit model may be derived, wherein the equivalent circuit model corresponds to a plasma system including the high frequency generator, the impedance matcher, and the chamber. A sheath voltage based on the equivalent circuit model may be determined, wherein the sheath voltage is applied to a space adjacent the loaded wafer by a matcher current from the impedance matcher. And, a selectivity of a layer as a ratio between a first thickness of a first deposition portion to be formed on the first region and a second thickness of the second deposition portion to be formed on the second region may be predicted by using relation between the determined sheath voltage and the selectivity.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0017] The above and other aspects, features, and advantages of certain example embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0018] FIG. 1 is a cross-sectional view illustrating a plasma layer deposition apparatus according to one or more embodiments;

[0019] FIG. 2 is a flowchart illustrating a method of predicting a thickness profile of a layer by using a plasma layer deposition apparatus;

[0020] FIGS. 3 to 6 are diagrams illustrating a method of predicting a thickness profile of a layer by using a plasma layer deposition apparatus according to one or more embodiments; and

[0021] FIGS. 7 to 10 are diagrams illustrating a method of manufacturing a semiconductor device by using a plasma layer deposition apparatus according to one or more embodiments.

DETAILED DESCRIPTION

[0022] Hereinafter, example embodiments of the disclosure will be described in detail with reference to the accompanying drawings. The same reference numerals are used for the same components in the drawings, and redundant descriptions thereof will be omitted. The embodiments described herein are example embodiments, and thus, the disclosure is not limited thereto and may be realized in various other forms.

[0023] As used herein, expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list. For example, the expression, “at least one of a, b, and c,” should be understood as including only a, only b, only c, both a and b, both a and c, both b and c, or all of a, b, and c.

[0024] It will be understood that when an element or layer is referred to as being “over,” “above,” “on,” “below,” “under,” “beneath,” “connected to” or “coupled to” another element or layer, it can be directly over, above, on, below, under, beneath, connected or coupled to the other element or layer or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly over,” “directly above,” “directly on,” “directly below,” “directly under,” “directly beneath,” “directly connected to” or “directly coupled to” another element or layer, there are no intervening elements or layers present.

[0025] FIG. 1 is a cross-sectional view illustrating a plasma layer deposition apparatus according to one or more embodiments.

[0026] Referring to FIG. 1, a plasma layer deposition apparatus 10 may include a chamber 20

having an inner space IS, a substrate stage **30** disposed within the chamber **20** and configured to load a wafer W, a gas supplier **40** configured to inject a gas onto the wafer W, and a controller **70**. The controller **70** may be connected to an upper electrode **22**, a lower electrode **31** provided within the substrate stage **30**, a source power circuit **50** electrically connected to the upper electrode **22** to supply RF power to the upper electrode **22**, and an impedance controller **60** electrically connected to the lower electrode **31**. Additionally, the controller **70** may further be connected to a simulation module **100**.

[0027] A plasma enhanced chemical vapor deposition (PECVD) process may be performed by using the plasma layer deposition apparatus **10**. For example, the plasma layer deposition apparatus **10** may be an apparatus configured to deposit a target layer on a substrate, such as a semiconductor wafer disposed within the chamber **20**. For example, the substrate may include a silicon substrate, etc.

[0028] Additionally, the plasma layer deposition apparatus **10** may be a capacitively coupled plasma (CCP) processing apparatus. However, the plasma layer deposition apparatus **10** is not limited to thereto, and, for example, the plasma layer deposition apparatus **10** may be an inductively coupled plasma (ICP) processing apparatus, etc. The PECVD process may include a chemical process in which electromagnetic energy is applied to at least one precursor gas or precursor vapor to convert the precursor into reactive plasma. The PECVD process may be used to deposit, for example, an insulation layer on a semiconductor device such as a semiconductor wafer, not being limited thereto.

[0029] In one or more embodiments, the inner space IS of the chamber **20** may be a sealed interior space in which the plasma deposition process is performed on the wafer W. The chamber **20** may be a vacuum chamber. The chamber **20** may include a metal such as aluminum, stainless steel, etc.

[0030] A substrate stage **30** may be disposed in the inner space IS of the chamber **20** and configured to support the wafer W. For example, the substrate stage **30** may serve as a susceptor for supporting the wafer W. The substrate stage **30** may include an electrostatic chuck for electrostatically holding the wafer W at an upper portion thereof. As will be described later, the lower electrode **31** may be provided within the substrate stage **30** such that the lower electrode **31** is disposed under the wafer W.

[0031] A gate may be installed in a side wall of the chamber **20** and may be configured for entry and exit of the wafer W. The wafers W may be loaded and unloaded onto the substrate stage **30** through the gate.

[0032] An exhaust port **24** may be provided in a lower portion of the chamber **20**. An exhaust portion **26** may be connected to the exhaust port **24** through an exhaust pipe. The exhaust portion **26** may include a vacuum pump, such as a turbomolecular pump, to control a pressure of a process space PS inside the chamber **20**. Additionally, by-products of process and residual process gases generated within the chamber **20** may be discharged through the exhaust port **24**.

[0033] The chamber **20** may include a cover **28** that is configured to cover an upper portion of the chamber **20**. The cover **28** may seal the upper portion of the chamber **20**.

[0034] The upper electrode **22** may be disposed on the upper portion of the chamber **20** such that the upper electrode **22** faces the lower electrode **31**. The upper electrode **22** may be disposed within the cover **28**. A process space PS between the upper electrode **22** and the lower electrode may be used as a plasma generation space. The upper electrode **22** may have a surface which faces the wafer W, which is supported on the substrate stage **30**.

[0035] The inner space IS of the chamber **20** may include a process space PS disposed between the substrate stage **30** and the cover **28**. The process space PS may be a space where the deposition process is performed. The process space PS may include a plasma region PR disposed between the upper electrode **22** and the lower electrode **31**, and a plurality of sheath regions SR1, SR2, SR3 surrounding the plasma region PR. The plasma region PR may be a region in which the plasma P is formed. The plurality of sheath regions SR1, SR2, SR3 may include a first sheath region SR1

located between the plasma P and the cover **28**, a second sheath region SR2 located between the plasma P and the substrate stage **30**, and a third sheath region SR3 disposed on an edge region ER located between the substrate stage **30** and a side portion of the chamber **20**.

[0036] For example, the plurality of sheath regions SR1, SR2 and SR3 may be regions where a voltage changes rapidly due to differences in movement speed between electrons and cations included in the plasma P when the plasma P is formed. For example, the plurality of sheath regions SR1, SR2 and SR3 may be formed in a region adjacent to the lower electrode **31**, a region adjacent to the upper electrode **22**, and a region adjacent to side walls of the chamber **20**, respectively.

[0037] In one or more embodiments, the substrate stage **30** may include a substrate support **33** having a receiving surface on which the wafer W is seated, and the lower electrode **31** may be disposed under the wafer W and disposed inside the substrate support **33**. The substrate stage **30** may further include a first signal line **34** that is configured to electrically connect the lower electrode **31** to the impedance controller **60**, which will be described later.

[0038] In one or more embodiments, the gas supplier **40** may include a shower head **41**, a flow controller **42** and a gas supply source **44**. The gas supplier **40** may be an apparatus that is configured to supply a gas to the inner space IS of the chamber. The gas may include different gases in various desired ratio. For example, the gas may include titanium tetrachloride (TiCl₄), hydrogen (H₂), argon (Ar), etc.

[0039] The gas supply source **44** may store the different gases and be in fluid communication with the shower head **41**. The gas introduced from the gas supply source **44** may be controlled at a desired flow rate by the flow controller **42**.

[0040] In one or more embodiments, the source power circuit **50** may provide a plasma source power to the upper electrode **22**. The source power circuit **50** may be electrically connected to the upper electrode **22** through a second signal line. For example, the source power circuit **50** may include plasma source elements, such as a high frequency generator **52** and an impedance matcher **54**. The high frequency generator **52** may generate a radio frequency (RF) signal. The impedance matcher **54** may match an output impedance of the RF signal generated by the high frequency generator **52** to a chamber impedance X generated by a plasma layer deposition apparatus that does not include a high frequency generator. For example, the impedance matcher **54** may vary capacitors within the impedance matcher **54** so that maximum power is transferred to the plasma layer deposition apparatus **10**.

[0041] In one or more embodiments, the impedance controller **60** may be electrically connected to the first signal line **34**. The impedance controller **60** may regulate a strength of current flowing through the lower electrode **31**, to control the location where the plasma P is formed. For example, the strength of the current flowing through the lower electrode **31** may be decreased to increase the strength of the current flowing through the side wall of the chamber **20**. In this case, the plasma P may be concentrated to an edge region adjacent to the side wall of the chamber **20**. In contrast, the strength of the current flowing to the lower electrode **31** may be increased to decrease the strength of the current flowing to the side wall of the chamber **20**. In this case, the plasma P may be concentrated to a center of the chamber where the substrate stage **30** is provided.

[0042] Although the impedance controller **60** is shown in the figures, the plasma layer deposition apparatus **10** may not include the impedance controller **60**.

[0043] In one or more embodiments, the controller **70** may be configured to change process conditions. The controller **70** may output control signals to the gas supplier **40** to control a flow rate of the gas injected into the chamber **20**. The controller **70** may output control signals to the source power circuit **50** to control an RF power applied by the high frequency generator **52**. The controller **70** may output a control signal to the impedance controller **60** to control an impedance of the impedance controller **60**. The controller **70** may output a control signal to the exhaust portion **26** to control a pressure in the chamber **20**.

[0044] For example, the controller **70** may include a simulation module **100**. The simulation

module **100** may be a module that is configured to predict a thickness profile (i.e., selectivity) of a layer formed by a deposition process by using the plasma layer deposition apparatus **10**. The selectivity of the layer may be a ratio of thicknesses of deposited portions of the layer. For example, a loaded wafer on the plasma layer deposition apparatus **10** may include a first region having a first material and a second region having a second material. The layer may include a first deposited portion formed on the first region and a second deposited portion formed on the second region. The first deposited portion on the first region may have a first thickness, and the second deposited portion formed on the second region may have a second thickness. In this case, a ratio of the first thickness to the second thickness may be the selectivity. For example, the first material may be silicon (Si). The second material may be an insulation material.

[0045] The simulation module **100** may derive an equivalent circuit model having an electrically equivalent relationship with a plasma system including the plasma layer deposition apparatus **10** and the loaded wafer W on the plasma layer deposition apparatus **10**. From the equivalent circuit model, a sheath voltage V1 (refer to FIG. 4) across the second sheath region SR2 may be determined based on a matcher current I1 (refer to FIG. 4) introduced by the impedance matcher **54**. The simulation module **100** may load stored data of the selectivity corresponding to the sheath voltage V1 and predict the selectivity by using a correlation between the sheath voltage V1 and the selectivity. For example, the simulation module **100** may determine a sheath voltage based on the equivalent circuit module, and a memory may store various pre-stored selectivities corresponding to various sheath voltages. Then, the simulation module **100** may compare the determined sheath voltage with the pre-stored selectivities, and use this comparison to predict the selectivity of the layer, based on the sheath voltage of the simulation potentially corresponding to the actual sheath voltage of the actual process performed by the plasma layer deposition apparatus **10** on the wafer W.

[0046] As described above, the plasma layer deposition apparatus **10** may include the chamber **20**, the substrate stage **30** provided within the chamber **20** and that is configured to load the wafer W, the gas supplier **40** configured to inject the gas onto the wafer W, and the controller **70**. The controller **70** may be connected to the upper electrode **22**, the lower electrode **31** provided within the substrate stage **30**, the source power circuit **50** electrically connected to the upper electrode, and the impedance controller **60** electrically connected to the lower electrode **31**. Further, the controller **70** may be connected to the simulation module **100**. The controller **70** may control the upper electrode **22**, the lower electrode **31**, the source power circuit **50**, and the impedance controller **60** to function as a plasma controller. Furthermore, the controller **70** may be connected to the simulation module **100** and may be configured to, using the simulation module **100**, to derive an equivalent circuit model having an electrically equivalent relationship with a plasma system including the plasma layer deposition apparatus **10** and the loaded wafer W on the plasma layer deposition apparatus **10**.

[0047] The simulation module **100** may predict the selectivity of the layer formed by the deposition process using the plasma layer deposition apparatus **10**. The simulation module **100** may derive the equivalent circuit model EC that is electrically equivalent to the plasma system including the plasma layer deposition apparatus **10** and the loaded wafer. From the equivalent circuit model, the sheath voltage V1 (refer to FIG. 4) across the second sheath region SR2 may be determined based on the matcher current I1 (refer to FIG. 4) introduced by the impedance matcher **54**. Then, the simulation module **100** may load the stored data of the selectivity corresponding to the sheath voltage and predict the selectivity using correlation between the sheath voltage V1 and the stored selectivity.

[0048] Accordingly, the plasma layer deposition apparatus **10** may predict the selectivity without conducting actual deposition process experiments, to thereby reduce the experiment time and cost consumed by the process experiment.

[0049] Hereinafter, a method of predicting a thickness profile, i.e., a selectivity of a layer, using a

plasma layer deposition apparatus **10** according to one or more embodiments will be described. [0050] FIG. **2** is a flowchart illustrating a method of predicting layer according to one or more embodiments. FIGS. **3** and **4** are diagrams illustrating a plasma layer deposition apparatus and a corresponding equivalent circuit model according to one or more embodiments. FIG. **5** is a graph illustrating the correlation between a selectivity of a layer and a determined sheath voltage from the equivalent circuit model, according to one or more embodiments.

[0051] First, a plasma layer deposition apparatus **10** may be provided in operation **S10**. Then, a wafer **W** may be loaded onto a substrate stage **30** of the plasma layer apparatus **10** in operation **S20**. The wafer may include a first region having a first material and a second region having a second material. For example, the first material may be silicon (Si). Further, the second material may be an insulation material.

[0052] Since the plasma layer deposition apparatus is substantially the same as the plasma layer deposition apparatus **10** in accordance with embodiments described in FIG. **1**, a repeated description of the same components may be omitted.

[0053] Referring to FIGS. **3** and **4**, an equivalent circuit model **EC** corresponding to the plasma layer deposition apparatus **10** and the loaded wafer **W** may be derived in operation **S110**, and a sheath voltage **V1** may be determined from the equivalent circuit model **EC** in operation **S120**. Thereafter, the correlation between the sheath voltage **V1** and the pre-stored selectivity may be utilized to predict the sheath voltage **V1** and the corresponding selectivity in operation **S130**.

[0054] First, in deriving the equivalent circuit model **EC**, the plasma layer deposition apparatus **10** and the loaded wafer **W** may be replaced with electrical elements having an electrically equivalent relationship to derive the equivalent circuit model **EC**. For example, the electrical elements may include capacitors, inductors, resistors, etc.

[0055] The high frequency generator **52** may be replaced by a power resistor **Rs** and a power voltage **Vs**, and the impedance matcher **54** may be replaced by a plurality of first inner capacitors **Cl**, **Ct** and at least one first inner inductor **Lm**. Further, the impedance controller **60** may be replaced by at least one second inner capacitor **Cx** and at least one second inner inductor **Lx**. For example, the plurality of first inner capacitors **Cl**, **Ct** may include a load capacitor **Cl** connected in parallel with the high frequency generator **52** and a regulating capacitor **Ct** connected in series with the high frequency generator **52**. The at least one second inner capacitor **Cx** and the at least one second inner inductor **Lx** may be connected in series with each other.

[0056] The plasma region **PR** may be replaced with a plurality of plasma resistors **R1**, **R2**, **R3**. Further, the plurality of sheath regions **SR1**, **SR2**, **SR3** may be replaced with a plurality of capacitors **C1**, **C2**, **C3**. For example, the first sheath region **SR1** disposed between the plasma region **PR** and the upper electrode **22** may be replaced with a first capacitor **C1**, the second sheath region **SR2** disposed between the plasma region **PR** and the loaded wafer **W** may be replaced with a second capacitor **C2**, and the third sheath region **SR3** surrounding an outer side portion of the plasma region **PR** may be replaced with a third capacitor **C3**, in the equivalent circuit model **EC**.

[0057] The equivalent circuit model **EC** may include a plurality of parasitic capacitors to better simulate the electrical characteristics of the plasma system. The equivalent circuit **EC** may further include a first parasitic capacitor **Cp1** and a second parasitic capacitor **Cp2**. For example, the first parasitic capacitor **Cp1** may be connected in parallel with the high frequency generator **52** and the impedance matcher **54** within the equivalent circuit model **EC**. The first parasitic capacitor **Cp1** may be an electrical element for simulating current, which flows from the upper electrode **22** to the chamber **20**, to the plasma layer deposition apparatus **10**. For example, the second parasitic capacitor **Cp2** may be connected in parallel with the impedance controller **60** in the equivalent circuit model **EC**. The second parasitic capacitor **Cp2** may be an electrical element for simulating current, which flows from the lower electrode **22** to the chamber **20**, to the plasma layer deposition apparatus **10**.

[0058] Further, the equivalent circuit model **EC** may include a fourth capacitor **C4** corresponding to

the loaded wafer W.

[0059] The equivalent circuit model EC may include a chamber portion X that does not include the high frequency generator 52 and the impedance matcher 54. An impedance value of the chamber portion X may be a chamber impedance Z_x . A generator impedance Z_{52} may be an impedance of a portion corresponding to the high frequency generator 52 in the equivalent circuit model EC. A matcher impedance Z_{54} may be an impedance of a portion corresponding to the impedance matcher 54.

[0060] Next, a plurality of process input conditions may be simulated in the equivalent circuit model EC. The plurality of process input conditions may be processing conditions that are entered during an actual layer deposition process. The plurality of process input conditions may include a power supplied from the high frequency generator 52, an impedance magnitude of the impedance controller 60, and a process pressure inside the chamber 20.

[0061] For example, the power may be varied by changing the power voltage V_s of the high frequency generator 52 in the equivalent circuit model EC so that the power has an identical power to that which is supplied by the actual layer deposition process. Further, the impedance magnitude may be varied by changing values of the at least one second inner capacitor C_x and the at least one second inner inductor L_x so that the impedance magnitude has an identical impedance to that which is applied in the actual layer deposition process.

[0062] Further, the process pressure may be controlled by changing the values of the plurality of plasma resistors R1, R2, R3 and the plurality of capacitors C1, C2, C3 for simulating a tendency of change of the plasma according to a change of the process pressure in an actual chamber. For example, the tendency occurs when the process pressure increase. In case that the process pressure increase, a plasma density may increase because an amount of a supplied gas increases, but a plasma temperature may decrease because an energy of a particle of the supplied gas decreases. Thus, values of the plurality of plasma resistors R1, R2, and R3 may decrease, and values of the plurality of capacitors C1, C2, and C3 may increase. To simulate the tendency, the values of the plurality of plasma resistors R1, R2, R3 and the plurality of capacitors C1, C2, C3 may be adjusted.

[0063] Next, based on the equivalent circuit model EC, values of the plurality of electrical elements included in the equivalent circuit model EC, values of current flowing through each of the plurality of electrical elements, and values of voltages applied to each of the plurality of electrical elements may be determined.

[0064] For example, a plurality of circuit equations may be derived from the generator impedance Z_{52} , the matcher impedance Z_{54} , and the chamber impedance Z_x of the equivalent circuit model EC. By determining the plurality of circuit equations using a computer program, values of the plurality of electrical elements included in the chamber portion X may be obtained.

[0065] However, the at least one second inner capacitor C_x and the at least one second inner inductor L_x may have values entered by the controller 70. Further, the power resistor R_s and the power voltage V_s may have preset values. For example, the power resistance may be 50 Ω . The power voltage may have a value entered by the controller 70.

[0066] The values of the plurality of first inner capacitors C_l and C_t and the at least one first inner inductor L_m may be determined according to a corresponding portion with the high frequency generator 52 and the chamber portion X. For example, the plurality of first inner capacitors C_l and C_t may be adjusted to maximize a power applied to the equivalent circuit model EC.

[0067] Next, a current value of the matcher current I1 introduced from the impedance matcher 54 may be determined by using the equivalent circuit model EC. From the matcher current I1, the sheath voltage V1 applied across the second capacitor C2 may be determined. For example, by using a current distribution law, a voltage value of the sheath voltage V1 may be determined from the value of the matcher current I1.

[0068] Then, a selectivity of a layer corresponding to the value of the sheath voltage V1 may be predicted by using the correlation between the sheath voltage V1 and the pre-stored selectivity. For

example, the simulation module **100** of the plasma layer deposition apparatus **10** may store data of the sheath voltage **V1** and the selectivity having a correlation relationship. The simulation module **100** may determine the sheath voltage **V1** based on the equivalent circuit model **EC**. Subsequently, the sheath voltage **V1** and the corresponding selectivity may be loaded from the stored data.

[0069] The selectivity of the layer may be a ratio of thicknesses between deposited portions of a layer formed by the deposition process in a plasma layer deposition process. For example, a wafer, which is loaded onto the plasma layer deposition apparatus **10**, may have a first region having a first material and a second region having a second material. The layer may include a first deposited portion formed on the first region and a second deposited portion formed on the second region. The first deposited portion on the first region may have a first thickness, and the second deposited portion formed on the second region may have a second thickness. In this case, the ratio of the first thickness to the second thickness may be the selectivity. For example, the first material may be silicon (Si). The second material may be an insulation material.

[0070] Referring to FIG. 5, the plurality of circuit equations may be derived from the equivalent circuit model **EC**. However, it will be appreciated that the plurality of circuit equations are exemplary and are not exclusive. Accordingly, the plurality of circuit equations may be replaced with other equations derived from the equivalent circuit model. For example, circuit equations may be analyzed in the frequency domain by being represented as complex numbers. An imaginary unit **j** may denote the square root of -1 . An angular frequency **w** may be defined according to the power voltage **Vs**.

[0071] For example, a first to sixth equation may be derived from the equivalent circuit model by using impedance.

[0072] A first impedance **Z1** may be expressed by Equation (1).

[00001] $Z1 = j * w * Lx + \frac{1}{j * w * Cx}$ (1) [0073] where **Z1** is a value of the first impedance in the equivalent circuit model **EC**, and **Lx** is a value of the at least one second inner inductor of the impedance controller **60**, and **Cx** is a value of the at least one second inner capacitor of the impedance controller **60**.

[0074] A second impedance **Z2** may be expressed by Equation (2).

[00002] $Z2 = \frac{Z1 * \frac{1}{j * w * Cp2}}{Z1 + \frac{1}{j * w * Cp2}}$ (2) [0075] where **Z1** is a value of the first impedance in the equivalent circuit model **EC**, **Z2** is a value of the second impedance in the equivalent circuit model **EC**, and **Cp2** is a value of the second parasitic capacitor.

[0076] A third impedance **Z2** may be expressed by Equation (3).

[00003] $Z3 = \frac{1}{j * w * C4} + \frac{1}{j * w * C2} + Z2 + R2$ (3) [0077] where **Z2** is a value of the second impedance in the equivalent circuit model **EC**, **Z3** is a value of the third impedance in the equivalent circuit model **EC**, and **C2** is a value of the second capacitor **C2** for the second sheath region **SR2**, and **C4** is a value of the fourth capacitor **C4** for the loaded wafer **W**, and **R2** is a value of one of the plurality of plasma resistors for the plasma region.

[0078] A fourth impedance **Z4** may be expressed by Equation (4).

[00004] $Z4 = \frac{Z3 * (R3 + \frac{1}{j * w * C3})}{Z3 + (R3 + \frac{1}{j * w * C3})}$ (4) [0079] where **Z3** is a value of the third impedance in the equivalent circuit model **EC**, and **Z4** is a value of the fourth impedance in the equivalent circuit model **EC**, and **R3** is a value of one of the plurality of plasma resistors for the plasma region, and **C3** is a value of the third capacitor for the third sheath region **SR3**.

[0080] A fifth impedance **Z5** may be expressed by Equation (5).

[00005] $Z5 = \frac{1}{j * w * C1} + R1 + Z4$ (5) [0081] where **Z4** is a value of the fourth impedance in the equivalent circuit model **EC**, and **Z5** is a value of the fifth impedance in the equivalent circuit model **EC**, and **R1** is a value of one of the plurality of plasma resistors for the plasma region, and

C1 is a value of the first capacitor for the first sheath region SR1.

[0082] The chamber impedance Zx may be expressed by Equation (6).

[00006] $Z_x = \frac{Z_5 * \frac{1}{j * \omega * C_{p1}}}{Z_5 + \frac{1}{j * \omega * C_{p1}}}$ (6) [0083] where Z5 is a value of the fifth impedance in the equivalent circuit model EC, and Zx is a value of the chamber impedance in the equivalent circuit model EC, and Cp1 is a value of the first parasitic capacitor.

[0084] Thus, by using first to sixth equation, the chamber impedance may be determined. For example, the at least one second inner inductor and the at least one second inner capacitor of the impedance controller 60 may be an input value

[0085] For example, a first to sixth equation may be derived from the equivalent circuit model by using current distribution law. According to the current distribution law, in circuits with parallel branches, total current may be distributed among the branches in inverse proportion to impedance of each branch.

[0086] A second current I2 may be expressed by Equation (7). For example, the second current may be a current through the first capacitor for the first sheath region SR1.

[00007] $I_2 = \frac{\frac{1}{j * \omega * C_{p1}}}{\frac{1}{j * \omega * C_{p1}} + Z_5} * I_1$ (7) [0087] where I1 is a value of the matcher current, and I2 is a

value of the second current through the first capacitor, and Z5 is a value of the fifth impedance in the equivalent circuit model EC, and Cp1 is a value of the first parasitic capacitor.

[0088] A third current I3 may be expressed by Equation (8). For example, the third current may be a current through the second capacitor C2 for the second sheath region SR2.

[00008] $I_3 = \frac{(R_3 + \frac{1}{j * \omega * C_3})}{(R_3 + \frac{1}{j * \omega * C_3}) + Z_3} * I_2$ (8)

where and I2 is a value of the second current through the first capacitor, and I3 is a value of the third current through the second capacitor C2, and R3 is a value of one of the plurality of plasma resistors for the plasma region, and C3 is a value of the third capacitor for the third sheath region SR3.

[0089] A fourth current I4 may be expressed by Equation (9). For example, the third current may be a current through the at least one second inner capacitor Cx and the at least one second inner inductor Lx of the impedance controller 60.

[00009] $I_4 = \frac{\frac{1}{j * \omega * C_{p2}}}{\frac{1}{j * \omega * C_{p2}} + Z_1} * I_3$ (9) [0090] where I3 is a value of the third current through the

second capacitor C2, and I4 is a value of the fourth current through the at least one second inner capacitor Cx and the at least one second inner inductor Lx, and Z1 is a value of the first impedance in the equivalent circuit model EC, and Cp2 is a value of the second parasitic capacitor.

[0091] The sheath voltage V1 may be expressed by Equation (10).

[00010] $V_1 = \text{Math} . \frac{1}{j * \omega * C_2} * I_3 \text{ . Math} .$ (10) [0092] where C2 is a value of the second

capacitor C2 for the second sheath region SR2, and I3 is a value of the third current through the second capacitor C2, and V1 is a value of voltage across the second sheath region SR2.

[0093] Thus, by using the first to tenth equation, the sheath voltage V1 may be determined. For example, by using simulation software, the first to tenth equation may be analyzed to determine the sheath voltage V1. For example, the matcher current may be an input value

[0094] Referring to FIG. 6, the sheath voltage V1 determined by the method of predicting the selectivity in accordance with one or more embodiments and the selectivity of the layer formed by the plasma layer deposition apparatus 10 may have a correlation with each other. In the graph of FIG. 6, a horizontal axis SV may represent a voltage value of the determined sheath voltage V1 and a vertical axis S may represent a measured value of the selectivity of the layer measured by experiment.

TABLE-US-00001 TABLE 1 Process Experimental Simulation Condition Result Result Pressure

Power I.sub.1 SV [Torr] [W] Z.sub.60[Ω] [A] S [V] 1 5 300 70 1.51 3.3 1.78 230 2 5
 200 70 1.3 3.8 1.53 197 3 6 200 70 1.32 4.2 1.50 195 4 6 150 70 1.22 5 1.34 167 5 9 200 70 1.45
 5 1.43 166 6 5 200 60 1.32 3.9 1.53 196 7 5 200 55 1.32 3.9 1.52 195 Correlation Coefficient
 (R.sup.2) 0.92 0.70

[0095] In the process conditions in Table 1, “pressure” may be the pressure inside the chamber **20**, “power” may be the power applied by the high frequency generator **52**, and “Z60” may be the impedance of the impedance controller **60**. In the results in Table 1, “I1” may be an actual measurement of the matcher current I1 introduced by the impedance matcher **54** of the plasma layer deposition apparatus **10**, and “S” may be a ratio of the thicknesses of the deposited portions of the layer (e.g., the first deposited portion on the first region and the second deposited portion formed on the second region) formed by the deposition process when the deposition process is performed by the plasma layer deposition apparatus **10**. In the simulation of Table 1, “I1” may be a determined value of the matcher current I1 measured in the equivalent circuit EC, and “SV” may be a determined value of the sheath voltage V1 measured in the equivalent circuit EC.

[0096] The graph of FIG. 6 illustrates the experimental results and the simulation results of Table 1. For example, the graph of FIG. 6 illustrates a correlation between the measured value S of the selectivity obtained by the experiment in Table 1 and the determined value SV of the sheath voltage obtained by the simulation in Table 1.

[0097] The correlation coefficient CO between the determined voltage value SV of the sheath voltage V1 and the measured value S of the selectivity of the layer may be ‘0.9213’. The correlation coefficient may have a value within the range of ‘0’ to ‘1’ as an indicator of a relevance between two values. For example, the closer the correlation coefficient is to ‘1’, the more related the two values are, and the closer the correlation coefficient is to ‘0’, the less related the two values are. Since the correlation coefficient CO has a value relatively close to ‘1’, there may be a relatively high correlation between the voltage value SV of the determined sheath voltage V1 and the measured value S of the selectivity of the layer.

[0098] Thus, from the graph of FIG. 6, the method of predicting a thickness profile of a layer in accordance with one or more embodiments effectively predicts the selectivity of a layer.

[0099] As described above, in the method of predicting layer, the plasma layer deposition apparatus **10** may be provided. The wafer W may be loaded onto the substrate stage **30** of the plasma layer deposition apparatus **10**, where the wafer includes the first region having the first material and the second region having the second material. The selectivity may be predicted by performing a simulation for a system including a simulated plasma layer deposition apparatus, where the selectivity is the ratio of the first thickness of the first deposition portion to be formed on the first region to the second thickness of the second deposition portion to be formed on the second region.

[0100] Accordingly, the method predicting layer by using the simulated plasma layer deposition apparatus may predict the selectivity of the layer without performing actual deposition process experiments, thereby reducing the experiment time and cost consumed by process experiments.

[0101] Hereinafter, a method of manufacturing semiconductor including the method of predicting a thickness profile of a layer in accordance with one or more embodiments will be described.

[0102] FIG. 7 is a cross-sectional view illustrating that a wafer according to one or more embodiments. FIG. 8 is a cross-sectional view illustrating that an insulation layer is formed on the wafer in FIG. 7 according to one or more embodiments. FIG. 9 is a cross-sectional view illustrating that a recess is formed on the insulation layer in FIG. 8 according to one or more embodiments. FIG. 10 is a cross-sectional view illustrating a first deposition portion and a second deposition portion are formed on the recess in FIG. 9 according to one or more embodiments.

[0103] Referring to FIG. 7, a wafer W may be provided on a support member SM, where the wafer may include a plurality of die regions DA and a scribe lane region SC surrounding the plurality of die regions DA. For example, each of the plurality of die regions DA may be regions on which a semiconductor is formed. The scribe lane region SC may be a region that is removed by a sawing

process to separate semiconductors from the wafer.

[0104] Referring to FIG. 8, a deposition process may be performed to form the insulation layer PL on a surface of the wafer W. For example, the deposition process may be a dry etching process such as CVD, etc.

[0105] Referring to FIG. 9, a photolithography process may be performed on the insulation layer PL to form recesses R on each of the plurality of die regions DR. The recesses R may be formed by partially removing the insulation layer PL and a portion of the wafer W provided under the insulation layer PL. Through the recesses R, at least a portion of the wafer W may be exposed.

[0106] For example, a photoresist layer may be applied on the insulation layer PL, an exposure process may be performed to emit light on the photoresist layer, and a development process may be performed to remove a portion of the photoresist layer to form a photoresist pattern that exposes a region where the recesses R is to be formed. Thereafter, an etching process may be performed on the photoresist pattern to form the recesses R.

[0107] Referring to FIG. 10, the wafer W may be loaded onto a plasma layer deposition apparatus (illustrated in FIG. 1), and a simulation (illustrated in FIGS. 2 to 5) may be performed on the plasma layer deposition apparatus and the loaded wafer W to predict a thickness profile, i.e., a selectivity of a layer. Thereafter, a plasma layer deposition process may be performed on the loaded wafer W to form a deposition layer DP including a first deposition portion DP1 having a first thickness T1 and a second deposition portion DP2 having a second thickness T2. The first thickness T1 and second thickness T2 may have a predicted selectivity.

[0108] For example, the wafer W and the insulation layer PL may include different materials. The wafer W may include a first material and the insulation layer PL may include a second material. For example, the first material may be silicon (Si). A ratio of the first thickness T1 of the first deposited portion DP1 to be deposited on the wafer W and the second thickness T2 of the second deposited portion DP2 to be deposited on the insulation layer PL may be predicted.

[0109] For example, the plasma layer deposition process may be a PECVD process.

[0110] Accordingly, the method of predicting a thickness profile of a layer using the plasma layer deposition apparatus may predict the selectivity of the layer without conducting actual deposition process experiments, thereby reducing an experiment time and an experiment cost consumed by a process experiment.

[0111] Each of the embodiments provided in the above description is not excluded from being associated with one or more features of another example or another embodiment also provided herein or not provided herein but consistent with the disclosure.

[0112] While the disclosure has been particularly shown and described with reference to embodiments thereof, it will be understood that various changes in form and details may be made therein without departing from the spirit and scope of the following claims.

Claims

1. A method of predicting a thickness profile of a layer, the method comprising: providing a plasma layer deposition apparatus, wherein the plasma layer deposition apparatus comprises a substrate stage provided in a chamber, a lower electrode, an upper electrode, and a source power circuit comprising a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode; loading a wafer on the substrate stage, wherein the wafer comprises a first region having a first material and a second region having a second material; deriving an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus; determining a sheath voltage based on the equivalent circuit model, the sheath voltage corresponding to a voltage applied to a space adjacent to the wafer by a matcher current from the impedance matcher; and predicting a selectivity of the layer as a ratio between a first thickness of a first deposition portion on the first region and a second thickness of a second deposition portion on

the second region based on a correlation between the determined sheath voltage and a pre-stored selectivity value.

2. The method of claim 1, wherein the determining the sheath voltage comprises: controlling values of a plurality of circuit elements of the equivalent circuit model to simulate process conditions of the plasma layer deposition apparatus; determining the matcher current from the equivalent circuit model based on a first impedance corresponding to a simulated high frequency generator, a second impedance corresponding to a simulated impedance matcher, and a third impedance corresponding to a simulated chamber portion that does not include a high frequency generator or an impedance matcher; and determining the sheath voltage from the equivalent circuit model based on the matcher current.

3. The method of claim 2, wherein the controlling values of the plurality of circuit elements comprises simulating a pressure in the chamber and the RF power supplied from the high frequency generator, with the equivalent circuit model.

4. The method of claim 1, wherein the predicting the selectivity comprises: storing data about the sheath voltage and the pre-stored selectivity value; and deriving the selectivity based on the stored data.

5. The method of claim 1, wherein the equivalent circuit model simulates a plasma region where plasma is formed in the chamber and a plurality of sheath regions surrounding the plasma region.

6. The method of claim 5, wherein the deriving the equivalent circuit model comprises: simulating the high frequency generator with a power resistor and a power voltage; and simulating the impedance matcher with a plurality of first inner capacitors and at least one first inner inductor.

7. The method of claim 5, wherein the deriving the equivalent circuit model comprises: simulating the plasma region with a plurality of plasma resistors; and simulating the plurality of sheath regions with a plurality of capacitors.

8. The method of claim 7, wherein the simulating the plurality of sheath regions with the plurality of capacitors comprises: simulating a first sheath region between the plasma region and the upper electrode with a first capacitor; simulating a second sheath region between the plasma region and the wafer with a second capacitor; and simulating a third sheath region surrounding an outer side portion of the plasma region with a third capacitor.

9. The method of claim 1, wherein the plasma layer deposition apparatus further comprises an impedance controller configured to control a current flowing to the lower electrode, and wherein the equivalent circuit model simulates the impedance controller.

10. The method of claim 9, wherein the deriving the equivalent circuit model comprises simulating the impedance controller with at least one second inner capacitor and at least one second inner inductor.

11. A method of predicting a thickness profile of a layer, the method comprising: providing a plasma layer deposition apparatus, wherein the plasma layer deposition apparatus comprises a chamber, a substrate stage provided in the chamber, a lower electrode, an upper electrode, a source power circuit comprising a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode, and an impedance controller configured to control a current flowing to the lower electrode; loading a wafer on the substrate stage; deriving an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus; determining a sheath voltage based on the equivalent circuit model, the sheath voltage corresponding to a voltage applied to a space adjacent to the wafer by a matcher current from the impedance matcher; and predicting a selectivity as a ratio between thicknesses of each of plurality of deposition portions of the layer to be formed on the wafer based on a correlation between the determined sheath voltage and a pre-stored selectivity value.

12. The method of claim 11, wherein the determining the sheath voltage comprises: controlling values of a plurality of circuit elements of the equivalent circuit model to simulate process conditions of the plasma layer deposition apparatus; determining the matcher current from the

equivalent circuit model based on a first impedance corresponding to a simulated high frequency generator, a second impedance corresponding to a simulated impedance matcher, and a third impedance corresponding to a simulated chamber portion that does not include a high frequency generator or an impedance matcher; and determining the sheath voltage from the equivalent circuit model based on the matcher current.

13. The method of claim 12, wherein the controlling values of the plurality of circuit elements comprises simulating a pressure in the chamber, the RF power supplied from the high frequency generator, and an impedance value of the impedance controller, with the equivalent circuit model.

14. The method of claim 11, wherein the predicting the selectivity comprises storing data about the sheath voltage and the pre-stored selectivity value; and deriving the selectivity based on the stored data.

15. The method of claim 11, wherein the equivalent circuit model simulates a plasma region where plasma is formed in the chamber and a plurality of sheath regions surrounding the plasma region.

16. The method of claim 15, wherein the deriving the equivalent circuit model comprises: simulating the high frequency generator with a power resistor and a power voltage; simulating the impedance matcher with a plurality of first inner capacitors and at least one first inner inductor; and simulating the impedance controller with at least one second inner capacitor and at least one second inner inductor.

17. The method of claim 15, wherein the deriving the equivalent circuit model comprises: simulating the plasma region with a plurality of plasma resistors; and simulating the plurality of sheath regions with a plurality of capacitors.

18. The method of claim 17, wherein the simulating the plurality of sheath regions with the plurality of capacitors comprises: simulating a first sheath region between the plasma region and the upper electrode with a first capacitor; simulating a second sheath region between the plasma region and the wafer with a second capacitor; and simulating a third sheath region surrounding an outer side portion of the plasma region with a third capacitor.

19. The method of claim 11, wherein the wafer comprises a first region comprising a first material and a second region comprising a second material, and wherein the predicting the selectivity comprises predicting the selectivity as a ratio between a first thickness of a first deposition portion on the first region and a second thickness of a second deposition portion on the second region.

20. A method of predicting a thickness profile of a layer, the method comprising: providing a plasma layer deposition apparatus, wherein the plasma layer deposition apparatus comprises a chamber comprising a plasma region where plasma is formed and a plurality of sheath regions surrounding the plasma region, a substrate stage in the chamber, a lower electrode, an upper electrode configured, and a source power circuit comprising a high frequency generator and an impedance matcher configured to supply a radio frequency (RF) power to the upper electrode; loading a wafer on the substrate stage, wherein the wafer comprises a first region having a first material and a second region having a second material; deriving an equivalent circuit model of a plasma system simulating the plasma layer deposition apparatus; determining a sheath voltage based on the equivalent circuit model, the sheath voltage corresponding to a voltage applied to a space adjacent to the wafer by a matcher current from the impedance matcher; and predicting a selectivity of the layer as a ratio between a first thickness of a first deposition portion to be formed on the first region and a second thickness of a second deposition portion to be formed on the second region based on the determined sheath voltage and a pre-stored selectivity value.

21.-29. (canceled)
