

(45) **Date of Patent:** \*Aug. 12, 2025

(Continued)

(52) **U.S. Cl.**  
CPC ..... ***A61B 17/025*** (2013.01); ***A61B 17/0218***  
(2013.01); ***A61B 17/3417*** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... A61B 17/025; A61B 17/0281; A61B  
2017/0268; A61B 2017/0275; A61B  
34/73; A61B 1/32  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,705,040 A \* 11/1987 Mueller ..... A61B 17/0401  
604/513

4,741,330 A 5/1988 Hayhurst  
(Continued)

*Primary Examiner* — Nicholas W Woodall

(74) *Attorney, Agent, or Firm* — Morrison & Foerster LLP

(57) **ABSTRACT**


Devices and methods are disclosed herein for accessing the hip joint. A first device can be securely attached to the capsule of a joint. The first device can tent the capsule to increase the volume of the peripheral compartment. A second device can be biased against the first device to pierce the tented capsule and create a portal. Devices and methods are also disclosed herein for distending the capsule of a joint. A distention device may access a portal established within the capsule. The distention device can expand the capsule by

(Continued)

(Continued)

US 2024/0415504 A1 Dec. 19, 2024

(63) Continuation of application No. 17/317,451, filed on May 11, 2021, now Pat. No. 11,974,736, which is a  
(Continued)



applying an expansive force within the peripheral compartment. The distention device can maintain distention of the peripheral compartment while other devices access the joint.

### 18 Claims, 65 Drawing Sheets

### Related U.S. Application Data

continuation of application No. 16/235,057, filed on Dec. 28, 2018, now Pat. No. 11,000,266, which is a continuation of application No. 15/620,901, filed on Jun. 13, 2017, now Pat. No. 10,166,020, which is a continuation of application No. 14/143,951, filed on Dec. 30, 2013, now Pat. No. 9,675,336, which is a continuation of application No. 12/961,213, filed on Dec. 6, 2010, now Pat. No. 8,617,167.

(60) Provisional application No. 61/266,785, filed on Dec. 4, 2009.

### (51) Int. Cl.

*A61B 17/34* (2006.01)  
*A61B 34/00* (2016.01)  
*A61B 34/30* (2016.01)  
*A61B 17/00* (2006.01)  
*A61B 17/04* (2006.01)  
*A61B 17/32* (2006.01)  
*A61B 18/00* (2006.01)

### (52) U.S. Cl.

CPC .... *A61B 34/73* (2016.02); *A61B 2017/00637* (2013.01); *A61B 2017/0225* (2013.01); *A61B 2017/0275* (2013.01); *A61B 2017/0409* (2013.01); *A61B 2017/0417* (2013.01); *A61B 2017/320048* (2013.01); *A61B 2017/3488* (2013.01); *A61B 2018/00273* (2013.01); *A61B 2018/00279* (2013.01)

(56)

### References Cited

#### U.S. PATENT DOCUMENTS

5,250,055 A	10/1993	Moore et al.	
5,337,736 A *	8/1994	Reddy .....	A61B 17/06109 606/191
5,362,294 A *	11/1994	Seitzinger .....	A61B 17/0218 604/11
5,407,427 A	4/1995	Zhu	
5,634,882 A *	6/1997	Gagner .....	A61B 17/02 600/209
5,906,210 A	5/1999	Herbert	
6,165,184 A	12/2000	Verdura	
6,436,098 B1	8/2002	Michelson	
6,488,691 B1	12/2002	Carroll	
6,595,911 B2 *	7/2003	LoVuolo .....	A61F 2/0063 128/DIG. 25
6,616,673 B1 *	9/2003	Stone .....	A61B 17/025 606/105
6,656,182 B1	12/2003	Hayhurst	
6,953,480 B2	10/2005	Mears	
7,244,273 B2	7/2007	Pedersen	
8,361,112 B2	1/2013	Carroll, II	
8,617,167 B2	12/2013	Weisel	
8,721,649 B2 *	5/2014	Gifford .....	A61B 17/8866 606/90
8,726,909 B2	5/2014	Cox	
8,900,243 B2 *	12/2014	Nikolchev .....	A61B 17/025 606/90
9,622,779 B2	4/2017	Horton	
9,675,336 B2 *	6/2017	Weisel .....	A61B 17/0218
2006/0293691 A1 *	12/2006	Mitra .....	A61B 17/8861 606/103
2008/0208223 A1 *	8/2008	Kraemer .....	A61B 17/82 24/712
2009/0018594 A1	1/2009	Laufer	
2009/0312807 A1	12/2009	Sutton	
2010/0160939 A1	6/2010	Braido	
2011/0040154 A1	2/2011	Reznik	
2011/0144442 A1	6/2011	Farrell et al.	

\* cited by examiner




FIG. 1




FIG. 2  
(PRIOR ART)




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F






FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F





FIG. 6A



(SECTION F-F)

FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 6F




FIG. 6G






FIG. 7A




FIG. 7B




FIG. 8A







FIG. 8B






FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D






FIG. 12E




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 15E




FIG. 15F




FIG. 16




FIG. 17B




FIG. 17A






FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23





FIG. 24








FIG. 26




FIG. 27




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 28D




FIG. 28E




FIG. 28F




FIG. 28G




FIG. 28H




FIG. 28I




FIG. 29

SIDE VIEW




FIG. 29A

FRONT VIEW




FIG. 29B




FIG. 29C




FIG. 29D

CROSS-SECTIONAL VIEWS




FIG. 29E





FIG. 29F





0306




FIG. 30A




FIG. 30B







FIG. 31






FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36A




FIG. 36B






FIG. 37




FIG. 38A




FIG. 38B




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47A






FIG. 47B








FIG. 49




FIG. 50

1

## METHODS AND DEVICES FOR ACCESSING AND RETRACTING A CAPSULE OF A JOINT

### REFERENCE TO PENDING PRIOR PATENT APPLICATIONS

This patent application is a continuation of pending prior U.S. patent application Ser. No. 17/317,451, filed May 11, 2021 by Stryker Corporation and Thomas Weisel et al. for METHODS AND DEVICES FOR ACCESSING AND RETRACTING A CAPSULE OF A JOINT, which patent application is a continuation of prior U.S. patent application Ser. No. 16/235,057, filed Dec. 28, 2018 by Stryker Corporation for METHODS AND DEVICES FOR ACCESSING AND RETRACTING A CAPSULE OF A JOINT, which patent application is a continuation of prior U.S. patent application Ser. No. 15/620,901, filed Jun. 13, 2017 by Pivot Medical, Inc. for METHODS AND DEVICES FOR ACCESSING AND RETRACTING A CAPSULE OF A JOINT, which patent application is a continuation of prior U.S. patent application Ser. No. 14/143,951, filed Dec. 30, 2013 by Pivot Medical, Inc. for METHODS AND DEVICES FOR ACCESSING AND RETRACTING A CAPSULE OF A JOINT, which in turn is a continuation of prior U.S. patent application Ser. No. 12/961,213, filed Dec. 6, 2010 by Thomas Weisel et al. for METHODS AND DEVICES FOR ACCESSING AND RETRACTING A CAPSULE OF A JOINT, which patent application claims benefit of prior U.S. Provisional Patent Application Ser. No. 61/266,785, filed Dec. 4, 2009 by Hanson S. Gifford et al. for METHODS AND DEVICES TO ACCESS A CAPSULE OF A JOINT. The six (6) above-identified patent applications are hereby incorporated herein by reference.

### FIELD OF THE INVENTION

The present invention relates to medical devices and methods for accessing a joint, and more specifically to devices and methods for providing minimally invasive access into the hip joint.

### BACKGROUND OF THE INVENTION

Obtaining arthroscopic access into orthopedic joints to perform surgical procedures can be extremely challenging. This is particularly true of the hip joint, which has two tissue barriers that must be crossed in order to gain access to the inner part of the joint. The outer barrier is known as the capsule, a series of tight overlapping ligaments surrounding the joint, effectively sealing off the hip joint from the remainder of the body. The area within the capsule is known as the peripheral compartment.

Within the peripheral compartment, the joint is fluidly sealed by a skirt-like tissue known as the labrum which is attached to the acetabular rim and hugs tightly around the base of the femoral head. The labrum/femoral head interface creates a vacuum seal within the joint which helps to hold the femoral head tightly within the acetabulum. In order to gain access to the central compartment (i.e., the portion of the joint within the labrum lying between the femoral head and acetabulum) the seal of the labrum must be broken and instruments then introduced into the very narrow opening between the bottom edge of the labrum and femoral head.

In arthroscopic surgery, access to the peripheral compartment is typically obtained through the use of elongate tubular devices (e.g., arthroscopic portals or cannulas), which are inserted through the patient's skin and through the

2

ligaments of the capsule to provide a tunnel or lumen through which instruments may be introduced. Multiple access portals are typically employed, with one access portal being used for visualization (e.g., for placement of an arthroscope), and the remaining portal(s) being available for the introduction of other instruments.

However, the creation of access portals can be problematic. For one thing, the patient's anatomy (e.g., bone, blood vessels, nerves, etc.) can greatly restrict the possible portal locations. Furthermore, some hip structures (e.g., the articular cartilage on the femoral head, the articular cartilage on the acetabular cup, etc.) can be quite delicate, thereby requiring great precision when forming the access portal so as to avoid damaging delicate structures. Additionally, some of the intervening tissue (e.g., the joint capsule) can be quite tough, thus requiring substantial force to penetrate the tissue, and thereby raising the danger of accidental plunging as an access tool breaks through the intervening tissue. Such accidental plunging increases the risk of inadvertently damaging delicate joint structures (e.g. articular cartilage).

Due to the numerous difficulties and concerns associated with forming an access portal, surgeons have traditionally resorted to a multi-step procedure for forming the access portal.

More particularly, surgeons have traditionally first passed a small needle (sometimes referred to as an access needle) down to the interior of the hip joint. This is generally done by first using external anatomical landmark and tactile feedback for needle guidance; then, as the sharp tip of access needle enters the capsule of the joint and approaches delicate structures (e.g. articular cartilage), fluoroscopy is used to carefully direct final needle placement. Inexperienced surgeons, or experienced surgeons dealing with particularly problematic cases, may also use fluoroscopy during the earlier stages of needle placement.

Next, a guidewire is placed through the lumen of the access needle, then the access needle is removed. Next, the tissue surrounding the guidewire is opened laterally by passing a series of tissue dilators over the guidewire. These dilators progressively increase in diameter so as to dilate the tissue disposed between the skin and the interior of the joint.

Once the opening from the top surface of the skin down to the interior of the joint has been established, a tubular liner (sometimes referred to as an "access cannula") is inserted over the guidewire, and the guidewire may be withdrawn from the joint. This access cannula holds the incision open and provides a surgical pathway (or "corridor") from the top surface of the skin down to the interior of the hip joint, thereby enabling instrumentation (e.g., arthroscopes, surgical instruments, etc.) to be passed through the central lumen of the access cannula so as to reach the remote surgical site within the joint.

This multi-step process requires substantial effort on the part of the surgeon, increases the instrumentation necessary for the procedure, and extends the duration of the procedure.

Surgeons have also created portals by inserting long spinal needles into the joint under fluoroscopic guidance. In order to avoid damaging the cartilage of the hip joint with the needle, the femur is distracted from the pelvis by approximately 5 to 10 millimeters to create a gap between the femoral head and the acetabulum of the pelvis. The needle is accordingly guided into the gap.

Hip distraction typically requires the use a distraction table, a surgical table that includes a post placed against the patient's perineum and a tensioning device which fastens to the patient's foot or ankle and allows high forces (e.g., 50 to 70 pounds) to be exerted on the patient's leg to distract the

femur and create space within the joint. These tables not only are large, cumbersome and expensive, but they limit the mobility of the joint during the procedure and frequently produce complications such as nerve damage.

Even with use of a distraction table, damage to the cartilage and other joint tissue may be difficult to avoid. The capsule surrounding the hip joint is significantly denser and “tougher” than tissue externally surrounding the capsule. Accordingly, a high amount of force is required to pierce the capsule, even with use of a sharp needle. However, the capsule is relatively thin, 2 to 15 millimeters, and the high amount of force required to pierce it can inadvertently cause a needle to uncontrollably “pop” through the capsule and damage tissue beyond. The space within the peripheral compartment is also relatively small for use with arthroscopic devices. Accordingly, several portals must be created to enable proper access to the joint. Each time a portal is created, the risk of unintended harm is increased.

Methods and devices have been proposed for accessing the hip joint without using a distraction table. For example, commonly assigned U.S. patent application Ser. No. 12/483,446, filed Jun. 12, 2009, entitled “Methods and Apparatus for Joint Distraction”, the entirety of which is incorporated by reference herein, discloses various internal distraction devices for distracting the hip and other joints. These devices use balloons or other expandable features placed within the central compartment to displace the femoral head further away from the acetabulum in order to allow access for surgical instruments. While such devices eliminate the need for a distraction table, challenges may still be encountered in introducing these devices into the peripheral and central compartments. Further, even where a conventional distraction table is used, the placement of portals and the introduction of instruments into the peripheral and central compartments remain challenging.

On account of the foregoing, there is a substantial need for a simpler, faster and more convenient approach for creating an access portal to the interior of the hip joint.

More particularly, there is a substantial need for a new approach for deploying an access cannula into the interior of the hip joint.

There is also a substantial need for locking an access cannula so that its distal tip is constrained within the capsule of the hip joint so as to facilitate the insertion and removal of instruments.

In addition to the foregoing, there is also a significant need for creating additional workspace once access is gained to the interior of the hip joint, whereby to afford surgeons improved visualization at the surgical site and more room to maneuver.

### SUMMARY OF THE INVENTION

These and other objects of the present invention are addressed by the provision and use of a novel method and apparatus for accessing a capsule of a joint.

More particularly, in one embodiment of the present invention, a capsule of a joint may be accessed by attaching a first device to the capsule of the joint. The capsule may then be distended by placing a second device into the capsule through a passage in the first device.

In another embodiment of the invention there is provided a system for creating a portal in a capsule of a joint. The system may include an elongated needle. The system may also include an elongated sheath with an inner surface. The inner surface may be diametrically sized to freely slide over

the elongated needle, the elongated sheath including a plurality of grasping members coupled near a distal end thereof.

Yet another embodiment of the invention provides a method for accessing a capsule of a joint. A needle may be advanced to a capsule of a joint. A sheath may be advanced over the needle to the capsule, the sheath holding an expansion device. Grasping members of the expansion device may be engaged into the capsule to secure the expansion device to the capsule. The needle may be advanced through the capsule of the joint to create a penetration therein.

Yet another embodiment of the invention provides a system for creating a portal in a capsule of a joint. The system may include an elongated needle. The system may also include an elongated sheath with an inner surface. The inner surface diametrically may be sized to freely slide over the elongated needle. The system may also include an elongated expansion device, which may include a plurality of grasping members at one end of the expansion device, the expansion device may be radially constrained by the inner surface of the elongated sheath.

Yet another embodiment of the invention provides a system for creating a portal in a capsule of a joint. The system may include an elongated needle. The system may also include an elongated sheath with an inner surface. The inner surface may be diametrically sized to freely slide over the elongated needle. The system may also include an elongated expansion device housed at the inner surface of the elongated sheath. The expansion device may have a plurality of grasping members at one end, the grasping members being biased radially inward. An inner shaft may be slidably disposed within the expansion device and sized to urge the grasping members towards radially inward when distally advanced.

Yet another embodiment of the invention provides a method for accessing a capsule of a joint. A needle may be advanced to a capsule of a joint. A sheath may be advanced over the needle to the capsule, a wall of the sheath holding grasping members constrained in a straightened configuration. The grasping members may be engaged into the capsule to secure the sheath to the capsule. The needle may be advanced through the capsule of the joint to create a penetration therein.

Yet another embodiment of the invention provides a system for creating a portal in a capsule of a joint. The system may include an elongated sheath with an inner diameter sized to freely slide over the elongated needle. The elongated sheath may include a wall with a plurality of pathways and including expandable zones between the pathways. A plurality of wires may be slidably housed within the plurality of pathways. The plurality of wires may include a plurality of hooks.

Yet another embodiment of the invention provides a method for accessing a capsule of a joint. A needle may be advanced to a capsule of a joint. A cannula may be advanced over the needle to the capsule. A first portion of the cannula may be maintained in place. A second portion of the cannula may be rotated with respect to the stationary first portion to engage grasping members of the expansion device into the capsule to secure the cannula to the capsule. The needle may be advanced through the capsule of the joint to create a penetration therein.

Yet another embodiment of the invention provides a system for accessing a capsule of a joint. The system may include an elongated inner tube including a plurality of expandable hooks. An elongated outer tube may be rotatably

5

engaged to the inner tube. The outer tube may include a plurality of slots. The plurality of expandable hooks may be slidably engaged with the plurality of slots.

Yet another embodiment of the invention provides a method for accessing a capsule of a joint. A capsule of a joint may be accessed. A cannula may be attached to the capsule of the joint. A penetration may be created in the capsule. The capsule may be distended using a distension device.

Yet another embodiment of the invention provides a system for creating a portal in a capsule of a joint. The system may include an elongated needle. An elongated cannula may be diametrically sized to freely slide over the elongated needle. The cannula may have a plurality of grasping members at one end of the expansion device. An elongated distension device may be moveably coupled to the elongated cannula.

Yet another embodiment of the invention provides a method for distending a capsule of a joint. A capsule of a joint may be accessed. A penetration through the capsule may be created. A delivery device holding a distention device may be inserted into the penetration. The distention device may be deposited into the portal and removed from the delivery device. The distention device may be activated to expand within the capsule.

Yet another embodiment of the invention provides a system for distending a capsule of a joint. The system may include a piston device. The piston device may include first and second atraumatic bumpers. One atraumatic bumper may be attached to an end of the elongate body and the other to an end of the moveable shaft. The system may include an elongated applicator including a holding device removably coupled to one of the bumpers.

Yet another embodiment of the invention provides a method for distending a capsule of a joint. A capsule of a joint may be accessed. A first portal and a second portal may be created through the capsule. A magnetic end of a first flexible strap may be guided into first portal. A magnetic end of a second flexible strap may be guided into the second portal. The magnetic ends may couple within the capsule. Either the first or second strap may be withdrawn from the capsule to place a mid-portion of the other of the first or second strap within the capsule. The non-withdrawn first or second strap may be pulled from both portals to distend the capsule away from the joint.

Yet, another embodiment of the invention provides a system for distending a capsule of a joint. The system may include a first and second cannula. The system may also include a first and second elongated strap. Each strap may be sized to slide within the first and second cannula. Each strap may include a magnetic member attached at an end of each strap configured to magnetically attract the magnetic member on the other strap.

In one preferred form of the invention, there is provided a method for accessing a capsule of a joint, the method comprising:

- accessing a capsule of a joint;
- attaching a first device to the capsule of the joint;
- distending the capsule; and
- placing a second device into the capsule through a passage in the first device.

In another preferred form of the invention, there is provided a system for creating a portal in a capsule of a joint, the system comprising:

- an elongated needle; and
- an elongated sheath with an inner surface, the inner surface diametrically sized to freely slide over the

6

elongated needle, the elongated sheath including a plurality of grasping members coupled near a distal end thereof.

In another preferred form of the invention, there is provided a method for accessing a capsule of a joint, the method comprising:

- advancing a needle to a capsule of a joint;
- advancing a sheath over the needle to the capsule, the sheath holding an expansion device;
- engaging grasping members of the expansion device into the capsule to secure the expansion device to the capsule; and
- advancing the needle through the capsule of the joint to create a penetration therein.

In another preferred form of the invention, there is provided a system for creating a portal in a capsule of a joint, the system comprising:

- an elongated needle;
- an elongated sheath with an inner surface, the inner surface diametrically sized to freely slide over the elongated needle; and
- an elongated expansion device including a plurality of grasping members at one end of the expansion device, the expansion device being radially constrained by the inner surface of the elongated sheath.

In another preferred form of the invention, there is provided a system for creating a portal in a capsule of a joint, the system comprising:

- an elongated needle;
- an elongated sheath with an inner surface, the inner surface diametrically sized to freely slide over the elongated needle;
- an elongated expansion device housed at the inner surface of the elongated sheath, the expansion device including a plurality of grasping members at one end, the grasping members being biased radially inward; and an inner shaft slidably disposed within the expansion device and sized to urge the grasping members radially outward when distally advanced.

In another preferred form of the invention, there is provided a method for accessing a capsule of a joint, the method comprising:

- advancing a needle to a capsule of a joint;
- advancing a sheath over the needle to the capsule, a wall of the sheath holding grasping members constrained in a straight configuration;
- engaging the grasping members into the capsule to secure the sheath to the capsule; and
- advancing the needle through the capsule of the joint to create a penetration therein.

In another preferred form of the invention, there is provided a system for creating a portal in a capsule of a joint, the system comprising:

- an elongated sheath with an inner diameter sized to freely slide over the elongated needle, the elongated sheath including a wall with a plurality of pathways and including expandable zones between the pathways; and
- a plurality of wires slidably housed within the plurality of pathways, the plurality of wires including a plurality of hooks.

In another preferred form of the invention, there is provided a method for accessing a capsule of a joint, the method comprising:

- advancing a needle to a capsule of a joint;
- advancing a cannula over the needle to the capsule;
- maintaining a first portion of the cannula in place;

7

rotating a second portion of the cannula with respect to the stationary first portion to engage grasping members of the expansion device into the capsule so as to secure the cannula to the capsule; and  
 advancing the needle through the capsule of the joint to create a penetration therein.

In another preferred form of the invention, there is provided a system for accessing a capsule of a joint, the system comprising:

an elongated inner tube including a plurality of expandable hooks; and  
 an elongated outer tube rotatably engaged to the inner tube, the outer tube including a plurality of slots, the plurality of expandable hooks being slidably engaged with the plurality of slots.

In another preferred form of the invention, there is provided a method for accessing a capsule of a joint, the method comprising:

accessing a capsule of a joint;  
 attaching a cannula to the capsule of the joint;  
 creating a penetration in the capsule; and  
 distending the capsule using a distension device.

In another preferred form of the invention, there is provided a system for creating a portal in a capsule of a joint, the system comprising:

an elongated needle;  
 an elongated cannula diametrically sized to freely slide over the elongated needle, the cannula including a plurality of grasping members at one end of the expansion device; and an elongated distension device moveably coupled to the elongated cannula.

In another preferred form of the invention, there is provided a method for distending a capsule of a joint, the method comprising:

accessing a capsule of a joint;  
 creating a penetration through the capsule;  
 inserting a delivery device holding a distention device into the penetration;  
 depositing the distention device into the portal and removing the delivery device; and  
 activating the distention device to expand within the capsule.

In another preferred form of the invention, there is provided a system for distending a capsule of a joint, the system comprising:

a piston device comprising:  
 an elongate body, a moveable shaft extending from the elongate body;  
 first and second atraumatic bumpers, one atraumatic bumper being attached to an end of the elongate body and the other to an end of the moveable shaft; and  
 an elongated applicator, the elongated applicator including a holding device removably coupled to one of the bumpers.

In another preferred form of the invention, there is provided a method for distending a capsule of a joint, the method comprising:

accessing a capsule of a joint;  
 creating a first portal and a second portal through the capsule;  
 guiding a magnetic end of a first flexible strap into the first portal;  
 guiding a magnetic end of a second flexible strap into the second portal, the magnetic ends coupling within the capsule;

8

withdrawing either the first or second strap from the capsule to place a mid-portion of the other of the first or second strap within the capsule; and  
 pulling on the non-withdrawn first or second strap from both portals to distend the capsule away from the joint.

In another preferred form of the invention, there is provided a system for distending a capsule of a joint, the system comprising:

first and second cannulas; and  
 first and second elongated straps, each strap sized to slide within the first and second cannula, each strap including a magnetic member attached to an end of the strap configured to magnetically attract the magnetic member on the other strap.

In another preferred form of the invention, there is provided an apparatus for accessing the interior of a joint and creating additional work space within the interior of a joint, the apparatus comprising:

an elongated shaft having a distal end and a proximal end, and a lumen extending between the distal end and the proximal end; and  
 an elongated sleeve for disposition over the elongated shaft, the elongated sleeve having a distal end and a proximal end and a lumen extending between the distal end and the proximal end, wherein the distal end of the elongated shaft comprises an expandable collar.

In another preferred form of the invention, there is provided a method of accessing the interior of a joint and creating additional work space within the interior of a joint, the method comprising:

providing an apparatus comprising:  
 an elongated shaft having a distal end and a proximal end, and a lumen extending between the distal end and the proximal end; and  
 an elongated sleeve for disposition over the elongated shaft, the elongated sleeve having a distal end and a proximal end and a lumen extending between the distal end and the proximal end, wherein the distal end of the elongated shaft comprises an expandable collar;

passing the apparatus into the joint so that the distal end of the elongated sleeve is positioned on the interior of a capsule of a joint;

expanding the expandable collar; and  
 tenting the capsule so as to create additional work space within the capsule of the joint.

In another preferred form of the invention, there is provided an apparatus for retracting a capsule of a joint, the apparatus comprising:

a length of suture; and  
 an anchor attached to one end of the length of suture.

In another preferred form of the invention, there is provided a method of retracting a capsule of a joint, the method comprising:

providing a length of suture and an anchor attached to one end of the length of suture, wherein the anchor comprises a body which is configured to assume (i) a first, folded configuration when the body is in a stressed condition, and (ii) a second, straight configuration when the body is in an unstressed condition;  
 loading the suture and the anchor into a sheath so that the anchor assumes its first folding configuration;  
 passing the sheath into the capsule of a joint;  
 pushing the anchor through the sheath and into the capsule of the joint so that as the anchor passes into the joint, the anchor assumes its second, straight configuration;

positioning the anchor against the interior surface of the capsule; and  
pulling the length of suture proximally so as to retract the capsule of the joint.

In another preferred form of the invention, there is provided an apparatus for retracting a capsule of a joint, the apparatus comprising:

an elongated rod having a proximal end and a distal end; and

a retraction element disposed on the distal end of the elongated rod.

In another preferred form of the invention, there is provided a method of retracting a capsule of a joint, the method comprising:

providing an elongated rod having a proximal end and a distal end and a retraction element disposed on the distal end of the elongated rod;

wherein the retraction element comprises a pivoting distal end, and further wherein the pivoting distal end may be pivoted between (i) a first position in which the distal end is aligned with the longitudinal axis of the elongated shaft, and (ii) a second position in which the distal end extends at an angle to the longitudinal axis of the elongated rod;

pivoting the distal end of the elongated rod into the first position;

passing the elongated rod into the capsule of a joint so that the distal end of the elongated rod is positioned within the interior of the joint;

pivoting the distal end of the elongated rod into the second position;

positioning the distal end of the elongated rod against the interior of the capsule; and

pulling the elongated rod proximally so as to retract the capsule of the joint.

In another preferred form of the invention, there is provided a method of retracting a capsule of a joint, the method comprising:

providing an elongated rod having a proximal end and a distal end and a retraction element disposed on the distal end of the elongated rod;

wherein the retraction element comprises a projection, and further wherein the projection may be moved between (i) a first position in which the projection is aligned with the longitudinal axis of the elongated shaft, and (ii) a second position in which the projection extends at an angle to the longitudinal axis of the elongated rod;

moving the projection into the first position;

passing the elongated rod into the capsule of a joint so that the distal end of the elongated rod is positioned within the interior of the joint;

moving the projection into the second position; and

positioning the elongated rod against the interior of the capsule and positioning the projection of the elongated rod against the neck of the femur so as to retract the capsule of the joint.

In another preferred form of the invention, there is provided a method of retracting a capsule of a joint, the method comprising:

providing an elongated rod having a proximal end and a distal end, the distal end comprising a retraction element;

wherein the retraction element comprises a corkscrew;

passing the elongated rod into the capsule of a joint so that the distal end of the elongated rod is positioned on the capsule;

rotating the elongated rod so as to pass the corkscrew through the capsule; and  
pulling the elongated rod proximally so as to retract the capsule of the joint.

In another preferred form of the invention, there is provided a method of retracting a capsule of a joint, the method comprising:

providing a length of suture and an anchor attached to one end of the length of suture;

loading the suture and the anchor into a sheath;

passing the sheath into the capsule of a joint;

pushing the anchor through the sheath into the capsule of the joint so that the anchor is positioned on the interior of the capsule, with the suture extending from the anchor; and

pulling the length of suture proximally so as to retract the capsule of the joint.

In another preferred form of the invention, there is provided a method of retracting a capsule of a joint and maintaining the retraction of the capsule of the joint, the method comprising:

providing a length of suture;

providing a cannula having a distal end for positioning in the joint and a proximal end comprising a projection for securing a length of suture;

passing the length of suture through the capsule of the joint so that two free ends of suture extend through the cannula;

pulling the length of suture proximally so as to retract the capsule of the joint; and

securing the length of suture around the projection so as to maintain the retraction of the capsule of the joint.

In another preferred form of the invention, there is provided a method of retracting capsule of a joint, the method comprising:

providing an elongated rod having a proximal end and a distal end, the distal end comprising a hook;

forming a cut in the capsule;

passing the hook of the elongated rod under one side of the cut capsule; and

pulling the elongated rod proximally so as to retract the capsule.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and features of the present invention will be more fully disclosed or rendered obvious by the following detailed description of the invention, which is to be considered together with the accompanying drawings wherein like numbers refer to like parts and further wherein:

FIG. 1 is a simplified cross-sectional view of a hip joint;

FIG. 2 is a simplified cross-sectional view of a hip joint undergoing a prior art method for distracting a femoral head from an acetabulum;

FIG. 3 is a simplified cross-sectional view of a hip joint;

FIG. 4A is a cross-sectional view of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIGS. 4B-4F are cross-sectional views of a hip joint being accessed by a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIGS. 5A and 5B are cross-sectional and side views of a system for accessing the capsule of a joint, according to an embodiment of the invention;



## 11

FIGS. 5C-5F are partial cross-sectional views of a hip joint being accessed by a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIG. 6A is a side cross-sectional view of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIGS. 6B and 6C are longitudinal cross-sectional and partial side views, respectively, of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIG. 6D is a longitudinal cross-sectional view of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIG. 6E is a partial perspective view of a grasping device, according to an embodiment of the invention;

FIG. 6F is a partial side view of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIG. 6G is a side view of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIGS. 7A and 7B are side and longitudinal cross-sectional views, respectively, of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIGS. 8A and 8B are side-perspective and cross-sectional views, respectively, of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIGS. 9A-9C are partial side views of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIG. 10A is a partial side cross-sectional view of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIG. 10B is partial side views of grasping devices, according to embodiments of the invention;

FIGS. 10C and 10D are longitudinal cross-sectional and partial side views, respectively, of a system for accessing the capsule of a joint, according to an embodiment of the invention;

FIGS. 11A and 11B are side views of systems for distending a capsule of a joint, according to embodiments of the invention;

FIG. 11C is a partial cross-sectional view of a hip joint being distended by a system for distending a capsule of a joint, according to an embodiment of the invention;

FIGS. 12A-12E are partial side views of systems for distending a capsule of a joint, according to embodiments of the invention;

FIG. 13A is a cross-sectional view of a device for distending a capsule of a joint, according to an embodiment of the invention;

FIG. 13B is a side view of a system for distending a capsule of a joint, according to an embodiment of the invention;

FIG. 13C is a partial cross-sectional view of a hip joint being distended by a device for distending a capsule of a joint, according to an embodiment of the invention;

FIG. 14A is a cross-sectional view of a system for distending a capsule of a joint, according to an embodiment of the invention;

FIG. 14B is a partial cross-sectional view of a hip joint being distended by a system for distending a capsule of a joint, according to an embodiment of the invention;

FIG. 15A is a side view of a system for distending a capsule of a joint, according to an embodiment of the invention;

## 12

FIGS. 15B-15F are partial cross-sectional views of a hip joint being distended by a system for distending a capsule of a joint, according to an embodiment of the invention;

FIGS. 16-19 are schematic views of a locking access cannula, according to an embodiment of the invention;

FIGS. 20-24 are schematic views of a method of using the access cannula of FIGS. 16-19;

FIG. 25 is a schematic view of a tensioning access cannula, according to an embodiment of the invention;

FIGS. 26 and 27 are schematic views of a method of using the tensioning access cannula of FIG. 25;

FIGS. 28A-28E are schematic views of a device for retracting the capsule of a joint, according to an embodiment of the invention;

FIGS. 28F-28I are schematic views of a method of using the device of FIGS. 28A-28E to retract the capsule of a joint, according to an embodiment of the invention;

FIGS. 29 and 29A-29D are schematic views of a device for retracting the capsule of a joint, according to an embodiment of the invention;

FIGS. 29E and 29F are schematic views of a method of using the device of FIGS. 29 and 29A-29D to retract the capsule of a joint, according to an embodiment of the invention;

FIG. 30 is a schematic view of a device for retracting the capsule of a joint, according to an embodiment of the invention;

FIGS. 30A and 30B are schematic views of a method of using the device of FIG. 30 to retract the capsule of a joint, according to an embodiment of the invention;

FIG. 31 is a schematic view of a device for retracting the capsule of a joint, according to an embodiment of the invention;

FIGS. 31A-31C are schematic views of a method of using the device of

FIG. 31 to retract the capsule of a joint, according to an embodiment of the invention;

FIG. 32 is a schematic view of a device for retracting the capsule of a joint, according to an embodiment of the invention;

FIGS. 33-38B are schematic views of a method of using the device of FIG. 32 to retract a capsule of a joint, wherein FIGS. 35 and 38 are schematic views taken from the outside of the capsule;

FIGS. 39-48 are schematic views of a method of using the device of FIG. 32 to close the capsule of a joint, wherein FIGS. 39-44 and 46-47B are cross-sectional views of the joint and FIGS. 45, 47C and 48 are schematic views taken from the outside of the capsule; and

FIGS. 49 and 50 are schematic views of devices for retracting a capsule of a joint, according to an embodiment of the invention.

#### DETAILED DESCRIPTION OF THE INVENTION

Devices and methods are disclosed herein for accessing the hip joint. The devices described herein can provide safely made portals within the capsule for access to the peripheral compartment by other devices. For example, the devices described herein generally provide access to the peripheral compartment by grasping and securely engaging the capsule with a first device, typically a cannula or sheath. The first device is secured enough to enable the first device to pull the capsule away from the joint and "tent" of the capsule. Tenting the capsule creates a larger volume within the peripheral compartment. A second device, typically a

13

needle, can then be biased against the first device to apply a piercing force against the tented capsule. The use of counter-traction against the first device allows the second device to be advanced into the capsule in a controlled manner to avoid “popping” uncontrollably into the peripheral compartment. Tenting of the capsule also provides an additional safety margin by providing extra space between the capsule and the tissue beyond it for the second device to traverse. The devices and methods herein do not require the use of a traction table to safely pierce the capsule.

Devices and methods are also disclosed herein for distending the capsule of a joint to enlarge the working area within the peripheral compartment. For example, a distension device can access the peripheral compartment after a safely made portal has been established as described herein. A distension device can then apply an expansive force within the peripheral compartment to distend and stretch the capsule. Accordingly, the peripheral compartment becomes enlarged which allows for better access by other surgical devices. In some embodiments, the distension device can continually distend the peripheral compartment while other devices access the joint. Distension of the capsule can allow for fewer portals to be established into the capsule, as greater working space is created. It should be understood that the devices of the invention may be useful for access into other joints besides the hip, such as the shoulder, knee, or ankle. It should also be understood that devices of the invention are useable in conjunction with visual guidance systems such as fluoroscopy and arthroscopy systems.

FIG. 1 illustrates the basic anatomy of a hip joint. The hip joint is formed between the head of the femur FH and the acetabulum A, a concave surface of the pelvis. The acetabular fossa AF is a recessed region in the acetabulum. A blanket of ligaments covers the joint forming a capsule C. Additionally, the acetabular labrum L, a fibrocartilaginous lip, surrounds the head of the femur, deepens the joint pocket and increases the surface area of contact. Labrum L divides the hip joint into two compartments within the joint capsule: a central compartment CC and a peripheral compartment PC. Central compartment CC is within the confines of labrum L and contains the majority of the joint cartilage and the ligamentum teres LT, a ligament attached to a depression in the acetabulum (the acetabular notch or fossa) and a depression on the femoral head (the fovea of the head). Peripheral compartment PC is everything outside the labrum and within the capsular ligaments C. The central compartment CC is generally not visible until the joint has been distracted.

FIG. 2 illustrates how traction 204 is conventionally applied to a patient's leg and against a post 202 positioned against the perineum region to distract femoral head FH away from acetabulum A, thereby creating a space 206 between the two joint surfaces. This space 206 allows a surgeon to access the joint and perform diagnostic or therapeutic procedures.

FIG. 3 illustrates some of the possible entry portals for delivering instruments into the hip joint. FIG. 3 is a top view of a hip joint in which femoral head FH rests against acetabulum A. The joint space is covered by capsule C and labrum L. Access into the joint may be obtained by introducing instruments through a posterolateral portal PLP along a side and posterior to the joint or an anterolateral portal ALP along a side and anterior to the joint.

#### Peripheral Compartment Access

FIG. 4A illustrates a system 400 for accessing the capsule of a joint. The system 400 includes an elongated needle 402.

14

As used herein, “needle” may encompass various devices for penetrating the capsular tissue, and is meant to include a variety of puncturing devices including, for example, trocars, coring (hollow) needles, non-coring (solid) needles, and stylet/needle combinations, as well as blunt-tipped instruments such as dilators or tubular devices. Needle 402 may be a commercially available 18-27 gauge spinal needle. Needle 402 may be constructed from a metal (e.g., stainless steel) or a polymer. Needle 402 may include one or more lumens fluidly connected to one or more openings in or near a distal tip 404. Distal tip 404 may include one or more bevels. Needle 402 may include a sensor, such as a strain gauge or load cell, functionally coupled to an interior or exterior portion of the needle.

Needle 402 may include an enlarged proximal member 406. Enlarged proximal member 406 may be a comparatively enlarged mass of material (e.g., a flange) with respect to a central portion 408 of needle 402. Proximal member 406 and/or central portion 408 may include threaded portions. Proximal member 406 may also be a fluidic connector, such as a Luer connector, in fluid communication with one or more lumens and respective distal openings. If a sensor is included with the needle, the sensor may be electrically connected to an electrical connector of proximal member 406.

System 400 also includes a cannula or elongated sheath 410. Sheath 410 includes a cylindrical body 412 with an inner surface 414. Inner surface 414 may be diametrically sized to enable needle 402 and sheath 410 to freely slide with respect to each other along longitudinal direction A-A. Inner surface 414 may include threads 415 which may threadably engage with a portion of needle 402. Inner surface 414 may be diametrically sized to allow other cylindrical devices, such as cannulas, sheaths, stents, etc., to fit between needle 402 and inner surface 414. Inner surface 414 may have a diameter ranging from 2 to 15 millimeters. Sheath 410 may be constructed from a metal (e.g., stainless steel) or a polymer. Sheath 410 includes a proximal flange 416 which extends circumferentially from cylindrical body 412. Sheath 410 may have an overall length of 50 to 150 millimeters.

A distal end 418 of sheath 410 includes a plurality of grasping members 420. Sheath 410 includes at least two opposed grasping members 420, and may include more (e.g., 3 to 20) grasping members 420. Grasping members 420 are circumferentially spaced with respect to cylindrical body 412 in an even manner. Grasping members 420 may extend in an approximate radial direction B-B, which is tangent to directions A-A, from cylindrical body 412. Grasping members 420 may also extend in an approximate tangential direction C-C, which is tangent to directions A-A and B-B, from cylindrical body 412. The grasping members may also extend in directions between directions A-A, B-B, and C-C.

Grasping members 420 may be configured as hooks or barbs. Grasping members 420 may fixedly extend from distal end 418 or be retractable and extendable within or along proximal end 418. Portions of grasping members 420 may slidably extend within cylindrical body 412 to proximal flange 416. Grasping members 420 may be constructed from a metal (e.g., stainless steel, shape-memory or super elastic nitinol (Ni—Ti)) or a polymer. Grasping members 420 may be part of a greater structure, such as a sheath or stent, internally or externally coupled to sheath 410.

FIGS. 4B-4F illustrate a method of use for system 400, for accessing and penetrating the capsule of a joint. In FIG. 4B, an incision is made in the skin and needle 402 is used to penetrate the outer tissue surrounding capsule C. Needle 402

## 15

may be placed in various portal access locations, such as the anterolateral, distal-anterolateral and anterior locations. Needle **402** is then maintained at the surface of the capsule. Optionally, needle **402** may partially or fully penetrate the capsular tissue.

In FIG. **4C**, sheath **410** is advanced over needle **402** to the surface of capsule **C**. In FIG. **4D**, grasping members **420** engage capsule **C** by penetrating into capsule **C** to securely attach sheath **410**. Grasping members **420** may engage capsule **C** by actuation of grasping members **420** at proximal flange **416** and/or by physical manipulation (e.g., rotating or pushing) of cylindrical body **412**. Needle **402** may be replaced by a different needle more suitable for penetrating capsule **C**, such as a specialized trocar, or an additional cutting sheath may supplement needle **402**, for example by inserting the cutting sheath between needle **402** and sheath **410**.

In FIG. **4E**, sheath **410** is pulled away from the joint as shown by the directional arrows and maintained in that position. This causes capsule **C** to tent away from femoral head **FH** and increase the volume of peripheral compartment **PC**.

In FIG. **4F**, needle **402** is used to penetrate capsule **C**. Needle **402** is advanced while sheath **410** tents capsule **C** by pulling sheath **410** away from femoral head **FH**. Needle **402** is unlikely to damage tissue underneath capsule **C**, as a significant gap is created between capsule **C** and femoral head **FH**. Accordingly, “popping” through capsule **C** and damaging tissue beyond is minimized. Needle **402** may threadably engage sheath **410**, and be turned to advance through capsule **C**, which results in a controlled rate of penetration. If a sensor is present on needle **402**, the sensor can provide an electrical signal to an indication system which indicates penetration of capsule **C** by a visual or aural indicator. Optionally, a distention fluid, such as saline, may be injected into peripheral compartment **PC** through needle **402** to distend capsule **C**.

FIGS. **5A** and **5B** illustrates another system **500** for accessing the capsule of a joint. System **500** includes a tear away cannula or sheath **502**. Sheath **502** is similarly configured to sheath **410**. Sheath **502** has an inner lumen **504** in which is placed an expansion device **506**, which is shown partially extending from sheath **502** (not shown). Before use, expansion device **506** is completely withdrawn within sheath **502**. Expansion device **506** may be constructed similarly to a stent. Expansion device **506** includes a plurality of struts **508** connected by a plurality of expandable members **510**. A plurality of grasping members **512** configured as tangential hooks are connected to struts **508**. Other configurations of grasping members **512** may be used, as disclosed elsewhere herein. Expansion device **506** may be constructed from a metal, such as a shape memory or super elastic Ni—Ti, or a stainless steel.

FIG. **5B** shows system **500** in an expanded configuration. A second cannula or sheath **514** is configured to slidably fit within expansion device **506**. Expansion device **506** may be diametrically sized in an expanded configuration such that sheath **502** may be used as second sheath **514**. A trocar **516** is slidably coupled with sheath **514**. Trocar **516** includes a cutting tip **518**. Cutting tip **518** may have a pyramid shape with a plurality of sharpened edges **520**. Stylet **522** is slidably coupled within trocar **516**. Stylet **522** includes a blunt distal tip **524** which extends past cutting tip **518**.

FIGS. **5C–5F** illustrate a method of use for system **500**, for accessing and penetrating the capsule of a joint. In FIG. **5C**, sheath **502** has been slightly withdrawn to expose grasping members **512** of expansion device **506**. Grasping members

## 16

**512** fixedly engage with capsule **C** by rotating the exposed grasping members **512** into capsule **C**. Needle **402** is then advanced relative to sheath **502** to puncture capsule **C** while sheath **502** tents capsule **C** by pulling sheath **502** away from femoral head **FH**. Grasping members **512** may exert a diametric expansion force on the capsule to expand and maintain the puncture site. Needle **402** may be used to inject capsule **C** with saline **530** to pressurize and distend capsule **C**. Needle **402** and sheath **502** may then be withdrawn from system **500**.

In FIG. **5D**, expansion device **506** is fully expanded after sheath **502** has been removed. Stylet **522** is exchanged with needle **402** to enlarge and maintain the opening created by needle **402**. Blunt distal tip **524** prevents damage to tissue beyond capsule **C**.

In FIG. **5E**, sheath **514** and trocar **516** are introduced over stylet **522** and through expansion device **506**. In FIG. **5F**, sheath **514** and trocar **516** are advanced to penetrate capsule **C**. Prior puncturing of capsule **C** by needle **402** and stylet **522** allows trocar **516** to easily penetrate capsule **C** and expand the opening. Blunt distal tip **524** of stylet **522** prevents damage to tissue beyond capsule **C**, while trocar **516** is advanced. Trocar **516** and stylet **522** may then be removed to allow access by other devices through sheath **514**.

FIG. **6A** illustrates a cannula or sheath **600**, which may be used in conjunction with the systems disclosed herein. Sheath **600** includes a cylindrical body **602**, a plurality of pathways **604** and a flange **606**. A distal end **607** of cylindrical body **602** may be tapered. Pathways **604** extend axially within the sidewall of sheath **600** from its proximal end to its distal end. Sheath **600** may be constructed from a metal or a polymer material. Sheath **600** may be constructed as an expandable stent and include expandable zones between pathways **604**. Pathways **604** may be circular or rectangular lumens.

A plurality of grasping members **610** are slidably housed within pathways **604**. Grasping members **610** may comprise elongated needles with precurved distal ends **612**. Distal ends **612** may be precurved to extend as hooks in an approximate inward or outward radial direction, tangential direction, or directions therebetween. Grasping members **610** may include respective proximal flanges **614**. Proximal flanges **614** may be connected to each other by e.g., a ring-shaped member or slide independently from each other. Grasping members **610** may be constructed from a metal (e.g., stainless steel, shape-memory or super elastic Ni—Ti) or a polymer. Grasping members **610** may have circular or rectangular cross-sections.

In use, sheath **600** is used for securing to a capsule in accordance with the methods disclosed herein. Distal ends **612** of grasping members **610** may secure to the capsule by moving proximal flanges **614** in a distal direction such that distal ends **612** of grasping members **610** extend from pathways **604** and assume a precurved hook shape to securely engage capsule **C**. Distal ends **612** of grasping members **610** may disengage from capsule **C** by moving proximal flanges **614** in a proximal direction away from flange **606** of sheath **600**. Accordingly, distal ends **612** of grasping members **610** will disengage from capsule **C** and withdraw back into pathways **604**.

FIGS. **6B** and **6C** illustrate a sheath **600b** according to an alternative construction of sheath **600**. Sheath **600b** includes a plurality of circumferentially expandable members **616** connected to axial struts **618**. Struts **618** may house pathways **604** through which grasping members **610** (shown in FIG. **6A**) slidably extend. Alternatively, precurved distal

17

ends **612** may be welded or otherwise fixed to the distal ends of axial struts **618**. Sheath **600b** may be constructed from a malleable, elastic, super-elastic, or shape-memory material biased into a radially expanded configuration.

In use, sheath **600b** may be used as described with respect to sheath **600**. Sheath **600b** may first engage capsule **C** and then apply tension to capsule **C** by expanding expandable members **616**. Sheath **600b** may also combine the functionality of expansion device **506** and sheath **514**, and be used in a similar manner to expand and maintain a passage in capsule **C**. Alternatively, sheath **600b** may be placed within a tubular cannula or portal and allowed to expand against the inner wall thereof to hold it in place. Precurved distal ends **612** may extend distally of the distal end of sheath **600b** and be used to grasp the capsular tissue to retain the cannula therein. Expandable members **616** may alternatively be a malleable material and expanded by applying internal force to sheath **600b**, for example by expanding a balloon therein. Alternatively, expandable members **616** may be expanded by applying heat, in the case of shape-memory material, or by disengaging from a constrained configuration, in the case of an elastic or super-elastic material.

FIGS. **6D-6F** illustrate a sheath **600c** according to an alternative construction of sheath **600**. Sheath **600c** includes an extruded cylindrical body **602c** with a plurality of longitudinal pathways **604c** configured in cross-section as rectangular slots. Pathways **604c** have an approximately rectangular cross-section and are partially open along the outer surface of cylindrical body **602c**. Pathways **604c** slidably house a plurality of grasping members **610c** (FIGS. **6E** and **6F**).

Grasping members **610c** are constructed from flattened wire and include precurved distal ends **612c**. Precurved distal ends **612c** are configured as flattened hooks.

In use, sheath **600c** may be used as described with respect to sheath **600**.

FIG. **6G** illustrates a sheath **600e** according to an alternative construction of sheath **600**. Sheath **600e** shares the general construction of sheath **600**. Sheath **600e** includes a proximally located threaded section **620** on a cylindrical body **602** which threadably couples to a cap **622**. Grasping members **610** are joined by a proximally located ring **624**, which is proximal to threaded section **620**. A compression spring may be coupled between threaded section **620** and ring **624**. Cap **622** may have a proximal opening. Cap **622** is diametrically sized to fit over and to be rotatable relative to ring **624**. Cap **622** may be coupled to ring **624** so the two move axially together as the cap is screwed in. Cap **622** may comprise a shaped knob. A flange may be distally located from threaded section **620** on cylindrical body **602**. The cap may be turned manually, or an electrical motor, control circuitry, and user interface may be functionally coupled to drive cap **622**.

In use, sheath **600e** may be used as described with respect to sheath **600**. Cap **622** is coupled to threaded section **620** and turned, which causes cap **622** to move in a distal direction. As cap **622** is turned, it will eventually contact ring **624**, or if cap **622** is fixedly attached to ring **624**, cap **622** and ring **624** will move in unison. Accordingly, cap **622** moves ring **624** in the distal direction while being turned to cause grasping members **610** to move within pathways **604**, and eventually cause distal ends **612** of grasping members **610** to extend out of cylindrical body **602** and engage capsule **C**. Cap **622** may be turned to move in a proximal direction to cause grasping members **610** to withdraw into cylindrical body **602** and disengage from capsule **C**. While distal ends

18

**612** are shown as being precurved inwardly, they may also be precurved in a radially-outward direction, or in a tangential direction.

FIGS. **7A** and **7B** illustrate a system **700** for accessing the capsule of a joint. System **700** includes a cannula or sheath **702**, generally constructed as the sheaths disclosed herein. Sheath **702** includes a cylindrical body **704** and a flange **706**. Sheath **702** may include a proximally located threaded section **708**.

An expansion device **710** is disposed within the inner lumen of sheath **702**. Expansion device **710** includes a plurality of grasping members **714** which are biased radially inwardly. Grasping members **714** include elongated axial shafts **715** and respective distal ends **716** located externally to sheath **702** at the distal end thereof. Distal ends **716** of grasping members **714** may be configured as L-shaped hooks arranged to point radially outwardly. Grasping members **714** may be malleable, or resilient and biased radially inwardly. Proximal sections **718** of grasping members **714** may be fixedly attached to inner surface **712** of cylindrical body **704** of sheath **702**, or grasping members **714** may be interconnected to create a tubular structure removably positionable in the lumen of sheath **702**.

An inner shaft **720** is slidably disposed within expansion device **710**. Inner shaft **720** is constructed as an elongated tube. Inner shaft **720** can include a threaded section **722** which threadably couples with threaded section **708** of sheath **702**. Alternatively, inner shaft **720** can freely slide within sheath **702**. Inner shaft **720** includes a flange **724**, which may be configured as a knob.

In use, system **700** can generally be used with a needle as described in the methods disclosed herein. The distal tip of sheath **702** is first advanced through a penetration in the capsule, which may be formed using a needle or trocar point placed through the inner lumen of inner shaft **720**. Sheath **702** may then be securely attached to the capsule by advancing inner shaft **720** with respect to sheath **702**. Turning flange **724** causes threaded section **722** to move in a distal direction, or in the case where no threaded sections are present, flange **724** can be simply slid towards flange **706**. Distal movement of inner shaft **720** eventually causes inner shaft **720** to displace grasping members **714** radially outwardly. In turn, distal ends **716** expand in a radial direction to securely engage the interior wall of the capsule **C**.

FIGS. **8A** and **8B** illustrate a cannula construction which may be used in conjunction with the systems disclosed herein. Sheath **800** includes a plurality of fixedly and distally attached grasping members **802**. Grasping members **802** are configured as inwardly spring-biased hooks, as shown in FIG. **8A**. Grasping members **802** may be constructed from a resilient, shape memory or super-elastic material, such as Ni—Ti. An inner tube **804** is slidably disposed within sheath **800**, and outwardly displaces grasping members **802** in one configuration as shown in FIG. **8B**.

In use, sheath **800** can generally be used in the manner described elsewhere in connection with the methods disclosed herein. Sheath **800** securely attaches to a capsule of a joint by withdrawing inner shaft **804** with respect to sheath **800**. Proximal movement of inner shaft **804** allows grasping members **802** to move from the configuration shown in FIG. **8B** to the configuration shown in FIG. **8A**. Accordingly, when inner shaft **804** releases grasping members **802**, grasping members **802** securely engage capsule **C**. A needle or other instrument can then be inserted through sheath **800** to puncture capsule **C**.

FIGS. **9A-9C** illustrate a cannula construction which may be used in conjunction with the systems disclosed herein. An

19

elongated stent **900** includes a plurality of struts **902** and resilient circumferentially expandable and contractible bands **904**. Struts **902** include a plurality of respective grasping members **906** configured as inwardly spring-biased hooks, as shown in FIG. 9A. Elongated stent **900** may be constructed from a super-elastic material, such as Ni—Ti. Elongated strut **900** is coupled to a cannula or sheath **908**. Sheath **908** is generally constructed as the sheaths disclosed herein. A plurality of travel limiters **910** may extend from sheath **908**. Elongated stent **900** is biased into a radially contracted configuration and is coupled to sheath **908** by forcibly expanding elongated stent **900** and inserting sheath **908** therein, as shown in FIG. 9B. Accordingly, elongated stent **900** securely holds onto sheath **908**.

In use grasping members **906** securely attach to the capsule of a joint by placing sheath **908** into contact with the outer surface of the capsule, and advancing elongated stent **900** relative to sheath **908**. When grasping members **906** have cleared the distal end of sheath **908**, grasping members **906** are allowed to move from the configuration shown in FIG. 9B to the configuration shown in FIG. 9C. Accordingly, when sheath **908** releases grasping members **906**, grasping members **906** securely engage capsule C. Travel limiters **910** prevent further movement of elongated stent **900** with respect to sheath **908**. A needle or other instrument can then be placed through sheath **908** to puncture capsule C and perform procedures therein.

FIGS. 10A-10D illustrate a cannula construction which may be used in conjunction with the systems disclosed herein. A cannula or sheath **1000** includes an elongated inner tube **1005** including a plurality of radial arranged grasping members **1010** extending therefrom. Grasping members **1010** may be constructed from a resilient or malleable material and include tapered, straight/flat, or duckbill configurations as shown from top to bottom in FIG. 10B. An outer tube **1015** is rotatably engaged over inner tube **1005**. Outer tube **1015** includes a plurality of slots **1020** (FIG. 10D) which are slidably engaged with grasping members **1010**. Outer tube **1015** is diametrically sized to fit over inner tube **1005** and rotationally movable from a first position in which grasping members **1010** are radially collapsed, as shown in FIG. 10A, to a second position in which grasping members **1010** are radially extended, as shown in FIGS. 10C and 10D. Outer tube **1015** and inner tube **1005** can include a locking mechanism, such as a button extending from inner tube **1005** which locks into an opening of outer tube **1015**, for maintaining the configuration shown in FIG. 10D.

In use, sheath **1000** can generally be used with a needle as described in the methods disclosed herein. Sheath **1000** is placed against the capsule and a needle may be positioned through sheath **1000** to puncture capsule C. The tip of sheath **1000** is then inserted into the capsule. Grasping members **1010** securely attach to capsule C of a joint by rotating inner tube **1005** and outer tube **1015** with respect to each other. Accordingly, either inner tube **1005** or outer tube **1015** is held stationary, and the other is rotated. This action causes grasping members **1010** to extend from slots **1020** and securely engage the inner surface of capsule C. Rotating either inner tube **1005** or outer tube **1015** back into its original position causes grasping members **1010** to withdraw back into sheath **1000** and disengage from capsule C.

#### Capsular Distention

Further embodiments of the invention include distension devices which are used to distend capsule C and enlarge peripheral compartment PC. It should be understood that the

20

distension devices disclosed herein can be used with any of the systems disclosed herein to access capsule C.

FIG. 11A illustrates a system **1100** for accessing and distending the capsule of a joint. System **1100** includes a cannula or sheath **1102**, which is configured similarly to the sheaths disclosed herein. An expansion device **1104** is coupled within sheath **1102**. Expansion device **1104** includes a plurality of grasping members **1106** shown in an exposed position. Expansion device **1104** may generally be configured similarly to the expansion devices disclosed herein.

A balloon device **1108** is slidably disposed within sheath **1102**. Balloon device **1108** includes an elongated shaft **1110** with a distally positioned balloon **1112**. Shaft **1110** may be constructed from a flexible or stiff material, such as a metal or polymer. Shaft **1110** may include at least one lumen. Shaft **1110** can be circular in cross-section and have an outer diameter sized to be exchangeable with the needles disclosed herein, for example 18-27 gauge. Balloon **1112** may be constructed from a non-compliant (e.g., 0-10% compliance range) thin-walled material such as polyethylene terephthalate (PET), or from a semi-compliant (e.g., 10-20% compliance range) thin-walled material, such as PET, nylon, and polyurethane. Balloon **1112** may be capable of withstanding high pressures (e.g., up to 400 psi), and include reinforcement features, such as integrated woven fibers, to help prevent bursting. Balloon **1112** can have a wall thickness ranging from 0.0001 to 0.0006 inches, and may also have multiple layered wall, e.g., 2-ply or 3-ply, with the layers either adhered to each other or not. Balloon **1112** is shown in an expanded configuration and may have an expanded diameter of 5 to 20 millimeters. Balloon **1112** may be folded or collapsed into an unexpanded configuration to have an effective diameter which is roughly equivalent to or slightly larger than the outer diameter of shaft **1110**. Balloon **1112** may utilize various shapes and sizes other than the generally spherical shape shown, such as spherical, donut, cylindrical, oval, curved, conical or kidney shapes.

An atraumatic tip **1114** extends from balloon **1112**. Atraumatic tip **1114** can be constructed from a soft material, such as rubber. A connector **1116** for coupling to an inflation device, such as a syringe or angioplasty balloon inflation device, is proximally located on shaft **1110**. Connector **1116** is fluidly coupled to balloon **1112**.

FIG. 11B illustrates a system **1100b** for accessing and distending the capsule of a joint. System **1100b** is largely identical to system **1100** except that in system **1100b**, sheath **1102b** has hinged sections **1118b**. Hinged sections **1118b** provide sheath **1102b** with a long configuration, and a short configuration as shown. Hinged sections **1118b** radially and outwardly expand into flanges in the short configuration. These flanges are configured to engage the outer wall of the capsule while grasping members **1106** engage the inner wall to sandwich the capsular wall therebetween, thereby firmly retaining sheath **1102b**. A clip **1120** may attach to a section **1122** between expansion device **1104** and sheath **1102b**, to prevent relative movement therebetween and maintain sheath **1102b** in the short configuration.

FIG. 11C illustrates a method of use for systems **1100**, **1100b**, for accessing and distending the capsule of a joint. In FIG. 11C, system **1100** or **1100b** has already been used to puncture capsule C, as similarly described herein. In the case of system **1100b**, hinged sections **1118b** can be moved to the short configuration to form a flange which holds capsule C between hinged section **1118b** and grasping members **1106**. Balloon device **1108** is then advanced into peripheral compartment PC and balloon **1112** is expanded to distend capsule C. Balloon **1112** can be maintained in this position

21

over time to stretch capsule C. Accordingly peripheral compartment PC is enlarged to enable access by other devices. Balloon 1112 may then be deflated and removed from shaft 1110. Alternatively catheters or other devices may be placed through an inner lumen of balloon device 1108, distally of balloon 1112 and into the peripheral or central compartments of the joint to perform interventional procedures therein.

FIG. 12A illustrates a basket device 1200 for distending the capsule of a joint after accessing the capsule in accordance with systems and methods described herein. Basket device 1200 includes an elongated shaft 1202. Shaft 1202 may be constructed from a flexible or stiff material, including metals or polymers. Shaft 1202 may include at least one lumen. Shaft 1202 can be circular in cross-section and have an outer diameter sized to be exchangeable with the needles disclosed herein, for example 18-27 gauge. An expandable basket 1204 extends distally from shaft 1202. Basket 1204 includes a plurality of basket leaves 1206 circumferentially arranged around shaft 1202. Basket leaves 1206 can be pre-shaped to bow outwardly, or naturally assume a straightened configuration. Basket leaves 1206 may be constructed from a metal, such as such as super-elastic Ni—Ti or stainless steel, or from a polymer material. An atraumatic tip 1208 joins basket leaves 1206 to a pull wire 1210 which proximally extends within shaft 1202.

FIG. 12B shows an alternatively constructed basket device 1200b where pull wire 1210 is positioned outside of shaft 1202.

In use, basket device 1200 or 1200b may be used to distend capsule C in a similar manner to balloon device 1108 of systems 1100 and 1100b. Basket 1204 is advanced within a cannula or sheath 1212 and into peripheral compartment PC. Pull wire 1210 is then pulled proximally with respect to shaft 1202 to expand basket leaves 1206 and distend capsule C. In the case where basket 1204 is pre-shaped, pull-wire 1210 is initially moved distally with respect to shaft 1202 to collapse basket leaves 1206 so that basket 1204 can be advanced down sheath 1212 and into peripheral compartment PC. Pull wire 1210 is then released (or pulled proximally) to expand basket leaves 1206 and distend capsule C. Other devices may access peripheral compartment PC through shaft 1202.

FIGS. 12C and 12D illustrate a basket device 1200c for distending capsule C. Basket device 1200c comprises a tubular shaft 1214 and an expandable basket 1204 coupled to its distal end. Basket 1204 comprises a plurality of elongated leaves 1206 or tines of a resilient material fixed at their proximal ends to the inner surface 1202 of shaft 1214. Shaft 1214 includes a cutout portion 1216 in its sidewall near the distal end thereof configured to receive a second shaft, cannula, or instrument introduced from a laterally offset location as described below. A pull wire 1210 is fixed at its distal end to the distal end of basket 1204 and extends proximally through the interior of shaft 1214. Exerting tension on pull wire 1210 causes leaves 1206 to bow outwardly into a radially expanded configuration.

In use, basket device 1200c is advanced through a penetration in the capsule to insert basket 1204 inside capsule C, as shown in FIG. 12D. Basket 1204 may then be expanded to distend the capsule. A sheath, cannula, or other instrument 1212 may then be introduced alongside shaft 1214 and positioned through cutout portion 1216 so that the distal end of instrument 1212 is within the expanded basket 1204. Cutout portion 1216 allows shaft 1214 and instrument 1212 to be arranged at a relatively shallow angle with respect to each other. Other devices can be inserted through instrument

22

1212 to perform procedures in the peripheral or central compartments while basket device 1200c maintains distension of capsule C.

FIG. 12E illustrates a basket device 1200d for distending a capsule. Basket device 1200d includes a plurality of basket leaves 1206 which are pre-shaped into basket 1204, as shown. A distal ring 1218 distally joins basket leaves 1206, while a proximate ring 1220 proximally joins basket leaves 1206. An elongated shaft 1222 is removably coupled to distal ring 1218 and slides within proximate ring 1220. A locking mechanism can be functionally coupled to proximate ring 1220 and shaft 1222 to lock proximate ring 1220 and shaft 1222 to each other. Alternatively, basket leaves 1206 may be normally biased into a straight configuration and bowed outwardly by exerting tension on shaft 1222.

In use, shaft 1222 is moved distally with respect to proximate ring 1220 to cause basket 1204 to unbow and move towards shaft 1222. This position reduces the effective diameter of basket 1204 and allows basket device 1200d to be advanced into instrument 1212 (shown in FIGS. 12A, 12B and 12D) and into peripheral compartment PC. Once basket 1204 is within peripheral compartment PC, shaft 1222 is moved proximally with respect to proximate ring 1220 which causes basket 1204 to bow and expand peripheral compartment PC. Shaft 1222 can then be removed from instrument 1212. Accordingly, as the interior of instrument 1212 is unoccupied by shaft 1222, other devices can simultaneously be inserted into instrument 1212 while basket device 1200d maintains distension of capsule C. Optionally, shaft 1222 may be tubular so as to allow the introduction of catheters or instruments therethrough.

FIGS. 13A and 13B illustrate a piston device 1300 for distending the capsule of a joint. Piston device 1300 includes an elongate body 1302. Elongate body 1302 can house a pneumatic or hydraulic cylinder 1304 or electrical motor, such as a step-motor. Pneumatic cylinder 1304 is moveable within elongate body 1302 and is also fluidly sealed therein. A moveable shaft 1306 extends from pneumatic cylinder 1304 and elongate body 1302. Moveable shaft 1306 has a range of motion between a fully extended position and a fully unextended position. Atraumatic bumpers 1308 are connected to one end of moveable shaft 1306 and to one end of elongate body 1302. A pressure hose 1310 is fluidly connected to elongate body 1302. Alternatively, an electrical cable can be connected to elongate body 1302 if an electrical motor is housed therein. An elongated applicator device 1312 is detachably coupled to one of the atraumatic bumpers 1308 at a distal cup 1314. A push rod 1316 is moveably housed within applicator device 1312 and can moveably extend into distal cup 1314.

FIG. 13C illustrates a method of use for piston device 1300 to distend capsule C of a joint. In FIG. 13C, capsule C has already been punctured in accordance with the methods disclosed herein. Applicator device 1312 is advanced into a sheath to deposit piston device 1300 within peripheral compartment PC. Actuation of push rod 1316 detaches piston device 1300 from distal cup 1314. Piston device 1300 may be placed within peripheral compartment PC so that atraumatic bumpers 1308 are positioned at capsule C and greater trochanter T, or at capsule C and femoral neck FN, or in various other positions. Pressure hose 1310 is coupled to a pressure source and pressurized. Accordingly, the increased pressure causes pneumatic cylinder 1304 to move moveable shaft 1306 to the fully extended position and distend capsule C between atraumatic bumpers 1308. Alternatively, an electrical signal is sent to piston device 1300, if

23

an electrical motor is used, to move moveable shaft **1306** to the fully extended position and distend capsule C between atraumatic bumpers **1308**.

FIG. **14A** illustrates a distention device **1400** for distending the capsule of a joint. Distention device **1400** includes an elongate shaft **1402**. An atraumatic foot **1404** is distally connected to shaft **1402**. Atraumatic foot **1404** may be curved to fit the profile of portions of a joint, such as femoral neck FN. Shaft **1402** includes a threaded section **1406** which is threadably coupled to a knob **1408**. Knob **1408** is rotatably coupled to a sheath **1410**. Sheath **1410** can assume the general construction of sheaths disclosed herein.

FIG. **14B** illustrates a method of use for distention device **1400** to distend capsule C of a joint. In FIG. **14B**, sheath **1410** has been securely attached to capsule C, and capsule C has already been punctured in accordance with the methods described herein. Shaft **1402** is advanced within sheath **1410** into peripheral compartment PC to contact atraumatic foot **1404** against femoral neck FN. Knob **1408** is then rotated until it contacts and couples with secured sheath **1410**. Knob **1408** is continually rotated to cause shaft **1402** to move distally with respect to knob **1408** and sheath **1410**. Accordingly, atraumatic foot **1404** of shaft **1402** pushes against femoral neck FN, which causes capsule C to stretch and distend between femoral neck FN and secured sheath **1410**.

FIG. **15A** illustrates a system **1500** for distending the capsule of a joint. System **1500** includes a first elongated strap **1502** and a second elongated strap **1504**. Straps **1502**, **1504** may be constructed from a flexible cord, such as a braided polymer rope. Straps **1502**, **1504** may each include a stiffening core wire **1506**. Core wire **1506** can be laterally stiffer than the braided rope. Core wire **1506** can be comprised from a preshaped, super-elastic alloy to angle a distal portion of each strap at a predefined angle, for example 30 to 90 degrees, as shown by the dotted lines. Straps **1502**, **1504** each include a distally connected magnetic member **1508a**, **1508b**. The straps are generally identical except for the configuration of the magnetic members **1508a**, **1508b**. Magnetic members **1508a**, **1508b** can be magnets with distally positioned opposite polarities. One magnetic member can be a ferromagnetic substance such as steel, while the other can be a magnet. Magnetic members **1508a**, **1508b** can include rare-earth magnets, such as neodymium magnets. The magnetic members **1508a**, **1508b** are shown configured as cylinders, but can include dissimilar and coupling shapes, such as a cup and ball arrangement. Straps **1502**, **1504** are diametrically configured to be slidable within a cannula or sheath **1510**.

FIGS. **15B-F** illustrate system **1500** in use for distending capsule C of a joint. In FIG. **15B**, two sheaths **1510** are made to access the peripheral compartment beyond capsule C. Sheaths **1510** can access the capsule in accordance with the methods disclosed herein. Capsule C can also be pre-distended in accordance with the methods disclosed herein.

In FIG. **15C**, straps **1502**, **1504** are respectively advanced within the sheaths into peripheral compartment PC. Straps **1502**, **1504** are manipulated to guide magnetic members **1508a**, **1508b** to unite. Core wires **1506**, if present, can aid to steer magnetic members **1508a**, **1508b** towards each other. Once magnetic members **1508a**, **1508b** are guided into general vicinity, a magnetic force will cause them to magnetically couple to join the two straps. Accordingly, straps **1502**, **1504** become united.

In FIG. **15D**, strap **1502** is pulled out of its respective sheath **1510**. Straps **1502**, **1504** are magnetically united which causes strap **1504** to follow as strap **1502** is pulled.

24

Accordingly, a mid-section of strap **1504** is made to occupy peripheral compartment PC. Sheaths **1510** can then be removed from capsule C.

In FIG. **15E**, two guide probes **1512** are advanced into the openings where sheaths **1510** previously resided. Sheaths **1510**, or other sheaths, can be guided over guide probes **1512** to be guided back into the openings adjacent to strap **1504**.

In FIG. **15F**, the ends of strap **1504** are pulled away from the joint to distend capsule C, as shown. Tension may be continuously maintained on strap **1504** by a traction mechanism to maintain capsule C in the distended position. Other devices may then access peripheral compartment PC using sheaths **1510** for a following procedure. Strap **1504** may be removed by discontinuing application of tension and pulling strap **1504** out of one the openings. Strap **1504** may be cut at a location near the joint to aid in removal.

#### Additional Methods and Apparatus for Accessing the Interior of a Hip Joint and Increasing the Workspace Adjacent to the Head of the Femur and/or the Acetabulum During an Arthroscopic Hip Procedure

##### Access Cannula with Capsulary Lock

The present embodiment is directed to a cannula that allows quick access to the interior of the hip joint while also providing a capsulary lock mechanism for selectively locking the distal end of the cannula within the capsule of the hip and/or creating additional workspace at the surgical site.

Looking next at FIGS. **16-24**, there is shown a locking access cannula **5** formed in accordance with the present invention. Locking access cannula **5** generally comprises a cannula sub-assembly **10** and a locking sub-assembly **15** for mounting over cannula sub-assembly **10**.

More particularly, and looking now at FIGS. **17A** and **17B**, cannula sub-assembly **10** generally comprises a hollow tube **20** having a distal end **25** and a proximal end **30** terminating in a proximal hub **35**. Cannula sub-assembly **10** is of the type generally known in the art, in the sense that it includes a central lumen opening on distal end **25** and proximal hub **35**, and may include a seal **40** for selectively sealing the central lumen and/or a luer lock **45** for introducing or removing fluid from the surgical site. Preferably cannula sub-assembly **10** includes a cannulated obturator **50** for selectively filling the lumen of hollow tube **20**, e.g., when locking access cannula **5** is inserted into the body. Cannula sub-assembly has windows **47** formed therein (FIG. **17A**) for receiving a finger of locking sub-assembly **15**, which will hereinafter be discussed in further detail.

Locking sub-assembly **15** (FIGS. **18** and **19**) comprises a sleeve **55** having an expandable collar **60** on its distal end, and a housing **65** which includes a locking lever **70** for expanding and retracting expandable collar **60**. Locking sub-assembly **15** also comprises an internal finger **72** (not shown) for extending through a window **47** formed in cannula sub-assembly **10**.

It should be appreciated that although locking access cannula **5** comprises two separate sub-assemblies, the two separate sub-assemblies may be joined during manufacture so as to create a single construction. At the time of manufacture, locking sub-assembly **15** is mounted onto cannula sub-assembly **10** so that finger **72** is aligned with window **47** (in order that the finger can thereafter be selectively moved through the window, as will hereinafter be discussed in

25

further detail), and then locking sub-assembly **15** is secured onto cannula sub-assembly **10**, e.g., by ultrasonic welding.

In use, and looking next at FIGS. **20-24**, a guidewire or access needle is first passed through the skin, through the intervening tissue, and then into the hip joint. Next, locking access cannula **5**, with obturator **50** in place, is passed coaxially over the guidewire (not shown), through the intervening tissue **75**, and into the interior of the capsule of the hip (FIG. **20**). Then obturator **50** is removed from the cannula and the guidewire is removed from the cannula (FIG. **21**). Locking lever **70** is then actuated so as to enlarge expandable collar **60** on the distal end of locking sub-assembly **15**. This causes expandable collar **60** to enlarge with the enlarged collar **60** being located on the joint side of the capsule. This helps hold the distal end of the cannula in place within the capsule (FIG. **22**).

Thereafter, if desired, locking access cannula can then be positioned by the surgeon so that expandable collar **60** is pressed against the interior surface of the capsule, and the capsule can then be “tented” by pulling outwardly on the proximal end of the locking access cannula whereby to create additional workspace between the capsule and the hip joint.

Locking lever **70** may be “un-locked” so as to withdraw finger **72** from window **47**, so as to allow a scope or other instrument **80** to be introduced through the lumen of cannula sub-assembly **10** and down to the surgical site (FIG. **23**). Locking lever **70** can then be actuated again so as to cause finger **72** to protrude through window **47** into the lumen of cannula sub-assembly **10** and thereby lock the scope or other instrument **80** to the inner cannula sub-assembly **10**, and hence to locking access cannula **5**.

It should be appreciated that although locking lever **70** may actuate both expandable collar **60** and finger **72**, more preferably, separate locking levers **70** can be used to separately actuate expandable collar **60** and finger **72**. Significantly, a surgeon can actuate a first lever to open expandable collar **60** and lock the distal end of the cannula within the capsule, and then be able to move the cannula so as to “tent” the tissue. In this embodiment of the present invention, a surgeon can then insert and/or otherwise move a scope within the locking access cannula and then actuate a second lever to lock the scope to the locking access cannula.

It should also be appreciated that expandable collar **60** may be expanded by other mechanisms well known in the art (e.g., fluid or air expansion, etc.).

In view of the foregoing, locking access cannula **5** can be used as both an access cannula for delivering scopes or other instruments to a surgical site, as well as used to create additional workspace in the hip joint during a procedure.

#### Access Cannula with Expansion Wheel Tensioner

In another preferred embodiment, the present invention is directed to a cannula that allows quick access to the interior of the hip joint while also providing an expansion wheel mechanism for creating additional workspace.

Looking next at FIGS. **25-27**, there is shown a tensioning access cannula **100** formed in accordance with the present invention. Tensioning access cannula **100** generally comprises a hollow tube **105** having a distal end **110** terminating in capsule locking sleeve **115**, and a proximal end **120** terminating in a proximal hub **125**.

Tensioning access cannula **100** includes a central lumen opening on its distal end and may include a proximal seal for selectively sealing the central lumen and/or a proximal luer lock for introducing or removing fluid from the surgical site.

26

Preferably tensioning access cannula includes a cannulated obturator (not shown) for selectively filling the lumen of hollow tube **105**, e.g., when tensioning access cannula **100** is inserted into the body.

Hollow tube **105** is partially threaded along a portion **T** of its length and also comprises an expansion wheel tensioner **130** mounted thereon. It should be appreciated that expansion wheel tensioner **130** has a complementary thread to threaded portion **T** of hollow tube **105**, so as to allow expansion wheel tensioner **130** to move laterally along threaded portion **T** of hollow tube **105**.

Proximal hub **125** comprises an actuator **135** for expanding capsule locking sleeve **115**.

In use, and looking next at FIGS. **26** and **27**, a guidewire or access needle is first passed through the skin, through the intervening tissue, and then into the hip joint. Next, tensioning access cannula **100**, with its obturator in place (not shown), is passed coaxially over the guidewire (not shown), through the intervening tissue **140**, and to the interior of the capsule of the hip (FIG. **26**). Then the obturator is removed from the cannula and the guidewire is removed from cannula. Actuator **135** is then actuated so as to expand capsule locking sleeve **115** so as to form a collar shape. Expansion wheel tensioner **130** is then tightened by the surgeon so as to shorten the distance between expansion wheel **130** and the enlarged capsule locking sleeve **115**. This causes capsule **C** to be “tented” by the retracting enlarged capsule locking sleeve **115** (FIG. **27**). Thus, tensioning access cannula **100** can be used to increase the workspace inside the hip joint, in the peripheral compartment.

By virtue of the fact that expansion wheel tensioner **130** is movably threaded on threaded portion **T** of hollow tube **105**, it can be used to adjust the tension applied to the tissue during the procedure. This is important since during a lengthy procedure, the tissue tends to swell due to the retention of saline fluids applied to the surgical site. Thus, the provision of expansion wheel tensioner **130** allows a surgeon to adjust the tension applied to the tissue so as to accommodate for tissue swelling.

In addition, since the enlarged capsule locking sleeve **115** and expansion wheel tensioner **130** form a stable construct, the tissue can be maintained in its tented position without constant manual intervention. This “hands-free” operation can be extremely useful to the surgeon.

In view of the foregoing, tensioning access cannula **100** can be used as both an access cannula for delivering scopes or other instruments to a surgical site, as well as used to create additional workspace in the hip joint and to adjust tension applied to tissue during a procedure.

#### Capsule Retraction with an Anchor Attached to a Length of Suture

In another embodiment of the present invention, and looking now at FIGS. **28A-28E**, an anchor **2000** attached to a length of suture **S** may be used to retract the capsule in order to create additional workspace in the hip joint. Anchor **2000** comprises a body **2005** which is attached at a center portion to a length of suture **S**. Body **2005** may be formed from a shape memory or super elastic material (e.g., nitinol) so that body **2005** may assume a first, folded configuration (FIGS. **28A** and **28B**) when body **2005** is in a stressed condition and a second, straight configuration (FIG. **28E**) when body **2005** is in a non-stressed condition.

In use, and looking now at FIGS. **28F-28I**, anchor **2000**, with suture **S** attached, is folded in half and passed through a sheath **2010** which maintains body **2005** in its first, folded



27

configuration. Sheath **2010** is then passed through capsule **C** so that the distal end of sheath **2010** is positioned within the interior of the joint (FIG. **28F**). Using a push rod **2015**, body **2005** is pushed through the distal end of sheath **2010**, forcing body **2005** into its second, straight configuration (FIG. **28G**). Sheath **2010** and push rod **2015** can now be removed from the joint (FIG. **28H**) and suture **S** can be manipulated so as to position body **2005** against the interior surface of the capsule. The capsule can then be “tented” by pulling suture **S** proximally, whereby to create additional workspace between the capsule and the hip joint (FIG. **28I**).

#### Capsule Retraction with a Rod Having a Pivoting Distal End

In another embodiment of the invention, and looking now at FIG. **29** and FIGS. **29A-D**, a rod **3000** may be used to retract capsule **C** in order to create additional workspace in the hip joint. Rod **3000** comprises an elongated shaft **3005** having a distal end **3010** with a pivot point **3020** axially spaced from distal end **3010**. Preferably, distal end **3010** comprises a sharpened distal end so that rod **3000** may be passed directly through the capsule. However, if desired, rod **3000** (with or without a sharpened distal tip) may also be passed through a cannula or sheath positioned against the capsule. Rod **3000** also comprises a pull wire **3025** (FIG. **29C**) extending through the center of elongated shaft **3005** which may be pushed or pulled in order to pivot distal end **3010** (at pivot point **3020**) from a first position in which distal end **3010** is substantially aligned with the longitudinal axis of elongated shaft **3005** (FIGS. **29A-C**) to a second position in which distal end **3010** extends at an angle (e.g., perpendicularly) to the longitudinal axis of elongated shaft **3005** (FIGS. **29** and **29D**).

In use, and looking now at FIGS. **29E** and **29F**, pull wire **3025** (not shown in FIGS. **29E** and **29F**, but shown in FIGS. **29C** and **29D**) is pulled proximally so as to position distal end **3010** in its first position. Rod **3000** is then inserted percutaneously directly through capsule **C**. After distal end **3010** of elongated shaft **3005** passes through capsule **C** (FIG. **29E**), pull wire **3025** may be pushed distally in order to cause distal end **3010** to pivot from its first position to its second position, with distal end **3010** positioned against the interior surface of capsule **C** (FIG. **29F**). Elongated shaft **3005** may then be pulled proximally so as to “tent” capsule **C** and create additional workspace between the capsule and the head of the femur. After a surgeon no longer needs access to the hip joint, pull wire **3025** may be pulled proximally in order to cause distal end **3010** to pivot back to its first position and rod **3000** may be removed from the joint.

#### Capsule Retraction with a Rod Having a Projection

Looking now at FIG. **30**, a rod **4000** may be used to retract capsule **C** in order to create additional workspace in the hip joint. Rod **4000** comprises an elongated shaft **4005** having a distal end **4010** with a pivot point **4020** axially spaced from distal end **4010**. A projection **4025** is attached to elongated shaft **4005** at pivot point **4020**. Rod **4000** also comprises a length of wire having two portions **4030** and **4035** extending along the longitudinal axis of elongated shaft **4005** and configured to cause projection **4025** to move from a first position which is substantially aligned with elongated rod **4005** to a second position in which projection **4025** extends at an angle to the longitudinal axis of elongated shaft **4005**.

In use, and looking now at FIGS. **30A** and **30B**, the wire is manipulated so as to position projection **4025** in its first

28

position. Rod **4000** may then be passed directly through the capsule, or through a cannula or sheath **4040** positioned through the capsule. After distal end **4010** of elongated shaft **4005** passes through capsule **C** (FIG. **30A**), portion **4035** of the wire may be pulled proximally in order to cause projection **4025** to move from its first position to its second position (FIG. **30B**). Rod **4000** may now be manipulated so as to position projection **4025** against the neck of the femur. When projection **4025** (extending at an angle to shaft **4005**) is positioned against the neck of the femur, the projection pushes against the neck of the femur, which causes capsule **C** to stretch and retract between the neck of the femur and the interior surface of the capsule, thereby creating additional workspace within the joint. After a surgeon no longer needs access to the hip joint, portion **4030** of the wire may be pulled proximally in order to cause projection **4025** to rotate back to its first position and rod **4000** may be removed from the joint.

#### Capsule Retraction with a Rod Having a Corkscrew

In another embodiment of the invention, and looking now at FIG. **31**, a rod **5000** having a corkscrew may be used to retract capsule **C** in order to create additional workspace in the hip joint. Rod **5000** comprises a body **5005** having a corkscrew **5010** at its distal end.

In use, and looking now at FIGS. **31A-31C**, rod **5000** may be passed through a cannula or needle **5015** positioned on the outside surface of capsule **C**, so that corkscrew **5010** of body **5005** is also positioned on the outside surface of capsule **C** (FIG. **31A**). Body **5005** is then rotated so as to cause corkscrew **5010** to advance into capsule **C**, thereby engaging capsule **C** (FIG. **31B**). Rod **5000** may then be pulled proximally so as to “tent” capsule **C** away from the joint, whereby to create additional workspace in the hip joint (FIG. **31C**).

#### Capsule Retraction with Suture

In another embodiment of the invention, a device and method are provided which may be used when the capsule is cut open, e.g., in a manner shown in FIG. **33**, in order to create additional workspace within the hip joint.

Looking now at FIG. **32**, a device for creating additional workspace within the joint is provided. The device shown in FIG. **32** comprises a length of suture **S** with a T-bar anchor **6000a** secured to one end of the length of suture **S** and a T-bar anchor **6000b** secured to the other end of the length of suture **S**.

In an alternative form of the present invention, T-bar anchor **6000b** is omitted from the device. In this embodiment, the device comprises a length of suture **S** having a T-bar anchor **6000a** secured to one end of the length of suture **S**, with the other end of the length of suture remaining free.

The device shown in FIG. **32**, and the device omitting T-bar anchor **6000b**, may be used in the following manner to create additional workspace within the hip joint.

Looking first at FIG. **33**, a T-shaped cut (or any other shaped cut which creates two edges in the capsule) is made in capsule **C** in order to create two flaps, **F1** and **F2**, and expose both the head of the femur and the acetabular cup.

Looking now at FIGS. **34-38B**, a push rod **6005** is used to load suture **S**, with at least one T-bar anchor extending therefrom, through a needle **6010** (FIG. **34**). Needle **6010** is passed percutaneously through the skin, into the hip joint and through flap **F1** of capsule **C**. A second needle **6010**,

29

with a suture S and at least one T-bar anchor loaded within the needle, is passed percutaneously through the skin, into the hip joint and through flap F2 of capsule C (FIG. 35). Push rod 6005 is used to push T-bar anchor 6000a and suture S through needle 6010 so that T-bar anchor 6000a extends out of the distal end of needle 6010 and into the interior of the capsule, leaving T-bar anchor 6000a located within the interior of the capsule and a length of suture extending to the exterior of the capsule (FIGS. 36A and 36B).

Looking next at FIG. 37, both push rod 6005 and needle 6010 are removed from capsule C, and suture S is pulled proximally so as to lock T-bar anchor 6000a on the underside of capsule C.

The two ends of suture S extending from T-bar anchors 6000a may now be pulled proximally so as to retract flaps F1 and F2 of capsule C (FIGS. 38A and 38B). This permits a surgeon improved access to the neck of the femur normally covered by the capsule.

It is important to note that the T-shaped cut in the capsule can also be made in the capsule after T-bar anchors 6000a have been locked on the underside of capsule C rather than before the T-bar anchors are locked on the underside of the capsule, as described above. Additionally, T-bar anchors 6000a could be used in capsule C where no cut is made; in other words, T-bar anchors 6000a are placed in a region of the capsule where it is desired to tent, or retract, the capsule.

Once the necessary arthroscopic procedures are completed, T-bar anchors 6000a may be removed from the joint as follows.

Looking now at FIG. 39, a cannula 6015 may be inserted into the capsule and grasping forceps 6020 may be passed through the cannula to grasp each T-bar anchor 6000a from the underside of capsule C (FIG. 39). Each T-bar anchor 6000a, with suture S attached, is then pulled proximally from the underside of capsule C until all the suture is removed from the joint space through the cannula. It is important to note that, when T-bar anchor 6000b is attached to the other end of the length of suture, T-bar anchor 6000b may be cut from the end of the suture prior to pulling T-bar anchor 6000a from the underside of capsule C so that the other end of the length of suture is free to slide out of the joint (in this example, from the skin to the capsule through the adjoining tissue structures).

Instead of removing T-bar anchors 6000a from the joint, it may also be desirable to close capsule C using T-bar anchors 6000a, with T-bar anchors 6000a remaining in the joint after the capsule has been closed. In this embodiment, and looking now at FIGS. 40-43, a cannula 6015 may be inserted into the capsule and a grasping or hooking instrument 6020 may be passed through the cannula to grasp or hook the portion of the suture positioned on the outside of capsule C (FIG. 40). Each leg of the suture is passed up through the cannula (FIG. 41) until two free ends of suture extend from the capsule (FIG. 42). The two free ends of the suture extending from the capsule may then be tied off (e.g., using a half hitch or other non-sliding knot well known to those skilled in the art) so as to re-stitch and secure the capsule (FIG. 43). If desired, suture S and T-bar anchors 6000a may be formed from an absorbable material so that they dissolve over time.

In another embodiment, it may be desirable to remove T-bar anchors 6000a from the joint, and close the capsule, leaving only suture S in the joint. In this embodiment, and looking now at FIG. 44, a cannula 6015 may be inserted into the capsule and a grasping or hooking instrument 6020 may be passed through the cannula to grasp or hook the portion of the suture positioned on the outside of capsule C. Each leg

30

of the suture is passed up through the cannula until two free ends of suture extend from the capsule. Once the free ends of suture S have been passed up through the cannula, a knot 6025 is formed on the free ends of suture S. Subsequently, a grasping instrument may be used to grasp each T-bar anchor 6000a from the underside of capsule C (not shown). Each T-bar anchor 6000a, with suture S attached, is then pulled proximally from the underside of capsule C until T-bar anchors 6000a are removed from the joint space through the cannula. As the T-bar anchors are removed from the joint space, knot 6025 is positioned along the capsule. The ends of the suture with T-bar anchors 6000a may then be tied off (e.g., using a half hitch or other non-sliding knot well known to those skilled in the art) so as to re-stitch and secure the capsule (not shown). If desired, suture S may be formed from an absorbable material so that the sutures dissolve over time.

In still another embodiment of the present invention, it may be desirable to close capsule C using T-bar anchors 6000a and 6000b, with T-bar anchors 6000b remaining in the joint after the capsule has been closed. In this embodiment, and looking now at FIGS. 45-48, a cannula may be inserted into the capsule and grasping forceps may be passed through the cannula to grasp each T-bar anchor 6000a from the underside of capsule C (FIG. 45). Each T-bar anchor 6000a, with suture S attached, is then pulled proximally from the underside of capsule C (FIG. 46) until T-bar anchors 6000b are resting on the outside of capsule C (FIG. 47A-47C). The free ends of the suture extending from the capsule may then be tied off (e.g., using a half hitch or other non-sliding knot well known to those skilled in the art) so as to re-stitch and secure the capsule (FIG. 48). If desired, suture S may be formed from an absorbable material so that the sutures dissolve over time.

In another form of the present invention, and looking at FIG. 49, a length of suture may be used to retract capsule C, and a cannula 7000 having a projection 7005 may be used to secure the suture so as to maintain the capsule in the retracted position while the necessary arthroscopic procedures are completed.

In use, a T-shaped cut (or any other shaped cut which creates two edges in the capsule) is made in capsule C so as to create two flaps, F1 and F2, and expose both the head of the femur and the acetabular cup.

A push rod may be used to load suture S through a needle (not shown). The needle is passed through cannula 7000 and through flap F1 of capsule C so that two free ends of suture S extend from flap F1. A second needle, with suture S loaded therein, is passed through cannula 7000b and through flap F2 of capsule C so that two free ends of suture S extend from flap F2. Each of the two free ends of suture S may now be pulled proximally so as to retract flaps F1 and F2 of capsule C. In order to permit a surgeon to better access the hip joint, each of the two free ends of suture extending from the flaps can be tied around projection 7005 in order to maintain the flaps in their retracted position.

Projection 7005 may comprise a post on which to wrap suture S. Post may include a narrow slit to capture a portion of suture S. The slit is narrower than the width of suture S so that the slit squeezes the suture to provide a gripping force. The slit may be formed out of an elastomeric material. Alternatively, projection 7005 may comprise a clamp into which suture S is secured. Clamp may be activated manually or with a spring.

It is important to note that a length of suture may also be used to retract capsule C, and cannula 7000 with projection

## 31

**7005** may be used to secure the suture so as to maintain the capsule in the retracted position even when a cut has not been made in the capsule.

#### Capsule Retraction with a Rod Having a Hook

Looking now at FIG. **50**, a rod **8000** having a hook **8005** may be used to retract capsule C after the capsule has been cut open, e.g., in a manner shown in FIG. **33** (or any other shaped cut which creates two edges in the capsule), in order to create additional workspace in the hip joint. Rod **8000** comprises a body **8005** having a hook **8010** at its distal end.

In use, a T-shaped cut is made in capsule C so as to create two flaps, and expose both the neck and/or head of the femur and/or the acetabular cup. Hook **8010** of rod **8000** may be positioned underneath a flap of the cut capsule. Rod **8000** may then be pulled proximally so as to pierce capsule C and retract capsule C away from the joint.

#### Use of the Present Method and Apparatus for Other Joints, Etc.

It should be appreciated that the present systems and methods disclosed herein may also be used for increasing the workspace in joints in addition to the hip joint, e.g., the present methods and systems may be used to increase the workspace in the knee joint, the shoulder joint, etc. Furthermore, the present methods and systems may also be used to increase workspace in other interior bodily spaces, e.g., the abdomen, the bladder, regions around the spine, etc.

#### Modifications of the Preferred Embodiments

It should be understood that many additional changes in the details, materials, steps and arrangements of parts, which have been herein described and illustrated in order to explain the nature of the present invention, may be made by those skilled in the art while still remaining within the principles and scope of the invention.

What is claimed is:

1. A method for distending tissue, the method comprising: guiding an end of a first strap through a first portion of the tissue; guiding an end of a second strap through a second portion of the tissue; joining the end of the first strap with the end of the second strap within the tissue; withdrawing either the first or second strap from the tissue to place a mid-portion of the other of the first or second strap within the tissue; and pulling on the non-withdrawn first or second strap to distend the tissue.
2. The method of claim 1, wherein guiding the end of the first strap through the first portion of the tissue comprises guiding the end of the first strap through a first cannula, and

## 32

guiding the end of the second strap through the second portion of the tissue comprises guiding the end of the second strap through a second cannula.

3. The method of claim 2, comprising:

- removing the first cannula and the second cannula; positioning a first guide probe adjacent to a first portion of the non-withdrawn first or second strap and a second guide probe adjacent to a second portion of the non-withdrawn first or second strap; and guiding the first cannula over the first guide probe and guiding the second cannula over the second guide probe so as to position the first cannula and the second cannula adjacent to the non-withdrawn first or second strap.

4. The method of claim 2, comprising:

- accessing a region beyond the tissue through at least one of the first cannula and the second cannula.

5. The method of claim 1, wherein joining the end of the first strap with the end of the second strap within the tissue comprises manipulating at least one of the first and second straps.

6. The method of claim 1, comprising maintaining tension on the non-withdrawn first or second strap using a traction mechanism.

7. The method of claim 1, wherein at least one of the first strap and the second strap comprises a cord.

8. The method of claim 7, wherein the cord comprises a braided rope.

9. The method of claim 1, wherein at least one of the first strap and the second strap comprises a stiffening core wire.

10. The method of claim 9, wherein the stiffening core wire comprises a super-elastic alloy.

11. The method of claim 9, wherein joining the end of the first strap with the end of the second strap within the tissue comprises steering at least one of the first and second straps toward the other of the first and second straps using the stiffening core wire.

12. The method of claim 9, wherein the end of at least one of the first strap and the second strap is angled relative to an axis of the respective strap by the stiffening core wire.

13. The method of claim 12, wherein the angle is in a range of 30 to 90 degrees.

14. The method of claim 1, wherein the tissue comprises a capsule of a joint.

15. The method of claim 14, wherein the joint comprises a hip joint, a knee joint, or a shoulder joint.

16. The method of claim 1, wherein the end of the first strap comprises a magnetic member.

17. The method of claim 1, wherein at least one of the ends of the first and second strap are steerable.

18. The method of claim 1, wherein the tissue is pre-distended and pulling on the non-withdrawn first or second strap to distend the tissue comprises pulling on the non-withdrawn first or second strap to further distend the tissue.

\* \* \* \* \*