



**Related U.S. Application Data**

- continuation of application No. 16/802,975, filed on Feb. 27, 2020, now Pat. No. 11,102,544, which is a continuation of application No. 15/197,579, filed on Jun. 29, 2016, now Pat. No. 10,582,259.
- (60) Provisional application No. 62/187,200, filed on Jun. 30, 2015.
- (51) **Int. Cl.**  
*B64U 20/87* (2023.01)  
*B64U 30/291* (2023.01)  
*B64U 30/293* (2023.01)  
*B64U 60/10* (2023.01)  
*B64U 60/40* (2023.01)  
*B64U 101/30* (2023.01)  
*H04L 65/75* (2022.01)  
*H04N 7/18* (2006.01)  
*H04N 21/4363* (2011.01)  
*H04N 23/54* (2023.01)  
*H04N 23/80* (2023.01)
- (52) **U.S. Cl.**  
 CPC ..... *B64U 30/291* (2023.01); *B64U 30/293* (2023.01); *B64U 60/40* (2023.01); *H04L 65/762* (2022.05); *H04N 7/185* (2013.01); *H04N 21/43637* (2013.01); *H04N 23/54* (2023.01); *H04N 23/80* (2023.01); *B64U 60/10* (2023.01); *B64U 2101/30* (2023.01); *B64U 2201/20* (2023.01)
- (58) **Field of Classification Search**  
 CPC .... H04N 23/661; H04N 23/80; B64C 39/024; H04L 65/762; B64U 2101/30; B64U 2201/20; B64U 20/87; B64U 60/10; B64U 10/14; B64U 30/291; B64U 30/293; B64U 60/40
- See application file for complete search history.

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

11,102,544	B2	8/2021	Enke	
11,711,572	B2	7/2023	Enke	
2005/0207436	A1	9/2005	Varma	
2006/0150071	A1	7/2006	Chen	
2006/0227145	A1 *	10/2006	Chow	G06F 3/1431 345/540
2012/0243602	A1	9/2012	Rajamani	
2013/0205169	A1	8/2013	Gaither	
2013/0223538	A1 *	8/2013	Wang	H04N 21/43637 375/E7.027
2014/0101478	A1	4/2014	Tal	
2015/0350483	A1 *	12/2015	Holtzberg	H04N 1/2112 348/231.2
2016/0147249	A1	5/2016	Gendler	
2016/0330782	A1 *	11/2016	Ang	H04W 28/0205
2017/0006340	A1	1/2017	Enke	
2020/0196009	A1	6/2020	Enke	
2022/0046321	A1	2/2022	Enke	


## FOREIGN PATENT DOCUMENTS

CN	101772803	A	7/2010
CN	101909218	A	12/2010
WO	2008115416	A1	9/2008
WO	2012040565	A1	3/2012
WO	2013098643	A2	7/2013

## OTHER PUBLICATIONS

PCT International Search Report and Written Opinion for PCT/US16/31076, Aug. 8, 2016, 19 Pages.  
 PCT Invitation to Pay Additional Fees and, Where Applicable, Protest Fee, for PCT/US2016/040272, Oct. 17, 2016, 7 Pages.

\* cited by examiner



**FIG. 1**




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E







FIG. 2G

FIG. 2F





**FIG. 3**








FIG. 4

**FIG. 5**

**FIG. 6**






FIG. 8




FIG. 9A








FIG. 9B




**FIG. 10**

**FIG. 11**

**FIG. 12**

**FIG. 13**

**FIG. 14**

1

# PIPELINED VIDEO INTERFACE FOR REMOTE CONTROLLED AERIAL VEHICLE WITH CAMERA

## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/404,764, filed Aug. 17, 2021, which is a continuation of U.S. patent application Ser. No. 16/802,975, filed Feb. 27, 2020, now U.S. Pat. No. 11,102,544, which is a continuation of U.S. patent application Ser. No. 15/197,579, filed Jun. 29, 2016, now U.S. Pat. No. 10,582,259, which claims the benefit of U.S. Provisional Application No. 62/187,200, filed Jun. 30, 2015, the contents of which are incorporated by reference in their entirety.

## TECHNICAL FIELD

The disclosure generally relates to the field of pipelining video interface and in particular a pipelining a video interface for a low latency camera system.

## BACKGROUND

Remote controlled devices with cameras mounted upon those devices are known. For example, a remote control road vehicle can be configured to mount a camera on it to capture images as the vehicle is moved about remotely by a user. Similarly, remote controlled unmanned aerial vehicles, e.g., drones such as quadcopters, have been mounted with cameras to capture aerial images through the camera as a user remotely controls the aerial vehicle.

Most cameras mounted on remote controlled vehicles do not take into consideration a multitude of issues involving the camera itself in relation to the vehicle to which it is mounted. These issues include, for example, using a non-dedicated camera and corresponding securing structure that is best suited to mount the camera to the remote controlled vehicle and use of a mounting configuration that allows the vehicle to remain in balance when coupled with a camera.

Yet another issue is being able to transfer the video or images captured by the camera mounted on the remote controlled vehicle to the display screen on the controller. The transfer takes place through a wireless interface between the camera system mounted on the remote controlled vehicle and the controller. To ensure that the transfer must be as seamless as possible, the latency of the wireless transfer of images must be low. To achieve low latency is a complex process and it is even harder to reduce the latency when the camera is moving with the remote controlled vehicle at a variable speed.

Hence, there is a need to resolve these and other issues involved with transferring images or video frames from the camera system to the controller.

## SUMMARY

The present teachings provide a system and method. The system and method include receiving images or video frames at a wireless receiver interface from a wireless transmitter. The system and method include performing video decoder nudging while decoding the images or the video frames received by the wireless transmitter. Overclocking a display of a controller to an overclocked frequency. Outputting decoded images or decoded video frames to the display of the controller at the overclocked frequency.

2

The present teachings provide a non-transitory computer readable storage medium configured to store instructions, the instructions when executed by a processor cause the processor to receive images or video frames at a wireless receiver interface from a wireless transmitter. The processor is configured to perform image decoding operations using decoding. The processor is configured to push dummy data to move the images or the video frames received by the wireless transmitter through the decoder. The processor is configured to overclock a display of a controller at an overclocked frequency. The processor is configured to output decoded images or decoded video frames to the display of the controller at the overclocked frequency so that a total latency of the images or the video frames is reduced relative to a latency of the images or the video frames received.

The present teachings provide a system with memory and a processor. The processor is configured to execute instructions stored on the memory to: receive images or video frames at a wireless receiver interface from a wireless transmitter. The processor is configured to perform image decoding operations using slice decoding. The processor is configured to perform decoder nudging to move the images or the video frames at a fast image decoder. The processor is configured to overclock a display of a controller. The processor is configured to output decoded images or decoded video frames to the display of the controller at an overclocked frequency.

## BRIEF DESCRIPTION OF THE DRAWINGS

The disclosed embodiments have advantages and features which will be more readily apparent from the detailed description, the appended claims, and the accompanying figures (or drawings). A brief introduction of the figures is below.

FIG. 1 illustrates an example configuration of remote controlled aerial vehicle in communication with a remote controller.

FIG. 2A illustrates an example of a remote controlled aerial vehicle.

FIG. 2B illustrates an example of an aerial vehicle in an open position.

FIG. 2C illustrates an example of an aerial vehicle in a closed position.

FIG. 2D illustrates an example of an aerial vehicle from a first end view.

FIG. 2E illustrates an example of an aerial vehicle from a second end view.

FIGS. 2F and 2G illustrate an example remote controller in an open position.

FIGS. 2H and 2I illustrate an example remote controller in a closed position.

FIG. 3 illustrates an example of a remote controlled aerial vehicle electronics and control systems.

FIG. 4 illustrates an example interconnect architecture of a remote controlled aerial vehicle with a gimbal.

FIG. 5 illustrates a block diagram of example camera architecture.

FIG. 6 illustrates a block diagram of an example remote control system of a remote controller.

FIG. 7A illustrates a block diagram of the video pipeline, according to an example embodiment.

FIG. 7B illustrates a time chart of the latency through each module of the pipeline, according to an example embodiment.

FIG. 8 illustrates multiple frames through different stages of a video pipeline, according to an example embodiment.

3

FIG. 9A illustrates overclocked frames, according to an example embodiment.

FIG. 9B illustrates forwarded frames, according to an example embodiment.

FIG. 10 illustrates a flowchart of a method for pipelining frames through a low latency camera system, according to an example embodiment.

FIG. 11 illustrates a flowchart of a method for pipelining frames through an encoder, according to an example embodiment.

FIG. 12 illustrates a flowchart of a method for pipelining frames through a wireless interface, according to an example embodiment.

FIG. 13 illustrates a flowchart of a method for pipelining frames through the remote controller, according to an example embodiment.

FIG. 14 illustrates an example machine for use with a system of the remote controlled aerial vehicle.

### DETAILED DESCRIPTION

The Figures (FIGS.) and the following description relate to preferred embodiments by way of illustration only. It should be noted that from the following discussion, alternative embodiments of the structures and methods disclosed herein will be readily recognized as viable alternatives that may be employed without departing from the principles of what is claimed.

Reference will now be made in detail to several embodiments, examples of which are illustrated in the accompanying figures. It is noted that wherever practicable similar or like reference numbers may be used in the figures and may indicate similar or like functionality. The figures depict embodiments of the disclosed system (or method) for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles described herein.

#### Configuration Overview

Disclosed by way of example embodiments is a video pipeline interface for an aerial capture platform. The aerial capture platform may include a remote controlled aerial vehicle coupled with a camera and may include a remote controller. The remote controlled aerial vehicle may also be referenced as an unmanned aerial vehicle (“UAV”) and/or drone. The aerial vehicle may be remotely controlled through a remote controller. The camera further may be coupled with a mounting structure (or configuration).

The remote controlled aerial vehicle can be directly and immediately controlled for flight. For example, the aerial vehicle may be operated remotely (e.g., via wireless connection) from a remote controller by a user. Remote controlled aerial vehicles may be pre-programmed for flight (e.g., a predetermined flight route (or path) as further described herein), and no control, or limited control, may be exercised via the remote controller during flight. Such configurations may be referred to as autopilot. Examples of limited control may be a manual override or a flight adjustment to the pre-programmed flight. For ease of discussion reference to aerial vehicle operation can refer to user controlled, autopilot and other instances of unmanned aerial vehicle flights.

The aerial vehicle may include a mounting structure that couples with a camera and can secure it. The mounting structure may be removably attachable from the aerial vehicle 110. The mounting structure may include a gimbal to

4

couple with the camera, which can assist with stabilization for image or a video capture (generally termed as a frame). A frame may be a still image (e.g., picture) or may be a frame within a series of frames that comprises a video. Moreover, the camera can be configured so that it may be removably attachable from the mounting structure and can operate as a standalone camera. The camera and mounting structure may also be compatible with other mounting solutions, for example, a handheld (or portable) handle, pole, sports board mount, etc. In some example embodiments, the aerial vehicle may include an integrated camera. The integrated camera also may incorporate a gimbal.

Also disclosed is a configuration for a remote controlled aerial vehicle to wirelessly transfer images or video frames from the camera mounted on the remote controlled aerial vehicle to the display on a remote controller of the aerial vehicle. The configuration includes reducing the latency of the wireless transfer of frames or images by pipelining operations throughout the blocks involved in the wireless transfer. The latency of transfer is reduced to be as low as possible so that the frames are transferred seamlessly to the controller display, thus rendering a high quality of user experience.

As disclosed herein the aerial capture platform is designed and configured to capture images from an aerial vehicle perspective. For ease of discussion, reference herein will be made to images but it should be understood that such reference to images may include any media, e.g., video, still images, and/or audio, without limitation. The aerial capture platform configuration allows for a content creation platform that can be integrated with other camera and camera-related systems and ecosystems, such as activity cameras (e.g., a GOPRO HERO camera) and their ecosystems.

The remote controller of the aerial capture platform can be configured for use in operating the aerial vehicle. The remote controller can be a dedicated mobile computing device or another mobile computing device, for example, a smartphone, a tablet, notebook computer, etc. By way of example, a dedicated remote controller can be configured to include a visual screen (e.g., liquid crystal display or plasma). In addition, the remote controller can include mechanical and/or solid state control elements, e.g. a joystick, touchpad, etc. The remote controller itself can be portable and contained within a casing (or housing). For example, the remote controller may include two parts, such as a display portion and control portion that fold into each other. An antenna system can be configured within the casing of the remote controller to further enhance portability. The remote controller can be primarily dedicated for use with the aerial vehicle and can include its own operating system (e.g., an ANDROID based OS).

#### Example System Configuration

The descriptions herein are in the context of a remote controlled aerial vehicle, for example, a rotary wing (or rotary blade) or fixed wing aircraft. However, disclosed configurations may apply to other remote controlled vehicles such as boats and cars. In addition, the remote controlled vehicles may have hobby sized form factors. As noted above remote control aerial vehicles may sometimes be referred to as unmanned aerial vehicles or drones and in this context may include camera units/hardware for capturing images.

Turning now to FIG. 1, it illustrates an example aerial capture platform (or system) 100. The aerial capture platform 100 may include a remote controlled aerial vehicle 110 in communication with a remote controller 120. The aerial vehicle 110 and the remote controller 120 are communicatively coupled through a wireless link 125. The wireless link

**125** can be a Wi-Fi link, cellular (e.g., long term evolution (LTE), 3G, 4G, 5G) or other wireless communication link. In this example of the aerial capture platform **100**, the aerial vehicle **110** can be, for example, a quadcopter or other multi-rotary blade aerial vehicle. Also in this example, the remote controller **120** is illustrated as a dedicated remote controller, but the principles described herein can apply to other devices that may operate as a remote controller, for example, a smartphone, tablet, a laptop, etc.

The aerial vehicle **110** in this example includes a housing (or body) **130**, a gimbal **210**, two or more arms **135**, and two or more propellers **140**. The housing **130** has one or more cavities for a payload. The payload can include, for example, electronic circuitry (including, e.g., controls and processing components), battery, sensors, etc. The payload may include mechanism such as a parachute. The parachute may be in a portion of the housing that can open so that the parachute can deploy in certain pre-determined situations. The parachute and/or corresponding portion of the housing **130** may couple with electronics that can provide the logic for deployment of the parachute. The housing **130** may include a communication subsystem (which may include corresponding electronics and/or firmware) and a control subsystem (which may include corresponding electronics and/or firmware). The communication subsystem may be used to wirelessly communicate with a remote controller, e.g., **120**, or other interfaces on the aerial vehicle **110**. The control subsystem may be configured to control operations of various systems on the aerial vehicle **110** such as the power system, the flight operation system and other such system. The communication subsystem and the control subsystem are described further in detail with respect to FIG. 3.

The gimbal **210** may be a removable structure. For example, the gimbal **210** may removably (or releasably) mount within an opening on the housing **130** of the aerial vehicle **110**. Further by example, when removed from the aerial vehicle **110**, the gimbal **210** may be mounted on another structure, for example, a pole mount. The gimbal **210** may couple with a removable camera frame. Alternately, the gimbal **210** may be integrated with the housing **130**. The gimbal **210** also may include a camera secured directly with it or through the camera frame. The camera frame can be removed and fitted for the particular camera that couples with it. Alternately, the camera frame may be integrated with the gimbal.

Each arm **135** of the aerial vehicle **110** can removably couple with the housing **130**. In addition, each arm **135** includes a thrust motor **240** (which may include a rotor) that can mechanically, and removably, couple with a propeller **140** to create a rotary assembly. When the rotary assembly is operational, all the propellers **140** spin at appropriate directions and/or speeds to allow the aerial vehicle **110** to lift (take off), tilt, turn, land, hover, and/or otherwise move (up, down, forward, reverse (or backward), etc.) in flight.

The aerial vehicle **110**, including gimbal **210**, and remote controller **120** are further described herein. Also described are some example operational configurations for each. Remote Controlled Aerial Vehicle

Beginning with the remote controlled aerial vehicle **110**, reference is now made to FIGS. 2A-2E. By way of example, at a high level the aerial vehicle **110** may include the housing **130**, arms **135**, thrust motors **240**, propellers **270** and landing gear **272**.

In the example of the aerial vehicle **110**, the arms **135** couple with the housing **130**. A thrust motor **240** couples with each end of an arm **130**, and this may form an arm assembly. Further, a propeller **270** may couple with each

thrust motor **240**. The thrust motor **240**, when coupled with the propeller **140** (shown in FIG. 2B), spins the propeller in an appropriate direction when the thrust motor **240** is operational.

The arms **135** are configured so they can pivot about their connection point at the housing **130**. For example, the arms **135** can be extended away from the housing for purposes of flight and can be folded back so the arms are close to the housing **130**, for example, for storage or transport (e.g., as shown in FIG. 2C). In addition, each of the arms **135** is removably coupled with the housing **130** so that they can be removed and/or replaced, for example, in the event of wear, breakage, structural compromise, or new designs. In addition, propellers **270** that couple to motors **240** on the end of each arm **135** are removable also, for example, for storage and/or replacement. Additionally, the arms **135** may incorporate connection electronics (e.g., electrical/electronic circuitry and/or components) and/or mechanical structures to extend or fold the arms automatically.

In example embodiments in which the arms **135** rotatably couple the housing **130** of the aerial vehicle, there may be a sensor and/or connection to a sensor (or sensor system) that may be used to determine if the arms **135** are in a closed position or in an open and locked position (e.g., for flight of the aerial vehicle **110**). If the aerial vehicle **110** is preparing to fly and any one arm is not properly in an open, locked position, a notification may be generated. Examples of notification include powering a light emitting diode (LED) that may be a warning light, generating an audible signal (e.g., a beep, an alarm or voice notification) or transmitting a message to another device (e.g., the remote controller). In some embodiments, power to the motors of the arm (or arms) that is not properly open and locked may be cut off (disabled). In some embodiments control signals received from the remote controller may be disabled.

The housing **130** of the aerial vehicle **110** can be configured to be waterproof to reduce and/or eliminate water or dust from entering the internal cavity of the housing **130** where electrical components are housed. For example, rubber gaskets can be structured around locations such as where the arm **135** connects with the housing **130** or moves to fold against the housing. Moreover, the aerial vehicle **110** is configured to allow incorporation of, or couple with, float structures made of, for example, removable foam, fiberglass, balloon, or other material that is structured to allow the aerial vehicle **110** to float in the event of a water landing. A further example of a foam floatation structure may be dense foam that enables floatation on water and may be wrapped around or substantially around an arm of the aerial vehicle **110** and/or the housing of the aerial vehicle **110**. A further example of a balloon floatation structure may include having the balloon within an arm or around an arm of the aerial vehicle. The balloon may be coupled with an air assembly, e.g., compressed air cartridge. The air assembly may be configured to inflate the balloon upon a signal from an external source, e.g., the remote controller **120**, configured to trigger (or activation) a switch to release the air from the compressed air cartridge into the balloon. Alternately, the air assembly may be configured to inflate the balloon or upon a sensor on the aerial vehicle **110** detecting water and triggering (or activating) the switch to release the air from the compressed air cartridge into the balloon.

The float structures, in addition to being removably coupled with the housing **130**, also are configured to be aerodynamic to reduce wind drag during flight. Further, the arms **135** also may include optional removable floatation structures that assist with overall buoyancy of the aerial



vehicle **110** in the event of a water landing or independently can float if they separate on from the housing **130** and land on water.

Turning now to further descriptions of configurations of the aerial vehicle **110**, FIG. 2B illustrates an example of the aerial vehicle **110** in an open position (or state). This example embodiment of the aerial vehicle **110** illustrates the housing **130**, removably foldable arms **135**, removable landing gear **272** (further described below), and the rotors **240**. Also shown is a start button **260** along a top of the housing **130**. The start button **260** can be used to place the aerial vehicle **110** in different operating states—e.g., ON, OFF, or STANDBY. Also shown is a gimbal opening **28** that is described further.

FIG. 2C illustrates an example of the aerial vehicle **110** in a closed (folded) position (or state) and the propellers **270** removed. In the closed position illustrated, the landing gear **275** can be folded under the housing **130** and/or decoupled from the housing **130**, e.g., for separate storage. Further, propellers **270** have been decoupled from the motors **240**, e.g., for separate storage. In addition, the arms **135** are shown folded against the housing **130** of the aerial vehicle **110**. In this example, the structural elements of the arms **135** help enhance portability of the aerial vehicle **110** in a closed position by providing a compact footprint. For example, the arms on the same side couple with the housing **130** such that when the arms are folded they are in a nested position relative to each other with rear arms substantially parallel with the front arms. Continuing with the example, a first set of arms (e.g., front arms) **135a** may have a lower elevational plane (e.g., “z-axis” plane) than a second set of arms (e.g., rear arms) **135b**, as further illustrated with FIGS. 2D and 2E, or vice versa. This offset can further help create a compact footprint in the closed position as at least a portion of the second arm may overlap with a portion of the first arm on its respective side in the nested position.

FIG. 2D and FIG. 2E illustrate additional views of the aerial vehicle **110**. FIG. 2D illustrates a first end view, e.g., where the gimbal opening **280** is located. FIG. 2E illustrates a second end view, e.g., opposite end of where the gimbal opening **280** (e.g., gimbal attachment mechanism) is located. The gimbal opening **280** is further described below.

In FIGS. 2D and 2E, the first set of arms **135a** are shown to be in a lower elevational plane (e.g., “z-axis” plane) along a portion of the arm than the second set of arms **135b**, which are in a higher elevational plane. As previously noted, this configuration helps allow the arms (generally **135**) to be closer to the housing **130** when the arms are rotated into a folding position, as further shown in FIG. 2C. Moreover, as each arm **135** can be a unibody construction. Unibody construction can help maintain structural rigidity and integrity by limiting potential break points while still providing a compact footprint.

The aerial vehicle **110** also includes removable landing gear **272**. The landing gear **272** can have two or more legs **275** (or arms). The legs **275** are what the aerial vehicle **110** rests upon when on the ground, e.g., prior to flight, at landing, etc. The landing gear **272** may be removably coupled with a bottom of the housing **130**. In addition, the legs **275** of the landing gear **272** can be folded flush or substantially flush against the bottom of the housing **130**.

FIGS. 2D and 2E illustrate the landing gear **272**. The landing gear **272** includes two pivot points **278** about which the legs **275** rotate to fold inward toward the bottom of the housing **130**. The landing gear **272** can be configured so that it fits within a recessed cavity of an underside, or bottom, of the housing **130**. The recessed cavity can allow the legs **275**

in the folded position to be substantially flush with the bottom of the housing **130** to further enhance portability by tucking the legs **275** within the overall aerial vehicle **110** volumetric footprint rather than having them remain apart from bottom of the housing **130** of the aerial vehicle **110**. The legs **275** of the landing gear **272** may be removable from the rest of the landing gear **272**. The legs **275** may be removed, for example, for storage, and/or replaced as needed, e.g., due to wear, tear, structural compromise, or updated structural configuration.

The landing gear **272** and/or its legs **275** may include optional removable flotation structures (e.g., foam or balloon) that assist with overall buoyancy of the aerial vehicle **110** in the event of a water landing or independently can float if they separate from the housing **130** and land on water. Moreover the landing gear **272**, including the legs **275**, may be made of a structurally rigid, yet buoyant material that can hold the weight of the aerial vehicle **110** when on the ground resting, and help with flotation in the event of a water landing.

The landing gear **272** may incorporate electronics and/or mechanical structures to extend and retract the legs **275** of the landing gear automatically. The electronics may have electrical connection points where the landing gear **272** can couple with the bottom of the housing. By way of example, the electronics may control the pivot points **278** to retract the foldable legs **275** toward a bottom of the housing **130** or extend away from the bottom of the housing **130**. By way of operational example, when the aerial vehicle **110** is at a predetermined distance from the ground (e.g., as detected from a proximity sensor on the aerial vehicle), the legs may be retracted during ascent (or lift off). When the aerial vehicle **110** is descending to land, when the aerial vehicle reaches a predetermined distance from the ground, the legs may be extended. Alternately, or in addition, the remote controller **120** may be used to transmit control signals to the aerial vehicle **110** to retract or extend the legs **275** of the landing gear **272**.

#### Removable Gimbal

Referring back to FIGS. 2A-2D, shown is the previously introduced gimbal opening **280**, which is integrated with the example embodiment of the aerial vehicle **110**. The gimbal opening **280** may be configured to receive a gimbal **210**. The gimbal opening **280** comprises a cavity that may include a releasable lock mechanism to receive an end of a gimbal **210** and securely connect (or couple) it relative to the aerial vehicle **110**. The coupling is such that the gimbal **210** can remain fixedly connected during flight. As the lock is releasable, the gimbal **210** can be disconnected (or decoupled) from the aerial vehicle **110** when desired. A portion of the gimbal opening **280** against the housing **130** may be sealed with a rubber gasket to assist with creating a water and/or dust barrier.

The gimbal **210**, when connected with the gimbal opening **280**, may be configured to allow for rotation of an object about an axis. The object in one example may be a camera mount **220**. The gimbal **210** allows for the camera mount **220** to maintain a particular position so that the camera mounted to it can assist with providing image stability and a consistent horizon view (a horizontal plane as may be predefined or defined by a user) or view relative to the horizon as the aerial vehicle **110** is in flight. The camera mount **220** may be, for example, a plate or a frame. In addition to allowing a camera (not shown in FIG. 2A) to couple (e.g., attach) to it, the camera mount **220** may include electrical connection points for the coupled camera. The electrical connection points can be used to power the camera

and/or communicate signals between the camera and the gimbal **210** and/or components of the aerial vehicle **110**.

The gimbal **210** can, in some example embodiments, be an electronic three-axis gimbal which rotates a mounted object (e.g., camera mount **220**, which may be a detachable camera frame connected to a camera) in space. Each axis of the gimbal **210** includes a motor (e.g., **210a**, **210b**) to control rotation. The gimbal **210** may include an electrical connection with a power subsystem of the aerial vehicle **110** to power the motors (e.g., **210a**, **210b**) or may include its own battery power supply. The gimbal may include connection electronics to provide part of an electronic connection between the camera and the aerial vehicle **110**. The gimbal may include a sensor unit and a control logic unit, both of which are part of a gimbal control system. The gimbal control system can detect the orientation of the gimbal **100** and camera, determine a preferred orientation of the camera, and control the motors of the gimbal in order to re-orient the camera to the preferred position.

A sensor unit within the gimbal can include an inertial measurement unit (IMU) which measures rotation, orientation, and acceleration using sensors, such as accelerometers, gyroscopes, and magnetometers. The sensor unit can contain rotary encoders, which detect the angular position of the motors of the gimbal **210**, and a magnetometer to detect a magnetic field, such as the earth's magnetic field. In some embodiments, the sensors of the sensor unit are placed such as to provide location diversity. For example, a set of accelerometers and gyroscopes can be located near the camera (e.g., near the connection to the detachable camera frame) and a set of accelerometers and gyroscopes can be placed at the opposite end of the gimbal (e.g., near the connection to the aerial vehicle **110**). The outputs of these two sets of sensors can be used by the IMU to calculate the orientation and rotational acceleration of the camera, which can then be output to the gimbal control logic. In some embodiments, the sensor unit is located on the aerial vehicle **110**. In some embodiments, the gimbal control logic receives data from sensors (e.g., an IMU) on the aerial vehicle **110** and from the sensor unit of the gimbal **210**.

In one embodiment, the gimbal **210** is removable from the camera mount **220** and structured for use with other devices, for example, a mount platform such as a tripod, a handheld grip, or an intelligent base. A mount platform also can removably couple with the gimbal **210**. By way of example, the mount platform (e.g., handheld grip) can include a plurality of buttons, which can be used by a user to control the camera and/or the gimbal **210**. Note that some mount platforms, e.g., handheld grip, may contain a battery from which it can provide power to the gimbal **210** and may also be used to power and/or charge the camera in addition to operating any electronic functions on the handheld grip itself. It is noted that the mount platform can have controls and circuitry for wireless communication with other computing devices.

#### Remote Controller

Referring next to the remote controller **120**, FIGS. 2F to 2I illustrate one example embodiment of the remote controller **120**. The remote controller **120** in this example includes a first control panel **150** and a second control panel **155**, an ignition button **160**, a return button **165** and a display **170**. It is noted that more or less control features and buttons may be included. In this example, the remote controller **120** can be used to control operation of the aerial vehicle **110**. This operation can include pitch, roll and yaw control for the aerial vehicle **110** in addition to other functions.

Continuing with the example, the control panels **150**, **155** can be used by a user to initiate control operations. The control panels can be mechanical (e.g., joystick, roller ball, etc.) or solid state (e.g., touch pad). For example, a first control panel **150** can be used to control vertical direction (e.g. lift and landing) of the aerial vehicle **110**. A second control panel **155** can be used to control horizontal (e.g., thrust/drag) direction of the aerial vehicle **110**. In addition, a combination of the panels **150**, **155** with another controller mechanism, e.g., a wheel, can be used for "left-right" and/or hover movement. It is noted that these are just examples and that the controllers can be assigned other or different functions.

The ignition button **160** can be used to remotely turn on and/or start (as well as turn off or pause operation of) the aerial vehicle **110** components. For example, a single press of the ignition button **160** may start operation of a first set of components, e.g., sensors and lighting, on the aerial vehicle **110** and a second press may start operation of a second set of components, e.g., the rotary assembly (e.g., start the propellers **140**), on the aerial vehicle **110**. The return to home (RTH) (or come home) button **165** can be used to override the controls of the remote controller **120** and transmit instructions to the aerial vehicle **110** to return to a predefined location. Examples of a return to home configuration as a part of a return path will be described further below.

The ignition button **160** and the return button **165** can be mechanical and/or solid state press sensitive buttons. In addition, each button **160**, **165** may be illuminated with one or more light emitting diodes (LED) to provide additional details. For example, the LED can switch from one visual state to another to indicate with respect to the ignition button **160** whether the aerial vehicle **110** is ready to fly (e.g., lit green) or not (e.g., lit red). The LED also can provide visual indicators corresponding to aerial vehicle **110** operation in flight, for example, if it is in an override mode on return path (e.g., lit yellow) or has a battery power level below a predefined threshold (e.g., lit green when above a first threshold, lit yellow when just below that threshold, and lit red below a lower threshold). It also is noted that the remote controller **120** may include other dedicated hardware buttons and/or switches and those buttons and switches may be mechanical and/or solid state buttons and switches. For example, another button may be added to transmit signals/instructions to the aerial vehicle **110** to deploy the parachute.

The remote controller **120** may include dedicated buttons corresponding to functions on the remote controlled aerial vehicle **110**, for example, a camera shutter button for signaling (or triggering) taking still or video images, changing image capture resolution, changing frame rate, etc. Other buttons can be used for functions such as camera controls, including control settings, for example, tagging images, transmitting (or sharing) captured images, etc.

The remote controller **120** may include a screen (or display) **170**. The screen **170** provides for visual display. The screen **170** can be a touch sensitive screen. The screen **170** can be, for example, a liquid crystal display (LCD), an LED display, an organic LED (OLED) display, or a plasma screen, etc. The screen **170** allows for display of information related to the remote controller **120**, for example, menus for configuring the controller **120** and/or remotely configuring the aerial vehicle **110**, and/or controlling a camera and/or gimbal **210** coupled with the aerial vehicle **110**. The screen **170** can display images captured from a camera coupled with the aerial vehicle **110**.

## 11

The remote controller **120** in this example includes a two-part casing (or housing) that may be coupled via pivot points **291**. The pivot points **291** may be a mechanical hinge. For example, a first part casing (or first casing) may include the screen **170**. Further by example, a second part casing (or second casing) may include the control panels **150**, **155**, buttons **160**, **165** and a speaker **293**. Each casing may include a cavity to house electronics and/or sensors for the components noted. Within either or both portions of the casing there may be an internal antenna. The antenna also may be configured external to the casing or a combination of internal and external.

In the example configurations of FIGS. 2F and 2G, illustrated is the remote controller **120** in an open position. This example remote controller **120** shows a power button **290**, pivot points **291**, wheel **292** and a speaker **293**. Here, the casing is illustrated in two portions, one with the screen **170** and one with the other components such as the control panels **150**, **155**, buttons **160**, **165** and the speaker **283**. Each in this example is individually enclosed. The two parts of the casing are coupled through pivot points **291**. The pivot points **291** are points or ends about which the first casing having the screen **170** rotates to cover the second casing to form a “closed” state of the remote controller **120**, as shown in FIGS. 2H and 2I.

In these example illustrations of the remote controller **120**, the shown power button **290** may powers the remote controller **120** in an ON, OFF, or STANDBY state. The wheel **292** can be provide assigned functionality, for example, fine movements, “left or right” and/or hover movements. The speaker **293** may be used for audio playback through the remote controller **120**. FIGS. 2H and 2I illustrate an example remote controller **120** in a closed position. FIG. 2I in particular also illustrates, by way of example, an additional switch **294**, which can be assigned functionality, including, for example, power state, or locking, etc.

FIG. 3 illustrates an example embodiment of an electronics and control (EC) system **310** of the aerial vehicle **110**. The example EC system **310** may include a flight controller **315**, an electronic speed controller (ESC) **320**, one or more thrust motors electronics **325**, a gimbal controller **330**, a sensor subsystem (which may include telemetric subsystems) **335**, a power subsystem **340**, an image link controller **345**, a camera interface **350**, and a long range communication subsystem **360**. The components communicate directly or indirectly with each other through a data bus within the aerial vehicle **110**.

The aerial vehicle **110** components may be embodied in hardware, software, or a combination thereof. The software, which can include firmware, may be referenced as program code, computer program product, or program instructions, and may be comprised of one or more instructions. Software may include an operating system, which provides an interface to a processor, and on which software applications run (or execute). Software can be executed by one or more processors within the aerial vehicle **110**. A processor also may include, for example, controllers, application specific integrated circuits (ASICs) and/or field programmable gate arrays (FPGAs). The processor can be configured to execute the software in a specific manner. FIG. 14 provides an example machine architecture with a processor that can be configured to execute software. It is noted that not all the components of FIG. 14 may be included in the aerial vehicle **110**. FIG. 14 is intended to be illustrative in describing an architecture of a computing system, of which all or parts can operate within the aerial vehicle **110** and the EC system **310**.

## 12

In this example, the aerial vehicle **110** may be configured to include an aerial vehicle operating system (AVOS). By way of example, the AVOS can be built on an operating system kernel, for example, LINUX, and/or be based on an operating system such as ANDROID OS. The software components of aerial vehicle described in the disclosure operate with the AVOS. Examples of these software configurations are found throughout this disclosure.

Turning now to the example components of the EC system **310**, a further description of each component is provided. In one example embodiment, the flight controller **315** of the EC system **310** coordinates and processes software for the aerial vehicle **110**. The flight controller **315** may integrate the AVOS. Examples of processing directed by the flight controller **315** include coordinating communication with the remote controller **120** through the communication subsystem **360** and processing commands to and from the remote controller **120**. The flight controller **315** also may control flight related operations of the aerial vehicle **110** by control over the other components such as the electronic speed controller **320** and the sensor subsystem **335**. The flight controller **315** also interfaces with the gimbal control **330** to assist with controlling the gimbal motors of the gimbal **210**. In addition, the flight controller **315** may be used to assist with the image link **345** for camera control operations.

Referring now to the electronic speed controller **320**, it is configured to interface with the thrust motors electronics **325**. The electronic speed controller **320** may be configured to control, via the thrust motors electronics **325**, the speed applied by the thrust motors **240** to the propellers **140**. The electronic speed controller **320** may control each thrust motor **240** through the thrust motors electronics **325** individually or in groups or subgroups. It is noted that the thrust motors electronics **325** may be integrated with the thrust motors **240**.

Next, the gimbal controller **330** may include control electronics (and may include firmware) that may be configured to control operation of the motors for each axis of the gimbal. The gimbal controller **330** receives commands via the flight controller **315**. The commands may originate from the remote controller **120**, which passes them to the flight controller **315** via the communication subsystem **360**.

Turning next to the image link controller **345**, it is configured to communicate with the camera interface **345** to transmit commands that can include capture of images from a camera for transmission to the remote controller **120** (and/or other device with screen such as a smart phone or tablet), e.g., via the communication subsystem **360**. The images may be overlaid and/or augmented with other data from the aerial vehicle such as the sensor data from the sensor subsystem **335**. When images are sent to both the remote controller **120** and another device, the overlaid information may be the same on each device or distinct on each device. It is noted that the image link controller **345** may have a processing configuration that allows commands to be directly transmitted between the communication subsystem **360** and the camera interface **350**. Alternately, or in addition, the image link controller **345** may communicate with the flight controller **315** for processing resources and application of software configurations.

The camera interface **350** may be configured to receive camera control commands from the image link controller **345**. The camera commands can include commands to set up camera operations, e.g., frame capture rate, still or video images, etc. The camera commands may originate from the

remote controller **120** and be received via the communication subsystem **360** and image link controller **345** of the EC system **310**.

Turning next to the sensor subsystem **335**, it may include one or more sensors. Each set of sensors may be further grouped as sensor modules to gather particular types of data. For example, one sensor module may be for positional sensors and another sensor module may be for environmental sensors. Positional sensors can provide location and/or relative location in space and orientation information of the aerial vehicle **110**. Positional sensors can assist with navigation and location related operations of the aerial vehicle **110**. Positional sensors can include, for example, a gyroscope, accelerometer, a compass, a global positioning system (GPS) sensor, a motion sensor, and/or an altimeter. Environmental sensors can provide information of a particular environment. For example, environmental sensors can provide information on environmental conditions external to the housing **130** of the aerial vehicle **110**. Further by example, environmental sensors can provide information on conditions within the housing **130** of the aerial vehicle **110**. Environmental sensors can include, for example, a temperature sensor, a photo detector, a heat sensor, a moisture sensor, and/or a barometric sensor. It is noted that in some example instances an environmental sensor can also operate as a positional sensor for purposes of how the data may be used and vice versa. For example, a photo detector may be used to determine time of day for a flight, but also can be used to detect shadows for avoidance detection during flight of the aerial vehicle **110**. Similarly by way of example, a barometric sensor may be used to determine atmospheric pressure and aerial vehicle **110** altitude. Note that other sensor configurations also may be included in addition to the examples given.

The sensor data from the sensor subsystem **335** may comprise sensor metadata and can be integrated with images and/or metadata from a camera. The images from the camera, which may also include additional metadata, can be transmitted wirelessly to other devices and/or stored for later playback. When the images are displayed (e.g., played in real time or from storage), the sensor data can be extracted from it and provided for display on a screen, e.g., the screen **170** of the remote controller **120** or a screen of a computing device (e.g., laptop, smartphone, tablet, desktop computer, etc.). The camera interface **350** can interface with a camera or may include an integrated camera. The integrated camera would be positioned similar to the camera mount **220**. Alternately, the camera may incorporate a camera mount.

The power subsystem **340** may be configured to manage and supply power to the components of the EC system **310**. The power subsystem **340** can include a battery pack and a protection circuit module as well as a power control/battery management system. The battery can be replaceable and/or rechargeable. The battery of the power subsystem **340** can be configured to charge the camera in flight as needed or pre-flight. Other devices also may be charged using the energy capacity of the battery of the power subsystem **340**, for example, the remote controller **120**, a powered handheld grip, or a mobile phone. The battery also can be used to charge the camera, or other devices, post-flight, depending on energy remaining in the battery. Further, the power subsystem **340** can be configured to include a dual power path. A first path allows for a first power level, e.g., low current, to be used to power up the aerial vehicle **110** and its onboard components. Once components are powered the aerial vehicle **110** can transition to a second power level, e.g., high current, which is sufficient to consistently drive the

thrust motors **240** and onboard components during flight. In addition, a regenerative charging configuration can be integrated into the power subsystem **340**. For example, the power subsystem **340** can include a recharge circuit electrically coupled with the thrust motors **240** so that when the thrust motors **240** are decelerating, current is pushed back through the recharge circuit to charge the battery of the power subsystem **340**.

The communication subsystem **360** may include communication electronics (and may include corresponding firmware) for the aerial vehicle **110**. For example, the communication subsystem **360** can include a long range Wi-Fi system. It can include additional wireless communication components. For example, it may include another Wi-Fi system, which may allow for one Wi-Fi system to be dedicated to direct control communications with the remote controller **120** and the other Wi-Fi system may be used for other communications, such as image transmissions). It can include a communication system such as one based on long term evolution (LTE), 3G, 4G, 5G or other mobile communication standard. The communication subsystem **360** may be configured with a uni-directional remote control channel for communication of controls from the remote controller **120** to the aerial vehicle **110** and a separate unidirectional channel for an image downlink from the aerial vehicle **110** to the remote controller **120** (or to a video receiver where direct image connection may be desired). The communication subsystem **360** can be used to allow for other services, for example, to provide over the air or hardware link updates, such as firmware updates to the aerial vehicle **110**. Some third-party services may be provided access to the communication subsystem **360** or components within via application programming interfaces (API).

Example Interconnect Architecture for Aerial Vehicle

Turning to FIG. 4, it illustrates an example interconnect architecture of the remote controlled aerial vehicle **110** with the gimbal **220**. This example embodiment includes the components illustrated and described in the prior figures, e.g., FIG. 3. In addition, there are shown additional components such as LEDs **410** on the aerial vehicle **110** that can be used to provide information, e.g., vehicle status related information. Also shown is a battery **440** as a part of the power subsystem **340**. The battery **440** provides direct current power and may be rechargeable. Also illustrated is an antenna **460**, which may be part of the communication subsystem **360**.

In addition, the figure illustrates an example embodiment in which the flight controller **315** is coupled with two electronic speed controllers **320**. Each electronic speed controller **320** in this configuration drives two thrust motors **240**, for example, through the thrust motors electronics **325** (not shown).

Also shown is a gimbal interface **430** that can couple the gimbal controller **330** with components of the EC system **310**. In particular, the gimbal interface **430** is communicatively coupled with the image link controller **345**, the sensor subsystem **335** (e.g., GPS, compass, etc.), and the antenna **460**. The gimbal interface **430** is used to transmit this data to the gimbal controller **330**. The gimbal controller **330** uses this data to adjust the camera mount **220**. It is noted that the camera mount **220** can secure a camera **450**.

The gimbal controller **330** is communicatively coupled with the camera **450** through one or more camera interface **350** connectors. The camera interface **350** connectors can include camera communication interfaces such as universal serial bus (USB) or HDMI. The images captured by the camera can be communicated (transmitted) back to the aerial

15

vehicle 110 through the camera interface 350 connectors and gimbal interface 430. The transmission of the images may be at high (or full) resolution (e.g., uncompressed) or at a lower (or partial) resolution (e.g., compressed). Data, e.g., sensor data from the sensor subsystem 335, also can be sent via the camera interface 350 connectors to the camera 450 to associate with frames captured and stored on the camera 450.

#### Example Camera Architecture

FIG. 5 illustrates a block diagram of an example camera architecture 505. The example camera architecture 505 corresponds to an architecture for the camera, e.g., 450. It is noted that the camera 450 may be independent of or integrated with the aerial vehicle 110. When integrated with the aerial vehicle 110, the camera 450 may also be integrated with a gimbal, e.g., 210. Alternately, when independent, the camera 450 may be removably attached to the aerial vehicle 110. When removably attached, the camera 450 may be removably coupled to the gimbal 210 that couples the aerial vehicle 110. As previously noted, the gimbal 210 may be removably coupled with the aerial vehicle 110. Alternately, the gimbal 210 may be integrated with the aerial vehicle 110. For ease of discussion, the camera 450 is described in a configuration where it is removably coupled with the gimbal 210 via a camera mount 220 and the gimbal 210 also is removably coupled with the aerial vehicle 110. However, the principles noted apply also in the instances in which the camera is integrated with the aerial vehicle 110.

Referring briefly to the camera 450 itself, it can include a camera body, one or more camera lenses, various indicators on the camera body (such as LEDs, displays, and the like), various input mechanisms (such as buttons, switches, and touch-screen mechanisms), and electronics (e.g., imaging electronics, power electronics, metadata sensors, etc.) internal to the camera body for capturing images via the one or more lenses and/or performing other functions. In one embodiment, the camera 450 is capable of capturing spherical or substantially spherical content. As used herein, spherical content may include still images or video having spherical or substantially spherical field of view. For example, in one embodiment, the camera 450 captures video frames having a 360 degree field of view in the horizontal plane and a 180 degree field of view in the vertical plane. Alternatively, the camera 450 may capture substantially spherical images or video frames having less than 360 degrees in the horizontal direction and less than 180 degrees in the vertical direction (e.g., within 10% of the field of view associated with fully spherical content). In other embodiments, the camera 450 may capture frames having a non-spherical wide angle field of view.

As described in greater detail below, the camera 450 may include sensors to capture metadata associated with frame data, such as timing data, motion data, speed data, acceleration data, altitude data, GPS data, and the like. In one example embodiment, location and/or time centric metadata (geographic location, time, speed, etc.) can be incorporated into an image (or media) file together with the captured content in order to track over time the location of the camera 450 or the subject being recorded by the camera 450. This and sensor metadata may be captured by the camera 450 itself or by another device proximate to the camera 450 (e.g., a mobile phone, a data tracker worn by a subject (e.g., a smart watch or fitness tracker equipped with tracking software or a dedicated radio frequency tracker), the aerial vehicle 110 via the camera interface 350, etc.).

In one embodiment, the metadata may be incorporated with the content stream by the camera 450 as the content is

16

being captured. In another embodiment, a metadata file separate from the image file may be captured (by the same capture device or a different capture device) and the two separate files can be combined or otherwise processed together in post-processing. It is noted that these sensors can be in addition to the sensors of the sensor subsystem 335. In embodiments in which the camera 450 is integrated with the aerial vehicle 110, the camera need not have (or need not operate) separate individual sensors, but rather could rely upon the sensors integrated with the aerial vehicle 110. The data captured by the sensors may be referenced as sensor metadata. The sensor metadata, as well as camera metadata from the camera 450, may be integrated with and/or used with aerial vehicle metadata captured from sensors on the aerial vehicle 110, for example, the environmental sensors, positional sensors, etc.

Referring now to the example camera architecture 505 of the camera 450, it may include a camera core 510 comprising a lens 512, an image sensor 514, and an image processor 516. The camera 450 also may include a system controller 520 (e.g., a microcontroller or microprocessor) that controls the operation and functionality of the camera 450 and system memory 530 configured to store executable computer instructions that, when executed by the system controller 520 and/or the image processors 516, perform the camera functionalities described herein. In some embodiments, a camera 450 may include multiple camera cores 510 to capture fields of view in different directions which may then be stitched together to form a cohesive image. For example, in an embodiment of a spherical camera system, the camera 450 may include two camera cores 510 each having a hemispherical or hyper hemispherical lens that each captures a hemispherical or hyper hemispherical field of view which is stitched together in post-processing to form a spherical image.

The lens 512 can be, for example, a wide angle lens, hemispherical, or hyper hemispherical lens that focuses light entering the lens to the image sensor 514 which captures frames. The image sensor 514 may capture high-definition images having a resolution of, for example, 720p, 1080p, 4 k, or higher. In one embodiment, spherical images may be captured as a 5760 pixels by 2880 pixels with a 360 degree horizontal field of view and a 180 degree vertical field of view. For images, the image sensor 514 may capture images at frame rates of, for example, 30 frames per second, 60 frames per second, 120 frames per second or higher.

The image processor 516 can perform one or more image processing functions of the captured frames. For example, the image processor 516 may perform a Bayer transformation, demosaicing, noise reduction, image sharpening, image stabilization, rolling shutter artifact reduction, color space conversion, compression, or other in-camera processing functions. The image processor 516 also may be configured to perform real-time stitching of images, for example, when images are captured from two or more cameras coupled with the aerial vehicle 110 and configured to capture images. Such example configurations may include, for example, an activity camera (which may include a spherical image capture camera) that captures images, each with a substantially different field of view (FOV), but where there may be some overlap where the images can be stitched together. Processed images may be temporarily or persistently stored to system memory 530 and/or to a non-volatile storage, which may be in the form of internal storage or an external memory card, as shown and described in the example architecture of FIG. 4.

An input/output (I/O) interface **560** transmits and receives data from various external devices. For example, the I/O interface **560** may facilitate the receiving or transmitting image information through an I/O port. Control information, e.g., from/to a gimbal controller **330**, also may be transmitted via the I/O interface **560**. Examples of I/O ports or interfaces include USB ports, HDMI ports, Ethernet ports, audio ports, and the like. Furthermore, embodiments of the I/O interface **560** may include wireless ports that can accommodate wireless connections. Examples of wireless ports include Bluetooth, Wireless USB, Near Field Communication (NFC), and the like. The I/O interface **560** may also include an interface to synchronize the camera **450** with other cameras or with other external devices, such as a remote control, a second camera, a smartphone, a client device, or a video server. For example, a camera **450** mounted to an aerial vehicle **110** may be synchronized wirelessly (e.g., using time codes) with a camera on another aerial vehicle or on the ground so that frames captured by the various cameras can be synchronized.

A control/display subsystem **570** includes various control components associated with operation of the camera **450** including, for example, LED lights, a display, buttons, microphones, speakers, etc. The audio subsystem **550** includes, for example, one or more microphones and one or more audio processors to capture and process audio data correlated with frame capture. In one embodiment, the audio subsystem **550** includes a microphone array having two or microphones arranged to obtain directional audio signals.

Sensors **540** capture various metadata concurrently with, or separately from, image capture. For example, the sensors **540** may capture time-stamped location information based on a global positioning system (GPS) sensor. Other sensors **540** may be used to detect and capture orientation of the camera **450** including, for example, an orientation sensor, an accelerometer, a gyroscope, an altimeter, or a magnetometer. Sensor data captured from the various sensors **540** may be processed to generate other types of metadata. For example, sensor data from the accelerometer may be used to generate motion metadata, comprising velocity and/or acceleration vectors representative of motion of the camera **450**. Furthermore, sensor data from the aerial vehicle **110** and/or the gimbal **210**/gimbal controller **330** may be used to generate orientation metadata describing the orientation of the camera **450**. Sensor data from the GPS sensor provides GPS coordinates identifying the location of the camera **450**, and the altimeter measures the altitude of the camera **450**. In one embodiment, the sensors **540** are rigidly coupled to the camera **450** such that any motion, orientation or change in location experienced by the camera **450** is also experienced by the sensors **540**. The sensors **540** furthermore may associate one or more time stamps representing when the data was captured by each sensor. In one embodiment, the sensors **540** automatically begin collecting sensor metadata when the camera **450** begins recording a video. As noted previously, the sensor data from the camera architecture may be integrated with and/or used with sensor data from the aerial vehicle **110**. It is noted that in example embodiments in which sensors of a particular type are missing from the aerial vehicle **110**, the sensors **540** of the camera **450** can provide the requisite sensor data for appropriate processing operations.

As noted above, the camera **450** may also be controlled remotely, for example, through the remote controller **120**, or through other devices in wireless communication with the camera, either directly or through the aerial vehicle **110**. Accordingly, control functions of the camera **450** can be

manipulated before, during or after flight (e.g., at landing). For example, during flight the camera **450** can be configured to switch from shooting images at 30 frames per second to 60 frames per second (fps). In this example, an aerial vehicle **110** may follow a skier down a slope and start capturing images through the camera **450** at 30 fps. As the skier accelerates, e.g., for a jump, the camera **450** automatically switches to capturing images at 60 fps. Also by way of example, if the skier is in the distance, e.g., 20 meters, the camera **450** may begin to capture images at 30 fps, but as the aerial vehicle draws closer, e.g., within 5 meters, the camera **450** can automatically switch to capturing images at 60 fps.

Moreover, an operator may seek to switch the camera **450** from taking images, in one mode, e.g., low resolution images (e.g., lower pixel count, lower frames per second, etc.), to taking images in another mode, e.g., high resolution images (e.g., higher pixel count, higher frames per second, etc.), while the aerial vehicle **110** is in flight and the camera **450** is operational. The positioning of the camera **450** can also be further controlled from an operator on the ground transmitting signals from the remote controller **120** or mobile device to move the camera angle through movement of appropriate gimbal **210** components. Further by example, at landing the camera **450** can be configured to take images, e.g., to assist with location analysis for locating the aerial vehicle **110**.

#### Example System Components of the Remote Controller

Referring now to FIG. 6, it illustrates a block diagram of example electronics system **605** components and/or subsystems of a remote controller, e.g., **120**. The electronics system **605** may include a processing subsystem **610**, a navigation subsystem **620**, an input/output (I/O) subsystem **630**, a display subsystem **640**, an audio/visual (A/V) subsystem **650**, a control subsystem **660**, a communication subsystem **670**, a power subsystem **680**, and sensor subsystem **690**. The subsystems may be communicatively coupled through a data bus **698** and may be powered, where necessary, through the power subsystem **680**.

The processing subsystem **610** may be configured to provide the electronic processing infrastructure to execute firmware and/or software comprised of instructions. The software, which can include firmware, may be referenced as program code, computer program product, or program instructions, and comprises instructions. Software, which may include operating system software, may be executed by one or more processors with the remote controller **120**. A processor also may include, for example, controllers, application specific integrated circuits (ASICs) and/or field programmable gate arrays (FPGAs). The processor may be configured to execute the software in a specific manner. Software may be configured to operate with an operating system, which provides an interface to the processor.

The processing subsystem **610**, which may include one or more processors, may be part of a machine and/or computer system. FIG. 14 provides an example machine with a processor that can be configured to execute software as part of the processing subsystem **610**. It is noted that not all the components of FIG. 14 may be included in the remote controller **120**. FIG. 14 is intended to be illustrative in describing an architecture of a computing system, of which all or parts can operate as part of the processing subsystem **610** of the remote controller **120**.

The processing subsystem **610** in this example also may be configured to include a remote controller operating system (RCOS). The RCOS may be built upon an operating system kernel, for example, an LINUX kernel, and/or an existing operating system, for example, an ANDROID oper-

ating system. In addition, the processing subsystem **610** can provide the execution framework for applications built to operate within the remote controller **120**.

The navigation subsystem **620** may include electronics, controls and interfaces for navigation instrumentation for the remote controller **120**. These may be embodied in hardware, software, or a combination thereof. For example, the navigation subsystem **620** uses a global position system (GPS) and a compass embodied in hardware (see sensor subsystem **690** below) and/or software for providing coordinates and headings information of the remote controller **120** relative to the aerial vehicle **110**. In this example, the GPS and/or compass may be used to track location and heading of the remote controller **120**, which can be helpful for the remote controller **120** and the aerial vehicle **110** to computationally understand location and positioning of each relative to the other.

The I/O subsystem **630** may include the input and output interfaces and electronic couplings to interface with devices that allow for transfer of information into or out of the remote controller **120**. For example, the I/O subsystem **630** can include a physical interface such as a universal serial bus (USB) or a media card (e.g., secure digital (SD)) slot. The I/O subsystem **630** also can be associated with the communication subsystems **670** to include a wireless interface, e.g., Bluetooth or a near field communication interface. In addition, it is noted that in one example embodiment, the aerial vehicle **110** uses long range Wi-Fi radio within the communication subsystem **670**, but may also use a second Wi-Fi radio or cellular data radio (as a part of the I/O subsystem **630**) for connection other wireless data enabled devices, for example, smart phones, tablets, laptop or desktop computers, and/or wireless internet access points. Moreover, the I/O subsystem **630** may also include other wireless interfaces, e.g., radio frequency tags, cellular (mobile) communication protocols, short range Wi-Fi, etc., for communicatively coupling devices that are similarly wirelessly enabled for short range communications.

The display subsystem **640** may be configured to provide an interface, electronics, and display drivers for the screen **170** of the remote controller **120**. The display subsystem **640** can be configured to display information corresponding to the remote controller **120**, for example, menus, settings, control information, etc. The display subsystem **640** also can be configured to display images captured from the camera **450** on the aerial vehicle **110**. Moreover, the display subsystem can overlay images captured from camera on the aerial vehicle **110** with a display of gauges corresponding to metadata associated with captured frames in a “dashboard” type visual display.

The A/V subsystem **650** may include the interfaces, electronics, and drivers for an audio output (e.g., headphone jack or speakers) as well as visual indicators (e.g., LED lighting associated with, for example, the buttons **160**, **165**). The A/V subsystem **650** can be configured to provide alarms, indicators, or other types of notifications audibly, visually, or a combination thereof. The notifications can be in voice format. The A/V subsystem **650** can provide notifications corresponding to operation of the aerial vehicle **110** and/or the remote controller **120**. For example, if battery power level drops below predetermined threshold on the aerial vehicle **110**, the aerial vehicle **110** can communicate this information back to the remote controller **120**. The communication subsystem **670** of the remote controller **120** receives this information and it gets passed to the A/V subsystem **650**. The A/V subsystem **650** can provide a visual notification, e.g., flashing or lighting an LED or light in red

and/or an audible notification such as a beeping alarm and/or pre-recorded voice notice (“low battery”). The A/V subsystem **650** also can provide notifications of other devices that may be communicatively coupled with the remote controller **120**, e.g., a smartphone coupled with the remote controller **120** through a Bluetooth connection.

The control subsystem **660** may include electronic and control logic and firmware for operation with the control panels **150**, **155**. The control subsystem **660** translates movements made through the control panels **150**, **155** into appropriate movement commands corresponding to the aerial vehicle **110**. The movement commands are transmitted through the communication subsystem **670** described below. The control subsystem **660** can be configured so that coarseness of movements through the control panels **150**, **155** can be calibrated prior to transmission to the aerial vehicle **110**. For example, users having a “light” touch (e.g., refined, smooth movement) can have touches through the control panels **150**, **155** translated by the control subsystem **660** into a greater range of fine movements. Also by example, user with a “heavy” touch (e.g., more “jerky” control) can have touches through the control panels **150**, **155** translated by the control subsystem **660** to have a lower range of fine movements to help ensure that such movements to not inadvertently jar the aerial vehicle **110** to an extreme operating condition that may cause it to stop flying.

The communication subsystem **670** may include electronics, firmware and interfaces for communications. The communications subsystem **670** can include one or more of wireless communication mechanisms, for example, Wi-Fi (short and long range), cellular/mobile communication systems (e.g., long term evolution (LTE), 3G/4G/5G), Bluetooth, etc. The communication subsystem **670** can include wired communication mechanisms such as Ethernet, USB, and HDMI. The communication subsystem **670** can be used to allow for third-party services to provide over the air or hardware link updates, such as firmware updates to the remote controller **120**. It is noted that in some example embodiments, the communication subsystem **670** can include two (or more) different Wi-Fi radios for communication. For example, one radio can be configured to be a dedicated connection between a Wi-Fi radio in the communication subsystem **670** of the remote controller **120** and a Wi-Fi radio in the communication subsystem **360** of the aerial vehicle **110**. This dedicated radio link (or communication coupling) may be for transmitting and receiving communications associated with flight control. The dedicated link can help enhance communication between the devices as no other devices may compete for bandwidth and processing cycles. Continuing with the example, a second radio can be configured for other communications, for example, transmission of images and/or data from the remote controller **120** to another device, e.g., a mobile hotspot, a laptop computer, a tablet, a smartphone, etc.

The power subsystem **680** may include electronics, firmware and interfaces for providing power to the electronics system **605** of the remote controller **120**. The power subsystem **680** may include direct current (DC) power sources (e.g., batteries, which may be rechargeable), but also can be configured for alternating current (AC) power sources. The power subsystem **680** also may include power management processes for extending DC power source lifespan.

In some embodiments, the power subsystem **680** may be comprised of power management integrated circuit and a low power microprocessor for power regulation. The microprocessor in such embodiments is configured to provide very low power states to preserve battery, and ability to wake

from low power states from such events as a button press or an on-board sensor (like a Hall effect sensor) trigger. It is noted that the power subsystem **680** may include a battery system that is replaceable and/or rechargeable. The battery can include a high energy storage capacity and can be configured to couple its power line with an interface, e.g., a universal serial bus interface, to which other devices, e.g., the aerial vehicle **110**, a mobile computing device, etc., can connect to have their batteries charge using this battery source.

The sensor subsystem **690** may include a wide range of sensors. For example, in addition to a GPS, the remote controller **120** also may include sensors such as barometer, temperature, altitude, moisture, etc. The sensor data from the sensors can be integrated with images received from a camera. The sensor data can augment or supplement the sensor data captured and received from the aerial vehicle **110** and/or the camera **450**. When the image is displayed (real time or from storage), the sensor data can be extracted from it can be provided for display on a screen, e.g., the screen **170** of the remote controller **120** or a screen of a computing device (e.g., laptop, smartphone, tablet, or desktop computer). The sensor data from the sensor subsystem **690** also can be used to assist with aerial vehicle **110** operations.

#### Pipeline Video Interface for Camera System

Turning now to preparing a camera mounted on an aerial vehicle, e.g., **110** to send frames to a display on the remote controller, when the aerial vehicle **110** is in flight, the disclosed configuration includes a method for reducing the latency of the wireless transfer of frames from the camera (e.g., **450**) to the display (e.g., **170**).

FIG. 7A illustrates a block diagram of the video pipeline and the latency through each module of the pipeline, according to an example embodiment. The video pipeline system **702** includes a camera module **705**, an encoder module **710**, a Wi-Fi transmitter (Wi-Fi Tx) module **715**, a Wi-Fi receiver (Wi-Fi Rx) module **720**, a decoder module **725** and a display module **730**. The camera module **705**, encoder module **710** and the Wi-Fi Tx module **715** are a part of the camera system **450** mounted on the aerial vehicle **110**. The camera module **705** and the encoder module **710** may be a part of the image processor **516** of the camera system **450**. The Wi-Fi Tx module **715** may be a part of the I/O interface **560** of the camera system **450**. The Wi-Fi Rx module **720**, the decoder module **725** and the display module **730** may be part of the remote controller **120** (e.g. as part of the electronics system **605**) of the aerial vehicle **110** located on the ground. Specifically, the Wi-Fi Rx module **720** may be a part of the communication subsystem **670** and the decoder module **725** may be a part of the processing subsystem **610**, and the display module **730** may be a part of the display subsystem **640**. It is noted that the modules may be embodied as software (including firmware) comprised on program code (or software or instructions) executable by the processing subsystem **610**.

Additionally, FIG. 7B illustrates the latency of a single frame through each module in the pipeline. The camera module **705** captures a frame, using the camera lens and sends the first bit to the last bit of an image or a frame to the HDMI port. This is known as the capture time. The captured frame may be processed by the encoder module **710**. The processing may include converting the frame to a standard format such as JPEG, MPEG or any other such format. The processed frame is packetized and transmitted by the Wi-Fi Tx module. The encoding, packetizing and transmitting together may be the frame latency. The Wi-Fi Rx module

**720** receives the frame, the decoder module **725** decodes and rotates the frame and the display module **730** displays the frame. The receiving, decoding, rotating and displaying time together is the display latency. The sum of the capture time, frame latency and display latency may be the total latency of a single frame.

The total latency of a frame without pipelining may be, for example, approximately 224 ms (67 ms at the camera module **705**+50 ms at the encoder module **710**+34 ms at the Wi-Fi Tx module **715**+33 ms at the Wi-Fi Rx module **720**+40 ms at the decoder module **725**+17 ms at the display module **730**). As shown in FIG. 7B, the camera latency (67 ms) includes the time taken by a camera lens (glass) to capture and deliver the first bit on HDMI (50 ms) and latency of propagation of the first bit to last bit from the camera lens on HDMI (17 ms). The encoder module latency of 50 ms includes the capture the bits from HDMI to the encoder (17 ms) and the encoding latency (33 ms). The 34 ms at the Wi-Fi Tx module **715** includes latency involved in packetizing and transmitting the frame bits. The receiver latency to receive all the bits of a frame by the Wi-Fi Rx module **720** is 33 ms. The decoder latency of 30 ms includes latency of decoding the bits of the frame (24 ms) and rotating (or post-processing) any bits of the frame (16 ms). Finally, the display latency is 17 ms.

The total latency shown in FIG. 7B may be the reduced latency, obtained by pipelining the processing elements involved in capturing a frame by a camera system (e.g., **450**), processing the frame by the aerial vehicle (e.g., **110**) and displaying the frame by a remote controller (e.g., **120**). The total latency may be reduced by breaking each processing element into smaller tasks that can be computed in parallel or can be pipelined, contributing to reducing the total latency. The different systems and methods of reducing the total latency are described below with respect to FIGS. 8-11.

FIG. 8 illustrates multiple frames through different stages of a video pipeline, according to an embodiment. The video pipeline includes five stages within the encoder and Wi-Fi Tx module, representing the frame latency in the system. The five stages are capture (c1, c2, c3 . . . cn), encode (e1, e2, e3 . . . en), packetize (p1, p2, p3 . . . pn), transmit (t1, t2, t3 . . . tn) and stall (s1, s2, s3 . . . sn) in each stage corresponding to a last packet. The figure shows three frames through the different stages of the pipeline. Every other frame is dropped as a result of image pipeline over-clocking. The image pipeline over-clocking is described in detail with respect to FIG. 9A.

Each stage from capture to transmit may be pipelined and lined up in time such that every frame may be transmitted immediately after the one before it. A stall stage may be inserted between the pipeline stages to comply with worst case transmission calculations, i.e., every transmit stage of consecutive frames must follow each other, i.e., t1 follows t2, t2 cannot be sent until t1 finishes. If the transmit occurs slower than the frame latency, the frame is dropped (e.g., 2nd frame in the figure).

Pipeline over-clocking uses the fastest possible clock frequency and frame rate in the camera system to minimize latency. Data may be dropped or decimated later to get back to the desired frame rate. For example, a camera system that will transmit frames at 30 frames per second needs to run its capture hardware clock at a frequency of  $\frac{1}{30}$  seconds to process one frame and thus have an average input latency of  $\frac{1}{(30 \times 2)}$  seconds. If the camera system is capable of running the hardware clock at a frequency high enough to capture 60 frames per second, the average input latency is reduced to



1/(60\*2) seconds and a single frame processing would complete in 1/60 seconds, thus reducing an overall frame latency.

FIG. 9A illustrates a conventional and overclocked frames, and its impact on input, output, and frame latency, according to an embodiment. For a frame rate, "f" in frames per second, the time for processing one frame (Tfps) is 1/f seconds, the input latency (Tc) and the output latency (Td) is Tfps/2. The overclocked system may be clocked at twice the speed of a conventional system as shown in FIG. 9A. The time for processing one frame (Tover) is Tfps/2 seconds, the input latency (Ta) and the output latency (Tb) is Tover/2. Tinter is the time between processing frames 1-(Tfps/2), this time is idle and is used to perform other operations in the video pipeline discussed above with respect to FIG. 7. As the rate of overclocking increases, the processor idle time increases and the frame latency can be improved by a theoretical maximum of

$$T(\text{improvement theoretical max}) = Tc + Td + Tfps = 2 * Tfps.$$

FIG. 9B further illustrates pipeline forwarded frames, according to an example embodiment. Pipeline forwarding may include performing latency sensitive external operations prior to the latency insensitive ones. For example, a camera 450 may capture an image in stage c1 of a video pipeline as shown in FIG. 8, in an alternate embodiment, the image may be preprocessed in the p1 stage before encoding in the e1 stage and sent on the Wi-Fi interface without encoding or packetizing it. The captured frame may be encoded e1 in a later stage of the pipeline and stored on a storage system for accessing it in the future. The encoding and packetizing of the image may be latency insensitive and thus, can be performed at a later stage of the pipeline.

The figure shows a re-arrangement of the stages of the pipeline for two frames. For both the frames, the images may be transmitted on an external interface (i.e. transmit stage), such as an HDMI or Wi-Fi Tx, after preprocessing p1 (can be a part of the encode stage or a separate stage) the frame. The frames are encoded later and saved on a storage medium such as a disk for using it in the future. The frame may be forwarded from one pipeline stage to another pipeline stage. It is noted that the latency insensitive stages may be skipped to reduce the total latency for processing the frame.

FIG. 10 illustrates a flowchart of a method (or process) for pipelining frames through a low latency camera system, according to an example embodiment. The method can be performed using components of a machine architecture for example, as described in FIG. 14. The camera module 705 captures a frame and transmits it from the camera lens to an HDMI or other similar port. The unprocessed frame is received 1005 by the low latency camera system and may be processed through a video/image pipeline 702. The video/image pipeline 702 may be overclocked 1010 to gain the idle processor time between frames. The image/video processing functions such as sharpening, compression, color conversion, etc., of the frames are performed 1015 in the encoding stage of the pipeline, with the pipeline overclocked to reduce the total latency for processing the frame.

An image processor on the low latency camera system detects the frames that do not require encoding or other pipeline stages to be performed before transmitting them, for example, by detecting a control flag in the incoming frame. The pipeline forwarding feature may be activated 1020 on such frames. Alternatively, pipeline forwarding may be activated on all incoming frames by setting a control switch in an image processor, e.g., image processor 516.

If an external interface such as an HDMI is present in the total latency path, wire squashing is performed 1025 on the processed frame to further reduce the latency. Wire squashing further includes overclocking an external interface clock, external interface synchronization and data forwarding.

The external interface may be clocked at the frame rate and the data to be transmitted is spread across the entire frame time. To reduce the total latency, the external interface clock is clocked as fast as possible, i.e., overclocked. Due to overclocking, the data to be transmitted is sent in bursts on the external interface that leads to idle time between frames.

The external interface synchronization method aligns the external clock, frame sync and line sync to start exactly when the data is ready from the video pipeline. There is no buffering necessary between the video pipeline and the external interface, leading to a reduction in the total frame latency.

Conventional camera systems have symmetrical frame blanking at the beginning and end of each frame as well as line blanking at the beginning and end of each line. The data forwarding moves all the frame data to the beginning of the transmission, and the blanking information is sent after the frame has been transmitted, thus reducing the total frame latency. Once the processed frame is squashed, the processed frame may be transmitted 1035 to the encoder module.

FIG. 11 illustrates a flowchart of an example method for pipelining frames through an encoder, according to an example embodiment. A processed frame may be received 1105 by a hardware image pre-processor (e.g., may be included in image processor 516) that performs 1110 image processing operations such as scaling, resizing, cropping, etc. prior to encoding the frame. A fast encoder such as a hardware encoder is selected over a software encoder to reduce the total latency. The hardware encoder performs 1115 slice based encoding. The input frames are encoded as soon as a fraction or slice of the frame is available. This eliminates the need for an input buffer, and thus eliminating the addition of the latency incurred by an input buffer.

Additionally, the selected hardware encoder supports slice based encoding at the output, i.e., the encoded slices of frames may be sent 1130 out to the wireless interface (Wi-Fi Tx). The hardware encoder does not wait for an entire frame to be encoded before transmission. This eliminates the need for an output buffer, thus eliminating the addition of latency incurred by an output buffer.

FIG. 12 illustrates a flowchart of a method for pipelining frames through a wireless interface, according to an example embodiment. A wireless transmit interface may receive 1205 an encoded slice of a frame that has a size equal to a maximum transmission unit (MTU) supported by the wireless system interface. The encoded frame of MTU size is transmitted over the wireless interface. Conventional systems use a transmit buffer to store the MTU sized frame slices and transmit over the wireless interface on receiving an entire frame. The MTU based transport transmit method does not wait for receiving the entire frame, thus eliminating the need for the transmit buffer and eliminating the addition of the latency incurred by a transmit buffer.

The wireless medium may be tuned using one or more of the methods described below to reduce the total latency. The methods for reducing the latency through the wireless medium further include queue sizing, queue flushing, bitrate feedback, physical medium rate feedback, dynamic encoder parameter tuning and wireless radio parameter adjustment. The wireless transmitters use queues that are sized to hold

one encoded frame of incoming data. The data may be dropped once the queue is full to reduce the number of out-of-date frames being transmitted when the wireless throughput drops below the required throughput to transmit video without loss. The transmit queue may be flushed out, i.e. emptied, when the data in the queue is detected to be old due to lack of transmission or switching of transmit or encoder parameters. This prevents transmission of irrelevant data, thus saving on transmit and retry latency.

The wireless interface determines the current capability of the wireless link by way of an algorithm that calculates the average instantaneous video throughput, i.e. the bit rate. The bit rate may be fed back to the encoder to select the encoder Q factor. This results in a larger or smaller encoded video throughput and reduces the number of frames that will be dropped, which significantly affects the total video frame latency.

Similar to the bitrate feedback, the wireless interface determines the current modulation rate of the physical medium and is fed back to the encoder. This provides a bitrate ceiling of the instantaneous throughput rate as well as a predicted throughput in the near future. Feeding the modulation rate back to the encoder block allows a better estimate of the bitrate that is used to encode frames as well as data. This further reduces latency by helping to reduce the number of frames that are dropped.

The encoder dynamically selects encoder parameters such as resolution, frame rate, compression factor, and bitrate based on the current state of the wireless medium (i.e. the bitrate feedback or the modulation rate feedback or any other such parameter of the wireless medium). This may reduce latency by helping to reduce the number of frames that are dropped.

The wireless radio parameters may be adjusted for low latency camera systems that use the 802.11 standard. The burst rate parameter may be adjusted such that a reduced number of acknowledgements are needed for each frame that is transmitted. This reduces the total latency. The retry rate parameter may be set to a lower rate, so that data is dropped rather than retransmitted. This may prevent incurring latency when the instantaneous bitrate is low.

FIG. 13 illustrates a flowchart of a method for pipelining frames through the remote controller, according to an example embodiment. In one embodiment, a remote controller may include a Wi-Fi Rx module, a decoder module and a display module. The Wi-Fi Rx module receives 1305 the frame transmitted from the Wi-Fi Tx module, over the wireless interface. The Wi-Fi Rx module may receive MTU sized chunks of data and are de-packetized on arrival. Conventional modules include a receiver buffer and wait for de-packetizing until a full frame is received. The Wi-Fi Rx module eliminates the need for the receiver buffer and reduces the total latency by eliminating the latency through the buffer.

The received frame or image may be sent to the decoder. A fast hardware decoder that performs 1310 decoding operations using slice based decoding is selected. The fast hardware decoder may be overclocked. The slice based decoding method may include operating the fast hardware decoder on a fraction of the frame, thus eliminating the need for buffers and reducing total latency.

Conventional decoders wait till the beginning of a new frame before the previous frame is sent to the next module such as display. Unlike the conventional decoders, the fast hardware decoder further may include a method known as decoder nudging. The decoder nudging method may include sending a signal 1315 to the fast hardware decoder as soon

as the last data of the current frame is at the input of the decoder. The decoder nudging signal may be as simple as inserting dummy data to push a frame out. The fast hardware decoder makes the entire decoded frame available to the next module as soon as the decode of each frame is completed. The fast hardware decoder does not wait for the frame blanking to be decoded before making the decoded frame available to the next module. The latency may be reduced by an amount equivalent to the frame blanking time between the frames.

The decoded image may be post processed before providing the image to the display. The frame post processing may be done by a hardware image processing module to maximize parallel processing and to avoid having the image/video pipeline display stage being executed in software.

The post processed image may be sent to the display module. Conventional display systems match the display refresh rate to the frame rate of the low latency camera system. The display module is overclocked 1320 to run the display at the fastest possible refresh rate to reduce the display latency and thus the overall latency. The frame is sent 1325 to the display at the overclocked refresh rate.

#### Example Machine Architecture

As has been noted, the remote controlled aerial vehicle 110 can be remotely controlled from the remote controller 120. The aerial vehicle 110 and the remote controller 120 are machines that that be configured operated using software. FIG. 14 is a block diagram illustrating components of an example machine able to read instructions from a machine-readable medium and execute them in one or more processors (or controllers). All or portions of the example machine described in FIG. 14 can be used with the aerial vehicle 110 or the remote controller 120 and/or other parts of a system that interfaces with the aerial vehicle 110 and/or remote controller 120.

In FIG. 14 there is a diagrammatic representation of a machine in the example form of a computer system 1400. The computer system 1400 can be used to execute instructions 1424 (e.g., program code or software) for causing the machine to perform any one or more of the methodologies (or processes) described herein. In alternative embodiments, the machine operates as a standalone device or a connected (e.g., networked) device that connects to other machines. In a networked deployment, the machine may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment.

The machine in this example is a handheld controller to control the remote controlled aerial vehicle. However, the architecture described may be applicable to other computer systems that operate in the system of the remote controlled aerial vehicle with camera and mounting configuration, e.g., in setting up a local positioning system. These other example computer systems include a server computer, a client computer, a personal computer (PC), a tablet PC, a smartphone, an internet of things (IoT) appliance, a network router, switch or bridge, or any machine capable of executing instructions 1424 (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term "machine" shall also be taken to include any collection of machines that individually or jointly execute instructions 1424 to perform any one or more of the methodologies discussed herein.

The example computer system 1400 includes one or more processing units (generally processor 1402). The processor 1402 is, for example, a central processing unit (CPU), a graphics processing unit (GPU), a digital signal processor

(DSP), a controller, a state machine, one or more application specific integrated circuits (ASICs), one or more radio-frequency integrated circuits (RFICs), or any combination of these. The processor **1402** and the memory **1404** can be a part of the flight controller **315**, image processor **516** and/or the processing subsystem **610**. The computer system **1400** also includes a main memory **1404**. The computer system may include a storage unit **1416**. The processor **102**, memory **1404** and the storage unit **1416** communicate via a bus **1408**.

In addition, the computer system **1406** can include a static memory **1406**, a display driver **1410** (e.g., to drive a plasma display panel (PDP), a liquid crystal display (LCD), or a projector). The computer system **1400** may also include input/output devices, e.g., an alphanumeric input device **1412** (e.g., a keyboard), a dimensional (e.g., 2-D or 3-D) control device **1414** (e.g., a mouse, a trackball, a joystick, a motion sensor, or other pointing instrument), a signal generation device **1418** (e.g., a speaker), and a network interface device **1420**, which also are configured to communicate via the bus **1408**.

The storage unit **1416** includes a machine-readable medium **1422** on which is stored instructions **1424** (e.g., software) embodying any one or more of the methodologies or functions described herein. The instructions **1424** may also reside, completely or at least partially, within the main memory **1404** or within the processor **1402** (e.g., within a processor's cache memory) during execution thereof by the computer system **1400**, the main memory **1404** and the processor **1402** also constituting machine-readable media. The instructions **1424** may be transmitted or received over a network **1426** via the network interface device **1420**.

While machine-readable medium **1422** is shown in an example embodiment to be a single medium, the term "machine-readable medium" should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store the instructions **1424**. The term "machine-readable medium" shall also be taken to include any medium that is capable of storing instructions **1424** for execution by the machine and that cause the machine to perform any one or more of the methodologies disclosed herein. The term "machine-readable medium" includes, but not be limited to, data repositories in the form of solid-state memories, optical media, and magnetic media.

#### Additional Considerations

The disclosed configuration beneficially reduces the total latency for transferring a frame from the low latency camera system mounted on an aerial vehicle to the display of the remote controller. The reduced latency allows a user of the remote controller to view the images or videos approximately in sync with the speed of the aerial vehicle. Moreover, the disclosed configurations also can apply to other camera systems to reduce to total frame transfer latency.

Throughout this specification, plural instances may implement components, operations, or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations may be performed concurrently, and nothing requires that the operations be performed in the order illustrated. Structures and functionality presented as separate components in example configurations may be implemented as a combined structure or component. Similarly, structures and functionality presented as a single component may be implemented as

separate components. These and other variations, modifications, additions, and improvements fall within the scope of the subject matter herein.

Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms, for example, as illustrated in FIGS. **3-13**. Modules may constitute either software modules (e.g., code embodied on a machine-readable medium or in a transmission signal) or hardware modules. A hardware module is a tangible unit capable of performing certain operations and may be configured or arranged in a certain manner. In example embodiments, one or more computer systems (e.g., a standalone, client or server computer system) or one or more hardware modules of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware module that operates to perform certain operations as described herein.

In various embodiments, a hardware module may be implemented mechanically or electronically. For example, a hardware module may comprise dedicated circuitry or logic that is permanently configured (e.g., as a special-purpose processor, such as a field programmable gate array (FPGA) or an application-specific integrated circuit (ASIC)) to perform certain operations. A hardware module may also comprise programmable logic or circuitry (e.g., as encompassed within a general-purpose processor or other programmable processor) that is temporarily configured by software to perform certain operations. It will be appreciated that the decision to implement a hardware module mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations.

The various operations of example methods described herein may be performed, at least partially, by one or more processors, e.g., image processor **516** and/or processor **1402**, that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented modules that operate to perform one or more operations or functions. The modules referred to herein may, in some example embodiments, comprise processor-implemented modules.

The one or more processors may also operate to support performance of the relevant operations in a "cloud computing" environment or as a "software as a service" (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., application program interfaces (APIs)).

The performance of certain of the operations may be distributed among the one or more processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the one or more processors or processor-implemented modules may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the one or more processors or processor-implemented modules may be distributed across a number of geographic locations.

Some portions of this specification are presented in terms of algorithms or symbolic representations of operations on data stored as bits or binary digital signals within a machine memory (e.g., a computer memory). These algorithms or symbolic representations are examples of techniques used by those of ordinary skill in the data processing arts to

convey the substance of their work to others skilled in the art. As used herein, an “algorithm” is a self-consistent sequence of operations or similar processing leading to a desired result. In this context, algorithms and operations involve physical manipulation of physical quantities. Typically, but not necessarily, such quantities may take the form of electrical, magnetic, or optical signals capable of being stored, accessed, transferred, combined, compared, or otherwise manipulated by a machine. It is convenient at times, principally for reasons of common usage, to refer to such signals using words such as “data,” “content,” “bits,” “values,” “elements,” “symbols,” “characters,” “terms,” “numbers,” “numerals,” or the like. These words, however, are merely convenient labels and are to be associated with appropriate physical quantities.

Unless specifically stated otherwise, discussions herein using words such as “processing,” “computing,” “calculating,” “determining,” “presenting,” “displaying,” or the like may refer to actions or processes of a machine (e.g., a computer) that manipulates or transforms data represented as physical (e.g., electronic, magnetic, or optical) quantities within one or more memories (e.g., volatile memory, non-volatile memory, or a combination thereof), registers, or other machine components that receive, store, transmit, or display information.

As used herein any reference to “one embodiment” or “an embodiment” means that a particular element, feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

Some embodiments may be described using the expression “coupled” and “connected” along with their derivatives. For example, some embodiments may be described using the term “coupled” to indicate that two or more elements are in direct physical or electrical contact. The term “coupled,” however, may also mean that two or more elements are not in direct contact with each other, but yet still co-operate or interact with each other. The embodiments are not limited in this context.

As used herein, the terms “comprises,” “comprising,” “includes,” “including,” “has,” “having” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article, or apparatus that comprises a list of elements is not necessarily limited to only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. Further, unless expressly stated to the contrary, “or” refers to an inclusive or and not to an exclusive or. For example, a condition A or B is satisfied by any one of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present).

In addition, use of the “a” or “an” are employed to describe elements and components of the embodiments herein. This description should be read to include one or at least one and the singular also includes the plural unless it is obvious that it is meant otherwise.

Upon reading this disclosure, those of skill in the art will appreciate still additional alternative structural and functional designs for a system and a process for reducing the total latency for transferring a frame from the low latency camera system mounted on an aerial vehicle to the display of the remote controller through the disclosed principles herein. Thus, while particular embodiments and applications have been illustrated and described, it is to be understood

that the disclosed embodiments are not limited to the precise construction and components disclosed herein. Various modifications, changes and variations, which will be apparent to those skilled in the art, may be made in the arrangement, operation and details of the method and apparatus disclosed herein without departing from the spirit and scope defined in the appended claims.

What is claimed is:

1. A method, comprising:
  - receiving images or video frames at a wireless receiver interface from a wireless transmitter;
  - decoding the images or the video frames;
  - performing decoder nudging at a fast image decoder while decoding the images or the video frames received by the wireless transmitter, wherein the fast image decoder makes an entire decoded image or an entire decoded video frame available as soon as the decoded images or the decoded videos are completed;
  - inserting dummy data into a transmission by the wireless transmitter to push the images or the video frames out from the fast image decoder;
  - overclocking a display of a controller at an overclocked frequency;
  - outputting the decoded images or the decoded video frames to the display of the controller at the overclocked frequency; and
  - displaying the decoded images or the decoded video frames on the display.
2. The method of claim 1, wherein the decoding includes slice based decoding.
3. The method of claim 1, wherein the overclocking increases clock frequency and frame rate of a camera system that captures the images or the video frames so that frame latency is reduced relative to the images or the video frames before the images or the video frames are overclocked.
4. The method of claim 3, wherein the overclocking reduces a total latency by half.
5. The method of claim 1, comprising:
  - post processing the decoded images or the decoded video frames before providing the decoded images or the decoded video frames to the display.
6. The method of claim 1, comprising:
  - preprocessing the images or the video frames via one or more preprocessing operations including at least one of scaling, resizing, or cropping.
7. A non-transitory computer readable storage medium configured to store instructions, the instructions when executed by a processor cause the processor to:
  - receive images or video frames at a wireless receiver interface from a wireless transmitter;
  - perform image decoding operations with a fast image decoder, wherein the fast image decoder makes an entire decoded image or an entire decoded video frame available as soon as the decoded images or the decoded video frames are completed;
  - insert dummy data into a transmission by the wireless transmitter to push the images or the video frames out from the fast image decoder;
  - push dummy data to move the images or the video frames received by the wireless transmitter through the fast image decoder;
  - overclock a display of a controller at an overclocked frequency;
  - output decoded images or decoded video frames to the display of the controller at the overclocked frequency so that a total latency of the images or the video frames

## 31

moved through the decoder is reduced relative to a latency of the images or the video frames received;  
 perform decoder nudging at the fast image decoder, wherein the fast image decoder does not wait for a frame blank to be decoded before making the decoded video frames or the decoded images available to a next module; and  
 display the decoded images or the decoded video frames on the display.

8. The non-transitory computer readable storage medium of claim 7, wherein one or more processing operations of the processor include at least one of sharpening, compression, color conversion, performing a Bayer transformation, demosaicing, noise reduction, image stabilization, or rolling shutter artifact reduction.

9. The non-transitory computer readable storage medium of claim 7, wherein to overclock includes to drop a frame or a video frame of one or more unprocessed frames of the frames or one or more unprocessed video frames of the video frames to increase an operating frequency of the processor.

10. The non-transitory computer readable storage medium of claim 9, wherein to overclock reduces the total latency by half.

11. The non-transitory computer readable storage medium of claim 7, wherein the images or the video frames are processed by being squashed to reduce latency by one or more frames, and the images or the video frames being squashed reduces a size of the images or the video frames without losing image information.

12. The non-transitory computer readable storage medium of claim 7, the instructions when executed by the processor causing the processor to:

store the images or the video frames in the non-transitory computer readable storage medium as processed images or processed video frames.

13. The non-transitory computer readable storage medium of claim 7, further comprising:

post process the decoded images or the decoded video frames before providing the decoded images or the decoded video frames to the display.

14. A system, comprising:

a memory; and

a processor configured to execute instructions stored on the memory to:

## 32

receive images or video frames at a wireless receiver interface from a wireless transmitter;

perform image decoding operations using a fast image decoder with slice decoding;

perform decoder nudging to move the images or the video frames through the fast image decoder, wherein the fast image decoder makes an entire decoded video frames or entire images available as soon as the decoded images or the decoded video frames are completed, and the fast image decoder does not wait for a frame blank to be decoded before making the decoded frame available to a next module;

overclock a display of a controller;

output decoded images or decoded video frames to the display of the controller at an overclocked frequency;

insert dummy data into a transmission by the wireless transmitter to push the image or the video frames out from the fast image decoder; and

display the decoded images or the decoded video frames on the display.

15. The system of claim 14, further comprising:

a decoder module in the processor that performs the slice decoding.

16. The system of claim 14, further comprising:

a Wi-Fi transmitter module that transmits the images or the video frames to a Wi-Fi receiver module.

17. The method of claim 1, wherein the fast image decoder does not wait for a frame blank to be decoded before making the decoded frame available to a next module.

18. The method of claim 6, wherein the preprocessing of the images or the video frames occurs before the images or the video frames are encoded and the images or the video frames are sent via Wi-Fi.

19. The non-transitory computer readable storage medium of claim 7, wherein the processor is further configured to: preprocess the images or the video frames before the images or the video frames are encoded and the images or the video frames are transmitted via Wi-Fi.

20. The system of claim 14, wherein the process is further configured to:

preprocess the images or the video frames before the images or the video frames are encoded and the images or the video frames are transmitted via Wi-Fi.

\* \* \* \* \*