

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267032

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Madonna; Robert P. et al.

MULTI-ROLE DEVICES FOR AUTOMATION ENVIRONMENTS

Abstract

In accordance with one aspect of the invention, an automation control device, such as a host or hub, is provided with functionality so that it becomes a multi-role automation control device. One such multi-role automation control device produces an on screen display which enables a user to select predetermined lighting scenes or television channels, and to control other devices.

Inventors: Madonna; Robert P. (Osterville, MA), Jacobson; Arthur A. (Long Lake, MN), Tatzel; David W. (West Yarmouth, MA), Rendina; Victor (Cambridge, MA), Locascio; Timothy R. (Osterville, MA)

Applicant: Savant Systems, Inc. (Hyannis, MA)

Family ID: 1000008586766

Appl. No.: 19/187003

Filed: April 23, 2025

Related U.S. Application Data

parent US continuation 18514261 20231120 parent-grant-document US 12316473 child US 19187003

parent US continuation 16790133 20200213 parent-grant-document US 11863343 child US 18514261

us-provisional-application US 62805456 20190214

Publication Classification

Int. Cl.: H04L12/28 (20060101); H04L67/125 (20220101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of U.S. patent application Ser. No. 18/514,261 filed on Nov. 20, 2023 by Robert P. Madonna et al., for MULTI-ROLE DEVICES FOR AUTOMATION ENVIRONMENTS, which is a continuation of U.S. patent application Ser. No. 16/790,133 filed on Feb. 13, 2020, issued on Jan. 2, 2024 as U.S. Pat. No. 11,863,343 by Robert P. Madonna et al., for MULTI-ROLE DEVICES FOR AUTOMATION ENVIRONMENTS, which claims the benefit of U.S. Provisional Patent Application Ser. No. 62/805,456, which was filed on Feb. 14, 2019, by Robert P. Madonna et al. for MULTI-ROLE DEVICES FOR AUTOMATION ENVIRONMENTS, all of which are hereby incorporated by reference in their entirety. INCORPORATED PATENTS AND APPLICATIONS [0002] U.S. Pat. No. 7,930,644, issued Apr. 19, 2011, and entitled PROGRAMMING ENVIRONMENT AND METADATA MANAGEMENT FOR PROGRAMMABLE MULTIMEDIA CONTROLLER, is assigned to a common assignee with the present application and is hereby incorporated by reference. U.S. Pat. No. 8,213,463, issued Jul. 3, 2012, and entitled LOCATION-BASED SHARING OF MULTIMEDIA CONTROL RESOURCES, is assigned to a common assignee with the present application and is hereby incorporated by reference. U.S. Pat. No. 8,296,669, issued Oct. 23, 2012, and entitled VIRTUAL ROOM-BASED LIGHT FIXTURE AND DEVICE CONTROL, is assigned to a common assignee with the present application and is hereby incorporated by reference. U.S. Pat. No. 8,659,704, issued Feb. 25, 2014, and entitled APPARATUS AND METHOD FOR MIXING GRAPHICS WITH VIDEO IMAGES, is assigned to a common assignee with the present application and is hereby incorporated by reference. U.S. Pat. No. 9,153,125, issued Oct. 6, 2015, and entitled PROGRAMMABLE MULTIMEDIA CONTROLLER WITH PROGRAMMABLE SERVICES, is assigned to a common assignee with the present application and is hereby incorporated by reference. Co-pending application Ser. No. 16/123,731, filed Sep. 6, 2018, issued on Apr. 7, 2020 as U.S. Pat. No. 10,613,704 and entitled SMALL SCREEN VIRTUAL ROOM-BASED USER INTERFACE, is assigned to a common assignee with the present application and is hereby incorporated by reference. Co-pending application Ser. No. 16/254,245, filed Jan. 22, 2019, issued on Apr. 4, 2023 as U.S. Pat. No. 11,622,179 and entitled DEVICE MOUNTING SYSTEM, is assigned to a common assignee with the present application and is hereby incorporated by reference.

FIELD OF THE INVENTION

[0003] The present invention relates generally to the field of automation and, more specifically, to enhancing the capabilities of various devices to enable them to perform multiple roles in automation environments.

BACKGROUND INFORMATION

[0004] Demand for automation of residential and commercial environments has resulted in a dramatically expanding market of “smart” doorbells, thermostats, lighting, security systems, audio, video, and numerous other devices. These devices are offered by a substantial number of manufacturers who, for competitive or performance reasons, have adopted different control protocols that are not generally compatible with each other.

[0005] Thus, a “smart” thermostat offered by one manufacturer does not operate in accordance with a widely adopted standard, and often will not interoperate with “smart” lighting offered by a different manufacturer. Among other disadvantages, this lack of interoperability limits the choices of an end user in selecting devices for a particular automation environment. Another disadvantage is that an end user is prevented from effectively controlling all of the devices in an environment

with a single control device (e.g., remote control, smartphone, or tablet).

[0006] As a result, an end user is often forced to either select one manufacturer, even though that manufacturer does not offer all of the “smart” devices of interest to the end user, or select multiple manufacturers at increased cost and lack of interoperability.

SUMMARY OF THE INVENTION

[0007] In accordance with one aspect of the invention, an automation control device, such as a host or hub, is provided with enhanced functionality so that it becomes a multi-role automation control device. The multi-role automation control device is capable of controlling an expanded variety of “smart” or other devices whose native control protocol is not generally compatible. The multi-role automation control device may be implemented using a variety of underlying devices including a host, hub, soundbar, “smart” thermostat, “smart” amplifier, audio speaker, or other device.

[0008] In accordance with another aspect of the invention, an automation control hub is provided with enhanced functionality so that it becomes a multi-role automation control hub. Leveraging high performance graphics processing available in the automation control hub, the multi-role automation control hub is provided with an enhanced on screen display. The enhanced on screen display provides a user interface for automation control over an expanded variety of devices than the automation control hub is capable of controlling with its native functionality. The enhanced on screen display may also provide advanced video display management including windowing, tiling, and picture-in-picture among others. The enhanced on screen display may also support configuration, as well as real time control and status of substantially all aspects of an automation environment. More specifically, the enhanced on screen display may provide access to and control over services, favorites, scenes, automations, and scheduling.

[0009] In addition, multiple automation control hubs with enhanced on screen displays may be pooled together as a shared resource that distributes such on screen displays to a large number of TVs or video monitors. Such distribution may be effected by transmitting or streaming over IP dedicated to a TV HDMI.

[0010] In accordance with another aspect of the invention, a ceiling or wall mountable speaker, which includes wired network connectivity, is provided with additional functionality including wireless network connectivity. As a result, each speaker becomes a multi-role speaker that functions both as an audio output device as well as a wireless network access point. In addition, the multi-role speaker may perform a third role, an automation control device, as referenced above.

[0011] In accordance with another aspect of the invention, an automation control hub is provided with AVB network connectivity and becomes a multi-role automation control hub. Through an AVB network, the multi-role automation control hub distributes music to networked speakers, soundbars, or other devices.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The invention description below refers to the accompanying drawings, of which:

[0013] FIG. 1 is a block diagram an automated environment which includes a multi-role automation host in accordance with one aspect of the present invention;

[0014] FIG. 2 is a block diagram of a soundbar which may be used as a base for the multi-role automation host shown in FIG. 1;

[0015] FIG. 3 is a message flow diagram of the illustrating an example of higher level messaging performed by the multi-role automation host and other devices shown in FIG. 1;

[0016] FIG. 4 is a message flow diagram of the illustrating an example of lower level messaging performed by the multi-role automation host and other devices shown in FIG. 1;

[0017] FIG. 5 is a block diagram of an automated environment which includes a multi-role

automation hub that provides an enhanced on screen display in accordance with one aspect of the present invention;

[0018] FIGS. **6A-6D** are exemplary screenshots of the enhanced on screen display produced by the multi-role automation hub shown in FIG. **5**;

[0019] FIG. **7** is a message flow diagram illustrating an example of higher level messaging performed by the multi-role automation hub with enhanced on screen display shown in FIG. **5**;

[0020] FIG. **7A** is a block diagram of an automated environment in which multiple are pooled to become a shared resource;

[0021] FIG. **7B** is a message flow diagram illustrating communication among various devices in FIG. **7A**;

[0022] FIG. **8** is a block diagram of a multi-role speaker in accordance with one aspect of the present invention; and

[0023] FIG. **9** is a block diagram of a multi-role amplifier in accordance with one aspect of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0024] FIG. **1** shows an automation environment **100** which includes a multi-role automation host **104**. A first network cloud **102** is accessible by multi-role automation host **104**. Multi-role automation host **104** includes a system configuration (not shown) which, in turn, includes a component or device profile (not shown) associated with each profiled device **108a . . . 108b** controlled by multi-role automation host **104**. In general, a device profile is a file or other data structure which describes the inputs, outputs, and available set of commands for the associated device. Through either internal storage, network cloud **102**, or another external source, multi-role automation host **104** must have access to an associated device profile in order to control a given device.

[0025] Examples of a system configuration, component profile, and hardware and software suitable for multi-role automation host **104** may be found in U.S. Pat. No. 9,153,125 incorporated by reference above.

[0026] A user may interact with, and effectively control, multi-role automation host **104** by operating a user device **116a** running a host control application **120** which is compatible with multi-role automation host **104**. User device **116a** may be implemented with a smartphone, tablet, or other device capable of running host control application **120** and having appropriate network connectivity to communicate with multi-role automation host **104**. Alternatively, a user may interact with and effectively control multi-role automation host **104** using a user remote **118a** which is compatible with multi-role automation host **104**. Multi-role automation host **104** may, for example, be based upon a Smart Host Model SHC-S2-00, a surround sound soundbar, a “smart” Multistat thermostat, a “smart” audio speaker (as described below in connection with FIG. **8**), a “smart” amplifier (as described below in connection with FIG. **9**), or other devices offered by Savant Systems, LLC of Hyannis, MA.

[0027] A second network cloud **110** is accessible by an automation hub **112**. Unlike multi-role automation host **104** which is capable of controlling any profiled device, automation hub **112** is conventionally capable of controlling only devices **114a-114c** which have been certified as control protocol compliant (i.e., devices which have been certified as compliant with the control protocol specified by the manufacturer of automation hub **112**).

[0028] A user may interact with and effectively control automation hub **112** by operating a user device **116b** running a hub control application **122** which is compatible with automation hub **112**. User device **116b** may be implemented with a smartphone, tablet, or other device capable of running hub control application **122** and having appropriate network connectivity to communicate with automation hub **112**. Alternatively, a user may interact with and effectively control automation hub **112** using a user remote **118b** which is compatible with automation hub **112**. Automation hub **112** may, for example, be based on an Apple TV®, HomePod™, or iPad® running HomeKit®, all

of which are offered by Apple Inc. of Cupertino, CA.

[0029] Multi-role automation host **104** includes an automation bridge **106**. In one embodiment, an SDK available from Apple Inc. may be used to create automation bridge **106** and embed it in multi-role automation host **104**. As described in greater detail below, automation bridge **106** functions, in part, to communicate (bidirectionally) with automation hub **112** using the same manufacturer-specified control protocol as used by certified control protocol compliant devices **114a-114c**. Automation bridge **106** also functions to convert control protocol messages received from automation hub **112** to an appropriate form for processing by multi-role automation host **104** (and vice versa). Advantageously, through such communication and protocol translation, and depending upon the type of device, profiled devices **108a . . . 108b** as well as user remote **118a** are exposed to automation hub **112**. That is, profiled devices **108a . . . 108b** and user remote **118a**, even though not certified as compliant with the control protocol used by automation hub **112**, become visible to and controllable by automation hub **112** by virtue of multi-role automation host **104**.

[0030] FIG. 2 shows a block diagram of a powered surround sound soundbar **200** which may be used to implement multi-role automation host **104** (FIG. 1). A microprocessor **202** is coupled in bidirectional communication with an audio digital signal processor (DSP) **204**. Audio DSP **204** is also coupled to a TosLink **214**. Audio DSP **204** is coupled to digital to analog converters (not shown) whose outputs are coupled to an amplifier **206** whose outputs are coupled to various audio speakers **208**.

[0031] Microprocessor **202** is also coupled in bidirectional communication with a WISA module **210** as well as a WiFi dual band module **212**. In addition, microprocessor **202** is coupled to an LAN/AVB port **216**, a microphone **218**, control ports **220** which may include RS232 control ports-infrared (IR) control ports, or other control ports. An AC/DC power supply **224** provides power to soundbar **200**.

[0032] FIG. 3 shows a message flow diagram illustrating an example of higher level messaging needed to make profiled devices **108a . . . 108b** and user remote **118a** (FIG. 1) visible to and controllable by automation hub **112**. Host control application **120**, running on user device **116a**, initiates a Discovery protocol **300** with multi-role automation host **104**. Host control application **120** next sends a Host Provision message **302**. In response, multi-role automation host **104** proceeds to Query **304** its configuration to identify any (profiled) device(s) that is of an appropriate type to be supported/controlled by automation hub **112**. Assuming at least one profiled device of an appropriate type is identified, multi-role automation host **104**, through bridge **106**, transmits an Add Bridged Devices to Hub message **306** to automation hub **112**.

[0033] Subsequently, host control application **120** issues a Control Device message **308** to multi-role automation host **104** which responds by exerting control **310** over the profiled device to which message **308** is directed. In contrast, when hub control application **122** issues a Control Device message **312** that is directed to a profiled device, automation hub **112** responds by forwarding a Control Request message **314** to multi-role automation host **104**. In turn, multi-role automation host **104** responds by exerting control **316** over the profiled device to which message **312** is directed.

[0034] FIG. 4 shows a message flow diagram illustrating an example of lower level messaging that occurs when hub control application **122** and automation hub **112** are exerting control over profiled device **108a** that has become visible through multi-role automation host **104** as described above. In this example, automation hub **112** represents an Apple TV®, HomePod™, or iPad® running HomeKit®. Hub control application **122** issues a HMAActionSet execute message **400** to automation hub **112** which, in turn, issues a Device Characteristic Write message **402** to multi-role automation host **104**. Device Characteristic Write message **402** could represent, for example, to dim a lamp.

[0035] In response, multi-role automation host **104** locates the profile corresponding with the device **404** to which message **402** is directed, and then sends a profiled command **406** to device **108a**. Profiled command **406** is in substance comparable to message **402** but is prepared by multi-

role automation host **104** in a form that is expected and understood by device **108a**. Following receipt and execution of profiled command **406**, device **108a** sends a command response **408** to multi-role automation host **104** which, in turns, sends a Characteristic Update message **410** to automation hub **112**.

[0036] Turning now to FIG. 5, an automation environment **500** is shown. In general, each component or device shown in FIG. 5 may include comparable structure and function to the corresponding component or device shown in FIG. 1 and described above with one exception. A multi-role automation hub **512**, in its role as a hub, functions in a substantially comparable manner to automation hub **112** (FIG. 1) described above. However, multi-role automation hub **512**, in an additional role, produces an enhanced on screen display (EOSD) for a television **524**.

[0037] In a preferred embodiment, as referenced above, automation hub **112** may be based on Apple TV® running HomeKit®. While Apple TV® includes a limited on screen display which allows a user to select audio/video to play, or power on/off an attached TV, that limited on screen display is not capable of controlling other devices. However, Apple TV® does include a high performance graphics processing capability.

[0038] In accordance with one aspect of the present invention, an application is provided which runs on Apple Inc.'s tvOS®, and leverages the high performance graphics processing built into Apple TV® to produce an EOSD **600** as shown in FIGS. 6A-6D. By placing an Apple TV® into a lockdown mode, the Apple TV® will automatically boot up into the application which produces EOSD **600**.

[0039] As shown in FIG. 6A, EOSD **600** may be formatted as three horizontal bands of rotating icons, graphics, images, video or other content. For example, band **602** displays a series of “Scenes” corresponding to various rooms or areas of a home. When a user selects a particular “Scene” (by interacting with EOSD **600** using user devices **516a** or **516b**, or user remotes **518a** or **518b** (FIG. 5)) to center and select the corresponding image, previously defined conditions or states of lighting, devices, shades, media, or any other resource that is under the control of multi-role automation host **504** or multi-role automation hub **512**, will be set in the selected room or area.

[0040] Band **604** of EOSD **600** displays icons corresponding to various systems and services. When a user selects a centered “Security” icon, EOSD **600** transitions to a screen shown in FIG. 6B in which band **608** displays live feeds from several closed circuit security cameras. Similarly, as shown in FIG. 6C, when a user selects a centered “Lighting” icon, EOSD **600** transitions to a screen shown in FIG. 6D in which band **610** displays true images of the current lighting conditions of individual rooms or lamps along with a vertical slider bar control. Exemplary techniques for generating and displaying such true images of current lighting conditions are described in U.S. Pat. Nos. 8,296,669, and 10,613,704, both of which are incorporated by reference above.

[0041] EOSD **600** may also provide advanced video display management including windowing, tiling, and picture-in-picture among others. Details regarding hardware and software for generating EOSD **600** may be found in the patents and pending patent applications incorporated by reference above.

[0042] FIG. 7 shows a message flow diagram illustrating an example of lower level messaging that occurs when multi-role automation hub **512** with EOSD **600** interacts with multi-role automation host **504**. Host control application **520** issues a Control Profiled Device message **700** to multi-role automation host **504**. Because message **700** is directed to a profiled device, multi-role automation host **504** proceeds to Execute Profiled Device Command **702**.

[0043] Subsequently, host control application **520** issues a Control Certified Device message **704**. Because message **704** is not directed to a profiled device, multi-role automation host **504** issues a Forward Request message **706**, via bridge **506**, to multi-role automation hub **512**. Multi-role automation hub **512**, in turn, issues a Control Request message **708** to automation hub **112** which proceeds to Execute Certified Device Command **710**.

[0044] In accordance with one aspect of the invention, an application is provided which runs on

Apple Inc.'s tvOS®, and provides the necessary functionality to transform an Apple TV® into multi-role automation host. Other devices which are controllable by a dedicated remote may also be suitable to serve as a multi-role automation host. In general, the application embodies all necessary automation host functionality including the ability to recognize and control profiled devices. Because of the native functionality of an Apple TV®, this type of multi-role automation host is capable of effectively controlling a mix of profiled devices and certified devices without an additional hub or other intermediate device. In addition, the capability of this type of multi-role automation host may be further enhanced by the addition of AVB network connectivity. Such connectivity, in the case of an Apple TV® multi-role automation host, permits distribution of music in digital form directly to AVB enabled speakers, soundbars or other devices.

[0045] In accordance with another aspect of the invention, multiple Apple TVs may be pooled together to become a shared resource for multiple TVs. As shown in FIG. 7A, an automated environment **700** includes a group of TVs **712a-712c**, each of which is coupled to a video switch **714**. A multi-role automation host **716** is coupled to video switch **714**, as are multiple Apple TVs **718a** and **718b**, and multiple hubs with enhanced OSD **726a** and **726b** (which are substantially similar to hub with enhanced OSD **512** (FIG. 5) described above).

[0046] In general, in response to commands from multi-role automation host **716**, video switch **714** functions to set up and tear down video signal connections or paths between various ones of TVs **712a-712c**, and various ones of Apple TVs **718a-718b** or hubs with enhanced OSD **726a-726b**. Multi-role automation host **716** may also command video switch **714** to set up a video signal connection between a single Apple TV **718a-718b** and multiple TVs **712a-712c**. Similarly, multi-role automation host **716** may also command video switch **714** to set up a video signal connection between a single hub with enhanced OSD **726a-726b** and multiple TVs **712a-712c**.

[0047] FIG. 7B is a message flow diagram illustrating communication among various devices in FIG. 7A needed to display an enhanced OSD on one of TVs **712a-712c**. The communication begins with a user (not shown) pressing a button on user remote **724** which causes transmission of an OSD Request for Zone X message **728** to multi-role automation host **716**. Multi-role automation host **716** responds first by Dequeue Menu Token Y which, in effect, dedicates a particular Apple TV **718a-718b** (associated with the token) to the requested OSD session. Next, multi-role automation host **716** transmits an Activate OSD message **732** to a Menu Resource Y **762** (i.e., a particular Apple TV associated with Token Y). This is followed by a Start Stream 1 message **734** from multi-role automation host **716** to a Menu Resource Y's Video Transmitter **758** which, in turn, is followed by a Start Stream 1 With Resized Video message **736** to Current Transmitter Used By Zone X **764**.

[0048] Next, multi-role automation host **716** sends a message **738** to Zone X Video Receiver **760** which sets up picture in picture and assigns the appropriate transmitters. At this point, the enhanced OSD appears in a picture in picture **740**. A User OSD Navigation message **742** is then transmitted from user remote **724** to Menu Resource Y **762**. This is followed by a Cancel or Select message **744** from user remote **724**. If a Cancel message **744** was transmitted, an OSD Deactivated message **746** is transmitted from Menu Resource Y to multi-role automation host **716**. This is followed by Menu Token Y being returned to the Queue **748** because the OSD session is over.

[0049] Subsequently, a message **750** is transmitted from multi-role host **716** to restore full screen video for the original transmitter. This is followed by a Stop Stream 1 message **752** to Current Transmitter **764**, a Stop Stream 1 message to Menu Resource Y's Video Transmitter **758**, and restoration of full screen video **756**.

[0050] In addition, similar to the enhanced OSD example described above, other services available on an Apple TV **718a-718b** may be shared with multiple TVs **712a-712c**. Thus, services such as Netflix, Weather, or many others may be shared with multiple TVs **712a-712c** by placing an Apple TV in lockdown mode and transmitting the selected video over IP, taking advantage of video switch **714** to set up the appropriate video connections.

[0051] In accordance with another aspect of the invention, a ceiling or wall mountable speaker,

such as those disclosed in co-pending application Ser. No. 16/254,245 and incorporated by reference above, or bookshelf or other speaker, is provided enhanced functionality and becomes a multi-role speaker. The previously disclosed speakers include a LAN/AVB port through which both digital audio and power over Ethernet (PoE) are received. As shown in FIG. 8, a multi-role speaker **800** includes a LAN/AVB port **802** coupled to a microprocessor **804**. A microphone **806** is coupled to microprocessor **804** as is a digital signal processor (DSP) **808**. An amplifier **810** is coupled to DSP **808** as well as speaker **812**. Multi-role speaker **800** also includes a WISA module **814** and a WiFi dual band module **816**, both of which provide wireless connectivity. Through its WISA module **814** or LAN/AVB port **802**, multi-role speaker **800** may distribute digital audio in either of two forms: 16-bit, 44.1 kHz form (used in Airplay 2), or higher fidelity 24-bit, 96 kHz form. [0052] Through its WiFi dual band module **816**, multi-role speaker **800** provides support for Airplay 2 as well as serving as a wireless access point. To provide whole house audio, speakers are frequently distributed throughout most rooms or other areas of a house. By providing such speakers with wireless network connectivity so that they become multi-role speakers, robust wireless network coverage is attained without the necessity of separate wireless access points. Through its WISA module **814**, multi-role speaker **800** may be paired with a WISA speaker **820** to provide stereo sound. Paired WISA speaker **820** includes a microcontroller **822** which is coupled to a WISA module **830** and a DSP **824**. DSP **824** is coupled to an amplifier **826**, which in turn is coupled to a speaker **828**. In general, paired WISA speaker **820** receives digital audio from multi-role speaker **800** via WISA module **830**.

[0053] Within an automation environment **100** (FIG. 1), multi-role speaker **800** is capable of serving in any combination of four roles: audio speaker; multi-role automation host **104** (FIG. 1); wireless access point; and pairing with WISA speaker **820**.

[0054] FIG. 9 shows a multi-role amplifier **900** which includes a microprocessor **902** coupled to a DSP **904** which in turn is coupled to an amplifier **906**. Microprocessor **902** is coupled, respectively, to a LAN/AVB port **908**, an analog input **910**, a TosLink input **912**, and control ports **914** which may include RS232, IR, or other control ports. An AC/DC power supply **916** provides power to multi-role amplifier **900**. Multi-role amplifier **900** provides an RCA pre-amp output **920** and may be used to drive external passive speakers **918**.

[0055] Within an automation environment **100** (FIG. 1), multi-role amplifier **900** is capable of serving as both an audio amplifier and a multi-role automation host **104** (FIG. 1).

[0056] The foregoing description has been directed to specific embodiments of this invention. It will be apparent, however, that other variations and modifications may be made to the described embodiments, with the attainment of some or all of their advantages. For example, it is expressly contemplated that the teachings of this invention can be implemented as software, including a computer-readable medium having program instructions executing on a computer, hardware, firmware, or a combination thereof. Accordingly, this description is to be taken only by way of example and not to otherwise limit the scope of the invention. It is thus the object of the appended claims to cover all such variations and modifications as come within the true spirit and scope of the invention.

Claims

1. An apparatus comprising: a multi-role audio speaker which includes a multi-role automation host, a WiFi dual band module capable of serving as a wireless access point, and a wireless digital audio distribution module capable of pairing with a WISA wireless audio speaker, said multi-role automation host having connectivity for communicating with a first user device, said first user device having a set of user commands to which said multi-role automation host is responsive; said multi-role automation host operating in a first role in which said multi-role automation host directly controls one or more profiled devices, each of said one or more profiled devices having an

associated profile which is accessible by said multi-role automation host, each said associated profile including information which describes a set of device commands to which the associated profiled device is responsive; said multi-role automation host operating in a second role in which said multi-role automation host directly controls a first set of one or more devices each of which is certified compliant with a predetermined control protocol, and indirectly controls through a first multi-role automation hub, operating in a third role, a second set of one or more devices each of which is certified compliant with said predetermined control protocol, wherein said multi-role automation host includes an automation bridge communicating with said first multi-role automation hub using messages in a first form based on said predetermined control protocol, and converting said first form to a second form for processing by said multi-role automation host, wherein said one or more profiled devices become visible to and controllable by said first multi-role automation hub.

2. An apparatus comprising: a multi-role audio speaker which includes a multi-role automation host, and a wireless digital audio distribution module capable of pairing with a WISA wireless audio speaker, said multi-role automation host having connectivity for communicating with a first user device, said first user device having a set of user commands to which said multi-role automation host is responsive; said multi-role automation host operating in a first role in which said multi-role automation host directly controls one or more profiled devices, each of said one or more profiled devices having an associated profile which is accessible by said multi-role automation host, each said associated profile including information which describes a set of device commands to which the associated profiled device is responsive; said multi-role automation host operating in a second role in which said multi-role automation host directly controls a first set of one or more devices each of which is certified compliant with a predetermined control protocol, and indirectly controls through a first multi-role automation hub, operating in a third role, a second set of one or more devices each of which is certified compliant with said predetermined control protocol, wherein said multi-role automation host includes an automation bridge communicating with said first multi-role automation hub using messages in a first form based on said predetermined control protocol, and converting said first form to a second form for processing by said multi-role automation host, wherein said one or more profiled devices become visible to and controllable by said first multi-role automation hub.

3. An apparatus comprising: a multi-role audio speaker which includes a multi-role automation host, and a WiFi dual band module capable of serving as a wireless access point, said multi-role automation host having connectivity for communicating with a first user device, said first user device having a set of user commands to which said multi-role automation host is responsive; said multi-role automation host operating in a first role in which said multi-role automation host directly controls one or more profiled devices, each of said one or more profiled devices having an associated profile which is accessible by said multi-role automation host, each said associated profile including information which describes a set of device commands to which the associated profiled device is responsive; said multi-role automation host operating in a second role in which said multi-role automation host directly controls a first set of one or more devices each of which is certified compliant with a predetermined control protocol, and indirectly controls through a first multi-role automation hub, operating in a third role, a second set of one or more devices each of which is certified compliant with said predetermined control protocol, wherein said multi-role automation host includes an automation bridge communicating with said first multi-role automation hub using messages in a first form based on said predetermined control protocol, and converting said first form to a second form for processing by said multi-role automation host, wherein said one or more profiled devices become visible to and controllable by said first multi-role automation hub.
