

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392270
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Sundaravel Damotharan; Arun Shori et al.

Systems and methods for exhaust aftertreatment sensor offset detection and diagnosis

Abstract

Systems and methods for diagnosing a sensor of an exhaust aftertreatment system can include a controller determining that an amount of an exhaust gas constituent at a particular location is expected to be at or below a predefined value for a period of time, and receiving data indicative of a sensed amount of the exhaust gas constituent from the sensor of the exhaust aftertreatment system during the period of time. The controller determines, based on the sensed amount of the exhaust gas constituent, an amount of offset affecting the sensor of the exhaust aftertreatment system, and initiates an action based on the determined amount of offset to diagnose the sensor.

Inventors:	Sundaravel Damotharan; Arun Shori (Columbus, IN), Gokhale; Rutika Kaustubh (Columbus, IN), Mohanty; Rakesh (Columbus, IN)
Applicant:	Cummins Inc. (Columbus, IN)
Family ID:	1000008766495
Assignee:	Cummins Inc. (Columbus, IN)
Appl. No.:	18/281064
Filed (or PCT Filed):	March 10, 2022
PCT No.:	PCT/US2022/019836
PCT Pub. No.:	WO2022/192595
PCT Pub. Date:	September 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240295185 A1	Sep. 05, 2024

Related U.S. Application Data

us-provisional-application US 63159598 20210311

Publication Classification

Int. Cl.: **F01N11/00** (20060101); **F01N3/20** (20060101); **G01M15/10** (20060101)

U.S. Cl.:

CPC **F01N11/002** (20130101); **F01N3/208** (20130101); **G01M15/102** (20130101);
 F01N2550/02 (20130101); **F01N2900/1602** (20130101)

Field of Classification Search

CPC: F01N (11/002); F01N (3/208); F01N (2550/02); F01N (2900/1602); F01N (3/2066);
 F01N (2560/02); F01N (2560/026); F01N (2560/06); F01N (2570/14); F01N (11/00);
 G01M (15/102); Y02T (10/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9606092	12/2016	Brahma	N/A	N/A
9784166	12/2016	Osburn et al.	N/A	N/A
2010/0180576	12/2009	Wang et al.	N/A	N/A
2011/0202230	12/2010	Sawada et al.	N/A	N/A
2012/0303206	12/2011	Rajagopalan et al.	N/A	N/A
2014/0360166	12/2013	Chandrasekaran	60/274	F02D 41/222
2015/0033704	12/2014	Ardanese	60/274	F01N 9/005
2015/0176512	12/2014	Smith	60/274	F02D 41/0235
2016/0041137	12/2015	Brahma	N/A	N/A
2018/0283248	12/2017	Upadhyay	N/A	F02D 41/1446
2020/0063633	12/2019	Lauritano et al.	N/A	N/A
2021/0148266	12/2020	Kim	N/A	F01N 3/208
2021/0293172	12/2020	Lundström	N/A	F01N 3/208

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2018/013038	12/2017	WO	N/A

OTHER PUBLICATIONS

PCT International Search Report and Written Opinion for International Application No.

PCT/US2022/019836 mailing date Jun. 9, 2022, 7 pages. cited by applicant

Extended Search Report for corresponding EP Patent Application No. 22768024.6, issued Dec. 2, 2024, 9 pages. cited by applicant

Primary Examiner: Lee; Brandon D

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims priority to and the benefit of U.S. Provisional Application No. 63/159,598 filed on Mar. 11, 2021 and titled “SYSTEMS AND METHODS FOR EXHAUST AFTERTREATMENT SENSOR OFFSET DETECTION AND DIAGNOSIS,” which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates to diagnosing exhaust aftertreatment systems. More particularly, the present disclosure relates to detection of aftertreatment sensor, and particularly nitrous oxide (NO_x) sensor, faults.

BACKGROUND

(2) Emissions regulations for internal combustion engines have become more stringent over recent

years. Environmental concerns have motivated the implementation of stricter emission requirements for internal combustion engines throughout much of the world. Governmental agencies, such as the Environmental Protection Agency (EPA) in the United States, carefully monitor the emission quality of engines and set emission standards to which engines must comply. Consequently, the use of exhaust aftertreatment systems on engines to reduce emissions is increasing. Exhaust aftertreatment systems are generally designed to reduce emission of particulate matter, nitrogen oxides, hydrocarbons, and other environmentally harmful pollutants.

SUMMARY

(3) One embodiment relates to a method for diagnosing a sensor of an exhaust aftertreatment system that includes determining, by a controller, that an amount of an exhaust gas constituent at a particular location is expected to be at or below a predefined value for a period of time; receiving, by the controller, data indicative of a sensed amount of the exhaust gas constituent from the sensor of the exhaust aftertreatment system during the period of time; determining, by the controller and based on the sensed amount of the exhaust gas constituent, an amount of offset affecting the sensor of the exhaust aftertreatment system; and initiating, by the controller, an action based on the determined amount of offset to diagnose the sensor.

(4) Another embodiment relates to a system for diagnosing a sensor of an exhaust aftertreatment system. The system includes a controller comprising a processor coupled to a memory storing executable instructions, the executable instructions when executed by the processor cause the processor to: determine that an amount of an exhaust gas constituent at a particular location is expected to be at or below a predefined value for a period of time; receive data indicative of a sensed amount of the exhaust gas constituent from the sensor of the exhaust aftertreatment system during the period of time; determine, based on the sensed amount of the exhaust gas constituent, an amount of offset affecting the sensor of the exhaust aftertreatment system; and initiate an action based on the determined amount of offset to diagnose the sensor.

(5) Still another embodiment relates to a non-transitory computer-readable medium comprising executable instructions that, when executed by a processor, cause the processor to: determine that an amount of an exhaust gas constituent at a particular location is expected to be at or below a predefined value for a period of time; receive data indicative of a sensed amount of the exhaust gas constituent from a sensor of the exhaust aftertreatment system during the period of time; determine, based on the sensed amount of the exhaust gas constituent, an amount of offset affecting the sensor of the exhaust aftertreatment system; and initiate an action based on the determined amount of offset to diagnose the sensor.

(6) This summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements. Numerous specific details are provided to impart a thorough understanding of embodiments of the subject matter of the present disclosure. The described features of the subject matter of the present disclosure may be combined in any suitable manner in one or more embodiments and/or implementations. In this regard, one or more features of an aspect of the invention may be combined with one or more features of a different aspect of the invention. Moreover, additional features may be recognized in certain embodiments and/or implementations that may not be present in all embodiments or implementations.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIG. 1 is a schematic diagram of a hybrid series vehicle system, according to an exemplary

embodiment.

(2) FIG. 2 is a schematic diagram of the controller of FIG. 1, according to an exemplary embodiment.

(3) FIG. 3 is a flow chart of a method for determining an amount of offset affecting a sensor and diagnosing the sensor based on the determined amount of offset, according to an exemplary embodiment.

DETAILED DESCRIPTION

(4) Following below are more detailed descriptions of various concepts related to, and implementations of, methods, apparatuses, and systems for diagnosing an exhaust aftertreatment sensor, and particularly, a tailpipe NO_x sensor based on periods of expected zero or close to zero NO_x output. Before turning to the figures, which illustrate certain exemplary embodiments in detail, it should be understood that the present disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology used herein is for the purpose of description only and should not be regarded as limiting.

(5) As environmental regulations become more stringent, consistent aftertreatment system performance is important to keep vehicle emissions within compliance. Consistent aftertreatment system performance is dependent on components of the aftertreatment system functioning correctly, so detecting when aftertreatment system components are malfunctioning (or functioning outside of acceptable bounds) may be an important function. One such aftertreatment system component is the Selective Catalytic Reduction (SCR) system, which converts nitrous oxides (NO_x) in the exhaust stream into less harmful nitrogen and water. SCR health can be determined based on a conversion efficiency, which refers to how efficiently the SCR is converting NO_x into less harmful elements. One way to determine SCR conversion efficiency is to compare a SCR NO_x inlet value to a SCR NO_x outlet value. As such, SCR conversion efficiency determinations may rely on sensed values from one or more NO_x sensors. Therefore, determining whether the SCR system is functioning properly may be dependent on the health/operation capability of the NO_x sensor.

(6) Sensors are inherently affected by offset and/or gain. Offset refers to a flat value that the sensed value is off from the actual value (e.g., an offset of 10° C. means that an actual temperature of 60° C. would be read as 70° C.), while gain refers to a percentage amount that the sensed value is off from the actual value (e.g., a gain of 10% or 1.1 means that an actual temperature of 60° C. would be read as 66° C.). Because offset and gain are generally unavoidable for sensors, some amount of offset and/or gain is allowed to be present without an error flag being raised for the sensor at-issue. Although reference is made throughout to determining an amount of offset affecting a system-out NO_x sensor, the systems and methods described herein should be read as applicable to either offset or gain and as applicable to any aftertreatment system sensor (e.g., engine-out NO_x sensor, flow sensor, temperature sensor, etc.) Furthermore, while reference is made throughout to use of Celsius for measuring temperatures, the systems and methods described herein should be read as applicable to measuring temperature in Fahrenheit.

(7) Referring now to FIG. 1, a vehicle **10** including a powertrain **100**, an aftertreatment system **120**, an operator input/output (I/O) device **130**, and a controller **140** is shown, according to an example embodiment. According to the example embodiment shown in FIG. 1, the powertrain **100** of the vehicle **10** is structured as a series hybrid powertrain. However, in other embodiments, the powertrain **100** is structured as an internal combustion-only powertrain (i.e., a non-hybrid vehicle applications). The vehicle **10** may be an on-road or an off-road vehicle including, but not limited to, line-haul trucks, mid-range trucks (e.g., pick-up truck), cars (e.g., sedans, hatchbacks, coupes, etc.), buses, vans, refuse vehicles, fire trucks, concrete trucks, delivery trucks, and any other type of vehicle. In other embodiments, the system or parts thereof described herein may be used with stationary applications, such as power generators. Thus, the present disclosure is applicable with a

wide variety of implementations.

(8) As shown in FIG. 1, the powertrain **100** includes an engine **101**, a transmission **102**, a driveshaft **103**, a differential **104**, a final drive **105**, a motor-generator **106**, and an energy storage device **109**. The engine **101** may be structured as any engine type, including a spark-ignition internal combustion engine, a compression-ignition internal combustion engine, and/or a fuel cell, among other alternatives. The engine **101** may be any type of engine that generates exhaust gas (e.g., compression ignition or a spark ignition engine that may utilize various fuels, such as natural gas, gasoline, diesel fuel, jet fuel, etc.). The engine **101** includes one or more cylinders and associated pistons. In this regard, air from the atmosphere is combined with fuel, and combusted, to power the engine **101**. In the example shown, the engine **101** is structured as a compression-ignition engine that utilizes diesel fuel. Combustion of the fuel and air in combustion chambers of the engine **101** produces exhaust gas that is operatively vented to an exhaust pipe and to the aftertreatment system **120**. In the example shown, the engine **101** is structured as an internal combustion engine and particularly, a compression-ignition engine powered by diesel fuel.

(9) The transmission **102** may be structured as any type of transmission, such as a continuous variable transmission, a manual transmission, an automatic transmission, an automatic-manual transmission, a dual clutch transmission, and so on. Accordingly, as transmissions vary from geared to continuous configurations (e.g., continuous variable transmission), the transmission **102** may include a variety of settings (gears, for a geared transmission) that affect different output speeds based on an input speed received thereby (e.g., from the motor generator **106**, etc.). Like the engine **101** and the transmission **102**, the driveshaft **103**, the differential **104**, and the final drive **105** may be structured in any configuration dependent on the application (e.g., the final drive **105** is structured as wheels in an automotive application and a propeller in a boat application, etc.). Further, the driveshaft **103** may be structured as any type of driveshaft including, but not limited to, a one-piece, two-piece, and a slip-in-tube driveshaft based on the application.

(10) In the series hybrid configuration depicted, the engine **101** and the motor generator **106** are mechanically coupled together (e.g., via a shaft, a gear box, etc.). In other embodiments, a parallel hybrid configuration may be utilized. In a parallel configuration, the engine **101** and motor generator **106** can provide power simultaneously to drive the vehicle. In the depicted series configuration, the drivetrain receives power from the motor generator **106**, which may be powered by the engine **101** or energy storage device **109**. Thus, in some embodiments, the engine **101** is structured to drive the motor generator **106** to generate electrical energy. As shown in FIG. 1, the motor generator **106** is electrically coupled to the energy storage device **109** such that the motor generator **106** may provide energy generated thereby to the energy storage device **109** for storage. In some embodiments, the motor generator **106** is structured to receive stored electrical energy from the energy storage device **109** to facilitate operation thereof. By way of example, the motor generator **106** may receive stored electrical energy from the energy storage device **109** to facilitate starting the engine **101** and/or driving the motor aspect of the motor generator **106**. In other embodiments, the motor generator **106** and energy storage device **109** are omitted, such that the vehicle **10** and powertrain **100** are powered only by the engine **101**.

(11) As shown in FIG. 1, in series hybrid configurations, the motor generator **106** is mechanically coupled to the transmission **102** (e.g., via a shaft, a gear box, etc.). In an alternative embodiment (e.g., a stationary application, such as a genset), the powertrain **100** does not include the transmission **102** and the motor generator **106** is directly coupled to the driveshaft **103**. In some embodiments, the motor generator **106** is a single device having both generating and motoring capabilities. In some embodiments, the motor generator **106** has only motoring capabilities. As shown in FIG. 1, the motor generator **106** is electrically coupled to the energy storage device **109** such that the motor generator **106** may receive energy stored by the energy storage device **109** to facilitate operation thereof. By way of example, the motor generator **106** may receive stored electrical energy from the energy storage device **109** to facilitate providing a mechanical output to

the transmission **102**. By way of example, the motor generator **106** may be structured to utilize a negative torque supply to perform energy regeneration (e.g., when the torque demand therefrom is zero, during engine braking, while the vehicle **10** is coasting down a hill, etc.).

(12) According to an example embodiment, the energy storage device **109** includes one or more batteries (e.g., high voltage batteries, a lead-acid batteries, a lithium-ion batteries, lithium iron phosphate batteries, etc.), one or more capacitors (e.g., super capacitors, etc.), and/or any other energy storage devices, or combination thereof. As shown in FIG. **1**, the energy storage device **109** is electrically coupled to the motor generator **106**. According to an example embodiment, the energy storage device **109** is structured to store electrical energy (i) received from a charging station (e.g., a vehicle charging station, etc.), (ii) generated by the motor generator **106**, and/or (iii) generated by a regenerative braking system. The energy storage device **109** may be structured to provide the stored electrical energy to (i) vehicle subsystems to operate various electrical based components of the vehicle **10** (e.g., while the engine **101** is running, while the engine **101** is off, etc.), (ii) the motor generator **106** to start the engine **101** (e.g., in response to a restart command after a stop-start feature turns off the engine **101**, when an operator keys on the engine **101**, etc.), and/or (iii) the motor generator **106** to facilitate providing a mechanical output to the transmission **102** (e.g., to drive the vehicle **20**, etc.).

(13) The aftertreatment system **120** is in exhaust-gas receiving communication with the engine **101**. In the example shown, the aftertreatment system includes a diesel particulate filter (DPF) **122**, a diesel oxidation catalyst (DOC) **121**, a selective catalytic reduction (SCR) system **123**, and an ammonia oxidation catalyst (AMOX) **124**. In other embodiments, certain components or systems may be omitted and/or rearranged in a different order than depicted in FIG. **1** (e.g., the DPF **122** omitted). The DOC **121** is structured to receive the exhaust gas from the engine **12** and to oxidize hydrocarbons and carbon monoxide in the exhaust gas, among its other functions such as NO oxidation to NO₂ to promote passive DPF regeneration and fast SCR reaction. The DPF **122** is arranged or positioned downstream of the DOC **121** and structured to remove particulates, such as soot, from exhaust gas flowing in the exhaust gas stream. The DPF **122** includes an inlet, where the exhaust gas is received, and an outlet, where the exhaust gas exits after having particulate matter substantially filtered from the exhaust gas and/or converting the particulate matter into carbon dioxide.

(14) The aftertreatment system **120** may further include a reductant delivery system which may include a decomposition chamber (e.g., decomposition reactor, reactor pipe, decomposition tube, reactor tube, etc.) to convert a reductant into ammonia. The reductant may be, for example, urea, diesel exhaust fluid (DEF), Adblue®, a urea water solution (UWS), an aqueous urea solution (e.g., AUS32, etc.), and other similar fluids. A diesel exhaust fluid (DEF) is added to the exhaust gas stream to aid in the catalytic reduction. The reductant may be injected upstream of the SCR catalyst member by a DEF doser such that the SCR catalyst member receives a mixture of the reductant and exhaust gas. The reductant droplets then undergo the processes of evaporation, thermolysis, and hydrolysis to form gaseous ammonia within the decomposition chamber, the SCR catalyst member, and/or the exhaust gas conduit system, which leaves the aftertreatment system **120**. The aftertreatment system **120** may further include an oxidation catalyst (e.g. the DOC **121**) fluidly coupled to the exhaust gas conduit system to oxidize hydrocarbons and carbon monoxide in the exhaust gas. In order to properly assist in this reduction, the DOC **121** may be required to be at a certain operating temperature. In some embodiments, this certain operating temperature is approximately between 200-500° C. In other embodiments, the certain operating temperature is the temperature at which the HC conversion efficiency of the DOC **121** exceeds a predefined threshold (e.g. the conversion of HC to less harmful compounds, which is known as the HC conversion efficiency).

(15) The SCR **123** is configured to assist in the reduction of NO_x emissions by accelerating a NO_x reduction process between the DEF and the NO_x of the exhaust gas into diatomic nitrogen, water,

and/or carbon dioxide. If the SCR catalyst member is not at or above a certain temperature or within a certain temperature range, the acceleration of the NO_x reduction process is limited and the SCR **123** may not be operating at a necessary level of efficiency to meet regulations. In some embodiments, this certain temperature is approximately 250-300° C. The SCR catalyst member may be made from a combination of an inactive material and an active catalyst, such that the inactive material, (e.g. ceramic metal) directs the exhaust gas towards the active catalyst, which is any sort of material suitable for catalytic reduction (e.g. base metals oxides like vanadium, molybdenum, tungsten, etc. or noble metals like platinum). In some embodiments, the AMOX **124** is included and structured to address ammonia slip by removing excess ammonia from the treated exhaust gas before the treated exhaust is released into the atmosphere.

(16) Because the aftertreatment system **120** treats the exhaust gas before the exhaust gas is released into the atmosphere, some of the particulate matter or chemicals that are treated or removed from the exhaust gas may build up in the aftertreatment system over time. For example, the soot filtered out from the exhaust gas by the DPF **122** may build up on the DPF **122** over time. Similarly, sulfur particles present in fuel may accumulate in the SCR **123** and deteriorate the effectiveness of the SCR catalyst member. Further, DEF that undergoes incomplete thermolysis upstream of the catalyst may build up and form deposits on downstream components of the aftertreatment system **120**. However, these build-ups on (and subsequent deterioration of effectiveness of) these components of the aftertreatment system **120** may be reversible. In other words, the soot, sulfur, and DEF deposits may be substantially removed from the DPF **122** and the SCR **123** by increasing a temperature of the exhaust gas running through the aftertreatment system to recover performance (e.g. for the SCR, conversion efficiency of NO_x to N₂ and other compounds). These removal processes are referred to as regeneration events and may be performed for the DPF **122**, SCR **123**, or another component in the aftertreatment system **120** on which deposits develop. However, exposure to high temperatures during active regenerations degrades the DOC, DPF, and SCR catalysts. An active regeneration event is specifically commanded, such as a flow rate measurement through a DPF being below a predefined threshold indicating a partially blocked DPF which, in turn, causes the controller to command a regeneration event where exhaust gas temperatures are elevated in order to raise the temperature of the DPF and burn off the accumulated PM and other components (e.g., raise engine power output, post-injection, and other means to increase exhaust gas temperatures to cause a regeneration event). In contrast, a passive regeneration event occurs naturally during operation of the vehicle (e.g., a high load condition that may be experienced while traversing a hill causes an increase in exhaust gas temperatures and regeneration event occurs naturally—not specifically commanded).

(17) Referring still to FIG. **1**, an operator input/output (I/O) device **130** is also shown. The operator I/O device **130** may be communicably coupled to the controller **140**, such that information may be exchanged between the controller **140** and the I/O device **130**, wherein the information may relate to one or more components of FIG. **1** or determinations (described below) of the controller **140**. The operator I/O device **130** enables an operator of the vehicle **100** to communicate with the controller **140** and one or more components of the vehicle **100** of FIG. **1**. For example, the operator input/output device **130** may include, but is not limited to, an interactive display, a touchscreen device, one or more buttons and switches, voice command receivers, etc.

(18) Briefly referencing FIG. **2**, as also shown, a sensor array **129** is included in the aftertreatment system **120**. The sensors are coupled to the controller **140**, such that the controller **140** can monitor and acquire data indicative of operation of the vehicle **10**. In this regard, the sensor array includes at least an inlet temperature sensor **125**, an outlet temperature sensor **126**, and a tailpipe (or system-out) NO_x sensor **127**. The inlet temperature sensor **125** is positioned in the exhaust flow upstream of the SCR **123**, and acquires data indicative of a temperature at or approximately at its disposed location. The outlet temperature sensor **126** is positioned in the exhaust flow downstream of the SCR **123**, and acquires data indicative of a temperature at or approximately at its disposed location.

The tailpipe NOx sensor **127** is positioned in the exhaust flow downstream of the aftertreatment system **120**, and acquires data indicative of a NOx amount at or approximately at its disposed location. It should be understood that the depicted locations, numbers, and type of sensors is illustrative only. In other embodiments, different/additional sensors may also be included with the vehicle **10** (e.g., an engine-out NOx sensor, a pressure sensor, a flow rate sensor, a temperature sensor, etc.). Those of ordinary skill in the art will appreciate and recognize the high configurability of the sensors in the vehicle **10**.

(19) As the components of FIG. **1** are shown to be embodied in the vehicle **10**, the controller **140** may be structured as one or more electronic control units (ECU). For example, the controller **140** may be included with or separate from an engine control unit, an aftertreatment system control unit, a transmission control unit, or another ECU included with the vehicle **10**. The function and structure of the controller **140** is described in greater detail in FIG. **2**.

(20) Referring now to FIG. **2**, a schematic diagram of the controller **140** of the vehicle **10** of FIG. **1** is shown, according to an example embodiment. As shown in FIG. **2**, the controller **140** includes a processing circuit **202** having a processor **204** and a memory **206**, an enable circuit **220**, a low NOx circuit **222**, an engine operation circuit **224**, a low flow circuit **226**, a diagnosis circuit **228**, and a communications interface **210**. Generally, the controller **140** is structured to determine that a condition is present for an amount of system-out NOx (SONOx) to be at or below a predefined threshold (in one embodiment, the SONOx threshold is approximately 7 ppm of NOx), determine that the low NOx condition persists for a certain period of time, and sample sensed SONOx values during the certain period of time. The controller **140** then filters the sensed SONOx values, compares a minimum of the filtered values to one or more thresholds, and diagnoses a health of the tailpipe NOx sensor **127** based on the comparison.

(21) In one configuration, the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** are embodied as machine or computer-readable media storing instructions that are executable by a processor, such as processor **204**. As described herein and amongst other uses, the machine-readable media facilitates performance of certain operations to enable reception and transmission of data. For example, the machine-readable media may provide an instruction (e.g., command, etc.) to, e.g., acquire data. In this regard, the machine-readable media may include programmable logic that defines the frequency of acquisition of the data (or, transmission of the data). The computer readable media instructions may include code, which may be written in any programming language including, but not limited to, Java or the like and any conventional procedural programming languages, such as the “C” programming language or similar programming languages. The computer readable program code may be executed on one processor or multiple remote processors. In the latter scenario, the remote processors may be connected to each other through any type of network (e.g., CAN bus, etc.).

(22) In another configuration, the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** are embodied as hardware units, such as electronic control units. As such, the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may be embodied as one or more circuitry components including, but not limited to, processing circuitry, network interfaces, peripheral devices, input devices, output devices, sensors, etc. In some embodiments, the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may take the form of one or more analog circuits, electronic circuits (e.g., integrated circuits (IC), discrete circuits, system on a chip (SOCs) circuits, microcontrollers, etc.), telecommunication circuits, hybrid circuits, and any other type of “circuit.” In this regard, the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may include any type of component for accomplishing or facilitating achievement of the operations described herein. For

example, a circuit as described herein may include one or more transistors, logic gates (e.g., NAND, AND, NOR, OR, XOR, NOT, XNOR, etc.), resistors, multiplexers, registers, capacitors, inductors, diodes, wiring, and so on). The enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may also include programmable hardware devices such as field programmable gate arrays, programmable array logic, programmable logic devices or the like. The enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may include one or more memory devices for storing instructions that are executable by the processor(s) of the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228**. The one or more memory devices and processor(s) may have the same definition as provided below with respect to the memory **206** and processor **204**. In some hardware unit configurations, the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may be geographically dispersed throughout separate locations in the vehicle. Alternatively and as shown, the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may be embodied in or within a single unit/housing, which is shown as the controller **140**.

(23) In the example shown, the controller **140** includes the processing circuit **202** having the processor **204** and the memory **206**. The processing circuit **202** may be structured or configured to execute or implement the instructions, commands, and/or control processes described herein with respect to the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228**. The depicted configuration represents the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** as machine or computer-readable media storing instructions. However, as mentioned above, this illustration is not meant to be limiting as the present disclosure contemplates other embodiments where the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228**, or at least one circuit of the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228**, is configured as a hardware unit. All such combinations and variations are intended to fall within the scope of the present disclosure.

(24) The processor **204** may be implemented as a single- or multi-chip processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A processor may be a microprocessor. A processor also may be implemented as a combination of computing devices, such as a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. In some embodiments, the one or more processors may be shared by multiple circuits (e.g., the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may comprise or otherwise share the same processor which, in some example embodiments, may execute instructions stored, or otherwise accessed, via different areas of memory). Alternatively or additionally, the one or more processors may be structured to perform or otherwise execute certain operations independent of one or more co-processors. In other example embodiments, two or more processors may be coupled via a bus to enable independent, parallel, pipelined, or multi-threaded instruction execution. All such variations are intended to fall within the scope of the present disclosure.

(25) The memory **206** (e.g., memory, memory unit, storage device) may include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present disclosure. The memory **206** may be communicably connected to the processor **204** to provide

computer code or instructions to the processor **204** for executing at least some of the processes described herein. Moreover, the memory **206** may be or include tangible, non-transient volatile memory or non-volatile memory. Accordingly, the memory **206** may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described herein.

(26) The communications interface **210** may include any combination of wired and/or wireless interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals) for conducting data communications with various systems, devices, or networks structured to enable in-vehicle communications (e.g., between and among the components of the vehicle) and out-of-vehicle communications (e.g., with a remote server). For example and regarding out-of-vehicle/system communications, the communications interface **210** may include an Ethernet card and port for sending and receiving data via an Ethernet-based communications network and/or a Wi-Fi transceiver for communicating via a wireless communications network. The communications interface **210** may be structured to communicate via local area networks or wide area networks (e.g., the Internet) and may use a variety of communications protocols (e.g., IP, LON, Bluetooth, ZigBee, radio, cellular, near field communication).

(27) Components of the vehicle **10** may communicate with each other or foreign components using any type and any number of wired or wireless connections. For example, a wired connection may include a serial cable, a fiber optic cable, a CAT5 cable, or any other form of wired connection. Wireless connections may include the Internet, Wi-Fi, cellular, radio, Bluetooth, ZigBee, etc. In one embodiment, a controller area network (CAN) bus provides the exchange of signals, information, and/or data. The CAN bus includes any number of wired and wireless connections. Because the controller **140** is communicably coupled to the systems and components in the vehicle **10**, the vehicle controller **140** is structured to acquire operation data and/or OBD capability data regarding one or more of the components or systems shown in FIG. **1**. For example, the operation data may include data regarding operating conditions of the powertrain **100** acquired by one or more sensors, such as sensors **130**.

(28) Each of the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** are configured to assist in the deduction of sensor offset for the tailpipe NOx sensor **127**. Sensor offset is defined as an amount of units (e.g., if the sensor is a temperature sensor acquiring values in the unit 'degrees,' the amount of sensor offset is in the unit 'degrees.') that the sensed value (i.e., the value output by the particular sensor) differs from an actual value. Offset can be either negative (i.e., the sensed value is less than the actual value) or positive (i.e., the sensed value is higher than the actual value). For example, if the sensor offset for a temperature sensor is +10° C. and the sensed value is 250° C., then the actual value is 240° C. Determining the amount of sensor offset may be critical for vehicle **10** operation because failing to account for a difference between sensed values and actual values can negatively affect those vehicle **10** operations that rely on accurate sensed values.

(29) The enable circuit **220** is structured or configured to determine if an enabling condition is satisfied or present prior to running or executing the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228**. The enable condition may relate to the health of the vehicle **10** and may include one or more a plurality of conditions that are indicative of a health of the vehicle **10** or components thereof. Healthy components refer to components that are operating as intended (e.g., no presence of fault or error codes, operating parameters are within predefined acceptable ranges, etc.). In operation, the controller **140** does not execute the various circuits if there are outstanding error or fault flags/codes raised for components within the vehicle **10** (i.e., the enable condition indicative of a healthy component is not satisfied). For example, if there are existing faults identified for the tailpipe NOx sensor **127**, the enable circuit **220** determines that the enabling condition is not satisfied. In addition, if a particular sensor is determined to be affected by gain by an adverse material amount, the enable circuit **220** determines that the enabling condition is

not satisfied.

(30) With particular regard to the aftertreatment system **120**, aftertreatment system-specific enabling conditions include a) whether SCR **123** temperature drops more than an amount (e.g., 20-50° C.) from an operating temperature as a significant drop in SCR **123** temperature expands ammonia storage capacity and leads to less (or no) ammonia release to avoid ammonia being falsely read as NO_x by the sensors **129**; b) whether DEF dosing occurs for at least a certain predefined period of time (e.g., 120-600 s) after a regeneration event, as regeneration events deplete ammonia storage, which is then replenished by this amount of DEF dosing; c) whether DEF dosing has been occurring for a certain predefined period of time regardless of regeneration events (e.g., 60-180 s), which ensures that ammonia storage is available for efficient NO_x conversion; and, d) whether a temperature of the SCR **123** is inside of a pre-determined temperature range (e.g., a range of temperatures at which the SCR **123** is efficiently reducing NO_x, such as 220-450° C.), as there are inherent inaccuracies of modeling NO_x amounts in the exhaust flow with an inefficient SCR. In some embodiments, the enable circuit **220** determines that operations are enabled if at least one of the aforementioned enabling conditions are satisfied. In other embodiments, the enable circuit **220** determines that operations are enabled if more than one enabling condition is satisfied (e.g., all enabling conditions, a majority of the conditions, etc.).

(31) The low NO_x circuit **222** is structured or configured to identify times during which the aftertreatment system **120** is expected to be outputting NO_x (i.e., an amount of tailpipe or system-out NO_x) at or below a predefined threshold (referred to herein as “low NO_x periods”). As described herein, the predefined threshold is approximately zero NO_x. In other embodiments, the predefined threshold may be less than 7-10 ppm of NO_x. In order to identify these low NO_x periods, the low NO_x circuit **222** determines when entry conditions are met and then when exit conditions are met. The entry conditions refer to characteristics indicative of the aftertreatment system **120** entering a period of substantially zero NO_x output, such that when the entry condition thresholds are passed, the low NO_x circuit **222** determines that the aftertreatment system **120** is entering a low NO_x period. In contrast, the exit conditions refer to characteristics indicative of the aftertreatment system **120** exiting a period of substantially zero NO_x output, such that when the exit condition thresholds are passed, the low NO_x circuit **222** determines that the aftertreatment system **120** is exiting a low NO_x period.

(32) In some embodiments, the entry and exit conditions are based on the inlet (i.e., frontside) and outlet (i.e., backside) temperatures for an SCR **123** catalyst (i.e., brick). Particularly, the entry and exit conditions are defined based on a rate of change (ROC) of temperature of the SCR **123** brick, as a low temperature ROC indicates that the SCR **123** brick has reached a desired operating temperature (i.e., a temperature at which the SCR **123** is efficiently reducing NO_x in the exhaust gas) because the SCR **123** brick temperature is no longer changing (e.g., increasing rapidly in order to reach the desired operating temperature). If the SCR **123** brick is at the desired operating temperature, the low NO_x circuit **222** assumes that the output from the aftertreatment system is substantially zero NO_x because the SCR **123** is efficiently reducing NO_x. In contrast, a high temperature ROC across the SCR indicates that the SCR **123** brick is not at a desired operating temperature, as rapid change in SCR **123** brick temperature occurs if there is movement towards a desired operating temperature (e.g., the vehicle **10** was recently started as is warming) or away from the desired operating temperature (e.g., the vehicle **10** is coasting and hot exhaust gas is no longer being output into the aftertreatment system **120**). Put simply, if the SCR **123** brick is experiencing a high temperature ROC, the low NO_x circuit **222** determines that the SCR **123** brick is not at the desired operating temperature.

(33) For the SCR **123** brick, the low NO_x circuit **222** determines a temperature at or near the frontside of the SCR **123** brick and a temperature at the backside of the SCR **123** brick based on a temperature at the inlet of the SCR **123** (from the inlet temperature sensor **125**) and at the outlet of the SCR **123** (from the outlet temperature sensor **126**). In some embodiments, the temperatures of

the frontside and the backside of the SCR **123** brick are based on a weighted average of the inlet temperature and the outlet temperature, where the inlet temperature is multiplied by a first weight factor, the outlet temperature is multiplied by a second weight factor, and the products are summed. For determining a frontside SCR **123** brick temperature, the low NOx circuit **222** applies a first weight factor of 0.8 and a second weight factor of 0.2, such that more weight is given to the inlet SCR **123** temperature. For determining a backside SCR **123** brick temperature, the low NOx circuit **222** applies a first weight factor of 0.2 and a second weight factor of 0.8, such that more weight is given to the outlet SCR **123** temperature.

(34) Once the low NOx circuit **222** determines the frontside and backside temperatures for the SCR **123** brick, the low NOx circuit **222** determines a ROC for each of the frontside and backside temperatures over a pre-defined period of time. In one embodiment, the period of time is 30-120 seconds. By taking ROC samples over a period of time rather than an instantaneous ROC, the low NOx circuit **222** filters out noise inherent in ROC determinations. Once the frontside and backside ROC have been time-filtered, the filtered frontside ROC value and the filtered backside ROC value are each compared to a pre-defined entry threshold (e.g., $-0.2^{\circ}\text{C./second}$). If both ROC values are lower than their respective entry thresholds, the low NOx circuit **222** determines that entry conditions are satisfied and that the aftertreatment system **120** is expected to be outputting substantially zero NOx. However, if either ROC value is greater than a pre-defined exit threshold (e.g., $0.1^{\circ}\text{C./second}$ for 30 seconds), the low NOx circuit **222** determines that exit conditions are satisfied and that the aftertreatment system **120** is no longer expected to be outputting substantially zero NOx. As such, the low NOx circuit **222** determines that the vehicle **10** is in a low NOx period if entry conditions are satisfied but that the exit conditions are not satisfied.

(35) Once the enable circuit **220** determines that operations are enabled and the low NOx circuit **222** determines that the vehicle **10** is in a low NOx period, the active flow circuit **224** is structured or configured to monitor operation of the vehicle **10** while the engine **101** is running (i.e. providing power to the motor generator or directly to the final drive **105**). As configured, the active flow circuit **224** monitors conditions with regard to the tailpipe NOx sensor **127** in order to assist in determining an amount of offset present for each sensor. While the engine **101** is operating, the active flow circuit **224** monitors operation for one of two conditions: a) the engine-out NOx (EONox) being less than a threshold (e.g., 20 parts per million (ppm)); and b) the EONox mass flow rate being less than a threshold (e.g., 0.05 grams/second) while DEF dosing is active. If either of these conditions are met, the active flow circuit **224** begins to take the integral (i.e., cumulatively sums) of the overall exhaust mass flow rate. Once that integrated value exceeds a pre-determined threshold (e.g., 1000 grams), the active flow circuit **224** increments an active flow timer if the NOx sensor reading is stable. The NOx sensor reading is determined to be stable if a virtual engine-out O.sub.2 reading ROC is higher than a pre-defined threshold (e.g., -0.5 percent change/second) and if one of the engine power ROC, exhaust pressure ROC, or exhaust flow ROC is below a pre-defined threshold (e.g., 5 horsepower/s, 10 kpa/s, and 5 g/s.sup.2 respectively).

(36) Once the active flow timer has ended (e.g., 10-30 seconds), the active flow circuit **224** increments an event timer and sets an active flow event flag based on the event timer in one of two situations. First, if the event timer exceeds a first threshold (e.g., 120-300 s), the active flow circuit **224** sets an active flow event flag regardless of other operating parameters. Second, if the event timer exceeds a second threshold (e.g., 10-120 s) that is lower than the first threshold, the active flow circuit **224** sets the active flow event flag if one of four secondary conditions is met: 1) a temperature spike (e.g., $>1^{\circ}\text{C./second}$ for 30 seconds) in the SCR **123** is detected; 2) the tailpipe NOx sensor **127** is inactive (i.e., a dew-point temperature threshold for sensor activation is not met); 3) an operation cycle, which is defined based on a type of the vehicle **10** (e.g., for a heavy-duty vehicle, the operation cycle is 4 hours), is complete; or 4) the vehicle **10** is keyed-off (i.e., the key, start button, or other ignition means for the vehicle is in an off state and the vehicle is not turned on). Put simply, an active flow event flag counts an instance in which a low NOx period

lasted for a certain length of time during a period of active flow. In this embodiment, the second threshold is lower than the first threshold in order for the active flow circuit **224** to be able to make decisions more quickly for short-duty cycles.

(37) Once the enable circuit **220** determines that operations are enabled and the low NOx circuit **222** determines that the vehicle **10** is in a low NOx period, the low flow circuit **226** is structured or configured to monitor operation of the vehicle **10** while the engine **101** is not running (e.g., ignition/propulsion for the engine **101** is turned off, the motor generator **106** is providing all of the power for the powertrain **100**, etc.). In particular, the low flow circuit **226** is configured to monitor an exhaust gas flow in the vehicle and particularly a characteristic of the exhaust gas flow in the vehicle. In one embodiment, the low flow circuit **226** monitors how an amount of EONox tapers to substantially zero (i.e., 'bleeds off') as no new EONox is generated due to the engine **101** not operating. When the amount of EONox goes below a pre-defined threshold (e.g., 100 ppm), the low flow circuit **226** starts a bleed-off timer. The length of this bleed-off timer is an estimated time (e.g., 10-120 s) for the SONox to taper off to substantially zero, and is set as a function of exhaust pressure and ambient pressure. For higher values of exhaust pressure, the bleed-off timer is set as a lower value, due to higher exhaust pressure resulting in shorter bleed-offs because the higher exhaust pressure pushes remaining NOx out of the engine **101** more quickly. In contrast, for higher values of ambient pressure, the bleed-off time is set as a higher value, due to higher ambient pressure resulting in longer bleed-offs because the higher ambient pressure affects the pressure differential, thereby reducing the movement speed of exhaust (and NOx) in the vehicle **10**. When the bleed-off timer expires, the low flow circuit **226** increments a low flow timer if the NOx sensor reading is stable. The NOx sensor reading is determined to be stable if a virtual engine-out O2 reading ROC is less than a pre-defined threshold (e.g., -0.5 percent change/second) and if one of the engine power ROC, exhaust pressure ROC, or exhaust flow ROC is below a pre-defined threshold (e.g., 5 horsepower/s, 10 kpa/s, and 5 g/s² respectively).

(38) Once the low flow timer has ended (e.g., 10-30 seconds), the low flow circuit **226** increments an event timer and sets a low flow event flag based on the event timer in one of two situations. First, if the event timer exceeds a first threshold (e.g., 120-300 seconds), the low flow circuit **226** sets a low flow event flag regardless of other operating parameters. Second, if the event timer exceeds a second threshold (e.g., 10-120 seconds) that is lower than the first threshold, the low flow circuit **226** sets the low flow event flag if one of four secondary conditions is met: 1) a temperature spike (e.g., >1° C./second for 30 s) in the SCR **123** is detected; 2) the tailpipe NOx sensor **127** is inactive (i.e., a dew-point temperature threshold for sensor activation is not met); 3) an operation cycle, which is defined based on a type of the vehicle **10** (e.g., for a heavy-duty vehicle, the operation cycle is 4 hours), is complete; or 4) the vehicle **10** is keyed-off (as defined above). Put simply, a low flow event flag counts an instance in which a low NOx period lasted for a certain length of time during a period of low flow. In this embodiment, the second threshold is lower than the first threshold in order for the low flow circuit **226** to be able to make decisions more quickly for short-duty cycles.

(39) The diagnosis circuit **228** is structured or configured to receive event flag information from the active flow circuit **224** and low flow circuit **226**, apply decision logic based on the event flags, filter the logic output values, and set or clear sensor failure indications based on the filtered output. First, the diagnosis circuit **228** increments an event counter based on each event flag (i.e., active flow flag and low flow flag) received from the active flow circuit **224** and low flow circuit **226**. As such, the event counter tracks the number of instances that the vehicle **10** is experiencing a low NOx period of a certain length of time in both active flow (i.e., engine **101** operating) and low flow (i.e., engine **101** off).

(40) The diagnosis circuit **228** determines that a decision update is due (i.e., enough time and enough low NOx periods have occurred that a determination of tailpipe NOx sensor **127** status is due). The diagnosis circuit **228** makes this determination in one of two situations. First, if the total

number of events flags exceeds a first threshold (e.g., 2 or 4), the diagnosis circuit **228** determines that a decision update is due. Second, if the total number of event flags exceeds a second threshold (e.g., 1 or 2) that is lower than the first threshold, the diagnosis circuit **228** determines that a decision update is due if one of three secondary conditions is satisfied: 1) the vehicle **10** is keyed-off; 2) an operation cycle, which is defined based on a type of the vehicle **10** (e.g., for a heavy-duty vehicle, the operation cycle is 4 hours), is complete; and 3) an exponentially weighted moving average (EWMA) fast initial response (FIR) or step change mode is detected. FIR is a user-initiated mode that affects the weighting effect for EWMA calculations that emphasizes most recent values in order to more quickly clear faults. Step change is a separate EWMA mode that emphasizes most recent values in order to more quickly react to changing conditions. In this embodiment, the second threshold is lower than the first threshold in order for the low flow circuit **226** to be able to make decisions more quickly for short-duty cycles. Furthermore, each of the secondary considerations are indicative of either an end of operation (such that a decision to check sensor status as an end-of-day task is logical) or an accelerated decision process (such that a more frequent status checks of the sensor is desired).

(41) If the diagnosis circuit **228** determines that a decision update is due, the diagnosis circuit **228** samples and tracks minimum values of system-out NOx (SONOx) from the tailpipe NOx sensor **127**. In some embodiments, the diagnosis circuit **228** only samples and tracks SONOx values when the NOx sensor reading is determined to be stable. The NOx sensor reading is determined to be stable if a virtual engine-out O.sub.2 reading ROC is higher than a pre-defined threshold (e.g., -0.5 percent change/second) and if one of the engine power ROC, exhaust pressure ROC, or exhaust flow ROC is below a pre-defined threshold (e.g., 5 horsepower/s, 10 kpa/s, and 5 g/s.sup.2 respectively). From there, the diagnosis circuit **228** takes a minimum of the sampled SONOx values from the sampling period and inputs the minimum value into a EWMA filter that improves the usability of a raw dataset and materially transforms an entire dataset down to a single value that is easily useable, that reduces memory storage requirements, and that may improve diagnostic operations for the vehicle. The EWMA filter takes the average of a particular value (e.g., minimum sampled SONOx) from multiple sampling periods (i.e., a moving average), and applies a weighting factor to the most recent values that decreases exponentially as values get less recent. In this way, the most recent values (e.g., values from the last x minutes or hours, or the last x values) receive exponentially more weight in the moving average calculation than less recent values (e.g., values from more than x minutes or hours ago, or the values older than the last x values), smoothing the data set by reducing the impact of noise within the data and emphasizing the most recently-sampled datapoints.

(42) Because these sampled SONOx values are collected while the controller **140** expects the SONOx to be zero (i.e., low NOx periods), if the SONOx values are not zero, that difference is likely due to offset affecting the tailpipe NOx sensor **127**. As such, the filtered SONOx value, which is determined by the diagnosis circuit **228** based on these sampled SONOx values from low NOx periods, is essentially a value of an amount of offset affecting the tailpipe NOx sensor **127**. This filtered SONOx value can therefore be compared against a first threshold indicative of an unacceptable high offset and a second threshold indicative of an unacceptable low offset. Based on this comparison, the diagnosis circuit **228** sets a tailpipe NOx sensor **127** offset fault flag. Put simply, if the minimum of the filtered SONOx values is above the first threshold (i.e., the offset is unacceptably high) or if the minimum of the filtered SONOx values is below the second threshold (i.e., the offset is unacceptably low or negative), the diagnosis circuit **228** determines that the tailpipe NOx sensor **127** is operating outside of acceptable offset levels. However, if the minimum of the filtered SONOx values is between the first and second thresholds (i.e., neither unacceptably high nor unacceptably low) and if a tailpipe NOx sensor **127** offset fault flag is currently set, the diagnosis circuit **228** clears the fault flag.

(43) In some embodiments, the diagnosis circuit **228** tracks separate fault flags for each of the

operating modes (i.e., low flow and active flow). Because low flow event flags and active flow event flags cannot be set at the same time due to the impossibility of the engine **101** simultaneously operating and not operating, when the diagnosis circuit **228** determines that a decision is due based on an accumulation of fault flags, the accumulated fault flags are either all active flow event flags or all low flow event flags. As such, when the diagnosis circuit **228** makes a fault flag determination based on the filtered SONOx value, that decision is associated with either active flow or low flow operation. In these embodiments then, the diagnosis circuit **228** sets/clears an active flow tailpipe NOx sensor **127** offset fault flag and a low flow tailpipe NOx sensor **127** offset fault flag.

(44) In these embodiments with separate fault flags, if the decision from the diagnosis circuit **228** is to clear the tailpipe NOx sensor **127** offset fault flag (i.e., the filtered SONOx value is between the two thresholds), the diagnosis circuit **228** only clears the fault flag if the operation mode for the decision update is the same as the operation mode for the fault flag. For example, if a fault flag is currently an active flow tailpipe NOx sensor **127** offset fault flag and if the decision update is triggered by an accumulation of active flow event flags, the diagnosis circuit **228** may decide to clear the active flow tailpipe NOx sensor **127** fault flag. However, if the fault flag is currently an active flow tailpipe NOx sensor **127** offset fault flag but the decision update is triggered by an accumulation of low flow event flags, the diagnosis circuit **228** cannot clear the active flow tailpipe NOx sensor **127** fault flag, even if the filtered SONOx value is between the thresholds.

(45) In addition to setting a fault flag, the diagnosis circuit **228** may take one or more actions based on the fault flag. In some embodiments, the diagnosis circuit **228** exits closed loop DEF control (i.e., DEF dosing is based on an engine-out NOx sensor and the tailpipe NOx sensor **127**) and enters open loop DEF control (i.e., DEF dosing is based entirely on the engine-out NOx sensor). In other embodiments, the diagnosis circuit **228** commands a visual indication (e.g., ‘check engine’ light, etc.) for the user indicative of the fault flag. In further embodiments, the diagnosis circuit **228** reduces or ceases DEF dosing based on the fault flag because the controller **140** ‘loses trust’ in the system-out NOx sensor **127**.

(46) FIG. **3** is a flow chart of a method **300** for determining an amount of offset affecting the tailpipe NOx sensor **127** and diagnosing a status of the tailpipe NOx sensor **127**. As shown in FIG. **3**, the method **300** begins at process **301**. At process **302**, the controller **140** determines if reset conditions have been met (e.g., if there are pre-existing fault flags for the vehicle **10**, etc.). If the reset conditions are met (**302:YES**), the method **300** returns to the start at process **301**. If the reset conditions are not met (**302:NO**), the method **300** proceeds to **310** and **364**. At **310**, the controller **140** determines if enable conditions for determining a valid or accurate SCR **123** temperature are satisfied in order to predict low NOx periods. These enable conditions are discussed herein with regard to the enable circuit **220**, such that process **310** is performed by the enable circuit **220**. From there, the method **300** proceeds to **320**, where the controller **140** determines if the vehicle **10** is expected to be experiencing substantially zero NOx output from the aftertreatment system **120**. As described herein, process **320** is performed by the low NOx circuit **222**.

(47) If the controller **140** determines that the vehicle **10** is not currently experiencing a low NOx period (**320:NO**), the method **300** returns to determining enable condition satisfaction at **310**. If the controller **140** determines that the vehicle **10** is currently expected to be experiencing zero SONOx (**320:YES**), the controller **140** proceeds to **330** or **340** depending on engine **101** operation. If the engine **101** is currently operating and exhaust is actively flowing through the aftertreatment system at **330**, the controller **140** determines that one of two conditions is satisfied. First, at **331**, the controller **140** detects that proper testing conditions are present for engine motoring based on an EONox value being below a threshold at **332**. Second, at **333**, the controller **333** determines that proper testing conditions are present for SCR **123** high efficiency based on an EONox mass flow rate being below a threshold while DEF dosing is active at **334**. If either of these two conditions (i.e., either **332** or **334**) are satisfied, the controller **140** takes an integral of the exhaust mass flow

rate at **335** while either of these two conditions are satisfied. Once the integrated value from **335** exceeds a threshold and NOx sensor readings are determined to be stable from **393** (discussed in more detail below), the controller **140** increments an active flow timer at **336**. Once this active flow timer expires, an event timer is incremented for the event update trigger logic at **350**, which sets thresholds for the event timer based on other operating parameters. Based on the event update trigger logic, the controller **140** sets an active flow event flag at **337**, which is output at **391**. As described herein, processes **330-337** are performed by the active flow circuit **224**.

(48) If the engine **101** is not currently operating such that no exhaust is being generated at **340**, the controller **140** determines that there is NOx “bleed out” (i.e., an amount of NOx in the aftertreatment system **120** is tapering towards substantially zero) at **342** based on the EONox being below a threshold at **343**. From there, the method **300** proceeds to **343**, where the controller **140** sets a bleed off timer based on an estimation of how long the remaining NOx in the aftertreatment system **120** will take to reach substantially zero, which is a function of exhaust pressure and ambient pressure. Once the bleed off timer expires, the controller **140** increments a low flow timer at **344** if the NOx sensor readings are determined to be stable from **393**. Once this low flow timer expires, an event timer is incremented for the event update trigger logic at **350**, which sets thresholds for the event timer based on other operating parameters. Based on the event update trigger logic, the controller **140** sets a low flow event flag at **345**, which is output at **392**. As described herein, processes **340-345** are performed by the low flow circuit **226**.

(49) Before the method **300** samples and tracks minimum SONox values at **364**, the controller **140** determines that the tailpipe NOx sensor **127** readings are stable at **363**. This determination is made based on a virtual engine-out O.sub.2 reading being stable at **361** and either the engine power, exhaust pressure, or exhaust flow reading (from the sensor array **129**) being stable at **362**. The determination of stability at **363** is output to **364** and to **393**. From there, the sampled minimum SONox value is fed into a EWMA filter at **366**. However, the filtered SONox value is not output from **366** until the decision update logic from **365** determines that a decision update is due. The decision update logic at **365** takes as inputs the active flow event flags from **391** and the no flow event flags from **392**.

(50) Once the filtered SONox value is output from **366**, the value is compared to a high threshold (i.e., a threshold value for offset indicative of unacceptably high offset) at **371** and to a low threshold (i.e., a threshold value for offset indicative of unacceptably low offset) at **372**. If the filtered SONox value is above the high threshold (**371:YES**) or below the low threshold (**372:YES**), the method **300** proceeds to **373** where the controller **140** sets a tailpipe NOx sensor **127** fault flag. However, if the filtered SONox value is below the high threshold (**371:NO**) and above the low threshold (**372:NO**), the method proceeds to **375**, where the controller **140** applies similar conditions logic to determine if a fault flag should be cleared. As discussed above with regard to the diagnosis circuit **228**, in those embodiments in which there are separate fault flags for active flow mode and no flow mode, the controller **140** clears a fault flag only if the fault flag is for the same operation mode as the current decision update. As such, the similar conditions logic at **375** takes as inputs the active fault event flag of **391** and the no flow event flag of **392**. If the similar condition logic at **375** indicates that the operation modes are the same, the controller **140** clears the associated tailpipe NOx sensor **127** offset fault flag at **376**.

(51) As utilized herein, the terms “approximately,” “about,” “substantially”, and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the disclosure as recited in the

appended claims.

(52) It should be noted that the term “exemplary” and variations thereof, as used herein to describe various embodiments, are intended to indicate that such embodiments are possible examples, representations, or illustrations of possible embodiments (and such terms are not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

(53) The term “coupled” and variations thereof, as used herein, means the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent or fixed) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members coupled directly to each other, with the two members coupled to each other using one or more separate intervening members, or with the two members coupled to each other using an intervening member that is integrally formed as a single unitary body with one of the two members. If “coupled” or variations thereof are modified by an additional term (e.g., directly coupled), the generic definition of “coupled” provided above is modified by the plain language meaning of the additional term (e.g., “directly coupled” means the joining of two members without any separate intervening member), resulting in a narrower definition than the generic definition of “coupled” provided above. Such coupling may be mechanical, electrical, or fluidic. For example, circuit A communicably “coupled” to circuit B may signify that the circuit A communicates directly with circuit B (i.e., no intermediary) or communicates indirectly with circuit B (e.g., through one or more intermediaries).

(54) References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below”) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

(55) While various circuits with particular functionality are shown in FIG. 2, it should be understood that the controller **140** may include any number of circuits for completing the functions described herein. For example, the activities and functionalities of the enable circuit **220**, the low NOx circuit **222**, the engine operation circuit **224**, the low flow circuit **226**, and the diagnosis circuit **228** may be combined in multiple circuits or as a single circuit. Additional circuits with additional functionality may also be included. Further, the controller **140** may further control other activity beyond the scope of the present disclosure.

(56) As mentioned above and in one configuration, the “circuits” may be implemented in machine-readable medium for execution by various types of processors, such as the processor **204** of FIG. 2. Executable code may, for instance, comprise one or more physical or logical blocks of computer instructions, which may, for instance, be organized as an object, procedure, or function.

Nevertheless, the executables need not be physically located together, but may comprise disparate instructions stored in different locations which, when joined logically together, comprise the circuit and achieve the stated purpose for the circuit. Indeed, a circuit of computer readable program code may be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and across several memory devices. Similarly, operational data may be identified and illustrated herein within circuits, and may be embodied in any suitable form and organized within any suitable type of data structure. The operational data may be collected as a single data set, or may be distributed over different locations including over different storage devices, and may exist, at least partially, merely as electronic signals on a system or network.

(57) While the term “processor” is briefly defined above, the term “processor” and “processing circuit” are meant to be broadly interpreted. In this regard and as mentioned above, the “processor” may be implemented as one or more processors, application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), digital signal processors (DSPs), or other suitable electronic data processing components structured to execute instructions provided by memory. The one or more processors may take the form of a single core processor, multi-core processor (e.g., a

dual core processor, triple core processor, quad core processor, etc.), microprocessor, etc. In some embodiments, the one or more processors may be external to the apparatus, for example the one or more processors may be a remote processor (e.g., a cloud based processor). Alternatively or additionally, the one or more processors may be internal and/or local to the apparatus. In this regard, a given circuit or components thereof may be disposed locally (e.g., as part of a local server, a local computing system, etc.) or remotely (e.g., as part of a remote server such as a cloud based server). To that end, a “circuit” as described herein may include components that are distributed across one or more locations.

(58) Although the figures and description may illustrate a specific order of method steps, the order of such steps may differ from what is depicted and described, unless specified differently above. Also, two or more steps may be performed concurrently or with partial concurrence, unless specified differently above. Such variation may depend, for example, on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations of the described methods could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps.

Claims

1. A method for diagnosing a sensor of an exhaust aftertreatment system, the method comprising: receiving, by a controller, a first indication of active exhaust gas flow from an engine to the exhaust aftertreatment system or a second indication of no or low exhaust gas flow to the exhaust aftertreatment system; determining, by the controller and in response to the first indication, that an amount of an exhaust gas constituent in the exhaust gas flow at a particular location is expected to be at or below a first predefined value or that an exhaust gas constituent mass flow rate is expected to be at or below a second predefined value for a period of time; determining, by the controller and in response to the second indication, that the amount of the exhaust gas constituent at the particular location is expected to be at or below the first predefined value for the period of time; receiving, by the controller, data indicative of a sensed amount of the exhaust gas constituent from the sensor of the exhaust aftertreatment system during the period of time; determining, by the controller and based on the sensed amount of the exhaust gas constituent, an amount of offset affecting the sensor of the exhaust aftertreatment system; and initiating, by the controller, an action based on the determined amount of offset to diagnose the sensor, wherein the action comprises adjusting a reductant dosing based on the offset.
2. The method of claim 1, wherein the exhaust gas constituent is nitrous oxide (NO_x).
3. The method of claim 1, wherein the first predefined value is approximately zero parts-per-million.
4. The method of claim 1, wherein the particular location is a system out location and wherein the exhaust gas constituent is NO_x.
5. The method of claim 1, wherein the sensor is a system-out NO_x sensor.
6. The method of claim 1, wherein determining that the amount of the exhaust gas constituent at the particular location is expected to be at or below the first predefined value for the period of time comprises: receiving, by the controller, data indicative of an inlet temperature for a selective catalytic reduction (SCR) of the exhaust aftertreatment system and of an outlet temperature for the SCR; determining, by the controller, a frontside temperature and a backside temperature for the SCR based on the inlet temperature and the outlet temperature; comparing, by the controller, each of the frontside temperature and the backside temperature to a first threshold and a second threshold; and responsive to a determination that both the frontside temperature and the backside temperature are greater than the first threshold and less than the second threshold, determining, by the controller, that the amount of the exhaust gas constituent is expected to be at or below the first

predefined value.

7. The method of claim 1, further comprising: determining, by the controller, that an enabling condition is satisfied prior to determining that the amount of the exhaust gas constituent is expected to be at or below the first predefined value or that the exhaust gas constituent mass flow rate is expected to be at or below the second predefined value.
8. The method of claim 1, wherein responsive to the determined amount of offset exceeding a predefined high threshold, the action comprises setting a fault indicator for the first indication or the second indication, the fault indicator regarding the sensor.
9. The method of claim 8, wherein responsive to the determined amount of offset being less than a predefined low threshold, the action comprises setting a fault indicator for the first indication or the second indication, the fault indicator regarding the sensor, and wherein responsive to the determined amount of offset falling between the predefined low and high thresholds, the fault indicator for the first indication or the second indication is bypassed.
10. A system for diagnosing a sensor of an exhaust aftertreatment system, the system comprising: a controller comprising a processor coupled to a memory storing executable instructions, the executable instructions when executed by the processor cause the processor to: receive a first indication of active exhaust gas flow from an engine to the exhaust aftertreatment system or a second indication of no or low active exhaust gas flow to the exhaust aftertreatment system; determine, in response to the first indication, that an amount of an exhaust gas constituent in the exhaust gas flow at a particular location is expected to be at or below a first predefined value or that an exhaust gas constituent mass flow rate is expected to be at or below a second predefined value for a period of time; determine, in response to the second indication, that the amount of the exhaust gas constituent at the particular location is expected to be at or below the first predefined value for the period of time; receive data indicative of a sensed amount of the exhaust gas constituent from the sensor of the exhaust aftertreatment system during the period of time; determine, based on the sensed amount of the exhaust gas constituent, an amount of offset affecting the sensor of the exhaust aftertreatment system; and initiate an action based on the determined amount of offset to diagnose the sensor, wherein the action comprises adjusting a reductant dosing based on the offset.
11. The system of claim 10, wherein the exhaust gas constituent is nitrous oxide (NO_x).
12. The system of claim 10, wherein the first predefined value is approximately zero parts-per-million.
13. The system of claim 10, wherein the particular location is a system out location and wherein the exhaust gas constituent is NO_x.
14. The system of claim 10, wherein the sensor is a system-out NO_x sensor.
15. The system of claim 10, wherein in determining that the amount of the exhaust gas constituent at the particular location is expected to be at or below the first predefined value for the period of time, the processor is configured to: receive data indicative of an inlet temperature for a selective catalytic reduction (SCR) of the exhaust aftertreatment system and of an outlet temperature for the SCR; determine a frontside temperature and a backside temperature for the SCR based on the inlet temperature and the outlet temperature; compare each of the frontside temperature and the backside temperature to a first threshold and second threshold; and responsive to a determination that both the frontside temperature and the backside temperature are greater than the first threshold and less than the second threshold, determine that the amount of the exhaust gas constituent is expected to be at or below the first predefined value.
16. The system of claim 10, wherein the executable instructions when executed by the processor further cause the processor to: determine that an enabling condition is satisfied prior to determining that the amount of the exhaust gas constituent is expected to be at or below the first predefined value or that the exhaust gas constituent mass flow rate is expected to be at or below the second predefined value.

17. The system of claim 10, wherein responsive to the determined amount of offset exceeding a predefined high threshold, the action comprises setting a fault indicator for the first indication or the second indication, the fault indicator regarding the sensor.

18. The system of claim 17, wherein responsive to the determined amount of offset being less than a predefined low threshold, the action comprises setting a fault indicator for the first indication or the second indication, the fault indicator regarding the sensor, and wherein responsive to the determined amount of offset falling between the predefined low and high thresholds, the fault indicator for the first indication or the second indication is bypassed.

19. A non-transitory computer-readable medium comprising executable instructions that, when executed by a processor, cause the processor to: receive a first indication of active exhaust gas flow from an engine to the exhaust aftertreatment system or a second indication of no or low active exhaust gas flow to the exhaust aftertreatment system; determine, in response to the first indication, that an amount of an exhaust gas constituent at a particular location is expected to be at or below a first predefined value or that an exhaust gas constituent mass flow rate is expected to be at or below a second predefined value for a period of time; determine, in response to the second indication, that the amount of the exhaust gas constituent at the particular location is expected to be at or below the first predefined value for the period of time; receive data indicative of a sensed amount of the exhaust gas constituent from a sensor of the exhaust aftertreatment system during the period of time; determine, based on the sensed amount of the exhaust gas constituent, an amount of offset affecting the sensor of the exhaust aftertreatment system; and initiate an action based on the determined amount of offset to diagnose the sensor, wherein the action comprises adjusting a reductant dosing based on the offset.

20. The non-transitory computer-readable medium of claim 19, wherein in determining that the amount of the exhaust gas constituent at the particular location is expected to be at or below the first predefined value for the period of time, the executable instructions when executed cause the processor to: receive data indicative of an inlet temperature for a selective catalytic reduction (SCR) of the exhaust aftertreatment system and of an outlet temperature for the SCR; determine a frontside temperature and a backside temperature for the SCR based on the inlet temperature and the outlet temperature; compare each of the frontside temperature and the backside temperature to a first threshold and a second threshold; and responsive to a determination that both the frontside temperature and the backside temperature are greater than the first threshold and less than the second threshold, determine that the amount of the exhaust gas constituent is expected to be at or below the first predefined value.
