

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12393944
B2
August 19, 2025
Lee; Earle Michael et al.

Transaction exchange platform having streaming transaction data and microservices

Abstract

Aspects described herein may relate to a transaction exchange platform using a streaming data platform (SDP) and microservices to process transactions according to review and approval workflows. The transaction exchange platform may receive transactions from origination sources, which may be added to the SDP as transaction objects. Microservices on the transaction exchange platform may interact with the transaction objects based on configured workflows associated with the transactions. Processing on the transaction exchange platform may facilitate clearing and settlement of transactions. Some aspects may provide for dynamic and flexible reconfiguration of workflows and/or microservices. Other aspects may provide for data snapshots and workflow tracking, allowing for monitoring, quality control, and auditability of transactions on the transaction exchange platform.

Inventors: Lee; Earle Michael (Midlothian, VA), Planck; William (Midlothian, VA)

Applicant: Capital One Services, LLC (McLean, VA)

Family ID: 1000008766827

Assignee: Capital One Services, LLC (McLean, VA)

Appl. No.: 18/605276

Filed: March 14, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240303657 A1	Sep. 12, 2024

Related U.S. Application Data

continuation parent-doc US 17942499 20220912 US 11961077 child-doc US 18605276
continuation parent-doc US 17144666 20210108 US 11481773 20221025 child-doc US 17942499
continuation parent-doc US 16723392 20191220 US 10891615 20210112 child-doc US 17144666

Publication Classification

Int. Cl.: G06F40/00 (20200101); G06F16/23 (20190101); G06Q20/40 (20120101)

U.S. Cl.:

CPC G06Q20/401 (20130101); G06F16/2379 (20190101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7110969	12/2005	Bennett et al.	N/A	N/A
9754318	12/2016	Spies et al.	N/A	N/A
10129078	12/2017	Kumar et al.	N/A	N/A
10474977	12/2018	Stevens et al.	N/A	N/A
10839022	12/2019	Klein et al.	N/A	N/A
11057353	12/2020	Smith et al.	N/A	N/A
2006/0149611	12/2005	Diep et al.	N/A	N/A
2007/0100961	12/2006	Moore	N/A	N/A
2007/0276714	12/2006	Beringer	N/A	N/A
2007/0288459	12/2006	Kashiyama	N/A	G06F 16/20
2007/0288635	12/2006	Gu et al.	N/A	N/A
2008/0010198	12/2007	Eliscu	N/A	N/A
2009/0313311	12/2008	Hoffmann et al.	N/A	N/A
2010/0138438	12/2009	Torikai	707/759	G06F 16/24568
2010/0232286	12/2009	Takahashi et al.	N/A	N/A
2011/0047054	12/2010	Ginter et al.	N/A	N/A
2012/0030094	12/2011	Khalil	N/A	N/A
2013/0152021	12/2012	Hatfield et al.	N/A	N/A
2013/0152041	12/2012	Hatfield et al.	N/A	N/A
2014/0372394	12/2013	Frankel	707/703	G06F 16/128
2015/0088756	12/2014	Makhotin et al.	N/A	N/A
2015/0379514	12/2014	Poole	705/44	G06Q 20/227
2016/0004751	12/2015	Lafuente Alvarez et al.	N/A	N/A
2016/0035014	12/2015	Smith	705/14.45	G06Q 30/0269

2016/0110687	12/2015	Kamat et al.	N/A	N/A
2016/0124742	12/2015	Rangasamy et al.	N/A	N/A
2016/0253645	12/2015	Ciabarra et al.	N/A	N/A
2016/0307190	12/2015	Zarakas et al.	N/A	N/A
2017/0041189	12/2016	Aswathanarayana et al.	N/A	N/A
2017/0060621	12/2016	Whipple et al.	N/A	N/A
2018/0032534	12/2017	Koerner et al.	N/A	N/A
2018/0077038	12/2017	Leff et al.	N/A	N/A
2018/0101848	12/2017	Castagna et al.	N/A	N/A
2018/0103042	12/2017	Castagna et al.	N/A	N/A
2018/0307514	12/2017	Koutyrine et al.	N/A	N/A
2018/0332138	12/2017	Liu et al.	N/A	N/A
2019/0043207	12/2018	Carranza et al.	N/A	N/A
2019/0199626	12/2018	Thubert et al.	N/A	N/A
2019/0333069	12/2018	Noble et al.	N/A	N/A
2020/0004604	12/2019	Lavoie et al.	N/A	N/A
2020/0241944	12/2019	Derdak et al.	N/A	N/A
2020/0257676	12/2019	Zhang et al.	N/A	N/A
2020/0310830	12/2019	Morgan et al.	N/A	N/A
2021/0019194	12/2020	Bahl et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108052996	12/2017	CN	N/A

OTHER PUBLICATIONS

Rimma Nehme, Efficient Query Processing for Rich and Diverse Real-Time Data, Purdue University, Jun. 10, 2009 (Year: 2009). cited by applicant

Nov. 25, 2020—Final Rejection—U.S. Appl. No. 16/723,545. cited by applicant

Feb. 1, 2021—Notice of Allowance—U.S. Appl. No. 16/723,439. cited by applicant

Rathnayake, A Realtime Monitoring Platform for Workflow Subroutines, 2018 IEEE (Year: 2018). cited by applicant

Feb. 12, 2021—Notice of Allowance—U.S. Appl. No. 16/723,509. cited by applicant

Apr. 1, 2021—International Search Report and Written Opinion—PCT/US2020/065979. cited by applicant

Goel Divya et al: “Reactive Microservices in Commodity Resources”, 2019 IEEE International Conference on Big Data (Big Data), IEEE, Dec. 9, 2019 (Dec. 9, 2019), pp. 3658-3665, XP033721750, DOI: 10.1109/BIGDATA47090.2019.9006584. cited by applicant

Limon Xavier et al: “SagaMAS: A Software Framework for Distributed Transactions in the Microservice Architecture”, 2018 6th International Conference in Software Engineering Research and Innovation (Conisoft), IEEE, Oct. 24, 2018 (Oct. 24, 2018), pp. 50-58, XP033520566, DOI: 10.1109/CONISOFT.2018.8645853. cited by applicant

Jun. 5, 2023—Extended European Search Report—EP 20903637.5. cited by applicant

Jun. 5, 2023—Extended European Search Report—EP 23163594.7. cited by applicant

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/942,499, now U.S. Pat. No. 11,961,077 and filed on Sep. 12, 2022, which is a continuation of U.S. application Ser. No. 17/144,666, now U.S. Pat. No. 11,481,773 and filed on Jan. 8, 2021, which is a continuation of prior U.S. application Ser. No. 16/723,392, now U.S. Pat. No. 10,891,615 and filed on Dec. 20, 2019, the entirety of which is incorporated herein by reference. (2) This application is related to the following U.S. patent applications, filed on the same day as U.S. application Ser. No. 16/723,392: U.S. patent application Ser. No. 16/723,439, now U.S. Pat. No. 11,023,528, titled “Transaction Exchange Platform Having Configurable Microservices” and filed Dec. 20, 2019; U.S. patent application Ser. No. 16/723,480, now U.S. Pat. No. 10,789,600, titled “Transaction Exchange Platform With Snapshot Microservice” and filed Dec. 20, 2019; U.S. patent application Ser. No. 16/723,509, now U.S. Pat. No. 11,037,168, titled “Transaction Exchange Platform With Watchdog Microservice” and filed Dec. 20, 2019; and U.S. patent application Ser. No. 16/723,545, now U.S. Pat. No. 11,080,120, titled “Transaction Exchange Platform With Watchdog Microservice” and filed Dec. 20, 2019.

Each of the related applications is incorporated by reference herein in its entirety for all purposes.

FIELD OF USE

(1) Aspects of the disclosure relate generally to a transaction exchange platform. More specifically, aspects of the disclosure may provide for dynamic, reliable, and auditable processing of transactions through use of a streaming data platform.

BACKGROUND

(2) Computer systems and applications have revolutionized the handling of transactions and greatly accelerated clearing and settlement processes. Software solutions have been created to facilitate processing, validation, and approval of transactions. These systems serve to interface transaction originators with clearing and settlement operations, allowing transactions to flow between enterprises and facilitating the movement of trillions of dollars per year. Yet regulations, security, and risk management processes have grown increasingly important and detailed, thereby complicating the approval and settlement of transactions.

(3) Different transaction types may be subject to different approval workflows. Payment processing systems may be configured to perform the required approval steps for each different transaction type. Yet such payment processing systems have become incredibly complex, monolithic software services designed to accommodate and enforce the many aspects of the process of reviewing and approving a transaction for settlement. Although sometimes divided into modules corresponding to different transactions, changes to single steps in a given transaction's approval workflow may require re-coding, re-compiling, and re-deploying large software components. Additionally, problems with individual steps of the workflows can grind the whole approval process to a halt.

(4) Aspects described herein may address these and other shortcomings present in existing solutions. Novel aspects discussed herein may implement a transaction exchange platform using a streaming data platform and microservices to provide faster, more dynamic, and more robust processing and approval of transactions. The novel transaction exchange platform may provide benefits such as improving the flexibility and reliability of transaction approval and processing systems, while offering robust record keeping for transaction audit purposes. The novel platform may also provide other benefits such as support for legacy and ongoing operations, solving for new and changing requirements in today's environment, and adapting to future technologies

SUMMARY

- (5) The following presents a simplified summary of various aspects described herein. This summary is not an extensive overview, and is not intended to identify key or critical elements or to delineate the scope of the claims. The following summary merely presents some concepts in a simplified form as an introductory prelude to the more detailed description provided below.
- (6) Aspects described herein may relate to a transaction exchange platform using a streaming data platform (SDP) and microservices to process transactions according to review and approval workflows. The transaction exchange platform may receive transactions from origination sources, which may be added to the SDP as transaction objects. Microservices on the transaction exchange platform may interact with the transaction objects based on configured workflows associated with the transactions. Processing on the transaction exchange platform may facilitate clearing and settlement of transactions. Some aspects may provide for dynamic and flexible reconfiguration of workflows and/or microservices. Other aspects may provide for data snapshots and workflow tracking, allowing for monitoring, quality control, and auditability of transactions on the transaction exchange platform.
- (7) In particular, some aspects may provide a transaction exchange platform implemented using a SDP and a plurality of microservices to process transactions. Transaction objects may be pushed to the SDP from origination sources via APIs associated with the transaction exchange platform. Transaction objects may include transaction details and transaction metadata. The transaction metadata may include at least an indication of a workflow corresponding to a transaction type of the transaction object and a current workflow stage of the transaction object. The workflow may comprise a plurality of processing steps required to approve a given transaction of the transaction type.
- (8) Microservices on the transaction exchange platform may poll the SDP to identify and retrieve transaction objects having a current workflow stage matching a workflow stage associated with the microservice. Transaction objects matching the microservice's assigned workflow stage may be processed by the microservice for review, approval, and/or any other suitable processing as part of the overall series of steps required to approve a transaction of the corresponding transaction type. Processing may result in updating one or more elements of the transaction metadata. Once the microservice completes its processing of the transaction object, the microservice can put the transaction object back to the SDP with an updated current workflow stage indicating that the microservice completed its processing. The updated transaction object may then be identified and processed by a next microservice based on the workflow.
- (9) The steps of the workflow corresponding to a given transaction type may be organized as a directed acyclic graph (DAG). The DAG may indicate the steps required to approve a transaction, from when it enters the transaction exchange platform until approval is completed and the transaction is ready for further processing by downstream systems. The DAG may include parallel paths, whereby the transaction object may be subject to concurrent processing by multiple microservices. The DAG may indicate pre-requisite conditions that govern the progression of the transaction object through the stages of the workflow. For example, processing by a microservice in the DAG may be conditioned on the completion of processing by one or more other microservices. The DAG may also indicate branching, conditional paths where a transaction object may be subject to processing by different microservices (and/or different processing generally) based on certain transaction attributes.
- (10) A current workflow stage value may be maintained as part of the transaction metadata in each transaction object. The current workflow stage may indicate which processing steps of the associated workflow have been completed on the transaction. The current workflow stage may indicate the completion of status of each respective step of the workflow. As such, in an example implementation the current workflow stage value may be a set of values and/or a data structure indicating the completion of individual workflow steps, e.g. processing by respective microservices. Microservices may be configured to poll the SDP for transactions having a current

workflow stage value that indicates completion of each of the pre-requisite steps for processing by the microservice.

(11) When the current workflow stage of a transaction object indicates it has completed the steps of the corresponding workflow, the transaction object may be removed from the SDP and routed or otherwise made available to other components of an overall transaction system. For example, the approved transaction object, having passed through all steps of the corresponding workflow, may be published to a public streaming data platform accessible outside of the transaction exchange platform. Enterprise systems, applications, users, and others may access the completed transaction objects on the public streaming data platform and further process for transaction settlement or other purposes.

(12) Some aspects described herein may provide for dynamic reconfiguration of the workflows and/or microservices. For example, a workflow may be modified to change a progression of a transaction object from one microservice to the next. This may be implemented by modifying the configuration of a microservice to look for a different current workflow stage on the streaming data platform. A microservice may be modified to change processing logic and/or any other aspect controlling how the microservice interacts with the streaming data platform and/or transaction objects, or any other aspect of the microservice. For example, processing logic of the microservice may be changed to an updated version to be used in processing future transactions. A configuration interface may generate configuration transaction objects that cause the dynamic reconfiguration of the workflow and/or microservices. Configuration transaction objects may be added to the SDP with a configuration workflow type, and the microservices may retrieve and process the configuration transaction objects. A configuration transaction object may be configured such that, when processed by a microservice, it causes reconfiguration of that microservice.

(13) Reconfiguration of the workflows and/or microservices may be handled in a versioned manner, such that transactions on the SDP may be handled according to an appropriate and auditable version of the workflow. When a new configuration version is pushed to the SDP for a given workflow, it may be added with a new version value. Transaction objects on the transaction exchange platform may include, as part of their transaction metadata, an indication of a current version value for the workflow at the time they entered the transaction exchange platform. The microservices on the transaction exchange platform may be further configured to identify transaction objects having an appropriate current workflow stages based on the version value of the transaction object. Thus, transactions added under a first workflow version may reliably be processed under the first workflow version, while transactions added after a shift to a second workflow version may be processed using the new, updated workflow version (and associated microservices and processing logic).

(14) Some aspects described herein may provide a snapshot microservice on the transaction exchange platform, configured to maintain a record of the data values of the transaction object as it progresses through the workflow. The snapshot microservice may be configured to identify and retrieve transaction objects added to the SDP in an initialization stage. The snapshot microservice may create a snapshot record for new transaction objects and store a copy of the data of the transaction object. As the transaction object progresses through the workflow and is processed by the other microservices, the snapshot microservice can identify transaction objects that have their data changed. The snapshot microservice can retrieve the changed objects and store snapshot data tracking the change of the transaction object.

(15) These snapshots of the transaction object may be used to correct processing errors in the approval workflow, as a transaction object may have its data reverted back to an earlier state and its workflow stage reverted to an earlier stage. In this way, the transaction object may be made to repeat an earlier step of the workflow and be subject to re-processing by a corresponding microservice. The snapshot data may also support audit of the transactions, offering a complete picture of how the transaction object changed while on the transaction exchange platform. The

snapshot microservice may track a number of times that a transaction object is reverted/replayed on one or more microservices, and may flag a transaction as presenting problems requiring manual or other review when the number of replays exceeds a transaction or based on other criteria.

(16) Corresponding apparatus, systems, and computer-readable media are also within the scope of the disclosure.

(17) These features, along with many others, are discussed in greater detail below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present disclosure is illustrated by way of example and not limited in the accompanying figures in which like reference numerals indicate similar elements and in which:
- (2) FIG. 1 depicts an example of a computing device that may be used in implementing one or more aspects of the disclosure in accordance with one or more illustrative aspects discussed herein;
- (3) FIG. 2 depicts an example operating environment used to discuss illustrative aspects of a transaction exchange according to one or more aspects of the disclosure;
- (4) FIG. 3A depicts an example transaction exchange platform according to one or more aspects of the disclosure;
- (5) FIGS. 3B-3C depict example structures for microservices according to one or more aspects of the disclosure;
- (6) FIG. 4 depicts an illustrative workflow as a directed acyclic graph according to one or more aspects of the disclosure;
- (7) FIG. 5 depicts an illustrative method for processing transactions on a streaming data platform according to one or more aspects of the disclosure;
- (8) FIG. 6 depicts an example transaction exchange platform having a configuration interface according to one or more aspects of the disclosure;
- (9) FIGS. 7A-7C depict illustrative changes to workflows, as graphs, according to one or more aspects of the disclosure;
- (10) FIG. 8 depicts an illustrative method for reconfiguring microservices according to one or more aspects of the disclosure;
- (11) FIG. 9 depicts an example transaction exchange platform having a snapshot microservice according to one or more aspects of the disclosure; and
- (12) FIGS. 10-11 depict illustrative methods for operation of the snapshot microservice according to one or more aspects of the disclosure.

DETAILED DESCRIPTION

(13) In the following description of the various embodiments, reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration various embodiments in which aspects of the disclosure may be practiced. It is to be understood that other embodiments may be utilized and structural and functional modifications may be made without departing from the scope of the present disclosure. Aspects of the disclosure are capable of other embodiments and of being practiced or being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein are for the purpose of description and should not be regarded as limiting. Rather, the phrases and terms used herein are to be given their broadest interpretation and meaning. The use of “including” and “comprising” and variations thereof is meant to encompass the items listed thereafter and equivalents thereof as well as additional items and equivalents thereof.

(14) By way of introduction, aspects described herein may relate to a transaction exchange platform using a streaming data platform and microservices to process transactions according to review and approval workflows. A transaction exchange platform, according to one or more aspects

discussed herein, may provide a version agnostic data streaming, reactive microservice solution that facilitates payment related workflows to be executed. Although the term “microservice” is used throughout this disclosure, aspects are not limited to “microservices” as used in cloud computing contexts. Generally, as used herein “microservice” may refer to a technology process that does work on an object on a streaming data platform in any given step of a workflow. Aspects discussed herein may refer to “approval” of transactions. This generally refers to the processing necessary to move a transaction through the transaction exchange platform from intake to output, and does not necessarily mean that the payment exchange platform affirmatively approves the nature of the transaction. Instead, “approval” as used herein may refer to processing, validating, and/or affirmatively approving a transaction according to a workflow indicating the steps necessary to process a transaction on the platform before it is ready for output to downstream processors. Some aspects may provide for dynamic and flexible reconfiguration of workflows and/or microservices. Other aspects may provide for data snapshots and workflow tracking, allowing for monitoring, quality control, and auditability. Each of these aspects may work in concert to provide a flexible, robust, and auditable processing platform for transaction clearing and approval.

(15) Before discussing these concepts in greater detail, however, several examples of a computing device that may be used in implementing and/or otherwise providing various aspects of the disclosure will first be discussed with respect to FIG. 1.

(16) FIG. 1 illustrates one example of a computing device **101** that may be used to implement one or more illustrative aspects discussed herein. For example, computing device **101** may, in some embodiments, implement one or more aspects of the disclosure by reading and/or executing instructions and performing one or more actions based on the instructions. In some embodiments, computing device **101** may represent, be incorporated in, and/or include various devices such as a desktop computer, a computer server, a mobile device (e.g., a laptop computer, a tablet computer, a smart phone, any other types of mobile computing devices, and the like), and/or any other type of data processing device.

(17) Computing device **101** may, in some embodiments, operate in a standalone environment. In others, computing device **101** may operate in a networked environment. As shown in FIG. 1, various network nodes **101**, **105**, **107**, and **109** may be interconnected via a network **103**, such as the Internet. Other networks may also or alternatively be used, including private intranets, corporate networks, LANs, wireless networks, personal networks (PAN), and the like. Network **103** is for illustration purposes and may be replaced with fewer or additional computer networks. A local area network (LAN) may have one or more of any known LAN topology and may use one or more of a variety of different protocols, such as Ethernet. Devices **101**, **105**, **107**, **109** and other devices (not shown) may be connected to one or more of the networks via twisted pair wires, coaxial cable, fiber optics, radio waves or other communication media.

(18) As seen in FIG. 1, computing device **101** may include a processor **111**, RAM **113**, ROM **115**, network interface **117**, input/output interfaces **119** (e.g., keyboard, mouse, display, printer, etc.), and memory **121**. Processor **111** may include one or more computer processing units (CPUs), graphical processing units (GPUs), and/or other processing units such as a processor adapted to perform computations associated with machine learning. I/O **119** may include a variety of interface units and drives for reading, writing, displaying, and/or printing data or files. I/O **119** may be coupled with a display such as display **120**. Memory **121** may store software for configuring computing device **101** into a special purpose computing device in order to perform one or more of the various functions discussed herein. Memory **121** may store operating system software **123** for controlling overall operation of computing device **101**, transaction exchange platform software **125** for instructing computing device **101** to perform aspects discussed herein, machine learning software **127**, smart database **129**, and other applications **131**. Machine learning software **127** may be incorporated in and may be a part of transaction exchange platform software **125**. In embodiments, computing device **101** may include two or more of any and/or all of these

components (e.g., two or more processors, two or more memories, etc.) and/or other components and/or subsystems not illustrated here.

(19) Devices **105**, **107**, **109** may have similar or different architecture as described with respect to computing device **101**. Those of skill in the art will appreciate that the functionality of computing device **101** (or device **105**, **107**, **109**) as described herein may be spread across multiple data processing devices, for example, to distribute processing load across multiple computers, to segregate transactions based on geographic location, user access level, quality of service (QoS), etc. For example, devices **101**, **105**, **107**, **109**, and others may operate in concert to provide parallel computing features in support of the operation of control logic **125** and/or software **127**.

(20) One or more aspects discussed herein may be embodied in computer-usable or readable data and/or computer-executable instructions, such as in one or more program modules, executed by one or more computers or other devices as described herein. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types when executed by a processor in a computer or other device. The modules may be written in a source code programming language that is subsequently compiled for execution, or may be written in a scripting language such as (but not limited to) HTML or XML. The computer executable instructions may be stored on a computer readable medium such as a hard disk, optical disk, removable storage media, solid state memory, RAM, etc. As will be appreciated by one of skill in the art, the functionality of the program modules may be combined or distributed as desired in various embodiments. In addition, the functionality may be embodied in whole or in part in firmware or hardware equivalents such as integrated circuits, field programmable gate arrays (FPGA), and the like. Particular data structures may be used to more effectively implement one or more aspects discussed herein, and such data structures are contemplated within the scope of computer executable instructions and computer-usable data described herein. Various aspects discussed herein may be embodied as a method, a computing device, a data processing system, or a computer program product.

(21) Having discussed several examples of computing devices which may be used to implement some aspects as discussed further below, discussion will now turn to methods and techniques for implementing a transaction exchange platform.

(22) Transaction Exchange Platform—Processing Streaming Transaction Data Using Microservices

(23) Aspects described herein may provide a transaction exchange platform implemented using a streaming data platform (SDP) and a plurality of microservices to process transactions according to workflows corresponding to different transaction types. Microservices on the transaction exchange platform may be configured to retrieve transactions having a current workflow stage that is assigned to the microservice from the SDP. The microservice may perform one or more steps of the approval/review workflow for the type of transaction, update the status of the object, and put it back to the SDP. Other microservices, later in the workflow, may see that the current workflow status of a transaction indicates that earlier pre-requisite processing steps have completed and may accordingly retrieve the transaction objects and perform their respective workflow steps. When the current workflow stage of a transaction indicates that all requisite steps of the workflow have been completed, the transaction may be removed from the SDP of the transaction exchange platform and output to downstream systems for further processing.

(24) A high level system **200** for processing transactions, such as payments, is illustrated in FIG. 2. Transaction processing system **200** may broadly illustrate the flow of transactions from origination source **205** through to settlement systems **220**. Transactions handled by system **200** may take any suitable form, generally as payment transactions. Example types of payment transactions include: wires, automated clearing house (ACH) payments, checks, cashier checks, real-time payments (RTP), credit cards, and/or many other types of payment transactions. Other factors that may inform the “type” of a transaction may include whether the transaction originates domestically or internationally, whether the destination is domestic or international, an amount of the transaction,

the identity of one or more financial entities associated with the transaction, and the like. For purposes of the discussion herein, a transaction type may be relevant primarily for informing the review/approval steps that should be applied to the transaction prior to final settlement.

(25) Transactions may begin at origination sources **205**. For example, if a customer were to purchase a donut at a bakery using a credit card, the transaction may be sent via a point-of-sale (POS) terminal at the bakery to a payment processor. As another example, an investor may cause a wire payment to be sent to their broker via a banking website. The banking website may receive the wire payment transaction and begin the process of facilitating settlement of the wire transaction via a transaction processing system **200**.

(26) Transactions may be routed to settlement systems **220** to effect the transfer of the monies indicated in the transaction. For example, the wire transaction may be routed to respective financial institutions associated with the investor and broker to indicate the respective debit/credit to their accounts. However, substantial review and approval processing may be required before a transaction may be settled. This processing may involve regulatory, security, and/or risk management.

(27) Transaction exchange platform **210** may serve as an interface between the origination source **205** and settlement systems **220**, and according to some aspects may implement the transaction review and approval workflow for each supported transaction type. Origination sources **205** may send transactions to transaction exchange platform **210** for review and approval processing, and ultimately for routing to settlement systems **220**. Transaction exchange platform **210** may be provided by the same entity operating settlement systems **220** and/or one or more of origination sources **205**, or may be provided by a third-party entity.

(28) Transaction exchange platform **210** may perform the review and approval processing for transactions. This may include interfacing with clearing systems **215**. Clearing systems **215** may provide regulatory, security, and/or risk management support for transactions. For example, transactions may be referred to systems provided by the U.S. Federal Reserve as part of a clearance process. As another example, the identities of the parties to the transaction may need to be evaluated against various criteria in support of anti-money laundering or other such efforts. Clearing systems **215** may be provided as part of transaction exchange platform **210**, or as logically separate systems. Clearing systems **215** may be provided by the entities operating origination sources **205**, transaction exchange platform **210**, settlement systems **220**, government entities, and/or other third parties.

(29) Transaction exchange platform **210** may interface with clearing systems **215** to complete review and approval processing on the transaction. Transactions that are approved on transaction exchange platform **210** may be routed to settlement systems **220** for settlement and/or further processing.

(30) FIG. 3A illustrates a system **300** that may provide further details of a novel transaction exchange platform **320** than provided in FIG. 2, according to some aspects described herein. Similarly, transactions may originate at transaction origination sources **303** and route to downstream settlement systems, illustrated in FIG. 3A as enterprise systems and users **350**.

(31) Transaction exchange platform **320** may serve to perform review and approval workflow processing on transactions received from transaction origination sources **303** via enterprise transaction intermediary services **305**. Transaction origination sources **303** may include both first- and third-party sources of transactions. The enterprise providing transaction exchange platform **320** may provide transaction intermediary services **305** to receive transactions, whether from third-parties or not, and route those transactions to transaction exchange platform **320**. Enterprise transaction intermediary service **305** may perform validation, pre-processing, standardization, and/or any other suitable processing to prepare transactions for further handling by transaction exchange platform **320**.

(32) Transactions may be sent to transaction exchange platform **320** via application programming

interfaces (APIs), such as API **311** and API **313**. The APIs may validate aspects of the transaction details, and may package and/or standardize transactions into transaction objects suitable for processing on transaction exchange platform **320**. In some implementations, transaction exchange platform **320** may provide different APIs for each type of transaction. For example, API **311** may correspond to ACH transactions while API **313** corresponds to wire transactions. In some implementations, fewer APIs (such as a single centralized API) may be used to flexibly validate and initialize transactions for processing by transaction exchange platform **320**. The APIs for interfacing with transaction exchange platform **320** may comprise a number of components, such as a public API front-end, basic input validation logic, message level integrity processes, monitoring, and/or integration aspects.

(33) Transaction objects may be pushed to a streaming data platform (SDP) **325** underlying transaction exchange platform **320**. Streaming data platforms, such as those based on the Apache Kafka open-source platform, may be used to process real-time data in computer systems. Message objects pushed to the streaming data platform may be read by consumer software modules, processed, and put back to the streaming data platform. Transaction objects on SDP **325** may be subject to processing by microservices on transaction exchange platform **320**, such as microservice **331**, microservice **332**, and microservice **333**. The microservices can read and write transaction objects from/to SDP **325**. Objects on SDP **325** may proceed logically through time, e.g. t.sub.0 through t.sub.n, as they progress through stages of the workflow associated with a corresponding transaction type.

(34) Transaction objects, such as transaction object **307**, may include transaction details, addenda, and transaction metadata. The transaction details and/or addenda may include the particulars of the transaction, such as the parties and/or accounts involved, as well as the amount of the payment. Addenda data of the transaction object may include, e.g., ABA routing numbers and other details that may be added, updated, and/or processed by the microservices on transaction exchange platform **320**. The transaction metadata may include at least an indication of a workflow corresponding to a transaction type of the transaction object and a current workflow stage of the transaction object. In some implementations, discussed further herein, the transaction metadata may also include workflow version information.

(35) As an example, transaction object **307** may include the following:

(36) TABLE-US-00001 { transaction ID : a SHA256 encoded token workflow type : ACH current workflow stage : init transaction details : ISO20022 token addenda data { ABA routing : xyz } }

(37) Transaction object **307** may encapsulate any suitable standard payment object, such as one storing transaction details in a recognized JSON format. As mentioned, and as illustrated further in FIG. **6**, transaction objects may also include a current workflow version assigned to the transaction object. Still other metadata may be included, such as a replay tracking count indicating the number of times that the transaction has been subject to replay through one or more steps of the workflow. Transaction details may be immutable, not subject to change while the transaction object is on the streaming data platform, whereas metadata and/or addenda data may be subject to change through additions, removals, updates, and/or other processing or modification by the microservices on transaction exchange platform **320**.

(38) A current workflow stage value may be maintained as part of the transaction metadata in each transaction object. The current workflow stage may indicate which processing steps of the associated workflow have been completed on the transaction. The current workflow stage may indicate the completion status of each respective step of the workflow. As such, in an example implementation the current workflow stage value may be a set of values and/or a data structure indicating the completion of individual workflow steps, e.g. processing by respective microservices. Microservices may be configured to poll the SDP for transactions having a current workflow stage value that indicates completion of each of the pre-requisite steps for processing by the microservice.

(39) Microservices on the transaction exchange platform may poll the SDP to identify and retrieve transaction objects having a current workflow stage matching a workflow stage associated with the microservice. Transaction objects matching the microservice's assigned workflow stage may be processed by the microservice for review, approval, and/or any other suitable processing as part of the overall series of steps required to approve a transaction of the corresponding transaction type. Processing may result in updating one or more elements of the transaction metadata. Once the microservice completes its processing of the transaction object, the microservice can put the transaction object back to the SDP with an updated current workflow stage indicating that the microservice completed its processing. The updated transaction object may then be identified and processed by a next microservice based on the workflow.

(40) Turning briefly to FIGS. 3B and 3C, FIG. 3B illustrates an example structure for a microservice **330N**. The microservice may comprise subcomponents configured to work in concert to apply processing logic associated with a workflow step assigned to the microservice. In the illustrated structure, microservice **330N** comprises a stream listener **3301** which may operate as a standardized way to read from SDP **325** and consume transaction objects that meet the workflow criteria (e.g., stage) associated with microservice **330N**. Microservice **330N** may also include private API **3302**, which may be a RESTful implementation used in synchronous calls supporting singleton integrations into transaction exchange platform **320**, and its use may allow only the response to be exposed to the public API aspect of microservice **330N**. Microservice **330N** may also include core logic **3303**, which may contain the business logic and associated computer instructions to fulfill microservice **330N**'s assigned role in the workflow. Core logic **3303** may be adapted to process transaction objects in accordance with one or more steps of regulatory, security, and/or risk management processes. Microservice **330N** may further include transient data **3304**, which may include a data management layer that deals with data that is attributed to the local functionality of the system, for example truth tables used in processing by core logic **3303**, and persistent data **3307**, which may include a construct to capture state data for the associated workflow stage. Microservice **330N** may further include messaging components **3305** to track message level integrity via natural key encryption derivations of the payment object. And microservice **330N** may include monitoring components **3306**, configured to provide oversight and tracking, and integration components **3308**, configured to provide the ability to integrate with software structure patterns such as Async SDP, SOAP, RESTful API, and the like. As illustrated in FIG. 3C, however, a microservice may be made up of a collection of other microservices. For example, as illustrated microservice **331N** comprises component microservices **3321**, **3322**, and **3323**.

(41) Returning to FIG. 3A, illustrative transaction exchange platform **320** includes three microservices (microservices **331**, **332**, and **333**) configured to operate on ACH transactions. Transaction object **307** is an example ACH transaction, and is added to SDP **325** via API **311**. Transaction object **307** may be added to SDP **325** in an "init" or initialization stage, indicating that none of the workflow steps have yet been completed. In some implementations, the initialization stage may be a separate stage that is marked completed prior to processing by a first microservice, or may be commensurate in scope with a first workflow stage associated with a first microservice of the workflow. In some implementations, the initialization stage for the object may be handled as part of the processing by the APIs **311**, **313** or otherwise handled alongside workflow processing by the respective microservices.

(42) Walking through the example, transaction object **307** may be added to SDP **325** in the initialization stage (stage '0'). Microservice **331** may be configured to perform a first step in an approval workflow for transaction having a transaction type of ACH. For example, microservice **331** may be configured to verify that the recipient account of the ACH transaction is valid. Microservice **331** may look for transaction objects on SDP **325** having a first workflow stage (stage '1'), for example a stage that indicates initialization pre-processing was completed or, in some

implementations, transaction objects in the initialization stage itself. As mentioned above, the current workflow stage of transaction object **307** may indicate each (and/or a subset) of the workflow steps that have been completed on transaction object **307**, and the current workflow stage thus may comprise a data structure listing the completion status of each (and/or a subset) of the workflow steps. Microservice **331** may poll SDP **325** to retrieve transaction objects having a current workflow stage matching (e.g., meeting) the first workflow stage assigned to microservice **331**. In this manner, microservice **331** may extract transaction objects from SDP **325** that have met the criteria for microservice **331** to begin processing. For example, microservice **331** may be configured to wait until initialization steps such as new object snapshotting is completed before performing its processing to verify the recipient account. Transaction objects retrieved by microservice **331** may be removed and/or otherwise blocked on SDP **325** pending processing by microservice **331**.

(43) Microservice **331**, having retrieved one or more transaction objects such as transaction object **307**, may perform its corresponding workflow step on the transaction object. The workflow step may comprise suitable processing of the transaction object, such as according to core logic of microservice **331** (similar to core logic **3303** of FIG. **3B**). Processing of the transaction object by microservice **331** (or any other microservice) may comprise any of: retrieving the transaction object; reviewing values and other characteristics of the transaction object; interfacing with clearing systems such as clearing systems **215** and/or other systems; comparing values or characteristics to rules, regulations, policies, and the like; adding, removing, updating, or otherwise changing any aspect of the transaction addenda data or transaction metadata; generating reports and/or alerts; presenting the transaction for manual or other review; and/or any other suitable processing associated with the respective step of the workflow for transactions of that type. For example, processing by a microservice may comprise verifying a value of the transaction details, addenda data, and/or transaction metadata against at least one rule. As another example, processing may comprise verifying a value of the transaction details, addenda data, and/or transaction metadata against a watchlist. Processing may comprise determining that the transaction details, addenda data, and/or transaction metadata fail at least one rule; flagging the transaction object for further review; and holding the transaction object in the current workflow stage pending the further review, where updating the current workflow stage of the transaction object to the third workflow stage is based on determining that the further review is completed. Flagging the transaction object for further review may comprise flagging the transaction object for manual review by a user and/or setting the current workflow stage of the transaction object to a current workflow stage associated with another microservice, other than the microservice that typically processes transactions after the first microservice.

(44) The processed transaction object may be put back to SDP **325** by microservice **331**, and the current workflow stage of the transaction object may be updated to indicate that microservice **331** has completed its processing. For example, transaction object **307** may be updated to have a current workflow stage of '2' after microservice **331** completes its processing.

(45) Back on the SDP **325**, the updated transaction object may be subject to further processing by other microservices in like fashion. For example, microservice **332** may correspond to a second step of processing in the workflow corresponding to ACH transactions, such as a regulatory check associated with anti-money laundering efforts. Microservice **332** may be configured to look for transaction objects having a second current workflow stage, e.g., stage '2', on SDP **325**.

Microservice **332** can poll SDP **325** to retrieve such transaction objects and process them according to its own core logic, similarly to that described above with respect to microservice **331**. The processed transaction object may be put back to the SDP **325** with an updated current workflow stage indicating that processing by microservice **332** is completed. Microservice **333** may be configured to look for a third current workflow stage, e.g. stage '3', and may process transaction objects similarly. For example, microservice **333** could perform processing to obligate a customer's

account for the value of the transaction.

(46) When the current workflow stage of a transaction object indicates it has completed the steps of the corresponding workflow, the transaction object may be removed from SDP **325** and routed or otherwise made available to other components of the overall transaction system. For example, the approved transaction object, having passed through all steps of the corresponding workflow, may be published to a public streaming data platform **340** accessible outside of the transaction exchange platform. Enterprise systems, applications, users, and others (e.g. enterprise services and users **350**) may access the completed transaction objects on the public streaming data platform and further process for transaction settlement or other purposes.

(47) The structure described herein, where microservices poll SDP **325** for transaction objects having corresponding current workflow stages, may drive payments and other transactions through the system and requisite review and approval workflows. As mentioned, the workflow for a given transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. Workflows may be implemented in the configurations of what workflow stage metadata each microservice is configured to look for on the SDP **325**. However, workflows may also be logically described and/or defined using a directed acyclic graph structure, as described further with respect to FIG. **4**.

(48) FIG. **4** illustrates a sample directed acyclic graph (DAG) **400** that may correspond to a workflow corresponding to transactions having a wire transaction type. The steps of the workflow corresponding to a given transaction type may be organized as a DAG. The DAG may comprise nodes corresponding to the individual steps of the workflow, and edges corresponding to pre-requisite relationships between the steps. The DAG may indicate how transactions from an origination source such as origination **410** flow through the transaction exchange platform **320**, until approval is completed and the transaction is ready for further processing by downstream systems. The DAG may include parallel paths, whereby the transaction object may be subject to concurrent processing by multiple microservices. The DAG may indicate pre-requisite conditions that govern the progression of the transaction object through the stages of the workflow. For example, processing by a microservice in the DAG may be conditioned on the completion of processing by one or more other microservices. The DAG may also indicate branching, conditional paths where a transaction object may be subject to processing by different microservices (and/or different processing generally) based on certain transaction attributes.

(49) Labels A-G in FIG. **4** generally correspond to the following steps of a sample wire transaction workflow: A—Verify the recipient account is valid. B—High value threshold causes a split to C for enhanced verification. C—Enhanced verification for high value transactions. D—Regulatory check that, would go to E if an international Wire. E—International wire processing. F—Occurs when C, D, and E pass and obligates the customer's account for the value until such time as the wire is actually processed. G—Sends the Wire

(50) These steps are explained further herein.

(51) In the example workflow for wire transactions **400** illustrated in FIG. **4**, a transaction object added to transaction platform **320** from origination **410** may first enter step 'A'. Step 'A' may correspond to a microservice that performs processing to verify that a recipient account in the transaction details and/or addenda is valid. Once step 'A' processing is complete, the workflow proceeds to step 'B', which may correspond to a high value thresholder that operates to split transactions for different processing based on their value (also implemented as a microservice). For example, once step 'A' is completed and a first microservice updates the current workflow stage of the transaction object, a microservice associated with step 'B' may pick up the transaction object and determine if it involves a payment over a certain value, e.g., payments more than \$5000. The microservice associated with step 'B' may update the transaction object with different current workflow stages depending on whether the transaction should be subject to high value processing (e.g., step 'C') or standard processing (e.g., step 'D'). Step 'C' may occur subsequent to step 'B'

determining that a high value transaction should be subject to enhanced verification, and may comprise performing the enhanced verification by a corresponding microservice. Step 'D' may comprise performing standard regulatory verification by a corresponding microservice. Step 'D' may also determine if the transaction is an international or domestic wire, and may update the current workflow stage and/or other transaction metadata accordingly. If the transaction is an international wire, it may be routed (by means of the updated transaction metadata) to a microservice associated with step 'E', which may perform further international wire processing. If the transaction is a domestic wire, it may proceed to step 'F' once regulatory checks are completed. Step 'F' may comprise a step to obligate the customer's account for the amount of the wire, and may be conditioned on successful completion of steps 'C', 'D', or 'E' depending on how the transaction progressed through the workflow. For example, a microservice corresponding to step 'F' may be configured to poll SDP 325 for transactions having a current workflow stage that indicates they have completed steps 'C', 'D', or 'E'. Finally, completing the workflow step 'G' may correspond to a microservice configured to send the wire transaction for settlement, such as to settlement systems 220 of FIG. 2 or enterprise services and users 350 of FIG. 3A. Having completed workflow step 'G', the transaction metadata may be updated to indicate completion of the workflow. For example, the current workflow stage of the transaction object may be updated to indicate completion of step 'G'. As another example, the current workflow stage of the transaction object may reflect the completion of each of steps 'A', 'B', 'D', 'F', and 'G'.

(52) Workflow 400 is just one example of a workflow corresponding to a transaction type, and the transaction exchange platform 320 may have many such workflows corresponding to different transaction types. Microservices on transaction exchange platform 320 may be involved in one or more workflows, and may operate on different stages of different workflows.

(53) Workflow steps may proceed in parallel, and may be independent of one or more other steps in the workflow. For example, if validating the account number of the sending party and validating the account number of the receiving party were handled by different microservices, the workflow may indicate that both may occur once the transaction is brought onto the platform. However, later steps may be conditioned on the completion of both steps. Either step may occur first in time, depending on the availability of each respective microservice to handle the transaction.

(54) Microservices on transaction exchange platform 320 may be automatically configured to look for a corresponding current workflow stage. This automatic configuration may be based on the DAG structure used to logically define the workflow. For example, the individual microservices may be automatically configured to poll SDP 325 for transactions having a current workflow stage that indicates that the pre-requisite criteria represented in the DAG is met prior to processing by the microservice. Each microservice may be configured to look for transaction objects on SDP 325 that have a given workflow type and also have a current workflow stage matching that assigned to the microservice. Thus, microservices may be configured to operate as part of multiple workflows, and can look for transaction objects at different stages of the workflows. As discussed further herein with respect to FIG. 6, changes to the DAG may be used to automatically re-configure the microservices to watch for transaction objects in different workflows and/or different workflow stages.

(55) FIG. 5 depicts a flowchart illustrating an example method 500 to process transactions by a transaction exchange platform, such as transaction exchange platform 320. Method 500 may be performed by any suitable computing device and/or combination of computing devices, referred to as the system implementing method 500.

(56) At step 505, the system may configure microservices on the transaction exchange platform to watch for transactions of the streaming data platform (SDP) that have transaction metadata indicating that they are in a current workflow stage corresponding to the individual microservice. As discussed above with respect to FIG. 4, the system may automatically configure the microservices based on a DAG structure that logically defines the steps of the workflow and their

relationships.

(57) At step **510**, the system may receive a transaction object and add it to the streaming data platform. The transaction object may be received from a transaction origination source such as origination source **303**, and may be received from an enterprise intermediary service, such as enterprise transaction intermediary service **305**. The transaction object may be received via one or more APIs of the transaction exchange platform, such as APIs **311** and **313** of transaction exchange platform **320**. The transaction object may be added to the SDP in an initialization stage, which may be implemented through setting a current workflow stage of the transaction object's transaction metadata to an initialization value. The initialization stage may be separate from a first workflow stage associated with a first microservice of the workflow, or could be the same as the first workflow stage. Objects in the initialization stage may be subject to various system processes on the transaction exchange platform, such as format or other verifications, standardization, snapshots, and the like. If the initialization stage is separate from a first workflow stage of the workflow, the transaction object may be updated to have the first workflow stage once initialization processing is completed.

(58) The transaction object, on the SDP, may be subject to processing by one or more microservices including first microservice **520** and second microservice **530**. First microservice may be configured to poll the SDP for transactions in a first workflow stage, while second microservice may be configured to poll the SDP for transactions in a second workflow stage.

(59) At step **521**, first microservice **520** may poll the SDP for transactions having a particular workflow type (corresponding to a transaction type) and having a first workflow stage within that workflow corresponding to first microservice **520**. The SDP may identify transaction objects that have a current workflow stage value that matches the first workflow stage criteria associated with the first microservice **520**. Identification of matching transaction may be based on transaction metadata indicating a type of workflow, a current workflow stage, and other information associated with the workflow (such as workflow version information, discussed below with respect to FIG. 6). At step **523**, first microservice **520** may retrieve the matching transaction objects for processing. Although steps **521** and **523** are illustrated separately, it will be understood that in practice they may be part of a single contiguous act.

(60) At step **525**, first microservice **520** may process the transaction objects it retrieved from the SDP according to processing logic associated with first microservice **520**. Processing a transaction object may include: reviewing, assessing, analyzing, updating, adding to, removing, and/or any other suitable processing of the transaction data, addenda data, and/or transaction metadata associated with the transaction object.

(61) At step **527**, first microservice **520** may update a current workflow stage of the transaction object to indicate completion of the processing corresponding to first microservice **520**. In some embodiments, the current workflow stage may be updated to different next step values depending on the processing by first microservice **520**. For example, as discussed with respect to workflow **400** in FIG. 4, a microservice may update the current workflow stage of a transaction object to route it to different next microservices depending on whether it meets certain criteria, such as having a value greater than a threshold amount.

(62) At step **529**, first microservice **520** may put the updated transaction object back to the SDP. The updated transaction object may have one or more changed values (or none) of its transaction data, addenda data, and/or transaction metadata, in addition to the updated current workflow stage.

(63) In the example of method **500**, first microservice **520** may update the current workflow stage of the transaction object to indicate completion of processing by the first microservice **520**. This updated current workflow stage may correspond to the second current workflow stage that second microservice **530** is looking for on the SDP.

(64) Thus, at step **531**, the second microservice **530** may poll the SDP for transactions having the second workflow stage and, at step **533**, may retrieve transaction objects matching the second

workflow stage. The second microservice **530** may perform similar processing to that described above with respect to first microservice **520**. That is, steps **531**, **533**, **535**, **537**, and **539** may be analogous to steps **521**, **523**, **525**, **527**, and **529**, modified as appropriate for the role assigned to second microservice **530** in the workflow for a given transaction type. The processed, updated transaction object may be put back to the SDP with an updated current workflow stage indicating completion of the processing corresponding to second microservice **530**.

(65) At step **540**, the system may determine that the current workflow stage metadata of the transaction object indicates that all requisite processing steps of the workflow have been completed. As a result, processing by the transaction exchange platform may be completed and the approved transaction object may be removed from the SDP and output for further processing and/or settlement. For example, as illustrated in FIG. **3A**, a completed, approved transaction may be output to a public SDP for access by downstream systems and users.

(66) Thus, according to some embodiments a computer-implemented method may receive a transaction object comprising transaction details and transaction metadata. That transaction metadata may comprise an indication of a workflow corresponding to a transaction type of the transaction object and a current workflow stage of the transaction object. The workflow corresponding to the transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The computer-implemented method may further comprise adding the transaction object to a streaming data platform and updating the current workflow stage of the transaction object to a first workflow stage. A first microservice may poll the streaming data platform to retrieve transactions matching the first workflow stage. The first workflow stage may be associated with the first microservice based on the workflow corresponding to the transaction type. The first microservice may retrieve, from the streaming data platform, the transaction object based on the current workflow stage matching the first workflow stage. The first microservice may process the transaction object. The computer-implemented method may further comprise updating the current workflow stage of the transaction object to a second workflow stage based on completing processing, by the first microservice, of the transaction object. A second microservice may poll the streaming data platform to retrieve transactions matching the second workflow stage. The second workflow stage may be associated with the second microservice based on the workflow corresponding to the transaction type. The second microservice may retrieve, from the streaming data platform, the transaction object based on the current workflow stage matching the second workflow stage. The second microservice may process the transaction object. The computer-implemented method may further comprises updating the current workflow stage of the transaction object to a third workflow stage based on completing processing, by the second microservice, of the transaction object; determining that the current workflow stage of the transaction object indicates that the transaction object has completed processing corresponding to the workflow; and removing the transaction object from the streaming data platform and outputting the transaction object and an indication that the transaction object has completed the processing corresponding to the workflow.

(67) The first and second microservice may be automatically configured to watch for transactions on the streaming data platform in the first and second workflow stages, respectively, based on the plurality of processing steps. A different second workflow may be associated with a second transaction type and may comprise a different second plurality of processing steps required to approve a given transaction of the second transaction type. The second transaction type may be different from the transaction type. The first microservice may operate on transactions associated with both the workflow and the different second workflow. The plurality of processing steps of the workflow may indicate that the first microservice processes the transaction object at a different stage than the different second plurality of processing steps of the different second workflow.

(68) The workflow corresponding to the transaction type may comprise a directed acyclic graph (DAG) indicating the plurality of processing steps required to approve a given transaction of the

transaction type. The first and second microservice may be automatically configured to watch for transactions on the streaming data platform in the first and second workflow stages, respectively, based on the DAG. The computer-implemented method may further comprise, responsive to an update to at least one of the plurality of processing steps indicated in the DAG, automatically reconfiguring at least one microservice based on the update.

(69) The current workflow stage of the transaction object may comprise a data structure indicating completion status of each respective step of a plurality of processing steps associated with the workflow. The transaction object may be updated to have a current workflow stage corresponding to the second workflow stage based on the current workflow stage indicating that the transaction object has been processed by at least the first microservice and a different third microservice. The first workflow stage and a fourth workflow stage may be independent, such that a third microservice receives the transaction object based on the current workflow stage of the transaction object matching the fourth workflow stage irrespective of whether the first microservice has processed the transaction object.

(70) The transaction details may be immutable and may not change while the transaction object is on the streaming data platform. The processing, by the first microservice, of the transaction object may comprise verifying a value of the transaction details, addenda data, and/or transaction metadata against at least one rule. Processing of the transaction object by the first microservice may comprise verifying a value of the transaction details, addenda data, and/or transaction metadata against a watchlist. Processing of the transaction object by the second microservice may comprise determining that the transaction details, addenda data, and/or transaction metadata fail at least one rule, flagging the transaction object for further review, and holding the transaction object in the second workflow stage pending the further review. Updating the current workflow stage of the transaction object to the third workflow stage may be based on determining that the further review is completed. Flagging the transaction object for further review may comprise flagging the transaction object for manual review by a user. Flagging the transaction object for further review may comprise setting the current workflow stage of the transaction object to a fourth workflow stage associated with a third microservice. Updating the current workflow stage of the transaction object to the third workflow stage may be based on determining that processing by the third microservice is completed.

(71) As examples, the transaction type of the transaction object may be a wire type transaction. The workflow may comprise a plurality of processing steps required to approve a wire transaction. The transaction type of the transaction object may be an automated clearing house (ACH) type transaction. The workflow may comprise a plurality of processing steps required to approve an ACH transaction. The transaction type of the transaction object may be a cashier check type transaction. The workflow may comprise a plurality of processing steps required to approve a cashier check transaction. The first microservice may process the transaction object to validate a routing number associated with the transaction object. The second microservice may process the transaction object to verify compliance with at least one regulatory requirement associated with the transaction type. The transaction object may be received via an application programming interface (API).

(72) According to some aspects, a transaction exchange platform may comprise a streaming data platform, a plurality of microservices, at least one processor, and memory. The plurality of microservices may comprise at least a first microservice and a second microservice. The first and second microservice may be automatically configured to watch for transactions on the streaming data platform in corresponding workflow stages based on a plurality of workflows corresponding to a plurality of transaction types. The memory may store instructions that, when executed by the at least one processor, cause the platform to receive a transaction object comprising transaction details and transaction metadata. The transaction metadata may comprise an indication of a workflow corresponding to a transaction type of the transaction object and a current workflow stage of the

transaction object. The workflow corresponding to the transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The instructions, when executed by the at least one processor, may further cause the platform to add the transaction object to the streaming data platform; update the current workflow stage of the transaction object to a first workflow stage; and poll, by the first microservice, the streaming data platform to retrieve transactions matching the first workflow stage. The first workflow stage may be associated with the first microservice based on the workflow corresponding to the transaction type. The instructions, when executed by the at least one processor, may further cause the platform to retrieve, by the first microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the first workflow stage; process, by the first microservice, the transaction object to add, remove, or update addenda data associated with the transaction object; update the current workflow stage of the transaction object to a second workflow stage based on completing processing, by the first microservice, of the transaction object; and poll, by the second microservice, the streaming data platform to retrieve transactions matching the second workflow stage. The second workflow stage may be associated with the second microservice based on the workflow corresponding to the transaction type. The instructions, when executed by the at least one processor, may further cause the platform to retrieve, by the second microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the second workflow stage; process, by the second microservice, the transaction object; update the current workflow stage of the transaction object to a third workflow stage based on completing processing, by the second microservice, of the transaction object; determine that the current workflow stage of the transaction object indicates that the transaction object has completed processing corresponding to the workflow; and remove the transaction object from the streaming data platform and output the transaction object and an indication that the transaction object has completed the processing corresponding to the workflow.

(73) According to some aspects, one or more non-transitory computer readable media may comprise instructions that, when executed by at least one processor, cause a transaction exchange platform to perform steps. Those steps may comprise receiving a transaction object comprising transaction details and transaction metadata. The transaction metadata may comprise an indication of a workflow corresponding to a transaction type of the transaction object, and a current workflow stage of the transaction object. The workflow corresponding to the transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise adding the transaction object to a streaming data platform; updating the current workflow stage of the transaction object to a first workflow stage; and polling, by a first microservice, the streaming data platform to retrieve transactions matching the first workflow stage. The first workflow stage may be associated with the first microservice based on the workflow corresponding to the transaction type. The steps may further comprise retrieving, by the first microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the first workflow stage; processing, by the first microservice, the transaction object; and polling, by a second microservice, the streaming data platform to retrieve transactions matching the first workflow stage. The first workflow stage may be also associated with the second microservice based on the workflow corresponding to the transaction type. The steps may further comprise retrieving, by the second microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the first workflow stage; processing, by the second microservice, the transaction object; updating the current workflow stage of the transaction object to a second workflow stage based on completing processing, by the first microservice and the second microservice, of the transaction object; and polling, by a third microservice, the streaming data platform to retrieve transactions matching the second workflow stage. The second workflow stage may be associated with the third microservice based on the workflow corresponding to the transaction type. The steps may further comprise

retrieving, by the third microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the second workflow stage; processing, by the third microservice, the transaction object; updating the current workflow stage of the transaction object to a third workflow stage based on completing processing, by the third microservice, of the transaction object; determining that the current workflow stage of the transaction object indicates that the transaction object has completed processing corresponding to the workflow; and removing the transaction object from the streaming data platform and outputting the transaction object and an indication that the transaction object has completed the processing corresponding to the workflow.

(74) According to some aspects, a computer-implemented method may comprise steps comprising receiving a transaction object comprising transaction details and transaction metadata. The transaction metadata may comprise an indication of a workflow corresponding to a transaction type of the transaction object, and a current workflow stage of the transaction object. The workflow corresponding to the transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise adding the transaction object to a streaming data platform; and retrieving, by a first microservice and from the streaming data platform, the transaction object based on the current workflow stage matching a first workflow stage. The first workflow stage may be associated with the first microservice based on the workflow corresponding to the transaction type. The steps may further comprise processing, by the first microservice, the transaction object; updating the current workflow stage of the transaction object to a second workflow stage based on completing processing, by the first microservice, of the transaction object; and retrieving, by a second microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the second workflow stage. The second workflow stage may be associated with the second microservice based on the workflow corresponding to the transaction type. The steps may further comprise processing, by the second microservice, the transaction object; updating the current workflow stage of the transaction object to a third workflow stage based on completing processing, by the second microservice, of the transaction object; determining that the current workflow stage of the transaction object indicates that the transaction object has completed processing corresponding to the workflow; and removing the transaction object from the streaming data platform and outputting the transaction object and an indication that the transaction object has completed the processing corresponding to the workflow.

(75) Configurator—Dynamic Microservice Configuration

(76) One or more aspects described herein may provide for dynamic reconfiguration of the workflows and/or microservices. For example, a workflow may be modified to change a progression of a transaction object from one microservice to the next. This may be implemented by modifying the configuration of a microservice to look for a different current workflow stage on the streaming data platform. A microservice may be modified to change processing logic and/or any other aspect controlling how the microservice interacts with the streaming data platform and/or transaction objects, or any other aspect of the microservice. For example, processing logic of the microservice may be changed to an updated version to be used in processing future transactions.

(77) A configuration interface may generate configuration transaction objects that cause the dynamic reconfiguration of the workflow and/or microservices. Configuration transaction objects may be added to the SDP with a configuration workflow type, and the microservices may retrieve and process the configuration transaction objects. The configuration transaction objects may operate such that a target microservice is reconfigured as a result of processing the configuration transaction object, whether to look for transactions on a different workflow and/or workflow stage, or to modify the processing logic applied to the transactions retrieved by the microservice.

(78) As discussed above, each defined workflow on transaction exchange platform **320** may accept a transaction as part of the transaction's “saga” through the transaction exchange platform. Through the workflow, the transaction may or may not undergo different processing steps, where each step may be provided by one or many microservices or vendor systems. In this way, updating the “saga”

that applies to the microservices, integrated vendor systems and datasets, and the entire transaction exchange ecosystem may be akin to an exercise in configuration control. Aspects described herein may allow configurations to be loaded into the transaction exchange platform via the streaming data platform, and may be used to update the entire transaction exchange platform, one or more components of the transaction exchange platform, and/or transactions on the platform.

(79) Traditional methods for doing this may require that each element of the workflow be updated, creating exponentially expanding complexity, downtime, and consequently interjecting risk to the transaction exchange ecosystem. Dynamic reconfiguration as described further herein may solve a problem of traditional deployments that interrupt the entire system and require each component to be individually validated. It may also interject a level of control in the deployment by enabling any level of control from the level of remapping the system up to controlling which component gets transactions associated with different versions of the corresponding workflow. Dynamic reconfiguration may also provide control over the system so that configuration can work from the most tactical single transaction (singleton) level up to the entire transaction exchange. Coupled with other tools, such as cloud-based resiliency tools, dynamic reconfiguration may provide a level of flexibility not present in other deployment approaches or solutions to simplifying and/or mitigating the risk of a failed deployment.

(80) The transaction exchange may exist in a space that includes numerous legacy, vendor, and future state solutions. Dynamic reconfiguration may provide advantages in supporting partnering with vendors and third parties of any kind as an integration approach can be agreed on and brought into the transaction exchange as a service controlled through dynamic reconfiguration. Once integrated, similarly to the version control described herein, the integration service can be toggled on and off easily through dynamic reconfiguration processes.

(81) FIG. 6 illustrates a transaction processing system **600**, similar to that illustrated in FIG. 3A and sharing many like components. However, transaction processing system **600** includes configuration interface **660** to provide dynamic reconfiguration of the workflows and/or microservices. Configuration interface **660** may push configuration transaction objects to SDP **325** to cause re-configuration of a first microservice **631a** (represented as first version **631a**, which may be updated to second version **631b**). Due to dynamic reconfiguration, transaction objects may be modified to keep track of the workflow version they should be processed under, as shown by example transaction object **607**.

(82) Users managing transaction exchange platform **320** may determine to dynamically reconfigure one or more aspects of the platform, such as by modifying a workflow or causing a new version of a microservice to be deployed. Reconfiguration may be done to update and/or improve software processes. Reconfiguration may also be done to address problems that arise during processing, such as when certain systems become unavailable or otherwise encounter problems. Reconfiguration may be done as a new persistent configuration, or could be temporary pending resolution of an issue. The reconfiguration may target any aspect of the platform with desired granularity. For example, the reconfiguration may apply to the entire platform, one or more microservices, and/or one or more transactions, as appropriate. Workflows on transaction exchange platform **320** may also be reconfigured, which may be accomplished through modifying individual microservices to control the workflow type and workflow stages that they watch for.

(83) Configuration interface **660** may generate configuration transaction objects that cause the dynamic reconfiguration of the workflow and/or microservices. Configuration transaction objects may be added to the SDP with a configuration workflow type, and the microservices may retrieve and process the configuration transaction objects. Each microservice on transaction exchange platform **320** may be configured to watch for transaction objects having a configuration workflow type (e.g., configuration transaction objects), and may have a corresponding workflow stage similarly to that discussed above with respect to FIGS. 3A and 4.

(84) A configuration transaction object may be configured such that, when processed by a

microservice, it causes reconfiguration of that microservice. Microservices on the transaction exchange platform **320** may be programmed to process configuration transaction objects and make suitable changes to their parameters based on the processed objects. For example, a microservice may process configuration transaction object comprising instructions to update the workflow assigned to the microservice to a second version of the workflow, e.g., ACH v. **2**, and may update a workflow stage assigned to the microservice. Reconfiguration of microservices can be used to update workflows to new versions, create new workflows, and/or modify existing workflows. Transactions requiring modified processing may be assigned to modified/updated/other workflows to change their assigned processing.

(85) Versioning may be used to control processing by appropriate workflows, and may facilitate reliable and accurate record keeping and playback. By tracking which version of a workflow handles a transaction, the transaction can be replayed using the same version at a later time as part of an audit. To this end, microservices may maintain separate indications of each workflow and version handled by the microservice. Transactions may maintain transaction metadata indicating a version value for the workflow applied to the transaction. Transactions may be assigned a current workflow value when added to the transaction exchange platform, and this may be maintained through the life of the transaction. In some circumstances, the version may be changed later and the transaction re-run through the new version of the workflow.

(86) Examples of some types of changes that may be implemented through dynamic reconfiguration will be discussed with references to FIGS. **7A-7C**.

(87) FIG. **7A** illustrates pushing a new configuration to one or more of the microservices associated with example workflow **710**, which may correspond to example wire transaction workflow **400**. This new configuration may modify the processing logic applied by one or more of the microservices corresponding to the steps of workflow **400/710**. Configuration interface **660** may generate a configuration transaction object comprising the new configuration and push it to the SDP stream. The configuration transaction object may cause update of the microservices mid-stream as part of the flow within the transaction exchange platform on the SDP. Each microservice, as with transaction objects, may be configured to watch for configuration transaction objects associated with a configuration workflow and corresponding workflow stage. The microservices may retrieve matching configuration transaction objects and process them to effect an update to their respective processing logic. A microservice, transaction object, and/or the configuration microservice may maintain a new and prior version of their configurations. This may allow for processing under an appropriate version, and may facilitate a transition between versions as further discussed herein.

(88) The mid-stream nature of the dynamic reconfiguration may help avoid significant interruptions and replayability problems posed by prior solutions. As illustrated, transactions **20, 30, 31, 32, and 33** may be on the SDP and already subject to processing by microservices in the current version of the workflow. When a new configuration is pushed (such as version 6.0), the transactions pending on the SDP may continue to be processed according to the prior version that they started under (e.g., version 5.0). New transactions **34, 35, 36, and 37** may be processed under the new version (6.0). As described above, this may be effected through transaction metadata tracking the workflow version associated with the transaction as well as by configuring the microservices to utilize version metadata in retrieving transactions from the SDP. For example, returning to FIG. **6**, microservice **631a** may represent a first version of a microservice that looks for transactions in a given workflow type that have a first version value at a corresponding first workflow stage. Microservice **631b** may represent a second version of the microservice, and may look for transactions in the same workflow type but having a second version value at the same corresponding first workflow stage. In some implementations, the version value may be combined with the workflow type rather than separate (e.g., “ACHv1” and “ACHv2” as separate workflows rather than version values).

(89) This procedure, pushing configuration transaction objects via the SDP, may provide additional advantages in that, when new components are added, the configuration interface **660** can interject that new component mid-stream so that it is enabled as a new route without updating the entire transaction exchange. This limits disruption to the local “new” component being added or changed while protecting the entire system for the change. This may be advantageous as change remains one of the single biggest drivers of break events. It also enables on-the-fly updates without taking the entire system down into maintenance.

(90) FIG. 7B illustrates a dynamic reconfiguration of a workflow process **720**, such as when a component becomes unavailable due to breakage or other adverse events. The dynamic reconfiguration may reconfigure the workflow to bypass problematic services and redirect the workflow to manual review and/or other replacement processing steps. The reconfiguration may avoid bottlenecks associated with microservices earlier in the workflow breaking and preventing transactions from advancing to later microservices. Reconfiguration of workflows may be accomplished through reconfiguring the microservices involved in the workflow to look for different current workflow stages on the SDP.

(91) For example, in reconfigured workflow process **720**, which may be a modification of example wire transaction workflow **400**, the dynamic reconfiguration may cause all wire transactions to be subject to the enhanced processing of step ‘C’ rather than the branching paths described above with respect to FIG. 4. This may be due to enhanced security concerns, problems with international wire processing, problems at other components, etc. The reconfiguration of FIG. 7B may be accomplished by configuration interface **660** pushing a configuration transaction object to the SDP that is configured to cause the microservices associated with workflow **400/720** to modify what workflows and workflow stages they look for, as well as how they update the current workflow once processing is completed. In particular, the modification shown in FIG. 7B could be effected by modifying the microservice associated with step ‘D’ to not pull any transactions, while the microservice affiliated with step ‘C’ may pull all transactions completed by step ‘B’; or step ‘B’ could be modified to update the current workflow of all processed transactions such that they progress to the enhanced verification of step ‘C’, for example.

(92) Modifications to the workflow may be done in response to determining conditions that indicate that modified workflow processing should be implemented. The modifications may also be done in response to user changes to a DAG representing the workflow. A user may modify the DAG to define a new workflow/version and the configuration interface **660** may generate a suitable configuration transaction object and push it to the SDP to effect the change. The system may provide a graphical user interface to facilitate users entering modifications to the DAG associated with the workflow processing.

(93) Reconfiguration of the workflows and/or microservices may be handled in a versioned manner, such that transactions on the SDP may be handled according to an appropriate and auditable version of the workflow. When a new configuration version is pushed to the SDP for a given workflow, it may be added with a new version value. Transaction objects on the transaction exchange platform may include, as part of their transaction metadata, an indication of a current version value for the workflow at the time they entered the transaction exchange platform. The microservices on the transaction exchange platform may be further configured to identify transaction objects having an appropriate current workflow stages based on the version value of the transaction object. Thus, transactions added under a first workflow version may reliably be processed under the first workflow version, while transaction added after a shift to a second workflow version may be processed using the new, updated workflow version (and associated microservices and processing logic).

(94) Thus, a first microservice in a first version **631a** may be originally configured to watch for transactions associated with the first workflow that have a first version value, while the first microservice in a second version **631b** may be configured to watch for transactions associated with

the first workflow that have a different second version value. Transactions added to the transaction exchange platform may be added having a first version value prior to reconfiguring the first microservice. The first version of the first microservice **631a** may retrieve transactions matching the first version value in a corresponding workflow/stage. Once a reconfiguration is pushed to the SDP, later transaction added to the SDP may be added having a second version value. The second version of the first microservice **631b** may retrieve transaction matching the second version value in a corresponding workflow/stage. This may allow for reliable and replayable processing of transactions according to the appropriate version of approval workflows.

(95) New workflow versions may be added as illustrated in FIG. 7C, through workflow **730**. One flexible use of this approach is the ability to generate a workflow designed to modify an individual transaction and/or group of transactions. Version 1 of the work flow, indicated by the single arrows, may be applied to general transaction objects of a given transaction type. Version 2 of the workflow, indicated by the double arrows, may be applied to problematic transactions subject to modified processing. The transaction exchange platform may support microservices, queuing, and manual workflows as part of being highly resilient, especially around high value workflows. As such, the dynamic configuration aspects may facilitate controlling a single transaction's path through the platform enabling it to bypass steps normally required by the common workflow. A new workflow can be introduced to the ecosystem with differentiating execution tied directly to a transaction.

(96) As an example implementation, the following sample data illustrates how a workflow may change across versions of the workflow according to one or more aspects:

(97) TABLE-US-00002 Initial Configuration Version 1 { "SecurityIdentifier": "<<identifier >>", "ConfigurationVersion": "1", "WorkflowStage": [{ "A": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["INIT"] }], "B": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["A"] }], "C": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["B"] }], "E": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["B"] }], "F": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["C", "E"] }], "G": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["F"] }]}] } Post Configuration Update Version 2 { "SecurityIdentifier": "<< identifier >>", "ConfigurationVersion": "2", "WorkflowStage": [{ "A": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["INIT"] }], "B": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["A"] }], "D": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["B"] }], "C": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["D"] }], "F": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["C"] }], "G": [{ "WorkflowType": ["WIRE", "ACH", "RTP", "CHECK", "CONFIG"], "WorkflowStageCompleted": ["F"] }]}] }

(98) Another aspect of dynamic reconfiguration may provide an event configuration library. Configurations employed to process transactions have certain characteristics may be stored for re-use in other settings, such as when those same characteristics are encountered again. Configurations that were pushed to resolve those transaction may be used again to facilitate handling of other similar transactions. For example, if manual or other review identifies a high risk transaction, a high risk transaction configuration can be pushed to apply a high risk version of the

workflow to the high risk transaction. As a particular example, consider when a transaction is associated with a merger of two companies. To facilitate the merger, transactions may be reconfigured to bypass standard workflows and feed through specialized microservices configured to meet specific reporting needs of M&A transactions.

(99) These configurations may be utilized manually, automatically, through a hybrid approach, and others. For example, machine learning may be employed to recognize problem situations with transactions. The machine learning system may flag a transaction to be reconfigured to follow a configuration of the configuration library that was previously employed on similar transactions. The system may be designed to self-optimize its own configurations, employing approaches based on features such as shortest path, fastest time, most secure, guaranteed deliver, or any other features desirable to customers.

(100) FIG. 8 depicts a flowchart illustrating an example method **800** to dynamically reconfigure a transaction exchange platform, such as transaction exchange platform **320**. Method **800** may be performed by any suitable computing device and/or combination of computing devices, referred to as the system implementing method **800**.

(101) At step **805**, the configuration interface **660** may generate a configuration transaction object. The configuration transaction object may be configured to cause a reconfiguration of the transaction exchange platform, one or more workflows, one or more microservices, and/or one or more transactions. The configuration interface **660** may receive a request to generate the configuration transaction object from a user and/or other system processes. The configuration transaction object may comprise transaction details and transaction metadata. The transaction metadata may indicate that the transaction object has a configuration workflow type and a current workflow stage of the configuration transaction object. In some embodiments, the workflow type of the configuration transaction object is a workflow that is modified by the configuration transaction object, and other aspects of the configuration transaction object indicate to a processing microservice that it includes an update to the processing of the microservice. The configuration transaction object may include instructions that, when processed by the microservice, cause the microservice to be reconfigured. Reconfiguration may include modifying which workflow/version/stage the microservice looks for on the SDP, and/or may include modifying the core processing logic employed by the microservice.

(102) At step **810**, the configuration interface **660** may add the configuration transaction object to the SDP, where it may await processing by first microservice **820** and second microservice **830**.

(103) The configuration transaction object may be picked up by first microservice **820** and second microservice **830** in a similar fashion to that described above with respect to FIG. 5. At steps **821** and **831**, first and second microservices **820** and **830** may poll the SDP to retrieve transactions matching their assigned workflow stages in corresponding workflow types. The configuration transaction objects may have a configuration workflow type, and the microservices may watch for a configuration workflow type object having the workflow stage corresponding to the microservice. At steps **823** and **833**, the microservices may retrieve the configuration transaction object for processing.

(104) At steps **825** and **835**, the microservices may process the configuration transaction object when it is in a corresponding workflow stage. Processing the configuration transaction object may cause the microservice to be updated. For example, the configuration transaction object may cause the microservice to update what workflow/version/stage it looks for on the SDP. As another example, processing the configuration transaction object may cause the microservice to update the core processing logic that it applies to transactions.

(105) At steps **827** and **837**, the microservices may update the current workflow stage of the configuration transaction object and, at steps **829** and **839**, the microservices may push the updated configuration object back to the SDP. For example, microservice **820** may update the current workflow stage of the configuration object to indicate that microservice **820** has completed

processing, and microservice **830** may be configured to look for transaction objects that have a current workflow stage that indicates that microservice **820** completed its processing.

(106) At step **840**, the system may determine that the current workflow stage of the configuration transaction object indicates that the processing associated with the configuration workflow has completed, and the configuration transaction object may be removed from the SDP. Notification may be provided to an entity that prompted the reconfiguration that it has been implemented, in some embodiments.

(107) Thus, according to some aspects, a computer-implemented method may comprise configuring a plurality of microservices on a streaming data platform to watch for transactions having a corresponding workflow stage associated with a first workflow. The first workflow may correspond to a transaction type and may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise generating a configuration transaction object that may be configured to cause reconfiguration of the first workflow by causing reconfiguration of at least one microservice of the plurality of microservices. The configuration transaction object may comprise transaction metadata that indicates a configuration workflow and a current workflow stage of the configuration transaction object. The steps may further comprise adding the configuration transaction object to the streaming data platform and updating the current workflow stage of the configuration transaction object to a first workflow stage. The method may comprise polling, by a first microservice of the plurality of microservices, the streaming data platform to retrieve transactions matching the first workflow stage; retrieving, by the first microservice and from the streaming data platform, the configuration transaction object based on the current workflow stage matching the first workflow stage; processing, by the first microservice, the configuration transaction object to reconfigure the first microservice; and updating the current workflow stage of the configuration transaction object to a second workflow stage based on completing processing, by the first microservice, of the configuration transaction object. The method may also comprise determining that the current workflow stage of the configuration transaction object indicates that the configuration transaction object has completed processing corresponding to the configuration workflow, and removing the configuration transaction object from the streaming data platform and outputting an indication that the configuration transaction object has completed the processing corresponding to the configuration workflow.

(108) Reconfiguring the first microservice may comprise reconfiguring the first microservice to watch for a different second workflow stage. Reconfiguring the first microservice may cause the first microservice to process transaction objects at a different stage of the plurality of processing steps of the first workflow. Reconfiguring the first microservice may comprise reconfiguring the first microservice to modify at least one operation that the first microservice performs on transaction objects associated with the first workflow. Reconfiguring the first microservice may cause removal of at least one second microservice from the first workflow. The first microservice may be originally configured to update completed transactions with a first completed workflow stage. Reconfiguring the first microservice may comprise reconfiguring the first microservice to update completed transactions with a different completed workflow stage. Reconfiguring the first microservice may cause transaction objects to bypass at least one second microservice included in the first workflow. The first microservice may be originally configured to watch for transactions associated with the first workflow that have a first version value. The reconfigured first microservice may be configured to watch for transactions associated with the first workflow that have a different second version value.

(109) The method may further comprise adding a first transaction object having a first version value to the streaming data platform prior to reconfiguring the first microservice; retrieving, by the first microservice and from the streaming data platform, the first transaction object based on a current workflow stage of the first transaction matching the first workflow stage; processing, by the first microservice, the first transaction object based on an original configuration of the first

microservice based on the first version value; adding a second transaction object having a different second version value to the streaming data platform subsequent to reconfiguring the first microservice; retrieving, by the first microservice and from the streaming data platform, the second transaction object based on a current workflow stage of the second transaction matching the first workflow stage; and processing, by the first microservice, the second transaction object based on the reconfiguration of the first microservice based on the second version value. The steps may further comprise adding a first transaction object to the streaming data platform; determining a current version of the first workflow implemented on the streaming data platform; and updating a version value of the first transaction object based on the current version. The first microservice may process the first transaction object based on an original configuration or a modified configuration based on the version value.

(110) The workflow corresponding to the transaction type may comprise a directed acyclic graph (DAG) indicating the plurality of processing steps required to approve a given transaction of the transaction type. The first microservice may be automatically configured to watch for transactions on the streaming data platform in the first workflow stage based on the DAG. Generating the configuration transaction object may be in response to an update to at least one of the plurality of processing steps indicated in the DAG. The steps may further comprise providing a graphical user interface to allow a user to update the at least one of the plurality of processing steps indicated in the DAG.

(111) According to some aspects, a transaction exchange platform may comprise a streaming data platform, a plurality of microservices, at least one processor, and memory. Each microservice of the plurality of microservices may be automatically configured to watch for transactions on the streaming data platform in a corresponding workflow stage based on a plurality of workflows corresponding to a plurality of transaction types. The memory may store instructions that, when executed by the at least one processor, cause the platform to perform steps including configuring the plurality of microservices on the streaming data platform to watch for transactions having a corresponding workflow stage associated with a first workflow. The first workflow may correspond to a transaction type and comprises a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise processing, by a first microservice, transaction objects on the streaming data platform based on the configuration; and generating a configuration transaction object that may be configured to cause reconfiguration of the first workflow by causing reconfiguration of at least one of microservice of the plurality of microservices. The configuration transaction object may comprise transaction metadata that indicates a configuration workflow and a current workflow stage of the configuration transaction object. The steps may further comprise adding the configuration transaction object to the streaming data platform; updating the current workflow stage of the configuration transaction object to a first workflow stage; polling, by a first microservice of the plurality of microservices, the streaming data platform to retrieve transactions matching the first workflow stage; retrieving, by the first microservice and from the streaming data platform, the configuration transaction object based on the current workflow stage matching the first workflow stage; and processing, by the first microservice, the configuration transaction object to reconfigure the first microservice. Subsequent to processing the configuration transaction object, the first microservice may process transaction objects on the streaming data platform based on the reconfiguration.

(112) According to some aspects, one or more non-transitory computer readable media may comprise instructions that, when executed by at least one processor, cause a transaction exchange platform to perform steps. Those steps may comprise configuring a first microservice on a streaming data platform to watch for transactions having a first workflow stage associated with a first workflow corresponding to a transaction type. The first workflow may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise configuring a second microservice on the streaming data platform to watch for

transactions having a second workflow stage associated with the first workflow; and generating a configuration transaction object that may be configured to cause reconfiguration of the first workflow by causing reconfiguration of the first microservice and the second microservice. The configuration transaction object may comprise transaction metadata that indicates a configuration workflow, and a current workflow stage of the configuration transaction object. The steps may further comprise adding the configuration transaction object to the streaming data platform; updating the current workflow stage of the configuration transaction object to the first workflow stage; polling, by the first microservice, the streaming data platform to retrieve transactions matching the first workflow stage; retrieving, by the first microservice and from the streaming data platform, the configuration transaction object based on the current workflow stage matching the first workflow stage; processing, by the first microservice, the configuration transaction object to reconfigure the first microservice; updating the current workflow stage of the configuration transaction object to a second workflow stage based on completing processing, by the first microservice, of the configuration transaction object; polling, by the second microservice, the streaming data platform to retrieve transactions matching the second workflow stage; retrieving, by the second microservice and from the streaming data platform, the configuration transaction object based on the current workflow stage matching the second workflow stage; processing, by the second microservice, the configuration transaction object to reconfigure the second microservice; updating the current workflow stage of the configuration transaction object to a third workflow stage based on completing processing, by the second microservice, of the transaction object; determining that the current workflow stage of the configuration transaction object indicates that the configuration transaction object has completed processing corresponding to the configuration workflow; and removing the configuration transaction object from the streaming data platform and outputting an indication that the configuration transaction object has completed the processing corresponding to the configuration workflow.

(113) According to some aspects, a computer-implemented method may comprise steps comprising configuring a plurality of microservices on a streaming data platform to watch for transactions having a corresponding workflow stage associated with a first workflow. The first workflow may correspond to a transaction type and comprises a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise generating a configuration transaction object that may be configured to cause reconfiguration of the first workflow by causing reconfiguration of at least one microservice of the plurality of microservices. The configuration transaction object may comprise transaction metadata that indicates: a configuration workflow, and a current workflow stage of the configuration transaction object. The steps may further comprise adding the configuration transaction object to the streaming data platform; retrieving, by a first microservice and from the streaming data platform, the configuration transaction object based on the current workflow stage matching a first workflow stage associated with the first microservice; processing, by the first microservice, the configuration transaction object to reconfigure the first microservice; and updating the current workflow stage of the configuration transaction object to a second workflow stage based on completing processing, by the first microservice, of the configuration transaction object.

(114) Chronos—Snapshot Microservice and Transaction Replay

(115) Some aspects described herein may provide a snapshot microservice on the transaction exchange platform, configured to maintain a record of the data values of each transaction object as they progress through the corresponding workflows. “Snapshot,” when used to refer to the snapshot microservice, may refer to the functionality of the snapshot microservice to track a transaction object's data values and each of its changed states as an archival service. The snapshot microservice thus may also be referred to as a payment transaction object changed state archive, or Chronos. The snapshot microservice may create a snapshot record for new transaction objects and store a copy of the data of the transaction object. As the transaction object progresses through the workflow and is

processed by the other microservices, the snapshot microservice can identify transaction objects that have their data changed. The snapshot microservice can retrieve the changed objects and store snapshot data tracking the change of the transaction object.

(116) FIG. 9 illustrates a transaction processing system **900** that may be similar to transaction processing systems **300** and/or **600** of FIGS. 3A and 6. Transaction processing system **900** may add, relative to systems **300** and **600**, snapshot microservice **970**.

(117) Snapshot microservice **970** may operate on transaction exchange platform **320** to maintain a record of the data values of each transaction object on the streaming data platform, and may track how the transaction objects change during processing on the platform. Snapshot data may be stored in snapshot database **975**, which may comprise on-disk storage capable of effectively storing large volumes of data. Snapshot microservice **970** and snapshot database **975** may be configured to store differential snapshots of a transaction object. Snapshot microservice **970** may store an original state of a transaction object when it is added to the SDP, and may store information indicating each subsequent change to the transaction object. Snapshot microservice may track data values associated with each of the transaction details, transaction addenda data, and/or transaction metadata. I

(118) The snapshot microservice **970** may be configured to identify and retrieve transaction objects added to SDP **325** in an initialization stage. Transaction objects may be added to the SDP **325** in an “init” or initialization stage, indicating that none of the workflow steps have yet been completed. In some implementations, the initialization stage may be a separate stage that is marked completed prior to processing by a first microservice **331**, or may be commensurate in scope with a first workflow stage associated with a first microservice **331** of the workflow. In some implementations, the initialization stage for the object may be handled as part of the processing by the APIs **311**, **313** that receive transactions to be added to the SDP **325**, or otherwise handled alongside workflow processing by the respective microservices **331**, **332**, and **333**.

(119) Snapshot microservice **970** may store an initial snapshot of a transaction object in the initialization stage, then update a current workflow stage of the transaction object to indicate that the initialization processing has completed. This may comprise updating the current workflow stage of the transaction object to match a first workflow stage associated with microservice **331**, which microservice **331** performs the first step of the workflow. Alternatively, snapshot microservice **970** may treat transaction objects in the first workflow stage as being subject to initialization (as new objects), and may determine that an initial, new snapshot should be recorded in snapshot database **975**.

(120) Snapshot microservice **970** may be configured to poll the SDP to retrieve all transaction objects having changed data. In some embodiments, this may comprise retrieving all transaction objects and determining whether there have been any changes. In other embodiments, it may comprise retrieving specifically the transaction objects that have changed, whether based on determining that the data has changed or merely that a workflow stage has advanced. Snapshot microservice **970** may determine a difference in the changed transaction object and store snapshot information indicating the difference. The snapshot information may include metadata such as an associated timestamp, workflow stage, and/or any other suitable metadata to facilitate audit and potential rollback of the transaction object and workflow processing.

(121) These snapshots of the transaction object may be used to correct processing errors in the approval workflow, as a transaction object may have its data reverted back to an earlier state and its workflow stage reverted to an earlier stage. In this way, the transaction object may be made to repeat an earlier step of the workflow and be subject to re-processing by a corresponding microservice (or, in some cases such as repeated failures, a human operator). The snapshot microservice **970** may regenerate a transaction object using the snapshot data corresponding to the transaction object from an earlier time, prior to a point in processing that is subject to the rewind. In effect, snapshot microservice **970** may roll back the values of the transaction object to an earlier

point in time. Then, the regenerated transaction object may be put back on SDP **325** and will be picked up for re-processing by the earlier microservice. For example, if an error is determined to have occurred during processing of transaction object **307** by first microservice **331**, the snapshot microservice **970** may revert transaction object **307** to state prior to processing by first microservice **331**. The first microservice **331** would have updated the stage of the transaction object **307** to the second workflow stage when processing completed. The snapshot microservice **970** may revert the current workflow stage of the transaction object **307** to the first workflow stage, so that when the transaction object **307** is pushed back to the SDP **325** it will be picked up for processing again by the first microservice **331**.

(122) A command to replay a transaction may be received by the snapshot microservice **970**. Other conditions may prompt a replay, such as an error state of a microservice or the transaction exchange platform **320**.

(123) The snapshot microservice may track the total number of times that a transaction object is reverted/replayed on one or more microservices, and may flag a transaction as presenting problems requiring manual or other review when the number of replays exceeds a transaction or based on other criteria. Replaying a transaction may cause update of a transaction replay count associated with the transaction, which may be stored as part of the transaction object's transaction metadata and/or as part of the snapshot information. If a threshold number of replays take place, for example a configurable maximum of 3 replays at a single stage of the workflow, the snapshot microservice **970** may flag the transaction as having failed and/or requiring further review. The maximum, which may be implemented as a threshold value, may be configured by a user and/or may be automatically configured by system processes based on historical data, current system state, and other performance metrics. The transaction may be held in a workflow stage corresponding to the microservice where processing failed, in some instance. In other instances, a failed transaction may be routed to additional processing, such as by a different workflow and/or other parts of the same workflow, where it may be processed by other microservices.

(124) When a replay occurs, the snapshot information may continue to track all subsequent events as well as all events that had occurred already on the transaction, even if they are subject to rewinding. Thus, the snapshot information may support a comparison during troubleshooting to assess which parts of the system led to errors in the workflow. This information may be archived to assist in troubleshooting and audits. Snapshot information related to error processing that is fixed via replay may be deleted upon successful completion of the re-attempt.

(125) The snapshot data may also support audit of the transactions, offering a complete picture of how the transaction object changed while on the transaction exchange platform. If desired as part of auditing results, the snapshot microservice **970** may replay an entire transaction snapshot by snapshot. This may be done in support of an audit or for troubleshooting and analysis.

(126) FIG. **10** depicts a flowchart illustrating an example method **1000** to generate snapshot information tracking a transaction object on a transaction exchange platform, such as transaction exchange platform **320**. Method **1000** may be performed by any suitable computing device and/or combination of computing devices, referred to as the system implementing method **1000**.

(127) At step **1005**, the transaction exchange platform may receive a transaction object and add it to a SDP. The transaction object may be added to the SDP in an initialization stage.

(128) At step **1031**, snapshot microservice **1030** may store an initial snapshot record for new transaction objects on the SDP. For example, snapshot microservice **1030** may poll the SDP for transaction objects in the initialization stage. Alternatively and/or additionally, snapshot microservice **1030** may poll SDP for all transaction objects, and determine which are new and should be stored as initial snapshot records.

(129) At step **1033**, snapshot microservice **1030** may update the current workflow stage of the transaction object to indicate completion of initialization processing by the snapshot microservice **1030**. This may comprise updating the current workflow stage of the transaction object to be a

workflow stage associated with a workflow microservice **1020**. At step **1035**, snapshot microservice **1030** may put the transaction object back to the SDP with the updated current workflow stage.

(130) At step **1021**, workflow microservice **1020** may poll the SDP for transactions having a current workflow stage assigned to the microservice, and at step **1023** the workflow microservice may retrieve the matching transaction objects. At step **1025**, workflow microservice **1020** may process the transaction objects according to its respective processing logic, which may include updating, adding, removing, and/or otherwise changing values of the transaction details, addenda data, and/or transaction metadata associated with the transaction object. At step **1027**, workflow microservice **1020** may update the transaction object's current workflow stage to indicate completion of processing by microservice **1020** and, at step **1029**, put the updated transaction object back to the SDP.

(131) At step **1037**, snapshot microservice **1030** may poll the SDP for transactions and, at step **1039**, determine transaction having changed data. Snapshot microservice **1030**, at step **1041**, may record snapshot data corresponding to the changed data as a result of processing by workflow microservices **1020**. The snapshot microservice **1030** may, at step **1043**, put the transaction object back to the SDP for further processing by workflow microservices **1020**.

(132) FIG. **11** depicts a flowchart illustrating an example method **1100** to replay a transaction (e.g., subject it to reprocessing) using a snapshot microservice on a transaction exchange platform, such as transaction exchange platform **320**. Method **1100** may be performed by any suitable computing device and/or combination of computing devices, referred to as the system implementing method **1100**.

(133) At step **1105**, the transaction exchange platform may receive a transaction object and add it to a SDP. The transaction object may be added to the SDP in an initialization stage.

(134) The transaction object may be processed by microservice **1120** in steps **1121**, **1123**, **1125**, **1127**, and **1129** as described herein, for example in similar fashion to that described with respect to FIG. **10** in steps **1021**, **1023**, **1025**, **1027**, and **1029**.

(135) Snapshot microservice **1130** may record initial and changed snapshot information in steps **1131** and **1131**, as described in greater detail above with respect to FIG. **10** in steps **1031**, **1033**, **1035**, **1037**, **1039**, **1041**, and **1043**.

(136) At step **1135**, snapshot microservice **1130** may receive a command to replay a workflow step for a transaction object. For example, another microservice may send snapshot microservice **1130** a command to replay the transaction object in a first workflow stage.

(137) At step **1137**, snapshot microservice **1130** may use the stored snapshot information to rollback the transaction object to its state prior to the point of replay. The transaction object may be made to repeat an earlier step of the workflow and be subject to re-processing by a microservice to the workflow step indicated to be replayed. The snapshot microservice **1130** may regenerate a transaction object using the snapshot data corresponding to the transaction object from an earlier time, prior to a point in processing that is subject to the rewind.

(138) At step **1139**, snapshot microservice **1130** may put the regenerated transaction object back on the SDP. Because the regenerated transaction object has the earlier workflow stage, it will be picked up for re-processing by the earlier microservice.

(139) Thus, according to some aspects, a computer-implemented method may comprise steps comprising receiving a transaction object comprising transaction details, addenda data, and transaction metadata. The transaction metadata may comprise an indication of a workflow corresponding to a transaction type of the transaction object, and a current workflow stage of the transaction object. The workflow corresponding to the transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise adding the transaction object to a streaming data platform. Adding the transaction object to the streaming data platform may comprise setting the current workflow stage of the

transaction object to an initialization stage. The steps may further comprise polling, by a snapshot microservice, the streaming data platform to retrieve transactions matching the initialization stage. The initialization stage may be associated with the snapshot microservice. The steps may further comprise retrieving, by the snapshot microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the initialization stage; storing, by the snapshot microservice, snapshot data corresponding to the transaction object; and updating the current workflow stage of the transaction object to a next workflow stage based on completing storing, by the snapshot microservice, the snapshot data corresponding to the transaction object. The method may comprise retrieving, by a first microservice and from the streaming data platform, the transaction object based on the current workflow stage matching a first workflow stage. The first workflow stage may be associated with the first microservice based on the workflow corresponding to the transaction type. The steps may further comprise processing, by the first microservice, the transaction object to modify the addenda data. The method may comprise determining, by the snapshot microservice and via the streaming data platform, that at least one value associated with the addenda data of the transaction object has changed after the transaction object has left the initialization stage, and storing, by the snapshot microservice, snapshot data corresponding to the changed at least one value associated with the addenda data.

(140) Determining that the at least one value associated with the addenda data of the transaction object has changed may comprise retrieving, by the snapshot microservice and from the streaming data platform, the transaction object. The steps may further comprise determining that the processing, by the first microservice, of the transaction object did not complete successfully, and causing the first microservice to repeat processing of the transaction object based on the snapshot data corresponding to the transaction object from prior to the start of the processing by the first microservice. Causing the first microservice to repeat processing of the transaction object may comprise regenerating, by the snapshot microservice, the transaction object based on the snapshot data corresponding to the transaction object from prior to the start of the processing by the first microservice, and returning the regenerated transaction object to the streaming data platform. The current workflow stage of the regenerated transaction object may be set to the first workflow stage. The steps may further comprise determining a number of times that the transaction object has undergone processing by the first microservice and, in response to determining that the number of times that the transaction object has undergone processing by the first microservice exceeds a threshold value, rejecting the transaction object as having failed processing associated with the first microservice. The steps may further comprise flagging the transaction object for further review based on rejecting the transaction and holding the transaction object in the first workflow stage pending the further review. Updating the current workflow stage of the transaction object to a second workflow stage may be based on determining that the further review is completed. Flagging the transaction object for further review may comprise flagging the transaction object for manual review by a user. Flagging the transaction object for further review may comprise causing the transaction object to be processed by a third microservice. Updating the current workflow stage of the transaction object to the second workflow stage may be based on determining that processing by the third microservice is completed. The snapshot microservice may record second snapshot data corresponding to the transaction object from prior to causing the first microservice to repeat processing of the transaction object. The second snapshot data may be maintained despite the repeat processing of the transaction object.

(141) The steps may further comprise determining, by the snapshot microservice and via the streaming data platform, that at least one value associated with the transaction metadata has changed; retrieving, by the snapshot microservice and from the streaming data platform, the transaction object based on determining that the at least one value has changed; and storing, by the snapshot microservice, data corresponding to the changed at least one value associated with the transaction metadata. The next workflow stage may correspond to the first workflow stage

associated with the first microservice. The initialization stage may correspond to the first workflow stage. The snapshot microservice may generate a transaction history for the transaction object. The snapshot microservice may generate a transaction history for each transaction object added to the streaming data platform. The snapshot microservice may store snapshot data in an on-disk database.

(142) According to some aspects, a transaction exchange platform may comprise a streaming data platform, a plurality of microservices, at least one processor, and memory. Each microservice of the plurality of microservices may be configured to watch for transactions on the streaming data platform in a corresponding workflow stage based on a plurality of workflows corresponding to a plurality of transaction types. The memory may store instructions that, when executed by the at least one processor, cause the platform to perform steps including receiving a transaction object comprising transaction details, addenda data, and transaction metadata. The transaction metadata may comprise an indication of a workflow corresponding to a transaction type of the transaction object and a current workflow stage of the transaction object. The workflow corresponding to the transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise adding the transaction object to a streaming data platform. Adding the transaction object to the streaming data platform may comprise setting the current workflow stage of the transaction object to an initialization stage. The steps may further comprise polling, by a snapshot microservice, the streaming data platform to retrieve transactions matching the initialization stage. The initialization stage may be associated with the snapshot microservice. The steps may further comprise retrieving, by the snapshot microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the initialization stage; and storing, by the snapshot microservice, snapshot data corresponding to the transaction object, updating the current workflow stage of the transaction object to a next workflow stage based on completing storing, by the snapshot microservice, the snapshot data corresponding to the transaction object; and retrieving, by a first microservice and from the streaming data platform, the transaction object based on the current workflow stage matching a first workflow stage. The first workflow stage may be associated with the first microservice based on the workflow corresponding to the transaction type. The steps may further comprise processing, by the first microservice, the transaction object to modify the addenda data; determining, by the snapshot microservice and via the streaming data platform, that at least one value associated with the addenda data of the transaction object has changed after the transaction object has left the initialization stage; and storing, by the snapshot microservice, snapshot data corresponding to the changed at least one value associated with the addenda data.

(143) The steps may further comprise determining that the processing, by the first microservice, of the transaction object did not complete successfully; and causing the first microservice to repeat processing of the transaction object based on the snapshot data corresponding to the transaction object from prior to the start of the processing by the first microservice. Causing the first microservice to repeat processing of the transaction object may comprise causing the transaction exchange platform to regenerate, by the snapshot microservice, the transaction object based on the snapshot data corresponding to the transaction object from prior to the start of the processing by the first microservice; and return the regenerated transaction object to the streaming data platform. A current workflow stage of the regenerated transaction object may be set to the first workflow stage. The snapshot microservice may generate a transaction history for each transaction object added to the streaming data platform.

(144) According to some aspects, one or more non-transitory computer readable media may comprise instructions that, when executed by at least one processor, cause a transaction exchange platform to perform steps. Those steps may comprise receiving a transaction object comprising transaction details, addenda data, and transaction metadata. The transaction metadata may comprise an indication of a workflow corresponding to a transaction type of the transaction object, and a

current workflow stage of the transaction object. The workflow corresponding to the transaction type may comprise a plurality of processing steps required to approve a given transaction of the transaction type. The steps may further comprise adding the transaction object to a streaming data platform. Adding the transaction object to the streaming data platform may comprise setting the current workflow stage of the transaction object to an initialization stage. The steps may further comprise polling, by a snapshot microservice, the streaming data platform to retrieve transactions matching the initialization stage. The initialization stage may be associated with the snapshot microservice. The steps may further comprise retrieving, by the snapshot microservice and from the streaming data platform, the transaction object based on the current workflow stage matching the initialization stage; and storing, by the snapshot microservice, snapshot data corresponding to the transaction object, updating the current workflow stage of the transaction object to a next workflow stage based on completing storing, by the snapshot microservice, the snapshot data corresponding to the transaction object; and retrieving, by a first microservice and from the streaming data platform, the transaction object based on the current workflow stage matching a first workflow stage. The first workflow stage may be associated with the first microservice based on the workflow corresponding to the transaction type. The steps may further comprise processing, by the first microservice, the transaction object to modify the addenda data; determining, by the snapshot microservice and via the streaming data platform, that at least one value associated with the addenda data of the transaction object has changed after the transaction object has left the initialization stage; storing, by the snapshot microservice, snapshot data corresponding to the changed at least one value associated with the addenda data; determining that the processing, by the first microservice, of the transaction object did not complete successfully; and causing the first microservice to repeat processing of the transaction object based on the snapshot data corresponding to the transaction object from prior to the start of the processing by the first microservice. Causing the first microservice to repeat processing of the transaction object may comprise regenerating, by the snapshot microservice, the transaction object based on the snapshot data corresponding to the transaction object from prior to the start of the processing by the first microservice; and returning the regenerated transaction object to the streaming data platform. A current workflow stage of the regenerated transaction object may be set to the first workflow stage.

(145) Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

Claims

1. A computer-implemented method comprising: configuring a streaming data platform and a plurality of microservices to validate transactions of a plurality of transaction types, wherein each transaction type is associated with a respective workflow, of a plurality of workflows, that comprises a plurality of processing steps required to validate a transaction of the corresponding transaction type; retrieving, by a first microservice and from the streaming data platform, a plurality of transaction objects, wherein each transaction object comprises: transaction details; an indication of a workflow corresponding to a transaction type of the transaction object; and a current workflow stage of the transaction object; determining, by the first microservice, whether the current workflow stage of a first transaction object, of the plurality of transaction objects, matches a first workflow stage associated with the first microservice, wherein the first workflow stage is associated with the first microservice in a first workflow corresponding to a first transaction type of the first transaction object; processing, by the first microservice, the first transaction object based on a determination that the current workflow stage matches the first workflow stage associated with the first microservice; adding, by the first microservice, the first transaction object to the streaming

data platform after the first transaction object is processed by the first microservice, wherein the current workflow stage of the first transaction object is updated to a second workflow stage based on the first microservice completing processing of the first transaction object; determining that the current workflow stage of the first transaction object indicates that the first transaction object has completed the plurality of processing steps of the first workflow corresponding to the first transaction type of the first transaction object; and removing the first transaction object from the streaming data platform and outputting the first transaction object and an indication that the first transaction object has completed the plurality of processing steps required to validate a transaction of the first transaction type corresponding to the first transaction object.

2. The method of claim 1, wherein the first microservice is automatically configured to watch for transactions on the streaming data platform in the first workflow stage based on the plurality of processing steps in the first workflow.

3. The method of claim 1, wherein: a different second workflow is associated with a second transaction type and comprises a different second plurality of processing steps required to validate a given transaction of the second transaction type, wherein the second transaction type is different from the first transaction type, the first microservice operates on transactions associated with both the first workflow and the different second workflow, and the plurality of processing steps of the first workflow indicates that the first microservice processes the transaction object at a different stage than the different second plurality of processing steps of the different second workflow.

4. The method of claim 1, wherein each workflow comprises a directed acyclic graph (DAG) indicating the plurality of processing steps required to validate a given transaction of the transaction type associated with the respective workflow.

5. The method of claim 4, wherein the first microservice is automatically configured to watch for transactions on the streaming data platform in the first workflow stage based on the DAG corresponding to the first workflow.

6. The method of claim 5, further comprising: responsive to an update to at least one of the plurality of processing steps indicated in the DAG corresponding to the first workflow, automatically reconfiguring at least one microservice based on the update.

7. The method of claim 1, wherein the current workflow stage of the transaction object comprises a data structure indicating completion status of each respective step of a plurality of processing steps associated with the first workflow.

8. The method of claim 7, wherein the transaction object is updated to have a current workflow stage corresponding to a third workflow stage based on the current workflow stage indicating that the transaction object has been processed by at least the first microservice and a different second microservice.

9. The method of claim 7, wherein the first workflow stage and a fourth workflow stage are independent, such that a second microservice receives the transaction object based on the current workflow stage of the transaction object matching the fourth workflow stage irrespective of whether the first microservice has processed the transaction object.

10. The method of claim 1, wherein the transaction details are immutable and do not change while the transaction object is on the streaming data platform.

11. The method of claim 1, wherein processing, by the first microservice, the transaction object comprises at least one of: adding data to addenda data associated with the transaction object; removing data from the addenda data; or updating data of the addenda data.

12. The method of claim 1, wherein processing, by the first microservice, the transaction object comprises: verifying a value of the transaction details against at least one rule associated with at least one processing step of the first workflow; or verifying a value of the transaction details against a watchlist of target values or characteristics associated with at least one processing step of the first workflow.

13. The method of claim 1, wherein the plurality of transaction types comprises: a wire transaction

type, wherein the workflow corresponding to a wire transaction type comprises a plurality of processing steps required to approve a wire transaction; an automated clearing house (ACH) transaction type, wherein the workflow corresponding to an ACH transaction type comprises a plurality of processing steps required to approve an ACH transaction; and a cashier check transaction type, wherein the workflow corresponding to the cashier check transaction type comprises a plurality of processing steps required to approve a cashier check transaction.

14. A transaction exchange platform comprising: a streaming data platform; a plurality of microservices comprising at least a first microservice, wherein the streaming data platform and the plurality of microservices are automatically configured to validate transactions of a plurality of transaction types, wherein each transaction type is associated with a respective workflow, of a plurality of workflows, that comprises a plurality of processing steps required to validate a transaction of the corresponding transaction type; at least one processor; and memory storing instructions that, when executed by the at least one processor, cause the transaction exchange platform to: retrieve, by the first microservice and from the streaming data platform, a plurality of transaction objects, wherein each transaction object comprises: transaction details; an indication of a workflow corresponding to a transaction type of the transaction object; and a current workflow stage of the transaction object; determine, by the first microservice, whether the current workflow stage of a first transaction object, of the plurality of transaction objects, matches a first workflow stage associated with the first microservice, wherein the first workflow stage is associated with the first microservice in first workflow corresponding to a first transaction type of the first transaction object; process, by the first microservice, the first transaction object based on a determination that the current workflow stage matches the first workflow stage associated with the first microservice; add, by the first microservice, the first transaction object to the streaming data platform after the first transaction object is processed by the first microservice, wherein the current workflow stage of the first transaction object is updated to a second workflow stage based on the first microservice completing processing of the first transaction object; determine that the current workflow stage of the first transaction object indicates that the first transaction object has completed processing corresponding to the first workflow, wherein the current workflow stage of the first transaction object is updated to a second workflow stage based on the first microservice completing processing of the first transaction object; and remove the first transaction object from the streaming data platform and output the first transaction object and an indication that the first transaction object has completed the plurality of processing steps required to validate a transaction of the first transaction type corresponding to the first transaction object.

15. The transaction exchange platform of claim 14, wherein: a different second workflow is associated with a second transaction type and comprises a different second plurality of processing steps required to validate a given transaction of the second transaction type, wherein the second transaction type is different from the first transaction type, the first microservice operates on transactions associated with both the first workflow and the different second workflow, and the plurality of processing steps of the first workflow indicates that the first microservice processes the transaction object at a different stage than the different second plurality of processing steps of the different second workflow.

16. The transaction exchange platform of claim 14, wherein: the first workflow corresponding to the first transaction type comprises a directed acyclic graph (DAG) indicating the plurality of processing steps required to validate a given transaction of the first transaction type; the first microservice is automatically configured to watch for transactions on the streaming data platform in the first workflow stage based on the DAG; and wherein the instructions further cause the transaction exchange platform to: responsive to an update to at least one of the plurality of processing steps indicated in the DAG, automatically reconfigure at least one microservice based on the update.

17. The transaction exchange platform of claim 14, wherein the plurality of transaction types

comprises: a wire transaction type, wherein the workflow corresponding to a wire transaction type comprises a plurality of processing steps required to approve a wire transaction; an automated clearing house (ACH) transaction type, wherein the workflow corresponding to an ACH transaction type comprises a plurality of processing steps required to approve an ACH transaction; and a cashier check transaction type, wherein the workflow corresponding to the cashier check transaction type comprises a plurality of processing steps required to approve a cashier check transaction.

18. One or more non-transitory computer readable media comprising instructions that, when executed by at least one processor, cause a transaction exchange platform to perform steps comprising: configuring a streaming data platform and a plurality of microservices to validate transactions of a plurality of transaction types, wherein each transaction type is associated with a respective workflow, of a plurality of workflows, that comprises a plurality of processing steps required to validate a transaction of the corresponding transaction type; retrieving, by a first microservice and from the streaming data platform, a plurality of transaction objects, wherein each transaction object comprises: transaction details; an indication of a workflow corresponding to a transaction type of the transaction object; and a current workflow stage of the transaction object; determining, by the first microservice, whether the current workflow stage of a first transaction object, of the plurality of transaction objects, matches a first workflow stage associated with the first microservice, wherein the first workflow stage is associated with the first microservice in a first workflow corresponding to a first transaction type of the first transaction object; processing, by the first microservice, the first transaction object based on a determination that the current workflow stage matches the first workflow stage associated with the first microservice; adding, by the first microservice, the first transaction object to the streaming data platform after the first transaction object is processed by the first microservice, wherein the current workflow stage of the first transaction object is updated to a second workflow stage based on the first microservice completing processing of the first transaction object; determining that the current workflow stage of the first transaction object indicates that the first transaction object has completed the plurality of processing steps of the first workflow corresponding to the first transaction type of the first transaction object; and removing the first transaction object from the streaming data platform and outputting the first transaction object and an indication that the first transaction object has completed the plurality of processing steps required to validate a transaction of the first transaction type corresponding to the first transaction object.

19. The computer readable media of claim 18, wherein: a different second workflow is associated with a second transaction type and comprises a different second plurality of processing steps required to validate a given transaction of the second transaction type, wherein the second transaction type is different from the first transaction type, the first microservice operates on transactions associated with both the first workflow and the different second workflow, and the plurality of processing steps of the first workflow indicates that the first microservice processes the transaction object at a different stage than the different second plurality of processing steps of the different second workflow.

20. The computer readable media of claim 18, wherein: each workflow comprises a directed acyclic graph (DAG) indicating the plurality of processing steps required to validate a given transaction of the transaction type associated with the respective workflow, the first microservice is automatically configured to watch for transactions on the streaming data platform in the first workflow stage based on the DAG corresponding to the first workflow, and the instructions cause the transaction exchange platform to perform further steps comprising: responsive to an update to at least one of the plurality of processing steps indicated in the DAG corresponding to the first workflow, automatically reconfiguring at least one microservice based on the update.
