

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication	20250264690
Kind Code	A1
Publication Date	August 21, 2025
Inventor(s)	JUNG; Phil Ho

---

### OPTICAL IMAGING SYSTEM

---

#### Abstract

An optical imaging system includes lenses sequentially disposed from an object side toward an imaging plane and including a refractive power in paraxial regions or edges of the paraxial regions. An object-side surface of a fifth lens of the lenses is planar in a paraxial region and the fifth lens includes a refractive power at an edge of the paraxial region.

---

---

<b>Inventors:</b>	<b>JUNG; Phil Ho (Suwon-si, KR)</b>
<b>Applicant:</b>	<b>Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)</b>
<b>Family ID:</b>	<b>1000008589445</b>
<b>Assignee:</b>	<b>Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)</b>
<b>Appl. No.:</b>	<b>19/185862</b>
<b>Filed:</b>	<b>April 22, 2025</b>

#### Foreign Application Priority Data

KR	10-2015-0164972	Nov. 24, 2015
----	-----------------	---------------

#### Related U.S. Application Data

parent US continuation 18463692 20230908 parent-grant-document US 12313908 child US 19185862  
parent US continuation 17541700 20211203 parent-grant-document US 11789235 child US 18463692  
parent US continuation 16695885 20191126 parent-grant-document US 11231562 child US 17541700  
parent US continuation 15950775 20180411 parent-grant-document US 10527823 child US 16695885

## Publication Classification

**Int. Cl.:** G02B9/62 (20060101); G02B9/60 (20060101); G02B13/00 (20060101)

**U.S. Cl.:**

**CPC** G02B9/62 (20130101); G02B9/60 (20130101); G02B13/0045 (20130101);

---

## Background/Summary

**CROSS-REFERENCE TO RELATED APPLICATIONS** [0001] This application is a continuation of U.S. patent application Ser. No. 18/463,692 filed on Sep. 8, 2023, which is a continuation of U.S. patent application Ser. No. 17/541,700 filed on Dec. 3, 2021, now U.S. Pat. No. 11,789,235 issued on Oct. 17, 2023, which is a continuation of U.S. patent application Ser. No. 16/695,885 filed on Nov. 26, 2019, now U.S. Pat. No. 11,231,562 issued on Jan. 25, 2022, which is a continuation of U.S. patent application Ser. No. 15/950,775 filed on Apr. 11, 2018, now U.S. Pat. No. 10,527,823 issued on Jan. 7, 2020, which is a continuation of U.S. patent application Ser. No. 15/138,780 filed on Apr. 26, 2016, now U.S. Pat. No. 9,971,125 issued on May 15, 2018, which claims the benefit under 35 USC § 119 (a) of Korean Patent Application No. 10-2015-0164972 filed on Nov. 24, 2015, in the Korean Intellectual Property Office, the entire disclosures of which are incorporated herein by reference for all purposes.

### BACKGROUND

#### 1. Field

[0002] The following description relates to an optical imaging system including lenses.

#### 2. Description of Related Art

[0003] Normally, a small camera module is mounted in a portable terminal, such as a mobile device or a tablet. The small camera module includes four or five lenses to realize an optical imaging system having a high level of resolution. However, as a result of a gradual increase in a number of pixels of an image sensor capturing images of a subject in the camera module, an optical imaging system that is able to capture the image of the subject much brighter than an existing optical imaging system is in demand.

[0004] Therefore, there is a need to develop an optical imaging system capable of being mounted in the small camera and having an F number of 2.0 or less.

### SUMMARY

[0005] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

[0006] In accordance with an embodiment, there is provided an optical imaging system, including: lenses sequentially disposed from an object side toward an imaging plane and including a refractive power in paraxial regions or edges of the paraxial regions, wherein an object-side surface of a fifth lens of the lenses is planar in a paraxial region and the fifth lens may include a refractive power at an edge of the paraxial region.

[0007] A first lens of the lenses may include a positive refractive power.

[0008] A second lens of the lenses may include a positive refractive power.

[0009] A third lens of the lenses may include a negative positive power.

[0010] A fourth lens of the lenses may include a positive refractive power.

[0011] A sixth lens of the lenses may include a negative refractive power.

[0012] A sixth lens of the lenses may include an aspherical shape in which one or more inflection points are formed on an image-side surface thereof.

[0013] The optical imaging system may also include a stop disposed between a second lens and a third lens of the lenses.  $0.05 < Th5/f < 0.25$  may be satisfied, in which Th5 is a thickness of an optical axis center of the fifth lens, and f is an overall focal length of the optical imaging system.

[0014]  $20 < V1 - V3 < 70$  may be satisfied, in which V1 is an Abbe number of a first lens of the lenses, and V3 is an Abbe number of a third lens of the lenses.

[0015]  $|Sag51/Th5| < 1.0$  may be satisfied, in which Sag51 is a Sag value at an end of an effective diameter of an object-side surface of the fifth lens, and Th5 is a thickness of an optical axis center of the fifth lens.

[0016]  $-1.5 < f3/f2$  may be satisfied, in which f2 is a focal length of a second lens of the lenses, and f3 is a focal length of a third lens of the lenses.

[0017]  $0.5 < OAL/f < 2.0$  may be satisfied, in which OAL is a distance from an object-side surface of a first lens of the lenses toward the imaging plane, and f is an overall focal length of the optical imaging system.

[0018]  $1.6 < n5 < 2.1$  may be satisfied, in which n5 is a refractive index of the fifth lens.

[0019] F number  $< 2.0$  may be satisfied.

[0020] In accordance with an embodiment, there is provided an optical imaging system, including: a first lens including a convex object-side surface; a second lens including a convex object-side surface and a convex image-side surface; a third lens including a convex object-side surface; a fourth lens including a convex object-side surface; a fifth lens including a planar surface on a paraxial region thereof; and a sixth lens including a convex object-side surface, wherein the first to sixth lenses are spaced apart and sequentially disposed from an object side toward an imaging plane.

[0021] In accordance with an embodiment, there is provided an optical imaging system, including: a first lens; a second lens; a third lens including a convex object-side surface; a fourth lens including, in a paraxial region, a convex object-side surface; a fifth lens including, in the paraxial region, at least one of a planar object-side surface and a planar image-side surface; and a sixth lens, wherein the third lens, the fourth lens, and the fifth lens may include a same refractive index.

[0022] The first lens, the second lens, and the sixth lens may include a same refractive index, different from the refractive index of the third lens, the fourth lens, and the fifth lens.

[0023] The first lens may include a convex object-side surface, the second lens may include a convex object-side surface and a convex image-side surface, and the sixth lens may include, in the paraxial region, a convex object-side surface and a concave image-side surface.

[0024] The object-side surface of the fourth lens gradually concaves at edge portions thereof.

[0025] The image-side surface of the fourth lens is convex in the paraxial region.

[0026] The image-side surface of the fourth lens is concave in the paraxial region.

[0027] Inflection points may be formed on the object-side surface and the image-side surface of the sixth lens.

[0028] The fifth lens excludes a refractive power in a paraxial region thereof.

[0029] In accordance with an embodiment, there is provided an optical imaging system, including: a first lens including a positive refractive power; a second lens including a positive refractive power; a third lens including a negative refractive power; a fourth lens including a positive refractive power; and a fifth lens of the lenses including, in a paraxial region, at least one planar side surface excluding a refractive power, and a sixth lens including a negative refractive power, wherein the first through sixth lenses satisfy F number  $< 2.0$ .

[0030]  $0.05 < Th5/f < 0.25$  may be satisfied, in which Th5 is a thickness of an optical axis center of

the fifth lens, and  $f$  is an overall focal length of the optical imaging system.  $20 < V1 - V3 < 70$  may be satisfied, in which  $V1$  is an Abbe number of the first lens, and  $V3$  is an Abbe number of the third lens.

[0031]  $|Sag51/Th5| < 1.0$  may be satisfied, in which  $Th5$  is a thickness of an optical axis center of the fifth lens, and  $Sag51$  is a Sag value at an end of an effective diameter of an object-side surface of the fifth lens.

[0032]  $-1.5 < f3/f2$  may be satisfied, in which  $f2$  is a focal length of the second lens, and  $f3$  is a focal length of the third lens.

[0033]  $0.5 < OAL/f < 2.0$  may be satisfied, in which  $OAL$  is a distance from the object-side surface of the first lens toward the imaging plane, and  $f$  is an overall focal length of the optical imaging system.

[0034]  $1.6 < n5 < 2.1$  may be satisfied, in which  $n5$  is a refractive index of the fifth lens.

[0035] Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

[0036] These and/or other aspects will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings in which:

[0037] FIG. 1 is a view of an optical imaging system, according to a first embodiment;

[0038] FIG. 2 is graphs representing aberration curves of the optical imaging system illustrated in FIG. 1;

[0039] FIG. 3 is a table representing characteristics of lenses of the optical imaging system illustrated in FIG. 1;

[0040] FIG. 4 is a view of an optical imaging system, according to a second embodiment;

[0041] FIG. 5 is graphs representing aberration curves of the optical imaging system illustrated in FIG. 4;

[0042] FIG. 6 is a table representing characteristics of lenses of the optical imaging system illustrated in FIG. 4;

[0043] FIG. 7 is a view of an optical imaging system, according to a third embodiment;

[0044] FIG. 8 is graphs representing aberration curves of the optical imaging system illustrated in FIG. 7; and

[0045] FIG. 9 is a table representing characteristics of lenses of the optical imaging system illustrated in FIG. 7.

[0046] Throughout the drawings and the detailed description, unless otherwise described, the same drawing reference numerals will be understood to refer to the same elements, features, and structures. The relative size and depiction of these elements may be exaggerated for clarity, illustration, and convenience.

### DETAILED DESCRIPTION

[0047] The following detailed description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. However, various changes, modifications, and equivalents of the methods, apparatuses, and/or methods described herein will be apparent to one of ordinary skill in the art. For example, the sequences of operations described herein are merely examples, and are not limited to those set forth herein, but may be changed as will be apparent to one of ordinary skill in the art, with the exception of operations necessarily occurring in a certain order. Also, descriptions of functions and constructions that are well known to one of ordinary skill in the art may be omitted for increased

clarity and conciseness.

[0048] Throughout the drawings and the detailed description, the same reference numerals refer to the same elements. The drawings may not be to scale, and the relative size, proportions, and depiction of elements in the drawings may be exaggerated for clarity, illustration, and convenience.

[0049] The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided so that this disclosure will be thorough and complete, and will convey the full scope of the disclosure to one of ordinary skill in the art.

[0050] Throughout the specification, it will be understood that when an element, such as a layer, region or wafer (substrate), is referred to as being “on,” “connected to,” or “coupled to” another element, it can be directly “on,” “connected to,” or “coupled to” the other element or other elements intervening therebetween may be present. In contrast, when an element is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element, there may be no elements or layers intervening therebetween. Like numerals refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0051] It will be apparent that though the terms first, second, third, etc. may be used herein to describe various members, components, regions, layers and/or sections, these members, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one member, component, region, layer or section from another region, layer or section. Thus, a first member, component, region, layer or section discussed below could be termed a second member, component, region, layer or section without departing from the teachings of the embodiments.

[0052] Spatially relative terms, such as “above,” “upper,” “below,” and “lower”, may be used herein for ease of description to describe one element's relationship to another element(s) as shown in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “above,” or “upper” other elements would then be oriented “below,” or “lower” the other elements or features. Thus, the term “above” can encompass both the above and below orientations depending on a particular direction of the figures. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may be interpreted accordingly.

[0053] The terminology used herein is for describing various embodiments only and is not intended to be limiting of the present inventive concept. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” and/or “comprising” when used in this specification, specify the presence of stated features, integers, steps, operations, members, elements, and/or groups thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, members, elements, and/or groups thereof.

[0054] Hereinafter, various embodiments will be described with reference to schematic views. In the drawings, for example, due to manufacturing techniques and/or tolerances, modifications of the shape shown may be estimated. Thus, embodiments should not be construed as being limited to the particular shapes of regions shown herein, for example, to include a change in shape results in manufacturing. The following embodiments may also be formed by one or a combination thereof.

[0055] In addition, in accordance with an embodiment, a first lens refers to a lens closest to an object or a subject from which an image is captured. A sixth lens is a lens closest to an imaging plane or an image sensor. In addition, all of radii of curvature and thicknesses of lenses, an OAL, an Img HT ( $\frac{1}{2}$  of a diagonal length of the imaging plane), and focal lengths are indicated in millimeters (mm).

[0056] A person skilled in the relevant art will appreciate that other units of measurement may be

used. Further, in the present specification, all radii of curvature, thicknesses, OALs (optical axis distances from the first surface of the first lens to the image sensor (OALs), a distance on the optical axis between the stop and the image sensor (SLs), image heights (IMGHs) (image heights), and back focus lengths (BFLs) (back focus lengths) of the lenses, an overall focal length of an optical system, and a focal length of each lens are indicated in millimeters (mm). Further, thicknesses of lenses, gaps between the lenses, OALs, and SLs are distances measured based on an optical axis of the lenses.

[0057] Further, concerning shapes of the lenses, such shapes are represented in relation to optical axes of the lenses. A surface of a lens being convex means that an optical axis portion of a corresponding surface is convex, and a surface of a lens being concave means that an optical axis portion of a corresponding surface is concave. Therefore, in a configuration in which one surface of a lens is described as being convex, an edge portion of the lens may be concave. Likewise, in a configuration in which one surface of a lens is described as being concave, an edge portion of the lens may be convex. In other words, a paraxial region of a lens may be convex, while the remaining portion of the lens outside the paraxial region is either convex, concave, or flat. Further, a paraxial region of a lens may be concave, while the remaining portion of the lens outside the paraxial region is either convex, concave, or flat.

[0058] In addition, in an embodiment, thicknesses and radii of curvatures of lenses are measured in relation to optical axes of the corresponding lenses.

[0059] An optical system, according to an embodiment, includes six lenses. As an example, the optical system may include a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens. The lens module may include from four lenses up to six lenses without departing from the scope of the embodiments herein described. In accordance with an illustrative example, the embodiments described of the optical system include six lenses with a refractive power. However, a person of ordinary skill in the relevant art will appreciate that the number of lenses in the optical system may vary, for example, between two to six lenses, while achieving the various results and benefits described hereinbelow. Also, although each lens is described with a particular refractive power, a different refractive power for at least one of the lenses may be used to achieve the intended result.

[0060] The first lens has a refractive power. For example, the first lens has a positive refractive power.

[0061] One surface of the first lens is convex. For example, an object-side surface of the first lens is convex.

[0062] The first lens has an aspherical surface. For example, both surfaces of the first lens are aspherical. The first lens may be formed of a material having high light transmissivity and excellent workability. For example, the first lens is formed of plastic or a polyurethane material. However, a material of the first lens is not limited to plastic. For example, the first lens may be formed of glass.

[0063] The second lens has a refractive power. For example, the second lens has a positive refractive power.

[0064] At least one surface of the second lens is convex. For example, both surfaces of the second lens are convex.

[0065] The second lens has an aspherical surface. For example, an object-side surface of the second lens is aspherical. The second lens is formed of a material having high light transmissivity and excellent workability. For example, the second lens may be formed of plastic or a polyurethane material. However, a material of the second lens is not limited to plastic. For example, the second lens may be formed of glass.

[0066] The third lens has a refractive power. For example, the third lens has a negative refractive power.

[0067] One surface of the third lens is convex. For example, an object-side surface of the third lens is convex. In an alternative embodiment, the first surface or the object-side surface of the third lens

is flat or substantially flat and the second surface or the image-side surface is concave.

[0068] The third lens has an aspherical surface. For example, both surfaces of the third lens are aspherical. The third lens is formed of a material having high light transmissivity and excellent workability. For example, the third lens may be formed of plastic or a polyurethane material. However, a material of the third lens is not limited to plastic. For example, the third lens may be formed of glass.

[0069] The fourth lens has a refractive power. For example, the fourth lens has a positive refractive power.

[0070] One surface of the fourth lens is convex. For example, an object-side surface of the fourth lens is convex. In one example, the object-side surface of the fourth lens is convex in a paraxial region and gradually concaves at edge portions thereof. In another example, the image-side surface of the fourth lens is convex in a paraxial region. In another example, the image-side surface of the fourth lens is concave in a paraxial region.

[0071] The fourth lens has an aspherical surface. For example, both surfaces of the fourth lens are aspherical. The fourth lens is formed of a material having high light transmissivity and excellent workability. For example, the fourth lens is formed of plastic or a polyurethane material. However, a material of the fourth lens is not limited to plastic. For example, the fourth lens may be formed of glass.

[0072] The fifth lens has refractive power. For example, the fifth lens may have a positive refractive power or a negative refractive power in an edge of a paraxial region thereof.

[0073] The fifth lens is partially flat or substantially flat. For example, the fifth lens may be planar in the paraxial region thereof. In one example, the object-side surface of the fifth lens is flat in a paraxial region and gradually concaves at edge portions thereof. In another example, the image-side surface of the fifth lens is flat or substantially flat in a paraxial region and gradually curves, in a convex shape, at edge portions thereof.

[0074] The fifth lens has an aspherical surface. For example, both surfaces of the fifth lens are aspherical. The fifth lens is formed of a material having high light transmissivity and excellent workability. For example, the fifth lens is formed of plastic or a polyurethane material. However, a material of the fifth lens is not limited to plastic. For example, the fifth lens may be formed of glass.

[0075] The sixth lens has a refractive power. For example, the sixth lens has a negative refractive power.

[0076] One surface of the sixth lens is convex. For example, an object-side surface of the sixth lens is convex. The sixth lens has inflection points. For example, one or more inflection points are formed on an object-side surface and an image-side surface of the sixth lens.

[0077] The sixth lens has an aspherical surface. For example, both surfaces of the sixth lens are aspherical. The sixth lens is formed of a material having high light transmissivity and excellent workability. For example, the sixth lens may be formed of plastic. However, a material of the sixth lens is not limited to plastic or a polyurethane material. For example, the sixth lens may be formed of glass.

[0078] In an embodiment, the image-side surface of the sixth lens is concave in a paraxial region and gradually curves to be convex towards edge portions thereof.

[0079] A person of ordinary skill in the relevant art will appreciate that each of the first through sixth lenses may be configured in an opposite refractive power from the configuration described above. For example, in an alternative configuration, the first lens has a negative refractive power, the second lens has a negative refractive power, the third lens has a positive refractive power, the fourth lens has a negative refractive power, the fifth lens no refractive power, and the sixth lens has a positive refractive power.

[0080] First to sixth lenses are formed of materials having a refractive index different from that of air. For example, the first to sixth lenses are formed of plastic or glass. At least one of the first to

sixth lenses has an aspherical shape. As an example, all of the first to sixth lenses have the aspherical shape. In an example, an aspherical surface of each lens is represented by the following Equation 1:

[00001]

$$Z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + Ar^4 + Br^6 + Cr^8 + Dr^{10} + Er^{12} + Fr^{14} + Gr^{16} + Hr^{18} + Jr^{20} . \quad [\text{Equation1}]$$

[0081] In an example, c is an inverse of a radius of curvature of the lens, k is a conic constant, r is a distance from a certain point on an aspherical surface of the lens to an optical axis, A to J are aspherical constants, and Z (or SAG) is a distance between the certain point on the aspherical surface of the lens at the distance Y and a tangential plane meeting the apex of the aspherical surface of the lens.

[0082] In one embodiment, the optical imaging system includes lenses having the same refractive index. For example, the third to fifth lenses may have the same refractive index. In addition, the first lens, the second lens, and the sixth lens may have the same refractive index, different from the refractive index of the third to fifth lenses.

[0083] The optical imaging system includes a stop. The stop is disposed between the second and third lenses. The stop disposed as described above adjusts an amount of light incident to the imaging plane.

[0084] The optical imaging system includes a filter. The filter filters a partial wavelength from light incident through the first to sixth lenses. For example, the filter filters an infrared wavelength of the incident light.

[0085] The optical imaging system includes an image sensor. The image sensor provides the imaging plane on which light refracted by the lenses may be imaged. For example, a surface of the image sensor forms the imaging plane. The image sensor is configured to realize a high resolution. For example, a unit size of pixels configuring the image sensor may be 1.12 μm or less.

[0086] Also, in one embodiment, each of the first to sixth lenses may be separate lenses configured as described above. A distance between lenses may vary. In another embodiment, at least one of the first to sixth lenses may be operatively connected or in contact with another one of the first to sixth lenses.

[0087] The optical imaging system satisfies the following Conditional Expressions 1 through 7:

[00002]  $0.05 < Th5 / f < 0.25$  [ConditionalExpression1]

$20 < V1 - V3 < 70$  [ConditionalExpression2]

$.Math. Sag51 / Th5 .Math. < 1.$  [ConditionalExpression3]  $-1.5 < f3 / f2$  [ConditionalExpression4]

$0.5 < OAL / f < 2.$  [ConditionalExpression5]  $1.6 < n5 < 2.1$  [ConditionalExpression6]

$Fnumber < 2..$  [ConditionalExpression7]

[0088] In one example, Th5 is a thickness of an optical axis center of the fifth lens, f is an overall focal length of the optical imaging system, V1 is an Abbe number of the first lens, V3 is an Abbe number of the third lens, Sag51 is a Sag value at an end of an effective diameter of an object-side surface of the fifth lens, f2 is a focal length of the second lens, f3 is a focal length of the third lens, OAL is a distance from the object-side surface of the first lens toward the imaging plane, and n5 is a refractive index of the fifth lens. F number is an angle of convergence in a cone of focusing light emanating from a circular aperture. The F number is defined by an effective focal length of the optical system (f) divided by the optical system's circular entrance pupil diameter (D).

[0089] The optical imaging system satisfying the above Conditional Expressions 1 through 7 may be miniaturized, and may realize a high resolution.

[0090] Next, optical imaging systems, according to various embodiments, will be described.

[0091] An optical imaging system, according to a first embodiment, will be described with reference to FIG. 1.

[0092] The optical imaging system **100**, according to the first embodiment, includes a plurality of



lenses having refractive power. For example, the optical imaging system **100** includes a first lens **110**, a second lens **120**, a third lens **130**, a fourth lens **140**, a fifth lens **150**, and a sixth lens **160**. [0093] In accordance with an example, the object-side surfaces and the image-side surfaces to be described below with respect to each of the first through sixth lenses **110** through **160** are described with respect to the paraxial regions. For instance, for the first lens **110**, an object-side surface thereof is convex in the paraxial region and an image-side surface thereof is concave in the paraxial region. Surface regions, on the object-side surface and the image-side surface, which neighbor or are in the vicinity of the paraxial regions may also have the same curvature as the corresponding paraxial regions or may be concave, convex, flat, or substantially flat. The configuration illustrated in FIG. **1** is one illustrative example of the surface regions in the vicinity of the paraxial regions. However, a person skilled in the art will appreciate that different curvatures or flatness may be implemented in the surface regions in the vicinity of the paraxial regions than those illustrated in FIG. **1**.

[0094] The first lens **110** has a positive refractive power, and an object-side surface thereof is convex and an image-side surface thereof is concave. The second lens **120** has a positive refractive power, and an object-side surface thereof is convex and an image-side surface thereof is convex. The third lens **130** has a negative refractive power, and an object-side surface thereof is convex and an image-side surface thereof is concave. The fourth lens **140** has a positive refractive power, and an object-side surface thereof is convex and an image-side surface thereof is convex. The fifth lens **150** may not have a refractive power in a paraxial region thereof. For example, the fifth lens **150** is planar in the paraxial region of the object-side surface thereof. The sixth lens **160** has a negative refractive power, and an object-side surface thereof is convex and an image-side surface thereof is concave. In addition, inflection points may be formed on both surfaces of the sixth lens **160**. For example, the object-side surface of the sixth lens is convex in a paraxial region thereof and concave in a vicinity of the paraxial region. Similarly, the image-side surface of the sixth lens is concave in a paraxial region thereof and convex in a vicinity of the paraxial region.

[0095] The optical imaging system **100** includes a stop ST. For example, the stop ST is disposed between the second lens **120** and the third lens **130**. The stop ST disposed as described above adjusts an amount of light incident to an imaging plane **180**.

[0096] The optical imaging system **100** includes a filter **170**. For example, the filter **170** is disposed between the sixth lens **160** and the imaging plane **180**. The filter **170** disposed as described above filters infrared rays incident to the imaging plane **180**.

[0097] The optical imaging system **100** includes an image sensor. The image sensor provides the imaging plane **180** on which light refracted through the lenses is imaged. In addition, the image sensor converts an optical signal imaged on the imaging plane **180** into an electrical signal.

[0098] The optical imaging system configured as described above may represent aberration characteristics as illustrated in FIG. **2**. FIG. **3** is a table representing characteristics of lenses of the optical imaging system, according to an embodiment.

[0099] An optical imaging system, according to a second embodiment will be described with reference to FIG. **4**.

[0100] The optical imaging system **200**, according to the second embodiment, includes a plurality of lenses having refractive power. For example, the optical imaging system **200** includes a first lens **210**, a second lens **220**, a third lens **230**, a fourth lens **240**, a fifth lens **250**, and a sixth lens **260**.

[0101] In accordance with an example, the object-side surfaces and the image-side surfaces to be described below with respect to each of the first through sixth lenses **210** through **260** are described with respect to the paraxial regions. For instance, for the first lens **210**, an object-side surface thereof is convex in the paraxial region and an image-side surface thereof is concave in the paraxial region. Surface regions, on the object-side surface and the image-side surface, which neighbor or are in the vicinity of the paraxial regions may also have the same curvature as the corresponding paraxial regions or may be concave, convex, flat, or substantially flat. The configuration illustrated

in FIG. 2 is one illustrative example of the surface regions in the vicinity of the paraxial regions. However, a person skilled in the art will appreciate that different curvatures or flatness may be implemented in the surface regions in the vicinity of the paraxial regions than those illustrated in FIG. 2.

[0102] The first lens **210** has a positive refractive power, and an object-side surface thereof is convex and an image-side surface thereof is concave. The second lens **220** has a positive refractive power, and an object-side surface thereof may be convex and an image-side surface thereof may be convex. The third lens **230** has a negative refractive power, and an object-side surface thereof is convex and an image-side surface thereof is concave. The fourth lens **240** has a positive refractive power, and an object-side surface thereof is convex and an image-side surface thereof is convex. The fifth lens **250** does not have a refractive power in a paraxial region thereof. For example, the fifth lens **250** is planar in the paraxial region thereof. In one embodiment, the fifth lens **250** is planar in the paraxial region of the object-side surface thereof and the paraxial region of the image-side surface thereof. In another embodiment, the fifth lens **250** is planar in the paraxial region only of the object-side surface thereof. In further another embodiment, the fifth lens **250** is planar in the paraxial region only of the image-side surface thereof. The sixth lens **260** has a negative refractive power, and an object-side surface thereof may be convex and an image-side surface thereof may be concave. In addition, inflection points are formed on both surfaces of the sixth lens **260**. For example, the object-side surface of the sixth lens is convex in a paraxial region thereof and concave in the vicinity of the paraxial region. Similarly, the image-side surface of the sixth lens is concave in a paraxial region thereof and convex in the vicinity of the paraxial region.

[0103] The optical imaging system **200** includes a stop ST. For example, the stop ST is disposed between the second lens **220** and the third lens **230**. The stop ST disposed as described above adjusts an amount of light incident to an imaging plane **280**.

[0104] The optical imaging system **200** includes a filter **270**. For example, the filter **270** is disposed between the sixth lens **260** and the imaging plane **280**. The filter **270** disposed as described above filters infrared rays incident to the imaging plane **280**.

[0105] The optical imaging system **200** includes an image sensor. The image sensor provides the imaging plane **280** on which light refracted through the lenses is imaged. In addition, the image sensor converts an optical signal imaged on the imaging plane **280** into an electrical signal.

[0106] The optical imaging system, configured as described above, represent aberration characteristics as illustrated in FIG. 5. FIG. 6 is a table representing characteristics of lenses of the optical imaging system, according to an embodiment.

[0107] An optical imaging system, according to a third embodiment will be described with reference to FIG. 7.

[0108] The optical imaging system **300**, according to the third embodiment, includes a plurality of lenses having refractive power. For example, the optical imaging system **300** includes a first lens **310**, a second lens **320**, a third lens **330**, a fourth lens **340**, a fifth lens **350**, and a sixth lens **360**.

[0109] In accordance with an example, the object-side surfaces and the image-side surfaces to be described below with respect to each of the first through sixth lenses **310** through **360** are described with respect to the paraxial regions. For instance, for the first lens **310**, an object-side surface thereof is convex in the paraxial region and an image-side surface thereof is concave in the paraxial region. Surface regions, on the object-side surface and the image-side surface, which neighbor or are in the vicinity of the paraxial regions may also have the same curvature as the corresponding paraxial regions or may be concave, convex, flat, or substantially flat. The configuration illustrated in FIG. 3 is one illustrative example of the surface regions in the vicinity of the paraxial regions. However, a person skilled in the art will appreciate that different curvatures or flatness may be implemented in the surface regions in the vicinity of the paraxial regions than those illustrated in FIG. 3.

[0110] The first lens **310** has a positive refractive power, and an object-side surface thereof is

convex and an image-side surface thereof is concave. The second lens **320** has a positive refractive power, and an object-side surface thereof is convex and an image-side surface thereof is convex. The third lens **330** has a negative refractive power, and an object-side surface thereof is convex and an image-side surface thereof is concave. The fourth lens **340** has a positive refractive power, and an object-side surface thereof is convex and an image-side surface thereof may be concave. The fifth lens **350** does not have refractive power in a paraxial region thereof. For example, the fifth lens **350** has a plane in the paraxial region thereof. In one embodiment, the fifth lens **350** is a plane in the paraxial region of the object-side surface thereof and the paraxial region of the image-side surface thereof. In another embodiment, the fifth lens **350** is a plane in the paraxial region only of the object-side surface thereof. In further another embodiment, the fifth lens **350** is a plane in the paraxial region only of the image-side surface thereof.

[0111] The sixth lens **360** has a negative refractive power, and an object-side surface thereof is convex and an image-side surface thereof is concave. In addition, inflection points are formed on both surfaces of the sixth lens **360**. For example, the object-side surface of the sixth lens is convex in a paraxial region thereof and concave in the vicinity of the paraxial region. Similarly, the image-side surface of the sixth lens is concave in a paraxial region thereof and convex in the vicinity of the paraxial region.

[0112] The optical imaging system **300** includes a stop ST. For example, the stop ST is disposed between the second lens **320** and the third lens **330**. The stop ST disposed as described above adjusts an amount of light incident to an imaging plane **380**.

[0113] The optical imaging system **300** includes a filter **370**. For example, the filter **370** is disposed between the sixth lens **360** and the imaging plane **380**. The filter **370** disposed as described above filters infrared rays incident to the imaging plane **380**.

[0114] The optical imaging system **300** includes an image sensor. The image sensor provides the imaging plane **380** on which light refracted through the lenses is imaged. In addition, the image sensor converts an optical signal imaged on the imaging plane **380** into an electrical signal.

[0115] The optical imaging system, configured as described above, represents aberration characteristics as illustrated in FIG. **8**. FIG. **9** is a table representing characteristics of lenses of the optical imaging system, according to an embodiment.

[0116] Table 1 represents values of Conditional Expressions 1 through 7 of the optical imaging systems according to the first to third embodiments. As seen in Table 1, the optical imaging systems according to the first to third embodiments may satisfy all of numerical according to Conditional Expressions 1 through 7, as described above.

TABLE-US-00001													
TABLE 1 First Second Third Conditional Expression Embodiment													
Embodiment	Embodiment	Th5/f	0.1550	0.1559	0.1926	V1-V3	34.600	34.600	34.600	Sag51/Th5			
	0.8862	0.8862	0.7093	f3/f2	-1.3290	-1.3311	-1.2995	OAL/f	1.1888	1.1911	1.1797	n5	1.6500
	1.6500	1.6500	F number	1.8000	1.8000	1.8000							

[0117] As set forth above, according to various embodiments, a clear image is realized.

[0118] While this disclosure includes specific examples, it will be apparent to one of ordinary skill in the art that various changes in form and details may be made in these examples without departing from the spirit and scope of the claims and their equivalents. The examples described herein are to be considered in a descriptive sense only, and not for purposes of limitation. Descriptions of features or aspects in each example are to be considered as being applicable to similar features or aspects in other examples. Suitable results may be achieved if the described techniques are performed in a different order, and/or if components in a described system, architecture, device, or circuit are combined in a different manner and/or replaced or supplemented by other components or their equivalents. Therefore, the scope of the disclosure is defined not by the detailed description, but by the claims and their equivalents, and all variations within the scope of the claims and their equivalents are to be construed as being included in the disclosure.

## Claims

1. An optical imaging system, comprising: a first lens comprising a refractive power; a second lens comprising positive refractive power; a third lens comprising a convex object-side surface; a fourth lens comprising a refractive power; a fifth lens comprising a refractive power; and a sixth lens comprising a refractive power, wherein the first to sixth lenses are sequentially disposed from an object side toward an imaging plane, wherein an absolute value of a radius of curvature of an object-side of the third lens is greater than an absolute value of a radius of curvature of an object-side of the second lens, wherein an absolute value of a radius of curvature of an image-side surface of the third lens is greater than an absolute value of a radius of curvature of an object-side surface of the sixth lens, and wherein  $-1.5 < f_3/f_2$ , where  $f_2$  is a focal length of the second lens and  $f_3$  is a focal length of the third lens.
  2. The optical imaging system of claim 1, wherein the first lens has a convex object-side surface.
  3. The optical imaging system of claim 1, wherein the second lens has a convex object-side surface.
  4. The optical imaging system of claim 1, wherein the fourth lens has a convex object-side surface.
  5. The optical imaging system of claim 1, wherein the sixth lens has a convex object-side surface.
  6. The optical imaging system of claim 1, wherein the sixth lens has an inflection point formed on an image-side surface of the sixth lens.
  7. An optical imaging system, comprising: a first lens comprising a refractive power; a second lens comprising positive refractive power; a third lens comprising a convex object-side surface; a fourth lens comprising positive refractive power; a fifth lens comprising a refractive power; and a sixth lens comprising a refractive power, wherein the first to sixth lenses are sequentially disposed from an object side toward an imaging plane, wherein a thickness of the fifth lens is greater than a distance from an image-side surface of the fourth lens to an object-side surface of the fifth lens, wherein an absolute value of a radius of curvature of an object-side of the third lens is greater than an absolute value of a radius of curvature of an object-side of the second lens, and wherein an absolute value of a radius of curvature of an image-side surface of the third lens is greater than an absolute value of a radius of curvature of an object-side surface of the sixth lens.
  8. The optical imaging system of claim 7, wherein the first lens has a convex object-side surface.
  9. The optical imaging system of claim 7, wherein the second lens has a convex object-side surface.
  10. The optical imaging system of claim 7, wherein the fourth lens has a convex object-side surface.
  11. The optical imaging system of claim 7, wherein the sixth lens has a convex object-side surface.
  12. The optical imaging system of claim 7, wherein the sixth lens has an inflection point formed on an image-side surface of the sixth lens.
-