

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383208
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Moisa; Saar et al.

Systems and methods for selecting, activating, or selecting and activating transducers

Abstract

A graphical representation may be displayed including at least a plurality of transducer graphical elements, each transducer graphical element of the plurality of transducer graphical elements representative of a respective transducer of a plurality of transducers of a transducer-based device. A set of user input may be received including an instruction set to reposition a first transducer graphical element in a state in which the first transducer graphical element is located at a first location in the graphical representation and a second transducer graphical element is located at a second location in the graphical representation, the second location closer to a predetermined location in the graphical representation than the first location. In response to conclusion of receipt of the set of user input, the first transducer graphical element may be repositioned from the first location in the graphical representation to the predetermined location in the graphical representation.

Inventors:	Moisa; Saar (Vancouver, CA), Weber; Michael Hermann (Sointula, CA)
Applicant:	Kardium Inc. (Burnaby, CA)
Family ID:	61618138
Assignee:	KARDIUM INC. (Burnaby, CA)
Appl. No.:	18/655869
Filed:	May 06, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240285241 A1	Aug. 29, 2024

Related U.S. Application Data

continuation parent-doc US 17177517 20210217 US 12133745 child-doc US 18655869
continuation parent-doc US 16388063 20190418 US 11026637 20210608 child-doc US 17177517
continuation parent-doc US 15827499 20171130 US 10722184 20200728 child-doc US 16388063
continuation-in-part parent-doc US 14942459 20151116 US 10368936 20190806 child-doc US
15827499
us-provisional-application US 62080750 20141117

Publication Classification

Int. Cl.: **A61B5/00** (20060101); **A61B5/01** (20060101); **A61B5/02** (20060101); **A61B5/283**
(20210101); **A61B5/287** (20210101); **G06F3/04815** (20220101); **G06F3/0482**
(20130101); **G06F3/04842** (20220101); **G06F3/04847** (20220101); A61B5/15
(20060101); A61B5/157 (20060101); A61B18/00 (20060101); A61B18/14 (20060101);
A61B34/10 (20160101); G16H40/63 (20180101)

U.S. Cl.:

CPC **A61B5/743** (20130101); **A61B5/015** (20130101); **A61B5/02** (20130101); **A61B5/283**
(20210101); **A61B5/287** (20210101); **A61B5/6859** (20130101); **A61B5/6869**
(20130101); **A61B5/72** (20130101); **A61B5/7435** (20130101); **A61B5/748** (20130101);
G06F3/04815 (20130101); **G06F3/0482** (20130101); **G06F3/04842** (20130101);
G06F3/04847 (20130101); A61B5/150022 (20130101); A61B5/150969 (20130101);
A61B5/157 (20130101); A61B2018/00214 (20130101); A61B2018/00267 (20130101);
A61B2018/00357 (20130101); A61B2018/00577 (20130101); A61B2018/00642
(20130101); A61B2018/00702 (20130101); A61B2018/00791 (20130101);
A61B2018/00839 (20130101); A61B2018/00875 (20130101); A61B2018/1467
(20130101); A61B18/1492 (20130101); A61B2034/107 (20160201); A61B2560/0475
(20130101); G16H40/63 (20180101)

Field of Classification Search

CPC: A61B (5/743); A61B (5/283); A61B (5/287)

USPC: 600/522

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4114202	12/1977	Roy et al.	N/A	N/A
4164046	12/1978	Cooley	N/A	N/A
4225148	12/1979	Andersson	N/A	N/A
4240441	12/1979	Khalil	N/A	N/A
4263680	12/1980	Reul et al.	N/A	N/A
4273128	12/1980	Lary	N/A	N/A
4411266	12/1982	Cosman	N/A	N/A
4490859	12/1984	Black et al.	N/A	N/A
4543090	12/1984	McCoy	N/A	N/A
4699147	12/1986	Chilson et al.	N/A	N/A

4770187	12/1987	Lash et al.	N/A	N/A
4794912	12/1988	Lia	N/A	N/A
4850957	12/1988	Summers	N/A	N/A
4887613	12/1988	Farr et al.	N/A	N/A
4890602	12/1989	Hake	N/A	N/A
4890612	12/1989	Kensey	N/A	N/A
4893613	12/1989	Hake	N/A	N/A
4895166	12/1989	Farr et al.	N/A	N/A
4921499	12/1989	Hoffman et al.	N/A	N/A
4940064	12/1989	Desai	N/A	N/A
4942788	12/1989	Farr et al.	N/A	N/A
4979514	12/1989	Sekii et al.	N/A	N/A
4998933	12/1990	Eggers et al.	N/A	N/A
5026384	12/1990	Farr et al.	N/A	N/A
5047047	12/1990	Yoon	N/A	N/A
5122137	12/1991	Lennox	N/A	N/A
5127902	12/1991	Fischell	N/A	N/A
5146926	12/1991	Cohen	N/A	N/A
5156151	12/1991	Imran	N/A	N/A
5174299	12/1991	Nelson	N/A	N/A
5176693	12/1992	Pannek, Jr.	N/A	N/A
5178620	12/1992	Eggers et al.	N/A	N/A
5192291	12/1992	Pannek, Jr.	N/A	N/A
5201316	12/1992	Pomeranz et al.	N/A	N/A
5228442	12/1992	Imran	N/A	N/A
5242386	12/1992	Holzer	N/A	N/A
5255679	12/1992	Imran	N/A	N/A
5279299	12/1993	Imran	N/A	N/A
5293869	12/1993	Edwards et al.	N/A	N/A
5312435	12/1993	Nash et al.	N/A	N/A
5317952	12/1993	Immega	N/A	N/A
5327889	12/1993	Imran	N/A	N/A
5341807	12/1993	Nardella	N/A	N/A
5366443	12/1993	Eggers et al.	N/A	N/A
5379773	12/1994	Hornsby	N/A	N/A
5419767	12/1994	Eggers et al.	N/A	N/A
5450860	12/1994	O'Conner	N/A	N/A
5478353	12/1994	Yoon	N/A	N/A
5496267	12/1995	Drasler et al.	N/A	N/A
5531760	12/1995	Alwafaie	N/A	N/A
5545193	12/1995	Fleischman et al.	N/A	N/A
5557967	12/1995	Renger	N/A	N/A
5588432	12/1995	Crowley	N/A	N/A
5593424	12/1996	Northrup, III	N/A	N/A
5598848	12/1996	Swanson et al.	N/A	N/A
5599345	12/1996	Edwards et al.	N/A	N/A
5620481	12/1996	Desai et al.	N/A	N/A
5662587	12/1996	Grundfest et al.	N/A	N/A
5681308	12/1996	Edward et al.	N/A	N/A
5681336	12/1996	Clement et al.	N/A	N/A

5687723	12/1996	Avitall	N/A	N/A
5687737	12/1996	Branham et al.	N/A	N/A
5697285	12/1996	Nappi et al.	N/A	N/A
5713896	12/1997	Nardella	N/A	N/A
5713942	12/1997	Sten et al.	N/A	N/A
5716397	12/1997	Myers	N/A	N/A
5720726	12/1997	Marcadis et al.	N/A	N/A
5728114	12/1997	Evans et al.	N/A	N/A
5730127	12/1997	Avitall	N/A	N/A
5762066	12/1997	Law et al.	N/A	N/A
5769846	12/1997	Edwards et al.	N/A	N/A
5782239	12/1997	Webster, Jr.	N/A	N/A
5782879	12/1997	Rosborough et al.	N/A	N/A
5800495	12/1997	Machek et al.	N/A	N/A
5810802	12/1997	Panescu et al.	N/A	N/A
5824066	12/1997	Gross	N/A	N/A
5836990	12/1997	Li	N/A	N/A
5848972	12/1997	Triedman et al.	N/A	N/A
5876343	12/1998	Teo	N/A	N/A
5881727	12/1998	Edwards	N/A	N/A
5891136	12/1998	McGee et al.	N/A	N/A
5904711	12/1998	Flom et al.	N/A	N/A
5916163	12/1998	Panescu et al.	N/A	N/A
5919207	12/1998	Taheri	N/A	N/A
5921924	12/1998	Avitall	N/A	N/A
5935075	12/1998	Casscells et al.	N/A	N/A
5935079	12/1998	Swanson et al.	N/A	N/A
5941251	12/1998	Panescu et al.	N/A	N/A
5961440	12/1998	Schweich, Jr. et al.	N/A	N/A
5968040	12/1998	Swanson et al.	N/A	N/A
5984950	12/1998	Cragg et al.	N/A	N/A
6001069	12/1998	Tachibana et al.	N/A	N/A
6014581	12/1999	Whayne et al.	N/A	N/A
6104944	12/1999	Martinelli	N/A	N/A
6138043	12/1999	Avitall	N/A	N/A
6142993	12/1999	Whayne et al.	N/A	N/A
6156046	12/1999	Passafaro et al.	N/A	N/A
6183468	12/2000	Swanson	N/A	N/A
6210432	12/2000	Solem et al.	N/A	N/A
6216043	12/2000	Swanson et al.	N/A	N/A
6217573	12/2000	Webster	N/A	N/A
6241747	12/2000	Ruff	N/A	N/A
6245064	12/2000	Lesh et al.	N/A	N/A
6248124	12/2000	Pedros et al.	N/A	N/A
6258258	12/2000	Sartori	N/A	N/A
6266550	12/2000	Selmon et al.	N/A	N/A
6304769	12/2000	Arenson et al.	N/A	N/A
6306135	12/2000	Ellmam et al.	N/A	N/A
6308091	12/2000	Avitall	N/A	N/A
6319249	12/2000	Töllner	N/A	N/A

6346105	12/2001	Tu et al.	N/A	N/A
6350263	12/2001	Wetzig et al.	N/A	N/A
6358258	12/2001	Arcia et al.	N/A	N/A
6383151	12/2001	Diederich et al.	N/A	N/A
6389311	12/2001	Whayne et al.	N/A	N/A
6391024	12/2001	Sun et al.	N/A	N/A
6391048	12/2001	Ginn et al.	N/A	N/A
6391054	12/2001	Carpentier et al.	N/A	N/A
6402781	12/2001	Langberg et al.	N/A	N/A
6436052	12/2001	Nikolic et al.	N/A	N/A
6475223	12/2001	Werp et al.	N/A	N/A
6485409	12/2001	Voloshin et al.	N/A	N/A
6485489	12/2001	Teirstein et al.	N/A	N/A
6506210	12/2002	Kanner	N/A	N/A
6514249	12/2002	Maguire et al.	N/A	N/A
6529756	12/2002	Phan et al.	N/A	N/A
6537198	12/2002	Mdlund et al.	N/A	N/A
6537314	12/2002	Langberg et al.	N/A	N/A
6540670	12/2002	Hirata et al.	N/A	N/A
6551312	12/2002	Zhang et al.	N/A	N/A
6569160	12/2002	Goldin et al.	N/A	N/A
6569198	12/2002	Wilson et al.	N/A	N/A
6575971	12/2002	Hauck et al.	N/A	N/A
6589208	12/2002	Ewers et al.	N/A	N/A
6626930	12/2002	Allen et al.	N/A	N/A
6632238	12/2002	Ginn et al.	N/A	N/A
6635056	12/2002	Kadhiresan et al.	N/A	N/A
6640119	12/2002	Budd et al.	N/A	N/A
6652515	12/2002	Maguire et al.	N/A	N/A
6652517	12/2002	Hall et al.	N/A	N/A
6662034	12/2002	Segner et al.	N/A	N/A
6666862	12/2002	Jain et al.	N/A	N/A
6704590	12/2003	Haldeman	N/A	N/A
6723038	12/2003	Schroeder et al.	N/A	N/A
6725085	12/2003	Schwartzman et al.	N/A	N/A
6726716	12/2003	Marquez	N/A	N/A
6733499	12/2003	Scheib	N/A	N/A
6735465	12/2003	Panescu	N/A	N/A
6760616	12/2003	Hoey et al.	N/A	N/A
6780197	12/2003	Roe et al.	N/A	N/A
6788969	12/2003	Dupree et al.	N/A	N/A
6795721	12/2003	Coleman et al.	N/A	N/A
6797001	12/2003	Mathis et al.	N/A	N/A
6800090	12/2003	Alferness et al.	N/A	N/A
6837886	12/2004	Collins et al.	N/A	N/A
6852076	12/2004	Nikolic et al.	N/A	N/A
6855143	12/2004	Davison et al.	N/A	N/A
6890353	12/2004	Cohn et al.	N/A	N/A
6892091	12/2004	Ben-Haim et al.	N/A	N/A
6899674	12/2004	Viebach et al.	N/A	N/A

6907297	12/2004	Wellman et al.	N/A	N/A
6908478	12/2004	Alferness et al.	N/A	N/A
6913576	12/2004	Bowman	N/A	N/A
6918903	12/2004	Bass	N/A	N/A
6926669	12/2004	Stewart et al.	N/A	N/A
6936047	12/2004	Nasab et al.	N/A	N/A
6942657	12/2004	Sinofsky et al.	N/A	N/A
6949122	12/2004	Adams et al.	N/A	N/A
6955640	12/2004	Sanders et al.	N/A	N/A
6960229	12/2004	Mathis et al.	N/A	N/A
6966908	12/2004	Maguire et al.	N/A	N/A
6986775	12/2005	Morales et al.	N/A	N/A
6989010	12/2005	Francischelli et al.	N/A	N/A
6989028	12/2005	Lashinski et al.	N/A	N/A
6994093	12/2005	Murphy et al.	N/A	N/A
6997925	12/2005	Maguire et al.	N/A	N/A
6997951	12/2005	Solem et al.	N/A	N/A
7001383	12/2005	Keidar	N/A	N/A
7003342	12/2005	Plaza	N/A	N/A
7025776	12/2005	Houser et al.	N/A	N/A
7044135	12/2005	Lesh	N/A	N/A
7048734	12/2005	Fleischman et al.	N/A	N/A
7050848	12/2005	Hoey et al.	N/A	N/A
7052487	12/2005	Cohn et al.	N/A	N/A
7068867	12/2005	Adoram et al.	N/A	N/A
7141019	12/2005	Pearlman	N/A	N/A
7144363	12/2005	Pai et al.	N/A	N/A
7177677	12/2006	Kaula et al.	N/A	N/A
7186210	12/2006	Feld et al.	N/A	N/A
7187964	12/2006	Khoury	N/A	N/A
7189202	12/2006	Lau et al.	N/A	N/A
7194294	12/2006	Panescu et al.	N/A	N/A
7252664	12/2006	Nasab et al.	N/A	N/A
7279007	12/2006	Nikolic et al.	N/A	N/A
7282030	12/2006	Frei et al.	N/A	N/A
7300435	12/2006	Wham et al.	N/A	N/A
7303526	12/2006	Sharkey et al.	N/A	N/A
7335196	12/2007	Swanson et al.	N/A	N/A
7340307	12/2007	Maguire et al.	N/A	N/A
7507252	12/2008	Lashinski et al.	N/A	N/A
7530980	12/2008	Hooven	N/A	N/A
7575566	12/2008	Scheib	N/A	N/A
7593760	12/2008	Rodriguez et al.	N/A	N/A
7610078	12/2008	Willis	N/A	N/A
7633502	12/2008	Willis et al.	N/A	N/A
7738967	12/2009	Salo	N/A	N/A
8103338	12/2011	Harlev et al.	N/A	N/A
8150499	12/2011	Gelbart et al.	N/A	N/A
8200308	12/2011	Zhang et al.	N/A	N/A
8216216	12/2011	Warnking et al.	N/A	N/A

8221411	12/2011	Francischelli et al.	N/A	N/A
8224432	12/2011	Macadam et al.	N/A	N/A
8326419	12/2011	Rosenberg et al.	N/A	N/A
8352019	12/2012	Starks	N/A	N/A
8398626	12/2012	Buysee et al.	N/A	N/A
8401645	12/2012	Rosenberg et al.	N/A	N/A
8414508	12/2012	Thapliyal et al.	N/A	N/A
8442613	12/2012	Kim et al.	N/A	N/A
8442625	12/2012	Markowitz et al.	N/A	N/A
8457371	12/2012	Markowitz et al.	N/A	N/A
8463368	12/2012	Harlev et al.	N/A	N/A
8478393	12/2012	Ramanathan et al.	N/A	N/A
8532734	12/2012	Markowitz et al.	N/A	N/A
8571647	12/2012	Harlev et al.	N/A	N/A
8615287	12/2012	Harlev et al.	N/A	N/A
8657814	12/2013	Werneth et al.	N/A	N/A
8663120	12/2013	Markowitz et al.	N/A	N/A
8706260	12/2013	Stewart et al.	N/A	N/A
8725240	12/2013	Harlev et al.	N/A	N/A
8831701	12/2013	Markowitz et al.	N/A	N/A
8834461	12/2013	Werneth et al.	N/A	N/A
8838216	12/2013	Francis et al.	N/A	N/A
8849384	12/2013	Greenspan	N/A	N/A
8897516	12/2013	Turgeman	N/A	N/A
8906011	12/2013	Gelbart et al.	N/A	N/A
8920411	12/2013	Gelbart et al.	N/A	N/A
8926605	12/2014	McCarthy et al.	N/A	N/A
8932284	12/2014	McCarthy et al.	N/A	N/A
8961506	12/2014	McCarthy et al.	N/A	N/A
9011423	12/2014	Brewster et al.	N/A	N/A
9033893	12/2014	Spector	N/A	N/A
9044245	12/2014	Condie et al.	N/A	N/A
9095350	12/2014	Condie et al.	N/A	N/A
9101333	12/2014	Schwartz	N/A	N/A
9107599	12/2014	Harlev et al.	N/A	N/A
9119633	12/2014	Gelbart et al.	N/A	N/A
9119634	12/2014	Gelbart et al.	N/A	N/A
9179860	12/2014	Markowitz et al.	N/A	N/A
9179972	12/2014	Olson	N/A	N/A
9204935	12/2014	Hauck et al.	N/A	N/A
9265434	12/2015	Merschon et al.	N/A	N/A
9277872	12/2015	Harlev et al.	N/A	N/A
9277960	12/2015	Weinkam et al.	N/A	N/A
9282910	12/2015	Narayan et al.	N/A	N/A
9332920	12/2015	Thakur et al.	N/A	N/A
9398862	12/2015	Harlev et al.	N/A	N/A
9408544	12/2015	Laughner et al.	N/A	N/A
9433465	12/2015	Gliner et al.	N/A	N/A
9439578	12/2015	Thakur et al.	N/A	N/A
9456759	12/2015	Lian et al.	N/A	N/A

9474491	12/2015	Li et al.	N/A	N/A
9486272	12/2015	Bonyak et al.	N/A	N/A
9504518	12/2015	Condie et al.	N/A	N/A
9532725	12/2016	Laughner et al.	N/A	N/A
9532828	12/2016	Condie et al.	N/A	N/A
9554718	12/2016	Bar-Tal et al.	N/A	N/A
9554847	12/2016	Govari et al.	N/A	N/A
9572620	12/2016	Ryu et al.	N/A	N/A
9579064	12/2016	Kovtun et al.	N/A	N/A
9603651	12/2016	Ghosh	N/A	N/A
9603661	12/2016	Gelbart et al.	N/A	N/A
9610045	12/2016	Du et al.	N/A	N/A
9622806	12/2016	Mihalik	N/A	N/A
9629567	12/2016	Porath et al.	N/A	N/A
9636032	12/2016	Thakur et al.	N/A	N/A
9655535	12/2016	Narayan et al.	N/A	N/A
9662033	12/2016	Severino	N/A	N/A
9693699	12/2016	Spector et al.	N/A	N/A
9730603	12/2016	Laughner et al.	N/A	N/A
9737267	12/2016	Strom et al.	N/A	N/A
9743854	12/2016	Stewart et al.	N/A	N/A
9763587	12/2016	Altmann	N/A	N/A
9763625	12/2016	Laughner et al.	N/A	N/A
9782094	12/2016	Du et al.	N/A	N/A
9795314	12/2016	Laughner et al.	N/A	N/A
9814523	12/2016	Condie et al.	N/A	N/A
9848833	12/2016	Govari et al.	N/A	N/A
9861802	12/2017	Mickelsen	N/A	N/A
9875578	12/2017	Zar et al.	N/A	N/A
9888972	12/2017	Brewster et al.	N/A	N/A
9895079	12/2017	Massarwa et al.	N/A	N/A
9913589	12/2017	Scharf et al.	N/A	N/A
9918649	12/2017	Thakur et al.	N/A	N/A
9918788	12/2017	Paul et al.	N/A	N/A
9940747	12/2017	Katz et al.	N/A	N/A
9949657	12/2017	Ravuna et al.	N/A	N/A
9955889	12/2017	Urman et al.	N/A	N/A
9980653	12/2017	Lichtenstein et al.	N/A	N/A
9987083	12/2017	Gelbart et al.	N/A	N/A
9987084	12/2017	Gelbart et al.	N/A	N/A
10004413	12/2017	Bokan et al.	N/A	N/A
10010368	12/2017	Laske et al.	N/A	N/A
10016145	12/2017	Thakur et al.	N/A	N/A
10028783	12/2017	Gelbart et al.	N/A	N/A
10064678	12/2017	Corvi et al.	N/A	N/A
10085659	12/2017	Laughner et al.	N/A	N/A
2001/0003158	12/2000	Kensey et al.	N/A	N/A
2001/0005787	12/2000	Oz et al.	N/A	N/A
2001/0018611	12/2000	Solem et al.	N/A	N/A
2001/0020126	12/2000	Swanson et al.	N/A	N/A

2002/0002329	12/2001	Avitall	N/A	N/A
2002/0016628	12/2001	Langberg et al.	N/A	N/A
2002/0087156	12/2001	Maguire et al.	N/A	N/A
2002/0087173	12/2001	Alferness et al.	N/A	N/A
2002/0099415	12/2001	Panescu et al.	N/A	N/A
2002/0107478	12/2001	Wendlandt	N/A	N/A
2002/0107511	12/2001	Collins et al.	N/A	N/A
2002/0115941	12/2001	Whayne et al.	N/A	N/A
2002/0115944	12/2001	Mendes et al.	N/A	N/A
2002/0165535	12/2001	Lesh et al.	N/A	N/A
2002/0169445	12/2001	Jain et al.	N/A	N/A
2002/0169504	12/2001	Alferness et al.	N/A	N/A
2002/0177782	12/2001	Penner	N/A	N/A
2002/0183836	12/2001	Liddicoat et al.	N/A	N/A
2002/0183841	12/2001	Cohn et al.	N/A	N/A
2002/0188170	12/2001	Santamore et al.	N/A	N/A
2003/0023130	12/2002	Ciaccio et al.	N/A	N/A
2003/0028118	12/2002	Dupree et al.	N/A	N/A
2003/0028183	12/2002	Sanchez et al.	N/A	N/A
2003/0050637	12/2002	Maguire et al.	N/A	N/A
2003/0050685	12/2002	Nikolic et al.	N/A	N/A
2003/0055420	12/2002	Kadhiresan et al.	N/A	N/A
2003/0060820	12/2002	Maguire et al.	N/A	N/A
2003/0069570	12/2002	Witzel et al.	N/A	N/A
2003/0069573	12/2002	Kadhiresan et al.	N/A	N/A
2003/0069636	12/2002	Solem et al.	N/A	N/A
2003/0078465	12/2002	Pai et al.	N/A	N/A
2003/0078494	12/2002	Panescu et al.	N/A	N/A
2003/0078509	12/2002	Panescu	N/A	N/A
2003/0078671	12/2002	Lesniak et al.	N/A	N/A
2003/0105384	12/2002	Sharkey et al.	N/A	N/A
2003/0105520	12/2002	Alferness et al.	N/A	N/A
2003/0109770	12/2002	Sharkey et al.	N/A	N/A
2003/0125726	12/2002	Maguire et al.	N/A	N/A
2003/0181819	12/2002	Desai	N/A	N/A
2003/0212395	12/2002	Woloszko et al.	N/A	N/A
2003/0229395	12/2002	Cox	N/A	N/A
2004/0002626	12/2003	Feld et al.	N/A	N/A
2004/0006337	12/2003	Nasab et al.	N/A	N/A
2004/0054279	12/2003	Hanley	N/A	N/A
2004/0133273	12/2003	Cox	N/A	N/A
2004/0138744	12/2003	Lashinski et al.	N/A	N/A
2004/0153146	12/2003	Lashinski et al.	N/A	N/A
2004/0158321	12/2003	Reuter et al.	N/A	N/A
2004/0176797	12/2003	Opolski	N/A	N/A
2004/0186566	12/2003	Hindrichs et al.	N/A	N/A
2004/0215232	12/2003	Belhe et al.	N/A	N/A
2004/0243170	12/2003	Suresh et al.	N/A	N/A
2004/0249408	12/2003	Murphy et al.	N/A	N/A
2004/0249453	12/2003	Cartledge et al.	N/A	N/A

2004/0267358	12/2003	Reitan	N/A	N/A
2005/0004668	12/2004	Aklog et al.	N/A	N/A
2005/0010206	12/2004	Nasab et al.	N/A	N/A
2005/0015109	12/2004	Lichtenstein	N/A	N/A
2005/0043604	12/2004	Beatty et al.	N/A	N/A
2005/0054938	12/2004	Wehman et al.	N/A	N/A
2005/0055089	12/2004	Macoviak et al.	N/A	N/A
2005/0060030	12/2004	Lashinski et al.	N/A	N/A
2005/0064665	12/2004	Han	N/A	N/A
2005/0065420	12/2004	Collins et al.	N/A	N/A
2005/0065504	12/2004	Melsky et al.	N/A	N/A
2005/0080402	12/2004	Santamore et al.	N/A	N/A
2005/0096047	12/2004	Haberman et al.	N/A	N/A
2005/0096647	12/2004	Steinke et al.	N/A	N/A
2005/0107723	12/2004	Wehman et al.	N/A	N/A
2005/0107871	12/2004	Realyvasques et al.	N/A	N/A
2005/0125030	12/2004	Forsberg et al.	N/A	N/A
2005/0148892	12/2004	Desai	N/A	N/A
2005/0149014	12/2004	Hauck et al.	N/A	N/A
2005/0154252	12/2004	Sharkey et al.	N/A	N/A
2005/0165388	12/2004	Bhola	N/A	N/A
2005/0182365	12/2004	Hennemann	N/A	N/A
2005/0187620	12/2004	Pai et al.	N/A	N/A
2005/0197692	12/2004	Pai et al.	N/A	N/A
2005/0197693	12/2004	Pai et al.	N/A	N/A
2005/0197694	12/2004	Pai et al.	N/A	N/A
2005/0203558	12/2004	Maschke	N/A	N/A
2005/0209525	12/2004	Bojovic et al.	N/A	N/A
2005/0209636	12/2004	Widomski et al.	N/A	N/A
2005/0216054	12/2004	Widomski et al.	N/A	N/A
2005/0240249	12/2004	Tu et al.	N/A	N/A
2005/0251116	12/2004	Steinke et al.	N/A	N/A
2005/0251132	12/2004	Oral et al.	N/A	N/A
2005/0256521	12/2004	Kozel	N/A	N/A
2005/0261580	12/2004	Willis et al.	N/A	N/A
2005/0267574	12/2004	Cohn et al.	N/A	N/A
2006/0009755	12/2005	Sra	N/A	N/A
2006/0009756	12/2005	Francischelli et al.	N/A	N/A
2006/0014998	12/2005	Sharkey et al.	N/A	N/A
2006/0015002	12/2005	Moaddeb et al.	N/A	N/A
2006/0015003	12/2005	Moaddes et al.	N/A	N/A
2006/0015038	12/2005	Weymarn-Scharli	N/A	N/A
2006/0015096	12/2005	Hauck et al.	N/A	N/A
2006/0025800	12/2005	Suresh	N/A	N/A
2006/0030881	12/2005	Sharkey et al.	N/A	N/A
2006/0064006	12/2005	Strommer et al.	N/A	N/A
2006/0084966	12/2005	Maguire et al.	N/A	N/A
2006/0085049	12/2005	Cory et al.	N/A	N/A
2006/0089637	12/2005	Werneth et al.	N/A	N/A
2006/0135968	12/2005	Schaller	N/A	N/A

2006/0135970	12/2005	Shaller	N/A	N/A
2006/0173251	12/2005	Govari et al.	N/A	N/A
2006/0184242	12/2005	Lichtenstein	N/A	N/A
2006/0199995	12/2005	Vijay	N/A	N/A
2006/0229491	12/2005	Sharkey et al.	N/A	N/A
2006/0235286	12/2005	Stone et al.	N/A	N/A
2006/0235314	12/2005	Migliuolo et al.	N/A	N/A
2006/0264980	12/2005	Khairkhahan et al.	N/A	N/A
2006/0281965	12/2005	Khairkhahan et al.	N/A	N/A
2006/0293698	12/2005	Douk	N/A	N/A
2006/0293725	12/2005	Rubinsky et al.	N/A	N/A
2007/0016068	12/2006	Grunwald et al.	N/A	N/A
2007/0038208	12/2006	Kefer	N/A	N/A
2007/0083193	12/2006	Werneth et al.	N/A	N/A
2007/0083195	12/2006	Werneth et al.	N/A	N/A
2007/0088362	12/2006	Bonutti et al.	N/A	N/A
2007/0115390	12/2006	Makara et al.	N/A	N/A
2007/0118215	12/2006	Moaddeb	N/A	N/A
2007/0129717	12/2006	Brown, III et al.	N/A	N/A
2007/0161846	12/2006	Nikolic et al.	N/A	N/A
2007/0198058	12/2006	Gelbart et al.	N/A	N/A
2007/0213578	12/2006	Khairkhahan et al.	N/A	N/A
2007/0213815	12/2006	Khairkhahan et al.	N/A	N/A
2007/0232949	12/2006	Saksena	N/A	N/A
2007/0236491	12/2006	Hundley et al.	N/A	N/A
2007/0239062	12/2006	Chopra	N/A	N/A
2007/0249999	12/2006	Sklar et al.	N/A	N/A
2007/0270688	12/2006	Gelbart et al.	N/A	N/A
2007/0299343	12/2006	Waters	N/A	N/A
2008/0004534	12/2007	Gelbart et al.	N/A	N/A
2008/0004643	12/2007	To et al.	N/A	N/A
2008/0004697	12/2007	Lichtenstein et al.	N/A	N/A
2008/0045778	12/2007	Lichtenstein et al.	N/A	N/A
2008/0071298	12/2007	Khairkhahan et al.	N/A	N/A
2008/0081990	12/2007	Berenfeld et al.	N/A	N/A
2008/0172048	12/2007	Martin et al.	N/A	N/A
2008/0194979	12/2007	Madry et al.	N/A	N/A
2008/0281322	12/2007	Sherman et al.	N/A	N/A
2008/0312713	12/2007	Wilfley et al.	N/A	N/A
2009/0018617	12/2008	Skelton et al.	N/A	N/A
2009/0069704	12/2008	Macadam et al.	N/A	N/A
2009/0131930	12/2008	Gelbart et al.	N/A	N/A
2009/0148012	12/2008	Altmann et al.	N/A	N/A
2009/0157058	12/2008	Ferren et al.	N/A	N/A
2009/0163801	12/2008	Sliwa	N/A	N/A
2009/0177111	12/2008	Miller et al.	N/A	N/A
2009/0182325	12/2008	Werneth et al.	N/A	N/A
2009/0192441	12/2008	Gelbart et al.	N/A	N/A
2009/0253976	12/2008	Harlev et al.	N/A	N/A
2009/0264781	12/2008	Scharf	N/A	N/A

2009/0287271	12/2008	Blum et al.	N/A	N/A
2009/0287304	12/2008	Dahlgren et al.	N/A	N/A
2010/0016762	12/2009	Thapliyal et al.	N/A	N/A
2010/0023004	12/2009	Francischelli et al.	N/A	N/A
2010/0113928	12/2009	Thapliyal et al.	N/A	N/A
2010/0113985	12/2009	Thapliyal et al.	N/A	N/A
2010/0114094	12/2009	Thapliyal	N/A	N/A
2010/0204694	12/2009	Mehta et al.	N/A	N/A
2010/0249771	12/2009	Pearson et al.	N/A	N/A
2010/0268059	12/2009	Ryu et al.	N/A	N/A
2010/0286551	12/2009	Harlev et al.	N/A	N/A
2011/0034912	12/2010	De Graff et al.	N/A	N/A
2011/0125172	12/2010	Gelbart et al.	N/A	N/A
2012/0078076	12/2011	Stewart et al.	N/A	N/A
2012/0136346	12/2011	Condie et al.	N/A	N/A
2012/0136348	12/2011	Condie et al.	N/A	N/A
2012/0172859	12/2011	Condie et al.	N/A	N/A
2012/0172867	12/2011	Ryu et al.	N/A	N/A
2012/0277567	12/2011	Harlev et al.	N/A	N/A
2013/0066220	12/2012	Weinkam et al.	N/A	N/A
2013/0172884	12/2012	Schoenbach et al.	N/A	N/A
2013/0274562	12/2012	Ghaffari et al.	N/A	N/A
2013/0296679	12/2012	Condie et al.	N/A	N/A
2013/0296850	12/2012	Olson	N/A	N/A
2013/0310702	12/2012	Reinders et al.	N/A	N/A
2013/0310826	12/2012	Goertzen et al.	N/A	N/A
2013/0310827	12/2012	Brewster et al.	N/A	N/A
2013/0310828	12/2012	Reinders et al.	N/A	N/A
2013/0345538	12/2012	Harlev et al.	N/A	N/A
2014/0121659	12/2013	Paul et al.	N/A	N/A
2014/0213894	12/2013	Gelbart et al.	N/A	N/A
2014/0296850	12/2013	Condie et al.	N/A	N/A
2014/0303610	12/2013	McCarthy et al.	N/A	N/A
2014/0303614	12/2013	McCarthy et al.	N/A	N/A
2014/0330266	12/2013	Thompson et al.	N/A	N/A
2014/0364848	12/2013	Heimbecher et al.	N/A	N/A
2015/0065899	12/2014	Reinders et al.	N/A	N/A
2015/0105701	12/2014	Mayer et al.	N/A	N/A
2015/0182740	12/2014	Mickelsen	N/A	N/A
2015/0366508	12/2014	Chou et al.	N/A	N/A
2016/0008061	12/2015	Fung et al.	N/A	N/A
2016/0058505	12/2015	Condie et al.	N/A	N/A
2016/0106498	12/2015	Highsmith	N/A	N/A
2016/0287137	12/2015	Condie et al.	N/A	N/A
2016/0346030	12/2015	Thapliyal et al.	N/A	N/A
2016/0367325	12/2015	Brewster et al.	N/A	N/A
2017/0035499	12/2016	Stewart et al.	N/A	N/A
2017/0065339	12/2016	Mickelsen	N/A	N/A
2017/0065340	12/2016	Long	N/A	N/A
2017/0079712	12/2016	Levin et al.	N/A	N/A

2017/0092013	12/2016	Perlman et al.	N/A	N/A
2017/0103570	12/2016	Zar et al.	N/A	N/A
2017/0105627	12/2016	Katz et al.	N/A	N/A
2017/0119453	12/2016	Ryu et al.	N/A	N/A
2017/0128013	12/2016	Reinders et al.	N/A	N/A
2017/0143414	12/2016	Sliwa et al.	N/A	N/A
2017/0156792	12/2016	Ziv-Ari et al.	N/A	N/A
2017/0202470	12/2016	Urman et al.	N/A	N/A
2017/0202516	12/2016	Bar-Tal et al.	N/A	N/A
2017/0202521	12/2016	Urman et al.	N/A	N/A
2017/0312012	12/2016	Harlev et al.	N/A	N/A
2018/0042674	12/2017	Mickelsen	N/A	N/A
2018/0042675	12/2017	Long	N/A	N/A
2018/0056074	12/2017	Clark et al.	N/A	N/A
2018/0064488	12/2017	Long et al.	N/A	N/A
2018/0068439	12/2017	Hareland	N/A	N/A
2018/0093088	12/2017	Mickelsen	N/A	N/A
2018/0110561	12/2017	Levin et al.	N/A	N/A
2018/0125575	12/2017	Schwartz et al.	N/A	N/A
2018/0140363	12/2017	Brewster et al.	N/A	N/A
2018/0158238	12/2017	Cohen et al.	N/A	N/A
2018/0160978	12/2017	Cohen et al.	N/A	N/A
2018/0161097	12/2017	Zoabi et al.	N/A	N/A
2018/0177467	12/2017	Katz et al.	N/A	N/A
2018/0177552	12/2017	Zoabi et al.	N/A	N/A
2018/0182157	12/2017	Zar et al.	N/A	N/A
2018/0182159	12/2017	Cohen et al.	N/A	N/A
2018/0190009	12/2017	Cohen et al.	N/A	N/A
2018/0199976	12/2017	Fischer	N/A	N/A
2018/0199990	12/2017	Monir et al.	N/A	N/A
2018/0200497	12/2017	Mickelsen	N/A	N/A
2018/0206920	12/2017	Pappone et al.	N/A	N/A
2018/0214202	12/2017	Howard et al.	N/A	N/A
2018/0242868	12/2017	Cohen et al.	N/A	N/A
2018/0242914	12/2017	Reinders et al.	N/A	N/A
2018/0256055	12/2017	Zigelman et al.	N/A	N/A
2018/0296114	12/2017	Welsh et al.	N/A	N/A
2018/0325597	12/2017	Schwartz et al.	N/A	N/A
2019/0029608	12/2018	Moisa et al.	N/A	N/A
2019/0029609	12/2018	Moisa et al.	N/A	N/A
2019/0239823	12/2018	Moisa	N/A	N/A
2019/0269367	12/2018	Reinders et al.	N/A	N/A
2019/0314092	12/2018	Brewster	N/A	N/A
2020/0054283	12/2019	Reinders	N/A	N/A
2021/0045689	12/2020	Reinders et al.	N/A	N/A
2021/0128256	12/2020	Brewster	N/A	N/A
2021/0267549	12/2020	Reinders et al.	N/A	N/A
2021/0346104	12/2020	Brewster et al.	N/A	N/A
2021/0346105	12/2020	Brewster et al.	N/A	N/A
2021/0353370	12/2020	Moisa	N/A	N/A

2022/0401029	12/2021	Reinders et al.	N/A	N/A
2023/0010183	12/2022	Brewster et al.	N/A	N/A
2023/0040602	12/2022	Brewster et al.	N/A	N/A
2023/0045231	12/2022	Reinders et al.	N/A	N/A
2024/0285241	12/2023	Moisa et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1169976	12/2001	EP	N/A
0723467	12/2001	EP	N/A
1240868	12/2001	EP	N/A
1645234	12/2005	EP	N/A
1182980	12/2005	EP	N/A
1280467	12/2007	EP	N/A
1451595	12/2008	EP	N/A
2499968	12/2011	EP	N/A
1909679	12/2012	EP	N/A
2307098	12/2014	EP	N/A
2848191	12/2014	EP	N/A
2873365	12/2014	EP	N/A
2984986	12/2015	EP	N/A
2645953	12/2015	EP	N/A
2661236	12/2015	EP	N/A
2749213	12/2015	EP	N/A
2604211	12/2015	EP	N/A
3130285	12/2016	EP	N/A
3141185	12/2016	EP	N/A
2689722	12/2016	EP	N/A
2613723	12/2016	EP	N/A
3225161	12/2016	EP	N/A
2892454	12/2017	EP	N/A
3318211	12/2017	EP	N/A
3321890	12/2017	EP	N/A
3139997	12/2017	EP	N/A
3375365	12/2017	EP	N/A
3395277	12/2017	EP	N/A
9313708	12/1992	WO	N/A
95/10320	12/1994	WO	N/A
95/20349	12/1994	WO	N/A
97/17892	12/1996	WO	N/A
0134026	12/2000	WO	N/A
0228303	12/2001	WO	N/A
03/015611	12/2002	WO	N/A
03022148	12/2002	WO	N/A
03/077800	12/2002	WO	N/A
2004/012629	12/2003	WO	N/A
2004/047679	12/2003	WO	N/A
2004/084746	12/2003	WO	N/A
2004/100803	12/2003	WO	N/A
2005/070330	12/2004	WO	N/A

2005/102181	12/2004	WO	N/A
2006/017809	12/2005	WO	N/A
2006/105121	12/2005	WO	N/A
2006/135747	12/2005	WO	N/A
2006/135749	12/2005	WO	N/A
2007/021647	12/2006	WO	N/A
2007/024983	12/2006	WO	N/A
2007/115390	12/2006	WO	N/A
2008/002606	12/2007	WO	N/A
2008135731	12/2007	WO	N/A
2009/065042	12/2008	WO	N/A
2010031830	12/2009	WO	N/A
2010054409	12/2009	WO	N/A
2012/033984	12/2011	WO	N/A
2012/100184	12/2011	WO	N/A
2012/100185	12/2011	WO	N/A
2012151301	12/2011	WO	N/A
2013/176880	12/2012	WO	N/A
2013/0176881	12/2012	WO	N/A
2016181317	12/2015	WO	N/A
2016181318	12/2015	WO	N/A
2016183468	12/2015	WO	N/A
2017009165	12/2016	WO	N/A
2017024123	12/2016	WO	N/A
2017087740	12/2016	WO	N/A
2017120169	12/2016	WO	N/A
2017192480	12/2016	WO	N/A
2017192495	12/2016	WO	N/A
2017192510	12/2016	WO	N/A
2017192542	12/2016	WO	N/A
2018023132	12/2017	WO	N/A
2018165425	12/2017	WO	N/A
2018191149	12/2017	WO	N/A
2018201037	12/2017	WO	N/A

OTHER PUBLICATIONS

Becker, et al., “Ablation of Atrial Fibrillation: Energy Sources and Navigation Tools: A Review”, Journal of Electrocardiology, Supplement 2004, pp. 55-62, vol. 37. cited by applicant

Buchbinder, Maurice, “Dynamic Mitral Valve Annuloplasty: A Reshapable Ring for Residual and Recurring MR”, Foundation for Cardiovascular Medicine, May 24, 2007. cited by applicant

Calkins, Hugh, “Electrophysiology: Radiofrequency Catheter Ablation of Supraventricular Arrhythmias”, Education in Heart, 2001; pp. 594-600, vol. 85. cited by applicant

De Ponti, et al., “Non-Fluoroscopic Mapping Systems for Electrophysiology: the Tool or Toy Dilemma After 10 Years”, European Heart Journal, 2006; pp. 1134-1136, vol. 27. cited by applicant

Gabriel, et al., “The Dielectric Properties of Biological Tissues: I. Literature Survey”, Phys. Med. Biol.; 1996, pp. 2231-2249, vol. 41. cited by applicant

Konings, et al., “Development of an Intravascular Impedance Catheter for Detection of Fatty Lesions in Arteries”, IEEE Transactions on Medical Imaging, Aug. 1997, pp. 439-446, vol. 16, No. 4. cited by applicant

Mack, Michael J., “New Techniques for Percutaneous Repair of the Mitral Valve”, Heart Fail Rev,

2006; pp. 259-268, vol. 11. cited by applicant

Otasevic, et al., "First-in-Man Implantation of Left Ventricular Partitioning Device in a Patient With Chronic Heart Failure: Twelve-Month Follow-Up", *Journal of Cardiac Failure*, 2007, pp. 517-520, vol. 13, No. 7. cited by applicant

Sharkey, et al., "Left Ventricular Apex Occluder. Description of a Ventricular Partitioning Device", *EuroIntervention*, 2006, pp. 125-127. cited by applicant

Stiles, et al., "Simulated Characterization of Atherosclerotic Lesions in the Coronary Arteries by Measurement of Bioimpedance", *IEEE Transactions on Biomedical Engineering*, Jul. 2003, pp. 916-921, vol. 50, No. 7. cited by applicant

Tanaka, et al., "Artificial SMA Valve for Treatment of Urinary Incontinence: Upgrading of Valve and Introduction of Transcutaneous Transformer", *Bio-Medical Materials and Engineering*; 1999, pp. 97-112, vol. 9. cited by applicant

Timek, et al., "Septal-Lateral Annular Cinching Abolishes Acute Ischemic Mitral Regurgitation", *Journal of Thoracic and Cardiovascular Surgery*, May 2002, pp. 881-888, vol. 123, No. 5. cited by applicant

Timek, et al., "Septal-Lateral Annular Cinching (SLAC) Reduces Mitral Annular Size Without Perturbing Normal Annular Dynamics", *Journal of Heart Valve Disease*, Jan. 2002, vol. 11, No. 1, pp. 1-9. cited by applicant

Valvano, et al., "Thermal Conductivity and Diffusivity of Biomaterials Measured with Self-Heated Thermistors", *International Journal of Thermophysics*, 1985, pp. 301-311, vol. 6, No. 3. cited by applicant

Prosecution Documents for U.S. Appl. No. 11/436,584, now abandoned. cited by applicant

Prosecution Documents for U.S. Appl. No. 11/941,819, now published as US 2009-0131930 A1. cited by applicant

Prosecution Documents for U.S. Appl. No. 12/010,458, now published as US 2009-0192441 A1. cited by applicant

Prosecution Documents for U.S. Appl. No. 12/950,871, now patented as US 8,150,499. cited by applicant

Specification and Drawings of U.S. Appl. No. 10/690,131. cited by applicant

International Search Report issued in PCT/US2007/014902 mailed Dec. 5, 2007, 5 pages. cited by applicant

International Search Report issued in PCT/US2008/083644 mailed Dec. 2, 2009, 5 pages. cited by applicant

International Preliminary Report on Patentability issued in PCT/US2007/014902 mailed Jan. 6, 2009, 8 pages. cited by applicant

Written Opinion issued in PCT/US2007/014902 mailed Dec. 5, 2007, 7 pages. cited by applicant

Written Opinion issued in PCT/US2008/083644 mailed Dec. 2, 2009, 9 pages. cited by applicant

"Waveforms and Segments", *Ensite System Instructions for use*, 54-06154-001 Rev02, Chapter 7, pp. 85-90 © 2007 St. Jude Medical. cited by applicant

Office Action issued in U.S. Appl. No. 14/948,924 mailed Aug. 8, 2016. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 14/686,457 mailed May 11, 2016. cited by applicant

Goertzen et al., "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Amendment filed on May 17, 2016 for U.S. Appl. No. 13/792,596. 20 pages. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers" Amendment filed Jun. 20, 2016 for U.S. Appl. No. 14/948,924. 8 pages. cited by applicant

Brewster et al., "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Response to NFOA and Terminal Disclaimer filed on Mar. 31, 2016 for U.S. Appl. No. 14/686,408. 5 pages. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 14/686,408 mailed May 11, 2016. cited by applicant

Office Action issued in U.S. Appl. No. 13/792,596 mailed Aug. 26, 2016. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 15/000,491 mailed Sep. 2, 2016. cited by applicant

Examination Report issued in European Application No. 13793690.2 mailed Nov. 17, 2016. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 14/948,924 mailed Dec. 21, 2016. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers" Response to FOA and Terminal Disclaimer filed in U.S. Appl. No. 14/948,924, filed Dec. 12, 2016. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers", Amendment After Allowance filed Feb. 13, 2015 for U.S. Appl. No. 13/792,945, 14 pages. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers", Amendment After Allowance filed Feb. 13, 2015 for U.S. Appl. No. 13/792,781, 14 pages. cited by applicant

Brewster et al. "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Preliminary Amendment filed in Sep. 21, 2016 for U.S. Appl. No. 15/254,207, 11 pages. cited by applicant

Brewster et al. "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Preliminary Amendment filed in May 15, 2015 for U.S. Appl. No. 14/686,408, 8 pages. cited by applicant

Brewster et al., "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Amendment After Allowance filed in Feb. 13, 2015 for U.S. Appl. No. 13/792,670, 11 pages. cited by applicant

Goertzen et al. "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Preliminary Amendment filed in Feb. 13, 2015 for U.S. Appl. No. 13/792,596, 11 pages. cited by applicant

Goertzen et al., "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Response to Restriction Requirement filed Jun. 29, 2015 for U.S. Appl. No. 13/792,596, 6 pages. cited by applicant

Goertzen et al., "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Amendment filed Jan. 10, 2017 for U.S. Appl. No. 13/792,596, 21 pages. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 16/388,063 mailed Feb. 8, 2021. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 16/388,093 mailed Feb. 22, 2021. cited by applicant

Office Action issued in U.S. Appl. No. 16/599,305 mailed on Dec. 23, 2020. cited by applicant

Response filed in U.S. Appl. No. 16/388,093, filed Nov. 10, 2020. cited by applicant

Response filed in U.S. Appl. No. 16/388,063, filed Nov. 10, 2020. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 17/148,054, filed Jan. 29, 2021. cited by applicant

Extended European Search Report issued in European Application No. 20208810.0 mailed Mar. 22, 2021. cited by applicant

Response filed in U.S. Appl. No. 16/599,305, filed Mar. 23, 2021. cited by applicant

Office Action issued in U.S. Appl. No. 16/599,305 mailed Jun. 2, 2021. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 17/324,157, filed Jun. 10, 2021. cited by applicant

Amendment filed in U.S. Appl. No. 16/599,305, filed Jun. 26, 2021. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 16/599,305 mailed on Jul. 7, 2021. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 17/382,498, filed Aug. 26, 2021. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 17/382,534, filed Aug. 26, 2021. cited by applicant

Office Action issued in U.S. Appl. No. 17/075,104 mailed Jul. 18, 2022. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 17/075,104, filed Nov. 19, 2020. cited by applicant

Preliminary Amendment filed in copending U.S. Appl. No. 17/893,667, filed Sep. 21, 2022. cited by applicant

Response to Non-Final Office Action filed in U.S. Appl. No. 17/075,104, filed Sep. 22, 2022. cited by applicant

Preliminary Amendment filed in copending U.S. Appl. No. 17/947,473, filed Oct. 11, 2022. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 17/075,104, mailed Oct. 26, 2022. cited by applicant

Preliminary Amendment filed in copending U.S. Appl. No. 17/969,027, filed Nov. 15, 2022. cited by applicant

Communication Pursuant to Article 94(3) EPC issued in European Application No. 19202799.3, mailed Jan. 13, 2023. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 17/324,157, mailed Mar. 15, 2023. cited by applicant

Non-Final Office Action issued in U.S. Appl. No. 17/382,498, mailed Mar. 30, 2023. cited by applicant

Communication Pursuant to Article 94(3) EPC issued in European Application No. 19188918.7, mailed Mar. 2, 2023. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 17/382,534, mailed Apr. 13, 2023. cited by applicant

Second Preliminary Amendment filed in copending U.S. Appl. No. 17/893,667, filed May 5, 2023. cited by applicant

Amendment filed in U.S. Appl. No. 17/382,498, filed Jun. 1, 2023. cited by applicant

International Search Report issued in International Appln. No. PCT/CA2023/050571, mailed Jun. 19, 2023. cited by applicant

Written Opinion issued in International Appln. No. PCT/CA2023/050571, mailed Jun. 19, 2023. cited by applicant

Office Action issued in U.S. Appl. No. 14/942,459 mailed Jan. 18, 2019. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 15/414,834 mailed Jan. 29, 2018. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 15/414,834, filed Feb. 23, 2017. cited by applicant

Amendment filed in U.S. Appl. No. 15/254,207, filed Aug. 23, 2017. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 15/254,207 mailed Oct. 4, 2017. cited by applicant

Office Action issued in European Application No. 13794418.7 mailed Jun. 7, 2017. cited by applicant

Office Action issued in U.S. Appl. No. 15/254,207 mailed Jun. 1, 2017. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 13/792,596 mailed May 5, 2017. cited by applicant

Response to Restriction Requirement and Amendment filed in U.S. Appl. No. 15/254,207, filed Apr. 5, 2017. cited by applicant

Amendment filed in U.S. Appl. No. 14/942,459, filed Feb. 26, 2019. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 14/942,459, filed Apr. 4, 2019. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 15/860,921 mailed Sep. 18, 2019. cited by applicant

Office Action issued in U.S. Appl. No. 15/827,499 mailed Jun. 17, 2019. cited by applicant

Intention to Grant issued in European Application No. 13794418.7 mailed Apr. 9, 2019. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 16/415,016, filed Jun. 25, 2019. cited by applicant

Intention to Grant issued in European Application No. 13793690.2 mailed May 27, 2019. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 16/426,091, filed Jun. 25, 2019. cited by applicant

Amendment filed in U.S. Appl. No. 15/827,499, filed Jul. 26, 2019. cited by applicant

Extended European Search Report issued in European Appln. No. 19188918.7 mailed Nov. 4, 2019. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 16/599,305, filed Oct. 29, 2019. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 15/964,951 mailed Nov. 7, 2019. cited by applicant

Office Action issued in U.S. Appl. No. 15/827,499 mailed Nov. 7, 2019. cited by applicant

Response filed in U.S. Appl. No. 15/827,499, filed Jan. 13, 2020. cited by applicant

Office Action issued in U.S. Appl. No. 16/139,860 mailed on Feb. 10, 2020. cited by applicant

Office Action issued in U.S. Appl. No. 16/139,772 mailed on Feb. 10, 2020. cited by applicant

Extended European Search Report issued in European Application No. 19202799.3 mailed on Jan. 29, 2020. cited by applicant

Response to Office Action filed in U.S. Appl. No. 15/827,499, filed Jan. 13, 2020. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 15/827,499, filed Apr. 9, 2020. cited by applicant

Response to Office Action filed in U.S. Appl. No. 16/139,772, filed Apr. 3, 2020. cited by applicant

Response to Office Action filed in U.S. Appl. No. 16/139,860, filed Apr. 3, 2020. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 16/139,860, filed May 11, 2020. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 16/139,772 mailed Jul. 2, 2020. cited by applicant

Office Action issued in U.S. Appl. No. 16/388,063 mailed Aug. 11, 2020. cited by applicant

Office Action issued in U.S. Appl. No. 16/388,093 mailed Aug. 11, 2020. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 16/415,016 mailed Sep. 10, 2020. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 16/426,091 mailed Oct. 19, 2020. cited by applicant

Notice of Allowance issued in copending U.S. Appl. No. 17/177,517 mailed Jul. 3, 2024. cited by applicant

Office Action issued in copending U.S. Appl. No. 17/947,473 mailed Sep. 26, 2024. cited by applicant

Office Action issued in copending U.S. Appl. No. 17/960,332 mailed Sep. 26, 2024. cited by applicant

International Search Report issued in Intl. Appln. No. PCT/CA2023/050571 mailed Jun. 19, 2023. cited by applicant

Written Opinion issued in Intl. Appln. No. PCT/CA2023/050571 mailed Jun. 19, 2023. cited by applicant

Office Action issued in copending U.S. Appl. No. 17/893,667 mailed Sep. 28, 2024. cited by applicant

Reinders et al. Copending U.S. Appl. No. 18/905,250, filed Oct. 3, 2024 (a copy is not included because the cited application is not yet available to the public and the Examiner has ready access to the cited application). cited by applicant

Goertzen et al. Copending U.S. Appl. No. 18/905,309, filed Oct. 3, 2024 (a copy is not included because the cited application is not yet available to the public and the Examiner has ready access to the cited application). cited by applicant

International Search Report issued in International Appln. No. PCT/CA2023/050572, mailed Jul. 19, 2023. cited by applicant

Written Opinion issued in International Appln. No. PCT/CA2023/050572, mailed Jul. 19, 2023. cited by applicant

Kottkamp et al. "Global multielectrode contact mapping plus ablation with a single catheter: Preclinical and preliminary experience in humans with atrial fibrillation." *Journal of Cardiovascular Electrophysiology*. 2017:1-10. cited by applicant

Mounsey. "A novel multielectrode combined mapping and ablation basket catheter: A future player in the atrial fibrillation ablation space?" *Journal of Cardiovascular Electrophysiology*. 2017:1-2. cited by applicant

Preliminary Amendment filed in U.S. Appl. No. 15/964,951, filed Jun. 6, 2018. cited by applicant

Office Action issued in European Appln. No. 13793690.2 mailed Oct. 19, 2018. cited by applicant

DESJARDINS. "Infarct Architecture and Characteristics on Delayed Enhanced Magnetic Resonance Imaging and Electroanatomic Mapping in Patients with Post-Infarction Ventricular Arrhythmia." *Heart Rhythm*. May 2009: 644-651. vol. 6, No. 5. cited by applicant

Yamada. "Pulmonary Vein Isolation with a Multielectrode Basket Catheter." *Indian Pacing and Electrophysiology Journal*. 2006: 97-109. vol. 7, No. 2. cited by applicant

Harada et al. "Computerized Potential Distribution Mapping: A New Intraoperative Mapping Technique for Ventricular Tachycardia Surgery." *The Society of Thoracic Surgeons*. 1990: 649-655.

vol. 49. cited by applicant

Yamada et al. "Computerized Three-Dimensional Potential Mapping with a Multielectrode Basket Catheter Can be Useful for Pulmonary Vein Electrical Disconnection." *Journal of Interventional Cardiac Electrophysiology*. 2005: 23-33. vol. 12. cited by applicant

Laxer. "A Graphical Display System for Animating Mapped Cardiac Potentials." *Third Annual IEEE Symposium on Computer-Based Medical Systems*. 1990: 197-204. cited by applicant

Keck et al. "Electromechanical Mapping for Determination of Myocardial Contractility and Viability." *Journal of the American College of Cardiology*. Sep. 18, 2002: 1067-1074. vol. 40, No. 6. cited by applicant

Linton et al. "Cardiac ripple mapping: A novel three-dimensional visualization method for use with electroanatomic mapping of cardiac arrhythmias." *Heart Rhythm Society*. Dec. 2009: 1754-1762. vol. 6. No. 12. cited by applicant

Bhakta et al. "Principles of Electroanatomic Mapping." *Indian Pacing and Electrophysiology Journal*. 2008: 32-50. vol. 8, No. 1. cited by applicant

EnSite System. "EnSite v.8.0. Chapter 1." St. Jude Medical. 2008: 3. cited by applicant

Ideker et al. "A Computerized Method for the Rapid Display of Ventricular Activation During the Intraoperative Study of Arrhythmias." *Circulation*. 1979: 449-458. vol. 59, No. 3. cited by applicant

Gupta et al. "Cardiac Mapping: Utility or Futility?" *Indian Pacing and Electrophysiology Journal*. 2002: 20-32. vol. 2, No. 1. cited by applicant

De Groot et al. "Voltage and Activation Mapping." *Circulation*. 2003: 2099-2106. vol. 108. cited by applicant

Schmitt et al. "Clinical Experience With a Novel Multielectrode Basket Catheter in Right Atrial Tachycardias." *Circulation*. 1999: 2414-2422. vol. 99. cited by applicant

Notice of Allowance issued in U.S. Appl. No. 17/382,498, mailed Aug. 18, 2023. cited by applicant

Office Action issued in copending U.S. Appl. No. 17/177,517, mailed Jan. 25, 2024. cited by applicant

Communication Pursuant to Article 94(3) EPC issued in European Appln. No. 20208810.0, mailed Mar. 7, 2024. cited by applicant

Amendment filed in copending U.S. Appl. No. 17/177,517, filed Apr. 22, 2024. cited by applicant

Supplemental Amendment filed in copending U.S. Appl. No. 17/177,517, filed Apr. 29, 2024. cited by applicant

Preliminary Amendment filed in copending U.S. Appl. No. 17/960,332, filed Nov. 10, 2022. cited by applicant

International Search Report and Written Opinion issued in PCT/CA2013/050350 mailed Aug. 2, 2013. cited by applicant

International Search Report and Written Opinion issued in PCT/US2013/039982 mailed Sep. 17, 2013. cited by applicant

International Search Report and Written Opinion issued in PCT/US2013/039977 mailed Sep. 27, 2013. cited by applicant

Brewster et al., "Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers", Response to Restriction Requirement filed Dec. 23, 2014 for U.S. Appl. No. 13/792,670, 15 pages. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers", Response to Restriction Requirement filed Dec. 23, 2014 for U.S. Appl. No. 13/792,945, 16 pages. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers", Notice of Allowance for U.S. Appl. No. 13/792,945 mailed Jan. 27, 2015, 49 pages. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers", Response to Restriction Requirement filed Dec. 23, 2014 for U.S. Appl. No. 13/792,781, 15 pages. cited by applicant

Reinders et al., "Systems and Methods for Activating Transducers", Notice of Allowance mailed

Feb. 3, 2015 for U.S. Appl. No. 13/792,781, 52 pages. cited by applicant
Brewster et al., “Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers”, Notice of Allowance mailed Feb. 4, 2015 for U.S. Appl. No. 13/792,670, 47 pages. cited by applicant
Partial Supplementary European Search Report issued in EP13794418.7, mailed Jun. 1, 2015. cited by applicant
Extended European Search Report issued in EP13793690.2, mailed May 22, 2015. cited by applicant
Extended European Search Report issued in EP13794418.7, mailed Sep. 16, 2015, 12 pages. cited by applicant
Reinders et al., “Systems and Methods for Activating Transducers”, Non-Final Office Action mailed Sep. 30, 2015 for U.S. Appl. No. 14/686,457, 54 pages. cited by applicant
Brewster et al., “Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers”, Non-Final Office Action mailed Oct. 2, 2015 for U.S. Appl. No. 14/686,408, 53 pages. cited by applicant
Goertzen et al., “Systems and Methods for Selecting, Activating, or Selecting and Activating Transducers ”, Office Action for U.S. Appl. No. 13/792,596 mailed Nov. 24, 2015, 64 pages. cited by applicant
Reinders et al., “Systems and Methods for Activating Transducers”, Office Action for U.S. Appl. No. 14/948,924 mailed Dec. 31, 2015, 55 pages. cited by applicant

Primary Examiner: Mahmood; Nadia A

Attorney, Agent or Firm: ROSSI, KIMMS & McDOWELL LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/177,517, filed Feb. 17, 2021, which is a continuation of Ser. No. 16/388,063, filed Apr. 18, 2019, issued as U.S. Pat. No. 11,026,637 on Jun. 8, 2021, which is a continuation of U.S. patent application Ser. No. 15/827,499, filed Nov. 30, 2017, issued as U.S. Pat. No. 10,722,184 on Jul. 28, 2020, which is a continuation-in-part of U.S. patent application Ser. No. 14/942,459, filed Nov. 16, 2015, issued as U.S. Pat. No. 10,368,936 on Aug. 6, 2019, which claims the benefit of U.S. Provisional Application No. 62/080,750, filed Nov. 17, 2014, the entire disclosure of each of the applications cited in this sentence is hereby incorporated herein by reference.

TECHNICAL FIELD

(1) Aspects of this disclosure generally are related to systems and methods for selecting, activating, or selecting and activating transducers, such systems and methods applicable to, among other things, medical systems.

BACKGROUND

(2) Cardiac surgery was initially undertaken using highly invasive open procedures. A sternotomy, which is a type of incision in the center of the chest that separates the sternum was typically employed to allow access to the heart. In the past several decades, more and more cardiac operations are performed using intravascular or percutaneous techniques, where access to inner organs or other tissue is gained via a catheter.

(3) Intravascular or percutaneous surgeries benefit patients by reducing surgery risk, complications and recovery time. However, the use of intravascular or percutaneous technologies also raises some

particular challenges. Medical devices used in intravascular or percutaneous surgery need to be deployed via catheter systems which significantly increase the complexity of the device structure. As well, doctors do not have direct visual contact with the medical devices once the devices are positioned within the body.

(4) One example of where intravascular or percutaneous medical techniques have been employed is in the treatment of a heart disorder called atrial fibrillation. Atrial fibrillation is a disorder in which spurious electrical signals cause an irregular heartbeat. Atrial fibrillation has been treated with open heart methods using a technique known as the “Cox-Maze procedure”. During this procedure, physicians create specific patterns of lesions in the left or right atria to block various paths taken by the spurious electrical signals. Such lesions were originally created using incisions, but are now typically created by ablating the tissue with various techniques including radio-frequency (RF) energy, microwave energy, laser energy and cryogenic techniques. The procedure is performed with a high success rate under the direct vision that is provided in open procedures, but is relatively complex to perform intravascularly or percutaneously because of the difficulty in creating the lesions in the correct locations. Various problems, potentially leading to severe adverse results, may occur if the lesions are placed incorrectly. It is particularly important to know the position of the various transducers which will be creating the lesions relative to cardiac features such as the pulmonary veins and mitral valve. The continuity, transmural and placement of the lesion patterns that are formed can impact the ability to block paths taken within the heart by spurious electrical signals. Other requirements for various ones of the transducers to perform additional functions such as, but not limited to, mapping various anatomical features, mapping electrophysiological activity, sensing tissue characteristics such as impedance and temperature and tissue stimulation can also complicate the operation of the employed medical device.

(5) In this regard, there is a need for improved intra-bodily-cavity transducer-based device systems or control mechanisms thereof with improved performance and reduced complexity as compared to conventional device systems.

(6) In this regard, there is a need for improved intra-bodily-cavity transducer-based device systems or control mechanisms thereof with enhanced graphical path generation capabilities, the graphical path forming an accurate basis for a tissue ablation path.

(7) In this regard, there is a need for improved intra-bodily-cavity transducer-based device systems or control mechanisms thereof with enhanced transducer selection capabilities.

SUMMARY

(8) At least the above-discussed need is addressed and technical solutions are achieved by various embodiments of the present invention. In some embodiments, device systems and methods executed by such systems exhibit enhanced capabilities for the selection or selection and activation of various transducers, which may be located within a bodily cavity, such as an intra-cardiac cavity. In some embodiments, the systems or a portion thereof may be percutaneously or intravascularly delivered to position the various transducers within the bodily cavity. Various ones of the transducers may be activated to distinguish tissue from blood and may be used to deliver positional information of the device relative to various anatomical features in the bodily cavity, such as the pulmonary veins and mitral valve in an atrium. Various ones of the transducers may employ characteristics such as blood flow detection, impedance change detection or deflection force detection to discriminate between blood and tissue. Various ones of the transducers may be used to treat tissue within a bodily cavity. Treatment may include tissue ablation by way of non-limiting example. Various ones of the transducers may be used to stimulate tissue within the bodily cavity. Stimulation can include pacing by way of non-limiting example. Other advantages will become apparent from the teaching herein to those of skill in the art.

(9) In some embodiments, a system may be summarized as including a data processing device system, an input-output device system communicatively connected to the data processing device system, and a memory device system communicatively connected to the data processing device

system and storing a program executable by the data processing device system. The program may include display instructions, input-processing instructions, and graphical representation modification instructions.

(10) The display instructions may be configured to cause the input-output device system to display a graphical representation including at least a plurality of transducer graphical elements, each transducer graphical element of the plurality of transducer graphical elements representative of a respective transducer of a plurality of transducers of a transducer-based device. The graphical representation may include a first spatial relationship between the plurality of transducer graphical elements that is consistent with a second spatial relationship between the plurality of transducers of the transducer-based device.

(11) The input-processing instructions may be configured to cause reception of a set of user input via the input-output device system. The set of user input may include an instruction set to reposition a first transducer graphical element of the plurality of transducer graphical elements in a state in which the first transducer graphical element is located at a first location in the graphical representation and a second transducer graphical element of the plurality of transducer graphical elements is located at a second location in the graphical representation. The second location may be closer to a predetermined location in the graphical representation than the first location.

(12) The graphical representation modification instructions may be configured to cause, in response to conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element, the input-output device system to reposition the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation. According to some embodiments, the second location and the predetermined location are different locations.

(13) In some embodiments, the predetermined location is more centrally located in the graphical representation than the first location, and the repositioning of the first transducer graphical element centralizes the first transducer graphical element in the graphical representation. In some embodiments, the graphical representation modification instructions are configured to cause, in response to the conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element, the input-output device system to reposition the second transducer graphical element from the second location in the graphical representation to a third location in the graphical representation, and the predetermined location is more centrally located in the graphical representation than the third location. In some embodiments, the predetermined location is in a first direction extending from the first location and in a second direction extending from the third location, with the first direction and the second direction being non-parallel directions. In some embodiments, the first location is spaced in the graphical representation from the predetermined location by a first distance and the third location is spaced from the second location by a second distance, with the first distance and the second distance being different distances.

(14) According to some embodiments, the system includes the transducer-based device, with the input-output device system including the transducer-based device. In some embodiments, the transducers of the plurality of transducers are circumferentially arranged about a pole of a structure of the transducer-based device, and a first particular location in the graphical representation corresponds to the pole of the structure. The first particular location in the graphical representation may be closer to the predetermined location than to the first location at least in a state in which the first transducer graphical element is located at the first location. In some embodiments, the first particular location in the graphical representation is located centrally in the graphical representation at least in the state in which the first transducer graphical element is located at the first location. In some embodiments, the graphical representation modification instructions are configured to cause, in response to the conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element, the input-output device system to reconfigure the

graphical representation to cause a second particular location in the graphical representation to correspond to the pole of the structure instead of the first particular location. The second particular location may be located farther from the predetermined location than the first particular location. In some embodiments, at least the second transducer graphical element appears rotated in the graphical representation about a graphical region corresponding to a pole location of the pole of the structure between a transition from the state in which the first transducer graphical element is located at the first location and a state in which the first transducer graphical element is located at the predetermined location upon conclusion of the repositioning of the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation. In some embodiments, at least the second transducer graphical element appears rotated in the graphical representation about a graphical region corresponding to a pole location of the pole of the structure upon conclusion of the repositioning of the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation. In some embodiments, the program includes sampling instructions configured to cause sampling of data by each of one or more transducers of the plurality of transducers of the transducer-based device, and generation instructions configured to cause generation of intra-cardiac information based at least in part on the sampled data. In some embodiments, the one or more transducers include the first transducer, the second transducer, or both the first transducer and the second transducer. The graphical representation may represent the intra-cardiac information among the plurality of transducer graphical elements. The graphical representation modification instructions may be configured to cause, in response to the conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element, the input-output device system to reposition the representation of the intra-cardiac information among the plurality of transducer graphical elements in accordance with the repositioning of the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation.

(15) According to some embodiments, the plurality of transducers are arranged in a three-dimensional distribution, and the plurality of transducer graphical elements are arranged in the graphical representation in a particular spatial distribution representing the three-dimensional distribution distorted onto a two-dimensional plane.

(16) According to some embodiments, the plurality of transducers are arranged in a three-dimensional distribution, and the plurality of transducer graphical elements are arranged in the graphical representation according to a conformal map of the three-dimensional distribution. The conformal map of the three-dimensional distribution may be a transverse Mercator map of the three-dimensional distribution.

(17) According to some embodiments, the program includes storage instructions configured to cause the memory device system to store particular information prior to the reception of the set of user input via the input-output device system. The particular information may be indicative of a location of the predetermined location in the graphical representation.

(18) According to some embodiments, the input-output device system is communicatively connected to the transducer-based device, and the set of user input is a first set of user input. The program may include selection instructions configured to cause reception of a second set of user input via the input-output device system. The second set of user input may include a second instruction set to select, in a state in which the input-output device system has repositioned the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation, a set of transducer graphical elements of the plurality of transducer graphical elements. The program may include activation instructions configured to cause activation, via the input-output device system, of a set of transducers of the plurality of transducers of the transducer-based device in response to reception of the second set of user input including the second instruction set to select the set of transducer graphical elements, the

set of transducers corresponding to the set of transducer graphical elements.

(19) In some embodiments, a transducer activation system may be summarized as including a data processing device system, an input-output device system communicatively connected to the data processing device system, and a memory device system communicatively connected to the data processing device system and storing a program executable by the data processing device system. The program may include display instructions configured to cause the input-output device system to display a graphical representation of at least intra-cardiac information. The program may include input-processing instructions configured to: cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state; and cause reception of motion-based user input via the input-output device system. The program may include path definition instructions configured to cause definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path defined according to a second parameter set associated with the second user input, and an elongate path portion of the graphical path defined according to a path traced by the motion-based user input. The program may include activation instructions configured to cause activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The display instructions may be configured to cause the input-output device system to display the graphical path including each of the first location, the second location, and the elongate path portion among the graphical representation of the intra-cardiac information.

(20) In some embodiments, the program may include sampling instructions configured to cause sampling of data by each of one or more transducers of the transducer-based device system, a portion of the transducer-based device system including the one or more transducers positionable in a cardiac chamber during the sampling. The program may include generation instructions configured to cause generation of the intra-cardiac information based at least in part on the sampled data. The sampled data may be sampled from each of a plurality of locations in the cardiac chamber, and the generation instructions may be configured to cause mapping of each of a plurality of parts of the intra-cardiac information to a respective one of the plurality of locations in the cardiac chamber. The display instructions may be configured to cause the input-output device system to display the plurality of parts of the intra-cardiac information with a first spatial relationship that is consistent with a second spatial relationship between the plurality of locations in the cardiac chamber. The one or more transducers may include a plurality of transducers and the sampling instructions may be configured to cause the sampled data to be sampled concurrently from the plurality of locations in the cardiac chamber.

(21) In some embodiments, the sampled data includes temperature data and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the temperature data or a derivation thereof. In some embodiments, the sampled data includes impedance data or conductivity data and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the impedance data or conductivity data or a derivation thereof. In some embodiments, the sampled data includes pressure data and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the pressure data or a derivation thereof. In some embodiments, the sampled data includes flow data associated with blood flow in the cardiac chamber and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the flow data or a derivation thereof. In some embodiments, the sampled data comprises intra-cardiac electrogram voltage data and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the intra-cardiac

electrogram voltage data or a derivation thereof.

(22) In some embodiments, the graphical representation of the intra-cardiac information may include a map of an interior tissue surface region of a cardiac chamber.

(23) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber, and the display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. In some embodiments, the graphical representation of the intra-cardiac information may include a map of an interior tissue surface region of the cardiac chamber displayed concurrently with the plurality of transducer graphical elements. In some embodiments, the first user input indicates a selection of a first transducer graphical element set including at least a first transducer graphical element of the plurality of transducer graphical elements, and the second user input indicates a selection of a second transducer graphical element set including at least a second transducer graphical element of the plurality of transducer graphical elements other than the first transducer graphical element.

(24) In some embodiments, the first user input indicates a selection of a first transducer graphical element set including at least a first transducer graphical element of the plurality of transducer graphical elements, and the motion-based user input indicates a selection of a second transducer graphical element set including at least a second transducer graphical element of the plurality of transducer graphical elements other than the first transducer graphical element. In some embodiments, the first transducer graphical element set, the second transducer graphical element set, or each of the first and the second transducer graphical element sets includes a group of transducer graphical elements, each group of transducer graphical elements corresponding to a respective one of a plurality of groups of adjacent ones of the transducers. In some embodiments, the activation instructions may be configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each respective transducer corresponding to each transducer graphical element in each of the first transducer graphical element set and the second transducer graphical element set. In some embodiments, the displayed graphical path is represented at least in part by the first transducer graphical element, the second transducer graphical element, and a third transducer graphical element other than the first and the second transducer graphical elements, the third transducer graphical element part of the first transducer graphical element set or the second transducer graphical element set, and the activation instructions may be configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each respective transducer corresponding to the first transducer graphical element, the second transducer graphical element, and the third transducer graphical element.

(25) In some embodiments, the second user input indicates a termination of the definition of the graphical path.

(26) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber. The display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. The display instructions may be configured to cause the input-output device system to display a plurality of between graphical elements concurrently with the transducer graphical elements, the graphical path, and the graphical

representation of the intra-cardiac information, each of the plurality of between graphical element associated with a region of space between transducers of a respective one of a plurality of groups of adjacent ones of the transducers, each region of space not including any transducer. The first user input may indicate a selection of a first between graphical element of the plurality of between graphical elements, and the second user input may indicate a selection of a second between graphical element of the plurality of between graphical elements other than the first between graphical element. The first between graphical element, the second between graphical element, or each of the first and the second between graphical elements may be associated with a region of space that is not associated with any physical part of the transducer-based device system. The first parameter set may include a first display-screen-location associated with the first user input, and the second parameter set may include a second display-screen-location associated with the second user input. The path definition instructions may be configured to cause definition of the first location based at least on an analysis of the first display-screen-location in relation to one or more of the transducer graphical elements, and the path definition instructions may be configured to cause definition of the second location based at least on an analysis of the second display-screen-location in relation to one or more of the transducer graphical elements. In some embodiments, the first location may be a location of a first one of the transducer graphical elements, and the second location may be a location of a second one of the transducer graphical elements.

(27) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber. The display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. The display instructions may be configured to cause the input-output device system to display a plurality of between graphical elements concurrently with the transducer graphical elements, the graphical path, and the graphical representation of the intra-cardiac information, each of the plurality of between graphical elements associated with a region of space between transducers of a respective one of a plurality of groups of adjacent ones of the transducers, each region of space not including any transducer. The path traced by the motion-based user input may indicate at least a selection of at least one of the between graphical elements. The selected at least one of the between graphical elements may be associated with a region of space that is not associated with any physical part of the transducer-based device system. The selected at least one of the between graphical elements may include an elongated portion extending between two respective ends, each of the respective ends located at least proximate a respective one of two of the transducer graphical elements, and the elongate path portion of the graphical path may be provided at least in part by the elongated portion of the selected at least one of the between graphical elements. In some embodiments, the activation instructions may be configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each transducer of the respective one of the plurality of groups of adjacent ones of the transducers corresponding to the selected at least one of the between graphical elements. The activation instructions may be configured to cause concurrent monopolar activation, initiated during or after completion of the definition of the graphical path, of the transducers of the respective one of the plurality of groups of adjacent ones of the transducers corresponding to the selected at least one of the between graphical elements.

(28) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber. The display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of

the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. The first user input may indicate a selection of a first transducer graphical element set including at least a first transducer graphical element of the plurality of transducer graphical elements, and the motion-based user input may indicate a selection of a second transducer graphical element set including at least a second transducer graphical element of the plurality of transducer graphical elements other than the first transducer graphical element. In some embodiments, the path definition instructions may be configured to cause the path traced by the motion-based user input or a portion thereof to snap to the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or the portion thereof being away from the second transducer graphical element but within a predetermined distance from the second transducer graphical element or a part thereof. In some embodiments, the path definition instructions may be configured to cause the elongate path portion of the graphical path to include the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the second transducer graphical element but within a predetermined display region associated with the second transducer graphical element. In some embodiments, the path definition instructions may be configured to cause the elongate path portion of the graphical path to include the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof passing through a predetermined display region associated with the second transducer graphical element, the predetermined display region including at least a part of the second transducer graphical element, and the second transducer graphical element not occupying all of the predetermined display region. In some embodiments, the path definition instructions may be configured to cause the elongate path portion of the graphical path to include the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the second transducer graphical element but within a predetermined distance from the second transducer graphical element or a part thereof. In some embodiments, the path definition instructions may be configured to cause the path traced by the motion-based user input or a portion thereof to snap to a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical element in response to the path traced by the motion-based user input or the portion thereof being away from the particular between graphical element but within a predetermined distance from the particular between graphical element or a part thereof. In some embodiments, the path definition instructions may be configured to cause the elongate path portion of the graphical path to include a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical element in response to the path traced by the motion-based user input or a portion thereof being away from the particular between graphical element but within a predetermined display region associated with the particular between graphical element. In some embodiments, the path definition instructions may be configured to cause the elongate path portion of the graphical path to include a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical element in response to the path traced by the motion-based user input or a portion thereof passing through a predetermined display region associated with the particular between graphical element, the predetermined display region including at least a part of the particular between graphical element, and the particular between graphical element not occupying all of the predetermined display region. In some embodiments, the path definition instructions may be configured to cause the elongate path portion of the graphical path to include a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical element in response to the path traced by the motion-based user input or a portion thereof being away from the particular between graphical element but within a

predetermined distance from the particular between graphical element or a part thereof.

(29) In some embodiments, the path definition instructions may further include graphical path adjustment instructions configured to reduce a size of the elongate path portion in response to a user-based retracing of a portion of the path traced by the motion-based user input.

(30) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber. The display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. In some embodiments, the motion-based user input may indicate a selection of a group of the transducer graphical elements, and the program may further include de-selection instructions configured to deselect at least one transducer graphical element in the group of the transducer graphical elements in response to a user-based retracing of a portion of the path traced by the motion-based user input. In some embodiments, the display instructions may be configured to cause the input-output device system to display a plurality of between graphical elements concurrently with the transducer graphical elements, the graphical path, and the graphical representation of the intra-cardiac information, each of the plurality of between graphical elements associated with a region of space between transducers of a respective one of a plurality of groups of adjacent ones of the transducers, each region of space not including any transducer, and wherein the path traced by the motion-based user input indicates at least a selection of a group of the between graphical elements, and the program may further include de-selection instructions configured to deselect at least one between graphical element in the group of the transducer graphical elements in response to a user-based retracing of a portion of the path traced by the motion-based user input.

(31) In some embodiments, the first user input may include at least engaging the first user input element and the second user input may include at least disengaging the first user input element. In some embodiments, the first user input element may include a keyboard key, a mouse button, or a touch screen. In some embodiments, the first user input element includes a touch screen, and the engaging of the first user input element may include a registering of an initiation of user-contact with the touch screen, and the disengaging the first user input element may include a registering of a cessation of the user-contact with the touch screen.

(32) In some embodiments, the first user input may include at least engaging each of at least two user input elements of the input-output device system and the second user input may include at least disengaging at least one but not all of the at least two user input elements.

(33) In some embodiments, the input-processing instructions may be configured to cause reception of a third user input other than the first and the second user inputs and the motion-based user input, and the path definition instructions may be configured to require reception of the third user input in order to at least enable definition of the elongate path portion of the graphical path according to the path traced by the motion-based user input. In some embodiments, the input-processing instructions may be configured to cause a second user input element to be placed in a respective activated state in response to receiving the third user input, and the path definition instructions may be configured to require that the first user input element and the second user input element be in the respective activated states in order to at least enable definition of the elongate path portion of the graphical path according to the path traced by the motion-based user input. In some embodiments, the input-processing instructions may be configured to cause reception of a fourth user input other than the first, second, and third user inputs. The input-processing instructions may be configured to cause the second user input element to be placed in a respective deactivated state in response to receiving the fourth user input, and the path definition instructions may be configured to cause further definition of the elongate path portion of the graphical path according to the path traced by

the motion-based user input even though the fourth user input has been received and the second user input element has, consequently, been placed in the respective deactivated state.

(34) In some embodiments, the first user input precedes the motion-based user input.

(35) In some embodiments, wherein a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber, and the display instructions are configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. In some embodiments, the display instructions may be configured to cause a change in a visual characteristic of at least one of the transducer graphical elements when the display instructions cause the input-output device system to display the graphical path. The display instructions may be configured to cause a change in a visual characteristic of the at least one of the between graphical elements in response to the reception of the motion-based user input. In some embodiments, each of two or more of the plurality of transducers may include a respective electrode, and the transducer graphical elements corresponding to the two or more of the plurality of transducers each may include a shape that is consistent with a shape of the respective electrode of a corresponding one of the two or more of the plurality of transducers, wherein at least two of the transducer graphical elements corresponding to the two or more of the plurality of transducers comprise different shapes.

(36) In some embodiments, the graphical path may be displayed as including an interrupted form. In some embodiments, the graphical path may be displayed as including a circumferential path that surrounds a region of the graphical representation of the intra-cardiac information. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map indicating a spatial relationship between various anatomical features in a cardiac chamber. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map of values of at least one tissue electrical characteristic sensed by the transducer-based device system in a cardiac chamber. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map of intra-cardiac electrogram values originating from information provided by the transducer-based device system. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map of temperature distribution in a cardiac chamber.

(37) In some embodiments, the input-output device system may include the transducer-based device system. The transducer-based device system may include a catheter-based device. A portion of the catheter-based device may include a structure selectively moveable between a delivery configuration in which the structure is sized to be percutaneously deliverable to a cardiac chamber and a deployed configuration in which the structure has a size too large to be percutaneously deliverable to the cardiac chamber. In some embodiments, the display instructions may be configured to cause the input-output device system to graphically display changes in the intra-cardiac information at least during: a) reception of the first user input, b) reception of the second user input, c) reception of the motion-based user input, or any combination of a), b) and c).

(38) Various systems may include combinations and subsets of all the systems summarized above.

(39) In some embodiments, a transducer activation system may be summarized as including a data processing device system, an input-output device system communicatively connected to the data processing device system, and a memory device system communicatively connected to the data processing device system and storing a program executable by the data processing device system. The data processing device system may be configured by the program at least to: (a) cause the input-output device system to display a graphical representation of at least intra-cardiac

information; (b) cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; (c) cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state; and (d) cause reception of motion-based user input via the input-output device system. The data processing device system may be further configured by the program at least to cause definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path defined according to a second parameter set associated with the second user input, and an elongate path portion of the graphical path defined according to a path traced by the motion-based user input. The data processing device system may be further configured by the program at least to cause activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The data processing device system may be further configured by the program at least to cause the input-output device system to display the graphical path including each of the first location, the second location, and the elongate path portion among the graphical representation of the intra-cardiac information.

(40) In some embodiments, a method may be executed by a data processing device system according to a program stored by a memory device system communicatively connected to the data processing device system, the data processing device system further communicatively connected to an input-output device system. The method may include the data processing device system (a) causing display, via the input-output device system, of a graphical representation including at least a plurality of transducer graphical elements, each transducer graphical element of the plurality of transducer graphical elements representative of a respective transducer of a plurality of transducers of a transducer-based device, and the graphical representation including a first spatial relationship between the plurality of transducer graphical elements that is consistent with a second spatial relationship between the plurality of transducers of the transducer-based device; (b) receiving, via the input-output device system, a set of user input, including an instruction set to reposition a first transducer graphical element of the plurality of transducer graphical elements in a state in which the first transducer graphical element is located at a first location in the graphical representation and a second transducer graphical element of the plurality of transducer graphical elements is located at a second location in the graphical representation, the second location closer to a predetermined location in the graphical representation than the first location; and (c) repositioning, in response to conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element, and via the input-output device system, the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation.

(41) In some embodiments, a transducer activation method may be executed by a data processing device system according to a program stored by a memory device system communicatively connected to the data processing device system, the data processing device system further communicatively connected to an input-output device system. The method may include the data processing device system (a) causing the input-output device system to display a graphical representation of at least intra-cardiac information; (b) causing reception of first user input via the input-output device system and, in response to receiving the first user input, placing a first user input element in an activated state; (c) causing reception of second user input via the input-output device system and, in response to receiving the second user input, placing the first user input element in a deactivated state; and (d) causing reception of motion-based user input via the input-output device system. The method may further include the data processing device system causing definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path

defined according to a second parameter set associated with the second user input, and an elongate path portion of the graphical path defined according to a path traced by the motion-based user input. The method may further include the data processing device system causing activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The method may further include the data processing device system causing the input-output device system to display the graphical path including each of the first location, the second location, and the elongate path portion among the graphical representation of the intra-cardiac information.

(42) In some embodiments, a computer-readable storage medium system may include one or more computer-readable storage mediums storing a program executable by one or more data processing devices of a data processing device system communicatively connected to an input-output device system. The program may include a display module configured to cause the input-output device system to display a graphical representation including at least a plurality of transducer graphical elements, each transducer graphical element of the plurality of transducer graphical elements representative of a respective transducer of a plurality of transducers of a transducer-based device, and the graphical representation including a first spatial relationship between the plurality of transducer graphical elements that is consistent with a second spatial relationship between the plurality of transducers of the transducer-based device. The program may also include an input-processing module configured to cause reception of a set of user input via the input-output device system, the set of user input including an instruction set to reposition a first transducer graphical element of the plurality of transducer graphical elements in a state in which the first transducer graphical element is located at a first location in the graphical representation and a second transducer graphical element of the plurality of transducer graphical elements is located at a second location in the graphical representation, the second location closer to a predetermined location in the graphical representation than the first location. The program may also include a graphical representation modification module configured to cause, in response to conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element, the input-output device system to reposition the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation.

(43) In some embodiments, a computer-readable storage medium system may include one or more computer-readable storage mediums storing a program executable by one or more data processing devices of a data processing device system communicatively connected to an input-output device system. The program may include a display module configured to cause the input-output device system to display a graphical representation of at least intra-cardiac information. The program may include an input-processing module configured to: cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state; and cause reception of motion-based user input via the input-output device system. The program may include a path definition module configured to cause definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path defined according to a second parameter set associated with the second user input, and an elongate path portion of the graphical path defined according to a path traced by the motion-based user input. The program may include an activation module configured to cause activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The display module may be configured to cause the input-output device system to display the graphical path

including each of the first location, the second location, and the elongate path portion among the graphical representation of the intra-cardiac information.

(44) In some embodiments, a transducer activation system may be summarized as including a data processing device system, an input-output device system communicatively connected to the data processing device system, and a memory device system communicatively connected to the data processing device system and storing a program executable by the data processing device system. The program may include display instructions configured to cause the input-output device system to display a graphical representation of at least intra-cardiac information. The program may include input-processing instructions configured to: cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state; and cause reception of motion-based user input via the input-output device system. The program may include path definition instructions configured to cause definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path defined according to a second parameter set associated with the second user input, and at least a third location on the graphical path other than the first location and the second location defined according to a path traced by the motion-based user input. The program may include activation instructions configured to cause activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The display instructions may be configured to cause the input-output device system to display the graphical path including the first location, the second location, and the at least the third location among the graphical representation of the intra-cardiac information.

(45) In some embodiments, the program may further include sampling instructions configured to cause sampling of data by each of one or more transducers of the transducer-based device system, a portion of the transducer-based device system including the one or more transducers positionable in a cardiac chamber during the sampling. The program may include generation instructions configured to cause generation of the intra-cardiac information based at least in part on the sampled data. The sampled data may be sampled from each of a plurality of locations in the cardiac chamber, and the generation instructions may be configured to cause mapping of each of a plurality of parts of the intra-cardiac information to a respective one of the plurality of locations in the cardiac chamber, and the display instructions may be configured to cause the input-output device system to display the plurality of parts of the intra-cardiac information with a first spatial relationship that is consistent with a second spatial relationship between the plurality of locations in the cardiac chamber. The one or more transducers may include a plurality of transducers and the sampling instructions may be configured to cause the sampled data to be sampled concurrently from the plurality of locations in the cardiac chamber. In some embodiments, the sampled data may include temperature data and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the temperature data or a derivation thereof. In some embodiments, the sampled data may include impedance data or conductivity data and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the impedance data or conductivity data or a derivation thereof. In some embodiments, the sampled data may include pressure data and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the pressure data or a derivation thereof. In some embodiments, the sampled data may include flow data associated with blood flow in the cardiac chamber and the graphical representation of the intra-cardiac information includes a graphical representation of at least some of the flow data or a derivation thereof. In some embodiments, the sampled data may include intra-cardiac electrogram voltage data and the

graphical representation of the intra-cardiac information includes a graphical representation of at least some of the intra-cardiac electrogram voltage data or a derivation thereof.

(46) In some embodiments, the graphical representation of the intra-cardiac information may include a map of an interior tissue surface region of a cardiac chamber.

(47) In some embodiments, a portion of the transducer-based device system may include a plurality of transducers positionable in a cardiac chamber, and the display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. In some embodiments, the graphical representation of the intra-cardiac information may include a map of an interior tissue surface region of the cardiac chamber displayed concurrently with the plurality of transducer graphical elements. In some embodiments, the first user input may indicate a selection of a first transducer graphical element set that includes at least a first transducer graphical element of the plurality of transducer graphical elements, and the second user input may indicate a selection of a second transducer graphical element set that includes at least a second transducer graphical element of the plurality of transducer graphical elements other than the first transducer graphical element. In some embodiments, the first user input may indicate a selection of a first transducer graphical element set that includes at least a first transducer graphical element of the plurality of transducer graphical elements, and the motion-based user input may indicate a selection of a second transducer graphical element set that includes at least a second transducer graphical element of the plurality of transducer graphical elements other than the first transducer graphical element. In the first transducer graphical element set, the second transducer graphical element set, or each of the first and the second transducer graphical element sets comprises a group of transducer graphical elements, each group of transducer graphical elements corresponding to a respective one of a plurality of groups of adjacent ones of the transducers. In some embodiments, the activation instructions may be configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each respective transducer corresponding to each transducer graphical element in each of the first transducer graphical element set and the second transducer graphical element set. In some embodiments, the displayed graphical path is represented at least in part by the first transducer graphical element, the second transducer graphical element, and a third transducer graphical element other than the first and the second transducer graphical elements, the third transducer graphical element part of the first transducer graphical element set or the second transducer graphical element set, and the activation instructions may be configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each respective transducer corresponding to the first transducer graphical element, the second transducer graphical element, and the third transducer graphical element.

(48) In some embodiments, the second user input indicates a termination of the definition of the graphical path.

(49) In some embodiments, a portion of the transducer-based device system may include a plurality of transducers positionable in a cardiac chamber, and the display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. In some embodiments, the display instructions may be configured to cause the input-output device system to display a plurality of between graphical elements concurrently with the transducer graphical

elements, the graphical path, and the graphical representation of the intra-cardiac information, each of the plurality of between graphical element associated with a region of space between transducers of a respective one of a plurality of groups of adjacent ones of the transducers, each region of space not including any transducer, and the first user input may indicate a selection of a first between graphical element of the plurality of between graphical elements, and the second user input may indicate a selection of a second between graphical element of the plurality of between graphical elements other than the first between graphical element. The first between graphical element, the second between graphical element, or each of the first and the second between graphical elements may be associated with a region of space that is not associated with any physical part of the transducer-based device system. In some embodiments, the first parameter set includes a first display-screen-location associated with the first user input, and the second parameter set includes a second display-screen-location associated with the second user input. The path definition instructions may be configured to cause definition of the first location based at least on an analysis of the first display-screen-location in relation to one or more of the transducer graphical elements, and the path definition instructions may be configured to cause definition of the second location based at least on an analysis of the second display-screen-location in relation to one or more of the transducer graphical elements. The first location may be a location of a first one of the transducer graphical elements, and the second location may be a location of a second one of the transducer graphical elements.

(50) In some embodiments, a portion of the transducer-based device system may include a plurality of transducers positionable in a cardiac chamber, and the display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. The display instructions may be configured to cause the input-output device system to display a plurality of between graphical elements concurrently with the transducer graphical elements, the graphical path, and the graphical representation of the intra-cardiac information, each of the plurality of between graphical elements associated with a region of space between transducers of a respective one of a plurality of groups of adjacent ones of the transducers, each region of space not including any transducer, and the path traced by the motion-based user input may indicate at least a selection of at least one of the between graphical elements. In some embodiments, the selected at least one of the between graphical elements may be associated with a region of space that is not associated with any physical part of the transducer-based device system. In some embodiments, the at least the third location may be indicated at least in part by the selected at least one of the between graphical elements. In some embodiments, the activation instructions may be configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each transducer of the respective one of the plurality of groups of adjacent ones of the transducers corresponding to the selected at least one of the between graphical elements. The activation instructions may be configured to cause concurrent monopolar activation, initiated during or after completion of the definition of the graphical path, of the transducers of the respective one of the plurality of groups of adjacent ones of the transducers corresponding to the selected at least one of the between graphical elements.

(51) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber, and the display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer

graphical elements consistent with a second spatial relationship between the transducers. The first user input may indicate a selection of a first transducer graphical element set that includes at least a first transducer graphical element of the plurality of transducer graphical elements, and the motion-based user input may indicate a selection of a second transducer graphical element set that includes at least a second transducer graphical element of the plurality of transducer graphical elements other than the first transducer graphical element. In some embodiments, the path definition instructions may be configured to cause the path traced by the motion-based user input or a portion thereof to snap to the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or the portion thereof being away from the second transducer graphical element but within a predetermined distance from the second transducer graphical element or a part thereof, and the second transducer graphical element includes the third location. In some embodiments, the path definition instructions may be configured to cause the graphical path to include the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the second transducer graphical element but within a predetermined display region associated with the second transducer graphical element, and the second transducer graphical element includes the third location. In some embodiments, the path definition instructions may be configured to cause the graphical path to include the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof passing through a predetermined display region associated with the second transducer graphical element, the predetermined display region including at least a part of the second transducer graphical element, and the second transducer graphical element not occupying all of the predetermined display region, and the second transducer graphical element includes the third location. In some embodiments, the path definition instructions may be configured to cause the graphical path to include the second transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the second transducer graphical element but within a predetermined distance from the second transducer graphical element or a part thereof, and the second transducer graphical element includes the third location. In some embodiments, the path definition instructions may be configured to cause the path traced by the motion-based user input or a portion thereof to snap to a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical element in response to the path traced by the motion-based user input or the portion thereof being away from the particular between graphical element but within a predetermined distance from the particular between graphical element or a part thereof, and the particular between graphical element includes the third location. In some embodiments, the path definition instructions may be configured to cause the graphical path to include a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical element in response to the path traced by the motion-based user input or a portion thereof being away from the particular between graphical element but within a predetermined display region associated with the particular between graphical element, and the particular between graphical element includes the third location. In some embodiments, the path definition instructions may be configured to cause the graphical path to include a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical element in response to the path traced by the motion-based user input or a portion thereof passing through a predetermined display region associated with the particular between graphical element, the predetermined display region including at least a part of the particular between graphical element, and the particular between graphical element not occupying all of the predetermined display region, and the particular between graphical element includes the third location. In some embodiments, the path definition instructions may be configured to cause the graphical path to include a particular between graphical element of the at least one of the between graphical elements or a portion of the particular between graphical

element in response to the path traced by the motion-based user input or a portion thereof being away from the particular between graphical element but within a predetermined distance from the particular between graphical element or a part thereof, and the particular between graphical element includes the third location.

(52) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber, and the display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. In some embodiments, the motion-based user input may indicate a selection of a group of the transducer graphical elements, and the program further includes de-selection instructions configured to deselect at least one transducer graphical element in the group of the transducer graphical elements in response to a user-based retracing of a portion of the path traced by the motion-based user input. In some embodiments, the display instructions may be configured to cause the input-output device system to display a plurality of between graphical elements concurrently with the transducer graphical elements, the graphical path, and the graphical representation of the intra-cardiac information, each of the plurality of between graphical elements associated with a region of space between transducers of a respective one of a plurality of groups of adjacent ones of the transducers, each region of space not including any transducer. The path traced by the motion-based user input may indicate at least a selection of a group of the between graphical elements, and the program may further include de-selection instructions configured to deselect at least one between graphical element in the group of the between graphical elements in response to a user-based retracing of a portion of the path traced by the motion-based user input.

(53) In some embodiments, the first user input may include at least engaging the first user input element and the second user input may include at least disengaging the first user input element. In some embodiments, the first user input element may include a keyboard key, a mouse button, or a touch screen. In some embodiments, the first user input element may include a touch screen, and the engaging of the first user input element includes a registering of an initiation of user-contact with the touch screen, and the disengaging the first user input element includes a registering of a cessation of the user-contact with the touch screen. In some embodiments, the first user input may include at least engaging each of at least two user input elements of the input-output device system and the second user input may include at least disengaging at least one but not all of the at least two user input elements.

(54) In some embodiments, the input-processing instructions may be configured to cause reception of a third user input other than the first and the second user input and the motion-based user input, and the path definition instructions may be configured to require reception of the third user input in order to at least enable definition of an elongate path portion of the graphical path according to the path traced by the motion-based user input, the elongate path portion including the third location. The input-processing instructions may be configured to cause a second user input element to be placed in a respective activated state in response to receiving the third user input, and the path definition instructions may be configured to require that the first user input element and the second user input element be in the respective activated states in order to at least enable definition of the elongate path portion of the graphical path according to the path traced by the motion-based user input. In some embodiments, the input-processing instructions may be configured to cause reception of a fourth user input other than the first, second, and third user inputs. The input-processing instructions may be configured to cause the second user input element to be placed in a respective deactivated state in response to receiving the fourth user input, and the path definition instructions may be configured to cause further definition of the elongate path portion of the

graphical path according to the path traced by the motion-based user input even though the fourth user input has been received and the second user input element has, consequently, been placed in the respective deactivated state.

(55) In some embodiments, the first user input precedes the motion-based user input.

(56) In some embodiments, a portion of the transducer-based device system includes a plurality of transducers positionable in a cardiac chamber, and the display instructions may be configured to cause the input-output device system to display a plurality of transducer graphical elements concurrently with the graphical path and the graphical representation of the intra-cardiac information, each of the transducer graphical elements corresponding to at least part of a respective one of the plurality of transducers, a first spatial relationship between the displayed transducer graphical elements consistent with a second spatial relationship between the transducers. In some embodiments, the display instructions may be configured to cause a change in a visual characteristic of at least one of the transducer graphical elements when the display instructions cause the input-output device system to display the graphical path. The display instructions may be configured to cause a change in a visual characteristic of the at least one of the between graphical elements in response to the reception of the motion-based user input. In some embodiments, each of two or more of the plurality of transducers may include a respective electrode, and the transducer graphical elements corresponding to the two or more of the plurality of transducers each include a shape that is consistent with a shape of the respective electrode of a corresponding one of the two or more of the plurality of transducers. At least two of the transducer graphical elements corresponding to the two or more of the plurality of transducers may include different shapes.

(57) In some embodiments, the graphical path may be displayed as including an interrupted form. In some embodiments, the graphical path may be displayed as including a circumferential path that surrounds a region of the graphical representation of the intra-cardiac information. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map indicating a spatial relationship between various anatomical features in a cardiac chamber. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map of values of at least one tissue electrical characteristic sensed by the transducer-based device system in a cardiac chamber. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map of intra-cardiac electrogram values originating from information provided by the transducer-based device system. In some embodiments, the graphical representation of the intra-cardiac information may include a graphical representation of at least a map of temperature distribution in a cardiac chamber.

(58) In some embodiments, the input-output device system may include the transducer-based device system. The transducer-based device system may include a catheter-based device. A portion of the catheter-based device may include a structure selectively moveable between a delivery configuration in which the structure is sized to be percutaneously deliverable to a cardiac chamber and a deployed configuration in which the structure has a size too large to be percutaneously deliverable to the cardiac chamber.

(59) In some embodiments, an elongate path portion of the graphical path is defined according to a path traced by the motion-based user input, the at least the third location located on the elongated path portion of the path. In some embodiments, the first location and the second location are the same location. In some embodiments, the display instructions may be configured to cause the input-output device system to graphically display changes in the intra-cardiac information at least during: a) reception of the first user input, b) reception of the second user input, c) reception of the motion-based user input, or any combination of a), b) and c).

(60) In some embodiments, a transducer activation system may be summarized as including a data processing device system, an input-output device system communicatively connected to the data processing device system, and a memory device system communicatively connected to the data

processing device system and storing a program executable by the data processing device system. The data processing device system may be configured by the program at least to: (a) cause the input-output device system to display a graphical representation of at least intra-cardiac information; (b) cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; (c) cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state; and (d) cause reception of motion-based user input via the input-output device system. The data processing device system may be further configured by the program at least to cause definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path defined according to a second parameter set associated with the second user input, and at least a third location on the graphical path other than the first location and the second location defined according to a path traced by the motion-based user input. The data processing device system may be further configured by the program at least to cause activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The data processing device system may be further configured by the program at least to cause the input-output device system to display the graphical path including the first location, the second location, and the at least the third location among the graphical representation of the intra-cardiac information.

(61) In some embodiments, a transducer activation method may be executed by a data processing device system according to a program stored by a memory device system communicatively connected to the data processing device system, the data processing device system further communicatively connected to an input-output device system. The method may include the data processing device system (a) causing the input-output device system to display a graphical representation of at least intra-cardiac information; (b) causing reception of first user input via the input-output device system and, in response to receiving the first user input, placing a first user input element in an activated state; (c) causing reception of second user input via the input-output device system and, in response to receiving the second user input, placing the first user input element in a deactivated state; and (d) causing reception of motion-based user input via the input-output device system. The method may include the data processing device system causing definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path defined according to a second parameter set associated with the second user input, and at least a third location on the graphical path other than the first location and the second location defined according to a path traced by the motion-based user input. The method may include the data processing device system causing activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The method may include the data processing device system causing the input-output device system to display the graphical path including the first location, the second location, and the at least the third location among the graphical representation of the intra-cardiac information.

(62) In some embodiments, a computer-readable storage medium system may include one or more computer-readable storage mediums storing a program executable by one or more data processing devices of a data processing device system communicatively connected to an input-output device system. The program may include a display module configured to cause the input-output device system to display a graphical representation of at least intra-cardiac information. The program may include an input-processing module configured to: cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; cause reception of second user input via the input-output device

system and, in response to receiving the second user input, place the first user input element in a deactivated state; and cause reception of motion-based user input via the input-output device system. The program may include a path definition module configured to cause definition of a graphical path including a first location on the graphical path defined according to a first parameter set associated with the first user input, a second location on the graphical path defined according to a second parameter set associated with the second user input, and at least a third location on the graphical path other than the first location and the second location defined according to a path traced by the motion-based user input. The program may include an activation module configured to cause activation of a transducer-based device system, initiated during or after completion of the definition of the graphical path, to transmit energy sufficient for tissue ablation along an ablation path corresponding to the graphical path. The display module may be configured to cause the input-output device system to display the graphical path including the first location, the second location, and the at least the third location among the graphical representation of the intra-cardiac information.

(63) In some embodiments, a graphical path display device system may be summarized as including a data processing device system, an input-output device system communicatively connected to the data processing device system, and a memory device system communicatively connected to the data processing device system and storing a program executable by the data processing device system. The program may include input-processing instructions configured to: cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; cause reception of motion-based user input via the input-output device system; and cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state. The program may include path definition instructions configured to cause definition of a graphical path including a plurality of graphical-path-elements, the path definition instructions configured to cause initiation of the definition of the graphical path in response to receiving the first user input, to cause generation of an interim-definition of the graphical path according to a path traced by the motion-based user input, and to cause conclusion of the definition of the graphical path in response to receiving the second user input, each of the respective graphical-path-elements associated with a respective display region including at least a portion of the respective graphical-path-element, but the respective graphical-path-element not occupying all of the respective display region. The path definition instructions may be configured to cause the interim-definition of the graphical path to be generated to identify the plurality of graphical-path-elements as those whose display regions have been passed through by at least some of the path traced by the motion-based user input. The program may include display instructions configured to cause the input-output device system to display, prior to the conclusion of the definition of the graphical path, a graphical representation of the graphical path including the identified plurality of graphical-path-elements consistent with the interim-definition of the graphical path. The path definition instructions may be configured to cause generation of a modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path to exclude at least one of the identified plurality of graphical-path-elements in response to a user-based retracing of a portion of the path traced by the motion-based user input, the excluded at least one of the identified plurality of graphical-path-elements being those whose display regions have been passed through by the retracing of the portion of the path traced by the motion-based user input. The display instructions may be configured to cause the input-output device system to change the display of the graphical representation of the graphical path to account for the excluded at least one of the identified plurality of graphical-path-elements consistent with the modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path.

(64) In some embodiments, the portion of the path traced by the motion-based user input and the

portion of the path retraced by the motion-based user input pass through the same ones of the display regions. In some embodiments, the portion of the path traced by the motion-based user input and the portion of the path retraced by the motion-based user input pass through the same ones of the display regions in a reverse order that the same ones of the display regions were passed through during the interim-definition of the graphical path.

(65) In some embodiments, a graphical path display device system may be summarized as including a data processing device system, an input-output device system communicatively connected to the data processing device system, and a memory device system communicatively connected to the data processing device system and storing a program executable by the data processing device system. The data processing device system may be configured by the program at least to: cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; cause reception of motion-based user input via the input-output device system; and cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state. The data processing device system may be further configured by the program at least to: cause definition of a graphical path including a plurality of graphical-path-elements; cause initiation of the definition of the graphical path in response to receiving the first user input, to cause generation of an interim-definition of the graphical path according to a path traced by the motion-based user input; and cause conclusion of the definition of the graphical path in response to receiving the second user input. Each of the respective graphical-path-elements may be associated with a respective display region including at least a portion of the respective graphical-path-element, but the respective graphical-path-element not occupying all of the respective display region. The data processing device system may be further configured by the program at least to cause the interim-definition of the graphical path to be generated to identify the plurality of graphical-path-elements as those whose display regions have been passed through by at least some of the path traced by the motion-based user input. The data processing device system may be further configured by the program at least to cause the input-output device system to display, prior to the conclusion of the definition of the graphical path, a graphical representation of the graphical path including the identified plurality of graphical-path-elements consistent with the interim-definition of the graphical path. The data processing device system may be further configured by the program at least to cause generation of a modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path to exclude at least one of the identified plurality of graphical-path-elements in response to a user-based retracing of a portion of the path traced by the motion-based user input. The excluded at least one of the identified plurality of graphical-path-elements may be those whose display regions have been passed through by the retracing of the portion of the path traced by the motion-based user input. The data processing device system may be further configured by the program at least to cause the input-output device system to change the display of the graphical representation of the graphical path to account for the excluded at least one of the identified plurality of graphical-path-elements consistent with the modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path.

(66) In some embodiments, a graphical path display method may be executed by a data processing device system according to a program stored by a memory device system communicatively connected to the data processing device system, the data processing device system further communicatively connected to an input-output device system. The method may include the data processing device system receiving first user input via the input-output device system and, in response to receiving the first user input, placing a first user input element in an activated state; receiving motion-based user input via the input-output device system; and receiving second user input via the input-output device system and, in response to receiving the second user input, placing the first user input element in a deactivated state. The method may further include the data

processing device system causing definition of a graphical path including a plurality of graphical-path-elements; causing initiation of the definition of the graphical path in response to receiving the first user input, to cause generation of an interim-definition of the graphical path according to a path traced by the motion-based user input; and causing conclusion of the definition of the graphical path in response to receiving the second user input. Each of the respective graphical-path-elements may be associated with a respective display region including at least a portion of the respective graphical-path-element, but the respective graphical-path-element not occupying all of the respective display region. The method may further include the data processing device system causing the interim-definition of the graphical path to be generated to identify the plurality of graphical-path-elements as those whose display regions have been passed through by at least some of the path traced by the motion-based user input. The method may further include the data processing device system causing the input-output device system to display, prior to the conclusion of the definition of the graphical path, a graphical representation of the graphical path including the identified plurality of graphical-path-elements consistent with the interim-definition of the graphical path. The method may further include the data processing device system causing generation of a modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path to exclude at least one of the identified plurality of graphical-path-elements in response to a user-based retracing of a portion of the path traced by the motion-based user input. The excluded at least one of the identified plurality of graphical-path-elements may be those whose display regions have been passed through by the retracing of the portion of the path traced by the motion-based user input. The method may further include the data processing device system causing the input-output device system to change the display of the graphical representation of the graphical path to account for the excluded at least one of the identified plurality of graphical-path-elements consistent with the modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path.

(67) In some embodiments, a computer-readable storage medium system may include one or more computer-readable storage mediums storing a program executable by one or more data processing devices of a data processing device system communicatively connected to an input-output device system. The program may include an input-processing module configured to: cause reception of first user input via the input-output device system and, in response to receiving the first user input, place a first user input element in an activated state; cause reception of motion-based user input via the input-output device system; and cause reception of second user input via the input-output device system and, in response to receiving the second user input, place the first user input element in a deactivated state. The program may include a path definition module configured to cause definition of a graphical path including a plurality of graphical-path-elements, the path definition module configured to cause initiation of the definition of the graphical path in response to receiving the first user input, to cause generation of an interim-definition of the graphical path according to a path traced by the motion-based user input, and to cause conclusion of the definition of the graphical path in response to receiving the second user input, each of the respective graphical-path-elements associated with a respective display region including at least a portion of the respective graphical-path-element, but the respective graphical-path-element not occupying all of the respective display region. The path definition module may be configured to cause the interim-definition of the graphical path to be generated to identify the plurality of graphical-path-elements as those whose display regions have been passed through by at least some of the path traced by the motion-based user input. The program may include a display module configured to cause the input-output device system to display, prior to the conclusion of the definition of the graphical path, a graphical representation of the graphical path including the identified plurality of graphical-path-elements consistent with the interim-definition of the graphical path. The path definition module may be configured to cause generation of a modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path to exclude at least one of the identified

plurality of graphical-path-elements in response to a user-based retracing of a portion of the path traced by the motion-based user input, the excluded at least one of the identified plurality of graphical-path-elements being those whose display regions have been passed through by the retracing of the portion of the path traced by the motion-based user input. The display module may be configured to cause the input-output device system to change the display of the graphical representation of the graphical path to account for the excluded at least one of the identified plurality of graphical-path-elements consistent with the modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path.

(68) Various systems may include combinations and subsets of all the systems summarized above or otherwise described herein.

(69) Any of the features of any of the methods discussed herein may be combined with any of the other features of any of the methods discussed herein. In addition, a computer program product may be provided that comprises program code portions for performing some or all of any of the methods and associated features thereof described herein, when the computer program product is executed by a computer or other computing device or device system. Such a computer program product may be stored on one or more computer-readable storage mediums.

(70) In some embodiments, each of any or all of the computer-readable storage mediums or medium systems described herein is a non-transitory computer-readable storage medium or medium system including one or more non-transitory computer-readable storage mediums storing the respective program(s).

(71) Further, any or all of the methods and associated features thereof discussed herein may be implemented by all or part of a device system or apparatus, such as any of those described herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) It is to be understood that the attached drawings are for purposes of illustrating aspects of various embodiments and may include elements that are not to scale.

(2) FIG. 1 includes a schematic representation of a transducer-activation system according to various example embodiments, the transducer-activation system including a data processing device system, an input-output device system, and a memory device system.

(3) FIG. 2 includes a cutaway diagram of a heart showing a transducer-based device percutaneously placed in a left atrium of the heart according to various example embodiments.

(4) FIG. 3A includes a partially schematic representation of a medical system according to various example embodiments, the medical system including a data processing device system, an input-output device system, a memory device system, and a transducer-based device having a plurality of transducers and an expandable structure shown in a delivery or unexpanded configuration.

(5) FIG. 3B includes a portion of the medical system of FIG. 3A as viewed from a different viewing direction.

(6) FIG. 3C includes the representation of the medical system of FIGS. 3A and 3B with the expandable structure shown in a deployed or expanded configuration.

(7) FIG. 3D includes a portion of the medical system of FIG. 3C as viewed from a different viewing direction.

(8) FIG. 4 includes a schematic representation of a transducer-based device that includes a flexible circuit structure according to various example embodiments.

(9) FIG. 5A includes a graphical interface providing a graphical representation according to various example embodiments, a depiction of at least a portion of a transducer-based device including a plurality of transducer graphical elements depicted among the graphical representation.

(10) FIG. 5B includes the graphical interface of FIG. 5A with the portion of the transducer-based

device depicted as viewed from a different viewing direction than that shown in FIG. 5A.

(11) FIG. 5C includes the graphical representation provided by the graphical interface of FIG. 5A with the addition of various between graphical elements positioned between various ones of the transducer graphical elements.

(12) FIG. 5D includes the graphical representation provided by the graphical interface of FIG. 5C but with the portion of the transducer-based device depicted as viewed from a different viewing direction than that shown in FIG. 5C.

(13) FIG. 5E includes the graphical representation provided by the graphical interface of FIGS. 5C and 5D depicted with one particular form of two-dimensional representation in accordance with various example embodiments.

(14) FIG. 5F includes the graphical representation provided by the graphical interface of FIGS. 5A and 5B depicted with another particular form of two-dimensional representation in accordance with various example embodiments.

(15) FIG. 5G includes the graphical representation provided by the graphical interface of FIG. 5E with the addition of various intra-cardiac information including various regions determined on the basis of flow data.

(16) FIG. 5H includes the graphical representation provided by the graphical interface of FIG. 5E with the addition of various intra-cardiac information including various regions determined on the basis of electrical data.

(17) FIGS. 5I, 5J and 5K include the graphical representation provided by the graphical interface of FIG. 5E including changes in intra-cardiac information occurring during three successive times during a display period.

(18) FIGS. 5L, 5M, 5N, 5O, 5P and 5Q show a sequence in which a plurality of portions of a graphical path are selected according to the sequence, each selected portion of the graphical path indicating a selection of at least one graphical element or at least one graphical-path-element.

(19) FIG. 5R includes the graphical representation provided by the graphical interface of FIG. 5Q but depicted three-dimensionally according to various example embodiments.

(20) FIG. 5S shows a selection of particular transducer graphical elements made in response of a first motion-based user input according to various example embodiments.

(21) FIG. 5T shows a selection of the particular transducer graphical elements of FIG. 5S but selected in response of a second motion-based user input according to various example embodiments.

(22) FIG. 5U shows a set of graphical elements or graphical-path-elements selected according to an interim-path definition of a graphical path.

(23) FIG. 5V shows at least some of the graphical elements or graphical-path-elements selected in FIG. 5U deselected according to a modified-interim-path definition of the graphical path.

(24) FIG. 5W shows each of the graphical elements or graphical-path-elements selected in FIG. 5U remaining selected when a portion of the graphical path is not retraced through the respective display regions of various ones of the graphical elements or graphical-path-elements.

(25) FIG. 5X illustrates the graphical representation provided by the graphical interface of FIG. 5Q but with change in visual characteristic set of the selected graphical elements or selected graphical-path-elements.

(26) FIG. 6A includes a block diagram of a method for activating transducers of a transducer-based device according to some example embodiments.

(27) FIG. 6B includes an exploded view of some of the blocks of the block diagram of FIG. 6A according to some example embodiments.

(28) FIG. 6C includes an exploded view of some of the blocks of FIG. 6A according to some example embodiments.

(29) FIG. 6D includes an exploded view of some of the blocks of FIG. 6A according to some example embodiments.

(30) FIG. 6E includes an exploded view of some of the blocks of FIG. 6A according to some example embodiments.

(31) FIG. 6F includes an exploded view of some of the blocks of FIG. 6A according to some example embodiments.

(32) FIG. 7 includes a block diagram of a method for graphical element repositioning according to some example embodiments.

(33) FIGS. 8A-8C illustrate a graphical representation according to various example embodiments illustrating at least some aspects of the method of FIG. 7, a depiction of at least a portion of a transducer-based device including a plurality of transducer graphical elements depicted among the graphical representation of FIGS. 8A-8C.

DETAILED DESCRIPTION

(34) In the following description, certain specific details are set forth in order to provide a thorough understanding of various embodiments of the invention. However, one skilled in the art will understand that the invention may be practiced at a more general level without these details. In other instances, well-known structures have not been shown or described in detail to avoid unnecessarily obscuring descriptions of various embodiments of the invention.

(35) Any reference throughout this specification to “one embodiment” or “an embodiment” or “an example embodiment” or “an illustrated embodiment” or “a particular embodiment” and the like means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, any appearance of the phrase “in one embodiment” or “in an embodiment” or “in an example embodiment” or “in this illustrated embodiment” or “in this particular embodiment” or the like in this specification is not necessarily all referring to one embodiment or a same embodiment. Furthermore, the particular features, structures or characteristics of different embodiments may be combined in any suitable manner to form one or more other embodiments.

(36) It is noted that, unless otherwise explicitly noted or required by context, the word “or” is used in this disclosure in a non-exclusive sense. In addition, unless otherwise explicitly noted or required by context, the word “set” is intended to mean one or more, and the word “subset” is intended to mean a set having the same or fewer elements of those present in the subset's parent or superset.

(37) Further, the phrase “at least” is used herein at times to emphasize the possibility that other elements can exist besides those explicitly listed. However, unless otherwise explicitly noted (such as by the use of the term “only”) or required by context, non-usage herein of the phrase “at least” does not exclude the possibility that other elements can exist besides those explicitly listed. For example, the phrase, “activation of at least transducer A” includes activation of transducer A by itself, as well as activation of transducer A and activation of one or more other additional elements besides transducer A. In the same manner, the phrase, “activation of transducer A” includes activation of transducer A by itself, as well as activation of transducer A and activation of one or more other additional elements besides transducer A. However, the phrase, “activation of only transducer A” includes only activation of transducer A, and excludes activation of any other transducers besides transducer A.

(38) The word “ablation” as used in this disclosure should be understood to include any disruption to certain properties of tissue. Most commonly, the disruption is to the electrical conductivity and is achieved by transferring thermal energy, which can be generated with resistive or radio-frequency (RF) techniques for example. Other properties, such as mechanical or chemical, and other means of disruption, such as optical, are included when the term “ablation” is used.

(39) The word “fluid” as used in this disclosure should be understood to include any fluid that can be contained within a bodily cavity or can flow into or out of, or both into and out of a bodily cavity via one or more bodily openings positioned in fluid communication with the bodily cavity. In the case of cardiac applications, fluid such as blood will flow into and out of various intra-

cardiac cavities (e.g., a left atrium or right atrium)

(40) The words “bodily opening” as used in this disclosure should be understood to include a naturally occurring bodily opening or channel or lumen; a bodily opening or channel or lumen formed by an instrument or tool using techniques that can include, but are not limited to, mechanical, thermal, electrical, chemical, and exposure or illumination techniques; a bodily opening or channel or lumen formed by trauma to a body; or various combinations of one or more of the above. Various elements having respective openings, lumens or channels and positioned within the bodily opening (e.g., a catheter sheath) may be present in various embodiments. These elements may provide a passageway through a bodily opening for various devices employed in various embodiments.

(41) The words “bodily cavity” as used in this disclosure should be understood to mean a cavity in a body. The bodily cavity may be a cavity or chamber provided in a bodily organ (e.g., an intra-cardiac cavity of a heart).

(42) The word “tissue” as used in some embodiments in this disclosure should be understood to include any surface-forming tissue that is used to form a surface of a body or a surface within a bodily cavity, a surface of an anatomical feature or a surface of a feature associated with a bodily opening positioned in fluid communication with the bodily cavity. The tissue can include part or all of a tissue wall or membrane that defines a surface of the bodily cavity. In this regard, the tissue can form an interior surface of the cavity that surrounds a fluid within the cavity. In the case of cardiac applications, tissue can include tissue used to form an interior surface of an intra-cardiac cavity such as a left atrium or right atrium. In some embodiments, the word tissue can refer to a tissue having fluidic properties (e.g., blood) and may be referred to as fluidic tissue.

(43) The term “transducer” as used in this disclosure should be interpreted broadly as any device capable of distinguishing between fluid and tissue, sensing temperature, creating heat, ablating tissue, sensing, sampling or measuring electrical activity of a tissue surface (e.g., sensing, sampling or measuring intra-cardiac electrograms, or sensing, sampling or measuring intra-cardiac voltage data), stimulating tissue, or any combination thereof. A transducer can convert input energy of one form into output energy of another form. Without limitation, a transducer can include an electrode that functions as, or as part of, a sensing device included in the transducer, an energy delivery device included in the transducer, or both a sensing device and an energy delivery device included in the transducer. A transducer may be constructed from several parts, which may be discrete components or may be integrally formed. In this regard, although transducers, electrodes, or both transducers and electrodes are referenced with respect to various embodiments, it is understood that other transducers or transducer elements may be employed in other embodiments. It is understood that a reference to a particular transducer in various embodiments may also imply a reference to an electrode, as an electrode may be part of the transducer as shown, e.g., with FIG. 4 discussed below.

(44) The term “activation” as used in this disclosure should be interpreted broadly as making active a particular function as related to various transducers disclosed in this disclosure. Particular functions may include, but are not limited to, tissue ablation, sensing, sampling or measuring electrophysiological activity (e.g., sensing, sampling or measuring intra-cardiac electrogram information or sensing, sampling or measuring intra-cardiac voltage data), sensing, sampling or measuring temperature and sensing, sampling or measuring electrical characteristics (e.g., tissue impedance or tissue conductivity). For example, in some embodiments, activation of a tissue ablation function of a particular transducer is initiated by causing energy sufficient for tissue ablation from an energy source device system to be delivered to the particular transducer.

Alternatively, in this example, the activation can be deemed to be initiated when the particular transducer causes a temperature sufficient for the tissue ablation due to the energy provided by the energy source device system. Also in this example, the activation can last for a duration of time concluding when the ablation function is no longer active, such as when energy sufficient for the

tissue ablation is no longer provided to the particular transducer. Alternatively, in this example, the activation period can be deemed to be concluded when the temperature caused by the particular transducer is below the temperature sufficient for the tissue ablation. In some contexts, however, the word “activation” can merely refer to the initiation of the activating of a particular function, as opposed to referring to both the initiation of the activating of the particular function and the subsequent duration in which the particular function is active. In these contexts, the phrase or a phrase similar to “activation initiation” may be used.

(45) The term “program” in this disclosure should be interpreted as a set of instructions or modules that can be executed by one or more components in a system, such a controller system or data processing device system, in order to cause the system to perform one or more operations. The set of instructions or modules can be stored by any kind of memory device, such as those described subsequently with respect to the memory device system **130** or **330** shown in FIGS. **1** and **3**, respectively. In addition, this disclosure sometimes describes that the instructions or modules of a program are configured to cause the performance of a function. The phrase “configured to” in this context is intended to include at least (a) instructions or modules that are presently in a form executable by one or more data processing devices to cause performance of the function (e.g., in the case where the instructions or modules are in a compiled and unencrypted form ready for execution), and (b) instructions or modules that are presently in a form not executable by the one or more data processing devices, but could be translated into the form executable by the one or more data processing devices to cause performance of the function (e.g., in the case where the instructions or modules are encrypted in a non-executable manner, but through performance of a decryption process, would be translated into a form ready for execution). The word “module” can be defined as a set of instructions. In some instances, this disclosure describes that the instructions or modules of a program perform a function. Such descriptions should be deemed to be equivalent to describing that the instructions or modules are configured to cause the performance of the function.

(46) Each of the phrases “derived from” or “derivation of” or “derivation thereof” or the like is intended to mean to come from at least some part of a source, be created from at least some part of a source, or be developed as a result of a process in which at least some part of a source forms an input. For example, a data set derived from some particular portion of data may include at least some part of the particular portion of data, or may be created from at least part of the particular portion of data, or may be developed in response to a data manipulation process in which at least part of the particular portion of data forms an input. In some embodiments, a data set may be derived from a subset of the particular portion of data. In some embodiments, the particular portion of data is analyzed to identify a particular subset of the particular portion of data, and a data set is derived from the subset. In various ones of these embodiments, the subset may include some, but not all, of the particular portion of data. In some embodiments, changes in least one part of a particular portion of data may result in changes in a data set derived at least in part from the particular portion of data.

(47) In this regard, each of the phrases “derived from” or “derivation of” or “derivation thereof” or the like is used herein at times merely to emphasize the possibility that such data or information may be modified or subject to one or more operations. For example, if a device generates first data for display, the process of converting the generated first data into a format capable of being displayed may alter the first data. This altered form of the first data may be considered a derivative or derivation of the first data. For instance, the first data may be a one-dimensional array of numbers, but the display of the first data may be a color-coded bar chart representing the numbers in the array. For another example, if the above-mentioned first data is transmitted over a network, the process of converting the first data into a format acceptable for network transmission or understanding by a receiving device may alter the first data. As before, this altered form of the first data may be considered a derivative or derivation of the first data. For yet another example,

generated first data may undergo a mathematical operation, a scaling, or a combining with other data to generate other data that may be considered derived from the first data. In this regard, it can be seen that data is commonly changing in form or being combined with other data throughout its movement through one or more data processing device systems, and any reference to information or data herein is intended to include these and like changes, regardless of whether or not the phrase “derived from” or “derivation of” or “derivation thereof” or the like is used in reference to the information or data. As indicated above, usage of the phrase “derived from” or “derivation of” or “derivation thereof” or the like merely emphasizes the possibility of such changes. Accordingly, the addition of or deletion of the phrase “derived from” or “derivation of” or “derivation thereof” or the like should have no impact on the interpretation of the respective data or information. For example, the above-discussed color-coded bar chart may be considered a derivative of the respective first data or may be considered the respective first data itself.

(48) The word “device” and the phrase “device system” both are intended to include one or more physical devices or sub-devices (e.g., pieces of equipment) that interact to perform one or more functions, regardless of whether such devices or sub-devices are located within a same housing or different housings. In this regard, for example, this disclosure sometimes refers to a “catheter device”, but such catheter device could equivalently be referred to as a “catheter device system”. The word “device” may equivalently be referred to as a “device system”.

(49) In some contexts, the term “adjacent” is used in this disclosure to refer to objects that do not have another substantially similar object between them. For example, object A and object B could be considered adjacent if they contact each other (and, thus, it could be considered that no other object is between them), or if they do not contact each other, but no other object that is substantially similar to object A, object B, or both objects A and B, depending on context, is between them.

(50) Further, the phrase “in response to” may be is used in this disclosure. For example, this phrase might be used in the following context, where an event A occurs in response to the occurrence of an event B. In this regard, such phrase can include, for example, that at least the occurrence of the event B causes or triggers the event A.

(51) Further, the phrase “graphical representation” used herein is intended to include a visual representation presented via a display device and may include computer-generated text, graphics, animations, or one or more combinations thereof, which may include one or more visual representations originally generated, at least in part, by an image-capture device, such as fluoroscopy images, CT scan images, MRI images, etc.

(52) Further still, example methods are described herein with respect to FIG. 6. Such figures are described to include blocks associated with computer-executable instructions. It should be noted that the respective instructions associated with any such blocks herein need not be separate instructions and may be combined with other instructions to form a combined instruction set. The same set of instructions may be associated with more than one block. In this regard, the block arrangement shown in each of the method figures herein is not limited to an actual structure of any program or set of instructions or required ordering of method tasks, and such method figures, according to some embodiments, merely illustrate the tasks that instructions are configured to perform, for example, upon execution by a data processing device system in conjunction with interactions with one or more other devices or device systems.

(53) FIG. 1 schematically illustrates a special purpose transducer selection, activation, or selection and activation system **100** that may be employed to at least select, control, activate, or monitor a function or activation of one or more transducers, according to some embodiments. The system **100** includes a data processing device system **110**, an input-output device system **120**, and a processor-accessible memory device system **130**. The processor-accessible memory device system **130** and the input-output device system **120** are communicatively connected to the data processing device system **110**.

(54) The data processing device system **110** includes one or more data processing devices that implement or execute, in conjunction with other devices, such as those in the system **100**, the methods of various embodiments, including the example methods of FIG. **6** described herein. Each of the phrases “data processing device”, “data processor”, “processor”, and “computer” is intended to include any data processing device, such as a central processing unit (CPU), a desktop computer, a laptop computer, a mainframe computer, a tablet computer, a personal digital assistant, a cellular phone, and any other device for processing data, managing data, or handling data, whether implemented with electrical, magnetic, optical, biological components, or otherwise.

(55) The memory device system **130** includes one or more processor-accessible memory devices configured to store information, including the information needed to execute the methods of various embodiments, including the example methods of FIGS. **6A-6F** and **7** described herein. The memory device system **130** may be a distributed processor-accessible memory device system including multiple processor-accessible memory devices communicatively connected to the data processing device system **110** via a plurality of computers and/or devices. On the other hand, the memory device system **130** need not be a distributed processor-accessible memory system and, consequently, may include one or more processor-accessible memory devices located within a single data processing device.

(56) Each of the phrases “processor-accessible memory” and “processor-accessible memory device” is intended to include any processor-accessible data storage device, whether volatile or nonvolatile, electronic, magnetic, optical, or otherwise, including but not limited to, registers, floppy disks, hard disks, Compact Discs, DVDs, flash memories, ROMs, and RAMs. In some embodiments, each of the phrases “processor-accessible memory” and “processor-accessible memory device” is intended to include a non-transitory computer-readable storage medium. And in some embodiments, the memory device system **130** can be considered a non-transitory computer-readable storage medium system.

(57) The phrase “communicatively connected” is intended to include any type of connection, whether wired or wireless, between devices, data processors, or programs between which data may be communicated. Further, the phrase “communicatively connected” is intended to include a connection between devices or programs within a single data processor, a connection between devices or programs located in different data processors, and a connection between devices not located in data processors at all. In this regard, although the memory device system **130** is shown separately from the data processing device system **110** and the input-output device system **120**, one skilled in the art will appreciate that the memory device system **130** may be located completely or partially within the data processing device system **110** or the input-output device system **120**. Further in this regard, although the input-output device system **120** is shown separately from the data processing device system **110** and the memory device system **130**, one skilled in the art will appreciate that such system may be located completely or partially within the data processing system **110** or the memory device system **130**, depending upon the contents of the input-output device system **120**. Further still, the data processing device system **110**, the input-output device system **120**, and the memory device system **130** may be located entirely within the same device or housing or may be separately located, but communicatively connected, among different devices or housings. In the case where the data processing device system **110**, the input-output device system **120**, and the memory device system **130** are located within the same device, the system **100** of FIG. **1** can be implemented by a single application-specific integrated circuit (ASIC) in some embodiments.

(58) The input-output device system **120** may include a mouse, a keyboard, a touch screen, another computer, or any device or combination of devices from which a desired selection, desired information, instructions, or any other data is input to the data processing device system **110**. The input-output device system **120** may include a user-activatable control system that is responsive to a user action. The user-activatable control system may include at least one user input element, such

as, for example, a mouse button, a keyboard key, a touch screen, or any other user input element that may be placed into an activated or deactivated state on the basis of a particular user action, such as, for example, the clicking/releasing of a mouse button, the pressing/releasing of a keyboard key, or the contacting of/separating from a touch screen. Such user input elements are described in more detail below. The input-output device system **120** may include any suitable interface for receiving information, instructions or any data from other devices and systems described in various ones of the embodiments. In this regard, the input-output device system **120** may include various ones of other systems described in various embodiments. For example, the input-output device system **120** may include at least a portion a transducer-based device system or catheter-based device. The phrase “transducer-based device system” is intended to include one or more physical systems that include various transducers. The phrase “transducer-based device” is intended to include one or more physical devices that include various transducers.

(59) The input-output device system **120** also may include an image generating device system, a display device system, a processor-accessible memory device, or any device or combination of devices to which information, instructions, or any other data is output by the data processing device system **110**. In this regard, if the input-output device system **120** includes a processor-accessible memory device, such memory device may or may not form part or all of the memory device system **130**. The input-output device system **120** may include any suitable interface for outputting information, instructions or data to other devices and systems described in various ones of the embodiments. In this regard, the input-output device system **120** may include various other devices or systems described in various embodiments. In some embodiments, the input-output device system **120** may include one or more display devices that display one or more of the graphical interfaces of FIGS. 5, described below.

(60) Various embodiments of transducer-based devices are described herein. Some of the described devices are medical devices that are percutaneously or intravascularly deployed. Some of the described devices are moveable between a delivery or unexpanded configuration (e.g., FIGS. 3A, 3B discussed below) in which a portion of the device is sized for passage through a bodily opening leading to a bodily cavity, and an expanded or deployed configuration (e.g., FIGS. 3C, 3D discussed below) in which the portion of the device has a size too large for passage through the bodily opening leading to the bodily cavity. An example of an expanded or deployed configuration is when the portion of the transducer-based device is in its intended-deployed-operational state inside the bodily cavity. Another example of the expanded or deployed configuration is when the portion of the transducer-based device is being changed from the delivery configuration to the intended-deployed-operational state to a point where the portion of the device now has a size too large for passage through the bodily opening leading to the bodily cavity.

(61) In some example embodiments, the device includes transducers that sense characteristics (e.g., convective cooling, permittivity, force) that distinguish between fluid, such as a fluidic tissue (e.g., blood), and tissue forming an interior surface of the bodily cavity. Such sensed characteristics can allow a medical system to map the cavity, for example, using positions of openings or ports into and out of the cavity to determine a position or orientation (e.g., pose), or both of the portion of the device in the bodily cavity. In some example embodiments, the described devices are capable of ablating tissue in a desired pattern within the bodily cavity.

(62) In some example embodiments, the devices are capable of sensing various cardiac functions (e.g., electrophysiological activity including intra-cardiac voltages). In some example embodiments, the devices are capable of providing stimulation (e.g., electrical stimulation) to tissue within the bodily cavity. Electrical stimulation may include pacing.

(63) FIG. 2 is a representation of a transducer-based device **200** useful in investigating or treating a bodily organ, for example, a heart **202**, according to one example embodiment.

(64) Transducer-based device **200** can be percutaneously or intravascularly inserted into a portion of the heart **202**, such as an intra-cardiac cavity like left atrium **204**. In this example, the

transducer-based device **200** is part of a catheter **206** inserted via the inferior vena cava **208** and penetrating through a bodily opening in transatrial septum **210** from right atrium **212**. (In this regard, transducer-based devices or device systems described herein that include a catheter may also be referred to as catheter devices or catheter-based devices, in some embodiments.) In other embodiments, other paths may be taken.

(65) Catheter **206** includes an elongated flexible rod or shaft member appropriately sized to be delivered percutaneously or intravascularly. Various portions of catheter **206** may be steerable. Catheter **206** may include one or more lumens. The lumen(s) may carry one or more communications or power paths, or both. For example, the lumens(s) may carry one or more electrical conductors **216** (two shown). Electrical conductors **216** provide electrical connections to transducer-based device **200** that are accessible externally from a patient in which the transducer-based device **200** is inserted.

(66) Transducer-based device **200** includes a frame or structure **218** which assumes an unexpanded configuration for delivery to left atrium **204**. Structure **218** is expanded (e.g., shown in a deployed or expanded configuration in FIG. 2) upon delivery to left atrium **204** to position a plurality of transducers **220** (three called out in FIG. 2) proximate the interior surface formed by tissue **222** of left atrium **204**. In some embodiments, at least some of the transducers **220** are used to sense a physical characteristic of a fluid (e.g., blood) or tissue **222**, or both, that may be used to determine a position or orientation (e.g., pose), or both, of a portion of a device **200** within, or with respect to left atrium **204**. For example, transducers **220** may be used to determine a location of pulmonary vein ostia or a mitral valve **226**, or both. In some embodiments, at least some of the transducers **220** may be used to selectively ablate portions of the tissue **222**. For example, some of the transducers **220** may be used to ablate a pattern around the bodily openings, ports or pulmonary vein ostia, for instance to reduce or eliminate the occurrence of atrial fibrillation. In some embodiments, at least some of the transducers **220** are used to ablate cardiac tissue. In some embodiments, at least some of the transducers **220** are used to sense or sample intra-cardiac voltage data or sense or sample intra-cardiac electrogram data. In some embodiments, at least some of the transducers **220** are used to sense or sample intra-cardiac voltage data or sense or sample intra-cardiac electrogram data while at least some of the transducers **220** are concurrently ablating cardiac tissue. In some embodiments, at least one of the sensing or sampling transducers **220** is provided by at least one of the ablating transducers **220**. In some embodiments, at least a first one of the transducers **220** senses or samples intra-cardiac voltage data or intra-cardiac electrogram data at a location at least proximate to a tissue location ablated by at least a second one of the transducers **220**. In some embodiments, the first one of the transducers **220** is other than the second one of the transducers **220**.

(67) FIGS. 3A, 3B, 3C and 3D (collectively, FIG. 3) include a transducer-based device system (e.g., a portion thereof shown schematically) that includes a transducer-based device **300** according to some embodiments. Transducer-based device **300** includes a plurality of elongate members **304** (not all of the elongate members called out in each of FIGS. 3A, 3B, 3C and 3D) and a plurality of transducers **306** (not all of the transducers called out in FIG. 3) (some of the transducers **306** called out in FIG. 3D as **306a**, **306b**, **306c**, **306d**, **306e** and **306f**). FIG. 3B includes a representation of a portion of the transducer-based device **300** shown in FIG. 3A but as viewed from a different viewing direction. FIG. 3D includes a representation of a portion of the transducer-based device **300** shown in FIG. 3C but as viewed from a different viewing direction. It is noted that for clarity of illustration, all the elongate members shown in FIGS. 3C and 3D are not represented in FIGS. 3A and 3B. As will become apparent, the plurality of transducers **306** is positionable within a bodily cavity. For example, in some embodiments, the transducers **306** are able to be positioned in a bodily cavity by movement into, within, or into and within the bodily cavity, with or without a change in a configuration of the plurality of transducers **306**. In some embodiments, the plurality of transducers **306** are arranged to form a two- or three-dimensional distribution, grid or array of the

transducers capable of mapping, ablating or stimulating an inside surface of a bodily cavity or lumen without requiring mechanical scanning. As shown, for example, in FIGS. 3A and 3B, the plurality of transducers **306** are arranged in a distribution receivable in a bodily cavity. In various ones of the FIGS. 3, each of at least some of transducers **306** includes a respective electrode **315** (not all of the electrode **315** called out in each of the FIGS. 3, some of the electrodes in FIG. 3D called out as **315a**, **315b**, **315c**, **315d**, **315e** and **315f**).

(68) The elongate members **304** are arranged in a frame or structure **308** that is selectively movable between an unexpanded or delivery configuration (e.g., as shown in FIGS. 3A, 3B) and an expanded or deployed configuration (e.g., as shown in FIGS. 3C, 3D) that may be used to position elongate members **304** against a tissue surface within the bodily cavity or position the elongate members **304** in the vicinity of the tissue surface. At least the expanded or deployed configuration shown in FIGS. 3C and 3D is an example of a three-dimensional distribution of the transducers **306**. In some embodiments, structure **308** has a size in the unexpanded or delivery configuration suitable for delivery through a bodily opening (e.g., via catheter sheath **312** (shown in FIGS. 3A and 3B, but removed from FIGS. 3C and 3D for clarity)) to the bodily cavity. At least in a state in which the structure **308** is in the expanded or deployed configuration, the structure **308** may be considered to have two opposing poles **341a** and **341b**, marked by the intersection with axis **342** extending through the structure **308** as shown in FIGS. 3C and 3D. At least some of the plurality of transducers **306** are circumferentially arranged, e.g., in successive ring-like arrangements, about each of the poles **341a** and **341b** according to some embodiments. Two such ring-like arrangements are illustrated, for example, as broken-line rings **343a** and **343b** in FIG. 3C and FIG. 3D, respectively. At least some of the plurality of transducers **306** are arranged in a plurality of groups of the transducers **306**, the groups of transducers **306** arranged like lines of longitude (e.g., along respective elongate members **304**) about the structure **308** between each of the poles **341a** and **341b**, according to some embodiments. At least some of the plurality of transducers **306** are arranged in a plurality of groups of the transducers **306**, the transducers in each group of transducers **306** arrayed along a path (e.g., along at least a respective portion of a respective elongate member **304**) that extends toward the pole **341a**, the pole **341b**, or both poles **341a** and **341b**, according to some embodiments. In some embodiments, each path extends like a line of longitude between the poles **341a** and **341b**.

(69) In various embodiments, catheter sheath **312** typically includes a length sufficient to allow the catheter sheath to extend between a location at least proximate a bodily cavity into which the structure **308** is to be delivered and a location outside a body comprising the bodily cavity. In some embodiments, structure **308** has a size in the expanded or deployed configuration too large for delivery through a bodily opening (e.g., via catheter sheath **312**) to the bodily cavity. The elongate members **304** may form part of a flexible circuit structure (e.g., also known as a flexible printed circuit board (PCB) circuit). The elongate members **304** can include a plurality of different material layers. Each of the elongate members **304** can include a plurality of different material layers. The structure **308** can include a shape memory material, for instance Nitinol. The structure **308** can include a metallic material, for instance stainless steel, or non-metallic material, for instance polyimide, or both a metallic and non-metallic material by way of non-limiting example. The incorporation of a specific material into structure **308** may be motivated by various factors including the specific requirements of each of the unexpanded or delivery configuration and expanded or deployed configuration, the required position or orientation (e.g., pose), or both of structure **308** in the bodily cavity or the requirements for successful ablation of a desired pattern.

(70) FIG. 4 is a schematic side elevation view of at least a portion of a transducer-based device **400** that includes a flexible circuit structure **401** that is employed to provide a plurality of transducers **406** (two called out) according to an example embodiment. In some embodiments, the flexible circuit structure **401** may form part of a structure (e.g., structure **308**) that is selectively movable between a delivery configuration sized for percutaneous delivery and expanded or deployed

configurations sized too large for percutaneous delivery. In some embodiments, the flexible circuit structure **401** may be located on, or form at least part of, a structural component (e.g., elongate member **304**) of a transducer-based device system.

(71) The flexible circuit structure **401** can be formed by various techniques including flexible printed circuit techniques. In some embodiments, the flexible circuit structure **401** includes various layers including flexible layers **403a**, **403b** and **403c** (e.g., collectively flexible layers **403**). In some embodiments, each of flexible layers **403** includes an electrical insulator material (e.g., polyimide). One or more of the flexible layers **403** can include a different material than another of the flexible layers **403**. In some embodiments, the flexible circuit structure **401** includes various electrically conductive layers **404a**, **404b** and **404c** (collectively electrically conductive layers **404**) that are interleaved with the flexible layers **403**. In some embodiments, each of the electrically conductive layers **404** is patterned to form various electrically conductive elements. For example, electrically conductive layer **404a** is patterned to form a respective electrode **415** of each of the transducers **406**. Electrodes **415** have respective electrode edges **415-1** that form a periphery of an electrically conductive surface associated with the respective electrode **415**. It is noted that other electrodes employed in other embodiments may have electrode edges arranged to form different electrodes shapes (for example, as shown by electrode edges **315-1** in FIG. 3C).

(72) Electrically conductive layer **404b** is patterned, in some embodiments, to form respective temperature sensors **408** for each of the transducers **406** as well as various leads **410a** arranged to provide electrical energy to the temperature sensors **408**. In some embodiments, each temperature sensor **408** includes a patterned resistive member **409** (two called out) having a predetermined electrical resistance. In some embodiments, each resistive member **409** includes a metal having relatively high electrical conductivity characteristics (e.g., copper). In some embodiments, electrically conductive layer **404c** is patterned to provide portions of various leads **410b** arranged to provide an electrical communication path to electrodes **415**. In some embodiments, leads **410b** are arranged to pass through vias in flexible layers **403a** and **403b** to connect with electrodes **415**. Although FIG. 4 shows flexible layer **403c** as being a bottom-most layer, some embodiments may include one or more additional layers underneath flexible layer **403c**, such as one or more structural layers, such as a steel or composite layer. These one or more structural layers, in some embodiments, are part of the flexible circuit structure **401** and can be part of, e.g., elongate member **304**. In some embodiments, the one or more structural layers may include at least one electrically conductive surface (e.g., a metallic surface) exposed to blood flow. In addition, although FIG. 4 shows only three flexible layers **403a-403c** and only three electrically conductive layers **404a-404c**, it should be noted that other numbers of flexible layers, other numbers of electrically conductive layers, or both, can be included.

(73) In some embodiments, electrodes **415** are employed to selectively deliver RF energy to various tissue structures within a bodily cavity (e.g., an intra-cardiac cavity or chamber). The energy delivered to the tissue structures may be sufficient for ablating portions of the tissue structures. The energy delivered to the tissue may be delivered to cause monopolar tissue ablation, bipolar tissue ablation or blended monopolar-bipolar tissue ablation by way of non-limiting example.

(74) Energy that is sufficient for tissue ablation may be dependent upon factors including transducer location, size, shape, relationship with respect to another transducer or a bodily cavity, material or lack thereof between transducers, et cetera. For example, a pair of electrodes that each is approximately 10 mm.^{sup.2} in surface area and present along a same structural member (e.g., an elongate member **304** in various ones of FIG. 3) may be expected, in some circumstances, to sufficiently ablate intra-cardiac tissue to a depth of approximately 3.1 mm with 2 W of power and to a depth of approximately 4.4 mm with 4 W of power. For yet another non-limiting example, if each electrode in this pair instead has approximately 20 mm.^{sup.2} of surface area, it may be expected that such pair of electrodes will sufficiently ablate intra-cardiac tissue to a depth of

approximately 3.1 mm with 4 W of power and to a depth of approximately 4.4 mm with 8 W of power. In these non-limiting examples, power refers to the average power of each electrode summed together, and the depth and power values may be different depending upon the particular shapes of the respective electrodes, the particular distance between them, a degree of electrode-to-tissue contact, and other factors. It is understood, however, that for the same control or target temperature, a larger electrode will achieve a given ablation depth sooner than a smaller electrode. A smaller electrode (e.g., an electrode with a smaller surface area) may need to operate at a higher target temperature to achieve the same ablation depth as compared to a larger (e.g., surface area) electrode (a phenomenon driven by a greater divergence of heat flux of smaller electrodes). Put differently, a maximum ablation depth (e.g., reached when the temperature profile approaches steady state) of a relatively smaller electrode is typically shallower than that of a relatively larger electrode when ablating at the same control or target temperature, and consequently, a given, less than maximum, ablation depth typically is a larger proportion of the final, maximum, ablation depth for a relatively smaller electrode and typically is reached later in the ablation as compared to a relatively larger electrode. This circumstance may be associated with a lower total power provided to the relatively smaller electrode as compared to a relatively larger electrode, but, nonetheless, the power density present in the relatively smaller electrode may be expected to be somewhat higher as compared to the relatively larger electrode. The phrase “power density” in this context means output power divided by electrode area. Note that power density approximately drives the realized control or target temperature, but in various cases, this is a simplification, and as indicated above, the relationship between power density and realized control or target temperature may be modified by such factors as electrode size, shape, separation, and so forth. It is further noted that when a comparison is made between a relatively larger electrode operated at a lower control temperature versus a relatively smaller electrode operated at a higher temperature, further complications may arise when limits on compensation for electrode size with temperature are also dictated, at least in part, by a desire to reduce occurrences of thermal coagulation of blood or steam formation in the ablated tissue. It is noted that power levels in irrigated electrode systems are typically higher (e.g., in the tens of Watts) than those described above.

(75) In some embodiments, each electrode **415** is employed to sense or sample an electrical potential in the tissue proximate the electrode **415** at a same or different time than delivering energy sufficient for tissue ablation. In some embodiments, each electrode **415** is employed to sense or sample intra-cardiac voltage data in the tissue proximate the electrode **415**. In some embodiments, each electrode **415** is employed to sense or sample data in the tissue proximate the electrode **415** from which an electrogram (e.g., an intra-cardiac electrogram) may be derived. In some embodiments, each resistive member **409** is positioned adjacent a respective one of the electrodes **415**. In some embodiments, each of the resistive members **409** is positioned in a stacked or layered array with a respective one of the electrodes **415** to form a respective one of the transducers **406**. In some embodiments, the resistive members **409** are connected in series to allow electrical current to pass through all of the resistive members **409**. In some embodiments, leads **410a** are arranged to allow for a sampling of electrical voltage in between each resistive members **409**. This arrangement allows for the electrical resistance of each resistive member **409** to be accurately measured. The ability to accurately measure the electrical resistance of each resistive member **409** may be motivated by various reasons including determining temperature values at locations at least proximate the resistive member **409** based at least on changes in the resistance caused by convective cooling effects (e.g., as provided by blood flow).

(76) Referring to FIGS. 3A, 3B, 3C, and 3D transducer-based device **300** can communicate with, receive power from or be controlled by a transducer-activation system **322**. In some embodiments, the transducer-activation system **322** represents one or more particular implementations of the system **100** illustrated in FIG. 1. In some embodiments, elongate members **304** can form a portion of an elongated cable **316** of leads **317** (e.g., control leads, data leads, power leads or any

combination thereof), for example, by stacking multiple layers, and terminating at a connector **321** or other interface with transducer-activation system **322**. The leads **317** may correspond to the electrical connectors **216** in FIG. 2 in some embodiments. The transducer-activation device system **322** may include a controller **324** that includes a data processing device system **310** (e.g., which may be a particular implementation of data processing device system **110** from FIG. 1) and a memory device system **330** (e.g., which may be a particular implementation of the memory device system **130** from FIG. 1) that stores data and instructions that are executable by the data processing device system **310** to process information received from transducer-based device **300** or to control operation of transducer-based device **300**, for example, activating various selected transducers **306** to ablate tissue and control a user interface (e.g., of input-output device system **320**) according to various embodiments including at least those described below with respect to various ones of FIGS. 5 and 6. Controller **324** may include one or more controllers.

(77) Transducer-activation device system **322** includes an input-output device system **320** (e.g., which may be a particular implementation of the input-output device system **120** from FIG. 1) communicatively connected to the data processing device system **310** (e.g., via controller **324** in some embodiments). Input-output device system **320** may include a user-activatable control that is responsive to a user action. Input-output device system **320** may include one or more user interfaces or input/output (I/O) devices, for example, one or more display device systems **332**, speaker device systems **334**, one or more keyboards, one or more mice (e.g., mouse **335**), one or more joysticks, one or more track pads, one or more touch screens or other transducers to transfer information to, from, or both to and from a user, for example, a care provider such as a physician or technician. For example, output from a mapping process may be displayed on a display device system **332**. Input-output device system **320** may include one or more user interfaces or input/output (I/O) devices, for example, one or more display device systems **332**, speaker device systems **334**, keyboards, mice, joysticks, track pads, touch screens or other transducers employed by a user to indicate a particular selection or series of selections of various graphical information. Input-output device system **320** may include a sensing device system **325** configured to detect various characteristics including, but not limited to, at least one of tissue characteristics (e.g., electrical characteristics such as tissue impedance, tissue conductivity, tissue type, tissue thickness) and thermal characteristics such as temperature. In this regard, the sensing device system **325** may include one, some, or all of the transducers **306** (or **406** of FIG. 4) of the transducer based device **300**, including the internal components of such transducers shown in FIG. 4, such as the electrodes **415** and temperature sensors **408**.

(78) Transducer-activation device system **322** may also include an energy source device system **340** including one or more energy source devices connected to transducers **306**. In this regard, although various ones of FIG. 3 show a communicative connection between the energy source device system **340** and the controller **324** (and its data processing device system **310**), the energy source device system **340** may also be connected to the transducers **306** via a communicative connection that is independent of the communicative connection with the controller **324** (and its data processing device system **310**). For example, the energy source device system **340** may receive control signals via the communicative connection with the controller **324** (and its data processing device system **310**), and, in response to such control signals, deliver energy to, receive energy from, or both deliver energy to and receive energy from one or more of the transducers **306** via a communicative connection with such transducers **306** (e.g., via one or more communication lines through catheter body or shaft **314**, elongated cable **316** or catheter sheath **312**) that does not pass through the controller **324**. In this regard, the energy source device system **340** may provide results of its delivering energy to, receiving energy from, or both delivering energy to and receiving energy from one or more of the transducers **306** to the controller **324** (and its data processing device system **310**) via the communicative connection between the energy source device system **340** and the controller **324**.

(79) In any event, the number of energy source devices in the energy source device system **340** is fewer than the number of transducers in some embodiments. The energy source device system **340** may, for example, be connected to various selected transducers **306** to selectively provide energy in the form of electrical current or power (e.g., RF energy), light or low temperature fluid to the various selected transducers **306** to cause ablation of tissue. The energy source device system **340** may, for example, selectively provide energy in the form of electrical current to various selected transducers **306** and measure a temperature characteristic, an electrical characteristic, or both at a respective location at least proximate each of the various transducers **306**. The energy source device system **340** may include various electrical current sources or electrical power sources as energy source devices. In some embodiments, an indifferent electrode **326** is provided to receive at least a portion of the energy transmitted by at least some of the transducers **306**. Consequently, although not shown in various ones of FIGS. **3**, the indifferent electrode **326** may be communicatively connected to the energy source device system **340** via one or more communication lines in some embodiments. In addition, although shown separately in various ones of FIGS. **3**, indifferent electrode **326** may be considered part of the energy source device system **340** in some embodiments. In various embodiments, indifferent electrode **326** is positioned on an external surface (e.g., a skin-based surface) of a body that comprises the bodily cavity into which at least transducers **306** are to be delivered.

(80) It is understood that input-output device system **320** may include other systems. In some embodiments, input-output device system **320** may optionally include energy source device system **340**, transducer-based device **300** or both energy source device system **340** and transducer-based device **300** by way of non-limiting example. Input-output device system **320** may include the memory device system **330** in some embodiments.

(81) Structure **308** can be delivered and retrieved via a catheter member, for example, a catheter sheath **312**. In some embodiments, a structure provides expansion and contraction capabilities for a portion of the medical device (e.g., an arrangement, distribution or array of transducers **306**). The transducers **306** can form part of, be positioned or located on, mounted or otherwise carried on the structure and the structure may be configurable to be appropriately sized to slide within catheter sheath **312** in order to be deployed percutaneously or intravascularly. FIGS. **3A**, **3B** show one embodiment of such a structure. In some embodiments, each of the elongate members **304** includes a respective distal end **305** (only one called out in each of FIGS. **3A**, **3B**), a respective proximal end **307** (only one called out in each of FIGS. **3A**, **3B**) and an intermediate portion **309** (only one called out in each of FIGS. **3A**, **3B**) positioned between the proximal end **307** and the distal end **305**. The respective intermediate portion **309** of each elongate member **304** includes a first or front surface **318a** that is positionable to face an interior tissue surface within a bodily cavity and a second or back surface **318b** opposite across a thickness of the intermediate portion **309** from the front surface **318a**. In some embodiments, each of the elongate members **304** is arranged front surface **318a**-toward-back surface **318b** in a stacked array during an unexpanded or delivery configuration similar to that described in co-assigned International Application No.:

PCT/US2012/022061 and co-assigned International Application No.: PCT/US2012/022062. In many cases a stacked array allows the structure **308** to have a suitable size for percutaneous or intravascular delivery. In some embodiments, the elongate members **304** are arranged to be introduced into a bodily cavity distal end **305** first. A flexible, elongated, catheter body **314** is used to deliver structure **308** through catheter sheath **312** according to some embodiments.

(82) In a manner similar to that described in co-assigned International Application No.: PCT/US2012/022061 and co-assigned International Application No.: PCT/US2012/022062, each of the elongate members **304** is arranged in a fanned arrangement **370** in FIGS. **3C**, **3D**. In some embodiments, the fanned arrangement **370** is formed during the expanded or deployed configuration in which structure **308** is manipulated to have a size too large for percutaneous or intravascular delivery. In some embodiments, structure **308** includes a proximal portion **308a**

having a first domed shape **309a** and a distal portion **308b** having a second domed shape **309b**. In some embodiments, the proximal and the distal portions **308a**, **308b** each include respective portions of elongate members **304**. In some embodiments, the structure **308** is arranged to be delivered distal portion **308b** first into a bodily cavity when the structure is in the unexpanded or delivery configuration as shown in FIGS. **3A**, **3B**. In various embodiments, the proximal and distal portions **308a**, **308b** do not include a domed shape in the delivery configuration (for example, as shown in FIGS. **3A**, **3B**). In some embodiments, the first domed shape **309a** of the proximal portion **308a** and the second domed shape **309b** of the distal portion **308b** are arranged in a clam shell configuration in the expanded or deployed configuration shown in FIGS. **3C**, **3D**.

(83) The transducers **306** can be arranged in various distributions or arrangements in various embodiments. In some embodiments, various ones of the transducers **306** are spaced apart from one another in a spaced apart distribution in the delivery configuration shown in FIGS. **3A**, **3B**. In some embodiments, various ones of the transducers **306** are arranged in a spaced apart distribution in the deployed configuration shown in FIGS. **3C**, **3D**. In some embodiments, various pairs of transducers **306** are spaced apart with respect to one another. In some embodiments, various regions of space are located between various pairs of the transducers **306**. For example, in FIG. **3D** the transducer-based device **300** includes at least a first transducer **306a**, a second transducer **306b** and a third transducer **306c** (all collectively referred to as transducers **306**). In some embodiments each of the first, the second and the third transducers **306a**, **306b** and **306c** are adjacent transducers in the spaced apart distribution. In some embodiments, the first and the second transducers **306a**, **306b** are located on different elongate members **304** while the second and the third transducers **306b**, **306c** are located on a same elongate member **304**. In some embodiments, a first region of space **350** is between the first and the second transducers **306a**, **306b**. In various embodiments, a first region of space **350** is between the respective electrodes **315a**, **315b** of the first and the second transducers **306a**, **306b**. In some embodiments, the first region of space **350** is not associated with any physical portion of structure **308**. In some embodiments, a second region of space **360** associated with a physical portion of device **300** (e.g., a portion of an elongate member **304**) is between the second and the third transducers **306b**, **306c**. In various embodiments, the second region of space **360** is between the respective electrodes **315b**, **315c** of the second and the third transducers **306b**, **306c**. In some embodiments, each of the first and the second regions of space **350**, **360** does not include a transducer of transducer-based device **300**. In some embodiments, each of the first and the second regions of space **350**, **360** does not include any transducer. It is noted that other embodiments need not employ a group of elongate members **304** as employed in the illustrated embodiment. For example, other embodiments may employ a structure having one or more surfaces, at least a portion of the one or more surfaces defining one or more openings in the structure. In these embodiments, a region of space not associated with any physical portion of the structure may extend over at least part of an opening of the one or more openings.

(84) In some embodiments, a first transducer set (e.g., a first set including one or more of transducers **306**) is arranged (e.g., axially, circumferentially, or both axially and circumferentially arranged) along, across, or over a portion of catheter body **314** while a second set (e.g., a second set including one or more of transducers **306**) is located on structure **308** extending outwardly from a distal end **314a** of catheter body **314**. An example first transducer set **380** and example second transducer set **382** are shown in FIG. **3C** according to some embodiments. In various example embodiments, transducer-based device **300** includes a first transducer set (e.g., first transducer set **380**) located proximally of a distal end **314a** of catheter body **314** while a second transducer set (e.g., second transducer set **382**) is located on structure **308** extending outwardly from the distal end **314a** of catheter body **314** (which is better seen in FIG. **3B**). In some of these various example embodiments, structure **308** is selectively moveable between a delivery configuration (e.g., FIGS. **3A**, **3B**) in which the first transducer set **380** and the second transducer set **382** are concurrently arranged in respective arrangements sized for movement through a lumen of catheter sheath **312**,

and an expanded or deployed configuration (e.g., FIGS. 3C, 3D) in which the second transducer set **382** is arranged in a respective arrangement sized too large for delivery through the lumen of catheter sheath **312** while the first transducer set **380** is arranged in a respective arrangement sized for movement through the lumen of the catheter sheath **312**. For example, in some embodiments of the expanded or deployed configuration, each of various transducers **306** in the first transducer set **380** is moveable inwardly into or outwardly from the lumen of catheter sheath **312** while the transducers **306** in the second transducer set **382** are arranged in an arrangement too large for movement inwardly into the lumen of the catheter sheath **312**. Advantageously, these embodiments may allow particular transducers (e.g., transducers **306** in the first transducer set **380** to be introduced into or removed from a bodily cavity when the structure **308** is repositioned in the bodily cavity in the expanded or deployed configuration. Repositioning of the structure **308** in the bodily cavity may be required due to variances in a size of the cavity (e.g., a larger than expected size) or variances in an expected positioning of various anatomical landmarks. In either case, additional transducers **306** may be brought into play or out of play as the specific circumstance may require. Bringing a particular transducer **306** into play within a bodily cavity may include appropriately positioning the transducer for a desired sensing function, an energy transmission function, or a sensing and energy transmission function within the bodily cavity.

(85) In FIG. 3C, structure **308** includes at least one elongate member **304a** (also shown in FIG. 3A) according to some embodiments. At least one elongate member **304a** is sized and arranged to position at least some of a first set of the transducers **306** (e.g., first transducer set **380**) diametrically opposite from a portion **314b** (best seen in FIG. 3B) of an outer surface of catheter body **314**, the portion of the outer surface not including any transducer. In some example embodiments, portion **314b** includes at least a semicircular portion of an outer surface of catheter body **314**. In some embodiments, various ones of the elongate members **304** of structure **308** extend outwardly away from the distal end **314a** of the catheter body **314** while at least one elongate member **304** (e.g., at least one elongate member **304a**) extends outwardly from a location (e.g., location **314c**) on the catheter body **314** spaced proximally inward from the distal end **314a** of the catheter body **314**. In some embodiments, one or more transducers **306** of the first transducer set **380** are located within a region of space between location **314c** and distal end **314a**. In some embodiments, elongate member **304a** is sized and arranged to position first transducer set **380** along the catheter body **314** inwardly from the distal end **314a** of the catheter body **314** while positioning a third transducer set **384** outwardly from the distal end **314a** of catheter body **314**, each of the first and the third transducer sets **380**, **384** located on elongate member **304a**. In some embodiments, elongate member **304a** is sized and arranged to position at least some of transducers **306** over a twisted region **311** of each of at least some of the other elongate members **304**. In some embodiments, respective portions of each of at least three of the elongate members **304** are arranged front surface **318a**-toward-back surface **318b** along a first direction (for example, indicated by arrow **318** in FIG. 3A) to form a stacked array in the delivery configuration (e.g., FIG. 3A), and at least one portion of the respective front surface **318a** of at least one elongate member **304a** is arranged to face in a direction (e.g., represented by arrow **319** in FIG. 3A) other than the first direction in the delivery configuration. In other example embodiments, other structures may be employed to support or carry transducers of a transducer-based device such as a transducer-based catheter. For example, an elongated catheter member may be used to distribute the transducers in a linear or curvilinear array. Basket catheters or balloon catheters may be used to distribute the transducers in a two-dimensional or three-dimensional array.

(86) FIGS. 6A-6F include respective data generation and flow diagrams, which may implement various embodiments of method **600** by way of associated computer-executable instructions according to some example embodiments. In various example embodiments, a memory device system (e.g., memory device systems **130**, **330**) is communicatively connected to a data processing device system (e.g., data processing device systems **110** or **310**, otherwise stated herein as “e.g.,

110, 310”) and stores a program executable by the data processing device system to cause the data processing device system to execute various embodiments of method **600** via interaction with at least, for example, a transducer-based device (e.g., transducer-based devices **200, 300, or 400**). In these various embodiments, the program may include instructions configured to perform, or cause to be performed, various ones of the instructions associated with execution of various embodiments of method **600**. In some embodiments, method **600** may include a subset of the associated blocks or additional blocks than those shown in FIGS. **6A-6F**. In some embodiments, method **600** may include a different sequence indicated between various ones of the associated blocks shown in FIGS. **6A-6F**.

(87) In some embodiments, block **604** is associated with computer-executable instructions (e.g., graphical representation instructions or graphical interface instructions or display instructions provided by a program) configured to cause an input-output device system (e.g., input-output device system **120 or 320**) to display a graphical representation. FIG. **5A** illustrates a graphical interface including a graphical representation **500** provided by the input-output device system according to one example embodiment provided in accordance with display instructions associated with block **604** in FIG. **6A**. In some embodiments, the graphical representation **500** includes a three-dimensional graphical representation of at least a portion of a transducer-based device (e.g., structure **308** in FIG. **3**) and is provided in accordance with the computer-executable program instructions associated with block **606**. The instructions associated with block **606** may be configured to access a predefined model (e.g., a computer-aided-design (“CAD”) or other computer-readable model stored in memory device system **130, 330**) of the at least the portion of the transducer-based device and display the at least the portion of the transducer-based device according to such model. In some embodiments encompassing FIG. **5A**, the representation of the transducer-based device is provided by or among various elements of graphical representation **500**. In some embodiments, the graphical interface depicts the transducer-based device as including a first domed portion **508a** associated with a first domed portion of the transducer-based device (e.g., proximal portion **308a** when having the first domed shape **309a**) and a second domed portion **508b** associated with a second domed portion of the transducer-based device (e.g., distal portion **308b** having the second domed shape **309b**). A separation graphical element **503** may be employed between the first and the second domed portions **508a, 508b** in some embodiments, but may be omitted in other embodiments. Various other transducer-based devices may be depicted according to the instructions associated with block **606** in other embodiments. FIGS. **5A, 5B, 5C, 5D, 5E, 5F, 5G, 5H, 5I, 5J, 5K, 5L, 5M, 5N, 5O, 5P, 5Q, 5R, 5S, 5T, 5U, 5V, 5W, and 5X** (collectively FIGS. **5**) are presented in this disclosure in association with various embodiments. It is understood that each of these embodiments need not be associated with all of the FIG. **5**, and in some cases will only be associated with a subset of the FIGS. **5**.

(88) In some embodiments according to FIG. **5A**, a plurality of graphical elements **501** (only two called out) are depicted (e.g., according to the instructions associated with block **606**) among various elements of graphical representation **500**. In various embodiments, each of the graphical elements **501** is respectively associated with a respective one of a plurality of transducer sets. Each respective transducer set includes at least one of a plurality of transducers included as part of the transducer-based device (e.g., transducer-based devices **200, 300, or 400**) and each respective transducer set has at least one different transducer than another of the other transducer sets. In various particular embodiments, each respective transducer set has at least one different transducer than each of the other transducer sets.

(89) FIG. **5B** shows the graphical interface in which the display instructions have been configured to cause (for example, in response to a user input via an input-output device system such as **120, 320**) the three-dimensional graphical representation of the transducer-based device to be manipulated so as to be viewed from a different viewing angle than that shown in FIG. **5A**. In some embodiments, the depiction of the transducer-base device may include various other elements

thereof. For example, FIG. 5B depicts the transducer-based device as including an elongated portion **500c** (e.g., extending from or toward domed portion **508a** in some embodiments). In various embodiments, elongated portion **500c** is representative of a particular element that is the same or similar to at least one elongate member **304a** in various ones of FIGS. 3B. It is noted that three-dimensional representations of at least portion of the transducer-based device are shown in FIGS. 5A, 5B, 5C, 5D, and 5R.

(90) Referring to some embodiments encompassing FIG. 5A, each of at least some of the graphical elements **501** is provided by a respective one of a plurality of transducer graphical elements **502** that include at least a first transducer graphical element **502a**, a second transducer graphical element **502b**, and a third transducer graphical element **502c** (e.g., all the transducer graphical elements forming part of a group of transducer graphical elements **502**). In some embodiments, each transducer graphical element **502** is associated with a single respective transducer of the transducer-based device. In some example embodiments, each transducer graphical element **502** is representative of a respective transducer of the transducer-based device. In some example embodiments, each transducer graphical element **502** is representative of a location or position of a respective transducer of the transducer-based device. In some embodiments, the graphical representation **500** includes a first spatial relationship between the transducer graphical elements **502** that is consistent with a second spatial relationship between the corresponding transducers associated with the transducer graphical elements **502**. For example, in some embodiments, the transducer graphical elements **502** in the three-dimensional graphical representation **500** in FIGS. 5A, 5B may exhibit a same spatial relationship that the transducers **306** exhibit in the transducer based device **300** in FIG. 3C. Or, in some embodiments, the transducer graphical elements **502** in other graphical representations **500** in others of FIG. 5 may exhibit a respective or corresponding spatial relationship that the transducers **306** exhibit in the transducer based device **300** in FIGS. 3C and 3D. In this regard, in some embodiments, the graphical representation **500** may include a first spatial relationship between the transducer graphical elements **502** that is consistent with a second spatial relationship between the corresponding transducers associated with the transducer graphical elements **502** when the corresponding transducers are arranged in a deployed configuration (e.g., FIGS. 3C, 3D). In some embodiments, each particular depicted transducer graphical element **502** is shown having a shape that is consistent with the particular transducer (or portion thereof) that the particular transducer graphical element **502** is representative of. For example, in FIG. 5A, transducer graphical element **502d** includes an essentially square shape with rounded corners that is consistent with the square, rounder cornered shape of the electrode **315d** of transducer **306d** shown in FIG. 3D. Additionally, in FIG. 5A, transducer graphical element **502e** includes an essentially triangular shape with rounded corners that is consistent with the triangular, rounded cornered shape of the electrode of transducer **306e** shown in FIG. 3D. Further, in FIG. 5A, transducer graphical element **502f** includes an essentially oval shape that is consistent with the oval shape of the electrode **315f** of transducer **306f** shown in FIG. 3D. Others transducer graphical elements **502** in FIGS. 5A and 5B have shapes that are consistent with respective ones of the electrodes shown in FIG. 3C and 3D. A graphical representation **523** of an electrocardiogram (ECG/EKG) signal is also shown in the graphical interface of various ones of FIG. 5.

(91) In some example embodiments, graphical elements **501** may include alternate or additional forms. For example, FIG. 5C shows an example embodiment in which each of at least some of the graphical elements **501** are provided by a respective one of a plurality of between graphical elements **504** including a first between graphical element **504a** and a second between graphical element **504b** (e.g., all the between graphical elements collectively referred to as between graphical elements **504**). FIG. 5D shows an embodiment of the graphical interface in which the display instructions have been configured to cause (for example, in response to a user input via an input-output device system such as **120**, **320**) the depiction of the transducer-based device to be manipulated so as to be viewed from a different viewing angle than that shown in FIG. 5C. In some

embodiments, between graphical elements **504** are shown in addition to various ones of the transducer graphical **502** shown in FIGS. 5A and 5B. In some embodiments, between graphical elements **504** are provided separately or with other embodiments of graphical elements **501**. In various embodiments, each of the between graphical elements **504** is associated with a set of at least two (e.g., a group) of the transducers of the transducer-based device. In some example embodiments, each of the between graphical elements **504** is associated with a pair of transducers in the transducer-based device. In some example embodiments, each between graphical element **504** is associated with a region of space between a respective pair of transducers in the transducer-based device. In some example embodiments, each between graphical element **504** is associated with a region of space between a respective pair of adjacent ones of the transducers in the transducer-based device.

(92) In some embodiments, first transducer graphical element **502a** is associated with a first transducer (e.g., first transducer **306a**) of the transducer-based device, second transducer graphical element **502b** associated with a second transducer (e.g., second transducer **306b**) of the transducer-based device, and third transducer graphical element **502c** associated with a third transducer (e.g., third transducer **306c**) of the transducer-based device. In some embodiments, each of the transducer graphical elements **502a**, **502b** and **502c** has a shape that is consistent with a shape of the respective electrode **315a**, **315b**, **351c** of the corresponding one of the transducers **306a**, **306b** and **306c**. In some embodiments, the first between graphical element **504a** is associated with a first region of space that is between the first and the second transducers and the second between graphical element **504b** is associated with a second region of space that is between the second and the third transducers. In some embodiments, the first region of space is a region of space that is not associated with any physical part of the transducer-based device (e.g., first region of space **350**) and the second region of space is a region of space that is associated with a physical part of the transducer-based device (e.g., second region of space **360**). In some embodiments, each of the first and the second between graphical elements **504a**, **504b** is associated with a region of space that does not include a transducer of the transducer-based device. In some embodiments, each of the first and the second between graphical elements **504a**, **504b** is associated with a region of space that does not include any transducer. It is understood that a “region of space” need not be a vacant space but can include physical matter therein.

(93) In some embodiments, the first between graphical element **504a** is positioned between the second and the first transducer graphical elements **502b**, **502a** among the graphical representation **500**. In some embodiments, the second between graphical element **504b** is positioned between the second and the third transducer graphical elements **502b**, **502c** among the graphical representation **500**. In other example embodiments, other spatial relationships exist between the transducer graphical elements **502** and the between graphical elements **504** in the graphical representation.

(94) The transducer graphical elements **502**, the between graphical elements **504**, or both may have different sizes, shapes or forms than those shown in the illustrated embodiment. In some embodiments, at least one particular one of the transducer graphical elements **502** may be depicted with a different shape, size, or form than the respective one of the shape, size or form of the respective portion of the particular transducer to which the particular one of the transducer graphical elements **502** corresponds. In some embodiments, different ones of the between graphical elements **504** may be depicted with different shapes, sizes, or forms.

(95) With reference to various ones of FIGS. 5, at least a portion of the transducer graphical elements **502**, and at least a portion of the between graphical elements **504** are arranged in a plurality of rows **510** (two called out in FIG. 5A) and a plurality of columns **512** (two called out in FIG. 5A). In some embodiments, each row corresponds to a respective one of number “0”, “1”, “2”, “3”, “4”, “5”, “6”, “7”, “8”, “9”, “10”, and “11”, and each column **512** corresponds to a respective one of letters “A”, “B”, “C”, “D”, “E”, “F”, “G”, “H”, “I”, “J”, “K”, “L”, “M”, “N”, “O”, “P”, “Q”, “R”, “S”, and “T”, each of the numbers and letters used as part of the unique

identifier **513** (only two called out with reference numeral **513** in FIG. 5A) of each transducer graphical element **504**. In some embodiments, the plurality of rows **510** and columns **512** correspond to condition in which structure **308** is in the deployed configuration. In some embodiments, a portion of each of the columns **512** corresponds to region of space associated with a physical portion of the transducer-based device (e.g., an elongate member **304**). In some embodiments, each of the columns **512** corresponds to at least a portion of the transducers located on a particular elongate member of a transducer-based device (e.g., an elongate member **304**). In some embodiments, at least one of the columns **512** includes at least one transducer graphical element **502** having a shape that is different than the respective shape comprised by any of the transducer graphical elements **502** included in at least one other of the columns **512**. For example, the “A” column **512** includes a transducer graphical element **502** identified as “A:10” that has a shape that is different than any of the transducer graphical elements **502** comprised by at least one of the other columns **512**. In some embodiments, at least a first one of the rows **510** includes identically shaped transducer graphical elements **502** (e.g., row **510** that includes transducer graphical elements **502** identified as “A:6”, “B:6”, “C:6”, “D:6”, “E:6”, “F:6”, “G:6”, “H:6”, “I:6”, “J:6”, “K:6”, “L:6”, “M:6”, “N:6”, “O:6”, “P:6”, “Q:6”, “R:6”, “S:6” and “T:6”), and at least a second one of the rows **510** includes differently shaped transducer graphical elements **502** (e.g., row **510** that includes transducer graphical elements **502** identified as “A:10”, “B:10”, “C:10”, “D:10”, “E:10”, “F:10”, “G:10”, “H:10”, “I:10”, “K:10”, “L:10”, “M:10”, “N:10”, “O:10”, “P:10”, “Q:10”, “R:10”, and “S:10”). In some example embodiments, a portion of each of the rows **510** corresponds to regions of space not associated with any physical portion of the transducer-based device (e.g., regions of space **350** between adjacent ones of the elongate members **304**). In other example embodiments, different numbers of transducer graphical elements **502** and different numbers and spatial arrangements of between graphical elements **504** may be depicted in the graphical representation. In other example embodiments, different numbers and spatial arrangements of rows **510** and columns **512** may be depicted in the graphical representation. In various embodiments, each of the between graphical elements (e.g., between graphical elements **504**) depicted in the graphical representation are representative of a respective physical path extending between a respective pair of transducers of the transducer-based device. Each of the physical paths may extend over a physical surface of the transducer-based device or over a portion of an opening defined by a physical surface of the transducer-based device. In the embodiment shown in FIG. 5C, each between graphical element **504** is representative of a respective physical path extending between the respective transducers associated with the adjacent pair of transducer graphical elements **502** that the between graphical element **504** extends between. In the embodiment shown in FIG. 5C, each adjacent pair of the transducer graphical elements **502** may be provided along a row **510** (two called out in FIG. 5C) of the graphical elements **501**, along a column **512** (two called out in FIG. 5C) of the graphical elements **501**, or diagonally between a row **510** and a column **512**.

(96) Referring back to FIGS. 5A, 5B, the plurality of rows **510** and the plurality of columns **512** are depicted as a three-dimensional arrangement in the graphical representation. In some embodiments, at least two of the plurality of columns **512** are depicted in the graphical representation extending along respective directions that converge with respect to one another. In some embodiments, at least two of the plurality of columns **512** are depicted in the graphical representation extending along non-parallel directions and at least two of the plurality of rows **510** are depicted extending along parallel directions. In some embodiments, the rows **510** and the columns **512** are depicted in the graphical representation in an arrangement in which the columns **512** are circumferentially arranged. In some embodiments, the rows **510** and the columns **512** are depicted in the graphical representation in an arrangement having a generally spherical shape. The plurality of columns **512** may be depicted like lines of longitude, and the plurality of rows **510** may be depicted like lines of latitude. Although the rows **510** and columns **512** are illustrated in FIGS. 5A-5D as circumferential

lines (like lines of longitude and latitude), such rows **510** and columns **512** can take other forms, as shown, for example, in FIGS. **5E** and **5F**, discussed in more detail below, according to some embodiments.

(97) The display instructions (e.g., according to block **604**, **606**, or both) may include instructions (e.g., instructions responsive to a user input made via an input-output device system) configured to vary the depiction of the portion of the transducer-based device between a three-dimensional representation (e.g., as depicted in various ones of at least FIGS. **5A**, **5B**, **5C**, and **5D**) and a two-dimensional representation (e.g., as depicted by at least FIG. **5E** or **5F**). Various two-dimensional representations are possible in various embodiments. For instance, the plurality of transducer graphical elements **502** may be arranged in the graphical representation **500** in a particular spatial distribution representing the three-dimensional distribution of transducers (e.g., **220** or **306**) distorted onto a two-dimensional plane to form the two-dimensional representation. In this regard, in some embodiments, the two-dimensional representation of the three-dimensional distribution of transducers (e.g., **220** or **306**) distorted onto a two-dimensional plane is not merely an isometric or other perspective view of the three-dimensional distribution of transducers, as such an isometric or other perspective view would be considered a three-dimensional representation, such as that shown in various ones of FIGS. **5A**, **5B**, **5C**, and **5D**. The two-dimensional representation may be generated according to the display instructions according to a conformal map or projection, such as a Mercator map or projection, a transverse Mercator map or projection, or other three-dimensional-to-two-dimensional map or projection, known in the art, according to some embodiments.

According to various embodiments, a conformal mapping is a function that preserves local angles. For example, according to some embodiments, when a particular spatial relationship between the plurality of transducers **306** is conformally mapped to the graphical representation **500**, an angle defined between a group of transducers (e.g., **306**) according to the particular spatial relationship is preserved between the corresponding group of transducer graphical elements **502**. In some embodiments, the two-dimensional representation need not be a projection or map from a three-dimensional model, and may merely be any two-dimensional representation, e.g., including an arrangement of transducers.

(98) The two-dimensional representation depicted in FIG. **5E**, according to some embodiments, represents the first domed portion **508a** (e.g., shown in FIGS. **5C**, **5D**) of the depicted transducer-based device as first Mercator projection **518a** and the second domed portion **508b** (e.g., shown in FIGS. **5C**, **5D**) of the depicted transducer-based device as a second Mercator projection **518b**. The first and the second Mercator projections **518a** and **518b** advantageously allow for simultaneous viewing of all the transducer graphical elements **502** and the between graphical elements **504**. Columns **512** and rows **510** are depicted two-dimensionally in FIG. **5E**. In some embodiments, separation graphical element **503** is also depicted in a two-dimensional configuration.

(99) As discussed above, other two-dimensional representations may be implemented and may be user-selectable for viewing. For example, FIG. **5F** illustrates a transverse Mercator projection employed according to some embodiments. In FIG. **5F**, the transverse Mercator projection includes two portions **518c**, **518d**, each of the portions **518c**, **518d** representative of a respective one of first and second domed portions **508a** and **508b** in the corresponding three-dimensional representation. In FIG. **5F**, portion **518d** of the transverse Mercator projection is shown as two parts, each part at least depicting the transducer graphical elements **502** in a respective one of two parts of the domed portion **508b**. In FIG. **5F**, portion **518c** is representative of first domed portion **508a**. In some embodiments, various ones of the columns **512** radiate outwardly radially or quasi-radially from particular ones of a plurality of pole regions **511a** and **511b** represented in the graphical representation **500**. In some embodiments, various ones of the rows **510** are circumferentially arranged about particular ones of a plurality of pole regions **511a** and **511b**.

(100) In some embodiments, at least some of the between graphical elements **504** are not shown in various ones of the displayable two-dimensional representations. For example, in FIG. **5F**, between

graphical elements **504** have been selectively controlled, e.g., in response to user input, not to be visible among the graphical representation. In various embodiments, the transducer graphical elements **502** shown in each of the FIGS. **5E** and **5F** are arranged with respect to one another according to a spatial relationship that corresponds to a spatial relationship that the transducer graphical elements are arranged in the three-dimensional representations shown in various ones of FIGS. **5A**, **5B**, **5C**, **5D**, and **5R**. In various embodiments, the transducer graphical elements **502** shown in each of the FIGS. **5E** and **5F** are arranged with respect to one another according to a spatial relationship that corresponds to a spatial relationship that particular transducers that the transducer graphical elements **502** correspond to, are arranged with respect to one another when a supporting structure (e.g., structure **308**) is in a deployed configuration.

(101) Various computer-executable instructions may be configured to control various input element control functions (e.g., mouse drag functions, touch screen drag functions) between various operating modes such as rotating and panning modes. A rotating mode may be advantageously used for manipulation of a three-dimensional representation of a transducer-based device or other portions of the graphical representation **500** to allow for viewing one or more portions of the three-dimensional representation of the transducer-based device or various portions of the graphical representation **500** that were not previously viewable (e.g., a manipulation between the views shown in FIGS. **5A** and **5B** or a manipulation between the views shown in FIGS. **5C** and **5D**). In some embodiments, a panning mode may be advantageously used for manipulation of a two-dimensional representation of the transducer-based device or other portions of the graphical representation **500** to allow for viewing of different arrangements of various graphical elements in the representation of a transducer-based device or other portions of the graphical representation **500**. For example, in FIG. **5F**, an up-down panning manipulation (e.g., caused in response to a mouse drag or touch screen drag function) may adjust a size of each of the portions **518d** that are representative of domed portion **508b** (e.g., one of the portions **518d** increasing in size while the other portion **518d** decreases in size) or in some cases combine the plurality of portions **518d** into a fewer number of portions (e.g., a single portion **518d**), or in some cases divide portion **518c** representative of the first domed portion **508a** into a plurality of portions **518c**.

(102) In some embodiments, a rotating mode may be advantageously used for manipulation of a two-dimensional representation of the transducer-based device or other portions of the graphical representation **500** to allow for viewing of different arrangements of various graphical elements in the transducer-based device or other portions of the graphical representation **500**. For example, in FIG. **5F**, a rotation mode (for example, caused in response to a mouse drag or touch screen drag function) may be employed to rotate or revolve various ones of the transducer graphical elements **502** or other elements of the graphical representation **500** about a selected one of two pole regions **511a** and **511b**. It is noted in some embodiments, a particular rotation of a first set of graphical elements about one of the pole regions **511a** and **511b** in a first particular rotational direction (e.g., a clockwise direction) may be automatically accompanied by a particular rotation of a second set of graphical elements about the other of the pole regions **511a** and **511b** in second particular rotation direction different than the first particular rotational direction (e.g., a counterclockwise direction).

(103) It is noted that, even though an entirety of the representation of the transducer-based device may be shown in the two-dimensional representation, various panning or rotation modes such as described above may be employed to position various ones of the displayed graphical elements in a configuration that may provide a better understanding of a particular relationship between the graphical elements. For example, in some embodiments, the transducer graphical elements **502k** and **502l** respectively identified as “P:5” and “P:6” in FIG. **5F** correspond to an adjacent pair of transducers, but are displayed apart from one another in the two portions **518d**. A rotation (for example, as described above) about one of the two pole regions **511a**, **511b** may be used to position the transducer graphical elements **502k** and **502l** respectively identified as “P:5” and “P:6” closer together, for example, in the medial region **511c** to better convey information describing the

adjacency of the transducers corresponding to the transducer graphical elements **502k** and **502l**. In some example embodiments, a rotation (for example, as described above) about one of the two pole regions **511a**, **511b** may be used to position the transducer graphical elements **502k** and **502l** adjacently together without any others of the transducer graphical elements **502** positioned therebetween.

(104) In some embodiments, the respective transducers of the adjacent pair of transducers (e.g., an adjacent pair of transducers **306**) corresponding to transducer graphical elements **502k** and **502l** are located a same structural member (e.g., a same one of elongate members **304**). In some embodiments, a region of space that includes a physical portion of the transducer-based device is located between the respective transducers of the adjacent pair of transducers (e.g., an adjacent pair of transducers **306**) corresponding to transducer graphical elements **502k** and **502l**. In various embodiments, the rotation mode synchronizes rotation about one of the pole regions **511a**, **511b** with the rotation about the other of the pole regions **511a**, **511b** such that various transducer graphical elements **502** representative of an adjacent pair of transducers maintain a spatial relationship when rotated into the medial region **511c** that is consistent with the spatial relationship of the corresponding adjacent transducers. In FIG. 5F, various columns of adjacent transducer graphical elements **502** radially extend or converge towards each of the pole regions **511a** and **511b**. The synchronized rotation about one of the pole regions **511a**, **511b** with the rotation about the other of the pole regions **511a**, **511b** allows each of the columns to continue to radially extend or converge towards each of the pole regions **511a** and **511b** at least while the columns are positioned in portion **518c**.

(105) In some embodiments, various ones of these manipulation modes may allow the user to better understand a relationship or interaction between the transducer graphical elements **502** and any displayed physiological information (e.g., intra-cardiac information) displayed in the graphical representation (e.g., as described below at least with respect to FIGS. 5G-5R). In some embodiments, various ones of these manipulation modes may allow the user to better understand a relationship of various ones of the transducers corresponding to various ones of the transducer graphical elements to facilitate a selection or non-selection thereof. It is noted that various ones of the manipulations modes are not limited to the two-dimensional representation of FIG. 5F and may be employed with other forms of two-dimensional representations. For example, in some embodiments, the transducer graphical elements **502m** and **502n** respectively identified as “T:5” and “A:5” in FIG. 5E correspond to an adjacent pair of transducers (e.g., an adjacent pair of transducers **306**), but are displayed apart from one another. An up-down panning manipulation (for example, as described above) may be employed to better visualize the adjacency of the transducers corresponding to the transducer graphical elements **502m** and **502n** respectively identified as “T:5” and “A:5”. In some embodiments, the respective transducers of the adjacent pair of transducers (e.g., an adjacent pair of transducers **306**) corresponding to transducer graphical elements **502m** and **502n** are located on different structural members (e.g., different or separate ones of elongate members **304**). In some embodiments, a region of space that does not include any physical portion of the transducer-based device is located between the respective transducers of the adjacent pair of transducers (e.g., an adjacent pair of transducers **306**) corresponding to transducer graphical elements **502m** and **502n**.

(106) A Mercator projection such as that employed in embodiments associated with FIG. 5E may include various distortions in some of the elements (e.g., transducer graphical elements **504**) at least proximate the boundary regions **517a**, **517b** of the projection. In some embodiments, the columns **512** of graphical elements **501** act like converging lines of longitude in a three-dimensional representation (e.g., FIGS. 5A, 5B, 5C and 5D) and the distortions at least proximate the boundary regions **517a**, **517b** may be provided to account or compensate for the convergence of columns **512**. It is noted, however, that a panning mode (e.g., a left-right panning mode) that may move one of the boundary regions **517a**, **517b** inwardly or centrally within the graphical

representation may, in some embodiments, maintain the distortions in the various graphical regions that occupy or move along with the moved one of the boundary regions **517a**, **517b**. Moving these distorted regions inwardly or centrally within the field of view of the user may not provide, in some cases, a readably understandable representation of various facets of these graphical elements (e.g., a spatial relationship therebetween). The two-dimensional representation depicted in FIG. 5F, on the other hand, centralizes the graphical elements (e.g., transducer graphical elements **502**) that are located in the boundary regions **517a**, **517b** of FIG. 5F centrally proximate the pole regions **511a**, **511b** of FIG. 5F with reduced levels of distortions. In this regard, the graphical representation of FIG. 5F provides a good understanding of the various relationships (e.g., spatial relationships) associated with “pole” areas (e.g., areas where the columns **512** converge like lines of longitude) of the corresponding three-dimensional representation. On the other hand, the graphical representation of FIG. 5E provides a good understanding of the various relationships (e.g., spatial relationships) associated with “equatorial areas (e.g., equatorial regions of columns **512** when acting like lines of longitude) of the corresponding three-dimensional representation. In some embodiments, two or more different two-dimensional representations are concurrently displayed via an input-output device system (e.g., **120**, **320**). In some embodiments, both of the two-dimensional representations shown in FIGS. 5E and 5F are concurrently displayed via an input-output device system (e.g., **120**, **320**).

(107) In each of the FIGS. 5E and 5F, each of the transducer graphical elements **502** has a respective shape that is the same, or generally the same as, a shape of at least a portion of a corresponding transducer (e.g., transducer **306**) that the transducer graphical element represents. In some embodiments, each of the transducer graphical elements **502** has a respective shape that is the same, or generally the same, as shape of an electrode (e.g., electrode **315**) of a corresponding transducer (e.g., transducer **306**) that the transducer graphical element represents. In each of the FIGS. 5E and 5F, the shape of each of at least some of the transducer graphical elements **502** is distorted and deviates in some aspects from the respective shape of a corresponding electrode. Unlike a distortion caused by the use of “perspective” (e.g., a varying of an appearance of objects in respect to their perceived relative distance and positions) in corresponding three-dimensional representations (e.g., FIGS. 5A, 5B, 5C, 5D), various graphical elements in FIGS. 5E and 5F employ other forms of distortion (for example, as described above in this description). For example, in FIG. 5F, increased levels of distortions (e.g., increased sizes or dimensions, increased stretching) accompany various ones of the transducer graphical elements **502** that are increasingly spaced from pole regions **511a** and **511b**. In FIG. 5E, increased levels of distortions (e.g., increased sizes or dimensions, increased stretching) accompany various ones of the transducer graphical elements **502** that are spaced relatively close to the boundary regions **517a**, **517b** as compared with various ones of the transducer graphical elements that are located relatively far from the boundary regions **517a**, **517b**. In either case, and unlike the perspective-based distortions employed in some three-dimensional representations, some of the more highly distorted transducer graphical elements **504** include enlarged shapes (e.g., relative to less distorted graphical elements **502** displayed centrally in each of two-dimensional representations) and correspond to transducers that would be spaced relatively farther from a viewer (e.g., with the less distorted transducer graphical elements **502** corresponding to transducers that would be spaced relatively closer to the viewer).

(108) In some embodiments associated with FIG. 5F, a rotation mode may be employed to rotate at least some of the transducer graphical elements **502** about one of the pole regions **511a** and **511b** and changes in the shape or size of various ones of transducer graphical elements **502** during the rotation may occur. In some embodiments associated with FIG. 5F, a rotation mode may be employed to rotate at least some of the transducer graphical elements **502** about one of the pole regions **511a** and **511b** to vary a level of distortion comprised by various ones of transducer graphical elements **502**. For example, the transducer graphical element **502o** identified as “A:6” may, in some embodiments, be rotated about pole region **511b** with its size or level distortion

reducing as it rotates toward medial region **511c**.

(109) Referring back to FIG. **6A**, the computer-executable display instructions associated with block **604** may include, in some embodiments, various instructions configured to allow for variations in the viewable content of the graphical representation. The computer-executable display instructions associated with block **604** may include various instructions (e.g., computer-executable instructions associated with block **606**) configured to allow for selective inclusions of the transducer graphical elements **502** and the selective inclusion of the between graphical elements **504** among the graphical representation **500**. (In this regard, although block **606** is shown separately from block **604**, block **606** may be a particular implementation of block **604** and such block may be combined into a single block.) In some example embodiments, the display instructions associated with block **606** may include instructions that allow for the selective inclusion of identification labels **513** that identify various ones of the transducer graphical elements **502**. In various example embodiments, each of the identification labels **513** employs an alpha-numeric format including a letter representative of the column **512** in which a corresponding transducer graphical element is located and a number representative of a location of the transducer graphical element **502** in the corresponding column **512**. Other identification schemes may be employed in other embodiments.

(110) Having discussed embodiments associated with blocks **604** and **606** in FIG. **6A**, a discussion will now begin regarding embodiments where block **604** follows block **602**. (Recall that block **606** may be included within block **604**, in some embodiments.) Block **602**, in some embodiments, is associated with instructions (e.g., input or acquisition instructions included in a program) that cause the data processing device system (e.g., data processing device systems **110** or **310**) to acquire or receive intra-cardiac information. Intra-cardiac information can take various forms, including, but not limited to, e.g., electrical information or a derivation thereof (e.g., electrical potential information, such as intra-cardiac electrogram information; electrical impedance information, such as fluidic or non-fluidic cardiac tissue impedance information; electrical conductivity information, such as fluidic or non-fluidic cardiac tissue electrical conductivity), thermal information or a derivation thereof (e.g., temperature information), fluid property information or a derivation thereof (e.g., blood flow information, blood pressure information), force information or a derivation thereof (e.g., contact information), and mapping information or a derivation thereof (e.g., electrical mapping; physical feature mapping, such as anatomical feature mapping). In various embodiments, intra-cardiac information may be related to any physiological parameter information related to a heart chamber. In various embodiments, intra-cardiac information may include any information related to, or resulting from an interaction with intra-cardiac tissue. By way of non-limiting example, interaction with intra-cardiac tissue may include an interaction made by way of a diagnostic procedure or treatment procedure.

(111) Intra-cardiac information may be acquired or received by various methods and from various device systems. For example, FIG. **6B** shows an exploded view of block **602**, according to some embodiments. The particular implementation of block **602** illustrated in FIG. **6B** is labeled as block **602-1**. In this regard, FIG. **6B** includes a sub-block **602-1a** associated with computer-executable instructions that receive or acquire the intra-cardiac information via data sampling performed by a transducer-based device system (e.g., which may be at least part of the data input-output device system **120**, **320**) deployed externally from an intra-cardiac chamber or cavity (e.g., outside the chamber or cavity or outside a body comprising the chamber or cavity). In this regard, the method **600** may include a sub-block **602-1b** in which the intra-cardiac information is generated (e.g., via generation instructions executable by a data-processing device system, e.g., **110**, **310**) from data provided or sampled (e.g., according to the computer-executable sampling instructions associated with block **602-1a**) by the transducer-based device system deployed externally from the intra-cardiac chamber or cavity. Such generation according to block **602-1b**, in some embodiments, may involve the associated instructions configuring the data processing device system (e.g., **110**, **310**) to

recognize and identify (e.g., in memory device system **130, 330**) the incoming sampled data or a derivation thereof as a set of respective intra-cardiac information (e.g., as an electrocardiogram or other form of intra-cardiac information discussed herein). By way of non-limiting example, various transducer-based device systems employed as per block **602-1a** may include various fluoroscopy device systems, ultra-sound device system, magnetic resonance device systems, computerized tomography device systems, and transthoracic electrocardiographic mapping device systems. It is noted that some of the embodiments associated with block **602-1a** are considered to employ non-invasive methods or technologies.

(112) FIG. **6C** shows an exploded view of block **602**, according to some embodiments. The particular implementation of block **602** illustrated in FIG. **6C** is labeled as block **602-2**. In this regard, FIG. **6C** includes a sub-block **602-2a** associated with computer-executable instructions that are configured to cause reception or acquisition of the intra-cardiac information via data sampling performed by a transducer-based device system (e.g., which may be at least part of the data input-output device system **120, 320**) deployed internally to an intra-cardiac chamber or cavity. In this regard, the method **600** may include a sub-block **602-2b** in which the intra-cardiac information is generated (e.g., via generation instructions executed by a data-processing device system (e.g., **110, 310**) from data provided or sampled (e.g., by the sampling instructions associated with block **602-2a**) by the transducer-based device system deployed internally within the intra-cardiac chamber or cavity (e.g., inside the chamber or cavity). Such generation according to block **602-2b**, in some embodiments, may involve the associated instructions configuring the data processing device system (e.g., **110, 310**) to recognize and identify (e.g., in memory device system **130, 330**) the incoming sampled data or a derivation thereof as a set of respective intra-cardiac information (e.g., as an intra-cardiac electrogram or other form of intra-cardiac information discussed herein). By way of non-limiting example, various transducer-based device systems that may be internally deployed within an intra-cardiac chamber include by way of non-limiting example transducer-based device systems **200, 300**, where data may be sampled according to the sampling instructions associated with block **602-2a** by each of one or more transducers of the transducer-based device system, a portion of the transducer-based device system including the one or more transducers positionable in a cardiac chamber during the sampling, such that the generation instructions associated with block **602-2b** may be configured to cause generation of the intra-cardiac information based at least in part on the sampled data. Various transducer-based device systems employed as per block **602-2a** may include various intravascularly deployable or percutaneously deployable catheter device systems. Various transducer-based device systems employed as per block **602-2a** may include detection capabilities, mapping capabilities, diagnostic capabilities, treatment capabilities, or any combination thereof. It is noted that some of the embodiments associated with block **602-2a** may be considered to employ invasive methods or technologies.

(113) Referring back to FIG. **6A**, the displaying of the graphical representation according to the computer-executable instructions associated with block **604** may, in some embodiments, include causing displaying of a graphical representation of intra-cardiac information generated, acquired, or received according to the computer-executable instructions associated with block **602**. Various embodiments may process or analyze (e.g., according to the instructions associated with block **604**) the transducer data received by the data processing device system according to the computer-executable instructions associated with block **602** in order to, for example, generate and cause the displayed graphical representation **500** to include the intra-cardiac information. Various embodiments may process or analyze the transducer data received by the data processing device system according to the instructions associated with block **602** in order to, for example, generate and possibly cause the displayed graphical representation **500** to include a map of the intra-cardiac information. In various embodiments, the data is sampled by a transducer-based device system from a plurality of locations in a cardiac chamber and the generation instructions associated with block **602** cause mapping of each of a plurality of parts or values of the intra-cardiac information

(which may represent a sensed tissue electrical characteristic or other information) to a respective one of the plurality of locations in the cardiac chamber. In some of these various embodiments, the display instructions associated with block **604** are configured to cause an input-output device system (e.g., **120, 320**) to display the plurality of parts of the intra-cardiac information with a first spatial relationship that is consistent with a second spatial relationship between the plurality of locations in the cardiac chamber (e.g., a map of the parts of the intra-cardiac information is displayed). In some embodiments, the transducer-based device includes a plurality of transducers (e.g., transducer-based device **200, 300**) and the sampling instructions (e.g., **602-1a, 602-2a**) are configured to cause the sampled data to be sampled concurrently from the plurality of locations in the cardiac chamber.

(114) It should be noted that some embodiments need not be limited to any particular form of processing or analysis of the transducer data received by the data processing device system according to the instructions associated with block **602**. Although various display procedures can be implemented according to the computer-executable instructions associated with block **604** to display intra-cardiac information, these display procedures can be performed at other times, such as any time during the generation of or after the display of a graphical representation of at least a portion of a transducer-based device (e.g., as per the computer-executable instructions associated with block **606**).

(115) An example of a display of a graphical representation that at least depicts intra-cardiac information according to various embodiments (such as those represented by block **604** in FIG. **6A**) would be a mapping locating the position of the ports of various bodily openings positioned in fluid communication with a cardiac chamber. For example, in some embodiments, it may be desired to determine intra-cardiac information indicating the locations of various ones of the pulmonary veins or the mitral valve that each interrupts an interior surface of an intra-cardiac cavity such as a left atrium.

(116) In some example embodiments, the mapping is based at least on locating such bodily openings by differentiating between fluid and tissue (e.g., tissue defining a surface of a bodily cavity). There are many ways to differentiate tissue from a fluid such as blood or to differentiate tissue from a bodily opening in case a fluid is not present. Four approaches may include by way of non-limiting example: 1. The use of convective cooling of heated transducer elements by fluid. A slightly heated arrangement of transducers that is positioned adjacent to the tissue that forms the interior surface(s) of a bodily cavity and across the ports of the bodily cavity will be cooler at the areas which are spanning the ports carrying the flow of fluid. 2. The use of tissue impedance measurements. A set of transducers positioned adjacently to tissue that forms the interior surface(s) of a bodily cavity and across the ports of the bodily cavity can be responsive to electrical tissue impedance. Typically, heart tissue will have higher associated tissue impedance values than the impedance values associated with blood. 3. The use of the differing change in dielectric constant as a function of frequency between blood and tissue. A set of transducers positioned around the tissue that forms the interior surface(s) of the atrium and across the ports of the atrium monitors the ratio of the dielectric constant from 1 KHz to 100 KHz. Such can be used to determine which of those transducers are not proximate to tissue, which is indicative of the locations of the ports. 4. The use of transducers that sense force (e.g., force sensors). A set of force detection transducers positioned around the tissue that forms the interior surface of the bodily cavity and across the bodily openings or ports of the bodily cavity can be used to determine which of the transducers are not engaged with the tissue, which is indicative of the locations of the ports.

(117) The graphical interface of FIG. **5G** includes various regions **525a, 525b, and 525c** (e.g., part of a plurality of regions collectively referred to as regions **525**) added to the graphical representation **500** shown in FIG. **5E**. The regions **525** could be displayed according to the instructions associated with block **604** in FIG. **6A** in some embodiments. Although, such regions **525** could be displayed at other times or according to other instructions. In some embodiments, the

graphical interface depicted in FIG. 5G is generated after the transducer-based device is received in a bodily cavity having various anatomical features of interest and the drop-down selection box **526** identified as “Surface Map” is activated via the input-output device system to select a mode referred to as “Flow”. Techniques for flow-based mapping techniques are disclosed in commonly assigned U.S. Patent Application Publication No.: US 2008/0004534. In various embodiments associated with various ones of FIGS. 5, the anatomical features of interest are ports of a mitral valve and various pulmonary veins positioned in fluid communication with an intra-cardiac cavity (e.g., a left atrium in some embodiments). In these various embodiments, the transducers of the transducer-based device are distributed adjacent respective regions in the intra-cardiac cavity that can include relatively lower blood flow regions (e.g., adjacent a tissue surface of the intra-cardiac cavity) and relatively higher flow regions (e.g., over the ports of the intra-cardiac cavity). It is noted that relatively lower blood flow regions in the intra-cardiac cavity may occur when a transducer is positioned in contact with a tissue surface to restrict blood flow at the contacted tissue. In some example embodiments, a relatively large number of transducers in the distribution advantageously allow for each of the transducers to be positioned adjacent their corresponding regions with little or no repositioning of the transducer-based device thereby facilitating an obtaining of transducer-based data concurrently from multiple locations in the bodily cavity.

(118) One or more of the above-discussed mapping procedures may be implemented according to instructions associated with block **604** to display a graphical representation **500** that includes intra-cardiac information that indicates at least a portion of one or more anatomical features based at least on an analysis of the transducer data acquired or received according to block **602**. In some of these embodiments, the one or more anatomical features are the ports of various bodily openings (e.g., pulmonary veins, left atrial appendage, mitral valve) positioned in fluid communication with the intra-cardiac cavity and the transducer data includes data containing various blood flow data within the bodily cavity. In various embodiments, the data sampled according to block **602** is temperature data and the graphical representation **500** includes a graphical representation of at least some of the temperature data or a derivation thereof (e.g., a map of temperature distribution in the cardiac chamber). For example, in various embodiments in which the use of convective cooling of heated transducer elements by fluid is employed to distinguish blood flow adjacent to the tissue that forms the interior surface(s) of a cardiac chamber from blood flow across the ports of the cardiac chamber, temperature data associated with the convective cooling can be sampled and displayed to provide the graphical representation of the intra-cardiac information. In FIG. 5G, the relatively large region **525a** (e.g., shown as two parts in this particular orientation of the two-dimensional representation) is associated with the mitral valve, region **525b** is associated with the left atrial appendage, and regions **525c** are associated with various pulmonary vein groups. Each of the regions **525** is depicted in the graphical representation **500** with a graduated pattern provided by the flow identifier **527a** in the graphical interface of FIG. 5G. In some embodiments, flow identifier **527a** provides a graduated scale from a condition indicated as “Contact” (e.g., when a transducer is contact with cardiac tissue) to a condition indicated as “Flow” (e.g., when a transducer overlies a port in the cardiac chamber). A graduated pattern can be employed to indicate various regions in the graphical representation corresponding to different regions of flow in the intra-cardiac cavity. The identified regions **525** may be identified by any suitable methods including the use of gray-scale patterns, different colors, different opacities, different intensities and different shapes. It is understood that other embodiments may employ other techniques to identify regions in the graphical representation corresponding to a desired anatomical feature. For example, transducer-based data containing blood and tissue impedance information may be employed to determine regions **525** as shown in FIG. 5H. In various embodiments, drop-down selection box **526** may be operated to allow for the selective inclusion in the graphical representation of impedance data (e.g., tissue impedance data) or conductivity data (e.g., tissue conductivity data) sampled according to the instructions associated with block **602**. In FIG. 5H, the

relatively large region **525-1a** (e.g., shown as two parts in this particular orientation of the two-dimensional representation) is associated with the mitral valve, region **525-1b** is associated with the left atrial appendage, regions **525-1c** are associated with various pulmonary vein groups. Each of the regions **525** is depicted in the graphical representation **500** with a graduated pattern provided by the impedance identifier **527b** in the graphical interface of FIG. 5H. In some embodiments, impedance identifier provides a graduated scale from a condition indicated as “Low” (e.g., when a transducer overlying a port in the cardiac chamber is used to measure the electrical impedance of blood) to a condition indicated as “High” (e.g., when a transducer adjacent cardiac tissue is used to measure the electrical impedance of cardiac tissue). A graduated pattern can be employed to indicate various regions in the graphical representation corresponding to different regions of impedance in the intra-cardiac cavity. The identified regions **525** may be identified by any suitable methods including the use of gray-scale patterns, different colors, different opacities, different intensities, and different shapes. It is understood that other embodiments may employ other techniques to identify regions in the graphical representation corresponding to a desired anatomical feature.

(119) Identification of the regions **525**, which may represent anatomical features, may be motivated for various reasons. For example, in embodiments in which transducers of transducer-based device are activated to treat, diagnose, or investigate various regions in a bodily cavity, the mapping of various regions **525** and their spatial relationship relative to one another may impact the efficacy of the treatment, diagnostic, or investigative procedure. For example, in situations in which at least some of the transducers of a transducer-based device are employed to ablate various regions within an intra-cardiac cavity (e.g., to treat atrial fibrillation), ablation of a pulmonary vein may result in an undesired condition referred to as pulmonary stenosis. Identification of various ones of the regions **525c** (e.g., **525-1c**) in the graphical representation along with their spatial relationship with various ones of the transducers at various times may be employed to reduce occurrences of this undesired condition.

(120) Without limitation, other forms of intra-cardiac data (e.g., as received, acquired, provided, generated, or sampled per block **602**) that may form part of the graphical representation **500** may include pressure data (e.g., blood pressure data, contact pressure data), electrophysiological activation timing data, isochronal data, propagation data, electrophysiological isopotential data, and other electrophysiological voltage data. Without limitation, various maps of intra-cardiac data may include tissue contact maps (e.g., contact maps inferred from flow data, impedance data, conductivity data, which may map an interior tissue surface region of a cardiac chamber), activation maps indicating the local activation times associated with a particular cardiac event, isochronal maps where contour lines may delineate regions of equal activation times associated with a particular cardiac event, propagation maps providing a dynamic representation of the moving activation wave-front associated with a particular cardiac event, isopotential maps, and various other voltage maps associated with intra-cardiac electrical activity. Various representations (e.g., maps) of intra-cardiac information may include portions corresponding to values measured at specific locations within an intra-cardiac cavity and portions corresponding to values that are interpolated (for example, interpolated from values measured at specific locations within an intra-cardiac cavity).

(121) In some embodiments, intra-cardiac information is depicted in the graphical representation statically or relatively statically. That is, the displayed intra-cardiac data remains unaltered or relatively unaltered during a defined display period. In some embodiments, intra-cardiac information is depicted in the graphical representation **500** such that variances in the intra-cardiac information are shown occurring over a defined display period. In some embodiments, the graphical representation includes an animation of changes in intra-cardiac information. FIGS. 5I, 5J, and 5K show graphical representation **500** including changes in intra-cardiac information occurring at three successive particular times during a display period. In some embodiments, the

intra-cardiac information displayed in each of FIGS. 5I, 5J, and 5K includes intra-cardiac voltage data showing a distribution of voltage values of intra-cardiac electrogram voltage data sampled (e.g., using a transducer-based device system **200**, **300**, e.g., according to the instructions associated with block **602**) at a particular time (e.g., each of the FIGS. 5I, 5J, and 5K associated with a respective different particular time), each of the voltage values associated with intra-cardiac electrogram data or information sampled at the particular time at a respective one of a plurality of locations in an intra-cardiac cavity (e.g., by respective transducers).

(122) In some embodiments, the displayed voltage values include positive values, negative values, or both positive and negative values. For example, various positive and negative voltage values are indicated in the graphical representation **500** shown in each of FIGS. 5I, 5J, and 5K, a magnitude and positive or negative indication varying in accordance with the voltage identifier **527c**. The voltage values shown in FIGS. 5I, 5J, and 5K may be identified by any suitable methods including the use of gray-scale patterns, different colors, different opacities, different intensities, and different shapes. In some embodiments, a grey-scale or color-scale pattern extending across both a positive and negative range is employed to represent the various voltage values or ranges of voltage values. In various embodiments, at least some of the displayed voltage values may include a peak value corresponding to a peak amplitude portion of a waveform representative of the intra-cardiac electrogram data or information associated with the particular displayed voltage values. In various embodiments, at least some of the displayed voltage values may include a non-peak value corresponding to non-peak amplitude portion of a waveform representative of the intra-cardiac electrogram data or information associated with the particular displayed voltage values. Without limitation, various ones of the displayed voltage values may include derivations of the actual measured voltage values (e.g., values derived from the actual measured voltage values) including RMS values, peak-to-peak values.

(123) In various embodiments, the sequence depicted in FIGS. 5I, 5J, and 5K shows time-varying changes in the voltage values associated with the intra-cardiac voltage data or information sampled at respective ones of a plurality of locations in an intra-cardiac cavity. By concurrently sensing intra-cardiac voltage data at each of plurality of locations within an intra-cardiac cavity at various successive times, a relationship indicating changes among all the voltage values associated the intra-cardiac voltage data or information sampled at various successive times across all of a plurality of locations in an intra-cardiac cavity is shown. For example, FIGS. 5I, 5J, and 5K include a depiction of various voltage values represented by moving wave-front **529** (sometimes referred to as propagation **529**). In this case, the moving wave-front **529** of voltage values propagates generally in a direction indicated by arrow **529a** (not part of the graphical representation **500** but provided to clarify the direction of propagation of wave-front **529** shown in the sequence depicted in FIGS. 5I, 5J, and 5K). It is understood that the propagation of the wave-front **529** of voltage values is not limited to the direction indicated by arrow **529a**, but rather, is influenced by various physiological factors associated with the flow of various electrical signals within the cardiac tissue.

(124) In some embodiments, the appearance of a propagating wave-front **529a** is caused by changes in the voltage values at each of a plurality of locations in the graphical representation **500**, the changes at each particular location represented by changes in a visual characteristic of the voltage value at that particular location. In this regard, an essentially real-time or quasi-real-time representation of the propagation of various electrical signals within an intra-cardiac cavity may be depicted.

(125) It is noted that in various example embodiments such as those associated with various ones of FIGS. 5G, 5H, 5I, 5J, and 5K, at least some of the graphical elements **501** (e.g., transducer graphical elements **502**, between graphical elements **504**) are depicted as overlaid or superimposed on the displayed graphical representation **500** that includes a depiction of the acquired intra-cardiac information. In various embodiments, various ones of the graphical elements **501** (e.g., various ones of the transducer graphical elements **502**) are depicted with a transparent, semi-transparent, or

translucent appearance that allows a user to view regions of the intra-cardiac information that underlie each of the various ones of the graphical elements **501** or visual changes in the regions of the intra-cardiac information that underlie each of the various ones of the graphical elements **501**. This configuration can be especially advantageous when one hundred, two hundred, or even more transducers are employed percutaneously to sample or gather the intra-cardiac information from a cardiac chamber. A graphical representation **500** that employs a similar, equal, or greater number of graphical elements **501** (e.g., transducer graphical elements **502**, between graphical elements **504** or both transducer graphical elements **502** and between graphical elements **504**) may obstruct a required viewing of the displayed intra-cardiac information, especially when transducer graphical elements **502** having a shape consistent with the shapes of corresponding ones of the transducers are employed or when transducer graphical elements having distorted appearances (e.g., enlarged distorted appearances described above) are employed. These situations may be effectively mitigated by the use of various graphical elements **501** having a transparent, semi-transparent, or translucent appearance.

(126) Having described examples of the graphical representation (e.g., **500**) displayed according to the instructions associated with block **604** in FIG. **6A**, the definition of a graphical path (e.g., via input-output device system **120**, **320**) within or among such graphical representation (e.g., **500**) will be described, according to some embodiments. In this regard, instructions associated with block **610** in FIG. **6A** may configure a data processing device system (e.g., **110**, **310**) to define, display, or both define and display such a graphical path. In various embodiments, the graphical path is defined, displayed, or both defined and displayed as including a plurality of the graphical elements **501**, according to the instructions associated with block **610**.

(127) For example, as shown in FIG. **5L**, a user may locate a mouse cursor over a transducer graphical element **502g**, depress a mouse button at that time, and while continuing to depress the mouse button (e.g., maintaining its activated state), move the mouse cursor **519** over transducer graphical element **502h** (FIG. **5M**), then to transducer graphical element **502j** (e.g., from location **519a** to location **519b** generally following a path indicated by arrow **539** (not part of the displayed output) in FIG. **5N**), then around a loop back to transducer graphical element **502g** (e.g., from location **519b** around the graphical path corners to location **519c** in FIG. **5O**, then to location **519d** in FIG. **5P** and location **519e** (e.g., ending at between graphical element **504f**) in FIG. **5Q**) to define the rectangular-shaped graphical path shown by highlighted transducer graphical elements (FIGS. **5M-5Q**), and at such time, release the mouse button (e.g., causing its deactivated state), according to some embodiments. According to some embodiments, the progression of movements of the mouse cursor **519** from FIG. **5L-5Q** progressively selects the respective graphical elements (transducer graphical elements **502** in this example, but also or instead, between graphical elements **504** in other embodiments). (For clarity, only part of the graphical interface shown in other various ones of FIG. **5** is shown in FIGS. **5L**, **5M**, **5N**, **5O**, **5P** and **5Q**.) The data processing device system (e.g., **110**, **310**) may be configured by the instructions associated with block **610**, according to some embodiments, to interpret at least (a) the initial depression of the mouse button and the location of the mouse cursor at that time to be the initiation of a definition of a graphical path at the graphical element **501** closest to the location of the mouse cursor; (b) the subsequent movement of the mouse cursor while the mouse button is depressed to be the definition of an intermediate portion of the graphical path, which may include an intermediate location at a particular graphical element **501** or may include at least one elongate path portion including a plurality of graphical elements **501** in a row; and (c) the release of the mouse button to be the termination of the definition of the graphical path at a graphical element **501** closest to the location of the mouse cursor at the time of the release of the mouse button. It is noted that the use of mouse cursor **519** is employed in FIG. **5** merely for the convenience of discussion, and other embodiments may employ other forms of motion-based user input elements (e.g., sliding of contact across a touch screen or touch pad or the movement of other pointing-based interfaces) of other forms of indicators employed by various motion-based

user input elements. In addition, other or additional user input or inputs than those discussed above may be required to enable definition of a graphical path. In this regard, it should be noted that various other embodiments are not limited to the details of these embodiments, which are referred to for purposes of illustration only.

(128) Further in this regard, the graphical path defined in accordance with the instructions associated with block **610** may be displayed in various forms, shapes, or configurations including embodiments that include, by way of non-limiting example, an elongated portion, a continuous portion, an interrupted portion, a linear portion, an arcuate portion, a portion defining an obtuse angle, a portion defining an acute angle, a beginning portion (e.g., a portion defining or associated with a beginning or start of the definition of the graphical path), an end portion (e.g., a portion defining or associated with an end or termination of the definition of the graphical path), an open or closed circumferential portion, or any combination thereof. In various embodiments, a graphical path defined in accordance with the instructions associated with block **610** may include a plurality of graphical-path-elements, which may be graphical elements **501**, such as transducer graphical elements **502**, between graphical elements **504**, or both. In various embodiments, a graphical path defined in accordance with the instructions associated with block **610** may include selection of some but not all of a plurality of selectable graphical-path-elements, such as graphical elements **501**.

(129) The definition of the graphical path in accordance with the instructions associated with block **610** may be accomplished at least in part by execution of such instructions by the data processing device system (e.g., **110**, **310**) in response to various user instructions, inputs, or actions. For instance, in some embodiments, a user instruction, input or action may originate from a user clicking a mouse button over a particular region or regions of graphical representation **500**. In this case, various instructions may configure the data processing device system to recognize this user instruction when it is received via an input-output device system (e.g., **120**, **320**) as a user instruction to form or define at least a portion of the graphical path. In some embodiments, the definition of the graphical path need not be defined according to user-input and, in some embodiments, may be automatically defined, e.g., based on anatomical feature locations (e.g., one or more regions **525**—see FIG. 5Q, e.g.).

(130) In some embodiments where user input facilitates graphical path definition, method **600** may include a block **608** associated with input-processing instructions indicating reception or reception and processing of various user inputs. In some embodiments, the instructions associated with block **608** include instructions (e.g., associated with block **608a**) configured to cause reception of first user input via an input-output device system (e.g., **120**, **320**, such as a mouse button click), and in response to receiving the first user input, place a first user input element in an activated state (e.g., the data processing device system **110**, **310** records in memory device system **130**, **330** that the mouse button is in an activated state due to reception of an indication of the mouse button click). In some embodiments, input-processing instructions associated with block **608** include instructions (e.g., associated with block **608b**) configured to cause reception of second user input via an input-output device system (e.g., **120**, **320**, such as a release of the mouse button), and in response to receiving the second user input, place the first user input element in a deactivated state (e.g., the data processing device system (e.g., **110**, **310**) records in memory device system (e.g., **130**, **330**) that the mouse button is in a deactivated state due to reception of an indication of the mouse button release). In some embodiments, input-processing instructions associated with block **608** include instructions (e.g., associated with block **608c**) configured to cause reception of motion-based user input via an input-output device system (e.g., **120**, **320**, such as movement of the mouse cursor).

(131) In various embodiments, the graphical path definition instructions associated with block **610** are configured to define a graphical path among the displayed graphical representation (e.g., **500**) including a first location, a second location, and a third location, according to the instructions associated with blocks **610a**, **610b**, and **610c**. In some embodiments, the instructions associated

with block **610a** configure the data processing device system (e.g., **110, 310**) to define the first location (e.g., an initial or first graphical element or element set (e.g., **502g** in the example of FIG. 5L)) on the graphical path being defined according to a first parameter set associated with the first user input (e.g., a location (an example of a parameter) of the mouse cursor when the mouse button is clicked (an example of the first user input)). In some embodiments, the instructions associated with block **610b** configure the data processing device system to define the second location (e.g., a terminating or second graphical element or element set (e.g., **502g** closing the loop in the example of FIG. 5Q)) on the graphical path according to a second parameter set associated with the second user input (e.g., a location (an example of a parameter) of the mouse cursor when the mouse button is released (an example of the second user input)). In some embodiments, the instructions associated with block **610c** configure the data processing device system to define the third location (e.g., a third or internal or intermediate graphical element or element set between the initial and terminating graphical elements or graphical element sets (e.g., **502i** in the example of FIG. 5N) on the graphical path other than the first and the second locations according to a path traced by the motion-based user input (e.g., movement of the mouse cursor). In some embodiments, the third, intermediate location on the graphical path is part of an elongate path portion of the graphical path (e.g., the row of four transducer graphical elements including transducer graphical elements **502h, 502i, and 502j** in the example of FIG. 5N). In this regard, the instructions associated with block **610d** may configure the data processing device system to define the elongate path portion on the graphical path according to the path traced by the motion-based user input. However, in some embodiments, the elongate path portion and the third location may be distinct.

(132) In various embodiments, as discussed above, the first user input (e.g., a mouse button click) precedes the motion-based user input (e.g., the movement of the mouse cursor) in the definition of the graphical path. Also, as discussed above, in some embodiments, the first and the second locations defined on the graphical path indicate respective ends or terminations of the graphical path. In some embodiments, one of the first and the second locations may be a location of a portion of the graphical path defined first during the definition of the graphical path and the other of the one of the first and the second locations may indicate a location of a portion of the graphical path defined last during the definition of the graphical path. In some embodiments, one of the first and the second locations may be a location of a portion of the graphical path displayed first (e.g., via in the input-output device system (e.g., **120, 320**) in accordance with display instructions associated with block **612**) during a display of the graphical path, and the other of the first and the second locations may be a location of a portion of the graphical path displayed last (e.g., via in the input-output device system (e.g., **120, 320**) in accordance with the display instructions associated with block **612**) during the display of the graphical path. In some embodiments, the first and the second locations indicate a same location or substantially the same location on the graphical path, such as when the graphical path is a closed path (e.g., a path having a closed form or continuous form, a looped form or circumferential form, like the example of FIG. 5Q). In some embodiments involving a closed path or substantially closed path, one of the first and the second locations may be a location of a portion of the graphical path defined or displayed first and the other of the first and the second locations may indicate a location of a portion of graphical path defined or displayed last, the first and the second locations sufficiently close to one another to impart a closed form or the appearance of the closed form onto the graphical path.

(133) Definition of the graphical path may be motivated by different reasons. For example, in some embodiments, an activation (e.g., according to instructions associated with block **614**) of various transducer sets of a transducer-based device (e.g., **200, 300, or 400**), initiated during or after the completion of the definition of the graphical path according to the instructions associated with block **610**, may cause energy sufficient for tissue ablation along an ablation path corresponding to the defined graphical path. In other words, for example, transducers in the transducer-based device that correspond to the selected transducer graphical elements **502** in the graphical path may be

activated, such as being caused to transmit energy sufficient for tissue ablation along an ablation path corresponding to the defined graphical path, according to some embodiments.

Advantageously, in some embodiments, the ability to define a graphical path based at least on a graphical representation that includes at least a representation of intra-cardiac information may allow for enhanced results, or a possible reduction in undesired results during a subsequent ablation of cardiac tissue within an intra-cardiac cavity (e.g., an intra-cardiac cavity that is the source of the intra-cardiac information discussed above) when the graphical path acts as a template for a desired ablation path. In this regard, a desired ablation path may be defined based at least on a modeled graphical path that may be generated based at least on various possible constraints indicated by the graphical representation of the intra-cardiac information. For example, various representations of intra-cardiac information that indicate at least a portion of one or more anatomical features (e.g., regions **525**, which may represent various cardiac ports provided by the pulmonary veins, left atrial appendage, or mitral valve as shown in FIGS. **5G** and **5H** by way of non-limiting example) may be used to assist a user or the data processing device system (e.g., **110**, **310**) in defining a graphical path that acts as a basis for a subsequent ablation path that takes into consideration (e.g., avoids) these anatomical features and reduce occurrences of undesired complications (e.g., stenosis which may arise if ablative energy is applied to particular ones of these anatomical features).

(134) In various embodiments, as discussed above, the graphical representation **500** may include a representation of various transducers (e.g., by way of transducer graphical elements **501**) of a transducer-based device (e.g., **100**, **200**, **300** or **400**) positioned within the intra-cardiac cavity. For example, a mapping indicating a particular positioning, pose, or orientation of the transducer-based device in the intra-cardiac cavity, and in particular, a spatial positioning between various ones of the transducers and various regions of the depicted intra-cardiac information may be displayed. In some of these various embodiments, the graphical representation **500** may form a basis for the definition of a particular graphical path that identifies particular ones of the transducers that may be suitable to perform ablation along an ablation path corresponding to the defined graphical path. Other motivations may drive the definition of the graphical path in other embodiments. In some embodiments, various combinations of the display instructions associated with block **604**, the display instructions associated with block **606**, and the display instructions associated with block **612** are provided by a same set of display instructions.

(135) Referring back to the examples of FIGS. **5L-5Q**, in some embodiments, the first user input (e.g., which may initiate the definition of a new graphical path) includes at least engaging a first user input element, and the second user input (e.g., which may indicate the termination of the definition of the graphical path) includes at least disengaging the first user input element. For example, the first user input element may include a keyboard key, a mouse button, a touch screen, or any other user input element capable of being engaged and disengaged. In some embodiments where the first user input includes an engaging of the first user input element, the first user input may include a pressing (or otherwise engaging with) the keyboard key, the mouse button, or the touch screen, for example. In the case of a touch screen, the engaging may include an initiation of user-contact with the touch screen, although the touch screen may be configured to interact with other entities, such as a stylus. In some embodiments where the second user input includes a disengaging of the first user input element, the second user input may include a releasing (or otherwise disengaging) the keyboard key or the mouse button, or a cessation of contact from the touch screen, for example. In either or both of the engaging and disengaging cases, the data processing device system (e.g., **110**, **310**) may be configured to register in a memory device system (e.g., **130**, **330**) that the user input element is in an activated or deactivated state, respectively, in response to registering or identifying that the engaging or disengaging of the first user input element has occurred. It is noted that other embodiments are not limited to the above example embodiments of first user input elements.

(136) In some embodiments, the first user input includes engaging at least two user input elements

(e.g., to initiate the definition of a new graphical path, according to some embodiments) of an input-output device system (e.g., **120**, **320**). For example, a combination of an engaging of a keyboard key and a mouse click, or some other combination of user input elements may be required to initiate the definition of a new graphical path, according to some embodiments. In some of these embodiments, the second user input may include at least a disengaging at least one but not all of the at least two user input elements.

(137) In this regard, the data processing device system (e.g., **110**, **310**) may be configured to require particular user input to enable the definition of a graphical path prior to or concurrently with receiving user input that defines an initial location on the graphical path. FIG. **6D** illustrates various blocks associated with instructions that may configure the data processing device system to operate in this manner. In particular, FIG. **6D** illustrates various embodiments of the input-processing instructions associated with block **608** (e.g., identified as **608-1** in FIG. **6D**) in which at least two user input elements are employed, according to some embodiments. Block **608-1** in FIG. **6D** includes additional sub-blocks **608d** and **608e**, as compared to block **608** in FIG. **6A**.

(138) The input-processing instructions associated with sub-block **608d** may be configured to cause reception of a third user input other than the first user input (e.g., which may facilitate definition of a first location in a new graphical path; see, e.g., block **608a**), the second user input (e.g., which may facilitate definition of a terminating location of the graphical path; see, e.g., block **608b**) and the motion-based user input (e.g., which may facilitate definition of the intermediate locations of the graphical path; see, e.g., block **608c**). In various embodiments, the graphical path definition instructions associated with block **610** are configured to require the reception of the third user input in order to enable definition of some or all of the graphical path.

(139) For example, in user interfaces where functionality of a user input element is overloaded (e.g., has many functions), or in implementations where the definition of a graphical path has important consequences (e.g., being a precursor to causing tissue ablation), it may be beneficial to require an additional user input element into an activated state in order to allow definition of some or all of the graphical path. For instance, instead of requiring only a mouse click (an example of a first user input element) to begin definition of a graphical path, it may be beneficial to require the pressing of a particular keyboard key (an example of a second user input element) prior to or concurrently with the mouse click to enable the definition of the graphical path.

(140) In some embodiments, the data processing device system (e.g., **110**, **310**) is configured to require an engaging of the second user input element (e.g., placing it into an activated state) to enable definition of the intermediate portion or location(s) in the graphical path. For example, engaging of the second user-input (e.g., a depression of a particular keyboard key) need not be required to allow definition of the initial location in the graphical path (e.g., by a mouse click), but may be required to allow the definition of the intermediate locations (e.g., third location per block **610c**, elongate path portion per block **610d** (or **610e** discussed below)) by way of a path traced by the motion-based user input, according to some embodiments. Such a circumstance may allow, e.g., selection of the transducer graphical element **502g** in FIG. **5L** by way of a mouse click at the location of the cursor **519**, but would not allow selection of the transducer graphical element **502h** in FIG. **5M** (or the subsequent transducer graphical elements in FIGS. **5N-5Q**) by the motion-based user input until the second user input is engaged (e.g., by depression of a particular keyboard key), according to some embodiments. Such circumstance may provide a user with feedback acknowledging an intent to form a new graphical path by allowing selection of transducer graphical element **502g**, but may require the user to more intently focus on forming the path traced by the motion-based user input, which can be erratic, to form the intermediate portions of the graphical path, by requiring the engagement of the second user input element to do so.

(141) In this regard, in some embodiments, the input-processing instructions associated with block **608-1** (sub-block **608d**) are configured to cause the second user input element to be placed in a respective activated state in response to receiving the third user input. For example, the third user

input might be the depression of a particular keyboard key, which may be an example of the second user input element. In some embodiments, the second user input element may be another keyboard key other than a keyboard key employed as the first user input element. The second user input element may, in some embodiments, be a selectable region of a touch screen other than a particular region of the touch screen employed as the first user input element. Accordingly, it should be noted that various embodiments are not limited to any particular user input elements or combinations thereof. In various embodiments, the graphical path definition instructions associated with block **610** may be configured to require that the first user input element and the second user input element be in their respective activated states in order to at least enable a definition of at least a portion of the graphical path. In some embodiments, the third user input may be required in addition to at least the first user input to enable the graphical path definition instructions associated with block **610** to cause a definition of at least part of the graphical path. It is noted that, in some embodiments, the presence of the third user input (or the second user input element being in an activated state) may be required to enable initiation of definition of at least a portion of the graphical path, but may not be required to allow a subsequent definition of at least a portion of the graphical path (e.g., an intermediate location or elongate path portion thereof). For example, the data processing device system (e.g., **110, 310**) may be configured to require depression of a particular keyboard key (e.g., to place that keyboard key in an activated state) to initiate definition of the graphical path, but may allow release of the particular keyboard key (e.g., to place that keyboard key in a deactivated state) during subsequent definition of the graphical path while continuing to allow such subsequent definition.

(142) The release of the second user input element may be considered a fourth user input, according to some embodiments. In this regard, the input-processing instructions associated with block **608-1** may further include instructions associated with sub-block **608e**, which configure the data processing device system (e.g., **110, 310**) to receive a fourth user input other than the motion-based user input and the first, the second, and the third user inputs. Such input-processing instructions may be configured to cause the second user input element to be placed in a respective deactivated state in response to receiving the fourth user input. In some embodiments, the path definition instructions associated with block **610** are configured to cause definition or further definition of the elongate path portion of the graphical path according to the path traced by the motion-based user input (e.g., via the instructions associated with block **610d**) even though the fourth user input has been received and the second user input element has, consequently, been placed in the respective deactivated state. In this regard, the fourth user input may be received by the data processing device system (e.g., **110, 310**) before or during the motion-based user input. However, such timing is not required, and the fourth user input may be received after conclusion of the motion-based user input (e.g., when the second user input is received, which may terminate definition of the graphical path).

(143) In this regard, the above discussion mentions that the graphical-path-enabling user input (e.g., the third user input that places the second user input element in the activated state) occurs prior to or concurrently with the graphical-path-initiating user input (e.g., the first user input that places the first user input element in the activated state), according to some embodiments, but this timing is not required. For example, in some embodiments, the first user input-element may be in an activated state prior to receipt of the graphical-path-enabling user input. In such a circumstance, the enabling of the graphical path does not occur until both the first user input element and the second user input element are in activated states, according to some embodiments.

(144) It is noted that in various embodiments, the first user input element remains in the activated state (e.g., as per the instructions associated with block **608a**) during the motion-based user input. In some embodiments, placement of the first user input element into its activated state as per the instructions associated with block **608a** precedes a selection of a set of one or more graphical elements or a set of one or more graphical-path-elements. In some embodiments, placement of the

first user input element into its activated state as per the instructions associated with block **608a** is required at least in part to move a particular user input element from a first state that does not allow for a selection of a set of one or more graphical elements or a set of one or more graphical-path-elements to be made to a second state that does allow for a selection of a set of one or more graphical elements or a set of one or more graphical-path-elements to be made. In various embodiments, where a graphical path is traced in accordance with a motion-based user input, a selection of various graphical elements along the path may occur solely on the basis of the motion-based user input without the requirement for the activation or deactivation of a particular user input element (e.g., a particular user input element employed to at least in part provide the motion-based user input or a particular user input element that is not employed to at least in part provide the motion-based user input).

(145) In some embodiments, each of the first user input (e.g., a graphical-path-initiating input) and the second user input (e.g., a graphical path termination input) may facilitate identification or selection of more than one graphical element **501**. FIG. **6E** shows examples of at least a portion of the path definition instructions associated with block **610** (e.g., identified as **610-1** in FIG. **6E**) employed according to some embodiments to configure a data processing device system (e.g., **110**, **310**) to accommodate such multi-graphical-element identification or selection. For example, in some embodiments, the first user input (e.g., a depression of a mouse button) might occur over a between graphical element **504** (e.g., **504c** in FIG. **5M**) associated with a respective plurality of transducer graphical elements **502** (e.g., between a pair of transducer graphical elements **502g**, **502h** in FIG. **5M**). In this case, in some embodiments, the instructions associated with at least block **610-1** may configure the data processing device system (e.g., **110**, **310**) to indicate a selection of the associated respective plurality of transducer graphical elements **502** (e.g., **502g**, **502h**; an example of a graphical element set) in response to receiving the first user input (e.g., according to the instructions associated with block **610-1a**).

(146) A corresponding configuration may apply to the second user input, where the second user input (e.g., a release of the mouse button) occurs over a between graphical element **504**. In this case, in some embodiments, the instructions associated with at least block **610-1** may configure the data processing device system (e.g., **110**, **310**) to indicate a selection of the respective plurality of transducer graphical elements **502** (an example of a graphical element set) associated with the between graphical element **504** in response to receiving the second user input (e.g., according to the instructions associated with block **610-1b**). In some embodiments, the graphical element set selected according to the second user input includes at least one transducer graphical element **502** that is other than a transducer graphical element **502** selected according to the first user input. For example, the first user input might cause selection of transducer graphical elements **502g**, **502h** in FIG. **5M**, and the second user input might cause selection of transducer graphical elements **502g** and the transducer graphical element adjacent **502g**, but on the opposite side compared to transducer graphical element **502h**. Or, the graphical path need not be closed loop like that shown in FIG. **5Q**, which may cause the transducer graphical elements selected according to the first user input and the second user input to be mutually exclusive, according to some embodiments.

(147) The motion-based user input (e.g., movement of the mouse cursor **519**) may also facilitate identification or selection of a plurality of graphical elements **501**, such that the instructions associated with at least block **610-1** may configure the data processing device system (e.g., **110**, **310**) to indicate a selection of the respective plurality of graphical elements **501** (an example of a graphical element set) in response to receiving the motion-based user input (e.g., according to the instructions associated with block **610-1c**). In some embodiments, the graphical element set selected according to the motion-based user input includes at least one transducer graphical element **502** that is other than a transducer graphical element **502** selected according to the first user input.

(148) It should be noted that, although the above examples refer to the selection of a between

graphical element **504** to cause the selection of a plurality of other graphical elements (e.g., transducer graphical elements **502**), other embodiments are not limited to any particular technique for selecting a plurality of graphical elements. Further, although these examples refer to a plurality of graphical elements **501** being a graphical element set, a graphical element set may only include a single graphical element in various embodiments.

(149) In this regard, in some embodiments, the graphical element set selected according to the first user input (e.g., block **610-1a**), the graphical element set selected according to the second user input (e.g., block **610-1b**), the graphical element set selected according to the motion-based user input (e.g., block **610-1c**), or a combination of some or all of the first user input, the second user input, and the motion-based user input may include a group of transducer graphical elements. In this regard, each group of transducer graphical elements may correspond to a respective one of a plurality of groups of adjacent transducers, according to some embodiments. For example, the first user input might cause selection of a group of adjacent transducer graphical elements **502g**, **502h** in FIG. 5M, which may correspond to a respective group of adjacent transducers **306** in FIG. 3C, according to some embodiments. Similar examples apply to the second user input and the motion-based user input.

(150) As discussed above, in various embodiments, a graphical path defined in accordance with the instructions associated with block **610** may include a selection of various ones of a plurality of selectable graphical-path-elements, which may be graphical elements **501**. Each of the selected graphical-path-elements may be arranged along the graphical path. In various embodiments, a graphical path defined in accordance with the instructions associated with block **610** may include a selection of various ones of a plurality of selectable graphical-path-elements, each selected one of the selectable graphical-path-elements defining a respective portion of the graphical path.

(151) In this regard, the selection according to the instructions associated with block **610-1** includes, in some embodiments, multiple constituent or sub-selections (although in other embodiments, the selection according to the instructions associated with block **610-1** includes selection instructions configured to cause, due to execution of the selection instructions by the data processing device system (e.g., exemplified by data processing device systems **110** or **310**), selection of a graphical element. In some embodiments, such selection instructions include a first group of instructions configured to cause the data processing device system to receive or process, via the input-output device system, a user instruction to select a graphical element. In some of these embodiments, such selection instructions also include a second group of instructions configured to cause the data processing device system to perform its own selection of the graphical element in response to receiving the user instruction. For instance, the user instruction to select the graphical element might originate from a user clicking a mouse button (e.g., a first constituent selection) while a cursor is above or within a display region of a user-selected graphical element. In this case, the first group of instructions could configure the data processing device system to recognize this user instruction when it is received via the data input-output device system as a user instruction to select the user-selected graphical element below the cursor at the time of the mouse-button click. In some embodiments, the second group of instructions may configure the data processing device system, in response to the first group of instructions recognizing this user instruction, to perform its own selection (e.g., a second constituent selection) of the user-selected graphical element at least by causing, via the input-output device system, the display of the user-selected graphical element to change one or more visual characteristics of the user-selected graphical element. Accordingly, the selection according to various ones of the instructions associated with block **610-1** may be deemed, in some embodiments, to involve a first, user-based constituent selection and a second, machine-based or automatic constituent selection triggered by the user-based constituent selection.

(152) Although a mouse click was provided above as an example of a user-based constituent selection, and the changing of a visual characteristic of the user-selected graphical element was provided as an example of a machine-based constituent selection, it should be noted, however, that

any form of user-based selection or machine-based selection of a graphical element known in the art can be used. In this regard, direct interaction with a graphical element itself (e.g., by way of a mouse click on the graphical element) is not required to directly select the graphical element or its corresponding transducer. For example, in some embodiments, a user might type a unique identifier associated with a graphical element or transducer via a keyboard, which can cause direct selection of that graphical element or transducer.

(153) Further, although a user-based constituent selection of a user-selected graphical element followed by a machine-based constituent selection of that user-selected graphical element was provided above as an example of constituent selections involved with block **610-1**, it should be noted that a user-based constituent selection of a first user-selected graphical element can also cause a machine-based constituent selection of a second, different, non-user-selected graphical element. For example, in some embodiments, a user-performed mouse click while the mouse cursor is above or within a display region of a user-selected between graphical element **504** (e.g., a user-based constituent selection) can cause, possibly among other things, a machine-based constituent selection of the non-user-selected transducer graphical elements **502** at each end of the user-selected between graphical element **504**. In this regard, the phrase, “user-selected”, when used herein to describe a selected graphical element (e.g., a transducer graphical element or a between graphical element), is intended to refer to a graphical element directly selected by a user, as opposed to a non-user-selected graphical element, which is a machine-selected graphical element that is machine-selected either in response to no user instruction to select any graphical element or in response to a user instruction to select a user-selected graphical element different than the machine-selected graphical element. In cases where a user selection of a user-selected graphical element causes a machine-selection of a different graphical element, it can be said that the different graphical element is indirectly selected by the user.

(154) Further still, although a user-based constituent selection followed by a machine-based constituent selection was provided above as an example of constituent selections involved with block **610-1**, it should be noted that any number of constituent selections, whether user-based or machine-based, can be involved with block **610-1**. For example, depending upon how the user interface is structured, one or more user-based constituent selections may result in one or more machine-based constituent selections. For instance, multiple user gestures might be required to identify a particular user-selected graphical element in order to cause the data processing device system to change the visual characteristics of (or provide another form of selection of) the particular user-selected graphical element. For example, according to some embodiments, the above-discussed first user input (e.g., block **610-1a**) might be a combination of the pressing of two keyboard keys, at least in part, concurrently, to place the first user input element (e.g., the two keyboard keys) in an activated state to change the visual characteristics of a correspondingly selected transducer graphical element (e.g., **502g** in FIG. 5L). If the same multi-key approach was applied to the selection of a between graphical element (e.g., **504c** in FIG. 5M), the data processing device system (e.g., **110**, **310**) may be configured to respond with at least two machine-based constituent selections to change the visual characteristics of the corresponding transducer graphical elements (e.g., **502g**, **502h** in FIG. 5M), according to some embodiments.

(155) Further still, although one or more user-based constituent selections followed by one or more machine-based constituent selections was provided above as an example of constituent selections involved with block **610-1**, it should be noted that block **610-1** might not involve any user-based constituent selections in some embodiments. For example, graphical element selection according to block **610-1a** might occur based upon data received from transducers, and this data might result in one or more machine-based or automatic constituent selections performed by the data processing device system.

(156) It should be noted that, whenever a selection of a graphical element is discussed herein, such selection, in some embodiments, may include the above-discussed constituent selections, according

to some embodiments. However, the above-discussed constituent selections are not limited to just selections of graphical elements and can apply to any selection described herein. For example, one or more user-based constituent selections of a user-selected graphical element can lead to one or more machine-based constituent selections of the user-selected graphical element or some other graphical element(s), which can lead to one or more machine-based selections of one or more transducers corresponding to the machine-selected graphical elements, the machine-based selection(s) of the one or more transducers possibly causing an activation of the one or more transducers. For another example, one or more user-based constituent selections of a user-selected graphical element can lead to one or more machine-based constituent selections of one or more data objects associated with the user-selected graphical element, one or more other associated graphical elements, one or more transducers associated with the user-selected graphical element, or one or more other objects associated with the user-selected graphical element, such as for purposes of viewing or changing properties of the one or more data objects or causing an activation based upon information provided by the one or more data objects.

(157) In some embodiments, the graphical path defined according to the instructions associated with block **610** (e.g., by way of the first user input, the second user input, the motion-based user input, or a combination of some or all of the first, second, and motion-based user inputs) includes transducer graphical elements **502**, between graphical elements **504**, or both transducer graphical elements **502** and between graphical elements **504**. In some embodiments, the graphical path includes a continuous series of selected transducer graphical elements **502** and selected between graphical elements **504**. In some embodiments, the between graphical elements **504** forming at least part of the graphical path are interleaved with the transducer graphical elements **502** forming at least part of the graphical path.

(158) In some embodiments, at least selected ones of the between graphical elements **504** include an elongated portion extending between two respective ends, each of the respective ends located at least proximate a respective one of two transducer graphical elements **502**, according to some embodiments. For example, various ones of FIG. 5 illustrate each between graphical element **504** as a line between two transducer graphical elements **502**. However, the invention is not limited to such a representation of a between graphical element **504**, and between graphical elements **504** need not be lines (or elongated portions) or contact their respective transducer graphical elements **502**. In some embodiments where an intermediate portion of the graphical path includes an elongate path portion, an elongated portion of each of at least some of the selected between graphical elements **504** may provide at least part of the elongate path portion.

(159) As discussed above with respect to FIG. 3D and regions of space **350**, **360**, at least some between graphical elements **504** (e.g., **504c**) may each be associated with a region of space that is not associated with any physical part or portion of the corresponding transducer-based device system. In some embodiments, at least some between graphical elements **504** (e.g., **504c**) may each be associated with a region of space that does not include any transducer (e.g., either between elongate members **304** or along a same elongate member **304**), the region of space being between transducers in a group of adjacent transducers (e.g., transducers **306** corresponding to transducer graphical elements **502g**, **502h**, in the case of between transducer graphical element **504c** in FIG. 5M). In some embodiments, at least some between graphical elements **504** (e.g., **504d** in FIG. 5N) may each be associated with a region of space that is associated with a physical part or portion of the transducer-base system (e.g., a region of space along a same elongate member **304** between transducers **306** associated with transducer graphical elements **502i**, **502j**, in the case of between graphical element **504d** in FIG. 5N).

(160) According to some embodiments, block **612** in FIG. 6A is associated with instructions configured to cause the data processing device system (e.g., **110**, **310**) to display the graphical path defined according to the instructions associated with block **610**. As discussed above, the graphical path defined in accordance with the instructions associated with block **610** may be displayed

according to the instructions associated with block **612** in various forms, shapes, or configurations including embodiments that include, by way of non-limiting example, an elongated portion, a continuous portion, an interrupted portion, a linear portion, an arcuate portion, a portion defining an obtuse angle, a portion defining an acute angle, a beginning portion (e.g., a portion defining or associated with a beginning or start of the definition of the graphical path), an end portion (e.g., a portion defining or associated with an end or termination of the definition of the graphical path), an open or closed circumferential portion or path, or any combination thereof.

(161) In cases where the graphical path is represented at least in part in an interrupted form including at least an interrupted portion, such interrupted portion may be caused, at least in part, by between graphical elements **504** that do not connect to their associated transducer graphical elements **502**, unlike the connecting between graphical elements **504** as shown in various ones of FIGS. 5 (e.g., each of FIG. 5L-5Q). Non-connecting between graphical elements **504** may be represented as line segments, double-line segments, squares, dots, or any other shape that does not contact at least on adjacent transducer graphical element **502**, according to some embodiments. In cases where the graphical path is displayed at least in part as a circumferential path, such circumferential path may enclose or surround a region (e.g., **525c** in FIG. 5Q corresponding to a pulmonary vein) in a graphical representation of intra-cardiac information.

(162) The instructions associated with block **612** may be configured to cause at least one visual characteristic set of each of various ones of the graphical elements **501** to change upon or after selection (e.g., by way of the first, second, or motion-based user inputs) and inclusion in the graphical path according to the instructions associated with blocks **608** and **610**, according to various embodiments. For example, at least each of FIGS. 5L-5Q show the changing of an interior color of each selected transducer graphical elements **502** as the graphical path is defined and displayed over time. Similarly, a color or other visual characteristic of between graphical elements **504** selected for inclusion in the graphical path may change when or as the graphical path is displayed. In some embodiments, selected transducer graphical elements **502**, selected between graphical elements **504**, or both, in the graphical path have different visual characteristics than unselected or non-selected respective ones of the transducer graphical elements **502**, the between graphical elements **504**, or both.

(163) In some embodiments, the graphical path may be defined according to selection of any selectable graphical-path-element. In some embodiments, the selectable graphical-path-elements are graphical elements **501**, including transducer graphical elements **502**, between graphical elements **504**, or both. However, other selectable graphical-path-elements may be used.

(164) In some embodiments, the selectable graphical-path-elements are provided by or among a displayed graphical representation (e.g., **500**). The selectable graphical-path-elements may be arranged in the graphical representation (e.g., **500**) in an arrayed configuration (e.g., a depicted two-dimensional or depicted three-dimensional arrayed configuration). In some embodiments, the selectable graphical-path-elements are arranged in a grid or grid-like configuration. Various ones of FIG. 5 show two-dimensional or three-dimensional arrangements of selectable graphical-path-elements according to some embodiments.

(165) It is noted that the display of the selectable graphical-path-elements or the defined graphical path is not limited to two-dimensional representations as shown, for example, in various ones of FIGS. 5. In this regard, FIG. 5R shows the graphical path generated in FIGS. 5L-5Q three-dimensionally. A graphical representation of intra-cardiac information (e.g., blood flow information) is also depicted three-dimensionally in FIG. 5R. In embodiments encompassing FIG. 5R, a plurality of graphical representations of intra-cardiac electrograms **535** may be additionally displayed by the graphical interface, each of the electrograms **535** derived from data sampled by a respective transducer (e.g., transducer **306**, **406**) corresponding to a particular one of the transducer graphical elements **502** selected along the graphical path. In various embodiments, each of the electrograms **535** is a unipolar or monopolar electrogram.

(166) In some embodiments, as discussed above with respect to FIG. 5A, each of at least some of the transducer graphical elements **502** includes a shape that is consistent with a shape of the respective electrode (e.g., **315**, **415**) of the transducer (e.g., **306**, **406**) to which the transducer graphical element **502** corresponds. In this regard, different transducer graphical elements **502** may have different shapes, like their respective transducers (e.g., **306**, **406**) or electrodes (e.g., **315**, **415**) thereof.

(167) In some embodiments, the display instructions associated with block **612** in FIG. 6A configure the data processing device system (e.g., **110**, **310**) to cause the input-output device system (e.g., a display device of **120**, **320**) to display the graphical path among a graphical representation of intra-cardiac information (see, e.g., FIGS. 5L-5R). Such intra-cardiac information has been described above with respect to at least FIGS. 5G-5K. In this regard, according to some embodiments, the display instructions associated with block **612** may be configured to cause the input-output device system to display a plurality of between graphical elements **504** concurrently with transducer graphical elements **502**, the graphical path, and the graphical representation of the intra-cardiac information.

(168) It is noted that in various embodiments, the intra-cardiac information that is displayed (e.g., via the instructions associated with block **604**) need not be static and may include changes in the displayed appearance thereof. For example, the display instructions associated with block **604** may be configured to, in some embodiments, cause an input-output device system (e.g., **120**, **320**) to graphically display changes in the intra-cardiac information (for example, as depicted in FIGS. 5I, 5J and 5K) during: a) reception of the first user input (e.g., block **608a**), b) reception of the second user input (e.g., block **608b**), c) reception of the motion-based user input (e.g., block **608c**), or any combination of a), b) and c). In some embodiments encompassing FIGS. 5L and 5M, additional information **521** (which may be another form of graphical representation of intra-cardiac information) is displayed upon a selection indicating a particular one of the graphical elements **501**. In at least some of these particular embodiments, the information **521** includes target temperature information associated with each of the transducers corresponding to the particular ones of the selected transducer graphical elements **502**. In some embodiments, the information **521** is related to, or reflective of systems-based or hardware-based information. In some embodiments, the information **521** is related to, or reflective of physiological parameter information. In some embodiments, the information **521** may represent target temperature information to monitor or control the transmittance of tissue ablation energy from a particular one of the transducers. In various embodiments, temperature data is sensed by a particular temperature sensor (e.g., temperature sensor **408**) provided by a particular transducer. The temperature data may, in some embodiments, be compared with the target temperature to monitor or control the transmittance of tissue ablation energy from the particular transducers. Other forms of information **521** may be displayed in other embodiments. It is noted that displayed information **521** need not solely arise from a selection indicated by the first user input, but may, in some embodiments, arise as a result of other user inputs (e.g., a second user input or a motion-based input as described herein). It is noted that in some embodiments, the display of information **521** occurs in response to a selection of various ones of the graphical elements **501**. Advantageously, the selective inclusion of information **521** only for the selected ones of the graphical elements **501** may reduce cluttering the display region if the information **521** were provided for a significant number of (e.g., a majority) or all of the selectable graphical elements **501**. This is especially important when several hundreds of selectable graphical elements **501** are displayed.

(169) Having the graphical path displayed among a graphical representation of intra-cardiac information (e.g., FIGS. 5L-5R) may facilitate better judgments regarding or improve the effectiveness or operational implementation of transducer activation (e.g., sensing, tissue ablation, both, or some other activation) within the cardiac cavity. In some embodiments, activation instructions associated with block **614** in FIG. 6A are configured to cause activation of various

transducer sets. In some embodiments, these various transducer sets include or are the transducers corresponding to those transducer graphical elements **502** included in the graphical path.

(170) In some embodiments, the activation instructions associated with block **614** are configured to cause transmission, initiated during or after completion of the definition of the graphical path (e.g., according to the instructions associated with block **610**), of energy sufficient for tissue ablation (e.g., via energy source device system **340**) from each of at least one of the respective transducers (e.g., **220**, **306**, **406**) corresponding to graphical elements **501** in the graphical path, such as transducer graphical elements **502**, between graphical elements **504**, or both, selected by the first user input (e.g., blocks **608a**, **610a**), the motion-based user input (e.g., blocks **608c**, **610c**), or the second user input (e.g., blocks **608b**, **610b**).

(171) In some embodiments, the activation instructions associated with block **614** are configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each respective transducer corresponding to a first transducer graphical element selected, e.g., based on a graphical-path-initiating first user input according to the instructions associated with block **608a** in FIG. 6A, a second transducer graphical element selected, e.g., based on motion-based user input according to the instructions associated with block **608c** in FIG. 6A, and a third transducer graphical element selected, e.g., based on graphical-path-terminating second user input according to the instructions associated with block **608b** in FIG. 6A.

(172) Similarly, in some embodiments, the activation instructions associated with block **614** are configured to cause transmission, initiated during or after completion of the definition of the graphical path (e.g., according to the instructions associated with block **610**), of energy sufficient for tissue ablation from at least each respective transducer (e.g., **220**, **306**, **406**) corresponding to each transducer graphical element **502** in each of a first transducer graphical element set selected, e.g., based on a graphical-path-initiating first user input according to the instructions associated with block **610-1a** in FIG. 6E, a second transducer graphical element set selected, e.g., based on motion-based user input according to the instructions associated with block **610-1c** in FIG. 6E, and a third transducer graphical element set selected, e.g., based on graphical-path-terminating second user input according to the instructions associated with block **610-1b** in FIG. 6E.

(173) In some embodiments, the activation instructions associated with block **614** are configured to cause transmission, initiated during or after completion of the definition of the graphical path, of energy sufficient for tissue ablation from at least each transducer (e.g., **220**, **306**, **406**) of a respective one of a plurality of groups of adjacent ones of the transducers corresponding to a selected at least one of the between graphical elements **504**. For example, if between graphical element **504** in FIG. 5M is selected, which causes inclusion of adjacent transducer graphical elements **502g** and **502h** in the graphical path, the group of adjacent transducers **306** corresponding to transducer graphical elements **502g** and **502h** may be caused to transmit tissue-ablative energy (e.g., via energy source device system **340**) in accordance with the instructions associated with block **614**, according to some embodiments.

(174) Advantageously, activating a set of two or more of the transducers based on a selection of a single graphical element (e.g., between graphical element **504**) provides for a workflow that may be less cumbersome and more expeditious than individually selecting the respective graphical elements (e.g., transducer graphical elements **502**) associated with each transducer of the set of two or more of the transducers, especially when 50, 100, 200 or even over 300 or more transducer graphical elements are provided in the graphical representation. This configuration may be even more advantageous, when a single graphical element (e.g., between graphical element **504**) provides additional information (e.g., spatial information) relating each of the transducers in the set of two or more of the transducers. For example, a between graphical element **504** may indicate a distance between or acceptability-of-activation of transducers of a corresponding transducer pair, and, accordingly, the between graphical element **504** provides, in some embodiments, information

about the corresponding group (e.g., pair) of transducers and, thereby, makes the selection process more efficient. In addition, allowing selection of the between graphical elements for corresponding transducer activation can provide a more intuitive user interface in certain applications. For example, such an arrangement allows a user to make selections along an ablation path or a path along which data is to be obtained, without having to focus on the transducers required to make that ablation path or acquire that data. The user may, for example, just select a path using between graphical elements (e.g., user-based selection(s)/constituent selection(s)), and the corresponding transducers are automatically selected (e.g., machine-based selection(s)/constituent selection(s)) in response. Since various ones of the between graphical elements need not be tied to any physical portion of the transducer-based device, they can be freely designed to reflect a path (e.g., over tissue or fluid) along which their corresponding transducers will interact when activated (e.g., by causing ablation). In this regard, if the between graphical elements are configured to accurately represent their respective path segments in which ablation or data gathering will occur, according to some embodiments, the user can gain an even better understanding of the expected results of activation of the corresponding transducers. This configuration may advantageously increase the likelihood that an ablation path that is consistent with the displayed graphical path will result.

(175) Activation of transducers according to the instructions associated with block **614** may occur when the definition, display, or both of the graphical path has not yet completed. For example, if FIG. 5Q represents the completion of definition and display of the graphical path, and FIGS. 5L-5P represent times during the definition and display of the graphical path (e.g., after a graphical-path-initiating first user input and during the motion-based user input), transducers associated with selected transducer graphical elements **502g** and **502h** may be activated according to the instructions associated with block **614** at the time represented by FIG. 5M or any time thereafter (e.g., at the time of FIG. 5M, 5N, 5O, 5P, 5Q, or thereafter). In some embodiments, all of the transducers corresponding to selected transducer graphical elements **502** may be concurrently queued for activation according to the instructions associated with block **614** by a particular user input. For example, after the graphical path of FIG. 5Q is completed, the user may engage an “ablate” software button on the user interface to queue all of the transducers corresponding to the highlighted transducer graphical elements **502** in FIG. 5Q to cause tissue ablation. In some embodiments, such an “ablate” software button (or, more generally, the activation instructions associated with block **614**) may be enabled for operation at least in response to a reception of a graphical-path-terminating second user input. Such an “ablate” software button need not be engaged only after path definition, however, and could be engaged during graphical path definition, display, or both, as discussed above. Note that queuing transducers for activation does not necessarily mean that all transducers will be activated concurrently or immediately, although this may be so in some embodiments. For example, in some embodiments, when a group of transducers are queued for tissue ablation, the transducers in the group are not activated for ablation concurrently, but are activated for ablation according to a sequence of sets of transducers to ensure proper tissue ablation and operate within hardware and driving constraints. For instance, if ablation occurs by way of delivery of energy from an energy source device system (e.g., energy source device system **340**) to the respective transducers, it may be that the energy source device system is capable of transmitting tissue-ablative energy to (e.g., “driving”) a predetermined number of transducers simultaneously, according to some embodiments. For example, if 20 transducers are queued for ablation, but only 8 transducers can be driven electrically at a time by the energy source device system, then the 20 transducers may be activated for ablation in sequential groups of 8, 8, and 4 or some other sequential grouping within the hardware constraints.

(176) In some embodiments, the activation caused according to the instructions associated with block **614** is concurrent monopolar activation, initiated during or after completion of the definition of the graphical path. Monopolar activation can include activation for monopolar ablation or monopolar electrogram generation by way of non-limiting example. In some embodiments, an

indifferent electrode (e.g., indifferent electrode **326**) is provided (e.g., usually to an external surface or skin-based surface of a body) while the transducer-based device (e.g., **200, 300, 400**) is received in a bodily cavity within the body. A portion of the tissue-ablating energy delivered to the respective transducer (e.g., **306, 406**) corresponding to the selected transducer graphical element (e.g., **502**) may be transmitted from the respective transducer to the indifferent electrode in a process typically referred to as monopolar ablation. In some embodiments, the activation caused according to the instructions associated with block **614** is bipolar tissue ablation, initiated during or after completion of the definition of the graphical path.

(177) In some embodiments, (a) a portion of the energy delivered to a first transducer of the respective set of two or more of the transducers (e.g., first transducer **306**) is transmitted by the first transducer, (b) a portion of the energy delivered to a second transducer of the respective set of two or more of the transducers (e.g., second transducer **306**) is transmitted by the second transducer, or both (a) or (b). In some embodiments, (a) a portion of the energy delivered to a first transducer of the respective set of two or more of the transducers (e.g., first transducer **306**) is transmitted by the first transducer to a second transducer of the respective set of two or more of the transducers (e.g., second transducer **306**), (b) a portion of the energy delivered to the second transducer of the respective set of two or more of the transducers is transmitted by the second transducer to the first transducer, or both (a) or (b). In some example embodiments, a selected between graphical element (e.g., between graphical element **504**) is representative of a physical path extending between a respective pair of the transducers associated with the selected between graphical element and the energy is sufficient for ablating a portion of tissue extending along the physical path. A portion of the tissue-ablating energy may be transmitted between the respective pair of the transducers in a process typically referred to as bipolar ablation. In some embodiments, an indifferent electrode (e.g., indifferent electrode **326**) is provided (e.g., usually to an external surface of a body) while the transducer-based device is received in a bodily cavity within the body. Some of the tissue-ablating energy may be transmitted between the respective pair of the transducers while some of the tissue-ablating energy may be transmitted from various ones of the respective pair of the transducers to the indifferent electrode in a process typically referred to as blended monopolar-bipolar ablation. The term “bipolar ablation” as used in this disclosure is to be interpreted broadly to include blended monopolar-bipolar ablation in some embodiments.

(178) In addition to embodiments where the instructions according to block **614** are configured to cause a data processing device system to cause bipolar ablation, the instructions according to block **614**, in some embodiments, are configured to cause a data processing device system to cause multi-transducer monopolar ablation with the respective set of two or more of the transducers, e.g., dual monopolar ablation for two transducers, or triple monopolar ablation for three transducers. In such cases, for example, the respective set of two or more of the transducers may be ‘queued’ for monopolar ablation, such that monopolar ablation occurs for each transducer in the respective set of two or more of the transducers within some period of time, but not necessarily at the same time or even one immediately after another. In this regard, references herein to the occurrence of monopolar ablation for more than one transducer may include this multi-transducer monopolar ablation according to some embodiments. In addition, any reference herein to the occurrence of bipolar ablation may be replaced with the occurrence of dual monopolar ablation (or other multi-transducer monopolar ablation when more than two transducers are involved), according to some embodiments. In some cases in which multi-monopolar ablation is employed, energy transfer sufficient to cause tissue ablation is not transferred between the particular transducers employed by the multi-monopolar ablation. Rather, in these cases energy sufficient for tissue ablation is transmitted between each of these particular transducers and an indifferent electrode (e.g., indifferent electrode **326**).

(179) The activation according to the instructions associated with block **614** need not be for tissue ablation. In some embodiments, a sensing device system (e.g., provided at least in part by a number

of the transducers **306, 406**) is arranged to sense intra-cardiac information or physiological parameter information at a respective location at least proximate the respective transducer corresponding to a selected transducer graphical element with the energy delivered to the transducer as at least part of the activation. In this regard, in some embodiments, the instructions associated with block **614** that are, in some embodiments, configured to activate a respective transducer (e.g., **306, 406**) corresponding to a selected transducer graphical element (e.g., **502**) include instructions that are configured to cause a sensing device system (e.g., sensing device system **325**) to detect electrophysiological activity (an example of intra-cardiac information in some embodiments) in an intra-cardiac cavity at a location at least proximate the respective transducer. The detected electrophysiological activity can be displayed as an intra-cardiac electrogram via the input-output device system (e.g. electrograms **535** shown in FIG. **5R**). In some embodiments, detection of electrophysiological activity in an intra-cardiac cavity at a location at least proximate various ones of the transducers occurs continuously. In some embodiments, a sensing device system (e.g., sensing device system **325**) is arranged to sense at least one tissue electrical characteristic (e.g., an example of intra-cardiac information) at respective locations at least proximate each transducer of the respective set or group of two or more of the transducers with the energy delivered to the respective set of two or more of the transducers. Other forms of activation of the respective transducer corresponding to the selected transducer graphical element are possible in other embodiments.

(180) In some embodiments, the above-discussed sensing functionality of one or more transducers (e.g., **306, 406**) occurs simultaneously with tissue-ablation performed by such one or more transducers, e.g., according to the instructions associated with block **614**.

(181) In some embodiments, the initiation, evolution, conclusion, or a combination thereof of the activation caused according to the instructions associated with block **614** may be represented in a displayed user interface (e.g., like that shown in various ones of FIG. **5**) by a change in a visual characteristic set of the activated transducer graphical elements (e.g., **502**). For example, FIG. **5X** shows the various particular transducer graphical elements **502** and between graphical elements **504** selected as per various embodiments associated with various one of FIGS. **5L, 5M, 5N, 5P, 5Q, and 5R** but after the corresponding transducers (e.g., **306, 406**) have been activated (e.g., to transmit tissue ablation energy). In FIG. **5X**, a visual characteristic set of the various particular transducer graphical elements **502** and between graphical elements **504** has changed (e.g., thicker and darker shading as compared with FIG. **5Q**) indicating a particular state (e.g., initiation, an intermediate state, or a completion) associated with the activation of each of the corresponding transducers.

(182) It should be noted that, with respect to every discussion of a change of visual characteristic or visual characteristic set discussed herein in various embodiments, other embodiments are not limited to any particular visual characteristic that may be changed. For example, such a visual characteristic may be, without limitation, a color, a color density, a shape, a texture, a location, etc. A visual characteristic set may be one or more visual characteristics, such that a change in a visual characteristic set may be a change in one or more visual characteristics.

(183) In various embodiments, the graphical path is defined, at least in part, based on (a) a positional relationship between various ones of the graphical elements **501**, (b) a positional relationship between various regions (e.g., **525**) of a graphical representation of intra-cardiac information, (c) a positional relationship between various ones of the graphical elements **501** and various regions of the graphical representation of the intra-cardiac information, or a combination of two or more of (a), (b) and (c). Enhanced or more efficient selection of various graphical elements **501** may be achieved in some embodiments, which allow a respective graphical element **501** to be selected if user input (e.g., graphical-path-initiating first user input, motion-based user input, or graphical-path-terminating second user input, e.g., respectively pursuant to blocks **608a, 608b, and 608c**) occurs within a display region associated with the respective graphical element **501**, the

display region including at least a portion that extends beyond at least a portion of its respective graphical element **501**.

(184) For example, each of FIGS. 5S and 5T shows a plurality of transducer graphical elements (e.g., similar to some transducer graphical elements **502** shown in various other ones of FIG. 5) including transducer graphical elements **502aa**, **502bb**, **502cc**, **502dd** (collectively, transducer graphical elements **502**). Each of the transducer graphical elements **502aa**, **502bb**, **502cc**, **502dd** resides, at least in part, within a respective one of display regions **502aa-1**, **502bb-1**, **502cc-1**, and **502dd-1** (e.g., shown in broken lines in these particular illustrated embodiments). In these embodiments, each of the transducer graphical elements **502** does not occupy the entirety, or all, of its respective display region. In addition to the transducer graphical elements included in FIG. 5S, FIG. 5T additionally includes a plurality of between graphical elements (e.g., similar to some between graphical elements shown in various other ones of FIG. 5) including between graphical elements **504ab**, **504bc**, **504cd**, and **504da** (collectively, between graphical elements **504**), each of the between graphical elements arranged between a respective adjacent pair of the transducer graphical elements **502**. In FIG. 5T, each of the between graphical elements **504ab**, **504bc**, **504cd**, and **504da** resides, at least in part, within a respective one of the display regions **504ab-1**, **504bc-1**, **504cd-1**, and **504da-1** (e.g., shown in broken lines in these particular illustrated embodiments). In these embodiments, each of the between graphical elements **504** does not occupy the entirety, or all, of its respective display region. It should be noted that, in some embodiments that do not include between graphical elements **504**, which may be represented by FIG. 5S, in some embodiments, the display regions associated with the transducer graphical elements **502** may contact each other, unlike FIG. 5S.

(185) In some embodiments encompassing FIGS. 5S and 5T, a selection of transducer graphical elements is indicated at least by user input, such as, but not limited to first user input (e.g., graphical-path-initiating first user input), motion-based user input, or second user input (e.g., graphical-path-terminating second user input), e.g., respectively pursuant to blocks **608a**, **608b**, and **608c** in FIG. 6A. For example, first user input (e.g., a graphical-path-initiating first user input) according to block **608a** may occur at the display-screen-location **519-1a** where the broken-line cursor **519-1** in FIG. 5S is located. In this regard, the instructions associated with block **610a** in FIG. 6A may be configured to cause the data processing device system (e.g., **110**, **310**) to analyze such display-screen-location (an example of a parameter in a first parameter set associated with the first user input) in relation to one or more of the transducer graphical elements **501**. For example, in some embodiments, the data processing device system may compare such display-screen-location to the display regions associated with the graphical elements to determine a display region in which the display-screen-location of the first user input occurs. In the example of FIG. 5S, the display-screen-location **519-1a** associated with the first user input is determined to be located in region **502aa-1** associated with transducer graphical element **502aa**. Consequently, the instructions associated with block **610a** in FIG. 6A may configure the data processing device system to identify the transducer graphical element **502aa** as the first location on the graphical path.

(186) Similarly, because the motion-based user input (e.g., according to block **608c**) passes through display region **502bb-1** (e.g., includes a display-screen-location **519-1b**, which is an example of a parameter in a parameter set, within such display region **502bb-1**), as shown by broken-line cursor **519-1** in the direction illustrated by arrow **531a**, the instructions associated with block **610c** in FIG. 6A may configure the data processing device system to identify the transducer graphical element **502bb** as another location on the graphical path, according to some embodiments. Further, a second user input (e.g., a graphical-path-terminating second user input) might occur at the display-screen-location **519-1c** (an example of a parameter in a second parameter set associated with the second user input) of cursor **519-1**, which is within the display region **502cc-1** of transducer graphical element **502cc**. In this regard, the instructions associated with block **610b** in FIG. 6A may configure the data processing device system to identify the transducer graphical element **502cc** as

yet another location on the graphical path, according to some embodiments. As shown in FIGS. 5S and 5T, a visual characteristic set of each of transducer graphical elements **502aa**, **502bb**, and **502cc** has been changed (for example, as compared with unselected transducer graphical element **502dd**) in a manner similar to, or the same as, that indicated by various other selected transducer graphical elements **502** shown in various other ones of FIG. 5. Additional information **521** is not shown in FIGS. 5S and 5T for clarity, although it is understood that information **521** may or may not be included in other embodiments.

(187) In FIG. 5T, transducer graphical elements **502aa**, **502bb**, and **502cc** are selected by employing a motion-based user input that moves a mouse cursor **519-2** along a path (e.g., schematically represented by arrow **531b** in some embodiments) sequentially through display regions **504ab-1** and **504bc-1** of between graphical elements **502ab-1** and **502bc-1**. That is, in some embodiments, transducer graphical elements **502aa**, **502bb**, and **502cc** may be indirectly selected in response to a user selection of between graphical elements **504ab** and **504bc**. Advantageously, the user-input(s) required to select transducer graphical elements **502aa**, **502bb**, and **502cc** in FIG. 5T may be simpler and shorter (e.g., as schematically represented by the non-jogged shape of arrow **531b** and the overall length of arrow **531b**) as compared with the user input(s) required to individually select transducer graphical elements **502aa**, **502bb**, and **502cc** in FIG. 5S (e.g., as schematically represented by the jogged shape of arrow **531a** and the longer overall length of arrow **531a**). It is noted that, in some embodiments, upon selection, a visual characteristic set of each directly selected between graphical element **504ab** and **504bc** is changed (e.g., as compared with unselected between graphical elements **504cd** and **504da**) along with a change in a visual characteristic set of transducer graphical elements **502aa**, **502bb**, and **502cc**. Changes in the visual characteristic set of various graphical elements in FIGS. 5S and 5T may be made in accordance with the instructions associated with block **612** in some embodiments. In FIG. 5T at least one of the display regions (e.g., **502aa-1**) has different dimensions or sizes than another of the display regions (e.g., **504ab-1**). In FIG. 5T at least one of the display regions (e.g., **502aa-1**) has a different shape than another of the display regions (e.g., **504ab-1**).

(188) In some embodiments associated with FIGS. 5S and 5T, each of the selections (e.g., direct or indirect) of transducer graphical elements **502aa**, **502bb** and **502cc** may be made in response to the path traced by the motion-based user input without any additional control element activation or deactivation (e.g., a mouse button click or de-click). It is noted that, intra-cardiac information similar to that shown in various other ones of FIG. 5 is not displayed in FIGS. 5S and 5T for clarity. Intra-cardiac information may or may not be additionally displayed in various embodiments.

(189) With respect to FIGS. 5U, 5V, and 5W, in some embodiments, each of a plurality of transducer graphical elements **502ee**, **502ff**, **502gg**, **502hh**, **502ii**, and **502jj** resides, at least in part, within a respective one of display regions **502ee-1**, **502ff-1**, **502gg-1**, **502hh-1**, **502ii-1**, and **502jj-1** (e.g., shown in broken lines in these particular illustrated embodiments). In addition to these transducer graphical elements, FIGS. 5U, 5V, and 5W includes a plurality of between graphical elements (e.g., similar to some between graphical elements shown in various other ones of FIG. 5) including between graphical elements **504ef**, **504fg**, **504gh**, **504hi**, **504ij**, **504ja**, and **504if** (collectively, between graphical elements **504**), each of the between graphical elements arranged between a respective adjacent pair of the transducer graphical elements **502**. In FIGS. 5U, 5V, and 5W, each of the between graphical elements **504ef**, **504fg**, **504gh**, **504hi**, **504ij**, **504ja**, and **504if** resides, at least in part, within a respective one of the display regions **504ef-1**, **504fg-1**, **504gh-1**, **504hi-1**, **504ij-1**, **504ja-1**, and **504if-1** (e.g., shown in broken lines in these particular illustrated embodiments). In these embodiments, each of the transducer graphical elements **502** and each of the between graphical elements **504** does not occupy the entirety, or all, of its respective display region.

(190) With respect to FIG. 5U, in some embodiments, a plurality of selectable graphical-path-

elements (e.g., at least **504ef**, **502ff**, **504fg**) are concurrently displayed with the graphical representation of intra-cardiac information (not shown in FIG. 5U, but shown, e.g., with respect to FIGS. 5G-5R and 5X). In this regard, in some embodiments, the graphical path includes a group of the graphical-path-elements (e.g., at least **504ef**, **502ff**, **504fg**) in response to a path traced by motion-based user input or a portion thereof (e.g., at least a portion of the path traced by mouse cursor **519-3** from location **519-3a** to location **519-3b**) passing through a respective predetermined display region associated with each of at least one graphical-path-element of the group of graphical-path-elements (e.g., at least region **504ef-1**, region **502ff-1**, or region **504fg-1**), the respective predetermined display regions of at least two of the group of the graphical-path-elements having different shapes (e.g., region **504fg-1** has a different shape than region **502ff-1**). In some embodiments, one of the plurality of graphical-path-elements (e.g., graphical element **502ff**) includes the third location (e.g., an internal or intermediate location in the graphical path) defined according to the instructions associated with block **610c**.

(191) In various embodiments, the analysis (which may be included as part of the instructions associated with blocks **610a**, **610b**, **610c**) of the display-screen location (e.g., a display-screen location associated with a first user input, motion-based user input, or second user input, e.g., respectively pursuant to blocks **608a**, **608b**, and **608c**) in relation to one or more of the graphical elements **501** (e.g., one or more transducer graphical elements **502** or one or more between graphical elements **504**) includes determining a proximity between the display-screen location and each of one or more graphical elements **501**. The one or more graphical elements may include, in some embodiments, two or more of the graphical elements (e.g., two or more of the transducer graphical elements **502** or two or more of the between graphical elements **504**), and the analysis of the display-screen location in relation to the two or more of the graphical elements **501** may include defining the respective location (e.g., first location, second location, or third location pursuant to blocks **610a**, **610b**, **610c**) on the graphical path as a location of a particular one of the two or more graphical elements **501** in closest proximity to the display-screen location.

(192) For example, a first user input at display-screen location **519-1a** in FIG. 5S is closest to transducer graphical element **502aa**, so transducer graphical element **502aa** may be determined by the data processing device system, according to the instructions associated with block **610a**, to be a first location in the graphical path, according to some embodiments. For another example, a user input occurring at cursor location **519-2a** in FIG. 5T is closest to between graphical element **504ab**, so between graphical element **504ab** may be determined by the data processing device system, according to the instructions associated with block **610c**, to be a location in the graphical path, according to some embodiments. Continuing this example, according to some embodiments, since the closest graphical element is a between graphical element **504ab**, the data processing device system may be configured to also determine that the transducer graphical elements **502aa** and **502bb** associated with the between graphical element **504ab** are to be included in the graphical path. Since transducer graphical elements **502aa** may have already been part of the graphical path (e.g., due to an earlier selection via the motion-based user input, or in some other embodiments via a previous first user input), such transducer graphical elements **502aa** may be neglected, and only transducer graphical element **502bb** would additionally be added to the graphical path, according to some embodiments.

(193) In view of the above-discussions with respect to FIGS. 5S and 5T, when a path traced by motion-based user input (e.g., per arrow **531a** or arrow **531b**) is away from an adjacent or closest graphical element (e.g., **501**), the path traced by the motion-based user input may be considered to “snap” to the adjacent or closest graphical element due to the change in visual characteristics and inclusion of the adjacent or closest graphical element. For example, although the path traced by the motion-based user input in FIG. 5T moves in a diagonal direction according to arrow **531b**, the graphical path follows a slightly different route including transducer graphical element **502aa**, between graphical element **504ab**, transducer graphical element **502bb**, between graphical element

504bc, and transducer graphical element **502cc**. In this regard, it may be considered that the path traced by the motion-based user input snaps to the defined and displayed graphical path, according to some embodiments. Similarly, it may be considered that the user input at the location **519-2a** of cursor **519-2** snaps to between graphical element **504ab**, and that the user input at the location **519-2b** of cursor **519-2** snaps to between graphical element **504bc**, according to some embodiments. In some embodiments, a snapping to a between graphical element (e.g., **504ab**) also causes a concurrent snapping to one or more associated transducer graphical elements (e.g., at least **502bb**).

(194) In some embodiments, path definition instructions (e.g., associated with block **610c** or **610-1c**) are configured to cause the path traced by the motion-based user input or a portion thereof to snap to a transducer graphical element (e.g., **502**) or a portion thereof in response to the path traced by the motion-based user input or the portion thereof being away from the transducer graphical element but within a predetermined distance from the transducer graphical element or a part thereof. The predetermined distance may define the outer limits of the respective display region (e.g., **502aa-1** for transducer graphical element **502aa**), according to some embodiments.

(195) In some embodiments, the path definition instructions are configured to cause an elongate path portion of the graphical path (e.g., defined according to motion-based user input per, e.g., blocks **608c** and **610d** in FIG. 6A) to include a transducer graphical element (e.g., **502**) or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the transducer graphical element but within a predetermined display region associated with the transducer graphical element. In this regard, it should be noted that a graphical path might include only a portion of a graphical element (e.g., **501**) in some embodiments. For example, FIG. 5T shows a graphical path portion represented, at least in part, by highlighting of transducer graphical element **502aa**, between graphical element **504ab**, transducer graphical element **502bb**, between graphical element **504bc**, and transducer graphical element **502cc**. In this regard, the highlighting in each of transducer graphical elements **502aa**, **502bb**, and **502cc** does not occupy the entirety of the interior region of the respective transducer graphical elements. Such a circumstance is an example where the graphical path includes only a portion of a graphical element included in the graphical path. In this regard, the graphical path illustrated in FIG. 5T by highlighting of respective graphical elements is an example of a graphical path having an interrupted form, because the highlighting of the respective transducer graphical elements **502** does not contact the highlighting of the adjacent between transducer graphical element(s) **504**. For another example, FIG. 5S shows highlighting within selected transducer graphical elements **502aa**, **502bb**, and **502cc**, with non-highlighted gaps between respective display regions **502aa-1**, **502bb-1**, and **502cc-1**, such gaps adding to an interrupted form of a graphical path, in some embodiments.

(196) In some embodiments, the path definition instructions are configured to cause the elongate path portion of the graphical path to include a transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof passing through a predetermined display region associated with the transducer graphical element, the predetermined display region including at least a part of the transducer graphical element, and the transducer graphical element not occupying all of the predetermined display region.

(197) In some embodiments, the path definition instructions are configured to cause the elongate path portion of the graphical path to include a transducer graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the transducer graphical element but within a predetermined distance from the transducer graphical element or a part thereof.

(198) In some embodiments, the path definition instructions are configured to cause the path traced by the motion-based user input or a portion thereof to snap to a particular between graphical element (e.g., **504**) or a portion thereof in response to the path traced by the motion-based user input or the portion thereof being away from the particular between graphical element but within a predetermined distance from the particular between graphical element or a part thereof.

(199) In some embodiments, the path definition instructions are configured to cause an elongate path portion of the graphical path (e.g., defined according to motion-based user input per, e.g., blocks **608c** and **610d** in FIG. 6A) to include a particular between graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the particular between graphical element but within a predetermined display region associated with the particular between graphical element.

(200) In some embodiments, the path definition instructions are configured to cause the elongate path portion of the graphical path to include a particular between graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof passing through a predetermined display region associated with the particular between graphical element, the predetermined display region including at least a part of the particular between graphical element, and the particular between graphical element not occupying all of the predetermined display region.

(201) In some embodiments, the path definition instructions are configured to cause the elongate path portion of the graphical path to include a particular between graphical element or a portion thereof in response to the path traced by the motion-based user input or a portion thereof being away from the particular between graphical element but within a predetermined distance from the particular between graphical element or a part thereof.

(202) In some embodiments, the above-discussed ‘snapping’ of a user-input display screen location to a graphical element, when the user-input display screen location is away from the graphical element but within a predetermined display region associated with the graphical element, need not only apply to motion-based user input. In this regard, such ‘snapping’ may apply to stationary user input, in some embodiments, such as a mouse click, a touch-screen contact, or other user input associated with a display screen location, to select a graphical element that is away from the display screen location, but the display screen location is within a predetermined display region associated with the graphical element.

(203) In some cases, a user may desire to adjust or revise the graphical path during the definition or generation of the graphical path. For example, in some embodiments employing arrays of hundreds of graphical elements such as those shown in various graphical elements **501** of FIGS. 5, numerous choices are presented to a user (e.g., a health care practitioner or technician) as to which of these numerous graphical elements should or should not be located on the graphical path or form part of the graphical path. In many cases, a particular set of one or more graphical elements may be deemed to be incorrectly chosen. For example, one or more graphical elements may be mistakenly chosen through an unintended manipulation of a particular user input control element or upon receipt of updated intra-cardiac information (e.g., physiological information) during or after the selection, the updated intra-cardiac information indicating or suggesting that a better selection can be made. In some embodiments, the graphical path definition instructions associated with block **610** further include path adjustment instructions (e.g., associated with block **610e**) configured to adjust (e.g., reduce) a size of at least an elongate path portion (e.g., defined according to motion-based user input per, e.g., **610d**) of the graphical path.

(204) In various embodiments, the path adjustment instructions associated with block **610e** are configured to adjust a size of the elongate path portion in response to a user-based retracing of a portion of the path traced by the motion-based user input. Adjusting a size of the elongate path portion may include a path reduction that still allows for at least some of the elongate path portion or at least some part of the graphical path to be maintained. In some embodiments, the instructions associated with block **610e** are configured to adjust the size of the elongate path portion of the graphical path so long as a graphical path terminating input (e.g., a second user input that places the first user input element in a deactivated state) has not been received (for example, as per the instructions associated with block **608b**). For example, in some embodiments, various instructions that, in response to the reception of the second user input, indicate a termination point in the

graphical path or indicate a termination of the graphical path generation process, may preclude reducing a size of the elongate path portion at least based on a retracing of a portion of the path traced by the motion-based user input. In this regard, in some embodiments, the instructions associated with block **610e** are configured to adjust (e.g., reduce) the size of the elongate path portion of the graphical path so long as a second location or locations (e.g., a set of graphical elements **501**) on the graphical path has not been defined according to a second parameter set associated with a graphical-path-terminating second user input (for example, as per the instructions associated with block **610b**). In some embodiments, other adjustment instructions responsive to other user inputs may be configured to adjust (e.g., reduce) a portion of the graphical path. For example, other instructions may include instructions that may cause an undoing of at least the entirety of the elongate path portion.

(205) In some embodiments, the motion-based user input (e.g., according to the instructions associated with block **608c**) indicates a selection of a group of transducer graphical elements (e.g., **502**). In some of these embodiments, the instructions associated with block **610e** may include de-selection instructions configured to deselect at least one transducer graphical element in the group of the transducer graphical elements in response to a user-based retracing of a portion of the path traced by the motion-based user input.

(206) FIG. **6F** shows an exploded view of blocks of at least some of the instructions of method **600** employed according to various aspects of block **610e** in FIG. **6A**, according to some embodiments. FIG. **6F** includes a set of instructions associated with block **610-2** and a set of instructions associated with block **612-2**. Block **610-2** shows an exploded view of path definition instructions of block **610** as employed in some embodiments. Block **612-2** shows an exploded view of the graphical path display instructions associated with block **612** as employed in some embodiments. The instructions associated with block **610-2** define a graphical path that includes a plurality of elements or graphical-path-elements in some embodiments. For the ease of convenience, reference is made to various ones of graphical elements **501** (e.g., various ones of transducer graphical elements **502**, various one of between graphical elements **504**, or both). It is understood however, that other embodiments may employ other forms of graphical elements or graphical-path-elements. Additionally, it is noted in various embodiments, a particular graphical element or graphical-path element may not necessarily be visible (e.g., visibly displayed by an input-output device system) prior to selection. For example, in some embodiments, various graphical elements along the path or various graphical-path-elements forming at least part of the path may not be made visible until indicated by some form of user input (e.g., a motion-based user input received, for example, in accordance with the instructions associated with block **608c**).

(207) Block **610-2a** is associated with, in some embodiments, instructions configured to initiate the graphical path at least in response to receiving first user input (e.g., first user input that places a first user input element into an activated state, for example, as received by the instructions associated with block **608a**). In this regard, block **610-2a** may encompass at least block **610a** in FIG. **6A**, **610-1a** in FIG. **6E**, or both. Block **610-2c** is associated with, in some embodiments, instructions configured to define an interim-definition of the graphical path according to a path traced by motion-based user input (e.g., motion-based user input received in accordance with the instructions associated with block **608c**). In this regard, block **610-2c** may correspond at least to or encompass at least block **610c** in FIG. **6A**, **610-1c** in FIG. **6E**, or both. The displayed graphical representation of the graphical path, as defined by the interim-definition, is discussed below with respect to FIG. **5U**. Block **610-2b** is associated with, in some embodiments, instructions configured to cause conclusion of the definition of the graphical path in response to receiving second user input (e.g., second user input that places a first user input element into a deactivated state, for example, as received by the instructions associated with block **608b**). In this regard, block **610-2b** may encompass at least block **610b** in FIG. **6A**, **610-1b** in FIG. **6E**, or both.

(208) In various embodiments, each of the graphical elements or graphical-path-elements includes

a respective display region, and an indication or identification or a status determination (e.g., visible/non-visible or selected/not selected) of each of the graphical elements or graphical-path-elements occurring in response to the selection of the respective display region. In some embodiments, each display region includes at least a portion of a respective graphical element or graphical-path-element. In some embodiments, each display region includes all of a respective graphical element or respective graphical-path-element. In some embodiments, the respective graphical element or graphical-path-element occupies all of its respective display region. In some embodiments, the respective graphical element or respective graphical-path-element does not occupy all of its respective display region.

(209) In various embodiments, display instructions (e.g., display instructions associated with block **612-2a**) are provided and are configured to cause an input-output device system (e.g., **120**, **320**) to display, prior to the conclusion of the definition of the graphical path, a graphical representation of the graphical path including the identified plurality of graphical elements or the identified plurality of graphical-path-elements consistent with the interim-definition (e.g., block **610-2c**) of the graphical path. In some embodiments, a visual characteristic set of the respective graphical element or respective graphical-path-element changes upon selection (e.g., a selection made on the basis of the first user input, the second user input, or the motion-based user input as described above).

(210) In various embodiments, the instructions associated with block **610-2d** are configured to cause generation of a modified-interim-definition of the graphical path prior to the conclusion of the definition of the graphical path. In this regard, block **610-2d** may correspond at least to or encompass at least block **610c** in FIG. **6A**, **610-1c** in FIG. **6E**, or both. The displayed graphical representation of the graphical path, as defined by the modified-interim-definition, is discussed below with respect to FIG. **5V**. In various embodiments, the modified-interim-definition of the graphical path excludes at least one of the identified plurality of graphical elements or graphical-path-elements in response to a user-based retracing of a portion of the path traced by the motion-based user input. In some of these various embodiments, the excluded at least one of the identified plurality of graphical elements or graphical-path-elements are those whose associated display regions have been passed through by the retracing of the portion of the path traced by the motion-based user input. In various embodiments, the display instructions (e.g., display instructions associated with block **612**) are configured to cause the input-output device system (e.g., **120**, **320**) to change the display of the graphical representation of the graphical path to account for the excluded at least one of the identified plurality of the graphical elements or graphical-path-elements consistent with the modified-interim-definition of the graphical path.

(211) For example, in FIG. **5U**, a graphical representation of graphical path including a plurality of graphical elements or graphical-path-elements is displayed prior to the conclusion of the definition of the graphical path (e.g., prior to an execution of the instructions associated with block **610-2b**), the selection of graphical elements or graphical-path-elements identified or indicated as per an interim-definition of the graphical path generated according to a path traced by a motion-based user input (for example, as per the instructions associated with block **610-2c**). In particular, the interim-definition of the graphical path identifies a selection of transducer graphical elements **502ee**, **502ff**, **502gg**, and **502hh** (e.g., selected from a group of transducer graphical elements **502ee**, **502ff**, **502gg**, **520hh**, **502ii**, and **502jj** (collectively transducer graphical elements **502**) in FIG. **5U**). It is noted that, upon selection, a visual characteristic set of each of transducer graphical elements **502ee**, **502ff**, **502gg**, and **502hh** has been changed (for example, as compared with unselected transducer graphical elements **502ii**, **502jj**) in a manner similar to, or the same as that indicated by various other selected transducer graphical elements **502** shown in various other ones of FIG. **5**. Additional information **521** is not shown in FIGS. **5U**, **5V** and **5W** for clarity, although it is understood that information **521** may or may not be included in other embodiments.

(212) In FIG. **5U**, transducer graphical elements **502ee**, **502ff**, **502gg**, and **502hh** are selected by employing a motion-based user input that moves a mouse cursor **519-3** along a path (e.g.,

schematically represented by arrow **531c** in some embodiments) sequentially through display regions **504ef-1**, **504fg-1**, and **504gh-1** of between graphical elements **504ef**, **504fg**, and **504gh**. That is, in some embodiments, transducer graphical elements **502ee**, **502ff**, **502gg**, and **502hh** are indirectly selected in response to a user selection of between graphical elements **504ef**, **504fg**, and **504gh**. In some embodiments, between graphical elements **504ef**, **504fg**, and **504gh** also form part of the graphical elements or graphical-path-elements identified or indicated by the interim-definition of the graphical path. In some embodiments, each of the between graphical elements **504ef**, **504fg**, and **504gh** along with each of the transducer graphical elements **502ee**, **502ff**, **502gg**, and **502hh** is identified or indicated as a graphical element or graphical-path-element forming part of, or included in the graphical path in accordance with the interim definition of the graphical path. (213) In some embodiments, each of the between graphical elements **504ef**, **504fg**, and **504gh** along with each of the transducer graphical elements **502ee**, **502ff**, **502gg**, and **502hh** is selected as the mouse cursor **519-3** moves along sequentially from position **519-3a** (indicated by mouse cursor **519-3** shown in broken lines) to **519-3b** (indicated by mouse cursor **519-3** shown in broken lines) to **519-3c** (indicated mouse cursor **519-3** shown in solid lines) along a path (e.g., schematically represented by arrow **531c**) traced by the motion-based user input, thereby providing the interim-definition of the graphical path. In some embodiments, each of the locations **519-3a**, **519-3b**, and **519-3c** is in a respective one of the display regions **504ef-1**, **504fg-1**, and **504gh-1** associated with between graphical elements **504ef**, **504fg**, and **504gh**. In some embodiments, each of between graphical elements **504ef**, **504fg**, and **504gh** does not occupy the entirety of a respective one of display regions **504ef-1**, **504fg-1**, and **504gh-1**.

(214) It is noted in some embodiments, that, upon selection, a visual characteristic set of each of the directly selected between graphical elements **504ef**, **504fg**, and **504gh** may be changed (e.g., as compared with unselected between graphical elements **504hi**, **504ij** and **504ja**) along with a change in a visual characteristic set of transducer graphical elements **502ee**, **502ff**, **502gg**, and **502hh**. Changes in a visual characteristic set of various graphical elements in FIGS. 5V and 5W (described below) may be made in accordance with the instructions associated with block **612** in some embodiments.

(215) In FIG. 5V, a modified-interim-definition of the graphical path is generated (for example, by execution of the instructions associated with block **610-2d**). In various embodiments, the modified-interim-definition of the graphical path is generated prior to the conclusion of the definition of the graphical path. In FIG. 5V, the modified interim definition of the graphical path excludes at least some of the selected graphical elements or graphical-path-elements (e.g., transducer graphical elements **502** and between graphical elements **504**) shown in FIG. 5U in response to a user-based retracing of a portion of the motion-based user input employed to generate the interim-definition of the graphical path shown in FIG. 5U. In various embodiments, the excluded graphical elements or excluded graphical-path-elements are those whose display regions have been passed through by the retracing of the portion of the path traced by the motion-based user input during the interim-definition of the graphical path.

(216) In various embodiments, display instructions (e.g., instructions associated with block **612-2b**) are configured to cause an input-output device system (e.g., **120**, **320**) to change the display of the graphical representation of the graphical path (for example, as provided by the interim-definition of the graphical path) to account for at least one of the identified excluded graphical elements or at least one of the identified excluded graphical-path-elements. In various embodiments, display instructions (e.g., instructions associated with block **612-2b**) are configured to cause an input-output device system (e.g., **120**, **320**) to change the display of the graphical representation of the graphical path (for example, as provided by the interim-definition of the graphical path) to account for at least one of the identified excluded graphical elements or at least one of the identified excluded graphical-path-elements in manner consistent with the modified-interim-definition of the graphical path. In various embodiments, display instructions (e.g., instructions associated with

block 612-2b) are configured to cause an input-output device system (e.g., 120, 320) to change the display of the graphical representation of the graphical path (for example, as provided by the interim-definition of the graphical path) to account for at least one of the identified excluded graphical elements or at least one of the identified excluded graphical-path-elements prior to a conclusion of the definition of the graphical path.

(217) In some embodiments encompassing FIG. 5V, transducer graphical elements 502hh and 520gg along with between graphical elements 504gh and 5094fg are excluded to generate the modified-interim-definition of the graphical path. In some embodiments, user-based retracing of a portion of the motion-based user input that results in the exclusion of transducer graphical elements 502hh and 520gg and between graphical elements 504gh and 504fg includes a movement of mouse cursor 519-3 along a path (e.g., schematically represented by arrow 531d in some embodiments) sequentially from position 519-3d (indicated by mouse cursor 519-3 shown in broken lines) to position 519-3e (indicated by mouse cursor 519-3 shown in broken lines) to position 519-3f (indicated by mouse cursor 519-3 shown in solid lines). In some embodiments, each of locations 519-3d and 519-3e are located in a respective one of the display regions 504gh-1 and 504fg-1 that were previously passed through during the interim definition of the graphical path in FIG. 5U. In this regard, particular ones of the graphical elements or graphical-path-elements selected by passing through their respective display regions during the interim-definition of the graphical path in FIG. 5U are deselected by retracing through the same respective display regions during the modified-interim-definition of the graphical path in FIG. 5V. For example, when the mouse cursor 519-3 is retraced along a path extending from location 519-3d in display region 504gh-1 to location 519-3e in display region 504fg-1, between graphical element 504gh and transducer graphical element 502hh (e.g., originally selected as part of the graphical elements or graphical-path-elements in FIG. 5U) are deselected. It is noted, in various embodiments, that transducer graphical element 502gg may be directly selected along with transducer graphical element 502hh when between graphical element 504gh is selected in accordance with a path traced by the motion-based user input (for example, as per the embodiment of FIG. 5U).

(218) In some of these various embodiments, transducer graphical element 502gg is not immediately deselected when the mouse cursor 519-3 is retraced out of the display region 504gh-1 for various reasons. For example, in some embodiments, transducer graphical element 502gg was indirectly selected e.g., when between graphical element 504fg was selected in accordance with a path traced by the motion-based user input as shown in FIG. 5U, and is not deselected until the retracing moves mouse cursor 519-3 into and out of the display region 504fg-1 of between graphical element 504fg. For example, in FIG. 5V, each of transducer graphical elements 502hh, 502gg and between graphical elements 504gh, 504fg are shown as deselected (e.g., via a change in their visual characteristics as compared with their selected state in FIG. 5U) when mouse cursor 519-3 is moved to location 519-3f in display region 502ff-1.

(219) It is noted in some embodiments, retracing may occur through various display regions whose respective graphical elements or graphical-path-elements occupy the entirety thereof. It is noted that an exact retracing of the motion-based user input employed during the interim-definition of the graphical path need not be required during the modified-interim-definition of the graphical path (e.g., location 519-3d need not be the same as location 519-3c and location 519-3e need not be the same as location 519-3b).

(220) In some embodiments, particular ones of graphical elements or graphical-path-elements are not deselected during the modified-interim-definition of the graphical path unless the path traced by the motion-based-user input during the selection of the particular ones of graphical elements or graphical-path-elements and the portion of the path retraced to deselect the particular ones of graphical elements or graphical-path-elements pass through the same ones of the display regions associated with the particular ones of graphical elements or graphical-path-elements. In some embodiments, particular ones of graphical elements or graphical-path-elements are not deselected

during the modified-interim-definition of the graphical path unless the path traced by the motion-based-user input during the selection of the particular ones of graphical elements or graphical-path-elements and the portion of the path retraced to deselect the particular ones of graphical elements or graphical-path-elements pass through the same ones of the display regions associated with the particular ones of graphical elements or graphical-path-elements in a reverse order that the display regions associated with the particular ones of graphical elements or graphical-path-elements were passed through during the interim-definition of the graphical path. For example, in FIG. 5W, each of transducer graphical elements **502hh**, **502gg** and between graphical elements **504gh** and **504fg** that were selected according to the embodiment of FIG. 5U are not deselected, according to some embodiments, when a retracing of a portion of the path traced by the motion-base user input in the embodiment associated with FIG. 5U is attempted to be retraced along a path (e.g., represented by arrow **531e**) generally different than the portion of the path originally employed to select transducer graphical elements **502hh**, **502gg** and between graphical elements **504gh**, **504fg**. The retrace path indicated in FIG. 5W does not pass from display region **504gh-1** to display region **504fg-1** to display region **502ff-1** (for example, as shown in FIG. 5V) and each of transducer graphical elements **502hh**, **502gg** and between graphical elements **504gh**, **504fg** are not deselected (e.g., as indicated by a lack of change in their visible characteristics as compared with FIG. 5U) according to some embodiments. The attempted retrace path indicated in FIG. 5W does not pass from display region **504gh-1** to display region **504fg-1** to display region **502ff-1** in a reverse order that these particular display regions were passed through by the path traced by the motion-based user input employed to select particular ones of the graphical elements corresponding to these particular display regions in FIG. 5U, and, consequently, in accordance with some embodiments, these particular graphical elements are not deselected during the retracing.

(221) In FIG. 5W, the retraced path moves from location **519-3g** (indicated by mouse cursor **519-3** in broken lines) in display region **504gh-1** to location **519-3h** (indicated by mouse cursor **519-3** in broken lines) in display region **504hi-1** to location **519-3i** (indicated by mouse cursor **519-3** in broken lines) in display region **504if-1** to location **519-3j** (indicated by mouse cursor **519-3** in unbroken lines) in display region **502ff-1**. Rather than deselecting various graphical elements or graphical-path-elements (e.g., transducer graphical elements **502hh**, **502gg** and between graphical elements **504gh** and **504fg**) selected during the interim-definition of the graphical path in FIG. 5U, additional graphical elements or graphical-path-elements are selected in response to the attempted retracing according to some embodiments. For example, between graphical elements **504hi** and **504if** and transducer graphical element **502ii** are shown selected (e.g., as indicated by change in their visual characteristics as compared with their unselected state in FIG. 5U) in response to the attempted retracing.

(222) Improved mechanisms by which a user can efficiently manipulate the map of transducers **306** via transducer graphical elements **502** in graphical representation **500** will now be described with respect to FIGS. 7 and 8A-8C, according to various embodiments. In some embodiments, the improved mechanisms allow a user to efficiently cause an automatic repositioning of a desired graphical element, such as a transducer graphical element **502**, to facilitate better viewing. Since viewing and interaction with the transducer graphical elements **502** to control a transducer based device, such as transducer-based device **300**, may occur during a medical procedure, time can be of the essence, and access to desired information may need to occur as quickly as possible.

Accordingly, the present inventors have developed mechanisms by which a user, such as a physician or other medical professional, can efficiently and accurately reposition the map of transducers **306** via transducer graphical elements **502** in graphical representation **500** so that the user can better view needed information quickly.

(223) In light of these and other benefits, FIG. 7 includes a respective data generation and flow diagram, which may implement various embodiments of method **700** by way of associated computer-executable instructions according to some example embodiments. In various example

embodiments, a memory device system (e.g., memory device systems **130**, **330**) is communicatively connected to a data processing device system (e.g., data processing device systems **110** or **310**, otherwise stated herein as “e.g., **110**, **310**”) and stores a program executable by the data processing device system to cause the data processing device system to execute various embodiments of method **700** via interaction with at least, for example, a transducer-based device (e.g., transducer-based devices **200**, **300**, or **400**). In these various embodiments, the program may include instructions configured to perform, or cause to be performed, various ones of the instructions associated with execution of various embodiments of method **700**. In some embodiments, method **700** may include a subset of the associated blocks or additional blocks than those shown in FIG. 7. In some embodiments, method **700** may include a different sequence indicated between various ones of the associated blocks shown in FIG. 7. In this regard, in some embodiments, blocks **702**, **704**, **706**, and **708** correspond to blocks **602**, **604**, **606**, and **608** described above with respect to FIG. 6 (although some embodiments of block **708** do not utilize some or all of sub-blocks **608-1**, **608a**, **608b**, **608c**, **608d**, and **608e** and may, e.g., utilize sub-blocks **708-1** and **708-2**, discussed below, instead). Accordingly, at least some duplicative descriptions will be omitted.

(224) In some embodiments, block **702** is associated with computer-executable instructions (e.g., input, acquisition, sampling, or generation instructions and provided by a program) configured to cause the data processing device system (e.g., data processing device systems **110** or **310**) to acquire or receive and, e.g., generate, intra-cardiac information from each of one or more transducers of the plurality of transducers (e.g., **220**, **306**) of the transducer-based device (e.g., **200**, **300**), as described above with respect to at least block **602** in FIG. 6A, block **602-1** in FIG. 6B, and block **602-2** in FIG. 6C.

(225) In some embodiments, block **704** is associated with computer-executable instructions (e.g., graphical representation instructions or graphical interface instructions or display instructions provided by a program) configured to cause an input-output device system (e.g., input-output device system **120** or **320**) to display a graphical representation, such as at least the various examples of the graphical representation **500** described and illustrated above with respect to at least FIGS. 5A-5R and 5X and block **604** in FIG. 6A. FIGS. 8A-8C illustrate other examples of such graphical representation **500**, according to various embodiments. Also, the instructions associated with block **706** may be configured to include in the graphical representation **500** a two-dimensional or three-dimensional graphical representation of at least a portion of a transducer-based device (e.g., structure **308** in FIG. 3) as described above with respect to block **606** in FIG. 6A. It is noted that the graphical representation of the portion of the transducer-based device shown in the graphical representation **500** in each of FIGS. 8A-8C is of a transducer-based device like the transducer-based device **300**, but which has fewer elongate members than elongate members **304** of the transducer-based device **300** and fewer transducers than transducers **306** of the transducer-based device **300**.

(226) With respect to at least FIG. 8A, only three graphical elements **502** are called out among the plurality for purposes of clarity. In addition, the graphical representation **500** includes a graphical location **841a** corresponding to a location of a first pole of the structure (e.g., a pole corresponding to pole **341a** of structure **308** shown in FIG. 3C), and a graphical location **841b** corresponding to a location of a second pole of the structure opposing the first pole (e.g., a pole corresponding to pole **341b** of structure **308** shown in FIG. 3D), according to some embodiments. In the embodiments illustrated in FIGS. 8A-8C, such graphical locations **841a** and **841b** corresponding to the locations of the poles of the structure of the transducer-based device do not include any particular distinguishing visible markers for the pole locations, but they may be included according to various embodiments. Also note that in FIG. 8A, the graphical location **841a** is shown twice at the top and bottom of the graphical representation **500**, since the representative location of the first pole is at the edge of the map in this view.

(227) Also with respect to FIG. 8A, the graphical representation **500** may include a graphical region **841a-1** (split across the top and bottom of the graphical representation **500**) corresponding to a first polar region surrounding the first pole of the structure (e.g., the pole corresponding to pole **341a** of structure **308** shown in FIG. 3C), and a graphical region **841b-1** corresponding to a second polar region surrounding the second pole of the structure (e.g., the pole corresponding to pole **341b** of structure **308** shown in FIG. 3D), according to some embodiments. Such polar regions may be defined to be at latitudes greater than or equal to 70 degrees, 75 degrees, 80 degrees, and 85 degrees, according to various embodiments. In some embodiments such as those illustrated in FIGS. 8A-8C, such graphical regions **841a-1** and **841b-1** corresponding to the polar regions of the structure of the transducer-based device do not include any particular distinguishing visible markers for the polar regions, but they may be included according to various embodiments.

(228) In some embodiments, block **708**, like block **608**, is associated with input-processing instructions indicating reception or reception and processing of various user inputs. In some embodiments, the instructions associated with block **708** may include instructions (e.g., storage instructions associated with block **708-1**) configured to cause reception and storage in a memory device system (e.g., memory device system **130** or **330**) of particular information indicative of a predetermined location in the graphical representation **500**, e.g., to where it may be desired to automatically reposition a location-of-interest in the graphical representation, such as a transducer graphical element **502**, for improved viewing by the user. The predetermined location may be a region of the graphical representation **500** that exhibits less mapping distortion so that, for example, a desired transducer graphical element **502** and its associated intra-cardiac information can be repositioned away from a region in the map exhibiting relatively greater distortion for improved viewing, such as away from large edge-based-distortion in a Mercator map or transverse Mercator map. Also, according to some embodiments, the predetermined location may be away from an edge of the graphical representation **500**, because such an edge may not only have increased mapping distortion in some embodiments, but such an edge may also or alternatively cause a splitting across the map or a partial disappearance of the associated transducer graphical element **502**, its associated intra-cardiac information, or both the associated transducer graphical element **502** and its associated intra-cardiac information. In this regard, depending on a display device or display configuration that a user has implemented, it may be preferable for the user to set the predetermined location to be a center of the graphical representation **500**, so that a transducer graphical element **502** of interest to the user can automatically be centered in the graphical representation **500** for improved viewing, e.g., with its improved positioning and reduced mapping distortion, according to some embodiments. However, such a predetermined location need not be the center of the graphical representation **500**, and may be any other preferable location within the graphical representation **500**. Further, such a predetermined location may have a default location (e.g., that is factory set or otherwise predefined), while allowing a user to redefine the predetermined location to another location within the graphical representation **500** according to the instructions associated with block **708-1**. In some embodiments, block **708-1** is omitted from the method **700**, so that a default assignment of the predetermined location is not changeable by a user or a particular class of users (e.g., non-administrators, with an administrator being, for instance, a super-user that has special access rights to the computer system needed to administer such system).

(229) In some embodiments, the instructions associated with block **708** may include instructions (e.g., associated with block **708-2**) configured to cause reception of a set of user input via the input-output device system (e.g., input-output device system **120** or **320**). The set of user input may include an instruction set to reposition a first transducer graphical element (e.g., first transducer graphical element **502-2G** in FIG. 8B) of the plurality of transducer graphical elements **502** in a state in which the first transducer graphical element is located at a first location (e.g., first location **801** in FIG. 8B) in the graphical representation **500** and a second transducer graphical element (e.g., second transducer graphical element **502-14D** in FIG. 8B) of the plurality of transducer

graphical elements **502** is located at a second location (e.g., second location **802** in FIG. **8B**) in the graphical representation **500**.

(230) The second transducer graphical element **502-14D** may be considered a reference transducer graphical element that is not user or machine selected, but merely chosen for this description for purposes of the examples of FIGS. **8B** and **8C** to help illustrate the dynamics of the movement of the map of transducers **306** via the transducer graphical elements **502** in the graphical representation **500** to reposition the user-selected first transducer graphical element **502-2G** to the predetermined location (e.g., predetermined location **804** in the examples of FIGS. **8B** and **8C**). Accordingly, it should be understood that the present invention is not limited to the user selection of any particular transducer graphical element (i.e., a transducer graphical element other than transducer graphical element **502-2G** may be user-selected for placement at the predetermined location) or the use of any particular transducer graphical element as the reference second transducer graphical element (i.e., a transducer graphical element other than transducer graphical element **502-14D** may be utilized as a reference to illustrate changes in positioning of the map of transducers **306** via the transducer graphical elements **502** in the graphical representation **500**). According to some embodiments, as shown, for example, in FIG. **8B**, the second location **802** is closer to a predetermined location **804** in the graphical representation **500** than the first location **801**. According to some embodiments, as shown for example in FIG. **8B**, the second location **802** and the predetermined location **804** are different locations.

(231) According to some embodiments associated with at least FIGS. **7** and **8A-8C**, the word “closer”, “distance” (see, e.g., the discussions regarding first distance **821** and second distance **822**, below), and the like as used in this and similar contexts pertaining to distances within the graphical representation **500** refers to relative distances or distances across the graphical representation **500** independent of an orientation of the underlying map of transducers (e.g., transducers **306**) represented by transducer graphical elements **502**. For example, first location **801** is in the same relative location in the graphical representation **500** in both FIGS. **8B** and **8C**, even though the orientation or configuration of the underlying map of transducers changes between FIGS. **8B** and **8C**. This definition of “closer”, “distance”, and the like in these contexts, according to some embodiments, is the same for both two-dimensional mappings of the transducers (e.g., such as those shown in FIGS. **8A-8C**) and three-dimensional representations of transducers (e.g., such as those shown in FIGS. **5A-5D** and **5R**). However, in some embodiments, a three-dimensional representation (e.g., such as those shown in FIGS. **5A-5D** and **5R**) of transducers (e.g., transducers **306**) on a structure (e.g., structure **308**) may permit viewing through a representation of a gap in the structure (e.g., through a representation of a gap **344** in FIG. **3D** in structure **308** between elongate members **304**). In some of such embodiments, it may be possible to view a representation of a transducer (e.g., transducer **306**) on a side of the structure (e.g., structure **308**) opposite the side represented as closest to the viewer. In these embodiments, it may appear that a representation of a first particular transducer (e.g., via a transducer graphical element **502**) on the opposite side of the structure is closer in the graphical representation **500** to a representation of a second particular transducer on the side of the structure represented as closest to the viewer, than a third particular transducer located on the side of the structure represented as closest to the viewer is located with respect to the second particular transducer, even though the third particular transducer physically is located closer to the second particular transducer than the first particular transducer is located with respect to the second particular transducer. In some of these embodiments, the term “closer”, “distance”, and the like excludes the representations of the transducers on the side of the structure represented as facing away from the viewer, as if the representations of the transducers on the opposing side of the structure were not viewable.

(232) Continuing with respect to the example of FIG. **8B**, the set of user input received according to the instructions associated with block **708-2** may include a user-selection of the first transducer graphical element **502-2G**, such as by a right-mouse click with a mouse cursor located over the

transducer graphical element **502-2G** or within some other region of the graphical representation **500** corresponding to transducer graphical element **502-2G**, such as, for example, a display region akin to display region **502aa-1** in FIG. 5S). However, any other manner of selecting a transducer graphical element may be implemented, although selection at the transducer graphical element itself or within its corresponding display region (e.g., like display region **502aa-1**) may be particularly intuitive and useful to a user in various contexts. The user-selection of the first transducer graphical element **502-2G** or any other transducer graphical element **502** may be motivated by various reasons, such as a desire to have such transducer graphical element automatically repositioned to the predetermined location **804** (which may have been defined according to the instructions associated with block **708-1**) for better viewing.

(233) In some embodiments, as shown for example in FIG. 8B, the user-selection of the first transducer graphical element **502-2G** causes, according to the instructions associated with block **708-2**, the display of a menu **850**. The menu **850** may include various menu options labeled generically in FIG. 8B as Menu Options **1-4** and **6-8**, with the fifth menu option **851** being a request to automatically reposition the selected transducer graphical element **502-2G** to the predetermined location. In the example of FIG. 8B, the predetermined location **804** is the center of the two-dimensional projection of the graphical representation **500**. However, the predetermined location **804** may be in other predetermined locations within the graphical representation **500** in other embodiments. Also in the example of FIG. 8B, the predetermined location **804** coincides with a first particular location **805** corresponding to the second pole of the structure (e.g., like pole **341b** of structure **308** shown in FIG. 3D). In this regard, in some embodiments, the first particular location **805** in the graphical representation **500** is closer to the predetermined location **804** than to the first location **801** at least in a state in which the first transducer graphical element **502-2G** is located at the first location **801**. In some embodiments, such as those encompassed by the example of FIG. 8B, the first particular location **805** is located centrally in the graphical representation **500** at least in the state in which the first transducer graphical element **502-2G** is located at the first location **801**.

(234) Upon display of the menu **850**, according to some embodiments, the user may select menu option **851**, e.g., by way of a mouse click or any other selection technique, to initiate the automatic repositioning of the selected first transducer graphical element **502-2G**, which occurs according to the instructions associated with block **709**. The set of user input received according to the instructions associated with block **708-2** with respect to the example of FIG. 8B may include or be the initial user selection that causes display of the menu **850** as well as the user's subsequent selection of menu option **851**, according to some embodiments. However, any number (one or more) and sequence (if more than one) of user inputs needed to produce an instruction set to reposition a transducer graphical element or other graphical element may be implemented, according to various embodiments.

(235) In some embodiments, the instructions associated with block **709** are associated with computer-executable instructions (e.g., graphical representation modification instructions provided by a program) configured to cause, in response to conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element (e.g., first transducer graphical element **502-2G**) according to the instructions associated with block **708-2**, an input-output device system (e.g., input-output device system **120** or **320**) to reposition the first transducer graphical element (e.g., first transducer graphical element **502-2G**) from the first location (e.g., first location **801**) in the graphical representation **500** to the predetermined location (e.g., predetermined location **804**) in the graphical representation **500**.

(236) For example, as shown in FIG. 8C, upon conclusion of receipt of the user's selection of the first transducer graphical element **502-2G** that brings up the menu **850** and the user's selection of menu option **851**, the map of transducers **306** via the transducer graphical elements **502** is automatically shifted from the state of FIG. 8B to the state of FIG. 8C to place the selected first

transducer graphical element **502-2G** at the predetermined location **804**, which, in this example, is centrally located in the graphical representation **500**, for improved viewing, according to the instructions associated with block **709**. The shifting of the map of transducers **306** via the transducer graphical elements **502** may be implemented, for example, by a re-calculation of the mapping (e.g., via a transverse Mercator projection according to the examples of FIGS. **8B** and **8C** or other projection) of the structure of the transducer-based device (e.g., like structure **308** of transducer-based device **300**), with the selected first transducer graphical element **502-2G** located at the predetermined location **804**, according to some embodiments. In this regard, it can be seen that the predetermined location **804** is more centrally located in the graphical representation **500** in the example of FIGS. **8B** and **8C** than the first location **801**, and the repositioning of the first transducer graphical element **502-2G** according to the instructions associated with block **709** centralizes (e.g., to draw or bring to or toward a center point or to gather into or about a center) the first transducer graphical element **502-2G** in the graphical representation **500**, according to some embodiments.

(237) According to some embodiments, the repositioning of the first transducer graphical element **502-2G** to the predetermined location **804**, according to the instructions associated with block **709**, causes the second transducer graphical element **502-14D** to be repositioned from the second location **802** in FIG. **8B** to a third location **803** in FIG. **8C**, due to the shifting of the map of transducers **306** via the transducer graphical elements **502** in the graphical representation **500** between FIGS. **8B** and **8C**. In some embodiments, such as those shown in FIG. **8C**, the predetermined location **804** is more centrally located in the graphical representation **500** than the third location **803**. According to some embodiments, such as those shown in FIG. **8C**, the first location **801** is spaced in the graphical representation **500** from the predetermined location **804** by a first distance **821** and the third location **803** is spaced from the second location **802** by a second distance **822**, the first distance **821** and the second distance **822** being different distances. According to some embodiments, this difference in distances may be due at least in part to distortion present in the map of transducers **306** via the transducer graphical elements **502** in the graphical representation **500**. According to some embodiments, this difference in distances may be due at least in part to distortion cause by the conformal mapping of transducers **306** via the transducer graphical elements **502** in the graphical representation **500**. According to some embodiments, this difference in distances may be due at least in part to distortion caused by a mapping of transducers **306** via the transducer graphical elements **502** in the graphical representation **500** according to a transverse Mercator projection. In the example of FIG. **8C**, the illustrated map of transducers **306** via transducer graphical elements **502** includes distortion that increases with distance from the depicted locations of the poles **841a**, **841b** in the graphical representation **500**, when mapping the three-dimensional structure (e.g., like structure **308**) into the two-dimensional planar view according to the transverse Mercator projection. Similarly, according to some embodiments, such as those shown in FIG. **8C**, the predetermined location **804** is in a first direction **811** extending from the first location **801** and in a second direction **812** extending from the third location **803** in the graphical representation **500**, with the first direction **811** and the second direction **812** being non-parallel directions.

(238) According to some embodiments, and as shown in FIG. **8C**, the repositioning of the first transducer graphical element **502-2G** to the predetermined location **804**, according to the instructions associated with block **709**, causes the graphical representation **500** to be reconfigured to cause a second particular location **806** in the graphical representation **500** to correspond to the second pole of the structure (e.g., like pole **341b** of structure **308** shown in FIG. **3D**) instead of the first particular location **805**, which corresponded to the second pole of the structure in the state of FIG. **8B**. In some embodiments, such as those shown in FIG. **8C**, the second particular location **806** is located farther from the predetermined location **804** than the first particular location **805**.

(239) According to some embodiments, and as shown by a comparison of FIGS. **8B** and **8C**, the

repositioning of the first transducer graphical element **502-2G** to the predetermined location **804**, according to the instructions associated with block **709**, causes at least the second transducer graphical element **502-14D** to appear rotated in the graphical representation **500** about a graphical region corresponding to a pole location (e.g., the graphical region being located at the first particular location **805** in FIG. **8B** and at the second particular location **806** in FIG. **8C**) of a pole (e.g., pole **841b**) of the structure (e.g., structure **308**) between a transition from a state in which the first transducer graphical element **502-2G** is located at the first location **801** in FIG. **8B** and a state in which the first transducer graphical element **502-2G** is located at the predetermined location **804** in FIG. **8C** upon conclusion of the repositioning of the first transducer graphical element **502-2G** from the first location **801** in the graphical representation **500** to the predetermined location **804** in the graphical representation **500**.

(240) Although not shown in FIGS. **8A-8C**, intra-cardiac information acquired according to the instructions associated with blocks **702** and **602** and illustrated, for example, in FIGS. **5G-5R**, may be included in the graphical representation **500** in FIGS. **8A-8C**. For instance, according to some embodiments, the graphical representation in FIGS. **8A-8C** may represent such intra-cardiac information among the plurality of transducer graphical elements **502**. Upon repositioning of the first transducer graphical element **502-2G** from the first location **801** to the predetermined location **804** between FIGS. **8B** and **8C**, any intra-cardiac information included in the graphical representation **500** of FIGS. **8B** and **8C** would be correspondingly repositioned and updated, according to some embodiments. For instance, the graphical representation modification instructions associated with block **709** may be configured to cause, in response to conclusion of receipt of the set of user input including the instruction set to reposition the first transducer graphical element **502-2G** according to the instructions associated with block **708-2**, the input-output device system (e.g., input-output device system **120** or **320**) to reposition the representation of the intra-cardiac information among the plurality of transducer graphical elements **502** in accordance with the repositioning of the first transducer graphical element **502-2G** from the first location **801** in the graphical representation **500** to the predetermined location **804** in the graphical representation **500**.

(241) Although the method **700** may appear to terminate with block **709** in FIG. **7**, additional blocks, such as, but not limited to, one or more or all of blocks **608**, **608-1** (including sub-blocks **608a-608e**), **610**, **610-1** (including sub-blocks **610-1a** to **610-1c**), **610-2** (including sub-blocks **610-2a** to **610-2d**), **612**, **612-2** (including sub-blocks **612-2a** and **612-2b**), and **614** in FIGS. **6A**, **6D**, **6E**, and **6F** may follow block **709**. For instance, upon repositioning first transducer graphical element **502-2G** to the predetermined location **804**, the user may proceed with defining a graphical path, activating transducers, or both, as earlier described, according to some embodiments. Also for example, in addition or in the alternative, the defining a graphical path, activating transducers, or both may occur before the repositioning or be interrupted by the repositioning, according to various embodiments.

(242) In this regard in some embodiments, the input-output device system (e.g., input-output device system **120** or **320**) is communicatively connected to the transducer-based device (e.g., transducer-based device **300**), and the program implementing method **600** or method **700** includes selection instructions (e.g., which may be the instructions associated with block **608** in some embodiments) configured to cause reception of a set of user input (e.g., a second set of user input which may be distinguished from the ('first') set of user input associated with block **708-2**) via the input-output device system. This second set of user input may include a second instruction set (e.g., which may be distinguished from the ('first') instruction set associated with block **708-2**) to select, in a state (e.g., upon conclusion of execution of the instructions associated with block **709**) in which the input-output device system has repositioned the first transducer graphical element from the first location in the graphical representation to the predetermined location in the graphical representation, a set of transducer graphical elements (e.g., such as those transducer graphical

elements **502** selected in FIG. 5Q) of the plurality of transducer graphical elements **502**. In some embodiments, the set of transducer graphical elements may include the first transducer graphical element (e.g., **502-2G**), the second transducer graphical element (e.g., **502-14D**), or both the first transducer graphical element (e.g., **502-2G**) and the second transducer graphical element (e.g., **502-14D**). In some embodiments, the program implementing method **600** or method **700** also includes activation instructions (e.g., which may be the instructions associated with block **614** in some embodiments) configured to cause activation, via the input-output device system, of a set of transducers (e.g., such as those transducers **306** corresponding to the selected transducer graphical elements **502** in FIG. 5Q) of the plurality of transducers **306** of the transducer-based device **300** in response to reception of the second set of user input including the second instruction set to select the set of transducer graphical elements, the set of transducers to be activated corresponding to the selected set of transducer graphical elements. In some embodiments, the activation of the set of transducers may include activating the set of transducers to transmit energy sufficient for tissue ablation.

(243) While some of the embodiments disclosed above are described with examples of cardiac mapping, the same or similar embodiments may be used for mapping other bodily organs, for example, gastric mapping, bladder mapping, arterial mapping and mapping of any lumen or cavity into which the devices of the present invention may be introduced.

(244) While some of the embodiments disclosed above are described with examples of cardiac ablation, the same or similar embodiments may be used for ablating other bodily organs or any lumen or cavity into which the devices of the present invention may be introduced.

(245) Subsets or combinations of various embodiments described above can provide further embodiments.

(246) These and other changes can be made to the invention in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the invention to the specific embodiments disclosed in the specification and the claims, but should be construed to include other transducer-based device systems including all medical treatment device systems and all medical diagnostic device systems in accordance with the claims. Accordingly, the invention is not limited by the disclosure, but instead its scope is to be determined entirely by the following claims.

Claims

1. A medical system comprising: a data processing device system; an input-output device system communicatively connected to the data processing device system; and a memory device system communicatively connected to the data processing device system and storing a program executable by the data processing device system, the data processing device system configured by the program at least to: cause display, via the input-output device system, of a graphical representation of at least a spatial distribution of a plurality of transducers of at least a portion of a transducer-based device, the at least the portion of the transducer-based device positionable within a bodily cavity, the plurality of transducers configured to at least detect electrophysiological activity within the bodily cavity; receive first input via the input-output device system, the first input indicating a graphical path indicating a group of transducers from the spatial distribution of the plurality of transducers graphically represented in the graphical representation; and cause, via the input-output device system and in response to the first input, altering of a display of electrogram signals, the altering resulting in a display of a first arrangement of electrogram signals derived from the electrophysiological activity detected by the group of transducers.

2. The medical system of claim 1, wherein the graphical representation of the at least the spatial distribution of the plurality of transducers includes transducer graphical elements graphically representing at least some transducers from the plurality of transducers.

3. The medical system of claim 2, wherein the group of transducers is included in the at least some transducers from the plurality of transducers that are graphically represented by the transducer graphical elements, and wherein the graphical path is graphically indicated at least in part as passing through the transducer graphical elements graphically representing the group of transducers.
4. The medical system of claim 3, wherein the group of transducers is included in the at least some transducers from the plurality of transducers that are graphically represented by the transducer graphical elements, and wherein the graphical path is graphically indicated at least in part as passing between the transducer graphical elements graphically representing the group of transducers.
5. The medical system of claim 2, wherein the group of transducers is included in the at least some transducers from the plurality of transducers that are graphically represented by the transducer graphical elements, and wherein the graphical path is graphically indicated at least in part as passing between the transducer graphical elements graphically representing the group of transducers.
6. The medical system of claim 1, wherein the graphical path represents an ablation path.
7. The medical system of claim 1, wherein the display of the first arrangement of electrogram signals is a graphical stacking of electrogram signals associated with the group of transducers.
8. The medical system of claim 1, wherein the graphical representation includes a graphical depiction of one or more ports in fluid communication with the bodily cavity.
9. The medical system of claim 8, wherein the graphical representation includes transducer graphical elements graphically representing the group of transducers and graphically surrounding a graphical depiction of a particular port of the one or more ports in fluid communication with the bodily cavity.
10. The medical system of claim 1, wherein altering of the display of electrogram signals includes repositioning displayed electrogram signals resulting in the displayed first arrangement of electrogram signals.
11. The medical system of claim 1, wherein altering of the display of electrogram signals includes adding an electrogram signal to the display of electrogram signals resulting in the displayed first arrangement of electrogram signals.
12. The medical system of claim 1, wherein (i) at least a first electrogram signal in the first arrangement of electrogram signals is a unipolar electrogram signal, (ii) at least a second electrogram signal in the first arrangement of electrogram signals is a bipolar electrogram signal, or (i) and (ii).
13. The medical system of claim 1, wherein each transducer of the plurality of transducers is configured to be selectively activatable to provide ablative energy.
14. A method executed by a data processing device system according to a program stored by a communicatively connected memory device system, the data processing device system also communicatively connected to an input-output device system, and the method comprising: causing display, via the input-output device system, of a graphical representation of at least a spatial distribution of a plurality of transducers of at least a portion of a transducer-based device, the at least the portion of the transducer-based device positionable within a bodily cavity, the plurality of transducers configured to at least detect electrophysiological activity within the bodily cavity; receiving first input via the input-output device system, the first input indicating a graphical path indicating a group of transducers from the spatial distribution of the plurality of transducers graphically represented in the graphical representation; and causing, via the input-output device system and in response to the first input, altering of a display of electrogram signals, the altering resulting in a display of a first arrangement of electrogram signals derived from the electrophysiological activity detected by the group of transducers.
15. One or more non-transitory computer-readable storage mediums storing a program executable

by a data processing device system communicatively connected to an input-output device system, the program comprising: display instructions configured to cause display, via the input-output device system, of a graphical representation of at least a spatial distribution of a plurality of transducers of at least a portion of a transducer-based device, the at least the portion of the transducer-based device positionable within a bodily cavity, the plurality of transducers configured to at least detect electrophysiological activity within the bodily cavity; reception instructions configured to cause reception of first input via the input-output device system, the first input indicating a graphical path indicating a group of transducers from the spatial distribution of the plurality of transducers graphically represented in the graphical representation; and altering instructions configured to cause, via the input-output device system and in response to the first input, altering of a display of electrogram signals, the altering resulting in a display of a first arrangement of electrogram signals derived from the electrophysiological activity detected by the group of transducers.
