



(19) **United States**

(12) **Patent Application Publication**

Lee et al.

(10) **Pub. No.: US 2025/0267058 A1**

(43) **Pub. Date: Aug. 21, 2025**

(54) **SYSTEM AND METHOD TO FACILITATE OPEN MOBILE NETWORKS**

(71) Applicant: **AT&T Intellectual Property I, L.P.**,
Atlanta, GA (US)

(72) Inventors: **Bo Lee**, Alpharetta, GA (US); **Zhi Cui**,
Sugar Hill, GA (US)

(73) Assignee: **AT&T Intellectual Property I, L.P.**,
Atlanta, GA (US)

(21) Appl. No.: **19/203,613**

(22) Filed: **May 9, 2025**

Related U.S. Application Data

(63) Continuation of application No. 18/660,568, filed on May 10, 2024, now Pat. No. 12,323,295, which is a continuation of application No. 17/543,971, filed on Dec. 7, 2021, now Pat. No. 12,009,973.


Publication Classification

(51) **Int. Cl.**
H04L 41/0806 (2022.01)
G06F 11/07 (2006.01)
H04L 41/0873 (2022.01)
H04W 4/50 (2018.01)

(52) **U.S. Cl.**
CPC *H04L 41/0809* (2013.01); *G06F 11/0742* (2013.01); *H04L 41/0873* (2013.01); *H04W 4/50* (2018.02); *G06F 11/0793* (2013.01)

(57) **ABSTRACT**

Aspects of the subject disclosure may include, for example, a device having a processing system including a processor; and a memory that stores executable instructions that, when executed by the processing system, facilitate performance of operations including facilitating activation of a first module for a wireless system; integrating the first module into the wireless system; checking for errors during the integration of the first module in the wireless system; responsive to a determination that the integrating of the first module is error free, placing the wireless system in an operational state; and receiving an operational error code from an originating module. Other embodiments are disclosed.








FIG. 1




200

FIG. 2A




201

FIG. 2B




220

FIG. 2C




230

FIG. 2D



240

FIG. 2E






FIG. 4





FIG. 5



600
FIG. 6

SYSTEM AND METHOD TO FACILITATE OPEN MOBILE NETWORKS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of and claims priority to U.S. patent application Ser. No. 18/660,568 filed on May 10, 2024, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/543,971 filed on Dec. 7, 2021 (now U.S. Pat. No. 12,009,973). All sections of the aforementioned application(s) and/or patent(s) are incorporated herein by reference in their entirety.

FIELD OF THE DISCLOSURE

[0002] The subject disclosure relates to a system and method to facilitate open mobile networks.

BACKGROUND

[0003] Disaggregated and open radio access networks (RAN) have unlocked a slew of innovations from operators and smaller vendors. Diverse RAN solutions have been produced through optimization driven by software and data-driven intelligence. Eventually, such disaggregated and open RAN ecosystems will allow plug-n-play solutions using products from various vendors.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] Reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

[0005] FIG. 1 is a block diagram illustrating an exemplary, non-limiting embodiment of a communications network in accordance with various aspects described herein.

[0006] FIG. 2A is a high-level block diagram illustrating an example, non-limiting embodiment of functional modules defined within a wireless system functioning within the communication network of FIG. 1 in accordance with various aspects described herein.

[0007] FIG. 2B is a high-level block diagram illustrating an example, non-limiting embodiment of functional modules defined within a radio access network.

[0008] FIG. 2C is a mid-level block diagram illustrating an example, non-limiting embodiment of a decomposition of functional modules defined within a base station.

[0009] FIG. 2D is a low-level block diagram illustrating an example, non-limiting embodiment of a decomposition of level two functional modules defined within a RAN distributed unit module.

[0010] FIG. 2E depicts an illustrative embodiment of a method of integrating modules into a wireless system in accordance with various aspects described herein.

[0011] FIG. 3 is a block diagram illustrating an example, non-limiting embodiment of a virtualized communication network in accordance with various aspects described herein.

[0012] FIG. 4 is a block diagram of an example, non-limiting embodiment of a computing environment in accordance with various aspects described herein.

[0013] FIG. 5 is a block diagram of an example, non-limiting embodiment of a mobile network platform in accordance with various aspects described herein.

[0014] FIG. 6 is a block diagram of an example, non-limiting embodiment of a communication device in accordance with various aspects described herein.

DETAILED DESCRIPTION

[0015] The subject disclosure describes, among other things, illustrative embodiments for activating and integrating open modules into a wireless system. Other embodiments are described in the subject disclosure.

[0016] One or more aspects of the subject disclosure include a device having a processing system including a processor; and a memory that stores executable instructions that, when executed by the processing system, facilitate performance of operations including facilitating activation of a first module for a wireless system; integrating the first module into the wireless system; checking for errors during the integration of the first module in the wireless system; responsive to a determination that the integrating of the first module is error free, placing the wireless system in an operational state; and receiving an operational error code from an originating module.

[0017] One or more aspects of the subject disclosure include a machine-readable medium with executable instructions that, when executed by a processing system including a processor, performs operations including: facilitating a selection of a first module for a wireless system; integrating the first module into the wireless system; checking for errors during the integrating of the first module in the wireless system; responsive to a determination that the integration of the first module is error free, placing the wireless system in an operational state; and receiving an operational error code from an originating module.

[0018] One or more aspects of the subject disclosure include a method of enabling, by a processing system including a processor, selection of a first module for a wireless system; integrating, by the processing system, the first module into the wireless system; identifying, by the processing system, errors during the integrating of the first module in the wireless system; responsive to a determination that the integrating of the first module is error free, placing, by the processing system, the wireless system in an operational state; and receiving, by the processing system, an operational error code from an originating module.

[0019] Referring now to FIG. 1, a block diagram is shown illustrating an example, non-limiting embodiment of a system 100 in accordance with various aspects described herein. For example, system 100 can facilitate in whole or in part selecting modules for a wireless system; integrating modules into the wireless system; identifying errors during the integrating of modules; putting the wireless system in an operational state; and receiving error codes from modules. In particular, a communications network 125 is presented for providing broadband access 110 to a plurality of data terminals 114 via access terminal 112, wireless access 120 to a plurality of mobile devices 124 and vehicle 126 via base station or access point 122, voice access 130 to a plurality of telephony devices 134, via switching device 132 and/or media access 140 to a plurality of audio/video display devices 144 via media terminal 142. In addition, communication network 125 is coupled to one or more content sources 175 of audio, video, graphics, text and/or other media. While broadband access 110, wireless access 120, voice access 130 and media access 140 are shown separately, one or more of these forms of access can be combined

to provide multiple access services to a single client device (e.g., mobile devices **124** can receive media content via media terminal **142**, data terminal **114** can be provided voice access via switching device **132**, and so on).

[0020] The communications network **125** includes a plurality of network elements (NE) **150**, **152**, **154**, **156**, etc. for facilitating the broadband access **110**, wireless access **120**, voice access **130**, media access **140** and/or the distribution of content from content sources **175**. The communications network **125** can include a circuit switched or packet switched network, a voice over Internet protocol (VoIP) network, Internet protocol (IP) network, a cable network, a passive or active optical network, a 4G, 5G, or higher generation wireless access network, WIMAX network, UltraWideband network, personal area network or other wireless access network, a broadcast satellite network and/or other communications network.

[0021] In various embodiments, the access terminal **112** can include a digital subscriber line access multiplexer (DSLAM), cable modem termination system (CMTS), optical line terminal (OLT) and/or other access terminal. The data terminals **114** can include personal computers, laptop computers, netbook computers, tablets or other computing devices along with digital subscriber line (DSL) modems, data over coax service interface specification (DOCSIS) modems or other cable modems, a wireless modem such as a 4G, 5G, or higher generation modem, an optical modem and/or other access devices.

[0022] In various embodiments, the base station or access point **122** can include a 4G, 5G, or higher generation base station, an access point that operates via an 802.11 standard such as 802.11n, 802.11ac or other wireless access terminal. The mobile devices **124** can include mobile phones, e-readers, tablets, phablets, wireless modems, and/or other mobile computing devices.

[0023] In various embodiments, the switching device **132** can include a private branch exchange or central office switch, a media services gateway, VoIP gateway or other gateway device and/or other switching device. The telephony devices **134** can include traditional telephones (with or without a terminal adapter), VoIP telephones and/or other telephony devices.

[0024] In various embodiments, the media terminal **142** can include a cable head-end or other TV head-end, a satellite receiver, gateway or other media terminal **142**. The display devices **144** can include televisions with or without a set top box, personal computers and/or other display devices.

[0025] In various embodiments, the content sources **175** include broadcast television and radio sources, video on demand platforms and streaming video and audio services platforms, one or more content data networks, data servers, web servers and other content servers, and/or other sources of media.

[0026] In various embodiments, the communications network **125** can include wired, optical and/or wireless links and the network elements **150**, **152**, **154**, **156**, etc. can include service switching points, signal transfer points, service control points, network gateways, media distribution hubs, servers, firewalls, routers, edge devices, switches and other network nodes for routing and controlling communications traffic over wired, optical and wireless links as part of the Internet and other public networks as well as one or

more private networks, for managing subscriber access, for billing and network management and for supporting other network functions.

[0027] The wireless industry is trending towards disaggregation network via open interfaces and modules. As an example, Operator Defined Open and Intelligent Radio Access Networks (O-RAN) is working on radio access network (RAN) function decomposition and open interfaces between open RAN functional modules. This work will allow operators to introduce piecemeal functionality, algorithms, and technologies from third party vendors without fully replacing current incumbent vendors. Intelligent software-based functions and modules will be available from newer, nimbler, and more innovative vendors introduced to fulfill network specific functions.

[0028] FIG. 2A is a high-level block diagram illustrating an example, non-limiting embodiment of functions defined within a wireless system **200**. As illustrated in FIG. 2A, wireless network system **200** comprises a variety of functions, including a RAN **201**, user plane function (UPF) **202**, Access & Mobility Management function (AMF) **203**, Session Management function (SMF) **204**, Policy Control function (PCF) **205**, Application function (AF) **206**, Network Slice Selection function (NSSF) **207**, Authentication Server function (AUSF) **208** and a Unified Data Management (UDM) function **209**. Also illustrated is user equipment **210** and a data network **211**. The functions are presented in the Third Generation Partnership (3GPP) Technical Specification 3GPP TS 23.501, System Architecture for the 5G System; Stage 2, which is incorporated by reference herein. Similar to OPEN RAN, each of the functions could be decomposed to a list of modules.

[0029] To enable plug-n-play integration of module components in a wireless network, suppliers and system operators must decompose each of these high-level modules and develop and integrate independent modules using universal error codes. Such decomposition can be extended to the virtualized end-to-end mobile network, including transport and core illustrated in FIG. 2A. Ideally, system operators can choose the platforms, virtual functions, and transport from different suppliers. An integrated system solution can then utilize various components in a plug-n-play fashion.

[0030] FIG. 2B is a high-level block diagram illustrating an example, non-limiting embodiment of functional modules defined within RAN **201**. As shown in FIG. 2B, the RAN architecture comprises base station modules O-DU and O-CU, which is a software architecture comprising defined application programming interfaces (APIs). A Service Management and Orchestration Framework **212** contains a non-real time RAN intelligent controller function. The functional modules in the radio include a near-real time RAN intelligent controller **213** that enables near-real-time control and optimization of the other modules, an O-RAN central unit (O-CU) control plane (CP) module **214** that hosts the radio resource control (RRC) and the control plane part of the packet data convergence protocol (PDCP) protocol, an O-CU user plane (UP) module **215** that hosts the user plane part of the PDCP protocol and the service data adaptation protocol (SDAP), an O-RAN distributed unit (O-DU) **216** that provides radio link control (RLC) protocol, medium access control (MAC) protocol, and the higher physical interface (PHY) layers based on a lower layer functional split, and an O-RAN radio unit (O-RU) module **217** that provides the lower layer physical interface.

[0031] FIG. 2C is a mid-level block diagram illustrating an example, non-limiting embodiment of a decomposition of functional modules defined within a base station (gNB) 220. As shown in FIG. 2C, the O-CU module 221 (such as O-CU-CP module 214 and O-CU-UP module 215 illustrated in FIG. 2B) is divided into a service data adaptation protocol (SDAP) module 222, a radio resource control (RRC) module 223, and a packet data convergence protocol (PDCP) protocol module 224. The O-DU module 216 (illustrated in FIG. 2B) is divided into a radio link control (RLC) protocol module 225, a medium access control (MAC) protocol module 226, and a higher physical interface (PHY) module 227. The O-RU module 217 (illustrated in FIG. 2B) comprises a lower PHY module 228.

[0032] FIG. 2D is a low-level block diagram illustrating an example, non-limiting embodiment of a decomposition of level two functional modules defined within a RAN distributed unit (O-DU) module. As shown in FIG. 2D, level two functional blocks 230 of an O-DU module 216 (i.e., RLC protocol module 225 and M A C protocol module 226 illustrated in FIG. 2C) are decomposed into an O-DU operations and management (OAM) agent 231, an F1AP handler 232, an F1 user (F1-U) interface 233, a new radio (NR) scheduler 234, a NR RLC 235 and a NR MAC 236. OAM agent 231 interacts with OAM on the O1 interface for configuration, alarms and performance management. F1AP handler 232 provides interface functionality for the F1A P interface. F1-U interface 233 provides interface functionality for the F1-U interface. NR scheduler 234 schedules resources in uplink (UL) and downlink (DL) for the cell and UE. NR RLC 235 provides services for transferring the control and data messages between MAC layer and O-CU. NR MAC 236 is responsible for multiplexing and de-multiplexing of the data on various logical channels.

[0033] The F1AP handler 232, F1-U interface 233, NR RLC 235 and NR MAC 236 are further decomposed into many other functional sub modules illustrated in FIG. 2D. Ideally, operators can configure any level of decomposition granularity for all the core modules illustrated in FIG. 2A. The level of granularity of the module definitions should be flexible and configurable per operator's needs.

[0034] When the system is configured in an open system mode, modules can be activated/deactivated as needed. For instance, there might be a need to specify a rigid set of modules that cannot be integrated with other potential replacements, and thus would not be considered as "open." On the other hand, there may be other functions where an operator or integrator can choose modules to build a rich set of features.

[0035] When in the open system mode, the activated modules will be enabled to provide detailed operational error codes. The operational error codes should be aligned with industry specified open system integration and operations. The developers and operators can use a universal hierarchical error code system to ease the mobile system integration and operations.

[0036] FIG. 2E depicts an illustrative embodiment of a method of integrating modules into a wireless system in accordance with various aspects described herein. As shown in FIG. 2E, method 240 begins at step 241, where the system facilitates selection of modules by the operator. Next, in step 242, the system facilitates activation of the modules. The activated modules are configured as open modules. The process continues in step 243, where the system integrates

activated modules into the wireless system and readies the wireless system for operation. In step 244, the system detects whether there are any errors during the integration process. If errors are present, then they are reported, and the process proceeds to step 245. Such error reporting may comprise detailed error codes. In an embodiment, the error codes reflect the hierarchy of the module decomposition. For example, the detailed error codes may comprise the following hierarchy format: aaaa-bbbb-cccc-dddd-eeee-ffff, where:

[0037] i. aaaa: an identifier for a highest-level module or first module, e.g., O-CU or O-DU

[0038] ii. bbbb: an identifier for a sub-module, e.g., O-CU-CP or O-CU-UP

[0039] iii. cccc: an identifier for a third-level module, e.g., SDAP

[0040] iv. dddd: an interface of an originating module, e.g., an interface of SDAP

[0041] v. eeee: an interface of a receiving module, e.g., an interface of PDCP

[0042] vi. ffff: an error code identifying the problem

[0043] In step 245, problems with the integration are corrected. In an embodiment, the operator may choose to deactivate any new modules that prove difficult to integrate into a functioning wireless system. Once all the errors are corrected, in step 246 the system is placed into an operational state. During operation, in step 247 the system is checked for errors. If any operational errors occur, they are reported using detailed error codes such as those identified above. Then in step 248, corrective actions are taken to fix the errors and the fixed module is taken back to integration as step 243.

[0044] While for purposes of simplicity of explanation, the respective processes are shown and described as a series of blocks in FIG. 2E, it is to be understood and appreciated that the claimed subject matter is not limited by the order of the blocks, as some blocks may occur in different orders and/or concurrently with other blocks from what is depicted and described herein. Moreover, not all illustrated blocks may be required to implement the methods described herein.

[0045] Referring now to FIG. 3, a block diagram 300 is shown illustrating an example, non-limiting embodiment of a virtualized communication network in accordance with various aspects described herein. A virtualized communication network is presented that can be used to implement some or all the subsystems and functions of system 100, the subsystems and functions of system 200 and method 240 presented in FIGS. 1, 2A, 2B, 2C, 2D, 2E and 3. For example, virtualized communication network 300 can facilitate in whole or in part selecting modules for a wireless system; integrating modules into the wireless system; identifying errors during the integrating of modules; putting the wireless system in an operational state; and receiving error codes from modules.

[0046] A cloud networking architecture is shown that leverages cloud technologies and supports rapid innovation and scalability via a transport layer 350, a virtualized network function cloud 325 and/or one or more cloud computing environments 375. In various embodiments, this cloud networking architecture is an open architecture that leverages application programming interfaces (APIs); reduces complexity from services and operations; supports more nimble business models; and rapidly and seamlessly scales to meet evolving customer requirements including

traffic growth, diversity of traffic types, and diversity of performance and reliability expectations.

[0047] In contrast to traditional network elements—which are typically integrated to perform a single function, the virtualized communication network employs virtual network elements (VNEs) 330, 332, 334, etc. that perform some or all the functions of network elements 150, 152, 154, 156, etc. For example, the network architecture can provide a substrate of networking capability, often called Network Function Virtualization Infrastructure (NFVI) or simply infrastructure that is capable of being directed with software and Software Defined Networking (SD N) protocols to perform a broad variety of network functions and services. This infrastructure can include several types of substrates. The most typical type of substrate being servers that support Network Function Virtualization (NFV), followed by packet forwarding capabilities based on generic computing resources, with specialized network technologies brought to bear when general-purpose processors or general-purpose integrated circuit devices offered by merchants (referred to herein as merchant silicon) are not appropriate. In this case, communication services can be implemented as cloud-centric workloads.

[0048] As an example, a traditional network element 150 (shown in FIG. 1), such as an edge router can be implemented via a VNE 330 composed of NFV software modules, merchant silicon, and associated controllers. The software can be written so that increasing workload consumes incremental resources from a common resource pool, and moreover so that it is elastic: so, the resources are only consumed when needed. In a similar fashion, other network elements such as other routers, switches, edge caches, and middle boxes are instantiated from the common resource pool. Such sharing of infrastructure across a broad set of uses makes planning and growing infrastructure easier to manage.

[0049] In an embodiment, the transport layer 350 includes fiber, cable, wired and/or wireless transport elements, network elements and interfaces to provide broadband access 110, wireless access 120, voice access 130, media access 140 and/or access to content sources 175 for distribution of content to any or all the access technologies. In some cases, a network element needs to be positioned at a specific place, and this allows for less sharing of common infrastructure. Other times, the network elements have specific physical layer adapters that cannot be abstracted or virtualized and might require special DSP code and analog front ends (AFEs) that do not lend themselves to implementation as VNEs 330, 332 or 334. These network elements can be included in transport layer 350.

[0050] The virtualized network function cloud 325 interfaces with the transport layer 350 to provide the VNEs 330, 332, 334, etc. to provide specific NFVs. In particular, the virtualized network function cloud 325 leverages cloud operations, applications, and architectures to support networking workloads. The virtualized network elements 330, 332 and 334 can employ network function software that provides either a one-for-one mapping of traditional network element function or alternately some combination of network functions designed for cloud computing. For example, VNEs 330, 332 and 334 can include route reflectors, domain name system (DNS) servers, and dynamic host configuration protocol (DHCP) servers, system architecture evolution (SAE) and/or mobility management entity (MME) gateways, broadband network gateways, IP edge routers for IP-VPN,

Ethernet and other services, load balancers, distributors, and other network elements. Because these elements do not typically need to forward large amounts of traffic, their workload can be distributed across several servers—each of which adds a portion of the capability, which creates an overall elastic function with higher availability than its former monolithic version. These virtual network elements 330, 332, 334, etc. can be instantiated and managed using an orchestration approach like those used in cloud compute services.

[0051] The cloud computing environments 375 can interface with the virtualized network function cloud 325 via APIs that expose functional capabilities of the VNEs 330, 332, 334, etc. to provide the flexible and expanded capabilities to the virtualized network function cloud 325. Network workloads may have applications distributed across the virtualized network function cloud 325 and cloud computing environment 375 and in the commercial cloud or might simply orchestrate workloads supported entirely in NFV infrastructure from these third-party locations.

[0052] Turning now to FIG. 4, there is illustrated a block diagram of a computing environment in accordance with various aspects described herein. To provide additional context for various embodiments of the embodiments described herein, FIG. 4 and the following discussion are intended to provide a brief, general description of a suitable computing environment 400 in which the various embodiments of the subject disclosure can be implemented. Computing environment 400 can be used in the implementation of network elements 150, 152, 154, 156, access terminal 112, base station or access point 122, switching device 132, media terminal 142, and/or VNEs 330, 332, 334, etc. Each of these devices can be implemented via computer-executable instructions that can run on one or more computers, and/or in combination with other program modules and/or as a combination of hardware and software. For example, computing environment 400 can facilitate in whole or in part selecting modules for a wireless system; integrating modules into the wireless system; identifying errors during the integrating of modules; putting the wireless system in an operational state; and receiving error codes from modules.

[0053] Program modules comprise routines, programs, components, data structures, etc., that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the methods can be practiced with other computer system configurations, comprising single-processor or multiprocessor computer systems, minicomputers, mainframe computers, as well as personal computers, hand-held computing devices, micro-processor-based or programmable consumer electronics, and the like, each of which can be operatively coupled to one or more associated devices.

[0054] As used herein, a processing circuit includes one or more processors as well as other application specific circuits such as an application specific integrated circuit, digital logic circuit, state machine, programmable gate array or other circuit that processes input signals or data and that produces output signals or data in response thereto. It should be noted that while any functions and features described herein in association with the operation of a processor could likewise be performed by a processing circuit.

[0055] The illustrated embodiments of the embodiments herein can be also practiced in distributed computing environments where certain tasks are performed by remote

processing devices that are linked through a communications network. In a distributed computing environment, program modules can be in both local and remote memory storage devices.

[0056] Computing devices typically comprise a variety of media, which can comprise computer-readable storage media and/or communications media, which two terms are used herein differently from one another as follows. Computer-readable storage media can be any available storage media that can be accessed by the computer and comprises both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable storage media can be implemented in connection with any method or technology for storage of information such as computer-readable instructions, program modules, structured data, or unstructured data.

[0057] Computer-readable storage media can comprise, but are not limited to, random access memory (RAM), read only memory (ROM), electrically erasable programmable read only memory (EEPROM), flash memory or other memory technology, compact disk read only memory (CD-ROM), digital versatile disk (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices or other tangible and/or non-transitory media which can be used to store desired information. In this regard, the terms “tangible” or “non-transitory” herein as applied to storage, memory, or computer-readable media, are to be understood to exclude only propagating transitory signals per se as modifiers and do not relinquish rights to all standard storage, memory or computer-readable media that are not only propagating transitory signals per se.

[0058] Computer-readable storage media can be accessed by one or more local or remote computing devices, e.g., via access requests, queries, or other data retrieval protocols, for a variety of operations with respect to the information stored by the medium.

[0059] Communications media typically embody computer-readable instructions, data structures, program modules or other structured or unstructured data in a data signal such as a modulated data signal, e.g., a carrier wave or other transport mechanism, and comprises any information delivery or transport media. The term “modulated data signal” or signals refers to a signal that has one or more of its characteristics set or changed in such a manner as to encode information in one or more signals. By way of example, and not limitation, communication media comprise wired media, such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media.

[0060] With reference again to FIG. 4, the example environment can comprise a computer 402, the computer 402 comprising a processing unit 404, a system memory 406 and a system bus 408. The system bus 408 couples system components including, but not limited to, the system memory 406 to the processing unit 404. The processing unit 404 can be any of various commercially available processors. Dual microprocessors and other multiprocessor architectures can also be employed as the processing unit 404.

[0061] The system bus 408 can be any of several types of bus structure that can further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. The system memory 406 comprises ROM

410 and RAM 412. A basic input/output system (BIOS) can be stored in a non-volatile memory such as ROM, erasable programmable read only memory (EPROM), EEPROM, which BIOS contains the basic routines that help to transfer information between elements within the computer 402, such as during startup. The RAM 412 can also comprise a high-speed RAM such as static RAM for caching data.

[0062] The computer 402 further comprises an internal hard disk drive (HDD) 414 (e.g., EIDE, SATA), which internal HDD 414 can also be configured for external use in a suitable chassis (not shown), a magnetic floppy disk drive (FDD) 416, (e.g., to read from or write to a removable diskette 418) and an optical disk drive 420, (e.g., reading a CD-ROM disk 422 or, to read from or write to other high capacity optical media such as the DVD). The HDD 414, magnetic FDD 416 and optical disk drive 420 can be connected to the system bus 408 by a hard disk drive interface 424, a magnetic disk drive interface 426 and an optical drive interface 428, respectively. The hard disk drive interface 424 for external drive implementations comprises at least one or both of Universal Serial Bus (USB) and Institute of Electrical and Electronics Engineers (IEEE) 1394 interface technologies. Other external drive connection technologies are within contemplation of the embodiments described herein.

[0063] The drives and their associated computer-readable storage media provide nonvolatile storage of data, data structures, computer-executable instructions, and so forth. For the computer 402, the drives and storage media accommodate the storage of any data in a suitable digital format. Although the description of computer-readable storage media above refers to a hard disk drive (HDD), a removable magnetic diskette, and a removable optical media such as a CD or DVD, it should be appreciated by those skilled in the art that other types of storage media which are readable by a computer, such as zip drives, magnetic cassettes, flash memory cards, cartridges, and the like, can also be used in the example operating environment, and further, that any such storage media can contain computer-executable instructions for performing the methods described herein.

[0064] Several program modules can be stored in the drives and RAM 412, comprising an operating system 430, one or more application programs 432, other program modules 434 and program data 436. All or portions of the operating system, applications, modules, and/or data can also be cached in the RAM 412. The systems and methods described herein can be implemented utilizing various commercially available operating systems or combinations of operating systems.

[0065] A user can enter commands and information into the computer 402 through one or more wired/wireless input devices, e.g., a keyboard 438 and a pointing device, such as a mouse 440. Other input devices (not shown) can comprise a microphone, an infrared (IR) remote control, a joystick, a game pad, a stylus pen, touch screen or the like. These and other input devices are often connected to the processing unit 404 through an input device interface 442 that can be coupled to the system bus 408, but can be connected by other interfaces, such as a parallel port, an IEEE 1394 serial port, a game port, a universal serial bus (USB) port, an IR interface, etc.

[0066] A monitor 444 or other type of display device can be also connected to the system bus 408 via an interface, such as a video adapter 446. It will also be appreciated that

in alternative embodiments, a monitor **444** can also be any display device (e.g., another computer having a display, a smart phone, a tablet computer, etc.) for receiving display information associated with computer **402** via any communication means, including via the Internet and cloud-based networks. In addition to the monitor **444**, a computer typically comprises other peripheral output devices (not shown), such as speakers, printers, etc.

[0067] The computer **402** can operate in a networked environment using logical connections via wired and/or wireless communications to one or more remote computers, such as a remote computer(s) **448**. The remote computer(s) **448** can be a workstation, a server computer, a router, a personal computer, portable computer, microprocessor-based entertainment appliance, a peer device or other common network node, and typically comprises many or all the elements described relative to the computer **402**, although, for purposes of brevity, only a remote memory/storage device **450** is illustrated. The logical connections depicted comprise wired/wireless connectivity to a local area network (LAN) **452** and/or larger networks, e.g., a wide area network (WAN) **454**. Such LAN and WAN networking environments are commonplace in offices and companies, and facilitate enterprise-wide computer networks, such as intranets, all of which can connect to a global communications network, e.g., the Internet.

[0068] When used in a LAN networking environment, the computer **402** can be connected to the LAN **452** through a wired and/or wireless communication network interface or adapter **456**. The adapter **456** can facilitate wired or wireless communication to the LAN **452**, which can also comprise a wireless A/P disposed thereon for communicating with the adapter **456**.

[0069] When used in a WAN networking environment, the computer **402** can comprise a modem **458** or can be connected to a communications server on the WAN **454** or has other means for establishing communications over the WAN **454**, such as by way of the Internet. The modem **458**, which can be internal or external and a wired or wireless device, can be connected to the system bus **408** via the input device interface **442**. In a networked environment, program modules depicted relative to the computer **402** or portions thereof, can be stored in the remote memory/storage device **450**. It will be appreciated that the network connections shown are example and other means of establishing a communications link between the computers can be used.

[0070] The computer **402** can be operable to communicate with any wireless devices or entities operatively disposed in wireless communication, e.g., a printer, scanner, desktop and/or portable computer, portable data assistant, communications satellite, any piece of equipment or location associated with a wirelessly detectable tag (e.g., a kiosk, news stand, restroom), and telephone. This can comprise Wireless Fidelity (Wi-Fi) and BLUETOOTH® wireless technologies. Thus, the communication can be a predefined structure as with a conventional network or simply an ad hoc communication between at least two devices.

[0071] Wi-Fi can allow connection to the Internet from a couch at home, a bed in a hotel room or a conference room at work, without wires. Wi-Fi is a wireless technology like that used in a cell phone that enables such devices, e.g., computers, to send and receive data indoors and out; anywhere within the range of a base station. Wi-Fi networks use radio technologies called IEEE 802.11 (a, b, g, n, ac, ag, etc.)

to provide secure, reliable, fast wireless connectivity. A Wi-Fi network can be used to connect computers to each other, to the Internet, and to wired networks (which can use IEEE 802.3 or Ethernet). Wi-Fi networks operate in the unlicensed 2.4 and 5 GHz radio bands for example or with products that contain both bands (dual band), so the networks can provide real-world performance like the basic 10BaseT wired Ethernet networks used in many offices.

[0072] Turning now to FIG. 5, an embodiment **500** of a mobile network platform **510** is shown that is an example of network elements **150**, **152**, **154**, **156**, and/or VNEs **330**, **332**, **334**, etc. For example, platform **510** can facilitate in whole or in part selecting modules for a wireless system; integrating modules into the wireless system; identifying errors during the integrating of modules; putting the wireless system in an operational state; and receiving error codes from modules. In one or more embodiments, the mobile network platform **510** can generate and receive signals transmitted and received by base stations or access points such as base station or access point **122**. Mobile network platform **510** can comprise components, e.g., nodes, gateways, interfaces, servers, or disparate platforms, which facilitate both packet-switched (PS) (e.g., internet protocol (IP), frame relay, asynchronous transfer mode (ATM)) and circuit-switched (CS) traffic (e.g., voice and data), as well as control generation for networked wireless telecommunication. As a non-limiting example, mobile network platform **510** can be included in telecommunications carrier networks and can be considered carrier-side components as discussed elsewhere herein. Mobile network platform **510** comprises CS gateway node(s) **512** which can interface CS traffic received from legacy networks like telephony network(s) **540** (e.g., public switched telephone network (PSTN), or public land mobile network (PLMN)) or a signaling system #7 (SS7) network **560**. CS gateway node(s) **512** can authorize and authenticate traffic (e.g., voice) arising from such networks. Additionally, CS gateway node(s) **512** can access mobility, or roaming, data generated through SS7 network **560**; for instance, mobility data stored in a visited location register (VLR), which can reside in memory **530**. Moreover, CS gateway node(s) **512** interfaces CS-based traffic and signaling and PS gateway node(s) **518**. As an example, in a 3GPP UMTS network, CS gateway node(s) **512** can be realized at least in part in gateway GPRS support node(s) (GGSN). It should be appreciated that functionality and specific operation of CS gateway node(s) **512**, PS gateway node(s) **518**, and serving node(s) **516**, is provided and dictated by radio technology(ies) utilized by mobile network platform **510** for telecommunication over a radio access network **520** with other devices, such as a radiotelephone **575**.

[0073] In addition to receiving and processing CS-switched traffic and signaling, PS gateway node(s) **518** can authorize and authenticate PS-based data sessions with served mobile devices. Data sessions can comprise traffic, or content(s), exchanged with networks external to the mobile network platform **510**, like wide area network(s) (WANs) **550**, enterprise network(s) **570**, and service network(s) **580**, which can be embodied in local area network(s) (LANs), can also be interfaced with mobile network platform **510** through PS gateway node(s) **518**. It is to be noted that WANs **550** and enterprise network(s) **570** can embody, at least in part, a service network(s) like IP multimedia subsystem (IMS). Based on radio technology layer(s) available in technol-

ogy resource(s) or radio access network 520, PS gateway node(s) 518 can generate packet data protocol contexts when a data session is established; other data structures that facilitate routing of packetized data also can be generated. To that end, in an aspect, PS gateway node(s) 518 can comprise a tunnel interface (e.g., tunnel termination gateway (TTG) in 3GPP UMTS network(s) (not shown)) which can facilitate packetized communication with disparate wireless network(s), such as Wi-Fi networks.

[0074] In embodiment 500, mobile network platform 510 also comprises serving node(s) 516 that, based upon available radio technology layer(s) within technology resource(s) in the radio access network 520, convey the various packetized flows of data streams received through PS gateway node(s) 518. It is to be noted that for technology resource(s) that rely primarily on CS communication, server node(s) can deliver traffic without reliance on PS gateway node(s) 518; for example, server node(s) can embody at least in part a mobile switching center. As an example, in a 3GPP UMTS network, serving node(s) 516 can be embodied in serving GPRS support node(s) (SGSN).

[0075] For radio technologies that exploit packetized communication, server(s) 514 in mobile network platform 510 can execute numerous applications that can generate multiple disparate packetized data streams or flows, and manage (e.g., schedule, queue, format . . .) such flows. Such application(s) can comprise add-on features to standard services (for example, provisioning, billing, customer support . . .) provided by mobile network platform 510. Data streams (e.g., content(s) that are part of a voice call or data session) can be conveyed to PS gateway node(s) 518 for authorization/authentication and initiation of a data session, and to serving node(s) 516 for communication thereafter. In addition to application server, server(s) 514 can comprise utility server(s), a utility server can comprise a provisioning server, an operations and maintenance server, a security server that can implement at least in part a certificate authority and firewalls as well as other security mechanisms, and the like. In an aspect, security server(s) secure communication served through mobile network platform 510 to ensure network's operation and data integrity in addition to authorization and authentication procedures that CS gateway node(s) 512 and PS gateway node(s) 518 can enact. Moreover, provisioning server(s) can provision services from external network(s) like networks operated by a disparate service provider; for instance, WAN 550 or Global Positioning System (GPS) network(s) (not shown). Provisioning server(s) can also provision coverage through networks associated to mobile network platform 510 (e.g., deployed and operated by the same service provider), such as the distributed antennas networks shown in FIG. 1(s) that enhance wireless service coverage by providing more network coverage.

[0076] It is to be noted that server(s) 514 can comprise one or more processors configured to confer at least in part the functionality of mobile network platform 510. To that end, the one or more processors can execute code instructions stored in memory 530, for example. It should be appreciated that server(s) 514 can comprise a content manager, which operates in the same manner as described hereinbefore.

[0077] In example embodiment 500, memory 530 can store information related to operation of mobile network platform 510. Other operational information can comprise provisioning information of mobile devices served through

mobile network platform 510, subscriber databases; application intelligence, pricing schemes, e.g., promotional rates, flat-rate programs, couponing campaigns; technical specification(s) consistent with telecommunication protocols for operation of disparate radio, or wireless, technology layers; and so forth. Memory 530 can also store information from at least one of telephony network(s) 540, WAN 550, SS7 network 560, or enterprise network(s) 570. In an aspect, memory 530 can be, for example, accessed as part of a data store component or as a remotely connected memory store.

[0078] To provide a context for the various aspects of the disclosed subject matter, FIG. 5, and the following discussion, are intended to provide a brief, general description of a suitable environment in which the various aspects of the disclosed subject matter can be implemented. While the subject matter has been described above in the general context of computer-executable instructions of a computer program that runs on a computer and/or computers, those skilled in the art will recognize that the disclosed subject matter also can be implemented in combination with other program modules. Program modules comprise routines, programs, components, data structures, etc. that perform particular tasks and/or implement particular abstract data types.

[0079] Turning now to FIG. 6, an illustrative embodiment of a communication device 600 is shown. The communication device 600 can serve as an illustrative embodiment of devices such as data terminals 114, mobile devices 124, vehicle 126, display devices 144 or other client devices for communication via either communications network 125. For example, computing device 600 can facilitate in whole or in part selecting modules for a wireless system; integrating modules into the wireless system; identifying errors during the integrating of modules; putting the wireless system in an operational state; and receiving error codes from modules.

[0080] The communication device 600 can comprise a wireline and/or wireless transceiver 602 (herein transceiver 602), a user interface (UI) 604, a power supply 614, a location receiver 616, a motion sensor 618, an orientation sensor 620, and a controller 606 for managing operations thereof. The transceiver 602 can support short-range or long-range wireless access technologies such as Bluetooth®, ZigBee®, Wi-Fi, DECT, or cellular communication technologies, just to mention a few (Bluetooth® and ZigBee® are trademarks registered by the Bluetooth® Special Interest Group and the ZigBee® Alliance, respectively). Cellular technologies can include, for example, CDMA-1X, UMTS/HSDPA, GSM/GPRS, TDMA/EDGE, EV/DO, WiMAX, SDR, LTE, as well as other next generation wireless communication technologies as they arise. The transceiver 602 can also be adapted to support circuit-switched wireline access technologies (such as PSTN), packet-switched wireline access technologies (such as TCP/IP, VoIP, etc.), and combinations thereof.

[0081] The UI 604 can include a depressible or touch-sensitive keypad 608 with a navigation mechanism such as a roller ball, a joystick, a mouse, or a navigation disk for manipulating operations of the communication device 600. The keypad 608 can be an integral part of a housing assembly of the communication device 600 or an independent device operably coupled thereto by a tethered wireline interface (such as a USB cable) or a wireless interface supporting for example Bluetooth®. The keypad 608 can represent a numeric keypad commonly used by phones, and/or a QWERTY keypad with alphanumeric keys. The UI

604 can further include a display **610** such as monochrome or color LCD (Liquid Crystal Display), OLED (Organic Light Emitting Diode) or other suitable display technology for conveying images to an end user of the communication device **600**. In an embodiment where the display **610** is touch-sensitive, a portion or all the keypad **608** can be presented by way of the display **610** with navigation features.

[0082] The display **610** can use touch screen technology to also serve as a user interface for detecting user input. As a touch screen display, the communication device **600** can be adapted to present a user interface having graphical user interface (GUI) elements that can be selected by a user with a touch of a finger. The display **610** can be equipped with capacitive, resistive or other forms of sensing technology to detect how much surface area of a user's finger has been placed on a portion of the touch screen display. This sensing information can be used to control the manipulation of the GUI elements or other functions of the user interface. The display **610** can be an integral part of the housing assembly of the communication device **600** or an independent device communicatively coupled thereto by a tethered wireline interface (such as a cable) or a wireless interface.

[0083] The UI **604** can also include an audio system **612** that utilizes audio technology for conveying low volume audio (such as audio heard in proximity of a human ear) and high-volume audio (such as speakerphone for hands free operation). The audio system **612** can further include a microphone for receiving audible signals of an end user. The audio system **612** can also be used for voice recognition applications. The UI **604** can further include an image sensor **613** such as a charged coupled device (CCD) camera for capturing still or moving images.

[0084] The power supply **614** can utilize common power management technologies such as replaceable and rechargeable batteries, supply regulation technologies, and/or charging system technologies for supplying energy to the components of the communication device **600** to facilitate long-range or short-range portable communications. Alternatively, or in combination, the charging system can utilize external power sources such as DC power supplied over a physical interface such as a USB port or other suitable tethering technologies.

[0085] The location receiver **616** can utilize location technology such as a global positioning system (GPS) receiver capable of assisted GPS for identifying a location of the communication device **600** based on signals generated by a constellation of GPS satellites, which can be used for facilitating location services such as navigation. The motion sensor **618** can utilize motion sensing technology such as an accelerometer, a gyroscope, or other suitable motion sensing technology to detect motion of the communication device **600** in three-dimensional space. The orientation sensor **620** can utilize orientation sensing technology such as a magnetometer to detect the orientation of the communication device **600** (north, south, west, and east, as well as combined orientations in degrees, minutes, or other suitable orientation metrics).

[0086] The communication device **600** can use the transceiver **602** to also determine a proximity to a cellular, Wi-Fi, Bluetooth®, or other wireless access points by sensing techniques such as utilizing a received signal strength indicator (RSSI) and/or signal time of arrival (TOA) or time of flight (TOF) measurements. The controller **606** can utilize

computing technologies such as a microprocessor, a digital signal processor (DSP), programmable gate arrays, application specific integrated circuits, and/or a video processor with associated storage memory such as Flash, ROM, RAM, SRAM, DRAM or other storage technologies for executing computer instructions, controlling, and processing data supplied by the aforementioned components of the communication device **600**.

[0087] Other components not shown in FIG. 6 can be used in one or more embodiments of the subject disclosure. For instance, the communication device **600** can include a slot for adding or removing an identity module such as a Subscriber Identity Module (SIM) card or Universal Integrated Circuit Card (UICC). SIM or UICC cards can be used for identifying subscriber services, executing programs, storing subscriber data, and so on.

[0088] The terms “first,” “second,” “third,” and so forth, as used in the claims, unless otherwise clear by context, is for clarity only and does not otherwise indicate or imply any order in time. For instance, “a first determination,” “a second determination,” and “a third determination,” does not indicate or imply that the first determination is to be made before the second determination, or vice versa, etc.

[0089] In the subject specification, terms such as “store,” “storage,” “data store,” data storage,” “database,” and any other information storage component relevant to operation and functionality of a component, refer to “memory components,” or entities embodied in a “memory” or components comprising the memory. It will be appreciated that the memory components described herein can be either volatile memory or nonvolatile memory, or can comprise both volatile and nonvolatile memory, by way of illustration, and not limitation, volatile memory, non-volatile memory, disk storage, and memory storage. Further, nonvolatile memory can be included in read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable ROM (EEPROM), or flash memory. Volatile memory can comprise random access memory (RAM), which acts as external cache memory. By way of illustration and not limitation, RAM is available in many forms such as synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), and direct Rambus RAM (DRRAM). Additionally, the disclosed memory components of systems or methods herein are intended to comprise, without being limited to comprising, these and any other suitable types of memory.

[0090] Moreover, it will be noted that the disclosed subject matter can be practiced with other computer system configurations, comprising single-processor or multiprocessor computer systems, mini-computing devices, mainframe computers, as well as personal computers, hand-held computing devices (e.g., PDA, phone, smartphone, watch, tablet computers, netbook computers, etc.), microprocessor-based or programmable consumer or industrial electronics, and the like. The illustrated aspects can also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network; however, some if not all aspects of the subject disclosure can be practiced on stand-alone computers. In a distributed computing environment, program modules can be in both local and remote memory storage devices.

[0091] In one or more embodiments, information regarding use of services can be generated including services being accessed, media consumption history, user preferences, and so forth. This information can be obtained by various methods including user input, detecting types of communications (e.g., video content vs. audio content), analysis of content streams, sampling, and so forth. The generating, obtaining and/or monitoring of this information can be responsive to an authorization provided by the user. In one or more embodiments, an analysis of data can be subject to authorization from user(s) associated with the data, such as an opt-in, an opt-out, acknowledgement requirements, notifications, selective authorization based on types of data, and so forth.

[0092] Some of the embodiments described herein can also employ artificial intelligence (AI) to facilitate automating one or more features described herein. The embodiments (e.g., in connection with automatically identifying acquired cell sites that provide a maximum value/benefit after addition to an existing communication network) can employ various AI-based schemes for conducting various embodiments thereof. Moreover, the classifier can be employed to determine a ranking or priority of each cell site of the acquired network. A classifier is a function that maps an input attribute vector, $x=(x_1, x_2, x_3, x_4 \dots x_n)$, to a confidence that the input belongs to a class, that is, $f(x)=\text{confidence}(\text{class})$. Such classification can employ a probabilistic and/or statistical-based analysis (e.g., factoring into the analysis utilities and costs) to determine or infer an action that a user desires to be automatically performed. A support vector machine (SVM) is an example of a classifier that can be employed. The SVM operates by finding a hypersurface in the space of possible inputs, which the hypersurface attempts to split the triggering criteria from the non-triggering events. Intuitively, this makes the classification correct for testing data that is near, but not identical to training data. Other directed and undirected model classification approaches comprise, e.g., naïve Bayes, Bayesian networks, decision trees, neural networks, fuzzy logic models, and probabilistic classification models providing different patterns of independence can be employed. Classification as used herein also is inclusive of statistical regression that is utilized to develop models of priority.

[0093] As will be readily appreciated, one or more of the embodiments can employ classifiers that are explicitly trained (e.g., via a generic training data) as well as implicitly trained (e.g., via observing UE behavior, operator preferences, historical information, receiving extrinsic information). For example, SVMs can be configured via a learning or training phase within a classifier constructor and feature selection module. Thus, the classifier(s) can be used to automatically learn and perform several functions, including but not limited to determining according to predetermined criteria which of the acquired cell sites will benefit a maximum number of subscribers and/or which of the acquired cell sites will add minimum value to the existing communication network coverage, etc.

[0094] As used in some contexts in this application, in some embodiments, the terms “component,” “system” and the like are intended to refer to, or comprise, a computer-related entity or an entity related to an operational apparatus with one or more specific functionalities, wherein the entity can be either hardware, a combination of hardware and software, software, or software in execution. As an example,

a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, computer-executable instructions, a program, and/or a computer. By way of illustration and not limitation, both an application running on a server and the server can be a component. One or more components may reside within a process and/or thread of execution and a component may be localized on one computer and/or distributed between two or more computers. In addition, these components can execute from various computer readable media having various data structures stored thereon. The components may communicate via local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry, which is operated by a software or firmware application executed by a processor, wherein the processor can be internal or external to the apparatus and executes at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, the electronic components can comprise a processor therein to execute software or firmware that confers at least in part the functionality of the electronic components. While various components have been illustrated as separate components, it will be appreciated that multiple components can be implemented as a single component, or a single component can be implemented as multiple components, without departing from example embodiments.

[0095] Further, the various embodiments can be implemented as a method, apparatus or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware or any combination thereof to control a computer to implement the disclosed subject matter. The term “article of manufacture” as used herein is intended to encompass a computer program accessible from any computer-readable device or computer-readable storage/communications media. For example, computer readable storage media can include, but are not limited to, magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips), optical disks (e.g., compact disk (CD), digital versatile disk (DVD)), smart cards, and flash memory devices (e.g., card, stick, key drive). Of course, those skilled in the art will recognize many modifications can be made to this configuration without departing from the scope or spirit of the various embodiments.

[0096] In addition, the words “example” and “exemplary” are used herein to mean serving as an instance or illustration. Any embodiment or design described herein as “example” or “exemplary” is not necessarily to be construed as preferred or advantageous over other embodiments or designs. Rather, use of the word example or exemplary is intended to present concepts in a concrete fashion. As used in this application, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise or clear from context, “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then “X employs A or B” is satisfied under any of

the foregoing instances. In addition, the articles “a” and “an” as used in this application and the appended claims should generally be construed to mean “one or more” unless specified otherwise or clear from context to be directed to a singular form.

[0097] Moreover, terms such as “user equipment,” “mobile station,” “mobile,” “subscriber station,” “access terminal,” “terminal,” “handset,” “mobile device” (and/or terms representing similar terminology) can refer to a wireless device utilized by a subscriber or user of a wireless communication service to receive or convey data, control, voice, video, sound, gaming or substantially any data-stream or signaling-stream. The foregoing terms are utilized interchangeably herein and with reference to the related drawings.

[0098] Furthermore, the terms “user,” “subscriber,” “customer,” “consumer” and the like are employed interchangeably throughout, unless context warrants particular distinctions among the terms. It should be appreciated that such terms can refer to human entities or automated components supported through artificial intelligence (e.g., a capacity to make inference based, at least, on complex mathematical formalisms), which can provide simulated vision, sound recognition and so forth.

[0099] As employed herein, the term “processor” can refer to any computing processing unit or device comprising, but not limited to comprising, single-core processors; single-processors with software multithread execution capability; multi-core processors; multi-core processors with software multithread execution capability; multi-core processors with hardware multithread technology; parallel platforms; and parallel platforms with distributed shared memory. Additionally, a processor can refer to an integrated circuit, an application specific integrated circuit (ASIC), a digital signal processor (DSP), a field programmable gate array (FPGA), a programmable logic controller (PLC), a complex programmable logic device (CPLD), a discrete gate or transistor logic, discrete hardware components or any combination thereof designed to perform the functions described herein. Processors can exploit nano-scale architectures such as, but not limited to, molecular and quantum-dot based transistors, switches and gates, in order to optimize space usage or enhance performance of user equipment. A processor can also be implemented as a combination of computing processing units.

[0100] As used herein, terms such as “data storage,” “data storage,” “database,” and any other information storage component relevant to operation and functionality of a Component, refer to “memory components,” or entities embodied in a “memory” or components comprising the memory. It will be appreciated that the memory components or computer-readable storage media, described herein can be either volatile memory or nonvolatile memory or can include both volatile and nonvolatile memory.

[0101] What has been described above includes mere examples of various embodiments. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing these examples, but one of ordinary skill in the art can recognize that many further combinations and permutations of the present embodiments are possible. Accordingly, the embodiments disclosed and/or claimed herein are intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims.

Furthermore, to the extent that the term “includes” is used in either the detailed description or the claims, such term is intended to be inclusive in a manner like the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

[0102] In addition, a flow diagram may include a “start” and/or “continue” indication. The “start” and “continue” indications reflect that the steps presented can optionally be incorporated in or otherwise used in conjunction with other routines. In this context, “start” indicates the beginning of the first step presented and may be preceded by other activities not specifically shown. Further, the “continue” indication reflects that the steps presented may be performed multiple times and/or may be succeeded by other activities not specifically shown. Further, while a flow diagram indicates a particular ordering of steps, other orderings are likewise possible provided that the principles of causality are maintained.

[0103] As may also be used herein, the term(s) “operably coupled to,” “coupled to,” and/or “coupling” includes direct coupling between items and/or indirect coupling between items via one or more intervening items. Such items and intervening items include, but are not limited to, junctions, communication paths, components, circuit elements, circuits, functional blocks, and/or devices. As an example of indirect coupling, a signal conveyed from a first item to a second item may be modified by one or more intervening items by modifying the form, nature or format of information in a signal, while one or more elements of the information in the signal are nevertheless conveyed in a manner than can be recognized by the second item. In a further example of indirect coupling, an action in a first item can cause a reaction on the second item, because of actions and/or reactions in one or more intervening items.

[0104] Although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement which achieves the same or similar purpose may be substituted for the embodiments described or shown by the subject disclosure. The subject disclosure is intended to cover all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, can be used in the subject disclosure. For instance, one or more features from one or more embodiments can be combined with one or more features of one or more other embodiments. In one or more embodiments, features that are positively recited can also be negatively recited and excluded from the embodiment with or without replacement by another structural and/or functional feature. The steps or functions described with respect to the embodiments of the subject disclosure can be performed in any order. The steps or functions described with respect to the embodiments of the subject disclosure can be performed alone or in combination with other steps or functions of the subject disclosure, as well as from other embodiments or from other steps that have not been described in the subject disclosure. Further, more than or less than all the features described with respect to an embodiment can also be utilized.

What is claimed is:

1. A device, comprising:

- a processing system including a processor; and
- a memory that stores executable instructions that, when executed by the processing system, facilitate performance of operations, the operations comprising:

after a placing of a wireless networking system in an operational state, receiving an operational error code from a Service Data Application Protocol (SDAP)-based originating module that is part of a first module in the wireless networking system, wherein the operational error code has a format indicating a hierarchy of a module decomposition of the first module in the wireless networking system by listing in sequential order, in the operational error code, an identifier of the first module, an identifier of the SDAP-based originating module of the first module, and an identifier of an interface of the SDAP-based originating module, and wherein the operational error code specifies an error number identifying a problem; and

initiating a corrective action based on the problem.

2. The device of claim 1, wherein the wireless networking system conforms to an Operator Defined Open and Intelligent Radio Access Networks (O-RAN) standard.

3. The device of claim 2, wherein the first module is connected to a O-RAN Distributed Unit (O-DU).

4. The device of claim 1, wherein the format of the operational error code specifies the first module, a sub-module for one of user plane or control plane of the first module, a first interface of the SDAP-based originating module, and a second interface of a receiving module that is part of the first module.

5. The device of claim 4, wherein the receiving module performs functions of a Packet Data Convergence Protocol (PDCP).

6. The device of claim 1, wherein the SDAP-based originating module performs functions of the SDAP.

7. The device of claim 1, wherein the first module is a software-based module that fulfills network specific functions.

8. The device of claim 1, wherein the processing system comprises a plurality of processors operating in a distributed computing environment.

9. A non-transitory, machine-readable medium, comprising executable instructions that, when executed by a processing system including a processor, perform operations comprising:

after a placing of a wireless networking system in an operational state, obtaining an operational error code from a Service Data Application Protocol (SDAP)-based originating module that is part of a first module in the wireless networking system, wherein the operational error code has a format indicating a hierarchy of a module decomposition of the first module in the wireless networking system by listing in sequential order, in the operational error code, an identifier of the first module, an identifier of the SDAP-based originating module of the first module, and an identifier of an interface of the SDAP-based originating module, and wherein the operational error code identifies a problem; and

initiating a corrective action based on the problem.

10. The non-transitory, machine-readable medium of claim 9, wherein the wireless networking system conforms to an Operator Defined Open and Intelligent Radio Access Networks (O-RAN) standard.

11. The non-transitory, machine-readable medium of claim 9, wherein the format of the operational error code specifies the first module, a sub-module for one of user plane or control plane of the first module, a first interface of the SDAP-based originating module, and a second interface of a receiving module that is part of the first module.

12. The non-transitory, machine-readable medium of claim 11, wherein the receiving module performs functions of a Packet Data Convergence Protocol (PDCP).

13. The non-transitory, machine-readable medium of claim 9, wherein the SDAP-based originating module performs functions of the SDAP.

14. The non-transitory, machine-readable medium of claim 9, wherein the first module is connected to a radio access network (RAN) Intelligent Controller (RIC).

15. The non-transitory, machine-readable medium of claim 14, wherein the first module is connected to a distributed unit associated with the RIC.

16. The non-transitory, machine-readable medium of claim 9, wherein the operational error code specifies an error number identifying the problem.

17. The non-transitory, machine-readable medium of claim 9, wherein the processing system comprises a plurality of processors operating in a distributed computing environment.

18. A method, comprising:

after a placing of a wireless networking system in an operational state, receiving, by the processing system, an operational error code from a Service Data Application Protocol (SDAP)-based originating module that is part of a first module in the wireless networking system, wherein the operational error code has a format indicating a hierarchy of a module decomposition of the first module in the wireless networking system by listing in sequential order, in the operational error code, an identifier of the first module, an identifier of the SDAP-based originating module of the first module, and an identifier of an interface of the SDAP-based originating module, and wherein the operational error code specifies an error number identifying a problem; and

initiating, by the processing system, a corrective action based on the problem.

19. The method of claim 18, wherein the SDAP-based originating module performs functions of the SDAP.

20. The method of claim 18, wherein the processing system comprises a plurality of processors operating in a distributed computing environment.

* * * * *