

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12390574
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Banko; William

Ocular surgical work tip adapter

Abstract

An adapter for a surgical hand piece with a single lumen work tip converts the handpiece to infusion/aspiration (I/A) cleanup of lens epithelial cells in the capsular bag of the eye a patient after phacoemulsification. The adapter is in the form of a sleeve whose proximal end is to be joined to the distal end of work tip. The sleeve also has at least one aspiration hole located toward the distal end of the sleeve.

Inventors:	Banko; William (Armonk, NY)
Applicant:	SURGICAL DESIGN CORPORATION (Armonk, NY)
Family ID:	1000008764620
Assignee:	SURGICAL DESIGN CORPORATION (Armonk, NY)
Appl. No.:	17/866621
Filed:	July 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220347371 A1	Nov. 03, 2022

Related U.S. Application Data

continuation parent-doc US 15687762 20170828 US 11419971 child-doc US 17866621

Publication Classification

Int. Cl.: A61M1/00 (20060101); A61F9/007 (20060101); A61M3/02 (20060101); A61M39/10 (20060101)

U.S. Cl.:

CPC **A61M1/774** (20210501); **A61M1/7411** (20210501); **A61M3/0283** (20130101); **A61M39/10** (20130101); A61F9/00745 (20130101); A61M1/77 (20210501); A61M2039/1038 (20130101); A61M2039/1077 (20130101); A61M2210/0612 (20130101)

Field of Classification Search

CPC: A61M (1/774); A61M (1/77); A61M (1/7411); A61M (1/741); A61M (3/0283); A61M (39/10); A61M (2039/1038); A61M (2039/1077); A61M (2210/0612); A61F (9/00745)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3088323	12/1962	Welkowitz	73/849	H04R 21/02
3618611	12/1970	Urban	30/240	A61B 17/32002
3710781	12/1972	Huthcins, IV	600/488	A61B 5/0215
3776238	12/1972	Peyman	606/171	A61F 9/00763
3805793	12/1973	Wright	606/29	A61B 17/32053
3815604	12/1973	O'Malley	606/171	A61B 18/12
3937222	12/1975	Banko	606/107	A61F 9/00763
4011869	12/1976	Seiler, Jr.	606/171	A61F 9/00763
4014333	12/1976	McIntyre	604/167.01	A61F 9/00736
4099529	12/1977	Peyman	606/171	A61F 9/00763
4111207	12/1977	Seiler, Jr.	606/171	A61F 9/00763
4210146	12/1979	Banko	606/171	A61F 9/00763
4368734	12/1982	Banko	606/107	A61F 9/00763
4386927	12/1982	Eichenbaum	604/541	A61F 9/00736
4504264	12/1984	Kelman	604/35	A61F 9/00745
4513745	12/1984	Amoils	606/171	A61F 9/00763
4548205	12/1984	Armeniades	600/561	A61F 9/00736
4643717	12/1986	Cook	604/48	A61F 9/00745

4678459	12/1986	Onik	604/22	A61B 17/32002
4722350	12/1987	Armeniades	600/398	A61B 5/02216
4819635	12/1988	Shapiro	600/565	A61F 9/00763
4850354	12/1988	McGurk- Burleson	30/240	A61B 17/32002
4919130	12/1989	Stoy	606/107	A61F 2/1664
5056902	12/1990	Chinnock	359/503	A61B 1/00066
5059204	12/1990	Lawson	606/171	A61F 9/00763
5217465	12/1992	Steppe	606/1	A61M 1/84
5242385	12/1992	Strukel	606/169	A61F 9/00745
5267996	12/1992	Fletcher	606/17	A61B 5/6848
5282786	12/1993	Ureche	604/22	A61M 3/0279
5285795	12/1993	Ryan	606/171	A61B 17/32002
5358473	12/1993	Mitchell	604/27	A61F 9/00736
5378234	12/1994	Hammerslag	604/95.04	A61M 25/0053
5464389	12/1994	Stahl	606/169	A61F 9/00745
5514086	12/1995	Parisi	604/35	A61B 17/22012
5667489	12/1996	Kraff	604/35	A61F 9/00745
5718677	12/1997	Capetan	604/35	A61M 1/84
5766194	12/1997	Smith	606/1	A61B 17/3203
5782849	12/1997	Miller	606/159	A61F 9/00763
6579270	12/2002	Sussman	604/27	A61F 9/00736
6902558	12/2004	Laks	604/521	A61F 9/00709
7238010	12/2006	Hershberger	417/477.2	F04B 43/1253
7276060	12/2006	Madden	606/27	A61F 9/00736
7329261	12/2007	Perkins	606/107	A61F 9/00745
7959597	12/2010	Baker	604/28	A61M 1/772
8282574	12/2011	Coonahan	600/568	A61B 10/0275

8282594	12/2011	Perkins	606/169	A61M 3/0279
8313501	12/2011	Miller	606/171	A61B 17/32
8403951	12/2012	Chon	606/171	A61F 9/00745
8545462	12/2012	Ghannoum	604/27	A61F 9/00736
8641658	12/2013	Banko	604/173	A61F 9/00745
8657840	12/2013	Palmer	606/170	A61B 17/32002
8721581	12/2013	Zolli	606/107	A61F 9/00825
9757536	12/2016	Abt	N/A	B29C 70/766
10166317	12/2018	Banko	N/A	N/A
10179068	12/2018	Banko	N/A	A61F 9/00745
10213533	12/2018	Walter	N/A	N/A
10244931	12/2018	Kern	N/A	A61M 5/14
2003/0114873	12/2002	Banko	606/169	A61F 9/00745
2005/0234473	12/2004	Zacharias	606/107	A61F 9/00745
2005/0256462	12/2004	Underwood	604/264	A61F 9/00736
2008/0167604	12/2007	Hong	604/27	A61F 9/00745
2010/0121260	12/2009	Ghannoum	604/35	A61F 9/00736
2012/0157934	12/2011	Liao	604/264	A61F 9/00745
2013/0231605	12/2012	Walter	604/27	A61F 9/00745
2014/0114335	12/2013	Banko	606/169	A61F 9/00745
2014/0276377	12/2013	Chang	604/35	A61F 9/00736
2015/0005753	12/2014	Walter	606/107	A61M 3/0283
2015/0025451	12/2014	Banko	604/35	A61M 1/774
2016/0106580	12/2015	Banko	604/22	A61F 9/00745
2019/0060534	12/2018	Banko	N/A	A61M 1/7411
2019/0117458	12/2018	Banko	N/A	A61F 9/00745

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
-------------------	-----------------------------	----------------	------------

OTHER PUBLICATIONS

Non Final Office Action in corresponding U.S. Appl. No. 15/687,762, dated Feb. 7, 2019. cited by applicant

Final Office Action in corresponding U.S. Appl. No. 15/687,762, dated Sep. 19, 2019. cited by applicant

Non Final Office Action in corresponding U.S. Appl. No. 15/687,762, dated Oct. 19, 2020. cited by applicant

Final Office Action in corresponding U.S. Appl. No. 15/687,762, dated Jul. 6, 2021. cited by applicant

Non Final Office Action in corresponding U.S. Appl. No. 15/687,762, dated Dec. 27, 2021. cited by applicant

Primary Examiner: Price; Nathan R

Assistant Examiner: Igel; Mark A

Attorney, Agent or Firm: Leason Ellis LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of prior U.S. patent application Ser. No. 15/687,762 filed on Aug. 28, 2017.

TECHNICAL FIELD

(1) The present invention is generally directed to hand pieces for ocular surgery, particularly for the removal of cataracts from the eye of a patient by phacoemulsification.

BACKGROUND OF THE INVENTION

(2) The use of instruments in ocular surgical applications is well known. One widely used type of instrument is an ultrasonic hand piece that is used in ophthalmic applications, such as in the removal of cataracts from the eye by phacoemulsification.

(3) FIG. 1 depicts one such type of prior art ultrasonic hand piece as shown in U.S. Pat. No. 4,504,264 of Kelman. This hand piece has a housing **10** of, for example, plastic or metal, within which is supported a transducer means **11** for generating mechanical vibrations upon excitation with an alternating-current electrical signal. The transducer **11** is shown as a magnetostrictive transducer with an electrical coil **12** wound about a stack of metal laminations so that longitudinal mechanical vibrations are produced. The transducer can also be of the piezoelectric type. There is a connecting body **16** of, for example, titanium, having a reduced diameter distal end portion, which also can be an attached separate portion. The connecting body forms an acoustic impedance transformer for conveying the longitudinal vibrations of the transducer **11** for application to an operative tool or working tip **14** connected to the distal end of the connecting body **16**.

(4) The work tip **14** is connected, such as by a screw thread, to the narrowed distal end of the connecting body **16** so as to be coupled to the transducer **11**. As a result, the work tip is longitudinally vibrated by the transducer. The working tip **14** is an elongated, hollow tip of a suitable metal, such as titanium, that is capable of supporting ultrasonic vibrations. It has a distal end of a desired shape to be placed against the tissue to be removed. The work tip **14** has a base portion **15** in threaded engagement with the distal end of the connecting body **16**. The tip **14** can be interchanged by use of the screw threads.

(5) The distal end of the tip **14** is shown surrounded by a sleeve **17**, which may be made of a material such as silicone, whose proximal end **18** is supported in threaded engagement on a reduced diameter end of the housing **10**. If desired, the proximal end of sleeve **17** can be engaged more proximally along the length of the housing **10**. The connecting body **16** has two elastomeric O-rings **19, 20** on its outer surface. These provide a fluid-tight seal between the connecting body **16** and the transducer means **11**. A plurality of screws **51** are shown disposed around the axis of the housing **10** for preventing longitudinal displacement (other than vibration) or rotational movement of the vibratory structure within the housing and also for radial centering of the vibratory structure within the housing. Other types of conventional mounting arrangements can be used.

(6) The hand piece also illustratively has electrical input terminals **40, 41** for applying a suitable electrical signal to the magnetostrictive transducer **11**. Cooling water is shown provided inside the housing **10** from an inlet **42** to an outlet **43** and within a chamber between O-ring **19** and a grommet **50** for circulation around the transducer. This is not always necessary and is not used in most present day hand pieces.

(7) The sleeve **17** around the tip **14** forms a first fluid passage **21** between the tip **14** and the sleeve for an infusion/irrigation fluid. An inlet **22** is provided on the housing or sleeve distally of the O-ring **20** for supplying the irrigation fluid to the passage **21** from a fluid supply, e.g., a bag of saline solution (not shown).

(8) A passage **23** is formed through the connecting body **16** that is in communication with a central passage **25** of the work tip **14**. An outlet **24** on the housing or sleeve receives a suction (aspiration) force that is applied to the passage **23** in the connecting body and the central passage **25** in the work tip. A chamber **31** is formed between the spaced O-rings **19, 20** on the body **16** and the housing **10**, with which the aspiration force from outlet **24** communicates. Thus the aspiration force is from the source (e.g., a suction pump not shown), into the chamber **31** between the O-rings, through the passage **23** in the connecting body and the passage **25** in the work tip **14**. Tissue that is emulsified by the work tip is aspirated from the operating site by the aspiration flow force. In particular, saline solution introduced into the eye through fluid passage **21** and tissue displaced by the vibration force of the tip **14**, is drawn into the distal end of passage **25** and passes out of the hand piece through outlet **24**. It should be noted that passage **25** is located concentrically within passage **21**.

(9) As indicated, other apparatus (not shown) for use with the hand piece include the suction pump for producing the aspiration fluid (suction), the treatment fluid supply (infusion/irrigation fluid, such as a saline liquid), an oscillator for applying an electrical signal to the vibratory structure and control apparatus therefore. All of these are of conventional construction.

(10) Considering now the operation of the hand piece of FIG. 1. When an electrical signal having a frequency of, for example, 40,000 cycles/second is applied to the coil **12** around the magnetostrictive transducer **11**, the transducer **11** vibrates longitudinally at 40,000 cycles per second, thereby vibrating the connecting bodies **13, 16** and the work tip **14**. Treatment fluid is supplied through inlet **22** and fluid passage **21** to bathe the tissue in the operating site region around the working tip **14**. Suction force is applied through inlet **24** and passage **23** to the working tip **14** passage **25** to withdraw the tissue fragmented by the work tip along with some of the treatment fluid.

(11) Instruments of the type described above are often used in cataract surgery in which the eye lens is removed from the eye capsule and an intra-ocular lens (IOL) is then implanted. In such a procedure before the IOL is implanted it has been found to be desirable to cleanup lens substance and lens epithelial cells (LEC's) in the capsular bag of the eye and to remove them. Doing this procedure provides a more stable and long-term fixation for certain types of IOL's in the capsular bag. One manner of accomplishing the cleanup is to use a combination of low force irrigation of the capsular bag interior with a liquid together with the application of low power ultrasonic energy. This dislodges the unwanted cells and substances without damage to the capsular bag. Further, this

material can be removed from the capsular bag by the aspiration fluid flow, which also may be reduced in pressure to avoid damage.

(12) In a cleanup procedure it is advantageous if the flow of the irrigation liquid can be made more directional than would be possible using the hand piece with the outer sleeve through which the liquid flows and exits from around the work tip that produces the ultrasonic energy. It is also better if the aspiration force is lower. As a result, typically a different tip from the one illustrated in FIG. 1, which breaks up the tissue, is used for the cleanup. In fact a completely different instrument called an irrigation or infusion/aspiration (I/A) instrument is often used for this purpose. Such an instrument **90** is illustrated in FIG. 2. It has a handle **91** at one end and a work tip **92** at the other end. An enlarged view of the work tip is shown in FIG. 3. The I/A instrument work tip has concentric infusion and aspiration lumens, and typically has no ultrasonic vibration capability. The infusion fluid enters the work tip at opening **93** and is in an outer concentric lumen so that its flow surrounds the distal part of lumen **95** of the work tip. The aspirated tissue enters a small hole **94** in the distal part and is withdrawn through lumen **95**. Thus, when the phacoemulsification has been completed and cleanup is to be started, the surgeon must remove the phacoemulsification tool from the eye. Then the surgeon removes the first or phacoemulsification work tip, replaces it with a different cleanup work tip and then inserts the new work tip or a separate I/A tool **90** is inserted in to the eye. This second insertion into the eye increases the possibilities of infection and trauma. Also, the I/A tool has a disadvantage in that the surgeon would have to keep inserting and withdrawing the ultrasonic work tip and the I/A tool from the eye as the process is completed, because the surgeon cannot be sure that all of the tissue has been broken up until the cleanup process has begun. As a result, this would also subject the patient to the increased possibilities of infection and trauma.

(13) As shown in the present inventor's own U.S. Pat. No. 8,641,658, the surgical instrument may be provided with dual lumens in tubes **132**, **134**, each of which can alternatively be used for aspiration of emulsified tissue and irrigation of the surgical site. FIG. 4 shows a work tip **130** that can be connected to an ultrasonic energy source **102** of a hand piece by means of a connecting body **204**. Two fluid passages **120** and **180** for aspiration or irrigation fluid pass through the connecting body **204**. For example the proximal end of passage **120** can be in communication with the irrigation fluid input of the supply line **124** and the proximal end of passage **180** can be in communication with the aspiration fluid of the supply line **164**. The distal ends of the two passages **120** and **180** terminate at the distal end of the connecting body **204**.

(14) There are threads **182** around the connecting body distal end. A hub **190** is around the proximal ends of the work tip tubes **132** and **134**, which are bent so that the proximal ends of their lumens are parallel to the distal ends of the connecting body passages **120** and **180**. A collar **194** with internal threads on its open end has its flange end rotatably mounted in a groove **192** in the hub **190**. There are mating index pieces, such as mating grooves and ribs or pins (not shown), on the opposing faces of the connecting body **204** distal end and the hub **190** so that the proximal end of the lumen of tube **132** will be aligned with the distal end of connecting body passage **120** and the proximal end of the lumen of tube **134** aligned with the distal end of passage **180**.

(15) When the tubes and connecting body are properly aligned the collar **194** is tightened on the connecting body threads **182** and the lumens at the proximal ends of tubes **132** and **134** will be brought into fluid communication with the distal ends of the connecting body passages **120** and **180**. O-rings **193** are provided in the connecting body at the distal ends of passages **120** and **180** to make the communications fluid tight.

(16) Both of the tubes **132** and **134** receive the ultrasonic energy from the source **102** (not shown). A valve (not shown) can be used with the hand piece of FIG. 4 to switch the fluid flow from the sources **124** and **164** to the lumens of tubes **132** and **134** of the integrated work tip. Since both tubes **132** and **134** receive ultrasonic energy the emulsification of tissue and its aspiration can take place through either one in addition to each tube being able to supply irrigation liquid through the

different types and shapes of openings at the distal ends of the tubes.

(17) The work tip can be used with only an irrigation/aspiration (I/A) function by turning off the source of ultrasonic energy and only supplying the aspiration and irrigation fluids. Thus, the same instrument can be used for the phacoemulsification function while performing irrigation and aspiration as an operation takes place and also only for I/A functions (no or minimal ultrasonic energy is used) useful for cleaning the capsular bag as described above. This eliminates the need for the surgeon changing instruments and also provides the surgeon with a work tip having two tubes with different shape openings available for both aspiration and irrigation.

(18) Only one of the tubes, e.g., **134**, can be used as an I/A work tip. In the oval shaped openings **165** along the tube length can be used alone in the eye capsular bag for the substance and cell cleanup procedure described above. The oval shaped openings **165** allow for both good dispersion of the irrigation fluid or a large area for aspiration of cells and substances dislodged by the irrigation liquid.

(19) While the work tip of U.S. Pat. No. 8,641,658 can use its dual lumen tubes for phacoemulsification and for I/A cleanup thereafter, it would be advantageous if these functions could be provided to a single axial work tip as shown in FIG. 1. In addition, it would be beneficial if phacoemulsification instruments with single lumens could have their operation varied without withdrawing the instrument from the eye and/or diverting the surgeon's attention from the operating site. This would reduce the chances of infection and trauma.

SUMMARY OF THE INVENTION

(20) In accordance with the invention a surgical hand piece is provided that can perform all of the functions of emulsification of tissue and other substances by ultrasonic energy and aspiration of such tissue and substances, as well as reduced pressure irrigation and aspiration of a site that is being worked on in order to clean up the site. The hand piece can be used for surgery on appropriate tissue throughout the body, e.g., neurological tissue and ocular tissue.

(21) The invention provides a surgical phacoemulsification hand piece that has a single axial work tip that is concentric to a surrounding irrigation tube. Thus it can be like the prior art work tip in FIG. 1 or an improved work tip as shown in the present inventor's U.S. Patent Application Publication No. US 2015/0025451 A1, which is incorporated herein by reference in its entirety. The improved design has a disposable work tip so that the entire handpiece need not be sterilized between operations.

(22) During a phacoemulsification procedure, an ultrasonic source in the hand piece causes the single work tip to vibrate and to remove cataract tissue. However, when this is complete, the ultrasonic vibration is ended and an adapter converts the work tip for I/A so that it is adapted to clean up of the capsular bag by changing the configuration of the aspiration opening.

(23) In one embodiment the work tip is removed from the eye and an adapter is placed over it so as to modify the opening. In a second embodiment the adapter is fixed to the work tip and its configuration is changed when I/A clean up is desired. With the second embodiment the adapter can be changed without removing the work tip from the eye. Also, the surgeon can select one of a variety of adapters such that the aspiration pattern during the cleanup can be selected to suit the circumstances. These different patterns can be achieved without the surgeon having to remove the I/A tool from the eye.

(24) The principles of the invention have numerous advantages. For example, the invention allows a phacoemulsification tool to be converted with an adapter to serve as an I/A clean up tool. Further, an embodiment of the invention allows for the elimination of the need for the surgeon to remove an ultrasonically-driven work tip from the operating site, such as the eye, and to insert a separate work tip or tips having I/A cleanup capability, in order to perform special procedures, such as cortical and lens epithelial cell cleanup. Further, if an I/A tool is used according to the present invention, clean up can be commenced without the surgeon having to divert his attention from the eye.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The foregoing and other objects and advantages of the present invention will become more apparent when considered in connection with the following detailed description and appended drawings in which like designations denote like elements in the various views, and wherein:
- (2) FIG. 1 is a view in partial cross-section of a prior art type of surgical hand piece;
- (3) FIG. 2. is a partial cross-sectional view of a prior art irrigation/aspiration instrument with a removable tip;
- (4) FIG. 3 is a partial cross-sectional enlarged view of the prior art tip for the infusion/aspiration instrument of FIG. 2;
- (5) FIG. 4 is cross-sectional view of a prior art dual lumen surgical hand piece;
- (6) FIG. 5A is a cross-sectional view of a first embodiment of a surgical hand piece with a single axial work tip and an adapter for I/A clean up of a capsular bag of the eye according to the present invention, and FIG. 5B is an enlarged view of the attachment of the adapter to the work tip;
- (7) FIG. 6 is an enlarged cross-sectional view of a second embodiment of a work tip and I/A clean up adapter according to the present invention;
- (8) FIGS. 7A and 7B are a cross-sectional view and an enlarged cross-sectional view, respectively, of a third embodiment of a work tip and I/A clean up adapter according to the present invention;
- (9) FIGS. 8A and 8B are a cross-sectional view and an enlarged cross-sectional view, respectively, of a fourth embodiment of a work tip and I/A clean up adapter according to the present invention;
- (10) FIGS. 9A and 9B are a cross-sectional view and an enlarged cross-sectional view, respectively, of a fifth embodiment of a work tip and I/A clean up adapter according to the present invention;
- (11) FIG. 10 is a cross-sectional view of a sixth embodiment of a work tip and I/A clean up adapter according to the present invention;
- (12) FIG. 11 is a perspective view of a hand piece with a mechanism for sliding a sleeve to change the function of an adapter according to the present invention without removing the work tip from the eye of the patient;
- (13) FIG. 12A is a front cross sectional view of an adapter in the form of a hinged sleeve according to the present invention mounted on a work tip in an open position, FIG. 12B is a front cross sectional view of the adapter of FIG. 12A with the hinge closed, FIG. 12C is a schematic side view of the adapter of FIG. 12A with the hinge open and FIG. 12D is a schematic side view of the adapter of FIG. 12B with the hinge closed;
- (14) FIG. 13A is a cross sectional elevation view of an adapter in the form of a flexible folding sleeve according to the present invention mounted on a work tip in an open position, FIG. 13B is a plan view of the adapter of FIG. 13A, FIG. 13C is a cross sectional elevation view of the adapter of FIG. 13A with the sleeve moved upward to partially close the end of the work piece, FIG. 13D is a plan view of FIG. 13C, FIG. 13E is a cross sectional elevation view of the adapter of FIG. 13A with the sleeve moved upward to nearly completely close the end of the work piece, and FIG. 13F is a plan view of FIG. 13E; and
- (15) FIG. 14A is a cross-sectional view of a dual lumen work tip with an adapter according the present invention installed at the distal end, and FIG. 14B shows a perspective view of the distal end of the work tip and the adapter prior to installation over the distal end.

DETAILED DESCRIPTION OF THE INVENTION

- (16) FIG. 5A shows an embodiment of a handpiece disclosed in the present inventor's US Patent Application Publication US 2015/0025451 A1, which is incorporated herein by reference in its entirety. This handpiece is shown receiving an adapter **230** according to the present invention. The handpiece uses a number of the components of the prior art type of handpiece described above with respect to FIG. 1. The source of the electro-mechanical energy is shown schematically as

transducer **11**. This transducer can be either the electromagnetic type or the piezoelectric crystal type. It is preferred, and is conventional, that the output power of the transducer **11** be controlled by electrical signals delivered over wires **40, 41** from a control unit (not shown). These signals allow the ultrasonic power at the work tip distal end **146** to be varied as needed by the surgeon.

(17) Connected to the transducer **11** is the connecting body **16**. Both the transducer **11** and connecting body **16** are provided in a housing **10**. Although not shown for the sake of clarity, the transducer and connecting body are suspended within housing **10** so as to permit the longitudinal vibration of the transducer and connecting body to occur relative to the housing. For example, the O-rings **19** and **20** shown in FIG. **1** are spaced apart around the connecting body **16** and engage the inner surface of the housing **10**.

(18) The work tip **14** has an opening **143** that leads to an axial channel **25** extending from the opening to an enlarged hub **140** at the proximal end of the work tip. Within the hub **140** there is a radial channel **142** that extends from the axial channel **25** to the outer surface of the hub. While the radial channel **142** is shown at a right angle to the axial channel, in fact it can be at any convenient angle that allows it to extend from the axial channel to the outer surface of the hub. A threaded connector **15** extends from the proximal end of the hub and engages the distal end of the connecting body **16**.

(19) A sleeve **17**, which may advantageously be made of silicone, is provided with a funnel shape so that its proximal end **18** is large enough to encompass the enlarged hub, and still leave space for chamber **117** between the outer surface of the hub and the inner surface of the sleeve. The distal end of the sleeve tapers down around the portion **144** of the work tip beyond the hub, which extends to a flared portion **146** of the work tip which is at the operating or distal end. As a result the axial channel has a larger diameter at the distal end that tapers down to a smaller diameter as it extends through the work tip into the hub **140**. The sleeve stops short of the portion **146**. The proximal end **18** of sleeve **17** makes a threaded connection with the body **10**. Although not shown, a sterile sheet may be fastened to the end **18** and draped over the housing to avoid contaminating the housing during procedures.

(20) Sleeve **17** has a first external connector **22** on its outer surface that is in fluid communication with the chamber **117**. A tube **210** carrying irrigation fluid may be connected to connector **22** in order to supply irrigation fluid to chamber **117**. Fluid in chamber **117** may flow between the outer surface of work tip portion **144** and the inner surface of sleeve **17** in a channel **21** so as to exit the handpiece just short of the flared portion **146** of the work tip, i.e., at the site of the operation of the handpiece on the patient's tissue. Sleeve **17** also has a second external connector **24** on its outer surface. In the drawing this connector is shown as being on the opposite side of the sleeve from the connector **22**. However, in practice this connector can be at any convenient location on the sleeve. A seal piece **148**, e.g., an O-ring or other form of seal, connects the radial channel **142** to the second connector **24**. A tube **220** provides a suction force (e.g., from a peristaltic aspiration pump) on connector **24**. This causes tissue to be drawn into the opening **143** at portion **146** of the work tip, to travel up the axial channel **25** and into the radial channel **142**, to pass through the O-ring **148** and the connector **24**, and finally to be drawn through tube **220** to the aspiration pump.

(21) In operation the handpiece of FIG. **5A** operates similar to other phacoemulsification handpieces. Electrical energy is applied through wires **40, 41**, which causes the ultrasonic transducer to vibrate axially at ultrasonic frequencies. The mechanical axial force is transmitted to the connecting body **16**, which in turn transmits it to the work tip **14**. When the end **146** of the work tip is placed in contact with tissue, e.g., a cataract, the vibration causes the tissue to break up. While this is occurring, irrigation fluid, e.g., saline solution, passes from a source, through tube **210** and connector **22** into chamber **117**, along channel **21** and is deposited at the operating site as shown by the arrows **230** in FIG. **5B**. At the same time the fragmented tissue is drawn into the opening **143** in portion **146** as shown by arrow **240** in FIG. **5A**. It passes up the axial channel **25** into the radial channel **142**, through the O-ring **148** and connector **24** to tube **220**.

(22) When the handpiece is used in its intended fashion and the procedure is over, the handpieces can be quickly readied for use on another patient without the need for sterilization. In particular, the tubes **210**, **220** are disconnected and discarded. Then the sleeve **17** with its sterile sheet at proximal end **18** is unthreaded from the housing **10** and the connecting body **16**. Next, the work tip **14** has its threaded connector **15** loosened from connecting body **16**. Then the working tip and sleeve **17** are discarded. The work tip and sleeve, as well as each of the sets of tubes are replaced with clean, pre-sterilized parts, and the handpiece is ready for the next use. This is possible because the only parts of the handpiece that come into contact with the aspiration fluid from the patient are the work tip, sleeve and the interior of tube **220**. Except for the work tip, the other disposable parts can be made of inexpensive materials, e.g., silicone. Thus, the cost of the replacement parts is not very great.

(23) The work tip of the present invention can be used with only an infusion/aspiration (1/A) function. That is, the source of ultrasonic energy can be turned off or reduced. The aspiration and infusion/irrigation fluids are supplied to the tubes **210** and **220**; but, the aspiration force can be lowered, e.g., from 500 mm Hg to 5-10 mm Hg during the cleaning operation so that the posterior capsule tissue at the back of the eye is not drawn into the tube. The irrigation fluid force can also be lowered. However, it is preferable to utilize smaller openings than that of the work tip at **146**. One way to accomplish this is to withdraw the work tip from the eye of the patient and to place an adapter **230** over the end of the work tip.

(24) The adapter **230** as best shown in FIG. 5B is a closed end tube with a small opening **234** or series of openings. During clean up, the remaining tissue (i.e., lens epithelial cells) is aspirated through this small hole while irrigation fluid continues to be applied to the site from channel **21**. The adapter can be made of metal or soft plastic. If it is made of metal, a soft plastic coating is preferred to avoid damage to the capsular bag of the eye.

(25) The cylindrical proximal end **231** of the adapter is slid into the flared part **146** of the work tip until protrusions **232** on its outer surface engage in recesses **145** within flared part **146**. This connection establishes locking engagement between the adapter **230** and work tip **14**. This engagement is aided by the suction force within the work tip. Distal end **233** of the adapter is made thicker than the end **231** and surrounds opening **234**. The end **231** is also made smooth so as to provide protection against harm to the capsular bag.

(26) FIG. 6 shows an arrangement similar to FIG. 5B, but instead of protrusions **232** and recesses **145**, the adapter **230** is fastened to the flared part **146** of the work tip by a protrusion **241** engaging a slot **242** in the flared part **146**.

(27) The adapter **230** of FIG. 7A is made larger than the flared part **146** so that the adapter extends over the flared part when installed on the work tip. The flared part has external threads **245** as shown in FIG. 7B which engage internal threads **247** on the adapter **230**. This forms the engagement between these parts.

(28) The adapter **230** of FIGS. 8A and 8B is made flexible and slightly larger than the flared part **146**. The ends **235** of the adapter bend inwardly. When the adapter is installed it is slid over the flared part, which causes at least the ends to expand outwardly. Once the adapter is nearly over the flared part, the ends **235** of the adapter snap into detents **149** in the exterior surface of the work tip to hold the adapter on the work tip. Note that the adapters shown in FIGS. 7 and 8 do not have the enlarged distal surface **233**. Depending on the size (diameter) of the adapter, the surface **233** may not be necessary to protect the capsular bag.

(29) The adapter of FIGS. 9A and 9B resemble that of FIG. 5B in that it is smaller in diameter than the flared part and slides within it. However, instead of protrusions and recesses, this design relies on a press fit between the parts and the aspiration force to hold the adapter on the work tip. Also in this design, the expanded distal part **233** of the adapter is designed to have a thickness that matches that of the flared part so that when joined the two parts have a smooth connection line.

(30) The embodiment of FIG. 10 is the opposite of that in FIG. 7. In particular, the adapter has threads **248** on a reduced diameter portion of its proximal end **231**, which end slides within the

flared part **146**. The threads **248** of the adapter engage threads **148** on the interior of the flared part. (31) In each of the designs of FIGS. **5-10**, the aspiration opening **234** has been shown as a simple hole. However, it should be understood that opening **234** may be a plurality of openings in different patterns, of different sizes and with different shapes. The surgeon will select the adapter to best meet the conditions that present during the surgery.

(32) With the designs of FIGS. **5-10**, it is necessary for the surgeon to remove the work tip from the eye of the patient in order to make use of any particular adapter. This of course takes time away from the procedure, exposes the surgical site to infection and/or trauma. Thus, it would be advantageous to be able to engage a clean-up adapter without having to remove the work tip from the eye. Such a design is shown in FIG. **11**.

(33) FIG. **11** shows a hand piece with a work tip **14** at the end. Either the irrigation sleeve **17** or an additional sleeve **320** located outside the irrigation sleeve can slide along the work tip. In the embodiment of FIG. **11**, the sliding of the sleeve **320** is achieved with a mechanism **300** attached to the exterior of the hand piece. Mechanism **300** includes a finger portion **302**. The finger portion is connected to a linear portion **304** that runs along the exterior surface of the hand piece and is slidable with respect to that surface. A slanted portion **306** extends from the linear portion down to the work tip and then connects to sleeve **320**. All of the portions of mechanism **300** are slidable with respect to the hand piece. The mechanism **300** is preferably located on the hand piece such that it does not interfere with the irrigation and aspiration tubes and is close to the body of the hand piece. Also, preferably, the pieces **302**, **304**, **306** and **320** are flexibly joined to each other so that during the sliding motion, they do not extend way from the body of the work piece. Depending on the shape of the hand piece, additional or fewer sections of the mechanism **300** may be used. Also, a sterile sheet **315** is shown attached to the hub of the work tip. A portion or portions of the mechanism would penetrate the sterile sheet, if used, to reach the finger portion **302** on the housing.

(34) When the surgeon completes the emulsification of the cataract and wants to start to clean up the remaining tissue, he or she turns off the ultrasonic energy or reduces it, reduces the force of the irrigation and aspiration fluid flows and uses his or her finger to slide the sleeve **320** forward. This can all be accomplished without removing the work tip from the surgical site within the patient's eye. In general the effect of sliding the adapter is to cause to openings in the work tip to be reconfigured for I/A clean up.

(35) During operations in the eye, sections **306** and **320** may become contaminated. As a result, they may be made detachable from the rest of the mechanism so that they can be discarded after a procedure, as opposed to being sterilized. At the same time the work tip **14** with the attached sterile sheet **315** would be disposed. The mechanism **300** is preferably made of plastic material to save on costs.

(36) FIG. **12A** shows a work tip with a flared part **146** in solid line. Sleeve **320** is shown in cross section surrounding it. It will be noted that the work tip has a small opening **150** near its distal end. Further, the sleeve **320** has a hole **332** at a distance from its distal end and two hinged semicircular portions **322** at its distal end. In the position shown in FIG. **12A** the sleeve **320** is in an extended position so that the flared end **146** of the work tip pushes the hinged portions of the sleeve aside. See the schematic view of FIG. **12C** which shows that the curved parts of the semicircular portions **322** are fastened to the sleeve by a spring **321**. In this position normal phacoemulsification can take place in which cataract tissue impacted by ultrasonic vibration is aspirated into opening **143** of flared portion **146**.

(37) When it is time for cleanup, the surgeon can use the finger portion **302** to slide or retract the sleeve. When this is done, the hinged semicircular portions **322** close off the work tip opening as shown in FIGS. **12B** and **12D**. The sleeve **320** has an opening **330** in it and as mentioned above the flared part has a lateral opening **150**. In the retracted position aspiration fluid is sucked into the lateral opening **150**. Because in this position the opening **330** and the hole **150** are generally

aligned as shown in FIG. 12B, opening 330 acts as the I/A opening during clean up. While the opening 330 is shown with a semicircular shape, it can be provided with any convenient and useful shape. It can also include a plurality of openings in different patterns and sizes. The surgeon will select the adapter to best meet the conditions that are present during the surgery.

(38) An alternative embodiment of a slidable sleeve 320 that can be configured for I/A clean up is shown in FIG. 13A in cross section located about a work tip with a flared part 146. The sleeve has a proximal part 354 and a distal part 352, with irrigation holes 332 located in the proximal part. At least the distal end of the part 352 is in the form of multiple (e.g., 8) segments 350 designed to naturally fold over the opening 143 of the work tip. Compare FIGS. 13B, 13D and 13F. In FIG. 13B the segments are fully retracted. In FIG. 13D the segments are shown as a twisting closure like the diaphragm of a camera. However, they could alternatively be segments of a hemisphere which are not quite together (not shown). FIG. 13F show a complete closure where the segments are segments of a hemisphere which are fully closed (folded) over the opening 143 in the work tip.

(39) FIG. 13A shows the sleeve 320 in its retracted position. In that position the flared end 146 is used in its normal phacoemulsification function. Irrigation fluid can flow and exit conventional sleeve 17, so long as adapter sleeve 320 does not block the flow. Where the sleeve 320 is used in place of the end of sleeve 17, the holes 232 in that sleeve provide irrigation fluid. When the finger portion 302 is pushed forward, the sleeve is caused to extend beyond the flared portion 146 as shown in FIG. 13C. As a result, the segments 350 begin to fold toward each other partially closing the opening 143 in flared part 146 as described above. See FIG. 13D.

(40) When sleeve 320 is fully extended, the segments 350 can completely close the opening 143 in flared part 146 or they may leave a small opening 352 that can be used for I/A clean up.

(41) FIG. 14A shows a dual lumen work tip of a type disclosed in the present inventor's U.S. Published Patent Application No. 2016/0106580 A1, which is incorporated herein by reference in its entirety. This work tip has two tubes 423 and 424 joined together at hub 425 and at various sections where the tubes come in contact with each other. The entire assembly can be connected with thread 465 to an ultrasonic hand piece. Depending on the preference of the surgeon, either one of the two tubes or both of the tubes can irrigate the surgical site or aspirate tissue and fluid from the surgical site. If both tubes aspirate through openings 426 and 428 then a separate infusion source needs to be provided. The dual lumen tip and hub can be tightened onto the hand piece with a wrench designed to be inserted into opening 475.

(42) In a typical phacoemulsification operation with the work tip of FIG. 14A, irrigation fluid is directed to the cataract through tube 424 to opening 428 and ports 460, 480. Tissue is aspirated through opening 426 into tube 423. As one aspect of the present invention, I/A clean up can be improved with this instrument by placing an adapter sleeve 420 over the distal ends of the tubes 423, 424. This adapter 420 is shown prior to installation in FIG. 14B. The adapter when installed blocks the irrigation and aspiration flow paths of the work tip through openings 426, 428, 460 and 480. In their place a plurality of aspiration holes 430 are provided in the adapter 420. Also, irrigation is limited to hole 432 in the adapter.

(43) With this design, the dual lumen work tip is removed from the eye. Then the adapter is placed on the work tip and retained there by any of the methods shown in FIGS. 5B, 6, 7A, 8B, 9B and 10. Finally the work tip is returned to the eye to complete the I/A clean up. However, the adapter 420 can be modified to have a shape like that in FIG. 12 or 13 so that it can be withdrawn from the distal end during phacoemulsification and extended during the subsequent clean up. During this extension a portion of the sleeve would extend over the openings 426, 428 in the distal ends of the tubes 423, 424 as shown in FIGS. 12 and 13. The extension and retraction of the sleeve 420 can be by way of a mechanism 300 shown in FIG. 11.

(44) While the invention has been shown and described in connection with the removal of a cataract from the eye of a patient and subsequent I/A clean up, the apparatus and method may also be used for other types of surgery in other parts of the body, e.g., the removal of neurological

tissue.

(45) Specific features of the invention are shown in one or more of the drawings for convenience only, as each feature may be combined with other features in accordance with the invention. Alternative embodiments will be recognized by those skilled in the art and are intended to be included within the scope of the claims. Accordingly, the above description should be construed as illustrating and not limiting the scope of the invention. All such obvious changes and modifications are within the scope of the appended claims.

Claims

1. A surgical handpiece comprising: a connecting body having a distal end; a work tip having a hub at a proximal end and an opening at an operating distal end thereof, said hub being attached to the connecting body, an axial aspiration channel extending through the work tip from the opening at the operating end of the work tip and through at least a part of the hub, said aspiration channel further including a lateral aspiration hole in the work tip adjacent its end; a housing containing the connecting body and at least a portion of the hub; an irrigation sleeve surrounding and spaced from the hub and aspiration channel, said irrigation sleeve extending to the vicinity of the operating end of the work tip, said irrigation sleeve forming an irrigation channel between the inner surface of the sleeve and the external surface of the work tip which extends to a lateral irrigation opening in the vicinity of the operating end of the work tip for delivery of irrigation fluid to that area, said irrigation channel being generally concentric with the axial aspiration channel in the work tip and hub, and aspiration fluid may be withdrawn from the opening at the operating end of the work tip; said irrigation sleeve extending beyond its lateral irrigation opening toward the distal end of the work tip, having a further lateral opening in the extended part, being slidable with respect to the work tip and being located closely about the distal end of the work tip so that it can be introduced into the eye of a patient along with the work tip; and a sleeve sliding mechanism that can move the slidable irrigation sleeve axially along the work tip distal end, said sliding mechanism including a finger portion located along the housing of the hand piece and being connected to the slidable sleeve; whereby sliding of the slidable irrigation sleeve through action of the sliding mechanism causes the irrigation sleeve to reconfigure the openings in the work tip for I/A clean up by causing at least partial blocking of the opening at the operating end of the aspiration channel and opening of the lateral aspiration hole and further lateral opening.

2. The surgical handpiece of claim 1 further comprising: wherein the lateral aspiration opening is a small opening compared to the further lateral irrigation channel near the distal end of the work tip; wherein the sliding sleeve includes two hinged semicircular portions at its distal end, wherein curved parts of the semicircular portions are hinged to the sleeve and urged into a closed position by an elastic member, the aperture provides irrigation fluid to a surgical site; whereby, when the sliding sleeve is retracted with respect to the work tip by the sliding mechanism, the end of the work tip pushes the hinged portions of the sleeve aside and the work tip can be used for phacoemulsification of cataracts in the eye of a patient; and whereby, when the sliding sleeve is extended with respect to the work tip by the sliding mechanism, the hinged portions of the sleeve close off the work tip opening at the operating distal end, the further lateral opening in the sliding sleeve and the lateral aspiration hole in the work tip align and define an aspiration opening during I/A cleanup of the capsular bag of the eye.

3. The surgical handpiece of claim 2 wherein the hole is in the form of a plurality of openings in different patterns and sizes.

4. A surgical handpiece comprising: a connecting body having a distal end; a work tip having a hub at a proximal end and an opening at an operating distal end thereof, said hub being attached to the connecting body, an axial aspiration channel extending through the work tip from the opening at the operating end to the work tip through at least a part of the hub; a housing containing the

connecting body and at least a portion of the hub; a sliding irrigation sleeve surrounding and spaced from the hub and aspiration channel, said sliding irrigation sleeve extending to the vicinity of the operating end of the work tip, said sliding irrigation sleeve forming an irrigation channel between the inner surface of the sleeve and the external surface of the work tip which extends to a lateral irrigation opening in the vicinity of the operating end of the work tip for delivery of irrigation fluid to that area, said irrigation channel being generally concentric with the axial aspiration channel in the work tip and hub, and aspiration fluid may be withdrawn from the opening at the operating end of the work tip, said sliding irrigation sleeve being slidable with respect to the work tip and located closely about the distal end of the work tip so that it can be introduced into the eye of a patient along with the work tip; and a sleeve sliding mechanism that can move the sliding irrigation sleeve axially along the work tip distal end, said sliding mechanism including a finger portion located along the housing of the hand piece and being connected to the sliding irrigation sleeve; wherein the sliding irrigation sleeve comprises a proximal part and a distal part, with apertures located in the proximal part, at least a distal end of the distal part is in the form of multiple segments designed to fold into a closure; whereby, when the sliding irrigation sleeve is retracted with respect to the work tip by the sliding mechanism, the operating end of the work tip is exposed and can be used for phacoemulsification of cataracts in the eye of a patient; and whereby, when the sliding irrigation sleeve is extended with respect to the work tip by the sliding mechanism, the segments fold toward each other partially closing the opening in the work tip except for a small space, which defines an aspiration opening during I/A cleanup of the capsular bag of the eye.

5. An adapter for a surgical hand piece having a single lumen work tip to convert it to infusion/aspiration (I/A) cleanup of lens epithelial cells in the capsular bag of the eye of a patient after phacoemulsification, comprising a sleeve adapted to be joined to the distal end of the work tip, said sleeve having a cylindrical shape with a smooth exterior surface connected to the distal end that has an external continuously curved smooth surface that smoothly joins the smooth exterior surface, a proximal end for attaching the adapter to the distal end of the work tip, and at least one aspiration hole located toward the distal end of the sleeve; and wherein the sleeve is sized to fit within the opening in the distal end of the work tip, the sleeve includes at least one protrusion on its exterior surface near its distal end and wherein the work tip has at least one recess in its interior surface that engages the sleeve protrusion to hold the adapter on the work tip.

6. The adapter according to claim 5 wherein the diameter of the sleeve with respect to the opening in the distal end is such that the adapter becomes press fit in the work tip, and the sleeve further includes a raised portion on its distal end that has the same diameter as the work tip so that the outer surfaces of the work tip and the adapter smoothly join when the adapter is installed on the work tip, the aspiration hole being located in the raised portion of the sleeve.
