

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12393203
B2
August 19, 2025
Estep; Ryan et al.

Systems and methods for relative pose determination and field enforcement of materials handling vehicles using ultra-wideband radio technology

Abstract

According to the embodiments described herein, system and methods for determining relative pose of materials handling vehicles in an industrial environment may include utilizing ultra-wideband (UWB) antenna array systems respective mounted on the materials handling vehicles to send mutually received information to determine the relative pose between the vehicles, determining one or more fields of each materials handling vehicle, and determining one or more overlapping fields between the materials handling vehicles based on the determined one or more fields and the relative pose. A vehicle control may be implemented based on the determined relative pose and the overlapping fields as a field enforcement, such as a control action to avoid collision between the vehicles.

Inventors: Estep; Ryan (Auckland, NZ), Bennett; Justin (Newburgh, IN), Ciholas; Mike Etienne (Newburgh, IN), Morelli; Ben (Auckland, NZ), Lefeld; Chad (Coldwater, OH), Luthman; Trisha Marie (Covington, OH)

Applicant: Crown Equipment Corporation (New Bremen, OH)

Family ID: 1000008768286

Assignee: Crown Equipment Corporation (New Bremen, OH)

Appl. No.: 17/493231

Filed: October 04, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220107635 A1	Apr. 07, 2022

Related U.S. Application Data

us-provisional-application US 63087541 20201005
us-provisional-application US 63104567 20201023
us-provisional-application US 63231508 20210810
us-provisional-application US 63087543 20201005
us-provisional-application US 63087548 20201005
us-provisional-application US 63087652 20201005
us-provisional-application US 63087544 20201005
us-provisional-application US 63104796 20201023
us-provisional-application US 63231506 20210810

Publication Classification

Int. Cl.: **G05D1/242** (20240101); **B66F9/06** (20060101); **B66F9/075** (20060101); **G01S5/02** (20100101); **G01S5/10** (20060101); **G05D1/00** (20240101); **G05D1/226** (20240101); **G05D1/24** (20240101); **G05D1/243** (20240101); **G05D1/69** (20240101); **G05D1/692** (20240101); **G05D1/693** (20240101); **G05D105/80** (20240101); **G05D107/70** (20240101); **G07C5/08** (20060101); **G08G1/16** (20060101); **H01Q1/12** (20060101); **H01Q5/25** (20150101); **H04B1/7163** (20110101)

U.S. Cl.:

CPC **G05D1/242** (20240101); **B66F9/063** (20130101); **B66F9/0755** (20130101); **G01S5/0284** (20130101); **G01S5/10** (20130101); **G05D1/0022** (20130101); **G05D1/0027** (20130101); **G05D1/0289** (20130101); **G05D1/226** (20240101); **G05D1/24** (20240101); **G05D1/2437** (20240101); **G05D1/69** (20240101); **G05D1/692** (20240101); **G05D1/693** (20240101); **G07C5/0825** (20130101); **G08G1/163** (20130101); **H01Q1/1221** (20130101); **H01Q5/25** (20150115); **H04B1/7163** (20130101); **G05D2105/93** (20240101); **G05D2107/70** (20240101)

Field of Classification Search

CPC: H01Q (1/1221); H01Q (1/32); H01Q (1/325); H01Q (1/3275); H01Q (5/25); G01S (5/0284); G01S (5/10); G05B (19/41895); G05B (2219/50391); H04B (1/38); H04B (1/7163); B60Q (9/008); B60Q (1/525); B60Q (2800/20); G06V (2201/06); Y04S (40/18); G05D (1/0291); G05D (1/0223); G05D (1/0027); G05D (1/0088); G05D (1/0022); G05D (1/0214); G05D (1/021); G05D (1/0282); G05D (2201/0216); G05D (1/0289); G05D (1/0212); G05D (1/0221); G05D (1/0287); G05D (2201/02); G05D (1/0278); G05D (1/027); E05F (15/77); B65G (69/28); B65G (1/00); B65G (1/1373); B65G (1/0492); G08G (1/166); G08G (1/20); G08G (1/207); G08G (1/164); G08G (1/161); G08G (1/22); G08G (1/16); G08G (1/163); H04W (4/46); H04W (4/70); H04W (4/029); H04W (4/021); H04W (84/005); H04W (24/08); H04W (4/30); H04W (4/33); H04W (88/10); H04W (4/027); H04W (4/02); H04W (52/0216); H04W (4/025); H04W (72/12); H04W (16/20); H04W (12/64); H04W (24/00); H04W (36/32); H04W (4/026); H04W (40/026); H04W (84/042); B66F (17/003); B66F (11/00); B66F (9/0755); B66F (9/24); B66F (9/07581); B66F (9/063); G06K (19/0723); G06Q (50/28); G06Q (10/08355); G06Q (10/08); G06Q (50/08); G06Q (30/0266); G06Q (50/30); H04L (67/12); H04L (67/04); H04L (67/104); H04L (67/1044); H04L (67/1051); G01C (21/20); G07C (5/0825)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6209913	12/2000	Ishikawa	340/440	B66F 17/003
7518556	12/2008	Kurashima	343/846	H01Q 9/40
8954252	12/2014	Urmson et al.	N/A	N/A
9174830	12/2014	Bell	N/A	N/A
9221392	12/2014	Chen	N/A	N/A
9340399	12/2015	Bell	N/A	N/A
9349181	12/2015	Chandrasekar et al.	N/A	N/A
9731417	12/2016	Bruemmer et al.	N/A	N/A
9811088	12/2016	Walton et al.	N/A	N/A
9958873	12/2017	Thomson	N/A	N/A
9984467	12/2017	Chandrasekar et al.	N/A	N/A
10409284	12/2018	Kentley-Klay	N/A	B60L 3/04
10430073	12/2018	Castaneda et al.	N/A	N/A
10522054	12/2018	Manci et al.	N/A	N/A
10754466	12/2019	Ochenas et al.	N/A	N/A
11074664	12/2020	John	N/A	G01S 5/0247
11756427	12/2022	Reed	340/903	B66F 17/003
2009/0174605	12/2008	Chang	N/A	N/A
2010/0114405	12/2009	Elston	701/1	B60W 30/09
2011/0046813	12/2010	Castaneda	701/41	B66F 9/07568
2011/0166721	12/2010	Castaneda	701/2	G05D 1/0255
2011/0279261	12/2010	Gauger	340/669	B66F 9/0755
2012/0078471	12/2011	Siefring	701/41	B62D 15/0265
2013/0197760	12/2012	Castaneda	701/41	B60T 8/17
2014/0188576	12/2013	de Oliveira et al.	N/A	N/A
2014/0195121	12/2013	Castaneda	701/41	G05D 1/0255
2016/0100522	12/2015	Yamauchi	701/25	G05D 1/0219
2017/0214112	12/2016	Ohno	N/A	H01Q 25/002
2017/0244444	12/2016	Bruemmer	N/A	H04L 67/12
2017/0374511	12/2016	Bachman et al.	N/A	N/A
2018/0059231	12/2017	Dewberry et al.	N/A	N/A
2018/0059682	12/2017	Thode	N/A	B66F 17/003
2018/0143312	12/2017	High	N/A	G05D 1/0261
2018/0294565	12/2017	Hollar	N/A	H01Q 1/36
2019/0033882	12/2018	Collett	N/A	G08G 1/162
2019/0053021	12/2018	Fuke	N/A	E05B 83/36

2019/0272757	12/2018	Grabbe	N/A	G08G 1/166
2019/0339690	12/2018	Kwak	N/A	G05D 1/0295
2019/0339713	12/2018	Kwak	N/A	N/A
2019/0355196	12/2018	Plattner et al.	N/A	N/A
2020/0050719	12/2019	Fuerstenberg	N/A	G05D 1/0088
2021/0179022	12/2020	Hasegawa	N/A	B60R 25/245
2021/0316975	12/2020	Yeo	N/A	G01S 17/42
2022/0267128	12/2021	Han	N/A	B66F 9/0755
2022/0384949	12/2021	Pirch	N/A	H01Q 1/1221

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2014203775	12/2015	AU	B60T 7/00
103094676	12/2012	CN	N/A
210404031	12/2019	CN	N/A
213799435	12/2020	CN	N/A
20090023693	12/2008	KR	N/A
2020/032412	12/2019	WO	N/A

OTHER PUBLICATIONS

Translation of CN-210404031-U retrieved from Espacenet on Nov. 27, 2023 (Year: 2023). cited by examiner

International Search Report and Written Opinion, PCT/US2021/053427 dated Mar. 28, 2022 (21 pages). cited by applicant

Office Action issued Apr. 19, 2024 in related European Patent Application No. 21810166.5 filed Oct. 4, 2021, pp. 1-7. cited by applicant

Examination Report issued on Nov. 15, 2024 in related European Patent Appl. No. 21810166.5 filed Oct. 4, 2021, pp. 1-7. cited by applicant

European Search Report issued Jan. 24, 2025 in related European Patent Application No. 24211596.2 filed Jan. 24, 2025. cited by applicant

Draganjac Ivica et al; “Highly-scalable traffic management of autonomous industrial transportation”, Robotics and Computer Integrated Manufacturing, Elsevier Science Publishers BV., Barking GB, vol. 63, Dec. 13, 2019. cited by applicant

Primary Examiner: Jabr; Fadey S.

Assistant Examiner: Shaikh; Faris Asim

Attorney, Agent or Firm: Dinsmore & Shohl LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application claims the benefit of U.S. Provisional App. No. 63/087,541, filed Oct. 5, 2020, entitled ANTENNA MOUNTING STRUCTURES FOR INDUSTRIAL VEHICLES; U.S. Provisional App. No. 63/104,567, filed Oct. 23, 2020, entitled INDUSTRIAL VEHICLE ANTENNA MOUNTING

STRUCTURES; U.S. Provisional App. No. 63/231,508, filed Aug. 10, 2021, entitled INDUSTRIAL VEHICLE ANTENNA MOUNTING STRUCTURES AND ANTENNA POSITIONING CONFIGURATIONS; U.S. Provisional App. No. 63/087,543, filed Oct. 5, 2020, entitled SYSTEMS AND METHODS FOR SENSING A RELATIVE POSE OF MATERIALS HANDLING VEHICLES USING ULTRA-WIDEBAND RADIO TECHNOLOGY; U.S. Provisional App. No. 63/087,548, filed Oct. 5, 2020, entitled SYSTEMS AND METHODS FOR FIELD ENFORCEMENT OF MATERIALS HANDLING VEHICLES USING ULTRA-WIDEBAND RADIO TECHNOLOGY; U.S. Provisional App. No. 63/087,652, filed Oct. 5, 2020, entitled SYSTEMS AND METHODS FOR FIELD ENFORCEMENT OF MATERIALS HANDLING VEHICLES USING ULTRA-WIDEBAND RADIO TECHNOLOGY; U.S. Provisional App. No. 63/087,544, filed Oct. 5, 2020, entitled LIGHT COMPONENTS FOR DISPLAYING SYMBOLS CORRESPONDING TO VEHICLE STATUSES; U.S. Provisional App. No. 63/104,796, filed Oct. 23, 2020, entitled LIGHT COMPONENTS FOR DISPLAYING SYMBOLS CORRESPONDING TO VEHICLE STATUSES; and U.S. Provisional App. No. 63/231,506, filed Aug. 10, 2021, entitled LIGHT COMPONENTS FOR DISPLAYING SYMBOLS AND LIGHT COMPONENT MOUNTING ARRANGEMENTS; the entireties of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present specification generally relates to systems and methods for relative pose sensing and field enforcement of materials handling vehicles to assist with managing vehicle operation within a defined area in an industrial environment and, more specifically, to systems and methods for sensing and determining a relative pose and field enforcement based on sensing and determining relative poses of materials handling vehicles using ultra-wideband (UWB) radio technology and overlapping fields.

BACKGROUND

(2) In order to move items about an industrial environment, workers often utilize industrial vehicles, including for example, forklift trucks, hand and motor driven pallet trucks, and/or other materials handling vehicles. The industrial vehicles can be configured as an automated guided vehicle that navigates through the industrial environment or a manually guided vehicle that knows its location within the industrial environment. In order to facilitate automated guidance, navigation, or both, the industrial vehicle may be adapted for localization within the environment. That is the industrial vehicle can be adapted with sensors and processors for determining the location of the industrial vehicle within the environment such as, for example, pose and position of the industrial vehicle.

SUMMARY

(3) In one embodiment, materials handling vehicle may comprise one or more vehicular processors, a drive mechanism configured to move the materials handling vehicle along an inventory transit surface, a materials handling mechanism configured to store and retrieve goods in a storage bay of an industrial environment, and vehicle control architecture in communication with the drive and materials handling mechanisms. The vehicular processor(s) of the materials handling vehicle may execute vehicle functions to determine a relative pose of a materials handling vehicle with respect to the materials handling vehicle based on UWB signals transmitted from multi-antenna arrays on each of the materials handling vehicles, determine one or more fields of each materials handling vehicle, and determine one or more overlapping fields between the materials handling vehicles based on the determined one or more fields and the relative pose, and implement a vehicle control action based on the determined one or more overlapping fields.

(4) According to an embodiment of the present disclosure, a relative pose determination system comprises a first materials handling vehicle, and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body and a vehicle position processor, wherein the

first and second materials handling vehicles are configured to navigate a vehicle transit surface in a warehouse environment, the first materials handling vehicle comprises a first ultra-wideband (UWB) antenna array mounted to the vehicle body, and the second materials handling vehicle comprises a second UWB antenna array mounted to the vehicle body. Each vehicle position processor is configured to: transmit a first UWB signal from the first UWB antenna array of the first materials handling vehicle to the second UWB antenna array of the second materials handling vehicle, receive the first UWB signal at the second UWB antenna array of the second materials handling vehicle, determine a second materials handling vehicle set of information based on the first UWB signal, and transmit a second UWB signal comprising the second materials handling vehicle set of information from the second UWB antenna array of the second materials handling vehicle to the first UWB antenna array of the first materials handling vehicle. Each vehicle position processor is further configured to: determine a first materials handling vehicle set of information based on the second UWB signal, transmit a third UWB signal comprising the first materials handling vehicle set of information from the first UWB antenna array of the first materials handling vehicle to the second UWB antenna array of the second materials handling vehicle, determine a relative pose of each of the first and second materials handling vehicles with respect to each other based on the second UWB signal and the third UWB signal, and operate at least one of the first and second materials handling vehicles based on the relative pose.

(5) In accordance with another embodiment of the present disclosure, a relative pose determination system comprises a vehicle position processor, a first materials handling vehicle, and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body. The first and second materials handling vehicles are configured to navigate a vehicle transit surface in a warehouse environment, the first materials handling vehicle comprises a first ultra-wideband (UWB) antenna array mounted to the vehicle body, and the second materials handling vehicle comprises a second UWB antenna array mounted to the vehicle body. The vehicle position processor is configured to: transmit a first UWB signal from the first UWB antenna array of the first materials handling vehicle to the second UWB antenna array of the second materials handling vehicle, receive the first UWB signal at the second UWB antenna array of the second materials handling vehicle, and determine a second materials handling vehicle set of information based on the first UWB signal. The vehicle position processor is further configured to: transmit a second UWB signal comprising the second materials handling vehicle set of information from the second UWB antenna array of the second materials handling vehicle to the first UWB antenna array of the first materials handling vehicle, determine a first materials handling vehicle set of information based on the second UWB signal, transmit a third UWB signal comprising the first materials handling vehicle set of information from the first UWB antenna array of the first materials handling vehicle to the second UWB antenna array of the second materials handling vehicle, determine a relative pose of each of the first and second materials handling vehicles with respect to each other based on the second UWB signal and the third UWB signal, and operate at least one of the first and second materials handling vehicles based on the relative pose.

(6) In accordance with yet another embodiment of the present disclosure, a method determines relative pose between a first materials handling vehicle and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body, the first materials handling vehicle comprising a first ultra-wideband (UWB) antenna array mounted to the vehicle body, the second materials handling vehicle comprising a second UWB antenna array mounted to the vehicle body. The method comprises transmitting a first UWB signal from the first UWB antenna array of the first materials handling vehicle to the second UWB antenna array of the second materials handling vehicle, receiving the first UWB signal at the second UWB antenna array of the second materials handling vehicle, determining a second materials handling vehicle set of information based on the first UWB signal, and transmitting a second UWB signal comprising the second materials handling vehicle set of information from the second UWB antenna array of the second materials handling

vehicle to the first UWB antenna array of the first materials handling vehicle. The method further comprises determining a first materials handling vehicle set of information based on the second UWB signal, transmitting a third UWB signal comprising the first materials handling vehicle set of information from the first UWB antenna array of the first materials handling vehicle to the second UWB antenna array of the second materials handling vehicle, determining a relative pose of each of the first and second materials handling vehicles with respect to each other based on the second UWB signal and the third UWB signal, and operating at least one of the first and second materials handling vehicles based on the relative pose.

(7) According to an embodiment of the present disclosure, a field enforcement system comprises a first materials handling vehicle, and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body and a vehicle position processor. The first and second materials handling vehicles are configured to navigate a vehicle transit surface in a warehouse environment, the first materials handling vehicle comprises a first ultra-wideband (UWB) antenna array mounted to the vehicle body, and the second materials handling vehicle comprises a second UWB antenna array mounted to the vehicle body. Each vehicle position processor is configured to: transmit respective UWB signals comprising vehicle information between respective UWB antenna arrays of the first and second materials handling vehicles, and determine a relative pose of each of the first and second materials handling vehicles with respect to each other based on transmitted UWB signals comprising the vehicle information. Each vehicle position processor is further configured to: determine a first virtual field for the first materials handling vehicle and a second virtual field for the second materials handling vehicle, determine a field infringement occurrence when a portion of the first virtual field overlaps a portion of the second virtual field based on the relative pose, and operate at least one of the first and second materials handling vehicles based on the field infringement occurrence.

(8) In accordance with another embodiment of the present disclosure, a field enforcement system comprises a vehicle position processor, a first materials handling vehicle, and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body. The first and second materials handling vehicles are configured to navigate a vehicle transit surface in a warehouse environment, the first materials handling vehicle comprises a first ultra-wideband (UWB) antenna array mounted to the vehicle body, and the second materials handling vehicle comprises a second UWB antenna array mounted to the vehicle body. The vehicle position processor is configured to: transmit respective UWB signals comprising vehicle information between respective UWB antenna arrays of the first and second materials handling vehicles, determine a relative pose of each of the first and second materials handling vehicles with respect to each other based on transmitted UWB signals comprising the vehicle information, and determine a first virtual field for the first materials handling vehicle and a second virtual field for the second materials handling vehicle. The vehicle position processor is further configured to: determine a field infringement occurrence when a portion of the first virtual field overlaps a portion of the second virtual field based on the relative pose, and operate at least one of the first and second materials handling vehicles based on the field infringement occurrence.

(9) In accordance with yet another embodiment of the present disclosure, a method is disclosed for field enforcement between a first materials handling vehicle and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body, the first materials handling vehicle comprising a first ultra-wideband (UWB) antenna array mounted to the vehicle body, the second materials handling vehicle comprising a second UWB antenna array mounted to the vehicle body. The method comprises transmitting respective UWB signals comprising vehicle information between respective UWB antenna arrays of the first and second materials handling vehicles, and determining a relative pose of each of the first and second materials handling vehicles with respect to each other based on transmitted UWB signals comprising the vehicle information. The method further comprises determining a first virtual field for the first materials handling vehicle and a

second virtual field for the second materials handling vehicle, determining a field infringement occurrence when a portion of the first virtual field overlaps a portion of the second virtual field based on the relative pose, and operating at least one of the first and second materials handling vehicles based on the field infringement occurrence.

(10) These and additional features provided by the embodiments described herein will be more fully understood in view of the following detailed description, in conjunction with the drawings.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) The embodiments set forth in the drawings are illustrative and exemplary in nature and not intended to limit the subject matter defined by the claims. The following detailed description of the illustrative embodiments can be understood when read in conjunction with the following drawings, where like structure is indicated with like reference numerals and in which:

(2) FIG. 1A depicts a materials handling vehicle in a warehouse including a UWB antenna system, according to one or more embodiments shown and described herein;

(3) FIG. 1B depicts a pair of UWB antenna systems respectively disposed on materials handling vehicles in a warehouse to determine a relative pose between the materials handling vehicles, according to one or more embodiments shown and described herein;

(4) FIG. 1C depicts a pair of UWB antenna systems respectively disposed on materials handling vehicles in a warehouse to determine a position and distance of one of the materials handling vehicles, according to one or more embodiments shown and described herein;

(5) FIG. 2 depicts a schematic illustration of a system for implementing computer and software based methods to determine pose or position, according to one or more embodiments shown and described herein;

(6) FIG. 3 depicts a flowchart overview of a method for pose or position determination between materials handling vehicles in a warehouse, according to one or more embodiments shown and described herein;

(7) FIG. 4 depicts fields of a materials handling vehicle, according to one or more embodiments shown and described herein;

(8) FIG. 5 depicts overlapping fields between a pair of materials handling vehicles, according to one or more embodiments shown and described herein;

(9) FIG. 6 depicts multiple overlapping fields between a pair of materials handling vehicles, according to one or more embodiments shown and described herein;

(10) FIG. 7 depicts types of field overlap between a pair of materials handling vehicles, according to one or more embodiments shown and described herein;

(11) FIG. 8 depicts a display of a materials handling vehicle including field and operational information, according to one or more embodiments shown and described herein;

(12) FIG. 9 depicts a materials handling vehicle including a first mounted UWB antenna array system including a plurality of enclosures;

(13) FIG. 10 depicts a UWB antenna as disposable in an enclosure of FIG. 9;

(14) FIG. 11 depicts a materials handling vehicle including a second mounted UWB antenna array system including a plurality of enclosures;

(15) FIG. 12 depicts a UWB antenna disposed in a first enclosure;

(16) FIG. 13 depicts a UWB antenna disposed in a second enclosure;

(17) FIG. 14A depicts a first set of lighting component modules mounted to a materials handling vehicle;

(18) FIG. 14B depicts a second set of lighting component modules mounted to a materials handling vehicle;

(19) FIG. 15A depicts a first lighting component module to mount to a materials handling vehicle; and

(20) FIG. 15B depicts a second lighting component module to mount to a materials handling vehicle.

DETAILED DESCRIPTION

(21) The embodiments described herein generally relate to systems and methods for relative pose sensing and field enforcement of materials handling vehicles using ultra-wideband (UWB) radio technology. The relative pose sensing systems and methods may be used on a Time of Flight (ToF) measuring system with bi-direction communication, as described in greater detail below. The field enforcement systems and methods may use localization techniques to determine and assist with managing vehicle presence in an industrial environment as described herein. Localization is utilized herein to refer to any of a variety of system configurations that enable active tracking of a vehicle location in a warehouse, industrial or commercial facility, or other environment. The concepts of the present disclosure are not limited to any particular localization system configuration and are deemed to be applicable to and used in combination with any of a variety of conventional and yet-to-be developed localization systems. Such localization systems may include those described in U.S. Pat. No. 9,349,181 issued on May 24, 2016, entitled LOST VEHICLE RECOVERY UTILIZING ASSOCIATED FEATURE PAIRS, and U.S. Pat. No. 9,984,467 issued May 29, 2018, entitled VEHICLE POSITIONING OR NAVIGATION UTILIZING ASSOCIATED FEATURE PAIRS.

(22) The localization systems may be used to localize and/or navigate an industrial vehicle through an industrial environment, such as a warehouse, stock yard, or the like. In some embodiments, a camera, laser based system, and/or UWB based system **150** can be mounted to an industrial vehicle (e.g., automated guided vehicle or a manually guided vehicle) that navigates through a warehouse and can assist with vehicle localization. The laser based system may include a laser scanner, a laser rangefinder, a 2D/3D mapping laser, a lidar, or combinations thereof. The UWB based system **150** may include a UWB system array including a plurality of UWB antenna coupled together, as described in greater detail below. In embodiments, the UWB systems described herein may be employed semi-autonomous or fully autonomous automation as a primary or secondary safety system working alongside the lidar and/or image sensors.

(23) Referring now to FIG. 1A, a vehicle **100** can be configured to navigate through an industrial facility such as a warehouse **110**. The vehicle **100** can comprise a materials handling vehicle including a drive mechanism to move the materials handling vehicle along an inventory transit surface, a materials handling mechanism configured to store and retrieve goods in a storage bay of an industrial facility, and vehicle control architecture in communication with the drive and materials handling mechanisms. The vehicle **100** can comprise an industrial vehicle such as a materials handling vehicle for lifting and moving a payload such as, for example, a forklift truck, a reach truck, a turret truck, a walkie stacker truck, a tow tractor, a pallet truck, a high/low, a stacker-truck, a trailer loader, a sideloader, a fork hoist, or the like. The industrial vehicle can be configured to automatically or manually navigate an inventory transit surface such as a surface **122** of the warehouse **110** along a desired path. Accordingly, the vehicle **100** can be directed forwards and backwards by rotation of one or more wheels **124**. Additionally, the vehicle **100** can be caused to change direction by steering the one or more wheels **124**. Optionally, the vehicle can comprise operator controls **126** for controlling functions of the vehicle such as, but not limited to, the speed of the wheels **124**, the orientation of the wheels **124**, or the like. The operator controls **126** can comprise controls that are assigned to functions of the vehicle **100** such as, for example, switches, buttons, levers, handles, pedals, input/output devices, or the like. It is noted that the term “navigate” as used herein means movement control or route planning of a vehicle from one place to another including, but not limited to, plotting a graphical path for a manual vehicle operation, providing a set of turn by turn instructions for manual operation, or providing an automated control

guiding the vehicle along a travel path that may include such turn by turn instructions for automated operation. It is noted that the term “operate” as used herein means operation or control of operation of a vehicle, such as performing a vehicle control action including, but not limited to, setting a speed limit, issuing operator alerts, and other vehicle control actions.

(24) In embodiments, the vehicle **100** can further comprise a camera **102** for capturing overhead images such as input images of overhead features. The camera **102** can be any device capable of capturing the visual appearance of an object and transforming the visual appearance into an image. In some embodiments, the vehicle **100** can be located within the warehouse **110** and be configured to capture overhead images of the ceiling **112** of the warehouse **110**.

(25) The ceiling **112** of the warehouse **110** can comprise overhead features such as, but not limited to, ceiling lights **114** for providing illumination from the ceiling **112** or generally from above a vehicle operating in the warehouse. The ceiling lights **114** can comprise substantially rectangular lights such as, for example, skylights **116**, fluorescent lights, or the like; and may be mounted in or suspended from the ceiling or wall structures so as to provide illumination from above.

(26) The embodiments described herein can comprise one or more vehicular processors such as processors **104** communicatively coupled to the vehicle **100**. The one or more processors **104** can execute machine readable instructions to implement any of the methods or functions described herein automatically. Memory **106** for storing machine readable instructions can be communicatively coupled to the one or more processors **104**, the vehicle **100**, or any combination thereof. The one or more processors **104** can comprise a processor, an integrated circuit, a microchip, a computer, or any other computing device capable of executing machine readable instructions or that has been configured to execute functions in a manner analogous to machine readable instructions. The memory **106** can comprise RAM, ROM, a flash memory, a hard drive, or any non-transitory device capable of storing machine readable instructions.

(27) The one or more processors **104** and the memory **106** may be integral with the vehicle **100**. Moreover, each of the one or more processors **104** and the memory **106** can be separated from the vehicle **100** and/or the camera **102**. For example, a management server, server, or a mobile computing device can comprise the one or more processors **104**, the memory **106**, or both. It is noted that the one or more processors **104**, the memory **106**, and the camera **102** may be discrete components communicatively coupled with one another without departing from the scope of the present disclosure. Accordingly, in some embodiments, components of the one or more processors **104**, components of the memory **106**, and components of the camera **102** can be physically separated from one another. The phrase “communicatively coupled,” as used herein, means that components are capable of exchanging data signals with one another such as, for example, electrical signals via conductive medium, electromagnetic signals via air, optical signals via optical waveguides, or the like.

(28) Thus, embodiments of the present disclosure may comprise logic or an algorithm written in any programming language of any generation (e.g., 1 GL, 2 GL, 3 GL, 4 GL, or 5 GL). The logic or an algorithm can be written as machine language that may be directly executed by the processor, or assembly language, object-oriented programming (OOP), scripting languages, microcode, etc., that may be compiled or assembled into machine readable instructions and stored on a machine readable medium. Alternatively or additionally, the logic or algorithm may be written in a hardware description language (HDL). Further, the logic or algorithm can be implemented via either a field-programmable gate array (FPGA) configuration or an application-specific integrated circuit (ASIC), or their equivalents.

(29) As is noted above, the vehicle **100** can comprise or be communicatively coupled with the one or more processors **104**. Accordingly, the one or more processors **104** can execute machine readable instructions to operate or replace the function of the operator controls **126**. The machine readable instructions can be stored upon the memory **106**. Accordingly, in some embodiments, the vehicle **100** can be navigated automatically by the one or more processors **104** executing the

machine readable instructions. In some embodiments, the location of the vehicle can be monitored by the localization system as the vehicle **100** is navigated.

(30) Referring to FIG. **1A**, the materials handling vehicle **100** can be configured to navigate through an industrial environment such as the warehouse **110**. The materials handling vehicle **100** can be configured to automatically or manually navigate an inventory transit surface such as a surface **122** of the warehouse **110** along a desired path. The materials handling vehicle **110** may further be configured to implement controls to take an action when determining a relative pose with respect to another materials handling vehicle **100** through a UWB system **150**. Such an action may be a braking action or other collision avoid action. In an embodiment, a UWB system **160** may include a UWB system **150A** as a System A mounted on a first materials handling vehicle **100** and a UWB system **150B** as a System B mounted on a second materials handling vehicle **100** as shown in FIG. **1B**. Each UWB system **150A**, **150B** may include a plurality of UWB antennas as anchors mounted together in an array with a determined center and positioned with respect to a selected and defined point of the vehicle that is measurable or determinable relative to the vehicle frame and individual anchor positions, such as a kinematic center of the vehicle.

(31) The array of UWB system **150A** of FIG. **1B** includes UWB antennas **R1**, **R2**, **R3**, and **R4**, with a center of the array defined by an X marking between the **R2** and **R3** antennas. In embodiments, the center of the array is the location from which an angle of arrival is sensed. Further, the angle of arrival may be corrected based on a predefined original point of each truck, such as the kinematic center of the vehicle. The array of UWB system **150B** of FIG. **1B** includes UWB antennas **R5**, **R6**, **R7**, and **R8**, with a center of the array defined by an X marking between the **R6** and **R7** antennas.

(32) Within each materials handling vehicle **100** including a multiple antenna UWB System **150A**, **150B**, the UWB antennas may be synced using a UWB sync signal and either a sync cable to each antenna (e.g., star topology) or a single clock cable connected to each antenna in turn (e.g., daisy chain topology). Once each array is synced, the array can sense both the distance a UWB signal has traveled (e.g., using a common method called Two Way Ranging) and angle of arrival of the UWB signal (e.g., by measuring the minute time differences of the reception of the signal on each antenna). As described in greater detail below with respect to the process **300** of FIG. **3**, a relative pose of a pair of vehicles **100** using a UWB antenna array mounted as UWB Systems **150A**, **150B** respectively to each vehicle **100** may be determined. By receiving UWB signal information from a node of the array (e.g., UWB antenna) including an angle of arrival and distance as described in greater detail below, and with a distance between the node and a center of the array being known, a position and orientation of the node is determined. Thus, a position and orientation of the vehicle onto which the node is mounted in a known configuration with respect to the center of the vehicle is determined to assist with determination of vehicle pose. As described herein, “pose” references a position and orientation of a materials handling vehicle **100**, such as within the warehouse **110**. A “relative pose” of a materials handling vehicle **100** references a position and orientation of the materials handling vehicle **100** relative to another object, such as a second materials handling vehicle **100** as described in greater detail below.

(33) In another embodiment, referring to FIG. **1C**, the UWB system **170** may include a UWB system **150A** as a System A mounted on a first materials handling vehicle **100** and another System B as a single UWB antenna system that may be mounted on a second materials handling vehicle **100** or in another location of the warehouse **110**. With the method of FIG. **1C**, a relative position can be determined for a remote vehicle in this system configuration, and circular fields may be enforced on the remote vehicle. In the vehicles **100** described herein, the vehicles may include one or more UWB antenna arrays and a beacon. At a lowered position of an operator compartment of at least one vehicle **100**, the system configuration of FIG. **1B** may be implemented to determine relative pose between vehicles **100** as relative pose observations. Regarding systems with multiple UWB antenna arrays on the different vehicles **100**, a control action from multiple observations (e.g., the relative pose observations) may be considered in combination to determine a best

observation (such as one of highest ranking or best fit) to determine field infringement between the vehicles **100**, as described in greater detail below.

(34) When the operator compartment is raised, the beacon may be configured to beacon out a signal and become a target for other vehicles **100** following the vehicle **100** with the operator compartment raised to perform the relative position observation of FIG. **1C** and enforce associated circular virtual fields. The system configuration of FIG. **1C** may thus aid to compensate for blindspots that are created for a UWB antenna array on an overhead guard when the vehicle is operating at a height such as when the operator compartment is raised. Thus, a relative position of vehicles **100** may be determined when a remote vehicle is not able to sense an angle of arrival due to a blindspot created for the UWB antenna array. The virtual fields for the remote vehicle in such an instance may be circular, and a field infringement calculation and behavior may proceed such that circular fields are checked for infringement with respect to a local vehicle's fully defined fields. The circular fields may be selected from a pre-programmed secondary fieldset or dynamically calculated based on primary operation fully defined fields.

(35) Referring to FIG. **2**, the embodiments described herein can comprise a system **200** including one or more vehicular processors such as processors **202** (which may be the one or more processors **104** and may be referenced herein as vehicle position processors **202**) that may be communicatively coupled to a memory **217**. A network interface hardware **212** may facilitate communications over a network **214** via wires, a wide area network, a local area network, a personal area network, a cellular network, a satellite network, and the like. Suitable personal area networks may include wireless technologies such as, for example, IrDA, Bluetooth®, Wireless USB, Z-Wave®, ZigBee®, and/or other near field communication protocols. Suitable personal area networks may similarly include wired computer buses such as, for example, USB and FireWire®. Suitable cellular networks include, but are not limited to, technologies such as LTE, WiMAX, UMTS, CDMA, and GSM. The network interface hardware **212** can be communicatively coupled to any device capable of transmitting and/or receiving data via the network **214**. Accordingly, the network interface hardware **212** can include a communication transceiver for sending and/or receiving any wired or wireless communication. For example, the network interface hardware **212** may include an antenna, a modem, LAN port, Wi-Fi card, WiMax card, mobile communications hardware, near-field communication hardware, satellite communication hardware and/or any wired or wireless hardware for communicating with other networks and/or devices.

(36) The one or more processors **202** can execute machine readable instructions to implement any of the methods or functions described herein automatically. Memory **217** as at least one of non-volatile memory **208** or volatile memory **210** in a computable readable medium **216** for storing machine readable instructions can be communicatively coupled to the one or more processors **202**. The one or more processors **202** can comprise a processor, an integrated circuit, a microchip, a computer, or any other computing device capable of executing machine readable instructions or that has been configured to execute functions in a manner analogous to machine readable instructions. The computable readable medium **216** can comprise RAM, ROM, a flash memory, a hard drive, or any non-transitory device capable of storing machine readable instructions.

(37) Each of the one or more processors **202** and the memory **217** can be integral with the vehicle **100**. Moreover, each of the one or more processors **202** and the memory **217** can be separated from the vehicle **100**. For example, a management server, server, or a mobile computing device can comprise the one or more processors **202**, the memory **217**, or both. It is noted that the one or more processors **202** and the memory **217** may be discrete components communicatively coupled with one another without departing from the scope of the present disclosure. Accordingly, in some embodiments, components of the one or more processors **202** and components of the memory **217** can be physically separated from one another. The phrase “communicatively coupled,” as used herein, means that components are capable of exchanging data signals with one another such as, for example, electrical signals via conductive medium, electromagnetic signals via air, optical signals

via optical waveguides, or the like.

(38) Thus, embodiments of the present disclosure may comprise logic or an algorithm written in any programming language of any generation (e.g., 1 GL, 2 GL, 3 GL, 4 GL, or 5 GL). The logic or an algorithm can be written as machine language that may be directly executed by the processor, or assembly language, object-oriented programming (OOP), scripting languages, microcode, etc., that may be compiled or assembled into machine readable instructions and stored on a machine readable medium such as computable readable medium **216**. Alternatively or additionally, the logic or algorithm may be written in a hardware description language (HDL). Further, the logic or algorithm can be implemented via either a field-programmable gate array (FPGA) configuration or an application-specific integrated circuit (ASIC), or their equivalents.

(39) In embodiments, one or more warehouse maps **30** of the warehouse **110** associated with a database **28** may be stored in the memory **217**. The system **200** can include one or more displays and/or output devices **204** such as monitors, speakers, headphones, projectors, wearable-displays, holographic displays, and/or printers, for example. Output devices **204** may be configured to output audio, visual, and/or tactile signals and may further include, for example, audio speakers, devices that emit energy (radio, microwave, infrared, visible light, ultraviolet, x-ray and gamma ray), electronic output devices (Wi-Fi, radar, laser, etc.), audio (of any frequency), etc.

(40) The system **200** may further include one or more input devices **206** which can include, by way of example, any type of mouse, keyboard, disk/media drive, memory stick/thumb-drive, memory card, pen, touch-input device, biometric scanner, voice/auditory input device, motion-detector, camera, scale, and the like. Input devices **206** may further include cameras (with or without audio recording), such as digital and/or analog cameras, still cameras, video cameras, thermal imaging cameras, infrared cameras, cameras with a charge-couple display, night-vision cameras, three dimensional cameras, webcams, audio recorders, a laser scanner, a laser rangefinder, a 2D/3D mapping laser, a lidar, UWB sensors, and the like. For example, an input device **206** may include the UWB system **150**, **160**, **170** described herein.

(41) As is noted above, the vehicle **100** can comprise or be communicatively coupled with the one or more processors **202**. Accordingly, the one or more processors **202** can execute machine readable instructions to operate or replace the function of the operator controls. The machine readable instructions can be stored upon the memory **106**, **217**. Accordingly, in some embodiments, the vehicle **100** can be navigated automatically by the one or more processors **202** executing the machine readable instructions. In some embodiments, the location of the vehicle can be monitored by the localization system as the vehicle **100** is navigated.

(42) As a non-limiting example, a navigation subsystem of the vehicle **100** may comprise one or more environmental sensors and an environmental database. In embodiments, the environmental sensors are configured to capture data indicative of a position of the vehicle **100** relative to the vehicle transit surface **122** in the warehouse **110**. Further, the environmental database may reside on or be remote from the vehicle **100** and may comprise stored data indicative of the vehicle transit surface **122**. The navigation subsystem may be configured to enable at least partially automated navigation of the vehicle **100** along the vehicle transit surface **122** utilizing the captured data and the stored data. For example, and not by way of limitation, it is contemplated that the navigation subsystem, the localization system, or both may utilize a stored warehouse map **30** and captured images of ceiling lights **114** or skylights **116** to enable navigation, localization, or both, as is disclosed in U.S. Pat. No. 9,174,830 issued on Nov. 3, 2015, U.S. Pat. No. 9,340,399 issued on May 17, 2016, U.S. Pat. No. 9,349,181 issued on May 24, 2016, U.S. Pat. No. 9,958,873 issued May 1, 2018, and other similar patents and patent publications. It is further contemplated that the navigation subsystem, a localization subsystem, or both may utilize a stored warehouse map **30** and a tag layout disposed on the vehicle transit surface **122** as disclosed in U.S. Pat. No. 9,811,088 issued on Nov. 7, 2017, and other similar patents and patent publications.

(43) Additional suitable environmental sensors include, but are not limited to, inertial sensors,

lasers, antennae for reading RFID tags, buried wires, WiFi signals, radio signals, global positioning system (GPS) sensors, global navigation satellite system (GNSS) sensors, ultra-wideband (UWB) sensors, or combinations thereof. By way of example and not as a limitation, UWB technology may be utilized for localization. UWB technology is a radio technology utilizing a low energy level for short-range, high-bandwidth communication over an ultra-wide radio spectrum portion, such as 3.1 to 10.6 GHz. UWB technology may include a transmitter on the materials handling vehicle **100** configured to transmit UWB transmissions for receipt by a receiver-anchor disposed in the warehouse **110**. Such UWB transmissions generate radio energy at specific time intervals while occupying a large bandwidth at low energy levels and enable pulse-position or time modulation, and may modulate transmitted information on UWB pulse signals. As described below, an ability for the UWB technology to determine a time of flight (ToF) of the transmission at different frequencies may assist with measuring distances at a high resolution and accuracy for localization.

(44) In embodiments described herein, UWB sensing utilizes UWB technology, such as UWB sensors, configured to implement radio technology via a pulse-based system that uses a low energy level for short-range, high-bandwidth communication over a broad portion of a radio spectrum, such as for transmission of information over a large bandwidth of greater than 500 MHz, or 20% of an arithmetic center frequency, as understood to one of ordinary skill in the art. Such UWB technology may employ time communication schemes such as use of Time of Flight (ToF) instead of signal strength measurement of electronic communications. UWB signals thus have very large bandwidths of at least 500 MHz (or a relative bandwidth of larger than 20%), have short duration waveforms, commonly transmit very short duration pulses with a low duty cycle (i.e., referable to as impulse radio), have a strong penetration capability (i.e., through walls) due to a large frequency spectrum, and may be realized in baseband (carrier-free) such that UWB pulses may be transmitted without a sine-wave carrier (i.e., non-sinusoidal). UWB signals may also be referenced as impulse radar, (time) impulse radio, non-sinusoidal signals, spread spectrum, and base band.

(45) The UWB systems described herein may be employed with radio technologies such as UWB, radio frequency (RF), impulse modulated radio, RADAR, and/or active radar. The UWB systems herein may employ UWB antenna technology with antenna systems such as Multiple Input Multiple Output (MIMO), Multiple Input Single Output (MISO), and/or Single Input Multiple Output (SIMO). Further, the UWB systems may employ location measurement techniques including, but not limited to, Angle of Arrival (AoA), Time of Flight (ToF), Two-Way Ranging, and/or Time Difference of Arrival (TDoA).

(46) In embodiments, a system may be a relative pose determination system and/or a field enforcement system. The system may include a first materials handling vehicle **100A** and a second materials handling vehicle **100B**, each materials handling vehicle **100** comprising a vehicle body. In an embodiment, each materials handling vehicle **100** may include a vehicle position processor **202**, and each vehicle position processor **202** may be configured to perform functionalities as described herein. In another embodiment, the system may include a vehicle position processor **202** such as a central hub remote from the vehicles **100** that may be configured to perform the functionalities as described herein. The first and second materials handling vehicles **100A**, **100B** are configured to navigate a vehicle transit surface **122** in a warehouse environment of warehouse **110**. The first materials handling vehicle **100A** comprises a first ultra-wideband (UWB) antenna array mounted to the vehicle body, and the second materials handling vehicle **100B** comprises a second UWB antenna array mounted to the vehicle body. The system may further include a plurality of vehicle wheels, a traction control unit, a braking system, and a steering assembly, and a navigation subsystem. The plurality of vehicle wheels support the vehicle body, the traction control unit, the braking system, and the steering assembly, are operatively coupled to one or more of the plurality of vehicle wheels, and the navigation subsystem is configured to cooperate with the traction control unit, the braking system, and the steering assembly to navigate the respective materials handling vehicle of the first and second materials handling vehicles **100A**, **100B** along

the vehicle transit surface in the warehouse environment (e.g., surface **122** of the warehouse **110**).

(47) As described in greater detail below with respect to FIG. **3**, the vehicle position processor **202** (which may reference throughout this disclosure each vehicle position processor **202** of a vehicle **100** or a vehicle position processor **202** separate from and communicatively coupled to the vehicles **100**) may be configured to transmit respective UWB signals comprising vehicle information between respective UWB antenna arrays of the first and second materials handling vehicles **100A**, **100B**, and determine a relative pose of each of the first and second materials handling vehicles **100A**, **100B** with respect to each other based on transmitted UWB signals comprising the vehicle information. The vehicle position processor **202** may further be configured to cooperate with the navigation subsystem of the first and second materials handling vehicles **100A**, **100B** to navigate the at least one of the first and second materials handling vehicles **100A**, **100B** based on the relative pose.

(48) Referring to FIG. **3**, the system **200** is configured to implement a process **300** through which a relative pose of a pair of vehicles **100** using a UWB antenna array mounted as UWB Systems **150A**, **150B** respectively to each vehicle **100** may be determined. As each UWB System **150A**, **150B** is configured to measure both a distance and an angle of received UWB signals, the signal and information exchanges may be utilized to sense the relative pose of the pair of materials handling vehicles **100** on which the UWB Systems **150A**, **150B** are respectively mounted, as described in greater detail below. Thus, the process **300** determines, through following machine-readable instructions, a relative pose of each of the material handling vehicles **100** of FIG. **1B** in the warehouse **110** with respect to each other.

(49) In block **302**, and with reference to UWB system **160** of FIG. **1B**, System B of UWB system **150B** transmits a UWB signal to System A of UWB system **150A**. System B emits the UWB signal that is received by each UWB antenna of System A. Each UWB system **150A**, **150B** is a multiple UWB antenna system with the antennas positioned in an array such that a center of the array is known and calibrated with respect to a center of the materials handling vehicle **100** on which the UWB system **150A**, **150B** is respectively mounted. System A receives the transmitted UWB signal and determines angle of arrival $\theta_{\text{sub.1}}$ and may determine some time-of-flight information between System A and System B.

(50) The vehicle position processor **202** may thus be configured to transmit a first UWB signal from the first UWB antenna array of the first materials handling vehicle **100A** (e.g., System B) to the second UWB antenna array of the second materials handling vehicle **100B** (e.g., System A), receive the first UWB signal at the second UWB antenna array of the second materials handling vehicle **100B** (e.g., System A), and determine a second materials handling vehicle set of information (at System A) based on the first UWB signal. The second materials handling vehicle set of information may include an angle of arrival (e.g., angle of arrival $\theta_{\text{sub.1}}$) and associated timing information based on the first UWB signal received at the second UWB antenna array. A determined distance (e.g., distance $d_{\text{sub.1}}$) may be determined (at System B in block **306** described further below) based on the associated timing information such as time of flight information as a distance between a pair of nodes of the second materials handling vehicle and the first materials handling vehicle.

(51) In block **304**, System A responds with a UWB signal transmitted to System B including information. System A emits the UWB signal that is received by each UWB antenna of System B. The information includes the angle of arrival $\theta_{\text{sub.1}}$ and associated timing information. Such timing information may be timestamped and utilized for a two-way ranging exchange to determine distance between nodes of the Systems A and B. In the two-way ranging exchange, a time of flight of a UWB radio-frequency (RF) signal may be determined and used to calculate a distance $d_{\text{sub.1}}$ between nodes by, for example, multiplying the time by speed of light (e.g., based on calculating time of flight that is convertible to distance). System B receives the transmitted UWB signal and determines distance $d_{\text{sub.1}}$ information between System B and System A.

(52) The vehicle position processor **202** may thus be configured to transmit a second UWB signal comprising the second materials handling vehicle set of information from the second UWB antenna array of the second materials handling vehicle **100B** (e.g., System A) to the first UWB antenna array of the first materials handling vehicle **100A** (e.g., System B), and determine a first materials handling vehicle set of information (at System B) based on the second UWB signal. The first materials handling vehicle set of information may include an angle of arrival (e.g., angle of arrival $\theta_{\text{sub.2}}$) and associated timing information based on the second UWB signal received at the first UWB antenna array. A determined distance (e.g., distance $d_{\text{sub.2}}$) may be determined (at System A) based on the associated timing information such as time of flight information as a distance between a pair of nodes of the second materials handling vehicle and the first materials handling vehicle. Each UWB antenna array may include four nodes on each of the second materials handling vehicle **100B** (e.g., System A) and the first materials handling vehicle **100A** (e.g., System B). Each node of the first UWB antenna array and the second UWB antenna array may include a UWB antenna arranged and positioned in the respective UWB antenna array and mounted on the vehicle body such that a center of the respective UWB antenna array is calibrated with respect to a center of the respective materials handling vehicle on which the respective UWB antenna array is mounted and a relative offset of each UWB antenna to the center of the respective materials handling vehicle.

(53) In block **306**, System B responds with a UWB signal transmitted to System A including information. The information includes the angle of arrival $\theta_{\text{sub.2}}$ and associated timing information. Such timing information may include time of flight information to be utilized for the two-way ranging exchange and that is timestamped. In the two-way ranging exchange, a time of flight of a UWB radio-frequency (RF) signal may be determined and used to calculate a distance $d_{\text{sub.2}}$ between nodes by, for example, multiplying the time by speed of light (e.g., based on calculating time of flight that is convertible to distance). System A receives the transmitted UWB signal and determines distance $d_{\text{sub.2}}$ information between System B and System A. Thus, both of System A and System B receive mutually received information including angle of arrival information of the UWB signals and distance between each system as measured from the other system. The vehicle position processor **202** may be configured to transmit a third UWB signal comprising the first materials handling vehicle set of information from the first UWB antenna array of the first materials handling vehicle **100A** (e.g., System B) to the second UWB antenna array of the second materials handling vehicle **100A** (e.g., System A).

(54) In block **308**, System A and System B respectively calculate a relative pose with respect to one another based on the mutually received information. Thus, the UWB antenna arrays respectively mounted as Systems A and B on each materials handling vehicle **100** are cooperatively used to sense the relative pose on both Systems A and B. By each of System A and System B determining a relative pose with respect to one another, the UWB system **160** may be used as a sensor system for enforcing speed limits and/or halting vehicle movements in hazardous conditions when the UWB system **160** detects two or more vehicles **100** are operating too close to one-another. The UWB system **160** may thus detect the full relative pose of one vehicle **100** to a high degree of accuracy and read other information from another vehicle **100** in order to determine if the pair of vehicles **100** are in a hazardous scenario with respect to one another and to take a preventative action accordingly (e.g., stopping, slowing, turning, automatic braking, active cruise control, or other collision avoidance action). The vehicle position processor **202** may thus be configured to determine a relative pose of each of the first and second materials handling vehicles **100A**, **100B** with respect to each other based on the second UWB signal and the third UWB signal, and navigate at least one of the first and second materials handling vehicles based on the relative pose.

(55) The relative pose may include a first vehicle pose and a second vehicle pose. The first vehicle pose may include a pose (i.e., position and orientation) of the first materials handling vehicle **100A** relative to the second materials handling vehicle **100B** based on the first materials handling vehicle

set of information, and the second vehicle pose may include a pose (e.g., position and orientation) of the second materials handling vehicle **100B** relative to the first materials handling vehicle **100A** based on the second materials handling vehicle set of information. The first materials handling vehicle **100A** may be configured to determine the second vehicle pose comprising the pose of the second materials handling vehicle **100B** relative to the first materials handling vehicle **100A** based on at least the second materials handling vehicle set of information transmitted with the second UWB signal. The second materials handling vehicle **100B** may be configured to determine the first vehicle pose comprising the pose of the first materials handling vehicle **100A** relative to the second materials handling vehicle **100B** based on at least the first materials handling vehicle set of information transmitted with the third UWB signal. The relative poses may further be based on extra data, such as at least relative coordinates of transmitting nodes on each vehicle **100A**, **100B** (e.g., the relative coordinates of transmitting nodes of the each UWB antenna array of each vehicle **100A**, **100B**).

(56) In embodiments, each of the first and second materials handling vehicle **100A**, **100B** are sensed to be constrained within an aisle, which may be a very-narrow aisle (VNA) in a warehouse, for example, such as when both vehicles are actively being wire guided. When each of the first and second materials handling vehicle **100A**, **100B** are sensed to be constrained within an aisle, each vehicle position processor **202** may be configured to independently determine an angle offset from a shared parallel structure, such as racking, embedded magnetic wires, and the like, and adjust a relative angle based on the angle offset and relative pose between the vehicles **100** to a closest angle configured to place the vehicles **100** in parallel. Thus, when each of the first and second materials handling vehicle **100A**, **100B** are wire guided, at least one or each vehicle position processor **202** is configured to adjust a relative angle based on the relative pose between the vehicles **100** to a closest angle configured to place the vehicles **100** in parallel. The angular offset may thus be used to correct the angle component of the relative pose for potential higher accuracy. Further, additional vehicle information can be sent in the locating signals. For man-up vehicles that have antennas mounted on the movable platform, such information may include lift height used for determining an accurate range from the two-way-ranging algorithm. Multiple systems may re-use some of these UWB signals for their own measurement of relative poses. A single UWB message may be used by multiple remote vehicle systems to calculate relative poses simultaneously where, for example, multiple associated timing information is sent for multiple respective vehicle systems. Further, integration and transfer of lift height information between the Systems A and B may allow for the placement of antennas of the Systems A and B on the lifting portions of the materials handling vehicles **100** on which the systems are respectively mounted.

(57) The system **200** utilizing the UWB system **170** of FIG. **1C** may operate with only one side having an antenna array. Such a mode may be utilized for pedestrian tracking applications such as through an ability to degrade to support pedestrians without utilizing an antenna array and/or with the relative position observation configuration of FIG. **1C** when an operating compartment is at a height such that an associated UWB antenna array has a blindspot due to the operating compartment height. The process employed for the UWB system **170** is similar to the process **300** described with respect to the UWB system **160** except single antenna System B does not measure or respond with an angle of arrival. System A will only have the relative position of single antenna System B and thus will not be able to sense the direction the system is facing to determine an orientation and thus pose of System B. Further, System B will only be able to determine a relative distance between the two systems.

(58) With respect to the UWB system **170** of FIG. **1C**, blocks **302**, **304** may be utilized. Single antenna System B transmits a UWB signal to System A (e.g., UWB system **150A**) in block **302**. System A responds with a UWB signal transmitted to the single antenna System B including information such as angle of arrival θ and timing information in block **304**. However, as System B is a single antenna system and is not calibrated with respect to a center of an antenna array and a

center of a materials handling vehicle, System A is configured to measure a relative position (and not orientation) of System B, and System B measures a relative distance d to System A.

(59) In some embodiments described herein, such as with respect to the UWB system **160** of FIG. **1B**, the system **200** utilizing the UWB system **160** does not require UWB radios mounted to infrastructure to operate but rather mounts UWB antenna arrays as UWB Systems **150A**, **150B** to respective materials handling vehicles **100**. Such a vehicle mounting system not dependent on infrastructure mounting may reduce a complexity of a commissioning process of a new installation and avoid expensive infrastructure installation and mapping exercises. Such a vehicle mounting system may further add confidence to safe control of the vehicles as a remote server is not required to be involved in sensing other vehicles. Further, through relative pose sensing between vehicles using the UWB Systems **150A**, **150B** respectively mounted to materials handling vehicles **100**, a relative pose in addition to a distance of one system to another may be sensed to provide more accurate pose determination and lead to less false positive triggers of detection of hazardous situations (e.g., a pair of vehicles **100** being determined to be too close to one another and at risk of collision).

(60) The sensing methods per the UWB systems described herein enables control of a materials handling vehicle **100** employing a UWB system **150** based on the determined position and orientation (e.g., pose) of other materials handling vehicles **100**. Such control enables more accurate identification of hazardous scenarios and limitation of speed only when required to keep false triggers of the system to a minimum. The UWB systems also enable small data transfers between the systems of the materials handling vehicles **100** for use in identifying hazardous scenarios.

(61) As described in greater detail below with respect to FIGS. **4-8**, the UWB systems described herein may further be used to achieve accuracy of materials handling vehicle intrusion protection through detecting and taking control of actions on overlapping fields via the UWB radio system mounted to each vehicle. A UWB radio system **150** mounted on a materials handling vehicle **100** is configured to sense other materials handling vehicles **100** in an immediate area that could potentially intrude on a current path of the materials handling vehicle **100**. The UWB radio system **150** may further be configured to determine which of the detected materials handling vehicles **100** would, given a respective current trajectory, be likely to lead to an overlap of field zones and a potential hazardous scenario such as a collision between the vehicles. As a non-limiting example, another vehicle **100** intruding on the path of the materials handling vehicle **100** may be likely to lead to collision. The system **200** may utilize vehicle controllers communicatively coupled to the UWB radio system **150** of respective vehicles **100** to enforce a control action on one or both systems **150** to reduce a risk of the hazardous scenario. Such a control action may be lowering the travel speed of or stopping a vehicle **100** altogether.

(62) The relative poses of neighboring vehicles **100** that the UWB localization system described herein produces may each be used as an input for a performance rated system of hardware and software as described herein that execute various safety functions to detect hazardous scenarios and command the necessary control actions of vehicles **100**.

(63) Referring to FIG. **4**, a materials handling vehicle **100** is shown with one or more fields **400**. To detect such hazardous scenarios, a hazardous scenario likelihood may be based on a current trajectory of a materials handling vehicle **100** and the one or more fields **400** of the materials handling vehicle **100**, which fields may overlap. The one or more fields **400** may also be referenced as zones herein. The one or more fields **400** are dynamic virtual boundaries outlining peripheries of virtual zones surrounding the materials handling vehicle **100**. The dynamic virtual boundaries are adjustable such that field shapes and/or sizes are selected based on velocity, steer wheel measurements, or combinations thereof with respect to the materials handling vehicle. In embodiments, field shapes and/or sizes may be selected from predefined sets based on velocity, steer wheel values, or combinations thereof for the materials handling vehicle **100**. The shape and

dimensions of the one or more fields **400** may change based on a current speed of the materials handling vehicle **100**, steer wheel angle, wire-guidance engagement status, lift height, or combinations thereof. A distinct set of these fields **400** may be pre-programmed and pre-loaded on the systems described herein. In embodiments, the one or more fields may be calculated in real-time.

(64) With respect to FIG. **4**, the materials handling vehicle **100** includes an awareness zone **402**, a slow field **404**, and a stop field **406** of decreasing surface area and periphery surrounding the materials handling vehicle **100**. The stop field **406** overlaps with a portion of the larger slow field **404**. Both the stop field **406** and the slow field **404** are within the awareness zone **402**. Thus, in embodiments, the stop field overlaps with a portion of the slow field, the slow field being larger than the stop field. The stop field and the slow field may both be within the awareness zone **402**. The awareness zone **402** is representative of a zone about (e.g., surrounding) the materials handling vehicle **100** in which the materials handling vehicle is configured to detect one or more field infringements, obstacles, or combinations thereof. Such obstacles may be virtual fields, another materials handling vehicle **100**, or combinations thereof.

(65) The stop field **406** may be configured to cover an area swept via a sensing by the materials handling vehicle **100** when traveling at a minimum limited speed such that the system or operator can safely stop the materials handling vehicle **100** to a stop. The slow field **404** may be defined as an area on top of and greater than the stop field **406** that is swept via a sensing by the materials handling vehicle **100** to decelerate to a minimum limited speed. Thus, the stop field **406** may be representative of an area for vehicular travel at a minimum speed limit and the slow field **404** is representative of an area of vehicular travel in which the respective materials handling vehicle **100** would be reduced to the minimum speed limit. The slow field **404** and the stop field **406** may be configured to cooperate to reduce a likelihood of a hazardous situation by alerting an operator of the materials handling vehicle **100**, automatically slowing or stopping the vehicle **100**, or combinations thereof.

(66) In embodiments, and as described in greater detail below with respect to FIG. **5**, the vehicle position processor **202** is configured to determine a first virtual field for the first materials handling vehicle **100A** and a second virtual field for the second materials handling vehicle **100B**, determine a field infringement occurrence when a portion of the first virtual field overlaps a portion of the second virtual field based on the relative pose, and operate at least one of the first and second materials handling vehicles **100A**, **100B** based on the field infringement occurrence. In embodiments, and as described in greater detail below, at least one of the first and second materials handling vehicles **100A**, **100B** may be configured to slow or stop based on the field infringement occurrence.

(67) Referring to FIG. **5**, field infringement of a materials handling vehicle **100A** by another materials handling vehicle **100B** or field **400B** of the other materials handling vehicle **100B** that infringes upon a portion of a field **400A** may be detected by the system **200**. The materials handling vehicles **100A**, **100B** may be traveling along respective trajectories as represented by directional arrows **D1**, **D2**.

(68) The location data described herein contains relative pose information between two vehicle systems. With such vehicle pose information, both vehicles can operate with respective small detection fields than relying on range data alone that may be provided by other UWB solutions and therefore trigger fewer false positives. The other UWB solutions relying on range data alone may generate large detection fields prone to false positive detection. The UWB systems described herein minimize a detection field geometry of a respective vehicle **100** to an extent that the field **400** remains long enough for the required stopping distance. Additionally, a factor of safety may be input, and the field **400** can be shaped to cover only an area the vehicle **100** will travel through. A weight, velocity of the vehicle **100**, velocity, acceleration profiles, brake performance coefficients, and predicted system latency, or combinations thereof, may be utilized to determine a required

stopping distance of the vehicle **100**. A field enforcement system **200** as described herein may use the velocity, steer wheel angle, wire guidance status, fork height, or combinations thereof as an input to generate or look-up a set of predefined field shapes for the field **400** required to safely avoid hazards. Each of the first and second virtual fields may be one of a static field or a dynamic field. The dynamic field may be configured to adjust size, shape, or both based on vehicle velocity, relative pose, steer direction, fork or operator compartment lift height, wire guidance status, vehicle model type, load weight, or combinations thereof.

(69) The UWB field enforcement system **200** described herein can also detect and reduce the risk of certain scenarios that a laser-based system alone may be unable to detect until it was too late. Such laser-based solutions alone may require sensing of a physical obstacle before a control action can be applied, which sensor limitation may lead to fields that are much larger than needed for the UWB field enforcement system **200** for hazard reduction. Thus, the UWB field enforcement system **200** described herein is configured to sense virtual obstacles such as a field infringement by overlapping virtual fields of a pair of materials handling vehicles **100A**, **100B** as shown in FIG. 5.

(70) In the embodiment shown in FIG. 5, the materials handling vehicle **100A** may be traveling along directional arrow D1 in an aisle defined between warehouse racking to exit the aisle at an aisle end, and the materials handling vehicle **100B** may be traveling in a perpendicular direction defined by directional arrow D2 approaching the aisle end such that a field infringement is possible between the vehicles **100A**, **100B**.

(71) The field infringement of fields **400A**, **400B** of the materials handling vehicles **100A**, **100B** is shown as an overlapping field infringement **410** in FIG. 5. The system **200** described herein may use the relative position and/or pose of the other materials handling vehicle **100B**, as supplied by a UWB location system **150**, and reported fields **400B** of the other materials handling vehicle **100B** to place the fields **400A**, **400B** relative to one-another and check for infringement. Such an infringement check may be a simple intersection check between the one or more fields **400A**, **400B** of each of the materials handling vehicles **100A**, **100B**. In embodiments, each field **400** only infringes with like fields. Thus, the stop field **406** infringes only with other stop fields, and the slow field **404** infringe only with other slow fields. Hence, the field infringement occurrence may be determined when the portion of the first virtual field overlapping the portion of second virtual field comprise matching field types comprising an awareness field type, a slow field type, and a stop field type. In embodiments, each of the first and second virtual fields may include a field type, which may be a slow field, or a stop field.

(72) Once a field infringement has been detected by a materials handling vehicle **100**, the onboard hardware and software may emit proper control signals for the materials handling vehicle **100** to avoid collision. In embodiments, other vehicle systems that are also running similar algorithms may be likewise detected and have begun respective control actions. In an event that an error leads to the other vehicle **100** not detecting infringement, the vehicles **100** may monitor an infringement status of neighboring vehicles **100**. If another vehicle **100** reports that respective fields of the vehicle **100** are infringing onto the fields of a materials handling vehicle **100**, the materials handling vehicle **100** may also begin control actions as if the materials handling vehicle **100** had detected the infringement.

(73) Referring to FIG. 6, the overlapping field infringement **410** may include overlapping portions of at least two fields **400** of the materials handling vehicles **100A**, **100B**. As a non-limiting example, the overlapping field infringement **410** may include overlapping portions of stop fields **406** and the slow fields **404** of each of the materials handling vehicles **100A**, **100B**.

(74) The UWB field enforcement system **200** described herein may work within a predefined range of safe speed limit enforcement set points that can be configured, such as by an end user or a service technician. A combination of the stop field **406** and the slow field **404** and system behavior in each field **406**, **404** and detection of overlap with virtual obstacles such as other virtual vehicle fields **400** as described herein aids to give an operator enough time to act. For example, the

operator may have enough time to act and reduce a risk of the hazard by slowing the vehicle **100** rather than having to completely stop the vehicle **100**.

(75) In embodiments, an overlapping of any two slow fields **404** of vehicles **100A**, **100B** may lead to a safely controlled deceleration of both vehicles **100A**, **100B**. The overlapping of any two stop fields **406** of vehicles **100A**, **100B** may lead to a controlled braking of the traction control motor of at least one of the vehicles **100A**, **100B** so to come to either a stop or to slow to a set speed. In an embodiment, a field infringement occurrence may be determined based on an overlap of the stop fields **406**, and the first and second materials handling vehicles **100A**, **100B** are each configured to decelerate based on the field infringement occurrence. When the field infringement occurrence is determined based on an overlap of the stop fields **406** for each the first and second materials handling vehicles **100A**, **100B**, at least one of the first and second materials handling vehicles **100A**, **100B** may be set to operate at a maximum speed of 1.0 or 0.5 miles per hour based on the overlap.

(76) Referring to FIG. 7, different types of field overlap are shown between a pair of materials handling vehicles **100A**, **100B**. In FIG. 7, a control zone is depicted as the stop field **406** and a deceleration zone is depicted as the slow field **404**. A larger awareness zone **402** encompasses both the control zone and the deceleration zone. Vehicle restrictions may be set when infringement is detected in the control zone and the deceleration zone. In embodiments, for the control zone, a sensed field infringement may result in maintaining a maximum speed such as 1.0 miles per hour (mph) for the vehicle **100**. The control zone as the stop field **406** may be static and of a fixed size and shape. In other embodiments, the control zone may be dynamic. For the deceleration zone as the slow field **404**, a sensed field infringement may result in progressively reducing vehicle speed to the maximum speed of 0.5 mph as distance to a closest vehicle **100** sensed by the field infringement decreases. In an embodiment, the deceleration zone may be dynamic to adjust size and/or shape of the slow field **404** based on vehicle velocity and steer direction. For the awareness zone **402**, a sensed field infringement may not affect behavior of the vehicle **100** but may be used to trigger internal communication within the vehicle **100**, external communication with other systems or vehicles **100**, or combinations thereof. In embodiments, the awareness zone **402** may be replaced by specific conditions utilizing UWB data sensed by the UWB systems **150** as described herein.

(77) Thus, the different types of field overlap of FIG. 7 between a pair of materials handling vehicles **100A**, **100B** may trigger different vehicle reactions. In an Out of Zone scenario, none of the fields **400** of the vehicles **100A**, **100B** overlap and rather are spaced by a non-overlap area **408**. In an Awareness Zone Overlap scenario, a pair of awareness zones **402** of the vehicles **100A**, **100B** overlap as an overlapping field infringement **410A** to trigger internal and/or external communications. In a Deceleration Zone Overlap scenario, a pair of deceleration zones (e.g., slow fields **404**) of the vehicles **100A**, **100B** overlap as an overlapping field infringement **410B** to progressively reduce vehicle speed to a maximum speed. In a Control Zone Overlap scenario, a pair of deceleration zones (e.g., stop fields **406**) of the vehicles **100A**, **100B** overlap as an overlapping field infringement **410B** to maintain the maximum speed, stop at least one of the vehicles **100A**, **100B**, or redirect at least one of the vehicles **100A**, **100B** to avoid collision.

(78) Referring to FIG. 8, a display **500** of a materials handling vehicle **100** of the inventory transit surface **122** is shown. The display **500** includes a display on a graphical user interface (GUI) **502** of the one or more fields **400** of the materials handling vehicle **100** such as the awareness zone **402**, the slow field **404**, and the stop field **406**. The display **500** may display a current field infringement as quadrants on the GUI **502** to give an operator a clear and quick reference to a direction of the infringing vehicle **100**. The display **500** further includes operational information **504** of the materials handling vehicle shown on the GUI **502**, which operational information may be used to dynamically adjust field shape as described herein. The operational information **504** displayed may include current speed and steer wheel angle, and a vehicle assigned slow field identification and

stop field identification.

(79) The field enforcement systems for materials handling vehicles as described herein may also be used in a very narrow aisle (VNA) warehouse as the warehouse house **110** that may include one or more powered industrial trucks as the materials handling vehicles **100** described herein.

(80) Referring to FIG. **9**, a materials handling vehicle **100A** is shown including a first mounted UWB antenna array system that includes a plurality of enclosures **902** mounted on a vehicle frame **906** such as an overhead guard via supporting elements **904**. Each enclosure **902** includes a UWB antenna disposed therein. Each enclosure **902** or other enclosures as described herein may represent a node. Thus, the first and second UWB antenna arrays as described herein may include one or more nodes, each node comprising a UWB antenna arranged and positioned in the respective UWB antenna array and mounted on the vehicle body such that a center of the respective UWB antenna array is calibrated with respect to a center of the respective materials handling vehicle **100** on which the respective UWB antenna array is mounted.

(81) The supporting elements **904** may extend from portions of the vehicle frame **906** or other vehicle portions in various angles or shapes. In FIG. **9**, the support elements **904** extend in a vertical upward direction from corners of the vehicle frame **906** shown as an overhead guard. The supporting elements may be made of the same material as the overhead guard **906**, such as fabricated steel, to have the same level of durability and sturdiness. The enclosures **902** may be transparent and formed from various non-occlusive materials, such as glass-filled nylon, rigid structural plastic, polyethylene, fiberglass, various rubber coated materials, non-metallic and non-ferrous materials, and the like to prevent occlusion of the signals from and to the UWB antennas disposed therein.

(82) Each UWB antenna described herein includes a PCB including a PCB longitudinal axis, an antenna feature comprising an antenna longitudinal axis aligned in parallel with (as shown in and described below for FIG. **12-13**) or perpendicular to (as shown in and described below for FIG. **10**) the PCB longitudinal axis, and an antenna enclosure shaped and sized to receive the PCB and the antenna feature. For instance, FIG. **10** shows an embodiment of a UWB antenna that may be disposed in an enclosure **902** of FIG. **9**. The UWB antenna includes an antenna feature **1000** and a printed circuit board (PCB) **1010**. The antenna feature **1000** is configured to transmit and receive signals, such as UWB signals, from other antennas. The PCB **1010** is configured to analyze and/or process the signals. The antenna feature **1000** includes an antenna longitudinal axis aligned perpendicular to the PCB longitudinal axis.

(83) In FIG. **11**, a materials handling vehicle **100B** is shown including a second mounted UWB antenna array system that has a plurality of enclosures **1102**. One or more of the enclosures **1102** may be mounted on an overhead guard **1104**, while other enclosures **1102** may be positioned at various other vehicle locations, such as on a power unit module **1106** or on a mast crossbrace **1108** of the materials handling vehicle **100B**.

(84) In FIG. **12**, a first type of UWB antenna disposed in a first type of enclosure **1102** is shown along with an interior of the enclosure **1102** of FIG. **11**. The enclosure **1102** includes a front cover **1202**, a back cover **1204**, a PCB **1404**, an antenna feature **1406**, and connector port housings **1206**. The back cover **1204** is configured to attach to the front cover **1202**. At least one of the back cover **1204** and the front cover **1202** may include curved wall portions defining at least a portion of an aperture sized and shaped to receive the connector port housings **1206**. The antenna enclosures described herein may thus include a wall defining a pair of apertures to receive mounting prongs as the connector port housings **1206** extending from the PCB **1404**. When the wall longitudinal axis of wall is disposed perpendicular to with the PCB longitudinal axis as shown in FIG. **12**, the mounting prongs extend in parallel with the PCB longitudinal axis to mount to the vehicle body at a zero-degree angle. When a wall longitudinal axis of wall is disposed in parallel with the PCB longitudinal axis as shown in FIG. **13**, the mounting prongs extend perpendicular to the PCB longitudinal axis to mount to the vehicle body at a ninety-degree angle.

(85) Referring again to FIG. 12, both the back cover **1204** and the front cover **1202** include curved wall portions defining at least a portion of an aperture such that, when attached, a pair of apertures at an end of the enclosure **1102** is sized and shaped to receive the connector port housings **1206**. The connector port housings **1206** are shown to attach directly to the PCB **1404**, which includes tapered portions **1408** on upper side walls. The antenna feature **1406** is shown to be positioned at an apex above the tapered portions **1408** along a PCB longitudinal axis. The antenna feature **1406** includes an antenna longitudinal axis aligned in parallel with the PCB longitudinal axis. The shape and positioning of the tapered portions **1408** and antenna feature **1406** aid to provide a teardrop shape, which a teardrop shape of the enclosure **1102** is sized and shaped to receive, to prevent or reduce signal interference. Each UWB antenna comprising the antenna feature **1406** with the antenna longitudinal axis aligned in parallel with the PCB longitudinal axis may include a teardrop shape included tapered in sidewalls (e.g., the tapered portions **1408**) of the PCB **1404** with the antenna feature **1406** disposed at a shortest end (e.g., apex) of the tapered sidewalls. The connector port housings **1206** may include connectors configured to be mounted or connected to external electrical connectors that may be positioned on various parts of the materials handling vehicle **100B** as described herein.

(86) In FIG. 13, a second type of UWB antenna disposed in a second type of enclosure **1102** is shown along with an interior of the enclosure **1102** of FIG. 11. The enclosure **1102** in FIG. 13 includes a front cover **1302**, a back cover **1304**, the PCB **1404**, the antenna feature **1406**, and connector port housings **1306**. The back cover **1304** is configured to attach to the front cover **1302**. In FIG. 13, the back cover **1304** includes a pair of apertures sized and shaped to receive the connector port housings **1306**. The connector port housings **1306** are shown to attach directly to the PCB **1404**, which includes tapered portions **1408** on upper side walls. Similar to FIG. 12, the antenna feature **1406** is shown to be positioned at an apex above the tapered portions **1408** along a PCB longitudinal axis.

(87) Referring to FIG. 14A, a first set of lighting component modules mounted to a materials handling vehicle **100** is shown. In FIG. 15A, a first lighting component module **1402A** to mount to a materials handling vehicle **100**, such as represented in FIG. 14A, is shown. Referring to FIG. 14B depicts a second set of lighting component modules mounted to a materials handling vehicle **100** is shown. In FIG. 15B, a second lighting component module **1402B** to mount to a materials handling vehicle **100**, such as represented in FIG. 14B, is shown.

(88) Each lighting component module **1402A**, **1402B** may be configured to mount to the vehicle body of the materials handling vehicle **100**. Each lighting component module **1402A**, **1402B** may include a plurality of symbols including at least a first symbol with a first color representative of vehicle operation without error, a second symbol with a second color representative of a cautionary vehicle warning operation, and a third symbol with a third color representative of a negative vehicle warning operation. In an embodiment, the first color is green, the second color is yellow, and the third color is red. The lighting component module **1402A**, **1402B** may be configured to generate an associated alert based on whether the first symbol, second symbol, or third symbol is lit. The first symbol may be configured to be lit in green as the first color and may be a proceed line portion (shown as the bottom symbol in FIGS. 15A-15B though able to be any of the top, middle, or bottom positions). The second symbol may be configured to be lit in yellow (or amber) and may include a caution triangular portion (shown as the top symbol in FIGS. 15A-15B though able to be any of the top, middle, or bottom positions). The third symbol may be configured to be lit in red and may include a block warning portion (shown as the middle symbol in FIGS. 15A-15B though able to be any of the top, middle, or bottom positions).

(89) Referring to FIGS. 14A and 15A, the light component module **1402A** may be attached to an overhead guard mounting component **1408**, which may be utilized to mount or attach the light component module **1402A** to an overhead guard **1400** extending from frame **1406** or to another portion of the materials handling vehicle **100**. The overhead guard mounting component **1408** may

include a curved part **1500** (FIG. 15A) that may be made of metal and is attached to a plate **1502** that may be metal such that the plate **1502** is positioned along a plane perpendicular to a plane intersecting the curved part **1500**. A bottom portion of the plate **1502** may be configured to be adhered or attached directly onto various portions of the materials handling vehicle **100**.

(90) Referring to FIGS. 14B and 15B, the light component module **1402B** may be attached to an overhead guard mounting component **1508**, which may be utilized to mount or attach the light component module **1402B** to another portion of the materials handling vehicle **100** such as a mast crossbrace **1404**. The overhead guard mounting component **1508** may include a portion **1510** (FIG. 15B) that may be made of metal and that may be attached to the light component module **1402B** and a side plate **1512** that extends in a lateral direction from the portion **1510** and includes multiple apertures **1514**. The side plate **1512** may be configured to be fastened to a portion of the materials handling vehicle **100** through one or more fasteners, such as fasteners received through the apertures **1514** to fasten the side plate **1512** to the portion of the materials handling vehicle **100**.

(91) The systems described herein may support vehicle to vehicle ranging applications in addition to vehicle to anchor ranging applications between a vehicle **100** and landmarks such as discrete beacons mounted to facility infrastructure. The systems described herein may further provide vehicle zone-based control based on a vehicle localization based on a constellation map of beacons mounted to facility infrastructure to determine vehicle control in one or more zones Z (FIG. 1). The zones Z may be configured as local where the respective beacons' relative position or pose is sensed as described herein. Using data passed between the devices during the localization operations, a defining of a zone Z and location offset from the respective beacon may be communicated independent of any computation of the vehicle location relative to the warehouse. The systems described herein may also support vehicle to pedestrian ranging applications between a vehicle **100** and discrete UWB tags inserted and powered within pedestrian personal protective equipment, wearable items, or reflective vest.

(92) The systems described herein may enable the vehicle systems to identify certain hazardous situations involving vehicle to vehicle interactions and command preventative actions accordingly, such as either slowing or stopping vehicle velocity. The systems accurately and dynamically utilize field shapes with respect to the materials handling vehicles **100** to reduce a false triggering rate of other UWB systems not dependent on relative pose and to protect against situations including virtual field overlaps that are undetectable by laser systems alone.

(93) For the purposes of describing and defining the present invention, it is noted that reference herein to a variable being a “function” of or “based on” a parameter or another variable is not intended to denote that the variable is exclusively a function of or “based on” the listed parameter or variable. Rather, reference herein to a variable that is a “function” of or “based on” a listed parameter is intended to be open ended such that the variable may be a function of a single parameter or a plurality of parameters.

(94) It is also noted that recitations herein of “at least one” component, element, etc., should not be used to create an inference that the alternative use of the articles “a” or “an” should be limited to a single component, element, etc.

(95) It is noted that recitations herein of a component of the present disclosure being “configured” or “programmed” in a particular way, to embody a particular property, or to function in a particular manner, are structural recitations, as opposed to recitations of intended use. More specifically, the references herein to the manner in which a component is “configured” or “programmed” denotes an existing physical condition of the component and, as such, is to be taken as a definite recitation of the structural characteristics of the component.

(96) Having described the subject matter of the present disclosure in detail and by reference to specific embodiments thereof, it is noted that the various details disclosed herein should not be taken to imply that these details relate to elements that are essential components of the various embodiments described herein, even in cases where a particular element is illustrated in each of the

drawings that accompany the present description. Further, it will be apparent that modifications and variations are possible without departing from the scope of the present disclosure, including, but not limited to, embodiments defined in the appended claims. More specifically, although some aspects of the present disclosure are identified herein as preferred or particularly advantageous, it is contemplated that the present disclosure is not necessarily limited to these aspects.

Claims

1. A field enforcement system comprising a first materials handling vehicle, and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body and a vehicle position processor, wherein: the first and second materials handling vehicles are configured to navigate a vehicle transit surface in a warehouse environment; the first materials handling vehicle comprises a first ultra-wideband (UWB) antenna array mounted to the vehicle body, the first UWB antenna array comprising at least two antennas and a first UWB antenna array center; the second materials handling vehicle comprises a second UWB antenna array mounted to the vehicle body, the second UWB antenna array comprising at least two antennas and a second UWB antenna array center; and each vehicle position processor is configured to: transmit respective UWB signals comprising vehicle information including center information of the first UWB antenna array center and the second UWB antenna array center between respective UWB antenna arrays of the first and second materials handling vehicles; determine a relative pose comprising position and orientation of each of the first and second materials handling vehicles with respect to each other based on the respective transmitted UWB signals comprising the vehicle information and measurements based on the center information of the first UWB antenna array center and the second UWB antenna array center; determine a first virtual field for the first materials handling vehicle and a second virtual field for the second materials handling vehicle based on the respective transmitted UWB signals comprising the vehicle information; determine a field infringement occurrence when a portion of the first virtual field overlaps a portion of a second virtual field based on the determined relative pose of each of the first and second materials handling vehicles; and operate at least one of the first and second materials handling vehicles based on the field infringement occurrence.
2. The field enforcement system of claim 1, wherein each of the first and second virtual fields comprise one of a static field or a dynamic field, wherein the dynamic field is configured to adjust size, shape, or both based on vehicle velocity, relative pose, steer direction, fork or operator compartment lift height, wire guidance status, vehicle model type, load weight, or combinations thereof.
3. The field enforcement system of claim 1, wherein the field infringement occurrence is determined when the portion of the first virtual field overlapping the portion of second virtual field comprise matching field types comprising an awareness field type, a slow field type, and a stop field type.
4. The field enforcement system of claim 1, wherein each of the first and second virtual fields comprise a field type, the field type comprising, a slow field, and a stop field.
5. The field enforcement system of claim 4, wherein the stop field overlaps with a portion of the slow field, the slow field being larger than the stop field.
6. The field enforcement system of claim 4, wherein the stop field and the slow field are both within an awareness zone, and the awareness zone is representative of a zone surrounding the respective materials handling vehicle in which the materials handling vehicle is configured to detect one or more field infringements.
7. The field enforcement system of claim 6, wherein the stop field is representative of an area for vehicular travel at a minimum speed limit and the slow field is representative of an area of vehicular travel in which the respective materials handling vehicle would be reduced to the minimum speed limit.

8. The field enforcement system of claim 4, wherein the field infringement occurrence is determined based on an overlap of the slow fields, and the first and second materials handling vehicles are each configured to decelerate based on the field infringement occurrence.
9. The field enforcement system of claim 4, wherein when the field infringement occurrence is determined based on an overlap of the stop fields for each the first and second materials handling vehicles, at least one of the first and second materials handling vehicles is set to operate at a maximum speed of 1.0 miles per hour based on the overlap.
10. The field enforcement system of claim 1, wherein at least one of the first and second materials handling vehicles is configured to slow or stop based on the field infringement occurrence.
11. The field enforcement system of claim 1, wherein each node of the first UWB antenna array and the second UWB antenna array comprises a UWB antenna arranged and positioned in the respective UWB antenna array and mounted on the vehicle body such that the center of the respective UWB antenna array is calibrated with respect to a center of the respective materials handling vehicle on which the respective UWB antenna array is mounted.
12. The field enforcement system of claim 11, wherein each UWB antenna comprises a printed circuit board (PCB) including a PCB longitudinal axis, an antenna feature comprising an antenna longitudinal axis aligned in parallel with or perpendicular to the PCB longitudinal axis, and an antenna enclosure shaped and sized to receive the PCB and the antenna feature.
13. The field enforcement system of claim 12, wherein each UWB antenna comprising the antenna feature with the antenna longitudinal axis aligned in parallel with the PCB longitudinal axis comprises a teardrop shape, the teardrop shape comprising tapered in sidewalls of the PCB with the antenna feature disposed at a shortest end of the tapered sidewalls.
14. The field enforcement system of claim 12, wherein the antenna enclosure comprises a wall defining a pair of apertures to receive mounting prongs extending from the PCB, such that when a wall longitudinal axis of wall is disposed in parallel with the PCB longitudinal axis, the mounting prongs extend perpendicular to the PCB longitudinal axis to mount to the vehicle body at a ninety-degree angle, and when the wall longitudinal axis of wall is disposed perpendicular to with the PCB longitudinal axis, the mounting prongs extend in parallel with the PCB longitudinal axis to mount to the vehicle body at a zero-degree angle.
15. The field enforcement system of claim 1, further comprising one or more lights configured to mount to the vehicle body, the one or more lights comprising a plurality of symbols, the plurality of symbols comprising at least a first symbol with a first color representative of vehicle operation without error, a second symbol with a second color representative of a cautionary vehicle warning operation, and a third symbol comprising a third color representative of a negative vehicle warning operation.
16. The field enforcement system of claim 15, wherein the first color is green, the second color is yellow, and the third color is red, and wherein the one or more lights are configured to generate an associated alert based on whether the first symbol, second symbol, or third symbol is lit.
17. A field enforcement system comprising a vehicle position processor, a first materials handling vehicle, and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body, wherein: the first and second materials handling vehicles are configured to navigate a vehicle transit surface in a warehouse environment; the first materials handling vehicle comprises a first ultra-wideband (UWB) antenna array mounted to the vehicle body, the first UWB antenna array comprising at least two antennas and a first UWB antenna array center; the second materials handling vehicle comprises a second UWB antenna array mounted to the vehicle body, the second UWB antenna array comprising at least two antennas and a second UWB antenna array center; and the vehicle position processor is configured to: transmit respective UWB signals comprising vehicle information including center information of the first UWB antenna array center and the second UWB antenna array center between respective UWB antenna arrays of the first and second materials handling vehicles; determine a relative pose comprising position and orientation of each

of the first and second materials handling vehicles with respect to each other based on the respective transmitted UWB signals comprising the vehicle information and measurements based on the center information of the first UWB antenna array center and the second UWB antenna array center; determine a first virtual field for the first materials handling vehicle and a second virtual field for the second materials handling vehicle based on the respective transmitted UWB signals comprising the vehicle information; determine a field infringement occurrence when a portion of the first virtual field overlaps a portion of the second virtual field based on the determined relative pose of each of the first and second materials handling vehicles; and operate at least one of the first and second materials handling vehicles based on the field infringement occurrence.

18. The field enforcement system of claim 17, wherein the field infringement occurrence is determined when the portion of the first virtual field overlapping the portion of second virtual field comprise matching field types comprising an awareness field type, a slow field type, and a stop field type.

19. A method for field enforcement between a first materials handling vehicle and a second materials handling vehicle, each materials handling vehicle comprising a vehicle body, the first materials handling vehicle comprising a first ultra-wideband (UWB) antenna array mounted to the vehicle body, the first UWB antenna array comprising at least two antennas and a first UWB antenna array center, the second materials handling vehicle comprising a second UWB antenna array mounted to the vehicle body, the second UWB antenna array comprising at least two antennas and a second UWB antenna array center, the method comprising: transmitting respective UWB signals comprising vehicle information including center information of the first UWB antenna array center and the second UWB antenna array center between respective UWB antenna arrays of the first and second materials handling vehicles; determining a relative pose comprising position and orientation of each of the first and second materials handling vehicles with respect to each other based on the respective transmitted UWB signals comprising the vehicle information and measurements based on the center information of the first UWB antenna array center and the second UWB antenna array center; determining a first virtual field for the first materials handling vehicle and a second virtual field for the second materials handling vehicle based on the respective transmitted UWB signals comprising the vehicle information; determining a field infringement occurrence when a portion of the first virtual field overlaps a portion of the second virtual field based on the determined relative pose of each of the first and second materials handling vehicles; and operating at least one of the first and second materials handling vehicles based on the field infringement occurrence.
