

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267471

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Schaafsma; Sasha Faye et al.

SYSTEMS AND METHODS FOR NETWORK BASED GEOGRAPHIC ANCHOR SELECTION

Abstract

A method may include identifying, in a network, a location of a Fifth Generation (5G) node and determining, based on the location of the 5G node and capabilities associated with the 5G node, a number of areas around the 5G node, wherein each area corresponds to a bin. The method may also include identifying, in at least some of the of bins, candidate anchor nodes for the 5G node and ranking the candidate anchor nodes based on parameters associated with the candidate anchor nodes. The method may further include selecting, for the 5G node, an anchor node from the candidate anchor nodes based on the ranking.

Inventors: Schaafsma; Sasha Faye (Twin Lake, MI), Robeck; Charles Aaron (Byron, MN), Coyle; Timothy E. (Chicopee, MA), Atkins; Brandon Scott (Evans, GA), Wozich; Zachary S. (Casco, ME)

Applicant: Verizon Patent and Licensing Inc. (Basking Ridge, NJ)

Family ID: 1000008586754

Appl. No.: 19/203256

Filed: May 09, 2025

Related U.S. Application Data

parent US continuation 17713451 20220405 parent-grant-document US 12323818 child US 19203256

Publication Classification

Int. Cl.: H04W16/18 (20090101); H04W64/00 (20090101)

U.S. Cl.:

Background/Summary

RELATED APPLICATION [0001] This patent application is a Continuation of U.S. application Ser. No. 17/713,451 filed on Apr. 5, 2022, titled “Systems and Methods for Network Based Geographic Anchor Selection,” the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND INFORMATION

[0002] User devices associated with a Fifth Generation (5G) New Radio (NR) system may have the capability to communicate via a 5G network, as well as communicate via other networks, such as a Fourth Generation Long Term Evolution (4G LTE) network. For example, an Evolved Universal Terrestrial Radio Access New Radio Dual Connectivity (EN-DC) device has the capability to exchange data with a 4G LTE base station (e.g., an eNode B), as well as exchange data with a 5G next generation base station (e.g., a gNode B).

[0003] However, for a 5G base station to use existing 4G architecture for communications, the 5G base station may need to anchor to a 4G base station. Selecting an appropriate anchor station for a 5G base station is typically based on identifying a 4G base station located closest to the 5G base station.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 illustrates an exemplary environment in which systems and methods described herein may be implemented;

[0005] FIG. 2 is a block diagram of components implemented in one or more of the devices of the environment of FIG. 1 in accordance with an exemplary implementation;

[0006] FIG. 3 illustrates logic components implemented in the anchor selection system of FIG. 1 in accordance with an exemplary implementation;

[0007] FIG. 4 illustrates a home bin and surrounding bins in accordance with an exemplary implementation;

[0008] FIG. 5 illustrates the identification of bins based on radio frequency capabilities of a 5G base station in accordance with an exemplary implementation; and

[0009] FIGS. 6 and 7 are flow diagrams illustrating processing by various components in the environment of FIG. 1 in accordance with an exemplary implementation.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

[0010] The following detailed description refers to the accompanying drawings. The same reference numbers in different drawings may identify the same or similar elements. Also, the following detailed description does not limit the invention.

[0011] Implementations described herein relate to selecting an anchor station for a 5G base station using call records and other metrics associated with 4G base stations located in areas near a 5G base station. For example, in one implementation, a geographic service area associated with a telecommunications service provider may be divided into a grid (e.g., using the Military Grid Reference System (MGRS)) and then subdivided into smaller sections or areas, referred to as geobins or bins. A footprint associated with the radio frequency (RF) capability for the 5G base station may then be used to identify bins and 4G LTE base stations, located in the bins, that may be candidate anchor stations. For each of the identified candidate anchor stations, user equipment

(UE) call records are analyzed to determine “hit counts” associated with a number of communications handled by a particular candidate anchor station, signal strength measurements associated with calls handled by the candidate anchor station, and a distance from the candidate anchor station to the 5G node, as well as other metrics.

[0012] An anchor station for a 5G base station may then be selected based on a ranking of the candidate anchor stations. In some implementations, additional factors may be considered when selecting the anchor station. For example, factors such as whether the 5G base station and 4G LTE base station are collocated (i.e., located at the same location), physical cell identifier (PCI) collision avoidance, or other factors may be considered when selecting an anchor station for a 5G base station to further facilitate the selection of the anchor station.

[0013] FIG. 1 is a diagram of an exemplary environment **100** in which systems and methods described herein may be implemented. Referring to FIG. 1, environment **100** includes user equipment (UE) device **110**, wireless station **120-1** associated with radio access network (RAN) **130-1**, wireless station **120-2** associated with RAN **130-2**, core network **140**, network devices **142**, anchor selection system **144**, and packet data network (PDN) **160**. Wireless stations **120-1** and **120-2** may be referred to herein collectively as wireless stations **120** and individually as wireless station **120** or **120-X**, and RANs **130-1** and **130-2** may be referred to herein collectively as RANs **130** and individually as RAN **130** or **130-X**. In other embodiments, environment **100** may include additional networks, fewer networks, and/or different types of networks than those illustrated and described herein.

[0014] In the configuration illustrated in FIG. 1, UE device **110** may use wireless channels **170-1** and **170-2** (referred to collectively as wireless channels **170**) to access wireless stations **120-1** and **120-2**, respectively. Wireless channels **170** may correspond, for example, to a physical layer in accordance with different radio access technology (RAT) types. For example, wireless channel **170-1** may correspond to the physical layer associated with 4G or 4.5G RAN standards (e.g., 3GPP standards for 4G and 4.5G air interfaces, collectively referred to herein as “4G”), while wireless channel **170-2** may correspond to the physical layer associated with 5G New Radio standards (e.g., 3GPP standards for 5G air interfaces).

[0015] UE device **110** (also referred to herein as UE **110** or user device **110**) may include any type of mobile device having multiple coverage mode capabilities (e.g., EN-DC capabilities) and is able to communicate with different wireless stations (e.g., wireless stations **120-1** and **120-2**) using different wireless channels (e.g., channels **170-1** and **170-2**) corresponding to different RANs (e.g., RANs **130-1** and **130-2**). UE device **110** may be a mobile device that may include, for example, a cellular radiotelephone, a smart phone, a tablet, any type of internet protocol (IP) communications device, a Voice over Internet Protocol (VoIP) device, a personal computer (PC), a laptop computer, a notebook, a netbook, a wearable computer (e.g., a wrist watch, eye glasses, etc.), a gaming device, a media playing device, a digital camera that includes communication capabilities (e.g., wireless communication mechanisms such as Wi-Fi), etc. In other implementations, UE device **110** may include a machine-type communications (MTC) device, an Internet of Things (IoT) device, a machine-to-machine (M2M) device, etc.

[0016] UE device **110** may connect to RANs **130** and other devices in environment **100** via any conventional technique, such as wired, wireless, optical connections or a combination of these techniques. UE device **110** and the person associated with UE device **110** (e.g., the party holding or using UE device **110**) may be referred to collectively as UE device **110** in the description below.

[0017] Wireless stations **120** may each include a network device that has computational and wireless communication capabilities. Wireless stations **120** may each include a transceiver system that connects UE device **110** to other components of RAN **130** and core network **140** using wireless/wired interfaces. Wireless stations **120** may be implemented as a base station (BS), a base transceiver station (BTS), a Node B, an evolved Node B (eNode B), an evolved LTE (eLTE) eNB, a next generation Node B (gNode B), a remote radio head (RRH), an RRH and a baseband unit

(BBU), a BBU, or other type of wireless node (e.g., a picocell node, a femtocell node, a microcell node, etc.) that provides wireless access to one of RANs **130**. Each wireless station **120** may support a RAN **130** having different RAT types. For example, in one implementation, RAN **130-1** may include an E-UTRAN for an LTE network, while RAN **130-2** may include a 5G NR RAN as well as an E-UTRAN for an LTE network. For example, RAN **130-2** may be configured to support communications via both LTE and 5G networks.

[0018] Core network **140** may include one or multiple networks of one or multiple types. For example, core network **140** may be implemented to include a terrestrial network and/or a satellite network. According to an exemplary implementation, core network **140** includes a network pertaining to multiple RANs **130**. For example, core network **140** may include the core part of an LTE network, an LTE-Advanced network, a 5G network, a legacy network, etc.

[0019] Depending on the implementation, core network **140** may include various network elements that may be implemented in network devices **142**. Such network elements may include a mobility management entity (MME), a user plane function (UPF), a session management function (SMF), a core access and mobility management function (AMF), a unified data management (UDM), a PDN gateway (PGW), a serving gateway (SGW), a policy control function (PCF), a home subscriber server (HSS), as well other network elements pertaining to various network-related functions, such as billing, security, authentication and authorization, network policies, subscriber profiles, network slicing, and/or other network elements that facilitate the operation of core network **140**.

[0020] Core network **140** may also include anchor selection system **144**. Anchor selection system **144** may include one or more computing devices that receive inputs regarding call data in environment **100**, signal strength measurements (e.g., Reference Signal Received Power (RSRP)), distance information from a candidate 4G LTE node to a particular 5G base station, as well as other information. Anchor selection system **144** may use this information to select a 4G anchor station for a 5G base station in environment **100**, as described in detail below.

[0021] PDN **160** may include one or more networks, such as a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), a telephone network, the Internet, etc., capable of communicating with UE device **110**. In one implementation, PDN **160** includes a network that provides data services (e.g., via packets or any other Internet protocol (IP) datagrams) to UE device **110**.

[0022] The number and arrangement of devices in environment **100** are exemplary. According to other embodiments, environment **100** may include additional devices (e.g., thousands of UE devices **110**s, hundreds of wireless stations **120**, dozens of RANs, multiple anchor selection systems **144**, etc.) and/or differently arranged devices, than those illustrated in FIG. 1. Environment **100** may also include elements, such as gateways, monitoring devices, network elements/functions, etc. (not shown), that aid in providing data services and routing data in environment **100**.

[0023] Various functions are described below as being performed by particular components in environment **100**. In other implementations, various functions being described as being performed by one device may be performed by another device or multiple other devices, and/or various functions described as being performed by multiple devices may be combined and performed by a single device.

[0024] FIG. 2 illustrates an exemplary configuration of a device **200**. One or more devices **200** may correspond to or be included in devices in environment **100**, such as UE device **110**, wireless station **120**, network device **142**, anchor selection system **144** and/or other devices included in environment **100**. Referring to FIG. 2, device **200** may include bus **210**, processor **220**, memory **230**, input device **240**, output device **250** and communication interface **270**. Bus **210** may include a path that permits communication among the elements of device **200**.

[0025] Processor **220** may include one or more processors, microprocessors, or processing logic that may interpret and execute instructions. Memory **230** may include a random access memory (RAM) or another type of dynamic storage device that may store information and instructions for

execution by processor **220**. Memory **230** may also include a read only memory (ROM) device or another type of static storage device that may store static information and instructions for use by processor **220**. Memory **230** may further include a solid state drive (SSD). Memory **230** may also include a magnetic and/or optical recording medium (e.g., a hard disk) and its corresponding drive. [0026] Input device **240** may include a mechanism that permits a user to input information, such as a keyboard, a keypad, a mouse, a pen, a microphone, a touch screen, voice recognition and/or biometric mechanisms, etc. Output device **250** may include a mechanism that outputs information to the user, including a display (e.g., a liquid crystal display (LCD)), a printer, a speaker, etc. In some implementations, a touch screen display may act as both an input device and an output device.

[0027] Communication interface **260** may include one or more transceivers that device **200** uses to communicate with other devices via wired, wireless or optical mechanisms. For example, communication interface **260** may include one or more radio frequency (RF) transmitters, receivers and/or transceivers and one or more antennas for transmitting and receiving RF data via links **170**. Communication interface **260** may also include a modem or an Ethernet interface to a LAN or other mechanisms for communicating with elements in a network, such as RAN **130** or another network.

[0028] The exemplary configuration illustrated in FIG. 2 is provided for simplicity. It should be understood that device **200** may include more or fewer devices than illustrated in FIG. 2. In an exemplary implementation, device **200** perform operations in response to processor **220** executing sequences of instructions contained in a computer-readable medium, such as memory **230**. A computer-readable medium may be defined as a physical or logical memory device. The software instructions may be read into memory **230** from another computer-readable medium (e.g., a hard disk drive (HDD), SSD, etc.), or from another device via communication interface **260**.

Alternatively, hard-wired circuitry may be used in place of or in combination with software instructions to implement processes consistent with the implementations described herein. Thus, implementations described herein are not limited to any specific combination of hardware circuitry and software.

[0029] FIG. 3 is a functional block diagram of components implemented in anchor selection system **144** in accordance with an exemplary implementation. In one implementation, all or some of the components illustrated in FIG. 3 may be implemented by processor **220** executing software instructions stored in memory **230**. In other implementations, all or some of the components illustrated in FIG. 3 may be implemented in hardware or a combination of hardware, firmware and software used to perform the functionality described below.

[0030] Anchor selection system **144** may include bin identifier **310**, data collector **320**, anchor candidate ranking logic **330**, anchor selection logic **340** and communication logic **350**. In alternative implementations, these components or a portion of these components may be located externally with respect to anchor selection system **144**.

[0031] Bin identifier **310** may include logic to identify a “home” geobin (also referred to as a home bin) corresponding to the location of a 5G wireless station **120**. For example, in one implementation, the Military Grid Reference System (MGRS) may be used to aid in formatting an area associated with a telecommunications service provider into a plurality of bins. The MGRS divides the entire Earth's surface into 100 kilometer (km)×100 km squares/blocks. The MGRS uses three digits to identify a particular grid zone, followed by two digits to identify 100,000 square meter blocks within the zone. Locations within each grid zone may be identified using five digits to identify an east-west position within the zone and five digits to identify a north-south position within the zone.

[0032] In an exemplary implementation, anchor selection system **144** may use MGRS bins that are smaller than the 100 km×100 km squares described above, such as MGRS bins having a size of 100 meters (m)×100 meters. For example, FIG. 4 illustrates a portion of a telecommunications

service provider's service area that includes nine bins, with each bin having a 100 m×100 m size. It should be understood that the actual bin size may be greater or smaller than 100 m×100 m, depending on the particular implementation. In FIG. 4, bin 0 represents a home bin (e.g., a bin in which a 5G wireless station 120, also referred to herein as a 5G node, is located) and bins 1-8 represent surroundings 100 m×100 m bins that may include a 4G LTE wireless station 120 (also referred to as a 4G node).

[0033] In this example, bin 0 is identified based on the known location of a 5G wireless station 120 deployed in environment 100. Bin identifier 310 may then identify a number of bins in proximity or surrounding home bin 0. For example, bin identifier 310 may identify the surrounding bins based on the radio frequency (RF) footprint or RF capabilities/parameters associated with the 5G node, including the orientation, azimuth and beamwidth associated with one or more antennas included in the 5G node and signals transmitted by the 5G node.

[0034] In one implementation, bin identifier 310 may generate an area or arc that falls within the azimuth and beamwidth associated with signals transmitted by the 5G node to identify candidate bins. One or more of the bins/areas may include candidate 4G LTE nodes that may act as anchor stations for the 5G node. For example, FIG. 5 illustrates home bin 0 with a 5G node 502. As illustrated, the azimuth associated with the 5G node is labeled 510. The leading and trailing beamwidths associated with the beams transmitted by 5G node 502, labeled 520 and 522, respectively, are identified based on the overall beamwidth and are located in either direction from the azimuth. For example, the azimuth angle associated with 5G node 502 plus or minus the beamwidth of 5G node 502 in angular degrees divided by two (e.g., azimuth \pm beamwidth/2) may identify a primary arc located between lines 520 and 522 in which bins are identified. That is, bins located between beamwidth leading line 520 and beamwidth trailing line 522 may be identified, as illustrated in FIG. 5.

[0035] Bin identifier 310 may then identify bins in tiers based on the distance from the home bin 0, where bins in the first tier that are located closest to the home bin and located in a forward direction with respect to the leading and trailing beamwidth lines 520 and 522 are labeled with "1"; the bins located in the second tier within the beamwidth are labeled with "2"; etc., up though bins in the fourth tier being labeled with "4." It should be understood that additional tiers of bins may be identified based on the RF capabilities of 5G node 502. For example, bin identifier 310 may traverse the surrounding RF footprint of 5G node 502 in a recursive manner to identify bins within the footprint of 5G node 502. In addition, bins located behind home bin 0 may be associated with a lower tier (e.g., tier 3 in FIG. 5) based on the orientation of the antenna(s) in 5G node 502 facing away from these bins. In each case, the identified bins may then be used to locate potential candidate anchor stations, as described below.

[0036] Data collector 320 may include logic to obtain call related data associated with candidate nodes located in the identified bins. For example, data collector 320 may identify 4G nodes within the identified bins. Data collector 320 may then identify the number of communications (also referred to as hits or a hit count that correspond to voice calls, text communications, etc.) serviced by the identified 4G nodes located in the bins illustrated in FIG. 5 over a period of time (e.g., one day, several days, one week, one month, etc.). Data collector 320 may also identify key performance indicators (KPIs), such as signal strengths associated with the communications. For example, data collector 320 may identify RSRP measurements and/or quality measurements associated with communications serviced by each 4G LTE node. Data collector 320 may also identify the distance of each 4G LTE node from 5G node 502 in home bin 0, as well as other information associated with each 4G LTE node. This information may then be used for ranking the 4G LTE nodes, as described below.

[0037] Anchor candidate ranking logic 330 may rank the 4G candidate nodes located in the bins based on, for example, UE device call records, signal strengths, distance from 5G node 502, etc. In one implementation, the hit count or number of communications serviced by a 4G LTE node in a

particular bin may be weighted more heavily than other factors, such as signal strength, signal quality, distance or other metrics. For example, the hit count may indicate that a particular 4G LTE node received a significant number of communications, which may indicate that the particular 4G node is an appropriate anchor node for 5G node **502** in environment **100**, as described in detail below. In other implementations, other factors may be weighted more heavily or all the factors may be weighted equally based on the particular implementation.

[0038] Anchor selection logic **340** may include logic to select an anchor node for 5G node **502**. For example, based on the rankings from anchor candidate ranking logic **330**, anchor selection logic **340** may select the 4G LTE node having the highest ranking. In an exemplary implementation, other factors may also be used to identify the appropriate anchor node, such as whether a particular 4G LTE node is collocated with 5G node **502**, frequency bands supported by the anchor station, whether the anchor station is capable of avoiding PCI conflicts between neighboring cells or stations, etc., as described below.

[0039] Communication logic **350** may include logic to communicate with devices in environment **100** via wired, wireless or optical mechanisms. For example, communication logic **350** may transmit data, such as anchor selection information to network personnel (not shown).

Communication logic **350** may also receive information from devices in environment **100**, such as devices in core network **140** providing information regarding hit counts, signal strengths, signal quality, distance information, other KPIs, etc. Communication logic **350** may also communicate with other devices in environment **100**. For example, communication logic **350** may include one or more transceivers and one or more antennas for transmitting and receiving RF data, a modem or an Ethernet interface to a LAN or other mechanisms for communicating with elements in a network.

[0040] Although FIG. **3** shows exemplary components of anchor selection system **144**, in other implementations, anchor selection system **144** may include fewer components, different components, differently arranged components, or additional components than depicted in FIG. **3**. In addition, functions described as being performed by one of the components in FIG. **3** may alternatively be performed by another one or more of the components of anchor selection system **144**.

[0041] FIG. **6** is a flow diagram illustrating processing associated with identifying bins associated with anchor selection in accordance with an exemplary implementation. Processing may begin with anchor selection system **144** identifying a home bin associated with a 5G node (block **610**). For example, based on known locations of 5G nodes deployed in environment **100**, anchor selection system **144** may identify a 100 m×100 m home bin using the sub-divided MGRS grid described above. For example, anchor selection system **144** may identify that the location of 5G node **502** is within the bin labeled as home bin **0** in FIG. **5**.

[0042] Anchor selection system **144** may then fan out from home bin **0** based on the RF parameters associated with the 5G node to identify bins of interest (block **620**). For example, as described above with respect to FIG. **5**, bin identifier **310** may scan out from home bin **0** in tiers based on the azimuth and beamwidth of the 5G node. FIG. **5** illustrates identifying four adjacent tiers of bins, labeled as 1-4, with the node in tier 4 located along azimuth **510** and represented by a black circle being approximately 400 meters from 5G node **502**. It should be understood that bin identifier **310** may identify more tiers of bins based on, for example, the RF capabilities (e.g., signal strength, azimuth and bandwidth) of 5G node **502**.

[0043] Anchor selection system **144** may also identify bin relevance for each of the identified bins (block **630**). For example, bin identifier **310** may determine if various bins are within tier 1, tier 2, tier 3 or tier 4 and/or within the beamwidth of 5G node **502** (e.g., between line **520** identified as beamwidth leading and line **522** identified as beamwidth trailing). If a particular bin is not within tiers 1-4 and/or outside the beamwidth, such bins may be dropped from consideration. In other instances, a bin that is in relatively close proximity to being within the beamwidth of 5G node may be included as one of the identified bins, but may be identified as being in a different tier than

adjacent bins that fall within the arc associated with the beamwidth. For example, bin **530** in FIG. 5 may be included as one of the identified bins, but may be identified as being in tier 4, as opposed to tier 2. Bin identifier **310** may then determine and/or verify that all relevant bins are included in the list of identified bins (block **640**). For example, bin identifier **310** may determine that all bins located within a certain proximity of the RF beam footprint of the 5G node (e.g., within or close to within the arc between lines **520** and **522** in FIG. 5) are included in a list of bins that are candidates associated with an anchor node. Once the bins have been identified, anchor selection system **144** may identify candidate anchor stations located in the bins, as described in detail below.

[0044] FIG. 7 is a flow diagram illustrating exemplary processing associated with selecting an anchor node for a 5G node in environment **100**. Processing may begin with anchor selection system **144** collecting call-related data for the identified bins described above with respect to FIG. 6 (block **710**). For example, data collector **320** may collect call records associated 4G LTE nodes located in the identified bins over a period of time, such as one day, several days, one week, one month, etc. The call records may include all communications made to a 4G LTE node in each identified bin. The call records may also include KPIs, such as signal strength measurements (e.g., RSRP), signal quality measurements (e.g., jitter, latency, delay, etc.) and/or other metrics associated with signals received by the 4G LTE node. Using the call records, data collector **320** may generate a hit count identifying the number of communications handled by each 4G LTE node over a period of time and various KPIs associated with the communications. The hit count may be used along with the KPIs to rank candidate nodes.

[0045] Anchor selection system **144** may also average the distance of all 4G LTE nodes from the 5G node (e.g., 5G node **502**) (block **720**). In one implementation, anchor candidate ranking logic **330** may then apply a multiplier to the average distance, such as a multiplier of 1.25, 1.5, etc. (block **720**). For example, assume that the average distance from all the candidate anchor nodes to 5G node **502** is 10 miles and that the multiplier is 1.5, resulting in a modified distance of 15 miles (i.e., 10×1.5). In this case, anchor candidate logic **330** removes any 4G LTE nodes from consideration as the anchor station that are greater than 15 miles from 5G node **502** (block **720**). The removed nodes may be too far from the 5G node to adequately function as an anchor node. Anchor candidate logic **330** may then re-average the distance of the 4G nodes from 5G node **502** based on the remaining 4G LTE nodes (i.e., the 4G LTE nodes that have not been removed from consideration) (block **730**).

[0046] Anchor selection system **144** may also determine if the 5G node is part of a nationwide 5G system or network (block **740**). For example, 5G node **502** may be part of a service provider's 5G network that provides certain guarantees, such as quality of service (QoS), service level agreement (SLA), etc., associated with 5G service. If the 5G node is part of a nationwide service (block **740**—yes), candidate ranking logic **330** may provide supplemental candidate nodes to ensure coverage inclusion (block **750**). For example, candidate ranking logic **330** may ensure that all first tier LTE neighbor nodes are included as candidate nodes. After ensuring that the first tier LTE neighbors are included, or candidate ranking logic **330** determines that the 5G node is not part of nationwide 5G coverage (block **740**—no), candidate ranking logic **330** may rank the candidate nodes (block **760**). For example, candidate ranking logic **330** may use a combination of factors to rank the candidate nodes. These factors may include average UE communication hit count over a period of time, signal strength (e.g., RSRP), signal quality, distance from the 5G node, etc. In one implementation, the average UE hit count over a period of time may be weighted more heavily than other KPIs, such as RSRP, signal quality and/or distance. In other implementations, the weighting may be equal for each factor or other factors may be weighted more heavily based on the particular implementation and service provider requirements.

[0047] In some implementations, anchor ranking logic **330** applies filters to reduce the number of candidate anchor nodes. Filters may, for example, identify an average RSRP of -105 decibel milliwatts (dbm) and identify distance metrics ranging from 200 m or more to 2500 m or more. For

example, in one implementation, a candidate anchor node collocated with 5G node **502** and having an RSRP of greater than -105 dbm may be given a rank of 0, which is the highest rank in this example. In this example, a candidate anchor node that has an RSRP of less than -105 dbm and located more than 2500 m from 5G node **502** may be given a rank of 1, a candidate anchor node that has an RSRP of less than -105 dbm and located more than 1200 m from 5G node **502** may be given a rank of 2, a candidate anchor node that has an RSRP of less than -105 dbm and located more than 500 m from 5G node **502** may be given a rank of 3, and a candidate anchor node that has an RSRP of less than -105 dbm and located more than 200 m from 5G node **502** may be given a rank of 4.

[0048] Anchor ranking logic **330** may also identify other factors, such as special priorities associated with the ranked candidates (block **770**). For example, in one implementation, collocation of a 4G LTE node with a 5G node may be of particular importance. In such a case, a collocated 4G node be ranked with the highest ranking. In other instances, particular frequency bands supported by the candidate nodes may be considered in ranking the candidates. For example, if a particular candidate node does not support a particular frequency band and/or the distance to a particular candidate node in combination with the frequency bands supported by the candidate node does not meet certain criteria, that candidate node may be withdrawn from consideration as an anchor stations.

[0049] In some implementations, a particular vendor's 4G node may have limitations with respect to how many 5G nodes for which the 4G node can act as an anchor. In such cases, a particular candidate anchor node may be eliminated from consideration as an anchor node if the 4G node is potentially functioning as an anchor node for too many 5G nodes. In other instances, a particular 5G node may be a 5G node used in a home/residence and may be given particular importance. In such a case, a network engineer may “whitelist” or select an anchor node for the 5G home node. Still further, PCI conflicts may exist between a 4G candidate anchor node and another 4G node having a same PCI value. In such case, a network engineer and/or anchor candidate ranking logic **330** may determine that the conflict may cause problems and eliminate the candidate node from consideration. Further, in some implementations, candidates with UE call records having a low confidence indicator included in the UE call records may be removed from consideration when determining, for example, UE hit count, RSRP and other K PIs.

[0050] In each case, anchor ranking logic **330** may filter candidate nodes based on the special priorities and additional considerations discussed above (block **770**). Anchor selection logic **340** may then select the anchor node based on the rankings and/or filtering (block **780**). For example, anchor selection logic **340** may select the highest ranked anchor node as the anchor node for 5G node **502**. In this example, anchor selection logic **340** may select the 4G node having a ranking of 0.

[0051] In some implementation, anchor selection logic **340** may forward the selection to the 5G node (e.g., wireless station **120-2**) and/or forward the selection to a network engineer responsible for deploying nodes and/or monitoring environment **100**.

[0052] Implementations described herein identify an anchor station for a 5G base station based on various metrics and/or KPIs associated with the anchor station. Candidate anchor stations may also be filtered based on particular requirements associated with the 5G base station to further facilitate the anchor selection process. As a result, user devices can take advantage of 5G services when the user devices are located in an area where 5G services are available.

[0053] The foregoing description of exemplary implementations provides illustration and description, but is not intended to be exhaustive or to limit the embodiments to the precise form disclosed. Modifications and variations are possible in light of the above teachings or may be acquired from practice of the embodiments.

[0054] For example, features have been described above with respect to selecting an anchor station for a 5G wireless station that has been deployed in a particular location in a network. In some

implementations, the processing described above may be used to select an appropriate location to deploy a 5G wireless station in environment **100** based on the availability of 4G candidate anchor stations. That is, potential locations for a 5G wireless station may be selected, and candidate anchor stations may be ranked based on the selected location of the 5G wireless station. If a particular location of the 5G wireless station results in a more desirable anchor station than another location for the 5G wireless station, the more desirable location may be selected to deploy the 5G wireless station.

[0055] Further, while series of acts have been described with respect to FIGS. **6** and **7**, the order of the acts and signal flows may be different in other implementations. Moreover, non-dependent acts may be implemented in parallel.

[0056] To the extent the aforementioned embodiments collect, store or employ personal information of individuals, it should be understood that such information shall be collected, stored and used in accordance with all applicable laws concerning protection of personal information. Additionally, the collection, storage and use of such information may be subject to consent of the individual to such activity, for example, through well known “opt-in” or “opt-out” processes as may be appropriate for the situation and type of information. Storage and use of personal information may be in an appropriately secure manner reflective of the type of information, for example, through various encryption and anonymization techniques for particularly sensitive information.

[0057] It will be apparent that various features described above may be implemented in many different forms of software, firmware, and hardware in the implementations illustrated in the figures. The actual software code or specialized control hardware used to implement the various features is not limiting. Thus, the operation and behavior of the features were described without reference to the specific software code—it being understood that one of ordinary skill in the art would be able to design software and control hardware to implement the various features based on the description herein.

[0058] Further, certain portions of the invention may be implemented as “logic” that performs one or more functions. This logic may include hardware, such as one or more processors, microprocessor, application specific integrated circuits, field programmable gate arrays or other processing logic, software, or a combination of hardware and software.

[0059] In the preceding specification, various preferred embodiments have been described with reference to the accompanying drawings. It will, however, be evident that various modifications and changes may be made thereto, and additional embodiments may be implemented, without departing from the broader scope of the invention as set forth in the claims that follow. The specification and drawings are accordingly to be regarded in an illustrative rather than restrictive sense.

[0060] No element, act, or instruction used in the description of the present application should be construed as critical or essential to the invention unless explicitly described as such. Also, as used herein, the article “a” is intended to include one or more items. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise.

Claims

1. A method, comprising: identifying, in a network, a location of a Fifth Generation (5G) node; determining, based on the location of the 5G node, a plurality of areas around the 5G node; identifying, in at least some of the plurality of areas, candidate anchor nodes for the 5G node; and ranking the candidate anchor nodes based on parameters associated with the candidate anchor nodes, wherein the parameters include at least one of a first parameter identifying a number of communications handled by each candidate anchor node over a period of time, a second parameter identifying an average signal strength associated with the communications handled by each

candidate anchor node or a third parameter identifying a signal quality associated with the communications handled by each candidate anchor node.

2. The method of claim 1, wherein the ranking comprises: determining the number of communications handled by each candidate anchor node over the period of time, and ranking the candidate anchor nodes based on the first parameter.

3. The method of claim 1, wherein the ranking comprises: determining the average signal strength associated with the communications handled by each candidate anchor node, and ranking the candidate anchor nodes based on the second parameter.

4. The method of claim 1, wherein the ranking comprises: determining the signal quality associated with the communications handled by each candidate anchor node, and ranking the candidate anchor nodes based on the third parameter.

5. The method of claim 1, further comprising: selecting, for the 5G node, an anchor node from the candidate anchor nodes based on the ranking.

6. The method of claim 1, further comprising: determining, for each of the candidate anchor nodes, a distance to the 5G node, and wherein the ranking comprises: ranking each candidate anchor nodes based on the distance to the 5G node, and assigning a preference to a first candidate anchor node collocated with the 5G node.

7. The method of claim 1, further comprising: filtering candidate anchor nodes based on at least one of a physical cell identifier (PCI) conflict in the network or a frequency band supported by the candidate anchor nodes.

8. The method of claim 1, wherein the candidate anchor nodes comprise Fourth Generation Long Term Evolution (4G LTE) nodes, the method further comprising: selecting a 4G LTE node as the anchor node based on the ranking, and assigning the selected 4G LTE anchor node to the 5G node.

9. The method of claim 1, further comprising: determining an average distance for a first plurality of candidate anchor nodes to the 5G node; and eliminating at least a first one of the candidate anchor nodes from consideration as the anchor node in response to determining that the distance from the first candidate anchor node to the 5G node is greater than a predetermined distance.

10. A device, comprising: at least one processor configured to: identify, in a network, a location of a Fifth Generation (5G) node; determine, based on the location of the 5G node, a plurality of areas around the 5G node; identify, in at least some of the plurality of area, candidate anchor nodes for the 5G node; and rank the candidate anchor nodes based on parameters associated with the candidate anchor nodes, wherein the parameters includes at least one of a first parameter identifying a number of communications handled by each candidate anchor node over a period of time, a second parameter identifying an average signal strength associated with the communications handled by each candidate anchor node or a third parameter identifying a signal quality associated with the communications handled by each candidate anchor node.

11. The device of claim 10, wherein when ranking, the at least one processor is further configured to: determine the number of communications handled by each candidate anchor node over the period of time, and rank the candidate anchor nodes based on the first parameter.

12. The device of claim 10, wherein when ranking, the at least one processor is further configured to: determine the average signal strength associated with the communications handled by each candidate anchor node, and rank the candidate anchor nodes based on the second parameter.

13. The device of claim 10, wherein when ranking, the at least one processor is further configured to: determine the signal quality associated with the communications handled by each candidate anchor node, and rank the candidate anchor nodes based on the third parameter.

14. The device of claim 10, where the at least one processor is further configured to: select, for the 5G node, an anchor node from the candidate anchor nodes based on the ranking.

15. The device of claim 10, wherein the at least one processor is further configured to: determine, for each of the candidate anchor nodes, a distance to the 5G node, and when ranking, the at least one processor is configured to: rank each candidate anchor nodes based on the distance to the 5G

node, and assign a preference to a first candidate anchor node collocated with the 5G node.

16. The device of claim 10, wherein the at least one processor is further configured to: filter candidate anchor nodes based on at least one of a physical cell identifier (PCI) conflict in the network or a frequency band supported by the candidate anchor nodes.

17. The device of claim 10, wherein the candidate anchor nodes comprise Fourth Generation Long Term Evolution (4G LTE) nodes, and wherein the at least one processor is further configured to: select a 4G LTE node as the anchor node based on the ranking, and assign the selected 4G LTE node as the anchor node to the 5G node.

18. The device of claim 10, wherein the at least one processor is further configured to: at least one of send a message identifying a selected anchor node to the 5G node or send a message identifying the selected anchor node to personnel associated with the network.

19. A non-transitory computer-readable medium having stored thereon sequences of instructions which, when executed by at least one processor, cause the at least one processor to: identify, in a network, a location of a Fifth Generation (5G) node; determine, based on the location of the 5G node, a plurality of areas around the 5G node; identify, in at least some of the plurality of areas, candidate anchor nodes for the 5G node; and rank the candidate anchor nodes based on parameters associated with the candidate anchor nodes, wherein the parameters includes at least one of a first parameter identifying a number of communications handled by each candidate anchor node over a period of time, a second parameter identifying an average signal strength associated with the communications handled by each candidate anchor node or a third parameter identifying a signal quality associated with the communications handled by each candidate anchor node.

20. The non-transitory computer-readable medium of claim 19, wherein the instructions cause the processor to: select, for the 5G node, an anchor node from the candidate anchor nodes based on the ranking.
