

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250266072

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Bedeschi; Ferdinando et al.

SINGLE PLATE CONFIGURATION AND MEMORY ARRAY OPERATION

Abstract

Methods, systems, and devices for a single plate configuration and memory array operation are described. A non-volatile memory array may utilize a single plate to cover a subset of the array. One or more memory cells of the subset may be selected by operating the plate and an access line of an unselected memory cell at a fixed voltage. A second voltage may be applied to an access line of the selected cell, and subsequently reduced to perform an access operation. Removing the applied voltage may allow for the memory cell to undergo a recovery period prior to a subsequent access operation.

Inventors: Bedeschi; Ferdinando (Biassono (MB), IT), Bolandrina; Efrem (Fiorano Al Serio (BG), IT)

Applicant: Micron Technology, Inc. (Boise, ID)

Family ID: 1000008576763

Appl. No.: 19/062975

Filed: February 25, 2025

Related U.S. Application Data

parent US continuation 18120133 20230310 parent-grant-document US 12249362 child US 19062975

parent US division 16983469 20200803 parent-grant-document US 11626151 child US 18120133

Publication Classification

Int. Cl.: G11C11/22 (20060101); G06F13/16 (20060101)

U.S. Cl.:

Background/Summary

CROSS REFERENCE [0001] The present Application for Patent is a continuation of U.S. patent application Ser. No. 18/120,133 by Bedeschi et al., entitled “SINGLE PLATE CONFIGURATION AND MEMORY ARRAY OPERATION,” filed Mar. 10, 2023, which is a divisional of U.S. patent application Ser. No. 16/983,469 by Bedeschi et al., entitled “SINGLE PLATE CONFIGURATION AND MEMORY ARRAY OPERATION,” filed Aug. 3, 2020, which is a continuation of U.S. patent application Ser. No. 15/845,893 by Bedeschi et al., entitled “SINGLE PLATE CONFIGURATION AND MEMORY ARRAY OPERATION,” filed Dec. 18, 2017, each of which is assigned to the assignee hereof, and each of which is expressly incorporated by reference in its entirety herein.

BACKGROUND

[0002] The following relates generally to operating a memory array and more specifically to a single plate configuration and memory array operation.

[0003] Memory devices are widely used to store information in various electronic devices such as computers, wireless communication devices, cameras, digital displays, and the like. Information is stored by programing different states of a memory device. For example, binary devices have two states, often denoted by a logic “1” or a logic “0.” In other systems, more than two states may be stored. To access the stored information, a component of the electronic device may read, or sense, the stored state in the memory device. To store information, a component of the electronic device may write, or program, the state in the memory device.

[0004] Various types of memory devices exist, including magnetic hard disks, random access memory (RAM), read only memory (ROM), dynamic RAM (DRAM), synchronous dynamic RAM (SDRAM), ferroelectric RAM (FeRAM), magnetic RAM (MRAM), resistive RAM (RRAM), flash memory, phase change memory (PCM), and others. Memory devices may be volatile or non-volatile. Non-volatile memory, e.g., FeRAM, may maintain their stored logic state for extended periods of time even in the absence of an external power source. Volatile memory devices, e.g., DRAM, may lose their stored state over time unless they are periodically refreshed by an external power source. FeRAM may use similar device architectures as volatile memory but may have non-volatile properties due to the use of a ferroelectric capacitor as a storage device. FeRAM devices may thus have improved performance compared to other non-volatile and volatile memory devices.

[0005] Improving memory devices, generally, may include increasing memory cell density, increasing read/write speeds, increasing reliability, increasing data retention, reducing power consumption, or reducing manufacturing costs, among other metrics. In some devices, having a number of plates associated with a memory array may result in increased power consumption and inhibited performance, among other challenges.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 illustrates an example memory array that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0007] FIG. 2 illustrates an example circuit that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0008] FIG. 3 illustrates an example hysteresis curves for a cell that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0009] FIG. 4 illustrates an example memory array that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0010] FIG. 5 illustrates an example timing diagram that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0011] FIG. 6 illustrates an example circuit that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0012] FIG. 7 illustrates an example memory device that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0013] FIG. 8 illustrates an example memory device that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0014] FIG. 9 illustrates an example memory device, including a memory array, that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure.

[0015] FIG. 10 is a flowchart that illustrates a method or methods that support a single plate configuration and memory array operation in accordance with examples of the present disclosure.

DETAILED DESCRIPTION

[0016] Memory devices may consume a certain amount of power when multiple plate drivers are activated to facilitate cell access (e.g., reading from or writing to a cell). Power consumption for plate driver activation may increase with the number of plate drivers utilized, e.g., additional plates require additional plate drivers, which increases power consumption. Thus a reduction in the amount of plate drivers utilized by a memory device results in significant power reduction when a large number of memory cells are coupled with a single plate.

[0017] A memory array with ferroelectric cells may utilize a single plate to cover a subset of the array. This may allow for the portions of the array associated with the single plate to utilize fewer plate drivers, which may mitigate power consumption of the array. Additionally, fewer plate drivers may reduce the amount of routing needed to accommodate the drivers, which may result in increased read and write speeds.

[0018] When utilizing a single plate across a subsection of a memory array, one or more access lines of the memory array may be coupled with the plate during some time intervals of the operation. By coupling the plate with access line, both may be operated at a same, fixed voltage. By operating the plate at a fixed voltage, the need for multiple plate drivers is reduced. A memory cell coupled with a second, different access line may then be selected by applying a second voltage to the second access line and subsequently reducing the applied voltage to access the cell. This configuration may allow for an unselected access line to be coupled with the plate line, which may result in increased read and write speeds to and from the selected memory cell, all while power consumption of the array is mitigated.

[0019] In some examples, a memory cell of a subsection of a memory array utilizing a single plate may be accessed (e.g., read from, written to). To access such a memory cell, a first voltage may be applied to the plate and a first access line coupled with a first memory cell. A second voltage may be applied to a second access line coupled with a second memory cell, which may result in the second memory cell being selected. The second memory cell may be accessed, for example, by reducing the second voltage to a third voltage, which may be a lower voltage than the second voltage. After accessing the second memory cell, the second voltage may be removed from the second access line.

[0020] Features of the disclosure introduced above are further described below in the context of a memory array. Specific examples are then described for a memory array that supports a single plate configuration and memory array operation. These and other features of the disclosure are further illustrated by and described with reference to apparatus diagrams, timing diagrams, circuit

diagrams, system diagrams, and flowcharts that relate to a single plate configuration and memory array operation.

[0021] FIG. 1 illustrates an example memory array **100** in accordance with various examples of the present disclosure. Memory array **100** may also be referred to as an electronic memory apparatus. Memory array **100** includes memory cells **105** that are programmable to store different states. Each memory cell **105** may be programmable to store two states, denoted as a logic 0 and a logic 1. In some cases, memory cell **105** is configured to store more than two logic states. A memory cell **105** may store a charge representative of the programmable states in a capacitor; for example, a charged and uncharged capacitor may represent two logic states, respectively. DRAM architectures may commonly use such a design, and the capacitor employed may include a dielectric material with linear or para-electric electric polarization properties as the insulator. By contrast, a ferroelectric memory cell may include a capacitor with a ferroelectric as the insulating material. Different levels of charge of a ferroelectric capacitor may represent different logic states. Ferroelectric materials have non-linear polarization properties; some details and advantages of a ferroelectric memory cell **105** are discussed below.

[0022] Operations such as reading and writing may be performed on memory cells **105** by activating or selecting access line **110** and digit line **115**. Access lines **110** may also be known as word lines **110**, and bit lines **115** may also be known digit lines **115**. References to word lines and bit lines, or their analogues, are interchangeable without loss of understanding or operation. Activating or selecting a word line **110** or a digit line **115** may include applying a voltage to the respective line. Word lines **110** and digit lines **115** may be made of conductive materials such as metals (e.g., copper (Cu), aluminum (Al), gold (Au), tungsten (W), etc.), metal alloys, carbon, conductively-doped semiconductors, or other conductive materials, alloys, compounds, or the like.

[0023] According to the example of FIG. 1, each row of memory cells **105** is connected to a single word line **110**, and each column of memory cells **105** is connected to a single digit line **115**. By activating one word line **110** and one digit line **115** (e.g., applying a voltage to the word line **110** or digit line **115**), a single memory cell **105** may be accessed at their intersection. Accessing the memory cell **105** may include reading or writing the memory cell **105**.

[0024] Memory array **100** may be a two-dimensional (2D) memory array or a three-dimensional (3D) memory array. A 3D memory array may include two-dimensional (2D) memory arrays formed on top of one another. This may increase the number of memory cells that may be placed or created on a single die or substrate as compared with 2D arrays, which in turn may reduce production costs or increase the performance of the memory array, or both. Memory array **100** may include any number of levels. Each level may be referred to as a deck and may be aligned or positioned so that memory cells **105** may be approximately aligned with one another across each deck.

[0025] Each row of memory cells **105** may be connected to a single word line **110**, and each column of memory cells **105** may be connected to a single digit line **115**. In some examples, the word line **110** and the digit line **115** may be referred to as access lines. For example, a digit line **115** of memory array **100** may be referred to as a first access line **115** and a word line **110** of memory array **100** may be referred to as a second access line **110**. In some examples, the first access line may be coupled with a first memory cell **105** and the second access line may be coupled with a second memory cell **105**. In the example depicted in FIG. 1, memory array **100** includes one deck of memory cells **105** and may thus be considered a two-dimensional memory array; however, the number of decks is not limited. By activating one word line **110** and one digit line **115** (e.g., applying a voltage to the word line **110** or digit line **115**), a single memory cell **105** may be accessed at their intersection. Additionally, for example, in a 3D memory array, each deck in a row may have common conductive lines such that each deck may share word lines **110** or digit lines **115** or contain separate word lines **110** or digit lines **115**. Thus in a 3D configuration one word line **110** and one digit line **115** of a same deck may be activated to access a single memory cell **105** at their intersection. The intersection of a word line **110** and digit line **115**, in either a 2D or 3D

configuration, may be referred to as an address of a memory cell.

[0026] In some architectures, the logic storing device of a cell, e.g., a capacitor, may be electrically isolated from the digit line by a selection component. The word line **110** may be connected to and may control the selection component. For example, the selection component may be a transistor and the word line **110** may be connected to the gate of the transistor. In other examples, the transistor may be a junction-less transistor. Activating the word line **110** results in an electrical connection or closed circuit between the capacitor of a memory cell **105** and its corresponding digit line **115**. The digit line may then be accessed to either read or write the memory cell **105**.

[0027] Accessing memory cells **105** may be controlled through a row decoder **120** and a column decoder **130**. For example, a row decoder **120** may receive a row address from the memory controller **140** and activate the appropriate word line **110** based on the received row address. Similarly, a column decoder **130** receives a column address from the memory controller **140** and activates the appropriate digit line **115**. For example, memory array **100** may include multiple word lines **110**, labeled WL_1 through WL_M, and multiple digit lines **115**, labeled DL_1 through DL_N, where M and N depend on the array size. In some examples, each of word lines WL_1 through WL_M may be coupled with a separate row decoder. In other examples, each of word lines WL_1 through WL_M may be coupled with one row decoder. In either instance, by activating a word line **110** and a digit line **115**, e.g., WL_2 and DL_3, the memory cell **105** at their intersection may be accessed.

[0028] Upon accessing, a memory cell **105** may be read, or sensed, by sense component **125** to determine the stored state of the memory cell **105**. For example, after accessing the memory cell **105**, the ferroelectric capacitor of memory cell **105** may discharge onto its corresponding digit line **115**. Discharging the ferroelectric capacitor may result from biasing, or applying a voltage, to the ferroelectric capacitor. The discharging may cause a change in the voltage of the digit line **115**, which sense component **125** may compare to a reference voltage (not shown) in order to determine the stored state of the memory cell **105**. For example, if digit line **115** has a higher voltage than the reference voltage, then sense component **125** may determine that the stored state in memory cell **105** was a logic 1 and vice versa. Sense component **125** may include various transistors or amplifiers in order to detect and amplify a difference in the signals, which may be referred to as latching. The detected logic state of memory cell **105** may then be output through column decoder **130** as output **135**. In some cases, sense component **125** may be part of a column decoder **130** or row decoder **120**. Or, sense component **125** may be connected to or in electronic communication with column decoder **130** or row decoder **120**. In some examples, multiple digit lines **115** may be coupled with a sense component **125**. For example, a first access line (e.g., a digit line **115**) may be coupled with an additional digit line **115** via column decoder **130**.

[0029] A memory cell **105** may be set, or written, by similarly activating the relevant word line **110** and digit line **115**—i.e., a logic value may be stored in the memory cell **105**. Column decoder **130** or row decoder **120** may accept data, for example input/output **135**, to be written to the memory cells **105**. A ferroelectric memory cell **105** may be written by applying a voltage across the ferroelectric capacitor. This process is discussed in more detail below.

[0030] The memory controller **140** may control the operation (e.g., read, write, re-write, refresh, discharge, etc.) of memory cells **105** through the various components, for example, row decoder **120**, column decoder **130**, and sense component **125**. In some cases, one or more of the row decoder **120**, column decoder **130**, and sense component **125** may be co-located with the memory controller **140**. Memory controller **140** may generate row and column address signals in order to activate the desired word line **110** and digit line **115**. Memory controller **140** may also generate and control various voltages or currents used during the operation of memory array **100**. For example, it may apply discharge voltages to a word line **110** or digit line **115** after accessing one or more memory cells **105**. In general, the amplitude, shape, or duration of an applied voltage or current discussed herein may be adjusted or varied and may be different for the various operations

discussed in operating memory array **100**. Furthermore, one, multiple, or all memory cells **105** within memory array **100** may be accessed simultaneously; for example, multiple or all cells of memory array **100** may be accessed simultaneously during a reset operation in which all memory cells **105**, or a group of memory cells **105**, are set to a single logic state.

[0031] In some examples, the memory controller **140** may be coupled with each of a first access line (e.g., a digit line **115**) and a second access line (e.g., a word line **110**). In some examples, the first access line may be coupled with a first memory cell **105** and the second access line may be coupled with a second memory cell **105**. The memory controller **140** may be coupled with a plate line (not shown), that may be coupled with each of the first access line, the first memory cell **105**, and the second memory cell **105**. The memory controller **140** may be configured, for example, to apply a first voltage to the plate line and the first access line. Additionally or alternatively, for example, the memory controller **140** may apply a second voltage to the second access line, which may select the second memory cell **105**. In some examples, the memory controller **140** may reduce the second voltage to a third voltage to access the second memory cell **105** and may, for example, remove the applied second voltage after accessing the second memory cell **105**. Such an operation may result in less power consumption by memory array **100**, as well as requiring fewer drivers (not shown) to operate various aspects of memory array **100**.

[0032] FIG. **2** illustrates an example circuit **200** in accordance with various examples of the present disclosure. Circuit **200** includes a memory cell **105-a**, word line **110-a**, digit line **115-a**, and sense component **125-a**, which may be examples of a memory cell **105**, word line **110**, digit line **115**, and sense component **125**, respectively, as described with reference to FIG. **1**. Memory cell **105-a** may include a logic storage component, such as capacitor **205** that has a first plate, cell plate **230**, and a second plate, cell bottom **215**. Cell plate **230** and cell bottom **215** may be capacitively coupled through a ferroelectric material positioned between them. The orientation of cell plate **230** and cell bottom **215** may be flipped without changing the operation of memory cell **105-a**. Circuit **200** also includes selection component **220** and reference line **225**. Cell plate **230** may be accessed via plate line **210** and cell bottom **215** may be accessed via digit line **115-a**. As described above, various states may be stored by charging or discharging capacitor **205**. In some examples, plate line **210** may be coupled with multiple memory cells **105-a**. For example, plate line **210** may be coupled with each of a first memory cell **105-a** and a second memory cell (not shown). Additionally or alternatively, for example, plate line **210** may be coupled with a first access line (e.g., digit line **115-a**).

[0033] The stored state of capacitor **205** may be read or sensed by operating various elements represented in circuit **200**. Capacitor **205** may be in electronic communication with digit line **115-a** and a plate line **210**. For example, capacitor **205** can be isolated from digit line **115-a** when selection component **220** is deactivated, and capacitor **205** can be connected to digit line **115-a** when selection component **220** is activated. Activating selection component **220** may be referred to as selecting memory cell **105-a**. In some cases, selection component **220** is a transistor and its operation is controlled by applying a voltage to the transistor gate, where the voltage magnitude is greater than the threshold magnitude of the transistor. Word line **110-a** may activate selection component **220**; for example, a voltage applied to word line **110-a** is applied to the transistor gate, connecting capacitor **205** with digit line **115-a**. In some examples, a first voltage may be applied to the plate line **210** and the first access line (e.g., digit line **115-a**) that are each coupled with memory cell **105-a**.

[0034] In some examples, a memory array (e.g., memory array **100** as described with reference to FIG. **1**) may contain multiple word lines and one or more plate lines coupled with a memory cell. For example, as described above, word line **110-a** and plate line **210** may be coupled with a memory cell **105-a**, and a second word line (not shown) and a second plate line (not shown) may be coupled with a second memory cell (not shown). In other examples, the plate line **210** may be coupled with each of the first memory cell and the second memory cell. In some embodiments, one

memory cell (such as the second memory cell) may be selected after applying a first voltage to the plate line **210** and the word line **110-a** that are each coupled with the memory cell **105-a**. This voltage may be referred to as a deselection voltage. In some examples, this voltage may be -1.7V . [0035] The second memory cell may then be selected by applying a second voltage to the second word line coupled with the second memory cell. The second memory cell may be accessed (e.g., written to or read from) by reducing the second voltage to a third voltage. The third voltage may be a different voltage than the second voltage. During this time, the first voltage (e.g., the deselection voltage) may be applied to the plate line **210** and the word line **110-a** (e.g., continually applied). After accessing the second memory cell, the second voltage may be removed from the second access line.

[0036] In other examples, the positions of selection component **220** and capacitor **205** may be switched, such that selection component **220** is connected between plate line **210** and cell plate **230** and such that capacitor **205** is between digit line **115-a** and the other terminal of selection component **220**. In this example, selection component **220** may remain in electronic communication with digit line **115-a** through capacitor **205**. This configuration may be associated with alternative timing and biasing for read and write operations.

[0037] Due to the ferroelectric material between the plates of capacitor **205**, and as discussed in more detail below, capacitor **205** may not discharge upon connection to digit line **115-a**. In one scheme, to sense the logic state stored by ferroelectric capacitor **205**, word line **110-a** may be biased to select memory cell **105-a** and a voltage may be applied to plate line **210**. In some cases, digit line **115-a** is virtually grounded and then isolated from the virtual ground, which may be referred to as “floating,” prior to biasing plate line **210** and word line **110-a**. Biasing plate line **210** may result in a voltage difference (e.g., plate line **210** voltage minus digit line **115-a** voltage) across capacitor **205**. The voltage difference may yield a change in the stored charge on capacitor **205**, where the magnitude of the change in stored charge may depend on the initial state of capacitor **205**—e.g., whether the initial state stored a logic 1 or a logic 0. This may cause a change in the voltage of digit line **115-a** based on the charge stored on capacitor **205**. Operation of memory cell **105-a** by varying the voltage to cell plate **230** may be referred to as “moving cell plate.” In other examples, capacitor **205** may be discharged to remove a second voltage applied to a second access line (e.g., a second digit line **115** as described with reference to FIG. 1).

[0038] The change in voltage of digit line **115-a** may depend on its intrinsic capacitance. That is, as charge flows through digit line **115-a**, some finite charge may be stored in digit line **115-a** and the resulting voltage depends on the intrinsic capacitance. The intrinsic capacitance may depend on physical characteristics, including the dimensions, of digit line **115-a**. Digit line **115-a** may connect many memory cells **105** so digit line **115-a** may have a length that results in a non-negligible capacitance (e.g., on the order of picofarads (pF)). The resulting voltage of digit line **115-a** may then be compared to a reference (e.g., a voltage of reference line **225**) by sense component **125-a** in order to determine the stored logic state in memory cell **105-a**. Other sensing processes may be used.

[0039] Sense component **125-a** may include various transistors or amplifiers to detect and amplify a difference in signals, which may be referred to as latching. Sense component **125-a** may include a sense amplifier that receives and compares the voltage of digit line **115-a** and reference line **225**, which may be a reference voltage. The sense amplifier output may be driven to the higher (e.g., a positive) or lower (e.g., negative or ground) supply voltage based on the comparison. For instance, if digit line **115-a** has a higher voltage than reference line **225**, then the sense amplifier output may be driven to a positive supply voltage. In some cases, the sense amplifier may additionally drive digit line **115-a** to the supply voltage. Sense component **125-a** may then latch the output of the sense amplifier and/or the voltage of digit line **115-a**, which may be used to determine the stored state in memory cell **105-a**, e.g., logic 1. Alternatively, if digit line **115-a** has a lower voltage than reference line **225**, the sense amplifier output may be driven to a negative or ground voltage. Sense

component **125-a** may similarly latch the sense amplifier output to determine the stored state in memory cell **105-a**, e.g., logic 0. The latched logic state of memory cell **105-a** may then be output, for example, through column decoder **130** as output **135** with reference to FIG. 1.

[0040] To write memory cell **105-a**, a voltage may be applied across capacitor **205**. Various methods may be used. In one example, selection component **220** may be activated through word line **110-a** in order to electrically connect capacitor **205** to digit line **115-a**. A voltage may be applied across capacitor **205** by controlling the voltage of cell plate **230** (through plate line **210**) and cell bottom **215** (through digit line **115-a**). To write a logic 0, cell plate **230** may be taken high, that is, a positive voltage may be applied to plate line **210**, and cell bottom **215** may be taken low, e.g., virtually grounding or applying a negative voltage to digit line **115-a**. The opposite process is performed to write a logic 1, where cell plate **230** is taken low and cell bottom **215** is taken high. In other examples, as described above, a memory cell (e.g., a second memory cell) may be written to by first applying a first voltage to the plate line **210** and first access line **115-a** that may each be coupled with a first memory cell **105-a**. The second memory cell (not shown) may be selected by applying a second voltage to a second access line (e.g., a word line) that may be coupled with the second memory cell. The second memory cell may then be written to by reducing the second voltage to a third voltage. In some examples, the third voltage may be lower than the second voltage. In other examples, the third voltage may be a different voltage than the second voltage. Additionally or alternatively, for example, the second voltage may be removed after accessing the second memory cell, which may be achieved by discharging a capacitor (not shown) of the second memory cell.

[0041] FIG. 3 illustrates an example of non-linear electrical properties with hysteresis curves **300-a** and **300-b** for a ferroelectric memory cell that is operated in accordance with various examples of the present disclosure. Hysteresis curves **300-a** and **300-b** illustrate an example ferroelectric memory cell writing and reading process, respectively. Hysteresis curves **300-a** and **300-b** depict the charge, Q , stored on a ferroelectric capacitor (e.g., capacitor **205** of FIG. 2) as a function of a voltage difference, V .

[0042] A ferroelectric material is characterized by a spontaneous electric polarization, i.e., it maintains a non-zero electric polarization in the absence of an electric field. Example ferroelectric materials include barium titanate (BaTiO_3), lead titanate (PbTiO_3), lead zirconium titanate (PZT), and strontium bismuth tantalate (SBT). The ferroelectric capacitors described herein may include these or other ferroelectric materials. Electric polarization within a ferroelectric capacitor results in a net charge at the ferroelectric material's surface and attracts opposite charge through the capacitor terminals. Thus, charge is stored at the interface of the ferroelectric material and the capacitor terminals. Because the electric polarization may be maintained in the absence of an externally applied electric field for relatively long times, even indefinitely, charge leakage may be significantly decreased as compared with, for example, capacitors employed in DRAM arrays. This may reduce the need to perform refresh operations as described above for some DRAM architectures.

[0043] Hysteresis curves **300-a** and **300-b** may be understood from the perspective of a single terminal of a capacitor. By way of example, if the ferroelectric material has a negative polarization, positive charge accumulates at the terminal. Likewise, if the ferroelectric material has a positive polarization, negative charge accumulates at the terminal. Additionally, it should be understood that the voltages in hysteresis curves **300-a** and **300-b** represent a voltage difference across the capacitor and are directional. For example, a positive voltage may be realized by applying a positive voltage to the terminal in question (e.g., a cell plate **230**) and maintaining the second terminal (e.g., a cell bottom **215**) at ground (or approximately zero volts (0V)). A negative voltage may be applied by maintaining the terminal in question at ground and applying a positive voltage to the second terminal—i.e., positive voltages may be applied to negatively polarize the terminal in question. Similarly, two positive voltages, two negative voltages, or any combination of positive

and negative voltages may be applied to the appropriate capacitor terminals to generate the voltage difference shown in hysteresis curves **300-a** and **300-b**.

[0044] As depicted in hysteresis curve **300-a**, the ferroelectric material may maintain a positive or negative polarization with a zero voltage difference, resulting in two possible charged states: charge state **305** and charge state **310**. According to the example of FIG. 3, charge state **305** represents a logic 0 and charge state **310** represents a logic 1. In some examples, the logic values of the respective charge states may be reversed to accommodate other schemes for operating a memory cell.

[0045] A logic “0” or “1” may be written to the memory cell by controlling the electric polarization of the ferroelectric material, and thus the charge on the capacitor terminals, by applying voltage. For example, applying a net positive voltage **315** across the capacitor results in charge accumulation until charge state **305-a** is reached. Upon removing voltage **315**, charge state **305-a** follows path **320** until it reaches charge state **305** at zero voltage. Similarly, charge state **310** is written by applying a net negative voltage **325**, which results in charge state **310-a**. After removing negative voltage **325**, charge state **310-a** follows path **330** until it reaches charge state **310** at zero voltage. Charge states **305-a** and **310-a** may also be referred to as the remnant polarization (Pr) values, i.e., the polarization (or charge) that remains upon removing the external bias (e.g., voltage). The coercive voltage is the voltage at which the charge (or polarization) is zero.

[0046] Additionally or alternatively, for example, a logic “0” or “1” may be written to a memory cell by first applying a voltage to a plate line (e.g., plate line **210** as described with reference to FIG. 2) and a first access line that are each coupled with a first memory cell (e.g., memory cell **105-a** as described with reference to FIG. 2). In some examples, the applied voltage may be referred to as a first voltage. A second memory cell (not shown) may subsequently be selected by applying a second voltage to a second access line (e.g., a word line) coupled with the second memory cell. In some examples, the second voltage may be applied after the first voltage. To access (e.g., to write a logic “0” or “1”) the second memory cell, the second voltage may be reduced to a third voltage. In some examples, the second voltage may be removed and a third voltage may be subsequently applied. In other examples, the voltage (e.g., the second voltage) may be applied by a voltage source and may be reduced to a third voltage by activating one or more switching components. In some examples, the second voltage may be reduced—e.g., by floating or grounding one or more nodes of the second access line. In some examples, the third voltage may be a lower voltage than the second voltage. The second voltage may be removed from the second access line after accessing the second memory cell.

[0047] To read, or sense, the stored state of the ferroelectric capacitor, a voltage may be applied across the capacitor. In response, the stored charge, Q , changes, and the degree of the change depends on the initial charge state—i.e., the final stored charge (Q) depends on whether charge state **305-b** or **310-b** was initially stored. For example, hysteresis curve **300-b** illustrates two possible stored charge states **305-b** and **310-b**. Voltage **335** may be applied across the capacitor as discussed with reference to FIG. 2. In other cases, a fixed voltage may be applied to the cell plate and, although depicted as a positive voltage, voltage **335** may be negative. In response to voltage **335**, charge state **305-b** may follow path **340**. Likewise, if charge state **310-b** was initially stored, then it follows path **345**. The final position of charge state **305-c** and charge state **310-c** depend on a number of factors, including the specific sensing scheme and circuitry.

[0048] Similar to the write operation described above, for example, the stored state of a memory cell may be ready by first applying a voltage to a plate line (e.g., plate line **210** as described with reference to FIG. 2) and a first access line (e.g., digit line **115-a** as described with reference to FIG. 2) that are each coupled with a first memory cell (e.g., memory cell **105-a** as described with reference to FIG. 2). In some examples, the applied voltage may be referred to as a first voltage. A second memory (not shown) cell may subsequently be selected by applying a second voltage to a second access line (e.g., a word line) coupled with the second memory cell. In some examples, the

second voltage may be applied after the first voltage. To access (e.g., to read the stored state) the second memory cell, the second voltage may be reduced to a third voltage. In some examples, the third voltage may be a lower voltage than the second voltage. The second voltage may be removed from the second access line after accessing the second memory cell.

[0049] In some cases, the final charge may depend on the intrinsic capacitance of the digit line connected to the memory cell. For example, if the capacitor is electrically connected to the digit line and voltage **335** is applied, the voltage of the digit line may rise due to its intrinsic capacitance. So a voltage measured at a sense component may not equal voltage **335** and instead may depend on the voltage of the digit line. The position of final charge states **305-c** and **310-c** on hysteresis curve **300-b** may thus depend on the capacitance of the digit line and may be determined through a load-line analysis—i.e., charge states **305-c** and **310-c** may be defined with respect to the digit line capacitance. As a result, the voltage of the capacitor, voltage **350** or voltage **355**, may be different and may depend on the initial state of the capacitor.

[0050] By comparing the digit line voltage to a reference voltage, the initial state of the capacitor may be determined. The digit line voltage may be the difference between voltage **335** and the final voltage across the capacitor, voltage **350** or voltage **355**—i.e., (voltage **335**—voltage **350**) or (voltage **335**—voltage **355**). A reference voltage may be generated such that its magnitude is between the two possible voltages of the two possible digit line voltages in order to determine the stored logic state—i.e., if the digit line voltage is higher or lower than the reference voltage. For example, the reference voltage may be an average of the two quantities, (voltage **335**—voltage **350**) and (voltage **335**—voltage **355**). Upon comparison by the sense component, the sensed digit line voltage may be determined to be higher or lower than the reference voltage, and the stored logic value of the ferroelectric memory cell (i.e., a logic 0 or 1) may be determined.

[0051] As discussed above, reading a memory cell that does not use a ferroelectric capacitor may degrade or destroy the stored logic state. A ferroelectric memory cell, however, may maintain the initial logic state after a read operation. For example, if charge state **305-b** is stored, the charge state may follow path **340** to charge state **305-c** during a read operation and, after removing voltage **335**, the charge state may return to initial charge state **305-b** by following path **340** in the opposite direction.

[0052] Hysteresis curve **300-b** illustrates an example of reading of stored charge states **305** a and **310-a**. A read voltage **335** may be applied, for example, as a voltage difference via a digit line **115-a** and a plate line **210** as described with reference to FIG. 2. Hysteresis curve **300-b** may illustrate read operations where the read voltage **335** is negative voltage difference V_{cap} (e.g., where $V_{\text{bottom}} - V_{\text{plate}}$ is negative). A negative read voltage across the capacitor may be referred to as a “plate high” read operation, where a plate line **210** is taken initially to a high voltage, and a digit line **115-a** is initially at a low voltage (e.g., a ground voltage). Although read voltage **335** is shown as a negative voltage across the ferroelectric capacitor **205**, in alternative operations a read voltage may be a positive voltage across the ferroelectric capacitor **205**, which may be referred to as a “plate low” read operation.

[0053] The read voltage **335** may be applied across the ferroelectric capacitor **205** when a memory cell **105** is selected (e.g., by activating a selection component **250** as described with reference to FIG. 2). Upon applying the read voltage **335** to the ferroelectric capacitor **205**, charge may flow into or out of the ferroelectric capacitor **205** via the digit line **115-a** and plate line **210**, and different charge states may result depending on whether the ferroelectric capacitor **205** was at charge state **305-a** (e.g., a logic 1) or at charge state **310-a** (e.g., a logic 0).

[0054] When performing a read operation on a ferroelectric capacitor **205** at the charge state **305-b** (e.g., a logic 0), additional negative charge may accumulate across the ferroelectric capacitor **205**, and the charge state may follow path **340** until reaching the charge and voltage of charge state **310-c**. The amount of charge flowing through the capacitor **205** may be related to the intrinsic capacitance of the digit line **115-a** (e.g., intrinsic capacitance **260** described with reference to FIG.

2). Accordingly, as shown by the transition between charge state **310-a** and charge state **310-c**, the resulting voltage difference **350** may be a relatively large negative value due to the relatively large change in voltage for the given change in charge. Thus, upon reading a logic 0 in a “plate high” read operation, the digit line voltage, equal to the sum of V_{PL} and the value of $(V_{bottom}-V_{plate})$ at charge state **310-c**, may be a relatively low voltage. Such a read operation may not change the remnant polarization of the ferroelectric capacitor **205** that stored charge state **310-a**, and thus after performing the read operation the ferroelectric capacitor **205** may return to charge state **310-a** via path **340** when the read voltage **335** is removed (e.g., by applying a zero net voltage across the ferroelectric capacitor **205**). Thus, performing a read operation with a negative read voltage on a ferroelectric capacitor **205** with a charge state **305-a** may be considered a non-destructive read process.

[0055] When performing the read operation on the ferroelectric capacitor **205** at the charge state **310-b** (e.g., a logic 1), the stored charge may reverse polarity as a net negative charge accumulates across the ferroelectric capacitor **205**, and the charge state may follow path **360** until reaching the charge and voltage of charge state **305-c**. The amount of charge flowing through the capacitor **205** may again be related to the intrinsic capacitance of the digit line **115-a** (e.g., intrinsic capacitance **260** described with reference to FIG. 2). Accordingly, as shown by the transition between charge state **305-a** and charge state **305-c**, the resulting voltage difference **355** may be a relatively small negative value due to the relatively small change in voltage for the given change in charge. Thus, upon reading a logic 1 in a “plate high” read operation, the digit line voltage, equal to the sum of V_{PL} and the value of $(V_{bottom}-V_{plate})$ at charge state **310-c**, may be a relatively high voltage.

[0056] Similar to the read option described above with reference to hysteresis curve **300-a**, the charge states **305-b** and **310-b** may be read during an access operation. For example, a voltage may be first applied to a plate line (e.g., plate line **210** as described with reference to FIG. 2) and a first access line that are each coupled with a first memory cell (e.g., memory cell **105-a** as described with reference to FIG. 2). In some examples, the applied voltage may be referred to as a first voltage. A second memory cell may subsequently be selected by applying a second voltage to a second access line coupled with the second memory cell. In some examples, the second voltage may be applied after the first voltage. To access (e.g., to read the stored state) the second memory cell, the second voltage may be reduced to a third voltage. In some examples, the third voltage may be a lower voltage than the second voltage. The second voltage may be removed from the second access line after accessing the second memory cell.

[0057] FIG. 4 illustrates an example memory array **400** that supports a single plate configuration and memory array operation in accordance with various examples of the present disclosure.

Memory array **400** may be an example of memory array **100** as described with reference to FIG. 1. Memory array **400** may include memory cells **105-b** and **105-c**, word lines **110-b** and **110-c**, and digit lines **115-b** and **115-c**. Memory cells **105-b** and **105-c** may be examples of memory cell **105** as described with reference to FIG. 1, word lines **110-b** and **110-c** may be examples of word line **110** as described with reference to FIG. 1, and digit lines **115-b** and **115-c** may be examples of digit line **115** as described with reference to FIG. 1. In other examples, memory array **400** may include row decoder **120-a**, sense component **125-b**, and column decoder **130-a**, which may be examples of row decoder **120**, sense component **125**, and column decoder **130**, respectively, as described with reference to FIG. 1. Additionally or alternatively, for example, memory array **400** may include selection components **220-a** and **220-b** and plate line **210-a**, which may be examples of selection component **220** and plate line **210**, respectively, as described with reference to FIG. 2. In some examples, memory cell **105-b** may include selection component **220-a** and capacitor **205-a**, which may be examples of selection component **220** and capacitor **205**, respectively, as described with reference to FIG. 2. In some examples, memory cell **105-c** may include selection component **220-b** and capacitor **205-b**, which may be examples of selection component **220** and capacitor **205**, respectively, as described with reference to FIG. 2.

[0058] Memory array **400** may be referred to as an array of ferroelectric memory cells and may include memory cells **105-b** and **105-c** (as well as other memory cells not shown). In some examples, memory cell **105-c** may be referred to as a first ferroelectric memory cell and memory cell **105-b** may be referred to as a second ferroelectric memory cell, though these cells are not otherwise limited to this type of memory cell. As depicted in FIG. **4**, each of first ferroelectric memory cell **105-c** and second ferroelectric memory cell **105-b** may be different memory cells. In some examples, plate line **210-a** may be coupled with each of first ferroelectric memory cell **105-c** and second ferroelectric memory cell **105-b**.

[0059] Each of first ferroelectric memory cell **105-c** and second ferroelectric memory cell **105-b** may be coupled with digit lines **115-c** and **115-b**, respectively. Additionally or alternatively, for example, each of first memory cell **105-c** and second memory cell **105-b** may be coupled with word line **110-b**. In some examples, the digit line **115-c** may be referred to as a first access line. In some examples, the word line **110-b** may be referred to as a second access line. As depicted in FIG. **4**, each of first access line **115-c** and second access line **110-b** may be different access lines.

[0060] In some examples, the second access line **110-b** may be coupled with each of memory cells **105-b** and **105-c**. For example, second access line **110-b** may be coupled with a plurality of memory cells, and each memory cell may be coupled with a different digit line. Additionally or alternatively, for example, first access line **115-c** may also be coupled with a plurality of memory cells, and each memory cell may be coupled with a different word line. In some examples, a memory cell coupled with access line **110-b** may share a digit line (e.g., digit line **115-b**) with one or more additional memory cells.

[0061] Memory array **400** may be configured for an access operation of a memory cell by first applying a voltage to the plate line **210-a** and the first access line **115-c**. In some examples, the voltage applied to the plate line **210-a** and the first access line **115-c** may be a same, fixed voltage, and each of the plate line **210-a** and the first access line **115-c** may be coupled with first memory cell **105-c**. In some examples, the first voltage may be zero volts (0V). Stated alternatively, the first access line **115-c** and the plate line **210-a** may be grounded. Because the first access line **115-c** may be in communication with digit line **115-b** through column decoder **130-a**, the column decoder **130-a** may prevent the first applied voltage from reaching digit line **115-b**. For example, the column decoder **130-a** may contain one or more transistors that, when activated, may isolate the first voltage from the digit line **115-b**. Thus, despite the digit line **115-b** and the first access line **115-c** being in communication, the first voltage may be applied only to the plate line **210-a** and the first access line **115-c**.

[0062] In other examples, a different, unrelated, voltage may be applied to the digit line **115-b**. This voltage may be a positive voltage or a negative voltage and, as discussed above, the digit line **115-b** may be isolated from the first access line **115-c** by one or more transistors of the column decoder **130-a** being activated. In further examples, memory array **400** may be coupled with a memory controller (e.g., memory controller **140** as described with reference to FIG. **1**) and a first voltage source (not shown). For example, the memory controller may send an indication to apply the first voltage to the plate line **210-a** and the first access line **115-c**. In some examples, the memory controller may send an indication to a switching component (not shown) coupled with the first voltage source. Application of the first voltage may, for example, allow for an unselected access line (e.g., word line **110-c**) to be operated at a negative voltage. In other examples, memory cell **105-c** may be referred to as an unselected memory cell due to access line **115-c** being operated at 0V (e.g., grounded). Additionally or alternatively, for example, memory cell **105-b** may be referred to as a selected memory cell upon the application of a voltage (e.g., a second voltage greater than or less than 0V) to the second access line **110-b**.

[0063] Memory cell **105-b** may be selected by applying a second voltage to the second access line **110-b** at a time different from applying the first voltage (e.g., after applying the first voltage). In other examples, the second voltage may be applied before the first voltage or concurrent with the

first voltage. In some examples, memory cell **105-b** may be coupled with the second access line **110-b**, and the second access line **110-b** may be operated at a different voltage than the plate line **210-a**. In other examples, the plate line **210-a** may be grounded and the first access line **115-c** may be shorted with the plate line **210-a**. As described above, memory array **400** may be coupled with a memory controller and, in some examples, may be coupled with a second voltage source (not shown). In some examples, the memory controller may send an indication to apply the second voltage to the second access line **110-b**. In some examples, the memory controller may send an indication to a switching component (not shown) coupled with the second voltage source.

Application of the second voltage may, for example, allow for operation of a selected access line (e.g., word line **110-b**) at a positive voltage concurrent with an unselected access line (e.g., word line **110-c**) operated at a negative voltage.

[0064] Memory cell **105-b** may, in some examples, be accessed by reducing the second voltage applied to the second access line **110-b** from a second voltage to a third voltage. In some examples, the third voltage may be a lower voltage than the second voltage. Additionally or alternatively, for example, the second voltage may be removed after accessing memory cell **105-b**. In some examples, memory array may be coupled with a memory controller, as described above, and a third voltage source. The memory controller may, for example, send an indication to apply the third voltage to the second access line **110-b**. In some examples, the memory controller may send an indication to a switching component (not shown) coupled with the third voltage source. In other examples, the memory controller may send an indication to merely reduce the applied second voltage to a third voltage. In either example, reducing the second voltage to a third voltage may preserve one or more materials (e.g., silicon oxide) of the accessed memory cell from degradation.

[0065] In some examples, the second access line may be maintained at a fixed voltage prior to selecting memory cell **105-b**. In some examples, when the second voltage is removed from the second access line **110-b**, the voltage of the second access line **110-b** may return to a same voltage as the maintained, fixed voltage. For example, the second access line **110-b** may be maintained at a negative one-point-seven volts (1.7V). The applied second voltage may increase the second access line **110-b** to a positive three volts (3V). When the second voltage is removed, for example, the second access line **110-b** may return to a negative 1.7V. Additionally or alternatively, for example, a fourth voltage may be applied to the second access line **110-b** in response to the removing the third voltage. This voltage may be a same voltage as the fixed voltage applied prior to selecting memory cell **105-b**. In other examples, both the fourth voltage and the fixed voltage applied to selected memory cell **105-b** may be a negative voltage. As described above, for example, memory array **400** may be coupled with a fourth voltage source and a memory controller may send an indication to apply the fourth voltage to the second access line **110-b**.

[0066] When applying the respective voltage to access line **115-c**, the voltage may be applied to selection component **220-b**. In some examples, selection component **220-b** may be or include one or more transistors. In other examples, selection component **220-b** may be or may include one or more junction-less transistors. For example, selection component **220-b** may be or may include a first junction-less transistor. In other examples, when applying the respective voltages to access line **110-b**, the voltages may be applied to selection component **220-a**. In some examples, selection component **220-a** may be or may include one or more transistors. In other examples, selection component **220-a** may be or may include one or more junction-less transistors. For example, selection component **220-a** may be or may include a second junction-less transistor.

[0067] In some examples, memory array **400** may include a sense component **125-b** that may be used for or during one or more access operations. For example, the sense component **125-b** may be coupled with column decoder **130-a**, which may be coupled with each of digit line **115-b** and digit line **115-c**. Stated alternatively, digit line **115-b** and digit line **115-c** may be coupled with each other through column decoder **130-a**. The sense component **125-b** may receive the voltage of digit line **115-b** during an access operation, and may compare the voltage with a reference voltage. As

described with reference to FIG. 1, for example, if digit line **115-b** has a higher voltage than the reference line voltage value, then the sense component **125-b** output may be driven to a voltage (e.g., a positive supply voltage). The sense component **125-b** may then latch the output of the sense amplifier and/or the voltage of digit line **115-b**, which may be used to determine the stored state in memory cell **105-c**.

[0068] In other examples, memory array **400** may include multiple decks of memory cells (not shown). For example, memory array **400** may include a second deck of ferroelectric memory cells coupled with the array. In some examples, the second deck of ferroelectric memory cells may include a third ferroelectric memory cell and a fourth ferroelectric memory cell different than the third ferroelectric memory cell. Additionally or alternatively, the second deck of ferroelectric memory cells may include a second plate coupled with the third and fourth ferroelectric memory cells and a third access line coupled with the third ferroelectric memory cell and the plate.

[0069] In some examples, the third access line and the plate may be configured to operate at a second fixed voltage level. In other examples, the second deck of ferroelectric memory cells may include a fourth access line coupled with the fourth ferroelectric memory cell. The fourth access line may be a different access line than the third access line. Additionally or alternatively, for example, the fourth access line may be configured to operate at a voltage level different than the second, fixed voltage level. In some examples, the fourth ferroelectric memory cell may be accessed in a similar manner as memory cell **105-b**. For example, a first voltage may be applied to both the plate and the third access line. The fourth ferroelectric memory cell may, for example, be selected by applying a second voltage to the fourth access line and subsequently reducing the voltage to access the memory cell. In some examples, the second voltage may be reduced to a third voltage, which may be lower than the second voltage. Additionally or alternatively, for example, the applied second voltage may be removed after accessing the fourth ferroelectric memory cell of the second deck.

[0070] FIG. 5 illustrates an example of a timing diagram **500** that supports a single plate configuration and memory array operation in accordance with various examples of the present disclosure. Timing diagram includes voltage (V) along the vertical axis and time (t) along the horizontal axis; and timing diagram **500** may represent at least a portion of an access operation. The voltages of various components as a function of time are also represented on timing diagram **500**. For example, timing diagram **500** includes first digit line voltage **525**, second digit line voltage **530**, selected word line voltage **535**, digit line selector voltage **540**, and plate line voltage **545**. In some examples, digit line selector voltage **540** may relate to the operation of digit line **115-b** as described with reference to FIG. 4. Thus, timing diagram **500** may correspond to operating memory array **400** as described with reference to FIG. 4, among other operations, and the following discussion is in the context of components depicted in FIG. 4.

[0071] As discussed above, a first voltage may be applied to a plate line (e.g., plate line **210-a** as described with reference to FIG. 4) and a first access line (e.g., first access line **115-c** as described with reference to FIG. 4) that are each coupled with a ferroelectric memory cell (e.g., first ferroelectric memory cell **105-c** as described with reference to FIG. 4). In some examples, the first voltage may be zero volts (0V). Stated alternatively, in some examples, the first access line and the plate may each be grounded. For example, the first voltage may be applied to deselect a memory cell (e.g., memory cell **105-c** as described with reference to FIG. 4) coupled with the first access line (e.g., first access line **115-c** as described with reference to FIG. 4). As described above, the first voltage applied to the first access line may be isolated from digit line **115-b**, for example, by activating one or more transistors of a column decoder (e.g., column decoder **130-a** as described with reference to FIG. 4). In some examples, the first memory cell may be deselected by applying the first voltage to the plate line and to the first access line. Additionally or alternatively, for example, the first voltage may remain constant throughout the operation. Stated alternatively, the first voltage may be applied throughout the access operation.

[0072] In some examples, a second ferroelectric memory cell (e.g., second ferroelectric memory cell **105-b** as described with reference to FIG. **4**) may be selected by applying a second voltage to a second access line (e.g., second access line **110-b** as described with reference to FIG. **4**) coupled with the second ferroelectric memory cell. In some examples, the second voltage may be applied after the first voltage. In other examples, the second voltage may be applied before the first voltage, or concurrent with the first voltage. Applying the second voltage may, for example, allow a selected access line (e.g., second access line **110-b** as described with reference to FIG. **4**) to be operated at a positive voltage, while an unselected access line (e.g., word line **110-c** as described with reference to FIG. **4**) is operated at a negative voltage. Additionally or alternatively, for example, the second ferroelectric memory cell may be accessed by reducing the second voltage to a third voltage. In some examples, the third voltage may be a lower voltage than the second voltage. In some examples, this voltage reduction may preserve one or more materials of the memory cell from degradation. The second applied voltage may be removed after accessing the second ferroelectric memory cell.

[0073] At time interval **505** an activate command (ACT) may be issued by a memory controller (e.g., memory controller **140** as described with reference to FIG. **1**). In some examples, an ACT command may include applying a first voltage to a plate line and to a first access line that are each coupled with a first ferroelectric memory cell. Additionally or alternatively, for example, a second ferroelectric memory cell may be selected by applying a second voltage to a second access line after applying the first voltage. In other examples, as described above, the second voltage may be applied before the first voltage, or concurrent with the first voltage.

[0074] The application of the second voltage may be depicted as an increased voltage in the selected word line voltage **535**. Depending on the stored state (e.g., logic “1” or logic “0”) of the selected memory cell, the voltage of the selected digit line may be depicted by first digit line voltage **525** or second digit line voltage **530**. For example, if the selected memory cell includes a stored logic “1”, the voltage of the of the corresponding digit line may be represented by first digit line voltage **525**. If the selected memory cell includes a stored logic “0”, the voltage of the corresponding digit line may be represented by second digit line voltage **530**. In either example, first digit line voltage **525** and second digit line voltage **530** may each be increased to, for example positive one-and-one-half volts (1.5V).

[0075] In some examples, when a second voltage is applied to a second access line (e.g., second access line **110-b** as described with reference to FIG. **4**), the voltage of selected word line voltage **535** may increase to, for example, a positive three volts (3V). In other examples, digit line selector voltage may also increase to a positive 3V. In other examples, plate line voltage **545** may remain at a constant voltage for the duration of time interval **505**. The plate line voltage may, for example, remain at zero volts (0V).

[0076] In other examples, at time interval **505**, a read/write command (RD/WR) may be issued by a memory controller (e.g., memory controller **140**, as described with reference to FIG. **1**). In some examples a RD/WR command may commence accessing the selected ferroelectric memory cell by reducing the second voltage applied to the second access line to a third voltage. In some examples, the third voltage may be lower than the second voltage.

[0077] The reduction of the second voltage to a third voltage may be depicted as a decreased voltage in the selected word line voltage **535**. In some examples, selected word line voltage **535** may be reduced from positive 3V to positive 1.5V. Depending on the stored state (e.g., logic “1” or logic “0”) of the selected memory cell, the voltage of the selected digit line may be depicted by first digit line voltage **525** or second digit line voltage **530**. In either example, first digit line voltage **525** and second digit line voltage **530** may each be reduced to, for example 0V. Additionally or alternatively, for example, during time interval **505**, digit line selector voltage **540** may also decrease to a positive 1.5V. In some examples, plate line voltage **545** may remain at a constant voltage for the duration of time interval **510**. The plate line voltage may, for example, remain at 0V.

[0078] At time interval **515** a write back operation and/or a precharge command (PCH) may be issued by a memory controller (e.g., memory controller **140** as described with reference to FIG. **1**). The PCH command may, for example, result in first digit line voltage **525**, selected word line voltage **535**, and digit line selector voltage **540** each remaining at a constant voltage level. In some examples, each of first digit line voltage **525**, selected word line voltage **535**, and digit line selector voltage **540** may remain at a positive 1.5V. In other examples, second digit line voltage **530** may be further-reduced to, for example, a negative 1.5V. This reduction may allow for recovery of the corresponding memory cell (e.g., memory cell **105-b** as described with reference to FIG. **4**). Additionally or alternatively, for example, the plate line voltage **545** may remain at a constant voltage for the duration of time interval **515**. In some examples, the plate line voltage may remain at 0V.

[0079] At time interval **520** a recovery pulse may be issued by a memory controller (e.g., memory controller **140** as described with reference to FIG. **1**). In some examples, the application of a recovery pulse may represent applying a recovery pulse to the second access line after the removal of the applied second voltage and may occur in response to the discharging of a ferroelectric capacitor of the second ferroelectric memory (e.g., second ferroelectric memory cell **105-b** as described with reference to FIG. **4**).

[0080] The application of the second voltage may be depicted as a decreased voltage in the selected word line voltage **535**. In some examples, the selected word line voltage may begin at a negative one-point-seven volts (1.7V). In some examples, the selected word line may be reduced to a same voltage as before the application of the second voltage. Depending on the stored state (e.g., logic “1” or logic “0”) of the selected memory cell, the voltage of the selected digit line may be depicted by first digit line voltage **525** or second digit line voltage **530**. For example, if the selected memory cell includes a stored logic “1”, the voltage of the of the corresponding digit line may be represented by first digit line voltage **525**. In some examples, the first digit line voltage may be reduced to, for example, a negative 1.5V, which may allow for recovery of the corresponding memory cell. In other examples, if the selected memory cell includes a stored logic “0”, the voltage of the corresponding digit line may be represented by second digit line voltage **530**. In either instance, the plate line voltage **545** may remain at a constant voltage for the duration of time interval **520**. In some examples, the plate line voltage may remain at 0V.

[0081] FIG. **6** illustrates an example of a circuit **600** that supports a single plate configuration and memory array operation in accordance with various examples of the present disclosure. Circuit **600** may be included in the operation of memory array **400** as described with reference to FIG. **4**. In some examples, circuit **600** may include digit line **605**, selection component **610**, and voltage source **615**. In some examples digit line **605** may be an example of digit line **115-a** as described with reference to FIG. **2**. In other examples, selection component **610** may be referred to as transistor **610** and voltage source **615** may be referred to as a negative voltage source **615**.

[0082] In some examples, selection component **610** may be coupled with a precharge voltage selector **670**. In some examples, precharge voltage selector **670** may include transistors **620**, **625**, and **630**, which may be referred to as a plurality of transistors, and voltage sources **635** and **640**. In some examples, voltage source **635** may be referred to as positive voltage source **635** and voltage source **640** may be referred to as negative voltage source **640**. Additionally or alternatively, for example, one or more of transistors **620**, **625**, and **630** may be a PMOS transistor.

[0083] In other examples, precharge voltage selector **670** may be coupled with a sense amplifier **645**. In some examples the sense amplifier **645** may include a latch **650**, which may be referred to as VDD latch **650**. The Latch **650** may be coupled with a transistor **655**, which may be coupled with a capacitor (e.g., capacitor **205** as described with reference to FIG. **2**) through line **675**. In other examples, the latch **650** may be coupled with a transistor **660**, which may be coupled with a reference line **665** (e.g., reference line **225** as described with reference to FIG. **2**). In some examples, the sense amplifier **645** may be configured such that if the latch stores a logic “1”, a

discharge pulse may be generated. In other examples, the sense amplifier **645** may be configured such that latch stores a logic “0”, a discharge pulse may not be generated.

[0084] In some examples, circuit **600** may be coupled with an one or more aspects of an array of ferroelectric memory cells (e.g., memory array **400** as described with reference to FIG. **4**). The array may include a first ferroelectric memory cell (e.g., first ferroelectric memory cell **105-b** as described with reference to FIG. **4**) coupled with a first access line (e.g., first access line **115-c** as described with reference to FIG. **4**) and a second ferroelectric memory cell (e.g., second ferroelectric memory cell **105-c** as described with reference to FIG. **4**) coupled with a second access line (e.g., a second access line **110-b** as described with reference to FIG. **4**). In some examples, the memory array may include a plate (e.g., plate line **210-a** as described with reference to FIG. **4**) coupled with the first ferroelectric memory cell, the second ferroelectric memory cell, and the first access line.

[0085] Additionally or alternatively, for example, circuit **600** may be coupled with the second ferroelectric memory cell through the second access line. In some examples, circuit **600** may be referred to as a driver **600**, and driver **600** may be coupled with the second ferroelectric memory cell through the second access line. In some examples, the precharge voltage selector **670** may be configured to apply a voltage to the second access line through transistor **610**. The applied voltage may represent selecting a second ferroelectric memory cell by applying a second voltage to a second access line that is coupled with the second ferroelectric memory cell after applying a first voltage to the plate and the first access line coupled with the first ferroelectric memory cell.

[0086] FIG. **7** illustrates a block diagram **700** of a memory array **705** that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure. Memory array **705** may be referred to as an electronic memory apparatus, and may be an example of a component of a memory array (e.g., memory array **100** as described with reference to FIG. **1**) as described herein.

[0087] Memory array **705** may include one or more memory cells **710**, a memory controller **715**, a word line **720**, a plate line **725**, a reference generator **730**, a sense component **735**, a digit line **740**, and a latch **745**. These components may be in electronic communication with each other and may perform one or more of the functions described herein. In some cases, memory controller **715** may include biasing component **750** and timing component **755**. In some cases, sense component **735** may serve as the reference generator **730**. In other cases, reference generator **730** may be optional.

[0088] Memory controller **715** may be in electronic communication with word line **720**, digit line **740**, sense component **735**, and plate line **725**, which may be examples of word line **110**, digit line **115**, sense component **125**, and plate line **210** described with reference to FIGS. **1**, and **2**. Memory array **705** may also include reference generator **730** and latch **745**. The components of memory array **705** may be in electronic communication with each other and may perform aspects of the functions described with reference to FIGS. **1** through **6**. In some cases, reference generator **730**, sense component **735**, and latch **745** may be components of memory controller **715**.

[0089] In some examples, digit line **740** is in electronic communication with sense component **735** and a ferroelectric capacitor of ferroelectric memory cells **710**. A ferroelectric memory cell **710** may be writable with a logic state (e.g., a first or second logic state). Word line **720** may be in electronic communication with memory controller **715** and a selection component of ferroelectric memory cell **710**. Plate line **725** may be in electronic communication with memory controller **715** and a plate of the ferroelectric capacitor of ferroelectric memory cell **710**. Sense component **735** may be in electronic communication with memory controller **715**, digit line **740**, latch **745**, and reference line **760**. reference generator **730** may be in electronic communication with memory controller **715** and reference line **760**. Sense control line **765** may be in electronic communication with sense component **735** and memory controller **715**. These components may also be in electronic communication with other components, both inside and outside of memory array **705**, in addition to components not listed above, via other components, connections, or buses.

[0090] Memory controller **715** may be configured to activate word line **720**, plate line **725**, or digit line **740** by applying voltages to those various nodes. For example, biasing component **750** may be configured to apply a voltage to operate memory cell **710** to read or write memory cell **710** as described above. In some cases, memory controller **715** may include a row decoder, column decoder, or both, as described herein. This may enable memory controller **715** to access one or more memory cells **105**. Biasing component **750** may also provide voltage to reference generator **730** in order to generate a reference signal for sense component **735**. Additionally, biasing component **750** may provide voltage for the operation of sense component **735**.

[0091] In some cases, memory controller **715** may perform its operations using timing component **755**. For example, timing component **755** may control the timing of the various word line selections or plate biasing, including timing for switching and voltage application to perform the memory functions, such as reading and writing, discussed herein. In some cases, timing component **755** may control the operations of biasing component **750**.

[0092] Reference generator **730** may include various components to generate a reference signal for sense component **735**. Reference generator **730** may include circuitry configured to produce a reference signal. In some cases, reference generator **730** may be implemented using other ferroelectric memory cells **105**. Sense component **735** may compare a signal from memory cell **710** (through digit line **740**) with a reference signal from reference generator **730**. Upon determining the logic state, the sense component may then store the output in latch **745**, where it may be used in accordance with the operations of an electronic device that memory array **705** is a part. Sense component **735** may include a sense amplifier in electronic communication with the latch and the ferroelectric memory cell.

[0093] Memory controller **715** and/or at least some of its various sub-components may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions of the memory controller **715** and/or at least some of its various sub-components may be executed by a general-purpose processor, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), an field-programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described in the present disclosure. The memory controller **715** and/or at least some of its various sub-components may be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations by one or more physical devices. In some examples, memory controller **715** and/or at least some of its various sub-components may be a separate and distinct component in accordance with various examples of the present disclosure. In other examples, memory controller **715** and/or at least some of its various sub-components may be combined with one or more other hardware components, including but not limited to an I/O component, a transceiver, a network server, another computing device, one or more other components described in the present disclosure, or a combination thereof in accordance with various examples of the present disclosure.

[0094] Memory controller **715** may apply a first voltage to a plate line and a first access line that are each coupled with a first ferroelectric memory cell. In some examples, memory controller **715** may select a second ferroelectric memory cell by applying a second voltage to a second access line that is coupled with the second ferroelectric memory cell after applying the first voltage. In other examples, memory controller **715** may access the second ferroelectric memory cell by reducing the second voltage applied to the second access line to a third voltage lower than the second voltage. Additionally or alternatively, for example, memory controller **715** may remove the applied second voltage after accessing the selected ferroelectric memory cell of. The memory controller **715** may also apply a second voltage to the second access line to select a second ferroelectric memory cell. In some examples, memory controller **715** may reduce the second voltage to a third voltage to access the second ferroelectric memory cell, and remove the applied second voltage after accessing

the second ferroelectric memory cell. In some cases, a memory controller **715** may be coupled with at least one memory cell of the array and may be operable to apply a first voltage to the plate line and the first access line.

[0095] FIG. **8** shows a block diagram **800** of a memory controller **815** that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure. The memory controller **815** may be an example of aspects of a memory controller **915** described with reference to FIG. **1**. The memory controller **815** may include biasing component **820**, timing component **825**, voltage application component **830**, selection component **835**, accessing component **840**, voltage removal component **845**, voltage maintenance component **850**, voltage setting component **855**, and coupling component **860**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

[0096] Voltage application component **830** may apply a first voltage to a plate line and a first access line that are each coupled with a first ferroelectric memory cell. In some examples voltage application component **830** may apply a recovery pulse to the second access line after the removal of the applied second voltage. In some examples, the discharging of the ferroelectric capacitor of the second ferroelectric memory cell may be based on the application of the recovery pulse. In other examples, voltage application component **830** may apply the first voltage to the plate line and the first access line that are each coupled with the first ferroelectric memory cell of a first deck of ferroelectric memory cells.

[0097] Selection component **835** may select a second ferroelectric memory cell by applying a second voltage to a second access line that is coupled with the second ferroelectric memory cell. In some examples, selection component **835** may select a second ferroelectric memory cell after applying the first voltage. In other examples, selection component **835** may select the second ferroelectric memory cell of a second deck of ferroelectric memory cells by applying the second voltage to the second access line that is coupled with the second deck of ferroelectric memory cells. In some examples, selection component **835** may select the second ferroelectric memory cell of the second deck of ferroelectric memory cells after applying the first voltage.

[0098] Accessing component **840** may access the second ferroelectric memory cell by reducing the second voltage applied to the second access line to a third voltage lower than the second voltage. In other examples, accessing component **840** may access the second ferroelectric memory cell of the second deck of ferroelectric memory cells by reducing the second voltage applied to the second access line to the third voltage lower than the second voltage.

[0099] Voltage removal component **845** may remove the applied second voltage after accessing the selected second ferroelectric memory cell. In other examples, voltage removal component **845** may remove the applied second voltage after accessing the selected second ferroelectric memory cell of the second deck of ferroelectric memory cells. In some cases, the removal of the applied second voltage may include discharging a ferroelectric capacitor of the second ferroelectric memory cell.

[0100] Voltage maintenance component **850** may maintain the second access line at a fixed voltage prior to selecting the second ferroelectric memory. In other examples, voltage maintenance component **850** may maintain the application of the first voltage to the plate line and the first access line until the removal of the applied second voltage.

[0101] Voltage setting component **855** may set a fourth voltage across the second access line in response to the removal of the applied second voltage. In some examples, the fourth voltage may be the same as the fixed voltage

[0102] Coupling component **860** may couple the plate line with each of the first ferroelectric memory cell, the second ferroelectric memory cell, and the first access line. In other examples, coupling component **860** may couple the plate line with each of the first deck of ferroelectric memory cells, the second deck of ferroelectric memory cells, and the first access line.

[0103] In other examples, memory controller **815** may reduce the second voltage to a third voltage to access the ferroelectric memory cell of the second deck. In some examples, memory controller

815 may remove the applied second voltage after accessing the ferroelectric memory cell.

Additionally or alternatively, for example, memory controller **815** may apply a second voltage to the second access line to select a second ferroelectric memory cell.

[0104] In some cases, memory controller **815** may operate the first ferroelectric memory cell and the plate at a same fixed voltage level. In other cases, memory controller **815** may operate the second access line at a voltage level different than the same fixed voltage level. In some examples, memory controller **815** may operate a set of plates coupled with each of the ferroelectric memory cells at a fixed voltage level.

[0105] In some cases, memory controller **815** may operate the second access line at a same voltage as the plate. In some examples, memory controller **815** may apply a first voltage to the plate line and the first access line. Additionally or alternatively, for example, memory controller **815** may apply a recovery pulse after the removal of the applied second voltage to discharge a ferroelectric capacitor of the second ferroelectric memory cell. In some cases, memory controller **815** may apply the first voltage to the plate line and the first access line until the removal of the applied second voltage. In some examples, memory controller **815** may apply a voltage to the second access line through the first transistor and a precharge voltage selector.

[0106] FIG. **9** shows a diagram of a system **900** including a device **905** that supports a single plate configuration and memory array operation in accordance with examples of the present disclosure. Device **905** may be an example of or include the components of a memory array (e.g., memory array **100** as described with reference to FIG. **1**) as described above. Device **905** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, including memory controller **915**, memory cells **920**, basic input/output system (BIOS) component **925**, processor **930**, I/O controller **935**, and peripheral components **940**. These components may be in electronic communication via one or more buses (e.g., bus **910**).

[0107] Memory controller **915** may operate one or more memory cells as described herein. Specifically, memory controller **915** may be configured to support a single plate configuration and memory array operation. In some cases, memory controller **915** may include a row decoder, column decoder, or both, as described herein (not shown).

[0108] Memory cells **920** may store information (i.e., in the form of a logical state) as described herein. BIOS component **925** be a software component that includes BIOS operated as firmware, which may initialize and run various hardware components. BIOS component **925** may also manage data flow between a processor and various other components, e.g., peripheral components, input/output control component, etc. BIOS component **925** may include a program or software stored in read only memory (ROM), flash memory, or any other non-volatile memory.

[0109] Processor **930** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a central processing unit (CPU), a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, processor **930** may be configured to operate a memory array using a memory controller. In other cases, a memory controller may be integrated into processor **930**. Processor **930** may be configured to execute computer-readable instructions stored in a memory to perform various functions (e.g., functions or tasks supporting a single plate configuration and memory array operation).

[0110] I/O controller **935** may manage input and output signals for device **905**. I/O controller **935** may also manage peripherals not integrated into device **905**. In some cases, I/O controller **935** may represent a physical connection or port to an external peripheral. In some cases, I/O controller **935** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. In other cases, I/O controller **935** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, I/O controller **935** may be implemented as part of a processor. In some cases, a user

may interact with device **905** via I/O controller **935** or via hardware components controlled by I/O controller **935**.

[0111] Peripheral components **940** may include any input or output device, or an interface for such devices. Examples may include disk controllers, sound controller, graphics controller, Ethernet controller, modem, universal serial bus (USB) controller, a serial or parallel port, or peripheral card slots, such as peripheral component interconnect (PCI) or accelerated graphics port (AGP) slots.

[0112] Input **945** may represent a device or signal external to device **905** that provides input to device **905** or its components. This may include a user interface or an interface with or between other devices. In some cases, input **945** may be managed by I/O controller **935**, and may interact with device **905** via a peripheral component **940**.

[0113] Output **950** may also represent a device or signal external to device **905** configured to receive output from device **905** or any of its components. Examples of output **950** may include a display, audio speakers, a printing device, another processor or printed circuit board, etc. In some cases, output **950** may be a peripheral element that interfaces with device **905** via peripheral component(s) **940**. In some cases, output **950** may be managed by I/O controller **935**.

[0114] The components of device **905** may include circuitry designed to carry out their functions. This may include various circuit elements, for example, conductive lines, transistors, capacitors, inductors, resistors, amplifiers, or other active or inactive elements, configured to carry out the functions described herein. Device **905** may be a computer, a server, a laptop computer, a notebook computer, a tablet computer, a mobile phone, a wearable electronic device, a personal electronic device, or the like. Or device **905** may be a portion or aspect of such a device.

[0115] FIG. **10** is a flowchart illustrating a method **1000** for a single plate configuration and memory array operation in accordance with examples of the present disclosure. The operations of method **1000** may be implemented by a memory array (e.g., memory array **100** as described with reference to FIG. **1**) or its components as described herein. For example, the operations of method **1000** may be performed by a memory controller (e.g., memory controller **815**) as described with reference to FIGS. **6** through **9**. In some examples, a memory array may execute a set of codes to control the functional elements of the device to perform the functions described below.

Additionally or alternatively, the memory array may perform aspects of the functions described below using special-purpose hardware.

[0116] At block **1005** the memory array may apply a first voltage to a plate line and a first access line that are each coupled with a first ferroelectric memory cell. The operations of block **1005** may be performed according to the methods described herein. In certain examples, aspects of the operations of block **1005** may be performed by a voltage application component as described with reference to FIGS. **6** through **9**.

[0117] At block **1010** the memory array may select a second ferroelectric memory cell by applying a second voltage to a second access line that is coupled with the second ferroelectric memory cell after applying the first voltage. The operations of block **1010** may be performed according to the methods described herein. In certain examples, aspects of the operations of block **1010** may be performed by a selection component as described with reference to FIGS. **6** through **9**.

[0118] At block **1015** the memory array may access the second ferroelectric memory cell by reducing the second voltage applied to the second access line to a third voltage lower than the second voltage. The operations of block **1015** may be performed according to the methods described herein. In certain examples, aspects of the operations of block **1015** may be performed by an accessing component as described with reference to FIGS. **6** through **9**.

[0119] At block **1020** the memory array may remove the applied second voltage after accessing the selected second ferroelectric memory cell. The operations of block **1020** may be performed according to the methods described herein. In certain examples, aspects of the operations of block **1020** may be performed by a voltage removal component as described with reference to FIGS. **6** through **9**.

[0120] In some cases, the method may include applying a first voltage to a plate line and a first access line that are each coupled with a first ferroelectric memory cell. In other examples, the method may include removing the applied second voltage after accessing the selected second ferroelectric memory cell of the second deck of ferroelectric memory cells. Additionally or alternatively, for example, the method may include accessing the second ferroelectric memory cell by reducing the second voltage applied to the second access line to a third voltage lower than the second voltage. In some cases, the method may include removing the applied second voltage after accessing the selected second ferroelectric memory cell.

[0121] In some examples, the method may include maintaining the second access line at a fixed voltage prior to selecting the second ferroelectric memory cell. Additionally or alternatively, for example, the method may include maintaining the application of the first voltage to the plate line and the first access line until the removal of the applied second voltage. In some cases, the method may include setting a fourth voltage across the second access line in response to the removal of the applied second voltage. In some examples, the fourth voltage may be the same as the fixed voltage.

[0122] In some cases, the method may include selecting a second ferroelectric memory cell by applying a second voltage to a second access line coupled with the second ferroelectric memory. In some examples, the second voltage may be applied after applying the first voltage. In other examples, the removal of the applied second voltage may include discharging a ferroelectric capacitor of the second ferroelectric memory cell. In some examples, the method may include applying a recovery pulse to the second access line after the removal of the applied second voltage. In some examples, the discharging of the ferroelectric capacitor of the second ferroelectric memory cell may be based at least in part on the application of the recovery pulse. Additionally or alternatively, for example, the plate line may be coupled with each of the first ferroelectric memory cell, the second ferroelectric memory cell, and the first access line.

[0123] In other cases, the method may include applying the first voltage to the plate line and the first access line. In some examples, the plate line and the first access line may each be coupled with the first ferroelectric memory cell of a first deck of ferroelectric memory cells. In some examples, the method may include selecting the second ferroelectric memory cell of a second deck of ferroelectric memory cells by applying the second voltage to the second access line that may be coupled with the second deck of ferroelectric memory cells. In some examples, the second voltage may be applied after applying the first voltage. Additionally or alternatively, for example, the method may include accessing the second ferroelectric memory cell of the second deck of ferroelectric memory cells by reducing the second voltage applied to the second access line to the third voltage lower than the second voltage. In some examples, the fourth voltage and the fixed voltage may include a negative voltage.

[0124] In some examples, the memory controller may support means for applying a first voltage to the plate line and the first access line. In other examples, the memory controller may support means for applying a second voltage to the second access line to select the second ferroelectric memory cell. Additionally or alternatively, for example, the memory controller may support means for reducing the second voltage to a third voltage to access the second ferroelectric memory cell. In other examples, the memory controller may support means for removing the applied second voltage after accessing the second ferroelectric memory cell. In some examples, the memory controller may support means for applying a recovery pulse, after the removal of the applied second voltage, to discharge a ferroelectric capacitor of the second ferroelectric memory cell. Additionally or alternatively, for example, the memory controller may support means for applying the first voltage to the plate line and the first access line until the removal of the applied second voltage.

[0125] It should be noted that the methods described above describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Furthermore, examples from two or more of the methods may be combined.

[0126] Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof. Some drawings may illustrate signals as a single signal; however, it will be understood by a person of ordinary skill in the art that the signal may represent a bus of signals, where the bus may have a variety of bit widths.

[0127] As used herein, the term “virtual ground” refers to a node of an electrical circuit that is held at a voltage of approximately zero volts (0V) but that is not directly connected with ground.

Accordingly, the voltage of a virtual ground may temporarily fluctuate and return to approximately 0V at steady state. A virtual ground may be implemented using various electronic circuit elements, such as a voltage divider consisting of operational amplifiers and resistors. Other implementations are also possible. “Virtual grounding” or “virtually grounded” means connected to approximately 0V.

[0128] The term “electronic communication” and “coupled” refer to a relationship between components that support electron flow between the components. This may include a direct connection between components or may include intermediate components.

[0129] Components in electronic communication or coupled to one another may be actively exchanging electrons or signals (e.g., in an energized circuit) or may not be actively exchanging electrons or signals (e.g., in a de-energized circuit) but may be configured and operable to exchange electrons or signals upon a circuit being energized. By way of example, two components physically connected via a switch (e.g., a transistor) are in electronic communication or may be coupled regardless of the state of the switch (i.e., open or closed).

[0130] The term “isolated” refers to a relationship between components in which electrons are not presently capable of flowing between them; components are isolated from each other if there is an open circuit between them. For example, two components physically connected by a switch may be isolated from each other when the switch is open.

[0131] As used herein, the term “shorting” refers to a relationship between components in which a conductive path is established between the components via the activation of a single intermediary component between the two components in question. For example, a first component shorted to a second component may exchange electrons with the second component when a switch between the two components is closed. Thus, shorting may be a dynamic operation that enables the flow of charge between components (or lines) that are in electronic communication.

[0132] The devices discussed herein, including memory array **100**, may be formed on a semiconductor substrate, such as silicon, germanium, silicon-germanium alloy, gallium arsenide, gallium nitride, etc. In some cases, the substrate is a semiconductor wafer. In other cases, the substrate may be a silicon-on-insulator (SOI) substrate, such as silicon-on-glass (SOG) or silicon-on-sapphire (SOP), or epitaxial layers of semiconductor materials on another substrate. The conductivity of the substrate, or sub-regions of the substrate, may be controlled through doping using various chemical species including, but not limited to, phosphorous, boron, or arsenic. Doping may be performed during the initial formation or growth of the substrate, by ion-implantation, or by any other doping means.

[0133] A transistor or transistors discussed herein may represent a field-effect transistor (FET) and comprise a three terminal device including a source, drain, and gate. The terminals may be connected to other electronic elements through conductive materials, e.g., metals. The source and drain may be conductive and may comprise a heavily-doped, e.g., degenerate, semiconductor region. The source and drain may be separated by a lightly-doped semiconductor region or channel. If the channel is n-type (i.e., majority carriers are electrons), then the FET may be referred to as a n-type FET. If the channel is p-type (i.e., majority carriers are holes), then the FET may be referred to as a p-type FET. The channel may be capped by an insulating gate oxide. The channel

conductivity may be controlled by applying a voltage to the gate. For example, applying a positive voltage or negative voltage to an n-type FET or a p-type FET, respectively, may result in the channel becoming conductive. A transistor may be “on” or “activated” when a voltage greater than or equal to the transistor's threshold voltage is applied to the transistor gate. The transistor may be “off” or “deactivated” when a voltage less than the transistor's threshold voltage is applied to the transistor gate.

[0134] The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

[0135] In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

[0136] Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

[0137] The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a digital signal processor (DSP) and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

[0138] The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

[0139] The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. (canceled)
2. A method, comprising: setting a plate to a first voltage, wherein the plate is coupled with a first memory cell and a first digit line; isolating the first digit line from a second digit line based at least in part on setting the plate to the first voltage; coupling the plate with the second digit line based at least in part on isolating the first digit line from the second digit line; and applying, based at least in part on coupling the plate with the second digit line, a second voltage to a word line that is coupled with the first memory cell.
3. The method of claim 2, further comprising: refraining from applying the first voltage to the first digit line based at least in part on isolating the first digit line from the second digit line.
4. The method of claim 2, further comprising: applying the first voltage to the second digit line based at least in part on coupling the plate with the second digit line.
5. The method of claim 2, wherein applying the second voltage to the word line is based at least in part on isolating the first digit line from the second digit line.
6. The method of claim 2, wherein a first deck of memory cells comprises the first memory cell and a second memory cell, and wherein a second deck of memory cells comprises a third memory cell, the method further comprising: setting a second plate to a third voltage, wherein the second plate is coupled with the third memory cell and a third digit line; isolating the third digit line from a fourth digit line based at least in part on setting the second plate to the third voltage; coupling the second plate with the fourth digit line based at least in part on isolating the third digit line from the fourth digit line; and applying, based at least in part on coupling the second plate with the fourth digit line, a fourth voltage to a second word line that is coupled with the third memory cell.
7. The method of claim 2, further comprising: applying a third voltage to the first digit line based at least in part on coupling the plate with the second digit line.
8. The method of claim 7, wherein the third voltage is less than the second voltage.
9. The method of claim 2, wherein the first voltage comprises a ground reference voltage.
10. A method, comprising: determining, based at least in part on a precharge command, a logic state of a memory cell that is coupled with a digit line; applying a first voltage to the digit line based at least in part on the logic state of the memory cell, wherein whether the first voltage has a negative polarity or is a ground reference voltage is based at least in part on the logic state of the memory cell; and applying a second voltage to the digit line that is different than the first voltage based at least in part on the logic state of the memory cell, wherein whether the second voltage has the negative polarity or is the ground reference voltage is based at least in part on the logic state of the memory cell.
11. The method of claim 10, further comprising: determining that the logic state is associated with a first logic value, wherein the first voltage has the negative polarity and the second voltage is the ground reference voltage based at least in part on determining the logic state of the memory cell is associated with the first logic value.
12. The method of claim 10, further comprising: determining that the logic state is associated with a second logic value, wherein the first voltage is the ground reference voltage and the second voltage has the negative polarity based at least in part on determining the logic state of the memory cell is associated with a second logic value.

- 13.** The method of claim 10, further comprising: performing a precharge operation, wherein the first voltage is applied to the digit line as part of the precharge operation.
- 14.** The method of claim 13, wherein the logic state is determined as part of the precharge operation.
- 15.** The method of claim 13, wherein the second voltage is applied after a completion of the precharge operation.
- 16.** The method of claim 13, further comprising: applying a third voltage to a word line that has the negative polarity based at least in part on applying the second voltage to the digit line.
- 17.** A memory system, comprising: one or more memory devices; and one or more controllers coupled with the one or more memory devices and configured to cause the memory system to: apply a first voltage to a plate that is coupled with a first digit line; isolate the first digit line from a second digit line based at least in part on applying the first voltage to the plate; refrain from applying the first voltage to the first digit line based at least in part on isolating the first digit line from the second digit line; and apply, based at least in part on isolating the first digit line from the second digit line, a second voltage to a word line.
- 18.** The memory system of claim 17, wherein the one or more controllers are further configured to cause the memory system to: couple the plate with the second digit line based at least in part on isolating the first digit line from the second digit line.
- 19.** The memory system of claim 18, wherein the one or more controllers are further configured to cause the memory system to: apply the first voltage to the second digit line based at least in part on coupling the plate with the second digit line.
- 20.** The memory system of claim 17, wherein the one or more controllers are configured to cause the memory system to apply the second voltage to the word line based at least in part on isolating the first digit line from the second digit line.
- 21.** The memory system of claim 17, wherein the one or more controllers are further configured to cause the memory system to: apply a third voltage to the first digit line based at least in part on isolating the first digit line from the second digit line.
-