

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392478
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Zhao; Xueliang

Lamp fixing member, lamp and lamp fixing structure

Abstract

The present invention discloses a lamp fixing member and a lamp and a lamp fixing structure. The lamp fixing member comprises a first fixing member and a second fixing member, the first fixing member and the second fixing member are movably connected to form a connected state or a disconnected state so as to fix the first fixing member on or disassemble it from the keel member.

Inventors:	Zhao; Xueliang (Ningbo, CN)
Applicant:	Zhao; Xueliang (Ningbo, CN)
Family ID:	1000008767532
Appl. No.:	18/812937
Filed:	August 22, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240410554 A1	Dec. 12, 2024

Foreign Application Priority Data

CN	202421453132.5	Jun. 24, 2024
----	----------------	---------------

Publication Classification

Int. Cl.: F21V21/04 (20060101); F21S8/04 (20060101); F21Y115/10 (20160101)

U.S. Cl.:

CPC	F21V21/047 (20130101); F21S8/04 (20130101); F21S8/043 (20130101); F21V21/043 (20130101); F21V21/045 (20130101); F21V21/048 (20130101); F21Y2115/10 (20160801)
-----	---

Field of Classification Search

CPC: F21V (21/048); F21S (8/043); F21S (8/04)

USPC: 362/148

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2010/0309658	12/2009	Rouse et al.	N/A	N/A
2011/0176319	12/2010	Hopkins	248/220.21	F21S 8/043
2013/0301267	12/2012	Badley	362/249.1	F21V 29/76
2016/0061395	12/2015	White et al.	N/A	N/A
2019/0145611	12/2018	May	362/147	F21S 8/043
2020/0200372	12/2019	Béland	N/A	F21V 21/14
2023/0304639	12/2022	Yan	N/A	F21V 21/048

Primary Examiner: Tso; Laura K

Background/Summary

TECHNICAL FIELD

(1) The present invention belongs to the field of lighting fixtures, in particular to a lamp fixing member, a lamp and a lamp fixing structure.

BACKGROUND

(2) Lighting fixtures are tools required for lighting in home and office space. The light sources include fluorescent tubes, LED lamp groups and other forms. For scenarios with suspended ceiling decoration, the lighting fixtures are usually embedded and installed in the suspended ceiling to replace one or more suspended ceiling tiles. For example, in kitchen or toilet decoration, the suspended ceiling tile is usually snap-fitted in the keel to achieve the purpose of lighting fixture installation. However, on the one hand, such an installation method requires for a specified shape of lamps that needs to be the size of one or two suspended ceiling tiles. On the other hand, since lamps replace the suspended ceiling tile, the original decorative layout of the suspended ceiling will also be damaged.

(3) Therefore, it is necessary to develop a new lamp fixing member that does not damage the original decorative layout of the suspended ceiling. In addition, the convenience of installation and disassembly may also need to be considered in practical application, as well as allowing users to set up the installation shape of lamps according to their own needs to meet different use habits or requirements.

SUMMARY

(4) The purpose of the present invention is to provide a lamp fixing member, which is easy to install and disassemble and has various shapes after assembly, as well as a lamp and a lamp fixing structure.

(5) As a first aspect of the present invention, there is provided a lamp fixing member for fixing a lamp body to a keel member. The lamp fixing member comprises a first fixing member and a second fixing member. The first fixing member is connected with the lamp body, and the first

fixing member and the second fixing member are movably connected to form a connected state or a disconnected state. In the connected state, the second fixing member fixes the first fixing member to the keel member, and in the disconnected state, the first fixing member can be disassembled from the keel member.

(6) According to the above-mentioned lamp fixing member, the second fixing member is pivotally connected to the first fixing member for snap-fitting on or separating from the keel member by pivoting of the second fixing member.

(7) According to the above-mentioned lamp fixing member, the second fixing member is detachably connected to the first fixing member to snap-fit the keel member on or separate it from the first fixing member through the second fixing member.

(8) According to the above-mentioned lamp fixing member, when the second fixing member is pivotally connected, the lamp fixing member further comprises a fastener; the second fixing member comprises a fourth arm part and a fifth arm part, and the fourth arm part is pivotally connected with the first fixing member; the fourth arm part and the fifth arm part are respectively provided with a first fastening hole and a second fastening hole; the fastener is inserted into the first fastening hole and the second fastening hole to drive the fifth arm part to approach or move away from the fourth arm part by screwing of the fastener.

(9) According to the above-mentioned lamp fixing member, the first fixing member comprises a first arm part and a second arm part. The first arm part is connected with or integrated with the second arm part. The fourth arm part is pivotally connected to the first arm part. The second arm part is connected with the lamp body.

(10) According to the above-mentioned lamp fixing member, a pivotal part of the first fixing member and the second fixing member is convexly arranged to abut against the lower part of an upper flange of the keel member.

(11) According to the above-mentioned lamp fixing member, the first fastening hole is a through hole and the second fastening hole is a threaded hole.

(12) According to the above-mentioned lamp fixing member, both the first fastening hole and the second fastening hole are through holes, and a nut is provided outside the second fastening hole to threadably engage with the fastener.

(13) According to the above-mentioned lamp fixing member, the fastener is a butterfly bolt.

(14) According to the above-mentioned lamp fixing member, the fifth arm part is further provided with a clamping convex, and a guide edge is further arranged below the clamping convex.

(15) According to the above-mentioned lamp fixing member, when the second fixing member is detachably connected, the second fixing member comprises a sixth arm part and a seventh arm part, the sixth arm part and the seventh arm part are spaced apart so as to form a snap-fit cavity therebetween; the first fixing member comprises a first arm part and a second arm part, the first arm part is connected with or integrated with the second arm part, and the first arm part fits to a side wall of the keel member and is fixed by the second fixing member in a snap-fit manner.

(16) According to the above-mentioned lamp fixing member, the second fixing member is made of an elastic material so that it can be elastically snap-fitted, and the width of the snap-fit cavity is less than the fitting width between the first arm part and the keel member, so that the second fixing member is in a resiliently expanded state after being snap-fitted.

(17) According to the above-mentioned lamp fixing member, the lamp fixing member further comprises a fastener; the first arm part and the sixth arm part are provided with a first fastening hole correspondingly, and the seventh arm part is provided with a second fastening hole; the fastener is inserted into the first fastening hole and the second fastening hole to drive the sixth arm part to approach or move away from the seventh arm part by screwing of the fastener.

(18) According to the above-mentioned lamp fixing member, the first arm part comprises an eighth arm part and a ninth arm part, the ninth arm part is offset from and protruded relative to the eighth arm part, and a boss is formed at the connection therebetween.

- (19) According to the above-mentioned lamp fixing member, when the second fixing member is elastically snap-fitted, a fastening slot and a fastening point are provided on the sixth arm part and the first arm part, respectively; the fastening slot is in concave-convex fit, friction fit or magnetic fit with the fastening point to position the second fixing member.
- (20) As a second aspect of the present invention, there is provided a lamp fixing member for fixing the lamp body to the keel member. The lamp fixing member comprises a third fixing member and a fastener, the third fixing member is fixedly connected to the keel member, and the third fixing member is detachably connected with the lamp body.
- (21) The third fixing member comprises a connecting arm and a locking arm arranged on both sides of the keel member, respectively, a fastening slot for providing at least part of the keel member therein is formed between a connecting arm and a locking arm, and the fastener acts between the connecting arm and the locking arm to press or unscrew them.
- (22) According to the above-mentioned lamp fixing member, the connecting arm and the locking arm are respectively provided with a first fastening hole and a second fastening hole, respectively.
- (23) According to the above-mentioned lamp fixing member, the connecting arm is detachably connected with the lamp body through a second arm part.
- (24) According to the above-mentioned lamp fixing member, wherein the first fastening hole is a through hole, and the second fastening hole is a threaded hole. The fastener is arranged passing through the first fastening hole and threadably engaged with the second fastening hole to drive the connecting arm to approach or move away from the locking arm by screwing of the fastener.
- (25) According to the above-mentioned lamp fixing member, both the first fastening hole and the second fastening hole are through holes. After passing through the first fastening hole and the second fastening hole, the fastener is threadably engaged with a separately provided nut, so that the connecting arm can be pressed or unscrewed to approach or move away from the locking arm.
- (26) According to the above-mentioned lamp fixing member, the fastener is a butterfly bolt for convenience of manual screwing.
- (27) According to the above-mentioned lamp fixing member, a lower end of the second arm part is bent downwards to form a third arm part, and the third arm part is spaced from the second arm part; the third arm part is further provided with a connecting positioning piece, and the connecting positioning piece abuts against a side wall or an inner wall of the lamp body fixing slot of the lamp body.
- (28) According to the above-mentioned lamp fixing member, the third arm part is arranged in parallel and spaced from the second arm part, and the connecting positioning piece comprises at least either a first positioning piece protruding on the third arm part or a second positioning piece formed on the third arm part.
- (29) As a third aspect of the present invention, there is provided a lamp comprising a lamp body and at least one lamp fixing member, wherein the lamp fixing member is any one of the above-mentioned lamp fixing member.
- (30) As a fourth aspect of the present invention, there is provided a lamp fixing structure comprising a keel member, a lamp body and a lamp fixing member, wherein the lamp fixing member is any one of the above-mentioned lamp fixing member.
- (31) According to the above-mentioned lamp fixing structure, the keel member comprises a keel riser, and an upper flange is formed at the top of the keel riser for clamping the locking part of the lamp fixing member below it.
- (32) According to the above-mentioned lamp fixing structure, a lamp body fixing slot is provided on the top surface of the lamp body, and the lamp body fixing slot has an "L" or "I" cross-sectional shape.
- (33) According to the above-mentioned lamp fixing structure, a hanger platform is further provided at a lower end of the keel riser, and the second arm part is arranged fitting to the hanger platform, so that the suspended ceiling tile is carried by the second arm part and the lamp body is arranged

adjacent to a lower surface of the keel member or the suspended ceiling tile.

(34) According to the above-mentioned lamp fixing structure, the third arm part is positioned in a tight or magnetic fit with the lamp body fixing slot, so that the position of the lamp body can be adjusted relative to the lamp fixing member.

(35) According to the above-mentioned lamp fixing structure, the lamp fixing structure further comprises a cable fixing member, the cable fixing member comprises a cable fixing body and a cable fixing buckle detachably connected with each other; the cable fixing body comprises a first body and a second body, and the second body is fixedly connected with the keel member and the lamp body; the cable fixing buckle comprises a cable trough and a second buckling piece, a first buckling piece is provided on the first body, and the first buckling piece is detachably connected with the second buckling piece.

(36) According to the above-mentioned lamp fixing structure, after assembly, the lamp fixing structure makes each lamp body in a linear, rectangular or cross-shaped layout.

(37) The lamp fixing member, the lamp and the lamp fixing structure of the present invention have at least the following beneficial effects: 1. The lamp body is fixed to the keel member through a lamp fixing member. The lamp fixing member is specifically composed of a first fixing member and a second fixing member movably arranged with each other, wherein the first fixing member is connected with the lamp body and fitted to a side wall of the keel member, and the first fixing member and the keel member are fixedly connected with each other through the second fixing member. The second fixing member can be, relative to the first fixing member, fixed or disassembled by a pivoting structure or a detachable snap-fit structure, so that the fixing and stabilization between the lamp body and the keel member can be realized for the convenience of installation and disassembly. 2. The lamp body is attached and fixed below the keel member, so that the shapes formed by multiple lamp bodies can be set as required, such as rectangular, square, L-shaped, cross-shaped, etc., providing a very flexible installation convenience and diversified assembly effects. 3. The lamp body can be slidably arranged relative to the lamp fixing member, so that the position of the lamp body can be adjusted within the setting range as required. This can form the above-mentioned diversified installation shapes when adjacent lamp bodies are spliced. 4. The lamp body is located at the junction of adjacent suspended ceiling tiles, which will not weaken the decorative effect of the suspended ceiling tiles.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram of the use state where the lamp body is fixed on the keel by the lamp fixing member according to Embodiment I of the present invention, which is from a bottom perspective;

(2) FIG. 2 is a structural schematic diagram and its partial enlarged schematic diagram with the suspended ceiling tile hidden in the embodiment of FIG. 1, which are from a top perspective;

(3) FIG. 3 is a structural schematic diagram and its partial enlarged schematic diagram of the lamp according to the embodiment shown in FIG. 1;

(4) FIG. 4 is a structural schematic diagram of the lamp fixing member according to the embodiment shown in FIG. 1;

(5) FIG. 5 is an exploded view of the structure in FIG. 4;

(6) FIG. 6 is a structural schematic diagram of the back view of FIG. 4;

(7) FIG. 7 is an exploded view of the cable fixing member according to the embodiment shown in FIG. 1;

(8) FIG. 8 is a schematic diagram of the fitting effect of the cable fixing member shown in FIG. 7;

(9) FIG. 9 is a structural schematic diagram of the lamp fixing member according to Embodiment

II of the present invention;

(10) FIG. **10** is an exploded view of the structure in FIG. **9**;

(11) FIG. **11** is an assembly diagram of the lamp fixing member according to Embodiment III of the present invention;

(12) FIG. **12** is a structural schematic diagram of the lamp according to Embodiment IV of the present invention;

(13) FIG. **13** is an exploded view of the partial structure according to the embodiment shown in FIG. **12**;

(14) FIG. **14** is a structural schematic diagram of the third fixing member according to the embodiment shown in FIG. **12**;

(15) FIG. **15** is a schematic diagram I of the assembled state of the lamp fixing structure according to the present invention, wherein each lamp body is arranged in a square layout and its length relative to two lamp bodies is greater than that of the other two lamp bodies; in some embodiments, the lamp bodies with equal length can be staggered to form a square layout;

(16) FIG. **16** is a schematic diagram II of the assembled state of the lamp fixing structure according to the present invention, wherein multiple lamp bodies are arranged in a cross-shaped layout;

(17) FIG. **17** is a schematic diagram III of the assembled state of the lamp fixing structure according to the present invention, wherein multiple lamp bodies are arranged in a straight line;

(18) FIG. **18** is the schematic diagram IV of the assembled state of the lamp fixing structure according to the present invention, wherein each lamp body is arranged in a rectangular layout, and the shorter lamp body is sandwiched between two longer lamp bodies;

(19) FIG. **19** is a schematic diagram V of the assembled state of the lamp fixing structure according to the present invention. The lamp body is arranged in an “L” shape, and the lengths of each lamp body may be equal or unequal.

REFERENCE NUMERALS IN THE DRAWINGS

(20) keel **100**, keel member **110**, suspended ceiling tile **120**, keel riser **111**, hanger platform **112**, upper flange **113**, slot **114** and hanger hole **102**, lamp **200**, lamp body **210**, lamp fixing member **220**, power cord **201**, connection sub-wire **202**, sub-wire connector **203**, pivot axis **204**, lamp body fixing slot **211**, slot wall **212**, first fixing member **221**, second fixing member **222**, fastener **223**, fastening slot **224**, connecting piece **225**, first positioning member **226**, third fixing member **227**, connecting arm **228**, locking arm **229** and top arm **230**, first arm part **241**, second arm part **242**, third arm part **243**, first pivot member **244**, second positioning member **245**, fourth arm part **251**, fifth arm part **252**, guide edge **253**, second pivot member **254**, first fastening hole **255**, second fastening hole **256**, pivotal part **257**, clamping convex **258**, sixth arm part **261**, seventh arm part **262**, snap-fit cavity **263**, fastening slot **264**, fastening point **265**, limiting piece **266**, eighth arm part **267**, ninth arm part **268**, boss **269**, cable fixing member **270**, cable fixing body **271**, cable fixing buckle **272**, first body **273**, second body **274**, first buckling piece **275**, second buckling piece **276**, cable trough **277**, buckle hole **278** and clamping table **279**.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(21) The protection scope of the present invention will be described in detail below with reference to embodiments and drawings of the present invention. It should be noted that the following descriptions are examples, and their purpose is to facilitate understanding but not limit the protection scope of the present invention. All conventional changes made on the basis of embodiments shall fall within the protection scope of the present invention.

Embodiment I

(22) As shown in FIGS. **1-6**, a lamp fixing structure is used to fix the lamp **200** on the keel **100** so that an assembled state as shown in any of FIG. **15**, **16**, **17**, **18** or **19** can be formed, wherein the lamp bodies **210** of the lamp **200** may have equal or different lengths, and each assembled lamp body **210** is generally arranged below the keel member **110** to which it is fixed.

(23) As shown in FIGS. **2-3**, the lamp **200** of this embodiment is composed of a lamp body **210** and

a power cord **201** for supplying power to the lamp body **210**. The lamp body **210** has several LED beads or LED light emitting modules for lighting. The power cord **201** comprises two connection sub-wires **202**, one end of each connection sub-wire **202** is electrically connected to the lamp body **210** and the other end is provided with a sub-wire connector **203**. The two connection sub-wires **202** are connected in parallel or series so that multiple lamps **200** are electrically connected in parallel or series. In other embodiments, the power cord **201** of each lamp **200** may also have only one connection sub-wire **202**.

(24) In this embodiment, the lamp **200** is fixed to a keel member **110** through at least one lamp fixing member **220**. The lower end of the lamp fixing member **220** is connected with the lamp body **210** and the upper end thereof is connected with the keel member **110**.

(25) The keel member **110** has a cross-sectional shape of “I” and extends to form an elongated member, which is known in the art. It consists of a keel riser **111** and a hanger platform **112**. The keel riser **111** is arranged in a vertical direction while the hanger platform **112** is arranged horizontally so as to form a cross-sectional shape of a “I” or similar shape. The hanger platform **112** is used for installing the suspended ceiling tile **120** thereon, and adjacent keel risers **111** form a hanger hole **102** in which the suspended ceiling tile **120** is installed to achieve the purpose of installing the suspended ceiling tile **120** on the keel **100**. Preferably, an upper flange **113** is convexly provided at the top end of the keel riser **111**. The upper flange **113** may be rectangular or circular and protruded on the side wall of the keel riser **111** to form a slot **114** between the upper flange **113** and the hanger platform **112** on the side wall of the keel riser **111** for engaging the first arm part **241** in the slot **114**.

(26) The top surface of the lamp body **210** is provided with a lamp fixing slot **211**. The lamp fixing slot **211** has an “L” or “I” shape in cross section for setting the lower end of the lamp fixing member **220** therein. Preferably, lamp body end caps **213** are provided at both ends of the lamp body **210** to cover the end face of the lamp body **210**. A slot wall **212** is formed on the side wall of the lamp body fixing slot **211**.

(27) As shown in FIGS. 4-6, the lamp fixing member **220** of this embodiment is specifically composed of a first fixing member **221**, a second fixing member **222** and a fastener **223**. The upper end of the first fixing member **221** is pivotally connected to the lower end of the second fixing member **222** so that they form a pivotal connection and are rotatably arranged around the pivot axis **204**. The lower end of the first fixing member **221** is connected to the lamp body fixing slot **211** of the lamp body **210**.

(28) Here, the second fixing member **222** is a U-shaped member or V-shaped member and arranged upside down to form a fastening slot **224** inside it for snap-fitting the keel riser **111**. The fastener **223** is provided on the second fixing member **222** to tension or loosen the second fixing member **222** by rotation of the fastener **223**. The tensioned second fixing member **222** is closely connected with the keel riser **111** to avoid separation of the lamp fixing member **220** from the keel riser **111**. A connecting piece **225** and a first positioning piece **226** are formed at the lower end of the first fixing member **221**. The connecting piece **225** is formed by bending the lower end of the first fixing member **221** so that the connecting piece **225** can be assembled and connected in the lamp body fixing slot **211**; the first positioning piece **226** is protruded on the connecting piece **225**. After the first fixing member **221** and the lamp body fixing slot **211** are assembled and connected, the first positioning piece **226** contacts with the slot wall **212** of the lamp body fixing slot **211**, so that the lamp fixing member **220** and the lamp body **210** form a relative positioning without arbitrary movement.

(29) In this embodiment, the first fixing member **221** is processed or molded from sheet material and mainly consists of a first arm part **241** and a second arm part **242**. The first arm part **241** and the second arm part **242** are connected end-to-end and perpendicular to each other to form an L-shaped structure. A first pivot member **244** is provided at the upper end of the first arm part **241**. The first pivot member **244** is preferably a pivot sleeve; the lower end of the second arm part **242** is

bent downward to form a third arm part **243**, the third arm part **243** is arranged in parallel and spaced from the second arm part **242** so that the third arm part **243** can be fitted to the lamp body fixing slot **211**. A second positioning member **245** is further formed on the third arm part **243**. The second positioning member **245** is formed by stamping the first arm part **241**. The width of the second positioning member **245** is greater than that of the third arm part **243**, preferably about equal to that of the lamp body fixing slot **211**, so as to position and fit the first fixing member **221** in the lamp body fixing slot **211** through the second positioning member **245**. The first positioning piece **226** is protruded on the third arm part **243** to contact with the slot wall **212**, and the first positioning piece **226** and the second positioning piece **245** are formed as connecting positioning pieces.

(30) The second fixing member **222** is a flat-bottomed V-shaped member and arranged upside down. The second fixing member **222** consists of the fourth arm part **251** and the fifth arm part **252**, which are preferably integrally molded. A second pivot member **254** is formed at an outer end of the fourth arm part **251** on the side where the fastening slot **224** is further formed in the fourth arm part **251** and the fifth arm part **252**. The second pivot member **254** is further preferably a pivot sleeve. After aligning and fitting the first pivot member **244** with the second pivot member **254**, a pivot is inserted to form a pivotal connection between the first fixing member **221** and the second fixing member **222**. Of course, in another embodiment, the first pivot member **244** and the second pivot member **254** may further be pivotally connected by one being a pivot sleeve and the other being a pivot.

(31) A guide edge **253** is provided at the outer end of the fourth arm part **251** on the other side of the second fixing member **222**, which has a beveled or curved configuration and is arranged outwardly to facilitate allowing the keel riser **111** to fit more conveniently to the fastening slot **224** when the second fixing member **222** pivots.

(32) The first fastening holes **255** are respectively provided on the two fourth arm parts **251**, and fasteners **223** act in the two first fastening holes **255** to tension or loosen the two fourth arm parts **251**; for example, a track-shaped through hole is provided on the fourth arm part **251** as the first fastening hole **255** and a threaded hole is provided on the fifth arm part **252** as the second fastening hole **256**.

(33) Optimally, the fastener **223** is a butterfly bolt which threads into the second fastening hole **256** after passing through the first fastening hole **255**. The butterfly bolt is screwed to resist against the fourth arm part **251** and pressed or loosened toward the fifth arm part **252**. In other embodiments, the fastener **223** may be compressed or unscrewed with a threaded fit between the first fastening hole **255** and the second fastening hole **256**, or the second fastening hole **256** may be a through hole to compress or unscrew the fourth and fifth arm parts by threading the fastener **223** at an outer side of the fifth arm part **252** by an additionally provided nut.

(34) Optimally, as shown in FIG. 3, the lamp **200** further has a cable fixing member **270**, the cable fixing member **270** is used for fixing the power cord **201** to the keel member **110**, such as fixing the connection between the lower end of the power cord **201** and the lamp **200** to the keel member **110**, so that the electrical connection between the power cord **201** and the lamp **200** is not easy to be damaged. The power cord **201** can also be bent and fixed to ensure that the suspended ceiling tile **120** (e.g., gypsum tile) is flat after installation without being raised.

(35) As shown in FIG. 7-8, the cable fixing member **270** comprises a cable fixing body **271** and a cable fixing buckle **272** detachably connected with each other. The power cord **201** is fixed on the cable fixing body **271** by the cable fixing buckle **272**. Here, the cable fixing body **271** is generally in an L-shaped shape and has a first body **273** and a second body **274** which are adjacently connected or integrated with each other. The second body **274** has a structure similar to that of the second arm part **242** for connecting with the lamp body fixing slot **211** and fastening the cable fixing body **271** to the hanger platform **112** of the keel member **110**. The first body **273** is fitted to the side wall of the keel riser **111**, and the assembled structure is as shown in FIG. 8. The cable

fixing buckle **272** comprises a cable trough **277** and second buckling pieces **276** formed on both sides of the cable trough **277**, while the first body **273** is correspondingly provided with a first buckling piece **275**. The cable trough **277** is used to receive the power cord **201** therein for fixing it. The first buckling piece **275** and the second buckling piece **276** form a detachable structure. The cable fixing buckle **272** is detachably connected to the cable fixing body **271**. For example, in this embodiment, the first buckling piece **275** is a card stamped and formed on the cable fixing body **271**. It is an elastic member with clamping protrusions, while the second buckling piece **276** is a set of buckle holes, which comprises two buckle holes **278** spaced apart and a clamping table **279** formed between the two buckle holes **278**. During use, the cable fixing body **271** is first installed in the lamp body fixing slot **211** and fixed on the keel **110** together with the lamp fixing member **220**. The power cord **201** is fitted to the cable fixing body **271** and then the cable fixing buckle **272** is fitted from top to bottom so that the first buckling piece **275** is fastened with the second buckling piece **276**, even if the clamping convex of the first buckling piece **275** is clamped into the clamping table **279**. During removal, it is only necessary to move the cable fixing buckle **272** upward.

Embodiment II

(36) As shown in FIGS. **9-10**, the main structure of a lamp fixing member is similar to that of Embodiment I, except that the connection mode between the lamp fixing member **220** and the keel riser **111** in this embodiment is different from that in Embodiment I. The lamp fixing member **220** is changed from being pivotally buckled with the keel riser **111** to being detachably buckled.

(37) In this embodiment, the lamp fixing member **220** is composed of a first fixing member **221** and a second fixing member **222**. The second fixing member **222** is detachably assembled on the first fixing member **221** to be snap-fitted to or separated from the first fixing member **221**. When the second fixing member **222** is snap-fitted to the first fixing member **221**, a snap-fit state as shown in FIG. **9** will be formed; when the second fixing member **222** is separated from the first fixing member **221**, a disconnected state as shown in FIG. **10** will be formed.

(38) The second fixing member **222** is a U-shaped member, which is preferably made of sheet material by bending or molding. The second fixing member **222** has the sixth arm part **261** and the seventh arm part **262** spaced from each other. The sixth arm part **261** is connected or integrated with the inner end of the seventh arm part **262**. The outer ends are respectively provided with guide edges **253** to play a guiding role during snap-fit; of course, the guide edge **253** may not be provided regardless of the guiding effect at the time of snap-fit. A snap-fit cavity **263** is provided between the sixth arm part **261** and the seventh arm part **262**. The snap-fit cavity **263** is used to snap-fit the keel riser **111** with the second fixing member **222** when the second fixing member **222** fits on the side wall of the keel riser **111**. The sixth arm part **261** is further provided with a fastening slot **264**. The fastening slot **264** is preferably in the shape of a track or an elongated strip, or a plurality of fastening slots spaced from each other along the snap-fit direction, so as to achieve the purpose of allowing the second fixing member **222** to be snap-fitted to the first fixing member **221** at different positions to meet the assembly needs of different keel risers **111**.

(39) The first fixing member **221** is formed by bending or molding a sheet-like material, and the first fixing member **221** has a generally L shape so as to form two arm parts which are relatively vertical or nearly vertical. One arm part fits to the side of the keel riser **111** substantially in parallel while the other arm part extends in parallel with the suspended ceiling tile. The arm part parallelly fitted to the keel riser **111** is specifically composed of an eighth arm part **267** and a ninth arm part **268**, the eighth arm part **267** is provided at the upper end of the ninth arm part **268**, a lower end of the ninth arm part **268** is connected or integrated with the second arm part **242**. The ninth arm part **268** is offset from and protruded relative to the eighth arm part **267**, and a boss **269** is formed at the connection therebetween. The eighth arm part **267** is further provided with a fastening point **265**, the fastening point **265** is used to snap-fit in the fastening slot **264** of the sixth arm part **261** so that the second fixing member **222** and the first fixing member **221** form a stable snap-fit connection.

(40) Preferably, limiting pieces **266** are respectively provided on both sides of the eighth arm part

267. The limiting piece **266** is preferably formed by bending to limit the second fixing member **222** during snap-fit and form a stable snap-fit whole.

(41) In this embodiment, the snap-fit structure of the second arm part **242** is the same as that of the lamp body fixing slot **211**, i.e., it further comprises the third arm part **243**, the first positioning member **226** and the second positioning member **245**, which will not be repeated here.

(42) The use process of this embodiment is as follows:

(43) First, fit the first fixing member **221** to one side of the keel riser **111**. At this moment, the second arm part **242** and the lamp body **210** may be pre-connected together to install the lamp body **210** and the first fixing member **221** at the same time, or the second arm part **242** may not be connected with the lamp body **210** but only the first fixing member **221** may be installed first.

(44) Then, snap-fit the second fixing member **222** from top to bottom so that at least a part of each of the keel riser **111** and the first fixing member **221** is snap-fitted to be received in the snap-fit cavity **263** to complete the installation.

(45) The width of the snap-fit cavity **263** of the second fixing member **222** is less than or equal to the overall width after the first fixing member **221** fits to the keel riser **111**, so that the first fixing member **221** is firmly fixed to the keel riser **111** without being prone to shaking. Preferably, the second fixing member **222** is made of an elastic material and the width of the snap-fit cavity **263** is smaller than the above-mentioned overall width so that the second fixing member **222** is deformed after the snap-fit assembly. Therefore, a force can be continuously applied to the first fixing member **221** to fit and fix it to the keel riser **111**. Preferably, the eighth arm part **267** or the ninth arm part **268** is further provided with ribs or beads and arranged in a snap-fit direction so that the eighth arm part **267** or the ninth arm part **268** can provide better elastic fixing force.

Embodiment III

(46) As shown in FIG. **11**, the main structure of a lamp fixing member is similar to that of Embodiment II, except that this embodiment comprises the fastener **223** to firmly connect the lamp fixing member **220** to the keel riser **111** through the fastening effect of the fastener **223** with the first fixing member **221** or the second fixing member **222**.

(47) Specifically, unlike the elastic deformation snap-fit of the second fixing member **222** in Embodiment II, this embodiment adopts a fastener tightening method similar to that in Embodiment I.

(48) To this end, the fastening slot **264** and the fastening point **265** in Embodiment II are canceled and replaced by the first fastening hole **255** in Embodiment I, and a second fastening hole **256** is correspondingly provided on the ninth arm part **268** of the second fixing member **222**. The fastener **223** is fastened to the first fastening hole **255** and the second fastening hole **256**, thus pressing or loosening the second fixing member **222**.

(49) Preferably, the fastener **223** is a butterfly bolt. The first fastening hole **255** is a through hole and the second fastening hole **256** is a threaded hole to facilitate operation. Preferably, both the first fastening hole **255** and the second fastening hole **256** are provided at a position higher than the keel riser **111** so that the fastener **223** is threaded above the keel riser **111**. Optimally, the second fastening hole **256** is arranged higher than the first fastening hole **255** so that the fastener **223** is obliquely assembled on the second fixing member **222**.

Embodiment IV

(50) As shown in FIGS. **12-14**, a lamp **200** comprises a lamp body **210** and two lamp fixing members **220** so that the lamp **200** can be fixed to the keel member **110** by the two lamp fixing members **220**.

(51) Here, the specific structure of the lamp body **210** is the same as that in Embodiments I to III, and a lamp body fixing slot **211** is provided on it for connecting the lamp fixing member **220** in it. In addition, the lower end of the lamp fixing member **220** is provided with a second arm part **242**, a third arm part **243**, a first positioning member **226** and a second positioning member **245** to connect the lamp fixing member **220** with the lamp body **210**. This is the same as that in Embodiments I to

III, and will not be repeated here, so that the lamp fixing member **220** is detachably connected with the lamp body **210** at the lower end. After the lamp fixing member **220** is fixed to the keel member **110**, the lamp body **210** and the lamp fixing member **220** are connected to realize the installation of the lamp **200**.

(52) As shown in FIGS. **13-14**, the lamp fixing member **220** in this embodiment is composed of a third fixing member **227** and a fastener **223**. The third fixing member **227** is used to connect to the keel member **110** and press or unscrew the third fixing member **227** by screwing the fastener **223** so that the third fixing member **227** can be fixedly connected with or detached from the keel member **110**. The third fixing member **227** is an integral member, which consists of a connecting arm **228**, a locking arm **229** and a second arm part **242**. They are integrated by bending or welding. The locking arm **229** is connected to the upper end of the connecting arm **228** by a top arm **230**, and the second arm part **242** is connected to the lower end of the connecting arm **228**. Locking arms **229** are spaced from connecting arms **228** to form a fastening slot **224** therebetween for at least partially receiving keel member **110** therein. A clamping convex **258** is further provided at the lower end of the locking arm **229**, and a guide edge **253** is provided below the clamping convex **258**.

(53) In which, the connecting arm **228** is provided with a first fastening hole **255**, the locking arm **229** is provided with a second fastening hole **256** correspondingly, and the fastener **223** is provided between the first fastening hole **255** and the second fastening hole **256** so that the fastener **223** can act on the connecting arm **228** and the locking arm **229** to approach or move away from each other through placement of it to press or unscrew the lamp fixing member **220**. Preferably, the fastener **223** is a butterfly bolt. The first fastening hole **255** is a through hole and the second fastening hole **256** is a threaded hole. After the butterfly bolt passes through the first fastening hole **255**, it threads into the second fastening hole **256**.

(54) Therefore, the lamp fixing member **220** of this embodiment is different from Embodiments I to III in that: 1. The lamp fixing member **220** and the lamp body **210** of Embodiments I to III have two assembly modes: Firstly, the lamp fixing member **220** and the lamp body **210** are assembled as a whole, and then the lamp fixing member **220** is connected and fixed on the keel member **110**. For example, in Embodiment I, the first fixing member **221** is fitted to one side of the keel member **110**, and then the second fixing member **222** is pivoted to form a connection relationship. Then the fifth arm part **252** of the second fixing member **222** is tightened relative to the fourth arm part **251** by screwing the fastener **223**, so as to realize the purpose of connecting and fixing the lamp fixing member **220** on the keel member **110**. For another example, in Embodiment II, the first arm part **241** of the first fixing member **221** is fitted to one side of the keel member **110**, and then the second fixing member **222** is pressed and buckled downward. The sixth arm part **261** and the seventh arm part **262** of the second fixing member **222** respectively act on both sides of the keel member **110** to realize the purpose of connecting and fixing the lamp fixing member **220** to the keel member **110**. For another example, in Embodiment III, in addition to the steps in Embodiment II, the sixth arm part **261** and the seventh arm part **262** are relatively tightened by providing fasteners **223** to realize the purpose of connecting and fixing the lamp fixing member **220** on the keel member **110**. Secondly, the two steps of the first assembly method can also be reversed, i.e. connecting and fixing the lamp fixing member **220** to the keel member **110**, and then assembling and connecting the lamp fixing member **220** with the lamp body **210**. The specific contents are the same as those of the first assembly method and will not be repeated here. 2. In this embodiment, the fixed connection of the lamp body **210** can only be completed by connecting and fixing the lamp fixing member **220** to the keel member **110** first, and then assembling and connecting the lamp body **210** with the lamp fixing member **220**. Here, the preliminary positioning is completed after the lamp fixing member **220** and the keel member **110** are assembled. After that, the fastener **223** can be screwed first to completely fix it, and then the lamp body **210** and the lamp fixing member **220** can be assembled and connected. Alternatively, after the preliminary positioning, the lamp body **210**

and the lamp fixing member 220 can be assembled and connected first, and then the fastener 223 can be screwed to fully fix the lamp 200.

Claims

1. A lamp fixing member for fixing a lamp body to a keel member, comprising: a first fixing member, the first fixing member is connected with the lamp body, and a second fixing member, the first fixing member is movably connected with the second fixing member to form a connected state or a disconnected state; wherein, the second fixing member fixes the first fixing member to the keel member in the connected state, and the first fixing member is detachable from the keel member in the disconnected state; the second fixing member is pivotally connected to the first fixing member for snap-fitting on or separating from the keel member by pivoting of the second fixing member; the lamp fixing member further comprises a fastener; the second fixing member comprises a fourth arm part and a fifth arm part, and the fourth arm part is pivotally connected with the first fixing member; the fourth arm part and the fifth arm part are respectively provided with a first fastening hole and a second fastening hole; the fastener is inserted into the first fastening hole and the second fastening hole to drive the fifth arm part to approach or move away from the fourth arm part by screwing of the fastener; or, the second fixing member is detachably connected to the first fixing member to snap-fit the keel member on or separate it from the first fixing member through the second fixing member; the second fixing member comprises a sixth arm part and a seventh arm part, the sixth arm part and the seventh arm part are spaced apart so as to form a snap-fit cavity therebetween; the first fixing member comprises a first arm part and a second arm part, the first arm part is connected with or integrated with the second arm part, and the first arm part fits to a side wall of the keel member and is fixed by the second fixing member in a snap-fit manner; the second fixing member is made of an elastic material so that it can be elastically snap-fitted, and the width of the snap-fit cavity is less than the fitting width between the first arm part and the keel member, so that the second fixing member is in a resiliently expanded state after being snap-fitted; or, the lamp fixing member further comprises a fastener; the first arm part and the sixth arm part are provided with a first fastening hole correspondingly, and the seventh arm part is provided with a second fastening hole; the fastener is inserted into the first fastening hole and the second fastening hole to drive the sixth arm part to approach or move away from the seventh arm part by screwing of the fastener.

2. The lamp fixing member according to claim 1, wherein when the second fixing member is pivotally connected, the first fixing member comprises a first arm part and a second arm part, the first arm part is connected with or integrally formed with the second arm part, the fourth arm part is pivotally connected with the first arm part, and the second arm part is connected with the lamp body; A pivotal part of the first fixing member and the second fixing member is convexly arranged to abut against the lower part of an upper flange of the keel member.

3. The lamp fixing member according to claim 2, wherein the first fastening hole is a through hole, and the second fastening hole is a threaded hole; or both the first fastening hole and the second fastening hole are through holes, and a nut is provided outside the second fastening hole to threadably engage with the fastener; and/or, the fastener is a butterfly bolt, the fifth arm part is further provided with a clamping convex, and a guide edge is further arranged below the clamping convex.

4. The lamp fixing member according to claim 1, wherein when the second fixing member is detachably connected, the first arm part comprises an eighth arm part and a ninth arm part, the ninth arm part is offset from and protruded relative to the eighth arm part, and a boss is formed at the connection therebetween; or, when the second fixing member is elastically snap-fitted, a fastening slot and a fastening point are provided on the sixth arm part and the first arm part, respectively; the fastening slot is in concave-convex fit, friction fit or magnetic fit with the

fastening point to position the second fixing member.

5. A lamp fixing member for fixing a lamp body to a keel member, comprising: a third fixing member, the third fixing member is fixedly connected to the keel member, and the third fixing member is detachably connected with the lamp body, and a fastener, wherein, the third fixing member comprises a connecting arm and a locking arm arranged on both sides of the keel member, respectively, a fastening slot for providing at least part of the keel member therein is formed between the connecting arm and the locking arm, and the fastener acts between the connecting arm and the locking arm to press or unscrew them.

6. The lamp fixing member according to claim 5, wherein the connecting arm and the locking arm are provided with a first fastening hole and a second fastening hole, respectively, and the connecting arm is detachably connected with the lamp body through a second arm part; the first fastening hole is a through hole, and the second fastening hole is a threaded hole; the fastener is inserted into the first fastening hole and threadably engaged with the second fastening hole; or the first fastening hole and the second fastening hole are both through holes, and the fastener passes through the first fastening hole and the second fastening hole to form a threaded engagement with the nut.

7. The lamp fixing member according to claim 6, wherein the fastener is a butterfly bolt.

8. The lamp fixing member according to claim 5, wherein a lower end of the second arm part is bent downwards to form a third arm part, and the third arm part is spaced from the second arm part; the third arm part is further provided with a connecting positioning piece, and the connecting positioning piece abuts against a side wall or an inner wall of the lamp body fixing slot of the lamp body.

9. The lamp fixing member according to claim 8, wherein the third arm part is arranged in parallel and spaced from the second arm part, and the connecting positioning piece comprises either a first positioning piece protruding on the third arm part or a second positioning piece formed on the third arm part.

10. A lamp, comprising a lamp body and at least one lamp fixing member, wherein the lamp fixing member is the lamp fixing member according to claim 1.

11. A lamp fixing structure, comprising a keel member, a lamp body and a lamp fixing member, wherein the lamp fixing member is the lamp fixing member according to claim 1.

12. The lamp fixing structure according to claim 11, wherein the keel member comprises a keel riser, and an upper flange is formed at the top of the keel riser for clamping a locking part of the lamp fixing member below it; or, a lamp body fixing slot is provided on the top surface of the lamp body, and the lamp body fixing slot has an “L” or “⊥” cross-sectional shape.

13. The lamp fixing structure according to claim 12, wherein a hanger platform is further provided at a lower end of the keel riser, and the second arm part is arranged fitting to the hanger platform, so that the suspended ceiling tile is carried by the second arm part and the lamp body is arranged adjacent to a lower surface of the keel member or the suspended ceiling tile; the third arm part is positioned in a tight or magnetic fit with the lamp body fixing slot, so that the position of the lamp body can be adjusted relative to the lamp fixing member; the lamp fixing structure further comprises a cable fixing member, the cable fixing member comprises a cable fixing body and a cable fixing buckle detachably connected with each other; the cable fixing body comprises a first body and a second body, and the second body is fixedly connected with the keel member and the lamp body; the cable fixing buckle comprises a cable trough and a second buckling piece, a first buckling piece is provided on the first body, and the first buckling piece is detachably connected with the second buckling piece.

14. The lamp fixing structure according to claim 11, wherein after assembly, the lamp fixing structure makes each lamp body in a linear, rectangular or cross-shaped layout.
