

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12395404
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Garcia del Valle; Pablo et al.

---

### Symbiotic network orchestrator for computing networks

---

#### Abstract

A method for providing a symbiotic network orchestrator utilized to automatically commission edge computing devices on corporate computing networks and edge site computing networks is presented. The method includes receiving an indication of a potential connection of an edge computing device to one or more computing networks associated with the orchestrator. The one or more computing networks includes a corporate computing network and an edge site computing network. The method further includes determining, based on the corporate computing network, the edge site computing network, and a predetermined set of rules, an intent for commissioning the edge computing device, reconfiguring, based on the intent, the corporate computing network and the edge site computing network, and commissioning the edge computing device on one or more of the corporate computing network or the edge site computing network in accordance with the reconfiguring.

---

**Inventors:** Garcia del Valle; Pablo (Vaud, CH), Brockners; Frank (Cologne, DE), Maoz; Tal (Jerusalem, IL), Ryder; Benjamin William (Lausanne, CH), Rom; Aviad (Pardes Hanna-Karkur, IL)

**Applicant:** Cisco Technology, Inc. (San Jose, CA)

**Family ID:** 1000008766928

**Assignee:** CISCO TECHNOLOGY, INC. (San Jose, CA)

**Appl. No.:** 18/732182

**Filed:** June 03, 2024

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20250055753 A1	Feb. 13, 2025

#### Related U.S. Application Data

## Publication Classification

**Int. Cl.:** H04L41/0816 (20220101); H04L41/0894 (20220101)

**U.S. Cl.:**

**CPC** H04L41/0816 (20130101); H04L41/0894 (20220501);

## Field of Classification Search

**CPC:** H04L (41/0816); H04L (41/0894)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11601327	12/2022	Khalid	N/A	H04L 41/40
2021/0011825	12/2020	Aggarwal et al.	N/A	N/A
2021/0243053	12/2020	Dunbar	N/A	N/A
2022/0086061	12/2021	Natal et al.	N/A	N/A
2022/0342649	12/2021	Cao	N/A	G06F 8/61

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2013122815	12/2012	WO	N/A

### OTHER PUBLICATIONS

Cisco: "Cisco SD-WAN: WAN Edge Onboarding", Prescriptive Deployment Guide, Jan. 2020, pp. 1-100. cited by applicant

---

*Primary Examiner:* Lee; Gil H.

*Attorney, Agent or Firm:* Baker Botts L.L.P.

---

## Background/Summary

**PRIORITY (1)** This application is a continuation, under 35 U.S.C. § 120, of U.S. patent application Ser. No. 18/446,021 filed on Aug. 8, 2023, which is hereby incorporated by reference in its entirety.

### TECHNICAL FIELD

(1) This disclosure relates generally to computing networks, and, more specifically, to a symbiotic network orchestrator for computing networks.

### BACKGROUND

(2) Large corporate computing networks with Kubernetes-like deployments may generally be organized into an outer centralized corporate computing network and an inner edge site computing network that connects a remote location of an organization to computing resources. Generally, each

of the computing networks may be managed and controlled independently of each by respective network controllers. Because of the siloed configuration of such computing networks, connecting new devices to the edge site computing network, for example, may be complex, time-consuming, and susceptible to immense human error. For example, in many instances, interconnectivity for new devices on the edge site computing network, and, by extension, onto the centralized corporate computing network, may not always be possible due to security and network policies that may be defined by the centralized corporate computing network and/or due to separations of the centralized corporate computing network into subnetworks.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A illustrates an example wireless computing network topology.
- (2) FIG. 1B illustrates an example wireless computing network topology including a newly connected edge computing device.
- (3) FIG. 2 illustrates a symbiotic network orchestrator computing system utilized to automatically commission edge computing devices on corporate computing networks and edge site computing networks.
- (4) FIG. 3 illustrates a flow diagram of a method for providing a symbiotic network orchestrator utilized to automatically commission edge computing devices on corporate computing networks and edge site computing networks.
- (5) FIG. 4 illustrates an example computer system.

### DESCRIPTION OF EXAMPLE EMBODIMENTS

#### Overview

(6) The present embodiments are directed to techniques for providing a symbiotic network orchestrator utilized to automatically commission edge computing devices on corporate computing networks and edge site computing networks. In particular embodiments, a symbiotic network orchestrator executing on one or more computing devices may receive an indication of a potential connection of an edge computing device to one or more computing networks associated with the symbiotic network orchestrator. For example, in particular embodiments, the one or more computing networks may include a corporate computing network (e.g., software-defined wide area network (SD-WAN)) and an edge site computing network. In particular embodiments, the corporate computing network may be configured to be controlled and managed by a network controller and the edge site computing network may be configured to be controlled and managed by an edge site controller. In particular embodiments, subsequent to receiving the indication of the potential connection of the edge computing device, the symbiotic network orchestrator executing on one or more computing devices may identify the edge computing device.

(7) In particular embodiments, the symbiotic network orchestrator executing on one or more computing devices may then determine, based on the corporate computing network, the edge site computing network, and a predetermined set of rules, an intent for commissioning the edge computing device. For example, in particular embodiments, the symbiotic network orchestrator executing on one or more computing devices may determine the intent for commissioning the edge computing device by receiving runtime event data from the network controller and the edge site controller. In particular embodiments, the runtime event data may include one or more of a configuration of the corporate computing network and the edge site computing network, one or more constraints associated with the corporate computing network and the edge site computing network, or one or more identified scenarios associated with the corporate computing network and the edge site computing network.

(8) In particular embodiments, the symbiotic network orchestrator executing on one or more

computing devices may then determine, based on the runtime event data and the predetermined set of rules, the intent for commissioning the edge computing device. In particular embodiments, the predetermined set of rules may include a predetermined set of matching rules for matching the edge computing device to one or more of the corporate computing network or the edge site computing network. For example, in particular embodiments, the predetermined set of matching rules may include one or more of a security rule, a privacy rule, a quality of service (QoS) rule, a policy rule, or a routing rule. In particular embodiments, the symbiotic network orchestrator executing on one or more computing devices may then reconfigure, based on the intent, the corporate computing network and the edge site computing network.

(9) In particular embodiments, the symbiotic network orchestrator executing on one or more computing devices may reconfigure the corporate computing network by providing the intent to the network controller configured to manage and control the corporate computing network, and then reconfiguring, by the network controller, and based on the intent, the corporate computing network by connecting and securing one or more data sources and data sinks associated with the corporate computing network and the edge computing device. In particular embodiments, the symbiotic network orchestrator executing on one or more computing devices may reconfigure the edge site computing network by providing the intent to a network controller configured to manage and control the corporate computing network, and reconfiguring, by the edge site controller, and based on the intent, the edge site computing network by instantiating one or more device drivers and containers associated with the edge site computing network and the edge computing device. In particular embodiments, the symbiotic network orchestrator executing on one or more computing devices may then commission the edge computing device on one or more of the corporate computing network or the edge site computing network in accordance with the reconfiguring.

(10) Technical advantages of particular embodiments of this disclosure may include one or more of the following. Certain systems and methods described herein provide a symbiotic network orchestrator utilized to automatically commission edge computing devices on corporate computing networks and edge site computing networks. For example, the symbiotic network orchestrator manages and records up-to-date event data that is provided by respective network controllers associated with a corporate computing network and edge site computing network to which an edge computing device is to potentially connect. In addition to the event data provided by the respective network controllers, the symbiotic network orchestrator further utilizes a predetermined set of rules (e.g., security rules, privacy rules, QoS rules, policy rules, routing rules, and so forth) to determine and generate an intent for commissioning the edge computing device onto the corporate computing network and the edge site computing network.

(11) In particular examples, the intent determines the manner and process by which the corporate computing network and the edge site computing network are to be reconfigured (e.g., in real-time or near real-time) to properly commission and onboard the edge computing device to the computing networks. In this way, the symbiotic network orchestrator configures and reconfigures the corporate computing network and the edge site computing network concurrently via their respective network controllers, thus allowing the independently controlled and managed corporate computing network and edge site computing network to each have knowledge and insight into the computing resources, data traffic, and requirements of the other of the computing networks. This may lead to an overall improved efficiency, robustness, and reliability of the corporate and edge site computing networks.

(12) Other technical advantages will be readily apparent to one skilled in the art from the following figures, descriptions, and claims. Moreover, while specific advantages have been enumerated above, various embodiments may include all, some, or none of the enumerated advantages.

#### EXAMPLE EMBODIMENTS

(13) FIG. 1A illustrates an example wireless computing network topology **100A**, in accordance with the presently disclosed embodiments. In particular embodiments, the wireless computing

network topology **100A** may include one or more routers **102** that may be connected to one or more transport routers **104** and **106** suitable for transferring data packets between a corporate computing network **107** (e.g., software-defined wide area network (SD-WAN)) and an edge site computing network **109**. In particular embodiments, the corporate computing network **107** (e.g., SD-WAN) may include one or more compute nodes **110**, one or more personal computers (PCs) **112**, a unified computing system (UCS) **114**, a transport router **116**, and a compute device **118**. In particular embodiments, the edge site computing network **109** may include computing network servers **120**, **122**, a router **124**, a wireless access point (WAP) **126**, edge compute devices **128**, **130**, and **132** and a single-board computer **134**.

(14) In particular embodiments, the corporate computing network **107** (e.g., SD-WAN) may be controlled and managed by a SD-WAN network controller **136**. In particular embodiments, the SD-WAN network controller **136** may include centralized controller suitable for controlling the flow of data traffic throughout the corporate computing network **107**. For example, in particular embodiments, the SD-WAN network controller **136** may be utilized to establish and manage a control plane of the corporate computing network **107** (e.g., SD-WAN overlay network) that may include establishing, adjusting, and maintaining the connections that form an SD-WAN fabric.

(15) In particular embodiments, the edge site computing network **109** may be controlled and managed by an edge-native site network controller **138**. In particular embodiments, the edge-native site network controller **138** may include, for example, an edge site controller that may be suitable for controlling and managing a number of clusters of devices and systems that may be included as part of the edge site computing network **109**. For example, in particular embodiments, the edge-native site network controller **138** may be utilized to establish and manage a control plane at the edge site computing network **109**, for example, allowing for the development and deployment of applications at the edge as a service or the deployment and management of applications across many edge locations of the edge site computing network **109**.

(16) FIG. 1B illustrates an example wireless computing network topology **100B** including a newly connected edge computing device **140**, in accordance with the presently disclosed embodiments. In particular embodiments, as generally discussed above with respect to FIG. 1B, the corporate computing network **107** (e.g., SD-WAN) and the edge site computing network **109** may include two different, coexisting computing networks in which the edge site computing network **109** is subsumed by the corporate computing network **107** (e.g., SD-WAN). For example, in one embodiment, the corporate computing network **107** (e.g., SD-WAN) may include an outer computing network and the edge site computing network **109** may include an inner computing network.

(17) In particular embodiments, each of the corporate computing network **107** (e.g., SD-WAN) and the edge site computing network **109** may be defined and operate separately and independently of each other, and thus the SD-WAN network controller **136** may have knowledge of the configuration and event data of only the corporate computing network **107** (e.g., SD-WAN) while the edge-native site network controller **138** may have knowledge of the configuration and event data of only the edge site computing network **109**. In particular embodiments, when an edge computing device **140** (e.g., one or more cameras, smart mirrors, digital signage, and so forth) is thus connected, for example, to the transport router **116** of the corporate computing network **107** (e.g., SD-WAN), it may be unclear as to the process in which the edge computing device **140** is to be commissioned on the corporate computing network **107** (e.g., SD-WAN) or the edge site computing network **109** and/or which of the corporate computing network **107** (e.g., SD-WAN) and the edge site computing network **109** is to be granted access to the edge computing device **140**.

(18) FIG. 2 illustrates a symbiotic network orchestration computing system **200** utilized to automatically commission edge computing devices on corporate computing networks and edge site computing networks, in accordance with the presently disclosed embodiments. As depicted by FIG. 2, in particular embodiments, the symbiotic network orchestration computing system **200** may

include a symbiotic network orchestrator **202**, an SD-WAN network controller **204** that may manage and control a corporate computing network (e.g., SD-WAN) infrastructure **206** (e.g., including various physical and virtual computing resources), and an edge-native site network controller **208** that may manage and control an edge site computing network infrastructure **210** (e.g., including various edge physical and virtual computing resources). In particular embodiments, the corporate computing network infrastructure **206** may correspond to the corporate computing network **107** (e.g., SD-WAN) as discussed above with respect to FIGS. **1A** and **1B**. Similarly, in particular embodiments, the edge site computing network infrastructure **210** may correspond to the edge site computing network **109** as discussed above with respect to FIGS. **1A** and **1B**.

(19) In particular embodiments, the symbiotic network orchestrator **202** may include any orchestrator that may be suitable for automatically coordinating the SD-WAN network controller **204** and associated corporate computing network infrastructure **206** and the edge-native site network controller **208** and associated edge site computing network infrastructure **210**, facilitating connectivity between the SD-WAN network controller **204**, the edge-native site network controller **208**, and edge routers, and commissioning, authenticating, and validating one or more edge computing devices **140** desiring to join, for example, one or more of the corporate computing network **107** (e.g., SD-WAN) or the edge site computing network **109** in accordance with the presently disclosed embodiments.

(20) For example, in particular embodiments, the symbiotic network orchestrator **202** may receive an indication by way of the SD-WAN network controller **204** or the edge-native site network controller **208** of a connection of one or more edge computing devices **140** to the corporate computing network **107** (e.g., SD-WAN) or the edge site computing network **109**. In particular embodiments, subsequent to receiving the indication of the connection of the one or more edge computing devices **140**, the symbiotic network orchestrator **202** may receive information identifying the one or more edge computing devices **140**. For example, as depicted in FIG. **2**, the SD-WAN network controller **204** may provide one or more unique identifiers (e.g., device identification information, device compatibility information, and so forth) associated with the one or more edge computing devices **140** to the symbiotic network orchestrator **202**.

(21) In particular embodiments, the symbiotic network orchestrator **202** may also receive real-time or near real-time event data (e.g., at runtime) from the SD-WAN network controller **204** and the edge-native site network controller **208**. For example, in particular embodiments, the runtime event data may include one or more of a configuration of the SD-WAN network controller **204** and the edge-native site network controller **208**, one or more constraints associated with the SD-WAN network controller **204** and the edge-native site network controller **208**, or one or more identified scenarios associated with commissioning edge devices on the SD-WAN network controller **204** and the edge-native site network controller **208**. In particular embodiments, the symbiotic network orchestrator **202** may then determine, based on the event data from the SD-WAN network controller **204** and the edge-native site network controller **208** and a predetermined set of rules, an intent for commissioning the one or more edge computing devices **140**.

(22) For example, in particular embodiments, the symbiotic network orchestrator **202** may access one or more customer requirements **212**, one or more services **214**, one or more application stores **216**, one or more matching rules (e.g., a security rule, a privacy rule, a quality of service (QOS) rule, a policy rule, a routing rule, and so forth), and/or one or more other rules **218** that may be associated with the one or more edge computing devices **140** and utilized to determine the intent for commissioning the one or more edge computing devices **140**. In particular embodiments, the symbiotic network orchestrator **202** may then generate an intent proposal **222**, which may be displayed or presented to one or more users or organizations **224** for feedback and/or approval. In particular embodiments, once the intent proposal **222** has been approved by the one or more users or organizations **224**, the symbiotic network orchestrator **202** may then push the generated intent **226** to the SD-WAN network controller **204** and the edge-native site network controller **208**,

respectively.

(23) In particular embodiments, the intent **226** as generated by the symbiotic network orchestrator **202** may include one or more sets of instructions of the manner in which the SD-WAN network controller **204** and the edge-native site network controller **208** are to be reconfigured for commissioning the one or more edge computing devices **140**. For example, in particular embodiments, based on the intent **226** as generated and provided by the symbiotic network orchestrator **202**, the SD-WAN network controller **204** may then reconfigure the corporate computing network infrastructure **206**. In particular embodiments, reconfiguring the corporate computing network infrastructure **206** may include connecting and securing one or more data sources and data sinks associated with the corporate computing network infrastructure **206** with respect to the one or more edge computing devices **140**.

(24) In particular embodiments, based on the intent **226** as generated and provided by the symbiotic network orchestrator **202**, the edge-native site network controller **208** may then reconfigure the edge site computing network infrastructure **210**. In particular embodiments, reconfiguring the edge site computing network infrastructure **210** may include instantiating one or more device drivers and containers associated with the edge site computing network infrastructure **210** with respect to the one or more edge computing devices **140**. In particular embodiments, the symbiotic network orchestrator **202** may then commission the one or more edge computing devices **140** on one or more of the corporate computing network infrastructure **206** or the edge site computing network infrastructure **210** in accordance with the respective reconfigurations. In particular embodiments, upon completion of the commissioning of the one or more edge computing devices **140**, the symbiotic network orchestrator **202** may also store a record of the reconfigurations of the corporate computing network infrastructure **206** and the edge site computing network infrastructure **210** to, for example, revert back to prior configurations in the case of failed commissioning or other system fault.

(25) FIG. 3 illustrates a flow diagram of a method **300** for providing a symbiotic network orchestrator utilized to automatically commission edge computing devices on corporate computing networks and edge site computing networks, in accordance with the presently disclosed embodiments. The method **300** may be performed utilizing one or more processors that may include hardware (e.g., a general purpose processor, a graphic processing units (GPU), an application-specific integrated circuit (ASIC), a system-on-chip (SoC), a microcontroller, a field-programmable gate array (FPGA), or any other processing device(s) that may be suitable for processing intents and/or desire states), software (e.g., instructions running/executing on one or more processors), firmware (e.g., microcode), or any combination thereof.

(26) The method **300** may begin at block **302** with a network orchestrator executing on one or more computing devices receiving an indication of a potential connection of an edge computing device to one or more computing networks associated with an orchestrator. In particular embodiments, the one or more computing networks may include a corporate computing network and an edge site computing network. The method **300** may continue at block **304** with the network orchestrator executing on one or more computing devices determining, based on the corporate computing network, the edge site computing network, and a predetermined set of rules, an intent for commissioning the edge computing device. For example, in particular embodiments, determining the intent for commissioning the edge computing device further may include receiving runtime event data from the network controller and the edge site controller, in which the runtime event data may include one or more of a configuration of the corporate computing network and the edge site computing network, one or more constraints associated with the corporate computing network and the edge site computing network, or one or more identified scenarios associated with the corporate computing network and the edge site computing network.

(27) In particular embodiments, the network orchestrator executing on one or more computing devices may then determine, based on the runtime event data and the predetermined set of rules, the

intent for commissioning the edge computing device. In particular embodiments, the predetermined set of rules may include a predetermined set of matching rules for matching the edge computing device to one or more of the corporate computing network or the edge site computing network. For example, in particular embodiments, the predetermined set of matching rules may include one or more of a security rule, a privacy rule, a quality of service (QOS) rule, a policy rule, or a routing rule. The method **300** may continue at block **306** with the network orchestrator executing on one or more computing devices reconfiguring, based on the intent, the corporate computing network and the edge site computing network.

(28) In particular embodiments, reconfiguring the corporate computing network may include providing the intent to a network controller configured to manage and control the corporate computing network, and reconfiguring, by the network controller, and based on the intent, the corporate computing network by connecting and securing one or more data sources and data sinks associated with the corporate computing network and the edge computing device. In particular embodiments, reconfiguring the edge site computing network may include providing the intent to a network controller configured to manage and control the corporate computing network, and reconfiguring, by the edge site controller, and based on the intent, the edge site computing network by instantiating one or more device drivers and containers associated with the edge site computing network and the edge computing device. The method **300** may conclude at block **308** with the network orchestrator executing on one or more computing devices commissioning the edge computing device on one or more of the corporate computing network or the edge site computing network in accordance with the reconfiguring.

(29) FIG. **4** illustrates an example computer system **400** that may be useful in performing one or more of the foregoing techniques as presently disclosed herein. In particular embodiments, one or more computer systems **400** perform one or more steps of one or more methods described or illustrated herein. In particular embodiments, one or more computer systems **400** provide functionality described or illustrated herein. In particular embodiments, software running on one or more computer systems **400** performs one or more steps of one or more methods described or illustrated herein or provides functionality described or illustrated herein. Particular embodiments include one or more portions of one or more computer systems **400**. Herein, reference to a computer system may encompass a computing device, and vice versa, where appropriate. Moreover, reference to a computer system may encompass one or more computer systems, where appropriate.

(30) This disclosure contemplates any suitable number of computer systems **400**. This disclosure contemplates computer system **400** taking any suitable physical form. As example and not by way of limitation, computer system **400** may be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) (such as, for example, a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, an interactive kiosk, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, a tablet computer system, an augmented/virtual reality device, or a combination of two or more of these. Where appropriate, computer system **400** may include one or more computer systems **400**; be unitary or distributed; span multiple locations; span multiple machines; span multiple data centers; or reside in a cloud, which may include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **400** may perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein.

(31) As an example, and not by way of limitation, one or more computer systems **400** may perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. One or more computer systems **400** may perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate. In particular embodiments, computer system **400** includes a processor **402**, memory **404**, storage **406**,



an input/output (I/O) interface **408**, a communication interface **410**, and a bus **412**. Although this disclosure describes and illustrates a particular computer system having a particular number of particular components in a particular arrangement, this disclosure contemplates any suitable computer system having any suitable number of any suitable components in any suitable arrangement.

(32) In particular embodiments, processor **402** includes hardware for executing instructions, such as those making up a computer program. As an example, and not by way of limitation, to execute instructions, processor **402** may retrieve (or fetch) the instructions from an internal register, an internal cache, memory **404**, or storage **406**; decode and execute them; and then write one or more results to an internal register, an internal cache, memory **404**, or storage **406**. In particular embodiments, processor **402** may include one or more internal caches for data, instructions, or addresses. This disclosure contemplates processor **402** including any suitable number of any suitable internal caches, where appropriate. As an example, and not by way of limitation, processor **402** may include one or more instruction caches, one or more data caches, and one or more translation lookaside buffers (TLBs). Instructions in the instruction caches may be copies of instructions in memory **404** or storage **406**, and the instruction caches may speed up retrieval of those instructions by processor **402**.

(33) Data in the data caches may be copies of data in memory **404** or storage **406** for instructions executing at processor **402** to operate on; the results of previous instructions executed at processor **402** for access by subsequent instructions executing at processor **402** or for writing to memory **404** or storage **406**; or other suitable data. The data caches may speed up read or write operations by processor **402**. The TLBs may speed up virtual-address translation for processor **402**. In particular embodiments, processor **402** may include one or more internal registers for data, instructions, or addresses. This disclosure contemplates processor **402** including any suitable number of any suitable internal registers, where appropriate. Where appropriate, processor **402** may include one or more arithmetic logic units (ALUs); be a multi-core processor; or include one or more processors **602**. Although this disclosure describes and illustrates a particular processor, this disclosure contemplates any suitable processor.

(34) In particular embodiments, memory **404** includes main memory for storing instructions for processor **402** to execute or data for processor **402** to operate on. As an example, and not by way of limitation, computer system **400** may load instructions from storage **406** or another source (such as, for example, another computer system **400**) to memory **404**. Processor **402** may then load the instructions from memory **404** to an internal register or internal cache. To execute the instructions, processor **402** may retrieve the instructions from the internal register or internal cache and decode them. During or after execution of the instructions, processor **402** may write one or more results (which may be intermediate or final results) to the internal register or internal cache. Processor **402** may then write one or more of those results to memory **404**. In particular embodiments, processor **402** executes only instructions in one or more internal registers or internal caches or in memory **404** (as opposed to storage **406** or elsewhere) and operates only on data in one or more internal registers or internal caches or in memory **404** (as opposed to storage **406** or elsewhere).

(35) One or more memory buses (which may each include an address bus and a data bus) may couple processor **402** to memory **404**. Bus **412** may include one or more memory buses, as described below. In particular embodiments, one or more memory management units (MMUs) reside between processor **402** and memory **404** and facilitate accesses to memory **404** requested by processor **402**. In particular embodiments, memory **404** includes random access memory (RAM). This RAM may be volatile memory, where appropriate. Where appropriate, this RAM may be dynamic RAM (DRAM) or static RAM (SRAM). Moreover, where appropriate, this RAM may be single-ported or multi-ported RAM. This disclosure contemplates any suitable RAM. Memory **404** may include one or more memories **404**, where appropriate. Although this disclosure describes and illustrates particular memory, this disclosure contemplates any suitable memory.

(36) In particular embodiments, storage **406** includes mass storage for data or instructions. As an example, and not by way of limitation, storage **406** may include a hard disk drive (HDD), a floppy disk drive, flash memory, an optical disc, a magneto-optical disc, magnetic tape, or a Universal Serial Bus (USB) drive or a combination of two or more of these. Storage **406** may include removable or non-removable (or fixed) media, where appropriate. Storage **406** may be internal or external to computer system **400**, where appropriate. In particular embodiments, storage **406** is non-volatile, solid-state memory. In particular embodiments, storage **406** includes read-only memory (ROM). Where appropriate, this ROM may be mask-programmed ROM, programmable ROM (PROM), erasable PROM (EPROM), electrically erasable PROM (EEPROM), electrically alterable ROM (EAROM), or flash memory or a combination of two or more of these. This disclosure contemplates mass storage **406** taking any suitable physical form. Storage **406** may include one or more storage control units facilitating communication between processor **402** and storage **406**, where appropriate. Where appropriate, storage **406** may include one or more storages **406**. Although this disclosure describes and illustrates particular storage, this disclosure contemplates any suitable storage.

(37) In particular embodiments, I/O interface **408** includes hardware, software, or both, providing one or more interfaces for communication between computer system **400** and one or more I/O devices. Computer system **400** may include one or more of these I/O devices, where appropriate. One or more of these I/O devices may enable communication between a person and computer system **400**. As an example, and not by way of limitation, an I/O device may include a keyboard, keypad, microphone, monitor, mouse, printer, scanner, speaker, still camera, stylus, tablet, touch screen, trackball, video camera, another suitable I/O device or a combination of two or more of these. An I/O device may include one or more sensors. This disclosure contemplates any suitable I/O devices and any suitable I/O interfaces **408** for them. Where appropriate, I/O interface **408** may include one or more device or software drivers enabling processor **402** to drive one or more of these I/O devices. I/O interface **408** may include one or more I/O interfaces **408**, where appropriate. Although this disclosure describes and illustrates a particular I/O interface, this disclosure contemplates any suitable I/O interface.

(38) In particular embodiments, communication interface **410** includes hardware, software, or both providing one or more interfaces for communication (such as, for example, packet-based communication) between computer system **400** and one or more other computer systems **400** or one or more networks. As an example, and not by way of limitation, communication interface **410** may include a network interface controller (NIC) or network adapter for communicating with an Ethernet or other wire-based network or a wireless NIC (WNIC) or wireless adapter for communicating with a wireless network, such as a WI-FI network. This disclosure contemplates any suitable network and any suitable communication interface **410** for it.

(39) As an example, and not by way of limitation, computer system **400** may communicate with an ad hoc network, a personal area network (PAN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), or one or more portions of the Internet or a combination of two or more of these. One or more portions of one or more of these networks may be wired or wireless. As an example, computer system **400** may communicate with a wireless PAN (WPAN) (such as, for example, a BLUETOOTH WPAN), a WI-FI network, a WI-MAX network, a cellular telephone network (such as, for example, a Global System for Mobile Communications (GSM) network), or other suitable wireless network or a combination of two or more of these. Computer system **400** may include any suitable communication interface **410** for any of these networks, where appropriate. Communication interface **410** may include one or more communication interfaces **410**, where appropriate. Although this disclosure describes and illustrates a particular communication interface, this disclosure contemplates any suitable communication interface.

(40) In particular embodiments, bus **412** includes hardware, software, or both coupling components

of computer system **400** to each other. As an example and not by way of limitation, bus **412** may include an Accelerated Graphics Port (AGP) or other graphics bus, an Enhanced Industry Standard Architecture (EISA) bus, a front-side bus (FSB), a HYPERTRANSPORT (HT) interconnect, an Industry Standard Architecture (ISA) bus, an INFINIBAND interconnect, a low-pin-count (LPC) bus, a memory bus, a Micro Channel Architecture (MCA) bus, a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCIe) bus, a serial advanced technology attachment (SATA) bus, a Video Electronics Standards Association local (VLB) bus, or another suitable bus or a combination of two or more of these. Bus **412** may include one or more buses **412**, where appropriate. Although this disclosure describes and illustrates a particular bus, this disclosure contemplates any suitable bus or interconnect.

(41) Herein, a computer-readable non-transitory storage medium or media may include one or more semiconductor-based or other integrated circuits (ICs) (such, as for example, field-programmable gate arrays (FPGAs) or application-specific ICs (ASICs)), hard disk drives (HDDs), hybrid hard drives (HHDs), optical discs, optical disc drives (ODDs), magneto-optical discs, magneto-optical drives, floppy diskettes, floppy disk drives (FDDs), magnetic tapes, solid-state drives (SSDs), RAM-drives, SECURE DIGITAL cards or drives, any other suitable computer-readable non-transitory storage media, or any suitable combination of two or more of these, where appropriate. A computer-readable non-transitory storage medium may be volatile, non-volatile, or a combination of volatile and non-volatile, where appropriate.

(42) Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

(43) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, feature, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative. Additionally, although this disclosure describes or illustrates particular embodiments as providing particular advantages, particular embodiments may provide none, some, or all of these advantages.

## Claims

1. A method, by one or more computing devices, comprising: receiving an indication of a connection of an edge computing device to one or more computing networks, wherein the one or more computing networks comprises a corporate computing network and an edge site computing network; determining, based on one or more of the corporate computing network or the edge site computing network, an intent for commissioning the edge computing device; reconfiguring, based on the intent, the corporate computing network and the edge site computing network; and

- commissioning the edge computing device on one or more of the corporate computing network or the edge site computing network in accordance with the reconfiguring.
2. The method of claim 1, wherein the one or more computing networks is configured to be controlled and managed by a controller.
  3. The method of claim 2, the method further comprising: subsequent to receiving the indication of the connection of the edge computing device, identifying, by the controller, the edge computing device.
  4. The method of claim 2, wherein determining the intent for commissioning the edge computing device further comprises: receiving runtime event data from the controller, wherein the runtime event data comprises one or more of a configuration of the corporate computing network and the edge site computing network, one or more constraints associated with the corporate computing network and the edge site computing network, or one or more identified scenarios associated with the corporate computing network and the edge site computing network; and determining, based at least in part on the runtime event data, the intent for commissioning the edge computing device.
  5. The method of claim 1, further comprising determining, based on one or more of the corporate computing network or the edge site computing network and a predetermined set of rules, the intent for commissioning the edge computing device.
  6. The method of claim 5, wherein the predetermined set of rules comprises a predetermined set of matching rules for matching the edge computing device to one or more of the corporate computing network or the edge site computing network.
  7. The method of claim 6, wherein the predetermined set of matching rules comprises one or more of a security rule, a privacy rule, a quality of service (QOS) rule, a policy rule, or a routing rule.
  8. The method of claim 1, wherein reconfiguring the corporate computing network comprises: providing the intent to a controller configured to manage and control the one or more computing networks; and reconfiguring, by the controller, and based on the intent, the one or more computing networks by connecting and securing one or more data sources and data sinks associated with the one or more computing networks.
  9. A system, comprising: one or more non-transitory computer-readable storage media including instructions; and one or more processors coupled to the storage media, the one or more processors configured to execute the instructions to: receive an indication of a connection of an edge computing device to one or more computing networks, wherein the one or more computing networks comprises a corporate computing network and an edge site computing network; determine, based on one or more of the corporate computing network or the edge site computing network, an intent for commissioning the edge computing device; reconfigure, based on the intent, the corporate computing network and the edge site computing network; and commission the edge computing device on one or more of the corporate computing network or the edge site computing network in accordance with the reconfiguring.
  10. The system of claim 9, wherein the one or more computing networks is configured to be controlled and managed by a controller.
  11. The system of claim 10, the instructions further comprising instructions to: subsequent to receiving the indication of the connection of the edge computing device, identify, by the controller, the edge computing device.
  12. The system of claim 10, wherein the instructions to determine the intent for commissioning the edge computing device further comprise instructions to: receive runtime event data from the controller, wherein the runtime event data comprises one or more of a configuration of the corporate computing network and the edge site computing network, one or more constraints associated with the corporate computing network and the edge site computing network, or one or more identified scenarios associated with the corporate computing network and the edge site computing network; and determine, based at least in part on the runtime event data, the intent for commissioning the edge computing device.

13. The system of claim 9, wherein the instructions further comprise instructions to determine, based on one or more of the corporate computing network or the edge site computing network and a predetermined set of rules, the intent for commissioning the edge computing device.
  14. The system of claim 13, wherein the predetermined set of rules comprises a predetermined set of matching rules for matching the edge computing device to one or more of the corporate computing network or the edge site computing network.
  15. The system of claim 14, wherein the predetermined set of matching rules comprises one or more of a security rule, a privacy rule, a quality of service (QOS) rule, a policy rule, or a routing rule.
  16. The system of claim 9, wherein the instructions to reconfigure the corporate computing network further comprise instructions to: provide the intent to a controller configured to manage and control the one or more computing networks; and reconfigure, by the controller, and based on the intent, the one or more computing networks by connecting and securing one or more data sources and data sinks associated with the one or more computing networks.
  17. A non-transitory computer-readable medium comprising instructions that, when executed by one or more processors of a computing system, cause the one or more processors to: receive an indication of a connection of an edge computing device to one or more computing networks, wherein the one or more computing networks comprises a corporate computing network and an edge site computing network; determine, based on one or more of the corporate computing network or the edge site computing network, an intent for commissioning the edge computing device; reconfigure, based on the intent, the corporate computing network and the edge site computing network; and commission the edge computing device on one or more of the corporate computing network or the edge site computing network in accordance with the reconfiguring.
  18. The non-transitory computer-readable medium of claim 17, wherein the instructions further comprise instructions to determine, based on one or more of the corporate computing network or the edge site computing network and a predetermined set of rules, the intent for commissioning the edge computing device.
  19. The non-transitory computer-readable medium of claim 18, wherein the predetermined set of rules comprises a predetermined set of matching rules for matching the edge computing device to one or more of the corporate computing network or the edge site computing network.
  20. The non-transitory computer-readable medium of claim 17, wherein the instructions to reconfigure the edge site computing network further comprise instructions to: provide the intent to a controller configured to manage and control the one or more computing networks; and reconfigure, by the controller, and based on the intent, the one or more computing networks by connecting and securing one or more data sources and data sinks associated with the one or more computing networks.
-