US Patent & Trademark Office
Patent Public Search | Text View

United States Design Patent	D1090770
Kind Code	S
Date of Patent	August 26, 2025
Inventor(s)	Skelton; Tyler et al.

Fast mounting device for multiple slot interface

Inventors: **Skelton; Tyler (Missouri City, TX), Gaddini; Joseph (Wilmington, NC)**

Applicant: **Sarissa Innovations LLC** (Wilmington, DE)

Family ID: **1000007118388**

Assignee: **SARISSA INNOVATIONS LLC (Wilmington, DE)**

(**) Term: 15 Years **Appl. No.:**

D/894020 **Filed:**

June 05, 2023

Related U.S. Application Data

continuation parent-doc US 18098454 20230118 US 11976899 child-doc US 29894020

Publication Classification

LOC Cl.: 2201

U.S. Cl.:

CPC **F41C27/00** (20130101); F41G11/003 (20130101)

USPC D22/109

Field of Classification Search

USPC: None

Description

(1) FIG. **1** is a lower rear perspective view of the assembled mounting device.
(2) FIG. **2** is an upper front perspective view of the mounting device of FIG. **1**.

(3) FIG. **3** is side view of the mounting device of FIG. **1**.
(4) FIG. **4** is top view of the mounting device of FIG. **1**.
(5) FIG. **5** is a bottom view of the mounting device of FIG. **1**.
(6) FIG. **6** is a rear end view of the mounting device of FIG. **1**.
(7) FIG. **7** is a front end view of the mounting device of FIG. **1**.
(8) FIG. **8** is a lower exploded perspective view of the mounting device of FIG. **1**.
(9) FIG. **9** is an upper exploded perspective view of the mounting device of FIG. **1**.
(10) FIG. **10** is another an upper exploded perspective view of the mounting device of FIG. **9**
(11) FIG. **11** is a lower front right side perspective view of the double wedge member of the preceding figures.
(12) FIG. **12** is another lower front right side perspective view of the double wedge member of the preceding figures
(13) FIG. **13** is an upper left side perspective view of the double wedge member of the preceding figures.
(14) FIG. **14** is a rear side perspective view of the double wedge member of the preceding figures.
(15) FIG. **15** is a right side view of the double wedge member of FIG. **11**.
(16) FIG. **16** is a left side view of the double wedge member of FIG. **11**.
(17) FIG. **17** is a top view of the double wedge member of FIG. **11**.
(18) FIG. **18** is a bottom view of the double wedge member of FIG. **11**.
(19) FIG. **19** is a front view of the double wedge member of FIG. **11**.
(20) FIG. **20** is a rear view of the double wedge member of FIG. **11**.
(21) FIG. **21** is an upper front right perspective view of the picatinny base mount of FIGS. **1-10**.
(22) FIG. **22** is an upper rear perspective view of the picatinny base mount of FIG. **21**
(23) FIG. **23** is a lower front left perspective view of the picatinny base mount of FIG. **21**.
(24) FIG. **24** is a lower rear right perspective view of the picatinny base mount of FIG. **21**.
(25) FIG. **25** is a front view of the picatinny base mount of FIG. **21**.
(26) FIG. **26** is a rear view of the picatinny base mount of FIG. **21**.
(27) FIG. **27** is a top view of the picatinny base mount of FIG. **21**.
(28) FIG. **28** is a bottom view of the picatinny base mount of FIG. **21**.
(29) FIG. **29** is a right side view of the picatinny base mount of FIG. **21**.
(30) FIG. **30** is a left side view of the picatinny base mount of FIG. **21**.
(31) FIG. **31** is a side cross-sectional view of the assembled mounting device detached from a multiple slot rail (mounting interface) on a firearm.
(32) FIG. **32** shows the mounting device of FIG. **31** with push button depressed causing the two wedge legs to extend below the assembly, ready to be positioned into a pair of slots on the rail.
(33) FIG. **33** shows the mounting device of FIG. **32** sitting flush on the mounting interface of the rail with the wedge legs within the two slots (with button still depressed).
(34) FIG. **34** shows the mounting device of FIG. **33** with the wedge legs moving in the direction of arrow X to locked positions, as the button is being released.
(35) FIG. **35** shows the mounting device of FIG. **33** with a thinner wall thickness on the multiple slot rail (mounting interface) on a firearm, with the wedge legs moving in the direction of arrow X to locked positions, as the button is being released.
(36) FIG. **36** is another view of FIGS. **34-35**, using a secondary locking **15** feature with the rear screw torqued down to prevent the wedge legs from moving out of their locked positions.
(37) FIG. **37** is a lower side perspective view of FIG. **31**.
(38) FIG. **38** is a lower side perspective view of FIG. **32**.
(39) FIG. **39** is a lower side perspective view of FIG. **33**.
(40) FIG. **40** is a lower side perspective view of FIG. **34**.
(41) FIG. **41** is a lower side perspective view of FIG. **35**.
(42) FIG. **42** is a lower side perspective view of FIG. **36**.

(43) FIG. **43** is a is a bottom view of FIG. **31**.
(44) FIG. **44** is a bottom view of FIG. **32**.
(45) FIG. **45** is a bottom view of FIG. **33**.
(46) FIG. **46** is a bottom view of FIG. **34**.
(47) FIG. **47** is a bottom view of FIG. **35**; and,
(48) FIG. **48** is a bottom view of FIG. **36**.
(49) The broken lines in FIGS. **1-48** are for illustrative purposes and form no part of the claimed design.

Claims

The ornamental design for fast mounting device for multiple slot interface, as shown and described.
