

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250265313

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Ojard; Eric Jon et al.

CLUSTER INTENSITY VARIATION CORRECTION AND BASE CALLING

Abstract

The technology disclosed corrects inter-cluster intensity profile variation for improved base calling on a cluster-by-cluster basis. The technology disclosed accesses current intensity data and historic intensity data of a target cluster, where the current intensity data is for a current sequencing cycle and the historic intensity data is for one or more preceding sequencing cycles. A first accumulated intensity correction parameter is determined by accumulating distribution intensities measured for the target cluster at the current and preceding sequencing cycles. A second accumulated intensity correction parameter is determined by accumulating intensity errors measured for the target cluster at the current and preceding sequencing cycles. Based on the first and second accumulated intensity correction parameters, next intensity data for a next sequencing cycle is corrected to generate corrected next intensity data, which is used to base call the target cluster at the next sequencing cycle.

Inventors: Ojard; Eric Jon (San Diego, CA), Kagalwalla; Abde Ali Hunaid (San Diego, CA), Mehio; Rami (San Diego, CA), Udpa; Nitin (San Diego, CA), Parnaby; Gavin Derek (Laguna Niguel, CA), Vieceli; John S. (San Diego, CA)

Applicant: Illumina, Inc. (San Diego, CA)

Family ID: 1000008576627

Appl. No.: 19/003449

Filed: December 27, 2024

Related U.S. Application Data

parent US continuation 18501904 20231103 parent-grant-document US 12216741 child US 19003449
parent US continuation 18154603 20230113 parent-grant-document US 11853396 child US 18501904
parent US continuation 17752789 20220524 parent-grant-document US 11593595 child US 18154603
parent US continuation 17510285 20211025 parent-grant-document US 11361194 child US 17752789
us-provisional-application US 63106256 20201027

Publication Classification

Int. Cl.: G06F18/2411 (20230101); G06F18/2135 (20230101); G06T7/187 (20170101); G06V10/50 (20220101)

U.S. Cl.:

CPC G06F18/2411 (20230101); G06F18/21355 (20230101); G06T7/187 (20170101); G06V10/507 (20220101);

Background/Summary

PRIORITY APPLICATION [0001] This application is a continuation of U.S. Nonprovisional patent application Ser. No. 18/501,904, entitled “INTER-CLUSTER INTENSITY VARIATION CORRECTION AND BASE CALLING,” filed Nov. 3, 2023, which is a continuation of U.S. Nonprovisional patent application Ser. No. 18/154,603, entitled “INTER-CLUSTER INTENSITY VARIATION CORRECTION AND BASE CALLING,” filed Jan. 13, 2023, which is a continuation of U.S. Nonprovisional patent application Ser. No. 17/752,789, entitled “INTER-CLUSTER INTENSITY VARIATION CORRECTION AND BASE CALLING,” filed May 24, 2022, which is a continuation of U.S. Nonprovisional patent application Ser. No. 17/510,285, entitled “SYSTEMS AND METHODS FOR PER-CLUSTER INTENSITY CORRECTION AND BASE CALLING,” filed Oct. 25, 2021, which in turn claims the benefit of U.S. Provisional Patent Application No. 63/106,256, entitled “SYSTEMS AND METHODS FOR PER-CLUSTER INTENSITY CORRECTION AND BASE CALLING,” filed Oct. 27, 2020. The foregoing applications are incorporated by reference for all purposes.

STATEMENT OF COMMON OWNERSHIP

[0002] Pursuant to 35 USC § 102 (b) (2) (C) and MPEP § 2146.02 (I), Applicant hereby states that this application and U.S. Provisional Patent Application No. 63/106,256, not later than the effective filing date of this application, were owned by or subject to an obligation of assignment to the same person (Illumina, Inc.), and that Illumina Software, Inc. is a wholly owned subsidiary of Illumina, Inc.

FIELD OF THE TECHNOLOGY DISCLOSED

[0003] The technology disclosed relates to apparatus and corresponding methods for the automated analysis of an image or recognition of a pattern. Included herein are systems that transform an image for the purpose of (a) enhancing its visual quality prior to recognition, (b) locating and registering the image relative to a sensor or stored prototype, or reducing the amount of image data by discarding irrelevant data, and (c) measuring significant characteristics of the image. In particular, the technology disclosed relates to generating variation correction coefficients to correct inter-cluster intensity profile variation in image data.

INCORPORATIONS

[0004] U.S. Provisional Patent Application No. 63/020,449, entitled, “EQUALIZATION-BASED IMAGE PROCESSING AND SPATIAL CROSSTALK ATTENUATOR,” filed May 5, 2020 (Attorney Docket No. ILLM 1032-1/IP-1991-PRV); [0005] U.S. Nonprovisional patent application Ser. No. 15/936,365, entitled “DETECTION APPARATUS HAVING A MICROFLUOROMETER, A FLUIDIC SYSTEM, AND A FLOW CELL LATCH CLAMP MODULE,” filed on Mar. 26, 2018; [0006] U.S. Nonprovisional patent application Ser. No. 16/567,224, entitled “FLOW CELLS AND METHODS RELATED TO SAME,” filed on Sep. 11, 2019; [0007] U.S. Nonprovisional patent application Ser. No. 16/439,635, entitled “DEVICE FOR LUMINESCENT IMAGING,” filed on Jun. 12, 2019; [0008] U.S. Nonprovisional patent application Ser. No. 15/594,413, entitled “INTEGRATED OPTOELECTRONIC READ HEAD AND FLUIDIC CARTRIDGE USEFUL FOR NUCLEIC ACID SEQUENCING,” filed on May 12, 2017; [0009] U.S. Nonprovisional patent application Ser. No. 16/351,193, entitled “ILLUMINATION FOR FLUORESCENCE IMAGING USING OBJECTIVE LENS,” filed on Mar. 12, 2019; [0010] U.S. Nonprovisional patent application Ser. No. 12/638,770, entitled “DYNAMIC AUTOFOCUS METHOD AND SYSTEM FOR ASSAY IMAGER,” filed on Dec. 15, 2009; [0011] U.S. Nonprovisional patent application Ser. No. 13/783,043, entitled “KINETIC EXCLUSION AMPLIFICATION OF NUCLEIC ACID LIBRARIES,” filed on Mar. 1, 2013; [0012] U.S. Nonprovisional patent application Ser. No. 13/006,206, entitled “DATA PROCESSING SYSTEM AND METHODS,” filed on Jan. 13, 2011; [0013] U.S. Nonprovisional patent application Ser. No. 14/530,299, entitled “IMAGE ANALYSIS USEFUL FOR PATTERNED OBJECTS,” filed on Oct. 31, 2014; [0014] U.S. Nonprovisional patent application Ser. No. 15/153,953, entitled “METHODS AND SYSTEMS FOR ANALYZING IMAGE DATA,” filed on Dec. 3, 2014; [0015] U.S. Nonprovisional patent application Ser. No. 14/020,570, entitled “CENTROID MARKERS FOR IMAGE ANALYSIS OF HIGH DENSITY CLUSTERS IN COMPLEX POLYNUCLEOTIDE SEQUENCING,” filed on Sep. 6, 2013; [0016] U.S. Nonprovisional patent application Ser. No. 14/530,299, entitled “IMAGE ANALYSIS USEFUL FOR PATTERNED OBJECTS,” filed on Oct. 31, 2014; [0017] U.S. Nonprovisional patent application Ser. No. 12/565,341, entitled “METHOD AND SYSTEM FOR DETERMINING THE ACCURACY OF DNA BASE IDENTIFICATIONS,” filed on Sep. 23, 2009; [0018] U.S. Nonprovisional patent application Ser. No. 12/295,337, entitled “SYSTEMS AND DEVICES FOR SEQUENCE BY SYNTHESIS ANALYSIS,” filed on Mar. 30, 2007; [0019] U.S. Nonprovisional patent application Ser. No. 12/020,739, entitled “IMAGE DATA EFFICIENT GENETIC SEQUENCING METHOD AND SYSTEM,” filed on Jan. 28, 2008; [0020] U.S. Nonprovisional patent application Ser. No. 13/833,619, entitled “BIOSENSORS FOR BIOLOGICAL OR CHEMICAL ANALYSIS AND SYSTEMS AND METHODS FOR SAME,” filed on Mar. 15, 2013, (Attorney Docket No. IP-0626-US); [0021] U.S. Nonprovisional patent application Ser. No. 15/175,489, entitled “BIOSENSORS FOR BIOLOGICAL OR CHEMICAL ANALYSIS AND METHODS OF MANUFACTURING THE SAME,” filed on Jun. 7, 2016, (Attorney Docket No. IP-0689-US); [0022] U.S. Nonprovisional patent application Ser. No. 13/882,088, entitled “MICRODEVICES AND BIOSENSOR CARTRIDGES FOR BIOLOGICAL OR CHEMICAL ANALYSIS AND SYSTEMS AND METHODS FOR THE

SAME,” filed on Apr. 26, 2013, (Attorney Docket No. IP-0462-US); [0023] U.S. Nonprovisional patent application Ser. No. 13/624,200, entitled “METHODS AND COMPOSITIONS FOR NUCLEIC ACID SEQUENCING,” filed on Sep. 21, 2012, (Attorney Docket No. IP-0538-US); [0024] U.S. Provisional Patent Application No. 62/821,602, entitled “TRAINING DATA GENERATION FOR ARTIFICIAL INTELLIGENCE-BASED SEQUENCING,” filed 21 Mar. 2019 (Attorney Docket No. ILLM 1008-1/IP-1693-PRV); [0025] U.S. Provisional Patent Application No. 62/821,618, entitled “ARTIFICIAL INTELLIGENCE-BASED GENERATION OF SEQUENCING METADATA,” filed 21 Mar. 2019 (Attorney Docket No. ILLM 1008-3/IP-1741-PRV); [0026] U.S. Provisional Patent Application No. 62/821,681, entitled “ARTIFICIAL INTELLIGENCE-BASED BASE CALLING,” filed 21 Mar. 2019 (Attorney Docket No. ILLM 1008-4/IP-1744-PRV); [0027] U.S. Provisional Patent Application No. 62/821,724, entitled “ARTIFICIAL INTELLIGENCE-BASED QUALITY SCORING,” filed 21 Mar. 2019 (Attorney Docket No. ILLM 1008-7/IP-1747-PRV); [0028] U.S. Provisional Patent Application No. 62/821,766, entitled “ARTIFICIAL INTELLIGENCE-BASED SEQUENCING,” filed 21 Mar. 2019 (Attorney Docket No. ILLM 1008-9/IP-1752-PRV); [0029] NL Application No. 2023310, entitled “TRAINING DATA GENERATION FOR ARTIFICIAL INTELLIGENCE-BASED SEQUENCING,” filed 14 Jun. 2019 (Attorney Docket No. ILLM 1008-11/IP-1693-NL); [0030] NL Application No. 2023311, entitled “ARTIFICIAL INTELLIGENCE-BASED GENERATION OF SEQUENCING METADATA,” filed 14 Jun. 2019 (Attorney Docket No. ILLM 1008-12/IP-1741-NL); [0031] NL Application No. 2023312, entitled “ARTIFICIAL INTELLIGENCE-BASED BASE CALLING,” filed 14 Jun. 2019 (Attorney Docket No. ILLM 1008-13/IP-1744-NL); [0032] NL Application No. 2023314, entitled “ARTIFICIAL INTELLIGENCE-BASED QUALITY SCORING,” filed 14 Jun. 2019 (Attorney Docket No. ILLM 1008-14/IP-1747-NL); and [0033] NL Application No. 2023316, entitled “ARTIFICIAL INTELLIGENCE-BASED SEQUENCING,” filed 14 Jun. 2019 (Attorney Docket No. ILLM 1008-15/IP-1752-NL). [0034] U.S. Nonprovisional patent application Ser. No. 16/825,987, entitled “TRAINING DATA GENERATION FOR ARTIFICIAL INTELLIGENCE-BASED SEQUENCING,” filed 20 Mar. 2020 (Attorney Docket No. ILLM 1008-16/IP-1693-US); [0035] U.S. Nonprovisional patent application Ser. No. 16/825,991 entitled “TRAINING DATA GENERATION FOR ARTIFICIAL INTELLIGENCE-BASED SEQUENCING,” filed 20 Mar. 2020 (Attorney Docket No. ILLM 1008-17/IP-1741-US); [0036] U.S. Nonprovisional patent application Ser. No. 16/826,126, entitled “ARTIFICIAL INTELLIGENCE-BASED BASE CALLING,” filed 20 Mar. 2020 (Attorney Docket No. ILLM 1008-18/IP-1744-US); [0037] U.S. Nonprovisional patent application Ser. No. 16/826,134, entitled “ARTIFICIAL INTELLIGENCE-BASED QUALITY SCORING,” filed 20 Mar. 2020 (Attorney Docket No. ILLM 1008-19/IP-1747-US); [0038] U.S. Nonprovisional patent application Ser. No. 16/826,168, entitled “ARTIFICIAL INTELLIGENCE-BASED SEQUENCING,” filed 21 Mar. 2020 (Attorney Docket No. ILLM 1008-20/IP-1752-PRV); [0039] U.S. Provisional Patent Application No. 62/849,091, entitled, “SYSTEMS AND DEVICES FOR CHARACTERIZATION AND PERFORMANCE ANALYSIS OF PIXEL-BASED SEQUENCING,” filed May 16, 2019 (Attorney Docket No. ILLM 1011-1/IP-1750-PRV); [0040] U.S. Provisional Patent Application No. 62/849,132, entitled, “BASE CALLING USING CONVOLUTIONS,” filed May 16, 2019 (Attorney Docket No. ILLM 1011-2/IP-1750-PR2); [0041] U.S. Provisional Patent Application No. 62/849,133, entitled, “BASE CALLING USING COMPACT CONVOLUTIONS,” filed May 16, 2019 (Attorney Docket No. ILLM 1011-3/IP-1750-PR3); [0042] U.S. Provisional Patent Application No. 62/979,384, entitled, “ARTIFICIAL INTELLIGENCE-BASED BASE CALLING OF INDEX SEQUENCES,” filed Feb. 20, 2020 (Attorney Docket No. ILLM 1015-1/IP-1857-PRV); [0043] U.S. Provisional Patent Application No. 62/979,414, entitled, “ARTIFICIAL INTELLIGENCE-BASED MANY-TO-MANY BASE CALLING,” filed Feb. 20, 2020 (Attorney Docket No. ILLM 1016-1/IP-1858-PRV); [0044] U.S. Provisional Patent Application No. 62/979,385, entitled, “KNOWLEDGE DISTILLATION-BASED COMPRESSION OF ARTIFICIAL INTELLIGENCE-BASED BASE CALLER,” filed Feb. 20, 2020 (Attorney Docket No. ILLM 1017-1/IP-1859-PRV); [0045] U.S. Provisional Patent Application No. 62/979,412, entitled, “MULTI-CYCLE CLUSTER BASED REAL TIME ANALYSIS SYSTEM,” filed Feb. 20, 2020 (Attorney Docket No. ILLM 1020-1/IP-1866-PRV); [0046] U.S. Provisional Patent Application No. 62/979,411, entitled, “DATA COMPRESSION FOR ARTIFICIAL INTELLIGENCE-BASED BASE CALLING,” filed Feb. 20, 2020 (Attorney Docket No. ILLM 1029-1/IP-1964-PRV); and [0047] U.S. Provisional Patent Application No. 62/979,399, entitled, “SQUEEZING LAYER FOR ARTIFICIAL INTELLIGENCE-BASED BASE CALLING,” filed Feb. 20, 2020 (Attorney Docket No. ILLM 1030-1/IP-1782-PRV).

BACKGROUND

[0048] The subject matter discussed in this section should not be assumed to be prior art merely as a result of its mention in this section. Similarly, a problem mentioned in this section or associated with the subject matter provided as background should not be assumed to have been previously recognized in the prior art. The subject matter in this section merely represents different approaches, which in and of themselves can also correspond to implementations of the claimed technology.

[0049] This disclosure relates to analyzing image data to base call clusters during a sequencing run. One challenge with the analysis of image data is variation in intensity profiles of clusters in a cluster population being base called. This causes a drop in data throughput and an increase in error rate during the sequencing run.

[0050] There are many potential reasons for the inter-cluster intensity profile variation. It may result from differences in cluster brightness, caused by fragment length distribution in the cluster population. It may result from phase error, which occurs when a molecule in a cluster does not incorporate a nucleotide in some sequencing cycle and lags behind other molecules, or when a molecule incorporates more than one nucleotide in a single sequencing cycle. It may result from fading, i.e., an exponential decay in signal intensity of clusters as a function of sequencing cycle number due to excessive washing and laser exposure as the sequencing run progresses. It may result from underdeveloped cluster colonies, i.e., small cluster sizes that produce empty or partially filled wells on a patterned flow cell. It may result from overlapping cluster colonies caused by unexclusive amplification. It may result from under-illumination or uneven-illumination, for example, due to clusters being located on edges of a flow cell. It may result from impurities on a flow cell that obfuscate emitted signal. It may result from polyclonal clusters, i.e., when multiple clusters are deposited in the same well.

[0051] An opportunity arises to correct the inter-cluster intensity profile variation. Improved base calling throughput and reduced base calling error rate during the sequencing run may result.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0052] The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.

[0053] The color drawings also may be available in PAIR via the Supplemental Content tab. In the drawings, like reference characters generally refer to like parts throughout the different views. Also, the drawings are not necessarily to scale, with an emphasis instead generally being placed upon illustrating the principles of the technology disclosed. In the following description, various implementations of the technology disclosed are described with reference to the following drawings, in which.

[0054] FIG. 1 illustrates one example of the inter-cluster intensity profile variation discovered and corrected by the technology disclosed.

[0055] FIG. 2 illustrates an example of a base calling pipeline that implements the variation correction logic disclosed herein.

[0056] FIG. 3 shows a least-squares solution determiner that implements a least-squares solution disclosed herein.

[0057] FIG. 4 shows an example of how the channel-specific distribution intensities are measured for a target cluster at a current sequencing cycle.

[0058] FIG. 5 shows an example of how the channel-specific intensity errors are calculated for the target cluster at the current sequencing cycle.

[0059] FIG. 6 shows an example of how the distribution centroid-to-origin distances are calculated for the target cluster at the current sequencing cycle.

[0060] FIG. 7 depicts another example of a base calling pipeline that implements the variation correction logic.

[0061] FIG. 8 shows one implementation of a weighting function described herein.

[0062] FIG. 9 shows one implementation of directly applying maximum likelihood weights to the variation correction coefficients.

[0063] FIG. 10 shows one implementation of applying an exponential decay factor to the variation correction coefficients.

[0064] FIG. 11 shows another implementation of determining channel-specific offset coefficients.

[0065] FIGS. 12, 13, and 14 compare performance of three approaches, namely, a scaling-only solution, an offsets-only solution (discussed in FIG. 11), and the least-squares solution (discussed in FIG. 3).

[0066] FIG. 15 is a computer system that can be used to implement the technology disclosed.

DETAILED DESCRIPTION

[0067] The following discussion is presented to enable any person skilled in the art to make and use the technology disclosed and is provided in the context of a particular application and its requirements. Various modifications to the disclosed implementations will be readily apparent to those skilled in the art, and the general principles defined herein may be applied to other implementations and applications without departing from the spirit and scope of the technology disclosed. Thus, the technology disclosed is not intended to be limited to the implementations shown but is to be accorded the widest scope consistent with the principles and features disclosed herein.



Introduction

[0068] Development of the technology disclosed began with the analysis of intensity profiles of clusters in a cluster population being base called during a sequencing run. Analysis revealed that the intensity profiles of the clusters in the cluster population take similar form (e.g., trapezoids), but differ in scale and shifts from an origin **132** of a multi-dimensional space **100**. We refer to this as “inter-cluster intensity profile variation.” The multi-dimensional space **100** can be a cartesian space, a polar space, a cylindrical space, or a spherical space.

[0069] FIG. 1 illustrates one example of the inter-cluster intensity profile variation discovered and corrected by the technology disclosed. FIG. 1 depicts intensity profiles **112**, **122**, and **132** of clusters 1, 2, and 3 in a cluster population, respectively. Intensity profile of a target cluster comprises intensity values that capture the chemiluminescent signals produced due to nucleotide incorporations in the target cluster at a plurality of sequencing cycles (e.g., 150) of the sequencing run.

[0070] In the implementation illustrated in FIG. 1, the intensity values are extracted from two different color/intensity channel sequencing images generated by a sequencer at each sequencing cycle in the plurality of sequencing cycles. Examples of the sequencer include Illumina's iSeq, HiSeqX, HiSeq 3000, HiSeq 4000, HiSeq 2500, NovaSeq 6000, NextSeq 550, NextSeq 1000, NextSeq 2000, NextSeqDx, MiSeq, and MiSeqDx.

[0071] In one implementation, the sequencer uses sequencing by synthesis (SBS) for generating the sequencing images. SBS relies on growing nascent strands complementary to cluster strands with fluorescently-labeled nucleotides, while tracking the emitted signal of each newly added nucleotide. The fluorescently-labeled nucleotides have a 3' removable block that anchors a fluorophore signal of the nucleotide type. SBS occurs in repetitive sequencing cycles, each comprising three steps: (a) extension of a nascent strand by adding the fluorescently-labeled nucleotide; (b) excitation of the fluorophore using one or more lasers of an optical system of the sequencer and imaging through different filters of the optical system, yielding the sequencing images; and (c) cleavage of the fluorophore and removal of the 3' block in preparation for the next sequencing cycle. Incorporation and imaging are repeated up to a designated number of sequencing cycles, defining the read length. Using this approach, each sequencing cycle interrogates a new position along the cluster strands.

[0072] In FIG. 1, the “custom-character” symbol represents the intensity values for cluster 1, the “custom-character” symbol represents the intensity values for cluster 2, and the “.” symbol represents the intensity values for cluster 3. The identity of the four different nucleotide types/bases A, C, T, and G is encoded as a combination of the intensity values in the two color images, i.e., the first and second intensity channels. For example, a nucleic acid can be sequenced by providing a first nucleotide type (e.g., base T) that is detected in the first intensity channel (x-axis of the multi-dimensional space **100**), a second nucleotide type (e.g., base C) that is detected in the second intensity channel (y-axis of the multi-dimensional space **100**), a third nucleotide type (e.g., base A) that is detected in both the first and the second intensity channels, and a fourth nucleotide type (e.g., base G) that lacks a label that is not, or minimally, detected in either intensity channels.

[0073] In some implementations, the intensity profile is generated by iteratively fitting four intensity distributions (e.g., Gaussian distributions) to the intensity values in the first and the second intensity channels. The four intensity distributions correspond to the four bases A, C, T, and G. In the intensity profile, the intensity values in the first intensity channel are plotted against the intensity values in the second intensity channel (e.g., as a scatterplot), and the intensity values segregate into the four intensity distributions.

[0074] The intensity profiles can take any shape (e.g., trapezoids, squares, rectangles, rhombus, etc.). Additional details about how the four intensity distributions are fitted to the intensity values for base calling can be found in U.S. Patent Application Publication No. 2018/0274023 A1, the disclosure of which is incorporated herein by reference in its entirety.

[0075] In one implementation, each intensity channel corresponds to one of a plurality of filter wavelength bands used by the optical system. In another implementation, each intensity channel corresponds to one of a plurality of imaging events at a sequencing cycle. In yet another implementation, each intensity channel corresponds to a combination of illumination with a specific laser and imaging through a specific optical filter of the optical system.

[0076] It would be apparent to one skilled in the art that the technology disclosed can be analogously applied to sequencing images generated using one-channel implementation, four-channel implementation, and so on. For example, in the case of four-channel implementation, four channel-specific offset coefficients are determined to correct shift variations in four intensity channels, respectively.

Variation Correction Logic

[0077] The inter-cluster intensity profile variation among intensity profiles of a large number (e.g., thousands, millions, billions, etc.) of clusters in the cluster population causes a drop in base calling throughput and an increase in base calling error rate. To correct the inter-cluster intensity profile variation, we disclose a variation correction logic that generates variation correction coefficients on a cluster-by-cluster basis.

[0078] In the two-channel implementation, the variation correction coefficients comprise an amplification coefficient that accounts for scale variation in the inter-cluster intensity profile variation, and two channel-specific offset coefficients that account for shift variation along the first and the second intensity channels in the inter-cluster intensity profile variation, respectively. In another implementation, the shift variation is accounted for by using a common offset coefficient for the different intensity channels (e.g., the first and the second intensity channels).

[0079] The variation correction coefficients for the target cluster are generated at a current sequencing cycle of the sequencing run based on combining analysis of historic intensity statistics determined for the target cluster at preceding sequencing cycles of the sequencing run with analysis of current intensity statistics determined for the target cluster at the current sequencing cycle. The variation correction coefficients are used to correct next intensity

readings registered for the target cluster a next sequencing cycle of the sequencing run. The corrected next intensity readings are used to base call the target cluster at the next sequencing cycle. The result of repeatedly applying respective variation correction coefficients to respective intensity profiles of respective clusters at successive sequencing cycles of the sequencing run is that the intensity profiles become coincidental and anchored to the origin **132** (e.g., at the bottom lower corner of the trapezoids).

[0080] FIG. 2 illustrates an example of a base calling pipeline **200** that implements the variation correction logic. Current Sequencing Cycle

[0081] At the current sequencing cycle i , the sequencer generates sequencing images **202**. The sequencing images **202** contain current intensity data **202t** registered for the target cluster at the current sequencing cycle i , along with containing current intensity data **202** registered for multiple clusters in the cluster population. The “t” in the current intensity data **202t** refers to the target cluster.

[0082] The current intensity data **202t** is provided to a base caller **212**. The base caller **212** processes the current intensity data **202t** and generates a current base call **222** for the target cluster at the current sequencing cycle i . Examples of the base caller **212** include Illumina's Real-Time Analysis (RTA) software, Illumina's neural network-based base caller (e.g., described in US Patent Publication No. US 2020/0302297 A1), and Illumina's equalizer-based base caller (e.g., described in U.S. Provisional Patent Application No. 63/020,449).

[0083] At the current sequencing cycle i , the intensity profile of the target cluster includes the current intensity data **202t**, and current historic intensity data registered for the target cluster at those sequencing cycles of the sequencing run that precede the current sequencing cycle i , i.e., preceding sequencing cycles 1 to $i-1$. We collectively refer to the current intensity data **202t** and the current historic intensity data as current available intensity data.

[0084] In the intensity profile, the four intensity distributions correspond to the four bases A, C, T, and G. In one implementation, the current base call **222** is made by determining which of the four intensity distributions the current intensity data **202t** belongs to. In some implementations, this is accomplished by using an expectation maximization algorithm. The expectation maximization algorithm iteratively maximizes the likelihood of observing means (centroids) and distributions (covariances) that best fit the current available intensity data.

[0085] Once the four intensity distributions are determined at the current sequencing cycle i by using the expectation maximization algorithm, the likelihoods of the current intensity data **202t** belonging to each of the four intensity distributions are calculated. The greatest likelihood gives the current base call **222**. As an example, consider that “m, n” are the intensity values of the current intensity data **202t** in the first and second intensity channels, respectively. The expectation maximization algorithm generates four values that represent the likelihoods of the “m, n” intensity values belonging to each of the four intensity distributions. The maximum of the four values identifies the called base.

[0086] In other implementations, a k-means clustering algorithm, a k-means-like clustering algorithm, a histogram based method, and the like can be used for base calling.

Next Sequencing Cycle

[0087] At the next sequencing cycle $i+1$, an intensity correction parameters determiner **232** determines intensity correction parameters **242** for the target cluster based on the current base call **222**. In the two-channel implementation, the intensity correction parameters **242** include distribution intensity in the first intensity channel, distribution intensity in the second intensity channel, intensity error in the first intensity channel, intensity error in the second intensity channel, distribution centroid-to-origin distance, and distribution intensity-to-intensity error similarity measure.

[0088] We define each of the intensity correction parameters **242** as follows: [0089] 1) A distribution intensity in the first intensity channel is the intensity value in the first intensity channel at a centroid of a base-specific intensity distribution to which the target cluster belongs at the current sequencing cycle i . Note that the base-specific intensity distribution is the basis for calling the current base call **222**. [0090] 2) A distribution intensity in the second intensity channel is the intensity value in the second intensity channel at the centroid of the base-specific intensity distribution. [0091] 3) An intensity error in the first intensity channel is the difference between the measured intensity value of the current intensity data **202t** in the first intensity channel and the distribution intensity in the first intensity channel. [0092] 4) An intensity error in the second intensity channel is the difference between the measured intensity value of the current intensity data **202t** in the second intensity channel and the distribution intensity in the second intensity channel. [0093] 5) A distribution centroid-to-origin distance is the Euclidean distance between the centroid of the base-specific intensity distribution and the origin **132** of the multi-dimensional space **100** in which the base-specific intensity distribution was fitted (e.g., by using the expectation maximization algorithm). In other implementations, distance metrics such as the Mahalanobis distance and the minimum covariance determinant (MCD) distances, and their associated centroid estimators can be used. [0094] 6) A distribution intensity-to-intensity error similarity measure is the summation of channel-wise dot products between the distribution intensities and the intensity errors in the first and second intensity channels.

[0095] An accumulated intensity correction parameter determiner **252** accumulates the intensity correction parameters **242** with historic accumulated intensity correction parameters **254** from preceding sequencing cycle $i-1$ to determine accumulated intensity correction parameters **262**. Examples of accumulation include summing and averaging.

[0096] A variation determination coefficients determiner **272** determines variation correction coefficients **282** based on the determined accumulated intensity correction parameters **262**.

[0097] At the next sequencing cycle $i+1$, the sequencer generates sequencing images **294**. The sequencing images **294** contain next intensity data **294t** registered for the target cluster at the next sequencing cycle $i+1$, along with containing next intensity data **294** registered for multiple clusters in the cluster population. The “t” in the next intensity data **294t** refers to the target cluster.

[0098] An intensity corrector **292** applies the variation correction coefficients **282** to the next intensity data **294t** to generate corrected next intensity data **296t**. The “t” in the corrected next intensity data **296t** refers to the target cluster.

[0099] At the next sequencing cycle $i+1$, the intensity profile of the target cluster includes the corrected next intensity data **296t**, and next historic intensity data registered for the target cluster at those sequencing cycles of the sequencing run that precede the next sequencing cycle $i+1$, i.e., preceding sequencing cycles 1 to i . We collectively refer to the corrected next intensity data **296t** and the next historic intensity data as next available intensity data.

[0100] The corrected next intensity data **296t** is provided to the base caller **212**. The base caller **212** processes the corrected next intensity data **296t** and generates a next base call **298** for the target cluster at the next sequencing cycle $i+1$. To generate the next base call **298**, the expectation maximization algorithm observes the means (centroids) and the distributions (covariances) based on the corrected next intensity data **296t** to best fit the next available intensity data.

[0101] Once the four intensity distributions are determined at the next sequencing cycle $i+1$ by using the expectation maximization algorithm, the likelihoods of the corrected next intensity data **296t** belonging to each of the four intensity distributions are calculated. The greatest likelihood gives the next base call **298**.

[0102] Note that the base calling pipeline **200** is executed on a cluster-by-cluster basis and is executed in parallel for the multiple clusters in the cluster population. Also, the base calling pipeline **200** is executed repeatedly for successive sequencing cycles of the sequencing run (e.g., for successive 150 sequencing cycles of read 1 and another successive 150 sequencing cycles of read 2 in a paired-end sequencing run).

Least-Squares Solution

[0103] FIG. 3 shows a least-squares solution determiner that implements a least-squares solution **300** disclosed herein. The least-squares solution **300** determines closed-form expressions for the accumulated intensity correction parameters **262** and the variation correction coefficients **282**. The least-squares solution determiner **302** comprises an intensity modeler **312** and a minimizer **322**.

[0104] The intensity modeler **312** models the relationship between the measured intensity for the target cluster and the variation correction coefficients **282** according to the following expression:

$$[00001] y_{C,i} = ax_{C,i} + d_i + n_{C,i} \quad \text{Equation(1)}$$

where [0105] a is the amplification coefficient for the target cluster [0106] $d_{\text{sub}.i}$ is the channel-specific offset coefficient for intensity channel i [0107] $x_{\text{sub}.C,i}$ is the distribution intensity in the intensity channel i for the target cluster at the current sequencing cycle C [0108] $y_{\text{sub}.C,i}$ is the measured intensity in the intensity channel i for the target cluster at the current sequencing cycle C [0109] $n_{\text{sub}.C,i}$ is the additive noise in the intensity channel i for the target cluster at the current sequencing cycle C

[0110] The minimizer **322** uses the least-squares solution **300** to minimize the following expression:

$$[00002] \text{errorf}(\hat{a}, \hat{d}_i) = \prod_{c=1}^C \prod_{i=1}^2 (\hat{a}x_{C,i} + \hat{d}_i - y_{C,i})^2 \quad \text{Equation(2)}$$

where: [0111] errorf is the error function [0112] \hat{a} is the amplification coefficient for the target cluster [0113] $\{\text{circumflex over (d)}\}_{\text{sub}.i}$ is the channel-specific offset coefficient for the intensity channel i [0114] C is the current sequencing cycle

[0115] Using the chain rule, the minimizer **322** calculates two partial derivatives of the error function with respect to the amplification coefficient \hat{a} and the channel-specific offset coefficients $\{\text{circumflex over (d)}\}_{\text{sub}.i}$. The partial derivatives set Equation 2 to zero to minimize the error function:

$$[00003] \frac{\partial \text{errorf}}{\partial \hat{a}} = \frac{\partial}{\partial \hat{a}} \left[\prod_{c=1}^C \prod_{i=1}^2 (\hat{a}x_{C,i} + \hat{d}_i - y_{C,i})^2 \right] = 0 \quad \text{Equation(3)}$$

$$\frac{\partial \text{errorf}}{\partial \hat{d}_i} = \frac{\partial}{\partial \hat{d}_i} \left[\prod_{c=1}^C \prod_{i=1}^2 (\hat{a}x_{C,i} + \hat{d}_i - y_{C,i})^2 \right] = 0 \quad \text{Equation(4)}$$

[0116] Channel-specific intensity error $e_{\text{sub}.c,i}$ is defined as follows:

$$[00004] e_{C,i} = y_{C,i} - x_{C,i} \quad \text{Equation(5)}$$

Closed-Form Expressions

[0117] The first partial derivative determines a closed-form expression for the amplification coefficient \hat{a} as follows:

$$[00005] \frac{\partial \text{errorf}}{\partial \hat{a}} = \prod_{c=1}^C \prod_{i=1}^2 2x_{C,i} (\hat{a}x_{C,i} + \hat{d}_i - y_{C,i}) = 0 \quad \text{Equation(6)}$$

$$= \sum_{c=1}^C \text{Math.} \sum_{i=1}^2 2x_{C,i}(\hat{a}x_{C,i} - x_{C,i} + \hat{d}_i - y_{C,i} + x_{C,i}) = 0 \quad \text{Equation(7)}$$

$$= \sum_{c=1}^C \text{Math.} \sum_{i=1}^2 x_{C,i}^2(\hat{a} - 1) + \hat{d}_i x_{C,i} - e_{C,i} x_{C,i} = 0 \quad \text{Equation(8)}$$

$$= (\hat{a} - 1) \sum_{c=1}^C (x_{C,1}^2 + x_{C,2}^2) + \hat{d}_1 \sum_{c=1}^C x_{C,1} + \hat{d}_2 \sum_{c=1}^C x_{C,2} - \sum_{c=1}^C e_{C,1} x_{C,1} - \sum_{c=1}^C e_{C,2} x_{C,2} = 0 \quad \text{Equation(9)}$$

[0118] Closed-form expressions $x_{\text{sub.1}}$, $x_{\text{sub.2}}$, $\bar{e}_{\text{sub.1}}$, $\bar{e}_{\text{sub.2}}$, xx , and xe for the accumulated intensity correction parameters **262** recharacterize Equation 9 as follows:

$$[00006] = C(\hat{a} - 1)xx + C\hat{x}_1\hat{d}_1 + C\hat{x}_2\hat{d}_2 - Cxe = 0 \quad \text{Equation(10)}$$

$$= (\hat{a} - 1)xx + \bar{x}_1\hat{d}_1 + \bar{x}_2\hat{d}_2 - xe = 0 \quad \text{Equation(11) where: } \bar{x}_1 = \sum_{c=1}^C x_{C,1} \quad \text{IntermediateTerm(1)}$$

$$\bar{x}_2 = \sum_{c=1}^C x_{C,2} \quad \text{IntermediateTerm(2)} \quad \bar{e}_1 = \sum_{c=1}^C e_{C,1} \quad \text{IntermediateTerm(3)}$$

$$\bar{e}_2 = \sum_{c=1}^C e_{C,2} \quad \text{IntermediateTerm(4)} \quad xx = \sum_{c=1}^C (x_{C,1}^2 + x_{C,2}^2) \quad \text{IntermediateTerm(5)}$$

$$xe = \sum_{c=1}^C (x_{C,1} e_{C,1} + x_{C,2} e_{C,2}) \quad \text{IntermediateTerm(6)}$$

[0119] We define each of the accumulated intensity correction parameters **262** as follows: [0120] 1) The first accumulated intensity correction parameter $x_{\text{sub.1}}$ is the sum of distribution intensities in the first intensity channel measured for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i .

[0121] 2) The second accumulated intensity correction parameter $x_{\text{sub.2}}$ is the sum of distribution intensities in the second intensity channel measured for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0122] 3) The third accumulated intensity correction parameter $\bar{e}_{\text{sub.1}}$ is the sum of intensity errors in the first intensity channel calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0123] 4) The fourth accumulated intensity correction parameter $\bar{e}_{\text{sub.2}}$ is the sum of intensity errors in the second intensity channel calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0124] 5) The fifth accumulated intensity correction parameter xx is the sum of distribution centroid-to-origin distances calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0125] 6) The sixth accumulated intensity correction parameter xe is the sum of distribution intensity-to-intensity error similarity measures calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i .

[0126] The second partial derivative determines a closed-form expression for the offset coefficients $\{\text{circumflex over (d)}\}_{\text{sub.i}}$ as follows:

$$[00007] \frac{\partial \text{errorf}}{\partial \hat{d}_i} = \sum_{c=1}^C \text{Math.} \sum_{i=1}^2 2(\hat{a}x_{C,i} + \hat{d}_i - y_{C,i}) = 0 \quad \text{Equation(12)}$$

$$= \sum_{c=1}^C \text{Math.} \sum_{i=1}^2 (\hat{a}x_{C,i} - x_{C,i} + \hat{d}_i - y_{C,i} + x_{C,i}) = 0 \quad \text{Equation(13)}$$

$$= \sum_{c=1}^C \text{Math.} \sum_{i=1}^2 x_{C,i}^2((\hat{a} - 1) + \sum_{i=1}^2 \hat{d}_i + \sum_{C=1}^C x_{C,i}) = 0 \quad \text{Equation(14)}$$

[0127] Then, for each intensity channel:

$$[00008] = C(\hat{a} - 1)\bar{x}_i + C\hat{d}_i - C\bar{e}_i = 0 \quad \text{Equation(15)} \quad = (\hat{a} - 1)\bar{x}_i + \hat{d}_i - \bar{e}_i = 0 \quad \text{Equation(16)}$$

[0128] For the first intensity channel, i.e., $i=1$:

$$[00009] \hat{d}_1 = \bar{e}_1 + (1 - \hat{a})\bar{x}_1 \quad \text{Equation(17)}$$

where: [0129] $\{\text{circumflex over (d)}\}_{\text{sub.1}}$ is the offset coefficient for the first intensity channel

[0130] For the second intensity channel, i.e., $i=2$:

$$[00010] \hat{d}_2 = \bar{e}_2 + (1 - \hat{a})\bar{x}_2 \quad \text{Equation(18)}$$

where: [0131] $\{\text{circumflex over (d)}\}_{\text{sub.2}}$ is the offset coefficient for the second intensity channel

[0132] Substituting Equations 17 and 18 in Equation 11:

$$[00011] \frac{\partial \text{errorf}}{\partial \hat{a}} = (\hat{a} - 1)xx + \bar{x}_1[\bar{e}_1 + (1 - \hat{a})\bar{x}_1] + \bar{x}_2[\bar{e}_2 + (1 - \hat{a})\bar{x}_2] - xe = 0 \quad \text{Equation(19)}$$

$$= (\hat{a} - 1)xx + (1 - \hat{a})\bar{x}_1^2 + (1 - \hat{a})\bar{x}_2^2 + \bar{x}_1\bar{e}_1 + \bar{x}_2\bar{e}_2 - xe = 0 \quad \text{Equation(20)}$$

$$= (\hat{a} - 1)(xx - \bar{x}_1^2 - \bar{x}_2^2) + \bar{x}_1\bar{e}_1 + \bar{x}_2\bar{e}_2 - xe = 0 \quad \text{Equation(21)} \quad \hat{a} - 1 = \frac{\bar{x}_1\bar{e}_1 + \bar{x}_2\bar{e}_2 - xe}{xx - \bar{x}_1^2 - \bar{x}_2^2} \quad \text{Equation(22)}$$

$$\hat{a} = 1 + \frac{\bar{x}_1\bar{e}_1 + \bar{x}_2\bar{e}_2 - xe}{xx - \bar{x}_1^2 - \bar{x}_2^2} \quad \text{Equation(23)}$$

where: [0133] \hat{a} is the amplification coefficient for the target cluster

[0134] In another implementation, to reduce the memory requirements per cluster, the common offset coefficient for the different intensity channels (e.g., the first and the second intensity channels) is determined as follows by introducing the constraint $\{\text{circumflex over (d)}\}_{\text{sub.1}} = \{\text{circumflex over (d)}\}_{\text{sub.2}}$:

$$[00012] \bar{x} = \frac{1}{C} \cdot \text{Math.} \left(\sum_{c=1}^C (x_{C,1} + x_{C,2}) \right) \text{ IntermediateTerm(1.1)}$$

$$xx = \frac{1}{C} \cdot \text{Math.} \left(\sum_{c=1}^C (x_{C,1}^2 + x_{C,2}^2) \right) \text{ IntermediateTerm(2.1)} \quad e = \frac{1}{C} \cdot \text{Math.} \left(\sum_{c=1}^C (e_{C,1} + e_{C,2}) \right) \text{ IntermediateTerm(3.1)}$$

$$xe = \frac{1}{C} \cdot \text{Math.} \left(\sum_{c=1}^C (x_{C,1} e_{C,1} + x_{C,2} e_{C,2}) \right) \text{ IntermediateTerm(4.1)} \quad \hat{a} = 1 + \frac{xe - 2\bar{x}e}{xx - 2\bar{x}^2} \text{ Equation(24)}$$


$$\hat{d}_1 = e + \bar{x}(1 - \hat{a}) \text{ Equation(25)} \quad \hat{d}_2 = e + \bar{x}(1 - \hat{a}) \text{ Equation(26)}$$

[0135] It would be apparent to one skilled in the art that the least-squares solution **300** is executed in advance of the sequencing run to determine the closed-form expressions. Once determined, the closed-form expressions are applied to the intensity values generated during the sequencing run on a cluster-by-cluster and iteratively at each sequencing cycle of the sequencing run.

Intensity Correction Parameters

[0136] The following discussion focuses on how the six intensity correction parameters, namely, the distribution intensity in the first intensity channel, the distribution intensity in the second intensity channel, the intensity error in the first intensity channel, the intensity error in the second intensity channel, the distribution centroid-to-origin distance, and the distribution intensity-to-intensity error similarity measure are determined for the target cluster at the current sequencing cycle.

[0137] It would be apparent to one skilled in the art that the number of the intensity correction parameters would change depending upon the number of intensity channels. For example, in the case of the four-channel implementation, four channel-specific distribution intensities and four channel-specific intensity errors would be calculated for the four intensity channels, respectively.

[0138] FIG. 4 shows an example **400** of how the channel-specific distribution intensities are measured for the target cluster at the current sequencing cycle i . In FIG. 4, the “” symbol represents the intensity values in the first and the second intensity channels registered for cluster 1 at the current sequencing cycle i and the preceding sequencing cycles 1 to $i-1$.

[0139] In FIG. 4, the four intensity distributions C **402**, A **406**, G **462**, and T **466** are connected to form the constellation **102** for cluster 1. In FIG. 4, the “*” symbol represents the measured intensities “m, n” **422** in the first and the second intensity channels registered for the cluster 1 at the current sequencing cycle i . Since the measured intensities “m, n” **422** are closest to centroid **414** of the intensity distribution C **402**, cluster 1 belongs to the intensity distribution C **402**, and therefore assigned the base call C at the current sequencing cycle i .

[0140] Furthermore, since cluster 1 belongs to the C intensity distribution **402**, intensity values “a, b” at the centroid **414** are the distribution intensities for cluster 1 at the current sequencing cycle i . Also, “a” is the channel-specific distribution intensity for the first intensity channel, and “b” is the channel-specific distribution intensity for the second intensity channel.

[0141] FIG. 5 shows an example **500** of how the channel-specific intensity errors are calculated for the target cluster at the current sequencing cycle i . The intensity error (er.sub.1) **532** in the first intensity channel is calculated for cluster 1 at the current sequencing cycle i as a difference between the channel-specific measured intensity in the first intensity channel (m) and the channel-specific distribution intensity in the first intensity channel (a):

$$[00013] er_1 = m - a \text{ Equation(27)}$$

[0142] The intensity error (er.sub.2) **502** in the second intensity channel is calculated for cluster 1 at the current sequencing cycle i as a difference between the channel-specific measured intensity in the second intensity channel (n) and the channel-specific distribution intensity in the second intensity channel (b):

$$[00014] er_2 = n - b \text{ Equation(28)}$$

[0143] FIG. 6 shows an example **600** of how the distribution centroid-to-origin distances are calculated for the target cluster at the current sequencing cycle i . Cluster 1 belongs to the C intensity distribution **402**, and the intensity values “a, b” at the centroid **414** are the distribution intensities for cluster 1 at the current sequencing cycle i .

[0144] The distribution centroid-to-origin distance is calculated for cluster 1 at the current sequencing cycle i as the Euclidean distance (d) **652** between the centroid **414** and the origin **132** “x, y”:

$$[00015] d = \sqrt{(a - x)^2 + (b - y)^2} \text{ Equation(29)}$$

[0145] The distribution intensity-to-intensity error similarity measure is calculated for cluster 1 at the current sequencing cycle i as a summation of channel-wise dot products between the channel-specific distribution intensities and the channel-specific intensity errors:

$$[00016] \text{similaritymeasure} = er_1 \cdot a + er_2 \cdot b \text{ Equation(30)}$$

where: [0146] .circle-solid. is the dot product operator

Base Calling Pipeline

[0147] FIG. 7 depicts another example of a base calling pipeline **700** that implements the variation correction logic. Consider that the current sequencing cycle i is the twenty-fifth sequencing cycle of the sequencing run, i.e., $i=25$. The preceding sequencing cycle $i-1$ is the twenty-fourth sequencing cycle of the sequencing run, i.e., $i-1=24$. The next sequencing cycle $i+1$ is the twenty-sixth sequencing cycle of the sequencing run, i.e., $i+1=26$. The subsequent sequencing cycle $i+2$ is the twenty-seventh sequencing cycle of the sequencing run, i.e., $i+2=27$.

Preceding Sequencing Cycles

[0148] At each of the first to the twenty-fourth sequencing cycles, respective sets of accumulated intensity correction parameters are determined from respective sets of intensity correction parameters. Preceding accumulated intensity correction parameters **702** for the target cluster are intensity correction parameter-wise accumulations of the twenty four sets of the intensity correction parameters. In the two-channel implementation, each of the twenty four sets of the intensity correction parameters includes the six intensity correction parameters, namely, the distribution intensity in the first intensity channel, the distribution intensity in the second intensity channel, the intensity error in the first intensity channel, the intensity error in the second intensity channel, the distribution centroid-to-origin distance, and the distribution intensity-to-intensity error similarity. Each of the twenty four sets of the accumulated intensity correction parameters includes the six accumulated intensity correction parameters $x_{\text{sub.1}}$, $x_{\text{sub.2}}$, $\bar{e}_{\text{sub.1}}$, $\bar{e}_{\text{sub.2}}$, \bar{x} , and \bar{e} .

[0149] The preceding accumulated intensity correction parameters **702** are metadata (or statistics) about the underlying preceding intensity values and preceding intensity correction parameters from which they are calculated. As a result, compared to the underlying preceding intensity values and the preceding intensity correction parameters, the preceding accumulated intensity correction parameters **702** have a much smaller memory footprint. The preceding accumulated intensity correction parameters **702** are cached in memory during the sequencing run and are accumulated with current intensity correction parameters **732** for the target cluster to generate current accumulated intensity correction parameters **742** for the target cluster, as depicted by triangle **734**.

[0150] In one implementation, the preceding accumulated intensity correction parameters **702** are stored in a quantized fixed bit width format. For example, one or two bytes can be used to store each preceding accumulated intensity correction parameter in the preceding accumulated intensity correction parameters **702**.

Current Sequencing Cycle

[0151] Current measured intensity **712** for the target cluster includes the intensity values registered for the target cluster at the twenty-fifth sequencing cycle. Based on the current measured intensity **712**, a current base call **722** is called for the target cluster at the twenty-fifth sequencing cycle (e.g., by using the expectation maximization algorithm).

Next Sequencing Cycle

[0152] Based on the current base call **722**, the current intensity correction parameters **732** are determined for the target cluster. The current accumulated intensity correction parameters **742** are calculated for the target cluster based on accumulating the preceding accumulated intensity correction parameters **702** with the current intensity correction parameters **732**, as depicted by the triangle **734**. One example of the accumulation is summing. In the summing implementation, the current accumulated intensity correction parameters **742** are calculated by summing the preceding accumulated intensity correction parameters **702** and the current intensity correction parameters **732** on an intensity correction parameter-basis (as shown above in Intermediate Terms 1 to 6).

[0153] Another example of the accumulation is averaging:

$$[00017] \quad x_1 = \frac{1}{C} \cdot \text{Math.} \sum_{c=1}^C x_{C,1} \quad \text{IntermediateTerm(1.2)} \quad x_2 = \frac{1}{C} \cdot \text{Math.} \sum_{c=1}^C x_{C,2} \quad \text{IntermediateTerm(2.2)}$$

$$e_1 = \frac{1}{C} \cdot \text{Math.} \sum_{c=1}^C e_{C,1} \quad \text{IntermediateTerm(3.2)} \quad e_2 = \frac{1}{C} \cdot \text{Math.} \sum_{c=1}^C e_{C,2} \quad \text{IntermediateTerm(4.2)}$$

$$\bar{x} = \frac{1}{C} \cdot \text{Math.} \sum_{c=1}^C (x_{C,1}^2 + x_{C,2}^2) \quad \text{IntermediateTerm(5.2)}$$

$$\bar{e} = \frac{1}{C} \cdot \text{Math.} \sum_{c=1}^C (x_{C,1} e_{C,1} + x_{C,2} e_{C,2}) \quad \text{IntermediateTerm(6.2)}$$

where C is the index for the current sequencing cycle i , i.e., $C=25$ in the example discussed herein

[0154] Based on the Intermediate Terms 1.2 to 6.2, we define each of the accumulated intensity correction parameters as follows: [0155] 1) The first accumulated intensity correction parameter $x_{\text{sub.1}}$ is the average of the distribution

intensities in the first intensity channel measured for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0156] 2) The second accumulated intensity correction parameter $x_{\text{sub.2}}$ is the average of the distribution intensities in the second intensity channel measured for the target cluster at each of the

preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0157] 3) The third accumulated intensity correction parameter $\bar{e}_{\text{sub.1}}$ is the average of the intensity errors in the first intensity channel calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0158] 4) The fourth

accumulated intensity correction parameter $\bar{e}_{\text{sub}.2}$ is the average of the intensity errors in the second intensity channel calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0159] 5) The fifth accumulated intensity correction parameter xx is the average of the distribution centroid-to-origin distances calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i . [0160] 6) The sixth accumulated intensity correction parameter xe is the average of the distribution intensity-to-intensity error similarity measures calculated for the target cluster at each of the preceding sequencing cycles 1 to $i-1$, and the current sequencing cycle i .

Compact Representation

[0161] In one implementation, the preceding accumulated intensity correction parameters **702** are stored in a compact representation (e.g., a summed representation or an averaged representation). In the averaging implementation, the preceding accumulated intensity correction parameters **702** are stored in their averaged representation and first multiplied by the number of sequencing cycles over which they are accumulated to retrieve the pre-average representation, i.e., 24 is the multiplier in the example discussed herein.

[0162] Then, the result of the multiplication, i.e., the pre-average representation is summed with the current intensity correction parameters **732** on the intensity correction parameter-basis. Then, the result of the sum is divided by the index C for the current sequencing cycle i ($C=25$) to determine the current accumulated intensity correction parameters **742**.

[0163] Consider that $x_{\text{sub}.1.\text{sup}.24}$ is the first accumulated intensity correction parameter for the twenty-fourth sequencing cycle. Consider that $x_{\text{sup}.25.\text{sub}.C,1}$ is the distribution intensity in the first intensity channel for the twenty-fifth sequencing cycle. Consider that $x_{\text{sub}.1.\text{sup}.2}$ is the first accumulated intensity correction parameter for the twenty-fifth sequencing cycle and used to correct the measured intensity for the twenty-sixth sequencing cycle.

Then,

$$[00018]\bar{x}_1^{25} = \frac{[(x_1^{24} * 24) + x_{C,1}^{25}]}{25}$$

[0164] Consider that $x_{\text{sub}.2.\text{sup}.24}$ is the second accumulated intensity correction parameter for the twenty-fourth sequencing cycle. Consider that $x_{\text{sup}.25.\text{sub}.C,2}$ is the distribution intensity in the second intensity channel for the twenty-fifth sequencing cycle. Consider that $x_{\text{sub}.2.\text{sup}.25}$ is the second accumulated intensity correction parameter for the twenty-fifth sequencing cycle and used to correct the measured intensity for the twenty-sixth sequencing cycle. Then,

$$[00019]\bar{x}_2^{25} = \frac{[(x_2^{24} * 24) + x_{C,2}^{25}]}{25}$$

[0165] Consider that $\bar{e}_{\text{sub}.1.\text{sup}.24}$ is the third accumulated intensity correction parameter for the twenty-fourth sequencing cycle. Consider that $\bar{e}_{\text{sup}.25.\text{sub}.C,1}$ is the intensity error in the first intensity channel for the twenty-fifth sequencing cycle. Consider that $\bar{e}_{\text{sub}.1.\text{sup}.25}$ is the third accumulated intensity correction parameter for the twenty-fifth sequencing cycle and used to correct the measured intensity for the twenty-sixth sequencing cycle. Then,

$$[00020]e_1^{25} = \frac{[(e_1^{24} * 24) + e_{C,1}^{25}]}{25}$$

[0166] Consider that $\bar{e}_{\text{sub}.2.\text{sup}.24}$ is the fourth accumulated intensity correction parameter for the twenty-fourth sequencing cycle. Consider that $\bar{e}_{\text{sup}.25.\text{sub}.C,2}$ is the intensity error in the second intensity channel for the twenty-fifth sequencing cycle. Consider that $\bar{e}_{\text{sub}.2.\text{sup}.25}$ is the fourth accumulated intensity correction parameter for the twenty-fifth sequencing cycle and used to correct the measured intensity for the twenty-sixth sequencing cycle. Then,

$$[00021]e_2^{25} = \frac{[(e_2^{24} * 24) + e_{C,2}^{25}]}{25}$$

[0167] Consider that $xx_{\text{sup}.24}$ is the fifth accumulated intensity correction parameter for the twenty-fourth sequencing cycle. Consider that $[(x_{\text{sub}.C,1.\text{sup}.25})_{\text{sup}.2} + (x_{\text{sub}.C,2.\text{sup}.25})_{\text{sup}.2}]$ is the distribution centroid-to-origin distance for the twenty-fifth sequencing cycle. Consider that $xx_{\text{sup}.25}$ is the fifth accumulated intensity correction parameter for the twenty-fifth sequencing cycle and used to correct the measured intensity for the twenty-sixth sequencing cycle. Then,

$$[00022]\bar{xx}^{25} = \frac{[(\bar{xx}^{24} * 24) + [(x_{C,1}^{25})^2 + (x_{C,2}^{25})^2]]}{25}$$

[0168] Consider that $xe_{\text{sup}.24}$ is the sixth accumulated intensity correction parameter for the twenty-fourth sequencing cycle. Consider that $[(x_{\text{sub}.C,1.\text{sup}.25e_{\text{sub}.C,2.\text{sup}.25}}) + (x_{\text{sub}.C,2.\text{sup}.25e_{\text{sub}.C,2.\text{sup}.2}})]$ is the distribution intensity-to-intensity error similarity measure for the twenty-fifth sequencing cycle. Consider that $xe_{\text{sup}.25}$ is the sixth accumulated intensity correction parameter for the twenty-fifth sequencing cycle and used to correct the measured intensity for the twenty-sixth sequencing cycle. Then,

$$[00023]\bar{xe}^{25} = \frac{[(\bar{xe}^{24} * 24) + [(x_{C,1}^{25}e_{C,1}^{25}) + (x_{C,2}^{25}e_{C,2}^{25})]]}{25}$$

[0169] The current accumulated intensity correction parameters **742** are metadata (or statistics) about the current measured intensity **712** and the current intensity correction parameters **732**. As a result, compared to the current measured intensity **712** and the current intensity correction parameters **732**, the current accumulated intensity correction parameters **742** have a much smaller memory footprint. The current accumulated intensity correction parameters **742** are cached in memory during the sequencing run and are accumulated with next intensity correction parameters **794** for the target cluster to generate next accumulated intensity correction parameters **796** for the target

cluster, as depicted by triangle **784**.

[0170] In one implementation, the current accumulated intensity correction parameters **742** are stored in a quantized fixed bit width format. For example, one or two bytes can be used to store each preceding accumulated intensity correction parameter in the current accumulated intensity correction parameters **742**.

[0171] The current accumulated intensity correction parameters **742** are used to determine a current amplification coefficient **752** for the target cluster. This includes executing the closed-form expression in Equation 23 in dependence upon the current accumulated intensity correction parameters **742**.

[0172] The current accumulated intensity correction parameters **742** and the current amplification coefficient **752** are used to determine current channel-specific offset coefficients **762** for the target cluster. This includes executing the closed-form expressions in Equations 17 and 18 in dependence upon the current accumulated intensity correction parameters **742** and the amplification coefficient **752**.

[0173] The current amplification coefficient **752** and the current channel-specific offset coefficients **762** are used to correct a next measured intensity **772** measured for the target cluster at the twenty-sixth sequencing cycle. In one implementation, the correcting includes channel-wise subtracting the current channel-specific offset coefficients **762** from the next measured intensity **772** to generate next shifted intensity, and dividing the next shifted intensity by the current amplification coefficient **752** to generate next corrected measured intensity **782** for the target cluster.

[0174] Then, a next base call **792** is called for the target cluster at the twenty-sixth sequencing cycle using the next corrected measured intensity **782**. This is accomplished by providing the next corrected measured intensity **782** as input to the base caller **212** (e.g., by using the expectation maximization algorithm).

Subsequent Sequencing Cycle

[0175] A controller (not shown) iterates the base calling pipeline **700** for successive sequencing cycles of the sequencing run, as exemplified by operations **794**, **796**, **798**, and **799**. For example, for the twenty-seventh sequencing cycle, the current accumulated intensity correction parameters **742** serve as the preceding accumulated intensity correction parameters **702**, as depicted by triangle **784**. Note that the base calling pipeline **700** is executed on a cluster-by-cluster basis and is executed in parallel for the multiple clusters in the cluster population.

Weighted Least-Squares Solution

[0176] FIG. **8** shows one implementation of a weighting function **800** described herein. Since the least-squares solution **300** can take several sequencing cycles to converge, the weighting function **800** is used to attenuate the variation correction coefficients in initial sequencing cycles of the sequencing run, and to amplify the variation correction coefficients in later sequencing cycles of the sequencing run.

[0177] The weighting function **800** works as follows. First, an initial amplification coefficient **802** and initial offset coefficients **822** and **832** are initialized. In one implementation, the initial amplification coefficient **802** is initialized at a first sequencing cycle of the sequencing run with a predetermined value (e.g., “1”) and the initial offset coefficients **822** and **832** are initialized at the first sequencing cycle with a predetermined value (e.g., “0”). The weighting function **800** combines (e.g., sums) the initial amplification coefficient **802** with the amplification coefficients **806** (determined by the least-squares solution **300**), and combines the initial first and second offset coefficients **822** and **832** with the first and second offset coefficients **826** and **836** (determined by the least-squares solution **300**), such that the amplification coefficient **806** and the first and second offset coefficients **826** and **836** are attenuated in the initial sequencing cycles and amplified in the later sequencing cycles.

[0178] In one implementation, the weighting function **800** applies (e.g., multiplies) an initial minimum weight (inimin weight) **804** to the initial amplification coefficient **802** and the initial first and second offset coefficients **822** and **832**, and a least-squares maximum weight (lsqmax weight) **808** to the amplification coefficient **806** and the first and second offset coefficients **826** and **836**, such that:

$$[00024] \text{lsqmaxweight} = (0, \frac{c-p}{c}) \quad \text{Equation(31)} \quad \text{iniminweight} = (1, 1 - [\frac{c-p}{c}]) \quad \text{Equation(32)}$$

where: [0179] c is an index of the current sequencing cycle [0180] p is a number between 2 to 7

[0181] For the first sequencing cycle, i.e., $c=1$, and for $p=2$, the expression

$$[00025] (\frac{c-p}{c})$$

equals to “-1”. Then, between “0” and “-1,” the lsqmax weight **808** selects the maximum of the two values, i.e., 0.

The expression

$$[00026] (1 - [\frac{c-p}{c}])$$

equals to “2.” Then, between “1” and “2,” the inimin weight **804** selects the minimum of the two values, i.e., 1.

[0182] Continuing ahead, 0 from the lsqmax weight **808** is multiplied with the amplification coefficient **806** and the first and second offset coefficients **826** and **836**, and 1 from the inimin weight **804** is multiplied with the initial amplification coefficient **802** and the initial first and second offset coefficients **822** and **832**. The results of the two multiplications are summed to generate the weighted amplification coefficient **810** and the weighted first and second offset coefficients **820** and **830**.

[0183] As the sequencing run progresses and the value of the index “ c ” increments, and the values of the lsqmax weight **808** and the inimin weight **804** also change and applied analogously, such that the amplification coefficient **806** and the first and second offset coefficients **826** and **836** (learned from the least-squares solution **300**) are

progressively amplified at each successive sequencing cycle.

[0184] The weighting function **800** generates the weighted amplification coefficient **810** and the weighted first and second offset coefficients **820** and **830**, which are used to correct the measured intensities for the target cluster at the next sequencing cycles $i+1$ and to generate the corrected measured intensities for base calling the target cluster at the next sequencing cycles $i+1$:

$$[00027] \hat{a} = 1 + \frac{W\bar{x}e - \bar{x}_1 e_1 - \bar{x}_2 e_2}{W\bar{x}\bar{x} - \bar{x}_1^2 - \bar{x}_2^2} \quad \text{Equation(33)} \quad \hat{d}_1 = \frac{-\bar{x}_1 W\bar{x}e + (W\bar{x}\bar{x} - \bar{x}_2^2)e_1 + \bar{x}_1 \bar{x}_2 e_2}{W(W\bar{x}\bar{x} - \bar{x}_1^2 - \bar{x}_2^2)} \quad \text{Equation(34)}$$

$$\hat{d}_2 = \frac{-\bar{x}_2 W\bar{x}e + (W\bar{x}\bar{x} - \bar{x}_1^2)e_2 + \bar{x}_1 \bar{x}_2 e_1}{W(W\bar{x}\bar{x} - \bar{x}_1^2 - \bar{x}_2^2)} \quad \text{Equation(35)}$$

where: [0185] W is the weight

Maximum Likelihood Solution

[0186] FIG. **9** shows one implementation of directly applying maximum likelihood weights **906**, **908**, and **910** to the variation correction coefficients. The maximum likelihood weights **906**, **908**, and **910** are generated by applying a maximum likelihood solution **900** to probability distributions **902** of historical values observed for the variation correction coefficients in previous sequencing runs. FIG. **9** also illustrates accumulated intensity correction parameters **904**.

[0187] The maximum likelihood weights **906**, **908**, and **910** are a function of the current sequencing cycle, as represented by the index “C.” The maximum likelihood weights **906**, **908**, and **910** change on a sequencing cycle-basis in dependence upon the index C. The maximum likelihood weights **906**, **908**, and **910** are also a function of the additive noise, as represented by the character “n.” The sigma term “o” represents the range of variation in the historical values observed for the respective variation correction coefficient, i.e., variance (62). In some implementations, the sigma term for the additive noise can be estimated using the maximum likelihood solution **900** or can be user-specified. The sigma terms for the amplification coefficient, the channel-specific offset coefficients, and the additive noise are determined on a sequencing run-basis and kept fixed for all the sequencing cycles of the sequencing run. The sigma terms incorporate apriori knowledge about the uncertainty observed in the variation correction coefficients.

[0188] Some example values of the sigma terms are: [0189] ‘ml_chanest_sigma_a’, 0.15 [0190]

‘ml_chanest_sigma_d1’, 0.1 [0191] ‘ml_chanest_sigma_d2’, 0.02 [0192] ‘ml_chanest_sigma_n’, 0.14

[0193] In one implementation, a center/initial/mean value for the probability distribution of the amplification coefficient is set to be “1,” and a center/initial/mean value for the probability distributions of the channel-specific offset coefficients is set to be “0.”

[0194] Smaller values of the sigma terms for the amplification coefficient and the channel-specific offset coefficients in the maximum likelihood weights **906**, **908**, and **910** indicate low variation in their respective historical values. This results in higher values of the maximum likelihood weights **906**, **908**, and **910**. This in turn leads to a weighted amplification coefficient **920** that is weighted in favor of the center value 1, and weighted channel-specific offset coefficients **930** and **940** that are weighted in favor of the center value 0, particularly in the early sequencing cycles.

[0195] Conversely, larger values of the sigma terms for the amplification coefficient and the channel-specific offset coefficients in the maximum likelihood weights **906**, **908**, and **910** indicate high variation in their respective historical values. This results in lower values of the maximum likelihood weights **906**, **908**, and **910**. This in turn leads to the weighted amplification coefficient **920** that is weighted in favor of the output of the least-squares solution **300** (e.g., Equation 23), and the weighted channel-specific offset coefficients **930** and **940** that are weighted in favor of the output of the least-squares solution **300** (e.g., Equations 17 and 18), particularly in the later sequencing cycles.

[0196] The maximum likelihood weights **906**, **908**, and **910** are directly incorporated to calculate the weighted amplification coefficient **920** and the weighted channel-specific offset coefficients **930** and **940**, respectively.

Exponential Decay Factor Solution

[0197] FIG. **10** shows one implementation of applying an exponential decay factor to the variation correction coefficients. Exponential decay logic **1000** is based on so-called “tau” and “stats.cycle.” The term “stats.cycle” refers to the current sequencing cycle.

[0198] Tau is set to a predetermined value depending on the degree of time variance observed in the intensity correction parameters. If the intensity correction parameters are time-invariant, then tau can be set to infinity. If the intensity correction parameters are rapidly time-variant, then tau can be set to a small value. In one implementation, tau is set to thirty-two.

[0199] Consider that tau is thirty-two. Then, according to statements **1002**, **1004**, and **1006**, the decay factor is “1” for sequencing cycles one to thirty-one, and this results in no decay in the accumulated intensity correction parameters. For sequencing cycles thirty-two and above, the decay factor is thirty-one over thirty-two, based on statement **1008**. The exponential decay character comes from the fact that, in statements **1010**, **1012**, **1014**, **1016**, **1018**, and **1020**, each of the accumulated intensity correction parameters is multiplied by the decay factor at each successive sequencing cycle, as shown below:

For sequencing cycle 32,

[00028]decayfactor = $\frac{31}{32}$

[00029] $\bar{x}_1^D = \frac{31}{32} * x_1$ DecayedIntermediateTerm(1.3) $\bar{x}_2^D = \frac{31}{32} * x_2$ DecayedIntermediateTerm(2.3)

$\bar{e}_1^D = \frac{31}{32} * e_1$ DecayedIntermediateTerm(3.3) $\bar{e}_2^D = \frac{31}{32} * e_2$ DecayedIntermediateTerm(4.3)

$\bar{x}\bar{x}^D = \frac{31}{32} * \bar{x}\bar{x}$ DecayedIntermediateTerm(5.3) $\bar{x}\bar{e}^D = \frac{31}{32} * \bar{x}\bar{e}$ DecayedIntermediateTerm(6.3)

For sequencing cycle 33,

[00030]decayfactor = $[\frac{31}{32}]^2$

[00031] $\bar{x}_1^D = [\frac{31}{32}]^2 * x_1$ DecayedIntermediateTerm(1.4) $\bar{x}_2^D = [\frac{31}{32}]^2 * x_2$ DecayedIntermediateTerm(2.4)

$\bar{e}_1^D = [\frac{31}{32}]^2 * e_1$ DecayedIntermediateTerm(3.4) $\bar{e}_2^D = [\frac{31}{32}]^2 * e_2$ DecayedIntermediateTerm(4.4)

$\bar{x}\bar{x}^D = [\frac{31}{32}]^2 * \bar{x}\bar{x}$ DecayedIntermediateTerm(5.4) $\bar{x}\bar{e}^D = [\frac{31}{32}]^2 * \bar{x}\bar{e}$ DecayedIntermediateTerm(6.4)

[0200] In FIG. 10, the accumulated intensity correction parameters are accumulated using the sum operation. In the averaging implementation of the exponential decay factor, the accumulated intensity correction parameters are accumulated using the average operation. In the averaging implementation of the exponential decay factor, the divisor “C” in the Intermediate Terms 1.2 to 6.2 is kept fixed after the tau number of sequencing cycles of the sequencing run, i.e., after thirty-second sequencing cycle of the sequencing run.

[0201] In some implementations, the weighted least-squares solution (FIG. 8), the maximum likelihood solution (FIG. 9), and the exponential decay factor solution (FIG. 10) are combined to generate weighted variation correction coefficients at each sequencing cycle of the sequencing run.

Channel-Specific Offset Coefficients

[0202] FIG. 11 shows another implementation of determining the channel-specific offset coefficients. In the two-channel implementation, a first channel-specific offset coefficient (“ Δx ”) for the first intensity channel and for the target cluster at the current sequencing cycle is calculated as a difference between the measured intensity (“p”) in the first intensity channel for the target cluster at the current sequencing cycle and the intensity value (“u”) in the first intensity channel at a centroid 1104 of a base-specific intensity distribution A 1102 to which the target cluster belongs at the current sequencing cycle (e.g., as determined by the expectation maximization algorithm).

[0203] In the two-channel implementation, a second channel-specific offset coefficient (“ Δy ”) for the second intensity channel and for the target cluster at the current sequencing cycle is calculated as a difference between the measured intensity (“q”) in the second intensity channel for the target cluster at the current sequencing cycle and the intensity value (“v”) in the second intensity channel at the centroid 1104 of the base-specific intensity distribution A 1102 to which the target cluster belongs at the current sequencing cycle.

[0204] In one implementation, the first channel-specific offset coefficient (“ Δx ”) and the second channel-specific offset coefficient (“ Δy ”) are determined at each sequencing cycle of the sequencing run. In some implementations, after a configurable number of sequencing cycles (e.g., ten or twenty sequencing cycles), the first channel-specific offset coefficient (“ Δx ”) and the second channel-specific offset coefficient (“ Δy ”) are initialized with a predetermined value (e.g., “0”).

[0205] In a rolling-average implementation, an average is calculated for the first offset channel-specific coefficient (“ Δx ”) and the second channel-specific offset coefficient (“ Δy ”) after the configurable number of sequencing cycles. The average is then used as a substitute for the first offset channel-specific coefficient (“ Δx ”) and the second channel-specific offset coefficient (“ Δy ”) until the next average is calculated for the next set of the configurable number of sequencing cycles.

[0206] In some implementations, the first channel-specific offset coefficient (“ Δx ”) and the second channel-specific offset coefficient (“ Δy ”) are calculated only when the target cluster belongs to the A, C, and T base-specific intensity distributions, and not when the target cluster belongs to the G (dark) base-specific intensity distribution. In implementations when the sequencing run involves pair-ended reads, the first channel-specific offset coefficient (“ Δx ”) and the second channel-specific offset coefficient (“ Δy ”) are initialized for the second read with the values available at the end of the first read, but updated thereafter each set of the configurable number of sequencing cycles.

Performance Results

[0207] FIGS. 12, 13, and 14 compare performance of three approaches, namely, a scaling-only solution, an offsets-only solution (discussed in FIG. 11), and the least-squares solution 300. The three approaches are applied to intensity data generated using Illumina's Real-Time Analysis (RTA) software over twenty datasets from Illumina's sequencer NextSeq 2000.

[0208] In FIG. 12, the performance of the scaling-only solution (blue), the offsets-only solution (orange), and the least-squares solution (grey) are comparatively plotted for the percentage of clusters passing the RTA's two-channel chastity filter. The comparison is done over the twenty datasets (shown as the x-axis). While all three approaches achieve >65% of clusters passing the two-channel chastity filter, 16 out of 20 cases (80%) score higher than 75% passing rate and 8/20 (or 20%) score >80% passing rate. Note that the least-squares solution 300 performs the best.

[0209] In FIG. 13, the performance of the scaling-only solution (blue), the offsets-only solution (orange), and the

least-squares solution (grey) are comparatively plotted for the error rates in low-diversity samples. The comparison is done over twenty low-diversity datasets spiked with a known phage genome (PhiX) (shown as the x-axis). Seventeen out of twenty (17/20 or 68%) achieve <35% error rate, while majority enjoy lower than 25% error rates. Note that the least-squares solution **300** performs the best.

[0210] In FIG. **14**, the performance of the scaling-only solution (blue), the offsets-only solution (orange), and the least-squares solution (grey) are comparatively plotted for the percentage of sequencing data have quality scores above Q30 (i.e. base call error <10.sup.-30/10 or 0.1%). The comparison is done over the same twenty datasets (shown as the x-axis). While all three approaches enjoy high Q30 quality score (e.g. >80%), 16 out of 20 cases (80%) score higher than 75% passing rate and 8/20 (or 20%) score >80% passing rate. Note that the least-squares solution **300** outperforms the others by >2% points.

Computer System

[0211] FIG. **15** is a computer system **1500** that can be used to implement the technology disclosed. Computer system **1500** includes at least one central processing unit (CPU) **1572** that communicates with a number of peripheral devices via bus subsystem **1555**. These peripheral devices can include a storage subsystem **1510** including, for example, memory devices and a file storage subsystem **1536**, user interface input devices **1538**, user interface output devices **1576**, and a network interface subsystem **1574**. The input and output devices allow user interaction with computer system **1500**. Network interface subsystem **1574** provides an interface to outside networks, including an interface to corresponding interface devices in other computer systems.

[0212] In one implementation, the least-squares solution determiner **302** is communicably linked to the storage subsystem **1510** and the user interface input devices **1538**.

[0213] User interface input devices **1538** can include a keyboard; pointing devices such as a mouse, trackball, touchpad, or graphics tablet; a scanner; a touch screen incorporated into the display; audio input devices such as voice recognition systems and microphones; and other types of input devices. In general, use of the term "input device" is intended to include all possible types of devices and ways to input information into computer system **1500**.

[0214] User interface output devices **1576** can include a display subsystem, a printer, a fax machine, or non-visual displays such as audio output devices. The display subsystem can include an LED display, a cathode ray tube (CRT), a flat-panel device such as a liquid crystal display (LCD), a projection device, or some other mechanism for creating a visible image. The display subsystem can also provide a non-visual display such as audio output devices. In general, use of the term "output device" is intended to include all possible types of devices and ways to output information from computer system **1500** to the user or to another machine or computer system.

[0215] Storage subsystem **1510** stores programming and data constructs that provide the functionality of some or all of the modules and methods described herein. These software modules are generally executed by processors **1578**.

[0216] Processors **1578** can be graphics processing units (GPUs), field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), and/or coarse-grained reconfigurable architectures (CGRAs). Processors **1578** can be hosted by a deep learning cloud platform such as Google Cloud Platform™, Xilinx™, and Cirrascale™. Examples of processors **1578** include Google's Tensor Processing Unit (TPU)™, rackmount solutions like GX4 Rackmount Series™, GX15 Rackmount Series™, NVIDIA DGX-1™, Microsoft's Stratix V FPGA™, Graphcore's Intelligent Processor Unit (IPU)™, Qualcomm's Zeroth Platform™ with Snapdragon processors™, NVIDIA's Volta™, NVIDIA's DRIVE PX™, NVIDIA's JETSON TX1/TX2 MODULE™, Intel's Nirvana™, Movidius VPU™, Fujitsu DPI™, ARM's DynamicIQ™, IBM TrueNorth™, Lambda GPU Server with Testa V100s™, and others.

[0217] Memory subsystem **1522** used in the storage subsystem **1510** can include a number of memories including a main random access memory (RAM) **1532** for storage of instructions and data during program execution and a read only memory (ROM) **1534** in which fixed instructions are stored. A file storage subsystem **1536** can provide persistent storage for program and data files, and can include a hard disk drive, a floppy disk drive along with associated removable media, a CD-ROM drive, an optical drive, or removable media cartridges. The modules implementing the functionality of certain implementations can be stored by file storage subsystem **1536** in the storage subsystem **1510**, or in other machines accessible by the processor.

[0218] Bus subsystem **1555** provides a mechanism for letting the various components and subsystems of computer system **1500** communicate with each other as intended. Although bus subsystem **1555** is shown schematically as a single bus, alternative implementations of the bus subsystem can use multiple busses.

[0219] Computer system **1500** itself can be of varying types including a personal computer, a portable computer, a workstation, a computer terminal, a network computer, a television, a mainframe, a server farm, a widely-distributed set of loosely networked computers, or any other data processing system or user device. Due to the ever-changing nature of computers and networks, the description of computer system **1500** depicted in FIG. **15** is intended only as a specific example for purposes of illustrating the preferred implementations of the present invention. Many other configurations of computer system **1500** are possible having more or less components than the computer system depicted in FIG. **15**.

[0220] Each of the processors or modules discussed herein may include an algorithm (e.g., instructions stored on a

tangible and/or non-transitory computer readable storage medium) or sub-algorithms to perform particular processes. The variation corrector 232 is illustrated conceptually as a collection of modules, but may be implemented utilizing any combination of dedicated hardware boards, DSPs, processors, etc. Alternatively, the variation corrector 232 may be implemented utilizing an off-the-shelf PC with a single processor or multiple processors, with the functional operations distributed between the processors. As a further option, the modules described below may be implemented utilizing a hybrid configuration in which certain modular functions are performed utilizing dedicated hardware, while the remaining modular functions are performed utilizing an off-the-shelf PC and the like. The modules also may be implemented as software modules within a processing unit.

[0221] Various processes and steps of the methods set forth herein (e.g., FIG. 9) can be carried out using a computer. The computer can include a processor that is part of a detection device, networked with a detection device used to obtain the data that is processed by the computer or separate from the detection device. In some implementations, information (e.g., image data) may be transmitted between components of a system disclosed herein directly or via a computer network. A local area network (LAN) or wide area network (WAN) may be a corporate computing network, including access to the Internet, to which computers and computing devices comprising the system are connected. In one implementation, the LAN conforms to the transmission control protocol/internet protocol (TCP/IP) industry standard. In some instances, the information (e.g., image data) is input to a system disclosed herein via an input device (e.g., disk drive, compact disk player, USB port etc.). In some instances, the information is received by loading the information, e.g., from a storage device such as a disk or flash drive.

[0222] A processor that is used to run an algorithm or other process set forth herein may comprise a microprocessor. The microprocessor may be any conventional general purpose single- or multi-chip microprocessor such as a Pentium™ processor made by Intel Corporation. A particularly useful computer can utilize an Intel Ivybridge dual-12 core processor, LSI raid controller, having 128 GB of RAM, and 2 TB solid state disk drive. In addition, the processor may comprise any conventional special purpose processor such as a digital signal processor or a graphics processor. The processor typically has conventional address lines, conventional data lines, and one or more conventional control lines.

[0223] The implementations disclosed herein may be implemented as a method (e.g., FIGS. 2 and 7), apparatus, system or article of manufacture using standard programming or engineering techniques to produce software, firmware, hardware, or any combination thereof. The term “article of manufacture” as used herein refers to code or logic implemented in hardware or computer readable media such as optical storage devices, and volatile or non-volatile memory devices. Such hardware may include, but is not limited to, field programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), complex programmable logic devices (CPLDs), programmable logic arrays (PLAs), microprocessors, or other similar processing devices. In particular implementations, information or algorithms set forth herein are present in non-transient storage media.

[0224] In particular implementations, a computer-implemented method set forth herein (e.g., (discussed in FIG. 11)) can occur in real time while multiple images of an object are being obtained. Such real time analysis is particularly useful for nucleic acid sequencing applications wherein an array of nucleic acids is subjected to repeated cycles of fluidic and detection steps. Analysis of the sequencing data can often be computationally intensive such that it can be beneficial to perform the methods set forth herein in real time or in the background while other data acquisition or analysis algorithms are in process. Example real time analysis methods that can be used with the present methods are those used for the MiSeq and HiSeq sequencing devices commercially available from Illumina, Inc. (San Diego, Calif.) and/or described in US Pat. App. Pub. No. 2012/0020537 A1, which is incorporated herein by reference.

[0225] In this application, the terms “cluster”, “well”, “sample”, “analyte,” and “fluorescent sample” are interchangeable because a well contains a corresponding cluster/sample/analyte/fluorescent sample. As defined herein, “sample” and its derivatives, is used in its broadest sense and includes any specimen, culture and the like that is suspected of including a target. In some implementations, the sample comprises DNA, RNA, PNA, LNA, chimeric or hybrid forms of nucleic acids. The sample can include any biological, clinical, surgical, agricultural, atmospheric, or aquatic-based specimen containing one or more nucleic acids. The term also includes any isolated nucleic acid sample such a genomic DNA, fresh-frozen or formalin-fixed paraffin-embedded nucleic acid specimen. It is also envisioned that the sample can be from a single individual, a collection of nucleic acid samples from genetically related members, nucleic acid samples from genetically unrelated members, nucleic acid samples (matched) from a single individual such as a tumor sample and normal tissue sample, or sample from a single source that contains two distinct forms of genetic material such as maternal and fetal DNA obtained from a maternal subject, or the presence of contaminating bacterial DNA in a sample that contains plant or animal DNA. In some implementations, the source of nucleic acid material can include nucleic acids obtained from a newborn, for example as typically used for newborn screening.

[0226] The nucleic acid sample can include high molecular weight material such as genomic DNA (gDNA). The sample can include low molecular weight material such as nucleic acid molecules obtained from FFPE or archived DNA samples. In another implementation, low molecular weight material includes enzymatically or mechanically fragmented DNA. The sample can include cell-free circulating DNA. In some implementations, the sample can

include nucleic acid molecules obtained from biopsies, tumors, scrapings, swabs, blood, mucus, urine, plasma, semen, hair, laser capture micro-dissections, surgical resections, and other clinical or laboratory obtained samples. In some implementations, the sample can be an epidemiological, agricultural, forensic, or pathogenic sample. In some implementations, the sample can include nucleic acid molecules obtained from an animal such as a human or mammalian source. In another implementation, the sample can include nucleic acid molecules obtained from a non-mammalian source such as a plant, bacteria, virus, or fungus. In some implementations, the source of the nucleic acid molecules may be an archived or extinct sample or species.

[0227] Further, the methods and compositions disclosed herein may be useful to amplify a nucleic acid sample having low-quality nucleic acid molecules, such as degraded and/or fragmented genomic DNA from a forensic sample. In one implementation, forensic samples can include nucleic acids obtained from a crime scene, nucleic acids obtained from a missing persons DNA database, nucleic acids obtained from a laboratory associated with a forensic investigation or include forensic samples obtained by law enforcement agencies, one or more military services or any such personnel. The nucleic acid sample may be a purified sample or a crude DNA containing lysate, for example derived from a buccal swab, paper, fabric, or other substrate that may be impregnated with saliva, blood, or other bodily fluids. As such, in some implementations, the nucleic acid sample may comprise low amounts of, or fragmented portions of DNA, such as genomic DNA. In some implementations, target sequences can be present in one or more bodily fluids including but not limited to, blood, sputum, plasma, semen, urine, and serum. In some implementations, target sequences can be obtained from hair, skin, tissue samples, autopsy, or remains of a victim. In some implementations, nucleic acids including one or more target sequences can be obtained from a deceased animal or human. In some implementations, target sequences can include nucleic acids obtained from non-human DNA such as a microbial, plant or entomological DNA. In some implementations, target sequences or amplified target sequences are directed to purposes of human identification. In some implementations, the disclosure relates generally to methods for identifying characteristics of a forensic sample. In some implementations, the disclosure relates generally to human identification methods using one or more target specific primers disclosed herein or one or more target specific primers designed using the primer design criteria outlined herein. In one implementation, a forensic or human identification sample containing at least one target sequence can be amplified using any one or more of the target-specific primers disclosed herein or using the primer criteria outlined herein.

[0228] The technology disclosed generates variation correction coefficients to correct inter-cluster intensity profile variation in image data. The technology disclosed can be practiced as a system, method, or article of manufacture. One or more features of an implementation can be combined with the base implementation. Implementations that are not mutually exclusive are taught to be combinable. One or more features of an implementation can be combined with other implementations. This disclosure periodically reminds the user of these options. Omission from some implementations of recitations that repeat these options should not be taken as limiting the combinations taught in the preceding sections—these recitations are hereby incorporated forward by reference into each of the following implementations.

[0229] Other implementations of the method described in this section can include a non-transitory computer readable storage medium storing instructions executable by a processor to perform any of the methods described above. Yet another implementation of the method described in this section can include a system including memory and one or more processors operable to execute instructions, stored in the memory, to perform any of the methods described above.

[0230] In another implementation, the variation correction is performed on non-intensity data, such as on pH changes induced by the release of hydrogen ions during molecule extension. The pH changes are detected and converted to a voltage change that is proportional to the number of bases incorporated (e.g., in the case of Ion Torrent).

[0231] In yet another implementation, the non-intensity data is constructed from nanopore sensing that uses biosensors to measure the disruption in current as an analyte passes through a nanopore or near its aperture while determining the identity of the base. For example, the Oxford Nanopore Technologies (ONT) sequencing is based on the following concept: pass a single strand of DNA (or RNA) through a membrane via a nanopore and apply a voltage difference across the membrane. The nucleotides present in the pore will affect the pore's electrical resistance, so current measurements over time can indicate the sequence of DNA bases passing through the pore. This electrical current signal (the ‘squiggle’ due to its appearance when plotted) is the raw data gathered by an ONT sequencer. These measurements are stored as 16-bit integer data acquisition (DAC) values, taken at 4 kHz frequency (for example). With a DNA strand velocity of ~450 base pairs per second, this gives approximately nine raw observations per base on average. This signal is then processed to identify breaks in the open pore signal corresponding to individual reads. These stretches of raw signal are base called—the process of converting DAC values into a sequence of DNA bases. In some implementations, the non-intensity data comprises normalized or scaled DAC values.

[0232] One or more implementations of the technology disclosed, or elements thereof can be implemented in the form of a computer product including a non-transitory computer readable storage medium with computer usable program code for performing the method steps indicated. Furthermore, one or more implementations of the technology disclosed, or elements thereof can be implemented in the form of an apparatus including a memory and at least one

processor that is coupled to the memory and operative to perform exemplary method steps. Yet further, in another aspect, one or more implementations of the technology disclosed or elements thereof can be implemented in the form of means for carrying out one or more of the method steps described herein; the means can include (i) hardware module(s), (ii) software module(s) executing on one or more hardware processors, or (iii) a combination of hardware and software modules; any of (i)-(iii) implement the specific techniques set forth herein, and the software modules are stored in a computer readable storage medium (or multiple such media).

[0233] This application uses the terms “accumulated intensity correction parameter(s)” and “intermediate term(s)” interchangeably.

[0234] This application uses the terms “pure intensity/intensities” and “distribution intensity/intensities” interchangeably.

[0235] This application uses the terms “intensity profile(s)” and “constellation(s)” interchangeably.

[0236] This application uses the terms “variation correction coefficient(s)” and “intensity correction coefficient(s)” interchangeably.

[0237] This application uses the terms “amplification coefficient” and “scaling factor” interchangeably.

[0238] This application uses the terms “offset coefficient(s)” and “offset(s)” interchangeably. This application uses the terms “target cluster” and “particular cluster” interchangeably.

[0239] This application uses the terms “next,” “subsequent,” and “successive” interchangeably. This application uses the terms “nucleotide(s)” and “base(s)” interchangeably.

[0240] This application uses the terms “accumulated intensity correction parameter determiner” and “accumulator” interchangeably.

[0241] This application uses the terms “accumulated intensity correction parameter determiner” and “accumulator” interchangeably.

Clauses

[0242] 1. A computer-implemented method of base calling a target cluster, the method including: [0243] for the target cluster, [0244] reading current channel-specific intensities registered for a current sequencing cycle of a sequencing run from a base-specific intensity distribution to which the target cluster is base called at the current sequencing cycle, [0245] reading current channel-specific distribution intensities from a centroid of the base-specific intensity distribution, [0246] determining a set of current intensity correction parameters for the current sequencing cycle based on the current channel-specific intensities and the current channel-specific distribution intensities, [0247] determining a set of current accumulated intensity correction parameters for the current sequencing cycle by accumulating the set of current intensity correction parameters and a set of preceding accumulated intensity correction parameters for a preceding sequencing cycle of the sequencing run, [0248] determining a current amplification coefficient and current channel-specific offset coefficients for the current sequencing cycle based on the set of current accumulated intensity correction parameters, and [0249] using the current amplification coefficient and the current channel-specific offset coefficients to correct next channel-specific intensities registered for a next sequencing cycle of the sequencing run and generate corrected next channel-specific intensities for the next sequencing cycle; and [0250] base calling the target cluster at the next sequencing cycle based on the corrected next channel-specific intensities.

[0251] 2. The computer-implemented method of clause 1, wherein the set of current intensity correction parameters includes the current channel-specific distribution intensities, current channel-specific intensity errors, current distribution centroid-to-origin distance, and current distribution intensity-to-intensity error similarity measure.

[0252] 3. The computer-implemented method of clause 2, wherein the current channel-specific intensity errors are channel-wise differences between the current channel-specific intensities and the current channel-specific distribution intensities.

[0253] 4. The computer-implemented method of clause 2, wherein the current distribution centroid-to-origin distance is Euclidean distance between the centroid and an origin of a multi-dimensional space that contains the base-specific intensity distribution.

[0254] 5. The computer-implemented method of clause 4, wherein the multi-dimensional space is at least one of a cartesian space, a polar space, a cylindrical space, and a spherical space.

[0255] 6. The computer-implemented method of clause 2, wherein the current distribution intensity-to-intensity error similarity measure is a summation of channel-wise dot products between the current channel-specific distribution intensities and the current channel-specific intensity errors.

[0256] 7. The computer-implemented method of clause 1, wherein the set of current accumulated intensity correction parameters are intensity correction parameter-wise sums of current intensity correction parameters in the set of current intensity correction parameters and preceding accumulated intensity correction parameters in the set of preceding accumulated intensity correction parameters.

[0257] 8. The computer-implemented method of clause 7, wherein the set of current accumulated intensity correction parameters are intensity correction parameter-wise averages of the current intensity correction parameters and the preceding accumulated intensity correction parameters.

[0258] 9. The computer-implemented method of clause 1, wherein the set of preceding accumulated intensity

correction parameters and the set of current accumulated intensity correction parameters are stored in a quantized fixed bit width format.

[0259] 10. The computer-implemented method of clause 1, wherein the current channel-specific offset coefficients are configured to be same.

[0260] 11. The computer-implemented method of clause 10, wherein current accumulated intensity correction parameters in the set of current accumulated intensity correction parameters include a first common current accumulated intensity correction parameter for the current channel-specific distribution intensities, and a second common current accumulated intensity correction parameter for the current channel-specific intensity errors.

[0261] 12. The computer-implemented method of clause 1, wherein the current channel-specific offset coefficients are channel-wise subtracted from the next channel-specific intensities to generate next channel-specific shifted intensities, and the next channel-specific shifted intensities are divided by the current amplification coefficient to generate the corrected next channel-specific intensities.

[0262] 13. The computer-implemented method of clause 1, further including using a weighting function to combine an initial amplification coefficient with the current amplification coefficient, and initial channel-specific offset coefficients with the current channel-specific offset coefficients to generate a weighted current amplification coefficient and weighted current channel-specific offset coefficients for the current sequencing cycle.

[0263] 14. The computer-implemented method of clause 13, wherein the weighting function applies a minimum weight ($w_{sub.min}$) to initial amplification coefficient and the initial channel-specific offset coefficients, and a maximum weight ($w_{sub.max}$) to the current amplification coefficient and the current channel-specific offset coefficients, wherein $w_{sub.min} = (1 - w_{sub.max})$.

[0264] 15. The computer-implemented method of clause 14, wherein the maximum weight ($w_{sub.max}$) is defined as $(c - p)/c$, where c is an index for the current sequencing cycle and p is a number between 2 to 7.

[0265] 16. The computer-implemented method of clause 15, further including using the weighted current amplification coefficient and the weighted current channel-specific offset coefficients to correct the next channel-specific intensities and generate the corrected next channel-specific intensities.

[0266] 17. The computer-implemented method of clause 1, further including: [0267] using a maximum likelihood solution to generate, for the current sequencing cycle, respective current maximum likelihood weights for the current amplification coefficient and the current channel-specific offset coefficients; [0268] respectively applying the current maximum likelihood weights to the current amplification coefficient and the current channel-specific offset coefficients to generate a maximum likelihood weighted current amplification coefficient and maximum likelihood weighted current channel-specific offset coefficients for the current sequencing cycle; and [0269] using the maximum likelihood weighted current amplification coefficient and the maximum likelihood weighted current channel-specific offset coefficients to correct the next channel-specific intensities and generate the corrected next channel-specific intensities.

[0270] 18. The computer-implemented method of clause 1, further including: [0271] applying a decay factor to the current intensity correction parameters to generate decayed current intensity correction parameters for the current sequencing cycle; and [0272] determining the current accumulated intensity correction parameters by intensity correction parameter-wise accumulating the decayed current intensity correction parameters and the preceding accumulated intensity correction parameters.

[0273] 19. The computer-implemented method of clause 18, wherein the decay factor is kept fixed for a certain number of sequencing cycles of the sequencing run, and exponentially decayed thereafter based on a decay logic.

[0274] 20. The computer-implemented method of clause 19, wherein the decay logic is $1 - 1/\tau$, where τ is a predefined number.

[0275] 21. The computer-implemented method of clause 1, further including iterating the reading, the reading, the determining, the determining, the determining, the using, and the base calling for the target cluster at successive sequencing cycles of the sequencing run.

[0276] 22. The computer-implemented method of clause 1, further including executing the reading, the reading, the determining, the determining, the determining, the using, and the base calling in parallel for multiple clusters.

[0277] 23. The computer-implemented method of clause 1, wherein closed-form expressions for the set of current intensity correction parameters, the set of current accumulated intensity correction parameters, the current amplification coefficient, and the current channel-specific offset coefficients are determined using a least-squares solution.

[0278] 24. The computer-implemented method of clause 1, wherein the current channel-specific intensities respectively correspond to intensity channels.

[0279] 25. The computer-implemented method of clause 1, wherein the current channel-specific offset coefficients are the channel-wise differences between the current channel-specific intensities and the current channel-specific distribution intensities.

[0280] 26. A non-transitory computer readable storage medium impressed with computer program instructions to base call a target cluster, the instructions, when executed on a processor, implement a method comprising: [0281] for the

target cluster, [0282] reading current channel-specific intensities registered for a current sequencing cycle of a sequencing run from a base-specific intensity distribution to which the target cluster is base called at the current sequencing cycle, [0283] reading current channel-specific distribution intensities from a centroid of the base-specific intensity distribution, [0284] determining a set of current intensity correction parameters for the current sequencing cycle based on the current channel-specific intensities and the current channel-specific distribution intensities, [0285] determining a set of current accumulated intensity correction parameters for the current sequencing cycle by accumulating the set of current intensity correction parameters and a set of preceding accumulated intensity correction parameters for a preceding sequencing cycle of the sequencing run, [0286] determining a current amplification coefficient and current channel-specific offset coefficients for the current sequencing cycle based on the set of current accumulated intensity correction parameters, and [0287] using the current amplification coefficient and the current channel-specific offset coefficients to correct next channel-specific intensities registered for a next sequencing cycle of the sequencing run and generate corrected next channel-specific intensities for the next sequencing cycle; and [0288] base calling the target cluster at the next sequencing cycle based on the corrected next channel-specific intensities.

[0289] 27. The non-transitory computer readable storage medium of clause 26, implementing each clause that ultimately depends on clause 1.

[0290] 28. A system including one or more processors coupled to memory, the memory loaded with computer instructions to base call a target cluster, the instructions, when executed on the processors, implement actions comprising: [0291] for the target cluster, [0292] reading current channel-specific intensities registered for a current sequencing cycle of a sequencing run from a base-specific intensity distribution to which the target cluster is base called at the current sequencing cycle, [0293] reading current channel-specific distribution intensities from a centroid of the base-specific intensity distribution, [0294] determining a set of current intensity correction parameters for the current sequencing cycle based on the current channel-specific intensities and the current channel-specific distribution intensities, [0295] determining a set of current accumulated intensity correction parameters for the current sequencing cycle by accumulating the set of current intensity correction parameters and a set of preceding accumulated intensity correction parameters for a preceding sequencing cycle of the sequencing run, [0296] determining a current amplification coefficient and current channel-specific offset coefficients for the current sequencing cycle based on the set of current accumulated intensity correction parameters, and [0297] using the current amplification coefficient and the current channel-specific offset coefficients to correct next channel-specific intensities registered for a next sequencing cycle of the sequencing run and generate corrected next channel-specific intensities for the next sequencing cycle; and [0298] base calling the target cluster at the next sequencing cycle based on the corrected next channel-specific intensities.

[0299] 29. The system of clause 28, implementing each clause that ultimately depends on clause 1.

[0300] 30. A computer-implemented method of base calling a target cluster, the method including: [0301] for the target cluster, [0302] accessing current intensity data and historic intensity data, [0303] wherein the current intensity data is for a current sequencing cycle of a sequencing run, and [0304] wherein the historic intensity data is for one or more preceding sequencing cycles of the sequencing run, [0305] determining a scale correction coefficient and channel-specific shift correction coefficients based on the current intensity data and the historic intensity data, [0306] using the scale correction coefficient and the channel-specific shift correction coefficients to correct next intensity data and generate corrected next intensity data, [0307] wherein the next intensity data is for a next sequencing cycle of the sequencing run; and [0308] base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

[0309] 31. The computer-implemented method of clause 30, implementing each clause that ultimately depends on clause 1.

[0310] 32. A non-transitory computer readable storage medium impressed with computer program instructions to base call a target cluster, the instructions, when executed on a processor, implement a method comprising: [0311] for the target cluster, [0312] accessing current intensity data and historic intensity data, [0313] wherein the current intensity data is for a current sequencing cycle of a sequencing run, and [0314] wherein the historic intensity data is for one or more preceding sequencing cycles of the sequencing run, [0315] determining a scale correction coefficient and channel-specific shift correction coefficients based on the current intensity data and the historic intensity data, [0316] using the scale correction coefficient and the channel-specific shift correction coefficients to correct next intensity data and generate corrected next intensity data, [0317] wherein the next intensity data is for a next sequencing cycle of the sequencing run; and [0318] base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

[0319] 33. The non-transitory computer readable storage medium of clause 32, implementing each clause that ultimately depends on clause 1.

[0320] 34. A system including one or more processors coupled to memory, the memory loaded with computer instructions to base call a target cluster, the instructions, when executed on the processors, implement actions comprising: [0321] for the target cluster, [0322] accessing current intensity data and historic intensity data, [0323]

wherein the current intensity data is for a current sequencing cycle of a sequencing run, and [0324] wherein the historic intensity data is for one or more preceding sequencing cycles of the sequencing run, [0325] determining a scale correction coefficient and channel-specific shift correction coefficients based on the current intensity data and the historic intensity data, [0326] using the scale correction coefficient and the channel-specific shift correction coefficients to correct next intensity data and generate corrected next intensity data, [0327] wherein the next intensity data is for a next sequencing cycle of the sequencing run; and [0328] base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

[0329] 35. The system of clause 34, implementing each clause that ultimately depends on clause 1.

[0330] 36. A computer-implemented method of base calling a target cluster, the method including: [0331] for the target cluster, [0332] accessing current intensity data and historic intensity data, [0333] wherein the current intensity data is for a current sequencing cycle of a sequencing run, and [0334] wherein the historic intensity data is for one or more preceding sequencing cycles of the sequencing run, [0335] using the current intensity data and the historic intensity data to correct next intensity data and generate corrected next intensity data, [0336] wherein the next intensity data is for a next sequencing cycle of the sequencing run; and [0337] base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

[0338] 37. The computer-implemented method of clause 36, implementing each clause that ultimately depends on clause 1.

[0339] 38. A non-transitory computer readable storage medium impressed with computer program instructions to base call a target cluster, the instructions, when executed on a processor, implement a method comprising: [0340] for the target cluster, [0341] accessing current intensity data and historic intensity data, [0342] wherein the current intensity data is for a current sequencing cycle of a sequencing run, and [0343] wherein the historic intensity data is for one or more preceding sequencing cycles of the sequencing run, [0344] using the current intensity data and the historic intensity data to correct next intensity data and generate corrected next intensity data, [0345] wherein the next intensity data is for a next sequencing cycle of the sequencing run; and [0346] base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

[0347] 39. The non-transitory computer readable storage medium of clause 38, implementing each clause that ultimately depends on clause 1.

[0348] 40. A system including one or more processors coupled to memory, the memory loaded with computer instructions to base call a target cluster, the instructions, when executed on the processors, implement actions comprising: [0349] for the target cluster, [0350] accessing current intensity data and historic intensity data, [0351] wherein the current intensity data is for a current sequencing cycle of a sequencing run, and [0352] wherein the historic intensity data is for one or more preceding sequencing cycles of the sequencing run, [0353] using the current intensity data and the historic intensity data to correct next intensity data and generate corrected next intensity data, [0354] wherein the next intensity data is for a next sequencing cycle of the sequencing run; and [0355] base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

[0356] 41. The system of clause 40, implementing each clause that ultimately depends on clause 1.

[0357] While the present invention is disclosed by reference to the preferred embodiments and examples detailed above, it is to be understood that these examples are intended in an illustrative rather than in a limiting sense. It is contemplated that modifications and combinations will readily occur to those skilled in the art, which modifications and combinations will be within the spirit of the invention and the scope of the following claims.

Claims

1-20. (canceled)

21. A system comprising at least one processor coupled to memory, the memory loaded with computer instructions that, when executed by the at least one processor, implement actions comprising: accessing, for a target cluster, current intensity data and preceding intensity data registered from the target cluster and other clusters for a current sequencing cycle and one or more preceding sequencing cycles of a sequencing run; correcting next intensity data registered for a next sequencing cycle based on the current intensity data and the preceding intensity data; and determining a base call for the target cluster at the next sequencing cycle based on the corrected next intensity data.

22. The system of claim 21, further comprising computer instructions that, when executed by the at least one processor, implement actions comprising: accessing the current intensity data and the preceding intensity data by accessing, for the target cluster, current channel-specific intensity data and preceding channel-specific intensity data; correcting the next intensity data by correcting next channel-specific intensity data registered for the next sequencing cycle based on the current channel-specific intensity data and the preceding channel-specific intensity data; and determining the base call for the target cluster at the next sequencing cycle based on the corrected next channel-specific intensity data.

23. The system of claim 21, further comprising computer instructions that, when executed by the at least one processor, implement actions comprising: accessing the current intensity data by accessing, for the target cluster,

distribution intensities from a base-specific intensity distribution; and correcting the next intensity data registered for the next sequencing cycle based further on the distribution intensities.

24. The system of claim 23, wherein the base-specific intensity distribution is determined from one or more of the current intensity data registered for the current sequencing cycle or the preceding intensity data registered for the one or more preceding sequencing cycles.

25. The system of claim 21, further comprising computer instructions that, when executed by the at least one processor, implement actions comprising correcting the next intensity data registered for the next sequencing cycle without reference to a subsequent sequencing cycle occurring after the next sequencing cycle.

26. The system of claim 21, wherein intensity values for the current intensity data or the preceding intensity data are extracted from sequencing images generated by a sequencer at the current sequencing cycle or at the one or more preceding sequencing cycles.

27. The system of claim 21, further comprising instructions that, when executed by the at least one processor, implement actions comprising correcting the next intensity data registered for the next sequencing cycle based on the current intensity data and the preceding intensity data by: determining a set of current accumulated intensity correction parameters for the current sequencing cycle based on the current intensity data; determining, for the target cluster and based on the set of current accumulated intensity correction parameters, a current amplification coefficient; correcting the next intensity data for the next sequencing cycle based on the current amplification coefficient.

28. A non-transitory computer readable storage medium storing computer instructions that, when executed by at least one processor, cause a system to: access, for a target cluster, current intensity data and preceding intensity data registered from the target cluster and other clusters for a current sequencing cycle and one or more preceding sequencing cycles of a sequencing run; correct next intensity data registered for a next sequencing cycle based on the current intensity data and the preceding intensity data; and determine a base call for the target cluster at the next sequencing cycle based on the corrected next intensity data.

29. The non-transitory computer readable storage medium of claim 28, further storing computer instructions that, when executed by the at least one processor, cause the system to: access the current intensity data and the preceding intensity data by accessing, for the target cluster, current channel-specific intensity data and preceding channel-specific intensity data; correct the next intensity data by correcting next channel-specific intensity data registered for the next sequencing cycle based on the current channel-specific intensity data and the preceding channel-specific intensity data; and determine the base call for the target cluster at the next sequencing cycle based on the corrected next channel-specific intensity data.

30. The non-transitory computer readable storage medium of claim 28, further storing computer instructions that, when executed by the at least one processor, cause the system to: access the current intensity data by accessing, for the target cluster, distribution intensities from a base-specific intensity distribution; and correct the next intensity data registered for the next sequencing cycle based further on the distribution intensities.

31. The non-transitory computer readable storage medium of claim 30, wherein the base-specific intensity distribution is determined from one or more of the current intensity data registered for the current sequencing cycle or the preceding intensity data registered for the one or more preceding sequencing cycles.

32. The non-transitory computer readable storage medium of claim 28, further storing computer instructions that, when executed by the at least one processor, cause the system to correct the next intensity data registered for the next sequencing cycle without reference to a subsequent sequencing cycle occurring after the next sequencing cycle.

33. The non-transitory computer readable storage medium of claim 28, wherein intensity values for the current intensity data or the preceding intensity data are extracted from sequencing images generated by a sequencer at the current sequencing cycle or at the one or more preceding sequencing cycles.

34. The non-transitory computer readable storage medium of claim 28, further storing computer instructions that, when executed by the at least one processor, cause the system to: determine a set of current accumulated intensity correction parameters for the current sequencing cycle based on the current intensity data; determine, for the target cluster and based on the set of current accumulated intensity correction parameters, a current amplification coefficient; correct the next intensity data for the next sequencing cycle based on the current amplification coefficient.

35. A computer-implemented method comprising: accessing, for a target cluster, current intensity data and preceding intensity data registered from the target cluster and other clusters for a current sequencing cycle and one or more preceding sequencing cycles of a sequencing run; correcting next intensity data registered for a next sequencing cycle based on the current intensity data and the preceding intensity data; and determining a base call for the target cluster at the next sequencing cycle based on the corrected next intensity data.

36. The computer-implemented method of claim 35, wherein: accessing the current intensity data and the preceding intensity data comprises accessing, for the target cluster, current channel-specific intensity data and preceding channel-specific intensity data; correcting the next intensity data comprises correcting next channel-specific intensity data registered for the next sequencing cycle based on the current channel-specific intensity data and the preceding channel-specific intensity data; and determining the base call comprises determining the base call for the target cluster

at the next sequencing cycle based on the corrected next channel-specific intensity data.

37. The computer-implemented method of claim 35, wherein: accessing the current intensity data by accessing, for the target cluster, distribution intensities from a base-specific intensity distribution; and correcting the next intensity data registered for the next sequencing cycle based further on the distribution intensities.

38. The computer-implemented method of claim 37, wherein the base-specific intensity distribution is determined from one or more of the current intensity data registered for the current sequencing cycle or the preceding intensity data registered for the one or more preceding sequencing cycles.

39. The computer-implemented method of claim 35, wherein correcting the next intensity data comprises correcting the next intensity data registered for the next sequencing cycle without reference to a subsequent sequencing cycle occurring after the next sequencing cycle.

40. The computer-implemented method of claim 35, wherein intensity values for the current intensity data or the preceding intensity data are extracted from sequencing images generated by a sequencer at the current sequencing cycle or at the one or more preceding sequencing cycles.
