

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250256060

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

FULLER; JEFFREY STEVEN et al.

GUIDE EXTENSION CATHETER

Abstract

Medical devices and methods for making and using medical devices are disclosed. An example medical device may include a guide extension catheter. The guide extension catheter may include a proximal member having a proximal end, a distal end, and a proximal diameter. The guide extension catheter may additionally include a collar member attached to an extension portion of the proximal member, where the extension portion may be located at the distal end of the proximal member. The extension portion may allow a delivery device to be inserted through the guide extension catheter to extend along a surface of the extension portion and align with a lumen of a distal sheath of the guide extension catheter.

Inventors: FULLER; JEFFREY STEVEN (BROOKLYN PARK, MN), YOON; SOO-YOUNG (MAPLE GROVE, MN), STEFANICH; LOUIS WARNER (MINNEAPOLIS, MN), USCHOLD; JOHN E. (NORTH BRANCH, MN)

Applicant: BOSTON SCIENTIFIC SCIMED, INC. (MAPLE GROVE, MN)

Family ID: 60191571

Assignee: BOSTON SCIENTIFIC SCIMED, INC. (MAPLE GROVE, MN)

Appl. No.: 19/197019

Filed: May 02, 2025

Related U.S. Application Data

parent US continuation 18380705 20231017 parent-grant-document US 12290642 child US 19197019

parent US continuation 16723519 20191220 parent-grant-document US 11826517 child US 18380705

parent US continuation 15787678 20171018 parent-grant-document US 10537709 child US 16723519

us-provisional-application US 62409603 20161018

Publication Classification

Int. Cl.: **A61M25/00** (20060101); **A61M25/01** (20060101); **A61M25/06** (20060101);
A61M25/10 (20130101)

U.S. Cl.:

CPC **A61M25/0023** (20130101); **A61M25/0014** (20130101); **A61M25/0045** (20130101);
A61M25/0662 (20130101); **A61M25/10** (20130101); A61M25/0004 (20130101);
A61M25/0046 (20130101); A61M25/0108 (20130101); A61M25/0175 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/380,705, filed Oct. 17, 2023, which is a continuation of U.S. patent application Ser. No. 16/723,519, filed Dec. 20, 2019, now U.S. Pat. No. 11,826,517, issued Nov. 28, 2023, which is a continuation of U.S. patent application Ser. No. 15/787,678, filed Oct. 18, 2017, now U.S. Pat. No. 10,537,709, issued Jan. 21, 2020, which claims the benefit of priority under 35 U.S.C. § 119 to U.S. Provisional Application Ser. No. 62/409,603, filed Oct. 18, 2016, the entirety of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure pertains to medical devices, and methods for manufacturing medical devices. More particularly, the present disclosure pertains to elongated intracorporeal medical devices including a guide extension catheter.

BACKGROUND

[0003] A wide variety of intracorporeal medical devices have been developed for medical use, for example, intravascular use. Some of these devices include guidewires, catheters, and the like. These devices are manufactured by any one of a variety of different manufacturing methods and may be used according to any one of a variety of methods. Of the known medical devices and methods, each has certain advantages and disadvantages. There is an ongoing need to provide alternative medical devices as well as alternative methods for manufacturing and using medical devices.

BRIEF SUMMARY

[0004] This disclosure provides design, material, manufacturing method, and use alternatives for medical devices. In a first aspect, a guide extension catheter may comprise a proximal member having a proximal outer diameter, a proximal portion, and an extension portion extending from a distal end of the proximal portion to a distal end of the proximal member. The guide extension catheter may further comprise a collar member attached to the extension portion and a distal sheath member attached to the collar member, the distal sheath member having a lumen and a distal outer diameter larger than the proximal outer diameter.

[0005] In addition or alternative, and in a second aspect, the extension portion of the proximal member may have a width and a length configured to allow a delivery device to extend along a surface of the extension portion and align with the lumen of the distal sheath member.

[0006] In addition or alternatively, and in a third aspect, the extension portion of the proximal member may include a transition region transitioning from the proximal portion to a flattened region of the extension portion. The flattened region may have an extension width greater than the proximal outer diameter and less than the distal outer diameter.

[0007] In addition or alternatively, and in a fourth aspect, the transition region may extend to a

distal end of the extension portion.

[0008] In addition or alternatively, and in a fifth aspect, the flattened region may extend proximally 1.5 millimeters from the distal end of the proximal member.

[0009] In addition or alternatively, and in a sixth aspect, the extension portion may extend less than 10 millimeters proximal of a distal end of the proximal member.

[0010] In addition or alternatively, and in a seventh aspect, the extension portion may extend less than 6.35 millimeters proximal of a distal end of the proximal member.

[0011] In addition or alternatively, and in an eighth aspect, the extension portion may extend less than 3 millimeters from a distal end of the proximal member.

[0012] In addition or alternatively, and in a ninth aspect, the extension portion may extend proximally 1.5 millimeters from the distal end of the proximal member.

[0013] In addition or alternatively, and in a tenth aspect, the collar member may comprise a base portion and one or more ribs connected to the base portion and extending distally away from the base portion. Further, the extension portion of the proximal member may be attached to the base portion of the collar member.

[0014] In addition or alternatively, and in an eleventh aspect, the extension portion may extend less than 8.5 millimeters from a proximal end of the collar member.

[0015] In addition or alternatively, and in a twelfth aspect, the extension portion may have an arcuate cross-section that mates with the arcuate cross-section of the base portion.

[0016] In addition or alternatively, and in a thirteenth aspect, a medical treatment delivery system may comprise a delivery device having a nose extending proximally from a distal end of the delivery device and a medical device location extending proximal from a proximal end of the nose, wherein the nose has a distal end with a length extending between the proximal end and the distal end of the nose. The medical treatment delivery system may further comprise a guide extension catheter comprising a proximal member having a proximal outer diameter, a proximal portion, and an extension portion extending from a distal end of the proximal portion to a distal end of the proximal member. The guide extension catheter may further comprise a distal sheath member axially fixed with respect to the proximal member and extending distally of the proximal member, the distal sheath member having a lumen and a distal outer diameter larger than the proximal outer diameter. The nose of the delivery device may be configured to track a guide wire extending through the lumen of the distal sheath member and align the medical device location of the delivery device with the lumen of the distal sheath member prior to the medical device location of the delivery device advancing to the extension portion of the proximal member.

[0017] In addition or alternatively, and in a fourteenth aspect, the nose of the delivery device may have a length that is greater than the length of the extension portion.

[0018] In addition or alternatively, and in a fifteenth aspect, the length of the extension portion may be less than 3.5 millimeters.

[0019] In addition or alternatively, and in a sixteenth aspect, the delivery device may be a stent delivery catheter and the medical device location may be configured to receive a stent.

[0020] In addition or alternatively, and in a seventeenth aspect, the delivery device may be a balloon catheter and the medical device location may include a balloon.

[0021] In addition or alternatively, and in an eighteenth aspect, the guide extension catheter may comprise a collar attached to the proximal member and the distal sheath member.

[0022] In addition or alternatively, and in a nineteenth aspect, a method for manufacturing a guide extension catheter may comprise flattening an extension portion of a proximal member having a proximal end and a distal end. The method may further include grasping the flattened extension portion and bringing the extension portion into contact with a collar. Yet further, the method may include affixing the extension portion to the collar and attaching a distal sheath member to the collar such that the distal sheath member extends distally of the proximal member and the collar. The extension portion of the proximal member may extend proximally from the distal end of the

proximal member and has a length configured to facilitate aligning a delivery catheter with a lumen of the distal sheath member.

[0023] In addition or alternatively, and in a twentieth aspect, the method may include flattening a portion of the proximal member that extends between the distal end of the proximal member and a location less than ten millimeters proximal of the distal end of the proximal member.

[0024] In addition or alternatively, and in a twenty-first aspect, the method may including stamping the extension portion of the proximal member.

[0025] The above summary of some embodiments is not intended to describe each disclosed embodiment or every implementation of the present invention. The Figures, and Detailed Description, which follow, more particularly exemplify these embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] The invention may be more completely understood in consideration of the following detailed description of various embodiments of the invention in connection with the accompanying drawings, in which:

[0027] FIG. 1 is a plan view illustrating an example guide catheter advanced through the aorta to the ostium of a coronary artery;

[0028] FIG. 2 is a plan view illustrating an example guide extension catheter used in conjunction with a guide catheter;

[0029] FIG. 3 is a cross-sectional side view of an example guide extension catheter;

[0030] FIG. 4 is side view of an example guide extension catheter collar;

[0031] FIG. 5 is a cross-sectional side view of an example guide extension catheter and an example guide catheter;

[0032] FIG. 6A is a schematic cross-sectional view of the guide extension catheter and guide catheter of FIG. 5 taken along line 6A-6A;

[0033] FIG. 6B is a schematic cross-sectional view of the guide extension catheter and guide catheter of FIG. 5 taken along line 6B-6B;

[0034] FIG. 7 is a schematic partial cross-sectional view of an example guide extension catheter, an example guide catheter, and an example delivery device;

[0035] FIG. 8A is a schematic cross-sectional view of the guide extension catheter, guide catheter, and delivery device of FIG. 7 taken along line 8A-8A;

[0036] FIG. 8B is a schematic cross-sectional view of the guide extension catheter, guide catheter, and delivery device of FIG. 7 taken along line 8B-8B;

[0037] FIG. 9A is a top view of an example guide extension catheter;

[0038] FIG. 9B is a side view of the guide extension catheter of FIG. 9A;

[0039] FIG. 10A is a top view of an example guide extension catheter;

[0040] FIG. 10B is a side view of the guide extension catheter of FIG. 10A;

[0041] FIG. 11 is a top view of a proximal member and a collar of an example guide extension catheter;

[0042] FIG. 12A is a schematic cross-sectional view of the proximal member and collar of FIG. 11 taken along line 12A-12A;

[0043] FIG. 12B is a schematic cross-sectional view of the proximal member and collar of FIG. 11 taken along line 12B-12B; and

[0044] FIG. 13 is a schematic flow diagram illustrating a method of manufacturing a guide extension catheter.

[0045] While the disclosure is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It

should be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure.

DETAILED DESCRIPTION

[0046] For the following defined terms, these definitions shall be applied, unless a different definition is given in the claims or elsewhere in this specification.

[0047] All numeric values are herein assumed to be modified by the term “about”, whether or not explicitly indicated. The term “about” generally refers to a range of numbers that one of skill in the art would consider equivalent to the recited value (e.g., having the same function or result). In many instances, the terms “about” may include numbers that are rounded to the nearest significant figure.

[0048] The recitation of numerical ranges by endpoints includes all numbers within that range (e.g. 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

[0049] As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise.

[0050] It is noted that references in the specification to “an embodiment”, “some embodiments”, “other embodiments”, etc., indicate that the embodiment described may include one or more particular features, structures, and/or characteristics. However, such recitations do not necessarily mean that all embodiments include the particular features, structures, and/or characteristics. Additionally, when particular features, structures, and/or characteristics are described in connection with one embodiment, it should be understood that such features, structures, and/or characteristics may also be used in connection with other embodiments whether or not explicitly described unless clearly stated to the contrary.

[0051] The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the invention.

[0052] Minimally-invasive cardiac interventions such as percutaneous transluminal coronary angioplasty are widely utilized throughout the world. These procedures may include the use of a guide catheter. For example, a guide catheter **10** may be advanced from a location exterior of vasculature of a patient through a blood vessel such as the aorta **A** to a position adjacent to the ostium **O** of a (e.g., left and/or right) coronary artery **CA** as illustrated in FIG. **1**, such that the guide catheter **10** may extend from exterior vasculature of a patient to adjacent the patient's coronary artery when inserted. When so positioned, a delivery device (e.g., a catheter, a balloon catheter, a stent delivery system, etc.) may be advanced through guide catheter **10** and into the coronary artery **CA** to a target location, such that the delivery device may extend from proximal a proximal end of the guide catheter exterior the patient's vasculature to the target location and the delivery device and/or device thereon may be used to perform an appropriate cardiac intervention at the target location.

[0053] In order for the delivery device to efficiently reach the intended target location, maintaining the position of guide catheter **10** at the ostium **O** of the coronary artery **CA** may be desirable. For example, given that the heart may be beating during the intervention (and/or other factors), the guide catheter **10** may lose its positioning or otherwise be shifted so that it no longer is positioned to efficiently guide the treatment catheter to the coronary arteries. This may include a distal end **12** of guide catheter **10** being shifted away from the ostium **O** of the coronary artery **CA**. Because of the shift away from the ostium **O**, access to the coronary arteries **CA** may require repositioning of guide catheter **10** in order to bring the distal end **12** back into engagement with the ostium **O** of the coronary artery **CA**.

[0054] Disclosed herein are medical devices and methods for making and using medical devices that may improve access to the coronary arteries CA. For example, FIG. 2 illustrates a guide extension catheter **14** extending through guide catheter **10** and beyond distal end **12** of guide catheter **10** into the coronary artery CA. The guide extension catheter **14** (e.g., a proximal portion **18** and a hub **24** of the guide extension catheter **14**) may extend from proximal a proximal end of the guide catheter **10** and exterior a patient's vasculature to the coronary artery CA or other target location. Because, for example, the guide extension catheter **14** may extend beyond distal end **12** of guide catheter **10**, guide extension catheter **14** may extend beyond the ostium O of the coronary artery CA and into a portion of the coronary artery CA. By extending beyond the ostium O, the guide extension catheter **14** may stabilize the positioning of the guide catheter **10** and allow for improved access to the coronary artery CA for a number of cardiac interventions.

[0055] FIG. 3 is a cross-sectional side view of guide extension catheter **14**. Here it can be seen that guide extension catheter **14** may include a shaft or proximal member **16**. Proximal member **16** may include the proximal portion **18** and an extension portion **20** (e.g., a distal portion extending distally from the proximal portion **18**). The hub **24** may be attached to proximal portion **18**.

[0056] The proximal portion **18** may have a lumen **22** defined therein. This, however, is not required and proximal portion **18** may be solid (e.g., a wire, a solid rod, etc.)

[0057] In some embodiments, lumen **22** may extend along the entire length of proximal portion **18**. In other embodiments, lumen **22** may extend along only a portion of the length of proximal portion **18**. In still other embodiments, proximal member **16** may be a hypotube and have a lumen extending along the entire length of proximal member **16**.

[0058] In addition, proximal portion **18** may include both proximal and distal openings (e.g., positioned at the proximal and distal end of proximal portion **18**) such that lumen **22** is "open" on both ends. Alternatively, one or both of the ends of proximal portion **18** may be closed or otherwise sealed. For example, the distal end of proximal portion **18** may be closed. In some of these and in other embodiments, proximal portion **18** may have an opening or port (not shown) formed in the wall of proximal portion **18** and spaced from the proximal and/or distal end of proximal portion **18**. The port may or may not be in fluid communication with lumen **22**.

[0059] A distal sheath **26** may be attached to proximal member **16**. In some cases, the distal sheath **26** may be axially fixed to proximal member **16**, but this is not required. Distal sheath **26** may have a lumen **28** formed therein. The distal sheath **26** may have a single lumen or two or more lumens. In general, lumen **28** (and/or the inner diameter of distal sheath **26**) may be larger than lumen **22** (and/or the inner diameter of proximal portion **18**) and may be larger than the outer diameter of proximal member **16**.

[0060] A distance of an inner diameter of the lumen **28** may be any distance configured to facilitate the distal sheath **26** to traversing a patient's vasculature. In some examples, the distance of the inner diameter of the lumen **28** may be between 0.025 inches (0.635 millimeters) and about 0.090 inches (2.29 millimeters), between about 0.035 inches (0.889 millimeters) and about 0.080 inches (2.03 millimeters), between about 0.040 inches (1.02 millimeters) and about 0.075 inches (1.91 millimeters), and/or may be between other distances. Illustratively, the distance of the inner diameter of the lumen **28** may be about 0.046 inches (1.17 mm), about 0.047 inches (1.19 millimeters), about 0.051 inches (1.30 millimeters), about 0.052 inches (1.32 millimeters), about 0.056 inches (1.42 millimeters), about 0.057 inches (1.45 millimeters), about 0.062 inches (1.57 millimeters), about 0.063 inches (1.60 millimeters), about 0.071 inches (1.80 millimeter), about 0.072 inches (1.83 millimeters), and/or one or more other distances.

[0061] As used herein, the term diameter may refer to a line from one side of something to a second side of the something, wherein the line passes through a center point of the something.

Illustratively, the something may be a cross-sectional shape of a square, a circle, a triangle, an oval, a rectangle, or other shape. With respect to proximal member **16** and/or distal sheath **26** that may not have a circular cross-sectional shape, the diameter of such shapes may be the largest cross-

sectional dimension of proximal member **16** or distal sheath **26** taken from a cross-section transverse to a longitudinal dimension (e.g., to a direction of a longitudinal axis. Accordingly, lumen **28** may be sufficiently large so as to allow a therapeutic catheter (e.g., a delivery device, a balloon catheter, a stent delivery system, etc.) to pass therethrough. For example, when guide extension catheter **14** is positioned within guide catheter **10**, the therapeutic catheter may extend within guide catheter **10** alongside proximal member **16** and through lumen **28** of distal sheath **26**.

[0062] Distal sheath **26** may include a body portion **30**. In at least some embodiments, body portion **30** may include one or more polymers including any of those disclosed herein. This may include the use of polymers with a differing durometer along the length of body portion **30**. For example, a more proximal section of body portion **30** may include a polymer with a higher durometer and a more distal section of body portion **30** may include a polymer with a lower durometer. Portions of all of the length of body portion **30** may be loaded with or otherwise include a radiopaque material.

[0063] Body portion **30** may also include a reinforcement member **32**, but this is not required. The form of reinforcement member **32** may vary. For example, reinforcement member **32** may include a braid, coil, mesh, rings, segments, fibers or interstitial arrays of fibers, or the like.

[0064] An inner layer or liner **34** may be disposed along an inner surface of body portion **30**, but this is not required. The form of liner **34** may vary. For example, liner **34** may be a lubricious liner or otherwise include a lubricious material such as polytetrafluoroethylene.

[0065] A tip member **36** may be attached to body portion **30**, for example at a distal end of body portion **30**, but this is not required. In some embodiments, tip member **36** may be a single layer of material. Alternatively, tip member **36** may include an outer layer **38** and an inner layer **40**. Outer layer **38** and inner layer **40** may be formed from the same material. In some of these embodiments, outer layer **38** and inner layer **40** may include the same polymeric material and each may be loaded with the same or different radiopaque materials. For example, inner layer **40** may include a polyether block amide loaded with approximately 75-95% (e.g., about 90%) by weight tungsten and outer layer **38** may include a polyether block amide loaded with approximately 30-50% (e.g., 40%) by weight bismuth subcarbonate. These are just examples. In other embodiments, outer layer **38** and inner layer **40** may be made from different materials.

[0066] Distal sheath **26** may be attached to extension portion **20** of proximal member **16**. The arrangement and/or configuration of the attachment between extension portion **20** and distal sheath **26** may vary. For example, distal sheath **26** may have an opening or lumen formed in a tube wall thereof and extension portion **20** may be disposed within the opening. This may include stamping, flattening, necking, skiving, and/or pinching down extension portion **20** and inserting the necked down portion into the opening. In some embodiments, inserting extension portion **20** into the opening may secure proximal member **16** to distal sheath **26** via a mechanical bond. In some of these and in other embodiments, additional and/or alternative bonding may be utilized including those bonding mechanisms commonly used for medical devices. Some example bonding mechanisms include adhesive bonding, welding, thermal bonding, brazing, metallurgical stamping, pressing etc. Other attachment mechanisms are also contemplated for attaching the proximal member **16** to distal sheath **26** including direct bonding (e.g., adhesive bonding, thermal bonding, welding, brazing, injection molding, 3D printing and bonding, overmolding, casting, sintering polymer/metal composites, etc.) and bonding that is facilitated by a third component such as a metal or polymer collar member **42** that may be bonded between the extension portion **20** and distal sheath **26**.

[0067] Guide extension catheter **14** may also include a number of coatings that may, for example, reduce friction. For example, proximal member **16** may have an inner and/or outer coating that includes a hydrophilic polymer that may reduce friction during tracking. An example coating may include BAYER CL-100, BIOSLIDE, NG-HPC, SLIP COAT, MDX, ZGLIDE, or the like. These are just examples. Other materials are contemplated including those disclosed herein.

[0068] As discussed, some embodiments of guide extension catheter **14** may include collar member

42 connected between proximal member **16** and distal sheath **26**, as illustrated in FIGS. 3 and 4. In some instances, collar member **42** may be sized to work with the guide catheter **10** or guide extension catheter **14** that have sizes between about 4 French to about 9 French. However, in other embodiments, collar member **42** may be sized differently to cooperate with guide catheters **10** and/or guide extension catheters **14** that are smaller than 4 French and larger than 9 French.

[0069] FIG. 4 is an illustrative perspective views of an example collar member **42** that may be used to facilitate bonding between an extension portion and a distal sheath of a guide extension catheter, such as extension portion **20** and distal sheath **26** of guide extension catheter **14** described with respect to FIGS. 3 and 4. Additionally, other configurations of collar members are contemplated.

[0070] FIG. 4 depicts collar member **42** including proximal end **221** and distal end **223**. Collar member **42** comprises base portion **234** and a distally extending portion **235**.

[0071] In some instances, distally extending portion **235** may comprise ribs **232** which extend distally away from base portion **234**. As shown in FIG. 4, ribs **232** may extend from base portion **234** all the way to distal end **223** of collar member **42**. However, in other instances this does not need to be the case. One or more of ribs **232** may not extend all the way to distal end **223** of collar member **42**. Additionally, ribs **232** are just one example of distally extending portion **235**.

[0072] Collar member **42** may additionally include slot **225**. To attach collar member **42** to a member, such as proximal member **16** of FIG. 3, a distal end of the member may be inserted into slot **225** and may be bonded to collar member **42** by bonding mechanisms commonly used for medical devices. Some example bonding mechanisms include adhesive bonding, welding, thermal bonding, brazing, etc.

[0073] Distally extending portion **235** may be attached to a sheath, such as the distal sheath **26** of FIG. 3, in a similar manner to how proximal member **16** may be attached to collar member **42**. In other instances, distally extending portion **235** may be inserted into one end of the sheath, and both the distally extending portion **235** and the sheath may be heated. This heat may cause the material of the sheath to melt and flow into and/or around distally extending portion **235**. When the heat is removed, the melted material may solidify, thereby bonding the sheath to distally extending portion **235**.

[0074] In instances where distally extending portion **235** comprises ribs **232**, ribs **232** may extend distally away from base portion **234**, which is defined as the angle between top **233** of base portion **234** and rib **232**. In one example, the angle at which ribs **232** extend distally away from the top **233** of the base portion **234** may be 45 degrees. However, illustratively, the angle may have any value between about 15 degrees and about 75 degrees. In some more specific instances, the angle at which ribs **232** extend away from the top **233** of the base portion **234** may have any value between about 30 degrees and about 60 degrees.

[0075] Although FIG. 4 depicts collar member **42** having five ribs **232**, in other instances, collar member **42** may have a different number of ribs **232**. For example, collar member **42** may have between about one rib **232** and about ten ribs **232**. In more specific instances, collar member **42** may have between about four ribs **232** and about seven ribs **232**. In other instances, the collar member **42** may have no ribs.

[0076] In at least some instances, ribs **232** may extend distally away from base portion **234** in a twisting manner. As one example, ribs **232** may have a helical twist and extend distally away from base portion **234** in a helical manner. Although shown as extending in a generally clock-wise helical manner when viewing collar member **42** from proximal end **221**, in other instances, the helical twist may be counter-clockwise.

[0077] In at least some instances, each of ribs **232** may extend helically around a longitudinal axis of the collar member **42** at least 90 degrees. In other instances, each of ribs **232** may extend helically around the longitudinal axis about 180 degrees, about 360 degrees, or anywhere between 90 degrees and 360 degrees. In still other instances, each of ribs **232** may helically twist around the longitudinal axis multiple times as ribs **232** extend distally from base portion **234**.

[0078] In still other instances, ribs **232** may not extend distally away from base portion **234** in a twisting manner at all. For instance, ribs **232** may extend distally away from base portion **234** in a straight manner.

[0079] In some additional instances, ribs **232** may have a wavy or sinusoidal shape. For instance, ribs **232** may extend generally distally away from base portion **234** in a straight fashion, except ribs **232** may curve back and forth transversely to a longitudinal axis. Or, in other instances, ribs **232** may undulate up and down in a manner parallel to a longitudinal axis of the collar member **42**.

[0080] In at least some embodiments, ribs **232** may have one or more connecting members disposed generally transverse to the direction of ribs **232**, connecting ribs **232** together. The connecting members may simply be thin portions of collar member **42** left during the processing to form ribs **232**. These connecting members may be relatively thin compared to the width of ribs **232**.

[0081] FIG. **4** additionally depicts ribs **232** extending away from the top **233** of base portion **234** a distance. In different instances, the distance may be any value between about 0.05 inches (1.27 mm) and about 0.5 inches (12.7 mm). Additionally, although all of ribs **232** are depicted as extending distally away from the top **233** of base portion **234** the same distance, in other instances, each of ribs **232** may extend distally away from the top **233** of the base portion **234** different distances, or groups of one or more ribs **232** may extend distally away from the top **233** of the base portion **234** different distances. In at least some instances where ribs **232** extend helically around longitudinal axis **237**, ribs **232** may extend away from base portion **234** a distance such that at least two separate ribs cross a longitudinal axis of the collar member **42**. In others of these embodiments, at least three separate ribs may cross the longitudinal axis of the collar member **42**. In still other embodiments, based on the distance ribs **232** extend distally away from base portion **234**, every one of ribs **232** may cross the longitudinal axis of the collar member **42**.

[0082] In some embodiments, collar member **42** may include channels **236** defined by distally extending portion **235**. For instance, collar member **42** may be made from a hollow tube. The hollow tube may be machined, laser cut, or otherwise processed to remove material to define channels **236** extending along the longitudinal axis for at least a portion of collar member **42**. Channels **236** may be angled with respect to the longitudinal axis at an angle similar to how ribs **232** may be angled with respect to base portion **234**. For instance, channels **236** may be angled with respect to a longitudinal axis of the collar member **42** between about 15 degrees and about 75 degrees, between about 30 degrees and about 60 degrees, or about 45 degrees. Channels **236** may have one closed end, for instance where each channel **236** meets the top **233** of the base portion **234**, and one open end, for instance at distal end **223**. Additionally, different instances of collar member **42** may include varying numbers of channels **236**, for instance any number between about two and ten channels, or between about four channels and seven channels.

[0083] As illustrated in FIG. **4**, in some instances, collar member **42** may additionally include angled extension **239**. Angled extension **239** may extend distally away from base portion **234** in a similar manner to ribs **232**. However, angled extension **239** may extend in a direction generally transverse to ribs **232**. For example, as ribs **232** are depicted extending helically in a clock-wise manner, angled extension **239** may extend in a generally counter-clockwise manner. As depicted in FIG. **4**, angled extension **239** may form an angle with a top **233** of the base portion **234** (e.g., a distal-most edge of base portion **234**). In the example of FIG. **4**, the angled extension **239** extends at an angle of 45 degrees. However, in different embodiments, the angle of angled extension **239** extending away from the top **233** of the base portion **234** may have any value between about 15 degrees and 75 degrees. In more specific instances, the angle may have any value between about 30 degrees and 60 degrees. In some instances, the angle may have the same value as the angle at which ribs **232** extend away from the top **233** of the base portion **234**, but this does not need to be true in all embodiments. Further, in at least some instances, one or more of ribs **232** may extend from angled extension **239**, as depicted in FIG. **4**, but this does not need to be the case in all embodiments.

[0084] FIG. 5 illustrates guide extension catheter **14** disposed within guide catheter **10** (e.g., disposed within a lumen **44** defined within guide catheter **10**). As shown, distal sheath **26** may be arranged to extend distally out from distal end **12** of guide catheter **10**. When so arranged, distal sheath **26** may engage the ostium **O** and/or extend within a portion of the coronary artery **CA** to help maintain the position of guide catheter **10** and improve access to the coronary artery **CA**. Proximal member **16** may be designed to be sufficiently small (while still being sufficiently sized and configured for pushability) so as to take up relatively little space within the interior or lumen **44** of guide catheter **10** and extend exterior a patient's vasculature when the distal sheath is at a target location. Accordingly, the use of guide extension catheter **14** allows for a therapeutic catheter or medical device to be advanced through guide catheter **10** in order to reach the desired target location for the intervention. In some embodiments, proximal member **16** may contact the inner wall surface of guide catheter **10**, which may provide even more space.

[0085] FIGS. **6A** and **6B** are cross-sectional views taken along line **6A-6A** and line **6B-6B** in FIG. **5**, respectively. Generally, FIGS. **6A** and **6B** depict example relative spacing within guide catheter **10** with respect to proximal member **16** of the guide extension catheter **14** at lines **6A-6A** and **6B-6B** of FIG. **5**.

[0086] As can be seen in FIG. **6A**, line **X** may represent an inner diameter of the guide catheter **10**, line **X'** may represent a distance from an outer surface of the proximal portion **18** of the proximal member **16** to an inner surface of the guide catheter **10**, and line **X''** may represent an outer diameter of the proximal portion **18** of the proximal member **16**. The line **X'** may represent a maximum possible diameter for a delivery device and/or a combined delivery device and medical device that may travel through the guide catheter while the guide extension catheter **14** is inserted therein.

[0087] Line **X** may have any length dimension. For example, line **X** may have a length dimension within a range of about 0.040 inches to about 0.100 inches, about 0.050 inches to about 0.090 inches, about 0.060 inches to about 0.080 inches, and/or within one or more other ranges. In one illustrative example, line **X** may have a length dimension of about 0.070 inches.

[0088] Line **X'** may have any length dimension. For example, line **X'** may have a length dimension within a range of about 0.0200 inches to about 0.0830 inches, about 0.0305 inches to about 0.0725 inches, about 0.0410 inches to about 0.0620 inches, and/or within one or more other ranges. In one illustrative example, line **X'** may have a length dimension of about 0.0515 inches.

[0089] Line **X''** may have any length dimension. For example, line **X''** may have a length dimension within a range of about 0.0170 inches to about 0.0200 inches, about 0.0175 inches to about 0.0195 inches, about 0.0180 inches to about 0.0190 inches, and/or within one or more other ranges. In one illustrative example, line **X''** may have a length dimension of about 0.0185 inches.

[0090] In some cases the extension portion **20** of the proximal member **16** may twist or shift within the guide catheter **10** as it extends proximally from a distal end thereof as seen in FIGS. **5** and **6B**. When the extension portion **20** twists or shifts within the guide catheter **10**, a maximum space for a delivery device or other device to travel through the guide catheter **10** may be reduced. As can be seen in FIG. **6B**, line **X'''** represents a width of extension portion **20** of the proximal member **16** and line **X''''** represents a distance from an outer surface of the extension portion **20** to an inner surface of the guide catheter **10**. The line **X''''** may represent a maximum possible diameter for a delivery device and/or combination of a delivery device and a medical device if the medical device need to cross from side **20b** to side **20a** of the extension portion **20** of the proximal member **16**. The distance represented by line **X''''** as shown in FIG. **6B** is less than the distance represented by line **X'** in FIG. **6A**, but this is not required.

[0091] Line **X'''** may have any length dimension. Although line **X'''** is depicted in FIG. **6B** as having a length greater than line **X''**, line **X'''** may alternatively have a length equal to or less than a length **X''**. Example length dimensions of line **X'''** may be within a range of about 0.010 inches to about 0.040 inches, about 0.019 inches to about 0.035 inches, about 0.024 inches to about 0.030

inches, and/or within one or more other ranges. In one illustrative example, line X''' may have a length dimension of about 0.027 inches.

[0092] Line X'''' may have any length dimension. For example, line X'''' may have a length dimension within a range of about 0.010 inches to about 0.090 inches, about 0.020 inches to about 0.071 inches, about 0.030 inches to about 0.056 inches, and/or within one or more other ranges. In one illustrative example, line X'''' may have a length dimension of about 0.043 inches.

[0093] In practice, a guide wire **50** may be thread through vasculature of a patient to a target location and the guide catheter **10** may be threaded through the patient's vasculature over the guide wire **50**. Then, the guide extension catheter **14** may be threaded through the guide catheter **10** to the target location or at least a location distal of a distal end of the guide extension catheter **14**. Once the guide extension catheter **14** is positioned, a delivery device and/or a medical device may be inserted and/or delivered through the guide catheter **10** and the guide extension catheter **14**.

[0094] FIG. 7 depicts the guide extension catheter **14** and a delivery device **52** (e.g., a stent delivery catheter, balloon catheter, and/or other delivery device) with a medical device **58** (e.g., a stent or other medical device) thereon inserted into the guide catheter **10**. The delivery device **52** may be threaded over the guide wire **50**, but this is not required.

[0095] As shown in FIG. 7, the guide extension catheter **14** may have the extension portion **20** having a flattened region **23** with a length D'' and the delivery device **52** have a nose **54** that has a length N. The delivery device **52** may include a medical device location **56** carrying thereon and/or enclosing therein the medical device **58**, such as a stent as shown in FIG. 7. Delivery devices other than delivery device **52** are contemplated.

[0096] In operation, the proximal member **16** of the guide extension catheter **14** be flexible and thus, may be at different radial locations within the guide catheter **10** at different axial locations along a length of the proximal member **16**, as shown in FIG. 7. As a result, the delivery device **52**, for example, may move along various sides of the proximal member **16** as it is inserted through the guide catheter **10** and as the delivery device **52** approaches a proximal end of the distal sheath **26**, the delivery device may be on an opposite side of the proximal member **16** than a side on which the delivery device **52** needs to be to be inserted into the lumen **28** of the distal sheath **26**. Such a situation is depicted in FIG. 7, where the delivery device **52** may be approaching the extension portion **20** of the proximal member **16** on side **20b** of the extension portion when it will need to be on side **20a** of the extension portion **20** to be inserted into and/or through lumen **28** of the distal sheath **26**.

[0097] FIG. 8A depicts a cross-sectional view of the guide extension catheter **14** and delivery device **52** inserted into the guide catheter **10** taken along line 8A-8A in FIG. 7. In FIG. 8A, the medical device **58** has been omitted for clarity purposes. In FIG. 8A, the delivery device **52** may have a cross-sectional diameter T at the medical device location **56** or other location along the delivery device **52**, which may be less than a distance of line X' extending from an outer surface of proximal portion **18** of the proximal member **16** to an inner surface of the guide catheter **10**.

[0098] FIG. 8B depicts a cross-sectional view of the guide extension catheter **14** and delivery device inserted into the guide catheter **10** taken along line 8B-8B in FIG. 7. In FIG. 8B, the guide wire **50** and the medical device **58** have been omitted for clarity purposes. As shown in FIGS. 7 and 8B, the delivery device **52** may be positioned on a side (e.g., an outer facing side) of the proximal member **16** that is opposite a side (e.g., an inner facing side) on which the delivery device **52** may need to be to be inserted into and/or through the lumen **28** of the distal sheath **26**. For example, as the delivery device **52** of FIGS. 7 and 8B is advanced distally, the delivery device **52** may advance along side **20b** of the extension portion **20** of the proximal member **16**. However, to advance into and/or through the lumen **28** of the distal sheath **26**, the delivery device **52** may need to be on side **20a** of the extension portion **20** of the proximal member **16**.

[0099] When the delivery device **52** or other device is advanced within the guide catheter **10** along an outer facing side of the proximal member **16** of the guide extension catheter **14**, the delivery

device **52** may need to switch to an inner facing side of the proximal member **16**. The do this, the delivery device **52** must switch sides of the proximal member at a location where a diameter T is less than a distance from an outer surface of the proximal member **16** to an inner surface of the guide catheter **10** (e.g., a distance of line X' or line X'''). As the diameter T may be greater than a distance of line X'''' between an outer surface of the extension portion **20** and an inner surface of the guide catheter **10**, the delivery device **52** may need to switch sides or begin switching sides at a longitudinal position within the guide catheter **10** that is proximal of the extension portion **20** or is proximal at least a widest portion of the extension portion **20** or a portion of the extension portion **20** that is wider than a diameter of the proximal portion **18** of the proximal member **16**.

[0100] If the delivery device **52** or other device having a diameter T is allowed to advance to a position on outer facing side **20b** of the extension portion **20** of the proximal member **16**, the delivery device **52** may get tangled between the proximal member **16** and the guide catheter. As a result, a physician may be required to apply undue push, pull, and/or rotational forces to the delivery device **52** to align or re-align the delivery device **52** (e.g., the medical device location **56** of the delivery device **52**) with the lumen **28** of the distal sheath **26**. These undue forces may cause physical damage to a patient that may not otherwise be applied to a patient if the delivery device **52** had not been tangled or caught on the proximal member **16**. Additionally or alternatively, the undue forces may cause movement of the distal end of the guide catheter **10** and/or guide extension catheter **14** away from a desired position.

[0101] FIGS. **9-12B** illustrate example guide extension catheters **14** or portions thereof that may be configured to allow a delivery device to extend along a surface of the extension portion **20** of the proximal member **16** and align with and/or extend through the lumen **28** of the distal sheath **26**. Although example guide extension catheters **14** may be depicted, other guide extension catheters **14** consistent with this specification may be utilized to allow a delivery device to extend along a surface of the extension portion **20** and align with or extend through the lumen **28** of the distal sheath **26**.

[0102] As shown in FIGS. **9A** and **9B**, the extension portion may include a transition region **21** and the flattened region **23**. In some cases, the flattened region **23** may have a width equal to a length of line X'''. Additionally or alternatively, a width of the flattened region **23** may be greater than a diameter of the proximal portion **18** (e.g., length of line X'') and/or less than an outer diameter of the distal sheath **26**. Further, a height, h, of the flattened region **23** (e.g., where height may be perpendicular to the width) may be within a range of about 0.001 to 0.020 inches or about 0.005 to 0.015 inches. In one illustrative example, the height, h, of the flattened region **23** may be about 0.010 inches.

[0103] The transition region **21** may be at a location of the proximal member **16** that transitions from the proximal portion **18** of the proximal member **16** to a flattened or widened region of the proximal member **16**. In one example, the transition region **21** may taper from the flattened or widened region in a proximal direction to the proximal portion **18** of the proximal member **16**.

[0104] The flattened or widened region (e.g., flattened region **23**) of the proximal member **16** may be configured for attachment to the collar member **42** and/or the distal sheath **26**. Additionally or alternatively, the flattened or widened region of the extension portion **20** may facilitate grasping of the proximal member **16** during manufacturing of the guide extension catheter **14** (e.g., for grasping while connecting the proximal member **16** to the collar member **42** or the distal sheath **26** and/or for grasping at other times).

[0105] In some instances, the transition region **21** may extend a length D' and flattened region **23** may extend a length D''. In FIGS. **9A** and **9B**, a sum of lengths D' and D'' may be a length D of the extension portion **20**. Although length D' may be depicted as having a length less than length D'', length D' may be greater than length D''.

[0106] FIGS. **10A** and **10B** depict an additional instance of guide extension catheter **14** having the proximal member **16** with the extension portion **20**. In FIGS. **10A** and **10B**, the extension portion

20 may include the transition region **21** that may extend an entire length of the extension portion **20**. For example, the extension portion **20** may transition from the proximal portion **18** of the proximal member **16** to a distal end of the proximal member **16** and extend a total length D'. The total length D'' in FIGS. **10A** and **10B** may have similar dimensions to those of length D'' discussed below.

[0107] As shown in FIGS. **9A-10B** and as discussed above, the extension portion **20** of the proximal member **16** may have a length D (or a length D' in the instance shown in FIGS. **10A** and **10B**). The length D may be a length extending from a distal end of the proximal member **16** to a location an axial location proximal of the distal end of the proximal member **16**. The length D of the extension portion **20** may include the transition region **21**, the flattened region **23**, or both of the transition region **21** and the flattened region **23**.

[0108] In some cases, as shown in FIGS. **9A** and **9B** for example, the length D may include a length D''' of the extension portion **20**, where the length D''' may represent a length of the extension portion **20** that overlaps with and/or may be attached to the collar member **42** and/or the distal sheath **26**. A length D'''' (length D minus length D''') of the extension portion **20** may be a length of the extension portion **20** extending proximally from a proximal end of the collar member **42**. In one example, length D''' may be in the range of about zero (0) millimeters to three (3) millimeters, about one (1) millimeters to two (2) millimeters, or other distance. In one instance, about 1.5 millimeters of the extension portion **20** may overlap with the collar member **42** and about 1.5 millimeters of the extension portion **20** may extend proximally of a proximal end of the collar member **42** to facilitate grasping the proximal member **16** and attaching the proximal member **16** to the collar member **42**.

[0109] Length D'' may have a length that is less than about nineteen (19) millimeters, less than about ten (10) millimeters, between about one (1) millimeter and ten (10) millimeters, between about zero (0) millimeters and six (6) millimeters, between about zero (0) millimeters and three (3) millimeters, between about zero (0) millimeters and one-point-five (1.5) millimeters, and/or a length D within one or more other ranges. In one instance, the length D'' may be about 6.35 millimeters. In another instance, the length D may be about three (3) millimeters. In yet a further instance, the length D'' may be one-point-five (1.5) millimeters. It has been found that a smaller length of the extension portion **20** may be desirable to prevent catching the delivery device **52** or other device on the extension portion **20**, but that it may be desirable for the extension portion to have some length to facilitate grasping the proximal member during manufacturing and connecting the proximal member **16** to the collar member **42** and/or the distal sheath **26**.

[0110] In some instances, length D'' may be configured to be a fractional distance of a distance of a length of the distal sheath **26**, where the distance of the length of the distal sheath **26** is a distance from a proximal end of the distal sheath **26** to a distal end of the distal sheath **26**. Where the length of the distal sheath **26** has a distance between about fifteen (15) centimeters and forty (40) centimeters or other length, for example, the length D'' of the extension portion **20** may be between about 0.375% and about 6.7% of the length of the distal sheath.

[0111] In some instances, distance of length D'' may be configured to be proportional to a distance of an inner diameter of the distal sheath **26**, where the distance of the inner diameter of the distal sheath **26** is a minimum diameter of lumen **28** of the distal sheath **26**. Where the distance of the inner diameter of the distal sheath **26** is between about 0.046 inches (e.g. 1.17 millimeters) and 0.072 inches (e.g., 1.83 millimeters), for example, the length D'' of the extension portion **20** may be between about 80% and about 855% of the length of the distal sheath. In some instances, length D'' may be configured to be shorter than a length N of the nose **54** of the delivery device **52** or other device, as shown in FIG. **7**, but this is not required. Delivery devices **52** may include nose **54** that is configured to track along a guide wire (e.g., guide wire **50**) or that may otherwise facilitate aligning the delivery device **52** (e.g., the medical device location **56** of the delivery device **52**) with a lumen (e.g., lumen **28** of the distal sheath **26**). In addition to length N, nose **54** may taper distally. The

distal taper of the nose **54** may facilitate the aligning the delivery device **52** with a lumen.

[0112] In instances when the length **N** of the nose **54** is longer than the length **D** of the extension portion **20**, the taper on the nose **54** of the delivery device **52** may facilitate aligning the delivery device with the lumen prior to the delivery device **52** catching on the proximal member **16**. In one example, when a length **N** of the nose **54** of the delivery device **52** is longer than a length of the extension portion **20** extending proximal from a proximal end of the collar member **42** (e.g., $D - D'''$), the taper of the nose **54** aligns the delivery device (e.g., the medical device location **56** on the delivery device **52**) with the lumen **28** of the distal sheath **26** regardless of which side of the proximal member the delivery device **52** may be located as it approaches the extension portion **20** and/or prior to the reaching the extension portion **20**.

[0113] FIGS. **11-12B** depict a further illustrative instance of the extension portion **20** of the proximal member **16**. The extension portion **20** may have an arcuate and/or concave configuration and may taper from a distal end of the proximal member **16** to the proximal portion **18**. An inner surface **20a** and/or an outer surface **20b** of the extension portion **20** may have a width and/or concavity configured to abut and/or engage an inner surface **42a** and/or an outer surface **42b** of the collar member **42**. In one example, as shown in FIGS. **11-12B**, the arcuate outer surface **20b** of the extension portion **20** may be sized to receive and/or attached to an arcuate inner surface **42a** of the collar member **42**.

[0114] Further, during manufacturing of the guide extension catheter **14**, a hole **25** in the extension portion **20** of the proximal member **16** and a hole **49** in the collar member **42** may be utilized to properly align the proximal member **16** with the collar member **42**. FIG. **12A**, which is a cross-sectional view taken along line **12A-12A** of FIG. **11**, depicts the axial alignment of the extension portion **20** and the collar member **42** facilitated by hole **25** and hole **49**. FIG. **12B**, which is a cross-sectional view taken along line **12B-12B** of FIG. **11**, depicts the longitudinal alignment of the extension portion **20** and the collar member **42** facilitated by hole **25** and hole **49**. As may be seen in FIG. **12B**, the extension portion **20** may overlap a distance D''' extending from a distal end of the proximal member **16** to a location proximal the distal end of the proximal member **16**, as discussed above. Further, although holes **25** and **49** are described as being used to align the proximal member **16** and the collar member **42**, this is not required and the holes **25**, **49** may be eliminated, the holes **25**, **49** may be used for other purposes, and/or other alignment features may be utilized.

[0115] The guide extension catheter **14** of the present disclosure may be manufactured in one or more manners. In one example method (**200**) of manufacturing the guide extension catheter **14** as shown in FIG. **13**, a portion of a distal portion (e.g., the extension portion **20**) of the proximal member **16** (e.g., a rod, wire, tube, or other elongated member) may be flattened (**202**). Flattening the distal portion of the proximal member **16** may include flattening a portion of the proximal member **16** that extends between the distal end of the proximal member **16** and a location less than nineteen (19) millimeters, less ten (10) millimeters, less than seven (7) millimeters, less than three millimeters, or at a different distance from the distal end of the proximal member **16**. Flattening may include stamping, necking, skiving, and/or pinching down extension portion **20**. As discussed above, the flattened portion of the extension portion **20** may be utilized for grasping and thus, the flattened or partially flattened extension portion **20** may be grasped (**204**) and the grasped extension portion **20** may be brought into contact with the collar member **42** (and/or the distal sheath **26**) (**206**).

[0116] The distal sheath **26** may be attached to the collar member **42** through any connection technique (**208**). The distal sheath **26** may be attached to the collar member **42** at any time during the method of manufacturing (**200**). In one example, the distal sheath **26** may be attached to the collar member **42** before the extension portion **20** is affixed to the collar member **42** (as discussed below, as shown in FIG. **13**). Alternatively, the distal sheath may be attached to the collar member **42** after the extension portion **20** is affixed to the collar member **42**. Illustrative connection techniques may include direct bonding, such as but not limited to reflow bonding, adhesive

bonding, thermal bonding, welding, 3D printing and bonding, overmolding, casting, sintering polymer/metal composites, and/or one or more other connection techniques.

[0117] When the extension portion **20** is in contact with the collar member **42**, the extension portion **20** may be affixed to the collar member **42** (and/or the distal sheath **26**) (**210**). In some instances, affixing the extension portion **20** to the collar and/or the distal sheath **26** may include one or more example bonding mechanisms including friction fit bonding, adhesive bonding, welding, thermal bonding, brazing, metallurgical stamping, pressing etc.

[0118] The materials that can be used for the various components of the guide extension catheters disclosed herein may vary. For simplicity purposes, the following discussion makes reference to proximal member **16**, distal sheath **26**, and collar member **42**. However, this is not intended to limit the devices and methods described herein, as the discussion may be applied to other similar tubular members and collars and/or components of tubular members or collars or other devices disclosed herein.

[0119] In general, collar member **42** may be made from any suitable method, and may vary depending on the specific material or materials chosen for collar member **42**. For example, if collar member **42** is made from a metal or metal alloy, collar member **42** may be formed by photo-etching, laser-cutting, micro-machining, 3D printing, sintering, rolled from flat sheet-stock. However, if collar member **42** is made from a polymer material, collar member **42** may be made through extrusion.

[0120] Proximal member **16**, distal sheath **26**, collar member **42** and/or other components of guide extension catheter **14** may be made from a metal, metal alloy, polymer (some examples of which are disclosed below), a metal-polymer composite, ceramics, combinations thereof, and the like, or other suitable material. Some examples of suitable polymers may include polytetrafluoroethylene (PTFE), ethylene tetrafluoroethylene (ETFE), fluorinated ethylene propylene (FEP), polyoxymethylene (POM, for example, DELRIN® available from DuPont), polyether block ester, polyurethane (for example, Polyurethane 85A), polypropylene (PP), polyvinylchloride (PVC), polyether-ester (for example, ARNITEL® available from DSM Engineering Plastics), ether or ester based copolymers (for example, butylene/poly (alkylene ether) phthalate and/or other polyester elastomers such as HYTREL® available from DuPont), polyamide (for example, DURETHAN® available from Bayer or CRISTAMID® available from Elf Atochem), elastomeric polyamides, block polyamide/ethers, polyether block amide (PEBA, for example available under the trade name PEBAX®), ethylene vinyl acetate copolymers (EVA), silicones, polyethylene (PE), Marlex high-density polyethylene, Marlex low-density polyethylene, linear low density polyethylene (for example REXELL®), polyester, polybutylene terephthalate (PBT), polyethylene terephthalate (PET), polytrimethylene terephthalate, polyethylene naphthalate (PEN), polyetheretherketone (PEEK), polyimide (PI), polyetherimide (PEI), polyphenylene sulfide (PPS), polyphenylene oxide (PPO), poly paraphenylene terephthalamide (for example, KEVLAR®), polysulfone, nylon, nylon-12 (such as GRILAMID® available from EMS American Grilon), perfluoro(propyl vinyl ether) (PFA), ethylene vinyl alcohol, polyolefin, polystyrene, epoxy, polyvinylidene chloride (PVdC), poly(styrene-b-isobutylene-b-styrene) (for example, SIBS and/or SIBS 50A), polycarbonates, ionomers, biocompatible polymers, other suitable materials, or mixtures, combinations, copolymers thereof, polymer/metal composites, and the like.

[0121] Some examples of suitable metals and metal alloys include stainless steel, such as 304V, 304L, and 316LV stainless steel; mild steel; nickel-titanium alloy such as linear-elastic and/or super-elastic nitinol; other nickel alloys such as nickel-chromium-molybdenum alloys (e.g., UNS: N06625 such as INCONEL® 625, UNS: N06022 such as HASTELLOY® C-22®, UNS: N10276 such as HASTELLOY® C276®, other HASTELLOY® alloys, and the like), nickel-copper alloys (e.g., UNS: N04400 such as MONEL® 400, NICKELVAC® 400, NICORROS® 400, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-N® and the like), nickel-molybdenum alloys (e.g., UNS: N10665 such as HASTELLOY® ALLOY B2®), other

nickel-chromium alloys, other nickel-molybdenum alloys, other nickel-cobalt alloys, other nickel-iron alloys, other nickel-copper alloys, other nickel-tungsten or tungsten alloys, and the like; cobalt-chromium alloys; cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNOX®, and the like); platinum enriched stainless steel; titanium; combinations thereof; and the like; or any other suitable material.

[0122] As alluded to herein, within the family of commercially available nickel-titanium or nitinol alloys, is a category designated “linear elastic” or “non-super-elastic” which, although may be similar in chemistry to conventional shape memory and super elastic varieties, may exhibit distinct and useful mechanical properties. Linear elastic and/or non-super-elastic nitinol may be distinguished from super elastic nitinol in that the linear elastic and/or non-super-elastic nitinol does not display a substantial “superelastic plateau” or “flag region” in its stress/strain curve like super elastic nitinol does. Instead, in the linear elastic and/or non-super-elastic nitinol, as recoverable strain increases, the stress continues to increase in a substantially linear, or a somewhat, but not necessarily entirely linear relationship until plastic deformation begins or at least in a relationship that is more linear than the super elastic plateau and/or flag region that may be seen with super elastic nitinol. Thus, for the purposes of this disclosure linear elastic and/or non-super-elastic nitinol may also be termed “substantially” linear elastic and/or non-super-elastic nitinol.

[0123] In some cases, linear elastic and/or non-super-elastic nitinol may also be distinguishable from super elastic nitinol in that linear elastic and/or non-super-elastic nitinol may accept up to about 2-5% strain while remaining substantially elastic (e.g., before plastically deforming) whereas super elastic nitinol may accept up to about 8% strain before plastically deforming. Both of these materials can be distinguished from other linear elastic materials such as stainless steel (that can also be distinguished based on its composition), which may accept only about 0.2 to 0.44 percent strain before plastically deforming.

[0124] In some embodiments, the linear elastic and/or non-super-elastic nickel-titanium alloy is an alloy that does not show any martensite/austenite phase changes that are detectable by differential scanning calorimetry (DSC) and dynamic mechanical thermal analysis (DMTA) analysis over a large temperature range. For example, in some embodiments, there may be no martensite/austenite phase changes detectable by DSC and DMTA analysis in the range of about -60 degrees Celsius (° C.) to about 120° C. in the linear elastic and/or non-super-elastic nickel-titanium alloy. The mechanical bending properties of such material may therefore be generally inert to the effect of temperature over this very broad range of temperature. In some embodiments, the mechanical bending properties of the linear elastic and/or non-super-elastic nickel-titanium alloy at ambient or room temperature are substantially the same as the mechanical properties at body temperature, for example, in that they do not display a super-elastic plateau and/or flag region. In other words, across a broad temperature range, the linear elastic and/or non-super-elastic nickel-titanium alloy maintains its linear elastic and/or non-super-elastic characteristics and/or properties.

[0125] In some embodiments, the linear elastic and/or non-super-elastic nickel-titanium alloy may be in the range of about 50 to about 60 weight percent nickel, with the remainder being essentially titanium. In some embodiments, the composition is in the range of about 54 to about 57 weight percent nickel. One example of a suitable nickel-titanium alloy is FHP-NT alloy commercially available from Furukawa Techno Material Co. of Kanagawa, Japan. Some examples of nickel titanium alloys are disclosed in U.S. Pat. Nos. 5,238,004 and 6,508,803, which are incorporated herein by reference. Other suitable materials may include ULTANIUM™ (available from Neo-Metrics) and GUM METAL™ (available from Toyota). In some other embodiments, a superelastic alloy, for example a superelastic nitinol can be used to achieve desired properties.

[0126] In at least some embodiments, portions or all of proximal member **16**, distal sheath **26**, and/or collar member **42** may also be loaded with, made of, or otherwise include a radiopaque material. Radiopaque materials are understood to be materials capable of producing a relatively bright image on a fluoroscopy screen or another imaging technique during a medical procedure.

This relatively bright image aids the user of guide extension catheter **14** in determining its location. Some examples of radiopaque materials can include, but are not limited to, gold, platinum, palladium, tantalum, tungsten alloy, polymer material loaded with a radiopaque filler (e.g., barium sulfate, bismuth subcarbonate, etc.), and the like. Additionally, other radiopaque marker bands and/or coils may also be incorporated into the design of guide extension catheter **14** to achieve the same result.

[0127] In some embodiments, a degree of Magnetic Resonance Imaging (MRI) compatibility is imparted into guide extension catheter **14**. For example, proximal member **16**, distal sheath **26**, and collar member **42**, or portions thereof, may be made of a material that does not substantially distort the image and create substantial artifacts (i.e., gaps in the image). Certain ferromagnetic materials, for example, may not be suitable because they may create artifacts in an MRI image. Proximal member **16**, distal sheath **26**, and collar member **42**, or portions thereof, may also be made from a material that the MRI machine can image. Some materials that exhibit these characteristics include, for example, tungsten, cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNEX®, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-N® and the like), nitinol, and the like, and others.

[0128] In at least some embodiments, a sheath or covering (not shown) may be disposed over portions or all of proximal member **16** and distal sheath **26** that may define a generally smooth outer surface for guide extension catheter **14**. In other embodiments, however, such a sheath or covering may be absent from a portion of all of guide extension catheter **14**, such that proximal member **16** and distal sheath **26** may form the outer surface. The sheath may be made from a polymer or other suitable material. Some examples of suitable polymers may include polytetrafluoroethylene (PTFE), ethylene tetrafluoroethylene (ETFE), fluorinated ethylene propylene (FEP), polyoxymethylene (POM, for example, DELRIN® available from DuPont), polyether block ester, polyurethane (for example, Polyurethane 85A), polypropylene (PP), polyvinylchloride (PVC), polyether-ester (for example, ARNITEL® available from DSM Engineering Plastics), ether or ester based copolymers (for example, butylene/poly(alkylene ether) phthalate and/or other polyester elastomers such as HYTREL® available from DuPont), polyamide (for example, DURETHAN® available from Bayer or CRISTAMID® available from Elf Atochem), elastomeric polyamides, block polyamide/ethers, polyether block amide (PEBA, for example available under the trade name PEBAX®), ethylene vinyl acetate copolymers (EVA), silicones, polyethylene (PE), Marlex high-density polyethylene, Marlex low-density polyethylene, linear low density polyethylene (for example REXELL®), polyester, polybutylene terephthalate (PBT), polyethylene terephthalate (PET), polytrimethylene terephthalate, polyethylene naphthalate (PEN), polyetheretherketone (PEEK), polyimide (PI), polyetherimide (PEI), polyphenylene sulfide (PPS), polyphenylene oxide (PPO), poly paraphenylene terephthalamide (for example, KEVLAR®), polysulfone, nylon, nylon-12 (such as GRILAMID® available from EMS American Grilon), perfluoro(propyl vinyl ether) (PFA), ethylene vinyl alcohol, polyolefin, polystyrene, epoxy, polyvinylidene chloride (PVdC), poly(styrene-b-isobutylene-b-styrene) (for example, SIBS and/or SIBS 50A), polycarbonates, ionomers, biocompatible polymers, other suitable materials, or mixtures, combinations, copolymers thereof, polymer/metal composites, and the like. In some embodiments the sheath can be blended with a liquid crystal polymer (LCP). For example, the mixture can contain up to about 6 percent LCP.

[0129] In some embodiments, the exterior surface of the guide extension catheter **14** (including, for example, the exterior surface of proximal member **16** and distal sheath **26**) may be sandblasted, beadblasted, sodium bicarbonate-blasted, electropolished, etc. In these as well as in some other embodiments, a coating, for example a lubricious, a hydrophilic, a protective, or other type of coating may be applied over portions or all of the sheath, or in embodiments without a sheath over portion of proximal member **16** and distal sheath **26**, or other portions of guide extension catheter **14**. Alternatively, the sheath may comprise a lubricious, hydrophilic, protective, or other type of

coating. Hydrophobic coatings such as fluoropolymers provide a dry lubricity which improves guidewire handling and device exchanges. Lubricious coatings improve steerability and improve lesion crossing capability. Suitable lubricious polymers are well known in the art and may include silicone and the like, hydrophilic polymers such as high-density polyethylene (HDPE), polytetrafluoroethylene (PTFE), polyarylene oxides, polyvinylpyrrolidones, polyvinylalcohols, hydroxy alkyl cellulose, algins, saccharides, caprolactones, and the like, and mixtures and combinations thereof. Hydrophilic polymers may be blended among themselves or with formulated amounts of water insoluble compounds (including some polymers) to yield coatings with suitable lubricity, bonding, and solubility. Some other examples of such coatings and materials and methods used to create such coatings can be found in U.S. Pat. Nos. 6,139,510 and 5,772,609, which are incorporated herein by reference.

[0130] The coating and/or sheath may be formed, for example, by coating, extrusion, co-extrusion, interrupted layer co-extrusion (ILC), or fusing several segments end-to-end. The layer may have a uniform stiffness or a gradual reduction in stiffness from the proximal end to the distal end thereof. The gradual reduction in stiffness may be continuous as by ILC or may be stepped as by fusing together separate extruded tubular segments. The outer layer may be impregnated with a radiopaque filler material to facilitate radiographic visualization. Those skilled in the art will recognize that these materials can vary widely without deviating from the scope of the present invention.

Claims

1. A guide extension catheter, comprising: a proximal member having a proximal portion with a proximal outer diameter and an extension portion having an arcuate cross-section; a collar member having an arcuate cross-section portion mating with and attached to the extension portion having the arcuate cross-section; and a distal sheath member attached to the collar member, the distal sheath member having a lumen and a distal outer diameter larger than the proximal outer diameter.
2. The guide extension catheter of claim 1, wherein the arcuate cross-section of the collar member is at a base portion of the collar member and one or more ribs extend distally away from the base portion.
3. The guide extension catheter of claim 1, wherein the proximal member includes a first hole through the extension portion having the arcuate cross-section and the collar member includes a second hole aligned with the first hole when the arcuate cross-section portion of the collar member is mating with and attached to the extension portion.
4. The guide extension catheter of claim 1, wherein an outer surface of the extension portion having the arcuate cross-section is attached to an inner surface of the arcuate cross-section portion of the collar member.
5. The guide extension catheter of claim 1, wherein an inner surface of the extension portion having the arcuate cross-section is attached to an outer surface of the arcuate cross-section portion of the collar member.
6. The guide extension catheter of claim 1, wherein the extension portion is configured to taper from a distal end of the proximal member to the proximal portion.
7. The guide extension catheter of claim 1, wherein the extension portion is a flattened extension portion.
8. The guide extension catheter of claim 1, wherein the proximal portion has a first cross-sectional area and the extension portion has a second cross-sectional area that is equal to or less than the first cross-sectional area.
9. A medical treatment delivery system, the system comprising: a delivery device comprising a nose extending proximally from a distal end of the delivery device and a medical device location extending proximal from a proximal end of the nose, wherein the nose has a distal end with a

length extending between the proximal end and the distal end of the nose; a guide extension catheter comprising: a proximal member having a proximal portion with a proximal outer diameter and an extension portion having an arcuate cross-section; a collar member having an arcuate cross-section portion mating with and attached to the extension portion having the arcuate cross-section; and a distal sheath member attached to the collar member, the distal sheath member having a lumen and a distal outer diameter larger than the proximal outer diameter.

10. The system of claim 9, wherein the arcuate cross-section of the collar member is at a base portion of the collar member and one or more ribs extend distally away from the base portion.

11. The guide extension catheter of claim 9, wherein the proximal member includes a first hole through the extension portion having the arcuate cross-section and the collar member includes a second hole aligned with the first hole when the arcuate cross-section portion of the collar member is mating with and attached to the extension portion.

12. The guide extension catheter of claim 9, wherein an outer surface of the extension portion having the arcuate cross-section is attached to an inner surface of the arcuate cross-section portion of the collar member.

13. The system of claim 9, wherein the length of the nose is greater than a length of the extension portion.

14. The system of claim 9, wherein the delivery device is a stent delivery catheter and the medical device location is configured to receive a stent.

15. The system of claim 9, wherein the delivery device is a balloon catheter and the medical device location includes a balloon.

16. A method for manufacturing a guide extension catheter, comprising: grasping the extension portion of a proximal member and bringing the extension portion into contact with a collar, the proximal member having a proximal end and a distal end; affixing the extension portion to the collar; attaching a distal sheath member to the collar such that the distal sheath member extends distally of the proximal member and the collar; and mating an arcuate surface of the extension portion with an arcuate surface of the collar.

17. The method of claim 16, further comprising: flattening the extension portion of the proximal member, wherein flattening the extension portion includes flattening a portion of the proximal member that extends between the distal end of the proximal member and a location less than ten millimeters proximal of the distal end of the proximal member.

18. The method of claim 16, further comprising: flattening the extension portion of the proximal member, wherein flattening the extension portion of the proximal member includes stamping the extension portion of the proximal member.

19. The method of claim 16, wherein mating the arcuate surface of the extension portion with the arcuate surface of the collar comprises mating an outer surface of the extension portion with an inner surface of the collar member.

20. The method of claim 19, further comprising: aligning a first opening through the arcuate surface of the flattened extension portion with a second opening through the arcuate surface of the collar.
