

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent  
Kind Code  
Date of Patent  
Inventor(s)

12392928  
B2  
August 19, 2025  
Hern; Randall A. et al.

### Sensor device for use in controlling irrigation

#### Abstract

Methods and apparatus are provided herein for sensing rain fall for use in irrigation control. In one embodiment, a wireless rain sensor comprises a housing at least partially covering a first sensor, a controller and a wireless transmitter. The first sensor comprises a moisture absorptive material located to be contacted by rain fall and configured to expand in response to the contact with the rain fall and contract in response to an absence of the rain fall. The controller is coupled to the first sensor and configured to output signals corresponding to a variable amount of expansion and contraction of the moisture absorptive material. The wireless transmitter is configured to transmit wireless signals, at least one wireless signal comprising data corresponding to the variable amount of expansion and contraction of the moisture absorptive material.

**Inventors:** Hern; Randall A. (San Diego, CA), Fern; David G. (Santee, CA), Peterson; Gerald E. (Riverside, CA), Redmond; David M. (Scottsdale, AZ)

**Applicant:** Rain Bird Corporation (Azusa, CA)

**Family ID:** 1000008762753

**Assignee:** Rain Bird Corporation (Azusa, CA)

**Appl. No.:** 18/516418

**Filed:** November 21, 2023

#### Prior Publication Data

Document Identifier	Publication Date
US 20240085588 A1	Mar. 14, 2024

#### Related U.S. Application Data

continuation parent-doc US 17730019 20220426 US 11822048 child-doc US 18516418  
continuation parent-doc US 16945668 20200731 US 11346981 20220531 child-doc US 17730019  
continuation parent-doc US 16422281 20190524 US 10732320 20200804 child-doc US 16945668  
continuation parent-doc US 15331565 20161021 US 10345487 20190709 child-doc US 16422281  
continuation parent-doc US 14253716 20140415 US 9500770 20161122 child-doc US 15331565  
continuation parent-doc US 13479111 20120523 US 8733165 20140527 child-doc US 14253716  
continuation parent-doc US 13113900 20110523 ABANDONED child-doc US 13479111  
continuation parent-doc US 11766092 20070620 US 7949433 20110524 child-doc US 13113900  
us-provisional-application US 60866595 20061120  
us-provisional-application US 60805331 20060620

## Publication Classification

**Int. Cl.:** **G01W1/14** (20060101); **A01G25/16** (20060101); **G01K13/00** (20210101)

**U.S. Cl.:**

**CPC** **G01W1/14** (20130101); **A01G25/167** (20130101); **G01K13/00** (20130101);

## Field of Classification Search

**CPC:** G01W (1/14); G01W (1/00); G01W (1/08); G01W (1/02); G01W (1/10); G01W (1/04); G01W (1/06); G01W (1/12); G01W (1/16); G01W (2001/003); G01W (2001/006); G01W (2203/00)

**USPC:** 73/170.16-1

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2202452	12/1939	Hildabrand	N/A	N/A
D127348	12/1940	Gayda	N/A	N/A
D153568	12/1948	Wagner	N/A	N/A
2688056	12/1953	Kettering	N/A	N/A
2776860	12/1956	Griffis	N/A	N/A
2991938	12/1960	Norcross	N/A	N/A
3127769	12/1963	Stucky	N/A	N/A
3243999	12/1965	Alan	N/A	N/A
3297254	12/1966	Coffman	N/A	N/A
3309474	12/1966	Heinrich	N/A	N/A
3485096	12/1968	Miller	N/A	N/A
3675672	12/1971	Freeman	N/A	N/A
3705533	12/1971	Kahl et al.	N/A	N/A
3721122	12/1972	Lucas	N/A	N/A
3808385	12/1973	Klinefelter	N/A	N/A
3943762	12/1975	Baer	N/A	N/A
4012673	12/1976	Saarem	N/A	N/A
4022384	12/1976	Hoyle	N/A	N/A
4064507	12/1976	Schmitz	N/A	N/A
4209131	12/1979	Barash	N/A	N/A
4246574	12/1980	Sanner	N/A	N/A
4264902	12/1980	Miller	N/A	N/A
4313042	12/1981	Ehrhart	N/A	N/A
4394603	12/1982	Widmayer	N/A	N/A
D270272	12/1982	Steele	N/A	N/A
4396149	12/1982	Hirsch	N/A	N/A
D276039	12/1983	Tanaka	N/A	N/A
4613764	12/1985	Lobato	N/A	N/A
4644786	12/1986	Jacobsen	N/A	N/A
4655076	12/1986	Weihe	N/A	N/A
4684920	12/1986	Reiter	N/A	N/A
4701613	12/1986	Watanabe	N/A	N/A
4718185	12/1987	Conlin	N/A	N/A
4760547	12/1987	Duxbury	N/A	N/A
4817875	12/1988	Karmeli	N/A	N/A
4862701	12/1988	Small	N/A	N/A
4916642	12/1989	Kaiser	N/A	N/A
4919165	12/1989	Lloyd	N/A	N/A

4921001	12/1989	Pittsinger	N/A	N/A
4922433	12/1989	Mark	N/A	N/A
4987296	12/1990	Kajioka	N/A	N/A
D316875	12/1990	Momot	N/A	N/A
5060859	12/1990	Bancroft	N/A	N/A
5087886	12/1991	Mann	N/A	N/A
5101083	12/1991	Tyler	N/A	N/A
5104045	12/1991	Carl	N/A	N/A
5109482	12/1991	Bohrman	N/A	N/A
D328763	12/1991	Laviana	N/A	N/A
5193570	12/1992	Mott	N/A	N/A
5207380	12/1992	Harryman	N/A	N/A
5299742	12/1993	Han	N/A	N/A
5321578	12/1993	Morrison	N/A	N/A
5329081	12/1993	Jones	N/A	N/A
5333785	12/1993	Dodds	N/A	N/A
5355122	12/1993	Erickson	N/A	N/A
5367627	12/1993	Johnson	N/A	N/A
5375617	12/1993	Young	N/A	N/A
5381331	12/1994	Mock	N/A	N/A
5394748	12/1994	McCarthy	N/A	N/A
5401262	12/1994	Karwoski	N/A	N/A
5424649	12/1994	Gluck	N/A	N/A
5444611	12/1994	Woytowitz	N/A	N/A
5465904	12/1994	Vaello	N/A	N/A
5499024	12/1995	Germanton	N/A	N/A
D368493	12/1995	Boes	N/A	N/A
5505082	12/1995	Cushman	N/A	N/A
5526982	12/1995	McKenzie	N/A	N/A
5554809	12/1995	Tobita	N/A	N/A
5568385	12/1995	Shelton	N/A	N/A
5598977	12/1996	Lemme	N/A	N/A
5640176	12/1996	Mundt	N/A	N/A
D388424	12/1996	Demuro	N/A	N/A
5696671	12/1996	Oliver	N/A	N/A
5727950	12/1997	Cook	N/A	N/A
5740038	12/1997	Hergert	N/A	N/A
5813606	12/1997	Ziff	N/A	N/A
D399837	12/1997	Garguilo	N/A	N/A
5818734	12/1997	Albright	N/A	N/A
5821864	12/1997	Knop	N/A	N/A
D400522	12/1997	Waldner	N/A	N/A
5836339	12/1997	Klever	N/A	N/A
5839660	12/1997	Morgenstern	N/A	N/A
D402645	12/1997	Garguilo	N/A	N/A
5853122	12/1997	Caprio	N/A	N/A
5870302	12/1998	Oliver	N/A	N/A
5886697	12/1998	Naughton	N/A	N/A
D407656	12/1998	Klever	N/A	N/A
5898110	12/1998	Hagstrom	N/A	N/A
5905480	12/1998	Palalau	N/A	N/A
5918276	12/1998	Grindle	N/A	N/A
5921280	12/1998	Ericksen	N/A	N/A
5925986	12/1998	Moisin	N/A	N/A
D415134	12/1998	Culp	N/A	N/A
6005517	12/1998	Friedrichs	N/A	N/A
6016971	12/1999	Welch	N/A	N/A
6038920	12/1999	Gilbert	N/A	N/A

6076740	12/1999	Townsend	N/A	N/A
6088621	12/1999	Woytowitz	N/A	N/A
6126093	12/1999	Grether	N/A	N/A
6145755	12/1999	Feltz	N/A	N/A
D437859	12/2000	Alvarez	N/A	N/A
6210383	12/2000	Want	N/A	N/A
D441764	12/2000	Minagawa	N/A	N/A
6240325	12/2000	Brundisini	N/A	N/A
6240336	12/2000	Brundisini	N/A	N/A
6260765	12/2000	Natale	N/A	N/A
6300728	12/2000	Blackburn	N/A	N/A
6314340	12/2000	Mecham	N/A	N/A
6369712	12/2001	Letkomiller	N/A	N/A
6401530	12/2001	Roman	N/A	N/A
6427535	12/2001	Sakai	N/A	N/A
6452499	12/2001	Runge	N/A	N/A
6453215	12/2001	Lavoie	N/A	N/A
6453216	12/2001	McCabe	N/A	N/A
D466519	12/2001	Shim	N/A	N/A
D469107	12/2002	Miller	N/A	N/A
D473239	12/2002	Cockerill	N/A	N/A
D473240	12/2002	Cockerill	N/A	N/A
6570109	12/2002	Klinefelter	N/A	N/A
6585168	12/2002	Caprio	N/A	N/A
6714134	12/2003	Addink	N/A	N/A
6721630	12/2003	Woytowitz	N/A	N/A
6782310	12/2003	Bailey	N/A	N/A
6782311	12/2003	Barlow	N/A	N/A
D496667	12/2003	Hoglund	N/A	N/A
6823239	12/2003	Sieminski	N/A	N/A
D503178	12/2004	Choi	N/A	N/A
6892114	12/2004	Addink	N/A	N/A
6895987	12/2004	Addink	N/A	N/A
6977351	12/2004	Woytowitz	N/A	N/A
7003357	12/2005	Kreikemeier	N/A	N/A
7010394	12/2005	Runge	N/A	N/A
7010395	12/2005	Goldberg	N/A	N/A
7050887	12/2005	Alvarez	N/A	N/A
7058478	12/2005	Alexanian	N/A	N/A
D526657	12/2005	Matsumoto	N/A	N/A
7096094	12/2005	Addink	N/A	N/A
7111179	12/2005	Girson	N/A	N/A
7114388	12/2005	French	N/A	N/A
7123993	12/2005	Freeman	N/A	N/A
7177728	12/2006	Gardner	N/A	N/A
7198393	12/2006	Tubidis	N/A	N/A
7216145	12/2006	Collings, III	N/A	N/A
7216659	12/2006	Caamano	N/A	N/A
7229026	12/2006	Evelyn-Veere	N/A	N/A
7236249	12/2006	Michenfelder	N/A	N/A
7241974	12/2006	Reusche	N/A	N/A
7243459	12/2006	Kaprielian	N/A	N/A
7245991	12/2006	Woytowitz	N/A	N/A
7249502	12/2006	Luukkala	N/A	N/A
7266428	12/2006	Alexanian	N/A	N/A
7280892	12/2006	Bavel	N/A	N/A
7286904	12/2006	Graham	N/A	N/A
7339957	12/2007	Hitt	N/A	N/A

7363113	12/2007	Runge	N/A	N/A
7386289	12/2007	Weller	N/A	N/A
7403840	12/2007	Moore	N/A	N/A
7412303	12/2007	Porter	N/A	N/A
D587278	12/2008	Sans	N/A	N/A
7494070	12/2008	Collins	N/A	N/A
7516002	12/2008	Veerasamy	N/A	N/A
7526365	12/2008	Frerich	N/A	N/A
D592222	12/2008	Chaudhri	N/A	N/A
7532954	12/2008	Evelyn-Veere	N/A	N/A
7540186	12/2008	Jeong	N/A	N/A
7552632	12/2008	Runge	N/A	N/A
D599816	12/2008	Kaczmarek	N/A	N/A
D600704	12/2008	Lamanna	N/A	N/A
D600713	12/2008	Lamanna	N/A	N/A
D600714	12/2008	Lamanna	N/A	N/A
7590471	12/2008	Jacobsen	N/A	N/A
7596429	12/2008	Cardinal	N/A	N/A
D601578	12/2008	Poulet	N/A	N/A
D602496	12/2008	Takano	N/A	N/A
D602944	12/2008	Barkhouse	N/A	N/A
7613546	12/2008	Nelson	N/A	N/A
D608789	12/2009	Kaczmarek	N/A	N/A
7654684	12/2009	Wight	N/A	N/A
7687028	12/2009	Coplen, II	N/A	N/A
D623194	12/2009	Cook	N/A	N/A
7805221	12/2009	Nickerson	N/A	N/A
D625622	12/2009	Mallela	N/A	N/A
7809475	12/2009	Kaprielian	N/A	N/A
7814197	12/2009	Collings, III	N/A	N/A
7844368	12/2009	Alexanian	N/A	N/A
7853363	12/2009	Porter	N/A	N/A
7877168	12/2010	Porter	N/A	N/A
7912588	12/2010	Runge	N/A	N/A
7930069	12/2010	Savelle	N/A	N/A
D638028	12/2010	Cook	N/A	N/A
7937187	12/2010	Kaprielian	N/A	N/A
7949433	12/2010	Hern	N/A	N/A
7962245	12/2010	Runge	N/A	N/A
8028572	12/2010	Matsuda	N/A	N/A
8104993	12/2011	Hitt	N/A	N/A
8160750	12/2011	Weiler	N/A	N/A
8209061	12/2011	Palmer	N/A	N/A
8209124	12/2011	Dannevik	N/A	N/A
8215570	12/2011	Hitt	N/A	N/A
8271198	12/2011	Teder	N/A	N/A
8301309	12/2011	Woytoxitz	N/A	N/A
8321365	12/2011	Anderson	N/A	N/A
8437879	12/2012	Anderson	N/A	N/A
8494774	12/2012	Pasken	N/A	N/A
8538592	12/2012	Alexanian	N/A	N/A
8548632	12/2012	Porter	N/A	N/A
8548669	12/2012	Naylor	N/A	N/A
8554380	12/2012	Nourian	N/A	N/A
8573049	12/2012	Ware	N/A	N/A
8606415	12/2012	Woytowitz	N/A	N/A
8620480	12/2012	Alexanian	N/A	N/A
8635024	12/2013	Brillhart	N/A	N/A

8660705	12/2013	Woytowitz	N/A	N/A
8714007	12/2013	Cullen	N/A	N/A
8733165	12/2013	Hern	N/A	N/A
8744773	12/2013	Woytowitz	N/A	N/A
8862275	12/2013	Runge	N/A	N/A
8874275	12/2013	Alexanian	N/A	N/A
8924032	12/2013	Woytowitz	N/A	N/A
8948921	12/2014	Halahan	N/A	N/A
8991108	12/2014	Zamrzla	N/A	N/A
9032998	12/2014	O'brien	N/A	N/A
9053585	12/2014	Naylor	N/A	N/A
9131642	12/2014	Groeneveld	N/A	N/A
9144204	12/2014	Redmond	N/A	N/A
9244192	12/2015	Cullen	N/A	N/A
9244449	12/2015	Tennyson	N/A	N/A
9247321	12/2015	Pryor	N/A	N/A
9301460	12/2015	Runge	N/A	N/A
9301461	12/2015	Woytowitz	N/A	N/A
9414552	12/2015	Halahan	N/A	N/A
9439367	12/2015	Abhyanker	N/A	N/A
9468162	12/2015	Weiler	N/A	N/A
9474216	12/2015	Reiss	N/A	N/A
9500770	12/2015	Hern	N/A	N/A
9519078	12/2015	Lanza	N/A	N/A
9633532	12/2016	Larrison	N/A	N/A
9655311	12/2016	Bell	N/A	N/A
9696459	12/2016	Murphy	N/A	N/A
9756844	12/2016	Groeneveld	N/A	N/A
9763393	12/2016	Parsons	N/A	N/A
9781887	12/2016	Woytowitz	N/A	N/A
10101753	12/2017	Levine	N/A	N/A
10123493	12/2017	Runge	N/A	N/A
10201133	12/2018	Tennyson	N/A	N/A
10206341	12/2018	Micu	N/A	N/A
10206342	12/2018	Redmond	N/A	N/A
10345487	12/2018	Hern	N/A	N/A
10444769	12/2018	Weiler	N/A	N/A
10531617	12/2019	Verma	N/A	N/A
10732320	12/2019	Hern	N/A	N/A
10757873	12/2019	Weiler	N/A	N/A
10849287	12/2019	Redmond	N/A	N/A
11006589	12/2020	Marsano	N/A	N/A
11119513	12/2020	Weiler	N/A	N/A
11281240	12/2021	Eyring	N/A	N/A
11297786	12/2021	Redmond	N/A	N/A
11346981	12/2021	Hern	N/A	N/A
11357182	12/2021	Weiler	N/A	N/A
11822048	12/2022	Hern	N/A	N/A
11957083	12/2023	Redmond	N/A	N/A
2001/0049563	12/2000	Addink	N/A	N/A
2002/0026284	12/2001	Brown	N/A	N/A
2002/0029111	12/2001	Peek	N/A	N/A
2002/0060631	12/2001	Runge	N/A	N/A
2002/0165700	12/2001	Zur	N/A	N/A
2003/0079974	12/2002	Klinefelter	N/A	N/A
2003/0085929	12/2002	Huber	N/A	N/A
2003/0117321	12/2002	Furse	N/A	N/A
2004/0011880	12/2003	Addink	N/A	N/A

2004/0039489	12/2003	Moore	N/A	N/A
2004/0100394	12/2003	Hitt	N/A	N/A
2004/0113106	12/2003	Pyun	N/A	N/A
2004/0140903	12/2003	Buhler	N/A	N/A
2004/0181315	12/2003	Cardinal	N/A	N/A
2004/0206395	12/2003	Addink	N/A	N/A
2004/0217189	12/2003	Regli	N/A	N/A
2004/0244833	12/2003	Buhler	N/A	N/A
2005/0046372	12/2004	Heo	N/A	N/A
2005/0082382	12/2004	Evelyn-Veere	N/A	N/A
2005/0090936	12/2004	Hitt	N/A	N/A
2005/0107924	12/2004	Bailey	N/A	N/A
2005/0171646	12/2004	Miller	N/A	N/A
2005/0192710	12/2004	Thornton	N/A	N/A
2005/0199842	12/2004	Parsons	N/A	N/A
2005/0206530	12/2004	Cumming	N/A	N/A
2005/0216130	12/2004	Clark	N/A	N/A
2006/0030971	12/2005	Nelson	N/A	N/A
2006/0049271	12/2005	Hitt	N/A	N/A
2006/0100747	12/2005	Runge	N/A	N/A
2006/0118200	12/2005	Nies	N/A	N/A
2006/0122736	12/2005	Alexanian	N/A	N/A
2006/0155489	12/2005	Addink	N/A	N/A
2006/0161309	12/2005	Moore	N/A	N/A
2006/0172714	12/2005	Weller	N/A	N/A
2006/0184285	12/2005	Evelyn-Veere	N/A	N/A
2006/0202051	12/2005	Parsons	N/A	N/A
2006/0293797	12/2005	Weiler	N/A	N/A
2007/0010915	12/2006	Burson	N/A	N/A
2007/0132599	12/2006	DuFaux	N/A	N/A
2007/0162201	12/2006	Veerasamy	N/A	N/A
2007/0191991	12/2006	Addink	N/A	N/A
2007/0293990	12/2006	Alexanain	N/A	N/A
2008/0027586	12/2007	Hern	N/A	N/A
2008/0034859	12/2007	Runge	N/A	N/A
2008/0129495	12/2007	Hitt	N/A	N/A
2008/0249664	12/2007	Runge	N/A	N/A
2008/0251602	12/2007	Leggett	N/A	N/A
2008/0288116	12/2007	Nickerson	N/A	N/A
2008/0295883	12/2007	Ducellier	N/A	N/A
2009/0001193	12/2008	Parsons	N/A	N/A
2009/0007706	12/2008	Hitt	N/A	N/A
2009/0083656	12/2008	Dukhon	N/A	N/A
2009/0177330	12/2008	Carl	N/A	N/A
2009/0179165	12/2008	Parsons	N/A	N/A
2009/0271044	12/2008	Bangalore	N/A	N/A
2009/0284598	12/2008	Busch	N/A	N/A
2010/0030389	12/2009	Palmer	N/A	N/A
2010/0030476	12/2009	Woytowitz	N/A	N/A
2010/0092107	12/2009	Mochizuki	N/A	N/A
2010/0145530	12/2009	Nickerson	N/A	N/A
2010/0147389	12/2009	Blanchard	N/A	N/A
2010/0222932	12/2009	O'Connor	N/A	N/A
2010/0263248	12/2009	Robert	N/A	N/A
2010/0306012	12/2009	Zyskowski	N/A	N/A
2011/0093123	12/2010	Alexanian	N/A	N/A
2011/0224836	12/2010	Hern	N/A	N/A
2011/0238227	12/2010	Hern	N/A	N/A

2011/0238228	12/2010	Woytowitz	N/A	N/A
2011/0238229	12/2010	Woytowitz	N/A	N/A
2011/0288775	12/2010	Woytowitz	N/A	N/A
2012/0041607	12/2011	Woytowitz	N/A	N/A
2012/0054125	12/2011	Clifton	N/A	N/A
2012/0072037	12/2011	Alexanian	N/A	N/A
2012/0089259	12/2011	Williams	N/A	N/A
2012/0203382	12/2011	Nourian	N/A	N/A
2012/0215366	12/2011	Redmond	N/A	N/A
2012/0221154	12/2011	Runge	N/A	N/A
2012/0261486	12/2011	Sarver	N/A	N/A
2012/0303168	12/2011	Halahan	N/A	N/A
2013/0047718	12/2012	Chae	N/A	N/A
2013/0079934	12/2012	Carskadon	N/A	N/A
2013/0110293	12/2012	Illig	N/A	N/A
2013/0173070	12/2012	Tennyson	N/A	N/A
2013/0253714	12/2012	Williams	N/A	N/A
2013/0269798	12/2012	Wood	N/A	N/A
2014/0027539	12/2013	Kim	N/A	N/A
2014/0081471	12/2013	Woytowitz	N/A	N/A
2014/0148959	12/2013	Levine	N/A	N/A
2014/0167969	12/2013	Wedig	N/A	N/A
2014/0172180	12/2013	Woytowitz	N/A	N/A
2014/0222223	12/2013	Horton	N/A	N/A
2015/0032274	12/2014	Runge	N/A	N/A
2015/0061888	12/2014	Lankford	N/A	N/A
2015/0112494	12/2014	Woytowitz	N/A	N/A
2015/0268380	12/2014	Anderson	N/A	N/A
2016/0037736	12/2015	Rainone	N/A	N/A
2016/0180473	12/2015	Groeneveld	N/A	N/A
2016/0192602	12/2015	Alexanian	N/A	N/A
2016/0198645	12/2015	Weatherill	N/A	N/A
2016/0212952	12/2015	Runge	N/A	N/A
2016/0219806	12/2015	Thiessen	N/A	N/A
2016/0327687	12/2015	Nylander	N/A	N/A
2017/0013810	12/2016	Grabell	N/A	N/A
2017/0055467	12/2016	Andrews	N/A	N/A
2017/0107967	12/2016	Kasten	N/A	N/A
2017/0112079	12/2016	Eyring	N/A	N/A
2017/0164569	12/2016	Andrews	N/A	N/A
2018/0014480	12/2017	Montgomery	N/A	N/A
2019/0020054	12/2018	Kawase	N/A	N/A
2019/0154875	12/2018	Midya	N/A	N/A
2019/0336994	12/2018	Duffin	N/A	N/A
2021/0360884	12/2020	Woytowitz	N/A	N/A
2021/0392829	12/2020	Marsano	N/A	N/A
2022/0004207	12/2021	Weiler	N/A	N/A
2022/0240464	12/2021	Redmond	N/A	N/A
2022/0272915	12/2021	Weiler	N/A	N/A
2024/0012434	12/2023	Weiler	N/A	N/A
2024/0215501	12/2023	Redmond	N/A	N/A
2024/0215502	12/2023	Weiler	N/A	N/A

#### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
9331864	12/1992	AU	A01G 25/167
2688197	12/2009	CA	N/A
237456	12/1985	DE	N/A
2883034	12/2014	EP	N/A



1498545	12/1977	GB	N/A
2412735	12/2004	GB	N/A
H02196990	12/1989	JP	N/A
2010237038	12/2009	JP	N/A
101467705	12/2013	KR	N/A
9727733	12/1996	WO	N/A
1999039567	12/1998	WO	N/A
030760	12/1999	WO	N/A
0227109	12/2001	WO	N/A
0227419	12/2001	WO	N/A
02086546	12/2001	WO	N/A
03038539	12/2002	WO	N/A
03041874	12/2002	WO	N/A
2004005628	12/2003	WO	N/A
2004052560	12/2003	WO	N/A
2004091286	12/2003	WO	N/A
2016162086	12/2015	WO	N/A
2019133273	12/2018	WO	N/A

## OTHER PUBLICATIONS

US 8,224,494 B2, 07/2012, Anderson (withdrawn) cited by applicant

U.S. Appl. No. 61/405,119, filed Oct. 20, 2010, Hern Randall A. cited by applicant

“Presenting the Wireless RainSensor for Irrigation Systems” brochure, R&D Engineering, 2000. Printed from archive.org dated May 2001 (5 pages). cited by applicant

“R&D Engineering Wireless Rain Sensor Products”, archive from May 2001 of <http://www.rainsensor.com/products1.htm> (3 pages). cited by applicant

Davis Instruments, Wireless and Cabled Weather Systems, Vantage Pro Catalog, 2 pages, Dec. 2004 (2 pages). cited by applicant

Davis Instruments; “User Manual Integrated Sensor Suite for Vantage Pro2 and Vantage Pro2 Plus”;

[https://www.davisinstruments.com/product\\_documents/weather/manuals/07395-333\\_IM-6322C-6334.pdf](https://www.davisinstruments.com/product_documents/weather/manuals/07395-333_IM-6322C-6334.pdf); May 22, 2015; pp. 1-44. cited by applicant

Dukes et al., Residential Irrigation System Rainfall Shutoff Devices, University of Florida IFAS Extension, 4 pages, Aug. 2002 (4 pages). cited by applicant

EPO, Extended European Search Report issued in Application No. 13768209.2, Nov. 24, 2015 (10 pages). cited by applicant

EPO; App. No. 07798852.5; Extended European Search Report mailed Aug. 1, 2012; (6 pages). cited by applicant

Graphic art Materials Reference Manual, Letraset, 1981, pp. 217 and 220. cited by applicant

Hunter Industries, 'Mini-Clik, The world's most simple, accurate, rugged, and reliable rain sensors',

<http://hunterindustries.com/Products/Sensors/miniclikintro.html>, Mar. 2006, p. 1, Hunter Industries Incorporated, San Marcos, CA. (1 page.). cited by applicant

Hunter Industries, 'Rain-Clik, The reliable rain sensor with instant shut-off',

<http://hunterindustries.com/Products/Sensors/rainclikintro.html>, Apr. 2007, p. 1, Hunter Industries Incorporated, San Marcos, CA. (1 page). cited by applicant

Hunter Industries; “Wireless Solar Sync Owner's Manual and Programming Instructions”; Oct. 12, 2008, San Marcos, CA, published at <http://web.archive.org/web/20081012080937/http://www.hunterindustries.com> (28 pages). cited by applicant

Hunter TM Wireless Rain-Clik(TM), Mar. 2006 (2 pages). cited by applicant

Hunter, Owner's Manual and Installation Instructions, ‘WRC Wireless Rain-Clik(TM) Sensors’, published at least on or before Dec. 31, 2005, Hunter Industries Incorporated, San Marcos, California (20 pages). cited by applicant

Hunter, Solar Sync Owner's Manual and Programming Instructions, Dec. 2009, San Marcos, CA published at

[http://web.archive.org/web/20120502050544/http://www.hunterindustries.com/sites/default/files/OM\\_SolarSync\\_DOM.pdf](http://web.archive.org/web/20120502050544/http://www.hunterindustries.com/sites/default/files/OM_SolarSync_DOM.pdf) (20 pages). cited by applicant

Iconfactory : Freeware : iPhonica vol. 2, [online] Jan. 30, 2007 [retrieved on Apr. 4, 2007]. Retrieved from the Internet

<URL: <http://iconfactory.com/freeware/preview/iph2>> (2 pages). cited by applicant

Iconfactory : Freeware : NewtCons, [online] Jun. 1, 1999 [retrieved on Apr. 4, 2007]. Retrieved from the Internet <URL:

<http://iconfactory.com/freeware/preview/nwtc>> (2 pages). cited by applicant

Iconfactory : Freeware : Winter Wonderland, [online] Dec. 23, 2003 [retrieved on Apr. 4, 2007]. Retrieved from the

Internet <URL: <http://iconfactory.com/freeware/preview/wwld>> (2 pages). cited by applicant

InterfaceLIFT: Microsoft Windows Icons (by date), [online] Dec. 24, 2006 [retrieved on Apr. 4, 2007]. Retrieved from the

Internet <URL: <http://interfacelift.com/icons-win/>> (4 pages). cited by applicant

Logo Lounge, by Catharine Fishel and Bill Gardner, Rockport Publishers, Gloucester, MA 2003 (2 pages). cited by applicant

PCT; App. No. PCT/US07/71713; International Preliminary Report on Patentability mailed Dec. 22, 2008; (9 pages). cited by applicant

PCT; App. No. PCT/US07/71713; International Search Report mailed Jul. 16, 2008; (4 pgs.). cited by applicant

PCT; App. No. PCT/US07/71713; Written Opinion mailed Jul. 16, 2008; (8 pgs.). cited by applicant

R & D Engineering, Inc.; "The Wireless RainSensor Installation Guide"; published at <http://web.archive.org/web/20010604063747/http://rainsensor.com/images/instr.pdf>; Jun. 4, 2001; pp. 1-8; R & D Engineering, Inc. (8 pages). cited by applicant

R&D Engineering, Inc., New Plus+ Model Catalog, 2002 (2 pages). cited by applicant

Rain Bird, Central Computer Control System, Maxicom, 'Landscape Irrigation Products, 1993-1994 Catalog', Cover page and pp. 98-99, US (3 pages). cited by applicant

Rain Bird, Central Control System, Maxicom, Feb. 1993, Rain Bird Sales, Inc.; US (19 pages). cited by applicant

Rain Bird, Central Control System, Maxicom, Jun. 1994, Cover page and pp. 2-8, Rain Bird Sales, Inc., US (8 pages). cited by applicant

Rain Bird, Components of the Maxicom System, Feb. 9, 1994, p. 3.2, Section 3, US. (1 page). cited by applicant

Rain Bird, Et Manager Series, Installation and Operation Manual, Apr. 2007, Rain Bird Corporation, Tucson, AZ (80 pages). cited by applicant

Rain Bird, Maxicom Guide to Operations, Oct. 1, 1994, Chapter 7, Rain Bird Corporation, Glendora, CA (54 pages). cited by applicant

Rainbird Corporation, 'RSD Series Rain Sensor', <http://www.rainbird.com/landscape/products/controllers/rsd.htm>, Dec. 2007, pp. 1-2, Rainbird Corporation, Tucson, AZ. (2 pages). cited by applicant

Signs and Symbols: Their Design and Meaning, by Adrian Frutiger, Watson-Guption Publications, New York, NY, 1978 Part 1, 1979 Part 2, 1981 Part 3, p. 356 (4 pages). cited by applicant

Symbol Source Book, by Henry Dreyfuss, Van Nostrand Reinhold Company, New York, NY, 1972, pp. 27, 35, and 160 (4 pages). cited by applicant

Toro, "TMC-424 Series Turf Catalog", 2008; pp. 88-89, The Toro Company, Riverside, CA (2 pages). cited by applicant

Toro, User's Guide, "Wireless Rain Sensor Series Rain Sensor, Model TWRS and RAIN/FREEZE Sensor, Model TWRS", published at least on or before Dec. 31, 2005, The Toro Company, Irrigation Division (28 pages). cited by applicant

Trenholm et al., "How to Calibrate Your Sprinkler System", University of Florida IFAS Extension, Jan. 2001 (2 pages). cited by applicant

USPTO; U.S. Appl. No. 13/277,224; Notice of Allowance mailed May 21, 2015; (8 pages). cited by applicant

USPTO; U.S. Appl. No. 11/766,092; Interview Summary and Notice of Allowability mailed Feb. 11, 2011 (10 pages). cited by applicant

USPTO; U.S. Appl. No. 11/766,092; Interview Summary mailed Dec. 15, 2010; (3 pages). cited by applicant

USPTO; U.S. Appl. No. 11/766,092; Notice of Allowance mailed Jan. 13, 2011 (15 pages). cited by applicant

USPTO; U.S. Appl. No. 11/766,092; Office Action mailed Jan. 5, 2009; (24 pages). cited by applicant

USPTO; U.S. Appl. No. 11/766,092; Office Action mailed Jun. 23, 2008; (24 pages). cited by applicant

USPTO; U.S. Appl. No. 11/766,092; Office Action mailed Jul. 8, 2010; (31 pages). cited by applicant

USPTO; U.S. Appl. No. 11/766,092; Office Action mailed Sep. 17, 2009; (30 pages). cited by applicant

USPTO; U.S. Appl. No. 13/113,900; Office Action mailed Feb. 29, 2012; (12 pages). cited by applicant

USPTO; U.S. Appl. No. 13/113,900; Office Action mailed Oct. 11, 2013; (13 pages). cited by applicant

USPTO; U.S. Appl. No. 13/113,900; Office Action mailed Nov. 9, 2012; (13 pgs.). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Applicant-Initiated Interview Summary mailed Feb. 14, 2012; (3 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Applicant-Initiated Interview Summary mailed Sep. 27, 2011; (3 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Examiner Interview Summary mailed Sep. 11, 2012; (3 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Final Rejection mailed Jul. 18, 2023; (pp. 1-43). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Non-Final Rejection mailed Dec. 20, 2022; (pp. 1-40). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Jan. 7, 2020; (42 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Jan. 18, 2012; (29 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Jan. 23, 2017; (51 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Jan. 23, 2018; (39 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Feb. 18, 2015; (42 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Apr. 27, 2021; (44 pages). cited by applicant

USPTO; U.S. Appl. No. 13/151,269; Office Action mailed May 6, 2014; (21 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed May 15, 2019; (37 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Jun. 17, 2016; (42 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Jul. 22, 2020; (37 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Oct. 23, 2013; (21 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Oct. 31, 2018; (42 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Nov. 6, 2012; (2 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Nov. 19, 2015; (42 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Office Action mailed Nov. 5, 2021; (37 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/277,224; Office Action mailed Jan. 16, 2015; (63 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/277,224; Office Action mailed Mar. 27, 2014; (8 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/277,224; Office Action mailed Jul. 17, 2014; (61 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/479,111; Notice of Allowance mailed Jan. 15, 2014; (10 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/479,111; Restriction Requirement mailed Oct. 21, 2013; (7 pages). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Non-Final Rejection mailed Feb. 13, 2024; (pp. 1-43). cited by applicant  
USPTO; U.S. Appl. No. 14/253,716; Notice of Allowance mailed Jul. 15, 2016; (6 pages). cited by applicant  
USPTO; U.S. Appl. No. 14/253,716; Office Action mailed Jan. 28, 2016; (8 pages). cited by applicant  
USPTO; U.S. Appl. No. 14/830,600; Advisory Action mailed Aug. 23, 2018; (3 pages). cited by applicant  
USPTO; U.S. Appl. No. 14/830,600; Notice of Allowance mailed Sep. 26, 2018; (11 pages). cited by applicant  
USPTO; U.S. Appl. No. 14/830,600; Office Action mailed May 31, 2018; (46 pages). cited by applicant  
USPTO; U.S. Appl. No. 14/830,600; Office Action mailed Oct. 18, 2017; (32 pages). cited by applicant  
USPTO; U.S. Appl. No. 15/331,565; Notice of Allowance mailed Feb. 26, 2019; (5 pages). cited by applicant  
USPTO; U.S. Appl. No. 15/331,565; Office Action mailed Nov. 1, 2018; (6 pages). cited by applicant  
USPTO; U.S. Appl. No. 16/230,672; Notice of Allowance mailed Jul. 23, 2020; (9 pages). cited by applicant  
USPTO; U.S. Appl. No. 16/230,672; Office Action mailed Feb. 25, 2020; (21 pages). cited by applicant  
USPTO; U.S. Appl. No. 16/422,281; Notice of Allowance mailed Mar. 23, 2020; (7 pages). cited by applicant  
USPTO; U.S. Appl. No. 16/422,281; Office Action mailed Nov. 29, 2019; (6 pages). cited by applicant  
USPTO; U.S. Appl. No. 16/945,668; Notice of Allowance and Fees Due (PTOL-85) mailed Feb. 4, 2022; (8 pages). cited by applicant  
USPTO; U.S. Appl. No. 16/945,668; Office Action (Non-Final Rejection) Sep. 24, 2021; (6 pages). cited by applicant  
USPTO; U.S. Appl. No. 17/094,649; Notice of Allowance Sep. 29, 2021; (34 pages). cited by applicant  
USPTO; U.S. Appl. No. 17/094,649; Notice of Allowance and Fees Due (PTOL-85) mailed Dec. 7, 2021; (9 pages). cited by applicant  
USPTO; U.S. Appl. No. 17/703,421; Non-Final Rejection mailed Dec. 27, 2022; (pp. 1-54). cited by applicant  
USPTO; U.S. Appl. No. 17/703,421; Notice of Allowance and Fees Due (PTOL-85) mailed Dec. 14, 2023; (pp. 1-9). cited by applicant  
USPTO; U.S. Appl. No. 17/730,019; Non-Final Rejection mailed Jan. 20, 2023; (pp. 1-5). cited by applicant  
USPTO; U.S. Appl. No. 17/730,019; Notice of Allowance and Fees Due (PTOL-85) mailed Jul. 13, 2023; (pp. 1-8). cited by applicant  
USPTO; U.S. Appl. No. 13/151,269; Final Rejection mailed Jan. 2, 2025; (pp. 1-46). cited by applicant  
USPTO; U.S. Appl. No. 18/604,235; Non-Final Rejection mailed Oct. 21, 2024; (pp. 1-59). cited by applicant  
USPTO; U.S. Appl. No. 18/604,235; Notice of Allowance and Fees Due (PTOL-85) mailed Mar. 19, 2025; (pp. 1-9). cited by applicant

---

*Primary Examiner:* Allen; Andre J

*Attorney, Agent or Firm:* Fitch, Even, Tabin & Flannery, LLP

---

## **Background/Summary**

(1) This application is a continuation of U.S. application Ser. No. 17/730,019, filed Apr. 26, 2022, entitled SENSOR DEVICE FOR CONTROLLING IRRIGATION, which is a continuation of U.S. application Ser. No. 16/945,668, filed Jul. 31, 2020, entitled SENSOR DEVICE FOR CONTROLLING IRRIGATION, now U.S. Pat. No. 11,346,981, which is a continuation of U.S. application Ser. No. 16/422,281, filed May 24, 2019, entitled SENSOR DEVICE FOR CONTROLLING IRRIGATION, now U.S. Pat. No. 10,732,320, which is a continuation of U.S. application Ser. No. 15/331,565, filed Oct. 21, 2016, entitled SENSOR DEVICE FOR CONTROLLING IRRIGATION, now U.S. Pat. No. 10,345,487, which is a continuation of U.S. application Ser. No. 14/253,716, filed

Apr. 15, 2014, entitled SENSOR DEVICE FOR USE IN CONTROLLING IRRIGATION, now U.S. Pat. No. 9,500,770, which is a continuation of U.S. application Ser. No. 13/479,111, filed May 23, 2012, entitled SENSOR DEVICE FOR USE IN CONTROLLING IRRIGATION, now U.S. Pat. No. 8,733,165, which is a continuation of U.S. application Ser. No. 13/113,900, filed May 23, 2011, entitled SENSOR DEVICE FOR INTERRUPTING IRRIGATION, which is a continuation of U.S. application Ser. No. 11/766,092, filed Jun. 20, 2007, entitled SENSOR DEVICE FOR INTERRUPTING IRRIGATION, now U.S. Pat. No. 7,949,433, which claims the benefit of U.S. Provisional Application No. 60/866,595, filed Nov. 20, 2006, entitled WIRELESS SENSOR FOR INTERRUPTING IRRIGATION and U.S. Provisional Application No. 60/805,331, filed Jun. 20, 2006, entitled RAIN SENSOR DEVICE AND METHOD FOR INTERRUPTING WATERING OF AN IRRIGATION CONTROLLER, all of which are incorporated in their entirety herein by reference.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

(1) The present invention relates generally to the controlling of the execution of a watering program by an irrigation controller.

### 2. Discussion of the Related Art

(2) Rain sensors for use in the interruption of programmed watering schedules of an irrigation controller are generally known to include a material that is responsive to rain, and in the event a preset level of rain is exceeded, a switch is activated which outputs a signal to the irrigation controller that causes the controller to cease the execution of watering schedules.

(3) U.S. Pat. No. 6,452,499 to Runge et al. (which is incorporated herein by reference) describes a wireless rain sensor that uses a hygroscopic material that expands when exposed to water. When the hygroscopic material expands beyond a specified point or threshold, an integrated transmitter wirelessly transmits a radio frequency signal to a receiver attached to the controller. The receiver receives the wireless signal and causes the controller to cease watering. Similarly, U.S. Pat. No. 6,977,351 to Woytowicz (which is incorporated herein by reference) describes a wireless rain sensor including a hygroscopic material that is not mechanically connected to the switch that triggers the transmission of the wireless signal that will cause the interruption of watering. The threshold level may be adjusted by a user through the mechanical adjustment of the distance the hygroscopic material must expand before actuating the switch, such as described in U.S. Pat. No. 6,570,109 to Klinefelter et al (which is incorporated herein by reference). Thus, in order to exceed a selectable threshold, the hygroscopic material must expand a selectable distance, which corresponds to a selectable level of rain fall.

## SUMMARY OF THE INVENTION

(4) Several embodiments of the invention provide methods and apparatus for sensing rain fall for use in irrigation control.

(5) In one embodiment, the invention may be characterized as a rain sensor comprising: a moisture absorptive material adapted to move in response to rain fall; a plunger adapted to move in response to and proportional to the movement of the moisture absorptive material; and a sensor element. The sensor element comprises a first element and a second element coupled to the plunger and adapted to move with the plunger relative to the first element causing a change in a variable corresponding to the amount of rain. The rain sensor also comprises a controller adapted to measure the variable and further adapted to generate a signal comprising an indication of the amount of rain fall based on the variable.

(6) In another embodiment, a wireless rain sensor comprises a housing at least partially covering a first sensor, a controller and a wireless transmitter. The first sensor comprises a moisture absorptive material located to be contacted by rain fall and configured to expand in response to the contact with the rain fall and contract in response to an absence of the rain fall. The controller is coupled to the first sensor and configured to output signals corresponding to a variable amount of expansion and contraction of the moisture absorptive material. The wireless transmitter is configured to transmit wireless signals, at least one wireless signal comprising data corresponding to the variable amount of expansion and contraction of the moisture absorptive material.

(7) In another embodiment, a method of sensing rain fall comprises: sensing, with a first sensor, a variable amount of expansion and contraction of a moisture absorptive material located to be contacted by rain fall, the moisture absorptive material configured to expand in response to contact with the rain fall and contract in response to an absence of the rain fall; outputting, with a controller, signaling corresponding to the variable amount of the expansion and contraction of the moisture absorptive material; and transmitting wireless signals with a wireless transmitter, at least one wireless signal comprising data corresponding to the variable amount of expansion and contraction of the moisture absorptive material, wherein the first sensor, the controller and the wireless transmitter are at least partially covered by a housing.

(8) In another embodiment, a wireless rain sensor comprises a housing at least partially covering a first sensor, a controller and a wireless transmitter. The first sensor comprises: a moisture absorptive material located to be

contacted by rain fall and configured to expand in response to the contact with the rain fall and contract in response to an absence of the rain fall; and a component coupled to a first portion of the moisture absorptive material and configured to move with the expansion and contraction of the moisture absorptive material. The controller is coupled to the first sensor and configured to output signals corresponding to a variable amount of expansion and contraction of the moisture absorptive material. The wireless transmitter is configured to transmit wireless signals independent of a rain fall threshold, at least one wireless signal comprising data corresponding to the variable amount of expansion and contraction of the moisture absorptive material, wherein the rain fall threshold is not set at the wireless rain sensor.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features and advantages of several embodiments of the present invention will be more apparent from the following more particular description thereof, presented in conjunction with the following drawings.
- (2) FIG. 1 is a diagram of a rain sensor device for interrupting execution of one or more watering schedules of an irrigation controller according to several embodiments.
- (3) FIG. 2 is a variation of the rain sensor device of FIG. 1 according to several embodiments.
- (4) FIG. 3 is a functional diagram of the components of some embodiments of a rain sensor unit of the rain sensor device of FIGS. 1 and/or 2.
- (5) FIG. 4 is a functional diagram of the components of some embodiments of an interface unit of the rain sensor device of FIGS. 1 and/or 2.
- (6) FIG. 5 depicts a simplified flow diagram of a process for use in adjusting the mode of operation of the sensor unit of FIG. 3.
- (7) FIG. 6 depicts a simplified flow diagram of a process for use in detecting and inhibiting an irrigation cycle in accordance with one embodiment.
- (8) FIG. 7A is one embodiment of the interface unit of the rain sensor device of FIG. 4 illustrating user inputs and display outputs.
- (9) FIG. 7B is another embodiment of the interface unit of the rain sensor device of FIG. 4 illustrating user inputs and display outputs.
- (10) FIG. 8 is another embodiment of the interface unit of the rain sensor device of FIG. 4 illustrating user inputs and display outputs.
- (11) FIG. 9 depicts a simplified flow diagram of a process for use in initializing the rain sensor device illustrated in FIGS. 1 and 2.
- (12) FIG. 10 illustrates a simplified flow diagram of a process for use in the event that loss of communication occurs between the sensor unit and interface unit of rain sensor device or system illustrated in FIGS. 1 and 2.
- (13) FIGS. 11-19, 27A-B and 28 illustrate various embodiments of the components of a rain sensor unit for use with a receiver unit for interrupting execution of one or more watering schedules of an irrigation controller according to several embodiments.
- (14) FIGS. 20 and 21 graphically illustrate signal strength profiles used to approximate the propagation environment over communication distances less than the breakpoint distance at 915 MHz and 868 MHz, respectively according to one embodiment.
- (15) FIG. 22 illustrates an example implementation of a “TEST” operational mode utilized during the installation of the sensor unit in accordance with one embodiment.
- (16) FIG. 23 illustrates a simplified flow diagram of an example implementation of a sleep or normal operational mode at the sensor unit of FIGS. 1 and 2, according to some embodiments.
- (17) FIG. 24 illustrates a simplified flow diagram of a process for use in detecting and inhibiting an irrigation cycle in accordance with one embodiment.
- (18) FIG. 25 illustrates a simplified diagram of one implementation of the low temperature operational mode according to some embodiments.
- (19) FIG. 26 illustrates one implementation of a “TEST” operational mode in accordance with some embodiments.
- (20) FIG. 29A is another embodiment of the interface unit of the rain sensor device of FIG. 4 illustrating user inputs and display outputs.
- (21) FIG. 29B is another embodiment of the interface unit of the rain sensor device of FIG. 4 illustrating user inputs and display outputs.
- (22) FIG. 30 graphically illustrates example rain profiles and the points at which irrigation is interrupted or reactivated based on a rate of change of a sensed amount of rain fall, according to some embodiments.
- (23) FIG. 31 illustrates a simplified flow diagram of one embodiment of the overall operation of the rain sensor

system **10**.

(24) FIG. **32** illustrates a simplified flow diagram of one embodiment of a process for installing and pairing the interface unit and the sensor unit of FIGS. **1** and **2** together.

(25) FIG. **33** illustrates an exemplary embodiment of a modular irrigation controller having an interface unit module.

(26) FIG. **34** illustrates a rain sensor system in which an interface unit is paired and communicates with  $n$  sensor units **12a-n** according to some embodiments.

(27) FIG. **35** illustrates a rain sensor system in which a sensor unit is paired with and communicates with  $n$  interface units **14a-n** according to some embodiments.

(28) Corresponding reference characters indicate corresponding components throughout the several views of the drawings. Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of various embodiments of the present invention. Also, common but well-understood elements that are useful or necessary in a commercially feasible embodiment are often not depicted in order to facilitate a less obstructed view of these various embodiments of the present invention.

#### DETAILED DESCRIPTION

(29) The following description is not to be taken in a limiting sense, but is made merely for the purpose of describing the general principles of exemplary embodiments. The scope of the invention should be determined with reference to the claims.

(30) Referring first to FIG. **1**, a diagram is shown of a rain sensor system **10** for interrupting execution of one or more watering schedules of an irrigation controller **30** according to several embodiments. The rain sensor system **10** includes a sensor unit **12** having a first input/output unit **16** and an interface unit or system **14** having a second input/output unit **18**. The first input/output unit **16** and the second input/output unit **18** are coupled to each other by a communication link **15**. The interface unit **14** is coupled to an irrigation controller **30** (either directly to the controller via an interface **38**, e.g., a rain sensor input, or indirectly, e.g., coupled to the controller output lines **32** or a common line **34**, as illustrated in dashed lines). Alternatively, in some embodiments, the interface unit may be implemented as a part of the irrigation controller. For example, in one embodiment, the interface unit may be implemented as a module that may be inserted into a modular irrigation controller. The irrigation controller **30** is programmed to execute one or more watering schedules. In one form, the irrigation controller **30** may output activation signals (e.g., 24 volt power signals) to respective ones of a plurality of activation lines **32**, each coupled to a valve located in the region to be irrigated, an electrical switch to activate or deactivate lighting or other devices controlled by the controller **30**. As is well known, one or more sprinkler devices, drip lines and/or other irrigation devices may be coupled to each valve.

(31) The sensor unit **12** is typically located remotely from the interface unit **14** in a position where it is exposed to rainfall. For example, the sensor unit **12** may be mounted to a rooftop, light pole, or telephone pole. In some embodiments the sensor unit **12** periodically obtains measurements of parameters such as amount of rain fall, and/or precipitation, temperature, and/or other parameters, and transmits the information to the interface unit **14**. The interface unit **14** receives the data from the sensor unit and processes it to determine whether to inhibit or interrupt irrigation. Additionally or alternatively, in some embodiments, the sensor unit may initiate transmission to the interface unit **14** once it detects a change in some atmospheric parameters, e.g., amount of rain fall and/or temperature, and sends an update message to the interface unit. In one embodiment, the message may include the amount of rain fall, temperature, battery strength, signal strength and/or other data available at the sensor unit.

(32) In some embodiments, once the interface unit **14** detects the beginning of an irrigation cycle, it is instructed and/or is activated to communicate with the sensor unit **12** to request information regarding measurement parameters, such as but not limited to precipitation data, temperature and/or other such parameters. In one embodiment, the sensor unit **12** receives the request, obtains the requested measurement data and transmits the information to the interface unit **14**. In some implementations, the interface unit **14** receives instructions from the irrigation controller **30** requesting the interface unit **14** to transmit a request to the sensor unit **12** requesting the measurement data.

(33) In some embodiments, the interface unit **14** is located remotely from the sensor unit **12** and proximate to the irrigation controller **30** in a location that is, in some implementations, accessible to the user. The interface unit is also coupled to the irrigation controller **30** (either directly or indirectly). In some embodiments the interface unit may be implemented as a part of the irrigation controller and located on the irrigation controller. In one embodiment, for example, the interface unit may be implemented as a module that may be inserted into a modular irrigation controller.

(34) In some embodiments, each interface unit **14** is specifically paired to a sensor unit so that each rain sensor system **10** includes a paired sensor unit **12** and interface unit **14**. Alternatively, in some embodiments each interface

unit **14** is paired to more than one sensor unit **12**. In these embodiments, each sensor unit **12** is paired with the interface unit independently. FIG. **34** illustrates a rain sensor system **10** in which the interface unit **14** is capable of pairing and communicating with *n* sensor units **12a-n** via communication links **15a-15n**. Additionally, in one or more embodiments, each sensor unit **12** is paired with more than one interface unit **14**, wherein, the sensor unit is paired with each of individual interface unit **14** of the plurality of interface units. FIG. **35** illustrates a system **10** in which the sensor unit **12** is capable of pairing with and communicating with *n* interface units **14a-n** via communication links **15a-15n**. The pairing may be implemented at the time of purchase, at the time of installation, during battery replacement, or at other such times before the system begins functioning.

(35) The interface unit and sensor unit may be paired together using several different methods. For example, in one embodiment, the sensor unit **12** and the interface unit **14** may be paired using a wired serial interface, e.g., the I2C (Inter Integrated Circuit bus) interface and protocol. The pairing may be implemented using an additional 3 pin header connector (not shown) on both the sensor unit **12**, and the interface unit **14**, and a short 3-wire cable (not shown) with matching receptacle connectors on both ends, and a firmware procedure for executing the pairing upon connecting both units together. This method of pairing the two units diminishes problems created by side radio transmissions when implementing the pairing. Alternatively, the interface unit and the sensor unit may be paired by invoking a special mode of operation of the interface unit **14**, in which the ID information regarding the sensor unit's radio signal may be memorized and used for matching with the same sensor unit **12** in the future.

(36) In another embodiment, pairing is implemented by temporarily positioning the sensor unit **12** and the interface unit **14** close together and putting the sensor unit **12** in a high (preferably highest) power-transmission mode with packets following each other without any gap between them and having a special pairing-mode identification bit, while the interface unit **14** is held in a low (preferably lowest) sensitivity mode. The close proximity between the sensor unit **12** and the interface unit **14**, combined with high-power transmissions from sensor unit and low-sensitivity of the interface unit help to eliminate any interfering emissions. The chance of catching a side emission may be further diminished by using a specific identifier for pairing mode, which helps eliminate any regular transmission from other sensor units.

(37) FIG. **32** illustrates one possible implementation of a process **3200** of installing and pairing the interface unit **14** and the sensor unit **12** together. At step **3210** the interface unit initiates a set up request and transmits the request. The sensor unit **12** receives the request, in step **3212**, and continues to step **3214** where it determines whether or not certain criteria are met. For example, the request message may comprise information about the interface unit **14**. In one embodiment, the sensor unit **12** may use this information in step **3214** to determine whether it is able to pair up with the interface unit **14**. For example, in some embodiments, the user may exert a manual force on a part of the sensor wherein the force fully depresses the plunger, the sensor unit will query the rain sensor **318** and will use the measurement to determine whether the plunger in the rain sensor **318** is fully depressed to determine whether there is user authorization to pair up with an interface unit.

(38) Once the sensor unit determines that it is ready to pair up with the interface unit, it will generate and send or transmit an acknowledgment message to the interface unit in step **3216**. The message may comprise identification information about the sensor unit, and/or other data stored in memory of the sensor unit and/or available from the sensors and or other devices coupled to the sensor unit **12**. Additionally, in step **3216**, the sensor unit may store information about the interface unit **14**, for example, information received in the request message into its memory. In step **3218**, the interface unit then receives the acknowledge message, and pairs up with the sensor unit. For example, the interface unit may store information about the sensor unit, received in the acknowledge message and/or other available sources, into its memory. Additionally or alternatively, when performing step **3214**, the sensor unit may also determine whether it is ready for set up by ensuring that a user input, e.g. authorization, has been entered.

(39) Referring generally back to FIG. **1**, the interface unit **14** receives measurement data from the sensor unit **12** and processes this data to determine if irrigation (such as programmed into an irrigation controller **30**) should be permitted or interrupted. For example, in one embodiment, the interface unit **14** determines whether a predetermined relationship exists between the received measurements detected and a stored preset level or threshold and/or other criteria. For example, the interface unit may determine if the signal indicative of an amount of rain has exceeded a threshold level of rainfall, and/or whether a relationship exists between the signal and some criteria. For example, in one embodiment, the interface unit may use the information transmitted from the sensor unit **12** to determine a rate of change, for example, for the rain fall accumulation, and determine whether the rate of change satisfies a predetermined relationship.

(40) Additionally or alternatively, the interface unit may look at the relationship between the received measurements when processing the data to determine whether irrigation should be inhibited or interrupted. For example in one embodiment the interface unit receives the measurements and analyzes the relationship between one or more of the amount of rainfall, the rate of rain fall and the temperature. Alternatively in some instances, the information may be processed by the sensor unit **12**, where the determination regarding the relationship may be made by the sensor unit,

and the determination may then be transmitted to the interface unit **14** by the sensor unit **12**, e.g., in response to the request from the interface unit **14**. If the predetermined relationship exists (e.g., the threshold level of rainfall has been exceeded by the amount of sensed or measured rain fall), the electronics of the interface unit **14** and/or the controller **30** generate the appropriate signaling to cause the interruption of the execution of watering schedules by the irrigation controller **30**.

(41) This approach to overriding or interrupting watering based on measured data, such as sensed rain fall amounts is fundamentally different than the approach of known rain sensor devices that interrupt controller operation when a threshold level of rain has been exceeded. That is, traditional rain sensors, such as described in U.S. Pat. No. 6,452,499 to Runge et al., and U.S. Pat. No. 6,977,351 to Woytowitz (both of which are incorporated herein by reference), employ a remote rain sensor that sends a signal to its receiver to indicate that the rain threshold has been exceeded, where the rain sensor initiates the communication and sends a signal to its receiver as soon as a rain threshold has been exceeded. In contrast, according to several embodiments, the sensor unit **12** sends measurement information to the interface unit **14**, and the processing of the data and determination of whether or not to interrupt and/or adjust irrigation occurs at the interface unit **14**. Additionally, according to some embodiments, the interface unit **14** initiates the communication between the sensor unit **12** and the interface unit **14** periodically or when it detects that an irrigation cycle is to be initiated. The sensor unit **12** sends a signal to the interface unit **14** after receiving a request or query from the interface unit **14**.

(42) It is also known that the threshold level of existing rain sensors may be adjusted by making a mechanical adjustment to the sensor unit, such as described in U.S. Pat. No. 6,570,109 to Klinefelter (which is incorporated herein by reference). However, since the sensor unit is located on a roof top or other similar location such that it may be exposed to the environment and be relatively tamperproof, it is very difficult to easily adjust the threshold level of rainfall that will trigger the interruption of irrigation. Several present embodiments address this concern by providing a manual adjustment of the threshold level at the interface unit **14**, since in some embodiments the interface unit **14** is the portion of the rain sensor system **10** that determines if the threshold has been exceeded. In other embodiments, the adjustment may be made at the interface unit **14** and/or controller **30** and transmitted to the sensor unit **12**. The interface unit **14** is typically in a location that is far more easily accessible to the user; thus, the user may more easily adjust the rain threshold in use, e.g., to account for seasonal changes.

(43) Additionally, known rain sensors only interrupt irrigation when the rain fall exceeds a fixed threshold. In contrast, according to several present embodiments, the sensor unit **12** sends measurement data to the interface unit **14** and the interface unit **14** analyzes the atmospheric measurement data to permit or interrupt irrigation based on one or more different considerations such as the amount of rain fall, the current or sensed temperature, the rate of change in the rain fall amount or temperature or the combination of several criteria.

(44) In many embodiments, the sensor unit **12** sends data, and receives requests or queries for sensed data from the interface unit **14** through a communication link **15**. The communication links **15** described herein may be any wireline or wireless communication link. Generically, the interface unit **14** includes an input/output unit **18**, which will correspond to the specific communication link **15**. For example, in a wireline communication link **15**, the input/output unit **18** will be a wireline signal transmitter, a wireline signal receiver and a wireline connector. However, in a two-way wireless communication link **40** (see FIG. 2), the output takes the form of a wireless transceiver **44**, such as a radio, optical, infrared, and/or ultrasonic transceiver. Furthermore, the input/output unit **16** of the sensor unit corresponds to the communication link **15**. For example, in a wireline communication link **15**, the input/output unit **16** will be a wireline signal transmitter, a wireline signal receiver and a wireline connector. However, in a wireless communication link **40** (see FIG. 2), the input/output unit **16** takes the form of a wireless transceiver **42**, such as a radio, optical, infrared, and/or ultrasonic transceiver. Advantageously, the wireless communication link **40** of FIG. 2 allows for easier installation since a wireline connection is not required between the sensor unit **12** and the interface unit **14**. It is understood that in some embodiments, both the interface unit **14** and the sensor unit **12** each have a transmitter and a separate receiver, instead of a transceiver, and in some instances includes input/output interfaces for both wired and wireless communication.

(45) The interface unit **14** may be coupled to the irrigation controller **30** in different ways depending on the controller **30** and user preference. In some embodiments, the output lines **36** may be connected from an input/output unit **20** of the interface unit **14** direct to an interface **38** (e.g., a rain sensor input) of the controller **30**. In the event the interface unit **14** determines or receives an indication that a relationship exists between a threshold or other criteria and the measurement data and/or in the event that a threshold has been exceeded, a switch is closed within the output **20** completing a circuit causing a current to flow through the output lines **36** to the interface **38**. The controller **30** is configured to sense this current, and in response, the controller **30** temporarily halts the execution of one or more watering schedules and/or determines other appropriate actions. The current flowing through the output lines **36** is switched off after a period of time, in response to instructions or reset from the controller and/or in response to a data transmission, or a reply from the sensor unit **12** to a subsequent data request (e.g., when the precipitation data has returned to below the threshold level and/or the relationship between the threshold level and



other criteria and the measured data no longer exists). In this case, the controller **30** senses the absence of the current at the interface **38** and resumes normal execution of watering schedules. In another embodiment, the signal from the input/output **20** is a data signal that includes a message instructing the controller **30** to temporarily halt execution of one or more watering schedules until a subsequent resume data signal is sent.

(46) In a further embodiment, rather than coupling to an interface **38** of the controller, the interface unit **14** couples in series with the common line **34** of the activation lines **32**. For example, the common line **34** electrically passes through the output **20** (e.g., a switching device) of the interface unit **14**. When the interface unit **14** determines or receives an indication that a rain threshold has been exceeded and/or that other criteria have been met, the interface unit opens the switching device, breaking the common line **34**. This effectively disables all electrical signals via the activation lines **32** to the valves, until the switch is closed. In this way, the controller is not aware that the watering has been interrupted or overridden. It is noted that in some embodiments, the interface unit **14** may be integrated into the functionality of the controller **30**.

(47) Alternatively, in some embodiments, the interface unit **14** may forward the measurement data or the determination that some criteria has been met, e.g., a threshold has been exceeded or other relationship exists between the measurement data and some criteria, to the irrigation controller **30**, where the processor or the irrigation controller will interrupt rain fall based on the received information.

(48) In some embodiments the interface unit **14** may be implemented as a part of the irrigation controller **30** and/or located on or integral to the irrigation controller. In one embodiment, for example, the interface unit is implemented as a module that may be inserted into a modular irrigation controller. FIG. **33** illustrates an exemplary embodiment of a modular irrigation controller **3300** having an interface unit module **3312**. The modular controller **3300** comprises a display **3302**, a rotary dial **3304**, one or more user inputs **3306**, a base module **3307**, one or more expansion modules **3308**, a sensor connection **3310**, and an interface unit module **3312**, all generally contained within a housing **3314**. Generally, modular irrigation controllers are known in the art to be controllers that accept expansion modules to provide additional station or zone outputs. Further details of various modular controllers are described in U.S. patent application Ser. No. 11/022,179 and published as U.S. Patent Application Publication No. 2005/0273205, the entirety of which is incorporated herein by reference. In one embodiment, a base module **3307** is provided that includes output connectors for the master valve (MV), common line (COM), and a number of station outputs (**3** are illustrated in the base module **3307**). Each expansion module **3308** includes an additional number of output connectors to allow connection of activation lines to actuate additional stations (in this case, three additional station outputs are provided with each module **3308**).

(49) In one embodiment, the interface unit module **3312** is coupled a module mounting location instead of an expansion module. The interface unit module **3312** includes an antenna **3316** (one embodiment of an input/output unit **18**) to communicate with one or more sensor units **12**. In one embodiment, the interface unit module **3312** includes two connectors that allow wires **3318** and **3320** to connect to the terminals or connections of the sensor connection **3310**, where the sensor connection **3310** provides a way to connect to the common line **34** without having to cut the common line. It is noted that in this case, the wires **3318** and **3320** would replace a wire connecting the two terminals of the sensor connection **3310** together. In several embodiments, the interface module unit **3312** is now coupled in series with the common line **34**. When the interface unit module **3312** determines that irrigation should be interrupted or when it receives an indication that a rain threshold has been exceeded and/or that other criteria have been met, the interface unit module **3312** opens an internal the switch, breaking the common line **34**. This effectively disables all electrical signals via the activation lines **32** to the valves, until the switch is re-closed.

(50) Alternatively, in another embodiment, the sensor connection **3310** is configured for connection to the microcontroller of the modular controller **3300**. For example, when the interface unit module **3312** determines that irrigation should be interrupted, the interface unit module **3312** causes a current to flow to the sensor connection. The microcontroller detects that presence of current flow at the sensor connection, which indicates to the microcontroller that irrigation should be interrupted and the microcontroller causes the interruption. In several embodiments, the interface unit module **3312** gets operational power from the backplane connection of the module to the controller **3300**. The above embodiments, allow the interface unit module **3312** to operate when connected to a module mounting location of the modular controller **3300** without sending control signals directly from the module **3312** to the microcontroller, since many modular controllers will not have sufficient programming to process such direct control signals. However, in other embodiments, the interface unit module **3312** directly outputs irrigation interrupt signals to the microcontroller via the backplane connections between the module mounting location and the microcontroller.

(51) In one embodiment the interface unit module **3312** is inserted within the modular controller **3300**, draws power therefrom and is coupled to an interface unit **14** mounted externally. In this embodiment, according to one implementation, the interruption is controlled by the external interface unit **14**. In one embodiment, the interface unit **14** sends the determination to interrupt irrigation to the interface unit module **3312** and the interface unit

module **3312** interrupts irrigation according to one or embodiments described above (e.g., breaks the common, or outputs a signal to the microcontroller which interrupts irrigation). In another implementation, the interface unit module **3312** includes a display and buttons, etc., to create a user interface to allow a user to program the interface unit module **3312** while it is inserted into the modular controller **3300**. In another embodiment, the interface unit module **3312** outputs signals to the microcontroller of the modular controller **3300** and uses the user interface of the modular controller to allow the user to configure the interface unit module **3312**.

(52) Referring again back to FIGS. **1** and **2** and in a further embodiment, the interface unit **14** will continue to indicate to the controller **30** that it should remain off even after the precipitation data has returned below the threshold and/or other conditions no longer exist. For example, for a period of time after the precipitation data returns below the threshold level, the interface unit **14** continues to allow current to flow to the interface **38**, continues to send the appropriate control message signaling to the interface **38**, delays sending a control message instructing the controller to resume watering, or continues to break the common line **34**. This delay in re-enabling the controller is settable by the user on the interface unit **14** and allows the system to postpone irrigation for several days after a heavy rain has occurred. In other embodiments, the delay can be automatically controlled, for example, using equations involving one or more of temperature, dry out rate, etc. This embodiment allows for increased water conservation.

(53) In some embodiments, as illustrated in FIGS. **1** and **2**, the interface unit **12** and the sensor unit **14** are coupled via a two-way communication link **15**. The communication link **15** may be a wired communication, as illustrated in FIG. **1**, or a wireless communication as illustrated in FIG. **2**. The two-way communication link **15** enables the sensor unit **12** and the interface unit **14** to send and receive signals, including one or more of data, status information and control signals to and from one another. For example, in one embodiment, the interface unit **14** sends control signals to the sensor unit **12** and, depending on the control signal, the sensor unit **12** takes the appropriate action/s. For example, in one embodiment, the interface unit **14** may send a request to the sensor unit **12** for data. The sensor unit **12** may, in response to the request, generate the data and send it via the two-way communication link **15** to the interface unit **14**. Further, in some embodiments, the interface unit sends control signals to the sensor unit **12** over the two-way communication link **15**, wherein the sensor unit receives the signal and makes an adjustment or change based on the control signal received. In one embodiment, the control signal from the interface unit **14** causes the sensor unit **12** to change a mode of operation (e.g., such as entering a low power or hibernation mode). Additionally or alternatively, the sensor unit **12** sends signals, e.g., including data, information and/or control signals, to the interface unit **14**, and the interface unit is adapted to receive the information and take actions and/or make determinations based on the information. For example, the sensor unit **12** may transmit information corresponding to an amount of rain and/or temperature sensed at the sensor unit **12**. This information may be a measurement of rain fall or an indication that a threshold amount of received rain fall has been exceeded. In several embodiments, the interface unit **14** receives a measurement of rain fall and/or temperature and makes a determination of whether or not to interrupt irrigation based at least in part on the received measurements. The interface unit **14** is adapted to cause an interruption of irrigation if it is determined that irrigation should be interrupted. Further, the sensor unit **12** and interface unit **14** may both comprise transceivers **16** and **18** (wired or wireless) wherein the transceivers are capable of sending and receiving signals to one another over the two-way communication link **15**. Alternatively, in one embodiment, the sensor unit **12** and the interface unit **14** each have separate transmitter and a separate receiver.

(54) It is noted that in many embodiments, the interface unit **14** is configured to break the common line **34** of an irrigation controller. In alternative embodiments, the interface unit **14** is coupled to and can break one or more individual activation lines **32**. That is, the interface unit **14** may be coupled in series with one or more of the activation lines **32**. When the interface unit **14** determines or receives an indication that a rain threshold has been exceeded and/or otherwise determines that irrigation should be interrupted, the interface unit **14** opens the switching device, breaking one or more of the activation lines. In this embodiment, the interface unit **14** may be adapted to interrupt irrigation for a specific set of activation lines while allowing irrigation for valves coupled to other activation lines. The breaking of the one or more activation lines **32** disables the electrical signals from those one or more activation lines **32** to the valves, until the switch is closed.

(55) Referring next to FIG. **3**, a diagram is shown of the functional components of some embodiments of a sensor unit **12** of the rain sensor system **10** of FIGS. **1** and **2**. The sensor unit **12** includes a controller **312**, a memory **314**, and a transceiver **316**. The sensor unit further includes and/or cooperates with a rain sensor **318**. The controller may be implemented through a single-processor or multiprocessor systems, minicomputers, microprocessor, processor, programmable electronics and the like, and/or combinations thereof.

(56) The memory may be a separate memory unit within the sensor unit **12**, external memory connected to the sensor unit via an interface (not shown), may be internal memory within the controller **312** as illustrated in FIG. **3**, and/or other such configurations. The controller **312** and the memory **314** together function as a microcontroller. In some embodiments, memory **314** comprises one or more of a random access memory (RAM), read only memory

(ROM), Flash memory, an EEPROM memory, on-chip RAM, optical disk storage, and/or any other medium which may be used to store the desired information and which may be accessed by the controller. In some embodiments, the microcontroller employs flash memory for storage of executable firmware, and is capable of being programmed "in-system". This may be accomplished in some instances by employing an in-system programming port in the unit **12** and/or on a printed circuit board, for example of the controller, for accomplishing the programming process during a final assembly. In some embodiments, the microcontroller further includes an EEPROM for non-volatile storage of miscellaneous data to support at least some of the functionality of the controller. Additionally or alternatively, on-chip RAM may be present in sufficient quantity to provide functional capabilities in many embodiments.

(57) The sensor unit **12**, in some instances, further includes a power source **324**, such as a battery, solar cell, wind powered generated and/or other such power source, to power the components of the sensor unit **12**. For example, the sensor unit **12** operates from a high capacity lithium-ion battery. As illustrated in FIG. **3**, in some embodiments, the controller includes an on-chip analog-to-digital converter (ADC) **326**. The ADC may, for example, have an 8-bit resolution or greater, and contain four or more input channels. In other embodiments, the ADC may be a separate unit within the sensor unit **12**, or separate components within the sensor unit may comprise a separate ADC.

(58) The transceiver **316** provides wired and/or wireless communication. Wireless radio frequency chips known in the art such as Texas Instruments CC1100, Melexis TH71211, Micrel MICRF112, or MICRF211, Semtech CE1201A, Atmel ATA5428, Analog Devices ADF7020 or ADF7021, and/or Maxim MAX7033 or MAX7044 may be used for the transceiver **316**. The wireless transceiver includes or couples to an antenna. In some implementations, the transceiver comprises a single-chip transceiver that provides an analog or digital Received Signal Strength Indicator (RSSI) output signal. If the RSSI output is an analog signal, it may be supplied initially to one channel of the ADC **326**.

(59) In some embodiments the sensor unit **12** may include and/or may couple with several additional sensors, such as a temperature sensor **322**, a battery voltage sensor **320** as shown in FIG. **3**, and/or other such sensors. The battery voltage sensor **320** is connected to the power source **324**. The temperature sensor **322** may be any temperature-sensitive device such as a thermistor, temperature-dependent current device, and the like. In some embodiments, the temperature sensor is capable of detecting an ambient temperature of between about, 150 to 0° F., for example detecting an ambient temperature of about 35-39° F., e.g., 37° F., with a tolerance of  $\pm 5\%$  or better.

(60) The rain sensor **318** reacts to the presence of water and generally reacts proportionally to the amount of water (rain fall) received, for example in one embodiment, the rain sensor generates an electrical signal that is indicative of a level of precipitation or rain. This electrical signal represents precipitation data. In some embodiments, the output signal is an output voltage signal of the rain sensor **318** that is provided to one channel of the controller's ADC **326**. In some embodiments, the level indicated by the electrical signal is transmitted to the interface unit **14** via transceiver **316** periodically and/or when the sensor unit determines that a change has occurred in the amount of rain fall, and/or stored in memory for future access. For example, in this or other embodiments, the level indicated by the electrical signal is stored in the memory **314** and upon receiving a request from the interface unit **14** the controller **312** retrieves the data from the memory **314** and forwards the data to the transceiver **316** to be transmitted to the interface unit **14**. Additionally or alternatively, the rain sensor may detect that a threshold level of rain or precipitation has been received and in response generate a signal that indicates that the threshold level of rain has been exceeded.

(61) In other embodiments, the rain sensor may output signals from the temperature sensor **322** and/or the battery voltage sensor **320** that may, for example, additionally or alternatively be provided to two other channels of the ADC **326**, and the indicated levels stored in memory **314**, to be supplied to the interface unit **14** periodically, upon detecting a change, and/or upon receiving a request from the interface unit. In some embodiments, the signal or measured levels may not be stored, and instead the controller **312** may retrieve the information from one or more of the sensors at the time of transmission and/or when a request is received from the interface unit **14**. For example, in one embodiment the sensor unit **12** requests measurements from the sensors at fixed intervals, e.g., every 5 minutes, and may additionally process the data to determine whether a change has occurred since the last received measurement. The controller **312** may generate a data signal based on the electrical signals received from the sensors, and may transmit the data signal to the interface unit **14** via the communication link **15**.

(62) In some embodiments, the measured data transmitted to the interface unit **14** is simply a measurement and does not include an indication that a threshold has been exceeded. Instead, the determination whether irrigation should be permitted or interrupted (e.g., whether a relationship exists between certain criteria and the data, such as when a threshold has been exceeded) is made at the interface unit **14** and/or irrigation controller **30** based on the received measurements from the sensor unit **12**. Alternatively, in other embodiments, the controller unit **312** may be configured to determine if a predefined relationship exists between the measurement and a level or threshold, and transmit that determination to the interface unit **14** upon receiving a request from the interface unit **14**. The sensor unit **12**, in some implementations, does not transmit measurement data regarding the information obtained through

the sensors to the interface unit **14** unless and until it receives a request from the interface unit **14** for such data. Alternatively, the sensor unit **12** may transmit the measurement data to the interface unit **14** at intervals, e.g., 6 hour intervals, or when it determines a change in the measurement data in addition to providing the data to the interface unit **14** upon receiving a request for the data. Further, the information may simply include an indication that a threshold has been exceeded. In other implementations, the information provided may include a level or measure of rain.

(63) In some embodiments, the rain sensor **318** comprises a sensor and controller circuitry where upon sensing a level of precipitation the sensor will cause an electrical voltage to be generated by the control circuitry. The sensor and circuitry may take different forms in different embodiments. By way of example, in some embodiments, the rain sensor **318** includes a moisture absorptive material that expands and contracts based on the presence of and absence of rain fall, such as a hygroscopic material. The level or amount of expansion or contraction is sensed or measured and provided as an electrical signal. The level and/or measurement data is then transmitted by the transceiver **316** to the interface unit **14**, wherein in some implementations, the interface unit determines if a rain threshold has been exceeded and/or if other relationship exists between the measurement data and certain criteria. In some embodiments, the electrical signal corresponding to the level of rain fall is converted to a measure of the amount of rainfall prior to being sent to the interface unit **14**, and/or an indication of a relationship of the measurement relative to a threshold may be forwarded to the interface unit **14**. Alternatively, the expansion of the absorptive material may cause activation of a switch when a preset level of rain is reached. Upon activation of the switch the control circuitry may send a signal to the controller and then store the indication in memory. In this embodiment, when a request from the interface unit is received for rain levels an indication that the preset level was reached is transmitted by the transceiver **316** to the interface unit **14**. In some embodiments, the rain sensor will not generate any signals until information is requested from the rain sensor, at which time the sensor transmits a signal indicating the measurement of rain fall or the signal indicating that the switch is activated. Alternatively, the sensor unit **12** may initiate transmission to the interface unit **14** based on the measurement data. For example, in one embodiment, the sensor unit **12** will process the signal indicating the measurement of rain fall or signal indicating that the switch has been activated to determine if a change in the atmospheric conditions has occurred. In this embodiment, if the sensor unit **12** determines that a change has occurred it will forward the signal to the interface unit **14**. Additionally or alternatively, in one embodiment, the sensor unit will initiate transmission to the interface unit **14** forwarding the signal at fixed intervals, e.g., every 6 hours. In some embodiments, the interface unit **14** may send a request to the sensor unit **12** requesting that the sensor unit obtains current and/or updated data from the sensors prior to the initiation of an irrigation cycle and/or at other times, for example, when the user requests the data through the user input, and or by other means. In some embodiments, for example, when the interface unit determines that an irrigation cycle is about to begin the interface unit may send a message to the sensor unit **12** requesting current data to determine whether to inhibit irrigation. In one exemplary embodiment, the interface unit may send a message to the sensor unit **12** requesting data when the operator of the interface unit has requested the data. For example, in one exemplary embodiment, the operator may periodically request data, for example, through the user input **424** (see FIG. 4), to ensure that the sensor unit **12** and the system **10** as a whole are working properly. The receipt of a signal from the sensor unit **12** with data indicates that the sensor unit is properly working. Additionally, in some embodiments, the sensor unit **12** also sends its battery strength. This allows the operator send a test request message to the sensor unit **12** to determine if it is working. Additionally, in some embodiments, the sensor unit **12** sends data indicating the battery strength or battery life (and thus, approximately when the battery of the sensor unit will need to be charged or replaced).

(64) Alternatively, in embodiments where the sensor unit **12** initiates transmission to the interface unit **14**, the rain sensor may generate a signal comprising the measurements and/or other data and transmit the signal to the interface unit **14** upon making some determination, e.g., that a change in one or more parameters has occurred and/or other criteria has been satisfied, and/or at fixed intervals.

(65) The shape and configuration of the hygroscopic material may be varied depending on the implementation. In some embodiments, the hygroscopic material is in the form of one or multiple disks. In another embodiment, the hygroscopic material is a granular and expandable material within a flexible envelope or casing. For example, the granular material may include polyacrylamide or similar materials.

(66) In several embodiments, the sensor unit **12** operates in one of several modes. The mode of operation may depend on one or more factors, such as battery charge level or expected battery life, weather and/or atmospheric conditions, anticipated requests for data and/or other such factors. The modes may be adjusted internally by the controller **312** and/or externally by the user via the user input **424** and/or by other means. In one implementation, the sensor unit **12** is in a sleep or quasi-powered down mode, which in some implementations, is a “normal mode”, which is in some embodiments the mode that the sensor unit **12** is most often operating in. The sensor unit **12** reduces and/or attempts minimize power consumption while in the sleep mode to better conserve power and/or maximize battery life. In some embodiments, while in the normal or sleep mode the sensor unit **12** does not initiate

a transmission to the interface unit **14**, and in some instance, will never initiate a transmission to the interface unit **14**. In other embodiments, during normal or sleep mode the sensor unit will initiate transmissions to the interface unit **14**, for example at fixed intervals and/or when some criteria are met, e.g., when there is a change in one of rain fall, temperature, and/or other parameters.

(67) In some embodiments, while in the sleep mode, the transceiver **316** may be similarly put into a sleep mode, where many of the components of the transceiver are powered down, while the transceiver is still capable of detecting the presence of an incoming message without needing to apply full power to all circuitry. In several implementations, during the sleep mode the sensor unit **12** is capable of receiving requests initiated by the interface unit **14**. The sensor unit may further receive requests for other information and/or operating parameters, such as requests for the measurements received by the sensors employed with the sensor unit, the signal strength, the transmittal power, identification information of the sensor unit, and/or a variety of other information. In one embodiment, after receiving requests from the interface unit **14** and/or other devices, the controller **312** will determine what information is requested, and will retrieve the information and/or initiate a measurement of the requested information by the sensors. In some embodiments, the measurement(s) by sensors occurs periodically, and the measurement data is forwarded to transceiver **316** and transmitted to the interface unit via communication link **15**. Alternatively, in some embodiments, the data obtained is stored onto the memory **314**.

(68) FIG. **23** illustrates an example implementation of a process **2300** of operating in sleep or normal mode at the sensor unit **12**, according to some embodiments. Normally, in the step **2302**, the sensor unit is in sleep mode. Accordingly, the sensor unit operates in a low battery usage state with only minimal portions of the controller **414** running. Periodically, the sensor unit wakes up in step **2304**. For example, the controller and other electronics of the sensor unit enter a normal power usage mode. In step **2310**, once awake, the sensor unit **12** queries the sensor/s and other devices and generates measurements. In some implementations, these intervals are predefined. Alternatively, in other embodiments, the sensor unit may adjust the rate at which it will wake up and query the sensors based on the amount of rain fall, the temperature, the rate of change of rain fall and/or temperature, and/or other such criteria. In some embodiments, the sensor unit **12** then stores the measurements in the memory **314** for later processing. Alternatively, the sensor unit processes the data as soon as it is received from the sensors and other peripheral devices. Next, in step **2312**, the sensor unit **12** processes the measurement data received from the sensors. The sensor unit **12** may process the signals to generate measurements to be sent to the interface units, and/or process the data to determine whether the data satisfy certain relationships and/or criteria. For example, in one embodiment, the sensor unit **12** analyzes the data received from the rain sensor **318** and temperature sensor **322** to determine a rate of rain fall, a rate of temperature and/or whether there is a change in the amount of rain fall and/or temperature.

(69) In step **2314** the sensor unit **12** determines if a request for data has been received from the interface unit **14**. When the sensor unit determines that a request has been received, in some embodiments, the process continues to step **2320** where the sensor unit **12** transmits a signal to the interface unit. For example, the controller **312** of the sensor unit constructs a message comprising data such as the obtained measurement data, e.g., rain fall and precipitation data, temperature, battery strength, signal strength of the received request, and/or other data into one or more data packets to be forwarded to the transceiver **316** to be transmitted to the interface unit **14**. The sensor unit then returns to the low power or sleep mode of step **2302**.

(70) Alternatively, if no request has been received from the interface unit **14**, the process moves to step **2316** where the sensor unit determines if there has been a change in the sensor data, for example, if there has been a change in sensed atmospheric conditions and/or other criteria have been met. For example, in one embodiment the sensor unit may process the data to determine whether there is a change in the amount of rain fall or temperature determined in step **2312**. In one embodiment, the sensor unit may retrieve the results of the determination from the memory **314** to determine whether a change has occurred. Alternatively, the sensor unit may retrieve the data from the memory **314** for current and previous data and/or query the sensors for the data before making the determination in step **2316**. If the sensor unit **12** determines that a change has occurred in one or more of the sensor data, then the process will continue to step **2320** where the sensor unit will send or transmit a signal to the interface unit comprising, for example, the measurements retrieved from the sensors, signal strength, and/or other data available at the sensor unit **12**. The sensor unit then returns to the low power or sleep mode of step **2302**. If, however, in step **2316** the sensor determines that no change has occurred in the atmospheric parameters, the process moves to step **2318** where the sensor unit determines if it is time for a periodic update to be sent to the interface unit. In one embodiment, the sensor unit **12** sends updates to the interface unit **14** at fixed intervals, e.g., every 6 hours. The updates may be sent to ensure the interface unit that the sensor unit is working and that the connection between the sensor unit and the interface unit **14** has not failed. If in step **2318** the sensor unit **12** determines that it is time for a periodic update, then it moves to step **2320** and sends a signal to the interface unit **14**, and then returns to the sleep mode in step **2302**. Alternatively, if it is not time for an update, then the sensor unit returns to step **2302** when it enters sleep mode before then proceeding back to step **2304**.

(71) In some embodiments, the content of the message or packet may vary based on different criteria or situation.

For example, in one embodiment, the contents of the packet may depend upon the type of request received from the interface unit. For example, a **SENSOR\_STATUS\_REQUEST** message may be received at the sensor unit from the interface unit **14**. Upon receipt of this message, the sensor unit **12** initiates a measurement of the precipitation level, ambient temperature, full-load battery voltage and/or other parameter depending on the received request according to some embodiments. The sensor unit may query the sensors to obtain such measurements, and/or retrieve the measurements from the memory **314**. After these one or more measurements have been obtained, the sensor unit **12** constructs a message packet containing the results of the measurements along with the **RSSI** value that was observed during the receipt of the message. The entire message packet is then transmitted to the interface unit **14** in the form of a **SENSOR\_STATUS** message. In some embodiments, in addition to information requests, while in the sleep mode, the sensor unit **12** may also receive “set” commands from the interface unit **14**. These commands provide a value for one or more variables stored in memory within the sensor unit **12**, such as transmittal power, threshold values, etc. Upon receiving such messages, the sensor unit **12** will store the value and transmit an acknowledge message to the interface unit **14**.

(72) In some embodiments, the sensor unit periodically monitors its stored power level and/or battery life while in the sleep mode. A process **510** by which the sensor unit monitors the battery life, according to some embodiments, is illustrated in **FIG. 5**. In step **512** the sensor unit **12** transitions out of the sleep or low-power mode. In step **514** the sensor unit activates one or more sensors and/or other peripheral systems in or cooperated with the sensor unit **12**. In some instances, the transmitter and/or transceiver is not powered up or only the transceiver or portions of the transceiver are active.

(73) The power or battery voltage level of the power source **324** is measured in step **516**. In step **518**, it is determined whether to enter a low-battery mode. This determination may be made by comparing a measured full battery voltage level measured while the sensors and other peripheral devices have been activated with a non-volatile constant value stored in memory **314** to determine if the power source **324** is nearing the end of its useful life or is below a threshold. In some embodiments, in order to accurately make this determination, the controller **312** may make a measurement of the ambient temperature, via the temperature sensor, to calibrate the measured battery voltage. If the battery is approaching the end of its life (e.g., the full-load battery voltage is below the minimum allowable voltage) the process **510** continues to step **522** where the controller **312** switches the sensor unit **12** into a low battery mode and attempts to reduce power consumption by eliminating or reducing the functions performed and/or the frequency of performing non-essential functions.

(74) Once the sensor unit **12** enters a low battery mode, step **524** is entered where the sensor notifies the interface unit **14** that it has detected a low battery condition. In some instances, the sensor unit **12** initiates the transmission of a warning message to the interface unit **14** at or below the transmission power last assigned by the interface. In step **526**, it is determined whether an acknowledgement has been received from the interface unit **14**. If the acknowledgment is not received (typically within a predefined period of time), the process continues to step **528** where the transmission power is increased and the process returns to step **524** to again transmit the warning message at the increased power level. The power is increased with each subsequent attempt until an acknowledgment is received, a predefined number of attempts are made and/or a predefined transmission power level is reached. In some embodiments, the loop through steps **524**, **526** and **528** may be repeated after a period of time when an acknowledgement is not received.

(75) In some embodiments when an acknowledgment is received from the interface unit **14**, the sensor unit **12** continues to step **530** where it adjusts the number of periodic updates it sends to the interface unit. For example, in one embodiment, where the sensor unit may send **4** periodic updates each day to the interface unit during normal mode, once it enters Low Battery mode the sensor unit may only send **1** periodic update per day to the interface unit. In some embodiments, the sensor unit **12** may also reduce the frequency at which it wakes up to query the sensors and/or other peripheral devices for information such as amount of rain, temperature, battery strength and/or other such data once it enters the Low Battery Mode of operation. Alternatively, in some embodiments, after receiving the acknowledge message, the sensor unit **12** will not initiate further transmissions other than in response to requests received from the interface unit. The interface unit **14**, upon receiving the warning message, may notify a user, such as displaying a message on a user display of the interface unit **14** alerting the user of the operational mode of the sensor unit **12**. Returning to step **518**, if it is determined that the end of battery life is not approaching the system continues to step **520** where the sensor unit continues to operate and/or returns to operating in normal or sleep mode.

(76) In some embodiments, the sensor unit **12**, will perform the battery monitoring process **510** once per day to obtain a current battery voltage level and stores the measurement in memory **314**, and/or forwards the measurement to the interface unit **14**. Alternatively, in some implementations, it may not be necessary to perform battery monitoring process **510** often since the low battery usage of the sensor unit **12** allows the battery or power source to function for long periods of time, and usage of power sources such as solar or wind power energy allows longer battery life so that the monitoring of the battery life does not have to be performed frequently.

(77) Further, in some embodiments, the sensor unit may operate in a “Low Temperature” or “hibernate” mode. The sensor unit **12**, according to some possible implementations, may enter low temperature mode when it determines that the temperature is below a certain threshold. FIG. 25 illustrates one possible implementation of the low temperature operational mode, according to several embodiments. In step **2510**, while in normal mode, the sensor unit will periodically, e.g. every 5 minutes, query the temperature and/or other sensors to determine the current temperature and other current values. Next, in step **2512** the sensor unit **12** will process the measurements and uses the measurement to determine if a certain relationship exists between the measurements, e.g., temperature, and a freeze threshold level in step **2514**. For example, a freeze threshold level may be set at 36 degrees Fahrenheit. If in step **2514**, the relationship does not exist, the sensor unit will remain in normal mode (step **2516**) and cycle back to step **2510**. If in step **2514**, the sensor unit determines that the relationship exists, the process will move to step **2518** where it will generate and send a low temperature message or warning to the interface unit **14**. Next, in step **2520** the sensor unit receives an acknowledgment message from the interface unit. In one embodiment, when the sensor unit **12** sends the low temperature message or warning and does not receive an acknowledgment it may retransmit the message for a certain period of time, e.g., five minutes, and or a certain number or retransmissions until acknowledgment is received. In some embodiments, the sensor unit **12** will increase its transmit power with each retransmission up to its maximum allowed transmit power. In one embodiment, if the acknowledgment is not received after the certain period of time and/or the certain number of retransmissions the sensor will monitor the ambient radio noise to determine if a certain level of noise exists. If the sensor unit **12** determines that noise exists, the sensor unit will wait a certain amount of time and check back to see if the noise goes away. When the sensor sees an opportunity to send in a noise free time period, it will retransmit the temperature message. In one embodiment, when the sensor unit determines that a noise free time does not exist, and or is not capable of retransmitting after a certain period of time, the sensor unit **12** will assume that the interface unit **14** is broken, has lost power or is powered down. Accordingly, the sensor unit **12** will stop trying to communicate and listens periodically to see when the interface unit is ready for communications and can receive transmissions. In some embodiments, when the interface unit does not hear a response from the sensor unit, the interface unit will cease transmissions so as not to clutter the air waves and listens constantly for communications from the sensor unit **12**.

(78) After the sensor unit **12** receives the acknowledgement message, it enters the low temperature mode in step **2522**. In one embodiment, the sensor may decrease the rate at which it sends updates to the interface unit **14**. Additionally or alternatively, the sensor unit may also decrease the frequency at which it wakes up to query the sensors and/or other local or peripheral devices for data. While in the low temperature mode, in step **2524** the sensor unit will query the temperature and/or other data. Next, in step **2524** the sensor unit uses the sensed temperature data to determine if the condition still exists at fixed intervals, e.g. once per day. For example, the sensor unit **12** may measure the temperature and determine whether the temperature exceeds a certain threshold. When, in step **2526** the sensor unit determines that condition still exists, e.g., that the temperature is still below a certain threshold level, in step **2528** the sensor unit generates an update message comprising the measurement of temperature and possibly other data and transmits the message to the interface unit **14**. Further, in step **2528** the sensor unit may make certain determinations to adjust its mode of operation, while remaining in low temperature mode. For example, in several embodiments, the sensor unit will measure the battery strength to determine if it needs to enter into the low battery mode. Next, the sensor unit returns to step **2524** where it will periodically, e.g. once per day, and processes the measurements, in step **2526** to determine if the atmospheric conditions have returned to a normal condition, e.g. temperature is above the threshold. When in step **2526** the sensor unit determines that the conditions have returned to normal, e.g. the relationship between the temperature and/or other data and the threshold no longer exists, in step **2530** the sensor unit will query sensor and other local sensor and devices for data such as rain amount, temperature, battery strength, signal strength and/or other data and transmits an update message to the interface unit **14** in step **2532** comprising some or all of the data. Next, in step **2534** the sensor unit enters Normal mode and the process will begin again at step **2510**.

(79) The sensor unit **12** may also operate in a “test mode” in some embodiments. In many embodiments the test mode is utilized, in part, during the installation of the sensor unit **12** to provide the installer with a relatively quick and simple-to-understand process for testing that the sensor unit **12** is installed at a location with, for example, adequate radio reception from the interface unit **14**. The installation process is described in further detail below.

(80) Referring next to FIG. 4, a diagram is shown of the functional components of some embodiments of the interface unit **14** of the rain sensor device of FIGS. 1 and 2. The interface unit **14** comprises a transceiver **412**, a controller **414**, a relay device **416**, a memory **418**, a user display **426**, and a user input **424**. In some embodiments, the interface unit **14** may also include a current sensor **420**, and a voltage sensor **422**. The components of the interface unit **14** are coupled to one another by a bus or other means. The transceiver **412** may be any hard wire, wireless, optical and/or other device capable of transmitting and receiving signals to and from the interface unit **12** via the communication link **15** or **40**. Examples of wireless radio frequency chips known in the art include Texas Instruments CC1100, Melexis TH71211, Micrel MICRF112, or MICRF211, Semtech CE1201A, Atmel ATA5428,

Analog Devices ADF7020 or ADF7021, and/or Maxim MAX7033 or MAX7044 may be used for the transceiver **316**. The wireless transceiver includes or couples to an antenna. The controller **414** may be implemented through a single-processor or multiprocessor systems, minicomputers, microprocessor, processor, programmable electronics and the like, and/or combinations thereof. The controller **414** and the memory **418**, in some implementations, together function as a microcontroller. The memory **418** may be a separate memory unit within the interface unit **14**, external memory connected to the interface unit via an interface (not shown), may be internal memory within the controller **414**, and/or other such configurations. Further, the memory may comprise one or more of flash memory, EEPROM memory, RAM, ROM, on-chip RAM, and/or other such memory or combinations of memory.

(81) In some embodiments, the controller **414** employs flash memory for storage of executable firmware, and is capable of being programmed “in-system”. This may be accomplished in some instances by employing an in-system programming port in the interface unit **14**, on a printed circuit board of the controller **414** and/or other configurations to accomplish the programming process during, for example, a final assembly. In some embodiments, the controller **414** further includes an EEPROM or other non-volatile memory for storage of data, executables and/or other software to support of the functional capabilities of the controller **414**. Additionally or alternatively, on-chip RAM may be included on the controller **414** in sufficient quantity for functional capabilities in many embodiments. Generally, the controller **414** executes instructions stored in the memory **418** to implement the functionality of the interface unit **14**.

(82) FIG. **24** illustrates a process **2400**, according to some embodiments, by which, at least in some part, the interface unit **14** provides some control over irrigation. When the sensor unit **12** transmits a signal to the interface unit **14**, the signal is received at the interface unit in step **2412**. In some embodiments, the sensor unit **12** will transmit the signal at fixed intervals, e.g., every 6 hours, and/or when it senses a change, for example, a change in the amount of rain fall or temperature. Additionally, the sensor unit **12** will send signals to the interface unit **14** when the interface unit sends a request to the sensor unit requesting information as shown in optional step **2410**. Alternatively, the signal may be received in response to a request for data sent from the interface unit in step **2410**.

(83) After receiving the signal, in step **2416**, the interface unit processes the signal to retrieve data such as temperature, amount of rain fall, and/or other data, such as battery strength. After processing the data, step **2422** is entered where the interface unit determines if irrigation is currently interrupted, e.g., if a relay or switch is currently open. When irrigation is not interrupted, in step **2418**, the controller of the interface unit **14** will determine whether to interrupt irrigation. For example, in one embodiment, in step **2418**, the interface unit compares the measurements received from the sensor unit to certain threshold levels and/or other criteria to determine whether a relationship exists between the measurements, e.g., amount of rain fall and/or temperature, rate of change thereof and the thresholds. Further, in one or more embodiments, the interface unit **14** may use the data to determine a relationship between current data and previous data received from the sensor unit. For example, in one embodiment the interface unit may determine a rate of change in the atmospheric data, e.g., rainfall, temperature, and/or other data. In some embodiments the decision to interrupt the irrigation is based on whether the measurement data exceeds certain preset thresholds. Additionally and/or alternatively the determination may be based on other criteria. For example, in one embodiment the sensor unit uses the data to determine a rate of change, and bases the determination at least in part on the calculated rate of change.

(84) FIG. **30** illustrates one example of how the decision to interrupt irrigation may be based at least in part on the rate of change in the amount of rain fall. An example graph of rain fall amount in inches versus time in hours is illustrated with two different rain fall profiles A and B. In both profiles, the rain fall cutoff (or interrupt) threshold **3002** is set at  $\frac{1}{2}$  inch. In profile A, the rate of increase of rainfall is high (indicated by a steep slope on the increasing side of profile), and therefore, in some embodiments, the interface unit **14** will interrupt irrigation before the threshold level is reached, for example at point **3004**. Alternatively, in profile B, rate of increase of rain fall is less (indicated by the gradual slope of the increasing side of the profile), and in that situation, the interface unit **14** may inhibit irrigation after the rain fall amount reaches and/or exceeds the threshold **3002**, for example at point **3006**. Thus, when determining whether to interrupt irrigation, several embodiments, use at least the rain fall measurement and a rate of rain fall.

(85) Referring back to FIG. **24**, when in step **2418** the interface unit determines that irrigation should be interrupted it will generate an interrupt signal in step **2420**. For example, in one embodiment, the interrupt signal is a signal to open a relay or switch that to break the common line of the irrigation controller. Alternatively, if in step **2418** the interface unit determines that irrigation should not be interrupted (irrigation should be permitted) it may continue to step **2430** where it may determine whether irrigation should be adjusted. Criteria similar to the determination of whether irrigation should be interrupted may be used to make the determination in step **2430**. If the interface unit determines that irrigation should be adjusted, it may generate a signal, in step **2432**, that cause an adjustment to the irrigation schedule or amount of irrigation. Alternatively, if the interface unit determines that an adjustment is not necessary it returns to step **2412** or optional step **2410** and repeats the process once a request is initiated and/or a transmission from the sensor unit is received. Alternatively, in some embodiments, once in step **2418** the interface



unit determines that irrigation should not be inhibited it returns to step **2412** or optional step **2410** and repeats the process once a request is initiated and/or a transmission from the sensor unit is received.

(86) Returning to step **2422**, when the interface unit determines that irrigation is currently interrupted, in step **2424** the interface unit **14** determines whether irrigation should be reactivated. For example, the interface unit uses the data from step **2416** and determines whether certain relationship exists between the data and certain levels and or thresholds. For example, the interface unit determines whether a relationship exists between a rain fall threshold and the amount of rain fall indicated by the data received from the sensor unit **12**.

(87) Additionally or alternatively, the interface unit may look at the rate of change in one or more atmospheric parameters to determine whether to reactivate irrigation. For example, in FIG. **30** the rate of rain fall in profile A indicates a gradual decrease in the amount of rain fall at the sensor unit **12** (i.e., it represents a gradual decrease or drying out of the sensor material, possibly indicating further rain or slowing rain). As such, the interface unit may reactivate or permit irrigation after the amount of rain fall is below the threshold level, for example, at point **3008**. Alternatively, in profile B the rate of rain fall decrease is greater (as indicated by the decreasing slope of profile B). Therefore, the interface unit may reactivate or permit irrigation before the rain fall amount has fallen below the threshold **3002**, for example at point **3010**. A rapidly decreasing slope could indicate that the rain fall quickly stopped and perhaps that the air is dry such that irrigation should be permitted sooner.

(88) Returning to FIG. **24**, if in step **2424** the interface unit determines that irrigation should be reactivated or permitted it may generate a signal to reactivate irrigation in step **2426**. For example, in one embodiment, the signal may cause a relay or switch breaking the common line of a controller to close. This would allow irrigation activation lines of the controller to function. Alternatively, if in step **2424** the interface unit **14** determines that irrigation should remain interrupted, it will return to step **2412** or optional step **2410** and repeats the process once a request is initiated and/or a transmission from the sensor unit is received.

(89) FIG. **6** illustrates an alternative process **610** to, at least in part, to provide some control over irrigation as implemented through the interface unit **14**, according to some embodiments. When an irrigation cycle is initiated or commanded by the irrigation controller **30**, the interface unit **14** is notified (e.g., a current flows in the common line **34** that is detected by the interface unit). In step **612**, the interface unit detects the initiation of an irrigation and/or the notification that an irrigation is about to be initiated, for example, the current sensor **420** detects the current flow through the common line. Following detection of the signal, in step **614** the current sensor **420** notifies the controller **414** and the controller initiates a transmission of a request to the sensor unit **12** by the transceiver **412**. Alternatively, in some embodiments the current sensor sends a signal to the controller **414** indicating the measurement of current flow and the controller determines whether an irrigation is about to be initiated. Following the detection of initiation of an irrigation cycle step **614** is entered where the controller **414** initiates a transmission of a request to the sensor unit **12** by the transceiver **412**. In step **616**, the transceiver **412** receives a signal carrying data transmitted by the sensor unit **12** in response to the request, and supplies the data to the controller **414**. In some instances, the signal provides measurement data taken by the sensor unit **12** and/or an indication that a threshold has been reached, and the measurement data or indication is stored or cached in the memory **418**. In some embodiments, the interface unit **14** may send a request to the sensor unit **12** requesting that the sensor unit obtains current and/or updated data from the sensors prior to the initiation of an irrigation cycle. In some embodiments, for example, when the interface unit determines that an irrigation cycle is about to begin the interface unit may send a message to the sensor unit **12** requesting current data to determine whether to inhibit irrigation.

(90) In step **618**, the interface unit **14** determines whether the irrigation cycle should be inhibited. Alternatively, the measurement data is forwarded to the irrigation controller **30** to evaluate and determine whether irrigation is to be interrupted. The signals received at the interface unit **14** from the sensor unit **12** may comprise an indicating a threshold level has been exceeded, data corresponding to a level of precipitation and/or rain fall, and in some instances may further include other measurement data, such as temperature data sensed by the sensor unit **12**. In one embodiment of determining in step **618** of whether to inhibit irrigation, the controller **414** compares the measurement of precipitation and/or rainfall to some criteria, e.g., a stored threshold level, to determine whether a predetermined relationship exists between these variables (e.g., if the amount of measured rain fall exceeds a threshold level of rain). In some embodiments, the determination of whether the irrigation cycle should be inhibited comprises one or more criteria, wherein the interface unit **14** and controller **414** processes the data received from the interface unit to determine whether certain criteria is met and based on this determination the interface unit may generate an interrupt message inhibit irrigation. In one embodiment, for example, the interface unit **14** uses the information received from the sensor unit to determine a rate of change of the received atmospheric measurements, the interface unit may then generate an interrupt message to inhibit irrigation when it senses a certain level of change in the received measurements, e.g., a positive rate of change in amount of precipitation or the rate of change of temperature, and/or other such data. In some embodiments, the instruction set operating in the interface unit **14** is calibrated to correlate the information received from the sensor unit **12** to a level of rainfall that may be related to the threshold level or other criteria. For example, in embodiments where the signal received at the interface unit **14**

represents a raw electrical signal output from the sensor unit **12**, the transceiver **412**, the controller **414** and/or other intermediate device processes this signal to correlate this signal to a corresponding level of rain fall. Alternatively, this correlation may be performed by the sensor unit **12**, and the resulting correlation is forwarded to the interface unit **14**. In some embodiments, when the rain fall relationship does not exist the controller **414** may further compare other parameters, such as the received measurement of temperature to a stored temperature threshold level to determine whether a predetermined relationship between these variables exists (e.g., if the measured temperature is below a threshold temperature). In other embodiments, the determination of whether a relationship exists between the measured rain level and a preset threshold, or whether other variables such as temperature exceed a preset threshold, is made at the sensor unit **12** and the signal received by the interface **14** from the sensor unit **12** provides these determinations from which the controller **414** determines whether to inhibit irrigation.

(91) Once the controller **414** determines that irrigation should be inhibited in step **618** (e.g., the threshold level of rainfall has been exceeded by the amount of sensed or measured rain fall or the threshold level of temperature is above the measured ambient temperature), the process **610** continues to step **620** where the controller **414** generates an interrupt signal. In some forms, a relay device which is normally closed is opened, interrupting irrigation. In some embodiments, the relay device is implemented as a switching device which is opened to inhibit the irrigation. In step **622** when irrigation is being commanded by the irrigation controller **30** while the interface unit **14** is commanding that irrigation be inhibited, a voltage sensor **422** monitors the voltage across the relay contacts. In step **624**, it is determined whether the irrigation cycle has terminated. When the irrigation cycle has not terminated, the process **610** returns to step **622** to monitor the irrigation cycle. When the irrigation cycle has terminated, the process moves to step **626** where the interface unit **14** closes the relay device. Following step **626** the process returns to step **612** where the interface unit determines whether an irrigation cycle is initiated (e.g., the current sensor device **420** monitors the current flow to determine if an irrigation cycle is detected).

(92) Returning to step **618**, when it is determined that irrigation should not be inhibited, the system returns to step **612** to determine whether an irrigation cycle is detected. In some embodiments, the determination that irrigation should be inhibited (e.g., that a relationship exists between the measured variables and the thresholds) is made at the sensor unit **12**, and upon transmitting a request to the sensor unit, the interface unit **14** will receive an “irrigate” or “inhibit” command.

(93) In some embodiments, when it is determined in step **618** that the irrigation is not to be interrupted (e.g., the level of rain fall or ambient temperature do not meet the predetermined relationship), optional step **630** is entered where the interface unit determines whether the level(s) of the measurement data (e.g., rain fall, temperature and/or other data) are such that the irrigation should be adjusted. This may be done by comparing the precipitation data and/or the temperature to a second set of thresholds. Additionally or alternatively, the interface unit **14** may forward one or more of the measurement data to the irrigation controller **30** allowing the irrigation controller to determine whether irrigation is to be adjusted.

(94) When it is determined in step **630** that the irrigation is to be adjusted, step **632** is entered and the interface unit **14** adjusts the run time of the irrigation cycle and/or notifies the irrigation controller **30** that the runtime should be adjusted (e.g., by forwarding measurement levels and/or adjustments to be implemented). When it is determined in step **630** that adjustments are not to be made or following step **632** the process **610** returns to step **612** to detect the start of an irrigation cycle.

(95) Referring back to FIG. **4**, the user input **424** allows a user to input and adjust the stored threshold level(s), enable or disable the sensor(s), and/or adjust other settings. Generically, in one embodiment, the user input **424** comprises at least one selectable user input that allows the user to make adjustments and/or selections. The user input **424** may comprise one or more of buttons, switches, levers, rotating dials, etc. The user display **426** may indicate the operational status of the interface unit **14**, e.g., the display may indicate that the receiver unit is powered on, what threshold level is selected, if the receiver unit is in an irrigation interrupt state, etc., and/or the operational status of sensor unit **12** such as the operational mode of the sensor unit. The user display **326** may be one or more of a display screen, liquid crystal display (LCD), touch screen display, lights, LEDs, and/or other relevant displays. In some, embodiments for example, the display comprises a backlit LCD, for example, which is capable of displaying alphanumeric characters with 11-segment LCD digits. It is noted that although the input/output unit **18** (whether wired or wireless) is illustrated as a transceiver (wired or wireless), in some embodiments the input/output **18** may comprise a separate transmitter and receiver.

(96) FIG. **7A** is an illustration of some embodiments of the interface unit **14** for use in the rain sensor system **10** of FIGS. **1** and **2**. In this embodiment, the user input **424** is embodied as including an ON/OFF switch **712**, an up button **714** and a down button **716**. The user display **426** is embodied as a small display screen **718**. The ON/OFF switch **712** turns the power to the interface unit **14** on and off. The up and down buttons **714** and **716** are used to set and adjust one or more threshold levels and/or other parameters and settings. These thresholds and/or parameter may be utilized and/or forwarded to the sensor unit **12** to adjust a remote rain sensor to different threshold levels at the sensor unit **12** of the rain sensor system **10**, such as described in U.S. Pat. No. 6,570,109; however, the threshold

level is set electronically and at the interface unit **14**. For example, by pressing the buttons **714** and **716**, the user switches between multiple discrete levels of rain thresholds, e.g., a low threshold, a mid threshold and a high threshold. In other embodiments, the up and down buttons **714**, **716** cause an up and down gradient or analog adjustment to the stored threshold level. The display **718** may be configured to indicate which threshold level the interface unit **14** is currently set, notify the user of battery strength or low battery, indicate if the interface unit **14** is in watering interrupt mode or not, and other such information. In some embodiments, the display screen **718** is not included.

(97) In other embodiments, such as shown in FIG. 7B, an additional selection button **715** is provided that allows a user to select different adjustable features or settings of the interface unit **14**. For example, the selection button **715** provides different adjustment functionality to buttons **714** and **716**. The display **718** indicates what parameter or setting the user may adjust with buttons **714** and **716**. For example, by repeatedly pressing the selection or menu button **715**, the user may navigate between different selectable or adjustable settings or features. For example, as described above, the selection button **715** allows the user to make adjustments to the rain fall threshold level. Pressing the button **715** again may allow the user to change the rain delay period after the water threshold has been exceeded and returned back below the threshold, to change the temperature threshold level, and/or change other parameters or settings. The button **715** may also allow features to be turned on or off with the buttons **714** and **716**. For example, button **714** may be used to turn a feature selected by button **715** on, while button **716** turns that feature off.

(98) Referring to FIG. 8, in some embodiments of the interface unit **14**, the threshold level is set by moving a multi-position switch **812** or other type of drag bar between multiple positions. Each switch position electrically signals to the processor what threshold level corresponds to the proper switch position. In many embodiments, precipitation amounts between, for example,  $\frac{1}{8}$ " to  $\frac{3}{4}$ " are selectable in discrete increments or continuous manner. Further, in some embodiments, the user input **424** comprises a three-position toggle switch **814** to allow the user to configure the unit for the desired operation. The switch **814** has a center, left and right position. In some embodiments, placing the switch into the center position places the interface unit **14** into a normal operational mode where irrigation is inhibited if sufficient precipitation has been detected by the sensor unit **12**. Placing the switch into the left position places the interface unit **14** into a bypass mode where irrigation is not inhibited by the system. The setting the switch into the right position places the interface unit **14** into a test mode. In some embodiments, the right position is a spring-loaded return to center, automatically releasing to center position e.g., normal mode, when the switch is no longer held in position. The user display **426**, in some embodiments, may include an LCD backlit display screen **816**. In many embodiments, the user input **424** may further include a pushbutton switch **820** to allow the user to activate the LCD backlight for a period of time.

(99) FIG. 29A is an illustration of alternate embodiment of the interface unit **14**. This embodiment comprises for example an LCD touch screen embodying both user input and user display functionality. In other embodiments, the user input may comprise selectable buttons, dials and/or switches, and the user display may be a graphical display and/or other means of displaying data to the user. The user input **424** is embodied as including a rain threshold selector **2936**, a temperature threshold selector **2926**, rain sensor activation selector **2932** and temperature activation selector **2930**. The rain threshold selector **2936** and temperature threshold selector **2926** enable the user to set or adjust the threshold level for the amount of rain or temperature respectively. These thresholds may be utilized at the interface unit **14** for making decisions regarding whether to inhibit/interrupt or permit/allow irrigation, and/or may be forwarded to the sensor unit **12** to adjust a remote rain sensor to different threshold levels at the sensor unit **12**. The rain activation selector **2932** and the temperature activation selector **2930** further allow the user to adjust the mode of operation wherein the user may select to inhibit irrigation based on the amount of rain or precipitation and/or the temperature. For example, using the selectors **2930** and **2932** the user may choose to interrupt irrigation based on both precipitation and temperature data by activating both selector and/or one or neither of the measurements by deactivating either or both of the selectors **2930** and **2932**. It is noted that the rain threshold selector **2936** and the temperature threshold selector **2926** may be generically referred to as selectable inputs that allows a user to adjust a respective threshold level.

(100) The display **2900**, as illustrated in FIG. 29A, is embodied as a connectivity indicator **2938**, a signal strength indicator **2920**, a connection indicator **2924**, a rain indicator **2934**, a battery strength indicator **2922**, a temperature indicator **2928**, and a system status indicator **2940**. The connectivity indicator **2938** indicates whether there is a connection between the interface unit **12** and the sensor unit **14**. The signal strength indicator **2920** displays the signal strength of the wireless connection between the sensor unit **12** and the interface unit **14**, where the number of bars represents the strength of the signals received from the sensor unit **12** at the interface unit **14**. The connection indicator **2924** displays the number of sensors **12** currently connected to the interface unit **14** and further displays which of the sensors **12a-n** is currently able to communicate with the interface unit. For example, two sensor units are illustrated, the upper left one in active communication with the interface unit, while the lower left one is not connected to the interface unit. The rain fall indicator **2934** and the temperature indicator **2928** display the amount

of rain fall and the temperature currently present at the sensor unit **12** relative to the thresholds (indicated by **2936** and **2926**). The signal strength indicator **2920** displays the signal strength between the interface unit **14** and the sensor unit **12**. The battery strength indicator **2922** may display the battery strength of the battery at the interface unit, sensor unit, and/or the rain sensor system **10** as a whole. For example, in one embodiment, the battery strength indicator displays the battery strength measurement that it receives from the sensor unit. The system status indicator **2940** displays the mode of operation, i.e., whether the system inhibits irrigation based on rain fall, temperature, and/or both, and additionally displays whether irrigation is inhibited currently.

(101) As illustrated in FIG. **29A**, the top section of the system status indicator **2940** indicates whether the system is controlling irrigation based on the measurement of rain, temperature, or both. For example, FIG. **29A** shows the system status indicator displaying that the system is currently only inhibiting based on the amount of rain, i.e., only the rain symbol is present at the top of the indicator. The system status indicator further indicates whether the system is currently interrupting irrigation, where the sprinkler symbol on the indicator is either showing irrigation or displays that no irrigation is occurring, for example, the system status indicator as illustrated in FIG. **29A** indicates that irrigation is currently not interrupted since the sprinkler symbol is showing irrigation.

(102) FIG. **29B** illustrates an alternative embodiment **2901** of the display **2900** of the interface unit **14** for use with the system **10**, for example in embodiments when the interface unit **14** is coupled with multiple sensor units. As illustrated, in some embodiments the connection indicator **2924** displays the interface unit, and also displays multiple sensor units coupled to the interface unit (in this case sensor units **1**, **2**, **3** and **4**). The interface unit also displays the battery strength and signal strength **2920**, and battery strength **2922** for each of the sensor units **12**.

(103) With respect to the embodiments of FIGS. **7A**, **7B**, **8**, **29A** and **29B** and others described herein, prevention of tampering of slide switches and/or push buttons may be provided by using a mechanical cover (not shown) over the switches/buttons. Additionally or alternatively, in some embodiments, buttons have to be pressed and held for a period of time (e.g., 2-5 seconds) before any changes occurs. This prevents the accidental altering of receiver unit settings.

(104) The interface unit **14** may be powered by connection to the controller **30**, e.g., it draws power from the 24 VAC power source of the controller **30**. In other embodiments, battery, solar, wind powered or other power sources and/or combinations of sources may be used to supply power to the interface unit **14**.

(105) In some embodiments, the sensor unit **12** includes an indicator light, such as a bi-color LED, that is visible to a user and also includes the driver circuitry and power to drive the indicator light. This indicator light is useful when initializing the sensor unit **12** and/or the interface unit **14**. For example, in some embodiments, the interface unit **14** includes a test mode button that when pressed sends a signal to the sensor unit **12**. In one embodiment, when the sensor unit **12** receives the signal, it illuminates the indicator light. An installer may mount the sensor unit **12** to a given location. The test button on the interface unit may be activated allowing the installer to return to the sensor unit to verify that the indicator light is illuminated, verifying that the communication between the sensor unit **12** and the interface unit **14** is valid.

(106) In some embodiments, additionally or alternatively, when the sensor unit receives the signal from the interface unit it determines the signal strength of the signal and displays the signal via the indicator light. For example, in one embodiment the indicator light blinks a certain number of times representing the signal strength of the test signal. An installer may use the signal strength indication to locate one of a plurality of possible installation locations with the best signal strength. Additionally, in some embodiments the installer may move the sensor unit where the signal strength varies with the change in location, and further where the determining and displaying of the signal strength is done automatically, so that the installer may install the interface unit, push the test message and then move the sensor unit in the remote location until the installer finds a location with the best signal strength where the sensor unit **12** may be installed.

(107) Additionally and/or alternatively, once power is applied to the interface unit **14**, the interface unit starts sending signals to the sensor unit **12** for a period of time. If the sensor unit **12** is in range, the indicator light is illuminated. For example, an installer may determine whether the location of the sensor unit **12** is adequate and/or in communication with the interface unit **14** based on the decision criteria of whether the bi-color LED is illuminated (e.g., illuminated green). If the location is determined to be inadequate, the bi-color LED is not illuminated or is illuminated a second color (e.g., illuminated red).

(108) FIG. **9** illustrates a flow chart of the process **900** by which the interface unit communicates with the sensor unit once communication is established between the interface unit **14** and the sensor unit **12**, according to some embodiments of the rain sensor system **10** illustrated in FIGS. **1** and **2**. In some embodiments, the process **900** initiates at step **910** where a determination is made as to whether there is a sensor unit **14** to receive an activation and/or start up message from the interface unit. This determination may include retrieving from memory **418** identification information for one or more sensor units **12** with which the interface unit is associated. Step **910** may be an optional step. For example, when there is only a single sensor unit **12** that is associated with the interface unit. Additionally or alternatively, the interface unit may instead skip to step **912** and broadcast a request as described

below to each sensor unit associated with the interface unit **14**. This identification information may include the version number of the sensor unit, an identification number of the sensor unit and/or other information uniquely assigned to the sensor unit. Further, this information, in some instances, is stored in the memory **418** at the time the sensor unit **12** is installed, or assigned to an interface unit **14**. If there are no sensor units associated with the interface unit, the process **900** moves to step **920** where a message is displayed on the user display **426** alerting the user that there are no sensor units **12** associated with the interface unit **14**.

(109) In step **912**, once power is applied to the interface unit **14** the interface unit enters an initialization mode and transmits a request to one or more sensor units **12**. In step **914**, the interface unit **14** checks to see if an acknowledgment message is received from the sensor unit **12**. When an acknowledgment is received in step **914** the process then continues to step **916**, where the interface unit **14** processes the message and displays the appropriate data on the display **426** (e.g., a confirmation of connection message, an identification of the one or more sensors from which responses are received and/or other such information). When the sensor unit **12** is in range, as introduced above, the indicator light may also be illuminated at the sensor unit.

(110) If it is determined in step **914** that an acknowledgment is not received, the process continues to step **918** where an incremental counter is increased by one, and it is determined whether the request signal has been transmitted a predefined number of times. If the request has not been sent the predefined number of times, the process returns to step **912** to again transmit the request. The subsequent transmission may be delayed for a period of time and/or the subsequent request may be transmitted at a higher transmit power in attempts to connect with the sensor unit **12**. Alternatively, when an acknowledgment is not received after a predetermined number of connection attempts the process continues to step **920** where it displays a message alerting the user.

(111) Following step **916**, following the initialization mode, the interface unit **14** enters the normal or sleep mode. In normal mode the interface unit will function in accordance with the process as described in FIG. **6**. In many embodiments, the interface unit **14** also provides a test mode to enable the user to determine whether or not a proposed location for the sensor unit will result in satisfactory signal reception and communications reliability. This is made possible, in such embodiments, by having a two way communication between the sensor and interface unit. In the test mode, the interface unit **14** initiates a test message transmitted to the sensor unit and receiving an acknowledgment to verify that the sensor unit **12** and interface unit **14** may communicate. The test mode may be initiated automatically by the system in the initialization step. In some embodiments, the user may also initiate a test mode by using the user input **424**.

(112) In many embodiments message traffic between the interface unit **14** and sensor unit **12** occurs in pairs, e.g., when a message is sent, there is an acknowledgement. In the event that the sender of an initial message does not receive an acknowledgement corresponding to the message sent, the originator of the message may assume that the message was lost and attempt to retransmit the message. FIG. **10** illustrates a process **1000** that is implemented in the event that loss of communication occurs between the sensor unit **12** and interface unit **14** of rain sensor device or system **10** illustrated in FIGS. **1** and **2**. In step **1010** after sending a message, the originator of the message, e.g., the sensor unit **12** or the interface unit **14**, determines whether an acknowledgment is received. When an acknowledgement is received, the process **1000** continues to step **1050** to continue normal operations. Alternatively, if an acknowledgment is not received, typically within a predefined period of time, then the process continues to step **1012** where the originator resends the message.

(113) In step **1014** the originator checks to see if an acknowledgment is received. When it is determined in step **1014** that an acknowledgment is received, the process continues to step **1050** and resumes its normal operation. If no acknowledgment is received then the process continues to step **1016** to determine whether a predefined time limit for reattempting to send the message is reached and/or whether the message is retransmitted a predefined number of times. When it is determined in step **1016** that the predefined time period and/or number of attempts is not reached, the process returns to step **1012** to continue attempting to transmit the message. Alternatively, when, an acknowledgment is not received within the predetermined period of time and/or within the limited number of attempts, the system continues onto step **1018** where the originator attempts to determine whether there is interference in the communications channel.

(114) In some embodiments, both the sensor unit **12** and interface unit **14** periodically monitor the RSSI values obtained from the receiver and/or transceiver **316**, **412** during periods where no message traffic is being passed. These values are noted and stored in memory so that information about the noise levels at the sensor unit **12** and interface unit **14** locations are available with which to assess the communications channel at a given time. In some embodiments, when no message traffic is being passed, the interface unit **14** samples the RSSI value randomly, at scheduled times, at intervals, e.g., at intervals of one minute, or the like. Additionally or alternatively, the sensor unit **12** may samples the RSSI value, randomly, at scheduled times or at intervals, e.g., at intervals of one hour. In step **1018** the originator of the message may samples the RSSI value, for example from its receiver chip, and assesses whether or not there is interference or noise levels that exceed limits. When it is determined that high noise level is present the system continues to step **1020** where the originator increases the transmittal power.

(115) In step **1022**, the device attempts retransmission of the message at the increased transmitter power. In some embodiments, this step comprises retrieving the maximum transmittal power from memory. In step **1024** the system checks to see if an acknowledgment is received. When an acknowledgement is received, the process continues to step **1050** to transition to a normal mode of operation. If the retransmission attempt does not result in an acknowledgment, step **1026** is entered where it is determined whether the noise level has returned to or is below a threshold and/or a nominal value. In some embodiments, the process may repeat steps **1022** and **1024** in attempts to resend the message for a certain period of time or a predetermined number of attempts before continuing to step **1026**. When it is determined in step **1026** that the noise level over the communication link has subsided or reduced to desired levels, the process returns to step **1012** to retransmit the message. In some embodiments when returning to step **1012** the interface unit sends a message to reset the transmittal power of the sensor unit.

(116) Alternatively, when it is determined in step **1026** that the noise level has not reduced, the originator device continues to sample RSSI values, e.g., at predetermine time intervals and the process then proceeds to step **1030**. In step **1030**, it is determined whether a period of time has elapsed without detecting a reduction in noise level (e.g., reduction to a desired level). If the time limit has not elapsed the process returns to step **1026** to determine whether there has been a reduction in noise over the channel. Alternatively, when the time period has elapsed, the process enters step **1032** where an error message is displayed and/or otherwise indicated and the process terminates. In some embodiments, during this process the user display **426** of the interface unit **14** displays status information, such as a noise message or levels, error message, acknowledgement not received and/or other such information. (117) Returning to step **1018**, when it is determined that the noise level is not in excess, it is presumed that the receiving device at the other end of the communication channel (e.g., wireless link) has failed. The system then continues to step **1040** where the transmitting device attempts to reestablish communication. In step **1042**, it is determined whether an acknowledgement is received for the reconnection. When the reconnection is achieved, the process **1000** returns to step **1012** to resend the message (or in some instances to step **1050** for normal operation). Alternatively, the process continues to step **1044**, where it is determined whether a time limit has expired while attempting to reestablish communication. When the time limit has not been reached the process returns to step **1040**. When the time limit has been reached, the process continues to step **1032**, and an error message is displayed and/or otherwise indicated and the process terminates.

(118) In some embodiments, the sensor unit **12** in performing steps **1016**, **1030** and/or **1044** may attempt implement a shorter amount of time and/or number of tries before ceasing to transmit, and waits until the interface unit **14** attempts to reconnect. Additionally or alternatively, the sensor unit **12** may not perform all of the steps of the process **1000**, and may termination communication earlier in the process to await communication from the interface unit **14**. In some embodiments, the user display **426** of the interface unit **14** displays a NO SIGNAL message or other indicator during the time the interface unit is waiting for an acknowledgement and/or is attempting to reconnect until reconnection is achieved or the process terminates.

(119) The next several figures illustrate and describe various types of sensors and circuitry for sensing or generating a signal indicative of the amount of rain fall. These drawings have been simplified and do not illustrate all components of the device. For example, all components of the circuitry and outputs such as a power source (battery and/or solar cell) and wireless transmitters are not illustrated. Depending on the embodiment, a signal representing a sensed value that corresponds to an amount of rain fall received is transmitted to the interface unit **14**. In some forms, the interface unit is configured to properly interpret the information in the signal and correlate that information to a corresponding level of rain fall received. In other embodiments, the signal is converted to a corresponding level of rain fall prior to being transmitted to the interface unit **14**. Still further in some implementations, the sensor unit **12** determines whether a threshold level of rain is received and transmits an indication of whether the threshold is exceeded in response to an inquiry from the interface unit **14**.

(120) Referring next to FIG. **11**, a diagram is shown of a sensor unit **1102** for use in a system to interrupt execution of one or more watering schedules of an irrigation controller according to several embodiments. In this embodiment, the sensor unit **1102** includes a housing **1104** having an opening **1106** to allow rain fall to enter a volume **1108**. Although not illustrated, a ceramic or other porous filter is located in the opening **1106** to allow rainfall to be received into the volume **1108** while preventing dirt and other debris from entering the volume. Within the volume **1108** is a moisture absorptive material that expands and contracts based on the presence of and absence of rain fall, such as a hygroscopic material **1110** comprising a plurality of hygroscopic discs. It is understood that the shape and configuration of the hygroscopic material may vary according to the specific implementation. For example, the hygroscopic material **1110** may comprise discs (as illustrated, or may comprise other suitable materials, such as an expandable granular material (e.g., polyacrylamide, etc.) contained within an envelope or flexible container.

(121) The material **1110** expands in the presence of water, expanding further as the presence of water increases, and contracting as water is evaporated from the volume **1108**. Vents (not illustrated) are provided to allow evaporation, i.e., allow the volume **1108** to dry when rainfall is not present. A plunger **1112** is coupled to the material **1110** and a

spring **1114** to bias the material **1110** upwardly. A metal piece **1116** (e.g., a metal plate or short section of metal cylindrical tubing) is mounted on the lower surface of the mechanical plunger **1112**. This metal piece **1116** is situated in proximity to a capacitor **1118** mounted on the printed circuit board **1120** comprising the sensor electronics. In some embodiments, the printed circuit board **1120** may comprise a controller, memory, transceiver and/or other relevant elements. The capacitor **1118** forms the capacitive arm of an oscillator. The capacitor **1118** is such that the electric field surrounding its plates should have sufficient extent so that the metal piece **1116** mounted on the plunger **1112** will affect its capacitance. Expansion of the hygroscopic material **1110** causes the spacing between the piece of metal **1116** and the capacitor **1118** to change, altering the capacitance of the plunger/capacitor system. Changes in the capacitance of the system will result in a change of the frequency of oscillation of the oscillator, the frequency of corresponding to the amount of precipitation. The sensed frequency provides an analog continuous measurement corresponding to the amount of rain fall. The value of this sensed frequency is transmitted to the interface unit for a determination of whether a rain threshold has been exceeded. Additionally or alternatively in some embodiments, the rain sensor unit **1102** detects when a threshold amount of water is received. For example, contact of the piece of metal **1116** with the capacitor **1118** or circuit board **1120** causes the closing of a switch indicating that a threshold amount of water has been exceeded such that a signal indicating that the threshold has been exceeded is then forwarded to the interface unit in response to the request from the interface unit. In another embodiment, item **1118** is a mechanical switch or button that when contacted by item **1116**, presses the switch. In this embodiment, the fact that the switch is pressed, closed or contacted indicates to the electronics that the threshold has been exceeded.

(122) Referring next to FIG. **12**, a sensor unit **1202** includes a strain gauge **1204** coupled to the printed circuit board **1120** and that engages the plunger **1112** when the material **1110** expands. Expansion of the material **1110** changes the force applied to the strain gauge **1204** by the plunger **1112**. The plunger **1112** may initially contact the strain gauge **1204** or not and a spring **1114** may optionally be included between the strain gauge **1204** and the plunger **1112**. This change in force on the strain gauge **1204** is detected by appropriate electronics on the printed circuit board **1120**. The sensed force provides an analog continuous measurement corresponding to the amount of rain fall. The value of this sensed force is transmitted to the interface unit **14** for a determination of whether a rain threshold has been exceeded and/or a determination of whether a threshold is exceeded may be transmitted to the interface unit **14**.

(123) Referring next to FIG. **13**, a sensor unit **1302** includes an inductor **1304** wrapping around the material **1110** and coupled to the printed circuit board **1120**. The inductor **1304** is fabricated from a fine wire and forms one arm of an oscillator circuit on the circuit board **1120**. Expansion of the hygroscopic discs (material **1110**) changes the inductance and internal dissipation of the inductor, changing the frequency and amplitude of the oscillator. This change is detected by appropriate electronics on the printed circuit board **1120**, providing an analog continuous measurement corresponding to the amount of rain fall and/or an indication of exceeding a threshold. The value of this sensed frequency and/or amplitude is transmitted to the interface unit **14** for a determination of whether a rain threshold has been exceeded.

(124) Referring next to FIG. **14**, a sensor unit **1402** includes graphite stack resistor **1404** coupled to the printed circuit board **1120** and that engages the plunger **1112** when the material **1110** expands. Expansion of the hygroscopic discs (material **1110**) changes the force applied to the graphite stack resistor **1404** by the plunger **1112**. The plunger **1112** may initially contact the stack resistor **1404** or not and a spring **1114** may optionally be included between the stack resistor **1404** and the plunger **1112**. This change in force on the graphite stack **1404** changes its electrical resistance, and is detected by appropriate electronics on the printed circuit board **1120**, providing an analog continuous measurement corresponding to the amount of rain fall. The value of this sensed resistance is transmitted to the interface unit **14** for a determination of whether a rain threshold has been exceeded.

(125) Referring next to FIG. **15**, a sensor unit **1502** includes a magnet **1504** on a surface of the mechanical plunger **1112**. This magnet **1504** is situated in close proximity to a Hall Effect device **1506** mounted on the printed circuit board **1120** comprising the circuitry or electronics of the sensor unit **1112**. Expansion of the hygroscopic discs (material **1110**) causes the spacing between the magnet **1504** and the Hall Effect device **1506** to change, changing the output of the Hall Effect device **1506**. This change in the output of the Hall effect device **1506** is detected by appropriate electronics on the printed circuit board **1120**, providing an analog continuous measurement corresponding to the amount of rain fall. The value of this output is transmitted to the interface unit **14** for a determination of whether a rain threshold has been exceeded.

(126) Referring next to FIG. **16**, a sensor unit **1602** is shown in which the base of the mechanical plunger **1112** is in contact with a wiper **1604** of a fixed resistive sensing element **1606**. In some embodiments, the resistive element and the wiper form a linear potentiometer. Expansion of the hygroscopic discs (material **1110**) changes the position of the linear wiper **1604** on the potentiometer **1606**, changing its resistance. This change in resistance is detected by appropriate electronics on the printed circuit board **1120**, providing an analog continuous measurement corresponding to the amount of rain fall. The value of this resistance is transmitted to the interface unit **14** for a

determination of whether a rain threshold has been exceeded.

(127) Referring next to FIG. 17, a sensor unit **1702** is shown which does not use a hygroscopic material, and instead uses a capacitor **1704** including a set of plates or electrodes. In the illustrated form, the electrodes are formed as coaxially aligned cylindrical tube electrodes **1706** and **1708**, electrode **1706** being the outer coaxial tube and electrode **1708** being the inner coaxial tube. These tubes are illustrated in cross section view. The capacitor **1702** forms the capacitive arm of an oscillator implemented on the circuit board **1120**. The volume **1108** and electrodes **1706** and **1708** are configured such that water collects in the space between the electrodes **1706**, **1708**, changing the capacitance of the coaxial system. The high dielectric constant of water will effect a large change in the capacitance of the system under conditions of small accumulations of precipitation. Changes in the capacitance of the system will result in a change of the frequency of oscillation, providing an analog continuous measurement corresponding to the amount of rain fall. The value of this changing frequency is transmitted to the interface unit **14** for a determination of whether a rain threshold has been exceeded.

(128) Referring next to FIG. 18, a sensor unit **1802** is shown which does not use a hygroscopic material. In this embodiment, a material whose electrical resistance changes when exposed to water is employed to detect precipitation. As illustrated, a resistance cell **1804** is located within the volume **1108**. Electrodes **1806** and **1808** couple from the resistance cell **1804** to the circuit board **1120** and measure the resistance across the cell. Resistance across the resistance cell **1804** decreases as it becomes wet relative to the initial readings when the sensor unit is initialized. Changes in the resistance of the cell **1804** correspond to changes in the level of rain fall received, providing an analog continuous measurement corresponding to the amount of rain fall. The value of this changing resistance is transmitted to the interface unit **14** for a determination of whether a rain threshold has been exceeded.

(129) Referring next to FIG. 19, a sensor unit **1902** is shown in which the base of the mechanical plunger **1112** is in contact with a ferrous plunger **1906**. This plunger **1906** is situated such that it moves within an inductive coil **1908** connected to the printed circuit board **1120**. The inductor **1908** is fabricated from a fine wire and forms one arm of an oscillator circuit on the circuit board **1120**. Expansion of the hygroscopic discs (material **1110**) changes the position of the plunger **1906** altering the inductance of the plunger/inductor system. Changes in the inductance of the system will result in a change of the frequency of oscillation of the oscillator. This frequency change is detected by appropriate electronics on the printed circuit board **1120**, providing an analog continuous measurement corresponding to the amount of rain fall. The value of this frequency is transmitted to the interface unit **14** for a determination of whether a rain threshold has been exceeded.

(130) Referring next to FIGS. 27A and 27B, a sensor unit **2700** is shown in which the mechanical plunger **1112** is in contact with the wiper **1604** of the fixed resistive sensing element **1606**. As illustrated in FIG. 27B, in one embodiment a spring **2712** is coupled to the wiper **1604** and the plunger **1112** pushes the wiper towards the resistive sensing material maintaining appropriate contact between the resistive sensing material and the wiper. In some embodiments the wiper and the resistive sensing element are parts of a linear potentiometer. Expansion of the hygroscopic discs (material **1110**) changes the position of the linear wiper **1604** on the resistive sensing element **1606**, changing its resistance. In some embodiments, this change in resistance is detected by appropriate electronics on the printed circuit board **1120**, where it is processed to generate an indication representing an amount of rain fall. For example, in one embodiment, the processing results in an analog continuous measurement corresponding to the amount of rain fall. The indication representing the amount of rain fall derived from this resistance is transmitted to the interface unit **14** for a determination of whether irrigation should be permitted or interrupted. In some embodiments, the indication may also be used by the sensor unit to determine whether some internal criteria are met, for example, when changing the mode of operation of the sensor unit. In some implementations, the sensor unit also includes an antenna **2704**, a light indicator **2706** and a temperature sensor **2708** coupled to the printed circuit board. Further, in some embodiments, the sensor unit comprises a battery housing **2710** which holds the batteries from which the sensor unit draws its power.

(131) According to several embodiments, the wiper **1604** can be generically referred to as a first element, while the resistive sensing element **1606** may be generically referred to as a second element. In a preferred embodiment, the first element is a moving element and the second element is fixed in a location. Generically, the plunger causes the first element to move relative to the second element causing a change in a variable (in this case, an electrical resistance) corresponding to an amount of rain fall. In some embodiments, the controller implemented on the circuit board measures the variable and generates signals comprising an indication of the amount of rain fall based on the measured variable.

(132) Referring next to FIG. 28, a sensor unit **2800** is shown in which the mechanical plunger **1112** is in contact with a first electrode **2804** (e.g., an electrode plate). In response to expansion/contraction of the hygroscopic disks, the moving plunger moves the first electrode **2804** relative to a second electrode **2808** (e.g., an electrode plate) fixed to the electronic circuit board **1120**. The fixed second electrode **2808** is covered with a layer of insulator material **2806**, e.g., Mylar insulation, where the insulator material is in contact with the moving first electrode **2804** such that it maintains a gap between the fixed electrode **2808** and the moving electrode **2804**. As illustrated in FIG. 8, in one



embodiment, a spring **2810** coupled to the fixed electrode **2804** and the plunger **1112** pushes the moving electrode **2804** towards the fixed electrode **2808** and the insulator material maintaining appropriate contact between the fixed electrode covered with the insulator material and the moving electrode. Expansion of the hygroscopic discs (moisture absorptive material **1110**) changes the position of the moving electrode **2804** relative to the fixed electrode **2808**, changing the surface area of the fixed electrode **2808** that is covered by the moving electrode **2804**. Accordingly, this changes the capacitance generated between the two electrodes given a voltage difference therebetween. For example, a voltage is applied to the fixed electrode. In some embodiments, this change in capacitance is detected by appropriate electronics on the printed circuit board **1120**, where it is processed to generate an indication representing an amount of rain fall. For example, in one embodiment, the processing results in an analog continuous measurement corresponding to the amount of rain fall. The indication representing the amount of rain fall derived from this capacitance is transmitted to the interface unit **14** for a determination of whether irrigation should be permitted or interrupted. In some embodiments, the indication may also be used by the sensor unit to determine whether some internal criteria are met, for example, when changing the mode of operation of the sensor unit.

(133) According to several embodiments, the first electrode **1804** can be generically referred to as a first element, while the second electrode **1808** may be generically referred to as a second element. In a preferred embodiment, the first element is a moving element and the second element is fixed in a location. Generically, the plunger causes the first element to move relative to the second element causing a change in a variable (in this case, an electrical capacitance due to a changing surface area of the first element positioned above the second element) corresponding to an amount of rain fall. In some embodiments, the controller implemented on the circuit board measures the variable and generates signals comprising an indication of the amount of rain fall based on the measured variable.

(134) In many embodiments, the rain sensor system **10** is capable of measuring rainfall and according to one or more selected settings to permit or prevent an irrigation controller **30** from irrigating. Rainfall settings are, for example, from  $\frac{1}{8}$ " to  $\frac{3}{4}$ " and are selectable at the interface unit **14**. The rain sensor system **10** comprises the remote sensor unit **12**, and an interface unit **14** mounted near an irrigation controller **30**. Communication between the remote sensor unit **12** and interface unit **14**, according to some embodiments, is a two way wireless radio link that may eliminate the need to route wires/cable between the units. The wireless sensor unit **12** may be in one of the following forms or a combinations thereof, a wireless rain sensor (transmitter/receiver combination pack), a wireless rain/freeze sensor (transmitter/receiver combination pack), a wireless rain sensor receiver, a wireless rain/freeze sensor transmitter, and/or a wireless rain/freeze sensor receiver.

(135) FIG. **31** illustrates one possible implementation of the overall operation of the system **10** according to several embodiments. In step **3112** the sensor unit **12** generates an indication of the amount of rain and/or other data such as temperature. In one embodiment, the rain sensor generates such data periodically e.g. every 5 minutes. In other embodiments, the sensor unit may generate such indications in response to a request from the interface unit **14**. Next, in step **3114** the sensor unit transmits a signal comprising at least the generated indication to the interface unit **14**. In some embodiments, the sensor unit may initiate transmission to the interface unit **14** once it detects a change in some atmospheric parameters, e.g., amount of rain fall and/or temperature, and sends an update message to the interface unit. Additionally or alternatively, the sensor unit **12** may transmit the indication to the interface unit **14** at fixed intervals, e.g. every 6 hours. The sensor unit may also transmit the indication to the interface unit **14** in response to a request from the interface unit **14**. In one embodiment, the message may include the sensed amount of rain fall, sensed temperature, battery strength, signal strength and/or other data available at the sensor unit.

(136) In step **3116**, the interface unit **14** receives the signal containing the data from the sensor unit. In step **3118**, the signal is processed to obtain the indication of data from the sensor unit, such as amount of rain or precipitation, and/or temperature. Next, in step **3120** the interface unit **14** determines whether a relationship exists between the indications and a threshold and/or other criteria. If in step **3120** the interface unit **14** determines that the relationship exists, then in step **3122** the interface unit generates an interrupt command to cause irrigation executed by an irrigation controller to be interrupted. Alternatively, when the interface unit **14** determines that the relationship does not exist, the interface unit **14** does not take any actions and returns to step **3116**. Thus, in this way, the interface unit allows or permits irrigation executed by the irrigation controller to occur. In some embodiments, steps **3118** and **3120** may be generically be referred to as the step of determining, based at least on the indication from the signal, whether irrigation should be interrupted.

(137) The interface unit **14** typically is mounted on a wall near to, and wired to, an irrigation controller **30**. The interface unit may include methods for outdoor and/or indoor mounting. For example, a mounting plate may be provided to be secured into position with one or more screws. The interface unit **14** then slips and/or otherwise is connected onto the mounting plate. Further, the interface unit **14** typically includes a housing. The housing may be made of plastic and may include means to secure the device to a wall without the mounting plate (e.g., a pair of keyhole slots). The housing may be made of polymetric material. It is desired that if the external housing is of a polymetric material, it meets UL standards for flammability, UL 94-5V or better, UV resistance, water absorption,

and other applicable UL safety standards. The housing is set up for outdoor/indoor mounting.

(138) An installation mode is activated in the interface unit **14** that the sensor unit **12** responds to by displaying the signal strength received from the interface unit. The sensor unit **12** may be mounted with one or more attached brackets in a location that indicates good signal and that catches direct rainfall. The mounting bracket employed by the sensor unit **12** is designed so that a minimum number of tools are needed for installation. The material employed for this bracket is light in weight and resistant to corrosion from water and sunlight.

(139) After installation a simple signal test may be performed to verify communication is working properly between the sensor unit **12** and the interface unit **14**. In some embodiments, the sensor unit **12** has batteries that last for 5 years or more under the following conditions: one (1) "TEST" mode activation per year for the duration of five minutes and a total of ten (10) one-second transmissions per day at a power level of +10 dBm. According to many implementations, the system does not require end-user calibration. Normal maintenance consists of debris removal, elimination of plant encroachment, and periodic battery replacement.

(140) The rain sensor unit **10** is used in conjunction with 24 VAC irrigation controllers **30** to conserve water usage by automatically preventing the irrigation controller from irrigating once the rainfall reaches a pre-set level.

(141) In some embodiments, the interface unit **14** operates by receiving periodic communication from the sensor unit and processing the data received to decide whether or not to irrigate based on internal rules including, for example, past history, rate of rainfall, thresholds, and/or other criteria. Additionally or alternatively, in some embodiments, the interface unit **14** may operate by interrogating the sensor unit **12** and then deciding to water or not water based on internal rules including past history. In some situations, for example, the sensor unit **12** will show dry conditions and the interface unit **14** will not allow watering due to recent rainfall. Watering may be prevented by breaking the continuity of the common circuit or connecting to the sensor input of the irrigation system, which prevents the solenoid valves of the irrigation system from operating.

(142) In some embodiments, the system operates in either the 868 MHz or 915 MHz license-free ISM bands. It is understood other embodiments will operate in other frequency bands, for example, some embodiments operate at 2.4 GHz and others operate in the 400 MHz ISM band. The system operates reliably at a straight-line distance of 300 feet or more with the sensor unit **12** installed ten feet above the ground and the interface unit **14** installed five feet above the ground.

(143) In one example implementation of the rain sensor device or system **10**, communications reliability is defined as a message reception rate of 99% or more between the sensor unit **12** and the interface unit **14** while the system is situated in a residential environment with buildings, trees and other obstructions. This 99% reliability performance metric is with respect to an environment where Rayleigh fading is present, having a link budget fading margin of 20 dB.

(144) In the 915 MHz band the received signal strength profile that is used to approximate the propagation environment over communication distances less than the breakpoint distance is graphically illustrated in FIG. **20**, with the breakpoint distance defined as

(145)  $\frac{4h_{TX}h_{RX}}{\lambda}$

where  $h_{sub.TX}$  is the transmitter height above ground,  $h_{sub.RX}$  is the receiver height above ground, and  $\lambda$  is wavelength. For the 868 MHz band, the received signal strength profile used is graphically illustrated in FIG. **21**.

(146) The sensor unit **12** and interface unit **14** may each employ a low-cost, single chip radio transceiver device that is capable of operating across the 868 MHz and/or 915 MHz ISM bands without requiring tuning or component changes. The transceiver devices **316**, **412** are capable of generating either direct sequence or frequency hopping spread spectrum signals. In some embodiments, it is desired that the transceiver device meets UL 1950 safety standard and CSA C22.2. In one embodiment, the devices may have a maximum transmitted power level of 10 milliwatts (+10 dBm) or more into a **5052** resistive load. The frequency of operation and transmitted power level are adjustable through firmware. The device is capable of achieving compliance with all applicable FCC regulations for unintentional and intentional radiators in the 868 MHz and/or 915 MHz bands. In some embodiments, the transceiver **412** may be implemented as a single-chip transceiver **412** employed on the sensor unit **12** providing an analog and/or digital Received Signal Strength Indicator (RSSI) output signal. In one embodiment where the RSSI output is an analog signal, it is provided to one channel of the microcontroller's ADC.

(147) In many embodiments, the sensor unit **12** operates from a high capacity lithium-ion battery. It may employ power conservation techniques to provide a battery lifetime of five years or more while meeting its other functional operating capabilities. A voltage sensing or other battery monitor circuit such as battery voltage sensor **320** is employed, in some embodiments, to measure the battery voltage while it is under load. According to some implementations, the output voltage signal of this monitor circuit is provided to one channel of the microcontroller's ADC **326**.

(148) In some embodiments, the sensor unit **12** may include an adjustable cap/collector, and a micro sensor on the PWB protected by a waterproof seal that measures rainfall total.

(149) According to some implementations, the sensor unit **12** utilizes a low-cost 8-bit microcontroller **312** that has

sufficient computational power and speed to support the functional capabilities of the unit. It is equipped with one or more very low power “sleep” modes capable of being terminated by externally and/or internally-generated interrupt events. The microcontroller or microprocessor may employ a quartz crystal for generation of an internal clock signal.

(150) In some embodiments, the microcontroller **312** additionally employs FLASH memory for storage of executable firmware, and is capable of being programmed “in-system”. An in-system programming port may be available on the printed circuit board for accomplishing the programming process during final assembly. The in-system programming port may be accessible via surface pads (through the use of “pogo” pins on an ICT fixture). A programming header may also be available on the printed circuit board to permit reprogramming the microcontroller during firmware development. In some implementations, Circuit boards may be designed for ease of testability such as using automated test fixture equipment.

(151) Additionally the microcontroller may include on-chip EEPROM for non-volatile storage of miscellaneous data for support of its functional capabilities, according to some embodiments. On-chip RAM may also be present in sufficient quantity for the microcontroller's functional capabilities. The microcontroller may also include an on-chip ADC **326** with 8-bit resolution or greater. In this and/or other implementations, the ADC **326** contains four or more input channels.

(152) In some embodiments, the sensor unit **12** includes a rain sensor **318** employing hygroscopic material suitable for the detection of precipitation. This material typically has a useful lifetime around that of the power source **324**, about five years or more. Upon exposure to precipitation, expansion of the hygroscopic material causes a change in a variable. This change in variable or a value derived from the change in the variable is provided to one channel of the microcontroller's ADC **326**.

(153) The hygroscopic material and the mechanical structures designed to contain it and translate its expansion to a linear displacement are calibrated, in some embodiments. This calibration establishes the ability of the structure to detect between about  $\frac{1}{8}$  and  $\frac{3}{4}$  inches of precipitation with a repeatability of  $\pm 20\%$  or better. Unit-to-unit variations in the detection of identical amounts of precipitation are  $\pm 20\%$  or less.

(154) In one embodiment, in order to detect ambient temperature, the sensor unit **12** may also employ a temperature-sensitive device **322** such as a thermistor, temperature-dependent current source, and/or other such device. For example, a “direct digital” temperature sensor may be employed as the temperature sensor **322**. According to some embodiments, the temperature-sensitive device **322** is capable of detecting an ambient temperature of 37° F. with a tolerance of  $\pm 5\%$  or better. In some embodiments, the output signal from the temperature-sensitive device is provided to one channel of the microcontroller's ADC.

(155) In one or more embodiments, the sensor unit **12** is also equipped with a light indicator, such as a bi-color LED capable of illumination in red or green. The LED is visible through a clear window in the unit's plastic enclosure to eliminate the need to create a penetration through the plastic. The enclosure of the sensor unit **12** may also include a mounting bracket for outdoor mounting of the sensor unit.

(156) In some embodiments, when the battery **324** is inserted into the sensor unit **12**, the unit powers up and enters “INITIALIZATION” operational mode. During the initialization mode the sensor may receive a signal from the interface unit **14** to establish a wireless and/or wired communication path between the interface unit **14** and the sensor unit **12**. Alternatively, the sensor unit may initiate a message to one or more interface units **14** and start the initialization process. Once the sensor unit **12** receives the set up signal from the interface unit it will send back an acknowledge signal. In one or more embodiments, the acknowledgment signal comprises identification information and/or other local information. The interface unit **14** then receives the acknowledgment message. In one embodiment, the interface unit **14** extracts the ID information and/or other information from the signal and may store the data onto memory **418**. According to some implementations, the interface unit **14** may use the data from the setup acknowledge signal in the future to validate communication from the sensor unit to ensue that it only responds to communication from the sensor units it is paired up with. Similarly, in some embodiments the setup signal may comprise ID information about the interface unit **14** which the sensor unit may retrieve and store in memory **314**, for example for future validation of signals from the interface unit. After processing the acknowledgment signal at the interface unit **14** the sensor unit **12** and the interface unit **14** are paired up and may communicate through the wireless and/or wired path **15**. In some embodiments, before sending an acknowledgment message the sensor unit **12** will determine if certain criteria are met. For example in one embodiment, the sensor unit **12** may determine whether there is user input at the sensor unit and will only transmit the acknowledge message when user input is present at the sensor unit. For example, the sensor unit may check to see if the plunger on the rain sensor unit is fully depressed.

(157) Additionally or alternatively, during this mode, the microcontroller **312** may complete firmware initializations in order to set the unit up for operation. In one embodiments, once firmware initializations are completed, the microcontroller **312** reads the battery voltage under full load (with the exception of the radio transmitter **316**). If the battery voltage is above a minimum voltage for proper operation in “NORMAL” mode, the sensor unit **12** transmits

a signal, i.e. a BATTERY\_OK message, to the interface unit **14**. This signal may be transmitted at a defined power and/or transmitted utilizing the maximum transmitter power available. The interface unit **14** may respond to receipt of this message by sending an acknowledgement signal, i.e., a BATTERY\_OK\_ACKNOWLEDGE message back to the sensor unit **12**. Upon receipt of this message, the sensor unit **12** enters a sleep or “NORMAL” operational mode. (158) Alternatively, if the measured battery voltage is below the minimum allowable voltage for proper operation in “NORMAL” mode, the unit transmits a low battery warning, e.g., a LOW\_BATTERY\_WARNING message, to the interface unit **14**. This message is transmitted at a defined power and/or utilizing the maximum transmitter power available. The interface unit **14** responds to receipt of this message by sending an acknowledgment, e.g., a LOW\_BATTERY\_ACKNOWLEDGE message, back to the sensor unit **12**. Upon receipt of this message, the sensor unit **12** enters “LOW BATTERY” operational mode.

(159) In some embodiments, during “INITIALIZATION” mode the bi-color LED will illuminate in both red and green for a period of one second. This provides a visual indication to the user that the unit has powered up and is operating. In other embodiments the light indicator may blink a number of times displaying the signal and/or connection strength between the sensor unit **12** and the interface unit **14**.

(160) In some embodiments, while the sensor unit **12** is in “NORMAL” mode, the microcontroller **312** brings itself out of its low-power mode periodically to query the sensors and/or other peripheral devices. In one or more embodiments, the microcontroller **312** will process the data to determine if there has been any change in the data obtained from the sensors and/or other devices, e.g., a change in temperature, change in the amount of rain, etc. When the controller determines that a change has occurred, it will initiate a transmission to the interface unit **14**. Additionally or alternatively, in some embodiments, the sensor unit **12** will initiate a transmission to the interface unit **14** periodically, at fixed intervals, sending the data received from the sensors. In this embodiment, the data may be queried from the sensors at the time of the transmission or may be retrieved from memory **314**. In an alternative embodiment, while in “NORMAL” mode, the sensor unit **12** typically will not initiate a radio transmission to the interface unit **14**. The sensor unit **12** will minimize its power consumption to maximize its battery life, and will place its radio receiver device into a “quasi-sleep” mode. In this embodiment, while in “quasi-sleep” mode, the radio receiver is capable of detecting the presence of an incoming message but may accomplish this without the need to apply full power to all receiver circuitry. In one or more embodiments, during normal mode the bi-color LED may be extinguished.

(161) At intervals, for example of approximately once per day, the microcontroller **312** brings itself out of its normal or sleep mode and activate one or more and typically all peripheral systems on the unit (with the exception of the radio transmitter **316**). Once all peripherals have been activated, the microcontroller **312** performs a measurement of the full-load battery voltage. The resulting measurement, at least in some embodiments, is stored in memory **314** and/or transmitted to the interface unit **14**. Additionally or alternatively, the resulting measurement may be compared with a non-volatile constant stored in memory **314**, i.e., EEPROM, to determine if the battery is nearing the end of its useful life. In order to accurately make this determination, the microcontroller may also make a measurement of the ambient temperature to calibrate the measured battery voltage. In some embodiments, if the full-load battery voltage is below the minimum allowable voltage (end of battery life is approaching), the microcontroller may switch the system into “LOW BATTERY” mode.

(162) While in “Normal” mode the sensor unit **12** may respond to a number of messages from the interface unit **14**. For example, the sensor unit **12** responds to a SENSOR\_STATUS\_REQUEST message from the interface unit **14**. Upon receipt of a SENSOR\_STATUS\_REQUEST message, the microcontroller initiates a measurement of the hygroscopic material displacement, ambient temperature, and full-load battery voltage. After these measurements have been completed, the sensor unit **12** constructs a message packet containing the results of the measurements. It also includes in the message packet the RSSI value observed during the receipt of the SENSOR\_STATUS\_REQUEST message. The entire message packet is transmitted to the interface unit **14** in the form of a SENSOR\_STATUS message.

(163) The sensor unit **12** may also respond to a LINK\_QUALITY\_REQUEST message from the interface unit **14**. A LINK\_QUALITY\_REQUEST message instructs the sensor unit **12** to transmit a LINK\_QUALITY message back to the interface unit **14** at the power level specified in the payload of the LINK\_QUALITY\_REQUEST. The LINK\_QUALITY message contains data packets that indicate the requested power level for the transmission and the RSSI value observed during the receipt of the LINK\_QUALITY\_REQUEST message.

(164) Additionally, the sensor unit **12** responds to a TX\_POWER\_ASSIGN message from the interface unit **14**. A TX\_POWER\_ASSIGN message instructs the sensor unit **12** to utilize a specific power level for future transmissions (with the exception of a LINK\_QUALITY, where the transmit power is assigned by a LINK\_QUALITY\_REQUEST). The sensor unit **12** responds with a TX\_POWER\_ACKNOWLEDGE message that contains a packet indicating the assigned transmit power and the RSSI value observed during the receipt of the TX\_POWER\_ASSIGN message.

(165) The sensor unit **12** responds to a VERSION\_REQUEST message from the interface unit **14**. A

VERSION\_REQUEST message instructs the sensor unit **12** to transmit a VERSION message containing the unit's unique ID number, the version number of the firmware stored in its FLASH memory, and the RSSI value observed during the receipt of the VERSION\_REQUEST message.

(166) In some embodiments, in “LOW BATTERY” operational mode the sensor unit **12** may notify the interface unit **14** that it has detected a low battery condition. It may also attempt to reduce power consumption by eliminating or reducing the frequency of performing non-essential functions. During the “LOW BATTERY” mode the bi-color LED will be extinguished at all times.

(167) In one or more embodiments, when a low battery condition is detected, the sensor unit **12** initiates a LOW\_BATTERY\_WARNING message to the interface unit **14**. In some embodiments, the power level used for this transmission is the power that was last assigned by the interface unit **14**, e.g., through a TX\_POWER\_ASSIGN message. In one implementation, the LOW\_BATTERY\_WARNING message instructs the interface unit **14** to transmit an acknowledgment, e.g., a LOW\_BATTERY\_ACKNOWLEDGE message, indicating that the LOW\_BATTERY\_WARNING was correctly received. In one embodiment, in the event that the sensor unit **12** does not receive a LOW\_BATTERY\_ACKNOWLEDGE message, it may increase the transmitter power and resend the LOW\_BATTERY\_WARNING message. In some embodiments, the transmitter power may be increased with each subsequent attempt to contact the interface unit **14** until an acknowledgment, e.g., a LOW\_BATTERY\_ACKNOWLEDGE message, is received.

(168) In one or more embodiments, once an acknowledgment has been received the sensor unit **12** may reduce the number of periodic updates it sends to the interface units. Additionally, or alternatively, the sensor unit **12** may also reduce the number of times it wakes up to query the sensors, and/or other peripheral devices. Alternatively, once an acknowledge message has been received the sensor unit **12** may not initiate further transmissions, but only acknowledges messages received from the interface unit **14**.

(169) FIG. **26** illustrates one possible implementation of the “TEST” operational mode utilized during the installation of the sensor unit **12**. This process provides the installer with a quick and simple-to-understand process for determining that the sensor unit **12** is installed at a location with adequate radio reception from the interface unit **14**. In some embodiments, the “TEST” operational mode is initiated by the interface unit **14** in response to a “Press and Hold” actuation of the button **820** on the interface unit **14**. Still further, in some implementations the “TEST” operational mode terminates automatically after a set period of time, e.g., 15 minutes.

(170) Further, according to some implementations, the “TEST” operational mode consists of an exchange of radio messages between the sensor unit **12** and the interface unit **14** to determine whether or not the sensor unit **12** is positioned at a satisfactory location. Moreover, in some implementations, the test operational mode allows the installer to determine the best possible location for the sensor unit **12** relative to the interface unit **14** before the sensor unit **12** is fixed at a location. In one or more embodiments, a location may be deemed satisfactory if the following conditions are satisfied:

$RSSI.sub.SENSOR \geq RSSI.sub.SENSORMIN$

$RSSI.sub.INTERFACE \geq RSSI.sub.INTERFACEMIN$

$P.sub.TXSENSOR \leq P.sub.TXNOMINAL$

(171) Where  $RSSI.sub.SENSOR$  is the RSSI value of the RF signal transmitted from the interface unit **14** as received at the sensor unit **12**.  $RSSI.sub.SENSORMIN$  is the minimum allowable value of  $RSSI.sub.SENSOR$  to achieve communication reliability for the system.  $RSSI.sub.INTERFACE$  is the RSSI value of the RF signal transmitted from the sensor unit **12** as received at the interface unit **14**.  $RSSI.sub.INTERFACEMIN$  is the minimum allowable value of  $RSSI.sub.INTERFACE$  to achieve communication reliability for the system.  $P.sub.TXSENSOR$  is the transmitter power employed by the sensor unit **12**.  $P.sub.TXNOMINAL$  is the maximum transmitter power allowed for the sensor unit **12** to utilize for operations under normal operating conditions. In some embodiments, the power level may typically be at least 6.0 dB below the maximum output power achievable by the transmitter, and may be selected to achieve the overall battery lifetime of the sensor unit **12** is adequate.

(172) According to some implementations, While in the “TEST” operational mode, the “TEST” operational mode flag in the FLAGS field of all message payloads may be SET.

(173) Still referring to FIG. **26**, in step **2610** the message transactions are initiated by the interface unit **14** at two-second intervals, and culminate in the determination of the optimal location to install the sensor unit and/or to determine the minimum transmitter power for the sensor unit **12** to communicate with the interface unit **14** to achieve the desired system reliability. In step **2612** the interface unit sends a test message to the sensor unit. Next, in step **2614** the sensor unit receives the signal and determines and responds with an acknowledgment message. In one or more implementations, the sensor unit then moves to step **2616** where it determines the signal strength of the test message and displays the signal strength (e.g., as a number of blinks of the light emitting diode). In some embodiments, as the location of the sensor unit **12** is changed by the installer and the sensor unit **12** automatically determines and displays the test acknowledge signal strength. According to some implementations, the signal strength is automatically updated by the sensor unit **12** with each two-second “TEST” operational mode message

exchange. In one embodiment, the sensor unit **12** displays the signal strength through an indicator, e.g., an LED, where, for example, the indicator blinks a number of times representing the signal strength at a particular location. Alternatively, or additionally the indicator may be an LCD display that displays the signal strength. The installer may then change the location of the sensor unit **12** and by observing the signal strength in different areas may determine a location to install the sensor unit **12**. Alternatively, in some embodiments, when the location of the sensor unit is determined to be adequate based on the decision criteria, a bi-color LED may be illuminated green. If the location is determined to be inadequate, the bi-color LED may be illuminated red. In one embodiment, the status of the bi-color LED is updated with each two-second “TEST” operational mode message exchange. In some embodiments, this initialization process continues for a preset period, e.g., 15 minutes where the interface unit and the sensor unit exchange messages to allow the user to find the optimal location for the sensor unit in terms of signal strength.

(174) In some embodiments, the TEST message may be identical in form to the LINK\_QUALITY\_REQUEST message with the exception that the “TEST” operational mode flag in the FLAGS field of the message payload may be SET. According to some implementations, the sensor unit **12** responds with a TEST\_ACKNOWLEDGE message. This message may be identical in form to the LINK\_QUALITY\_ACKNOWLEDGE message with the exception that the “TEST” operational mode flag in the FLAGS field of the message payload is SET.

(175) In one implementation, in step **2620** the interface unit **14** decodes the message to obtain the value of RSSI.sub.INTERFACE. In step **2622** the interface unit determines if  $\text{RSSI.sub.SENSOR} \geq \text{RSSI.sub.SENSORMIN}$ . If the condition is satisfied, in step **2624** the interface unit checks to see whether the last message sent was a TX\_POWER\_INCREASE message. If the last message received was not a TX\_POWER\_INCREASE message, in step **2626** the interface unit **14** issues a TX\_POWER\_DECREASE message to the sensor unit **12**. In step **2632** the sensor unit determines whether it is at the minimum TX power necessary for proper functioning, in step **2634** the sensor unit send a TX\_LEAST\_POWER message to the interface unit. In response to this message, in step **2636**, the interface unit issues a TX\_LEAST\_POWER\_ACKNOWLEDGEMENT message to the sensor unit **12**.

Alternatively, when in step **2632** the sensor unit is not at the minimum TX power, then in step **2638** the sensor unit **12** decreases its transmittal power by the smallest possible amount and replies with a TX\_POWER\_DECREASE\_ACKNOWLEDGE message.

(176) Returning to step **2624**, if the last message sent by the interface unit was a TX\_POWER\_INCREASE message, in step **2644** the interface unit then issues a TX\_MINIMUM\_POWER message to the sensor unit **12** notifying it of the transmitter power for use in future transmissions. In step **2646** sensor unit decodes the message and obtains the RSSI.sub.SENSOR value. In step **2648** the sensor responds with a TX\_MINIMUM\_POWER\_ACKNOWLEDGE message.

(177) If alternatively in step **2622**  $\text{RSSI.sub.INTERFACE} < \text{RSSI.sub.INTERFACEMIN}$  has been satisfied, in step **2628**, the interface unit **14** issues a TX\_POWER\_INCREASE message to the sensor unit **12** notifying it to increase its transmitter power by the smallest possible amount. In response to the TX\_POWER\_INCREASE message, in step **2652** the sensor unit determines if it is at the maximum TX power it is capable of producing. If the sensor unit is not at the maximum TX power, then in step **2658** the sensor unit **12** increases the transmitter power by the smallest allowable increment and initiates a TX\_POWER\_INCREASE\_ACKNOWLEDGE message to the interface unit **14**. Alternatively, if the sensor unit **12** is already set to transmit the maximum power it is capable of producing, the process continues to step **2654** where the sensor unit initiates a TX\_MOST\_POWER message to the interface unit **14** indicating that it may no longer increase its transmit power. In response to this message, in step **2656** the interface unit issues a TX\_MOST\_POWER\_ACKNOWLEDGE message to the sensor unit **12**.

(178) In one embodiment, after the initializations are complete the sensor unit **12** may query all of the sensors and/or other peripheral devices and construct a data packet comprising atmospheric data, battery strength, signal strength, and/or other data and forward the data packet to the interface unit **14**.

(179) An alternative implementation of “TEST” operational mode is illustrated in FIG. **22**. The “TEST” operational mode is utilized during the installation of the sensor unit **12** to provide the installer with a quick and simple-to-understand process for determining that the sensor unit **12** is installed at a location with adequate radio reception from the interface unit **14**. Further, the “TEST” operational mode is initiated by the interface unit **14** in response to a “Press and Hold” actuation of the button **820** on the interface unit **14**. Still further, the “TEST” operational mode terminates automatically after a period of five minutes.

(180) Additionally, the “TEST” operational mode consists of an exchange of radio messages between the sensor unit **12** and the interface unit **14** to determine whether or not the sensor unit **12** is positioned at a satisfactory location. A location is deemed to be satisfactory if the following conditions are satisfied:

$\text{RSSI.sub.SENSOR} \geq \text{RSSI.sub.SENSORMIN}$

$\text{RSSI.sub.INTERFACE} \geq \text{RSSI.sub.INTERFACEMIN}$

$\text{P.sub.TXSENSOR} \leq \text{P.sub.TXNOMINAL}$

(181) Where RSSI.sub.SENSOR is the RSSI value of the RF signal transmitted from the interface unit **14** as

received at the sensor unit **12**. RSSI.sub.SENSORMIN is the minimum allowable value of RSSI.sub.SENSOR to achieve communication reliability for the system. RSSI.sub.INTERFACE is the RSSI value of the RF signal transmitted from the sensor unit **12** as received at the interface unit **14**. RSSI.sub.INTERFACEMIN is the minimum allowable value of RSSI.sub.INTERFACE to achieve communication reliability for the system. P.sub.TXSENSOR is the transmitter power employed by the sensor unit **12**. P.sub.TXNOMINAL is the maximum transmitter power allowed for the sensor unit **12** to utilize for operations under normal operating conditions. This power level is typically at least 6.0 dB below the maximum output power achievable by the transmitter, and is selected to achieve the overall battery lifetime of the sensor unit **12** is adequate.

(182) While in the “TEST” operational mode, the “TEST” operational mode flag in the FLAGS field of all message payloads will be SET.

(183) Still referring to FIG. 22, in step **2210** the message transactions are initiated by the interface unit **14** at two-second intervals, and culminate in the determination of the minimum transmitter power for the sensor unit **12** to communicate with the interface unit **14** to achieve the desired system reliability. If the location of the sensor unit **12** is determined to be adequate based on the decision criteria, the bi-color LED is illuminated green. If the location is determined to be inadequate, the bi-color LED is illuminated red. The status of the bi-color LED is updated with each two-second “TEST” operational mode message exchange.

(184) In step **2212** the interface unit sends a TEST message to the sensor unit **12**. In step **2214** the sensor unit **12** responds to the TEST message from the interface unit **14**. The TEST message may be identical in form to the LINK\_QUALITY\_REQUEST message with the exception that the “TEST” operational mode flag in the FLAGS field of the message payload is SET. The sensor unit **12** responds with a TEST\_ACKNOWLEDGE message. This message may be identical in form to the LINK\_QUALITY\_ACKNOWLEDGE message with the exception that the “TEST” operational mode flag in the FLAGS field of the message payload is SET.

(185) In step **2216** the interface unit **14** decodes the message to obtain the value of RSSI.sub.INTERFACE. In step **2218** the interface unit determines if  $\text{RSSI.sub.SENSOR} \geq \text{RSSI.sub.SENSORMIN}$ . If the condition is satisfied, in step **2220** the interface unit checks to see whether the last message sent was a TX\_POWER\_INCREASE message. If the last message received was not a TX\_POWER\_INCREASE message, in step **2222** the interface unit **14** issues a TX\_POWER\_DECREASE message to the sensor unit **12**. In step **2224** the sensor unit determines whether it is at the minimum TX power necessary for proper functioning, in step **2228** the sensor unit send a TX\_LEAST\_POWER message to the interface unit. In response to this message, in step **2230**, the interface unit issues a TX\_LEAST\_POWER\_ACKNOWLEDGMENT message to the sensor unit **12**. Following receipt of the message the sensor unit continues to step **2250**. Alternatively, when in step **2224** the sensor unit is not at the minimum TX power, then in step **2226** the sensor unit **12** decreases its transmittal power by the smallest possible amount and replies with a TX\_POWER\_DECREASE\_ACKNOWLEDGE message.

(186) Returning to step **2220**, if the last message sent by the interface unit was a TX\_POWER\_INCREASE message, in step **2244** the interface unit then issues a TX\_MINIMUM\_POWER message to the sensor unit **12** notifying it of the transmitter power for use in future transmissions. In step **2246** sensor unit decodes the message and obtains the RSSI.sub.SENSOR value. In step **2248** the sensor responds with a TX\_MINIMUM\_POWER\_ACKNOWLEDGE message. Following step **2248**, in step **2250** the sensor unit determines if  $\text{RSSI.sub.SENSOR} \geq \text{RSSI.sub.SENSORMIN}$ . When the condition is satisfied, then in step **2256** the sensor unit determines whether  $\text{P.sub.TXSENSOR} \leq \text{P.sub.TXNOMINAL}$ . If this condition is satisfied, then the sensor unit continues to step **2258** where the bi-color led is illuminated green, indicating that the sensor location is acceptable. Alternatively, if in step **2256** the sensor unit determines the  $\text{P.sub.TXSENSOR} > \text{P.sub.TXNOMINAL}$  then in step **2252** the bi-color led is illuminated in red indicating that the sensor location is unacceptable.

(187) Similarly, if in step **2250** the sensor unit determines that  $\text{RSSI.sub.SENSOR} < \text{RSSI.sub.SENSORMIN}$  process continues to step **2252**, where the bi-color led is illuminated in red indicating that the sensor location is unacceptable.

(188) Following receipt of the message, in step **2216** the interface unit **14** decodes the message and obtains the value of RSSI.sub.INTERFACE. The interface unit then repeats steps **2218-2226**, as described above, until  $\text{RSSI.sub.INTERFACE} < \text{RSSI.sub.INTERFACEMIN}$  has been satisfied by the power decrease. If this condition has been satisfied, in step **2232**, the interface unit **14** issues a TX\_POWER\_INCREASE message to the sensor unit **12** notifying it to increase its transmitter power by the smallest possible amount. In response to the TX\_POWER\_INCREASE message, in step **2234** the sensor unit determines if it is at the maximum TX power it is capable of producing. If the sensor unit is not at the maximum TX power, then in step **2236** the sensor unit **12** increases the transmitter power by the smallest allowable increment and initiates a TX\_POWER\_INCREASE\_ACKNOWLEDGE message to the interface unit **14**. Alternatively, if the sensor unit **12** is already set to transmit the maximum power it is capable of producing, the process continues to step **2238** where the sensor unit initiates a TX\_MOST\_POWER message to the interface unit **14** indicating that it may no longer increase its transmit power. In response to this message, in step **2240** the interface unit issues a

TX Most\_POWER\_KNOWLEDGE message to the sensor unit **12**. Then in step **2252** the sensor unit causes the bi-color led to be illuminated in red indicating that the sensor location is unacceptable.

(189) In one or more implementations the interface unit **14** draws power from the main irrigation controller **30**. The interface unit **14** may operate from 22 to 30.8 VAC input voltage. Typically, the interface unit **14** operates by taking 24 VAC electrical power from its associated irrigation controller. Additionally or alternatively, the interface unit may comprise a power source, such a battery, solar power, and/or other such source, where the interface unit draws some or all of its power from the power source.

(190) In some embodiments, the interface unit **14** may be implemented utilizing a low-cost 8-bit microcontroller **414** that has sufficient computational power and speed to support all of the functional capabilities of the unit. In one embodiment, the microcontroller **414** may employ a quartz crystal for generation of an internal clock signal. It may be desired that the same type of microcontroller be used in both the sensor unit **12** and the interface unit **14**.

(191) According to some implementations, the microcontroller typically employs FLASH memory for storage of executable firmware, and is capable of being programmed “in-system”. For example, an in-system programming port may be available on the printed circuit board for accomplishing the programming process during final assembly. The in-system programming port may be accessible via surface pads (through the use of “pogo” pins on an ICT fixture), in one or more embodiments. A programming header may also be available on the printed circuit board to permit reprogramming the microcontroller during firmware development. In some embodiments, the circuit board may be designed for ease of testability such as using automated test fixture equipment. In this embodiment, standard solder connections with conformal coating are used for the circuit board.

(192) In some implementations, the microcontroller **414** may also include on-chip EEPROM for non-volatile storage of miscellaneous data required for support of all functional capabilities. On-chip RAM is also typically present in sufficient quantity for all functional capabilities, according to some embodiments.

(193) In some embodiments, the interface unit employs a single-chip transceiver **412** which provides an analog or digital Received Signal Strength Indicator (RSSI) output signal. In one embodiment, where the RSSI output is an analog signal, it may be provided to one channel of the microcontroller's ADC.

(194) The interface unit **14**, according to some implementations, may also be equipped with a backlit LCD **816**. The display may be capable of displaying alphanumeric characters with 11-segment LCD digits. A sufficient number of LCD digits are provided to display at least the following messages: a) BATT OK b) BATT LOW c) BYPASS d) NORMAL e) INHIBIT f) FREEZE g) TEST h) NO SIGNAL i) NO SENSOR j) NOISE

(195) Additionally, or alternatively the interface unit may be capable of displaying the mode and or status of the system through other means. For example, in one embodiment the user display **426** comprises a graphic display capable of displaying the mode of operation or status of the system. For example, in one embodiment, the display **426** may display the status of the system using graphical symbols displayed on the graphic display of the interface unit **14**.

(196) In some implementations, the interface unit **14** employs a “normally closed” relay device to permit breaking the COMMON return line connection between the sprinkler valve solenoids and the irrigation controller **30**. In one or more embodiments, this relay may be actuated by a voltage that is compatible with the voltage output of one of the microcontroller output pins. according to some implementations, the maximum current rating of the relay contacts may be no less than 3.0 amperes.

(197) In some embodiments, the interface unit **14** also employs a current sensing device **420** to allow detection of the current flow in the COMMON return line. In one embodiment, when an irrigation cycle is commanded by the irrigation Controller, current flows in the COMMON line. The current sensor may detect this signal, triggering the microcontroller **414** to initiate a SENSOR\_STATUS\_REQUEST to the sensor unit **12**. In one embodiment, when the SENSOR\_STATUS message returned by the sensor unit **12** indicates that irrigation should be inhibited, the current interruption relay **416** is OPEN, interrupting irrigation.

(198) Additionally or alternatively, the interface unit **14** may employ a voltage sensing device **422**, in one or more embodiments, to allow detection of the voltage across the current interruption relay **416** in the COMMON return line. When irrigation is being commanded by the irrigation controller **30** while the system **10** is commanding that irrigation be inhibited, the voltage sensor **422** may monitor the voltage across the relay contacts to determine when the irrigation cycle has terminated. Once the irrigation cycle has terminated the interface unit **14** will CLOSE the current interruption relay.

(199) In some embodiments, the interface unit comprises a user input **424**, wherein in one or more embodiments the user input allows the user to change the mode of operation of the interface unit and/or perform other adjustments in the operation of the interface unit **14**. For example, in one embodiment, the interface unit **14** is equipped with a three-position toggle switch **814** to allow the user to configure the unit for the desired operation. The switch has a CENTER position in addition to a LEFT and a RIGHT position. Placing the switch into the CENTER position places the interface unit **14** into NORMAL operational mode where irrigation is inhibited if sufficient precipitation has been detected by the sensor unit **12**. Placing the switch into the LEFT position places the interface unit **14** into



BYPASS mode, where irrigation will not be inhibited by the system. The RIGHT switch position is a spring-loaded “return to center”, automatically releasing back to CENTER when the switch is no longer held in position. This spring-loaded position places the interface unit **14** into TEST operational mode. The interface unit may also include a way to override or shut-off the device. Alternatively, and or additionally, in one embodiment, the interface unit **14** is equipped with a touch screen comprising buttons that allow the user to switch the mode of operation.

(200) In some embodiments, the interface unit **14** is equipped with a pushbutton switch **820** to allow the user to activate an LCD backlight for a period of five seconds. When the pushbutton is depressed, the LCD backlight is illuminated. The LCD backlight remains illuminated for a period of time, e.g., 5 seconds, after the pushbutton has been released. In one or more embodiments, when the toggle switch on the interface unit **14** is set to the BYPASS position, the LCD display continuously displays the “BYPASS” message.

(201) In many embodiments, the interface unit **14** incorporates a user-friendly method of adjusting the rainfall level desired by the user. For example, the interface unit **14** may be equipped with a linearly-adjustable slide switch **812** that allows the user to select the level of precipitation at which irrigation will be interrupted. In one or more embodiments, precipitation amounts between  $\frac{1}{8}$ " and  $\frac{3}{4}$ " are selectable in a continuous manner.

(202) When power is first applied to the interface unit **14**, the unit powers up and enters “INITIALIZATION” operational mode. In some embodiments, during the initialization mode, the microcontroller **414** executes the initializations that need to be completed in order to set the unit up for operation. During the initialization mode the interface unit may also attempt to pair up with one or more sensor units **12**, such as illustrated in the system diagram of FIG. **34**. In one implementation, the interface unit will send a setup signal to one or more sensor units **12**. Next, the interface unit may receive an acknowledgement signal from one or more sensor units **12** in response to the setup signal. In some embodiments, the acknowledgment signal may comprise identification and/or other information about the sensor unit. In some embodiments, the interface unit **14** may store the data in memory **418** and/or use the data to pair up with the sensor unit **12**. Once the setup is complete the interface unit and sensor unit **12** may communicate through the communication path **15**. In one embodiment, during “INITIALIZATION MODE” the LCD backlight may be continuously illuminated.

(203) In one embodiment, after the initializations are complete the sensor unit **12** may query all of the sensors and/or other peripheral devices and construct a data packet comprising atmospheric data, battery strength, signal strength, and/or other data and forward the data packet to the interface unit **14**. The interface unit **14**, according to some implementations, may receive the data from the sensor unit **12**, and process the data and display information about the sensor unit on the user display **426**.

(204) Additionally or alternatively, in some embodiments, at the conclusion of the internal initializations, the microcontroller may retrieve from its memory **418**, and more specifically the EEPROM, the identification number of the sensor unit **12** with which it is associated and transmit a SENSOR\_STATUS\_REQUEST message. Upon receipt of a SENSOR\_STATUS message from the sensor unit **12**, the interface unit **14** may process the message. In one embodiment, the interface unit **14** may further display the appropriate sensor unit **12** status message on the LCD display **426**.

(205) In one or more embodiments, when no sensor unit is associated with the interface unit **14**, the user display **426** may display a “NO SENSOR” message and/or a similar message and or graphic display. In one embodiment, when the “NO SENSOR” message is displayed the LCD backlight flashes on and off at a 4-second rate (two seconds on, two second off). According to one implementation, at the conclusion of the “INITIALIZATION” mode, the interface unit **14** enters “NORMAL” mode.

(206) In some embodiments, the interface unit **14** spends the majority of its time in the “NORMAL” operation mode. In “NORMAL” mode, the LCD backlight is OFF unless illuminated by the user by depressing the pushbutton, or by an event requiring its illumination.

(207) In one or more embodiments, when the interface unit **14** is set to BYPASS, the current interruption relay is set to CLOSED. In one implementation, a “BYPASS” message may be continuously displayed on the LCD. In this or other implementations, The LCD backlight may be OFF.

(208) In some embodiments, during “NORMAL” mode, the interface unit **14** will continually monitor the open-circuit voltage across the current interruption relay to detect when irrigation is being commanded from the irrigation controller **30**. In this embodiment, when 24 VAC is detected across the current interruption relay, the interface unit **14** initiates a SENSOR\_STATUS\_REQUEST to its associated sensor unit **12**. If the SENSOR\_STATUS reply message received from the sensor unit **12** indicates that irrigation should be inhibited, the current interruption relay is OPENED. Once the relay has been OPENED, the interface unit **14** may monitor the current flow in the COMMON return line to detect when irrigation has ceased, at which time the current interruption relay is set to CLOSE. Alternatively, if the SENSOR\_STATUS reply message received from the sensor unit **12** indicates that irrigation should be permitted, the current interruption relay remains in its default CLOSED state. In some embodiments, while in normal mode, the current interruption relay is normally CLOSED, unless the

SENSOR\_STATUS message received from the sensor unit **12** indicates that irrigation should be inhibited. In these embodiments if system failure occurs at any time the relay is in its default CLOSED state.

(209) Alternatively, in some embodiments, the interface unit will open and close the relay based on transmission of signals initiated from the sensor unit. In one embodiment the sensor unit **12** will initiate an update message to the interface unit when it senses a change in one or more of the data retrieved from sensors and/or other peripheral devices. Additionally or alternatively, the sensor unit may initiate communication with the interface unit **14**, in some embodiments, at fixed intervals, e.g., 4 times a day, when it may query one or more sensors and/or other devices and send an update signal to the interface unit **14**. In one or more embodiments the frequency of transmission of periodic updates based on internal and/or external criteria. For example, in one embodiment the sensor unit **12** may decrease the number of updates it will send the interface unit **12** during the Low Battery mode. Additionally or alternatively, the sensor unit may also reduce the number of updates it transmits to the interface unit **14** during low temperature or hibernation mode. In some embodiments, in addition to these messages the sensor unit may also send a message to the interface unit when it receives a request for data from the interface unit **14**.

(210) In one embodiment, after the SENSOR\_STATUS message, or an update message is received from the sensor unit **12**, the interface unit **14** may continuously displays the appropriate system status message on the user display **426**. In one embodiment, for example: a) when irrigation is currently enabled, the message “NORMAL” is displayed b) when irrigation is currently disabled because of precipitation, the message “INHIBIT” is displayed c) when irrigation is currently disabled because of low temperature, the message “FREEZE” is displayed

(211) In one implementation, while these messages are being displayed, the LCD backlight may be turned OFF.

(212) Alternatively, in another exemplary embodiment, the display may be a graphical display. In this and other embodiments, the interface unit may display the status and other data received from the sensor unit through a graphical representation.

(213) In many embodiments, while in “NORMAL” operational mode the interface unit **14** responds to a BATTERY\_OK message from the sensor unit **12**. Upon receipt of this message the interface unit **14** may send a BATTERY\_OK\_ACKNOWLEDGE message back to the sensor unit **12**. In one embodiment, after transmitting this message, the message “BATT OK” is displayed on the display for a certain period, e.g., five seconds. In an alternative embodiment, the interface unit may display the battery strength of the sensor unit **12** on the display **426**.

(214) The interface unit **14**, in some embodiments, may also responds to a low battery warning message, e.g., a LOW\_BATTERY\_WARNING message, from the sensor unit **12**. In one embodiment, the interface unit **14** may respond to receipt of this message by sending a LOW\_BATTERY\_ACKNOWLEDGE message back to the sensor unit **12**. In one implementation, after this message is transmitted a low battery indication, e.g., a “BATT LOW” message, is displayed continuously on the user display **426**. Additionally, in some embodiments, the LCD backlight is flashed on and off at a 4-second rate (two seconds on, two second off). In some embodiments, the other irrigation control functions at the interface unit **14** continue to operate normally. In one embodiment, in order to indicate this, the low battery indication is displayed alternately with the status indication that is appropriate for the current state of the system (e.g., “NORMAL”, “INHIBIT”, “FREEZE”, “BYPASS”, etc.).

(215) In some embodiments, at fixed intervals, e.g., approximately once per day, the interface unit **14** initiates a measurement of the communications link quality, for example by issuing a LINK\_QUALITY\_REQUEST message to the sensor unit **12**. Upon receipt of the response from the sensor unit **12**, for example the LINK\_QUALITY\_ACKNOWLEDGE message, the interface unit **14** determines if the value of  $RSSI.sub.INTERFACE \geq RSSI.sub.INTERFACEMIN$

(216) In one embodiment, when  $RSSI.sub.INTERFACE < RSSI.sub.INTERFACEMIN$  the interface unit **14** may send a power increase message, for example a TX\_POWER\_INCREASE message, to the sensor unit **12**. In one embodiment the sensor unit **12** may respond to the message by increasing its transmit power by the smallest possible amount and reply, for example with a TX\_POWER\_INCREASE\_ACKNOWLEDGE message. Upon receipt of this message, in one or more implementations, the interface unit **14** may determine if the condition  $RSSI.sub.INTERFACE \geq RSSI.sub.INTERFACEMIN$  has been satisfied by the power increase. If this condition has been satisfied, the interface unit **14** may issues a message, e.g., a TX\_MINIMUM\_POWER message, to the sensor unit **12** notifying it of the transmitter power to use for future transmissions. Alternatively, when this condition is not satisfied, the interface unit **14** may continue to issue power increase requests, e.g., TX\_POWER\_INCREASE messages, to the sensor unit **12** until the condition is satisfied and/or a preset period of time has lapsed. In some embodiments, when the sensor unit **12** reaches the maximum power that it may transmit during this process, it may send a message indicating that it has reached it maximum power level, e.g., a TX\_MOST\_POWER message, to the interface unit **14**. In this case, the interface unit **14** may respond with an acknowledgment message, e.g., a TX\_MOST\_POWER\_ACKNOWLEDGE message, and terminate the power adjustment process.

(217) Alternatively, according to some embodiments, when  $RSSI.sub.INTERFACE \geq RSSI.sub.INTERFACEMIN$ , the interface unit may **14** issues a message to the sensor unit **12**, requesting that the sensor unit **12** decrease its

transmit power, e.g., a TX\_POWER\_DECREASE message. In one implementation, as a result of this message the sensor unit **12** may decrease its transmit power by the smallest possible amount and may further reply with an acknowledgment message, for example a TX\_POWER\_DECREASE\_ACKNOWLEDGE message. Upon receipt of this message, the interface unit **14** may determine if the condition  $RSSI.sub.INTERFACE < RSSI.sub.INTERFACEMIN$  has been satisfied by the power decrease, according to some implementations. In one embodiments, when this condition has been satisfied, the interface unit **14** may issue a request to the sensor unit **12** notifying it to increase its transmitter power by the smallest possible amount, e.g., TX\_POWER\_INCREASE message. The sensor unit **12** may respond to the request with an acknowledgement message, e.g., a TX\_POWER\_INCREASE\_ACKNOWLEDGE message, and, in one or more embodiments, the interface unit **14** may verify that the condition  $RSSI.sub.INTERFACE \geq RSSI.sub.INTERFACEMIN$  is now satisfied. The interface unit **14** may then issue a message to the sensor unit **12** notifying it of the transmitter power to use for future transmissions, e.g., a TX\_MINIMUM\_POWER message.

(218) In some embodiments, so long as the condition  $RSSI.sub.INTERFACE < RSSI.sub.INTERFACEMIN$  is not satisfied, the interface unit **14** may continue to issue requests to the sensor unit **12** notifying it to decrease its transmitter power, e.g., a TX\_POWER\_DECREASE messages, until the condition is satisfied. In one embodiment, once the sensor unit **12** reaches the minimum power that it may transmit during this process, it will send a message to the interface unit notifying it that it has reached its minimum power, e.g., a TX\_LEAST\_POWER message. In this or other embodiments, the interface unit **14** may respond with an acknowledgment, for example a TX\_LEAST\_POWER\_ACKNOWLEDGE message, and may further terminate the power adjustment process.

(219) As described with respect to FIGS. **22** and **26**, the “TEST” mode may be used during the installation of the sensor unit **12** and provides a method for a single installer to easily determine whether or not the proposed location for the sensor unit **12** will result in satisfactory signal reception and communications reliability in one or more embodiments. In one implementations, the “TEST” mode is initiated by switching the toggle switch to “TEST” mode and holding it for a minimum of three seconds. In this embodiment, after this time requirement has been met, the interface unit **14** continuously displays an indication, e.g., the message “TEST”, on the user display **426**. In one embodiments, the LCD backlight may be continuously illuminated while in “TEST” mode. Additionally or alternatively, the test mode may be initiated through other forms of user input, e.g., activating a test button, selecting the test option, etc. In one embodiment, the test mode may also be initiated by the interface unit once the interface unit is powered up and paired with one or more sensor units.

(220) After the test mode has been initiated, according to some implementations, the interface unit **14** may initiate a TEST message at intervals of no more frequently than, for example, two seconds. Alternative procedures followed throughout the “TEST” mode are described in the flowchart depicted in FIGS. **22** and **26**. In some embodiments, the “TEST” mode may be terminated by the operator, for example by selecting and holding the toggle switch in the “TEST” position for a period, such as, a period of no less than two seconds, and/or automatically after a period of, for example, fifteen minutes.

(221) In many embodiments, message traffic between the interface unit **14** and sensor unit **12** typically occur in pairs, i.e, for every message that is sent, there is an acknowledgement.

(222) In one embodiment, in the event that the sender of an initial message does not receive an acknowledgement corresponding to the message sent within a period of time (e.g., five seconds), the originator of the message may assume that the message was lost. In one embodiment, retransmission of the message may be attempted for a period (e.g., one minute). When the message may not be successfully transmitted and acknowledged within a period (e.g., one minute), in one or more embodiments, the sender of the message may assume either that the communications channel is suffering from an unusually high level of interference or that a malfunction has occurred at the other end of the communications link.

(223) In order to assess potential interference in the communications channel, both the interface unit **14** and the sensor unit **12** may periodically monitor the RSSI values obtained from the receiver chip during periods where no message traffic is being passed, according to some embodiments. In one embodiment, these values may be noted and stored, e.g. in a histogram, so that a statistical archive of the distribution of noise levels at the sensor unit **12** and interface unit **14** locations is available with which to assess the communications channel at any given time. In some implementations, when no message traffic is being passed, the interface unit **14** may sample the RSSI value from its receiver chip at intervals of one minute. In one or more embodiments, the sensor unit **12** may sample the RSSI value from its receiver chip at fixed intervals, e.g. one hour.

(224) In some embodiments, after a failure to receive a timely acknowledgement to a message that has been sent, the originator of the message may sample the RSSI value from its receiver chip and may further assess whether or not the sample obtained meets some criteria, for example whether the sample obtained lies within the bins of the histogram associated with the expected noise floor. In one implementation, when it is determined that an unusually high noise level is present, an attempt at a retransmission may be made at the maximum possible transmitter power. when this attempt fails to result in a successful acknowledgement, in some embodiments, the device may sample the

RSSI value from its receiver chip at fixed intervals, e.g. 15 minute intervals, and may retransmit the message when the noise level has returned to its nominal value.

(225) In one embodiment when a certain amount of time lapses without reduction in noise level the interface and/or sensor unit may cease attempts to transmit the message. For example, in one exemplary embodiment, when 24 hours elapses with no reduction in the atmospheric noise level, the interface unit **14** may cease attempting to retransmit the message. In one implementation of this exemplary embodiment, the interface unit may continuously display an indication of the presence of noise, e.g. the “NOISE” message, on the user display **426**. In this embodiment, while this indication is being displayed, the LCD backlight may be illuminated continuously. In one embodiment, when the noise level has returned to its nominal level, the interface unit **14** may initiate a message, e.g. a LINK\_QUALITY\_REQUEST message, to re-establish the communications link and configure the appropriate transmitter power for the sensor unit **12**. In one exemplary embodiment, if 1 hour elapses with no reduction in the atmospheric noise level, the sensor unit **12**, the unit may cease attempting to retransmit the message.

(226) Alternatively, when sampling the RSSI value from the receiver chip, when the device determines that no excess atmospheric noise is present in the communications channel; it may presume that the device at the other end of the wireless link has failed.

(227) In one embodiment when the interface unit **14** determines that the sensor unit **12** has failed, it may continue to attempt making contact with the sensor unit **12** at fixed intervals, e.g. five-minute intervals, for a period, e.g., 24 hours. In one embodiment, when no contact with the sensor unit **12** is made after a certain period of time, e.g. 24 hours, the interface unit **14** may cease further attempts at contacting the sensor unit **12** and, in one or more embodiment, may continuously display an indication that communication has failed, e.g. the “NO SIGNAL” message, on the user display. In one embodiment, while this message is displayed, the LCD backlight is ON. In some embodiments, the interface unit may reattempt to communicate with the interface unit after a period of time has lapsed.

(228) Further, in some embodiment, when the sensor unit **12** determines that the interface unit **14** has failed, it may continue to attempt making contact with the interface unit **14** at fixed intervals, e.g. five-minute intervals, for a certain period of time, e.g. one hour. In some embodiments, when communication has not been re-established after this period, the sensor unit **12** may cease further attempts at contacting the interface unit **14**. In one embodiment, no further transmissions may be attempted until the interface unit **14** attempts to establish contact with the sensor unit **12**. Alternatively, in some embodiments, the sensor unit **12** may try to reconnect to reestablish communication with the interface unit **14** after a certain period of time.

(229) In some implementations of the rain sensor system **10**, communication messages may comply with a desired Protocol. As such messages may have the following format:

(230) TABLE-US-00001 Start End Frame Message Frame Preamble Marker Length Data Checksum Marker F5hex F5hex 1Chex 1 byte up to 255 1 byte 1Dhex bytes

(231) The preamble consists of 2 or more F5 (hex) transmissions. The purpose of the preamble is to give the receiving device an opportunity to sync up with the transmitting device.

(232) Packet frames use the byte 1C hex as the start of frame marker and 1D hex as the end of frame marker. When the payload contains a data byte equal to 1C or 1D, that byte is replaced by the sequence 1B, 01 or 1B, 03. When the payload contains a data byte equal to 1B, that byte is replaced by the sequence 1B, 02. Upon reception, sequences 1B, 01 are replaced as 1C, sequences 1B, 02 are replaced as 1B, and sequences 1B, 03 are replaced as 1D. This is similar to SLIP protocol used for TCP/IP. Packets start with the value 1C, and that value typically does not appear in the payload. Packets end with the value 1D, and that value typically does not appear in the payload. It may be desirable in some instances that the length, message data or checksum contain the combination of 1B followed by one of a 01, 02 or a 03.

(233) The length element is a single byte that describes the length of the message data element in terms of byte count. For example, a frame that has 4 bytes in the message data element would have a length of 4. A length of 0 would denote a blank frame. Because of the 1-byte limitation, a message data element may not be any longer than 256 bytes. Also, if a frame has been subjected to the replacement of 1Cs with 1B, 01, 1Bs with 1B, 02, or 1Ds with 1B, 03, the length describes the length of the intended packet before it was encoded to remove the 1Cs, 1Bs or 1Ds. This provides another check of the packet's integrity.

(234) The message data element carries the data payload for the frame. The message data typically has the same number of bytes as the described in the length element.

(235) The checksum is the logical addition (ignoring carry overflows) of the length byte and all of the bytes in the message data element. This may be used to ensure the integrity of the frame. Also, if a frame has been subjected to the replacement of 1Cs with 1B, 01, 1Bs with 1B, 02, or 1Ds with 1B, 03, the checksum is performed on the intended packet before it was encoded to remove the 1Cs, 1Bs or 1Ds. This provides another check of the packet's integrity.

(236) For messages that originate from the interface unit **14** the first byte of the message payload is desired to be **3E** hex. Similarly, to comply with the desired protocol, messages that originate from the sensor unit **12** the first byte of the message payload shall be **BE** hex.

(237) Reference throughout this specification to “one embodiment,” “an embodiment,” “some embodiments,” or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, appearances of the phrases “in one embodiment,” “in an embodiment,” “in some embodiments” and similar language throughout this specification may, but do not necessarily, all refer to the same embodiment.

(238) In one embodiment, a method for controlling irrigation comprises the steps of: generating an indication representing the amount of rain fall at a sensor unit; transmitting a signal comprising at least the indication from the sensor unit to an interface unit, wherein the interface unit is adapted to cause an interruption of programmed watering schedules of an irrigation controller; receiving the signal at the interface unit; determining, based at least on the indication from the signal, whether irrigation should be interrupted; and generating an interrupt command to interrupt irrigation.

(239) In another embodiment, a device for controlling irrigation comprises an interface unit. The interface unit comprises an input unit adapted to receive a signal from a sensor unit, the signal comprising an indication representing an amount of rain fall at the sensor unit. The interface unit also comprises a controller coupled to the input unit adapted to process the signal to determine based at least on the indication from the signal, whether irrigation executed by an irrigation controller should be interrupted and to generate an interrupt command to cause the interruption of the irrigation.

(240) In yet another embodiment, a method for wireless installation of an irrigation control device comprises the steps of: locating a first wireless unit at a first location; establishing a wireless path of communication between the first wireless unit and a second wireless unit remote from the first location; moving the second wireless unit to a plurality of possible installation locations, wherein the signal strength changes as the second wireless unit is moved; automatically determining the signal strength as the second wireless unit is moved; automatically displaying the signal strength at the second wireless unit as the second wireless unit is moved; and determining which of the plurality of possible installation locations to fix the second wireless unit based on the displayed signal strength.

(241) In a further embodiment, a device for controlling irrigation comprises a sensor unit adapted to sense an amount of rain fall; a two-way communication link coupling the sensor unit to an interface unit; and the interface unit adapted to receive information corresponding to the amount of rain fall via the two-way communication link from the sensor unit. The interface unit is further adapted to cause an interruption of irrigation executed by an irrigation controller based at least in part on the information from the sensor unit.

(242) In another embodiment, a method for controlling irrigation comprises the steps: sensing an amount of rain fall at a sensor unit; communicating information corresponding to the amount of rain fall from the sensor unit via a two-way communication link to an interface unit; and causing, at the interface unit, an interruption of irrigation executed by an irrigation controller based at least in part on the information from the sensor unit, the interface unit being adapted to communicate with the sensor unit via the two-way communication link.

(243) In yet another embodiment, a method for controlling irrigation comprises the steps of: generating an indication representing the amount of rain fall at a sensor unit; transmitting a signal comprising at least the indication from the sensor unit to an interface unit, wherein the interface unit is adapted to cause an interruption of programmed watering schedules of an irrigation controller and wherein the interface unit is separate from the irrigation controller; receiving the signal at the interface unit; receiving user input relating to the interruption of the programmed watering schedules of the irrigation controller via a user interface integrated with the interface unit, wherein the user input defines a rain interruption threshold; determining, at the interface unit, based at least on the indication from the signal and the user input, whether irrigation should be interrupted; and generating an interrupt command to interrupt irrigation in the event it is determined that the irrigation should be interrupted.

(244) While the invention herein disclosed has been described by means of specific embodiments, examples and applications thereof, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope of the invention set forth in the claims.

## Claims

1. A wireless rain sensor comprising: a housing at least partially covering a first sensor, a controller and a wireless transmitter; wherein the first sensor comprises a material configured to change in response to rain fall and/or an absence of the rain fall; and wherein the wireless transmitter is coupled to the controller and is configured to transmit wireless signals, at least one wireless signal comprising data corresponding to the change of the material.
2. The wireless rain sensor of claim 1, wherein a portion of the material comprises a moisture absorptive material that is fixed such that the moisture absorptive material expands in a direction away from the portion.

3. The wireless rain sensor of claim 2, wherein the first sensor further comprises a spring fixed at one end and coupled at a second end to a movable component coupled to the moisture absorptive material, wherein the spring is configured to cause the movable component to apply a biasing pressure on the moisture absorptive material in a direction against expansion of the moisture absorptive material.
  4. The wireless rain sensor of claim 3, wherein the movable component is coupled to a wiper of a fixed resistive sensing element.
  5. The wireless rain sensor of claim 4, wherein the resistive element and the wiper form a linear potentiometer.
  6. The wireless rain sensor of claim 5, wherein expansion of the moisture absorptive material changes the position of the linear wiper on the potentiometer and causes a change in resistance.
  7. The wireless rain sensor of claim 6, wherein the change in the resistance is detected by the controller to provide an analog continuous measurement corresponding to an amount of rain fall.
  8. The wireless rain sensor of claim 1, wherein the housing comprises an opening configured to allow rain fall to enter the housing into a volume.
  9. The wireless rain sensor of claim 8, wherein the material of the first sensor is located in the volume to be contacted by rain fall.
  10. The wireless rain sensor of claim 8, wherein the housing comprises a plurality of vents configured to permit evaporation from the material to leave the volume.
  11. A method of wirelessly sensing rain, the method comprising: providing a housing at least partially covering a first sensor, a controller and a wireless transmitter, wherein the first sensor comprises a material configured to change in response to rain fall and/or an absence of the rain fall; not setting a rain fall threshold at the wireless rain sensor; and transmitting, via the wireless transmitter, at least one wireless signal comprising data corresponding to the change of the material.
  12. The method of claim 11, wherein a portion of the material comprises a moisture absorptive material that is fixed such that the moisture absorptive material expands in a direction away from the portion.
  13. The method of claim 12, wherein the first sensor further comprises a spring fixed at one end and coupled at a second end to a movable component coupled to the moisture absorptive material, wherein the spring is configured to cause the movable component to apply a biasing pressure on the moisture absorptive material in a direction against expansion of the moisture absorptive material.
  14. The method of claim 13, wherein the movable component is coupled to a wiper of a fixed resistive sensing element.
  15. The method of claim 14, wherein the resistive element and the wiper form a linear potentiometer.
  16. The method of claim 15, wherein expansion of the moisture absorptive material changes the position of the linear wiper on the potentiometer and causes a change in resistance.
  17. The method of claim 16, wherein the change in the resistance is detected by the controller to provide an analog continuous measurement corresponding to an amount of rain fall.
  18. The method of claim 11, wherein the housing comprises an opening configured to allow rain fall to enter the housing into a volume.
  19. The method of claim 18, wherein the material of the first sensor is located in the volume to be contacted by rain fall.
  20. The method of claim 18, wherein the housing comprises a plurality of vents configured to permit evaporation from the material to leave the volume.
-