

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250262641

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Downey; Adam D. et al.

---

### System And Method For Driving An Ultrasonic Handpiece With A Linear Amplifier

---

#### Abstract

A control console for a powered surgical tool. The console includes a transformer that supplies the drive signal to the surgical tool. A linear amplifier with active resistors selectively ties the ends of the transformer primary winding between ground and the open circuit state. Feedback voltages from the transformer windings regulate the resistances of the active resistors.

---

**Inventors:** Downey; Adam D. (Kalamazoo, MI), Butler; Neal R. (Acton, MA), Rhodes; Scott A. (North Andover, MA)

**Applicant:** Stryker Corporation (Portage, MI)

**Family ID:** 1000008589447

**Assignee:** Stryker Corporation (Portage, MI)

**Appl. No.:** 19/203948

**Filed:** May 09, 2025

#### Related U.S. Application Data

parent US continuation 18763438 20240703 PENDING child US 19203948

parent US continuation 18227416 20230728 parent-grant-document US 12064790 child US 18763438

parent US continuation 17460509 20210830 parent-grant-document US 11717853 child US 18227416

parent US continuation 16589815 20191001 parent-grant-document US 11241716 child US 17460509

parent US continuation 15805849 20171107 parent-grant-document US 10449570 child US 16589815

## Publication Classification

**Int. Cl.:** **B06B1/02** (20060101); **A61B17/00** (20060101); **A61B17/14** (20060101); **A61B17/32** (20060101); **A61B18/00** (20060101); **A61B18/14** (20060101); **A61B18/18** (20060101); **A61B90/98** (20160101); **A61F9/007** (20060101); **H02M3/158** (20060101); **H03F1/02** (20060101); **H03F3/45** (20060101)

## U.S. Cl.:

**CPC** **B06B1/0253** (20130101); **A61B17/320068** (20130101); **A61F9/00745** (20130101); **B06B1/0246** (20130101); **H03F1/0216** (20130101); A61B2017/00017 (20130101); A61B2017/0003 (20130101); A61B2017/00199 (20130101); A61B2017/00477 (20130101); A61B2017/00973 (20130101); A61B17/142 (20161101); A61B2017/320069 (20170801); A61B2017/32007 (20170801); A61B2018/00029 (20130101); A61B2018/00577 (20130101); A61B18/14 (20130101); A61B2018/1807 (20130101); A61B90/98 (20160201); A61B2217/005 (20130101); A61B2217/007 (20130101); B06B2201/55 (20130101); B06B2201/76 (20130101); H02M3/158 (20130101); H03F3/45475 (20130101); H03F2200/541 (20130101)

---

## Background/Summary

**RELATED APPLICATIONS** [0001] This application is a continuation of U.S. patent application Ser. No. 18/763,438 filed on Jul. 3, 2024, which is a continuation of U.S. patent application Ser. No. 18/227,416 filed on Jul. 28, 2023, which is a continuation of U.S. patent application Ser. No. 17/460,509 filed on Aug. 30, 2021, which is a continuation of U.S. patent application Ser. No. 16/589,815 filed on Oct. 1, 2019, which is a continuation of U.S. patent application Ser. No. 15/805,849 filed on Nov. 7, 2017, which is a continuation of PCT Application No. PCT/US2016/031651 filed on May 10, 2016, which claims priority to U.S. Provisional Application No. 62/159,672 filed on May 11, 2015, the disclosures of which are all hereby incorporated herein by reference in their entirety.

## GENERAL FIELD

[0002] This invention relates generally to an ultrasonically driven surgical tool system. More particularly, this invention relates to an ultrasonic tool system with a console capable of outputting drive signals over a wide range of frequencies and a wide range of voltages.

## BACKGROUND

[0003] Ultrasonic surgical instruments are useful surgical instruments for performing certain medical and surgical procedures. Generally, an ultrasonic surgical tool includes a handpiece that contains at least one piezoelectric driver. A tip is mechanically coupled to the driver and extends forward from the housing or shell in which the driver is disposed. The tip has a head. The head is provided with features, often teeth or flutes, dimensioned to accomplish a specific medical/surgical task. The handpiece is part of an ultrasonic tool system. The system also includes a control console. The control console supplies an AC drive signal to the driver. Upon the application of the drive signal to the driver, the driver cyclically expands and contracts. The expansion/contraction of the driver induces a like movement in the tip and, more particularly, the head of the tip. When the tip so moves, the tip is considered to be vibrating. The vibrating head of the tip is applied against

tissue to perform a specific surgical or medical task. For example, some tip heads are applied against hard tissue. One form of hard tissue is bone. When this type of tip head is vibrated, the back and forth vibrations of the tip head remove, saw, the adjacent hard tissue. Other tip heads are designed to be placed against soft tissue. When this tip head vibrates the teeth often remove the tissue by a cutting action. Other ultrasonic tips remove tissue by inducing cavitation in the tissue and surrounding fluid. Cavitation occurs as a result of the tip head moving back and forth. Specifically, as a result of these vibrations, small cavities form in the fluid located immediately adjacent the tissue. These cavities are very small zones of extremely low pressure. A pressure differential develops between contents of the cells forming the tissue and these cavities. Owing to the magnitude of this pressure differential, the cell walls burst. The bursting of these cell walls, removes, ablates, the cells forming the tissue.

[0004] The head of an ultrasonic tip is often relatively small. Some heads have diameters of less than 1.0 cm. An ultrasonic tool essentially only removes the tissue adjacent to where the head is applied. Owing to the relatively small surface area of their heads, ultrasonic handpieces have proven to be useful tools for precisely removing both hard and soft tissue.

[0005] Some ultrasonic tips are provided with a through bore. Simultaneously with the application of a drive signal to this type of tip, a suction is drawn through the bore. The suction draws away the debris created by tissue removal process. This is why some ultrasonic tools are sometimes called ultrasonic aspirators.

[0006] For an ultrasonic surgical instrument, sometimes called a handpiece or a tool, to efficiently function, a drive signal having the appropriate characteristics should be applied to the tool. If the drive signal does not have the appropriate characteristics, the tip head may undergo vibrations of less than optimal amplitude. If the handpiece is in this state, the ability of the handpiece to, at a given instant, remove tissue may be appreciably reduced.

[0007] One means of ensuring that an ultrasonic handpiece operates efficiently is to apply a drive signal to the handpiece that is at the resonant frequency of the handpiece. When the drive signal is at a given voltage or current, the application of the drive signal at the resonant frequency induces vibrations in the tip that are large in amplitude in comparison to the application of the same voltage at a frequency that is off resonance.

[0008] Still other ultrasonic tool systems are designed to apply a drive signal at the anti-resonant frequency of the handpiece. The anti-resonant frequency may be a frequency at which the handpiece would have the highest impedance. Sometimes it is desirable to apply a drive signal that is at a frequency somewhere between resonant and anti-resonant frequencies of the handpiece.

[0009] Further, the amplitude of the tip vibrations is also related to the potential, the voltage, of the drive signal. Generally, the amplitude of the tip vibrations is proportional to the voltage of the drive signal. There is however, typically a voltage that, once exceeded, will not result in an increase in the amplitude of the tip vibrations.

[0010] Internal to the console are the components that generate the drive signal. Generally, the components integral with the console can be broken down into four main sub-assemblies. A first sub-assembly includes the sensing components. These components monitor the characteristics of the drive signal sourced to the handpiece. An input/output assembly serves as an interface through which the surgeon enters commands regarding the characteristics of the drive signal that is to be applied to the handpiece and over which information regarding the status of the operation of the system is displayed. The third assembly is the controller. The controller, based on the user-entered commands and the signals from the sensing components, generates control signals. The controller also generates information that is presented on the input/output assembly.

[0011] The control signals generated by the controller are applied to the fourth sub-assembly of console components, the amplifier. This is because, owing to the limitations of components forming the controller, the control signals typically have potentials of 10 Volts or less and often 5 Volts or less. For the drive signal to induce the desired contractions and expansions of the

transducers, the signal typically needs to have a potential of at least 500 volts and often 1000 volts. The amplifiers of many consoles amplify the control signal so the output signal produced by the amplifier is at the potential at which the output signal can function as the drive signal applied to the handpiece.

[0012] Applicant's SONOPET® Ultrasonic Aspirator includes a console with components designed to generate and apply a variable drive signal to the attached handpiece. Internal to the console is a resonance circuit. At the time of manufacture of the console, the inductance and capacitance of this resonance circuit are set as a function of the impedance of the specific handpiece with which the console is intended to be used. The characteristics of the drive signal output by the console are set as a function of the voltage across this impedance circuit.

[0013] The control consoles provided with many ultrasonic tool systems include amplifiers capable of outputting drive signals that, over narrow frequency ranges, foster the desired handpiece driver expansions and contractions. For example, some control consoles output drive signals that have a frequency between 25.2 kHz and 25.6 kHz. This type of control console works well with a handpiece that includes drivers designed for actuation by drive signals have a frequency within this range of frequencies. If a handpiece with drivers designed to receive drive signals over a different frequency range is attached to the console, the responsiveness of the handpiece to the out of range drive signals will be less than optimal.

[0014] As a consequence of this limitation, if a facility wants to use ultrasonic handpieces to which appreciably different drive signals are applied, it may be necessary to provide plural control consoles. Specifically, one console would be used to provide drive signals to handpieces to which drive signals having a first set of characteristics are applied. A second console is used to provide drive signals to the handpieces to which drive signals having a second set of characteristics are applied. Having to provide these plural consoles that differ only in the form of the drive signals they generate adds to the expense and administrative burden of operating the facility using this equipment.

[0015] Further, a console may not generate the optimal drive signals for some operating states even when the console is generating the signals within the intended frequency range of drive signals the console is designed to produce. This is because at one or both ends of the range of voltages of the drive signals the console is intended to produce, the amplifier internal to the console may not provide a linear response to input signals used to establish the voltage of the drive signals.

[0016] In addition, some tips are designed to, when actuated, vibrate with a motion that is combination of two distinct motions. For example, some tips are designed to engage in vibrational motion that is the sum of two components. The first component is the longitudinal vibration. This is the back and forth vibration along the longitudinal axis of the tip. The second component is the rotational or torsional vibration. This motion is a back and forth rotational motion around the longitudinal axis of the tip. Generally, a tip able to vibrate simultaneously in two modes is referred to as a tip able to engage in a bi-modal vibration. A tip designed to vibrate simultaneously in three or more modes is referred to as a tip able to engage in multi-modal vibration.

[0017] For a tip to engage in bi-modal or multi-modal vibrations, it is desirable to apply a drive signal to the tip that is a composite of the signals best suited to drive the tip in each of its vibratory modes. Often these signals are at different frequencies. A console that can only generate drive signals over a narrow range of frequencies is often for unsuitable for generating a drive signal that is composite of components that have frequencies that may differ by 1,000 Hz or more.

## SUMMARY

[0018] This invention is directed to a new and useful ultrasonic tool system. The system of this invention includes a console to which a handpiece is attached. The console supplies the drive signal that actuates the drivers internal to the handpiece. It is a further feature of this invention, that the console is able to source drive signals over both a wide range of frequencies and a wide range of potentials. The console of this invention can thus be used to provide drive signals to different

handpieces that require drive signals with different characteristics.

[0019] A further feature of the system of this invention is that the console is designed to have a relatively low internal energy loss. More specifically, the console of this invention, while having a relatively low internal energy loss is able to, when necessary, rapidly ramp up the potential of the drive signal applied to the handpiece drivers. This minimizes the time lag between when a handpiece tip is applied to tissue to perform a procedure and when the tip vibrates over the distance desired by the practitioner using the tip.

[0020] The console of this system includes an amplifier assembly that typically consists of: a linear amplifier; a power supply; and a transformer. The power supply applies a DC signal to a center tap of the primary winding of the transformer. The linear amplifier selectively pulls the opposed ends of the transformer primary winding to ground or essentially an open circuit state. The sequenced connection of the ends of the transformer primary winding to ground or the open circuit causes an AC signal to develop across the windings. This causes induces an AC signal, to appear across the transformer secondary winding. The signal that appears across the transformer secondary winding is the drive signal applied to the handpiece drivers.

[0021] The linear amplifier includes transistors tied to the ends of the transformer primary windings. The amplifier controls the application of signals to the transistors. The transistors, in turn, selectively connect and disconnect the ends of the primary winding to ground. The transistors thus function as active resistors.

[0022] In preferred versions of the invention, the linear amplifier includes a negative feedback loop. This negative feedback loop controls the application of signals to the transistors.

[0023] In preferred versions of the invention at least some voltage is always present at the gate or base of each transistor. This ensures the rapid response of the transistor when it is necessary to turn on the transistor. Also, in some preferred versions of the invention the transistors attached to the transformer primary winding are MOSFETS.

[0024] In preferred versions of the invention the voltage of the signal the power supply applies to the center tap can be varied.

[0025] A processor, also part of the control console, sets the DC voltage level of the signal output by the power supply and applies an input signal to the linear amplifier. More particularly, the processor sets the DC voltage of the signal output by the power supply so that the minimum voltage present across the transistors is ideally at least at a headroom voltage. This is to ensure that the transistors are always in saturation. The processor also normally maintains the voltage across the transistors to level that typically does not appreciably exceed the headroom voltage. This is to minimize the loss of heat by the transistors. Also by maintaining a headroom voltage, the amplifier can rapidly increase the potential of the drive signal without having the initially increased drive signal appear as a clipped signal.

[0026] The processor regulates the signals output by the linear amplifier and the power supply to substantially eliminate the possibility that, when the voltage of the drive signal is increased, a jump in primary winding voltage will take the transistors out of saturation. The processor regulates the signals output by the power supply so that when the voltage of the drive signal is reduced, the center tap voltage is not allowed to drop so a subsequent need to increase the voltage the drive signal will not appreciably slow the increase in this voltage.

[0027] While one specific form of this invention is an ultrasonic surgical tool system it should be understood that the console of this invention may have other applications. Thus, the console of this tool system may be employed to apply an AC drive signal to powered surgical handpiece where the power generating unit is assembly other than a set of ultrasonic drivers.

---

## Description

## BRIEF DESCRIPTION OF THE DRAWINGS

[0028] The invention is pointed out with particularity in the claims. The above and further features and advantages of this invention are understood from the following Detailed Description taken in conjunction with the accompanying drawings in which:

[0029] FIG. **1** depicts the basic components of an ultrasonic tool system that includes the features of this invention;

[0030] FIG. **2** is a diagrammatic depiction of the mechanical components of the tool, the handpiece, of the system;

[0031] FIG. **3** is a block diagram of the electrical components of both the control console and handpiece components of the system of this invention;

[0032] FIG. **4** is a block diagram of the linear amplifier and

[0033] the DC power supply internal to the control console;

[0034] FIG. **5** is a schematic and block diagram of the some of the components integral with the Boost converter of the power supply of the control console;

[0035] FIG. **6** is an assembly diagram illustrating how FIGS. **6A-6D** form a schematic drawing of the linear amplifier of the control console of this invention;

[0036] FIGS. **6A-6D** are schematic drawings illustrating the linear amplifier;

[0037] FIG. **7** depicts the waveform present at the output of the operational amplifier of the linear amplifier;

[0038] FIGS. **8A** and **8B** depict the waveforms present at the outputs of the rectifier and splitter of the linear amplifier;

[0039] FIG. **9A** depicts the waveform of the current produced by a first one of the current sources of the linear amplifier;

[0040] FIG. **9B** depicts the waveform of the current produced by a second one of the current sources of the linear amplifier;

[0041] FIG. **10** depicts the voltages present at each end of the transformer primary winding;

[0042] FIG. **11** depicts the voltages present across the transformer primary winding when the voltages of FIG. **10** are present at each end of the winding;

[0043] FIG. **12** depicts the voltage present across the transformer primary winding when the minimum voltage is at the headroom voltage;

[0044] FIG. **13** depicts the voltage present across the transformer primary winding when, owing to an increase in the voltage amplitude, the minimum voltage is below the headroom voltage;

[0045] FIG. **14** depicts types of data stored in the memory internal to the handpiece;

[0046] FIG. **15** is an assembly diagram that depicts how FIGS. **15A-15D** are assembled together to represent the software modules run on the processor internal to the control console to regulate the characteristics of the drive signal output by the console;

[0047] FIGS. **15A-15D** illustrate software modules run on the processor internal to the control console to regulate the characteristics of the drive signal output by the console;

[0048] FIG. **16** is a flow chart of process steps executed by the base voltage limiter module run on the console processor;

[0049] FIG. **17** is a flow chart of process steps executed by the power supply voltage limiter module run on the console processor; and

[0050] FIG. **18** is a schematic drawing of an alternative circuit of this invention for producing a signal representative across the transistors that form the active resistors of the linear amplifier.

## DETAILED DESCRIPTION

[0051] An ultrasonic tool system **40** that includes the features of this invention is now generally described by reference to FIGS. **1** and **2**. System **40** includes a handpiece **330**. Handpiece **330** includes a body or shell **342** that forms the proximal end of the handpiece. ("Proximal" is understood to mean towards the practitioner holding the handpiece, away from the site to which the

handpiece is applied. “Distal” is understood to mean away from the practitioner, towards the site to which the handpiece is applied.)

[0052] One or more vibrating piezoelectric drivers **344** (four shown) are disposed inside shell **342**. In FIG. **2** the handpiece shell **342** is not seen so the internal components of the handpiece **330** are exposed. Each driver **344** is formed from material that, when a current is applied to the driver, undergoes a momentary expansion or contraction. These expansions/contractions are on the longitudinal axis of a driver **344**, the axis that extends between the proximally and distally directed faces of the driver. A pair of leads **346** (FIG. **3**) extends away from each driver **344**. The leads **346** are attached to the opposed proximally and distally directed faces of the drivers **344**. Many, but not all handpieces **330**, include piezoelectric drivers **348** that are disc shaped. These drivers **348** are arranged end to end in a stack. Leads **346** are the components of system **40** which the current, in the form of a drive signal, is applied to the drivers **348**. Insulating discs **350**, one shown, separate adjacent leads **346** connected to adjacent drivers **348** from each other. In FIG. **2**, drivers **348** are shown spaced apart from each other. This is for ease of illustrating the components. In practice insulating drivers **344** and discs **350** tightly abut.

[0053] A post **336** extends longitudinally through drivers **348** and insulating discs **350**. The post **336** extends through the drivers **344** along the collinear longitudinal axes of the drivers. Not seen are through bores internal to the drivers **348** and insulating discs **350** through which the post **336** extends. Post **336** projects outwardly of both the most proximally located driver **40** and the most distally located driver.

[0054] A proximal end mass **334** is attached to the proximally directed face of the most proximally located driver **348**. The exposed proximal end section of the post **336** is fixedly attached to mass **334**. If post **336** is threaded, then mass **334** may be a nut.

[0055] A horn **356** extends forward from the distally directed face of the most distally located driver **344**. While not shown, an insulating disc **350** may be between the distal driver **344** and horn **356**. Horn **356** has a base with a diameter approximately equal to the diameter of the drivers **344**. Extending distally forward from the drivers **348**, the diameter of the horn **356** decreases. The exposed distal end section of post **336** is affixed to the horn **356**. If the post **336** is threaded, the horn base may be formed with a threaded closed end bore (not identified) for receiving the post **336**. Handpiece **330** is constructed so that the stack of drivers **344** is compressed between proximal end mass **334** and horn **356**.

[0056] A tip **360** extends forward from the distal end of the horn **356**. A coupling assembly, represented by a collar **358**, typically removably holds the tip **360** to horn **356** and therefore the rest of the handpiece **330**. The structure of the coupling assembly is not part of the present invention. Tip **360** includes an elongated stem **362**. Stem **362** is the portion of the tip that, through the coupling assembly, is attached to the horn **356**. Stem **362** extends forward of the handpiece shell **342**. Tip **360** is formed to have a head **364** at the distal end of stem **362**. Some tip heads **364** have smooth surfaces. Some heads **364** are formed with teeth **366**. The geometry of the head **364** is not part of the present invention. Tip head **364** is the portion of the handpiece **330** applied to the site on the patient at which the procedure is performed.

[0057] Some tips **360** are provided with teeth designed to be applied directly to hard tissue, bone. When this type of tip is reciprocated, the teeth cut the tissue in the same manner in which a conventional saw blade cuts tissue.

[0058] A sleeve **370**, depicted as a ring in FIG. **2**, is typically disposed over tip stem **362**. Sleeve **370** typically extends from a location near where the stem is attached to the horn **356** to a location approximately 0.5 cm proximal to the head **364**. Collectively the handpiece **330**, tip **360** and sleeve **370** are constructed so that the sleeve defines a fluid flow conduit that extends between the outer surface of the tip and the surrounding inner surface of the sleeve. The sleeve **370** also has a fitting (not seen) adjacent the proximal end of the sleeve that extends to this conduit. The conduit is open at the distal end of the sleeve. When the handpiece **330** is in use, irrigating solution is flowed from

the sleeve fitting, down the sleeve and discharged adjacent the tip head **364**. In some versions of the system, the fluid serves as a medium through which the mechanical vibrations of the tip head are transferred to the tissue. This irrigating solution also functions as a heat sink for the thermal energy developed by the tip head as a consequence of the vibration of the head.

[0059] While not seen, the handpiece post **336**, horn **356** and tip **360** are often formed with conduits. These conduits collectively define a fluid flow path from the tip head **364** to the proximal end of the handpiece **330**. When the handpiece is in operation, suction is drawn through these conduits. The suction draws the irrigating fluid discharged through the sleeve **370** away from the site to which the tip is applied. Entrained in this irrigating fluid are debris generated as a result of the actuation of the tip **360**. The suction also draws the tissue towards the tip head. The shortening of the distance between the tip head and the tissue improves the transmission of the mechanical vibrations from the tip head to the tissue.

[0060] A handpiece **330** of system **40** able to draw a suction is sometimes referred to as an aspirator or an ultrasonic aspirator.

[0061] Handpiece **330** also includes a memory **338**. Memory **338** contains data describing the characteristics of the handpiece. Memory **338** may take the form of an EPROM, an EEPROM or an RFID tag. The structure of the memory is not part of the invention. The memory **338** contains data that identifies the handpiece. Memory **338** also contains data describing characteristics of the drive signal that can be applied to the handpiece drivers **348**. Most handpieces **330** of this invention include a memory that, in addition to containing data capable of being read are able to store data written to the memory after manufacture of the handpiece. Ancillary components not illustrated are mounted to the handpiece to facilitate the reading of data from and the writing of data to the memory. These components consist of one or more of the following: conductors; exposed contacts/contact pins; a coil/antenna; or an isolation circuit.

[0062] A control console **50** is also part of system **40** of this invention. Control console **50** sources drive signals over a cable **326** to which handpiece **330** is connected. In many but not all versions of system **40**, cable **326** and handpiece **330** are assembled as a single unit. The drive signals are applied to the drivers **344**. At any given instant, the same drive signal is applied to each driver **344**. The application of the drive signals causes the drivers to simultaneously and cyclically expand and contract. A stack of drivers **344** is often between 1 and 5 cm in length. The distance, the amplitude, of movement over a single expansion/contraction cycle of the drivers may be between 1 and 10 microns. Horn **356** amplifies this movement. Consequently, the distal end of the horn **356** and, by extension, tip head **364**, when moving from the fully contracted position to the fully extended position, moves typically a maximum of 1000 microns and often 500 microns or less. Some tips **360** are further designed so the longitudinal extension/retraction of the tip stem **362** also induces a rotational movement in the head. This rotational movement is sometimes referred to as a torsional movement. When handpiece **330** is actuated to cause the cyclic movement of the tip, the head **364** is considered to be vibrating.

[0063] The components internal to the control console **40**, generally seen in FIG. **3**, includes a power supply **84**. Power supply **84** outputs a variable voltage between 25 and 250 VDC. The signal output by the power supply is applied to the center tap of the primary winding of an isolation transformer **250**. The potential of the signal output by the power supply **84** is set based on a POWER\_SUPPLY\_CONTROL (PS\_CNTRL) signal applied to the power supply. The opposed ends of the primary winding of the transformer are tied to an amplifier **115**. Amplifier **115** applies AC signals that vary in both potential and frequency to the ends of the transformer primary winding. A BASE signal applied to amplifier **115** as a control signal regulates the frequency and potential of the signals output by the amplifier.

[0064] The AC signal developed across the primary winding of transformer **250** induces an AC signal across the secondary winding **258** of the transformer **250**. This signal across the secondary winding of transformer **250** is the drive signal applied over cable **326** to the handpiece drivers **348**.



[0065] Transformer **250** includes a tickler coil **256**. The voltage of the signal present across tickler coil **256** is applied to a voltage measuring circuit **66**. Based on the signal across tickler coil **256**, circuit **66** produces a signal representative of Vs the magnitude and phase of the potential of the drive signal across the drivers **344**. Given the function and location of tickler coil **256**, this component is sometimes referred to as a sense winding. A coil **262**, also disposed in control console **50**, is located in close proximity to one of the conductors that extends from the transformer secondary winding **258**. The signal across coil **262** is applied to a current measuring circuit **68**. Circuit **68** produces a signal that represents the magnitude and phase of current is, the current of the drive signal sourced to the handpiece drivers **344**.

[0066] The signals representative of the voltage and current of the drive signal applied to handpiece **330** are applied to a processor **80** also internal to the control console **50**. Control console **50** also includes a memory reader **78**. Memory reader **78** is capable of reading the data in handpiece memory **338**. The structure of memory reader **78** complements the handpiece memory **338**. Thus, memory reader can be: an assembly capable of reading data in an EPROM or EEPROM or an assembly capable of interrogating and reading data from an RFID tag. In versions of the invention in which the data read from the memory **338** are read over the conductors over which the drive signal is sourced to the handpiece **32**, the memory reader **78** may include an isolation circuit. Data read by reader **78** are applied to processor **80**.

[0067] Connected to control console **64** is an on/off switch. In FIGS. **1** and **3**, the on/off switch is represented by a foot pedal **54**. The state of pedal **54** is monitored by processor **80**. The on/off switch is the user actuated control member that regulates the on/off state of the system **30**. In FIG. **1**, foot pedal **54** is shown as being part of a foot pedal assembly that includes plural pedals. The added pedals may be used to control devices such as irrigation pump, a suction pump or a light. These supplemental devices are not part of the current invention.

[0068] Control console **50** is shown as having a slide switch **56**. Like foot pedal **54**, the state of switch **56** is monitored by processor **80**. Switch **56** is set by the practitioner to control the magnitude of the amplitude of the vibrations of tip head **52**. Foot pedal **54** and switch **56** are understood to be general representations of the means of entering on/off and amplitude setting commands to system **40**. In some constructions of the system a single control member may perform both functions. Thus the system may be configured so that when a lever or foot pedal is initially first depressed, the system causes tip head to undergo a vibration cycle that is of relatively small amplitude. As a result of the continued depression of the lever or foot pedal, the control console resets the drive signal applied to the handpiece so as to cause tip head **364** to undergo vibration cycles that are of a larger magnitude.

[0069] A display **82** is built into control console **50**. The image on display **82** is shown as being generated by processor **80**. Information depicted on display **82** includes information identifying the handpiece and possibly the tip; information describing characteristics of the operating rate of the system. Display **82** may be a touch screen display. In these versions of the invention, by depressing images of buttons presented on the display **82** command can be entered into processor **80**. Not shown are interface components between the display **82** and the processor **80**. These interface components facilitate the presentation of images on the display **82** and the entry of commands into the processor **80**.

[0070] The processor **80** regulates the outputting of the drive signal from the control console **40**. The practitioner-controlled inputs upon which the processor **80** sets the drive signals are the state of the on/off pedal **54** and the state of the slide switch **56**. Commands entered through the display **82** may also control the setting of the drive signal. The characteristics of the drive signal are also set based on data read from the handpiece memory **338**. The characteristics of the drive signal are also employed by the console as feedback signals that further contribute to the setting of the drive signal. Based on these plural inputs, processor **80** outputs the signals that control the drive signal. These signals are the POWER\_SUPPLY\_CONTROL signal applied to power supply **84** and the

BASE signal applied to amplifier **115**.

[0071] FIG. **4** is a block diagram of sub-assemblies internal to the console that form power supply **84** and amplifier **115**. The power supply **84** includes a constant voltage power supply **86**. In one version of the invention constant voltage power supply **86** outputs a 24 VDC signal. Not identified are any transformers, rectifiers, filters and voltage regulators that, as part of voltage supply **86**, convert the line voltage to the stable DC voltage. Also not identified are voltage sources internal to the console that produce the constant voltage signals needed to run the components internal to the console such as processor **80** and display **82**. These voltage sources include the voltage sources that produce the below discussed V.sub.CC and -V.sub.EE voltages.

[0072] The stable DC voltage output by power supply **86** is output to an adjustable boost converter **88**, also part of the power supply **84**. Boost converter **88** amplifies the potential of the signal from constant voltage power supply **86** to a different potential and outputs the signal as the VAMP signal. In one version of the invention, the boost converter **88** converts the received potential from the constant voltage power supply to a boosted signal between 25 and 500 VDC. In other versions of the invention, the Boost converter **88** produces a variable output signal between 25 and 250 VDC. The POWER\_SUPPLY\_CONTROL signal output by the processor **80** is applied to the Boost converter **88**. The POWER\_SUPPLY\_CONTROL signal functions as the control input signal upon which the Boost converter **88** sets the potential of the VAMP signal.

[0073] Amplifier **115** is a linear amplifier. One of the sub-assemblies of amplifier **115** is the summing amplifier **122**. There are two inputs into the summing amplifier **122**. A first one of these inputs is the BASE signal from the processor **80**. A second input into operational amplifier is a feedback signal the source of which is discussed below. Based on the input signals, the summing amplifier **122** produces a feedback adjusted BASE signal.

[0074] The feedback adjusted BASE signal is applied to a rectifier and splitter **138**. Rectifier and splitter **138** splits the feedback adjusted BASE signal into positive and negative components. The negative component of the feedback adjusted BASE signal is applied to an inverting voltage controlled current source **156**. The positive component of the feedback adjusted BASE signal is applied to a non-inverting voltage controller current source **174**. From FIG. **6D** it can be seen that the output signal from current source **156** is applied to the gate of a MOSFET **162**. The output of current source **174** is applied to the gate of a MOSFET **184**.

[0075] Current sources **156** and **174** are DC biased. Each current source **156** and **174** is on even when the source does not receive the component of the feedback adjusted BASE signal applied to the source. The drains of MOSFETs **162** and **184** are tied to the opposed ends of transformer primary winding **252**.

[0076] The signals present at the drains of MOSFETs **162** and **184** are also applied to the inputs of a differential amplifier **118**, also part of linear amplifier **115**. The output signal from the differential amplifier **118** is the feedback signal is applied to summing amplifier **122**.

[0077] The signals present at the drains of MOSFETS **162** and **184** are also applied to a headroom monitor **190**. Headroom monitor **190** monitors these signals to ensure that there is a sufficient voltage across the MOSFETs **162** and **184** to ensure these MOSFETs are always in saturation. Processor **80** uses the measurements made by the headroom monitor **190** to regulate the voltage of the VAMP signal produced by the boost converter **88**.

[0078] As seen by reference FIG. **5**, boost converter **88** includes plural boost circuits. Each boost circuit includes inductor **110**. One end of inductor **110** is tied to a constant voltage bus **91**. Bus **91** is the conductor over which the constant voltage signal from power supply **86** is applied to the boost converter **88**. In some versions of the invention a 24 VDC signal is present on bus **91**. The opposed end of the inductor **110** is tied to an n-channel FET **112**. The source of the FET **112** is tied to ground through a resistor **114**, also part of the boost circuit. Each boost circuit includes a diode **111** the anode of which is connected to the junction of the inductor **110** and FET **112**. The gating of each FET **112** is controlled by a DC/DC controller **90**. In the illustrated version of the invention,

the controller **90** outputs the gate signals to the two illustrated FETs **112**. In one version of the invention the LTC3862 Multi-Phase Current Mode Step-Up DC/DC Controller available from Linear Technology Corporation of Milpitas, California can function as the DC/DC controller **90**. Each gate signal output by the controller **90** is applied to a gate driver **92**. In one version of the invention the TC4422 9 Amp High-Speed MOSFET Driver available from the Microchip Company of Chandler, Arizona is employed as the gate driver **92**.

[0079] The cathodes of the plural diodes **111** are connected to a single rail **117**. A capacitor **113** is tied between rail **117** and ground.

[0080] The signal present on rail **117** is the output signal, VAMP, from the boost amplifier applied to the center tap of the primary winding **252** of transformer **250**. The signal present at rail **117** is also applied to ground through series connected resistors **96** and **98**. The POWER\_SUPPLY\_CONTROL signal from processor **80** is applied to through a resistor **97** to the junction of resistors **96** and **98**. The signal present at the junction of resistors **96**, **97** and **98** is applied to the feedback input of the DC/DC controller **90**. Not illustrated are the resistors and capacitors connected to the other pins of the controller **90** to regulate variables such as blanking, duty cycle, operating frequency and phase.

[0081] Generally, it is understood that each FET **112** is cyclically gated on and off. When each FET **112** is gated on, there is current flow through the associated inductor **110**. When the FET **112** is gated off, the energy stored in the magnetic field around the inductor **110** causes current to flow through the adjacent diode **111**. The charge of this current is stored in capacitor **113**. During a subsequent turning on of the FET **112** the voltage present at the junction of inductor **110**, the diode **111** and FET **112** goes to ground. This process results in an increase in the potential of the signal present on the rail **117** over the potential of the signal applied to the inductors **110**.

[0082] Plural boost circuits consisting of an inductor **110**, a diode **111**, a FET **112** and resistor **114** are provided. The plural boost circuits are gated on and off at different times to smooth the voltage of the signal present on rail **117**. The DC/DC controller **90** controls the on and off gating of the boost circuits. Controller **90** regulates this gating based on the feedback signal to ensure that the voltage present on rail **117** is at the desired potential.

[0083] In FIG. 5, boost converter **88** is shown as having a single DC/DC controller **90** and two boost circuits. This is for ease of illustration and to minimize redundancy. In some versions of the invention, to reduce ripple of the DC signal present on rail **117**, the boost converter **88** has more than two boost circuits. In some versions of the invention, the boost converter can have six or more boost circuits. Many known DC/DC controllers are known to only be able to gate two Boost converters. Accordingly, many boost power supplies of this application will also have plural DC/DC controllers **90**. Not shown are the connections between these plural DC/DC controllers that regulate when each controller gates the boost circuits attached to the controller. More specifically, the DC/DC controllers are configured so the multiple boost circuits are gated on and off at different times. By providing signals from the plural converters, the voltage present at rail **117** is further smoothed.

[0084] FIGS. 6A-6D, when assembled together, illustrate components of the amplifier **115**. Amplifier **122**, as seen in FIG. 6C, is an operational amplifier. The BASE signal from processor **80** is applied to the inverting input of the amplifier **122** through a resistor **120**. The BASE signal can thus be considered the external control signal amplifier **115** receives to regulate the voltage that appears across the transformer primary winding **252**. Also applied to the inverting input of amplifier **122** is the voltage feedback signal from differential amplifier **240**. This signal from amplifier **240** is applied to the inverting input of amplifier **122** through a resistor **121**. A resistor **124** is tied between the output of amplifier **122** and the inverting input. Also tied across the output of amplifier **122** and the inverting input of the amplifier are a series connected resistor **126** and a capacitor **128**. The noninverting input of the summing amplifier **122** is tied to ground.

[0085] Summing amplifier **122** is configured as an inverting amplifier. In many versions of the

invention this gain is between 4 and 10. The series connected feedback circuit of resistor **126** and capacitor **128** limit the localized gain of amplifier **122** by reducing the gain of the amplifier at high frequencies, typically above 1 MHz. This increases the overall stability of the amplifier circuit. The signal produced by summing amplifier **122** is referred to as the feedback adjusted BASE signal.

[0086] The feedback adjusted BASE signal from summing amplifier **122** is applied through a capacitor **132** and resistor **134** to the inverting input of an operation amplifier **140**. Operational amplifier **140** is part of rectifier and splitter **138**. The non-inverting input of amplifier **140** is tied to ground. The output signal from amplifier **140** is applied to the junction of two series connected diodes Schottky diodes **148** and **150**. A resistor **144** is tied between the inverting input of amplifier **140** and the anode of diode **148**. A resistor **146** is tied between the inverting input of amplifier **140** and the cathode of diode **150**. The signal present at the junction of resistor **144** and diode **148** is the negative component of the feedback adjusted BASE signal. The signal present at the junction of the resistor **146** and diode **150** is the positive component of the feedback adjusted BASE signal.

[0087] Rectifier and splitter **138** is configured so the gain out of amplifier **140** is fixed. Typically, the gain is less than 5. Often the gain is unity.

[0088] The negative component of the feedback adjusted BASE signal is applied through a resistor **154** to the inverting input of an amplifier **158**. Amplifier **158** is part of the inverting voltage controlled current source **156**. The non-inverting input of amplifier **158** is tied to ground. A capacitor **160** is tied between the output of amplifier **158** and the inverting input. The output signal from amplifier **158** is also applied through a resistor **161** to the gate of MOSFET **162**. The source of MOSFET **162** is tied to ground through a resistor **168**. A resistor **166** connects the inverting input of amplifier **158** to the junction between MOSFET **162** and resistor **168**. A resistor **165** ties the junction of resistor **154**, amplifier **158** resistor **166** to the  $-V_{sub,EE}$  voltage source.

[0089] The positive component of the feedback adjusted BASE signal is applied to the non-inverting input of amplifier **176**. Amplifier **176** is part of non-inverting voltage controlled current source **174**. The output signal from amplifier **176** is applied through a resistor **183** to the gate of MOSFET **184**. The signal present at the output of amplifier **176** is applied through a capacitor **178** to the inverting input of the amplifier. The inverting input of amplifier **176** is tied to the  $-V_{sub,EE}$  voltage source through a resistor **179**. The junction of amplifier **176**, capacitor **178** and resistor **179** is tied to the source of MOSFET **184** through a resistor **180**. A resistor **182** ties the junction of resistor **180** and MOSFET **184** to ground.

[0090] Amplifiers **158** and **176** have an identical gain that is fixed. Typically, this gain is less than 5. Often the gain is unity.

[0091] The signal present at the drain of MOSFET **162** is applied through a resistor **237** to the inverting input of differential amplifier **240**. The signal present at the drain of MOSFET **184** is applied to through a resistor **238** to the noninverting input of differential amplifier **240**. (Not shown are capacitors that may be in series between resistors **237** and **238** and the associated inputs into amplifier **240**.) The noninverting input of differential amplifier **240** is tied to ground through a resistor **239**. Feedback to amplifier **240** is through a resistor **241** tied between the output of the amplifier and the inverting input. The signal present at the output of amplifier **240** is the signal applied through resistor **121** to summing amplifier **122**.

[0092] An inductor **187** is connected between the drains of MOSFETS **162** and **184**. The drains of MOSFETS **162** and **184** are connected to the opposed ends of primary winding **252** of transformer **250**.

[0093] Inductor **187** is selected to have an inductance that, ideally, if the inductor was connected in parallel across the drivers would form a circuit that has a resonant frequency substantially equal to the resonant frequency of the handpiece. It is understood that the resonant frequencies of the handpieces **330** will vary. The inductance of inductor **187** is fixed. Accordingly, the inductance of the inductor is selected so that if the inductor was tied in parallel across the drivers **344**, the resonant frequency of this circuit would be within 50% and more ideally within 25% of the

resonant frequency of the handpiece **330**. Again, the resonant frequency of the handpiece is understood to be a frequency of the drive signal that, at a given voltage or current, the application of the drive signal at that frequency induces vibrations in the tip that are larger in amplitude in comparison to the application of the same voltage or current at frequency that is off resonance. [0094] While not illustrated, in some versions of the invention, the connection of each MOSFET **162** and **184** is through a current sensing transformer. This current sensing transformer has on one side two primary windings and the opposed sides a single secondary winding. Each MOSFET **162** and **184** is tied to one end of a separate one the primary windings of the current sensing transformer. The opposed end of the primary winding of the current sensing transformer to which MOSFET **162** is connected is tied to a first end of transformer primary winding **252**. The opposed end of the primary winding of the current sensing transformer to which MOSFET **184** is connected is tied to the second end of transformer primary winding **252**. The signal across the secondary winding of this current sensing transformer thus represents the current sourced by the amplifier. A digitized representation of the signal across the current sensing transform is applied to the processor **80**. The processor **80** monitors this signal to determine if an excessive amount of power is being sourced from the amplifier. If the processor **80** determines the console is in this state, the processor takes steps to terminate or reduce the sourcing of power from the amplifier. The processes by which the processor **80** performs this monitoring and so regulates the operation of the console are not part of the present invention.

[0095] An understanding of operation of linear amplifier **115** is obtained by initial reference to FIGS. **7**, **8A** and **8B**. FIG. **7** is a waveform of the feedback adjusted BASE signal output from summing amplifier **122**. Rectifier and splitter **138** splits the feedback adjusted BASE signal into its positive and negative components. FIG. **8A** depicts the positive component of the feedback adjusted BASE signal present at the cathode of diode **150**. FIG. **8B** depicts the negative component of the feedback adjusted BASE signal present at the anode of diode **148**.

[0096] The positive component of the feedback adjusted BASE signal is applied to the non-inverting voltage controlled current source **174**. The half sinusoidal portions of the waveform seen in FIG. **9A** represent that when the input signal applied to current source **174** is above zero volts, the output signal from the current source tracks the input signal. By returning to FIG. **8A** it is understood that there are times when the input signal to current source **174** is near zero. It will be recalled that the  $-V_{sub EE}$  signal is applied to the inverting input of amplifier **176**. As a consequence of the  $-V_{sub EE}$  signal being so applied to amplifier **176**, even when input signal is zero volts, amplifier **176** produces a constant low voltage output signal. In FIG. **9A** this is represented by the linear sections of the waveform between the adjacent half sinusoidal sections. These linear portions of the signal are above zero Volts.

[0097] The negative components of the feedback adjusted BASE signal are applied to amplifier **158**. The half sinusoidal portions of the waveform seen in FIG. **9B** represent that these portions of the feedback adjusted BASE signal are inverted and output by amplifier **158**. Again it is understood that the  $-V_{sub EE}$  signal is also applied to amplifier **158**. This is why, during periods in which the negative components of the feedback adjusted BASE signal are zero, amplifier will output a low level signal. In FIG. **9B** this is represented by the linear sections of the waveform between the half sinusoidal sections being at a voltage greater than zero volts.

[0098] The signals applied to the gates of MOSFETs **162** and **184** are therefore applied to the MOSFETs in interleaved time frames. FIG. **10** represents the effects of turning on and turning off of MOSFETs **162** and **184** on the opposed ends of the transformer primary winding **252**. The waveforms of this Figure are based on the condition that power supply **84** is applying a 100 VDC signal to the winding center tap. For ease of understanding the operation of amplifier **115**, the waveforms of FIG. **10** do not consider the need to ensure that there is a sufficient headroom voltage across the MOSFETs **162** and **184**.

[0099] Solid line waveform **186** of FIG. **10** represents the voltage present at the end of the winding

**252** to which MOSFET **162** is connected. This is the end of winding **252** at the top of transformer **250** in FIG. **6B**. Dashed line waveform **188** represents the voltage present at the end of the winding **252** to which MOSFET **184** is connected. This is the end of the winding at the bottom of transformer **250**. During an initial time frame, MOSFET **162** is assumed to be turned off. As a result of the turning on of MOSFET **184**, the voltage present at the associated end of primary winding is tied to ground and therefore pulled low. This is represented by dashed line waveform falling from the 100 Volts to near zero. The electric field at this end of the winding essentially collapses. Simultaneously, during this time frame, MOSFET **162** is effectively off. The collapse of the electric field of the end of the winding **252** to which MOSFET **184** is connected induces an increase in the electric field at the opposite end of the winding. Owing to this end of the winding **252** effectively being an open circuit, the voltage at this end of the winding rises. This rise in voltage is essentially equal to the drop in voltage at the opposed end of the winding. Thus as represented by the initial positive going progression of waveform **186**, the voltage at this end of the winding rises from 100 V to 200 V. As a consequence of these change in voltage levels at the opposed ends of primary winding the voltage present at the top of winding **252** is 200 Volts more positive than the voltage at the bottom of the winding. In FIG. **11** this is represented by the initial rise of waveform **189** from 0 Volts to 200 Volts.

[0100] As MOSFET **184** is turned off, the voltage present at the bottom of the winding **252** rises back to 100 Volts, the voltage present at the center tap. The voltage present at the top of winding **252** drops back to the center tap voltage. The voltage across the winding **252** essentially falls to zero. FIG. **11** this is represented by the initial fall of waveform **189** from 200 Volts to 0 Volts.

[0101] During the next time frame, MOSFET **162** is turned on while MOSFET **184** remains off. The turning off of MOSFET **162** connects the associated end of the winding to ground. The voltage present at the top of winding **252** drops from 100 Volts to near ground. In FIG. **10** this is represented by the section of waveform **186** that falls from 100 Volts to essential zero volts. At this time, owing to MOSFET **184** being off, the bottom of winding **252** is effectively an open circuit. The collapse of the field around the top of winding **252** results in the rise of the field around the bottom of the winding. This results in the potential at the bottom of the winding increasing. This is represented the section of waveform **188** that rises from 100 Volts to 200 Volts. As a result in the shift of voltages across the primary winding **252**, the top of the winding develops a voltage that is negative with respect to the voltage at the bottom of the winding. In FIG. **11** this is represented by the drop of waveform **189** from 0 Volts to -200 Volts.

[0102] After MOSFET **162** is turned on, the MOSFET **162** is turned off while MOSFET **184** remains off. This results in the voltage present at the top of winding **252** rising back to 100 Volts. Simultaneously, the voltage present at the bottom of winding **252** drops back to 100 Voltages. During the moment when both MOSFETs **162** and **184** are effectively off, there is effectively no voltage drop across the winding. This is represented in FIG. **11** by the rise in waveform **189** from -200 Volts back to 0 Volts. Thus this turning on and off of the MOSFETs **162** and **184** causes an AC voltage to develop across the transformer primary winding **252**.

[0103] The frames then repeat. In some versions of the invention ratio of turns of the secondary winding **258** to the primary winding **252** is between 2 and 10. In more preferred versions the range is between 2 and 5.

[0104] In actuality it is understood that only when it is necessary to cause the maximum voltage to appear across the transformer primary winding **252** are the MOSFETs **162** and **184** turned fully on or turned fully off. These MOSFETs **162** and **184** function as active resistors. The varying of the resistances of the MOSFETS by the current sources **156** and **174** is what causes peak to peak voltages to appear across the primary winding that are less than a voltage that is two times the DC voltage present at the center tap.

[0105] As discussed above, processor **80**, in addition to regulating the characteristics of the BASE signal, also regulates the voltage of the VAMP signal applied to the center tap of transformer

winding **252**. This is to ensure that, regardless of the voltage present at the ends of the transformer winding **252**, there is sufficient but not excessive headroom voltage present at the drains of MOSFETs **162** and **184**. The reason this monitoring is performed is understood by first reference to FIG. **12**. This Figure represents the voltage present at the one end of transformed winding **252**, arbitrarily the top end. More particularly, FIG. **12** represents the voltage present when the center tap voltage is 30 Volts and the MOSFETs **162** and **184** are operated to cause the voltage to oscillate 40 Volts peak to peak. When console **50** is in this state, the minimum drain to source voltage across MOSFET **184**, is 10 Volts. For the purposes of understanding the invention, it will be assumed that 10 Volts is the minimum headroom voltage for the particular operating state of the system. This means that, when 10 Volts are applied to MOSFETs **162** and **184** there will be sufficient voltage across the MOSFET to ensure that they are in saturation. This ensures that any changes in the voltage applied to the gate of each MOSFET **162** and **184** will result in the desired proportional change of current flow through the MOSFET.

[0106] FIG. **13** represents the condition when the voltage at the center tap remains at 30 Volts, but, owing to a need to increase the voltage of the drive signal, MOSFETs **162** and **184** are operated to cause transformer primary winding voltage to oscillate 50 Volts peak to peak. Assuming the voltage level at the center tap remains at 30 Volts, the minimum drain to source voltage drops to 5 Volts. When the voltage across the MOSFET **184** drops to this level, the MOSFET may no longer be in saturation. If MOSFET **184** goes out of saturation, a change in the voltage of the signal applied to the gate may not result in the desired proportional change in current flow through the MOSFET. This would result in the potential present at the associated end of transformer primary winding **252** not being at the potential needed to cause a drive signal of the appropriate potential to appear across the secondary winding **258**.

[0107] Furthermore, like any amplifier, there are states in which the linear amplifier **115** of this invention will not respond to a change in the potential of the input drive signal with a proportional change in the output of the output signal, here the drive signal. This is especially true when the change in drive signal voltage is based on a change of the load to which the drive signal is applied. The presence of this headroom voltage at the transformer center tap makes it possible for the amplifier's output to rapidly change with a sudden change in load.

[0108] Console **50** could be configured so that, at all times, a voltage is presented at the center tap that is high enough so that, even with the greatest swing in winding voltage, the voltages present at the drains of MOSFETs **162** and **184** will always be above saturation level. A disadvantage of so operating the console is that by continually applying high voltages to MOSFETs **162** and **184**, a significant amount of the electrical energy applied to the MOSFETs is turned into thermal energy, unwanted heat. To prevent excessive heat loss, processor **80** thus continually adjusts the boost converter **88** to ensure that the VAMP signal output by the converter provides sufficient headroom to the MOSFETs **162** and **184** but is not a level that results in needless heat loss through the MOSFETS.

[0109] For the processor **80** to be able adjust the VAMP signal, as well as the BASE signal the processor receives as an input a HEADROOM (HDRM) signal representative of the headroom voltage. The HEADROOM signal is received from the headroom monitor **190** now described by reference to FIGS. **6A** and **6B**. The headroom monitor **190** includes two diodes **196** and **198**. The anodes of both diodes **196** and **198** are connected to the V.sub.CC voltage source through a capacitor **192**. The cathode of diode **196** is connected to the drain of MOSFET **162**. The cathode of diode **198** is connected to the drain of MOSFET **184**. A resistor **202** is connected across capacitor **192**. The signal present at the junction of capacitor **192**, diodes **196** and **198** and resistor **202** is applied through a resistor **204** to the noninverting input of amplifier **212**. A capacitor **206** is tied between the noninverting input of amplifier **212** and ground. The output signal from amplifier **212** is tied to the inverting input of the amplifier.

[0110] The output signal from amplifier **212** is applied through a resistor **214** to the noninverting

input of amplifier **230**. A resistor **216** and capacitor **218** are connected in parallel between the noninverting input of amplifier **230** and ground.

[0111] Headroom monitor **190** also includes two series connected resistors **224** and **226**. The free end of resistor **224** is connected to the V.sub.CC rail. The free end of resistor **226** is tied to ground. A capacitor **228** is connected across resistor **226**. The signal present at the junction of resistors **224** and **226** and capacitor **228** is applied through a resistor **229** to the inverting input of amplifier **230**. A capacitor **232** and a resistor **234** connected in parallel extend between the output of amplifier **230** and the inverting input of the amplifier. The output signal from amplifier **230** is applied to a resistor **231**. The end of resistor **234** spaced from amplifier **228** is tied to ground through a capacitor **236**. The signal present at the junction of resistor **234** and capacitor **236** is the HEADROOM signal representative of the V.sub.DS voltages across MOSFETs **162** and **184**.

[0112] Headroom monitor **190** does not monitor the V.sub.DS voltages directly. Instead, the headroom monitor **190** monitors the voltage present at the drains of the MOSFETs **162** and **184** to ground. For MOSFET **164** this is the voltage across the MOSFET and resistor **168**. For MOSFET **182** this is the voltage across the MOSFET and resistor **182**. Current flows across diode **196** or **198** when the voltage present at the drain of the associated MOSFET **162** or **184**, falls below the potential of the V.sub.CC signal. When this condition exits, the potential of the signal applied through resistor **204** to the noninverting input of amplifier **212** falls. The output signal from the amplifier **212** undergoes a like drop. This results in a like drop in the output signal from amplifier **228** and by extension a drop in the voltage of the HEADROOM signal.

[0113] By selectively setting the resistances of resistors **224** and **226**, the potential of the HEADROOM signal relative to the actual headroom voltage across the MOSFETs **162** and **184** can be selectively set. In one version of the invention resistors **224** and **226** are selected so that when the potential of HEADROOM signal is zero volts, the voltage present at the MOSFET drains is a specific voltage somewhere between 8.5 and 10.5 Volts.

[0114] The VAMP signal from the boost converter **88** is applied to the center tap of primary winding **252** of transformer **250**. A single capacitor **248** is also shown connected between the conductor over which the VAMP signal is applied to transformer **250**. Capacitor **248** represents the filtering of the VAMP signal to minimize the AC components of the signal.

[0115] Not shown is a relay that may be in line with the conductor over which the VAMP signal is applied from the Boost converter **88** to the transformer center tap **252**. This relay is turned on by the processor after diagnostic checks that are part of the process of readying the system indicate that no faults were detected. The process of performing these diagnostic checks is not part of the present invention. When the relay is present a reverse biased diode is also connected between the bus over which the VAMP signal is applied to the transformer center tap. This diode protects the console when the relay is opened.

[0116] In FIG. **6B**, the opposed ends of the transformer secondary winding **258** are the source of the drive signal applied to the handpiece drivers **344**. One end of tickler coil **256** is tied to ground. The HPVMON signal present at the opposed end of the tickler coiler **256** is the signal representative of the voltage of the drive signal V.sub.S. The HPVMON signal is the signal applied to the voltage monitor **66**. Internal to the console **40**, one of the conductors that extends from the transformer secondary winding **258** is shown in close proximity to coil **262**. The signal across coil **262**, the HPISNS+ and HPISNS- signals of FIG. **6B**, is the signal representative of the drive signal current is. The HPISNS+ and HPISNS- signals are the signals applied to the current monitor **68**. Based on the HPISNS+ and HPISNS- signals, current monitor **68** produces a representation of current is.

[0117] To facilitate operation of system **40**, memory **338** internal to the handpiece is loaded with data during the assembly of the handpiece. These data, as represented by field **372** of FIG. **14**, include data identifying the handpiece **330**. These data are useful for verifying that the console **50** is able to apply a drive signal to the handpiece. Data in field **372** may also indicate the type of



information regarding the handpiece that is presented on console display **82**. Field **374** contains data indicating the capacitance  $C_o$  of the stack of drivers **348**. Driver capacitance can be determined by analysis during the process of assembling the handpiece **330**. Often the sum of the capacitance of the drivers **348** is between 500 to 5000 pF. Data regarding the maximum current that should be applied to the handpiece, current  $i_{sub.S.sup.MAX}$ , are contained in a field **376**. Current  $i_{sub.S.sup.MAX}$  is often less than 1 Amp peak and more often 0.5 Amp peak or smaller. Field **378** contains data indicating current  $i_{sub.M.sup.MAX}$ , the maximum equivalent of current that should be applied mechanical components of the handpiece. Current;  $i_{sub.M.sup.MAX}$  is typically 0.25 Amps peak or less. LM The maximum potential of the drive signal, voltage  $V_{sub.S.sup.MAX}$ , are stored in field **380**. Voltage  $V_{sub.S.sup.MAX}$  is typically 1500 Volts or less AC peak.

[0118] Also stored in handpiece memory **338** are data indicating the minimum and maximum frequencies of the drive signal that should be applied to handpiece **330**. The minimum frequency, stored in field **382**, is typically the minimum frequency of the drive signal that can be sourced by the control console. The maximum frequency of the drive signal, stored in field **384**, is typically between 5 kHz and 40 kHz greater than the minimum frequency.

[0119] Field **386** contains coefficients for filtering the signals output by processor **80**. Field **388** contains data regarding any step limits associated with increasing the magnitude of the potential of drive signal applied to the handpiece. It should be understood that the data in fields **372**, **376**, **378**, **380**, **382**, **384**, **386** and **388** like the data in field **374**, are stored in the handpiece memory **58** as part of the process of assembling the handpiece.

[0120] Handpiece memory **338** also contains field **390** as a use history field. Control console **50**, during use of the handpiece, writes data into field **388** so as to provide a log of the operation of the handpiece.

[0121] FIGS. **15A-15D**, when assembled together, provide a view of the processes run on processor **80** to regulate the drive signal output by the console **50** to the handpiece **330**. In brief, it should be understood that the objective is for the console **50** to output a drive signal at the frequency and voltage that results in the desired cyclical expanses and contractions of the handpiece drivers **344**. The BASE signal and the POWER\_SUPPLY\_CONTROL signals are the control signals are output by the processor **80** to cause the other components internal to the console **50** to output the target drive signal. Processor **80** generates the BASE signal. Amplifier **115** produces a feedback adjusted BASE signal that is a function of the BASE signal and the signal produced by the amplifier. This feedback adjusted BASE signal is at a frequency and potential that results in the amplifier **115** causing a signal to appear across the transformer primary winding **252**. The specific signal the amplifier **115** causes to appear across the transformer primary winding **252** is a signal that causes the target drive signal to be induced across the secondary winding **258**.

[0122] Processor **80** outputs a POWER\_SUPPLY\_CONTROL signal that ensures that the potential VAMP power supply **84** applies to the center tap of transformer primary winding **252** is at a level that results in a sufficient but not excessive headroom voltage appearing at the drains of MOSFETs **162** and **184**.

[0123] To generate the BASE and POWER\_SUPPLY\_CONTROL signals, processor **80** continually executes three control loops. A first control loop sets the frequency of the BASE signal. A second control loop sets the voltage of the BASE signal. The outputs of these two control loops are combined to produce the BASE signal. The third control loop generates the POWER\_SUPPLY\_CONTROL signal. An output from the second control loop, the control loop used set the voltage of the BASE signal, is an input into the third control loop.

[0124] The gains of amplifiers **118** and **122**, rectifier and splitter **138** and current sources **156** and **174** are fixed. Therefore, the voltage of the signal applied across the transformer primary winding **252** is proportional to the voltage of the BASE signal. The frequency of the BASE signal is the frequency of the signal present across the transformer primary winding **252**. Accordingly, in the following descriptions of the modules run on processor **80**, the voltage and frequency of the BASE

signal are used as the input variables representative of these characteristics of the signal present across the primary winding **252**. It should also be understood that the frequency of the BASE signal is the frequency of the drive signal present across transformer secondary winding **258**. This is why the modules run on the processor are able to use the frequency of the BASE signal as an input variable representative of the frequency of the drive signal.

[0125] One of the modules of the first control loop is the frequency tracking calculator **292**.

Frequency tracking calculator **292** determines the characteristics of the drive signal presently applied to the handpiece drivers **348**. In one version of the invention, frequency tracking calculator **292** determines the ratio of  $i_{sub.O}$  the current flowing through the handpiece drivers **344** to  $i_{sub.M}$ . Variable  $i_{sub.M}$  is a mathematical equivalent of current applied to the mechanical components of the handpiece **330**. The mechanical components of the handpiece are the components of the handpiece that, in response to the application of the drive signal, vibrate. These components include: the proximal end mass **334**; post **336**; drivers **344**; horn **356**, including the coupling assembly; and the tip **360**. Drivers **344** are included as part of these components because the drivers, since they vibrate, are part of the vibrating mechanical assembly of this invention. Sleeve **370** is typically not considered one of these components. This is because, while the sleeve **370** vibrates, the sleeve is not part of the vibrating system. More specifically, sleeve **370** can be considered a component that places a load on the vibrating system.

[0126] Current  $i_{sub.O}$  through drivers **344** is a function of  $C_{sub.O}$ , the capacitance of the drivers, the voltage across the drivers and  $\omega$ , the radian frequency of the drive signal. More specifically,

$$[00001] i_O = j C_O V_S \quad (1)$$

The voltage across the drivers,  $V_{sub.S}$ , is the voltage of the drive signal. The equivalent of current  $i_{sub.M}$  through the mechanical components of the handpiece **330** is the difference between  $i_{sub.S}$ , the current applied to the handpiece **330**. The equivalent of current  $i_{sub.M}$ , is thus determined according to the equation:

$$[00002] I_M = i_S - j C_O V_S \quad (2)$$

Currents  $i_{sub.S}$  and  $i_{sub.O}$ , the equivalent of current  $i_{sub.M}$  and voltage  $V_{sub.S}$  are understood to be vectors each of which has a magnitude component and a phase component.

[0127] Frequency tracking calculator **292** therefore receives as inputs: the digitized representation of  $V_{sub.S}$  as measured across tickler coil **256** and the digitized representation of  $i_{sub.S}$  based on the potential across coil **262**. A third input into the calculator **292** is capacitance  $C_{sub.O}$  from field **374** of handpiece memory **338**. A fourth input into calculator **292** is the present frequency of the drive signal. Based on these variables, the frequency tracking calculator **292** determines the ratio of current through the drivers to the equivalent of current through the mechanical components of the handpiece according to the following formula:

$$[00003] -\text{Re}\left\{\frac{j V_S C_O}{i_S - j V_S C_O}\right\} \quad (3)$$

[0128] The ratio output by calculator **292** is applied to base frequency controller **294**. The base frequency controller **294** compares the ratio of Equation (3) to a fixed value, arbitrarily F. In practice, F can be between  $-100$  and  $100$ . It should be understood that this range is exemplary, not limiting. There are a number of constructions of the invention wherein F is between  $-1.0$  and  $1.0$ . If the system is intended to apply a drive signal that matches the mechanical resonance of the handpiece F is typically zero. Value F is typically constant throughout a single use of system **40**.

[0129] Controller **294** thus performs the following evaluation:

$$[00004] -\text{Re}\left\{\frac{j V_S C_O}{i_S - j V_S C_O}\right\} \approx F \quad (4)$$

Generally, if the ratio is within  $\pm 0.1$  of F, more often within  $\pm 0.05$  of F and, ideally, within  $\pm 0.01$  of F, the present drive frequency is considered to be close enough to the target drive frequency that the controller does not need to adjust this frequency.

[0130] If the evaluation of Equation (4) tests false, controller **294** generates a new frequency for the

drive signal. This new frequency is a frequency that should, during a subsequent evaluation of Equation (4) result in the evaluation testing true. The new frequency is based in part of the present frequency of the drive signal. The present frequency of the drive signal is understood to be the frequency of the drive signal previously calculated by controller **294** in the last cycle of the frequency calculation process. This is why, in FIG. **15B** the previously calculated drive frequency is shown as being feedback to base frequency controller **294**. This previously calculated value drive frequency is also depicted as being fed back to frequency tracking calculator **292**. Calculator **292** uses this previous calculated value BASE signal frequency as the input variable  $w$ , the radian frequency of the drive signal.

[0131] A detailed analysis of the basis for Equations (1), (2), (3) and (4) is contained in PCT Pub. No. WO 2015/021216 A1/US Pat. Pub. No. 2017/0071621 A1, the contents of which are explicitly incorporated herein by reference.

[0132] The new frequency for the drive signal is generated using a proportional, integral and derivative (PID) control loop. While not shown in FIG. **15B**, the coefficients for the PID loop may be based on coefficients from handpiece memory field **388**. The new frequency the drive signal generated by base frequency controller **294** is applied to a base signal generator **310**. The minimum and maximum limits of the drive frequency are based on the data in fields **382** and **386** in the handpiece memory **338**.

[0133] The second control loop includes an equivalent of current calculator **296**. The equivalent of current calculator **296** determines the equivalent of current for the mechanical components of the handpiece **330**. This is the equivalent of current calculated according to Equation (2). To distinguish between the below discussed target equivalent of current, this calculated equivalent of current is referred to as variable  $i_{sub.M.sup.CALC}$ . From the above it should be understood that the equivalent of current is calculated by the frequency tracking calculator **292**. Accordingly, in some versions of the invention, there is no calculator **296**. In these versions of the invention, the equivalent of current;  $i_{sub.M.sup.CALC}$  calculated by the frequency tracking calculator **292** as a consequence of the determination of the frequency tracking ratio is applied to the next module of the control loop that sets the potential of the drive signal, the base voltage controller **306**.

[0134] A second input into the base voltage controller **306** is a value representative of the target equivalent of mechanical current,  $i_{sub.M.sup.TARG}$ . Target equivalent of mechanical current  $i_{sub.M.sup.TARG}$  comes from a calculator **305**, another module run on processor **80**. The input into calculator **305** is the signal representing the practitioner desired operating rate for the handpiece **330**. This operating rate is based on the practitioner's setting of switch **56** of the equivalent foot pedal. Calculator **305**, based on the input signal supplied by the switch, generates the value for the target equivalent of mechanical current  $i_{sub.M.sup.TARG}$ . A second input calculator **305** employs to generate the target equivalent of mechanical current  $i_{sub.M.sup.TARG}$  is the frequency of the drive signal. Calculator **305** employs the frequency of the BASE signal previously calculated by the base frequency controller **294** as the variable representative of drive signal frequency.

[0135] The base voltage controller **306** is the module that generates the next value of the voltage for the BASE signal. Base voltage controller **306** first determines the difference between the; target equivalent of current  $i_{sub.M.sup.TARG}$  and the current calculated equivalent of current  $i_{sub.M.sup.CALC}$ . Based on the difference between these two values, controller **306** then, if necessary, resets the value of the voltage of the BASE signal. This is because the voltage of the BASE signal is the variable that causes a drive signal having the voltage necessary to foster the target equivalent of current to appear across the transformer secondary winding **258**. Controller **306** operates a PID control loop to determine the new value of the voltage of the BASE signal. The coefficients for the control loop come from field **386** of handpiece memory **338**.

[0136] In theory, the base voltage controller **306** should generate signals indicating the newly

adjusted potential for the BASE signal based on a conventional control loop such as a PID control loop.

[0137] It is understood that the rate of change of BASE signal may further be governed by variables such as the ability of the linear amplifier **115** to rapidly ramp up the drive signal and the handpiece drivers **344** ability to respond to a rapid change in drive signal voltage. Voltage controller **306** is further understood to limit changes in the voltage level of the BASE signal based on these variables. The voltage step limiting variables that are specific to the handpiece are based on data read from field **388** of the handpiece memory **338** when system **40** is initially configured for use. The voltage step limiting variables specific to the console are loaded into the processor **80** during assembly of the console **50**.

[0138] In practice, other factors affect the ability of the amplifier to increase the voltage level of the drive signal applied to the handpiece drivers **344**. These factors include: the voltages present on MOSFETs **162** and **184**; the maximum current that can be drawn from the transformer **250**; and the maximum voltage of the drive signal that should be applied to the handpiece drivers **344**. A voltage limiter **304**, another control module run on processor **80**, selectively generates commands that limit increases in the commanded voltage level for the BASE signal that is output by voltage controller **306**.

[0139] Voltage limiter **304** selectively limits the magnitude of the voltage of the BASE signal as well as the rate of change of the voltage of the BASE signal based on a number of input variables. One variable upon which the voltage limiter **304** may determine it is necessary to limit the voltage of the BASE signal is that it would result in a signal appearing across the transformer secondary winding **258** that is in excess of the designed maximum voltage. Often this value is fixed. In some versions of the invention this voltage is at least 1000 Volts peak and more preferably at least 1250 Volts peak. In still other versions of the invention, this voltage can vary. The primary reason this voltage could vary is that the characteristics of the handpiece **330** are such that, in some operating states, the handpiece could draw an excessive amount of current from the console **50**.

[0140] Accordingly, in some versions of the invention, processor **80** runs a full scale voltage calculator **298**. Inputs into calculator **298** are handpiece driver capacitance  $C_o$  and the frequency of the drive signal. Again, it should be understood that the frequency of the BASE signal is used as a substitute for the frequency of the drive signal. Collectively, these values may indicate that if the drive signal applied to the handpiece **330** reaches a certain potential, the impedance of the drivers is such that they will draw more current than the console **50** should provide. In general, the handpiece may be in a state in which there is potential for excessive current draw by the drivers **344**, when the drivers have a relatively low capacitance and the drive signal is at a relatively high frequency.

[0141] Calculator **298** is a second module that uses as an input variable the previously calculated frequency of the BASE signal. A second variable into calculator **298** is driver capacitance  $C_o$ . Again, handpiece driver capacitance  $C_o$  is understood is loaded to processor **80** during the initialization of the system. As a result of this monitoring, calculator **298** may determine that the handpiece drivers **344** are entering a state in which an increase in the voltage of the drive signal will result in excessive current draw from the console **50**. If calculator **298** determines that system **30** is in this state, the calculator generates an instruction to the voltage limiter **304** indicating that the maximum voltage that should appear across the transformer secondary winding **258**, the maximum voltage that should be output by the console **50**, is a level less than the default maximum voltage. In some versions of the invention, calculator **298** actually determines the maximum voltage that should be allowed to develop across the transformer primary winding **252**.

[0142] Voltage limiter **304** also receives from the voltage controller **306** data indicating the voltage level for the BASE signal determined in the previous cycle of calculations used to generate the BASE signal. This voltage is used as the input variable for determining the present input voltage across primary winding **252**. Given that the ratio of the voltage across the secondary winding **258**

relative to the primary winding is fixed, the voltage of the previously calculated BASE signal is also used as a variable that inferentially indicates the voltage across the secondary winding **258**. [0143] Another variable applied to voltage limiter **304** is the maximum voltage that can be applied to the handpiece **330**. This voltage is the V.sub.S.sup.MAX voltage from handpiece memory field **380**.

[0144] The voltage limiter **304** also receives the measured headroom voltage, the HDRM signal, from the headroom monitor **190** as an input variable. Not shown is the circuit that provides the digitized representation of this voltage to limiter **304**. A related variable applied to voltage limiter **304** is the target headroom voltage. This is a voltage level below which the headroom voltage should not drop. The target headroom voltage comes from another module run on processor **80**, a target headroom calculator **312**.

[0145] Based on these variables and the time it takes for the limiter **304** to perform a sequence of evaluations, the voltage limiter engages in the evaluations of FIG. **16**. In a first step, step **402**, limiter **304** compares the voltage across the transformer secondary winding **258** to the voltage V.sub.S.sup.MAX, voltage limit of the drive signal.

[0146] The evaluation of step **402** may indicate that the voltage across the transformer secondary winding **258** is approaching the maximum voltage of the drive signal that can be applied to the handpiece drivers **344**. If this is the result of the evaluation, in a step **404**, the voltage limiter **304** asserts signals to the voltage controller **306** indicating that the control should not allow the calculated voltage for the next BASE signal to exceed a given amount. Another result of the evaluation of step **402** is that the voltage being applied to the drivers **344** is already at the maximum voltage. If this is the result of the evaluation of step **402**, in step **404** the voltage limiter **304** generates a command to the voltage controller **306** indicating that the controller cannot increase the voltage of the BASE signal beyond the present level.

[0147] In a step **406**, the voltage limiter **304** evaluates whether or not the voltage being allowed to develop across the transformer primary winding **252** is approaching or equal to the maximum voltage of the signal that should be allowed to develop across this winding. The level of maximum winding voltage is understood to be the lower of the maximum default maximum voltage or the maximum voltage level generated by full scale voltage calculator **298**.

[0148] In step **406** it may be determined that the drive signal is near the maximum transformer voltage. If this is the result of the evaluation, in a step **408**, the voltage limiter **304** outputs a command to the voltage controller that the controller should not allow the increase in the voltage of the BASE signal exceed a step amount. Another result of the evaluation of step **406** is that the voltage limiter **304** determines that the voltage across the transformer secondary winding **258** is already at the maximum permissible voltage. If this is the result of the analysis of step **406**, in step **408** the voltage limiter **304** outputs a command to the voltage controller **306** that the controller cannot output a command increasing the voltage of the BASE signal beyond the present level.

[0149] In a step **410** the voltage limiter **304** evaluates whether or not the amplifier is in a state in which headroom voltage is sufficient to ensure that MOSFETS **162** and **184** will be in saturation. In step **410**, compares the measured headroom voltage, the voltage based on the HDRM signal, to the target headroom voltage. In some versions of the invention, the target headroom voltage is between 2 and 20 Volts. Often the minimum target headroom voltage is between 4 and 15 Volts. If the measured headroom voltage is below the target headroom voltage, the voltage limiter **304** executes a step **412**. In step **412** the voltage limiter **304** generates an instruction to the voltage controller **306** that the controller should limit the magnitude of the increase in the level of the BASE signal. More specifically, the voltage controller **306** is instructed that the controller can only increase the voltage level of the BASE signal by a set maximum amount.

[0150] In FIG. **16**, step **406**, is shown as being executed after step **404**. Step **410** is shown as being executed after step **408**. This is to represent that if necessary the voltage limiter **304** may send plural commands limited the level of voltage increase to the voltage controller **306** if any

combination of the three evaluations indicate that such limitations are necessary. If any one of steps **402**, **406** or **410** are executed, the voltage controller **306** acts on the received instructions and limits the level of the voltage of the drive signal contained in the instruction generated by the controller. [0151] Often, the evaluation of step **402** indicates that the drive voltage that is to be applied does exceed the maximum voltage that should be applied to the handpiece drivers. Often in the evaluation of step **406** it is determined that the voltage that is to be developed across the console transformer **250** is below the maximum permissible voltage. Likewise, in step **410** it is often determined that the measured headroom voltage is above the target headroom voltage. When these are the results of the evaluations of steps **402**, **406** and **410**, as represented by step **414**, the voltage limiter **304** does not assert instructions to the voltage controller **306** that result in the limiting of the level of the voltage of the BASE signal as initially calculated by the controller **306**. The controller **306**, when generating the instruction indicating the voltage level of the BASE signal does not attenuate the level from the level calculated in the PID calculations initially run by the controller. [0152] In FIGS. **15A**, **15B** and **15C**, the instruction from the voltage controller **306** is shown applied to the base signal generator **310**. As described above, the command from the frequency controller **294** is also applied to the base signal generator **310**. Based on these two input commands, the base signal generator generates the appropriate BASE signal. Specifically, this is the BASE signal that is applied to amplifier **115** to causing the desired drive signal to be induced across the secondary winding **258**.

[0153] As mentioned above, the control console **50** of this invention continuously adjusts the voltage applied to the center tap of transformer primary winding **252**. One input variable that determines the level of this adjustment is the target headroom voltage that should be present at the drains of MOSFETs **162** and **184**. This target headroom voltage, sometimes referred to as the minimum headroom voltage, could be a fixed voltage. Arbitrarily, this voltage could be 10 Volts. This headroom voltage can be considered the default headroom voltage. There are times when, owing to the characteristics of the handpiece drivers **344** and the characteristics of the drive signal applied to the drivers, this voltage is appreciably above the voltage that needs to be present to ensure that MOSFETs **162** and **184** are in saturation. Thus, when system **40** of this invention is in some operating states, the minimum headroom voltage needed to ensure the MOSFETs are in saturation may be 5 Volts or less.

[0154] The target headroom calculator **312** determines if, based on the operating state of the system **40**, the target headroom voltage can be lower than the default target headroom voltage. One input into the headroom calculator **318** is handpiece driver capacitance  $C_o$ . Data describing the previously calculated voltage and frequency for the BASE signal are also supplied to calculator **318**. An additional input into the headroom for the calculator **318** is the target mechanical current handpiece **330**.

[0155] Based on the above input variables, target headroom calculator **318** determines if the target headroom voltage for the amplifier for the current operating state of the system **40** can be lower than the default target headroom voltage. When the target mechanical current is relatively low, calculator **318** can decrease the level of the target headroom voltage. When the voltage of the drive signal is relatively high, calculator **318** can also decrease the target headroom voltage. This is because, when the drive signal is relatively high for a given target mechanical current, the overall handpiece impedance is also high. This impedance may approach a maximum impedance value. This maximum impedance value is based primarily on driver capacitance. This means, during any short period of time, 0.5 seconds or less, it is unlikely that a large increase in drive signal voltage will result in the voltage present at the ends of the transformer primary winding **252** falling below what is needed to keep the MOSFETs in saturation. The headroom voltage therefore can be lowered. Driver capacitance does not directly affect the level of the target headroom voltage. However, when the drive signal frequency or capacitance is relatively high, calculator **318** increases the effect changes in the voltage of the drive signal has on the determination of the target

headroom voltage.

[0156] The operating state-adjusted target headroom voltage generated by calculator **312** is the target headroom voltage provided to voltage limiter **304**. In step **410**, the limiter **304** compares the measured headroom voltage to this target headroom voltage.

[0157] Another module run on processor **80** to adjust the winding center tap voltage is the base voltage jump calculator **314**. One input into the base voltage jump calculator **314** is the just calculated voltage level of the BASE signal generated by the base voltage controller **306**. A second input into calculator **314** is the voltage level of the BASE signal generated by controller **306** in the previous calculation of this voltage. Based on these two voltages, calculator **314** determines the change in the voltage across the primary winding **252** from what is currently being applied (the voltage based on the previous cycle voltage level), to the voltage that will be presented across the winding **252** (the voltage based on the most recently calculation of voltage level). If the voltage level between cycles increasing, the value generated by calculator **314** is positive. If the voltage level between adjacent cycles decreases, the value generated by calculator **314** is negative.

[0158] The value generated by calculator **314** is applied to a headroom adjustor module **316**. A second input into module **316** is the measured headroom voltage, the HDRM signal. The magnitude of the voltage change from the voltage jump calculator **314** is subtracted from the measured headroom voltage. The sum, which is output by module **316** is the adjusted measured headroom voltage. When, between two successive cycles of calculations, the voltage level of the BASE signal increases, module **316** outputs an adjusted measured headroom voltage that is less than the actual measured headroom voltage. When, between two successive cycles of calculations, the voltage level of the BASE signal decreases, the module **316** outputs an adjusted measured headroom voltage that is greater than the actual measured headroom voltage.

[0159] The adjusted headroom voltage is applied to a power supply controller **324**. A second input into the power supply controller **324** is the target headroom voltage from calculator **312**. Power supply controller **324** is the feedback loop controller. Controller **324** first determines the difference between the adjusted measured headroom voltage and target headroom voltage. Based on this difference and a PID algorithm, the controller **324** produces the POWER\_SUPPLY\_CONTROL signal. More specifically, controller **324** adjusts the POWER\_SUPPLY\_CONTROL signal so the voltage applied to the center tap of the transformer **250** is high enough to ensures MOSFETs **162** and **184** will be in saturation but will not be at a level that results in excessive heating of the MOSFETS.

[0160] The PID algorithm executed by controller **324** establishes the POWER\_SUPPLY\_CONTROL signal based on two additional variables other than the adjusted measured headroom voltage and the target headroom voltage. These variables are limit variables that define a lower boundary voltage and an upper boundary voltage for the VAMP signal based on the current voltage of the VAMP signal. These limit variables are generated by a power supply limiter **320** which is another module run on processor **80**.

[0161] The input into limiter **320** is the POWER\_SUPPLY\_CONTROL signal previously generated by power supply controller **324**. It will be understood that this voltage level of the POWER\_SUPPLY\_CONTROL signal is proportional to the center tap voltage. Limiter **320** therefore uses the magnitude of POWER\_SUPPLY\_CONTROL signal as a proportional substitute for the center tap voltage being applied to the transformer **250**.

[0162] Based on this signal representative of the present center tap voltage, as represented by FIG. **17**, the limiter generates two instructions to the controller **324**. Specifically in a step **420**, limiter calculates a maximum level for the voltage that should next be generated by the center tap. It is necessary to generate this maximum voltage because there is a limit to the rate the adjustable boost converter **88** can ramp up the voltage applied to the center tap. By limiting the rate of increase in the POWER\_SUPPLY\_CONTROL signal, processor **80** substantially eliminates the likelihood that the power supply amplifier will receive signals that would attempt to force the boost converter **88**

to operate beyond its design specifications.

[0163] In many versions of the invention, the maximum level of the change for the center tap voltage is a fixed scalar value throughout the range of center tap voltages. In these versions of the invention, in step **420**, this POWER\_SUPPLY\_CONTROL voltage equivalent of this voltage is added to the value of the previous POWER\_SUPPLY\_CONTROL voltage received from controller **324**. Step **422** represents limiter **320** sending an instruction with this upper limit for the POWER\_SUPPLY\_CONTROL signal to controller **324**.

[0164] In a step **424** the power supply limiter **320** generates a minimum level for the center tap voltage. The reason it is desirable to limit the rate at which the center tap voltage is allowed to drop is appreciated by understanding how a handpiece of this invention is used. During the course of a procedure, the handpiece is moved so the tip **360** is repeatedly moved against and retracted away from the tissue on which the procedure is being performed. When the tip **360** is applied to the tissue, the tip is under a relatively large mechanical load. When the tip **360** is retracted away from the tissue, the mechanical load to which the tip is exposed rapidly drops. This results in a like drop in the equivalent of current  $i_{sub.M}$  through the mechanical components of the handpiece. Controller **80** is configured to hold this equivalent of current constant. Accordingly, when handpiece is moved away from the tissue, the controller reduces the voltage of the BASE signal to reduce the voltage  $V_s$  of the drive signal.

[0165] This drop in drive signal voltage means it would be possible to appreciably reduce the voltage that power supply **84** applies to the center tap of the transformer **250**. Again, it is desirable to keep this voltage as low as possible to minimize heat loss through MOSFETs **162** and **184**.

[0166] However, during the procedure, the handpiece tip **360** can be held against tissue for a time period of 2 seconds or less, retracted away from the tissue for a time period of 2 seconds or less and then again reapplied to the tissue. During the short time period the tip is retracted away from the tissue, the power supply **84** could be instructed to, significantly reduce the voltage applied to the center tap again. If this event occurs, when the tip head **364** is again applied to the tissue, the system may be in a state in which the center tap voltage is not at a level sufficient to maintain the voltages present across MOSFETs **162** and **184** above the target headroom voltage. If the console enters this state, as discussed above, base voltage limiter **304** and base voltage controller **306** cooperate to limit the rate of increase in the voltage, drive signal voltage. This would mean that when the tip head **364** is again applied to the tissue, that could be a relatively long lead time before the drive signal voltage ramps to a level that would result in the tip vibrations desired by the practitioner.

[0167] To reduce the incidence of the practitioner having to wait for the tip vibrations to ramp up, power supply limiter **320** limits the rate at which power supply controller **324** is able to lower the center tap voltage. Specifically, the power supply limiter in a step **424** calculates a lower limit of the next POWER\_SUPPLY\_CONTROL signal that the controller **324** can produce. In some versions of the invention, step **424** is performed by subtracting a fixed to value the value of previous POWER\_SUPPLY\_CONTROL signal the controller forwarded to the limiter **320**.

[0168] In many versions of the invention, this fixed value of maximum permitted decrease in level of the POWER\_SUPPLY\_CONTROL signal is less than the fixed value of the maximum permitted increase in the level of the POWER\_SUPPLY\_CONTROL signal. This is because, the rapid response to the increase in load applied to the tip is more beneficial than limiting the loss of heat through the MOSFETS **162** and **184**.

[0169] In a step **426** the power supply limiter **304** sends an instruction to the power supply controller **306** indicating the minimum level of the POWER\_SUPPLY\_CONTROL signal the controller is allowed to output.

[0170] The voltage limits generated by the power supply limiter **304** function as the output range limit variables of the PID algorithm executed by the power supply controller **320**. This ensures that calculated the POWER\_SUPPLY\_CONTROL signal subsequently applied to the boost circuit will



not result in the output of a VAMP signal that is outside of the range of voltages for this signal given the present state of this signal.

[0171] The power supply controller **324** also ensures that the output POWER\_SUPPLY\_CONTROL signal does not cause a VAMP signal to appear at the center tap of the primary winding **252** that is outside of the operating range of the console **50**. Specifically, the POWER\_SUPPLY\_CONTROL signal is not allowed to drop below a level that would result in the center tap voltage falling below a minimum voltage level. Often this minimum voltage level is between 10 and 50 Volts. Similarly, controller **320**, if necessary, limits the POWER\_SUPPLY\_CONTROL signal to prevent the power supply from applying a voltage to the center tap that is above a design limit. Typically, this voltage is between 100 and 500 Volts. More often the limit of this voltage is between 200 and 400 Volts. In one version of this invention, this voltage is 250 volts.

[0172] System **40** of this invention is configured for use by attaching a tip **360** to the handpiece **330**. Handpiece cable **326** is attached to console **50**. When the console **50** is first actuated, processor **80**, through memory reader **78**, reads the data in handpiece memory **338**. The reading of the data in the handpiece memory **338** into the processor **80** essentially completes the process of readying the system **40** for use.

[0173] The practitioner sets the amplitude of tip head **364** vibrations by setting the position of slide switch **56** or otherwise entering the appropriate command through display **82**.

[0174] The practitioner actuates the handpiece by depressing the foot pedal **54** or equivalent control member. In response to the processor **80** receiving the command to so actuate handpiece **330**, vibrate the tip **360**, the console generates instructions that cause the power supply **84** to output a voltage to the center tap of the transformer primary winding **252**. For the purposes of understanding the present invention, these instructions include the outputting of an initial POWER\_SUPPLY\_CONTROL signal to the boost converter **88**. Processor **80** also outputs instructions that cause an AC signal to appear across the transformer primary winding **252**. For the purposes of understanding the present invention, these instructions include the outputting of the BASE signal.

[0175] In response to an AC signal appearing across the transformer primary winding **252**, a signal is introduced across the secondary winding **258**. The signal across the secondary winding is the drive signal. The drive signal is output from the console **50** over cable **326** to the handpiece drivers **338**. The application of the drive signal to the drivers **338** results in the vibration of the drivers. The vibrations of the drivers are transferred through the horn **356** and tip stem **362** to the head **364** to result in the desired vibration of the head.

[0176] During the actuation of the handpiece, the POWER\_SUPPLY\_CONTROL signal and a signal proportional to the VAMP signal are applied to the DC/DC controller **90**. Based on the states of these signals, DC/DC controller **90** selectively gates the MOSFETs **112**. The MOSFETs **112** are gated to cause the controller **90** to output a VAMP signal to the transformer center tap that is at the voltage specified by the POWER\_SUPPLY\_CONTROL signal.-

[0177] While the handpiece **330** is actuated, signals proportional to the signals present at the opposed ends of the transformer primary winding **252** are supplied to the opposed inputs of differential amplifier **118**, more precisely, amplifier **240**. These signals are understood to be out of phase with each other. Amplifier **240** and associated components thus output an attenuated version of the difference between the signals to the summing amplifier **122**.

[0178] The output signal from amplifier **240** and the BASE signal are combined prior to being applied to the inverting input of summing amplifier **122**. Ideally, these two signals are 180° out of phase. In actuality, the signals are not out of phase. Summing amplifier **122** therefore produces an AC signal based on the difference between the two input signals. In many versions of the invention, this signal is amplified version of the difference between the two signals. This signal is the feedback adjusted BASE signal. Rectifier and splitter **138** splits the feedback adjusted BASE signal

into its the positive and negative components.

[0179] The negative component of the feedback adjusted BASE signal is the input signal into the inverting voltage controlled current source **156**. Based on the voltage of this signal, current source **156** selectively turns MOSFET **162** on and off. The positive component of the feedback adjusted BASE signal is the input signal into noninverting voltage controlled current source **174**. Based on the voltage of this signal, current source **174** selectively turns MOSFET **184** on and off. Owing to the application of the bias voltages to current sources **156** and **174**, there is never a time when MOSFETs **162** and **184** are ever turned fully off. This means that when the primary winding voltage transitions between the positive and negative states, there is essentially no break or discontinuity in the rate of change of this potential. By extension, this ensures that the drive signal that is induced across the transformer secondary winding **258** is does not have any unusual inflections. In other words, the drive signal is essentially sinusoidal in shape. The application of this sinusoidal drive signal to the handpiece drivers **344** ensures that the drivers contract and expand at even, regular rates.

[0180] Further, console **50** is constructed so that control of the potential allowed to develop across the transformer primary winding **252** is based on two inputs. The first input is the BASE signal, the signal that sets the target for the potential that should develop across winding **252**. The second input is the feedback signal, the actual potential across winding **252**. This feature of the invention ensures that, with a reasonable degree of accuracy, a change in the voltage of the BASE signal results in a substantially linear corresponding change in the voltage across the primary winding **252**. This, in turn, results in the signal that is induced across the secondary winding **258** and applied to the handpiece as the drive signal as having relatively ideal characteristics. Here, relatively ideal characteristics are the characteristics that cause the drive signal to, when applied to the drivers **344**, result in the pattern of tip head **364** vibrations desired by the surgeon to perform the procedure.

[0181] Inductor **187** reduces the extent to which the voltage across and the current flows through each of MOSFETS **162** and **184** are out of phase. During periods of relatively high voltage across or current flow through each MOSFET **162** or **194**, the MOSFET generates an appreciable amount of heat in comparison to when there is a lower voltage across or lower current through the MOSFET. By regulating these voltages and currents there are time periods when both the voltage across and current through the MOSFET **162** or **184** are relatively low. This serves to, during these time periods, reduce the amount of heat generated by the MOSFET **162** or **184**. The reduction in this MOSFET-generated heat reduces the overall amount of heat generated by the control console of this invention.

[0182] The frequency tracking calculator **292** and base frequency controller **294** monitor and, when necessary, adjust the frequency of the BASE signal output by processor **80**. This ensures that, when the mechanical load to which the tip **360** is exposed changes, the frequency of the drive signal maintains the appropriate relationship relative to handpiece resonant frequency in order to facilitate the desired vibrations of the tip head **364**.

[0183] The base voltage controller **306**, when necessary, adjusts the voltage of the BASE signal. This adjustment is performed to also ensure that when the load of the tip head **364** changes, the tip head **364** continues to have vibrations of the amplitude desired by the practitioner in order to accomplish the procedure.

[0184] Base voltage limiter **304** essentially eliminates the likelihood that an increase in the voltage of the BASE signal could result in a voltage appearing across the transformer primary winding that takes MOSFETs **162** and **184** out of saturation. This results in a like substantial elimination of the possibility that when it is necessary to rapidly increase the drive signal, owing to the MOSFETs being out of saturation, the drive signals will be clipped. If this clipping of the drive signal is allowed to occur, the drivers and tip could transition from undergoing regular expansions and contracts to a movement that is less periodic. This clipping can also induce undesirable vibration modes in the tip.

[0185] Other modules on the processor **80** regulate the voltage of the signal applied to the center tap of the transformer primary winding **252**. The voltage jump calculator **314** headroom adjustor **316** collectively provide an adjusted value of the headroom voltage that is a look forward measurement of this voltage. By look forward measurement, it is understood to be the value of this measurement if there is no change in the voltage applied to the transformer center tap and there is a change in the voltage difference across the ends of the primary winding **252**. This gives the power supply controller **324** the ability to adjust the center tap voltage in anticipation of the change in the voltage across the transformer winding **252**.

[0186] When system **40** is in a state in which the voltage of the drive signal increases, this feature causes the center tap voltage to start to ramp up when there is an indication that the drive voltage will so increase. This reduces the likelihood that owing to a rapid increase in drive signal voltage, the evaluation of step **390** will test positive. Again, when in step **390** it appears that the measured headroom voltage falls below the target headroom voltage the processor will slow the rate at which the drive voltage is ramped up.

[0187] When system **40** is in a state in which the voltage of the drive signal decreases, this feature of the invention facilitates the lowering of the center tap voltage. This reduces the voltage drop across the MOSFETs **162** and **184** so as to reduce the heat loss through the MOSFETs.

[0188] A further feature of this invention is that when the voltage of the drive signal is decreased, the power supply limiter **320** only allows the transformer center tap voltage to decrease at a relatively slow rate. Here this rate of voltage decrease is understood to be relatively slow in comparison the power supply voltage limiter **304** allows the transformer center tap voltage to increase. This feature of the invention system **40** is of use when during a procedure the tip head **260** is moved back and forth, towards and away from, the tissue being subjected to the removal procedure. During the phases of this use of the handpiece **330** when the tip is moved towards the tissue, this feature of the invention ensures that owing to the center tap voltage not appreciably falling, there is sufficient headroom voltage to allow the rapid ramping up of the voltage of the drive signal. The allowing of this rapid rise in drive signal voltage means reduces the loss of energy that occurs when the tip **364** is initially pressed against the tissue.

[0189] When system **40** of this invention is in certain operating states, the target headroom voltage calculator **312** lowers the target headroom voltage from the default level for this voltage. This allows the console to, when system **40** is in these states reduce the center tap voltage to that at which must be maintained when the target headroom voltage is at the default level. This feature of the invention further reduces the level of voltage that has to be maintained across MOSFETs **162** and **184** and the undesirable effects of maintaining this voltage at a high level.

[0190] Further the linear amplifier **115** of this invention is able to amplify BASE signals with little distortion over a relatively wide range of frequencies. In many versions of the invention, the console is able to output drive signals between 15 kHz and 45 kHz. In still more preferred versions of the invention, the console is able to output drive signals with no or acceptable levels of distortion between 10 kHz and 100 kHz. Thus, the system of this invention is well suited to drive ultrasonic handpieces to which drive signals have multiple components are applied. More specifically, the console of this invention can be used to produce a drive signal wherein the individual components of the signal differ in frequency by 2,000 Hz or more.

[0191] The above described is directed to a specific embodiment of the system **40** of this invention.

[0192] Alternative versions of this invention are possible. For example, there is no requirement that each of the above described features be included in each version of the system of this invention. Thus, it is within the scope of this invention, to provide a console with a Class A amplifier, a Class B amplifier, a Class AB amplifier, or variation of these amplifiers and a power supply that provides a fixed voltage to the center tap of the transformer primary winding. The system of this invention can thus include one or two Class A amplifiers or one or two Class B amplifiers.

[0193] In versions of the invention wherein the console monitors the headroom voltage and adjusts the center tap voltage based on the headroom voltage, not all features of the disclosed system may be present. Thus, in an alternative version of the system the monitored headroom voltage may not be adjusted based on a look forward change in winding voltage prior to being compared to the target headroom voltage. In some versions of the invention, the target headroom voltage may be a fixed value.

[0194] Similarly, some versions of the console **50** may be constructed so that there is no need to provide a module like the full scale voltage calculator **298** that lowers the maximum voltage the processor **80** allows to appear across the primary winding **252**.

[0195] The structure of the features of the invention may likewise change from what is described. Bipolar transistors can substitute for one or more of the MOSFETs. However, given that voltages in excess of 150 volts peak may be present at the ends of transformer primary winding **252**, it is believed MOSFETs are preferred form of active resistors for selectively connecting the winding to ground or effectively, an open circuit. The amplifiers, the rectifier and splitter, the current sources and the power supply that supplies the VAMP signal to the transformer center tap may have structures different from what has been described

[0196] In the described version of the invention, the headroom monitor **190** is configured to monitor the voltages present between the drains of each of MOSFETs **162** and **184** and ground. In an alternative version of the invention, the headroom monitor may be constructed to monitor the drain to source voltages across the MOSFETs **162** and **184**. In versions of the invention wherein the bipolar transistors function as the active resistors, this type of headroom monitor would monitor the collector emitter voltage across the transistors.

[0197] One such headroom voltage monitoring circuit is now described by reference to FIG. **18**. This circuit substitutes for the circuit capable of monitoring the headroom voltage described with reference to FIG. **6A**. Some of the component of the circuit of FIG. **6A** are included in the circuit of FIG. **18**. To avoid redundancy in this document, the components previously described are now only minimally described again. the input. In the circuit of FIG. **18**, like the circuit of FIG. **6A**, the anodes of diodes **196** and **198** are connected to the noninverting input of amplifier **212**. The anodes of diodes **196** and **198** are connected to amplifier **212** through resistor **204**. A reference voltage  $V_{ref}$ , is applied to the inverting input of amplifier **212** through a resistor **452**. In some versions of this invention voltage  $V_{ref}$  is a constant voltage between 15 and 30 VDC. Not illustrated and not part of the invention is the circuit internal to console **50** that generates voltage  $V_{ref}$ . A capacitor **454** is tied between the rail to on which the  $V_{ref}$  is present and the junction between the diodes **196** and **198** and resistor **204**. A resistor **456** is connected in parallel across capacitor **454**.

[0198] A diode **458** and a resistor **460** are connected parallel between the inverting input of amplifier **212** and the output of the amplifier. More specifically, the anode of diode **458** is connected to the inverting input of amplifier **212**; the cathode is connected to the junction of the amplifier and resistor **214**.

[0199] The circuit of FIG. **18** also receives as inputs the voltages present at the sources of MOSFETs **162** and **184**. Each of these voltages is applied to a unity gain amplifier circuit that functions as a rectifier. The amplifier circuit to which the signal present at the source of MOSFET **162** is applied includes an amplifier **464**. The signal present at the source of the MOSFET **162** is applied to the noninverting input of the amplifier **464**. Not identified are the resistor through which the voltage is applied to the noninverting input of amplifier **464** or the capacitor tied between this input and ground. The anode of a diode **466** is connected to the inverting input into amplifier **464**. The cathode of diode **466** is tied to the output of the amplifier **464**. The signal present at the Output of amplifier **464** is applied through a resistor **468** to the anode of a diode **470**.

[0200] The source of MOSFET **184** is tied to the same type of rectifier to which the source of MOSFET **162** is applied.

[0201] The signals present at the cathodes of diodes **470** are both applied to the noninverting input

of an amplifier **480**. A capacitor **472** is tied between the junctions of the diodes **470** and the input into amplifier **480**. A resistor **474** is connected in parallel across capacitor **472**. The signal present at the output of amplifier **480** is applied back to the inverting input of the amplifier. The signal present at the output of amplifier **480** is through separate resistors **462** applied to the inverting input of each of the amplifiers **464**.

[0202] The signal present at the output of amplifier **480** is, through a resistor **482**, applied to the inverting input of amplifier **230**. Thus, the input into the noninverting input of amplifier **230** is the lower of the two voltages present at the drains of MOSFETs **162** and **184**. The input into the inverting input of amplifier **230** is the higher of the two peak voltages present at the sources of the MOSFETs **162** and **184**. The output of amplifier **230** is the difference between the minimum one of these drain voltages and the higher of the one of these source voltages. This is the signal that is output by the circuit of FIG. **18**, at the junction of resistor **231** and capacitor **236** and the HEADROOM voltage.

[0203] In some versions of the invention, the signal gain of the individual sub-circuits of the amplifier may be lower or higher than what has been described.

[0204] Alternative assemblies for monitoring the headroom voltages are also possible. In the described system, the analog circuit produces the HDRM signal. In other versions of the invention, the analog circuit may include a FET that substitutes for the resistor disposed across capacitor **192**. Each control loop cycle the capacitor is turned on once to discharge the capacitor **192**. This would increase the response rate of the headroom monitoring circuit to changes in the voltages measured at the transistors. Other means may be employed to provide the reference voltage applied to the inverting input of amplifier **230**. Thus the voltage could be provided from a digital to analog converter. This is useful in versions of the invention in which it may be desirable to change the potential of the reference voltage. In other versions of this invention, drains of collectors of the switching transistors are digitized and applied to the processor **80**. A module run on the processor evaluates these voltage measurements and based on the evaluation produces the HDRM signal.

[0205] Similarly, the control processes, the control modules, run on the console processor **80** may operate differently from what has been described.

[0206] This invention is not limited to ultrasonic tool systems wherein equations based on Equations (1) to (3) are used to determine the voltage and frequency of the drive signal. Other versions of the invention may not rely of comparisons based on any one of measured, measured voltage, drive signal frequency, the equivalent of mechanical current to determine the voltage and frequency of the drive signal.

[0207] For example in some versions of the invention the default target headroom voltage may be the lowest possible target headroom voltage. In these versions of the invention, based on the operating state of the system, the headroom voltage calculator selectively increases the headroom voltage to a level above the default value. This construction of the invention can further reduce the extent to which the voltage drop across the MOSFETS **162** and **184** is in excess of what is needed to hold the transistors **162** and **184** in saturation.

[0208] In some versions of the invention, the headroom adjustor simply consists of a module that adds a fixed value to the measured headroom. It is acknowledged that this version of the system may result in the center tap voltage sometime being in excess of what is needed to hold the MOSFETS **162** and **184**. A benefit of this version of the invention, is that it reduces the time required to generate the value of the adjusted measured headroom.

[0209] In some versions of the invention, power supply limiter **320** outputs voltage limits for the next adjustment of the POWER\_SUPPLY\_CONTROL signal by multiplying the current voltage of the VAMP signal by a fixed coefficient. In still other versions of the invention one or both of the power supply limiter **320** or power supply controller **324** is or are configured to prevent the controller **324** from, immediately after the voltage of the drive signal is to be lowered, lowering the voltage applied to the transformer center tap. For example, in some versions of this invention,

console **50** is constructed to prevent the voltage of this signal from being lowered until a period of 1 to 5 seconds has passed from when the console starts to lower the drive signal. A benefit of this arrangement is that during the phase of a procedure in which the tip head **364** is reapplied to the bone, the center tap voltage will clearly be at a voltage that will allow the processor to rapidly increase the voltage of the drive signal.

[0210] In some versions of the invention, the power supply controller **324** may not use the voltage limits output by the power supply limiter **320** in a primary PID control algorithm to calculate the next value of the POWER\_SUPPLY\_CONTROL signal. Instead, in these versions of the invention, the power supply controller **324** compares an initially calculated POWER\_SUPPLY\_CONTROL signal to the voltage limits. If this initial POWER\_SUPPLY\_CONTROL signal is within the voltage limits, initially calculated POWER\_SUPPLY\_CONTROL signal is the POWER\_SUPPLY\_CONTROL output to the boost converter **88**. If the initially calculated POWER\_SUPPLY\_CONTROL signal is outside of the voltage limit, one of two possible events may occur. In some versions of the invention, the closest voltage limit is output as the POWER\_SUPPLY\_CONTROL signal.

[0211] In other versions of the invention, the power supply controller **324** reexecutes the PID control algorithm. In this execution of the PID control algorithm, the voltage limit is employed as the target headroom voltage. A benefit of this version of the invention is that each individual execution of the PID algorithm does not include a step to limit the POWER\_SUPPLY\_CONTROL signal. It should however be appreciated that should it be necessary to voltage limit the POWER\_SUPPLY\_CONTROL signal, two executions of the PID algorithm are performed. The first execution produces the initial POWER\_SUPPLY\_CONTROL signal, the signal indicating that the center tap voltage will fall outside of the limits defined by the power supply voltage limiter **320**. The second execution of the algorithm produces the POWER\_SUPPLY\_CONTROL signal that will result in the boost voltage being within the defined voltage limits.

[0212] It should thus be appreciated that all the disclosed software modules run on the processor **80** may not be present or may be present in different form. For example, there may be a construction of the invention in which loss of heat through the transistors functioning as the active resistors, MOSFETS **162** and **184**, in the disclosed version of the invention, is not a significant concern. In these versions of the invention as well as other versions of the invention the center tap voltage may be kept constant. Alternatively, while the voltage applied to the center tap voltage may be varied, the voltage may be set to have a relatively high minimum voltage level, a minimum voltage of 25 Volts or possibly a minimum voltage of 50 Volts or more. In these versions of the invention, the voltages present at the drains or collectors of the transistors would always be in saturation. This would eliminate the need for the voltage limiter **304** to limit increases in the voltage level of the BASE signal to ensure that the amplifier is in this state. This may make it possible to not require that presence of the above described power supply limiter.

[0213] In versions of the invention where the center tap voltage is constant, the power supply that produces this voltage may not be a variable power supply. This would eliminate the need to provide software for setting the DC voltage of the signal produced by this power supply.

[0214] Here for the purposes of this invention, it is understood that the DC voltage applied to the center tap of the transformer primary winding **252** is a voltage above ground. This voltage may even be considered constant if for some design consideration not relevant to the current invention, the voltage level varies at a constant frequency.

[0215] In some versions of the invention wherein the center tap voltage is regulated to ensure the proper headroom voltage, it may be possible to not include the circuit that produces a measure of the headroom voltage. In these versions of the invention, virtual value of headroom voltage is calculated based as a function of drive signal voltage and/or drive signal current.

[0216] In some versions of the invention, voltages across resistors attached to the transformer secondary winding provide the signals upon which at least one of drive signal voltage or drive

signal current is based.

[0217] The invention is also not limited to amplifiers wherein a boost converter functions as the variable DC voltage power supply. One alternative power supply is a buck converter.

[0218] There may be alternative control consoles that do not include all the inventive features of the described console **50**. Thus, some consoles of this invention may include the linear amplifier of this invention and not include either of the described headroom voltage measuring circuits.

Similarly, there may be versions of the invention wherein it may be desirable to employ one of the headroom voltage measuring circuits of this invention without the described linear amplifier.

[0219] It would be possible to provide an amplifier of this invention wherein the amplifier, instead of being a voltage controlled voltage source, is a voltage controlled current source. In these versions of the invention, it is typically not necessary to provide the feedback loop for regulating the voltage of the signal applied to the transformer primary winding.

[0220] Likewise it should be understood that the control console **50** of this invention may be used to provide AC drive signals to surgical tools other than handpieces that include power generating units other than ultrasonic drivers. For example, the control console may be used to provide an AC drive signal where the power generating unit is a sub-assembly that, in response to the application of the drive signal, emits light (photonic energy) or some form of mechanical energy other than ultrasonic energy. Alternatively the power generating unit may be an electrode that applies the drive signal, which is a form of RF energy, to the tissue to which the electrode is applied. In this type of procedure, the electrical energy is applied to the tissue so as to turn the electrical energy into heat. The application of this heat causes a desirable therapeutic effect on the tissue. Typically this therapeutic effect is the ablation of the tissue.

[0221] Further, the transformer and associated linear amplifier of this invention may have applications for generating a drive signal that is used to power a device used to perform a task other than a task associated with medicine or surgery.

[0222] Accordingly, it is an object of the appended claims to cover all such variations and modifications that come within the true spirit and scope of this invention.

## Claims

**1.** A control console for supplying an AC drive signal to a driver of an ultrasonic handpiece to vibrate a tip of the ultrasonic handpiece, the control console comprising: a transformer including a primary winding having first and second opposed ends and a center tap to which a DC voltage is applied, and including a secondary winding across which the AC drive signal is developed for vibrating the tip of the ultrasonic handpiece; and first and second transistors functioning as first and second active resistors coupled to the first and second opposed ends of the primary winding respectively for developing an AC voltage across the primary winding, wherein the control console is configured to vary a level of the DC voltage applied to the center tap of the primary winding based on the AC voltage developed across the primary winding.

**2.** The control console of claim 1, further comprising a processor configured to: determine a voltage across the first and second transistors that relates to the AC voltage developed across the primary winding; and set the level of the DC voltage applied to the center tap of the primary winding based on the determined voltage.

**3.** The control console of claim 1, further comprising: a headroom monitor coupled to the first and second transistors and configured to generate a headroom signal representative of a voltage across the first and second transistors that relates to the AC voltage developed across the primary winding; and a processor coupled to the headroom monitor and configured to set the level of the DC voltage applied to the center tap of the primary winding based on the headroom signal.

**4.** The control console of claim 3, wherein the headroom monitor is configured to receive as inputs voltages at first ends of the first and second transistors and voltages at second ends of the first and

second transistors that are opposite the first ends, and to generate the headroom signal based on a difference between the lower of the voltages present at the first ends of the first and second transistors and the higher of the voltages present at the second ends of the first and second transistors.

**5.** The control console of claim 3, wherein the headroom monitor is constructed so that voltages present between the first and second transistors and the transformer primary winding are applied to separate reverse biased diodes, the anodes of the reverse biased diodes are connected at a junction, and a constant voltage is applied to the junction of the anodes so that the voltage present at the junction of the anodes is the lower of the voltages present between the first and second transistors and the transformer primary winding, and wherein the headroom monitor is configured to generate the headroom signal based on the voltage present at the junction of the anodes.

**6.** The control console of claim 5, wherein the headroom monitor is constructed so that voltages present at ends of the first and second transistors that are distal to the transformer primary winding are applied to separate forward biased diodes, the cathodes of the forward biased diodes are connected at a junction, and the voltage present at the junction of the cathodes is the higher of the voltages at the ends of the first and second transistors, and wherein the headroom monitor is configured to generate the headroom signal based on the voltage present at the junction of the cathodes.

**7.** The control console of claim 3, wherein the processor is configured to: determine a change in voltage to be developed across the primary winding; and set the level of the DC voltage applied to the center tap of the primary winding based on the determined change in voltage and the headroom signal.

**8.** The control console of claim 7, further comprising: a sensor for measuring a voltage of the AC drive signal supplied to the ultrasonic handpiece; and a sensor for measuring a current of the AC drive signal supplied to the ultrasonic handpiece, wherein the processor is configured to determine the change in voltage to be developed across the primary winding based on the measured voltage and current of the AC drive signal.

**9.** The control console of claim 7, wherein the processor is configured to determine the change in voltage to be developed across the primary winding based on the headroom signal.

**10.** The control console of claim 7, wherein the processor is configured to: determine an adjusted headroom voltage based on the headroom signal and the determined change in voltage to be developed across the primary winding; compare the adjusted headroom voltage to a target headroom voltage; and set the level of the DC voltage applied to the center tap of the primary winding based on the comparison.

**11.** The control console of claim 10, wherein the processor is configured to adjust the target headroom voltage for comparison with the adjusted headroom voltage based on a voltage of the AC drive signal.

**12.** The control console of claim 7, wherein the processor is configured to: determine whether the AC voltage developed across the primary winding is to decrease based on the determined change in voltage; and responsive to determining that the AC voltage developed across the primary winding is to decrease, prevent the level of the DC voltage applied to the center tap of the primary winding from being lowered for at least a set period.

**13.** The control console of claim 7, wherein the processor is configured to: determine whether the AC voltage developed across the primary winding is to decrease based on the determined change in voltage; and responsive to determining that the AC voltage developed across the primary winding is to decrease, lower the level of the DC voltage applied to the center tap of the primary winding at a first rate that is slower than a second rate at which the AC voltage developed across the primary winding is decreased.

**14.** The control console of claim 13, wherein the processor is configured to: determine whether the AC voltage developed across the primary winding is to increase based on the determined change in



voltage; and responsive to determining that the AC voltage developed across the primary winding is to increase, raise the level of the DC voltage at a third rate that is faster than the first rate.

**15.** A control console for supplying an AC drive signal to a driver of an ultrasonic handpiece to vibrate a tip of the ultrasonic handpiece, the control console comprising: a transformer including a primary winding having first and second opposed ends and a center tap to which a DC voltage is applied, and including a secondary winding across which the AC drive signal is developed for vibrating the tip of the ultrasonic handpiece; first and second transistors functioning as first and second active resistors coupled to the first and second opposed ends of the primary winding respectively for developing an AC voltage across the primary winding; and a processor configured to: determine a change in voltage to be developed across the primary winding; and vary a level of the DC voltage applied to the center tap of the primary winding based on the determined change in voltage.

**16.** The control console of claim 15, further comprising: a sensor for measuring a voltage of the AC drive signal supplied to the ultrasonic handpiece; and a sensor for measuring a current of the AC drive signal supplied to the ultrasonic handpiece, wherein the processor is configured to determine the change in voltage to be developed across the primary winding based on the measured voltage and current of the AC drive signal.

**17.** The control console of claim 15, wherein the processor is configured to: determine whether the AC voltage developed across the primary winding is to decrease based on the determined change in voltage; and responsive to determining that the AC voltage developed across the primary winding is to decrease, prevent the level of the DC voltage applied to the center tap of the primary winding from being lowered for at least a set period.

**18.** The control console of claim 15, wherein the processor is configured to: determine whether the AC voltage developed across the primary winding is to decrease based on the determined change in voltage; and responsive to determining that the AC voltage developed across the primary winding is to decrease, lower the level of the DC voltage applied to the center tap of the primary winding at a first rate that is slower than a second rate at which the AC voltage developed across the primary winding is decreased.

**19.** The control console of claim 18, wherein the processor is configured to: determine whether the AC voltage developed across the primary winding is to increase based on the determined change in voltage; and responsive to determining that the AC voltage developed across the primary winding is to increase, raise the level of the DC voltage at a third rate that is faster than the first rate.

**20.** A method for regulating a DC voltage applied to a center tap of a primary winding of a transformer for inducing an AC drive signal across a secondary winding of the transformer that is supplied to an ultrasonic handpiece to vibrate a tip of the ultrasonic handpiece, the method comprising: applying the DC voltage to the center tap of the primary winding of the transformer; developing from the DC voltage an AC voltage across the primary winding that induces the AC drive signal across the secondary winding; and varying a level of the DC voltage applied to the center tap of the primary winding based on the AC voltage developed across the primary winding.

---