

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250259526

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Sermanoukian; Edouard et al.

---

### **Apparatus, System and Method for a Portable Personal Air Quality Monitor**

---

#### **Abstract**

Apparatuses, systems and methods of providing a personal air quality monitor. The personal air quality monitor may include a housing suitable for physical association with a person; an air inlet capable of providing air flow from an environment outside the housing to a chamber within the housing; a plurality of sensor resident within the chamber, suitable for receiving the airflow and measuring air quality factors associated with the airflow; and a communication system suitable for processing the air quality factor measurements and communicating the processed air quality factor measurements to a user interface cognizable to the person.

---

**Inventors:** Sermanoukian; Edouard (St. Petersburg, FL), Petker; Jason (St. Petersburg, FL)

**Applicant:** NYPRO INC. (Clinton, MA)

**Family ID:** 61619779

**Appl. No.:** 19/052635

**Filed:** February 13, 2025

#### **Related U.S. Application Data**

parent US continuation 18483976 20231010 parent-grant-document US 12254756 child US 19052635

parent US continuation 16333903 20190315 parent-grant-document US 11816970 US continuation PCT/US17/52076 20170918 child US 18483976

parent US continuation 15268310 20160916 parent-grant-document US 10467880 child US 16333903

---

#### **Publication Classification**

**Int. Cl.:** G08B21/12 (20060101); G01N33/00 (20060101)

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present disclosure claims priority to U.S. application Ser. No. 18/483,976 filed Oct. 10, 2023, which claims priority to U.S. application Ser. No. 16/333,903 filed Mar. 15, 2019, which claims priority to International Application No. PCT/US17/52076 filed Sep. 18, 2017, which claims priority to U.S. application Ser. No. 15/268,310 filed Sep. 16, 2016, the contents of which is incorporated by reference in entireties herein.

### BACKGROUND

#### Field of the Disclosure

[0002] The disclosure relates to air quality, and, more particularly, relates to an apparatus, system and method for a portable, personal air quality monitor.

#### Description of the Background

[0003] The term “air quality” indicates the state of the air in a given environment. Good air quality typically refers to “clean,” i.e., unpolluted, air. Clean air is essential for the health of humans, wildlife, vegetation, water and soil. Poor air quality may be the result of a number of factors, including emissions from various sources, including natural and human-caused emissions. For example, automobile, fossil fuel burning and livestock emissions can all have a significant effect on air quality. Poor air quality occurs when pollutants reach sufficiently significant concentrations to endanger or adversely impact human health or the environment.

[0004] Good outdoor air quality is vital to the well-being of humans and the natural environment. On average, a person inhales about 14,000 liters of air daily, and so the presence of significant pollutants in the inhaled air will have a significant adverse effect on health, either acutely or over time. Needless to say, those with pre-existing respiratory and heart conditions, diabetes, the young, and the elderly are particularly vulnerable.

[0005] Studies have repeatedly shown that poor air quality also adversely affects the natural environment. For example, ecological damage may occur when air pollutants come into direct contact with vegetation, or when inhaled by animals inhale. Pollutants may also settle out of the air onto land and water. From the soil, pollutants may wash into waterways, or be taken up by plants and animals. Further, some pollutants have a warming effect on the atmosphere.

[0006] The detrimental effects of poor air quality on human health and the environment, in turn, have negative economic impacts. Significant costs, for example, for hospitalization and medical treatment, premature death, and lost work time, may be incurred due to poor air quality. Moreover, damage to soil, vegetation, and waterways may reduce agricultural productivity, and, in urban areas, air pollution can be costly by, for example, disrupting transport or travel, or by corroding equipment or buildings.

[0007] Ambient air quality refers to the quality of outdoor air. It is preferably measured near ground level, away from direct sources of pollution and at the height relevant to breathing of the air by humans. Accordingly, outdoor air quality stations are typically placed in various geographical locations at ground level, such as by government agencies, in order to monitor and collect air quality data.

[0008] Air quality may be degraded when unwanted chemicals, substances or materials enter the air in large enough quantities to have detrimental effect, such as on the health of people, plants, animals, buildings, equipment, and/or the environment. This is termed “air pollution,” and the

substances detrimental to the air are termed “air pollutants.” The extent of the pollution of the air depends on the amount of pollutants, the rate at which the pollutants are released from various sources, and how quickly the pollutants disperse, or conversely, how long the pollutants are held or trapped in an area.

[0009] More particularly, air pollutants may occur as gases, or tiny solid particles, such as dust, mold, smoke, soot, cigarette smoke, mites, dander, formaldehyde, volatile organic compounds (VOCs), or radon gas. Pollutants may be emitted from natural sources, such as volcanoes, but many come from human and animal activity.

[0010] In areas with good airflow, pollutants will mix with the air and quickly disperse. However, when pollutants are trapped in an area, pollutant concentrations may increase rapidly. Trapping of pollution may occur, for example, when weather conditions (e.g., light winds and/or a temperature inversion), and/or nearby terrain (e.g., mountains) limit the movement of pollutants away from an area, thus resulting in poor air quality.

[0011] Air quality may be measured in one of two ways: either through continuous or noncontinuous monitoring. For continuous monitoring, air is constantly measured, and the data on air quality is continuously generated and stored. For noncontinuous monitoring, air may be monitored only periodically, or contaminants may be collected on a filter or in a canister over a period of time. In noncontinuous monitoring, data is only generated intermittently correspondent to the measurement period.

[0012] Therefore, the need exists for an air quality monitor that provides for improved monitoring of air quality in locations most important to particular individuals and to the environment, continuously or noncontinuously.

#### SUMMARY

[0013] The disclosed apparatuses, systems and methods provide at least a personal air quality monitor. The personal air quality monitor may include a housing suitable for physical association with a person; an air inlet capable of providing air flow from an environment outside the housing to a chamber within the housing; a plurality of sensor resident within the chamber, suitable for receiving the airflow and measuring air quality factors associated with the airflow; and a communication system suitable for processing the air quality factor measurements and communicating the processed air quality factor measurements to a user interface cognizable to the person.

[0014] More particularly, the disclosed method of monitoring air quality may include providing, through an air access point, air to one or more air quality factor sensors of a personal, portable air quality monitor; reading an air quality factor indicated by each of the one or more air quality factor sensors; processing the data from the one or more sensors into at least one indication of air quality; and displaying the at least one indication of air quality to a person associated with the personal, portable air quality monitor.

[0015] Thus, the disclosed embodiments provide an air quality monitor that provides for improved monitoring of air quality in locations most important to particular individuals and to the environment, continuously or noncontinuously.

---

## Description

### BRIEF DESCRIPTION OF THE FIGURES

[0016] The foregoing summary, as well as the following detailed description, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there are shown in the drawings embodiments which are exemplary. It should thus be understood that the disclosure is not limited to the precise arrangements and instrumentalities shown. In the drawings, like numerals represent like elements, and

[0017] FIG. 1A is a diagram illustrating an embodiment of a personal, portable air quality monitor;  
[0018] FIG. 1B is a diagram illustrating an embodiment of a personal, portable air quality monitor;  
[0019] FIG. 1C is a diagram illustrating an embodiment of a personal, portable air quality monitor;  
[0020] FIG. 2A is a diagram illustrating an embodiment integrating a portable, personal air quality monitor into a mobile device;  
[0021] FIG. 2B is a diagram illustrating an embodiment of a user interface of a portable, personal air quality monitor integrated into a mobile device;  
[0022] FIG. 3 is a diagram illustrating an embodiment of the connectivity of a portable, personal air quality monitor;  
[0023] FIG. 4 is a schematic block diagram illustrating a computing system in an embodiment;  
[0024] FIG. 5 is a diagram of an embodiment of a system employing multiple portable, personal air quality monitors;  
[0025] FIG. 6 is a flow diagram illustrating a method of monitoring air quality in accordance with an embodiment; and  
[0026] FIG. 7 is an environmental optionality illustration for a portable, personal air quality monitor.

#### DETAILED DESCRIPTION

[0027] The figures and descriptions provided herein may have been simplified to illustrate aspects that are relevant for a clear understanding of the herein described apparatuses, systems, and methods, while eliminating, for the purpose of clarity, other aspects that may be found in typical similar devices, systems, and methods. Those of ordinary skill may thus recognize that other elements and/or operations may be desirable and/or necessary to implement the devices, systems, and methods described herein. But because such elements and operations are known in the art, and because they do not facilitate a better understanding of the present disclosure, for the sake of brevity a discussion of such elements and operations may not be provided herein. However, the present disclosure is deemed to nevertheless include all such elements, variations, and modifications to the described aspects that would be known to those of ordinary skill in the art.

[0028] Embodiments are provided throughout so that this disclosure is sufficiently thorough and fully conveys the scope of the disclosed embodiments to those who are skilled in the art. Numerous specific details are set forth, such as examples of specific components, devices, and methods, to provide a thorough understanding of embodiments of the present disclosure. Nevertheless, it will be apparent to those skilled in the art that certain specific disclosed details need not be employed, and that embodiments may be embodied in different forms. As such, the embodiments detailed herein should not be construed to limit the scope of the disclosure. As referenced above, in some embodiments, well-known processes, well-known device structures, and well-known technologies may not be described in detail.

[0029] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting. For example, as used herein, the singular forms “a”, “an” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The steps, processes, and operations described herein are not to be construed as necessarily requiring their respective performance in the particular order discussed or illustrated, unless specifically identified as a preferred or required order of performance. It is also to be understood that additional or alternative steps may be employed, in place of or in conjunction with the disclosed aspects.

[0030] When an element or layer is referred to as being “on”, “engaged to”, “connected to” or “coupled to” another element or layer, it may be directly on, engaged, connected or coupled to the other element or layer, or intervening elements or layers may be present, unless clearly indicated

otherwise. In contrast, when an element is referred to as being “directly on,” “directly engaged to,” “directly connected to” or “directly coupled to” another element or layer, there may be no intervening elements or layers present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.). Further, as used herein the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0031] Yet further, although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Terms such as “first,” “second,” and other numerical terms when used herein do not imply a sequence or order unless clearly indicated by the context. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the embodiments.

[0032] In light of the aforementioned effects of negative, or poor, air quality, it is vital to the public health, to environmental well-being, and to the success of business and government, and it is particularly important for: the elderly, the young, and those in ill-health; livestock and food sources; the profitability of industry; the support of governments; and indeed to entire countries and the world, that acceptable levels of air quality be maintained. Although air quality monitoring may be important for both indoor, such as in offices, homes, airports, or gyms, and outdoor air quality, the importance of monitoring may be of particular importance in outdoor environments for a number of reasons, including that outdoor environments are shared by all of the foregoing, and that the air circulated in indoor environments is generally air initially obtained from the outdoor environment.

[0033] It has been estimated that roughly half of the world's population lives in an urban environment and suffers from some significant level of air pollution. Further, it has been estimated that some 896,000,000 persons of the world population suffer from some level of physical distress that is due to or exacerbated by air pollution. Such persons include sufferers of allergies, asthma, and COPD. It has also been estimated that approximately 50,000,000 users regularly employ fitness bands or activity trackers.

[0034] The disclosed embodiments are very relevant to all of the aforementioned persons. This is due, in part, to the ability of the disclosed personal, portable air quality monitor, system, and method to monitor for myriad air quality factors, such as carbon monoxide, carbon dioxide, nitrogen dioxide, sulfur dioxide, ground ozone, particulate pollution, lead, UV, pollen, and so on, in-situ for the user. These air quality factors are highly significant to urbanites, those suffering physical distress due to air quality, and fitness and activity enthusiasts, by way of non-limiting example.

[0035] The embodiments allow for air quality monitoring in a more relevant manner to the user than has historically been the case, i.e., the embodiments provide for improved air quality monitoring over the known, infrequently-placed government sensors. It is, of course, the case that optimal monitoring of air quality at locations where humans congregate is not accomplished by associating air quality monitoring with discrete, government-placed outdoor sensors, but rather is accomplished by associating air quality monitoring with the people, in-situ, in each environment on whose behalf the air quality should be monitored. Therefore, the disclosure provides air quality monitoring capabilities for association with individuals, and individual environments of those individuals, as the individuals move about, such that any current environment in which an individual finds herself may be monitored. That is, if the user of the disclosed individual air quality monitor is inside an office, at a restaurant, in a park walking a dog, at a farm, inside an airplane, at a sporting event, or the like, the air quality for the air then-being consumed by that individual may be uniquely monitored in the immediate vicinity of that individual.

[0036] Moreover, the capability to independently monitor air quality may allow for the providing of alerts or notifications to the user associated with the individual air quality monitor, and in addition may allow for sharing of the data incurred by that individual's air quality monitor, such that users may additionally monitor environments in which those users are currently not present. That is, the air quality data, and/or any alerts or notifications associated with that data, may not only be made available to the user of the monitor, but may additionally be shared, such as via upload to a cloud community associated with a Web-based thin client, a desktop or mobile app, or the like, such that other users or non-users of the monitors may assess air quality in nearly any environment, whether or not those individuals are then-present in that environment. Alerts may be presented, for example: visually, such as on simple or complex display; audibly, such as by one or more tones indicating one or more aspects of air quality; tactily, such as via one or more types of vibration indicating one or more aspects of air quality; on device or off device, such as on a smartphone proximate to the device; or via any other known manner.

[0037] The afore-discussed capabilities may allow for heretofore unknown proactivity in: individual decisions for a healthier lifestyle; local and regional decisions to improve air quality; and globally addressing environmental and atmospheric issues. By way of example, not only will the monitor allow the user of the monitor, and any individuals with whom the monitor's data is shared, to avoid exposure or prolonged exposure to poor air quality environments, but additionally the disclosed embodiments may allow for an improved assessment of individuals, businesses, or locations that make adverse environmental contributions, such as an assessment of those who are significantly contributing to greenhouse gases, ozone depletion, and global warming, by way of non-limiting example.

[0038] In accordance with the foregoing, the disclosure of a mobile air quality monitor may include a personal, portable stand-alone monitor, such as may be associated with a wristband, a necklace, a hair band, a sweat band, or an article of clothing, by way of non-limiting example; and may include a mobile monitor that may be an integrated aspect of another device, such integration with a watch, a computer, a mobile communications device, an automobile, or a piece of wearable equipment, by way of non-limiting example. Mobile equipment integrating the mobile air quality monitor of the embodiments may include equipment used in industries particularly susceptible to injurious air quality, such as helmets used in mining applications, mobile or wearable equipment in laboratories, movable equipment in a doctor's office, or the like. Thus, the embodiments of a monitor may serve to be or be part of products dedicated to improving lifestyle, recreation, healthcare, mining and high-risk industries, research laboratories, automotive industry, tourism, and the like.

[0039] In light of the foregoing, discussed herein is a personal, portable air quality monitor. More specifically, FIGS. 1A, 1B and 1C respectively illustrate a front, side and profile view of a personal, portable monitor **10**, illustrated in the form of standalone bracelet, such as may be formed by injection molding or other known methods, and which may structurally comprise plastics, polymers, polycarbonate, rubber, metal, silicone, neoprene, fabrics, or the like. The exemplary monitor **10** may be for use by an individual to monitor air quality for air in the vicinity of the individual. Of note, the bracelet shown in FIG. 1 is provided only by way of example, and is non-limiting as to the disclosed embodiments of a personal, portable air quality monitor.

[0040] In embodiments of FIGS. 1, the monitor **10** may include a complex user interface **14a**, such as a small display screen, to present sensed air data and/or notifications **16** to the user, and/or may include one or more simplistic user interfaces **14b**, such as multiple colors of LEDs indicative of levels of air contaminants in the immediate environment, to present air quality data to the user.

[0041] A first tier communications system **22** may be provided between sensors of air quality **40** and the user interfaces **14a**, **14b**, to allow for this communication of air quality to the user. Of note, the first tier communication system **22** may carry the information from sensors **40** to a user interface **14a**, **14b** not physically associated with the device including sensors **40**, as discussed further herein below. The first tier communications system **22** may include hard wiring, Bluetooth,

near field communication, wifi or internet of things (IoT) connectivity, by way of non-limiting example, and may, of course, include processing of the sensor data before the data is provided to the user interface **14a**, **14b**.

[0042] Further, the monitor **10** may include a second tier communication system **23** to, in additional and alternative embodiments, allow for sharing of the data incurred by the monitor **10** outside of the immediate vicinity **24** of the monitor, such as to the cloud (not shown). Of note, the second tier communication system **23** may send the information to a physical location remote from sensors **40**, and may also not be physically associated with the device including sensors **40**, as discussed further herein below. The second tier communication system **23** may include hard wiring, Bluetooth, near field communication, wifi or internet of things (IoT) connectivity, GPS, cellular communications capability, or the like, by way of example, and may additionally include processing of the sensor data prior to the remote communication of the data.

[0043] In some embodiments, the communication system tiers **22**, **23** may be combinations of the same, different, local, or remote communications systems, such as wherein a smartphone app **30** provides, on the smartphone display **14a**, indications to the user of air quality and notifications upon receipt of same from the sensors **40** of monitor **10**, such as wherein the monitor **10** is worn by the user but communicates via the first communication tier **22** with the smartphone app. Then, in turn and by way of non-limiting example, the smartphone may display the received information on display **14a**.

[0044] Further, the smartphone may communicate the received information to the cloud, thus acting as communications tier **23**. That is, the smartphone's cellular or wifi capabilities may serve as the second tier communication system **23**. Accordingly, the monitor **10** may effectively "use" the smartphone's communication capabilities to communicate its incurred data remotely, such as to the cloud, for provision to other users, as discussed further herein.

[0045] Needless to say, in some embodiments similar to those discussed immediately herein above, an independent user interface on the monitor **10** itself may be unnecessary. Or, the monitor **10** may include only a simple interface **14b**, such as one or more LED's, to indicate to the user that the user should view her smartphone app on smartphone display **14a** for a more informative indication related to air quality.

[0046] The air quality monitor **10** thus may include one or more air quality aspect sensors **40**, and at least one air access point **42a** for those sensors **40**. That is, the sensors **40** that make the air quality assessment in the monitor must have access to air in the localized area through an access point **42a**, i.e., the sensor is not hermetically sealed within the monitor **10**. The access point(s) **42a** may have associated therewith an access chamber or chambers **42b** that internally serve(s) the air received through access point **42a** to the sensors within the monitor **10**. The access point chamber **42b** may preferably be small in size so as to minimize the form factor of monitor **10**. For example, the access point chamber **42b** may be on the order of millimeters to ½ inch in size, and may accommodate the sensors and/or sensor board, and the requisite clearance for the same, therein.

[0047] Further, the air entering access point **42a** or chamber **42b** may be forced air or natural air. As such, access point **42a** may have associated therewith one or more fans or blowers (not shown), or air may enter naturally through access point **42a**, such as due to air currents or user movements, by way of non-limiting example.

[0048] Sensor types for sensors **40** may include any of a variety of partially, substantially or fully miniaturized sensors, such as: printed gas sensors-including polymer printed technologies; substrate level sensors; MEMS and MOS sensors; temperature or pressure sensors; integrated circuit sensors; electrochemical or printed electrochemical sensors; chemiresistive sensors; optical sensors; humidity sensors; and the like. The sensor types may sense any of the various factors that make up air quality, such as those factors discussed throughout.

[0049] Sensors **40** may each operate continuously or non-continuously, or may vary between continuous or non-continuous operation. For non-continuous operation, a clock (not shown) may

indicate the timing of the sensing operation. The timing of the sensing for each sensor may vary, such as in accordance with the danger level of that which is sensed, by way of non-limiting example. For example, carbon monoxide may be sensed at more regular intervals than is ozone. [0050] The disclosed monitor **10** may vary as to its productive life time without departing from the spirit or scope of the disclosure. That is, the individual monitor **10** may be intended for longer term use or limited term use. For example, a limited term use monitor **10** may be disposable to enable use in, for example, high risk environments such as in a mining helmet, or to enable use in temporary environments, such as in a wristband for use in a theme park. As such, the power requirements of the device may be met in a variety of ways as will be understood by the skilled artisan in light of the discussion herein, such as using a battery, a rechargeable battery, a solar-rechargeable battery, wired or wireless charging, solar charging, or the like.

[0051] With reference to FIG. 2A, illustrated is the inclusion of an air quality monitor **10** within a mobile device **110**. The exemplary device illustrated in FIG. 2 is a “walkie-talkie”, although the skilled artisan will appreciate that this illustration is exemplary in nature only, and that any portable device may include an integrated embodiment of the disclosed air quality monitor. By way of non-limiting example, the air quality monitor may be integrated with a smartphone, a watch, an employee badge, a belt buckle, a smartphone cover or similar cover for a mobile device, a shoe, or the like. Moreover, although the illustrated device may communicate over short distances using radio frequencies, such as in a high risk mining environment in the manner of a walkie talkie, or with a closely-coupled device, such as a smartphone, the disclosed embodiments may also be operable with devices that use any type of communication methodologies. Accordingly, the monitor may be equipped to communicate, with local and/or remote devices, using any type of known communication method, such as Bluetooth, RF, NFC, cellular, wifi, IoT protocols, or the like, as discussed throughout.

[0052] In the illustration of FIG. 2A, air quality monitor data **112** may be provided to the user over the same user interface **114** as is otherwise used by the device **110**, or may be communicated to the user via an additional or alternative user interface. For example, a typical user interface **114** for a walkie talkie may include a display, such as on a liquid crystal display (LCD) or LED or OLED display, of available power levels, signal strength, and/or activity of communications, and in the disclosed embodiments the user interface **114** may additionally include: one or more buttons to receive user input or commands **115**; a simple or complex display of air quality **116**, such as a number of bars indicative of air quality; and/or one or more LED's **117** on the walkie talkie, such as may indicate to the user that the user should check his or her mobile device app for air quality information (as discussed above, by way of example, with respect to FIG. 1).

[0053] A user interface for air quality monitoring may include different indications for different aspects of air quality. For example, aspects of air quality of particular interest in a given environment or to a particular individual may be monitored with particularity, and the choice of such particular elements of air quality may or may not be subjected to choice by and/or display or indication to the user. For example, in the illustration of FIG. 2B, the air quality aspect **116** of the user interface **114** may comprise six circles **116a**, **116b**, **116c**, **116d**, **116e**, **116f**, each having four “pie slices” per circle, to indicate factors of air quality.

[0054] In the illustrated embodiment, four pie slices in a given circle may indicate optimal air quality for that factor of air quality. Exemplary air quality factors may include CO.sub.2 levels, particulate levels, pollen levels, UV levels, mold levels, and dust levels. Other air quality aspects which may be monitored include, but are not limited to, CO, NO.sub.2, SO.sub.2, O.sub.3, particle pollution PM 2.5, particle pollution PM 10, or lead (Pb), by way of non-limiting example. As such, it goes without saying that sensors **40** associated with each of the air quality factors to be monitored would be included in the mobile air quality monitor **10**, should have access to the air in that particular environment via air access point **42a**, and should have sufficient connectivity to be able to communicate sensor data via first communication tier **22** to the understandable user interface



**114.**

[0055] Thereby, a user may be informed, in-situ, as to the particular air quality factor or factors important to that person. Those factors may be selectable to the person, or may be preset for monitor **10**. Thus, for example, if an individual suffers from severe asthma, an alert of a high pollen particulate count may indicate to that person that she should leave the vicinity immediately. These selections may be based on user wants or needs that are input from user, such as to the user interface, such as during initial setup or during discrete operation timeframes.

[0056] FIG. **3** illustrates the connection of the sensors **40** to the user interface **114**, optionally to an external communication interface (such as a nearby smartphone) **212**, and, optionally, to the cloud or another remote location **214** via communication means **23**, such as to enable sharing of incurred data **215**. In the embodiment of FIG. **3**, the mobile air quality monitor **202** may be equipped with a plurality of sensors **40** capable of monitoring a number of air quality factors, such as six factors in the example herein above. Through the user interface **114**, the user may be provided with the capability to access the data from all, or only select or selected ones, of these sensors **40**.

[0057] The data from the sensors **40** may be communicated to the user interface **114** via communication first tier **22** using any of the communication methodologies discussed herein or others known to the art, such as, by way of non-limiting example, RF, hardware, Bluetooth, wifi, cellular, or the like. Prior to presentation on the user interface **114**, the data may be stored in one or more computing memories, such as in a database format, and may be time buffered as necessary prior to presentation on the user interface, as discussed further herein below in relation to FIG. **4**. Presentation on the user interface **114** may preferably occur pursuant to an indication to make such a display from one or more computing processors associated with the user interface **114** and/or the sensors **40**, as also discussed further herein below in relation to FIG. **4**.

[0058] Communication of user input to the user interface **114** may or may not occur in the same manner as discussed herein with respect to communication from the sensors to the user interface, as will be understood by the skilled artisan in light of the discussion herein. That is to say, the user interface **14a**, **14b**, **114** connectivity first tier communication system **22** may or may not be bidirectional.

[0059] Yet further, and with or without direction from the user as input to the user interface **114**, one or more second tier communication methodologies **23** may allow for communication of the sensor data to the cloud, such as to allow for sharing with other users in different environments, or in the same environment, as is also discussed further in relation to FIG. **5**. That is, the air quality monitor **10** may be capable of communicating **23**, such as via RF, Bluetooth, NFC, or cellular communications, the incurred data in relation to air quality, and/or any alerts or notifications associated therewith, to a remote location, such as to the cloud, for storage, such as in a database, for access at a later time by the user of that sensor, and/or for access by other users.

[0060] The communication from the monitor to the cloud may or may not occur using the same communication methodology as the communication from the monitor to the local user interface or interfaces, i.e., the first and second tier communications **22**, **23**, may use the same or substantially the same hardware. Moreover, communications may occur serially through the first and second tiers **22**, **23**, such as from the sensors **40** to the user interface **14a**, **14b**, **114**, and then from a processing system associated with the user interface **14a**, **14b**, **114** (such as the processing system of a smartphone proximate to the monitor **10**) to the cloud.

[0061] Whether or not the first and second tier communication systems **22**, **23** overlap or are distinct, the eventual presence of in-situ data at a remote storage site, such as in the cloud, may allow for remote users to make decisions about an environment in which they are not then-present. For example, a parent of a child with a medical condition may be able to review air quality in an amusement park, and may thus be enabled to avoid starting a trip to that amusement park if the cloud data from in-situ monitors **10** at the amusement park indicates that the air quality would exacerbate the child's condition.

[0062] FIG. 4 illustrates an embodiment of a computer processing system **400** that may receive monitor data and other inputs, such as user inputs, as discussed herein, and that may perform the processing, logic, and communications control discussed throughout. That is, the computing system **400** may be used in accordance with herein described monitor **10**, systems and methods.

[0063] Computing system **400** is capable of executing software, such as an operating system (OS) and one or more computing applications **490**. The software may likewise be suitable for operating hardware, such as via inputs/outputs (I/O), using said applications **490**.

[0064] The operation of computing system **400** is controlled primarily by computer readable instructions, such as instructions stored in a computer readable storage medium, such as on a hard disk drive (HDD) **415**, RAM, ROM, EEPROM, or the like (not shown). Such instructions may be executed within central processing unit (CPU) **410** to cause computing system **400** to perform the disclosed operations. In many known computer servers, workstations, PLCs, personal computers, mobile devices, and the like, CPU **410** is implemented in an integrated circuit called a processor.

[0065] The various illustrative logics, logical blocks, modules, alerts and assessments described in connection with the embodiments disclosed herein may be implemented or performed with any of a general purpose CPU, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof, respectively acting as CPU **410**. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

[0066] It is appreciated that, although computing system **400** is shown to comprise a single CPU **410**, such description is merely illustrative, as computing system **400** may comprise a plurality of CPUs **410**, which may be distributed on and off of monitor **10**. Additionally, the computing system **400** may exploit the resources of remote or parallel CPUs (not shown), for example, through local or remote communications network **470** or some other data communications means.

[0067] In operation, CPU **410** fetches, decodes, and executes instructions from a computer readable storage medium, such as HDD **415**. Such instructions can be included in the software, such as the operating system (OS), machine code, executable programs/applications, and the like. Information, such as computer instructions and other computer readable data, is transferred between components of computing system **400** via the system's main data-transfer path. The main data-transfer path may use a system bus architecture **405**, although other computer architectures (not shown) can be used.

[0068] System bus **405** may include data lines for sending data, address lines for sending addresses, and control lines for sending interrupts and for operating the system bus. Some busses provide bus arbitration that regulates access to the bus by extension cards, controllers, and CPU **410**.

[0069] Memory devices coupled to system bus **405** can include random access memory (RAM) **425** and read only memory (ROM) **430**. Such memories include circuitry that allows information to be stored and retrieved. ROMs **430** generally contain stored data that cannot be modified. Data stored in RAM **425** can generally be read or changed by CPU **410** or other communicative hardware devices. Access to RAM **425** and/or ROM **430** may be controlled by memory controller **420**. Memory controller **420** may provide an address translation function that translates virtual addresses into physical addresses as instructions are executed.

[0070] The steps and/or actions described in connection with the aspects disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two, in communication with memory controller **420** in order to gain the requisite performance instructions. That is, the described software modules to perform the functions and provide the directions discussed herein throughout may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, a hard disk, a removable disk, a

CD-ROM, or any other form of storage medium known in the art. Any one or more of these storage medium may be coupled to the processor **410**, such that the processor can read information from, and write information to, that storage medium. In the alternative, the storage medium may be integral to the processor. Further, in some aspects, the processor and the storage medium may reside in an ASIC. Additionally, in some aspects, the steps and/or actions may reside as one or any combination or set of instructions on an external machine readable medium and/or computer readable medium as may be integrated through I/O port(s) **485**, which may include wireless ports. [0071] In addition, computing system **400** may contain peripheral controller **435** responsible for communicating instructions using a peripheral bus from CPU **410** to peripherals and other hardware, such as printer **440**, keyboard **445**, and mouse **450**. An example of a peripheral bus is the Peripheral Component Interconnect (PCI) bus.

[0072] One or more hardware input/output (I/O) devices **485**, such as sensors **40**, may be in communication with hardware controller **490**. This hardware communication and control may be implemented in a variety of ways and may include one or more computer busses and/or bridges and/or routers. The I/O devices controlled may include any type of port-based (including wireless “ports”) hardware, and may additionally comprise software, firmware, or the like, such as the disclosed sensors inputs/outputs **40**, and can also include network adapters and/or mass storage devices from which the computer system **400** can send and receive data for the purposes disclosed herein. The computer system **400** may thus be in communication with the Internet/cloud or other networked devices/PLCs via the I/O devices **485** and/or via communications network **470**.

[0073] Display **460**, which is controlled by display controller **455**, may optionally be used to display visual output generated by computing system **400**, and may comprise, for example, display **14a**. Display controller **455** may also control, or otherwise be communicative with, the display. Visual output may include text, graphics, animated graphics, and/or video, for example. Display **460** may be implemented with a CRT-based video display, an LCD-based display, gas plasma-based display, touch-panel, or the like.

[0074] Further, computing system **400** may contain network adapter **465** which may be used to couple computing system **400** to external devices or an external communication network **470**, which may include or provide access to the Internet, and hence which may provide cloud access to the air quality data discussed herein as the second tier communication system **23**. Communications network **470** may provide user access to computing system **400** with means of communicating and transferring software and information electronically, and may be coupled directly or indirectly to computing system **400**. It is appreciated that the network connections shown are exemplary, and other means of establishing communications links between multiple computing systems **400**, and/or with remote users, may be used.

[0075] It is appreciated that computing system **400** is merely illustrative of a computing environment in which the herein described systems and methods may operate, and thus does not limit the implementation of the herein described systems and methods in computing environments having differing components and configurations. That is, the inventive concepts described herein may be implemented in various computing environments using various components and configurations.

[0076] FIG. 5 illustrates a system incorporating multiple air quality monitors **10a**, **10b**, **10c**, . . . **10n**. In the illustration, several air quality monitors, each in different environments and each comprising standalone, integrated, portable air quality monitors, receive individual sensor data via a first communications tier **22**, and communicate data from each such air quality monitor **10a**, **10b**, **10c**, . . . **10n** to one or more servers **504**, such as may be resident in or associated with the cloud **506**, to allow for storage of this data in one or more databases associated with the servers **504**. The communication of this data may occur, by way of non-limiting example and as illustrated, over the second tier system **23** in the form of a cellular network, a Bluetooth network, a wired network, or combinations thereof, by way of non-limiting example. Once stored at the server database **505**, this

data may be made available, such as in a searchable format based on entry of a geographic location, from the cloud **506**, as illustrated.

[0077] FIG. **6** is a flow diagram illustrating a method **600** related to the disclosed embodiments. In the illustration, at step **602** air is provided to one or more air quality factor sensors of a personal, portable air quality monitor. At step **604**, each of the one or more sensors reads the factor relevant to that sensor. This data is provided, via one or more processors, to a user interface at step **606**. As discussed herein, the user interface may preferably be associated with one or more mobile devices. [0078] At optional step **608**, the data provided to the user interface, and any additional data deemed suitable for upload, is uploaded over one or more networks to the cloud. This accumulated data over multiple locations may then be made available by the aforementioned user interface, or over other secondary user interfaces, to multiple other users at step **612**.

[0079] Data safety and security for uploads/downloads may be managed using cellular, networking, and/or IP protocols. For example, cellular security and encryption protocols for mobile devices may be used to maintain user confidentiality during the data exchanges of steps **608** and **612**.

[0080] Moreover, aspects of a method executed in accordance with the disclosure may, as will be understood by the skilled artisan, include the execution of software, such as using the computing system indicated in FIG. **4**. In order to perform that aspects discussed herein, such software may include engines, subroutines, or the like to performed the disclosed functionality, including evaluation of current air quality data and historical air quality data, including enablement of user interaction with such data, such as via the user interface(s) discussed herein; GPS or similar geo-location of the air quality monitor and/or geo-coding of the data associated therewith; profile settings, such as user preferences; indoor versus outdoor indications or settings; external input to enable analysis for or providing of air quality data to a user, such as external input from weather stations, other user, or the like; and other analytics or network communications suitable for use in the disclosed embodiments.

[0081] Thus, disclosed is a personal, portable air quality monitor. The monitor **10** may be independent, or may be associated with a variety of secondary devices in a variety of sensing environments, such as environments **702**, **704**, **706**, **708**, **710**, **712**, **714**. This is illustrated by way of example in the environmental illustration of FIG. **7**, although it will be appreciated that the disclosure is not limited to the environments and/or the devices associated with monitor **10** in FIG. **7**.

[0082] In the foregoing detailed description, it may be that various features are grouped together in individual embodiments for the purpose of brevity in the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that any subsequently claimed embodiments require more features than are expressly recited.

[0083] Further, the descriptions of the disclosure are provided to enable any person skilled in the art to make or use the disclosed embodiments. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the spirit or scope of the disclosure. Thus, the disclosure is not intended to be limited to the examples and designs described herein, but rather is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

## Claims

**1.** A personal air quality monitor, comprising: a housing suitable for physical association with a person; an air inlet capable of providing air flow from an environment outside the housing to at least one chamber within the housing; a plurality of sensor resident within the at least one chamber, suitable for receiving the airflow and measuring air quality factors associated with the airflow; a communication system suitable for processing the air quality factor measurements and communicating the processed air quality factor measurements to a local user interface cognizable

to the person; and a remote processing system that is configured to: receive the air quality factor measurements wirelessly from the communication system; and; process the received air quality factor measurements for display on a remote user interface.

2. The monitor of claim 1, wherein the housing at least partially forms a bracelet.
  3. The monitor of claim 1, wherein the physical association comprises integration with a garment.
  4. The monitor of claim 1, wherein the housing is integrated with a mobile communications device.
  5. The monitor of claim 1, wherein the housing is comprised of at least one selected from the group consisting of plastics, polymers, polycarbonate, rubber, metal, silicone, neoprene, and fabrics.
  6. The monitor of claim 1, further comprising a second communication system suitable for remotely communicating the processed air quality factor measurements.
  7. The monitor of claim 1, wherein the user interface comprises a display screen.
  8. The monitor of claim 1, wherein the user interface comprises at least one light emitting diode.
  9. The monitor of claim 1, wherein the user interface comprises alerts regarding the processed air quality factor measurements.
  10. The monitor of claim 9, wherein at least one of the alerts refers the person to view a secondary device's user interface.
  11. The monitor of claim 1, wherein the communication system comprises at least one of hard wiring, Bluetooth, near field communication, wifi and internet of things (IoT) connectivity.
  12. The monitor of claim 1, wherein the sensors comprise partially, substantially or fully miniaturized sensors.
  13. The monitor of claim 1, wherein the sensors comprise at least one selected from the group consisting of printed gas sensors, substrate level sensors, MEMS and MOS sensors, temperature sensors, pressure sensors, integrated circuit sensors, electrochemical sensors, printed electrochemical sensors, humidity sensors, chemiresistive sensors, and optical sensors.
  14. The monitor of claim 1, wherein at least ones of the sensors comprise noncontinuously operating sensors.
  15. The monitor of claim 1, wherein the housing comprises a disposable housing and a power source.
  16. The monitor of claim 1, wherein the processed air quality factor measurements comprise levels of at least one of CO.sub.2, particulate, pollen, UV, mold, dust, CO, NO.sub.2, SO.sub.2, O.sub.3, particle pollution PM 2.5, particle pollution PM 10, and lead.
-