

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261083

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Saghir; Amir et al.

SMALL CELL AGGREGATION SERVICE

Abstract

A method, a device, and a non-transitory computer-readable storage medium are described in which a small cell aggregation service is provided. The service may include providing a global identifier for small cell devices that may be used for the transmission and reception of messages between small cell devices and core network devices. The service may include an intermediary network device, such as a gateway device or an aggregation device that uses the global identifier to transmit and receive control plane, user plane, or both types of messages, for example.

Inventors: Saghir; Amir (Frisco, TX), Hanbaly; Said (Prosper, TX)

Applicant: Verizon Patent and Licensing Inc. (N/A, N/A)

Family ID: 88239117

Appl. No.: 19/192828

Filed: April 29, 2025

Related U.S. Application Data

parent US continuation 17718945 20220412 parent-grant-document US 12309685 child US 19192828

Publication Classification

Int. Cl.: H04W40/24 (20090101); H04W8/26 (20090101); H04W16/32 (20090101); H04W40/02 (20090101); H04W48/16 (20090101); H04W88/16 (20090101)

U.S. Cl.:

CPC H04W40/246 (20130101); H04W8/26 (20130101); H04W16/32 (20130101); H04W40/02 (20130101); H04W48/16 (20130101); H04W88/16 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION [0001] This patent application is a continuation of U.S. patent application Ser. No. 17/718,945 entitled “SMALL CELL AGGREGATION SERVICE” and filed on Apr. 12, 2022, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

[0002] Development and design of networks present certain challenges from a network-side perspective and an end device perspective. For example, Next Generation (NG) wireless networks, such as Fifth Generation New Radio (5G NR) networks are being deployed and under development.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] FIG. 1 is a diagram illustrating an exemplary environment in which an exemplary embodiment of a small cell aggregation service may be implemented;

[0004] FIG. 2A is a diagram illustrating another exemplary environment in which an exemplary embodiment of the small cell aggregation service may be implemented;

[0005] FIG. 2B is a diagram illustrating still another exemplary environment in which an exemplary embodiment of the small cell aggregation service may be implemented;

[0006] FIG. 2C is a diagram illustrating yet another exemplary environment in which an exemplary embodiment of the small cell aggregation service may be implemented;

[0007] FIG. 2D is a diagram illustrating an exemplary embodiment of a global small cell device identifier scheme associated with the small cell aggregation service;

[0008] FIG. 3 is a diagram illustrating exemplary components of a device that may correspond to one or more of the devices illustrated and described herein;

[0009] FIG. 4 is a flow diagram illustrating an exemplary process of an exemplary embodiment of the small cell aggregation service; and

[0010] FIG. 5 is another flow diagram illustrating another exemplary process of an exemplary embodiment of the small cell aggregation service.

DETAILED DESCRIPTION

[0011] The following detailed description refers to the accompanying drawings. The same reference numbers in different drawings may identify the same or similar elements. Also, the following detailed description does not limit the invention.

[0012] In order to provide and/or extend wireless signal coverage in a given geographic area, a provider of a wireless communication service may deploy small and/or low-power cellular radio access nodes. As such, the deployment of femtocells, picocells, microcells, and/or the like, for example, naturally leads to cell densification. Each small cell device, such as a femtocell device has a direct connection with a core network device. For example, the femtocell device may have a direct connection with a user plane function (UPF) and an access and mobility management function (AMF) of a Fifth Generation (5G) core network. Given this framework, there are various technological challenges that relate to scalability and link capacity associated with communication links between a radio access network and a core network; user plane traffic and control plane traffic; network communications and activities associated with a small cell device (e.g., maintenance, updates, pinging, rebooting, etc.); impacting core network communications and activities (e.g., logging, alarms, etc.); and taxing of network resources, network services, and operations of a network. Also, Internet Protocol (IP)-based backhaul links that may be used to

connect small cell devices to a core network may be unreliable, lack security, and/or unable to support various performance metrics (e.g., quality of service (QOS), etc.) of an application service. [0013] According to exemplary embodiments, a small cell aggregation service is described. According to an exemplary embodiment, the small cell aggregation service may be implemented by an intermediary network device, such as a gateway device, an aggregation device, a concentrator device, or similar network device (e.g., a relay server) that may manage and route traffic between small cell devices and another network device. For example, the intermediary network device may manage user plane and/or control plane traffic between small cell devices and a core network device, such as an AMF and/or a UPF of a core network.

[0014] According to an exemplary embodiment, the small cell aggregation service may aggregate control plane and/or user plane interfaces based on an identifier scheme. According to an exemplary embodiment, a global identifier may include a portion of bits that uniquely identifies the intermediary network device that is common for a set of small cell devices. According to an exemplary embodiment, the global identifier may include a remainder portion of the bits which may be used to differentiate each small cell device and/or a cell or a sector of each small cell device from among the set of small cell devices common to the intermediary network device. According to an exemplary embodiment, the global identifier may uniquely and globally identify each small cell device and/or the cell or the sector.

[0015] In this way, user plane and/or control plane interfaces, communication links, and traffic between small cell devices and core network devices may be aggregated and identified via the intermediary network device. Additionally, the intermediary network device may provide a consolidated connection and interface to core network devices, such as the UPF and the AMF, on behalf of the set of small cell devices. For example, the intermediary network device may aggregate traffic to and disaggregate traffic from the core network and other types of networks (e.g., an application layer network, such as a MEC network, Internet, cloud network, packet data network, data center, or the like).

[0016] In view of the foregoing, the small cell aggregation service may aggregate traffic and control plane and/or user plane interfaces between small cell devices and core network devices. For example, the intermediary network device may consolidate the multiple interfaces of the set of small cell devices to a single interface. The small cell aggregation service may improve link capacity, scalability, and various network operations, network procedures, and communications pertaining to small cell devices, as described herein. The small cell aggregation service may manage and route the traffic between small cell devices and a core network and/or another type of network based on the global identifier, as described herein. The small cell aggregation service may also improve reliability, security, and/or other performance metrics (e.g., bit rate, latency, etc.) relative to IP-based customer backhaul connections.

[0017] Control plane aggregation and/or user plane aggregation of the small cell aggregation service may provide a higher link capacity and facilitate 5G core network scalability as the number of small cell devices grow in the network. The control plane aggregation may be beneficial during maintenance and service disruptions of small cell devices which will become transparent to the core network. For example, femtocells may reboot because of software updates and configuration changes, surrounding Macro deployment updates/changes, and other activities that may trigger massive femtocell reboots/re-establishment resulting in excessive signaling. The control plane aggregation of the small cell aggregation service may also avoid backhaul (Internet Service Provider (ISP)) issues impacting 5G core operations (logs/alarms etc.) and interface reliability relating to a customer backhaul. Additionally, user plane aggregation may make tunneling issues (e.g., bounce, re-establishments) transparent to the 5G core network.

[0018] FIG. 1 is a diagram illustrating an exemplary environment **100** in which an exemplary embodiment of a small cell aggregation service may be implemented. As illustrated, environment **100** includes an access network **105** and a core network **120**. Access network **105** includes access

devices **107** (also referred to individually or generally as access device **107**). Core network **120** includes core devices **122** (also referred to individually or generally as core device **122**).

[0019] According to an exemplary embodiment of environment **100**, at least some of access devices **107** may be provisioned in accordance with an exemplary embodiment of the small cell aggregation service, as described herein.

[0020] The number, type, and arrangement of networks illustrated in environment **100** are exemplary. For example, according to other exemplary embodiments, environment **100** may include fewer networks, additional networks, and/or different networks. For example, according to other exemplary embodiments, other networks not illustrated in FIG. **1** may be included, such as an X-haul network (e.g., backhaul, mid-haul, fronthaul, etc.), a transport network (e.g., Signaling System No. 7 (SS7), etc.), an application layer network (e.g., a mobile edge computing (MEC) network, the Internet, or the like), or another type of network that may support a wireless service and/or an application service, as described herein.

[0021] A network device, a network element, or a network function (referred to herein simply as a network device) may be implemented according to one or multiple network architectures, such as a client device, a server device, a peer device, a proxy device, a cloud device, and/or a virtualized network device. Additionally, a network device may be implemented according to various computing architectures, such as centralized, distributed, cloud, and/or another type of computing architecture, and may be incorporated into distinct types of network architectures (e.g., Software Defined Networking (SDN), virtual, logical, network slice, etc.). The number, the type, and the arrangement of network devices are exemplary.

[0022] Environment **100** includes communication links between the networks and between the network devices. Environment **100** may be implemented to include wired, optical, and/or wireless communication links. A communicative connection via a communication link may be direct or indirect. For example, an indirect communicative connection may involve an intermediary device and/or an intermediary network not illustrated in FIG. **1**. A direct communicative connection may not involve an intermediary device and/or an intermediary network. The number, type, and arrangement of communication links illustrated in environment **100** are exemplary.

[0023] Environment **100** may include various planes of communication including, for example, a control plane, a user plane, a service plane, and/or a network management plane. Environment **100** may include other types of planes of communication. A message communicated in support of the small cell aggregation service may use at least one of these planes of communication. Additionally, an interface of a network device may be modified (e.g., relative to an interface defined by a standards body, such as Third Generation Partnership Project (3GPP), 3GPP2, International Telecommunication Union (ITU), European Telecommunications Standards Institute (ETSI), GSM Association (GSMA), and the like) or a new interface of the network device may be provided in order to support the communication (e.g., transmission and reception of messages, an information element (IE), an attribute value pair (AVP), an object, a parameter, or another form of a data instance) between devices and small cell aggregation service logic of the device. According to various exemplary implementations, the interface of the network device may be a service-based interface, a reference point-based interface, an Open Radio Access Network (O-RAN) interface, a 5G interface, another generation of interface (e.g., 5.5G, Sixth Generation (6G), Seventh Generation (7G), etc.), or some other type of network interface.

[0024] Access network **105** may include one or multiple networks of one or multiple types and technologies. For example, access network **105** may be implemented to include a 5G RAN, a future generation RAN (e.g., a 6G RAN, a 7G RAN, or a subsequent generation RAN), a centralized-RAN (C-RAN), an O-RAN, and/or another type of access network. Access network **105** may include a legacy RAN (e.g., a Fourth Generation (4G) or 4.5 RAN, etc.). Access network **105** may communicate with and/or include other types of access networks, such as, for example, a Wi-Fi network, a Worldwide Interoperability for Microwave Access (WiMAX) network, a local area

network (LAN), a Citizens Broadband Radio System (CBRS) network, a cloud RAN, an O-RAN network, a virtualized RAN (vRAN), a self-organizing network (SON), a wired network (e.g., optical, cable, etc.), or another type of network that provides access to or can be used as an on-ramp to access network **105**.

[0025] Access network **105** may include different and multiple functional splitting, such as options **1, 2, 3, 4, 5, 6, 7, or 8** that relate to combinations of access network **105** and a core network **120** including, for example, an evolved packet core (EPC) network and/or a 5G core network, or the splitting of the various layers (e.g., physical layer, medium access control (MAC) layer, radio link control (RLC) layer, packet data convergence protocol (PDCP) layer, and/or other layers), plane splitting (e.g., user plane, control plane, etc.), interface splitting (e.g., F1-U, F1-C, F2-C, F2-U, E1, Xn-C, Xn-U, X2-C, Common Public Radio Interface (CPRI), etc.) as well as other types of network services, such as dual connectivity (DC) or higher, carrier aggregation (CA), edge and core network slicing, coordinated multipoint (COMP), various duplex schemes, and/or another type of connectivity service (e.g., non-standalone (NSA) new radio (NR), stand-alone (SA) NR, and the like).

[0026] Depending on the implementation, access network **105** may include one or multiple types of network devices, such as access devices **107**. For example, access device **107** may include a next generation Node B (gNB), an evolved LTE (eLTE) evolved Node B (eNB), an eNB, a radio network controller (RNC), a remote radio head (RRH), a baseband unit (BBU), a radio unit (RU), a remote radio unit (RRU), a centralized unit (CU), a CU control plane (CU-CP), a CU user plane (CU-UP), a distributed unit (DU), a small cell device (e.g., a picocell device, a femtocell device, a microcell device, a home gNB, or another types of low power cellular network device), an open network device (e.g., O-RAN Centralized Unit (O-CU), O-RAN Distributed Unit (O-DU), or the like), a 5G ultra-wide band (UWB) node, a future generation wireless access device (e.g., a 6G wireless station, a 7G wireless station, or another generation of wireless station), another type of wireless node (e.g., a WiFi device, a WiMax device, a hotspot device, etc.) that provides a wireless access service, or another type of network device that provides a transport service (e.g., routing and forwarding), such as a router, a switch, or another type of layer **3** (e.g., network layer of the Open Systems Interconnection (OSI) model) network device. Access device **107** may also include other types of network devices, such as a radio network controller (RNC), a RAN Intelligent Controller (RIC), an orchestrator device, an artificial intelligence (AI) and/or machine learning (ML) device, or another type of RAN management or control level network device.

[0027] According to various exemplary implementations, access device **107** may include one or multiple sectors or antennas. The antenna may be implemented according to various configurations, such as single input single output (SISO), single input multiple output (SIMO), multiple input single output (MISO), multiple input multiple output (MIMO), massive MIMO, three dimensional (3D) and adaptive beamforming (also known as full-dimensional agile MIMO), two dimensional (2D) beamforming, antenna spacing, tilt (relative to the ground), radiation pattern, directivity, elevation, planar arrays, and so forth. Depending on the implementation, access device **107** may provide a wireless access service at a cell, a sector, a sub-sector (also known as a geo-bin), and/or another configurable level.

[0028] According to an exemplary embodiment, some of access devices **107** include logic that provides the small cell aggregation service. For example, the logic of a small cell device may include generating and transmitting messages that include the global small cell device identifier, as described herein. The logic of the small cell device may include performing other types of wireless service operations and/or procedures (e.g., maintenance activities, updating, handovers, reporting (e.g., network performance, congestion, etc.)) based on the global small cell device identifier, as described herein.

[0029] Additionally, for example, the logic of an intermediary network device may include generating and transmitting messages that include the global small cell device identifier, as

described herein. The logic of the intermediary network device may include routing traffic to a small cell device and core network devices based on the global small cell device identifier, as described herein. The logic of the intermediary network device may also consolidate the multiple interfaces of the set of small cell devices to a single interface and may improve link capacity, scalability, and various network operations, network procedures, and communications pertaining to small cell devices, as described herein.

[0030] Core network **120** may include one or multiple networks of one or multiple network types and technologies. Core network **120** may include a complementary network of access network **105**. For example, core network **120** may be implemented to include a 5G core network, an evolved packet core (EPC) of a Long Term Evolution (LTE) network, an LTE-Advanced (LTE-A) network, and/or an LTE-A Pro network, a future generation core network (e.g., a 5.5G, a 6G, a 7G, or another generation of core network), and/or another type of core network.

[0031] Depending on the implementation of core network **120**, core network **120** may include diverse types of network devices that are illustrated in FIG. **1** as core devices **122**. For example, core devices **122** may include a UPF, a Non-3GPP Interworking Function (N3IWF), AMF, a session management function (SMF), a unified data management (UDM) device, a unified data repository (UDR), an authentication server function (AUSF), a network slice selection function (NSSF), a network repository function (NRF), a policy control function (PCF), a binding support function (BSF), a network data analytics function (NWDAF), a network exposure function (NEF), a service capability exposure function (SCEF), a lifecycle management (LCM) device, an application function (AF), a mobility management entity (MME), a packet gateway (PGW), an enhanced packet data gateway (ePDG), a serving gateway (SGW), an application function (AF), a home agent (HA), a General Packet Radio Service (GPRS) support node (GGSN), a home subscriber server (HSS), an authentication, authorization, and accounting (AAA) server, a policy and charging rules function (PCRF), a policy and charging enforcement function (PCEF), a charging system (CS), and/or another type of network device that may be well-known but not particularly mentioned herein. Core devices **122** may also include a network device that provides a multi-RAT functionality (e.g., 4G and 5G, 5G and 5.5G, 5G and 6G, etc.), such as an SMF with PGW control plane functionality (e.g., SMF+PGW-C), a UPF with PGW user plane functionality (e.g., UPF+PGW-U), and/or other combined nodes (e.g., an HSS with a UDM and/or UDR, an MME with an AMF, etc.). Also, core devices **122** may include a split core device **122**. For example, core devices **122** may include a session management (SM) PCF, an access management (AM) PCF, a user equipment (UE) PCF, and/or another type of split architecture associated with another core device **122**, as described herein.

[0032] FIG. **2A** is a diagram illustrating an exemplary environment **200** in which an exemplary embodiment of an exemplary process of the small cell aggregation service may be implemented. As illustrated, environment **200** may include small cell device **202-1** through **202-X** (also collectively referred to as small cell devices **202** and generally or individually as small cell device **202**), an aggregator device **205**, a UPF **215** and an AMF **220**. Similar to that described in relation to FIG. **1** and environment **100**, the number, type, and arrangement of network devices illustrated in environment **200** are exemplary. Additionally, the number, type, and arrangement of communication links illustrated in environment **200** are exemplary.

[0033] For purposes of description, 5G reference point interfaces N2 and N3 are depicted. According to other exemplary embodiments, depending on the core network, non-5G interfaces and/or non-reference point interfaces may be implemented for control plane and user plane traffic between access network **107** and core network **120**.

[0034] Small cell device **202** may be implemented as a femtocell device, a picocell device, a microcell device, or another type of low-powered cellular radio access node. Small cell device **202** may be implemented in a 5G deployment, a legacy deployment (e.g., 4G, 4.5G), or a future generation deployment (e.g., 5.5G, 6G, etc.). According to various exemplary embodiments, small

cell device **202** may or may not differ among another small cell device **202** based on various features, such as coverage area, power, number of users supported, radio spectrum (e.g., radio frequency, radio band, etc.), and/or application (e.g., outdoor, indoor, rural, urban, remote area, etc.), for example.

[0035] According to an exemplary embodiment, small cell device **202** may provide a wireless service based on the global small cell device identifier, as described herein. For example, small cell device **202** may generate and transmit/receive user plane and control plane messages to/from UPF **215** and AMF **220** via aggregator device **205**. According to some exemplary embodiments, small cell device **202** may support multiple and different radio spectrum (e.g., carriers, frequency bands, radio beams, etc.). For example, a 5G wireless service may include certain categories of radio frequency bands, such as above 6 GHz and below 6 GHz, as well as other nomenclatures, such as sub-3 (e.g., below 3 GHz), mid-band (e.g., between 3 GHz and 6 GHz), low band, millimeter wave (mm Wave), above mm Wave, and so forth. According to some exemplary embodiments, small cell device **202** may provide wireless service to multiple and different coverage areas (e.g., sectors, sub-sectors, etc.) according to multiple and different radio spectrum that may be used by various types of end device (e.g., user equipment, mobile devices, Internet of Things (IoT) devices, and the like) (not illustrated). According to an exemplary embodiment, the global small cell device identifier may globally and uniquely identify each of such coverage areas.

[0036] Aggregator device **205** may be implemented as a gateway device or a concentrator device, for example. According to an exemplary embodiment, aggregator device **205** may include logic of an exemplary embodiment of the small cell aggregation service. For example, aggregator device **205** may aggregate and disaggregate both control plane and user plane traffic of the N2 and N3 interfaces based on the global small cell device identifier scheme, as described herein. According to some exemplary embodiments, aggregator device **205** may be an access device **107** that resides in access network **105**.

[0037] Referring to FIG. 2D, an exemplary embodiment of the global small cell device identifier structure **250** is illustrated. As illustrated, a small cell device global identifier **255** may include an aggregator identifier **260**, a small cell device identifier **265**, and a sub-cell identifier **270**. According to other exemplary embodiments, global small cell device identifier structure **250** may include fewer identifiers and/or additional identifiers. For example, small cell device global identifier **255** may omit sub-cell identifier **270**.

[0038] According to an exemplary embodiment, the number of bits of small cell device global identifier **255** may be the same as a radio access network (RAN) device global identifier (e.g., a global gNB ID or a NR cell identity (NCI)) of a standard (e.g., 3GPP, 3GPP2, etc.). According to other exemplary embodiments, the number of bits of small cell device global identifier **255** may be different (e.g., fewer bits, greater number of bits) from a RAN device global identifier of a standard. Consequently, the number of bits allocated to any sub-identifier included in small cell device global identifier **255** may vary among various exemplary embodiments.

[0039] For purposes of description, small cell device global identifier **255** will be described as 36 bits in length. However, according to other exemplary embodiments, small cell device global identifier **255** may include an additional number or a fewer number of bits. According to various exemplary embodiments and according to the exemplary 36 bit length, aggregator identifier **260** may be allocated between 22 bits through 32 bits. Aggregator identifier **260** may identify aggregator device **205**. Aggregator identifier **260** may be globally unique within a network (e.g., access network **105**, access network **105** and core network **120**, etc.).

[0040] Small cell device identifier **265** may be allocated a remainder portion of bits of the small cell device global identifier **255** or another portion of bits of the small cell global identifier **255** (e.g., when sub-cell identifier **270** may be implemented). For example, according to the 36 bit length example, small cell device identifier **265** may have a bit length between 4 bits through 14 bits. Small cell device identifier **265** may identify small cell device **202** among small cell devices

202 that are connected to aggregator device **205**. Small cell device identifier **265** may not be globally unique.

[0041] Sub-cell identifier **270** may be allocated any remaining number of bits in view of aggregator identifier **260** and small cell device identifier **265**. Sub-cell identifier **270** may indicate a portion of radio spectrum (e.g., a frequency band, a carrier, etc.) associated with small cell device **202**.

According to other examples, sub-cell identifier **270** may indicate a sub-coverage area (e.g., a sector, etc.) that is among multiple coverages area (e.g., sectors, etc.) of small cell device **202**.

Additionally, or alternatively, sub-cell identifier **270** may indicate an operator associated with small cell device **202**, which may differ among small cell devices **202** and/or may differ from an operator associated with aggregator device **205**. According to various exemplary embodiments, small cell device identifier **265** or the combination of small cell device identifier **265** and sub-cell identifier **270** may uniquely identify small cell device **202** or a frequency/band/sub-coverage area of small cell device **202** among the set of small cell devices **202** that are common to aggregator device **205**.

[0042] Referring back to FIG. 2A, the N2 and N3 reference point interfaces between aggregator device **205** and AMF **220** and UPF **215**, respectively, may provide a reduction in connections that would otherwise exist if not for aggregator device **205**. For example, assume that there are 1024 small cell devices **202**. Small cell device identifier **265** may identify **1024** different small cell devices **202**, and each of the N2 and N3 interfaces and connections between aggregator device **205** and AMF **220** and UPF **215** may provide a reduction of 1024:1.

[0043] UPF **215** and AMF **220** may each include logic that provides services according to a network standard (e.g., 3GPP, 3GPP2, etc.) and/or of a proprietary nature. For example, UPF **215** may function as an external PDU session point of interconnect to a data network, provide packet inspection, user plane part of policy rule enforcement, traffic usage reporting, QoS handling for user plane, transport level packet marking, among other functions. AMF **220** may provide registration, connection, reachability, and mobility management, security context management, location service management, UE mobility event notification, among other functions. According to an exemplary embodiment, UPF **215** and AMF **220** may include logic that provides UPF and AMF services, respectively, based on the small cell aggregation service and the small cell device global identifier scheme, as described herein.

[0044] FIG. 2A is a diagram illustrating an exemplary environment in which an exemplary process of the small cell aggregation service may be implemented. According to other exemplary embodiments, the exemplary environment may be different and/or the exemplary process may include additional, different, or fewer operations than those illustrated and described in relation to FIG. 2A.

[0045] FIG. 2B is a diagram illustrating another exemplary environment **225** in which an exemplary embodiment of an exemplary process of the small cell aggregation service may be implemented. Similar to that described in relation to FIG. 1 and environment **100**, the number, type, and arrangement of network devices illustrated in environment **225** are exemplary. Additionally, the number, type, and arrangement of communication links illustrated in environment **200** are exemplary.

[0046] Referring to FIG. 2B, in contrast to environment **200** of FIG. 2A, an aggregator device **230** may provide the small cell aggregation service in relation to control plane traffic but not user plane traffic for small cell devices **202**. Small cell device **202** and AMF **220** may operate according to the small cell aggregation service and associated small cell device global identifier scheme, as described herein.

[0047] FIG. 2B is a diagram illustrating an exemplary environment in which an exemplary process of the small cell aggregation service may be implemented. According to other exemplary embodiments, the exemplary environment may be different and/or the exemplary process may include additional, different, or fewer operations than those illustrated and described in relation to FIG. 2B.

[0048] FIG. 2C is a diagram illustrating yet another exemplary environment **240** in which an exemplary embodiment of an exemplary process of the small cell aggregation service may be implemented. Similar to that described in relation to FIG. 1 and environment **100**, the number, type, and arrangement of network devices illustrated in environment **240** are exemplary. Additionally, the number, type, and arrangement of communication links illustrated in environment **240** are exemplary.

[0049] Referring to FIG. 2C, in contrast to environments **200** and **225** of FIGS. 2A and 2B, respectively, an aggregator device **245** may provide the small cell aggregation service in relation to user plane traffic but not control plane traffic for small cell devices **202**. Small cell device **202** and UPF **215** may operate according to the small cell aggregation service and associated small cell device global identifier scheme, as described herein.

[0050] FIG. 2C is a diagram illustrating an exemplary environment in which an exemplary process of the small cell aggregation service may be implemented. According to other exemplary embodiments, the exemplary environment may be different and/or the exemplary process may include additional, different, or fewer operations than those illustrated and described in relation to FIG. 2C.

[0051] According to other exemplary embodiments, in relation to FIGS. 2A-2C, there may be multiple aggregator devices **205** connected to small cell devices **202**. For example, a primary aggregator device may connect to multiple secondary aggregator devices, which in turn may connect to different sets of small cell devices **202**. According to such an embodiment, small cell device global identifier **255** may include a globally unique identifier for the primary aggregator device and a globally unique identifier for the second aggregator device, along with various implementations of small cell device identifier **265** and sub-cell identifier **270**, as described herein.

[0052] FIG. 3 is a diagram illustrating exemplary components of a device **300** that may be included in one or more of the devices described herein. For example, device **300** may correspond to access device **107**, core device **122**, small cell device **202**, aggregator device **205**, UPF **215**, AMF **220**, aggregator device **230**, aggregator device **245**, and/or other types of devices, as described herein. As illustrated in FIG. 3, device **300** includes a bus **305**, a processor **310**, a memory/storage **315** that stores software **320**, a communication interface **325**, an input **330**, and an output **335**. According to other embodiments, device **300** may include fewer components, additional components, different components, and/or a different arrangement of components than those illustrated in FIG. 3 and described herein.

[0053] Bus **305** includes a path that permits communication among the components of device **300**. For example, bus **305** may include a system bus, an address bus, a data bus, and/or a control bus. Bus **305** may also include bus drivers, bus arbiters, bus interfaces, clocks, and so forth.

[0054] Processor **310** includes one or multiple processors, microprocessors, data processors, co-processors, graphics processing units (GPUs), application specific integrated circuits (ASICs), controllers, programmable logic devices, chipsets, field-programmable gate arrays (FPGAs), application specific instruction-set processors (ASIPs), system-on-chips (SoCs), central processing units (CPUs) (e.g., one or multiple cores), microcontrollers, neural processing unit (NPU), and/or some other type of component that interprets and/or executes instructions and/or data. Processor **310** may be implemented as hardware (e.g., a microprocessor, etc.), a combination of hardware and software (e.g., a SoC, an ASIC, etc.), may include one or multiple memories (e.g., cache, etc.), etc.

[0055] Processor **310** may control the overall operation, or a portion of operation(s) performed by device **300**. Processor **310** may perform one or multiple operations based on an operating system and/or various applications or computer programs (e.g., software **320**). Processor **310** may access instructions from memory/storage **315**, from other components of device **300**, and/or from a source external to device **300** (e.g., a network, another device, etc.). Processor **310** may perform an operation and/or a process based on various techniques including, for example, multithreading, parallel processing, pipelining, interleaving, learning, model-based, etc.

[0056] Memory/storage **315** includes one or multiple memories and/or one or multiple other types of storage mediums. For example, memory/storage **315** may include one or multiple types of memories, such as, a random access memory (RAM), a dynamic RAM (DRAM), a static RAM (SRAM), a cache, a read only memory (ROM), a programmable ROM (PROM), an erasable PROM (EPROM), an electrically EPROM (EEPROM), a single in-line memory module (SIMM), a dual in-line memory module (DIMM), a flash memory (e.g., 2D, 3D, NOR, NAND, etc.), a solid state memory, and/or some other type of memory. Memory/storage **315** may include a hard disk (e.g., a magnetic disk, an optical disk, a magneto-optic disk, a solid-state component, etc.), a Micro-Electromechanical System (MEMS)-based storage medium, and/or a nanotechnology-based storage medium.

[0057] Memory/storage **315** may be external to and/or removable from device **300**, such as, for example, a Universal Serial Bus (USB) memory stick, a dongle, a hard disk, mass storage, off-line storage, or some other type of storing medium. Memory/storage **315** may store data, software, and/or instructions related to the operation of device **300**.

[0058] Software **320** includes an application or a program that provides a function and/or a process. As an example, with reference to aggregator device **205**, software **320** may include an application that, when executed by processor **310**, provides a function and/or a process of the small cell aggregation service, as described herein. Additionally, with reference to small cell device **202**, software **320** may include an application that, when executed by processor **310**, provides a function and/or a process of the small cell aggregation service, as described herein. Software **320** may also include firmware, middleware, microcode, hardware description language (HDL), and/or other form of instruction. Software **320** may also be virtualized. Software **320** may further include an operating system (OS) (e.g., Windows, Linux, Android, proprietary, etc.).

[0059] Communication interface **325** permits device **300** to communicate with other devices, networks, systems, and/or the like. Communication interface **325** includes one or multiple wireless interfaces, optical interfaces, and/or wired interfaces. For example, communication interface **325** may include one or multiple transmitters and receivers, or transceivers. Communication interface **325** may operate according to a protocol stack and a communication standard.

[0060] Input **330** permits an input into device **300**. For example, input **330** may include a keyboard, a mouse, a display, a touchscreen, a touchless screen, a button, a switch, an input port, a joystick, speech recognition logic, and/or some other type of visual, auditory, tactile, affective, olfactory, etc., input component. Output **335** permits an output from device **300**. For example, output **335** may include a speaker, a display, a touchscreen, a touchless screen, a light, an output port, and/or some other type of visual, auditory, tactile, etc., output component.

[0061] As previously described, a network device may be implemented according to various computing architectures (e.g., in a cloud, etc.) and according to various network architectures (e.g., a virtualized function, PaaS, etc.). Device **300** may be implemented in the same manner. For example, device **300** may be instantiated, created, deleted, or some other operational state during its life-cycle (e.g., refreshed, paused, suspended, rebooting, or another type of state or status), using well-known virtualization technologies. For example, access device **107**, core device **122**, and/or aggregator device, as described herein, may be a virtualized device.

[0062] Device **300** may perform a process and/or a function, as described herein, in response to processor **310** executing software **320** stored by memory/storage **315**. By way of example, instructions may be read into memory/storage **315** from another memory/storage **315** (not shown) or read from another device (not shown) via communication interface **325**. The instructions stored by memory/storage **315** cause processor **310** to perform a function or a process described herein. Alternatively, for example, according to other implementations, device **300** performs a function or a process described herein based on the execution of hardware (processor **310**, etc.).

[0063] FIG. **4** is a flow diagram illustrating an exemplary process **400** of an exemplary embodiment of the small cell aggregation service. According to an exemplary embodiment, an

intermediary network device, such as aggregator device **205** may perform a step of process **400**. According to an exemplary implementation, processor **310** executes software **320** to perform the step of process **400**, as described herein.

[0064] In block **405**, aggregator device **205** may receive a message that includes a small cell device global identifier. The small cell device global identifier may include a globally unique identifier for aggregator device **205** and an identifier for small cell device **202** or small cell device **202** and a frequency/band/sub-coverage area of small cell device **202**, for example. The message may be received from a core device **122**, such as UPF **215**, AMF **220**, an application layer network device (e.g., a MEC server device or the like), or another network device that may communicate with small cell device **202** via core network **120**, for example.

[0065] In block **410**, aggregator device **205** may determine a network path based on the small cell device global identifier. For example, aggregator device **205** may store small cell device aggregation service data that may map or correlate communication links or interfaces (e.g., N2 and/or N3 interfaces), which are between aggregator device **205** and small cell devices **202**, with the small cell device global identifiers. Aggregator device **205** may compare the small cell device global identifier to the small cell device aggregation service data. Based on the result of the comparison, aggregator device **205** may select the network path that matches the correlated small cell device global identifier. In block **415**, aggregator device **205** may transmit the message to small cell device **202** based on the network path and associated small cell device global identifier.

[0066] As previously described, the message may be a user plane message, a control plane message, or another type of plane message (e.g., network management plane, etc.). For example, the control plane message may be a stream control transmission protocol (SCTP) message, a non-access stratum (NAS) message, a next generation application protocol (NGAP) message, or another type of protocol and/or message that may be transmitted via an N2 interface. According to another example, the user plane message may be an application service message or another type of message that may be transmitted via an N3 interface. The application service may relate to extreme real-time communications (e.g., tactile Internet, augmented reality (AR), virtual reality (VR), etc.), lifeline communications (e.g., natural disaster, emergency response, etc.), ultra-reliable communications (e.g., automated traffic control and driving, collaborative robots, health-related services (e.g., monitoring, remote surgery, etc.), drone delivery, public safety, etc.), broadcast-like services, communication services (e.g., email, text (e.g., Short Messaging Service (SMS), Multimedia Messaging Service (MMS), etc.), voice, conferencing, etc.), video streaming, and/or other types of wireless application services. The application service may be provided to an end device (e.g., UE, IoT device, mobile device, or the like) via small cell device **202**.

[0067] FIG. **4** illustrates an exemplary embodiment of a process of the small cell aggregation service, according to other exemplary embodiments, the small cell aggregation service may perform additional operations, fewer operations, and/or different operations than those illustrated and described. For example, according to an embodiment in which a hierarchical arrangement of aggregator devices is implemented (e.g., two or more), a highest tier or primary aggregator device may select the network path based on the small cell device global identifier, which may include global identifiers for each aggregator device connected (directly or indirectly) to small cell device **202**.

[0068] FIG. **5** is a flow diagram illustrating an exemplary process **500** of an exemplary embodiment of the small cell aggregation service. According to an exemplary embodiment, an intermediary network device, such as aggregator device **205** may perform a step of process **500**. According to an exemplary implementation, processor **310** executes software **320** to perform the step of process **500**, as described herein.

[0069] In block **505**, aggregator device **205** may receive a message that includes a small cell device global identifier. The small cell device global identifier may include a globally unique identifier for aggregator device **205** and an identifier for small cell device **202** or small cell device **202** and a

frequency/band/sub-coverage area of small cell device **202**, for example. The message may be received from small cell device **202**.

[0070] In block **510**, aggregator device **205** may determine a network path based on the small cell device global identifier. For example, aggregator device **205** may store small cell device aggregation service data that may map or correlate communication links or interfaces (e.g., N2 and/or N3 interfaces), which are between aggregator device **205** and core device(s) **122**, with the small cell device global identifiers. In block **515**, aggregator device **205** may transmit the message to core device **122** based on the network path and associated small cell device global identifier.

[0071] FIG. **5** illustrates an exemplary embodiment of a process of the small cell aggregation service, according to other exemplary embodiments, the small cell aggregation service may perform additional operations, fewer operations, and/or different operations than those illustrated and described. For example, according to an embodiment in which a hierarchical arrangement of aggregator devices is implemented (e.g., two or more), a lowest tier or a secondary aggregator device may select the network path based on the small cell device global identifier, which may include global identifiers for each aggregator device connected (directly or indirectly) to core device **122**.

[0072] As set forth in this description and illustrated by the drawings, reference is made to “an exemplary embodiment,” “exemplary embodiments,” “an embodiment,” “embodiments,” etc., which may include a particular feature, structure, or characteristic in connection with an embodiment(s). However, the use of the phrase or term “an embodiment,” “embodiments,” etc., in various places in the description does not necessarily refer to all embodiments described, nor does it necessarily refer to the same embodiment, nor are separate or alternative embodiments necessarily mutually exclusive of other embodiment(s). The same applies to the term “implementation,” “implementations,” etc.

[0073] The foregoing description of embodiments provides illustration but is not intended to be exhaustive or to limit the embodiments to the precise form disclosed. Accordingly, modifications to the embodiments described herein may be possible. For example, various modifications and changes may be made thereto, and additional embodiments may be implemented, without departing from the broader scope of the invention as set forth in the claims that follow. The description and drawings are accordingly to be regarded as illustrative rather than restrictive.

[0074] The terms “a,” “an,” and “the” are intended to be interpreted to include one or more items. Further, the phrase “based on” is intended to be interpreted as “based, at least in part, on,” unless explicitly stated otherwise. The term “and/or” is intended to be interpreted to include any and all combinations of one or more of the associated items. The word “exemplary” is used herein to mean “serving as an example.” Any embodiment or implementation described as “exemplary” is not necessarily to be construed as preferred or advantageous over other embodiments or implementations.

[0075] In addition, while series of blocks have been described regarding the processes illustrated in FIGS. **4** and **5**, the order of the blocks may be modified according to other embodiments. Further, non-dependent blocks may be performed in parallel. Additionally, other processes described in this description may be modified and/or non-dependent operations may be performed in parallel.

[0076] Embodiments described herein may be implemented in many different forms of software executed by hardware. For example, a process or a function may be implemented as “logic,” a “component,” or an “element.” The logic, the component, or the element, may include, for example, hardware (e.g., processor **310**, etc.), or a combination of hardware and software (e.g., software **320**).

[0077] Embodiments have been described without reference to the specific software code because the software code can be designed to implement the embodiments based on the description herein and commercially available software design environments and/or languages. For example, diverse types of programming languages including, for example, a compiled language, an interpreted

language, a declarative language, or a procedural language may be implemented.

[0078] Use of ordinal terms such as “first,” “second,” “third,” etc., in the claims to modify a claim element does not by itself connote any priority, precedence, or order of one claim element over another, the temporal order in which acts of a method are performed, the temporal order in which instructions executed by a device are performed, etc., but are used merely as labels to distinguish one claim element having a certain name from another element having a same name (but for use of the ordinal term) to distinguish the claim elements.

[0079] Additionally, embodiments described herein may be implemented as a non-transitory computer-readable storage medium that stores data and/or information, such as instructions, program code, a data structure, a program module, an application, a script, or other known or conventional form suitable for use in a computing environment. The program code, instructions, application, etc., is readable and executable by a processor (e.g., processor **310**) of a device. A non-transitory storage medium includes one or more of the storage mediums described in relation to memory/storage **315**. The non-transitory computer-readable storage medium may be implemented in a centralized, distributed, or logical division that may include a single physical memory device or multiple physical memory devices spread across one or multiple network devices.

[0080] To the extent the aforementioned embodiments collect, store, or employ personal information of individuals, it should be understood that such information shall be collected, stored, and used in accordance with all applicable laws concerning protection of personal information. Additionally, the collection, storage and use of such information can be subject to consent of the individual to such activity, for example, through well known “opt-in” or “opt-out” processes as can be appropriate for the situation and type of information. Collection, storage, and use of personal information can be in an appropriately secure manner reflective of the type of information, for example, through various encryption and anonymization techniques for particularly sensitive information.

[0081] No element, act, or instruction set forth in this description should be construed as critical or essential to the embodiments described herein unless explicitly indicated as such.

[0082] All structural and functional equivalents to the elements of the various aspects set forth in this disclosure that are known or later come to be known are expressly incorporated herein by reference and are intended to be encompassed by the claims.

Claims

1. A method comprising: receiving, by the network device, a message, wherein the network device is communicatively coupled to small cell devices of a first number via at least one of first control plane interfaces of the first number or first user plane interfaces of the first number, and further communicatively coupled to at least one of a first core network device via a single user plane interface or a second core network device via a single control plane interface; determining, by the network device, a network path for the message; and transmitting, by the network device based on the network path, the message to a destination of the message.
2. The method of claim 1, wherein the transmitting further comprises: transmitting, by the network device via one of the first control plane interfaces or one of the first user plane interfaces, the message to one of the small cell devices.
3. The method of claim 1, wherein the message includes a global identifier of one of the small cell devices.
4. The method of claim 1, wherein the first core network device is a user plane function (UPF) and the single user plane interface is an N3 interface, and wherein the second core network device is an access and mobility management function (AMF) and the single control plane interface is an N2 interface.
5. The method of claim 1, wherein the network device is communicatively coupled to the small cell

devices via the first user plane interfaces and the first control plane interfaces.

6. The method of claim 1, wherein the first control plane interfaces include N2 interfaces and the first user plane interfaces include N3 interfaces.

7. The method of claim 1, wherein the small cell device is one of a Fifth Generation (5G) femtocell device, a 5G picocell device, a 5G microcell device, or a home next generation Node B device.

8. The method of claim 1, wherein the network device includes an aggregator device or a gateway device of a radio access network.

9. A network device comprising: a processor configured to: receive a message, wherein the network device is communicatively coupled to small cell devices of a first number via at least one of first control plane interfaces of the first number or first user plane interfaces of the first number, and further communicatively coupled to at least one of a first core network device via a single user plane interface or a second core network device via a single control plane interface; determine a network path for the message; and transmit, based on the network path, the message to a destination of the message.

10. The network device of claim 9, wherein, when transmitting, the processor is further configured to: transmit via one of the first control plane interfaces or one of the first user plane interfaces, the message to one of the small cell devices.

11. The network device of claim 9, wherein the message includes a global identifier of one of the small cell devices.

12. The network device of claim 9, wherein the first core network device is a user plane function (UPF) and the single user plane interface is an N3 interface, and wherein the second core network device is an access and mobility management function (AMF) and the single control plane interface is an N2 interface.

13. The network device of claim 9, wherein the network device is communicatively coupled to the small cell devices via the first user plane interfaces and the first control plane interfaces.

14. The network device of claim 9, wherein the first control plane interfaces include N2 interfaces and the first user plane interfaces include N3 interfaces.

15. The network device of claim 9, wherein the small cell device is one of a Fifth Generation (5G) femtocell device, a 5G picocell device, a 5G microcell device, or a home next generation Node B device.

16. The network device of claim 9, wherein the network device includes an aggregator device or a gateway device of a radio access network.

17. A method comprising: receiving, by a femto gateway device, a message, wherein the femto gateway device is communicatively coupled to femtocell devices and further communicatively coupled to a Fifth Generation (5G) core network via a control plane interface; determining, by the femto gateway device, a network path for the message; and transmitting, by the femto gateway device based on the network path, the message to a destination of the message.

18. The method of claim 17, wherein the control plane interface includes an N2 interface.

19. The method of claim 17, wherein the femtocell devices include 5G femtocell devices.

20. The method of claim 17, wherein the message includes a global identifier of one of the femtocell devices.
