

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261813

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Conrad; Wayne Ernest

SURFACE CLEANING APPARATUS

Abstract

A surface cleaner has a pre-motor filter housing downstream from an air treatment chamber. In in operation to clean a surface, the pre-motor filter housing is configured to position a pre-motor filter media. A suction motor housing has a suction motor housing air inlet, wherein a plurality of ribs are provided at the suction motor housing air inlet, and, in operation, the ribs induce rotation of the air travelling to the suction motor.

Inventors: Conrad; Wayne Ernest (Hampton, CA)

Applicant: Omachron Intellectual Property Inc. (Hampton, CA)

Family ID: 1000008578313

Appl. No.: 19/200981

Filed: May 07, 2025

Related U.S. Application Data

parent US continuation 17670296 20220211 PENDING child US 19200981

parent US continuation 17150551 20210115 parent-grant-document US 11857140 child US 17670296

parent US continuation 13780428 20130228 ABANDONED child US 17150551

Publication Classification

Int. Cl.: A47L9/16 (20060101)

U.S. Cl.:

CPC A47L9/1608 (20130101); A47L9/165 (20130101); A47L9/1658 (20130101);
A47L9/1683 (20130101); A47L9/1666 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/670,296 filed on Feb. 11, 2022 which is allowed, which itself is a continuation of U.S. patent application Ser. No. 17/150,551 filed on Jan. 15, 2021 and issued as U.S. Pat. No. 11,857,140 on Dec. 13, 2023, which itself is a continuation of co-pending patent application Ser. No. 13/780,428, filed on Feb. 28, 2013, the entirety of which is herein incorporated by reference.

FIELD

[0002] This specification relates to cyclones having improved efficiency. In a preferred embodiment, a surface cleaning apparatus, such as a vacuum cleaner, is provided which utilizes one or more improved cyclones.

INTRODUCTION

[0003] The following is not an admission that anything discussed below is part of the prior art or part of the common general knowledge of a person skilled in the art.

[0004] Various types of surface cleaning apparatus are known. Typically, an upright vacuum cleaner includes an upper section, including an air treatment member such as one or more cyclones and/or filters, drivably mounted to a surface cleaning head. An up flow conduit is typically provided between the surface cleaning head and the upper section. In some such vacuum cleaners, a spine, casing or backbone extends between the surface cleaning head and the upper section for supporting the air treatment member. The suction motor may be provided in the upper section or in the surface cleaning head.

[0005] Currently, many vacuum cleaners utilize one or more cyclonic stages to remove particulate matter from an air stream. Typically, the cyclones which are utilized comprise a cyclone chamber defined by an upper wall which is planar, a lower wall which is planar and the side wall which is cylindrical. Typically, an air inlet is provided at one end and an air outlet is provided at the opposed end. Alternate cyclone designs have been disclosed. For example, U.S. Pat. No. 8,250,702 discloses a cyclone having an air inlet and an air outlet at one end and a dirt outlet at the opposed end. The opposed end with the dirt outlet has a rounded transition member extending between the end wall facing the air outlet and the side wall of the cyclone chamber.

SUMMARY

[0006] This summary is intended to introduce the reader to the more detailed description that follows and not to limit or define any claimed or as yet unclaimed invention. One or more inventions may reside in any combination or sub-combination of the elements or process steps disclosed in any part of this document including its claims and figures.

[0007] According to a broad aspect, a cyclone, such as may be used in a vacuum cleaner or other surface cleaning apparatus, is provided. Turbulence or eddy currents which develop in a cyclone chamber may reduce the efficiency of the cyclone chamber. For example, the eddy currents may result in mixing of different layers of air and accordingly, air which has had particulate matter removed therefrom could be mixed with air which still contains particulate matter. In addition, the back pressure created by the passage of air through a cyclone chamber may be increased by turbulence and eddy currents which are created in a cyclone chamber. The cleaning efficiency of a surface cleaning apparatus, such as a vacuum cleaner, depends upon the velocity of air flow at the air inlet. All other factors remaining the same, an increase in the rate of air flow at the dirty air inlet of a vacuum cleaner will increase the cleaning efficiency of the vacuum cleaner. Accordingly, reducing the back pressure through a cyclone chamber may increase the cleaning efficiency of a vacuum cleaner.

[0008] In one embodiment, a cyclone chamber is provided wherein the portion of the cyclone

chamber at the cyclone air inlet is configured to have a shape that is at least preferably proximate the shape of the air exiting the cyclone air inlet and entering the cyclone chamber. For example, the cyclone air inlet may be provided at a position where the sidewall of a cyclone chamber meets an end wall of the cyclone chamber. Typically, the sidewall and end wall of cyclone chambers meet at a 90° angle. In accordance with this embodiment, the juncture of the sidewall and the end wall are preferably configured to at least approximate a portion of the shape of the air inlet adjacent this juncture. For example, the juncture of the end wall and side wall of the cyclone chamber may be angled and, preferably, rounded and, most preferably, radiused so as to have the same shape as the outlet end of the cyclone chamber inlet. Accordingly, the air which travels through the cyclone air inlet into the cyclone chamber may maintain its same cross-sectional shape as it enters the cyclone chamber. The airstream may expand increasing its cross-sectional area as it travels through the cyclone chamber. However, the air will have a smoother transition to the cyclonic flow in the cyclone chamber than if the juncture of the sidewall and end walls is at a 90° angle. An advantage of this design is that the back pressure created by the cyclone chamber may be reduced and turbulence or eddy currents may be reduced or eliminated by smoothing the transition from the air inlet to the cyclone chamber at the air inlet end.

[0009] In some embodiments, the air inlet may be at the same end as the air outlet. In such a case, a vortex finder may extend inwardly into the cyclone chamber from the same end wall at which the cyclone air inlet is provided. In such a case, it is preferred that the vortex finder is positioned such that the air entering the cyclone chamber from the outlet end of the cyclone air inlet is spaced from the vortex finder. The distance between the sidewall and the vortex finder is preferably greater than the diameter of the outlet end of the cyclone air inlet. Accordingly, as air enters the cyclone chamber from the cyclone air inlet, it will be spaced from the vortex finder. In accordance with this embodiment, a portion of the end wall will extend from a position that is equivalent to the diameter of the outlet end of the air inlet and the vortex finder. This portion of the end wall may be of various configurations. For example, it may be rounded or angled. Preferably, this portion of the end wall is flat.

[0010] It will be appreciated by a person skilled in the art that the spacing of the vortex finder from the sidewall disclosed herein need not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0011] Alternately or in addition, the juncture of the sidewall of the vortex finder and the end wall of the cyclone chamber may also be rounded. An advantage of this design is that the back pressure through the cyclone chamber may be reduced. It will be appreciated that the juncture of the sidewall of the vortex finder and the end wall of the cyclone chamber may be angled, but is preferably rounded and, more preferably has a radius that is proximate the radius of the juncture of the sidewall and end wall at the cyclone air inlet. It will be appreciated by a person skilled in the art that any of the features of the rounding of the juncture of the vortex finder and the end wall of the cyclone chamber discussed herein need not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0012] In some embodiments, the air inlet and the air outlet of the cyclone chamber may be at the same end. An insert may be provided on the opposed wall of the cyclone chamber and extend into the cyclone chamber. For example, the insert may be aligned with the vortex finder but at the opposed wall. In such a case, the sidewall of the insert and the opposed end wall may meet at the juncture which is shaped similar to that of any of the junctures disclosed herein. For example, the juncture of the sidewall of the insert in the opposed end wall of the cyclone chamber may be angled and is preferably rounded and, more preferably, has a radius which is proximate to that of the radius of the juncture of the sidewall and the end wall at the air inlet. It will be appreciated by a person skilled in the art that any of the features of the shaping of the juncture of the sidewall and

the opposed end wall need not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0013] In another embodiment, a vacuum cleaner may have a pre-motor filter. A header may be provided upstream and/or downstream of the pre-motor filter. For example, the cyclone air outlet may extend to a header upstream of the pre-motor filter. The header enables the air exiting the air outlet to extend across the entire pre-motor filter upstream surface thereby allowing the entire pre-motor upstream surface to be used as a filtration mechanism. A header may be provided on the downstream side of the pre-motor filter. The header allows air to exit the pre-motor filter from all portions of the downstream side of the pre-motor filter and to be directed towards, e.g. as central outlet so as to convey the air to a suction motor inlet. The walls of the upstream and/or downstream header may be configured to reduce back pressure through such a pre-motor filter housing. For example, the juncture of the cyclone air outlet and the wall of the pre-motor filter header facing the upstream side of the pre-motor filter may be shaped similar to that of any of the junctures disclosed herein and may be angled or radiused. Alternately, or in addition, the juncture of the wall of the pre-motor filter header facing the upstream side of the pre-motor filter where it meets a sidewall of the pre-motor filter housing may be shaped similar to that of any of the junctures disclosed herein and may be angled or radiused. The wall of the header opposed to the upstream surface of the pre-motor filter may itself be continuously curved or angled as it extends outwardly to the sidewall of the filter housing and need not be parallel to the pre-motor filter. In a particularly preferred embodiment, the air outlet of the cyclone chamber may be trumpet shaped (e.g., flared) and accordingly the transition to the wall opposed to the upstream end of the pre-motor filter may be smooth (i.e., there may be no discontinuities). It will be appreciated that such a design may permit the air exiting the cyclone chamber to transition with less turbulence into the header thereby reducing the back pressure of the air travelling through the upstream header of a pre-motor filter.

[0014] Alternately, or in addition, the juncture of the downstream header air outlet and the wall of the pre-motor filter header facing the downstream side of the pre-motor filter may be shaped similar to that of any of the junctures disclosed herein and may be angled or radiused. Alternately, or in addition, the juncture of the wall of the pre-motor filter header facing the downstream side of the pre-motor filter where it meets a sidewall of the pre-motor filter housing may be shaped similar to that of any of the junctures disclosed herein and may be angled or radiused. The wall of the header opposed to the downstream surface of the pre-motor filter may itself be continuously curved or angled as it extends outwardly to the sidewall of the filter housing and need not be parallel to the pre-motor filter. In a particularly preferred embodiment, the air outlet of the downstream header may be trumpet shaped (e.g., flared) and accordingly the transition from the wall opposed to the downstream end of the pre-motor filter to the header outlet may be smooth (i.e., there may be no discontinuities). It will be appreciated that such a design may permit the air exiting the pre-motor filter to transition with less turbulence into the downstream header outlet thereby reducing the back pressure of the air travelling through the downstream header of a pre-motor filter.

[0015] It will be appreciated by a person skilled in the art that any of the features relating to the shaping of the upstream and/or downstream pre-motor filter header need not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0016] In accordance with another embodiment, the pre-motor filter may be supported on a plurality of ribs which are provided on the end wall of the downstream header facing the pre-motor filter. The ribs are preferably configured so as to impart a flow of air in the same direction as the direction of rotating fan blade of the suction motor. Accordingly, the ribs may be rounded and extend towards a center of the suction motor air inlet.

[0017] In a preferred embodiment, the suction motor inlet may be trumpet shaped (e.g. flared) and the ribs may extend along a portion of the trumpet shaped section of the air inlet to the suction

motor. In such a case, the upstream side of the ribs preferably is at the same height so as to provide a flat surface to support the pre-motor filter. Accordingly, the height of the ribs may increase as the ribs extend into the trumpet shaped portion of the suction motor inlet. It will be appreciated by a person skilled in the art that any of the features of the ribs of the suction motor inlet need not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0018] In accordance with another embodiment, the vortex finder may be provided with a screen. The screen may surround a portion of the sidewall of the vortex finder and extend further into the cyclone chamber further than the vortex finder. Alternately, the screen may be mounted on the innermost end of the vortex finder and extend further into the cyclone chamber. Preferably, the inner end of the screen (i.e. the end of the screen that is inner most of the cyclone chamber) has a diameter that is less than the diameter of the vortex finder and/or a diameter that is less than the diameter of the outlet end of the cyclone air inlet. The screen may be conical in shape and may extend from the innermost end of the screen to a position adjacent the sidewall of a vortex finder or it may abut the innermost end of the vortex finder. Alternately, the screen may be cylindrical or any other shape. Preferably, the outermost end of the screen (e.g. the screen adjacent the inlet end of the vortex finder) has a diameter approximate the diameter of the vortex finder. An advantage of this design is that the distance between the screen and the sidewall of the cyclone chamber is increased and provides additional room to allow the air travelling in the cyclone chamber to reverse direction and enter the vortex finder. The additional room reduces, for example, the likelihood of the treated air mixing with the air entering the cyclone chamber and transferring particulate matter from the air entering the cyclone chamber to the treated air.

[0019] It will be appreciated by a person skilled in the art that any of the features of the shaping of the screen discussed herein may not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0020] In accordance with another embodiment, the cyclone chamber may have a sidewall outlet. For example, a dirt collection chamber may be provided adjacent one side of or may surround all of the cyclone chamber. The dirt outlet may be provided at an upper end of the sidewall and comprise a gap between all or a portion of the sidewall and the end wall of the cyclone chamber and preferably a portion of the sidewall and the end wall of the cyclone chamber (e.g., a slot provided in the sidewall at the end wall of the cyclone chamber). The slot may be of various shapes. For example, the walls of the slot may be rounded and one end of the slot may be taller than the other, preferably the downstream side in the direction of rotation of air in a cyclone chamber.

[0021] Alternately, or in addition, a barrier wall may be provided spaced from the dirt outlet and accordingly extend between the dirt outlet and the sidewall of the dirt collection chamber facing the dirt outlet. The barrier wall may be parallel to the cyclone chamber wall or the downstream end of the barrier wall may be spaced further from the cyclone chamber wall than the upstream end of the barrier wall. The barrier wall may be affixed to an end wall of the dirt collection chamber, a sidewall of the dirt collection chamber and/or the sidewall of the cyclone chamber. If the barrier wall is connected to the sidewall of the cyclone chamber, the barrier wall is preferably connected to the sidewall of the dirt collection chamber upstream of the dirt outlet. The height of the barrier wall may be the same as the dirt outlet but it may be shorter or longer. In addition, the height may vary in the downstream direction.

[0022] It will be appreciated by a person skilled in the art that any of the features of the dirt outlet and/or barrier wall discussed here need not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0023] In another embodiment, the suction motor housing may have an inner wall which is scalloped. For example, the end wall of the motor housing facing the suction motor may be

scalloped. Alternately, the sidewall generally parallel to the cyclone motor axis may be scalloped. Preferably, the sidewall which is scalloped is opposed to a sidewall air outlet from the suction motor housing. An advantage of this design is that the scalloped shape reflects noise back towards the suction motor thereby reducing the sound of the suction motor of a vacuum cleaner. The reduction in noise can also result in a reduction in the back pressure through the vacuum cleaner, and, accordingly, an increase in the cleaning efficiency of the vacuum cleaner. It will be appreciated by a person skilled in the art that any of the features of the shaping of the suction motor housing discussed herein may not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0024] The vacuum cleaner which uses the cyclone and/or pre-motor filter housing and/or suction motor housing that is disclosed herein may be provided with a turbo brush. For example, this vacuum cleaner may have an above-floor cleaning wand and a turbo brush may be attachable thereto. Due to the reduced back pressure which may be achieved utilizing one of more of the features disclosed herein, a turbo brush may be used while still obtaining good cleaning efficiency. Accordingly, by reducing the back pressure through the cyclone chamber and/or pre-motor filter housing and/or motor housing, the saving in the reduction of the back pressure may be utilized to power or assist in powering a turbo brush thereby providing good cleaning efficiency while enabling a turbo brush to be utilized.

[0025] In accordance with another embodiment, the suction motor housing may incorporate a sound absorbing material or structure. For example, a sound absorbing material may be provided in the suction motor housing which is constructed from a plurality of different sound absorbing materials. For example, a sound absorbing sheet may be produced using small pieces of different sound absorbing material such as polyurethane, silicon and the like. Each material will typically absorb sound in a particular frequency range. The use of a combination of different materials will allow a single piece of sound absorbing material to absorb a greater frequency range of sounds. Further, the sheet may be made utilizing different sized pieces of the different materials. Alternately, or in addition, a sound shield may be provided which has a plurality of layers with different sized openings. For example, a plurality of screens having different sized openings may be spaced apart and may have foam provided therebetween. The different sized openings will restrict the transmission of sound therethrough in a different way. Preferably, the screens are made of one or more of a metallic material, glass or carbon fiber. The combination enables a vacuum cleaner to have a quieter sound by reducing the transmission of sound through the multiple layers without unduly impeding the flow of air therethrough. It will be appreciated by a person skilled in the art that any of the features of the sound absorbing material or shield disclose herein may not be utilized with the contouring of the juncture of the end wall and side wall at the cyclone air inlet, but may be used by itself, or in combination with any other feature disclosed herein.

[0026] In one embodiment, there is provided a cyclone comprising a cyclone chamber having an air inlet, an air outlet, a screen upstream of the air outlet, a longitudinal axis, a first end wall, a second end wall and a sidewall. The air inlet may have a cross sectional area in a plane transverse to a direction of airflow through the air inlet. The screen may have an inner end spaced longitudinally inwardly from the air outlet and may have a cross-sectional area transverse to the cyclone axis that is less than the cross sectional area of the air inlet.

[0027] In some embodiments, the cross sectional area of the inner end of the screen may be 60-90% the cross sectional area of the air inlet.

[0028] In some embodiments, the cross sectional area of the inner end of the screen may be 70-80% the cross sectional area of the air inlet.

[0029] In some embodiments, the screen may be tapered outwardly towards to air outlet.

[0030] In some embodiments, the screen may have an outer end at the air outlet and the air outlet may have a diameter proximate that of the outer end of the screen.

[0031] In some embodiments, the screen may have an outer end at the air outlet that is recessed radially inwardly of the air outlet.

[0032] In some embodiments, the air outlet may comprise a vortex finder. The air inlet and the vortex finder may be provided at the first end wall. The vortex finder may extend into the cyclone chamber a first distance and the air inlet may have an inner end that extends into the cyclone chamber a distance less than the first distance.

[0033] In some embodiments, the air outlet may comprise a vortex finder. The air inlet and the vortex finder may be provided at the first end wall and a portion of the first end wall may extend between the air inlet and the vortex finder and the portion may be flat.

[0034] In some embodiments, the air inlet may be provided at a first juncture of the sidewall and the first end wall. The first juncture downstream of the air inlet may be configured to at least approximate a portion of a shape of the air inlet that is adjacent the first juncture.

[0035] In some embodiments, the first juncture may extend at an angle to the walls between which it is positioned.

[0036] In some embodiments, at the first juncture may be rounded.

[0037] In some embodiments, the air outlet may comprise a vortex finder having an upstream end and a downstream end and the downstream end may be wider than the upstream end.

[0038] In some embodiments, the vortex finder may be flared in a downstream direction.

[0039] In one embodiment, there is provided a surface cleaning apparatus comprising the cyclone, an air flow path extending from a dirty air inlet to a clean air outlet and including a suction motor and the cyclone, a pre-motor filter having an outer perimeter and positioned in the air flow path between the cyclone and the suction motor and at least one of an upstream air plenum that is positioned upstream of the pre-motor filter and a downstream air plenum that is positioned downstream of the pre-motor filter. At least one of the upstream and the downstream air plenum may comprise an end wall spaced from the pre-motor filter and comprising a first portion having an air flow port and a second portion proximate the outer perimeter of the pre-motor filter. The first portion and the second portion may meet at a first juncture that extends at an angle to the first portion and the second portion.

[0040] In some embodiments, the first portion may extend generally laterally and may have an outer end and an inner end proximate the air flow port and the outer end may be closer to the pre-motor filter than the inner end.

[0041] In some embodiments, the first juncture may be rounded.

[0042] In some embodiments, the air outlet may comprise a vortex finder. The surface cleaning apparatus may comprise the upstream air plenum and the air flow port may comprise an air inlet port that is aligned with the vortex finder.

[0043] In some embodiments, the vortex finder may extend to the air inlet port.

[0044] In some embodiments, the vortex finder and the end wall may meet at a second juncture. The second juncture may extend at an angle to both the vortex finder and the end wall.

[0045] In some embodiments, the second juncture may be rounded.

[0046] It will be appreciated by a person skilled in the art that a surface cleaning apparatus may embody any one or more of the features contained herein and that the features may be used in any particular combination or sub-combination.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0047] The drawings included herewith are for illustrating various examples of articles, methods, and apparatuses of the teaching of the present specification and are not intended to limit the scope of what is taught in any way.

[0048] In the drawings:

[0049] FIG. **1** is a perspective view of a surface cleaning apparatus in a storage position;

[0050] FIG. **2** is a rear perspective view of the surface cleaning apparatus of FIG. **1**;

[0051] FIG. **3** is a perspective view of the surface cleaning apparatus of FIG. **1** in a floor cleaning position;

[0052] FIG. **4** is a cross sectional perspective view taken along line F4-F4 in FIG. **1**;

[0053] FIG. **5** is cross sectional view taken along line F5-F5 in FIG. **2**;

[0054] FIG. **6** is a perspective view of the surface cleaning apparatus of FIG. **1** in a cleaning configuration;

[0055] FIG. **7** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0056] FIG. **8** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0057] FIG. **9** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0058] FIG. **10** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0059] FIG. **11** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0060] FIG. **12** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0061] FIG. **13** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0062] FIG. **14** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0063] FIG. **15** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0064] FIG. **16** is a perspective view of the surface cleaning apparatus of FIG. **1** in another cleaning configuration;

[0065] FIG. **17** is a partially exploded perspective view of the surface cleaning apparatus of FIG. **1** wherein the cyclone bin assembly is removed for emptying;

[0066] FIG. **18** is a partially exploded perspective view of the surface cleaning apparatus of FIG. **1** wherein the cyclone bin assembly is removed for emptying and the pre-motor filers are removed for cleaning;

[0067] FIG. **19** is a perspective view of a cyclone bin assembly from the surface cleaning apparatus of FIG. **1**;

[0068] FIG. **20** is a sectional view of the cyclone bin assembly of FIG. **19**, taken along line F20-F20 in FIG. **19**;

[0069] FIG. **21** is a sectional view of the cyclone bin assembly of FIG. **19**, taken along line F21-F21 in FIG. **19**;

[0070] FIG. **22** is a sectional view of the cyclone bin assembly of FIG. **19**, taken along line F22-F22 in FIG. **19**;

[0071] FIG. **23** is a sectional view of the cyclone bin assembly of FIG. **19**, taken along line F23-F23 in FIG. **19**;

[0072] FIG. **24** is a perspective view of the cyclone bin assembly of FIG. **19** with the bottom door in an open position;

[0073] FIG. **25** is a cross sectional view of another embodiment of a cyclone bin assembly;

[0074] FIG. **26** is a cross sectional view of another embodiment of a cyclone bin assembly;

[0075] FIG. **27** is a cross sectional view of another embodiment of a cyclone bin assembly;

[0076] FIG. **28** is a cross sectional view of another embodiment of a cyclone bin assembly;

[0077] FIG. **29** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0078] FIG. **30** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0079] FIG. **31** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0080] FIG. **32** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0081] FIG. **33** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0082] FIG. **34** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0083] FIG. **35** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0084] FIG. **36** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0085] FIG. **37** is a cross sectional view of another embodiment of a cyclone bin assembly;
[0086] FIG. **38** is a schematic representation of another embodiment of a cyclone bin assembly;
[0087] FIG. **39** is a schematic representation of another embodiment of a cyclone bin assembly;
[0088] FIG. **40** is a schematic representation of another embodiment of a cyclone bin assembly;
[0089] FIG. **41** is a schematic representation of another embodiment of a cyclone bin assembly;
[0090] FIG. **42** is a schematic representation of another embodiment of a cyclone bin assembly;
[0091] FIG. **43** is a schematic representation of another embodiment of a cyclone bin assembly;
[0092] FIG. **44** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0093] FIG. **45** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0094] FIG. **46** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0095] FIG. **47** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0096] FIG. **48** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0097] FIG. **49** is an exploded perspective schematic representation of another embodiment of a cyclone bin assembly;
[0098] FIG. **50** is an exploded perspective schematic representation of another embodiment of a cyclone bin assembly;
[0099] FIG. **51** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0100] FIG. **52** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0101] FIG. **53** is a schematic representation of another embodiment of a cyclone bin assembly;
[0102] FIG. **54** is a schematic representation of another embodiment of a cyclone bin assembly;
[0103] FIG. **55** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0104] FIG. **56** is a perspective schematic representation of another embodiment of a cyclone bin assembly;
[0105] FIG. **57** is a schematic representation of a surface cleaning unit;
[0106] FIG. **58** is a schematic representation of another embodiment of a surface cleaning unit;
[0107] FIG. **59** is a modified version of the schematic representation of FIG. **59**;
[0108] FIG. **60** is a schematic representation of another embodiment of a surface cleaning unit;
[0109] FIG. **61** is a perspective view of a the top of the suction motor housing of the surface cleaning apparatus of FIG. **1**;
[0110] FIG. **62** is a top view of the top of the suction motor housing of the surface cleaning apparatus of FIG. **61**;
[0111] FIG. **63** is a perspective cut away of a suction motor housing of another embodiment of a surface cleaning apparatus;
[0112] FIG. **64** is a perspective cut away of a suction motor housing of another embodiment of a

surface cleaning apparatus;

[0113] FIG. **65** is a perspective cut away of a suction motor housing of another embodiment of a surface cleaning apparatus;

[0114] FIG. **66** is a perspective view of a suction motor housing of another embodiment of a surface cleaning apparatus;

[0115] FIG. **67** is a cross sectional view of the portion of the surface cleaning apparatus of FIG. **66**; and,

[0116] FIG. **68** is a schematic representation of an embodiment of a sound absorbing material.

DETAILED DESCRIPTION

[0117] Various apparatuses or processes will be described below to provide an example of an embodiment of each claimed invention. No embodiment described below limits any claimed invention and any claimed invention may cover processes or apparatuses that differ from those described below. The claimed inventions are not limited to apparatuses or processes having all of the features of any one apparatus or process described below or to features common to multiple or all of the apparatuses described below. It is possible that an apparatus or process described below is not an embodiment of any claimed invention. Any invention disclosed in an apparatus or process described below that is not claimed in this document may be the subject matter of another protective instrument, for example, a continuing patent application, and the applicants, inventors or owners do not intend to abandon, disclaim or dedicate to the public any such invention by its disclosure in this document.

General Description of an Upright Vacuum Cleaner

[0118] Referring to FIGS. **1-3**, a first embodiment of a surface cleaning apparatus **1** is shown. In the embodiment shown, the surface cleaning apparatus is an upright vacuum cleaner. In alternate embodiments, the surface cleaning apparatus may be another suitable type of surface cleaning apparatus, such as a canister type vacuum cleaner, and hand vacuum cleaner, a stick vac, a wet-dry type vacuum cleaner or a carpet extractor.

[0119] In the illustrated example, the surface cleaning apparatus **1** includes an upper portion or support structure **2** that is movably and drivingly connected to a surface cleaning head **3**. A surface cleaning unit **4** is mounted on the upper portion **2**. The surface cleaning apparatus **1** also has at least one dirty air inlet **5**, at least one clean air outlet **6**, and an air flow path or passage extending therebetween. In the illustrated example, the air flow path includes at least one flexible air flow conduit member (such as a hose **7** or other flexible conduit). Alternatively, the air flow path may be formed from rigid members.

[0120] At least one suction motor and at least one air treatment member are positioned in the air flow path to separate dirt and other debris from the airflow. The suction motor and the air treatment member may be provided in the upper portion and/or the surface cleaning head of an upright surface cleaning apparatus. Preferably, the suction motor and the air treatment member are provided in a removable surface cleaning unit. The air treatment member may be any suitable air treatment member, including, for example, one or more cyclones, filters, and bags, and preferably the at least one air treatment member is provided upstream from the suction motor. Preferably, as exemplified in FIG. **4**, the surface cleaning unit includes both the suction motor **8**, in a motor housing **12** and an air treatment member in form of a cyclone bin assembly **9**. The motor housing can include at least one removable or openable door **13** which may allow a user to access the interior of the motor housing **12**, for example to access the motor **8**, a filter or any other component within the housing **12**. The cyclone bin assembly **9** includes a cyclone chamber **10** and a dirt collection chamber **11**.

[0121] Optionally, the surface cleaning unit **4** may be a portable surface cleaning unit and may be detachable from the upper portion (FIG. **5**). In such embodiments, the surface cleaning unit **4** may be connected to the upper portion **2** by a mount apparatus **14** that allows the surface cleaning unit **4** to be detached from the upper section **2**. It will be appreciated that a portable surface cleaning unit

4 could be carried by a hand of a user, a shoulder strap or the like and could be in the form of a pod or other portable surface cleaning apparatus. All such surface cleaning apparatus are referred to herein as a hand carryable surface cleaning apparatus.

[0122] In the embodiment shown, the surface cleaning head **3** includes the dirty air inlet **5** in the form of a slot or opening **15** (FIG. **4**) formed in a generally downward facing surface of the surface cleaning head **3**. From the dirty air inlet **5**, the air flow path extends through the surface cleaning head **3**, and through an up flow conduit **16** (FIG. **2**) in the upper portion **2** to the surface cleaning unit **4**. In the illustrated example, the clean air outlet **6** is provided in the front of the surface cleaning unit **4**, and is configured to direct the clear air in a generally lateral direction, toward the front of the apparatus **1**.

[0123] A handle **17** is provided on the upper portion **2** to allow a user to manipulate the surface cleaning apparatus **1**. Referring to FIGS. **1** and **3**, the upper portion extends along an upper axis **18** and is moveably mounted to the surface cleaning head **3**. In the illustrated example, the upper portion **2** is pivotally mounted to the surface cleaning head via a pivot joint **19**. The pivot joint **19** may be any suitable pivot joint. In this embodiment, the upper portion **2** is movable, relative to the surface cleaning head **3**, between a storage position (FIG. **1**), and a use or floor cleaning position (FIG. **3**). In the floor cleaning position the upper portion **2** may be inclined relative to the surface being cleaned, and an angle **19** between a plane **20** parallel to the surface and the upper axis **18** may be between about 20 and about 85°.

[0124] Alternatively, or in addition to being pivotally coupled to the surface cleaning head, the upper portion may also be rotatably mounted to the surface cleaning head. In this configuration, the upper portion, and the surface cleaning unit supported thereon, may be rotatable about the upper axis. In this configuration, rotation of the upper portion about the upper axis may help steer the surface cleaning head across the floor (or other surface being cleaned). It will be appreciated that the forgoing discussion is exemplary and that an upright vacuum cleaner may use a surface cleaning head and upper portion of any design and they may be moveably connected together by any means known in the art.

Handle/Cleaning Wand Construction

[0125] In accordance with one aspect of the teachings described herein, which may be used in combination with any one or more other aspects, the air flow path between the surface cleaning head **3** and the surface cleaning unit **4** includes a bendable hollow conduit or wand member **100**, which may be used in combination with a flexible hose portion **7**. Preferably, the hose **7** is extensible and more preferably is elastically or resiliently extensible.

[0126] Referring to FIG. **2**, the wand member **100** includes an upper wand portion **101** and a lower wand portion **102**. The upper and lower wand portions **101**, **102** are connected to each other via a connection, e.g., a hinge **103** member, which allows relative movement between the upper and lower wand portions **102**, **103**. Optionally, the hinge member **103** can be configured to form part of the air flow path and to provide fluid communication between the upper and lower wand portions **101**, **102**, as well as provide a pivoting, mechanical linkage. For example, upper and lower wand portions **101**, **102** may be moveably connected to each other by providing a pivot joint that permits the upper and lower wand portions **101**, **102** to be connected in air flow communication or by each wand portion having projections that are pivotally connected to each other and with a flexible hose to provide the air flow communication between the wand portions. Alternatively, the air flow path can be external to the hinge. The handle **17** is provided toward the top of the upper portion **2** and is attached to the upper or downstream end of the upper wand portion **101**. In the illustrated embodiment, the handle **17** includes a hand grip portion **21** that is configured to be grasped by a user. The hinge member **103** can be locked in a straight configuration (FIG. **9**) and can be unlocked to allow the upper wand portion **101** to pivot relative to the lower wand member **102** (FIG. **10**).

[0127] In the illustrated example, the upper and lower wand portions **101**, **102** and the handle **17** are hollow tube-like conduit members that form part of the air flow path and can carry at least some

of the weight of the surface cleaning apparatus **4**. The wand **100** is also configured to transfer driving and steering forces between the handle **17** and the surface cleaning head **3**.

[0128] The upper and lower wand portions **101**, **102** may be made of any suitable material that can withstand the weight of the surface cleaning apparatus **4** and the driving and steering forces, including, for example, plastic, metal and the like. Optionally, upper and lower wand portions **101**, **102** may be formed from the same material. Alternatively, they may be formed from different materials.

[0129] Referring to FIG. **9** the distance **104** between the surface cleaning head **3** and the upper end of the handle **17** defines an upper portion height. Preferably, the upper portion height **104** can be selected so that the handle **17** is positioned so to be grasped by users of varying heights. The upper portion height **104** may be between, for example, about 35 inches and about 60 inches, and preferably is between about 40 inches and about 50 inches. In the illustrated example, the upper portion height **104** is between about 41 inches and about 45 inches.

[0130] The upper wand portion **101** defines an upper wand length **105** and the lower wand portion **102** defines a lower wand length **106**. The upper and lower wand lengths **105**, **106** may be the same, or may be different. Preferably, each of the upper and lower wand lengths **105**, **106** are between about 15% and about 80% of the upper portion height **104**. Altering the relative lengths of the upper and lower wand portions may change the position of the hinge **103** relative to the surface cleaning head **3**.

[0131] In one aspect of the teachings described herein, which may be used in combination with any one or more other aspects, the upright vacuum cleaner **1** may be operable in a variety different functional configurations or operating modes. The versatility of operating in different operating modes may be achieved by permitting the surface cleaning unit to be detachable from the upper portion. Alternatively, or in addition, further versatility may be achieved by permitting portions of the vacuum cleaner to be detachable from each other at a plurality of locations in the upper portion, and re-connectable to each other in a variety of combinations and configurations.

[0132] In the example illustrated, mounting the surface cleaning unit **4** on the upper portion **2** increases the weight of the upper portion **2** and can affect the maneuverability and ease of use of the surface cleaning apparatus. With the surface cleaning unit **4** attached, the vacuum cleaner **1** may be operated like a traditional upright style vacuum cleaner, as illustrated in FIGS. **1-3**.

[0133] Alternatively, in some cleaning situations the user may preferably detach the surface cleaning unit **4** from the upper portion **2** and choose to carry the surface cleaning unit **4** (e.g. by hand or by a strap) separately from the upper portion **2**, while still using the upper portion **2** to drivingly maneuver the surface cleaning head **3**. When the surface cleaning unit **4** is detached, a user may more easily maneuver the surface cleaning head **3** around or under obstacles, like furniture and stairs.

[0134] To enable the vacuum suction generated by the surface cleaning unit **4** to reach the surface cleaning head **3** when the surface cleaning unit **4** is detached from the support structure **2**, the airflow connection between the surface cleaning head **3** and the cleaning unit **4** is preferably at least partially formed by a flexible conduit, such as the flexible hose **7**. The use of a flexible conduit allows a user to detach the surface cleaning unit **4** and maintain a flow connection between the portable surface cleaning unit **4** and the surface cleaning head **3** without having to reconfigure or reconnect any portions of the airflow conduit **16** (FIG. **6**).

[0135] Referring to FIG. **6**, when the surface cleaning apparatus **1** is in use, a user may detach the surface cleaning unit **4** from the upper portion **2** without interrupting the airflow communication between the cleaning unit **4** and the surface cleaning head **3**. This allows a user to selectively detach and re-attach the cleaning unit **4** to the support structure **2** during use without having to stop and reconfigure the connecting hoses **7** or other portions of the airflow conduit **16**.

[0136] FIGS. **6**, **9** and **10** and illustrate a configuration in which the vacuum cleaner **1** can be operated with the surface cleaning unit **4** detached from the upper portion **2** and the air flow path

between the surface cleaning unit **4** and the surface cleaning head **3** remains intact. FIG. **9** shows the upper portion **2** in a straight configuration. FIG. **10** shows the upper portion **2** in an optional bent configuration. In both configurations, the surface cleaning head **3** is operable to clean the floor.

[0137] Alternatively, in some cleaning operations the user may wish to reconfigure portions of the air flow path to provide a surface cleaning apparatus with a desired configuration. For example, in another configuration, as exemplified in FIG. **8**, the wand portion of the upper section **2** is removed and the upstream end of the handle **17** is coupled directly to the surface cleaning head **3**. This configuration may be useful when cleaning stairs or other surfaces that are elevated. This is another example of a floor or surface cleaning operating mode.

[0138] In addition to being operable to clean floors or surfaces, the vacuum cleaner may be operated in a variety of cleaning modes that do not include use of the surface cleaning head, and may be generally described as above floor cleaning modes. This can generally include cleaning furniture, walls, drapes and other objects as opposed to cleaning a large, planar surface.

[0139] In one example of an above floor cleaning mode, as exemplified in FIG. **7**, the surface cleaning unit **4** can remain mounted on the upper portion **2**. This eliminates the need for the user to separately support the weight of the surface cleaning unit **4**. In the illustrated configuration, the upstream end of the handle **17** is separated from the downstream end of the upper wand portion **100**. In this configuration the upstream end **22** of the handle **17** can function as the dirty air inlet for the vacuum cleaner **1**. Optionally, accessory tools, such as wands, crevasse tools, turbo brushes, hoses or other devices may be coupled to the upstream end **22** of the handle **17**.

[0140] In another example of an above floor cleaning mode, as exemplified in FIG. **11**, the surface cleaning unit **4** can remain mounted on the upper portion **2** and the upper wand portion **101** can be detached from the hinge **103** to provide an extended wand for above floor cleaning. This configuration may help extend the reach of a user, as compared to the configuration of FIG. **7**. Optionally, additional accessory tools may be coupled to the upstream end **25** of the upper wand portion **101**, including for example a crevice tool (FIG. **15**), a cleaning brush **26** (optionally an electrically powered brush or an air driven turbo brush, see FIG. **14**) and any other type of accessory including a power tool such as a sander **27** (FIG. **16**).

[0141] In another example of an above floor cleaning mode, as exemplified in FIG. **12**, the surface cleaning unit **4** can be detached from the upper portion **2**, and substantially all of the upper portion **2** can be detached from the surface cleaning head **3**. In this configuration, both the upper and lower wand portions **101**, **102** co-operate to further extend the user's reach, as compared to the configurations of FIGS. **7** and **11**. Optionally, additional accessory tools may be coupled to the upstream end **28** of the upper portion **2**.

[0142] In another example of an above floor cleaning mode, as exemplified in FIG. **13**, the surface cleaning unit **4** can be detached from the upper portion **2** and the handle **17** can be detached from the upper portion **2**.

[0143] Optionally, one or more auxiliary support members, including for example a wheel and a roller, can be provided on the rear of the surface cleaning apparatus and/or the upper portion and configured to contact the floor (or other surface) when the upper portion is inclined or placed close to the surface (see FIG. **10**). Providing an auxiliary support member may help carry some of the weight of the surface cleaning unit and/or upper portion when in a generally horizontal configuration. The auxiliary support member may also help the upper portion **2** and/or surface cleaning unit **4** to roll relatively easily over the floor when in the horizontal position. This may help a user to more easily maneuver the upper portion and/or surface cleaning unit under obstacles, such as a bed, cabinet or other piece of furniture. In the illustrated embodiment the auxiliary support member is a roller **30** provided on the back side of the lower wand portion **102**.

Removable Cyclone

[0144] The following is a description of a removable cyclone that may be used by itself in any

surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0145] Optionally, the cyclone bin assembly **9** can be detachable from the motor housing **12**. Providing a detachable cyclone bin assembly **9** may allow a user to carry the cyclone bin assembly **9** to a garbage can for emptying, without needing to carry or move the rest of the surface cleaning apparatus **1**. Preferably, the cyclone bin assembly **9** can be separated from the motor housing **12** while the surface cleaning unit **4** is mounted on the upper portion **2** and also when the surface cleaning unit **4** is separated from the upper portion **2**. Referring to FIG. **17**, in the illustrated embodiment the cyclone bin assembly **9** is removable as a closed module, which may help prevent dirt and debris from spilling out of the cyclone bin assembly **9** during transport.

[0146] In the illustrated embodiment, removing the cyclone bin assembly **9** reveals a pre-motor filter chamber **31** that is positioned in the air flow path between the cyclone bin assembly **9** and the suction motor **8** (see also FIG. **4**). One or more filters can be provided in the pre-motor filter chamber **31** to filter the air exiting the cyclone bin assembly **9** before it reaches the motor **8**. In the illustrated example, the pre-motor filter includes a foam filter **32** and a downstream felt layer **33** positioned within the pre-motor filter chamber **31**. Preferably, the filters **32**, **33** are removable (FIG. **18**) to allow a user to clean and/or replace them when they are dirty. Optionally, part or all of the sidewalls **34** of the pre-motor filter chamber or housing **31** can be at least partially transparent so that a user can visually inspect the condition of the filters **32**, **33** without having to remove the cyclone bin assembly **9**.

[0147] Referring to FIG. **19**, the cyclone bin assembly **9** includes an outer sidewall **35** and a lid **36**. Preferably, as illustrated, a bin handle **37** is provided on the lid **36**. The bin handle **37** may allow a user to carry the surface cleaning unit **4** when it is detached from the upper portion **2**, and preferably is removable from the suction motor housing **12** with the cyclone bin assembly **9** so that it can also be used to carry the cyclone bin assembly for emptying.

[0148] Referring to FIGS. **20** and **21** in the illustrated embodiment the cyclone chamber **10** extends along a cyclone axis **38** and includes a first end wall **39**, a second end wall **40** axially spaced apart from the first end wall **39** and a generally cylindrical sidewall **41** extending between the first and second end walls **39**, **40**. Optionally, some or all of the cyclone walls can coincide with portions of the dirt collection chamber walls, suction motor housing walls and/or may form portions of the outer surface of surface cleaning unit. Alternatively, in some examples some or all of the cyclone walls can be distinct from other portions of the surface cleaning unit. In the illustrated embodiment, the cyclone chamber **10** is arranged in a generally vertical, inverted cyclone configuration.

Alternatively, the cyclone chamber can be provided in another configuration, including, having at least one or both of the air inlet and air outlet positioned toward the top of the cyclone chamber, or as a horizontal or inclined cyclone.

[0149] In the illustrated embodiment, the cyclone chamber **10** includes a cyclone air inlet **42** and a cyclone air outlet **43**. The cyclone chamber **10** preferably also includes at least one dirt outlet **44**, through which dirt and debris that is separated from the air flow can exit the cyclone chamber **10**. While it is preferred that most or all of the dirt exit the cyclone chamber via the dirt outlet, some dirt may settle on the bottom end wall **40** of the cyclone chamber **10** and/or may be carried with the air exiting the cyclone chamber via the air outlet **43**.

[0150] Preferably the cyclone air inlet **42** is located toward one end of the cyclone chamber **10** (the lower end in the example illustrated) and may be positioned adjacent the corresponding cyclone chamber end wall **40**. Alternatively, the cyclone air inlet **42** may be provided at another location within the cyclone chamber **10**.

[0151] Referring to FIG. **20**, in the illustrated embodiment the air inlet **42** includes an upstream or inlet end **45**, which may be coupled to the hose **7** or other suitable conduit, and a downstream end **46** (FIG. **22**) that is spaced apart from the upstream end **45**. In the illustrated configuration, the cyclone bin assembly **9** can be removed from the surface cleaning unit **4**, for example for cleaning

or emptying, while the hose 7 remains with the upper portion 2. This may allow a user to remove the cyclone bin assembly 9 without having to detach or decouple the hose 7. Alternatively, the downstream end of the hose 7 may be coupled to the cyclone bin assembly 9 such that the downstream end of the hose travels with the cyclone bin assembly when it is removed.

[0152] The air inlet 42 defines an inlet axis 47 and has an inlet diameter 48 (FIG. 21). The cross-sectional area of the air inlet 42 taken in a plane orthogonal to the inlet axis 47 can be referred to as the cross-sectional area or flow area of the air inlet 42. Preferably, the air inlet 42 is positioned so that air flowing out of the downstream end is travelling generally tangentially relative to, and preferably adjacent, the sidewall 41 of the cyclone chamber 10.

[0153] The perimeter of the air inlet 42 defines a cross-sectional shape of the air inlet. The cross-sectional shape of the air inlet can be any suitable shape. In the illustrated example the air inlet has a generally round or circular cross-sectional shape with a diameter 48. Optionally, the diameter 48 may be between about 0.25 inches and about 5 inches or more, preferably between about 1 inch and about 5 inches, more preferably is between about 0.75 and 2 inches or between about 1.5 inches and about 3 inches, and most preferably is about 2 to 2.5 inches or between about 1 to 1.5 inches. Alternatively, instead of being circular, the cross-sectional shape of the air inlet may be another shape, including, for example, oval, square and rectangle.

[0154] Air can exit the cyclone chamber 10 via the air outlet 43. Optionally, the cyclone air outlet may be positioned in one of the cyclone chamber end walls and, in the example illustrated, is positioned in the same end as the air inlet 42 and air inlet 42 may be positioned adjacent or at the end wall 40. In the illustrated example, the cyclone air outlet 43 comprises a vortex finder 49. In the example illustrated, the longitudinal cyclone axis 38 is aligned with the orientation of the vortex finder. Alternatively, the cyclone air outlet 43 may be spaced apart from the cyclone air inlet 42, and may be located toward the other end of the cyclone chamber 10.

[0155] In the illustrated embodiment the air outlet 43 is generally circular in cross-sectional shape and defines an air outlet diameter 51 (FIG. 21). Optionally, the cross-sectional or flow area of the cyclone air outlet 43 may be between about 50% and about 150% and between about 60%-90% and about 70%-80% of the cross-sectional area of the cyclone air inlet 42, and preferable is generally equal to the cyclone air inlet area. In this configuration, the air outlet diameter 51 may be about the same as the air inlet diameter 48.

[0156] When combined with any other embodiment, the cyclone bin assembly 9 may be of any particular design and may use any number of cyclone chambers and dirt collection chambers. The following is a description of exemplified features of a cyclone bin assembly any of which may be used either individually or in any combination or sub-combination with any other feature disclosed herein.

Screen

[0157] The following is a description of a cyclone and a screen that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0158] Optionally, a screen or other type of filter member may be provided on the cyclone air outlet 43 to help prevent fluff, lint and other debris from exiting via the air outlet. Referring to FIG. 21, in the illustrated example a screen 50 is positioned at the air outlet 43 and connected to the vortex finder 49. In FIG. 21 the screen is illustrated with mesh in place, however for clarity the mesh has been omitted from the other Figures. The screen 50 is generally cylindrical in the illustrated embodiment, but may be of any suitable shape in other embodiments. Optionally, the screen 50 can be removable from the vortex finder 49.

[0159] Optionally, the screen 50 may be sized to have a cross-section area that is larger than, smaller than or generally equal to the air outlet 43 cross-sectional area. Referring to FIG. 23, in the illustrated example, the diameter 52 of the screen 43 is less than the diameter 51 of the vortex finder 49 conduit providing the cyclone air outlet 43. In this configuration, the radial surface 53 of

the screen **50** is radially offset inwardly from the surface **54** of the vortex finder **49** by an offset distance **55**. Providing the offset gap **55** between the surfaces **53**, **54** of the screen **50** and vortex finder **49** may help provide a relatively calmer region (i.e. a region of reduced air flow turbulence and/or laminar air flow) within the cyclone chamber **10**. It may also assist the air that has been treated in the cyclone chamber to travel towards the vortex finder while mixing less with the air entering the cyclone chamber via the air inlet and thereby reduce the likelihood of dirt bypassing treatment in the cyclone chamber and travelling directly to the air outlet. Providing a relatively calmer air flow region adjacent the surface **53** of the screen **50** may help enable air to more easily flow through the screen **50** and into the vortex finder **49**, which may help reduce backpressure in the air flow path. Reducing back pressure may help improve the efficiency of the cyclone chamber and/or may help reduce power requirements for generating and/or maintaining a desired level of suction.

[0160] In the illustrated embodiment the screen **50** is of generally constant diameter. Alternatively, the diameter of the screen **50** may vary along its length. For example, the screen may be generally tapered and may narrow toward its upper end (i.e. the end that is spaced apart from the vortex finder **49**). The cross sectional area of the inner end of the screen may be 60-90% the cross sectional area of the air inlet and preferably is 70-80% the cross sectional area of the air inlet.

[0161] Referring to FIG. **25**, another embodiment of a cyclone bin assembly **1009** is shown. Cyclone bin assembly **1009** is similar to cyclone bin assembly **9**, and analogous elements are identified using like reference characters indexed by 1000. In this embodiment, the screen **1050** is tapered such that the width **1052** at the base of the screen **1050** (adjacent the vortex finder **1049**) is greater than the width **1052a** at the upper end of the screen **1050**. In this configuration the cross-sectional area of the screen **1050** (in a plane that is generally perpendicular to the screen **50**) is greater at the base of the screen **1050** than at its upper end. The amount of taper on the screen **1050** may any suitable amount, and for example may be selected so that the cross-sectional area at the upper end of the screen **1050** is between about 60% and 90%, between about 70% and 80% and may be about 63%-67% of the cross-sectional area of the base of the screen **1050**.

Dirt Outlet

[0162] The following is a description of a cyclone dirt outlet that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0163] Cyclone chamber **10** may be in communication with a dirt collection chamber by any suitable means. Preferably, as exemplified, the dirt collection chamber **11** is exterior to cyclone chamber **10**, and preferably has a sidewall **56** that at least partially or completely laterally surrounds the cyclone chamber **10**. At least partially nesting the cyclone chamber **10** within the dirt collection chamber **11** may help reduce the overall size of the cyclone bin assembly. As exemplified in FIG. **20**, the cyclone chamber sidewall **41** may be coincident with the sidewall **56** at one or more (e.g., three locations) around its perimeter.

[0164] In the illustrated embodiment, the dirt outlet **44** is in communication the cyclone chamber **10** and the dirt collection chamber **11**. Optionally, the dirt outlet **44** can be axially and/or angularly spaced from the cyclone air inlet. Preferably, the cyclone dirt outlet **44** is positioned toward the opposite end of the cyclone chamber **10** from the cyclone air inlet **42**. The cyclone dirt outlet **44** may be any type of opening and may be in communication with the dirt collection chamber to allow dirt and debris to exit the cyclone chamber **10** and enter the dirt collection chamber **11**.

[0165] In the illustrated example, the cyclone dirt outlet **44** is in the form of a slot bounded by the cyclone side wall **41** and the upper cyclone end wall **39**, and is located toward the upper end of the cyclone chamber **10**. Alternatively, in other embodiments, the dirt outlet may be of any other suitable configuration, and may be provided at another location in the cyclone chamber, including, for example as an annular gap between the sidewall and an end wall of the cyclone chamber or an arrestor plate or other suitable member.

[0166] Referring to FIG. 21, the dirt slot **44** may be of any suitable length **57**, generally measured in the axial direction, and may be between about 0.1 inches and about 2 inches, or more. Optionally, the length **57** of the slot **44** may be constant along its width, or alternatively the length **57** may vary along the width of the slot **44**, preferably in the downstream direction as measured by the direction of air rotation in the cyclone chamber.

[0167] Optionally, the slot may extend around the entire perimeter of the cyclone chamber (forming a generally continuous annular gap) or may extend around only a portion of the cyclone chamber perimeter. For example, the slot may subtend an angle (see angle **58** in FIG. 20) that is between about 30° and about 360°, and may be between about 30 and about 180°, between about 45 and about 90° and between about 60 and 80°. Similarly, the slot **44** may extend around about 10% to about 80% of the cyclone chamber perimeter, and preferably may extend around about 15% to about 40% of the cyclone chamber perimeter.

[0168] Optionally, the slot **44** may be positioned so that it is angularly aligned with the cyclone air inlet **42**, or so that an angle **60** (FIG. 20) between the air inlet and the slot **44** (measured to a center line of the slot **44**) is between about 0 and about 350° or more, and may be between about 90° and about 180°. In some embodiments, the slot **44** can be positioned so that an upstream end of the slot (i.e. the end of the slot that is upstream relative to the direction of the air circulating within the cyclone chamber) is between about 0° and about 350° from the air inlet, and may be between about 5° and 180° and between about 10° and about 50° downstream from the air inlet.

[0169] Referring to FIGS. 38-43, schematic representations of alternate embodiments of a cyclone chamber and a dirt collection chamber are shown. Each embodiment is generally similar to the cyclone chamber **10** and dirt collection chamber **11**, and analogous elements are identified using like reference characters with a unique suffix (a, b, c, etc.). Each of the schematic embodiments illustrates one example of a possible angular arrangement between the air inlet **42**, dirt outlet slot **44** (represented by angle **60**) and dirt outlet slots **44** of varying widths, represented by different angles **58**. For clarity, in these Figures portions of the air inlet **42** and the dirt outlet slot **44** are identified by cross-hatching.

[0170] Referring to FIG. 38, in this embodiment the angle **60a** between the slot **44a** and the air inlet **42a** is about 45 degrees, and the dirt slot **44a** subtends an angle **58a** of about 60 degrees. In this configuration, the dirt slot **44a** is 45 degrees downstream from the air inlet **42a** and is located in a first quadrant of the cyclone chamber sidewall (i.e. in a quadrant where the angle **60** is between about 0 degrees and about 90 degrees).

[0171] Referring to FIG. 39, in this embodiment the angle **60b** between the slot outlet **44b** and the air inlet **42a** is about 0 degrees. That is, the centre line of the slot **44b** is generally aligned with the tangential edge of the air inlet **42b**. In this configuration, a portion of the dirt slot **44b** (located at one end of the cyclone chamber **10b**) may overlap a portion of the air inlet **42b** (located at the other end of the cyclone chamber **10b**). In this embodiment, the angle **58b** swept by the dirt slot **44b** is about 35 degrees. Also in this embodiment, portions of the cyclone chamber sidewall **41b** are integral with portions of the dirt collection chamber sidewall **56b**, and the air inlet **42a** is at an angle relative to the dirt collection chamber sidewall **56b**. Referring to FIG. 40, this embodiment is similar to the embodiment of FIG. 39, but is configured so that air will circulate in the opposite direction. In both embodiments, the dirt slot partially overlaps the air inlet.

[0172] Referring to FIG. 41, in this embodiment the dirt slot **44d** is located in a third quadrant of the cyclone chamber, where the angle **60d** is greater than 180 degrees. As illustrated, the angle **60d** is about 130 degrees. In this embodiment the dirt slot **44d** covers an angle **58d** of about 80 degrees.

[0173] Referring to FIG. 42, in this embodiment the dirt slot **44e** is about 125 degrees downstream from the air inlet **42e** (i.e. the angle **60e** is about 125 degrees), and sweeps an angle **58e** of about 70 degrees. In this embodiment the upstream end of the dirt slot **44e** is located at the intersection of the cyclone chamber sidewall **41e** and the dirt collection chamber sidewall **56e**.

[0174] Referring to FIG. 43, in this embodiment the dirt slot **44f** overlies substantially all of the air

inlet **42f** and the angle **60f** (measured in the direction of air flow) is about 325 degrees (i.e. the dirt slot **44f** is located about 45 degrees upstream from the air outlet **42f**). In this configuration, the downstream end of the dirt slot **44f** is located at the intersection between the cyclone chamber sidewall **41f** and the dirt collection chamber sidewall **56f**.

[0175] The dirt collection chamber **11** may be of any suitable configuration. Referring to FIG. **21**, in the illustrated example, the dirt collection chamber **11** includes a first end wall **61**, a second end wall **62** and the sidewall **56** extending therebetween.

[0176] To help facilitate emptying the dirt collection chamber **11**, at least one of or both of the end walls **61**, **62** may be openable. Similarly, one or both of the cyclone chamber end walls **39** and **40** may be openable to allow a user to empty debris from the cyclone chamber. Referring to FIGS. **21** and **24**, in the illustrated example, the upper dirt chamber end wall **61** is integral with the upper cyclone end wall **39** and the lower dirt collection chamber end wall **62** is integral with, and openable with, the lower cyclone chamber end wall **40** and both form part of the openable bottom door **63**. The door **63** is moveable between a closed position (FIG. **21**) and an open position (FIG. **24**). When the door **63** is open, both the cyclone chamber **10** and the dirt collection chamber can be emptied concurrently. Alternatively, the end walls of the dirt collection chamber **11** and the cyclone chamber **10** need not be integral with each other, and the dirt collection chamber **11** may be openable independently of the cyclone chamber **10**.

Cyclone with Curved or Angled Surfaces

[0177] The following is a description of a cyclone construction that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0178] Referring to FIG. **21**, in the illustrated embodiment, the upper end wall **39** closes the upper end of the sidewall **41**. In the illustrated example, the intersection or juncture **64** between the end wall **39** and the side wall **41** is a relatively sharp corner that does not include any type of angled or radiused surface. In contrast, the lower end wall **40** preferably meets the lower end of the cyclone sidewall **41** at a juncture **65** that may comprise an angled or a curved juncture surface **66** (see also FIG. **22**). The radius **67** of the curved surface **66** may be selected based on the radius of the air inlet **42** (e.g. half of the diameter **48**), and optionally may be selected so that the juncture surface **66** has the same radius as the air inlet **42**.

[0179] Optionally, the curved juncture surface **66** can be formed as a portion of the sidewall **41** or as a portion of the end wall **40**. In the illustrated embodiment, the curved juncture surface **66** is provided as part of an insert member **68** (FIG. **24**) that is provided on the bottom end wall **40** and extends upward into the interior of the cyclone chamber **10**.

[0180] Alternately, or in addition, the juncture between the vortex finder **49** and the end wall **40** may also be provided with an angled or curved surface. In the illustrated embodiment, the juncture **70** between the end wall **40** and the vortex finder **49** may also include a curved surface **72**. The curved surface **72** can be sized to have a radius **71** that is the same as the radius **67** of the juncture **66** between the end wall **40** and the sidewall **41**. Providing curved surfaces **66**, **72** at one or both of the junctures **65**, **70** may help reduce backpressure and may help improve cyclone efficiency. In the illustrated embodiment, the radii **65** and **70** are equal to the radius of the air inlet **42**. Alternatively, the radii **65** and **70** may be different.

[0181] In the illustrated example, member **68** provides the juncture surface **72**. Optionally, the curved juncture surfaces within the cyclone chamber **10** (e.g., member **68**) may be removable from the cyclone chamber **10** when the cyclone chamber is opened. In the illustrated embodiment, the member **68** is provided on the movable door **63**, and is removed from the cyclone chamber **10** when the door **63** is opened. The vortex finder **49** and screen **50** are also mounted to the door **63** and are removed from the cyclone chamber **10** when the door opens. Removing some or all of the curved juncture surfaces **66**, **72** from the cyclone chamber **10** when the door **63** is opened for emptying may help ensure dirt and debris can fall out of the cyclone chamber without settling on or

otherwise becoming hung-up on the juncture surfaces **66**, **72**. Alternatively, the juncture surfaces may be formed as part of the sidewall **41**, or otherwise fixed within the cyclone chamber **10** such that the juncture surfaces are not removable from the cyclone chamber **10** and do not move with the door **63**. A further advantage is that member **68** may abut the inner surface of the sidewall of the cyclone chamber and the lower edge of the sidewall may engage a gasket or other sealing member provided in a recess on the door **63**. Such a construction provides an enhanced seal when a curved openable door is provided.

[0182] Optionally, the juncture surfaces **66** and **72** may be positioned such that they abut each other to form a generally continuous curved or angled surface (or a combination of a curved surface and an angled or inclined surface). If the radii of curvature of the surfaces **66** and **72** are equal, the surfaces **66** and **72** may co-operate to form a surface with a generally consistent curvature (e.g., a half toroid shape) that may approximate the shape and curvature of the air inlet **42**. Matching the curvature of the juncture surfaces **66** and **72** to the curvature to the air inlet **42** may help improve cyclone performance. Alternatively, the curvature of the junctures **66** and **72** need not match the curvature of the air inlet **42**.

[0183] Alternatively, the juncture surfaces **66** and **72** may be radially spaced apart from each other such that they do not connect directly to each other. In such embodiments, a transition or bridge region may be defined between the juncture surfaces **66**, **72**. Referring to FIG. **24**, in the illustrated embodiment the juncture surfaces **66** and **72** are radially separated from each other by a bridge surface **73** that has radial width **74** (FIG. **21**). The width **74** may be any suitable width, including, for example, between and 3% and about 15% or more of the diameter **48** of the air inlet **42**. Optionally, the width **74** may be greater than 0.5%, such as between about 0.5-12%, 3%-12%, 3%-7% and 3%-5% of the diameter **48**. In this configuration, the juncture surfaces **66** and **72** are separate from each other, and from bridge surface **73**.

[0184] Optionally, in addition to (or as an alternative to) the member **68** on the bottom wall **40**, an additional insert member may be provided within the cyclone chamber **10**, and may be located toward the upper end wall **39**. In the illustrated embodiment, an upper insert member **76** is provided at the upper end of the cyclone chamber **10**. The insert member **76** includes a downwardly extending central wall or projection member **77** that extends into the interior of the cyclone chamber **10** and may optionally engage the distal end **78** of the screen **50** (FIG. **21**). Together, the vortex finder **49**, screen **50** and projection member **77** may form a generally continuous internal column member that extends between the first and second end walls **39** and **40** of the cyclone chamber. Providing the projection member **77** may help direct air flow within the cyclone chamber, and may help support and/or stabilize the distal end **78** of the screen **50**.

[0185] Optionally, the juncture **79** between the end wall **39** and the projection member **77** may include a curved juncture surface **80** (see FIGS. **21** and **22**). The surface **80** is curved and defines a radius **81**. The radius **81** may be any suitable radius, and in the illustrated embodiment is the same as radii **66** and **72**. Providing curved surfaces **80** at the junctures between the end wall **39** and the projection member **77**, may help reduce backpressure and may help improve cyclone efficiency. Optionally, in some embodiments the juncture **64** may also include an angled or curved surface.

[0186] In the illustrated embodiment, the bottom of the air inlet **42** is generally aligned with the surface of the member **68**, such that the air inlet **42** is positioned at the bottom of the cyclone chamber **10**.

[0187] The radial distance **81** (FIG. **21**) between the cyclone chamber sidewall **41** and the surface **54** of the vortex finder **49**, which form an upstanding wall portion of the member **68**, may be any suitable distance. Preferably, the distance **81** is greater than the air inlet width **48** such that the vortex finder **49** is radially offset from the edge of the air inlet **42** by an offset distance **82**. The offset distance **82** may be any suitable distance, and may, for example, be between about 0% and about 100% or more of the air inlet width **48**, between about 2% and about 25% of the width **48**, between about 5% and about 15% of the width **48** and may be about 10% of the width **48**. Altering

the distance **81** may affect the efficiency and performance of the cyclone.

[0188] In the illustrated embodiment, the air inlet **42** is positioned at the juncture **65** between the sidewall **41** and the end wall **40** and is positioned such that the air inlet **42** is adjacent the sidewall **41** (i.e., there is no radial gap between the outer edge of the air inlet **42** and the sidewall **41**). Alternatively, the air inlet **42** may be spaced radially inwardly from the sidewall **41** such that a gap is provided between the edge of the air inlet **42** and the sidewall **41**.

[0189] It will be appreciated that if the air outlet is provided in wall **39**, then insert member **76** may be configured as vortex finder **49** and vortex finder **49** may be configured as insert member **76**.

[0190] In the embodiment FIG. **25**, the juncture **1065** between the sidewall **1041** and the bottom wall **1040** is not rounded, but instead includes an angled surface **1066**. The angle of the surface **1066** is selected so that the juncture surface **1066** is generally tangential to the air inlet **1042**. In the illustrated example, the surface **1066** extends generally continuously from the sidewall **1041** to the bridge surface **1073**. In this example the juncture surface **1072** is rounded, as described in detail above.

[0191] The air inlet and the vortex finder are preferably sized such that the top (upper inward extent) of the air inlet is below the innermost end of the vortex finder. For example, in the illustrated embodiment, the bottom of the air inlet **1042** is adjacent the bottom wall **1040** and the top of the air inlet **1042** is spaced apart from the bottom wall by a height **1094**, which in the illustrated configuration is equal to the diameter **1048**. The vortex finder **1049** also extends away from the bottom wall **1040** and has a height **1096** measured in the axial direction. In this embodiment, the height **1096** is greater than the height **1095** and the upper end of the vortex finder **1049** is offset above the top of the air inlet **1042** by a distance **1097**. The distance **1097** can be any suitable distance, and may be, for example, between 0% and about 25% or more of the air inlet diameter **1048** (e.g., between about 0.05-1 inches, preferably between about 0.1-0.5 inches and more preferably about 0.25 inches). Alternatively, the top of the air inlet **1042** can be flush with, or extend above the top of the vortex finder **1049**.

[0192] Referring to FIGS. **26-37**, additional embodiments of a cyclone bin assembly are illustrated. Each embodiment is generally similar to cyclone bin assembly **9**, and analogous features are identified using like reference numerals indexed by a given amount (**2000**, **3000**, **4000**, etc.). Features of any one embodiment of the cyclone bin assembly may be combined in combination or sub-combination with any compatible features from any of the other embodiments of the cyclone bin assembly.

[0193] Referring to FIG. **26**, in this embodiment the juncture surface **2066** is kinked as opposed to being a generally flat surface as shown in FIG. **25**. In this embodiment, the juncture surface **2066** is not tangential to the sidewall of the air inlet **2042**. In this illustrated example, the juncture surface **2072** is curved with a radius that generally matches the curvature of the air inlet **2042** and the bridge surface **2073** extends between surfaces **2072** and **2066** and has a width **2074**. In this embodiment, the screen **2050** is generally cylindrical and has a constant width along its entire height.

[0194] Referring to FIG. **27**, in this embodiment, the juncture **3065** between the sidewall **3041** and the bottom wall **3040** forms a sharp corner and is not angled or radiused and the juncture **3070** between the bottom wall **3040** and the vortex finder **3049** is also formed as a sharp corner. While the lower junctures are both formed as sharp corners, the juncture surface **3080** extending between the upper wall **3039** and the insert **3076** remains a curved surface with radius **3081**. In this configuration, the air inlet **3042** is positioned in juncture **3065** and is tangential to both the cyclone chamber sidewalls **3041** and the bottom wall **3040**. Further, a bridge surface is provided.

[0195] Referring to FIG. **28**, in this embodiment, juncture surfaces **4066** and **4072** are both curved surfaces but radiuses **4067** and **4071** are different. In the illustrated example, radius **4067** is smaller than the curvature of the air inlet **4042** such that the surface **4066** is not aligned with the side of the air inlet **4042**. Optionally, the radius **4071** can be selected to match the curvature of the air inlet

4042.

[0196] Referring to FIG. 29, in this embodiment, the member **5068** is configured such that the radial distance **5081** between the cyclone chamber sidewall **5041** and the vortex finder **5049** is the same as the diameter **5048** of the air inlet **5042**. In this configuration, there is no gap between a radial distance in equal to the diameter of the air inlet **5042** and the vortex finder **5049**. In the example illustrated, juncture surfaces **5066** and **5072** are both curved surfaces and are configured so that the radiuses **5067** and **5071** are the same and are selected to match the curvature of the air inlet **5042**. In this configuration, substantially all of the lower half of the air inlet **5042** is aligned with the juncture surfaces **5066** and **5072**. In this embodiment, the juncture surface **5080** is also curved. When configured in this manner, juncture surfaces **5066** and **5072** meet so as to form one generally continuous curve surface that extends from the cyclone chamber sidewall **5041** to vortex finder **5049**.

[0197] Referring to FIG. 30, in this embodiment, juncture surface **6066** is curved with a curvature that is selected to match the shape of air inlet **6042** whereas juncture **6070** is formed as a sharp corner.

[0198] Referring to FIG. 31, in this embodiment, the cyclone chamber **7010** and member **7068** are configured such that the radial distance **7081** between the cyclone chamber sidewall **7041** and the vortex finder **7049** is substantially larger than the diameter **7048** of the air inlet **7042**. In this configuration, the width **7074** of the bridge surface **7073** is relatively large and in the example illustrated, is greater than the radial width **7098** of juncture surface **7066**. In this example, both juncture surfaces **7066** and **7072** are both curved surfaces and are configured such that their curvature generally matches the shape of air inlet **7042**.

[0199] Referring to FIG. 32, in this embodiment, member **8068** is configured so that the juncture **8065** has an angled or inclined juncture surface **8066** and the juncture **8070** is formed as a sharp corner. Illustrated as a curved, juncture surface **8080** can optionally be configured as a sharp corner or as an inclined or angled surface.

[0200] Referring to FIG. 33, in this embodiment member **9068** is configured so that the juncture between **9070**, between bottom wall **9040** and vortex finder **9049** is configured as a sharp corner and juncture **9065** between the bottom wall **9040** and the cyclone chamber sidewall **9041** includes a curved juncture surface **9066**. The curvature of juncture surface **9066** is selected to generally match the curvature of air inlet **9042**. In this configuration, the air inlet **9042** is provided at a different location within the cyclone chamber **9010**, but is still positioned generally tangential relative to cyclone chamber sidewall **9041**. Changing the position of the air inlet **9042** may affect the air flow within the cyclone chamber and, in the example illustrated, may result in air circulating within the cyclone chamber **9010** in the direction that is generally opposite to the direction of air circulation in the cyclone chambers of the previous embodiments. Also, in this configuration, the air inlet **9042** is located adjacent and generally below the dirt outlet slot **9044**.

[0201] Referring to FIG. 34, in this embodiment, member **10068** is configured so that outer juncture **10065** (between cyclone chamber sidewall **10041** and bottom wall **10040**) is configured as a generally sharp corner and inner juncture **10070** is configured as a curved surface. In this embodiment, the air inlet **10042** is generally rectangular (as opposed to being generally circular as in the previous embodiments) and has an air inlet height **10096**. In the cited example, the air inlet height **10096** is still less than the height of the vortex finder **10049** thereby providing a gap of height **10097** between the top of the air inlet **10042** and top of the vortex finder **10049**. In this embodiment, the sharp corner configure of juncture **10065** generally matches the shape of the lower portion of the air inlet **10042** and the air inlet is generally tangential to the cyclone chamber sidewall **10041**.

[0202] Referring to FIG. 35, in this embodiment the air inlet **11042** is a partially rectangular partially curved configuration. In the illustrated example, the lower portion of the air inlet **11042** located towards the inner section of the cyclone chamber sidewall **11041**, and the lower wall **11040**

is curved, and the surface **11072** at juncture **11070**, is a curved surface that is configured to generally match the shape of the air inlet **11042**. The juncture **11065** between the lower end wall **11040** and the vortex finder **11049** is configured as a sharp corner. Also in this example, the air inlet **11042** is positioned toward the center of the cyclone bin of the assembly **11009** and is adjacent to a portion of the cyclone chamber sidewall **11041** that separates the cyclone chamber **11010** from the dirt collection chamber **11011**.

[0203] Referring to FIG. **36**, this embodiment is generally similar to the embodiment of FIG. **35** but the air inlet **12042** is of a different configuration than air inlet **11042**. In this example, the lower portion of the air inlet **12042** is curved and the juncture **12070** is also curved so that the juncture surface **12072** generally matches the shape of the air inlet **12042**. The juncture **12065** between the bottom wall **12040** and the vortex finder **12049** is configured as a generally sharp corner.

[0204] Referring to FIG. **37**, in this embodiment, member **13068** is configured so that the bottom wall **13040** of the cyclone chamber **13010** is spaced below the bottom of the air inlet **13042**. In the illustrated example, the bottom wall **13040** is offset below the bottom of the air inlet **13042** by distance **13099**. The distance **13099** may be any suitable distance, and may be between about 0% and about 50% of the diameter **13048** of the air inlet **13042**. In this example, junctures **13065** and **13070** are both curved but because of the vertical offset **13099**, portions of the juncture **13070** are spaced apart from the edges of the air inlet **13042**.

[0205] As exemplified in the forgoing, the juncture of the sidewall and the end wall at the cyclone air inlet end is preferably configured to permit air exiting the air inlet to transition smoothly (e.g., without forming eddy currents or other turbulence) as the air enters the cyclone chamber.

Accordingly, the juncture of the side and end walls is preferably configured to match the shape of the cyclone air inlet and the cyclone air inlet is preferably positioned adjacent the juncture.

However, as exemplified, the juncture may be angled so as to approximate the curvature of the air inlet. Alternately, if the air inlet is not circular, the juncture may be shaped similarly to the portion of the air inlet that abuts the juncture or may approximate the shape. As also exemplified, the air inlet may be spaced from the juncture of the side and end walls (e.g., above and/or inwardly therefrom) but may abut the sidewall and/or end wall inwards of the juncture.

[0206] Alternately or in addition, the juncture of the sidewall of a vortex finder (or insert) and an end wall may be shaped to match the shaped of the juncture of the sidewall and the end wall at the air inlet or may be angled or curved so as to reduce eddy currents or turbulence.

[0207] Alternately, or in addition, distance between the sidewall and the vortex finder and/or the innermost end of the vortex finder and the end wall may be greater than the diameter of the air inlet.

[0208] It will be appreciated that, in a preferred embodiment, each of these features is used.

However, the use of any of the features may beneficially reduce eddy currents or other turbulence in the cyclone chamber and thereby reduce back pressure through the cyclone chamber. A reduction in the back pressure through the cyclone chamber will permit the velocity of air flow at the dirty air inlet to be increased, all other factors remaining the same, and thereby increase the cleaning efficiency of a vacuum cleaner.

Barrier Wall

[0209] The following is a description of a barrier wall that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0210] Referring to FIGS. **44-54**, schematic representations of alternate embodiments of a cyclone chamber and dirt collection chamber are shown. These schematic representations are generally similar to the cyclone chamber **10** and dirt collection chamber **11**, and analogous features are identified using like reference characters with a unique suffix.

[0211] Referring to FIG. **44**, a cyclone chamber **10g** is illustrated in combination with a dirt collection chamber **11g**. The cyclone chamber **10g** includes an air inlet **42a**, air outlet (not shown),

sidewall **41a** and a dirt outlet **44**. For ease of description the upper walls of the cyclone chamber **10g** and dirt collection chamber **11g** have been removed, but it is understood that the upper ends of the dirt collection chamber **11g** and cyclone chamber **10g** can be covered with any suitable upper wall or lid. The air inlet **42a** is provided toward the bottom end of the cyclone chamber **10g** and the dirt outlet **44g** is provided toward the top of the cyclone chamber **10g**. Alternatively, the positions of the air inlet **42g** and dirt outlet **44g** may be reversed.

[0212] In the illustrated embodiment, a deflector or barrier wall **83g** is positioned in the dirt collection chamber **11g** generally opposite the dirt outlet **44g**. In this position, dirty air exiting the cyclone chamber **10g** may tend to contact the barrier wall **83g**, which may help dis-entrain dirt and debris from the air flow. The barrier wall **83g** may also guide or direct dirt particles in a desired direction within the dirt collection chamber **11g**. Alternatively, instead of being positioned within the dirt collection chamber **11g**, the barrier wall **83g** may be provided in any other air passage or conduit that is in air flow communication between the dirt outlet **44g** and the dirt collection chamber **11g** (for example if the dirt outlet **44g** is not in direct communication with the dirt collection chamber **11g**).

[0213] The barrier wall **83g** has a first or inner face **84g** that faces and is spaced from the dirt outlet **44g** and an opposed outer face **85g** that is spaced from and faces the sidewall **56g** of the dirt collection chamber **11g**. The barrier wall **83g** also defines an upstream end **86g** and a downstream end **87g** relative to the direction of air circulation within the cyclone chamber **10g**. Barrier wall may be fixed in position by any means. For example, it may be affixed to the cyclone chamber sidewall, the end wall or a sidewall of the exterior dirt collection chamber. In the illustrated embodiment the barrier wall **83g** extends from the cyclone chamber sidewall **41g**, and the upstream end **86g** of the barrier wall **83g** is connected to the cyclone chamber sidewall **41g** at a location upstream from the upstream end of the slot **44g**, and is sealed against the sidewall **41g**. The downstream end **87g** of the barrier wall **83g** is spaced apart from the cyclone chamber sidewall **41g**. Alternatively, the upstream end **86g** of the barrier wall **83g** may be spaced apart from the cyclone chamber sidewall **41g**. If the barrier wall is connected to or extends from the sidewall of the cyclone chamber, then the position from which the barrier wall extends is preferably up to 1 inch and more preferably 0.125 to 0.5 inches upstream from the upstream side of the dirt outlet.

[0214] The barrier wall **83g** is radially spaced apart from the dirt outlet **44g** and the cyclone chamber sidewall by a distance **88g**. In the illustrated embodiment the distance **88g** is generally constant and the distance between the upstream end of the dirt slot and the barrier wall **83g** is the same as the distance between the downstream end of the dirt slot and the barrier wall **83g** (i.e. most of the barrier wall **83g** is generally concentric with or parallel to the cyclone chamber sidewall **41a**). The distance **88g** may be selected to be any suitable distance, and preferably is large enough to allow debris to pass between the barrier wall **83g** and the sidewall **41g**. For example, the distance **88g** may be selected to be up to 1.5 inches or more, and may be configured to be less than 1 inch (e.g., 0.5-0.075 inches) and may be between about 0.125 and 0.5 inches. If the surface cleaning apparatus is to be used to clean, e.g., dry wall dust, then the spacing may be between 0.075-0.2 inches. In configurations in which one end of the barrier wall **83** flares away from the cyclone chamber sidewall **41** downstream from the dirt outlet (as explained herein), the distance between the flared portion of the barrier wall and the cyclone chamber sidewall **41** may exceed the ranges given above. For example, the distance between the cyclone chamber sidewall and the barrier wall at the downstream end of the dirt outlet may be between 10-50% further from the cyclone chamber sidewall than the distance between the cyclone chamber sidewall and the barrier wall at the upstream end of the dirt outlet and is preferably about 10-20% further.

[0215] In the illustrated embodiment, the barrier wall **83g** is slightly wider in the axial direction than the dirt outlet slot **44g**, so that the barrier wall **83g** covers or overlaps the full width of the dirt slot **44g** (e.g., it has a similar angular extent). Alternatively, the barrier wall **83g** may have a width that is equal to or less than the width of the dirt slot **44g**.

[0216] The height of the barrier wall may be from 35-150% the height of the dirt outlet. For example, in the illustrated embodiment, the barrier wall **83g** extends substantially the entire height of the cyclone chamber **10g** in the axial direction, and the height of the barrier wall **83g** is greater than the height **57g** of the dirt slot **44g**. In this embodiment the barrier wall **83g** has a constant height along its width, but alternatively the height of the barrier wall **83g** may vary along its width (e.g. the upstream end of the wall may be taller than the downstream end, or vice versa).

[0217] Referring to FIG. **45**, in another embodiment, the barrier wall **83h** does not extend the full height of the cyclone chamber **10h**, and the upper end of the barrier wall **83h** is axially offset below the upper end of the cyclone chamber sidewall **41h**. In this configuration, the barrier wall **83h** does not cover the full axial height of the dirt outlet **44h**, but does extend to cover the full width of the dirt outlet **44h**.

[0218] Also in this embodiment, the barrier wall **83h** is not parallel to or concentric to the sidewall **41h**. In this configuration, the distance **88h** between the upstream end of the slot **44h** and the barrier wall **83h** is less than the distance **88h** between the downstream end of the slot **44h** and the barrier wall **83h**. Further, the barrier wall **83h** continues to diverge from the sidewall **41h** so that the distance **88** between the barrier wall **83h** and the sidewall **41** at a location downstream from the slot **44h** is greater than the distance **88g** at the downstream end of the slot **44h**.

[0219] Referring to FIG. **46**, in another embodiment a barrier wall **83i** flares more substantially away from the outer surface of the cyclone chamber sidewall **41i** so that the distance **88i** at the downstream end of the dirt slot **44i** is much greater than the distance **88i** at the upstream end of the slot **44i**.

[0220] Referring to FIG. **47**, in another embodiment a barrier wall **83j** has a width that is less than the width of the dirt slot **44j**. In this configuration, the barrier wall **83j** covers the upstream end of the slot **44j** and a portion of its width, but the downstream end **87j** of the barrier wall **83j** does not reach or cover the downstream end of the slot **44j**.

[0221] Referring to FIG. **48**, in another embodiment a barrier wall **83k** extends the full width and full height of the dirt slot **44k**, but is configured such that the upstream end **86k** of the barrier wall **84k** is spaced apart from the sidewall **41k** to provide a passage **89k** between the wall **83k** and the sidewall **41k**. In this configuration the barrier wall **83k** is not supported by the sidewall **41k** and instead may extend upward from the bottom wall of the dirt collection chamber **11g**. Alternatively, or in addition, one or more optional support ribs **90k** (illustrated as optional using dashed lines) may extend between the dirt collection chamber sidewall **56k** (and/or from sidewall **41k**) and the barrier wall **83k** to help provide support.

[0222] Alternatively, instead of extending upwardly from the bottom wall of the dirt collection chamber, the barrier wall may depend downwardly from the upper wall of the dirt collection chamber. Referring to FIG. **49**, in another embodiment a barrier wall **83L** extends downwardly from the upper wall of the dirt collection chamber **11L** and is sized to cover dirt slot **44L**.

Optionally, referring to FIG. **50**, a barrier wall **83m** that depends from the upper wall of the dirt collection chamber **11m** can be configured to have a height that is less than the height of the cyclone chamber **10m**, and optionally less than the height **57m** of the slot **44m**.

[0223] Optionally, some or all of the barrier wall may be integral with other portions of the cyclone chamber or dirt collection chamber. Referring to FIG. **51**, in another embodiment a barrier wall **83n** is integral with the dirt collection chamber sidewall **56n** or optionally a passage extending to a dirt collection chamber. In this embodiment, the inner surface **84n** of the barrier wall **83n** faces the cyclone chamber sidewall **41n** and the outer surface **85n** may be part of the exterior surface of the cyclone chamber assembly (or optionally surrounded by another housing, etc.). If the barrier wall is integral with other portions of the cyclone chamber or the dirt collection chamber or a passage thereto, it preferably extends from a position somewhat upstream from the upstream end of the dirt outlet.

[0224] Referring to FIG. **52**, in another embodiment the barrier wall **880** has a variable height, and

in the configuration illustrated, increases in height from the upstream end **860** toward the downstream end **870**. In the illustrated configuration, the upstream end **860** of the barrier wall **830** does not cover the full height **570** of the slot **440**, whereas the downstream end **870** covers more of the full height of the slot **440**. FIG. **53** is a section view showing the elevation of the barrier wall **830** relative to cyclone chamber **100** and slot **440**. FIG. **54** is an alternate embodiment in which the barrier wall **83p** varies in height in the opposite direction (the upstream end **86p** is shorted than the downstream end **87p**).

Dirt Slot of Varying Heights

[0225] Referring to FIGS. **55-57**, schematic representations of alternate embodiments of a cyclone chamber **10** are shown. The schematic embodiments are generally similar to the cyclone chamber **10**, and analogous features are identified using like reference numerals with a unique suffix.

[0226] Referring to FIG. **55**, the cyclone chamber **10q** includes a dirt slot **44q** that varies in height **57q** along its width. In this embodiment, the height **57q** at the upstream end of the slot **44q** is less than the height **57q** at the downstream end of the slot **44**. Also, in this embodiment the intersection of the upstream edge **91q** and the bottom edge **92q** is rounded, as is the intersection between the downstream edge **93q** and the bottom edge **92q**. Alternatively, only one of these intersections may be rounded.

[0227] Referring to FIG. **56**, in another embodiment the slot **44r** is configured so that there are sharp corners between edges **91r** and **93r** and bottom edge **92r**, and that the upstream end of the slot **44r** is taller than the downstream end.

[0228] The slot **44r** (and any other dirt outlet slot) can be configured so that the height at the shortest portion of the slot is between about 35% to about 100% (i.e. no change) of the height at the tallest portion of the slot.

[0229] The features of the dirt slot illustrated in the above embodiments may be used by itself or in any combination or sub-combination with any other feature or features disclosed herein.

Pre-Motor Filter Housing Construction

[0230] The following is a description of a pre-motor filter housing that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0231] Referring to FIG. **57**, a schematic representation of a surface cleaning unit **4** is shown. In the illustrated example, two pre-motor filters **32** and **33** are positioned within the pre-motor filter chamber **31**, although a differing number may be used. The pre-motor filter chamber **31** is defined by a housing that comprises an upper end wall **110** that may optionally include the downstream end of the vortex finder, a sidewall **111** and a lower end wall **112** that may optionally include the upstream end of the suction motor inlet.

[0232] The open headspace or header between the bottom of the cyclone bin assembly and the upper side **123** of the filter **32** defines an upstream air plenum **124**. Providing the upstream plenum **124** allows air to flow across the upper side **123** of the filter **32**. The open headspace or header downstream of the filters **32**, **33**, between the downstream side **125** of filter **33**, provides a downstream air plenum. Providing a downstream plenum **126** allows air exiting the filters **32**, **33** to flow inwardly and toward the suction motor inlet. In use, air exiting the cyclone chamber **10**, via the air outlet **43**, flows into upstream plenum **124**, through filters **32**, **33**, into downstream plenum **126** and into the air inlet portion **113** of the suction motor **8**.

[0233] As exemplified in FIG. **17**, the outer sidewall of the motor housing **12** may surround some or all of the pre-motor filter chamber **31**. Further, most or all of the upper end wall **110** may be provided by the lower surface of the cyclone bin assembly **9**, including portions of the cyclone chamber end wall **40** and the dirt collection chamber end wall **62**. In this configuration, when the cyclone bin assembly **9** is removed, most of the upper end wall **110** is also removed, which may “open” the pre-motor filter chamber **31** and allow a user to access the filters **32**, **33**. Similarly, most of the lower end wall **112** is provided by the suction motor inlet sidewall **114**.

[0234] Optionally, the pre-motor filter housing has an upstream and/or a downstream header that is configured to reduce turbulence. Accordingly, some or all of the intersections between, the walls **110** and **111**, the walls **111** and **112**, and the wall **112** and the suction motor inlet may include angled or curved surfaces, which may be shaped in a similar manner to the configuration of the junctures of the cyclone chamber **10** discussed previously. Providing curved or smoother junctures within the pre-motor filter housing **31** may help reduce backpressure caused by the pre-motor filter chamber. This may help improve the efficiency of the surface cleaning apparatus **1** by increase the velocity of the air flow at the dirty air inlet, all other factors remaining the same. Improving the efficiency may allow the surface cleaning apparatus to provide improved suction capabilities, and/or may allow the surface cleaning apparatus to maintain its existing suction capabilities while requiring a smaller, less powerful motor **8**.

[0235] In the illustrated embodiment, the juncture **115** between the sidewall **111** and the upper wall **110** includes a curved juncture surface **116**. The curvature of the surface **116** can be selected to help improve air flow into the upstream plenum **124**. Optionally, the juncture surface **116** can remain with the pre-motor filter chamber **31** when the cyclone bin assembly **9** is removed, or alternatively the juncture surface **116** may be part of the cyclone bin assembly **9** and may be removable from the pre-motor filter chamber **31**.

[0236] The juncture **117** between the sidewall **111** and the wall **112** forming part of the suction motor inlet **113** also includes a curved juncture surface **118**. The curvature of surface **118** may be the same as, or different than the curvature of surface **116**. Optionally, the juncture between the wall **112** and the inlet sidewall **114** of the suction motor inlet may also be curved or angled. In the illustrated embodiment, the juncture **119** between walls **112** and **114** includes a curved surface **120**, which may help improve air flow into the suction motor **8**. Alternatively, instead of being curved, junctures surfaces **116**, **118** and **120**, as well as the juncture of the vortex finder and wall **110**, may be generally planar angled or inclined surfaces. The curvature of surfaces **116**, **118** and **120** may be any of suitable magnitude that helps improve air flow efficiency through the pre-motor filter chamber **31** and suction motor air inlet **113**.

[0237] A generally flat bridging surface **121** forms part of wall **112** and extends between juncture surfaces **118** and **120** and has a length **122**. Together, the juncture surfaces **118** and **120** and surfaces **121** and **114** may co-operate to form a generally flared or trumpet-like motor inlet **113**. As illustrated, the vortex finder may also be flared or trumpet-shaped.

[0238] Referring to FIG. **58**, another embodiment of a surface cleaning unit **14004** is shown. Surface cleaning **14004** is generally similar to surface cleaning unit **4**, and analogous features are identified using like reference characters indexed by 14000.

[0239] In the illustrated embodiment, the surface cleaning unit **14004** includes a cyclone bin assembly **14009** that is positioned below the suction motor **14008** and suction motor housing **14012**. The pre motored filter chamber **14031**, containing filter **14032** and **14033**, is located between cyclone bin assembly **14009** and the suction motor **14008** and the illustrated configuration is positioned above cyclone bin assembly **14009**.

[0240] In this embodiment, air enters the cyclone chamber **14010** via air inlet **14042** and exits via air outlet **14043**. Air then flows into the upstream header or plenum **14125** before contacting the upstream face **14123** of filter **14032** and flowing through the filters **14032** and **14033** into the downstream headspace or plenum **14126**. From the downstream plenum **14126**, air is guided by walls **14112**, **14114**, to the air inlet of the suction motor **14008**. Like the previous embodiment, juncture **14115** between the end wall **14110** and the side wall **14111** includes a curved or a radiused surface **14116** to help improve air flow. Similarly junctures **14117** and **14119** provided in the downstream plenum **14126** include curved or radius surface **14118** and **14120**, respect to the leak. A flat bridging surface **14121** connects curved surfaces **14118** and **14120** and helps provide the flared or trumpet like inlet for the suction motor **14008**.

[0241] Referring to FIG. **59**, the embodiment of FIG. **58** is shown having curved juncture surfaces

14118 and **14120** that have a larger radius or degree of curvature than those shown in FIG. 58. A bridge surface **14121** is still provided between surfaces **14120** and **14118** but its length **14122** in the embodiment of FIG. 59 is substantially less than its length in the previous embodiment. The curvature of juncture surface **14116** remains unchanged from the embodiment of FIG. 58. Providing a higher degree or curvature and/or larger curved juncture surfaces **14118**, **14120** may help improve air flow from the downstream plenum **14126** to the suction motor **14008**.

[0242] Referring to FIG. 60 another embodiment of the surface cleaning unit **15004** is shown. Surface cleaning unit **15004** is generally similar to surface cleaning unit **4** and analogous features are identified using like referencing characters indexed by 15000. In the illustrated embodiment the cyclone bin assembly **15009** is positioned above the suction motor **15008** and surrounding housing **15012**, and the pre-motor chamber **15031** is defined there between.

[0243] In the illustrated embodiment air enters cyclone chamber **15010** via inlet **15042** and exists via air outlet **15043**. In this configuration air outlet **15043** is not directly connected to upstream plenum **15124** and instead is connected via an external air flow conduit **15127** which is provided outside cyclone chamber **15010** and provides air flow communication between air outlet **15043** and plenum **15124**.

[0244] As in the previous embodiment, air exiting the cyclone chamber **15010** goes into upstream plenum **15124**, through filters **15032**, **15033** and into downstream plenum **15126**. In this embodiment, the juncture **15115** between upper wall **15110** and side wall **15111** is not curved, and instead and is formed as a sharp corner. Juncture **15117** and **15119** provided downstream of the filters **15032**, **15033** are curved in this embodiment and include curved juncture services **15118** and **15120** respectively.

Suction Motor Air Inlet

[0245] The following is a description of a suction motor air inlet that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0246] Referring to FIG. 61, the suction motor housing **12** is shown separated from the upper portion **2**, and with the cyclone bin assembly **9**, filters **32**, **32** and door **13** removed. In this embodiment, the suction motor housing **12** includes the sidewall **111** and the bottom wall **112** that bound part of the pre-motor filter chamber **31**. The bottom wall **112** includes a plurality of optional supporting ribs **130** that project upwards from the wall **112** into the chamber **31**. The ribs **130** are configured to contact the downstream side **125** of the filters (in this example felt filter **33**) in the chamber **31** and to hold it above the wall **112**, thereby help to maintaining the downstream plenum **126** (FIG. 57). The ribs **130** are spaced apart from each other to allow air to flow between them, within the plenum **126**, and toward the suction motor air inlet **113**.

[0247] Optionally, some or all of the support ribs in the pre-motor filter chamber **31** may be configured to help guide or direct the air flowing through the downstream plenum **126**. For example, some of the ribs may be configured to help induce rotation of the air within the plenum **126**, before it flows into the suction motor **8**. Preferably, this pre-rotation of the air flow can be selected so that the air is rotated in the direction of revolution of the fan of the suction motor **8**. Pre-rotating the air in this manner may help improve the efficiency of the surface cleaning unit **4**. The ribs may be configured in any suitable manner to help impart rotation to the air flow.

[0248] In the illustrated embodiment, the plurality of ribs **130** includes a plurality of curved ribs **131** that are provide around the suction motor air inlet **113**. The ribs **131** are curved to impart rotation of the air flow in the direction indicated by arrow **132**, which preferably is the same direction as the direction of revolution of the suction motor **8**.

[0249] The ribs **130** define a rib height **133**. If the lower wall **112** of the pre-motor filter is flat, the height **133** of each rib **130**, **131** may remain constant along its entire with. Alternatively, if the lower wall **112** varies in height (e.g., the extend inwardly along a portion of a trumpet-shaped suction motor inlet), the ribs **130**, **131** may also vary in height. Preferably, the ribs **130**, **131** are

configured such that the upper ends of the ribs **130**, **131** lie in a common plane to support the filter **33**, and the lower ends of the ribs are in contact with the wall **112**.

[0250] In the illustrated example, the wall **112** has a slight curvature and portions of the wall **112** are generally inclined toward the suction motor air inlet **113**. In this configuration, the height **133** at the outer end of the ribs **131** (disposed away from the air inlet **113**) is less than the height **113** at the inner ends of the ribs **131** (the ends adjacent the suction motor inlet **113**). Providing constant contact between the lower edges of the ribs **131** and the wall **112** may help impart rotation to the air flow and may help prevent air from flowing underneath the ribs **131**.

[0251] Also referring to FIG. **61**, the suction motor housing **12** optionally includes a shroud **135** surrounding the suction motor **8**. The shroud **135** is configured to protect and optionally support the suction motor **8**, and may also function as a finger guard to prevent a user from accidentally contacting the suction motor **8** when the door **13** is open or removed. The shroud **135** also includes a plurality of air flow apertures **136** to allow air exiting the suction motor **8** to flow through the to the clean air outlet **6**.

Suction Motor Housing Construction

[0252] The following is a description of a suction motor construction that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0253] Optionally, portions of the shroud **135** and/or motor housing **12** may be configured to help reduce the amount of suction motor noise that escapes the housing **12**. This may help reduce the overall amount of noise produced by the surface cleaning apparatus **1**. Alternatively, or in addition, to reducing the noise output, the shroud **135** and housing **12** may be configured to help tune the noise generated and to filter out particular noise frequencies.

[0254] Referring to FIG. **63**, a schematic cross-sectional representation of another embodiment of a suction motor shroud **16135** is illustrated. The suction motor shroud **16135** is analogous to shroud **135**, and analogous features may be identified using like reference characters indexed by 16,000. In this embodiment, the housing **16012** includes a sidewall **16137** surrounding the suction motor **16008** and a bottom wall **138**. The suction motor **16008** is mounted to a collar **16139** that is suspended within the housing **16012** via ribs **16140**.

[0255] In this configuration, air enters the suction motor **16008** via its air inlet **16113** and exits via the motor outlet **16141**, which is in the radial direction in the illustrated example. From the air outlet **16141**, the air is directed downwardly and flows toward the bottom wall **16138**. In the illustrated embodiment, the bottom wall **16138** is curved or scalloped to help smoothly redirect the airflow upwards, towards the air outlet **16136** (which in this example is a generally annular gap between the wall **13137** and collar **16139**). Providing curved surfaces on the bottom wall **16138** may help reduce turbulence in the airflow and may help reduce the noise escaping the suction motor housing by directing some of the noise inwardly. The radius **16142** of the curved portions of the wall **16138** may be any suitable radius. Upstanding projection **16142** extends upwardly from the bottom wall **16138** and helps form the curved portions of the bottom wall **16138** into a generally torus-like configuration, instead of forming a single continuous bowl-like surface covering the entire lower end of the shroud **16135**. This may help prevent air from flowing across the centerline of the shroud **16135**, which may help prevent mixing or other turbulent behavior.

[0256] Referring to FIG. **64**, another embodiment of a motor shroud **17135** is shown. Shroud **17135** is generally similarly to shroud **135** and analogous features are indicated using like reference characters indexed by 17000. In this embodiment the upper end of the shroud **17135** is closed and supports the upper end of the motor **17008**. The bottom end of the shroud **17135** includes a bottom wall **17138** that is curved. As air exits the air outlet **17141** of the suction motor **17008** it can flow downwardly within the shroud **17135** and may be re-directed smoothly by the rounded wall **17138**, and then ejected via the air apertures **17136**. Providing a smooth transition surface on bottom wall **17138** to re-direct and guide the air flow may help reduce the turbulence and may help smooth the

air flow. This may help reduce noise generated by the surface cleaning apparatus. An upstanding projection **17142** projects inwardly from the bottom wall **17138** and helps shape the bottom of the shroud **17135** into a generally torus-shaped configuration as opposed to a generally bowl-like shape. Providing projection **17142** may help prevent air from flowing across the center of the shroud **17135** (i.e. from left to right as illustrated, or vice versa) which may help limit mixing or other turbulence inducing flows.

[0257] Referring to FIG. **65**, another embodiment of a motor shroud **18135** is shown. Shroud **18135** is generally similarly to shroud **135** and analogous features are indicated using like reference characters indexed by 18000. Alternatively, or in addition, to providing rounded features on the end wall or bottom surface of the shroud **18135**, the shroud **18135** may also be configured to include scalloped or rounded portions in the sidewall of the shroud **18137**. FIG. **65** is a top view of section motor **18008** positioned within the shroud **18135** and the motor **18008** is configured to receive air via air inlet **18113** and to eject air radially via outlet **18141**. In the illustrated example, radial air outlet **18141** is directed in one direction, to the right as illustrated, such that air exiting the motor will tend to be directed to the right side of the shroud **18135** as illustrated. In this configuration, portions of the sidewall **18137** that are facing the air outlet **18141** may be curved to help guide and direct air exiting the outlet **18141** and directed inwardly and, optionally, to an opposing side of the shroud **18135** that comprises the air apertures **18136**. Optionally, a projection **18142** can extend inwardly from the sidewall **18137** to divide the interior of the shroud **18135** into two portions and to prevent airflow at the outlet **18141** from mixing. Providing the air outlet **18141** directly opposite (i.e., 180° apart from) the air apertures **18136** may help extend the amount of time it takes for air exiting the motor to reach the apertures **18136** which may increase the likelihood that air exiting the outlets **18136** will be smooth or laminar which may help reduce noise output. Alternatively, instead of the configuration illustrated, the air outlet has a motor **18141** may be positioned at any relative orientation to the air outlets **18136** including for example 90° to the outlets **18136** or directly opposite the outlets **18136**.

Motor Shroud

[0258] The following is a description of a suction motor shroud that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0259] Referring to FIG. **66**, an alternate embodiment of a motor shroud **19135** is shown. Shroud **19135** is generally similar to motor shroud **135** in analogous features will be identified using like reference characters indexed by 19000's. In this embodiment, instead of comprising a single layer, the motor shroud **19135** includes four concentric sub-shrouds **19145**, **19146**, **19147** and **19148**. Each sub-shroud **19145**, **19146**, **19147** and **19148** is positioned to generally surround the motor **19008** and to nest amongst the other sub-shrouds. Referring also to FIG. **67**, in this configuration air flowing radially from the suction motor outlets **19141** will sequentially pass through each sub-shroud **19148**, **19147**, **19146**, **19145** before reaching the outer most air apertures **19136**.

[0260] Optionally, each sub-shroud can be provided with air openings or apertures of a different configuration. For example, apertures in the sub-shrouds may be of different sizes, different shapes and may be in different positions relative to each other. Providing apertures or openings of different sizes and/or configurations may help limit overall noise output as each opening may be relatively more effective at screening noise at a given frequency and therefore stacking the openings in sequence may help sequentially filter out a variety of different frequencies.

[0261] In the illustrated example, the outer most sub-shroud **19145** may form the overall outer wall **19137** of the shroud **19135** and includes generally rectangular apertures **19136**. The next sub-shroud **19146** includes a plurality of generally circular air apertures **19149**. The apertures **19149** can be sized so that they have a different cross-sectional area than rectangular apertures **19136** and can be positioned such that they are generally radially aligned with or alternatively generally radially offset from apertures **19136** in the outer wall **19137**. The next shroud **19147** includes a

plurality of generally smaller, triangular shaped apertures **19150** and the inner most shroud **19148** contains a plurality of even smaller circular apertures **19151**. The number of apertures formed on any given shroud and their configuration, shape and/or surface area may be varied and may be selected to help filter out given frequencies generated by suction motor **19008** and air flow flowing through the shroud **19135**. While the illustrated with an open top, the shroud **19135** may have an upper cover or upper wall that is solid to seal the upper ends of all of the shrouds and to help direct air to flow radially outwardly through the apertures.

Sound Absorbing Material

[0262] The following is a description of a sound absorbing material that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

[0263] Optionally, portions of the surface cleaning apparatus **1** can be formed from or covered/lined with a sound absorbing or sound dampening material. The material may include a plurality of regions of different density. Portions of the material at a given density may tend to resonate at a given natural frequency, and the densities of the regions in the material may be selected so that the regions will resonate, or not resonate, at frequencies that are likely to be produced by the suction motor **8** and air flowing through the housing **12**. Providing different regions with different densities, each having their own natural frequency, may allow the sound absorbing material to counter act noises at a variety of different frequencies. This may be advantageous when compared to a generally homogenous material that may tend to have a single natural frequency. Accordingly, a sheet of sound absorbing material may be constructed from portions of different sound absorbing materials that are adhered together to some a continuous self-supporting sheet.

[0264] For example, the sound absorbing material may include a plurality of pieces of different sound absorbing material or nodes held within a surrounding matrix. The plurality of nodes may include variety of different nodes having different shapes, sizes and/or densities. Optionally, the nodes may be made from the same material as each other, or some of the nodes may be made from a different material. Similarly, some or all of the nodes may be formed from the same material as the surrounding matrix, or alternatively the matrix may be formed from a different material than the nodes.

[0265] Each of the nodes and surrounding matrix may be formed from any suitable material, including, for example, one or more of polyurethane, polypropylene, polyethylene, rubber, ABS plastic, other plastics, glass, metal and composite materials.

[0266] Referring to FIG. **68**, a schematic representation of a material **155** that includes three sets of nodes **156**, **157** and **158** held within a surrounding matrix of material **159** is provided. Each set of nodes **156**, **157**, **158** has a different density, and optionally may have a different shape as illustrated. Alternatively, the nodes **156**, **157**, **158** may have different shapes and the same density, or different densities and the same shapes.

[0267] Optionally, the nodes **156**, **157**, **158** may be generally randomly distributed within the matrix **159**. Alternatively, the nodes **156**, **157**, **158** may be arranged in pre-determined patterns.

[0268] In the illustrated embodiment, each set of nodes **156**, **157**, **158** may tend to resonate at a different natural frequency due to their varying densities and geometries. Excitation of any given set of the nodes **156**, **157**, **158** by sound produced by the surface cleaning apparatus **1** may cause the set of nodes **156**, **157**, **158** to vibrate. The matrix **159** may absorb and/or dissipate some or all of the vibrations, thereby dampening sound waves at the given frequency, and reducing the amount of sound that passes through the material **155**.

[0269] What has been described above has been intended to be illustrative of the invention and non-limiting and it will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto. The scope of the claims should not be limited by the preferred

embodiments and examples, but should be given the broadest interpretation consistent with the description as a whole.

Claims

1. A surface cleaner comprising: (a) an air flow path from a dirty air inlet to a clean air outlet with a suction motor provided in the air flow path, the suction motor having a motor axis of rotation that extends in an axial direction and, in operation, rotates in a rotational direction; (b) a pre-motor filter housing downstream from an air treatment chamber wherein, in operation to clean a surface, a pre-motor filter media is positioned in the pre-motor filter housing; (c) a suction motor housing having a suction motor housing air inlet, wherein a plurality of ribs are provided at the suction motor housing air inlet, and, in operation, the ribs induce rotation of the air travelling to the suction motor.
2. The surface cleaner of claim 1 wherein the ribs are curved and induce rotation of the air travelling to the suction motor in the rotational direction of the suction motor.
3. The surface cleaner of claim 2 wherein each rib has a height in the axial direction from a distal side of each rib to a proximal side of each rib and, in operation, the pre-motor filter media seats on the proximal sides of the ribs.
4. The surface cleaner of claim 3 wherein the ribs are spaced apart from each other whereby, in operation, air travels through passages between adjacent spaced apart ribs in a flow direction, the passage having an upstream side and a downstream side in the flow direction and the ribs have an upstream end and a downstream end in the flow direction, the upstream end is spaced inwardly from a sidewall of the pre-motor filter housing.
5. The surface cleaner of claim 3 wherein the proximal sides of the ribs lie in a plane.
6. The surface cleaner of claim 1 wherein the suction motor housing air inlet is provided in a downstream end wall of the pre-motor filter housing, the ribs extend away from the downstream end wall of the pre-motor filter housing, the downstream end wall of the pre-motor filter housing is inclined in the axial direction towards the suction motor housing air inlet.
7. The surface cleaner of claim 1 wherein each rib has a height in the axial direction from a distal side of each rib to a proximal side of each rib, in operation, the pre-motor filter media seats on the proximal sides of the ribs, and the height of at least some of the ribs in the axial direction vary whereby the upstream sides of the ribs lie in a plane.
8. The surface cleaner of claim 7 wherein the ribs are spaced apart from each other whereby, in operation, air travels through passages between adjacent spaced apart ribs in a flow direction, the passage having an upstream side and a downstream side in the flow direction and the ribs have an upstream end and a downstream end in the flow direction, the upstream end has a smaller height than the downstream end.
9. The surface cleaner of claim 1 wherein the air treatment chamber comprises a cyclone having a cyclone axis of rotation.
10. The surface cleaner of claim 9 wherein the cyclone axis of rotation extends through the suction motor housing air inlet.
11. The surface cleaner of claim 10 wherein the cyclone axis of rotation extends in the axial direction.
12. A surface cleaner comprising an air flow path from a dirty air inlet to a clean air outlet and a suction motor housing which houses a suction motor that is provided in the air flow path, the suction motor having a motor axis of rotation that extends in an axial direction, the suction motor housing having a suction motor housing air inlet which, in operation, induces rotational flow in air which travels through the suction motor air inlet to the suction motor.
13. The surface cleaner of claim 12 further comprising a plurality of curved ribs associated with the suction motor housing air inlet wherein each rib has a height in the axial direction from a distal side of each rib to a proximal side of each rib and, in operation, the pre-motor filter media seats on the

proximal sides of the ribs.

14. The surface cleaner of claim 13 wherein the ribs are spaced apart from each other whereby, in operation, air travels through passages between adjacent spaced apart ribs in a flow direction, the passage having an upstream side and a downstream side in the flow direction and the ribs have an upstream end and a downstream end in the flow direction, the upstream end is spaced inwardly from a sidewall of a pre-motor filter housing.

15. The surface cleaner of claim 12 wherein the ribs are spaced apart from each other whereby, in operation, air travels through passages between adjacent spaced apart ribs in a flow direction, the passage having an upstream side and a downstream side in the flow direction and the ribs have an upstream end and a downstream end in the flow direction, the upstream end has a smaller height in the axial direction than the downstream end.

16. A surface cleaner comprising an air flow path from a dirty air inlet to a clean air outlet and a suction motor housing which houses a suction motor that is provided in the air flow path, the suction motor having a motor axis of rotation that extends in an axial direction, the suction motor housing having a suction motor housing air inlet wherein, in operation, rotational flow is induced in air which travels through the suction motor air inlet to the suction motor.

17. The surface cleaner of claim 16 further comprising a plurality of curved ribs associated with the suction motor housing air inlet wherein each rib has a height in the axial direction from a distal side of each rib to a proximal side of each rib and, in operation, the pre-motor filter media seats on the proximal sides of the ribs.

18. The surface cleaner of claim 17 wherein the ribs are spaced apart from each other whereby, in operation, air travels through passages between adjacent spaced apart ribs in a flow direction, the passage having an upstream side and a downstream side in the flow direction and the ribs have an upstream end and a downstream end in the flow direction, the upstream end is spaced inwardly from a sidewall of a pre-motor filter housing.

19. The surface cleaner of claim 17 wherein the ribs are spaced apart from each other whereby, in operation, air travels through passages between adjacent spaced apart ribs in a flow direction, the passage having an upstream side and a downstream side in the flow direction and the ribs have an upstream end and a downstream end in the flow direction, the upstream end has a smaller height in the axial direction than the downstream end.

20. The surface cleaner of claim 19 wherein the upstream sides of the ribs lie in a plane.
