

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392459
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kaye; Douglas et al.

Dual power light source

Abstract

Various embodiments of dual-powered lighting devices are described. In some examples, the device includes a light source, a first power source, a second power source, and one or more switching devices. The switching device switches between the first power source and the second power source to power the light source.

Inventors: Kaye; Douglas (Alpharetta, GA), Hires; Kelly (Alpharetta, GA), Tanha; Hamida (Tucker, GA), Lindley; Lauren (Atlanta, GA), Dosani; Kaif (Lawrenceville, GA)

Applicant: LB Marketing, Inc. (Alpharetta, GA)

Family ID: 1000008763672

Assignee: LB Marketing, Inc. (Alpharetta, GA)

Appl. No.: 18/915668

Filed: October 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250035272 A1	Jan. 30, 2025

Related U.S. Application Data

continuation parent-doc US 18130024 20230403 US 12146624 child-doc US 18915668
us-provisional-application US 63328940 20220408

Publication Classification

Int. Cl.: F21L4/08 (20060101); F21L4/00 (20060101); F21V23/04 (20060101)

U.S. Cl.:

CPC **F21L4/085** (20130101); **F21L4/005** (20130101); **F21V23/04** (20130101);

Field of Classification Search

CPC: F21L (4/005); F21L (4/0085)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6616296	12/2002	Roux	362/208	F21V 19/047
12146624	12/2023	Kaye	N/A	F21V 23/04
2003/0206410	12/2002	Parsons	362/183	F21L 4/08
2005/0225969	12/2004	Chen	362/157	F21L 4/085
2009/0154148	12/2008	Meyer	315/86	F21S 6/005
2013/0343042	12/2012	Windom	362/183	F21L 4/005
2018/0128461	12/2017	Le	N/A	F21L 4/08
2023/0324015	12/2022	Kaye	N/A	F21L 4/005
2025/0035272	12/2024	Kaye	N/A	F21V 23/0414

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2013169233	12/2012	WO	F21L 4/005
WO-2018057705	12/2017	WO	N/A

Primary Examiner: Garlen; Alexander K

Attorney, Agent or Firm: Perilla Knox & Hildebrandt LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 18/130,024, entitled, “DUAL POWER LIGHT SOURCE,” filed Apr. 3, 2023, which claims the benefit of and priority to U.S. Provisional Patent Application No. 63/328,940, entitled “DUAL POWER LIGHT SOURCE,” filed Apr. 8, 2022, the contents of which are hereby incorporated herein by reference in its entirety.

BACKGROUND

(1) Several forms of handheld lighting sources exist. For instance, a flashlight or handheld lamp can provide handheld convenience in a wide variety of environments. A flashlight can refer to a portable handheld electric light source. The light source can include an incandescent light bulb, one or more light-emitting diodes (LEDs), and other types of light sources. Handheld and portable light sources can use a portable power source.

FIELD OF THE INVENTION

(2) The present invention relates to a portable lighting device. More specifically, the present invention relates to a flashlight or another light source having multiple power sources.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Many aspects of the present disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the disclosure. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.
- (2) FIG. 1 is a drawing that includes a side view of a dual power light device and a detail view of an example dual power selector, in accordance with various embodiments of the present disclosure.
- (3) FIG. 2 is a drawing that includes another side view of a dual power light device, in accordance with various embodiments of the present disclosure.
- (4) FIG. 3 is a drawing that includes another side view of a dual power light source and cross-sectional view of the dual power light device, in accordance with various embodiments of the present disclosure.
- (5) FIG. 4 is a drawing that includes a bottom perspective view of a dual power light device and its dual power source cartridge, as well as detail views, in accordance with various embodiments of the present disclosure.
- (6) FIG. 5 is a drawing that includes a bottom view of a dual power light device with its base removed, in accordance with various embodiments of the present disclosure.
- (7) FIG. 6 is a drawing that includes various views of the dual power device cartridge of a dual power light device, in accordance with various embodiments of the present disclosure.

DETAILED DESCRIPTION

- (8) The present invention relates to a dual power light source device. More specifically, the present invention relates to a flashlight, lantern, or another light source having multiple power sources. Generally, the dual power light source can include first and second power sources for powering the light source. In one example embodiment, the first power source is a rechargeable battery and the second power source is one or more alkaline or other non-rechargeable batteries. A user operating the light source can switch between the first and second power sources to select the desired power source or can use both power sources.
- (9) In some example embodiments, the rechargeable battery is built into the light source, and the alkaline batteries are removable and replaceable by a user. In some example embodiments, the dual power light source can include a dual power battery cartridge that holds and provides two different types of power sources. For example, the dual power battery cartridge can hold a first power source, such as rechargeable batteries, in a permanently or semi permanently sealed portion; the dual power battery cartridge can hold a second power source, such as non-rechargeable batteries, in an open or unsealed portion of the dual power battery cartridge. The dual power battery cartridge can provide separate power outputs for the two different power sources.
- (10) FIG. 1 shows a side view of the dual power light device **100** and a detail view of an example dual power selector **103**. The dual power light device **100** can also include a detachable base cap **109** that enables servicing the dual power sources of the device.
- (11) The dual power selector **103** of the dual power light device **100** can provide a user with the ability to select between two or more power sources. The power sources of the dual power light device **100** can include an alkaline, replaceable, or non-rechargeable power source, as well as a rechargeable power source.
- (12) The dual power selector **103** can provide one or more button, slider, toggle, or other types of physical selection components that a user can interact with to select between two or more power sources, and otherwise control modes of the dual power light device **100**. The dual power selector **103** can include two power selector components or buttons. In other examples, the dual power selector **103** can include a mechanism that physically moves to mechanically engage contacts that

select between two or more power sources.

(13) In some examples, the power selectors can include a rechargeable power selection component **112**, and an alkaline or replaceable power selection component **115**. The two power selectors of the dual power selector **103** can be provided using an integrated two-part external button such as a rocker or membrane, or alternatively using two separate physical buttons. In some examples, the underlying electronics include two different switches or a multi-pole switch, among other options.

(14) The dual power selector **103** can also provide one or more light or illuminated indicators that provide a power selection status. The power selection status can indicate which power source is selected and in use for the dual power light device **100**. In this example, the dual power selector **103** shows a separate power status indicator for each power source of the device. In other examples, a single power status indicator can change a color, a hue, a pattern, icon, cutout, or another feature in order to indicate the selected power source.

(15) The power status indicator or indicators can also show a charge level or power level for the associated power source or sources. In some examples, the power level is only shown for the selected power source. The power status indicator or indicators can also indicate whether the power source is low below a threshold value, whether the power source is fully charged or charged over a threshold value, whether the power source is charging, and so on.

(16) A specific charge level can also be provided. The specific charge level can refer to a fraction or percentage of the total. The charge levels, power type selection, and other information discussed for the power status indicator or indicators can be shown as a number of lights, a length (distance) of light illumination across a bar, a status light color, a predetermined light flashing and/or an intensity fluctuation pattern, and so on.

(17) For example, a first status light color, a predetermined light flashing and/or intensity fluctuation pattern can indicate a low power level that has crossed a predetermined threshold voltage or another threshold value. A second status light color, predetermined light flashing and/or an intensity fluctuation pattern can indicate a high or fully charged power level that has crossed a predetermined threshold value. A third status light color, predetermined light flashing and/or an intensity fluctuation pattern can indicate that the power source is charging. Generally, a status indicator can provide a number of charge statuses for a power source, such as charging, charged, low, and so on. A non-rechargeable power source will not utilize the “charging” indication of the status indicator, since the non-rechargeable power source will not be charging within the device.

(18) The status indicators shown include a rechargeable power indicator **118** and an alkaline or replaceable power indicator **121**. The rechargeable power indicator **118** can provide an illuminated or non-illuminated indication that the rechargeable power source has been selected and is in use. The replaceable power indicator **121** can provide an illuminated or non-illuminated indication that the replaceable power source has been selected and is in use.

(19) The dual power selector **103**, such as the rechargeable power selection component **112** and the replaceable power selection component **115**, can also be used to select a lighting mode of a primary light source of the dual power light device **100**. In various modes for a selected power source, the light source can be set to flash, pulsate, or strobe; can be set to provide a constant light source typical to a flashlight; can be set to a particular color; can be set to continuously or periodically change colors; can be set to various luminous intensities, and other operations as can be appreciated. The illuminated status indicators can indicate the selected mode, in some embodiments.

(20) FIG. 2 shows a side view of the dual power light device **100**. This view shows an opposite side of the dual power light device **100** relative to FIG. 1. In this view, the base cap **109** can be seen at the bottom, and a charging port **203** can be seen on the handle.

(21) While shown on the handle at a position close to the connection with the lighting head of the dual power light device **100**, the charging port **203** can alternatively be located closer to the base cap **109**. The charging port **203** can also be incorporated into the base cap **109** or the lighting head

component. The charging port **203** can include a tab-like cover that can act as a dust protector. In some examples, the cover can also provide a waterproof or water resistant protection for the charging port **203**. The cover can include a push-fit, snap-fit, a latch, or another closure mechanism.

(22) The charging port **203** can charge a rechargeable power source such as a battery that is permanently installed within the body of the dual power light device **100**, or a battery that is sealed within a dual power source cartridge of the dual power light device **100**. An example of the dual power source cartridge is shown in FIGS. **3-6**. In instances that include a rechargeable power source installed within the dual power light device **100**, the replaceable, alkaline, or non-rechargeable power source can be directly inserted into the dual power light device **100**, for example, into a hatch in the body once open, or into the bottom of the device once the base cap **109** is removed. However, the replaceable, alkaline, or non-rechargeable power source can also be inserted into a single-power-source cartridge.

(23) FIG. **3** shows a side view of a dual power light device **100** and cross-section A-A of the dual power light device **100**. The cross-section A-A shows the internal components of the dual power light device **100**. The cross-section A-A represents a top-to-bottom slice of the dual power light device **100**, which passes through the head **303**, body **304**, and base cap **109**. The cross-section A-A notably passes through the dual power selector **103**, the charging port **203**, and the power status indicators **118** and **121**.

(24) The dual power light device **100** can include a head **303**. The head **303** can be a durable exterior component that contains a number of light source components. The head **303** can include one or more of metal, plastic, rubber, and other materials selected for durability. The head **303** can contain a light source housing **306**.

(25) The light source housing **306** can be a rigid interior component inside the head **303**. The light source housing **306** can include one or more of metal, plastic, and other materials selected to provide a rigid housing for the light source **309**, the exterior of the head **303**, as well as a reflector **312**, a lens **315**, and a lens ring **318**, among other components.

(26) The light source **309** can include a light emitting diode (LED) light, an incandescent light bulb, a chip on board (COB) LED, or another type of light source, among the various embodiments. The light source **309** can be connected to a chip, circuit board or another light source circuit of the dual power light device **100**. The light source circuit can connect to both power sources of the dual power light device **100**, such that the light source **309** can be powered using either of the power sources.

(27) The reflector **312** can include a parabolic, conic, or other type of reflector that provides a desired distribution of light from the light source **309** to the lens **315**. The reflector can also provide an appropriate spacing between the light source **309** and the lens **315**. The lens **315** can include a glass, polycarbonate, plastic, or other type of transparent or translucent material.

(28) The lens **315** can provide a desired throw of light from the dual power light device **100**. In some cases, the dual power light device **100** can enable a lens adjustment or beam adjustment by pulling, twisting or otherwise manipulating the head **303**, the body **304**, the base cap **109**, or another beam adjustment button or slider component. The beam adjustment can move the lens **315** towards and away from the light source **309**, the light source **309** towards and away from the lens **315**. This can cause the light beam from the dual power light device **100** to become wider and more distributed, or narrower and more concentrated.

(29) The lens ring **318** can hold the lens **315** in the head **303**. The head **303** can include a ridge or another component that can hold the lens ring **318** against the lens **315**. Alternatively, the lens ring **318** can be held by a friction fit, physical fasteners such as screws, or a chemical fastener such as glue or epoxy.

(30) The dual power light device **100** can also include a chip, circuit board, or another primary circuit component **320**, which can also be referred to as a switching circuit. The primary circuit

component **320** can include power switches **321** and **324** corresponding to the power selection components **112** and **115**, respectively. The dual power light device **100** can also include an electronics housing or other housing **333** within the body **304**. The housing **333** can hold the primary circuit component **320**, the switches, and other components shown within the body **304** of the dual power light device **100**.

(31) The “rechargeable power” switch **321** can be used in connection with the rechargeable power selection component **112**. When a user depresses, slides or otherwise manipulates the rechargeable power selection component **112**, the rechargeable power switch **321** can provide a switching action to the primary circuit component **320** to enable or switch power to rechargeable power source **348** if the dual power light device **100** is off, or if a replaceable power source **351** is currently being used. If the rechargeable power source **348** is in use, further depressing or manipulating the rechargeable power selection component **112** can cause the rechargeable power switch **321** to change a lighting mode of the dual power light device **100** and/or turn off the dual power light device **100**. A switching device of the dual power light device **100** can include one or more power selection components or buttons as well as one or more electrical switch components.

(32) The “alkaline or replaceable power” switch **324** can be used in connection with the replaceable power selection component **115**. When a user depresses, slides or otherwise manipulates the replaceable power selection component **115**, the replaceable power switch **324** can provide a switching action to the primary circuit component **320** to enable or switch power to the replaceable power source **351** if the dual power light device **100** is off, or if a rechargeable power source **348** is currently being used. If the replaceable power source **351** is in use, further depressing or manipulating the replaceable power selection component **115** can cause the replaceable power switch **324** to change a lighting mode of the dual power light device **100** and/or turn off the dual power light device **100**.

(33) The rechargeable power source **348** and the replaceable power source **351** can be detachably connected to the primary circuit component **320** using pogo pins or another type of contacts **352**. While one of the contacts **352** is shown, others can be in line or otherwise on another plane or cross section. There can be three or more contacts **352**, including one (or more) negative or ground connection, and two power connections with one for each of the rechargeable power source **348** and the replaceable power source **351**. While the three or more contacts **352** can be on the top of the dual power source cartridge **355** to reduce wiring in the body **304**, other embodiments can include contacts **352** on the bottom of the dual power source cartridge **355**, with wiring, traces, or other electronic circuit connections to the primary circuit component **320** in the body **304**.

(34) Notably, the dual power source cartridge **355** can be designed to align within the body **304** of the dual power light device **100** such that it is limited to a single desired alignment. This alignment feature can prevent non-rechargeable (or replaceable) batteries from being inadvertently charged when an external power source is connected to the charging port **203**. This and other safety mechanisms can also prevent the user from shorting the two different power sources of the dual power source cartridge **355**. The alignment feature of the dual power source cartridge **355** is discussed further with respect to FIGS. 4-6.

(35) The charging port **203** can connect to the primary circuit component **320**, which provides a connection to the rechargeable power source **348** through the appropriate subset of contacts **352**. The charging port **203** can alternatively connect to a charging circuit **336** that connects to the contacts **352** or another set of contacts of the rechargeable power source **348**. The charging port **203** can include a standardized or proprietary power connector. Standardized power connectors can include barrel plug connectors, universal serial bus (USB) type connectors, and others.

(36) USB connectors can include USB-A, USB-B, USB-C, Mini USB-A, Mini USB-B, Micro USB-A, Micro USB-B, and others. While the charging port **203** can be located on the body of the dual power light device **100**, it can alternatively be located on the side of the base cap **109**, or on the bottom of the dual power light device **100** opposite from the lens **315** and light source **309**.

(37) FIG. 4 shows a bottom perspective view of a dual power light device **100** and its dual power source cartridge **355**, as well as detail views. In this view, the base cap **109** is removed from the bottom of the body **304**. The dual power source cartridge **355** is removed from within the body **304**. FIG. 4 includes a detailed view of an alignment system **403**.

(38) The alignment system **403** can include one or more alignment notches **406** that are matched with a corresponding one or more alignment tabs **412** (including the alignment tabs **412a-412c**), as well as one or more alignment rails **415**. Alignment tabs **412** and alignment rails **415** can be considered alignment components of a housing or a body of the dual power light device **100**.

(39) The alignment notches **406** can include notches in a bottom side of the body **304**, or a bottom side of an insert within the body **304**. The bottommost surface of the body **304** or insert can be a circular, n-gonal (polygonal with n-sides), or another shape with the alignment notches **406** cutout from that surface. The alignment notches **406** can allow the dual power source cartridge **355** to be fully inserted into the body **304** in a single orientation, and can prevent the dual power source cartridge **355** from being fully inserted into the body **304** in any other orientation. The alignment system **403** can thereby prevent the power contacts of the dual power source cartridge **355** from touching corresponding contacts unless the dual power source cartridge **355** is properly aligned. This can ensure that the non-rechargeable batteries are not inadvertently charged, and can enforce all power contacts of the dual power source cartridge **355** to align properly with corresponding power contacts within the dual power light device **100**.

(40) In this example, there are two alignment notches **406**, but any number of alignment notches **406** can be used. The two alignment notches **406** can be of different sizes. The different sized notches can prevent improper orientations since the larger one of the alignment tabs **412** cannot fit into the smaller one of the alignment notches **406**.

(41) The alignment tabs **412** can be present on one or both ends of the dual power source cartridge **355**. In the example shown, the alignment tabs **412** include two alignment tabs **412a** and **412b** on a replaceable, alkaline, or non-rechargeable side of the dual power source cartridge **355**. The alignment tabs **412** can also include two alignment tabs on a rechargeable side of the dual power source cartridge **355**, but only the alignment tab **412c** can be seen from the angle shown. When alignment tabs **412** are present on both ends of the dual power source cartridge **355**, the alignment rails **415** can be used. The alignment tab **412a** can be at a top-end or inserted-end of the dual power source cartridge **355**. The alignment tabs **412b** and **412c** can be at a bottom-end or outer-end of the dual power source cartridge **355**. In some examples, top-end alignment tabs **412** can be smaller than bottom-end alignment tabs **412**. The alignment rails **415** can be sized to accept or fit at least a size and shape of the top-end or inserted-end alignment tabs **412**.

(42) In some examples, the alignment rails **415** can be too small to accept the bottom-end alignment tabs **412**. This can prevent reverse-insertion of the dual power source cartridge **355**. However, the alignment notches **406** can be sized to accommodate the bottom-end alignment tabs **412**. Some embodiments can omit the alignment rail or rails **415**. In such examples, the alignment tabs **412** can be present on the bottom end of the dual power source cartridge **355**, and can be omitted or absent from the top end. While some alignment tabs **412** can be referred to as non-rechargeable side and rechargeable-side alignment tabs **412** for convenience, the alignment tabs **412** can be located at any orientation on the dual power source cartridge **355**.

(43) While the top-end or alignment tab **412a** that is inserted into the alignment rail **415** is shown aligned with the bottom-end alignment tab **412b**, other embodiments can have bottom-end alignment tabs **412** that are offset from the top-end alignment tabs **412**. In such an example, the alignment notches **406** can be offset from the alignment rail **415**, to accommodate the offset bottom-end alignment tabs **412**.

(44) The dual power source cartridge **355** is shown with its non-rechargeable, alkaline, or replaceable side facing. From this view, it can be seen that the non-rechargeable, alkaline, or replaceable batteries can be inserted into corresponding open slots in the dual power source

cartridge **355**. While not shown, the rechargeable batteries of the dual power source cartridge **355** can be covered with an unremovable cover so that the rechargeable batteries are embedded or sealed within. In some examples, a removable cover can be used to seal the rechargeable batteries into the dual power source cartridge **355**. An unremovable cover can refer to a cover that is glued in place, held in place using a separate physical fastener, or is held in place with an integrated fastener such as a clip that is hidden once in place.

(45) In some examples, the dual power source cartridge **355** can include a solid plastic housing into which the rechargeable batteries are inserted during assembly of the dual power source cartridge **355**. Once assembly is complete, there may be no way to remove the embedded rechargeable batteries without destruction or disassembly of the dual power source cartridge **355**. In any case, sealing or embedding the rechargeable batteries can prevent inadvertent removal of the rechargeable battery or batteries when the alkaline or other non-rechargeable batteries are being replaced by a user.

(46) FIG. 5 is a drawing that includes a bottom view of a dual power light device **100** with its base cap **109** removed. This view shows a set of three contacts **352**. In other examples, another number of contacts **352** can be used, such as four contacts **352**. The set of three contacts **352** can include a negative or ground connection, and two power connections, with one for the rechargeable power source **348** and one for the replaceable power source **351**.

(47) While the contacts **352** are aligned in a linear shape in this example, the contacts **352** can alternatively form a triangular shape if there are three contacts, or a rectangular or another four-sided shape if there are four contacts. In any case, the alignment notches **406** and alignment rails **415** can ensure that the dual power source cartridge **355** (not shown) can only be inserted so that the rechargeable power contact **352** of the dual power light device **100** mates with the rechargeable power contact of the dual power source cartridge **355**, and the non-rechargeable power contact **352** of the dual power light device **100** mates with the non-rechargeable power contact of the dual power source cartridge **355**.

(48) FIG. 6 shows various views of the dual power source cartridge **355** of a dual power light device **100**. The views include a top view, a bottom view, a front view, a side view, a rear view, and a cross-sectional view.

(49) From the top view, a set of cartridge contacts **703** of the dual power source cartridge **355** are shown. The cartridge contacts **703** can be arranged to match the contacts **352** of the dual power light device **100**. While the cartridge contacts **703** are in a linear shape in this example, the cartridge contacts **703** can alternatively form a triangular shape if there are three cartridge contacts **703**, or a rectangular or another four-sided shape if there are four cartridge contacts **703**. In any case, the cartridge contacts **703** can match and mate with the contacts **352** of the dual power light device **100**.

(50) From the bottom view of the dual power source cartridge **355**, the bottom-side alignment tabs **412b** and **412c** are shown. The bottom-side alignment tabs **412** can align with and fit into the alignment notches **406** of the dual power light device **100**. The bottom-side alignment tabs **412** can, in some examples, also align with and fit into the alignment rails **415** of the dual power light device **100**.

(51) From the front view of the dual power source cartridge **355**, the non-rechargeable, replaceable, or alkaline batteries **706** are shown. The batteries **706** can be inserted into the open-faced battery slots of the dual power source cartridge **355**. The front view of the dual power source cartridge **355** also shows the line where the cross-sectional view B-B is taken.

(52) From the cross-sectional view B-B of the dual power source cartridge **355**, the non-rechargeable, replaceable, or alkaline batteries **706** are shown in black, and the rechargeable battery or batteries **709** are shown with cross hatching. As can be seen from this view, the batteries **706** are inserted into the open-faced battery slots. The batteries **706** can be easily removed from these open-faced battery slots. A user can quickly identify that the batteries **706** are available and easily

removable, while the rechargeable battery or batteries **709** are sealed within the dual power source cartridge **355**. Since the rechargeable battery or batteries **709** are sealed or embedded within the dual power source cartridge **355**, or sealed or embedded within the dual power light device **100** housing or body, they can be considered non-replaceable, even if the cartridge is removable.

(53) Even if there is a removable face plate that can be removed in order to service the rechargeable battery or batteries **709**, the rechargeable battery or batteries **709** are sealed within the dual power source cartridge **355** and are more difficult to remove. This can prevent inadvertent removal of the rechargeable battery or batteries **709**, when the non-rechargeable, replaceable, or alkaline batteries **706** are ready to be replaced.

(54) From the side view of the dual power source cartridge **355**, the non-rechargeable, replaceable, or alkaline batteries **706** are shown on the left side of the image, and a housing or cover is shown encasing the area where the rechargeable battery or batteries **709** are located. As can be seen from this view, the batteries **706** are inserted into the open-faced battery slots. The batteries **706** can be easily removed from these open-faced battery slots. A user can quickly identify that the batteries **706** are available and easily removable, while the rechargeable battery or batteries **709** are sealed within the dual power source cartridge **355**.

(55) From the rear view of the dual power source cartridge **355**, a housing or cover is shown encasing the area where the rechargeable battery or batteries **709** are located. The housing or cover can prevent inadvertent removal of the rechargeable battery or batteries **709** when the non-rechargeable, replaceable, or alkaline batteries **706** are ready to be replaced.

(56) Although relative terms are used in this specification, such as “up” and “down” to describe the relative relationship between one component and another component of an icon, these terms are used in this specification for convenience only, for example according to the directions of the examples described in the drawings. It can be understood that if the device is turned upside down, the component described “up” will become the component “down.” When a structure is “on” or “positioned on” another structure, it may mean that a structure is integrally formed on another structure, or that a structure is “directly” arranged on another structure, or that a structure is arranged “indirectly” on another structure through another structure.

(57) The terms “a,” “an,” “the,” and “said” are used to indicate that there are one or more elements, components, etc. The terms “comprising” and “having” are used to indicate open-ended inclusion, and refers to that, in addition to the listed elements, components, etc., there may be other elements, components, etc. The terms “first” and “second” are used only as labels, and are not intended to be a limitation on the number of objects. The term “substantially” can describe an approximate fit, value, direction, orientation, or other parameter within a predetermined tolerance such as 1%, 2%, 3%, 4%, 5%, or another predetermined tolerance.

(58) It should be emphasized that the above-described embodiments of the present disclosure are merely possible examples of implementations set forth for a clear understanding of the principles of the disclosure. While a feature can be described in connection with a particular figure, the feature can also be combined with features of the other figures. Many variations and modifications may be made to the above-described embodiment(s) without departing substantially from the spirit and principles of the disclosure. All such modifications and variations are intended to be included herein within the scope of this disclosure and protected by the following claims.

Claims

1. A dual-power source lighting device, comprising: a light source; a removable cartridge comprising: a sealed first housing configured to contain a rechargeable battery; a second housing configured to contain a user-replaceable non-rechargeable battery; one or more alignment components configured to ensure proper insertion of the removable cartridge into a body of the dual-power source lighting device; and an output terminal configured to electrically connect to both

the rechargeable battery and the user-replaceable non-rechargeable battery to provide power to the light source of the dual-power source lighting device; and a lighting device body comprising: a housing configured to receive the removable cartridge; a corresponding one or more alignment components within the housing and configured to engage with the one or more alignment components on the removable cartridge to ensure proper orientation of the removable cartridge within the housing; and a detachable base cap that provides user access to replace the user-replaceable non-rechargeable battery without removing the removable cartridge.

2. The dual-power source lighting device of claim 1, wherein the lighting device body further comprises a locking mechanism configured to secure the removable cartridge within the housing.

3. The dual-power source lighting device of claim 1, wherein the lighting device body further comprises a charging port integrated into the housing, the charging port configured to provide an electrical connection for charging the rechargeable battery when the removable cartridge is inserted.

4. The dual-power source lighting device of claim 3, wherein the charging port is positioned such that the rechargeable battery can be charged while the dual-power source lighting device is in use.

5. The dual-power source lighting device of claim 4, wherein the charging port includes an indicator light configured to display a charging status of the rechargeable battery.

6. The dual-power source lighting device of claim 1, wherein the corresponding one or more alignment components of the lighting device body comprise one or more alignment tabs and the one or more alignment components of the removable cartridge comprise one or more alignment notches.

7. The dual-power source lighting device of claim 1, wherein the corresponding one or more alignment components of the lighting device body comprise one or more alignment notches and the one or more alignment components of the removable cartridge comprise one or more alignment tabs.

8. A body for a dual-power source lighting device, the body comprising: a housing configured to receive a removable cartridge containing a first power source and a second power source that is different from the first power source, the second power source comprising a non-rechargeable battery; one or more alignment components within the housing and configured to engage with one or more corresponding alignment components on the removable cartridge to ensure proper orientation of the removable cartridge within the housing; and a detachable base cap that provides user access to replace the second power source without removing the removable cartridge.

9. The body of claim 8, further comprising a locking mechanism configured to secure the removable cartridge within the housing.

10. The body of claim 8, further comprising a charging port integrated into the housing, the charging port configured to provide an electrical connection for charging the first power source when the removable cartridge is inserted.

11. The body of claim 10, wherein the charging port is positioned such that the first power source can be charged while the dual-power source lighting device is in use.

12. The body of claim 10, wherein the charging port includes an indicator light configured to display a charging status of the first power source.

13. The body of claim 8, wherein the one or more alignment components further comprise electrical contacts positioned to automatically engage corresponding terminals on the removable cartridge when the removable cartridge is properly aligned and inserted into the housing.

14. The body of claim 8, further comprising a sealing element positioned at an interface between the housing and the removable cartridge, the sealing element configured to provide a waterproof seal when the cartridge is fully inserted.

15. The body of claim 8, wherein the one or more alignment components comprise one or more alignment tabs that are matched with a corresponding one or more alignment notches of the removable cartridge.

16. The body of claim 8, wherein the one or more alignment components comprise one or more alignment notches that are matched with a corresponding one or more alignment tabs of the removable cartridge.

17. A dual-power source cartridge for use in a lighting device, the dual-power source cartridge comprising: a sealed first housing configured to contain a rechargeable battery; a second housing configured to contain a user-replaceable non-rechargeable battery; one or more alignment components configured to ensure proper insertion of the dual-power source cartridge into a body of the lighting device, the body comprising a detachable base cap that provides user access to replace the user-replaceable non-rechargeable battery without removing the dual-power source cartridge; and an output terminal configured to electrically connect to both the rechargeable battery and the user-replaceable non-rechargeable battery to provide power to a light source of the lighting device.

18. The dual-power source cartridge of claim 17, wherein the one or more alignment components comprise one or more alignment tabs that are matched with a corresponding one or more alignment notches of the body of the lighting device.

19. The dual-power source cartridge of claim 17, wherein the one or more alignment components comprise one or more notches that are matched with a corresponding one or more alignment tabs of the body of the lighting device.
