

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12383318
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Seavey; Jeff F. et al.

---

### Orthopedic implant and methods of implanting and removing same

---

#### Abstract

Illustrative embodiments of orthopedic implants and methods for surgically repairing hammertoe are disclosed. According to at least one illustrative embodiment, an orthopedic implant includes a proximal segment comprising a number of spring arms forming an anchored barb at a first end of the implant, a distal segment extending between the proximal segment and a second end of the implant, and a central segment disposed between the proximal and distal segment.

---

**Inventors:** Seavey; Jeff F. (Houston, TX), Terrill; Lance N. (Glounthaune, IE), Kilgore; Kasey A. (Houston, TX)

**Applicant:** Howmedica Osteonics Corp. (Mahwah, NJ)

**Family ID:** 56849493

**Assignee:** Howmedica Osteonics Corp. (Mahwah, NJ)

**Appl. No.:** 18/195024

**Filed:** May 09, 2023

#### Prior Publication Data

Document Identifier	Publication Date
US 20230270479 A1	Aug. 31, 2023

#### Related U.S. Application Data

continuation parent-doc US 16891732 20200603 US 11672576 child-doc US 18195024  
division parent-doc US 15669370 20170804 US 10702318 20200707 child-doc US 16891732  
division parent-doc US 14637032 20150303 US 9757168 20170912 child-doc US 15669370

---

#### Publication Classification

**Int. Cl.:** **A61F2/42** (20060101); **A61B17/16** (20060101); **A61B17/68** (20060101); **A61B17/72** (20060101); **A61B17/86** (20060101); **A61B17/88** (20060101)

**U.S. Cl.:**

**CPC** **A61B17/7291** (20130101); **A61B17/1617** (20130101); **A61B17/1682** (20130101); **A61B17/68** (20130101); **A61B17/863** (20130101); **A61B17/8872** (20130101); **A61B17/888** (20130101); **A61B17/8883** (20130101); **A61F2/4225** (20130101); A61B17/7266 (20130101); A61F2002/4228 (20130101)

## Field of Classification Search

**CPC:** A61B (17/7291); A61B (17/1617); A61B (17/1682); A61B (17/68); A61B (17/863); A61B (17/8872); A61B (17/888); A61B (17/8883); A61B (17/7266); A61F (2/4225); A61F (2002/4228)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
321389	12/1884	Schirmer	N/A	N/A
1095054	12/1913	Wiesenfeld	N/A	N/A
1517334	12/1923	Young	N/A	N/A
1893864	12/1932	Kocher	N/A	N/A
2128005	12/1937	Lombard	N/A	N/A
2208848	12/1939	Jorgensen	N/A	N/A
2531911	12/1949	Johnson	N/A	N/A
2580821	12/1951	Nicola	N/A	N/A
2984248	12/1960	Sidelman	N/A	N/A
3338689	12/1966	Hetzel et al.	N/A	N/A
3462765	12/1968	Swanson	N/A	N/A
3466669	12/1968	Flatt	N/A	N/A
3593342	12/1970	Niebauer et al.	N/A	N/A
3646654	12/1971	Cervenka et al.	N/A	N/A
3681786	12/1971	Lynch	N/A	N/A
3739403	12/1972	Nicolle	N/A	N/A
3805302	12/1973	Mathys	N/A	N/A
3824631	12/1973	Burstein et al.	N/A	N/A
3875594	12/1974	Swanson	N/A	N/A
D243716	12/1976	Treace et al.	N/A	N/A
4091806	12/1977	Aginsky et al.	N/A	N/A
4158893	12/1978	Swanson	N/A	N/A
4204284	12/1979	Koeneman	N/A	N/A
4237875	12/1979	Termanini	N/A	N/A
4276660	12/1980	Laure	N/A	N/A
4364382	12/1981	Mennen	N/A	N/A
4367562	12/1982	Gauthier et al.	N/A	N/A
4485816	12/1983	Krumme	N/A	N/A
D277509	12/1984	Lawrence et al.	N/A	N/A

D277784	12/1984	Sgarlato et al.	N/A	N/A
4522200	12/1984	Stednitz	N/A	N/A
D284099	12/1985	Laporta et al.	N/A	N/A
4634382	12/1986	Kusano et al.	N/A	N/A
D291731	12/1986	Aikins	N/A	N/A
4759768	12/1987	Hermann et al.	N/A	N/A
4871367	12/1988	Christensen et al.	N/A	N/A
4905679	12/1989	Morgan	N/A	N/A
4955916	12/1989	Carignan et al.	N/A	N/A
4969909	12/1989	Barouk	N/A	N/A
5011497	12/1990	Persson et al.	N/A	N/A
5047059	12/1990	Saffar	N/A	N/A
5062851	12/1990	Branemark	N/A	N/A
5074865	12/1990	Fahmy	N/A	N/A
5092896	12/1991	Meuli et al.	N/A	N/A
5108443	12/1991	Branemark	N/A	N/A
5133761	12/1991	Krouskop	N/A	N/A
5179915	12/1992	Cohen et al.	N/A	N/A
5190546	12/1992	Jervis	N/A	N/A
5207712	12/1992	Cohen	N/A	N/A
5326364	12/1993	Clift, Jr. et al.	N/A	N/A
5360450	12/1993	Giannini	N/A	N/A
5382251	12/1994	Hood et al.	N/A	N/A
5405400	12/1994	Linscheid et al.	N/A	N/A
5405401	12/1994	Lippincott, III et al.	N/A	N/A
5417692	12/1994	Goble et al.	N/A	N/A
5425776	12/1994	Cohen	N/A	N/A
5425777	12/1994	Sarkisian et al.	N/A	N/A
5454814	12/1994	Comte	N/A	N/A
5464427	12/1994	Curtis et al.	N/A	N/A
5474557	12/1994	Mai	N/A	N/A
D366114	12/1995	Ohata	N/A	N/A
5480447	12/1995	Skiba	N/A	N/A
5484443	12/1995	Pascarella et al.	N/A	N/A
D369412	12/1995	Morgan	N/A	N/A
5507822	12/1995	Bouchon et al.	N/A	N/A
5522903	12/1995	Sokolow et al.	N/A	N/A
5554157	12/1995	Errico et al.	N/A	N/A
5578036	12/1995	Stone et al.	N/A	N/A
5634925	12/1996	Urbanski	N/A	N/A
5674297	12/1996	Lane et al.	N/A	N/A
5690631	12/1996	Duncan et al.	N/A	N/A
5702472	12/1996	Huebner	N/A	N/A
D388877	12/1997	Morgan	N/A	N/A
5725585	12/1997	Zobel	N/A	N/A
5779707	12/1997	Bertholet et al.	N/A	N/A
5782927	12/1997	Klawitter et al.	N/A	N/A
5824095	12/1997	Di Maio, Jr. et al.	N/A	N/A
5876434	12/1998	Flomenblit et al.	N/A	N/A
5881443	12/1998	Roberts et al.	N/A	N/A

5882444	12/1998	Flomenblit et al.	N/A	N/A
5919193	12/1998	Slavitt	N/A	N/A
5951288	12/1998	Sawa	N/A	N/A
5958159	12/1998	Prandi	N/A	N/A
5984970	12/1998	Bramlet	N/A	N/A
5984971	12/1998	Faccioli et al.	N/A	N/A
6011497	12/1999	Tsang et al.	N/A	N/A
6017366	12/1999	Berman	N/A	N/A
6093188	12/1999	Murray	N/A	N/A
6123709	12/1999	Jones	N/A	N/A
6146387	12/1999	Trott et al.	N/A	N/A
6162234	12/1999	Freedland et al.	N/A	N/A
6187008	12/2000	Hamman	N/A	N/A
6193757	12/2000	Foley et al.	N/A	N/A
6197037	12/2000	Hair	N/A	N/A
6200330	12/2000	Benderev et al.	N/A	N/A
6248109	12/2000	Stoffella	N/A	N/A
6261289	12/2000	Levy	N/A	N/A
6319284	12/2000	Rushdy et al.	N/A	N/A
6325805	12/2000	Ogilvie et al.	N/A	N/A
6342076	12/2001	Lundborg	N/A	N/A
6348052	12/2001	Sammarco	N/A	N/A
6352560	12/2001	Poeschmann et al.	N/A	N/A
6383223	12/2001	Baehler et al.	N/A	N/A
6386877	12/2001	Sutter	N/A	N/A
6395031	12/2001	Foley et al.	N/A	N/A
6413260	12/2001	Berrevoets et al.	N/A	N/A
6423097	12/2001	Rauscher	N/A	N/A
6428634	12/2001	Besselink et al.	N/A	N/A
6454808	12/2001	Masada	N/A	N/A
6458134	12/2001	Songer et al.	N/A	N/A
6475242	12/2001	Bramlet	N/A	N/A
6517543	12/2002	Berrevoets et al.	N/A	N/A
6554833	12/2002	Levy et al.	N/A	N/A
6689169	12/2003	Harris	N/A	N/A
6692499	12/2003	Tormala et al.	N/A	N/A
6699247	12/2003	Zucherman et al.	N/A	N/A
6699292	12/2003	Ogilvie et al.	N/A	N/A
6706045	12/2003	Lin et al.	N/A	N/A
6736818	12/2003	Perren et al.	N/A	N/A
6773437	12/2003	Ogilvie et al.	N/A	N/A
6811568	12/2003	Minamikawa	N/A	N/A
6827741	12/2003	Reeder	N/A	N/A
6833006	12/2003	Foley et al.	N/A	N/A
6869449	12/2004	Ball et al.	N/A	N/A
6896177	12/2004	Carter	N/A	N/A
6981974	12/2005	Berger	N/A	N/A
7025789	12/2005	Chow et al.	N/A	N/A
7037342	12/2005	Nilsson et al.	N/A	N/A
7041106	12/2005	Carver et al.	N/A	N/A

7044953	12/2005	Capanni	N/A	N/A
7052498	12/2005	Levy et al.	N/A	N/A
7182787	12/2006	Hassler et al.	N/A	N/A
7240677	12/2006	Fox	N/A	N/A
7291175	12/2006	Gordon	N/A	N/A
7537664	12/2008	O'Neill et al.	N/A	N/A
7588603	12/2008	Leonard	N/A	N/A
7600956	12/2008	McDuff et al.	N/A	N/A
7601152	12/2008	Levy et al.	N/A	N/A
7655042	12/2009	Foley et al.	N/A	N/A
7670339	12/2009	Levy et al.	N/A	N/A
7674426	12/2009	Grohowski, Jr.	N/A	N/A
7780737	12/2009	Bonnard et al.	N/A	N/A
7794483	12/2009	Capanni	N/A	N/A
7837738	12/2009	Reigstad et al.	N/A	N/A
7842091	12/2009	Johnstone et al.	N/A	N/A
7909880	12/2010	Grant	N/A	N/A
7918879	12/2010	Yeung et al.	N/A	N/A
7922765	12/2010	Reiley	N/A	N/A
7955388	12/2010	Jensen et al.	N/A	N/A
7976580	12/2010	Berger	N/A	N/A
7993403	12/2010	Foley et al.	N/A	N/A
8048173	12/2010	Ochoa	N/A	N/A
8100983	12/2011	Schulte	N/A	N/A
8162942	12/2011	Coati et al.	N/A	N/A
8202305	12/2011	Reiley	N/A	N/A
8262712	12/2011	Coilard-Lavirotte et al.	N/A	N/A
8308779	12/2011	Reiley	N/A	N/A
8388667	12/2012	Reiley et al.	N/A	N/A
8394097	12/2012	Peyrot et al.	N/A	N/A
8414583	12/2012	Prandi et al.	N/A	N/A
8414648	12/2012	Reiley	N/A	N/A
8425570	12/2012	Reiley	N/A	N/A
8444693	12/2012	Reiley	N/A	N/A
8470004	12/2012	Reiley	N/A	N/A
8475456	12/2012	Augoyard et al.	N/A	N/A
8529611	12/2012	Champagne et al.	N/A	N/A
8597337	12/2012	Champagne	N/A	N/A
8608785	12/2012	Reed et al.	N/A	N/A
8685024	12/2013	Roman	N/A	N/A
8715325	12/2013	Weiner et al.	N/A	N/A
8728387	12/2013	Jones et al.	N/A	N/A
8734462	12/2013	Reiley et al.	N/A	N/A
8734491	12/2013	Seavey	N/A	N/A
8834483	12/2013	Cheney et al.	N/A	N/A
8834572	12/2013	Averous et al.	N/A	N/A
8840623	12/2013	Reiley	N/A	N/A
8840651	12/2013	Reiley	N/A	N/A
8858601	12/2013	Reiley	N/A	N/A

8864804	12/2013	Champagne et al.	N/A	N/A
8920477	12/2013	Reiley	N/A	N/A
8986348	12/2014	Reiley	N/A	N/A
8992703	12/2014	O'Neill et al.	N/A	N/A
8998999	12/2014	Lewis et al.	N/A	N/A
9011504	12/2014	Reed	N/A	N/A
9039743	12/2014	Reiley	N/A	N/A
9044287	12/2014	Reed et al.	N/A	N/A
9056014	12/2014	McCormick et al.	N/A	N/A
9072562	12/2014	Weiner et al.	N/A	N/A
9072564	12/2014	Reed et al.	N/A	N/A
9089427	12/2014	Grohowski, Jr.	N/A	N/A
9089431	12/2014	Grohowski, Jr.	N/A	N/A
D738504	12/2014	Weiner et al.	N/A	N/A
9125698	12/2014	Miller	N/A	N/A
9125704	12/2014	Reed et al.	N/A	N/A
9135374	12/2014	Jones et al.	N/A	N/A
9161789	12/2014	Peyrot et al.	N/A	N/A
9168074	12/2014	Prandi et al.	N/A	N/A
9180010	12/2014	Dong et al.	N/A	N/A
9282977	12/2015	Penzimer et al.	N/A	N/A
9283007	12/2015	Augoyard et al.	N/A	N/A
9403213	12/2015	Lapszynski	N/A	N/A
9452002	12/2015	Roman et al.	N/A	N/A
9492215	12/2015	Augoyard et al.	N/A	N/A
9498266	12/2015	McCormick et al.	N/A	N/A
9498273	12/2015	Thoren et al.	N/A	N/A
9554914	12/2016	Taylor et al.	N/A	N/A
9724140	12/2016	McCormick	N/A	N/A
9757168	12/2016	Seavey et al.	N/A	N/A
9775630	12/2016	Leavitt et al.	N/A	N/A
10022167	12/2017	Augoyard et al.	N/A	N/A
10111690	12/2017	Anderson et al.	N/A	N/A
2001/0025199	12/2000	Rauscher	N/A	N/A
2001/0049529	12/2000	Cachia et al.	N/A	N/A
2002/0019636	12/2001	Ogilvie et al.	N/A	N/A
2002/0055785	12/2001	Harris	N/A	N/A
2002/0065561	12/2001	Ogilvie et al.	N/A	N/A
2002/0068939	12/2001	Levy et al.	N/A	N/A
2002/0082705	12/2001	Bouman et al.	N/A	N/A
2002/0099395	12/2001	Acampora et al.	N/A	N/A
2002/0133156	12/2001	Cole	N/A	N/A
2002/0169066	12/2001	Cassidy et al.	N/A	N/A
2002/0189622	12/2001	Cauthen et al.	N/A	N/A
2003/0040805	12/2002	Minamikawa	N/A	N/A
2003/0069645	12/2002	Ball et al.	N/A	N/A
2003/0120277	12/2002	Berger	N/A	N/A
2003/0130660	12/2002	Levy et al.	N/A	N/A
2004/0002759	12/2003	Ferree	N/A	N/A
2004/0093081	12/2003	Nilsson et al.	N/A	N/A

2004/0102853	12/2003	Boumann et al.	N/A	N/A
2004/0138756	12/2003	Reeder	N/A	N/A
2004/0172031	12/2003	Rubecamp et al.	N/A	N/A
2004/0220574	12/2003	Pelo et al.	N/A	N/A
2004/0220678	12/2003	Chow et al.	N/A	N/A
2004/0230193	12/2003	Cheung et al.	N/A	N/A
2005/0065589	12/2004	Schneider et al.	N/A	N/A
2005/0119757	12/2004	Hassler et al.	N/A	N/A
2005/0124990	12/2004	Teague et al.	N/A	N/A
2005/0216015	12/2004	Kreidler	606/104	B25B 15/007
2005/0251265	12/2004	Calandruccio et al.	N/A	N/A
2005/0261768	12/2004	Trieu	N/A	N/A
2005/0283159	12/2004	Amara	N/A	N/A
2006/0015181	12/2005	Elberg	N/A	N/A
2006/0036322	12/2005	Reiley	N/A	N/A
2006/0052725	12/2005	Santilli	N/A	N/A
2006/0052878	12/2005	Schmieding	N/A	N/A
2006/0074492	12/2005	Frey	N/A	N/A
2006/0084998	12/2005	Levy et al.	N/A	N/A
2006/0085075	12/2005	McLeer	N/A	N/A
2006/0147332	12/2005	Jones et al.	N/A	N/A
2006/0247787	12/2005	Rydell et al.	N/A	N/A
2007/0038303	12/2006	Myerson et al.	N/A	N/A
2007/0123993	12/2006	Hassler et al.	N/A	N/A
2007/0142920	12/2006	Niemi	N/A	N/A
2007/0156241	12/2006	Reiley et al.	N/A	N/A
2007/0162018	12/2006	Jensen et al.	N/A	N/A
2007/0185584	12/2006	Kaufmann et al.	N/A	N/A
2007/0198088	12/2006	Biedermann et al.	N/A	N/A
2007/0213831	12/2006	de Cubber	N/A	N/A
2007/0233110	12/2006	Muhanna et al.	N/A	N/A
2007/0239158	12/2006	Trieu et al.	N/A	N/A
2008/0039949	12/2007	Meesenburg et al.	N/A	N/A
2008/0132894	12/2007	Coilard-Lavirotte et al.	N/A	N/A
2008/0154385	12/2007	Trail et al.	N/A	N/A
2008/0177262	12/2007	Augoyard et al.	N/A	N/A
2008/0177291	12/2007	Jensen et al.	N/A	N/A
2008/0195219	12/2007	Wiley et al.	N/A	N/A
2008/0221697	12/2007	Graser	N/A	N/A
2008/0221698	12/2007	Berger	N/A	N/A
2008/0234763	12/2007	Patterson et al.	N/A	N/A
2008/0269908	12/2007	Warburton	N/A	N/A
2009/0005821	12/2008	Chirico et al.	N/A	N/A
2009/0012564	12/2008	Chirico et al.	N/A	N/A
2009/0018556	12/2008	Prandi	N/A	N/A
2009/0138096	12/2008	Myerson et al.	N/A	N/A
2009/0254189	12/2008	Scheker	N/A	N/A
2009/0254190	12/2008	Gannoe et al.	N/A	N/A
2010/0010637	12/2009	Pequignot	N/A	N/A

2010/0016905	12/2009	Greenhalgh et al.	N/A	N/A
2010/0016982	12/2009	Solomons	N/A	N/A
2010/0057214	12/2009	Graham et al.	N/A	N/A
2010/0121390	12/2009	Kleinman	N/A	N/A
2010/0131014	12/2009	Peyrot	N/A	N/A
2010/0131072	12/2009	Schulte	N/A	N/A
2010/0161068	12/2009	Lindner et al.	N/A	N/A
2010/0185295	12/2009	Emmanuel	N/A	N/A
2010/0228301	12/2009	Greenhalgh et al.	N/A	N/A
2010/0249942	12/2009	Goswami et al.	N/A	N/A
2010/0256731	12/2009	Mangiardi	N/A	N/A
2010/0256770	12/2009	Hakansson et al.	N/A	N/A
2010/0262254	12/2009	Lawrence et al.	N/A	N/A
2011/0004317	12/2010	Hacking et al.	N/A	N/A
2011/0093084	12/2010	Morton	N/A	N/A
2011/0093085	12/2010	Morton	N/A	N/A
2011/0144644	12/2010	Prandi et al.	N/A	N/A
2011/0208304	12/2010	Justin et al.	N/A	N/A
2011/0301652	12/2010	Reed et al.	N/A	N/A
2011/0301653	12/2010	Reed et al.	N/A	N/A
2012/0029579	12/2011	Bottlang et al.	N/A	N/A
2012/0065692	12/2011	Champagne et al.	N/A	N/A
2012/0083791	12/2011	Cheney et al.	N/A	N/A
2012/0089197	12/2011	Anderson	N/A	N/A
2012/0197311	12/2011	Kirschman	N/A	N/A
2012/0259419	12/2011	Brown et al.	N/A	N/A
2013/0053975	12/2012	Reed et al.	N/A	N/A
2013/0060295	12/2012	Reed et al.	N/A	N/A
2013/0066435	12/2012	Averous et al.	N/A	N/A
2013/0123862	12/2012	Anderson et al.	N/A	N/A
2013/0131822	12/2012	Lewis et al.	N/A	N/A
2013/0150965	12/2012	Taylor et al.	N/A	N/A
2013/0190761	12/2012	Prandi et al.	N/A	N/A
2013/0190831	12/2012	Ek et al.	N/A	N/A
2013/0231744	12/2012	Taylor et al.	N/A	N/A
2013/0317559	12/2012	Leavitt et al.	N/A	N/A
2013/0325077	12/2012	Champagne et al.	N/A	N/A
2014/0005219	12/2013	Foster et al.	N/A	N/A
2014/0039630	12/2013	Peyrot et al.	N/A	N/A
2014/0058462	12/2013	Reed et al.	N/A	N/A
2014/0107712	12/2013	Fallin et al.	N/A	N/A
2014/0142715	12/2013	McCormick	N/A	N/A
2014/0180428	12/2013	McCormick	N/A	N/A
2014/0188239	12/2013	Cummings	N/A	N/A
2014/0257509	12/2013	Dacosta et al.	N/A	N/A
2014/0276827	12/2013	Roman et al.	N/A	N/A
2014/0277554	12/2013	Roman et al.	N/A	N/A
2014/0309747	12/2013	Taylor et al.	N/A	N/A
2014/0316474	12/2013	Graham	N/A	N/A
2014/0343615	12/2013	Cheney et al.	N/A	N/A



2015/0011998	12/2014	McCormick et al.	N/A	N/A
2015/0066097	12/2014	Biedermann	N/A	N/A
2015/0073413	12/2014	Palmer et al.	N/A	N/A
2015/0094778	12/2014	McCormick et al.	N/A	N/A
2015/0112341	12/2014	Penzimer et al.	N/A	N/A
2015/0112342	12/2014	Penzimer et al.	N/A	N/A
2015/0112446	12/2014	Melamed et al.	N/A	N/A
2015/0150607	12/2014	Chen et al.	N/A	N/A
2015/0164563	12/2014	Lewis et al.	N/A	N/A
2015/0223848	12/2014	McCormick	N/A	N/A
2015/0223849	12/2014	McCormick et al.	N/A	N/A
2015/0223850	12/2014	Reed	N/A	N/A
2015/0223853	12/2014	Appenzeller et al.	N/A	N/A
2015/0342655	12/2014	Reed et al.	N/A	N/A
2016/0058484	12/2015	McCombs-Stearnes et al.	N/A	N/A
2016/0338751	12/2015	Kellar et al.	N/A	N/A
2017/0065310	12/2016	Girod et al.	N/A	N/A
2017/0239059	12/2016	Boublil et al.	N/A	N/A
2017/0252084	12/2016	Anderson et al.	N/A	N/A
2017/0333081	12/2016	Cordier et al.	N/A	N/A
2018/0021145	12/2017	Seavey et al.	N/A	N/A
2018/0161170	12/2017	Petranto	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
2551021	12/2004	CA	N/A
2243699	12/2005	CA	N/A
2836654	12/2013	CA	N/A
2837497	12/2013	CA	N/A
0042808	12/1980	EP	N/A
0340159	12/1988	EP	N/A
0420794	12/1990	EP	N/A
0454645	12/1990	EP	N/A
1300122	12/2002	EP	N/A
1356794	12/2002	EP	N/A
1582159	12/2004	EP	N/A
1923012	12/2007	EP	N/A
2228015	12/2010	EP	N/A
2471477	12/2011	EP	N/A
2471478	12/2011	EP	N/A
2544633	12/2012	EP	N/A
2749236	12/2013	EP	N/A
2663838	12/1991	FR	N/A
2725126	12/1995	FR	N/A
2783702	12/1999	FR	N/A
2787313	12/1999	FR	N/A
2794019	12/1999	FR	N/A
2801189	12/2000	FR	N/A
2846545	12/2003	FR	N/A

2856269	12/2003	FR	N/A
2884406	12/2005	FR	N/A
2927529	12/2008	FR	N/A
2935601	12/2009	FR	N/A
2957244	12/2010	FR	N/A
2119655	12/1982	GB	N/A
2430625	12/2006	GB	N/A
S60145133	12/1984	JP	N/A
03001854	12/1990	JP	N/A
H7303662	12/1994	JP	N/A
2004535249	12/2003	JP	N/A
3648687	12/2004	JP	N/A
2007530194	12/2006	JP	N/A
2008188411	12/2007	JP	N/A
2008537696	12/2007	JP	N/A
4695511	12/2010	JP	N/A
5631597	12/2013	JP	N/A
5645826	12/2013	JP	N/A
20070004513	12/2006	KR	N/A
20070022256	12/2006	KR	N/A
101004561	12/2010	KR	N/A
101235983	12/2012	KR	N/A
9116014	12/1990	WO	N/A
9625129	12/1995	WO	N/A
9641596	12/1995	WO	N/A
9726846	12/1996	WO	N/A
9733537	12/1996	WO	N/A
0117445	12/2000	WO	N/A
03084416	12/2002	WO	N/A
2005020830	12/2004	WO	N/A
2005020831	12/2004	WO	N/A
2005063149	12/2004	WO	N/A
2005104961	12/2004	WO	N/A
2006109004	12/2005	WO	N/A
2007135322	12/2006	WO	N/A
2008057404	12/2007	WO	N/A
2008112308	12/2007	WO	N/A
2008129214	12/2007	WO	N/A
2009055952	12/2008	WO	N/A
2009103085	12/2008	WO	N/A
2010029246	12/2009	WO	N/A
2011082343	12/2010	WO	N/A
2011110784	12/2010	WO	N/A
2011116078	12/2010	WO	N/A
2011130229	12/2010	WO	N/A
2012089330	12/2011	WO	N/A
2012089331	12/2011	WO	N/A
2013164819	12/2012	WO	N/A
2014031947	12/2013	WO	N/A
2014165123	12/2013	WO	N/A

**OTHER PUBLICATIONS**

Pietrzak WS, et al., "A bioabsorbable fixation implant for use in proximal interphalangeal joint (hammer toe) arthrodesis: Biomechanical testing in a synthetic bone substrate". J Foot Ankle Surg. Sep.-Oct. 2006;45(5):288-94. doi: 10.1053/j.jfas.2006.05.004. PMID: 16949524. 7 pgs. [Exhibit No. 1007 to Petition for Inter Partes Review of U.S. Pat. No. 9,168,074]. cited by applicant

The American Heritage College Dictionary, Fourth Edition, Houghton Mifflin Company (Apr. 2007). 3 pgs. [Exhibit No. 1008 to Petition for Inter Partes Review of U.S. Pat. No. 9,168,074]. cited by applicant

Cross section, <<https://byjus.com/maths/cross-section/>> (last visited Jan. 26, 2022). 4 pgs. [Exhibit No. 1009 to Petition for Inter Partes Review of U.S. Pat. No. 9,168,074]. cited by applicant

Declaration of Michael Sherman (Jan. 28, 2022). 119 pgs. [Exhibit No. 1002 to Petition for Inter Partes Review of U.S. Pat. No. 9,168,074]. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 9,168,074 , *OsteoMed LLC v. Stryker European Operations Holdings LLC*. (Jan. 28, 2022). 98 pgs. cited by applicant

Patent Owner's Preliminary Response and Exhibits List, IPR2022-00486 of U.S. Pat. No. 9,168,074 , *OsteoMed LLC v. Stryker European Operations Holdings LLC*. (Filed May 16, 2022), 77 pages. [Including Appendices at Exhibits 2003 and 2004]. cited by applicant

Collins English Dictionary Excerpt (Jun. 2007), 6 pages. [Exhibit No. 2001 to Patent Owner's Preliminary Response, IPR2022-00486 of U.S. Pat. No. 9,168,074 filed May 16, 2022]. cited by applicant

Excerpt from Tool.com—File and Rasp Tools, (Copyright 2022), 6 pages. [Exhibit No. 2002 to Patent Owner's Preliminary Response, IPR2022-00486 of U.S. Pat. No. 9,168,074 filed May 16, 2022]. cited by applicant

Jung, H. J. et al., JJ., Decision Denying Institution of Inter Partes Review, IPR2022-00486 of U.S. Pat. No. 9,168,074 , *OsteoMed LLC v. Stryker European Operations Holdings LLC*. (Aug. 12, 2022). 42 pages. cited by applicant

HammerFix IP Fusion System, Hammertoe Deformity Surgical Technique, designed by Extremity Medical, published Mar. 31, 2014 (8 pages). cited by applicant

Intraosseous Fixation System, Hammertoe Surgical Technique, designed by OrthoHelix, published Aug. 23, 2012 (16 pages). cited by applicant

International Search Report for PCT/FR2008/050453 dated Nov. 4, 2008, 4 pages. cited by applicant

International Search Report, PCT/FR2006/050345, dated Aug. 30, 2006, 3 pages. cited by applicant

Japanese Office Action for Application No. 2011-526540 dated Aug. 13, 2013, 3 pages. cited by applicant

EP Notification for Application No. 09741356.1 dated Feb. 12, 2015, 4 pages. cited by applicant

---

*Primary Examiner:* Ganesan; Suba

*Attorney, Agent or Firm:* Lerner David LLP

---

**Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATION (1) The present application is a continuation of U.S. patent application Ser. No. 16/891,732, filed on Jun. 3, 2020 which is a divisional of U.S. patent application Ser. No. 15/669,370, filed on Aug. 4, 2017, which is a

## TECHNICAL FIELD

(1) The present disclosure relates generally to orthopedic implants. More particularly, the present disclosure relates to orthopedic implants for surgically repairing joints and methods of implanting and removing same.

## BACKGROUND OF THE INVENTION

(2) A hammertoe is condition in which the proximal interphalangeal joints of the second, third, fourth, or fifth toe has become deformed, thereby causing the toe to be permanently bent. Hammertoe occurs from a muscle and ligament imbalance around the joints between the toes, which causes the joints to bend and become stuck in a bent position. Hammertoe oftentimes causes painful rubbing and irritation on the top of the bent toe. If caring for any callouses or corns, changing ones footwear, and/or utilizing cushions, supports, or comfort devices in ones shoes do not alleviate the pain associate with hammertoe, surgical intervention may be required to alleviate the pain. A procedure may be utilized to anatomically correct the joint using a pin, screw, or other implant. After anatomical correction, fusion or bony consolidation of the joint area occurs.

## SUMMARY OF THE INVENTION

(3) The present application discloses one or more of the features recited in the appended claims and/or the following features which alone or in any combination, may comprise patentable subject matter.

(4) According to a first aspect of the present disclosure, an orthopedic implant may include a proximal segment comprising at least three spring arms forming an anchored barb at a first end of the implant, wherein first threading extends around outer surfaces of at least a portion of each spring arm and the first threading includes minor and major diameters. The surgical implant may further include a distal segment extending between the proximal segment and a second end of the implant and including second threading extending along at least a portion of the distal segment.

(5) In some embodiments, at least two of the major diameters of the first threading may increase between the distal segment and the first end of the implant.

(6) In some embodiments, each of the major diameters of the first threading may increase between the distal segment and the first end of the implant.

(7) In some embodiments, the proximal segment may be configured to be implanted within a proximal phalanx of a patient and the distal segment may be configured to be threaded into a middle phalanx of the patient.

(8) In some embodiments, the surgical implant may include a marking disposed on the surgical implant between the proximal and distal segments, wherein the marking may be configured to identify an optimal depth for implantation of the distal segment of the implant into a middle phalanx of a patient.

(9) In some embodiments, the implant may be manufactured of polyetheretherketone (PEEK).

(10) In some embodiments, the second threading may include minor diameters and major diameters and at least two of the minor diameters may increase between the second end and the proximal segment.

(11) In some embodiments, each of the minor diameters of the second threading may increase between the second end and the proximal segment.

(12) In some embodiments, the proximal segment may include a drive feature formed in an end thereof that is configured to accept a tool for removal of the implant from a phalanx.

(13) According to a second aspect of the present disclosure, an orthopedic implant may include a proximal segment comprising at least two spring arms forming an anchored barb at a first end of the implant, wherein first threading may extend around outer surfaces of at least a portion of each spring arm and the first threading may include minor and major diameters. The surgical implant

may further include a distal segment extending between the proximal segment and a second end of the implant and include second threading extending along at least a portion of the distal segment, wherein the second threading may include minor and major diameters and at least two of the minor diameters may increase between the second end and the proximal segment.

(14) In some embodiments, each of the minor diameters of the second threading of the distal segment may increase between the second end and the proximal segment.

(15) In some embodiments, each of the major diameters of the first threading of the proximal segment may increase between the distal segment and the first end of the implant.

(16) In some embodiments, the proximal segment may be configured to be implanted within a proximal phalanx of a patient and the distal segment may be configured to be threaded into a middle phalanx of the patient.

(17) In some embodiments, a marking may be disposed on the surgical implant between the proximal and distal segments, wherein the marking may be configured to identify an optimal depth for implantation of the distal segment of the implant into a middle phalanx of a patient.

(18) In some embodiments, the implant may be manufactured of polyetheretherketone (PEEK).

(19) In some embodiments, the proximal segment may include at least three spring arms forming the anchored barb at the first end of the implant.

(20) In some embodiments, the proximal segment may include a drive feature formed in an end thereof that is configured to accept a tool for removal of the implant from a phalanx.

(21) According to a third aspect of the present disclosure, a method of removing an orthopedic implant from a patient may include the step of severing an orthopedic implant in a central segment of the orthopedic implant that is disposed between a proximal segment configured for implantation within a proximal phalanx of the patient and a distal segment opposite the proximal segment and configured for implantation within a middle phalanx of the patient. The method may further include the steps of inserting a tool into the proximal or distal segment of the orthopedic implant and rotating the tool to remove the proximal or distal segment from the proximal or middle phalanx, respectively.

(22) In some embodiments, the method may include one or more of the steps of severing the implant, inserting the tool, which is made of a high-strength stainless steel, into the distal segment, which is made of a polymeric material, to thereby tap the tool into the distal segment, and removing the distal segment from the middle phalanx.

(23) In some embodiments, the method may include one or more of the steps of inserting the tool into an end of the proximal segment, mating a portion of the tool with a drive feature in the proximal segment of the implant, and rotating the tool to remove at least a portion of the surgical implant.

(24) In some embodiments, the drive feature may include a plurality of semi-cylindrical channels.

(25) According to a fourth aspect, a tool for implantation of an orthopedic implant having a proximal segment with at least three arms spaced from one another by recesses, the three arms configured for implantation with a proximal phalanx of a patient and a distal segment opposite the proximal segment and configured for implantation within a middle phalanx of the patient is disclosed. The implantation tool may include a body and at least three arms extending from an end of the body, wherein each of the arms is sized and shaped to fit within one of the recesses disposed between the three arms in the proximal segment of the implant.

(26) In some embodiments, the arms may have an outer diameter that is less than an outer diameter of the arms of the proximal segment of the implant.

(27) In some embodiments, the tool may be configured to retain the proximal segment of the implant on the end of the body.

---

## Description

## BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The concepts described in the present disclosure are illustrated by way of example and not by way of limitation in the accompanying figures. For simplicity and clarity of illustration, elements illustrated in the figures are not necessarily drawn to scale. For example, the dimensions of some elements may be exaggerated relative to other elements for clarity. Further, where considered appropriate, the same or similar reference labels have been repeated among the figures to indicate corresponding or analogous elements.
- (2) FIG. 1 is an isometric view of a first embodiment of an orthopedic implant taken generally from a first end of the implant;
- (3) FIG. 2 is an elevational view of a first side of the implant of FIG. 1;
- (4) FIG. 3 is an elevational view of a second side of the implant of FIG. 1, wherein the second side is opposite the first side depicted in FIG. 2;
- (5) FIG. 4 is an elevational view of the first end of the implant of FIG. 1;
- (6) FIG. 5 is a cross-sectional view of the implant of FIG. 1 taken generally along the lines 5-5 of FIG. 4;
- (7) FIG. 6 is an isometric view of a second embodiment of an orthopedic implant taken generally from a first end of the implant;
- (8) FIG. 7 is an elevational view of a first side of the implant of FIG. 6;
- (9) FIG. 8 is an elevational view of a second side of the implant of FIG. 6, wherein the second side is opposite the first side depicted in FIG. 7;
- (10) FIG. 9 is an elevational view of the first end of the implant of FIG. 6;
- (11) FIG. 10 is an elevational view of a second end of the implant of FIG. 7, wherein the second end is opposite the first end;
- (12) FIG. 11 is a cross-sectional view of the implant of FIG. 6 taken generally along the lines 11-11 of FIG. 9;
- (13) FIG. 12 is a view depicting a tap advanced over a distal Kirschner wire (K-wire) into a middle phalanx of a patient during a first method of implantation of an orthopedic implant disclosed herein;
- (14) FIG. 13 is a view depicting a proximal K-wire inserted into a center of a proximal phalanx of a patient and a drill advanced over the K-wire during the first method of implantation of an orthopedic implant;
- (15) FIG. 14A is a view depicting a second end of a distal segment of an orthopedic implant threaded into the middle phalanx of a patient during the first method of implantation of an orthopedic implant utilizing an implantation tool;
- (16) FIG. 14B is a perspective view of a drive end of the implantation tool shown in use in FIG. 14A, wherein the implantation tool is utilized to thread the distal segment of the orthopedic implant into the middle phalanx;
- (17) FIG. 15 is a view depicting insertion of a barbed anchor disposed at a first end of a proximal segment of an orthopedic implant into a pre-drilled hole in the proximal phalanx of the patient during the first method of implantation of an orthopedic implant;
- (18) FIG. 16 is a view depicting a method of removing a distal segment of an orthopedic implant in which a threaded tool is utilized to tap an inner surface of the distal segment;
- (19) FIG. 17 is a view depicting a method of removing an orthopedic implant in which a tool having a drive features is utilized in combination with a complementary drive feature within a proximal segment of an orthopedic implant to remove the implant; and
- (20) FIGS. 18A and 18B are views depicting bending axes for orthopedic implants having two and three arms, respectively.

## DETAILED DESCRIPTION

- (21) While the concepts of the present disclosure are susceptible to various modifications and

alternative forms, specific exemplary embodiments thereof have been shown by way of example in the figures and will herein be described in detail. It should be understood, however, that there is no intent to limit the concepts of the present disclosure to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the present disclosure.

(22) A first embodiment of an orthopedic implant **20** suitable for treatment and correction of hammertoe is depicted in FIGS. **1-5**. The implant **20** generally includes a pin-shaped body **22** extending along a longitudinal axis **24** and further includes a proximal segment **26** terminating in a first end **28** and a distal segment **30** terminating in a second end **32**. The proximal and distal segments **26, 30** may be integral with one another and joined at a central, narrowed segment **34** of the implant **20**. The proximal segment **26** of the body **22** may generally comprise the central, narrowed segment **34** and three spring arms **36** that form a barbed anchor **38** and which extend away from the central, narrowed segment **34**. While the segment **34** is depicted as being narrowed, the segment **34** may alternatively not be narrowed or may have a constant outer diameter.

(23) As seen in FIGS. **1, 2, and 4**, each of the arms **36** is separated from adjacent arms **36** by a channel **40**. Helical threading **41** may be disposed about outer edges or surfaces **42** of each of the arms **36** and may continue between arms **36** (despite the existence of channels **40** therebetween). Each of the arms **36** is formed by opposing side edges **44** that, with side edges **44** of adjacent arms **36**, form the channels **40**. As seen in FIGS. **2 and 6**, each side edge **44** is formed of a straight segment **46** that is generally parallel to a longitudinal axis **24** of the implant **20** and a tapered segment **50** that tapers outwardly from the straight segment **46** at an angle **A1** of greater than 0 degrees to a tip forming a flattened edge **54**. In an illustrative embodiment, the angle **A1** may be between about 1 degree and about 15 degrees. In another illustrative embodiment, the angle **A1** may be between about 3 degrees and about 10 degrees. In a further illustrative embodiment, the angle **A1** may be about 7 degrees. As seen in FIG. **4**, each arm **36** further includes a generally cylindrical inner edge **56** (FIG. **4**) that tapers outwardly from an inner, generally cylindrical surface **57** of the proximal segment **26**. The tapered segment **50** and the inner edge **56** are tapered to thin out the arms **36** to provide a desired stiffness and even stress distribution for each of the arms **36**.

(24) The use of three arms **36** provides more resistance to bending of the arms **36** along various axes that are perpendicular to the longitudinal axis **24**. Less bending equates to higher contact forces and improved fixation. Three arms **36** also stabilize the bone in which implantation occurs more than two arms, since two arms leave a weak bending axis.

(25) Currently, a number of hammertoe implant designs incorporate two spring arms for retention in the proximal phalanx, the middle phalanx, or both. Designs with two arms are intrinsically easier to manufacture through machining and may be easier to insert into the bone, as well. It has been discovered in the present invention that designs with multiple arms, for example, those with an odd number of arms, impart a strong advantage to implant fixation in the bone. Implant fixation into the bone is a common failure mode because bone in older hammertoe patients is oftentimes osteopenic and poorly supports an interface with the implant. The key to implant stability is the ability of the implant to uniformly impart stresses to the underlying bone. The loading vector for a hammertoe implant is predominantly in the dorsal-plantar direction as the foot moves through the gait cycle, however, complex tri-axial stresses also occur in all planes as the foot pushes laterally or moves over uneven surfaces. The objective of the implant designer should be to create a design that retains strength and fixation even in a tri-axial stress state.

(26) A two-arm implant design, as seen in FIG. **18A**, has a weak bending axis **55a** on a plane of symmetry between the two arms. This weak axis **55a** imparts a deficiency to the design in resisting tri-axial stresses, particularly when the dorsal-plantar loading vector is aligned perpendicularly to a vector of the arm spring force **59a**. In this case, the spring arms contribute little to the stability of the implant in the bone.

(27) As seen in FIG. **18B**, a three-arm implant design still has weak bending axis **55b**, but the weak

bending axis **55b** is not as weak as the weak bending axis **55a** of the two-arm design since there are now arms at more angular positions along a diameter of the implant. Even if a weak axis **55b** of the implant is aligned with the dorsal-plantar loading vector, there are portions of the adjacent spring arms that directly contribute to resistance on the loading vector. This advantage is shared by all arm designs having three or more arms, although odd-numbered arm designs convey a particular evenness between the strong and weak axes. Additionally, with odd-numbered arm designs, the dorsal-plantar loading vector is not aligned perpendicularly to the vector of the arms spring force **59b**. An additional advantage of a three-arm design is that it self-centers in a center of a hole in the bone in which it is implanted.

(28) Referring to FIG. 6, the inner surface **57** of the proximal segment **26** has an inner diameter **58** that does not vary along a first section **62** that includes both the central, narrowed segment **34** and a portion of the arms **36**. The inner surface **58** further includes a second section **64** that includes the generally cylindrical surface **57** of the arms **36** and which has a diameter **65** that increases along the longitudinal axis **24** from the central segment **34** toward the first end **28**. The arms **36**, as seen in FIG. 6, include outer edges **42** that, due to the helical threading **41**, have minor diameters **66a-66e** and major diameters **68a-68e**. The minor diameters **66a-66e** of the helical threading **41** may be constant in that the diameters thereof do not vary along a length of the threading **41**. The major diameters **68a-68e** of the helical threading **41** may increase from a first major diameter **68a** closest the central segment **34** toward the first end **28** of the proximal segment **30**. More particularly, a major diameter **68a** of the threading **41** may be smaller than each of the other major diameters **68b-68e** and the major diameters **68b-68e** may each increase between the central segment **34** and the first end **28**. An increasing major diameter **68a-68e** maximizes bony contact during insertion of the second end **28** of the implant **20** into a proximal phalanx, as discussed in more detail below. In other illustrative embodiments, two or more consecutive or non-consecutive major diameters **68a-68e** may be increasing between the major diameter **68a** and the major diameter **68e** and/or two or more consecutive or non-consecutive major diameters **68a-68e** may be the same.

(29) Referring again to FIG. 6, the distal segment **30** includes an inner cylindrical surface **80** having an inner diameter **82**. The inner diameter **82** may be the same or different than the inner diameter **58** of the proximal segment **26**. Helical threading **84** may be disposed on an outer surface **86** of all or a portion of the distal segment **30**. As seen in FIG. 6, the helical threading **84** includes minor diameters **88a-88e** and major diameters **92a-92e**, wherein the minor diameters **88a-88e** may increase along the longitudinal axis **24** of the implant **20** between the second end **32** and the first end **28**. More particularly, a minor diameter **88a** of the threading **84** may be smaller than each of the other minor diameters **88b-88e** and the minor diameters **88a-88e** may increase between minor diameter **88a** and minor diameter **88e**. Increasing minor diameters **88a-88e** provide tactile feedback when implanting the distal segment **30** of the implant **20** into a middle phalanx, as discussed in greater detail below. In alternative illustrative embodiments, two or more consecutive or non-consecutive minor diameters **88a-88e** may increase between minor diameter **88a** and minor diameter **88e** and/or two or more consecutive or non-consecutive minor diameters **88a-88e** may be same. Major diameters **92a-92e** of the helical threading **84** may increase in diameter from the major diameter **92a** to the major diameter **92e** or the major diameters **92a-92e** may be the same. Still alternatively, two or more consecutive or non-consecutive major diameters **92a-92e** may be increasing between the major diameters **92a** and the major diameter **92e** and/or two or more consecutive or non-consecutive major diameters **92a-92e** may be the same.

(30) While a particular number of threads are depicted for the threading **41** and **84**, any number of threads may be present depending on a particular application for the implant **20**.

(31) A second embodiment of an orthopedic implant **220** suitable for treatment and correction of hammertoe is depicted in FIGS. 6-11. The implant **220** generally includes a pin-shaped body **222** extending along a longitudinal axis **224** and further includes a proximal segment **226** terminating in a first end **228** and a distal segment **230** terminating in a second end **232**. The proximal and distal



segments **226**, **230** may be integral with one another and joined at a central, cylindrical flattened segment **234** of the implant **220**. The proximal segment **226** of the body **222** may generally comprise the central flattened segment **234** and three arms **236** that form a barbed anchor **238** and which extend away from the central, flattened segment **234**.

(32) As seen in FIGS. 5, 6, 7, and 9, each of the arms **236** is separated from adjacent arms **236** by a channel **240**. Helical threading **241** may be disposed about outer edges or surfaces **242** of each of the arms **236** and may continue between arms **236** (despite the existence of channels **240** therebetween). Each of the arms **236** is formed by opposing side edges **244** that, with side edges **244** of adjacent arms **236**, form the channels **240**. As seen in FIGS. 7 and 12, each side edge **244** tapers outwardly at an angle **A2** of greater than 0 degrees to a tip forming a flattened edge **254**. In an illustrative embodiment, the angle **A2** may be between about 1 degree and about 15 degrees. In another illustrative embodiment, the angle **A2** may be between about 3 degrees and about 10 degrees. In a further illustrative embodiment, the angle **A2** may be about 7 degrees. As seen in FIGS. 6 and 10, each arm **236** further includes an inner, generally cylindrical edge **256** that tapers outwardly from an inner, generally cylindrical surface **258** of the proximal segment **226**.

(33) Referring to FIG. 11, the inner surface **258** of the proximal segment **226** has an inner diameter **259** that may not vary along a first section **262** and that may include both the central segment **234** and a portion of the arms **236**. The inner diameter **258** may further include a second section **264** that includes at least a portion of the arms **236** and which has a diameter **265** that increases along the longitudinal axis **224** from the central segment **234** toward the first end **228**. The arms **236**, as seen in FIG. 11 include helical threading **241** that has minor diameters **266a-266e** and major diameters **268a-268e**. The minor diameters **266a-266e** of the helical threading **41** may be constant in that the diameters thereof do not vary along a length of the threading **241** or the minor diameters **266a-266e** may have different or varying diameters. The major diameters **268a-268e** of the helical threading **41** may be constant in that the diameters thereof do not vary along a length of the threading **241** or the major diameters **268a-268e** may have different or varying diameters. In illustrative embodiments and similar to the embodiment of FIGS. 1-5, the major diameters **268a-286e** may increase from a first major diameter **268a** closest the central segment **234** toward the first end **228** of the proximal segment **230**. In other illustrative embodiments, two or more consecutive or non-consecutive major diameters **268a-268e** may be increasing between the major diameter **268a** and the major diameter **268e** and/or two or more consecutive or non-consecutive major diameters **268a-268e** may be the same.

(34) Referring again to FIG. 11, the distal segment **230** includes an inner cylindrical surface **280** having an inner diameter **282**. The inner diameter **282** may be constant or may vary along the longitudinal axis **224**. The inner diameter **282** may be the same as or less than the inner diameter **259** of the proximal segment **226**. Helical threading **284** may be disposed on an outer surface **286** of all or a portion of the distal segment **230**. As seen in FIG. 11, a minor diameter **288a-288e** of the helical threading **284** may be the same for each thread or may increase along the longitudinal axis **224** of the implant **220** from the second end **232** toward the first end **228**, as discussed above with respect to the embodiment of FIGS. 1-5. In other illustrative embodiments, two or more consecutive or non-consecutive minor diameters **288a-288e** may be increasing between the minor diameter **288a** and the minor diameters **288e** and/or two or more consecutive or non-consecutive minor diameters **288a-288e** may be the same.

(35) Major diameters **292a-292e** of the helical threading **284** may increase in diameter from the major diameter **292a** to the major diameter **292e** or the major diameters **292a-292e** may be the same. Still alternatively, two or more consecutive or non-consecutive major diameters **292a-292e** may be increasing between the major diameters **292a** and the major diameter **292e** and/or two or more consecutive or non-consecutive major diameters **292a-292e** may be the same.

(36) While a particular number of threads are depicted for the threading **241** and **284**, any number of threads may be present depending on a particular application for the implants **20**, **220**.

(37) Implantation of the implants **20**, **220** will now be discussed in detail. Prior to implantation, the proximal interphalangeal (PIP) joint of the patient is opened using, for example, a dorsal approach. A head of a proximal phalanx **104** of the patient is prepared by reaming until bleeding bone is reached, for example, using a proximal phalanx reamer and a base of a middle phalanx **100** of the patient is also reamed until bleeding bone is reached, for example, using a middle phalanx reamer. Once the middle phalanx **400** is reamed, a distal K-wire may be inserted into a center of the middle phalanx **400**. As seen in FIG. **12**, tap **410** of the appropriate size **410** is selected for the desired implant size and, using firm axial pressure, the tap **410** is advanced over the distal K-wire into the middle phalanx **100** until a laser line **412** on the tap **410** is level with an outer surface **414** of the middle phalanx **400**. A proximal K-wire **416** may be inserted into a center of the proximal phalanx **404**, as seen in FIG. **13**. In an illustrative embodiment, the K-wire **416** may be introduced at a 10 degree angle plantar to a medial axis of the proximal phalanx **404**. An appropriate drill size may be selected and advanced over the K-wire **416** into the proximal phalanx **404** until a laser line **420** on the drill **418** is level with an outer surface **422** of the proximal phalanx **404**, as seen in FIG. **13**, and the proximal K-wire **416** may be removed after drilling.

(38) The second end **32**, **232** of the distal segment **30**, **230** of either implant **20**, **220** is threaded into the middle phalanx **400** of the patient, as seen in FIG. **14A**, using an implantation tool **500**, until an increase in torque indicates firm seating of the implant **20**, **220**. Additionally, an outer edge of the middle phalanx **400** may be aligned with a laser line **402** positioned between the proximal and distal segments **26** or **226**, **30** or **230** and should be facing dorsally. The laser line **402** is formed of one or more of a black burn, engraving, one or more dyes, or any other suitable substance capable of creating a line, marker, or other indicator. The laser line **402** provides guidance to a surgeon or other healthcare professional such that the distal segment **30**, **230** of the implant **20**, **220** is threaded into the middle phalanx **400** to an optimal or ideal depth. The laser lines on the tap **410** and the drill **418** additionally prepare the bone for insertion of the implant **20**, **220** to an appropriate depth.

(39) The implantation tool **500**, as best seen in FIG. **14B**, may include a generally cylindrical body **502**, although, the body **502** need not be cylindrical. Three arms **504** extend outwardly from a first end **506** of the body **502**. Each of the arms **504** includes a wider based **508** that tapers into a narrowed tip **510**. The arms **504** are sized and shaped to be complementary to and fit within the channels **40**, **240** formed by the arms **36**, **236** of the implant **20**, **220**, as seen in FIG. **14A**. In illustrative embodiments, the implantation tool **500** may retain the implant **20**, **220** on the first end **506** by, for example, an interference fit. In other illustrative embodiments, the implantation tool **500** may fit within the implant **20**, **220**, but may not retain the implant **20**, **220** on the first end **506**.

(40) As may be seen in FIG. **14A**, an outer diameter of the arms **504** of the implantation tool **500** is fully within an outer or major diameter of the threads **68a-68e**, **268a-268e**. Each of the arms **504** may also include a laser mark **512** that denote which way the implant arms **36**, **236** are oriented. As one skilled in the art will understand, if an implant includes more than three arms/three recesses, the implantation tool **500** may include a similar number of arms.

(41) After the distal segment **30**, **230** is implanted within the middle phalanx **400** and the distal K-wire **416** is removed, the proximal segment **26**, **226** of the implant **20**, **220** is aligned with a proximal phalanx **404** of the patient. More specifically, the barbed anchor **38**, **238** at the first end **28**, **228** of the proximal segment **26**, **226** is aligned with and inserted into the pre-drilled hole in the proximal phalanx **404**, as seen in FIG. **15**. The proximal segment **26**, **226** is thereafter pressed into the proximal phalanx **404**. Once both the proximal and distal segments **26** or **226**, **30** or **230** are implanted within the proximal and middle phalanges **404**, **400**, respectively, a typical surgical procedure is used to close the patient.

(42) Oftentimes, implants, such as implant **20**, **220** or any of the implants disclosed herein, must be removed and replaced (during, for example, a revision surgical procedure). It can be very difficult to remove the distal and/or proximal segments **30** or **230**, **26** or **226** from the middle and proximal phalanges **400**, **404**, respectively. The implant **20**, **220** may be provided with features that allow for

easier removal of the implant **20, 220** from the middle and proximal phalanges **400, 404**. More particularly, in illustrative embodiments, the implant **20, 220** may be manufactured of a polymeric material, for example, ultra-high molecular weight polyethylene (UHMWPE), polyetheretherketone (PEEK), or any other suitable polymeric material. The central segment **34, 234** of the implant **20, 220** may be cut to sever the proximal and distal segments **26** or **226, 30** or **230** from one another. In illustrative embodiments, the central segment **34, 234** may be cut at a point **130** adjacent the distal segment **30, 230**.

(43) In illustrative embodiments, once the implant, for example, the implant **20**, is severed, a tool **440** that is made of a high-strength material, for example, stainless steel, having threading **442** may be threaded into the distal segment **30**. In illustrative embodiments, the threading **442** on the tool **440** taps out the inner cylindrical surface **80** of the distal segment **30** such that opposing threads are created therein. Once the tool **440** is threaded a sufficient distance into the distal segment **30**, the tool **440** may be threaded or pulled in a direction **444** opposite the direction of threading to remove the distal segment **30** from the middle phalanx **400**. In a similar manner, the tool **440** may be threaded into the proximal segment **26**, for example, such that the threading **442** on the tool **440** taps out an inner surface **446** of the central segment **34** and/or the proximal segment **26**, thereby creating opposing threads therein. Once the tool **440** is threaded a sufficient distance into the proximal segment **26**, the tool **440** may be threaded or pulled in a direction opposite the direction of threading to remove the proximal segment **26** from the proximal phalanx **404**.

(44) In other illustrative embodiments, the implant, for example, the implant **220**, may include a proximal segment **226** having an internal drive feature **450** (see FIG. 9) that mates with a tool **452** such that, upon rotation of the tool **452**, the distal segment **230** may be threaded out of the bore in which it was implanted. In the illustrative embodiment, the drive feature **450** may be comprised of a hexalobe bore formed by the cylindrical inner edge **256** that form semi-cylindrical channels and portions of the central segment **34** that form semi-cylindrical channels. Alternatively or additionally, the drive feature **450** may include any suitable feature(s) or geometr(ies) configured to accept a tool and allows for rotation of the implant **220** using the tool **452**. While six semi-cylindrical channels are depicted in FIG. 9, any suitable number of semi-cylindrical channels may be utilized.

(45) Any of the implants disclosed herein may be manufactured in different sizes, for example, for differently-sized phalanges of the same foot or phalanges of persons with differently-sized feet, toes, and/or phalanges. In an illustrative embodiment, three or more differently-sized implants may be provided, for example, small, medium, and large implants or small, medium, large, and extra-large implants. In an illustrative embodiment with small, medium, and large implants, an overall length of the small implant may be 13 millimeters, a proximal length **L1** may be 7 millimeters, and a distal length **L2** may be 6 millimeters. Similarly, an overall length of the medium implant may be 14 millimeters, the proximal length **L1** may be 7 millimeters, and the distal length **L2** may be 7 millimeters. Still further, an overall length of the large implant may be 15 millimeters, the proximal length **L1** may be 7 millimeters, and the distal length may be 8 millimeters. In other embodiments, the overall length of one or more implants may be between about 5 millimeters and about 20 millimeters.

(46) Any of the implants disclosed herein may be manufactured of one or more of metal, ultra-high molecular weight polyethylene (UHMWPE), ceramic, polyetheretherketone (PEEK), or any other suitable material or materials.

(47) While the implants disclosed in detail herein are discussed as being suitable for treatment and correction of hammertoe, the implants disclosed herein may be utilized for treatment and/or correction of other conditions, for example, other conditions in the foot or hand and/or conditions related to other joints.

(48) Any one or more features of any of the implant disclosed herein may be incorporated (alone or in combination) into any of the other implants disclosed herein.

(49) While certain illustrative embodiments have been described in detail in the figures and the foregoing description, such an illustration and description is to be considered as exemplary and not restrictive in character, it being understood that only illustrative embodiments have been shown and described and that all changes and modifications that come within the spirit of the disclosure are desired to be protected. There are a plurality of advantages of the present disclosure arising from the various features of the apparatus, systems, and methods described herein. It will be noted that alternative embodiments of the apparatus, systems, and methods of the present disclosure may not include all of the features described yet still benefit from at least some of the advantages of such features. Those of ordinary skill in the art may readily devise their own implementations of the apparatus, systems, and methods that incorporate one or more of the features of the present disclosure.

## Claims

1. An orthopedic implantation kit, comprising: an orthopedic implantation tool including: a body defining a longitudinal axis; three circumferentially spaced apart tool arms extending from the body, each of the tool arms including: a first surface extending from the body and within a first plane parallel to the longitudinal axis; and a second surface distal to and extending distally from the first surface, the second surface being within a second plane transverse to the longitudinal axis, wherein each of the first and the second surfaces extends across a full width of the arm defined within a plane extending radially from the longitudinal axis; and an orthopedic implant defining respective recesses configured to receive the three circumferentially spaced tool arms of the orthopedic implantation tool, wherein the tool arms are configured for moving and thereby causing implantation of the orthopedic implant when the tool arms are received by the recesses of the orthopedic implant.
2. The orthopedic implantation kit of claim 1, wherein the orthopedic implant includes a laser line configured to indicate alignment of the orthopedic implant with a surface of the bone.
3. The orthopedic implantation kit of claim 1, wherein each of the tool arms is inserted between respective sets of two circumferentially spaced apart implant arms of the orthopedic implant when recesses of the orthopedic implant receive the tool arms.
4. The orthopedic implantation kit of claim 3, wherein each of the tool arms includes a base and a tip that is attached to and thinner than the base, wherein the respective sets of two circumferentially spaced apart implant arms of the orthopedic implant each define a semi-cylindrical channel, and wherein the tip of each implant arm is complementary to each semi-cylindrical channel and the base is complementary to a surface wider than each semi-cylindrical channel.
5. The orthopedic implantation kit of claim 1, wherein the orthopedic implant extends between a first end and a second end opposite the first end, wherein the recesses of the orthopedic implant are positioned at the first end, and wherein the second end is threaded.
6. The orthopedic implantation kit of claim 1, wherein each of the implant arms includes a third surface within a third plane, the third plane being transverse to the second plane and the third surface being distal to the second surface, the third surface further extending from the second surface along a full width of the second surface.
7. The orthopedic implantation kit of claim 1, wherein the tool arms of the orthopedic implantation tool are configured to rotate the orthopedic implant when the recesses of the orthopedic implant receive the tool arms of the orthopedic implantation tool.
8. An orthopedic implantation kit, comprising: an orthopedic implantation tool including: a body; three tool arms extending from the body, wherein each of the tool arms defines a central plane that extends radially from the center of the implantation tool, wherein a distal end of each of the tool arms is spaced apart from the distal ends of each of the other tool arms, and wherein each of the tool arms includes a side having a plurality of surfaces defining a set of planes, each of the planes

of the set of planes of the side being parallel to or forming a different angle with respect to the central plane of the respective tool arm than the other planes of the set of planes; and an orthopedic implant defining respective recesses configured to receive the three tool arms of the orthopedic implantation tool, wherein the tool arms are configured for moving and thereby causing implantation of the orthopedic implant when the tool arms are received by the recesses of the orthopedic implant.

9. The orthopedic implantation kit of claim 8, wherein the tool arms of the orthopedic implantation tool are configured to rotate the orthopedic implant when the recesses of the orthopedic implant receive the tool arms of the orthopedic implantation tool.

10. The orthopedic implantation kit of claim 8, wherein each of the tool arms of the implantation tool is sized and shaped to be a complementary fit within a channel formed between adjacent implant arms on a first end of the implant.

11. The orthopedic implantation kit of claim 10, wherein each of the tool arms of the implantation tool has a base at a proximal end of the tool that tapers in a distal direction to a tip narrower than the base.

12. The orthopedic implantation kit of claim 8, wherein each of the tool arms includes a first surface extending from the tool body along a plane parallel to a longitudinal axis defined by the tool body, each of the tool arms further including a second surface distal to the first surface and extending along a plane parallel to the longitudinal axis, the first and the second surface spanning a full width of each of the respective tool arms.

13. The orthopedic implantation kit of claim 8, wherein each of the tool arms defines a respective tip spanning a full width of the respective tool arm.

14. An orthopedic implantation kit, comprising: an orthopedic implant extending from a first end to a second end and including: a central segment; and three circumferentially spaced bendable implant arms at the first end extending from the central segment and defining a channel between adjacent ones of the implant arms; and an orthopedic implantation tool including: tool arms sized and shaped to complementarily fit into the first end of the implant, wherein a surface of each of the tool arms contacts first and second surfaces of corresponding ones of the implant arms and each of the tool arms contacts at least two of the implant arms, and wherein the first and second surfaces of each of the implant arms define planes extending in transverse directions to each other.

15. The orthopedic implantation kit of claim 14, wherein the first surface of each of the tool arms defines a plane parallel to a longitudinal axis of the tool arm and the second surface of each of the tool arms defines a plane transverse to the respective first surface.

16. The orthopedic implantation kit of claim 14, wherein the orthopedic implant is configured to be implanted into a middle phalanx.

17. The orthopedic implantation kit of claim 14, wherein the first end of the orthopedic implant is configured to be implanted into a proximal phalanx and the second end of the orthopedic implant is configured to be threaded into a middle phalanx.

18. The orthopedic implantation kit of claim 14, wherein the second end of the implant includes an outer surface having a helical threading.

19. The orthopedic implantation kit of claim 14, wherein the orthopedic implant includes a marking configured to indicate alignment of the orthopedic implant with a surface of a bone.

20. The orthopedic implantation kit of claim 14, wherein each of the implant arms includes a barb at the first end of the implant for anchoring the implant.

---