

US Patent & Trademark Office

Patent Public Search | Text View

| | |
|----------------------|-------------------------------|
| United States Patent | 12395171 |
| Kind Code | B2 |
| Date of Patent | August 19, 2025 |
| Inventor(s) | Malladi; Venkata Naga Koushik |

Switch circuits with parallel transistor stacks and capacitor networks for balancing off-state RF voltages, and methods of their operation

Abstract

A switch circuit includes first and second transistor stacks coupled in parallel between first and second ports. The first transistor stack includes a first plurality of transistors coupled in series between the first and second ports to provide a first variably-conductive path between the first and second ports. A first network of one or more balancing capacitors includes a first capacitor coupled across multiple transistors of the first plurality of transistors. The second transistor stack includes a second plurality of transistors coupled in series between the first and second ports to provide a second variably-conductive path between the first and second ports. A second network of one or more balancing capacitors includes a second capacitor coupled across multiple transistors of the second plurality of transistors.

| | |
|-------------------|---|
| Inventors: | Malladi; Venkata Naga Koushik (Chandler, AZ) |
| Applicant: | NXP USA, Inc. (Austin, TX) |
| Family ID: | 1000008763558 |
| Assignee: | NXP USA, Inc. (Austin, TX) |
| Appl. No.: | 17/449486 |
| Filed: | September 30, 2021 |

Prior Publication Data

| | |
|----------------------------|-------------------------|
| Document Identifier | Publication Date |
| US 20220038098 A1 | Feb. 03, 2022 |

Related U.S. Application Data

continuation-in-part parent-doc US 16944612 20200731 US 11368180 child-doc US 17449486

Publication Classification

Int. Cl.: H03K17/687 (20060101); H04B1/40 (20150101)

U.S. Cl.:

CPC H03K17/6871 (20130101); H04B1/40 (20130101);

Field of Classification Search

CPC: H03K (17/6871); H03K (17/002); H03K (17/162); H03K (17/063); H04B (1/48)

References Cited

U.S. PATENT DOCUMENTS

| Patent No. | Issued Date | Patentee Name | U.S. Cl. | CPC |
|--------------|-------------|----------------------|-------------|------------------|
| 7983627 | 12/2010 | Adler et al. | N/A | N/A |
| 8008988 | 12/2010 | Yang et al. | N/A | N/A |
| 8401496 | 12/2012 | Goto et al. | N/A | N/A |
| 8536636 | 12/2012 | Englekirk | N/A | N/A |
| 9438223 | 12/2015 | de Jongh | N/A | N/A |
| 9484973 | 12/2015 | Carroll et al. | N/A | N/A |
| 9595951 | 12/2016 | Sprinkle et al. | N/A | N/A |
| 9866209 | 12/2017 | Keane et al. | N/A | N/A |
| 9893722 | 12/2017 | Mokalla | N/A | N/A |
| 10326440 | 12/2018 | Malladi | N/A | H01L 28/20 |
| 10897246 | 12/2020 | Scott et al. | N/A | N/A |
| 2011/0316062 | 12/2010 | Kondo | 257/E29.345 | H01L 29/93 |
| 2012/0112832 | 12/2011 | Kawano et al. | N/A | N/A |
| 2013/0222075 | 12/2012 | Reedy | 333/32 | H03H 7/38 |
| 2013/0288617 | 12/2012 | Kim et al. | N/A | N/A |
| 2014/0340181 | 12/2013 | Bakalski | 334/55 | H03J 5/244 |
| 2015/0116023 | 12/2014 | Keane et al. | N/A | N/A |
| 2016/0020326 | 12/2015 | Mazure | 257/365 | H01L 29/66795 |
| 2016/0285447 | 12/2015 | Krishnamurthi et al. | N/A | N/A |
| 2017/0026031 | 12/2016 | Levesque | N/A | H03H 7/1758 |
| 2018/0145678 | 12/2017 | Maxim | N/A | H03K 17/102 |
| 2018/0183431 | 12/2017 | Zhu et al. | N/A | N/A |
| 2019/0140687 | 12/2018 | Tombak | N/A | H03K 17/693 |
| 2019/0149142 | 12/2018 | Scott et al. | N/A | N/A |
| 2019/0245574 | 12/2018 | Jo et al. | N/A | N/A |

OTHER PUBLICATIONS

Shifrin, M. et.al; “High Power Control Components Using a New Monolithic FET Structure”; IEEE Microwave and Millimeter-Wave Monolithic Circuits Symposium Digest of Papers; 6 pages (1989). cited by applicant

U.S. Appl. No. 16/566,710; not yet published; 40 pages (Sep. 10, 2019). cited by applicant

U.S. Appl. No. 16/701,927; not yet published; 42 pages (Dec. 3, 2019). cited by applicant

Primary Examiner: Chen; Patrick C

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation-in-part of co-pending, U.S. patent application Ser. No. 16/944,612 filed on Jul. 31, 2020.

TECHNICAL FIELD

(1) Embodiments of the subject matter described herein relate generally to RF switches, and methods for operating such RF switches.

BACKGROUND

(2) Radio frequency (RF) switches are commonly used in communication transceivers to selectively connect transmitter and receiver circuitry to an antenna or other communication means. To configure the transceiver in a transmit state, an RF switch is controlled to provide a signal path between transmitter and antenna ports of the RF switch, while establishing a high impedance (e.g., open circuit) between the antenna and receiver ports of the RF switch. Conversely, to configure the transceiver in a receive state, the RF switch is controlled to provide a signal path between the antenna and receiver ports, while establishing a high impedance (e.g., open circuit) between the transmitter and antenna ports.

(3) Some RF switches include stacks (i.e., series-coupled arrangements) of field effect transistors (FETs) between their transmit, receive, and antenna ports to achieve higher power handling capability. However, in high-power switches that include relatively large FET stacks, the settling time associated with switching between transmit and receive states may be relatively slow, thus limiting system performance. In addition, non-uniform RF voltage distribution across the FETs in a stack may result in a relatively low power handling capability for the stack. Conventional techniques for balancing the RF voltage distribution may result in undesirably high levels of leakage currents when the stack is in the off state, which may in turn lead to undesirably high signal losses. Accordingly, what are needed are RF switches that are characterized by faster settling times, and that are capable of withstanding higher off-state RF voltages, when compared with conventional RF switches.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A more complete understanding of the subject matter may be derived by referring to the detailed description and claims when considered in conjunction with the following figures, wherein like reference numbers refer to similar elements throughout the figures.

(2) FIG. 1 is a simplified block diagram of an embodiment of a radio frequency (RF) transceiver system;

(3) FIG. 2 is a simplified block diagram of another embodiment of an RF transceiver system;

(4) FIG. 3 is a top view of a surface mount device that embodies a portion of the RF transceiver system of FIG. 1 or FIG. 2, in accordance with an embodiment;

(5) FIG. 4 is a top view of a module that embodies a portion of the RF transceiver system of FIG. 1 or FIG. 2, in accordance with an embodiment;

(6) FIG. 5 is a simplified circuit diagram of an RF switch with parallel transistor stacks in all branches, in accordance with an embodiment;

(7) FIG. 6 is a simplified circuit diagram of an RF switch with parallel transistor stacks in a subset of branches, in accordance with an embodiment;

(8) FIG. 7A is a more detailed circuit diagram of the RF switch of FIG. 6, in accordance with an embodiment;

(9) FIG. 7B illustrates “on-state” and “off-state” models for FETs in a stack;

(10) FIG. 7C is a detailed circuit diagram of an alternate embodiment of a switch branch that may be used for any or all of the switch branches in FIG. 5, 6 or 7A, in accordance with an alternate embodiment;

(11) FIG. 8 is a top view of a monolithic RF switch integrated circuit (IC) that includes an embodiment of the RF switch branch of FIG. 7C, in accordance with an embodiment;

(12) FIG. 9 is a simplified circuit diagram of a single-gate FET and associated circuitry, in accordance with an embodiment;

(13) FIG. 10 is a simplified circuit diagram of a multiple-gate FET and associated circuitry, in

accordance with another embodiment; and

(14) FIG. 11 is a flowchart of a method of operating an RF switch in an RF transceiver, in accordance with an embodiment.

DETAILED DESCRIPTION

(15) Embodiments of the inventive subject matter include radio frequency (RF) switches and transceivers for use in cellular base stations or other applications. In various embodiments, an RF switch includes at least one branch with multiple FET stacks arranged in parallel between switch ports (e.g., between the transmit and antenna ports, between the antenna and receive ports, and/or between a ground reference and the transmit port and/or receive port). During operation, an RF signal conveyed through a branch with parallel FET stacks is divided, and thus of relatively low power in each stack. Accordingly, given the same signal power conveyed through a branch, the FETs in the parallel FET stacks may be smaller in periphery, when compared with conventional RF switches that include only a single FET stack in a branch between switch ports. Further, because the relatively small FETs have lower gate capacitance, when compared with their larger counterparts, the time constants of the relatively small FETs also are smaller than the time constants of their larger counterparts. Accordingly, the settling time associated with switching between transmit and receive states may be relatively fast using implementations of the various embodiments, when compared with the settling times for conventional RF switches. This may enable systems to support faster and faster transmit/receive mode switching speeds, and thus higher data throughput.

(16) In addition, at least some of the FET stacks include a capacitor network coupled between terminals of the transistors, and the capacitor network functions to balance RF voltages (or more generally, “AC voltages”) across the transistors when the stack is in an off state. At least one capacitor in the capacitor network is coupled across multiple transistors in the stack, which may result in reduced off-state leakage currents, when compared with conventional stacks with capacitive balancing networks. This configuration enables the stack to withstand relatively high power signals with relatively low off-state leakage currents and associated signal losses.

(17) Before describing RF switch embodiments in detail, examples of systems, devices, and modules in which such RF switch embodiments may be implemented are described in conjunction with FIGS. 1-4. It is to be understood that the later-described RF switch embodiments may be implemented in a wide variety of other systems, devices, modules, and circuits. Therefore, the example system, device, and module illustrated in FIGS. 1-4 are not to be construed as limiting the scope of the inventive subject matter.

(18) FIG. 1 is a simplified block diagram of an example of an RF transceiver system **100** that includes an RF switch **110**, a transmitter **120**, a receiver **130**, an antenna **140**, and an RF switch controller **150**. Transceiver system **100** is a half-duplex transceiver, in which only one of the transmitter **120** or the receiver **130** are coupled, through the RF switch **110**, to the antenna **140** at any given time. More specifically, the state of the RF switch **110** is controlled by RF switch controller **150** to alternate between coupling an RF transmit signal produced by the transmitter **120** to the antenna **140**, or coupling an RF receive signal received by the antenna **140** to the receiver **130**.

(19) The transmitter **120** may include, for example, a transmit (TX) signal processor **122** and a power amplifier **124**. The transmit signal processor **122** is configured to produce transmit signals, and to provide the transmit signals to the power amplifier **124**. The power amplifier **124** amplifies the transmit signals, and provides the amplified transmit signals to the RF switch **110**. The receiver **130** may include, for example, a receive amplifier **132** (e.g., a low noise amplifier) and a receive (RX) signal processor **134**. The receive amplifier **132** is configured to amplify relatively low power received signals from the RF switch **110**, and to provide the amplified received signals to the receive signal processor **134**. The receive signal processor **134** is configured to consume or process the receive signals.

(20) During each transmit time interval, when the transceiver **100** is in a “transmit mode,” the RF switch controller **150** controls the RF switch **110** to be in a first or “transmit” state, as depicted in FIG. **1**, in which a conductive transmit signal path is established between transmitter node **128** and antenna node **148**, and in which a receive signal path is in a high impedance state (e.g., open circuit) between antenna node **148** and receiver node **138**. Conversely, during each receive time interval, when the transceiver **100** is in a “receive mode,” the RF switch controller **150** controls the RF switch **110** to be in a second or “receive” state, in which a conductive receive signal path, indicated by a dashed line in FIG. **1**, is established between antenna node **148** and receiver node **138**, and in which the transmit signal path is in a high impedance state (e.g., open circuit) between transmitter node **128** and antenna node **148**.

(21) According to an embodiment, the RF switch controller **150** includes up to n drivers, **D1-Dn**, **151**, **152**. As will be described in more detail later, n is the maximum number of parallel switches or FET stacks (e.g., parallel switches **531/532**, **525/526**, **631/632**, **625/626**, FIGS. **5**, **6**, **7A**, **7C**) in any branch of the RF switch **110**, and each driver **151-152** is used to turn the FETs in a given stack on and off (i.e., to render the FET channels conducting or non-conducting). According to an embodiment, n may be any integer between 2 and 5, although n may be greater than 5, as well.

(22) FIG. **2** is a simplified block diagram of another example of RF transceiver system **200** that includes an RF switch **210**, a circulator **216**, a transmitter **220**, a receiver **230**, an antenna **240**, and an RF switch controller **250**. The transmitter **220** and the receiver **230** are coupled to the antenna **240** through the circulator **216**. More specifically, the circulator **216** is a three-port device, with a first port **217** coupled to the transmitter **220**, a second port **218** couplable to the receiver **230** through RF switch **210**, and a third port **219** coupled to the antenna **240**. The RF switch **210** also is a three-port device, with a first port **248** coupled to the receiver port **218** of the circulator **216**, a second port **238** coupled to the receiver **230**, and a third port **228** coupled to a ground reference node **254** through a resistor **256**.

(23) Again, the transmitter **220** may include, for example, a TX signal processor **222** and a power amplifier **224**. The transmit signal processor **222** is configured to produce transmit signals, and to provide the transmit signals to the power amplifier **224**. The power amplifier **224** amplifies the transmit signals, and provides the amplified transmit signals to the antenna **240** through the circulator **216**. The receiver **230** may include, for example, a receive amplifier **232** (e.g., a low noise amplifier) and an RX signal processor **234**. The receive amplifier **232** is configured to amplify relatively low power received signals received from the antenna **240** (through the circulator **216** and the RF switch **210**), and to provide the amplified received signals to the receive signal processor **234**. The receive signal processor **234** is configured to consume or process the receive signals.

(24) The circulator **216** is characterized by a signal-conduction directivity, which is indicated by the arrows within the depiction of circulator **216**. Essentially, RF signals may be conveyed between the circulator ports **217-219** in the indicated direction (counter-clockwise), and not in the opposite direction (clockwise). Accordingly, during normal operations, signals may be conveyed through the circulator **216** from transmitter port **217** to antenna port **219**, and from antenna port **219** to receiver port **218**, but not directly from transmitter port **217** to receiver port **218** or from receiver port **218** to antenna port **219**.

(25) In some situations, while the transceiver **200** is in the transmit mode, the circulator **216** may not be able to convey signal energy received through transmitter port **217** from the transmitter **220** to the antenna **240** through antenna port **219**. For example, the antenna **240** may be disconnected from the antenna port **219**, or may otherwise be in a very high impedance state. In such situations, the circulator **216** may convey signal energy from the transmitter **220** (i.e., signal energy received through transmitter port **217**) past the antenna port **219** to the receiver port **218**. To avoid conveying transmitter signal energy into the receiver **230** while the transceiver **200** is in the transmit mode, the RF switch controller **250** operates the RF switch **210** as a fail-safe switch by coupling the first port

248 to a ground reference node **254**.

(26) More specifically, when the transceiver **200** is in a receive mode, the RF switch **210** is controlled by RF switch controller **250** to be in a receive state, as shown in FIG. 2. In the receive state, the receiver port **218** of the circulator **216** is coupled through RF switch **210** to the receiver **230** (i.e., RF switch controller **250** configures RF switch **210** to have a conductive path between ports **248** and **238**, and a high-impedance, open-circuit condition between ports **248** and **228**). Conversely, when the transceiver **200** is in a transmit mode, the RF switch **210** is controlled by RF switch controller **250** to be in a transmit state, in which the receiver port **218** of the circulator **216** is coupled through the RF switch **210** to the ground termination **254** through resistor **256** (i.e., RF switch controller **250** configures RF switch **210** to have a conductive path, indicated by a dashed line in FIG. 2, between ports **248** and **228**, and a high-impedance, open-circuit condition between ports **248** and **238**). Accordingly, if the transmitter signal energy bypasses the antenna port **219** while the transceiver **200** is in the transmit mode, any signal energy that is conveyed through the receiver port **218** of the circulator **216** to the RF switch **210** will be shunted to the ground termination **254** through port **228** of the RF switch **210**.

(27) According to an embodiment, the RF switch controller **250** includes up to n drivers, **D1-Dn**, **251**, **252**. Again, as will be described in more detail later, n is the maximum number of parallel FET stacks (e.g., FET stacks **631/632** or stacks **625/626**, FIGS. 6, 7A, 7C) in any branch of the RF switch **210**, and each driver **251-252** is used to turn the FETs in a given stack on and off (i.e., to render the FET channels conducting or non-conducting). According to an embodiment, n may be any integer between 2 and 5, although n may be greater than 5, as well.

(28) The RF transceiver systems **100**, **200** (FIGS. 1, 2) may be physically implemented using a variety of active and passive electrical devices, which may be housed in one or more device packages and/or on one or more printed circuit boards (PCBs) and/or other substrates. More specifically, various components of the RF transceiver systems **100**, **200** may be implemented in self-contained modules or electrical devices, which may be coupled to a substrate that electrically connects the module/devices to other portions of the RF transceiver system **100**, **200**. As used herein, the term “module” means a set of active and/or passive electrical devices (e.g., ICs and components) that are physically contained within a single housing (e.g., the device(s) are coupled to a common “module substrate” or within a single device package). A “module” also includes a plurality of conductive terminals for electrically connecting the set of devices to external circuitry that forms other portions of an electrical system. Essentially, the module substrate configuration, the method of coupling the device(s) to the module's terminals, and the number of devices within the module defines the module type. For example, in various embodiments, a module may be in the form of a PCB-based system, a surface mount device, a chip carrier device, a ball, pin, or land grid array device, a flat package device (e.g., a quad or dual flat no-lead package), a chip scale packaged device, a system-in-package (SiP) device, or in the form of some other type of integrated circuit package. Although two particular types of modules/devices are described below in conjunction with FIGS. 3 and 4, it is to be understood that embodiments of the inventive subject matter may be included in other types of modules/devices, as well.

(29) For example, FIG. 3 is a top view of a device **300** that embodies a portion of the RF transceiver system **100** of FIG. 1, in accordance with an embodiment. More specifically, FIG. 3 illustrates that portions of the transceiver may be packaged in a surface mount package. Device **300** is packaged as a quad flat no-lead (QFN) device, which includes a conductive pad **302** and a plurality of terminals (e.g., terminals **328**, **338**, **348**, **352**, **360**, **361**, **362**) held in a fixed spatial relationship with non-conductive encapsulation **303** (e.g., plastic encapsulation). Device **300** also includes a plurality of ICs coupled to the conductive pad **302**, including an RF switch integrated circuit (IC) **310** (e.g., an IC that embodies RF switch **110**, FIG. 1), a receive amplifier IC **332** (e.g., receive amplifier **132**, FIG. 1), a receive matching circuit IC **334**, and an RF switch controller IC **350** (e.g., an IC that embodies RF switch controller **150**, FIG. 1). In addition, device **300** includes a

transmit signal input terminal **328** (e.g., corresponding to transmitter node **128**, FIG. 1), a receive signal output terminal **338** (e.g., corresponding to receiver node **138**, FIG. 1), an antenna terminal **348** (e.g., corresponding to antenna terminal **148**, FIG. 1), a transmit/receive (TX/RX) control signal terminal **352**, one or more ground terminals **360**, **361**, and one or more power terminals **362**.

(30) The various ICs **310**, **332**, **334**, **350** and terminals **328**, **338**, **348**, **352**, **360-362** are electrically connected together through a plurality of wirebonds (e.g., wirebond **370**). In other embodiments, various ones of the ICs **310**, **332**, **334**, **350** and terminals **328**, **338**, **348**, **352**, **360-362** may be electrically connected together using other conductive structures. In various embodiments, the device **300** may be housed in an air-cavity package or an overmolded (e.g., encapsulated) package, although the device **300** may be considered to be complete without such packaging, as well.

(31) After incorporation of device **300** into a transceiver system (e.g., system **100**, FIG. 1), and during operation of the transceiver system, power and ground reference voltages may be provided to device **300** through power and ground terminals **360-362**. RF switch controller IC **350** may receive transmit/receive mode control signals through a control signal terminal **352**. Based on the received mode control signals, the RF switch controller IC **350** provides switch control signals to, or “drives”, the control terminals (e.g., gates) of various transistors (e.g., transistors within branches **520**, **524**, **530**, **534**, **620**, **624**, **630**, **634**, **820**, **824**, **840**, **834**, FIGS. 5, 6, 7A, 7C, 8) of the RF switch IC **310**. As will be described in more detail later, the switch control signals determine whether each of the various transistors is in a conducting or non-conducting state at any given time. More specifically, the switch control signals determine whether the RF switch IC **310** is in a transmit state (i.e., a state in which the switch is configured to convey an RF signal from the transmitter **120** to the antenna **140**) or a receive state (i.e., a state in which the switch is configured to convey an RF signal from the antenna **140** to the receiver **130**) at any given time.

(32) When the switch control signals configure the RF switch IC **310** in the transmit state, transmit signals received by the RF switch IC **310** from a power amplifier (e.g., power amplifier **124**, FIG. 1) through the transmit signal input terminal **328** are passed through the RF switch IC **310** to the antenna terminal **348**. Conversely, when the switch control signals place the RF switch IC **310** in the receive state, signals received from the antenna terminal **348** are passed through the RF switch IC **310** to the receive matching circuit IC **334**. The receive matching circuit IC **334** may include one or more integrated passive devices (e.g., capacitors, inductors, and/or resistors). The integrated passive devices, along with inductances of the wirebonds **370** between the receive matching circuit IC **334**, the RF switch IC **310**, and the receive amplifier IC **332**, compose an impedance matching circuit between the RF switch IC **310** and the receive amplifier IC **332**. In an alternate embodiment, the receive matching circuit IC **334** may be replaced by discrete components. Either way, the impedance matching circuit also may perform filtering of receive signals that pass from the RF switch IC **310** to the receive amplifier IC **332** through the impedance matching circuit. The receive amplifier IC **332** receives the receive signals from the receive matching circuit IC **334**, and amplifies the receive signals. The receive amplifier IC **332** then provides the amplified receive signals to receive signal output terminal **338**.

(33) FIG. 4 is a perspective view of a module **400** that embodies a portion of the RF transceiver system **200** of FIG. 2, in accordance with an embodiment. More specifically, FIG. 4 illustrates that portions of the transceiver may be configured as a printed circuit board (PCB) module. The components of module **400** are mounted on (or coupled to) a system substrate **402**, which may be, for example, a multi-layer PCB or other type of substrate. More specifically, module **400** includes a plurality of ICs and devices coupled to the system substrate **402**, including a transmit amplifier module **424** (e.g., a module that embodies RF amplifier **224**, FIG. 2), an RF switch and receive amplifier module **410** (e.g., a module that embodies RF switch **210** and the receive amplifier **232**, FIG. 2), a circulator **416** (e.g., circulator **216**, FIG. 2), and an RF switch controller IC **450** (e.g., an IC that embodies RF switch controller **250**, FIG. 2). In addition, device **400** includes a transmit signal input connector **420** (e.g., corresponding to the input to amplifier **224**, FIG. 2), a receive

signal output connector **430** (e.g., corresponding to the output of amplifier **232**, FIG. 2), and an antenna connector **440** (e.g., corresponding to an input to antenna **240**, FIG. 2). The various ICs, devices, and connectors **410**, **416**, **420**, **424**, **430**, **440**, **450** are electrically connected together through a plurality of conductive traces on and within the system substrate **402**.

(34) After incorporation of module **400** into a transceiver system (e.g., system **200**, FIG. 2), and during operation of the transceiver system, power and ground reference voltages may be provided to device **400** through power and ground terminals (not numbered). RF switch controller IC **450** may receive transmit/receive mode control signals through a control signal terminal (not numbered). Based on the received mode control signals, the RF switch controller IC **450** provides switch control signals to control terminals (e.g., gates) of various transistors (e.g., transistors within branches **520**, **524**, **530**, **534**, **620**, **624**, **630**, **634**, **820**, **824**, **840**, **834**, FIGS. 5, 6, 7A, 7C, 8) of the RF switch (e.g., RF switch **210**, FIG. 2) within the RF switch and receive amplifier module **410**. As will be described in more detail later, the switch control signals determine whether each of the various transistors is in a conducting or non-conducting state at any given time. More specifically, the switch control signals determine whether the RF switch within module **410** is in a transmit state or a receive state. When the RF switch is in the transmit state, the RF switch is configured to convey an RF signal from the circulator **416** to a ground reference terminal (e.g., node **254**, FIG. 2). When the RF switch is in the receive state, the RF switch is configured to convey an RF signal from the circulator **216** to the receive amplifier (e.g., amplifier **232**, FIG. 2) within module **410**.

(35) Those of skill in the art would understand, based on the description herein, that although the transceiver **100** of FIG. 1 is shown in FIG. 3 to be implemented as a surface-mount device (i.e., QFN device **300**, FIG. 3), transceiver **100** alternatively could be implemented as a PCB-based module (e.g., similar to PCB-based module **400**, FIG. 4). Similarly, those of skill in the art would understand, based on the description herein, that although the transceiver **200** of FIG. 2 is shown in FIG. 4 to be implemented as a PCB-based module (i.e., module **400**, FIG. 4), transceiver **200** alternatively could be implemented as a surface-mount device (e.g., similar to QFN device **300**, FIG. 3). Transceivers **100**, **200** could be implemented and/or packaged in other forms, as well.

(36) Details regarding embodiments of an RF switch (e.g., RF switch **110**, **210**, FIGS. 1, 2) will now be discussed. In particular, FIG. 5 is a simplified circuit diagram of an RF switch **500**, in accordance with an embodiment. RF switch **500** may provide the functionality of RF switch **110** (FIG. 1) and/or RF switch **210** (FIG. 2). RF switch **500** includes a plurality of input/output (I/O) ports, including a first port **528** (e.g., port **128**, **228**, FIGS. 1, 2), a second port **538** (e.g., port **138**, **238**, FIGS. 1, 2), a third port **548** (e.g., port **148**, **248**, FIGS. 1, 2), and voltage reference ports **552**, **553**, in an embodiment.

(37) Further, RF switch **500** includes a plurality of “branches” **520**, **524**, **530**, **534** electrically coupled between the various ports **528**, **538**, **548**, **552**, **553**. As used herein, a switch “branch” includes the switching circuitry connected between any two ports of an RF switch. Accordingly, RF switch **500** is shown to include four branches, where a first branch **520** (“TX series branch”) includes switch circuitry between ports **528** and **548**, a second branch **524** (“TX shunt branch”) includes switch circuitry between ports **528** and **552**, a third branch **530** (“RX series branch”) includes switch circuitry between ports **538** and **548**, and a fourth branch **534** (“RX shunt branch”) includes switch circuitry between ports **538** and **553**.

(38) According to the illustrated embodiment, each branch **520**, **524**, **530**, **534** includes multiple parallel-coupled “switches” **521/522**, **525/526**, **531/532**, **535/536**. In the context of FIGS. 5 and 6, the term “switch”, as it applies to each of elements **521**, **522**, **525**, **526**, **531**, **532**, **535**, **536**, **622**, **625**, **626**, **631**, **632**, and **635**, may mean a single active switching device (e.g., a single FET) or a plurality of active switching devices (e.g., multiple FETs) that are coupled in series between two ports of an RF switch, thus comprising a “stack” of FET switches, or a “FET stack,” as will be defined later. In the embodiment illustrated in FIG. 5, each branch **520**, **524**, **530**, **534** is shown to include two parallel-coupled switches. However, as indicated by the ellipses between each parallel-

coupled set of switches, each branch **520, 524, 530, 534** may include more than two parallel-coupled switches. For example, each branch **520, 524, 530, 534** may include from 2 to n branches, where n may be any integer between 2 and 5. In other embodiments, n may be greater than 5. As will be described in more detail later, the maximum number of parallel-coupled switches in any branch **520, 524, 530, 534** is equal to the number of drivers in the RF switch controller (e.g., drivers **151, 152, 251, 252**, FIGS. **1, 2**).

(39) In some embodiments, the number of parallel-coupled switches in each branch **520, 524, 530, 534** may be the same (e.g., each branch **520, 524, 530, 534** may include two parallel-coupled switches). In other embodiments, the number of parallel-coupled switches in each branch **520, 524, 530, 534** may be different (e.g., branches **520** and **534** each may include two parallel-coupled switches, and branches **524** and **530** each may include three parallel-coupled switches). In still other embodiments, some branches may include multiple parallel-coupled switches, while other branches may include only a single switch.

(40) For example, FIG. **6** is a simplified circuit diagram of an RF switch **600** with parallel switches in only a subset of branches **624, 630**, in accordance with an embodiment, while other branches **620, 634** include only a single switch. Similar to RF switch **500** (FIG. **5**), RF switch **600** also includes a plurality of I/O ports, including a first port **628** (e.g., port **128, 248**, FIGS. **1, 2**), a second port **638** (e.g., port **138, 238**, FIGS. **1, 2**), a third port **648** (e.g., port **148, 228**, FIGS. **1, 2**), and voltage reference ports **652, 653**, in an embodiment.

(41) According to the illustrated embodiment, each of branches **620** and **634** includes only a single switch **622, 635**, whereas each of branches **624, 630** includes multiple parallel-coupled switches **625/626, 631/632**. In the embodiment illustrated in FIG. **6**, each branch **624, 630** is shown to include two parallel-coupled switches. However, as indicated by the ellipses between each parallel-coupled set of switches, each branch **624, 630** may include more than two parallel-coupled switches. For example, each branch **624, 630** may include from 2 to n parallel-coupled switches, where n may be any integer between 2 and 5. In other embodiments, n may be greater than 5. As will be described in more detail later, the maximum number of parallel-coupled switches in either of branches **624** or **630** may be equal to the number of drivers in the RF switch controller (e.g., drivers **151, 152, 251, 252**, FIGS. **1, 2**). Further, the number of parallel-coupled switches in branches **624** and **630** may be equal or unequal.

(42) Although FIG. **6** shows parallel-coupled switches **625/626, 631/632** in two specific branches **624, 630**, in other embodiments, parallel-coupled switches may be implemented in only a single branch (e.g., only branch **620, 624, 630**, or **634**), while each other branch includes only a single switch. In still other embodiments, parallel-coupled switches may be implemented in some other subset of branches (e.g., in branches **620/624, 620/630, 620/634, 620/624/630, 620/624/634, 620/630/634, 624/634**, or **630/634**), while each other branch includes only a single switch. Either way, in some embodiments, the number of parallel-coupled switches in each branch may be the same, whereas in other embodiments, the number of parallel-coupled switches in each branch may be different.

(43) If either of RF switches **500, 600** were implemented in the transceiver **100** of FIG. **1**, for example, port **528/628** may correspond to port **128**, and thus may be coupled to transmitter **120**. Port **538, 638** may correspond to port **138**, and thus may be coupled to receiver **130**. Port **548, 648** may correspond to port **148**, and thus may be coupled to antenna **140**. Finally, ports **552, 553, 652, 653** may be coupled to ground reference nodes. In an alternate embodiment, if either of RF switches **500, 600** were implemented in the transceiver of FIG. **1**, port **528/628** may correspond to port **138**, and thus may be coupled to receiver **130**, and port **538, 638** may correspond to port **128**, and thus may be coupled to transmitter **120**.

(44) Conversely, if either of RF switches **500, 600** were implemented in the transceiver **200** of FIG. **2**, for example, port **548/648** may correspond to port **248**, and thus may be coupled to the receiver port **218** of circulator **216**. Port **538, 638** may correspond to port **238**, and thus may be coupled to

receiver **230**. Port **528, 628** may correspond to port **228**, and thus may be coupled to ground reference node **254** through resistor **256**. Finally, ports **552, 553, 652, 653** also may be coupled to ground reference nodes. In an alternate embodiment, if either of RF switches **500, 600** were implemented in the transceiver of FIG. 2, port **528/628** may correspond to port **238**, and thus may be coupled to receiver port **218** of circulator **216**, and port **538, 638** may correspond to port **228**, and thus may be coupled to ground reference node **254** through resistor **256**.

(45) To illustrate various aspects of the inventive subject matter in more detail, FIG. 7A depicts a detailed circuit diagram of an embodiment of an RF switch **700** that corresponds to the RF switch **600** of FIG. 6. In FIG. 7A, elements that correspond to the same elements in FIG. 6 have the same reference number (e.g., ports **628, 638, 648, 652, 653**, branches **620, 624, 630, 634**, and switches **622, 625, 626, 631, 632, 635**).

(46) As used herein, the terms “stack” and “FET stack” refer to multiple FETs that are coupled in series with each other (or “series-coupled”) between two ports of an RF switch. Each stack may be considered to be a “switch” or a “variably-conductive path”, in that the conductivity of a signal through the stack (or more specifically through the series of channels of the FETs in the stack) can be controlled or varied (i.e., increased or decreased) based on control signals provided at the stack control terminals (e.g., terminals **732, 735, 736, 741, 742, 745**, FIGS. 7A, 7C). In other words, a stack (or switch or variably-conductive path) can be placed in a low-impedance state (e.g., closed, “on state” or “on-state”) or a high-impedance state (e.g., open, “off state” or “off-state”) based on control signals provided at the stack control terminal. Further, the terms “coupled in series” and “series-coupled,” in reference to the electrical coupling between multiple FETs in a stack, means that the current-conducting terminals (e.g., source/drain terminals) of the multiple FETs are connected together to provide a continuous electrically conductive channel/path between a first port (e.g., port **628, 728**, FIGS. 6, 7A) and a second port (e.g., port **648, 748**, FIGS. 6, 7A) when the multiple FETs are in a conducting state (e.g., “on” or “closed”). Although the description herein refers to series-coupled arrangements in which a first FET has a drain terminal connected to a node, and has a source terminal connected to a drain terminal of a second FET, the source and drain terminal connections could be reversed, in other embodiments (e.g., a series-coupled arrangement may have a first FET with a source terminal connected to a node, and a drain terminal connected to a source terminal of a second FET). More generally, each of the source and drain terminals of a FET may be referred to as a “current-conducting terminal,” and that term could be used interchangeably for either a source terminal or a drain terminal. Also, when two FETs are coupled in the above manner (i.e., the source of one FET in a stack is connected to the drain of another FET in the stack), these two FETs may be considered to be “adjacent” to each other.

(47) According to an embodiment, in FIGS. 5, 6, 7A, and 7C, each switch **521, 522, 525, 526, 531, 532, 535, 536, 622, 625, 626, 631, 632, 635** is implemented as a stack of series-coupled FETs **701-703, 704-706, 707-709, 710-718, 719-727, 728-730** that is electrically coupled between two ports. In branches that include only a single switch (e.g., branches **620, 634**, FIGS. 6, 7A), a single stack of series-coupled FETs is electrically coupled between the respective ports, whereas in branches that include multiple, parallel-coupled switches (e.g., branches **520, 524, 530, 534, 624, 630**), multiple stacks of series-coupled FETs are electrically coupled between the respective ports.

(48) According to the embodiment illustrated in FIGS. 6 and 7A, branch **620** includes a single switch **622**, which may be implemented as a first stack of series-coupled FETs **701, 702, 703** that are electrically coupled between port **628** and port **648**. Branch **624** includes two, parallel-coupled switches **625, 626**, which may be implemented as second and third stacks of series-coupled FETs **704, 705, 706** and **707, 708, 709**, respectively, that are electrically coupled between port **628** and port **652**. Branch **630** also includes two, parallel-coupled switches **631, 632**, which may be implemented as fourth and fifth stacks of series-coupled FETs **710-718** and **719-727**, respectively, that are electrically coupled between port **638** and port **648**. Finally, branch **634** includes a single switch **635**, which may be implemented as a sixth stack of series-coupled FETs **728, 729, 730** that

are electrically coupled between port **638** and port **653**. When incorporated into a larger electrical system, ports **652** and **653** typically would be coupled to a ground reference (e.g., zero volts), although ports **652** and **653** alternatively could be coupled to a positive or negative DC voltage reference, as well.

(49) As best depicted in the enlarged view of FET **701** in the upper left corner of FIG. 7A, each FET **701-730** includes a drain terminal (e.g., terminal **784** of FET **701**), a source terminal (e.g., terminal **785** of FET **701**), and a gate terminal (e.g., gate terminal **783** of FET **701**). According to some embodiments, each FET **701-730** also may include a body bias terminal **786**, which enables a DC bias voltage to be provided to the FET body. The electrical conductivity of a variable-conductivity channel between the source and drain terminals of any given FET is controlled by control signals provided to the FET's gate terminal (e.g., terminal **783**). Some (and possibly all) of the above-discussed FETs may be "single-gate FETs", although some or all of the FETs may be "multiple-gate FETs", as well. Essentially, as will be described in more detail in conjunction with FIG. 9, a single-gate FET is a monolithic transistor device that includes a variable-conductivity channel between drain and source terminals, along with only one gate positioned over the channel. Conversely, as will be described in more detail in conjunction with FIG. 10, a multiple-gate FET is a monolithic transistor device that includes a variable-conductivity channel between drain and source terminals, along with multiple gates positioned over the channel. Electrical signals provided to the multiple gates control the conductivity of the channel during operation of the FET. In some applications, utilization of multiple gates may enable better electrical control over the channel, when compared with single-gate FETs. This, in turn, may enable more effective suppression of "off-state" leakage current, and/or enhanced current in the "on" state (i.e., drive current).

(50) In the series-coupled sequence of multiple-gate FETs corresponding to switch **622**, the drain terminal **784** of FET **701** may be coupled to port **628**, the source terminal **785** of FET **701** may be coupled to the drain terminal of FET **702**, the source terminal of FET **702** may be coupled to the drain terminal of FET **703**, and the source terminal of FET **703** may be coupled to port **648**.

Although the description herein refers to series-coupled arrangements in which a first FET has a drain terminal connected to a port, and has a source terminal connected to a drain terminal of a second FET, the source and drain terminal connections could be reversed, in other embodiments (e.g., a series-coupled arrangement may have a first FET with a source terminal connected to a port, and a drain terminal connected to a source terminal of a second FET). More generally, each of the source and drain terminals of a FET may be referred to as a "current-conducting terminal," and that term could be used interchangeably for either a source terminal or a drain terminal.

(51) According to an embodiment, during operation, the control signals provided to the series-coupled FETs in any particular switch **622**, **625**, **626**, **631**, **632**, **635** are synchronous, in that they simultaneously cause all of the FETs in that switch either to be substantially conducting (e.g., "on" or "closed") or substantially non-conducting (e.g., "off" or "open"). To accomplish simultaneous control of all FETs in each switch, the gate terminals of the FETs in each switch may be electrically coupled to a single control node. For example, in FIGS. 7A and 7C, the gate terminals of FETs **701-703** are electrically coupled to control terminal **732**, the gate terminals of FETs **704-706** are electrically coupled to control terminal **735**, the gate terminals of FETs **707-709** are electrically coupled to control terminal **736**, the gate terminals of FETs **710-718** are electrically coupled to control terminal **741**, the gate terminals of FETs **719-727** are electrically coupled to control terminal **742**, and the gate terminals of FETs **728-730** are electrically coupled to control terminal **745**.

(52) As indicated previously, a system that includes RF switch **700** may include a switch controller (e.g., switch controller **150**, **250**, FIGS. 1, 2) with multiple drivers (e.g., drivers **151**, **152**, **251**, **252**, FIGS. 1, 2), and each driver is coupled to one or more of the control terminals **732**, **735**, **736**, **741**, **742**, **745** of the switches **622**, **625**, **626**, **631**, **632**, **635**. To cause an entire switch to become substantially conductive between the ports to which the switch is connected (e.g., to turn the switch

“on” or to “close” the switch), the driver that is connected to the control node associated with that switch provides a control signal (or “drive signal”) to the control node, and that control signal causes all of the FETs within the switch simultaneously to become substantially conducting. For example, a driver (e.g., driver **151, 251**) coupled to control terminal **732** may provide a control signal to terminal **722**, which simultaneously causes all of FETs **701-703** to become substantially conducting (e.g., to “turn on” or “close”), thus causing switch **622** to become substantially conductive between ports **628** and **648**. Alternatively, the driver may provide a control signal to terminal **722**, which simultaneously causes all of FETs **701-703** to become substantially non-conducting (e.g., to “turn off” or “open”), thus causing switch **622** to become substantially non-conductive between ports **628** and **648**.

(53) Further, according to an embodiment, in branches that include multiple, parallel-coupled switches/stacks (e.g., branches **624** and **630**), the control signals provided to the FETs of the parallel-coupled switches of the branch also are synchronous, in that they simultaneously cause all of the FETs in that entire branch either to be substantially conducting (e.g., “on” or “closed”) or substantially non-conducting (e.g., “off” or “open”). Although a single driver could provide control signals to all of the FETs of the parallel-coupled switches of a branch, separate drivers (e.g., drivers **151, 152, 251, 252**, FIGS. **1, 2**) may be used to drive each of the multiple switches in any given multi-switch branch. For example, in the branch between ports **638** and **648**, a first driver (e.g., driver **151, 251**, FIGS. **1, 2**) may be coupled to control terminal **741**, and that driver may provide a control signal to control terminal **741**. A second driver (e.g., driver **152, 252**, FIGS. **1, 2**) may be coupled to control terminal **742**, and that driver may provide a second control signal to control terminal **742**. To turn switches **631** and **632** on or off synchronously, the control signals provided by the first and second driver are synchronous. Said another way, separate drivers are used to drive the parallel-coupled switches/stacks of any given branch synchronously, according to an embodiment.

(54) As will now be explained, the above-described configuration of a branch that includes multiple-parallel coupled FET stacks (e.g., the branch between ports **638** and **648** or the branch between ports **628** and **652**) may have improved settling time, in comparison to a conventional branch with a single FET stack that is designed to conduct signals with the same level of power. More specifically, during operation, an RF signal conveyed through a branch with multiple parallel-coupled FET stacks is divided between the parallel stacks. When the parallel-coupled FET stacks are substantially identical, each stack would convey approximately 50 percent of the total power of the RF signal. Accordingly, in comparison with a conventional switch branch that includes only a single stack designed to conduct a signal of the same power, the parallel-coupled FET stacks of the present embodiments need only to be designed to conduct signals of approximately half power in each stack. Thus, given the same signal power conveyed through a branch with parallel-coupled FET stacks and a conventional branch with a single stack, the FETs in the parallel-coupled FET stacks may be smaller in gate width/periphery. For example, a conventional RF switch may include a single FET stack between switch ports in which each FET has a 4 millimeter (mm) gate width, whereas each parallel-coupled FET stack may include FETs with only a 2 mm gate width.

(55) Further, the parasitic capacitance on the gate of a FET is proportional to the gate width. Thus, the relatively small FETs associated with the various embodiments have shorter gate widths and thus lower gate capacitance, when compared with their larger counterparts in a conventional single-stack branch. Given that each of the parallel-coupled FET stacks also are separately driven (e.g., by separate drivers **151, 152, 251, 252**, FIGS. **1, 2**), in accordance with various embodiments, the time constants of the relatively small FETs in the parallel-coupled FET stacks also are smaller than the time constants of their larger conventional counterparts. This may result in a significantly faster (e.g., about 50 percent faster) settling time associated with switching between transmit and receive states, when using implementations of the various embodiments, when compared with the settling

times for conventional RF switches.

(56) In FIG. 7A, each of the switches **620, 625, 626, 631, 632, 635** is shown to include a stack of three series-coupled FETs **701-703, 704-706, 707-709, 710/711/718, 719/720/727, and 728-730**. Although each of the switches **620, 625, 626, 631, 632, 635** may include a stack of three series-coupled FETs in some embodiments, each of the switches **620, 625, 626, 631, 632, 635** alternatively may include a single FET, two FETs, or more than three FETs (as indicated with the ellipses in each FET stack). In some embodiments, either or both of the shunt branches **624, 634** may not include any FETs, and instead port **628** and/or port **638** could be directly coupled to the corresponding voltage reference nodes **652, 653**, respectively.

(57) According to an embodiment, the parallel-coupled switches (or the parallel-coupled FET stacks) in a same branch are substantially identical (e.g., switches **631** and **632** are substantially identical), although switches in different branches may be different from each other (e.g., switches **631** and **625** may be different, although they may be substantially identical, as well). More specifically, within a same branch, each of the parallel-coupled switches may include the same number of series-coupled FETs, with the same total periphery and/or gate width. In other embodiments, the parallel-coupled switches (or the parallel-coupled FET stacks) in a same branch may be different from each other (e.g., they may have a different number of parallel-coupled FETs, and/or they may have different total peripheries and/or gate widths).

(58) In addition to the FETs, each stack may include a DC bias distribution network of high-value (e.g., multiple kilohm) resistors (e.g., resistors **791-793**, FIG. 7A), in an embodiment, where each resistor is coupled between the source and drain terminals of a FET. The DC bias distribution network essentially ensures that the DC bias voltage provided to the drains/sources of each FET in the stack is the same. Although DC bias distribution networks are shown only in switches **622, 631, 632** in FIG. 7A, such networks also may be included in switches **625, 626, and 635**.

(59) Each stack also may include an RF blocking network of high-value (e.g., multiple kilohm) resistors (e.g., resistors **794-796**, FIG. 7A) coupled between the gate terminals of the FETs and the control terminal (e.g., control terminal **732**, FIG. 7A) for the stack, in an embodiment. The RF blocking network presents a high impedance to RF signal energy to ensure that the RF signal energy conveyed through a branch does not leak to the control/driver circuitry (e.g., to controller **150, 250**, FIGS. 1, 2).

(60) Further still, each stack also may include body bias circuitry coupled between the body node of each FET, if included, and a body bias terminal (e.g., body bias terminal **786**, FIG. 7A). The body bias circuitry also may include an RF blocking network of high-value (e.g., multiple kilohm) resistors (e.g., resistors **797-799**, FIG. 7A) coupled between the body nodes of the FETs and the body bias terminal for the stack, in an embodiment. Again, the RF blocking network presents a high impedance to RF signal energy to ensure that the RF signal energy conveyed through a branch does not leak to the body bias circuitry (not illustrated). Although body bias circuitry is shown only in switches **622, 631, 632** in FIG. 7A, such circuitry also may be included in switches **625, 626, and 635**.

(61) As described in conjunction with FIGS. 1 and 2, during operation of an embodiment of an RF switch (e.g., switches **110, 210, 500, 600, 700**, FIGS. 1, 2, 5-7A), the state of the RF switch is controlled (e.g., through control signals sent by RF switch controller **150, 250**, FIGS. 1, 2) based on whether the system (e.g., transceiver **100, 200**, FIGS. 1, 2) is in a transmit mode or a receive mode (e.g., during a transmit time interval or a receive time interval, respectively, of a wireless communication session).

(62) More specifically, when the system is in a transmit mode, the state of the RF switch is controlled to establish a low-impedance connection between port **148, 248, 548, 648** and port **128, 228, 528, 628**, and to establish a high-impedance between port **148, 248, 548, 648** and port **138, 238, 538, 638**. Further, in the transmit mode, the state of the RF switch is controlled (e.g., through control signals sent by RF switch controller **150, 250**, FIGS. 1, 2) to establish a low-impedance

connection between port **538, 638** and port **553, 653**, and to establish a high-impedance between port **528, 628** and port **552, 652**. In other words, in the transmit mode, switches **521, 522, 535, 536, 622, 635** are closed, and switches **525, 526, 531, 532, 631, 632** are open. Referring to FIG. 7A, this means that the RF switch controller sends control signals to control terminals **732** and **745** to cause FETs **701-703** and **728-730** to be in a substantially conducting state, and the RF switch controller sends control signals to control terminals **735, 736, 741, and 742** to cause FETs **704-709** and **710-727** to be in a substantially non-conducting state. Accordingly, in the transmit state, signal energy present at node **628** is conveyed through switch **622** (or branch **620**) to node **648**, and the conductive path between node **628** and voltage reference node **652** is open. In addition, in the transmit state, signal energy present at node **638** is conveyed through switch **635** (or branch **634**) to voltage reference node **653**, and the conductive path between node **638** and node **648** is open.

(63) Conversely, when the system is in a receive mode, the state of the RF switch is controlled to establish a low-impedance connection between port **148, 248, 548, 648** and port **138, 238, 538, 638**, and to establish a high-impedance between port **148, 248, 548, 648** and port **128, 228, 528, 628**. Further, in the receive mode, the state of the RF switch is controlled to establish a low-impedance connection between port **528, 628** and port **552, 652**, and to establish a high-impedance between port **538, 638** and port **553, 653**. In other words, in the receive mode, switches **525, 526, 531, 532, 625, 626, 631, 632** are closed, and switches **521, 522, 535, 536, 622, 635** are open. Referring to FIG. 7A, this means that the RF switch controller sends control signals to control terminals **732** and **745** to cause FETs **701-703** and **728-730** to be in a substantially non-conducting state, and the RF switch controller sends control signals to control terminals **735, 736, 741, and 742** to cause FETs **704-709** and **710-727** to be in a substantially conducting state. Accordingly, in the receive state, signal energy present at node **638** is conveyed through switches **631** and **632** (or branch **630**) to node **648**, and the conductive path between node **638** and voltage reference node **653** is open. In addition, in the receive state, signal energy present at node **628** is conveyed through switches **625** and **626** (or branch **624**) to voltage reference node **652**, and the conductive path between node **628** and node **648** is open.

(64) As indicated previously, to cause an entire stack to become substantially conductive between the ports to which the stack is connected (e.g., to turn the stack “on” or to “close” the switch), a switch driver provides a control signal (or “drive signal”) to a stack control terminal, which causes all of the FETs within the stack simultaneously to become substantially conducting. This causes the stack to become substantially conductive between the ports to which the stack is coupled. In other words, referring to stack **620** as an example, when an appropriate control signal is provided to control terminal **732** to turn the stack “on”, the FETs **701-703** and stack **620** are in the “on state”. Referring to FIG. 7B, as shown in box **740**, in the “on state”, each FET **701-703** may be simply modeled as a resistor **743** with a first terminal corresponding to a drain terminal **784**, and a second terminal corresponding to a source terminal **785**. Alternatively, the driver may provide a control signal to stack control terminal **732**, which simultaneously causes all of FETs **701-703** to become substantially non-conducting, thus causing the stack to become substantially non-conductive between the ports to which the stack is coupled. In other words, the FETs **701-703** and stack **620** are in the “off state”. As shown in box **746** of FIG. 7B, in the “off state”, each FET **701-703** may be simply modeled as a capacitor **747** (“Cds”) with a first terminal corresponding to the drain terminal **784**, and a second terminal corresponding to the source terminal **785**, along with a first additional shunt capacitance **748** (“Csub1”) between the source terminal and a ground reference, and a second additional shunt capacitance **749** (“Csub2”) between the drain terminal and the ground reference. Csub1 **748** and Csub2 **749** represent the parasitic capacitance from the transistor body to the semiconductor substrate on which the FET is formed.

(65) In the off state, the parasitic capacitances modeled by Csub1 **748** and Csub2 **749** each may facilitate an undesirable leakage current between the FET and the substrate, which ultimately results in RF signal loss. Further, these leakage currents may create an unequal or non-uniform RF

voltage division across the stack. This non-uniform voltage distribution across the stack may lead to a lower power handling capability for the stack, because in the off state, the first and/or first few FETs in the stack may experience the stack breakdown voltage before the rest of the FETs in the off-state branch.

(66) According to another embodiment, to balance the voltage distribution across a stack, and thus to increase the RF voltage handling capability of the stack, a stack also may include a network of “balancing” capacitors, in an embodiment. When parallel stacks are implemented (e.g., as in branches **624**, **630**, FIGS. **6**, **7A**, **7C**), the balancing capacitor network may be implemented in each parallel stack.

(67) To illustrate this concept in a generic way, reference is made to FIG. **7C**, which is a simplified circuit diagram of another embodiment of branch **630** (e.g., branch **630**, FIGS. **6**, **7A**), in which parallel stacks **631**, **632** of FETs **710-727** are implemented. It should be understood that implementation of a balancing capacitor network in branch **630** is for example purposes, and in other embodiments, balancing capacitor network(s) may alternatively or also be implemented in any or all of branches **620**, **624**, and/or **634**.

(68) In FIG. **7C**, each FET **710-727** includes gate, drain, source, and (optionally) body bias terminals (e.g., terminals **783-785**, FIG. **7A**), and the on and off states of the FETs **710-727** may be modeled as depicted in boxes **740**, **746** (FIG. **7B**), respectively. Further, each FET **710-727** may be a single-gate FET or a multiple-gate FET.

(69) In FIG. **7C**, the FETs **710-727** of each stack **631**, **632** of branch **630** are divided into groups **780-1**, **780-2**, **781-1**, **781-2**, **782-1**, **782-2**, of FETs, where each group includes three or more (as indicated by the ellipses) adjacent, series-coupled FETs. Selection of three FETs per group is for example purposes, and each group may include fewer or more FETs. In various embodiments, each group **780-1**, **780-2**, **781-1**, **781-2**, **782-1**, **782-2** may include from two to 10 adjacent FETs, for example, and the number of FETs in each group **780-1**, **780-2**, **781-1**, **781-2**, **782-1**, **782-2** may be the same or different (e.g., group **781-1** may include fewer or more FETs than group **782-1**, and so on). Although each stack **631**, **632** is shown to include three groups **780-1**, **780-2**, **781-1**, **781-2**, **782-1**, **782-2** of FETs, each stack **631**, **632** may include as few as two groups, or more than three groups, in other embodiments. According to an embodiment, however, stacks **631** and **632** are identical (e.g., including identical numbers of FETs, identical balancing capacitor networks, etc.).

(70) In the series-coupled sequence of FETs corresponding to stack **631**, the drain terminal of FET **710** may be coupled through current-conducting node **750** to port **648**, the source terminal of FET **710** may be coupled through current-conducting node **751** to the drain terminal of FET **711**, the source terminal of FET **711** may be coupled through current-conducting node **752** (and through zero or more additional FETs, not illustrated) to the drain terminal of FET **712**, the source terminal of FET **712** may be coupled through current-conducting node **753** (and through zero or more additional FETs, not illustrated) to the drain terminal of FET **713**, and so on, with the source terminal of FET **718** being coupled through current-conducting node **759** to port **638**.

(71) Similarly, in the series-coupled sequence of FETs corresponding to stack **632**, the drain terminal of FET **719** may be coupled through current-conducting node **760** to port **648**, the source terminal of FET **719** may be coupled through current-conducting node **761** to the drain terminal of FET **720**, the source terminal of FET **720** may be coupled through current-conducting node **762** (and through zero or more additional FETs, not illustrated) to the drain terminal of FET **721**, the source terminal of FET **721** may be coupled through current-conducting node **763** (and through zero or more additional FETs, not illustrated) to the drain terminal of FET **722**, and so on, with the source terminal of FET **727** being coupled through current-conducting node **769** to port **638**.

(72) As discussed previously, simultaneous control of all FETs **710-718**, **719-727** in each stack **631**, **632** is accomplished by electrically coupling the gate terminals of the FETs **710-718**, **719-727** in each stack **631**, **632** to a stack control terminal **741**, **742**. To cause each entire stack **631**, **632** to become substantially conductive between ports **648**, **638** (e.g., to turn each stack “on” or to “close”

each switch), two drivers (e.g., of switch controller **150**, **250**, FIGS. **1**, **2**) provide drive signals to the stack control terminals **741**, **742**. Each control signal causes all of the FETs **710-718**, **719-727** within each stack **631**, **632** simultaneously to become substantially conducting, thus causing each stack **631**, **632** to become substantially conductive between ports **648** and **638**.

(73) In addition, as discussed in conjunction with FIG. **7A**, each stack **631**, **632** may include a DC bias distribution network of high-value (e.g., multiple kilohm) resistors (e.g., including resistors **791-793**, FIG. **7A**), in an embodiment, where each resistor is coupled between the source and drain terminals of a FET **710-727**. Further, as also discussed in conjunction with FIG. **7A**, each stack **631**, **632** also may include an RF blocking network of high-value (e.g., multiple kilohm) resistors (e.g., including resistors **794-796**, FIG. **7A**) coupled between the gate terminals of the FETs **710-727** and the stack control terminals **741**, **742**, in an embodiment. Further still, each stack **631**, **632** also may include body bias circuitry coupled between the body node of each FET, if included, and a body bias terminal (e.g., body bias terminal **790**, FIG. **7A**). The body bias circuitry also may include an RF blocking network of high-value (e.g., multiple kilohm) resistors (e.g., resistors **797-799**, FIG. **7A**) coupled between the body nodes of the FETs and the body bias terminal for each stack **631**, **632**, in an embodiment.

(74) To balance the voltage distribution across each stack **631**, **632**, and thus to increase the RF voltage handling capability of each stack **631**, **632**, each stack **631**, **632** also includes a network of balancing capacitors **774-776**, **777-779**, in an embodiment. According to an embodiment, the balancing capacitors **774-776**, **777-779** are coupled to some (but not all) of the current-conducting nodes **750-769** of each stack **631**, **632**, meaning that each balancing capacitor is connected across a different group of multiple adjacent FETs **710-727** in each stack **631**, **632**. In the embodiment of FIG. **7C**, for example, each balancing capacitor **774-779** is connected across a different group of three or more adjacent FETs in the series-coupled arrangement of FETs **710-727** in each stack **631**, **632**.

(75) More specifically, in stack **631**, a first balancing capacitor **774** is coupled across a first group **780-1** of three or more FETs **710-712**, where a first terminal of capacitor **774** is coupled to current-conducting node **750** (and thus to the drain of FET **710**), and a second terminal of capacitor **774** is coupled to current-conducting node **753** (and thus to the source of FET **712** and the drain of FET **713**). Node **750** may be considered to be an “input” of the first group of FETs **710-712**, and node **753** may be considered to be an “output” of the first group of FETs **710-712**. A second balancing capacitor **775** is coupled across a second group **781-1** of three or more FETs **713-715**, where a first terminal of capacitor **775** is coupled to current-conducting node **753** (and thus to the source of FET **712** and the drain of FET **713**), and a second terminal of capacitor **775** is coupled to current-conducting node **756** (and thus to the source of FET **715** and the drain of FET **716**). Node **753** may be considered to be an “input” of the second group of FETs **712-714**, and node **756** may be considered to be an “output” of the second group of FETs **712-714**. Finally, a third balancing capacitor **776** is coupled across a third group **782-1** of three or more FETs **715-718**, where a first terminal of capacitor **776** is coupled to current-conducting node **756** (and thus to the source of FET **715** and the drain of FET **716**), and a second terminal of capacitor **776** is coupled to current-conducting node **759** (and thus to the source of FET **718** and terminal **638**). Node **756** may be considered to be an “input” of the third group of FETs **716-718**, and node **759** may be considered to be an “output” of the third group of FETs **716-718**.

(76) Similarly, in stack **633**, a first balancing capacitor **777** is coupled across a first group **780-2** of three or more FETs **719-721**, where a first terminal of capacitor **777** is coupled to current-conducting node **760** (and thus to the drain of FET **719**), and a second terminal of capacitor **777** is coupled to current-conducting node **763** (and thus to the source of FET **721** and the drain of FET **722**). Node **760** may be considered to be an “input” of the first group of FETs **719-721**, and node **763** may be considered to be an “output” of the first group of FETs **719-721**. A second balancing capacitor **778** is coupled across a second group **781-2** of three or more FETs **722-724**, where a first

terminal of capacitor **778** is coupled to current-conducting node **763** (and thus to the source of FET **721** and the drain of FET **722**), and a second terminal of capacitor **778** is coupled to current-conducting node **766** (and thus to the source of FET **724** and the drain of FET **725**). Node **763** may be considered to be an “input” of the second group of FETs **722-724**, and node **766** may be considered to be an “output” of the second group of FETs **722-724**. Finally, a third balancing capacitor **779** is coupled across a third group **782-2** of three or more FETs **725-727**, where a first terminal of capacitor **779** is coupled to current-conducting node **766** (and thus to the source of FET **724** and the drain of FET **725**), and a second terminal of capacitor **779** is coupled to current-conducting node **769** (and thus to the source of FET **727** and terminal **638**). Node **766** may be considered to be an “input” of the third group of FETs **725-727**, and node **769** may be considered to be an “output” of the third group of FETs **725-727**.

(77) It should be noted that current-conducting nodes that are in-between the FETs in any given group (e.g., current-conducting nodes **751, 752, 754, 755, 757, 758, 761, 762, 764, 765, 767, 768**) are not directly connected to the networks of balancing capacitors **774-779**. In addition, although FIG. 7C depicts three groups **780-1, 780-2, 781-1, 781-2, 782-1, 782-2** of FETs in each stack **631, 632**, each stack **631, 632** may have as few as two groups or more than three groups, in other embodiments. According to an embodiment, each of the balancing capacitors **774-779** has a capacitance value in a range of about 50 femto-Farads (fF) to about 500 fF, although the capacitance values may be lower or higher, as well.

(78) In some embodiments, balancing capacitors **774-776** and **777-779** are connected across all of the groups of FETs **710-718** and **719-727** in the stacks **631, 632**. In other embodiments, balancing capacitors may be connected across some, but not all, FETs in a stack. For example, as indicated with the dashed-line connections between balancing capacitors **774, 777** and nodes **750/753, 760/763**, each of balancing capacitors **774, 777** may be omitted. In other embodiments, one or more other or additional balancing capacitors may be omitted (e.g., balancing capacitors **775/778** and/or **776/779** also or alternatively may be omitted).

(79) An embodiment of an RF switch integrated circuit (IC) that embodies the circuitry of FIG. 7C will now be described. More particularly, FIG. 8 is a top view of a monolithic RF switch IC **800** that includes the combination of FET stacks of FIGS. 6 and 7, in accordance with an embodiment. RF switch IC **800** includes a plurality of branches **820, 824, 840, 834** (e.g., branches **620, 624, 630, 634, 720, 724, 730, 734**, FIGS. 6, 7A, 7C). Each branch includes one or two switches/FET stacks **822, 825, 826, 831, 832, 835** (e.g., switches **622, 625, 626, 631, 632, 635**, FIGS. 6, 7A, 7C), and each FET stack includes multiple, series-coupled FETs **801-803, 804-806, 807-809, 810-818, 819-827, 828-830** (e.g., FETs **701-703, 704-706, 707-709, 710-718, 719-727, 728-730**, FIG. 7A, 7C). According to an embodiment, the branches **820, 824, 840, 834** may form portions of a single, monolithic semiconductor chip (i.e., a single semiconductor substrate). Alternatively, some or all of the branches **820, 824, 840, 834** may be included within distinct semiconductor chips that are electrically connected together using wirebonds and/or other electrically conductive structures.

(80) According to an embodiment, the RF switch IC **800** is “monolithic,” in that the FETs **801-830** are formed in and on a single integrated circuit substrate **860**. For example, according to an embodiment, the RF switch IC **800** may be formed on a gallium arsenide (GaAs)-based substrate **860**, although those of skill in the art would understand, based on the description herein, that the circuitry of the RF switch may be formed on other types of substrates, as well, including silicon (Si)-based substrates (e.g., bulk Si CMOS, silicon-on insulator (SoI) CMOS, and so on) and gallium nitride (GaN)-based substrates (e.g., GaN on silicon, GaN on silicon carbide (SiC), and so on). Further, the FETs may include metal oxide semiconductor FETs (MOSFETs), high electron mobility transistors (HEMTs), metal-semiconductor field effect transistors (MESFETs), laterally diffused metal-oxide semiconductor (LDMOS) FETs, Enhancement-mode MOSFETs (EMOSFETs), and/or junction gate FETs (JFETs), to name a few.

(81) In addition to branches **820, 824, 840, 834**, RF switch IC **800** includes a plurality of I/O,

control, and voltage reference nodes **828, 838, 848, 852, 853**, each of which may provide for electrical connectivity with external circuitry (e.g., connectivity with antenna **140**, transmitter **120**, receiver **130, 230**, circulator **216**, RF switch controller **150, 250**, and so on) and/or electrical connectivity with one or more power sources and/or voltage references (e.g., power, ground and other voltage references). For example, some or all of the I/O, control, and voltage reference nodes **828, 838, 848, 852, 853** may be implemented as conductive pads that are exposed at a top surface of the RF switch IC **800**. Accordingly, the various nodes **828, 838, 848, 852, 853** may serve as bond pads for wirebonds (e.g., wirebonds **370**, FIG. 3), which provide for electrical connectivity to the above-mentioned external circuitry or to other circuitry. According to an embodiment, the various nodes include a first node **828** (e.g., node **128, 228, 528, 628**, FIGS. 1, 2, 5, 6, 7A), a second node **838** (e.g., node **138, 238, 538, 638**, FIGS. 1, 2, 5, 6, 7A, 7C), a third node **848** (e.g., node **148, 248, 548, 648**, FIGS. 1, 2, 5, 6, 7A, 7C), and voltage reference nodes **852, 853** (e.g., reference nodes **552, 553, 652, 653**, FIGS. 5, 6, 7A).

(82) For each FET **801-830**, the electrical conductivity of the FET channel between the source and drain terminals is controlled by control signals provided to each gate structure through a gate terminal (e.g., terminal **783**, FIG. 7A). To enable such channel conductivity control, RF switch IC **800** also includes a plurality of control nodes (not illustrated in FIG. 8, but corresponding to control terminals **732, 735, 736, 741, 742, 745**, FIGS. 7A, 7C) that enable control signals to be provided by external circuitry to the gate terminals of the FETs **801-830**. According to an embodiment, the control signals provided to the FETs in any particular branch **820, 824, 840, 834** are synchronous, in that they simultaneously cause all of the FETs in that branch either to be substantially conducting (e.g., “on” or “closed”) or substantially non-conducting (e.g., “off” or “open”).

(83) A first branch **820**, consisting of a first stack **822** of series-coupled FETs **801, 802, 803** (e.g., FETs **701-703**, FIG. 7A), is electrically coupled between node **828** and node **848**. More specifically, a drain terminal of FET **801** is electrically coupled to node **828**, a source terminal of FET **801** is electrically coupled to a drain terminal of FET **802**, a source terminal of FET **802** is electrically coupled to a drain terminal of FET **803**, and a source terminal of FET **803** is electrically coupled to node **848**, in an embodiment. Although not shown in FIG. 8, one or more balancing capacitors may be coupled between FETs **801-803**, in an alternate embodiment.

(84) A second branch **824**, consisting of two parallel-coupled FET stacks **825, 826** (e.g., including FETs **704-709**, FIG. 7A), is electrically coupled between node **828** and voltage reference node **852**. More specifically, in stack **825**, a drain terminal of FET **804** is electrically coupled to node **828**, a source terminal of FET **804** is electrically coupled to a drain terminal of FET **805**, a source terminal of FET **805** is electrically coupled to a drain terminal of FET **806**, and a source terminal of FET **806** is electrically coupled to voltage reference node **852**. In addition, according to an embodiment, a balancing capacitor **871** has a first terminal coupled to the drain of FET **805**, and a second terminal coupled to the source of FET **806**. As discussed above, the balancing capacitor **871** functions to balance RF voltages across the FETs **804-806** when the stack **825** is in an off state.

(85) In stack **826**, a drain terminal of FET **807** is electrically coupled to node **828**, a source terminal of FET **807** is electrically coupled to a drain terminal of FET **808**, a source terminal of FET **808** is electrically coupled to a drain terminal of FET **809**, and a source terminal of FET **809** is electrically coupled to voltage reference node **852**. In addition, according to an embodiment, a balancing capacitor **872** has a first terminal coupled to the drain of FET **808**, and a second terminal coupled to the source of FET **809**. As discussed above, the balancing capacitor **872** functions to balance RF voltages across the FETs **807-809** when the stack **826** is in an off state.

(86) A third branch **840**, consisting of two parallel-coupled FET stacks **831, 832** (e.g., including FETs **710-727**, FIGS. 7A, 7C), is electrically coupled between node **848** and node **838**. More specifically, in stack **831**, a drain terminal of FET **810** is electrically coupled to node **848**, a source terminal of FET **810** is electrically coupled to a drain terminal of FET **811**, a source terminal of FET **811** is electrically coupled to a drain terminal of FET **812**, and so on through FETs **812-818**,

until a source terminal of FET **818** is electrically coupled to node **838**. In addition, according to an embodiment, stack **831** also includes a network of balancing capacitors **875**, **876**, which includes a first balancing capacitor **875** with a first terminal coupled to the drain of FET **813**, and a second terminal coupled to the source of FET **815**, and a second balancing capacitor **876** with a first terminal coupled to the drain of FET **816**, and a second terminal coupled to the source of FET **818**. Although not shown in FIG. **8**, a balancing capacitor also or alternatively may be coupled between FETs **810-812**, in an alternate embodiment. As discussed above, the network of balancing capacitors **875**, **876** functions to balance RF voltages across the FETs **810-818** when the stack **831** is in an off state.

(87) In stack **832**, a drain terminal of FET **819** is electrically coupled to node **848**, a source terminal of FET **819** is electrically coupled to a drain terminal of FET **820**, a source terminal of FET **820** is electrically coupled to a drain terminal of FET **821**, and so on through FETs **821-827**, until a source terminal of FET **827** is electrically coupled to node **838**. In addition, according to an embodiment, stack **832** also includes a network of balancing capacitors **878**, **879**, which includes a first balancing capacitor **878** with a first terminal coupled to the drain of FET **822**, and a second terminal coupled to the source of FET **824**, and a second balancing capacitor **879** with a first terminal coupled to the drain of FET **825**, and a second terminal coupled to the source of FET **827**. Although not shown in FIG. **8**, a balancing capacitor also or alternatively may be coupled between FETs **819-821**, in an alternate embodiment. As discussed above, the network of balancing capacitors **878**, **879** functions to balance RF voltages across the FETs **819-827** when the stack **832** is in an off state.

(88) Finally, a fourth branch **834**, consisting of a sixth stack **835** of series-coupled FETs **828**, **829**, **830** (e.g., FETs **728-730**, FIG. **7A**), is electrically coupled between node **838** and voltage reference node **853**. More specifically, a drain terminal of FET **828** is electrically coupled to node **838**, a source terminal of FET **828** is electrically coupled to a drain terminal of FET **829**, a source terminal of FET **829** is electrically coupled to a drain terminal of FET **830**, and a source terminal of FET **830** is electrically coupled to voltage reference node **853**, in an embodiment. Although not shown in FIG. **8**, one or more balancing capacitors may be coupled between FETs **828-830**, in an alternate embodiment. When incorporated into a larger electrical system (e.g., transceiver **100**, **200**, FIGS. **1**, **2**), voltage reference nodes **852**, **853** typically would be coupled to a ground reference (e.g., zero volts), although nodes **852**, **853** alternatively could be coupled to a positive or negative DC voltage reference, as well.

(89) A comparison of the FETs **801-803** in branch **820** to the FETs **810-827** in branch **840** illustrates that, to conduct signals of substantially the same maximum power, a conventional switch branch that includes only a single stack (e.g., stack **822** in branch **820**) would include significantly larger FETs (e.g., FETs **801-803**) than the FETs (e.g., FETs **810-827**) in an embodiment of a switch branch that includes multiple stacks (e.g., stacks **831**, **832** in branch **840**). In other words, given the same signal power conveyed through a branch with parallel-coupled FET stacks (e.g., branch **840**) and a conventional branch with a single stack (e.g., branch **820**), the FETs in the parallel-coupled FET stacks (e.g., FETs **810-827**) may be smaller in gate width/periphery than the FETs in the conventional FET stack (e.g., FETs **801-803**). Because the relatively small FETs have lower gate capacitance, when compared with their larger counterparts, the time constants of the relatively small FETs also are smaller than the time constants of their larger counterparts. Accordingly, the settling time for the parallel-coupled FET stacks may be significantly faster than the settling time for the conventional single FET stack.

(90) As previously mentioned, the various FETs in the above-described embodiments of RF switches may include single-gate FETs and/or multiple-gate FETs. For example, FIG. **9** is a simplified circuit depiction of a single-gate FET **900** that may be used for some or all of the FETs (e.g., FETs **701-730**, **801-830**, FIGS. **7A**, **7C**, **8**) in an RF switch, in accordance with an embodiment. The single-gate FET **900** has a source terminal **970** (e.g., source terminal **785**, FIG.

7A), a drain terminal **980** (e.g., drain terminal **784**, FIG. 7A), and a gate **960** (e.g., gate terminal **783**, FIG. 7A). The gate **960** overlies a FET channel (depicted with dashed line **990**) that extends between the source terminal **970** and the drain terminal **980**. Although not shown in FIG. 9, a body bias terminal may be connected to the FET **900** to enable a body bias voltage to be supplied to the FET **900** from an external voltage source.

(91) The gate **960** is electrically coupled to a control terminal **910** (e.g., terminal **783**, FIG. 7A) through a resistance **912**. The source terminal **970** is electrically coupled to a first node **914** (e.g., directly or indirectly coupled to any of nodes **750-769**, FIG. 7C, or to the drain terminal of another FET), and the drain terminal **980** is electrically coupled to a second node **916** (e.g., directly or indirectly coupled to any of nodes **750-759**, FIG. 7C or to the source terminal of another FET).

(92) In other embodiments, some or all of the various FETs in the above-described embodiments of RF switches may include multiple-gate FETs and/or multiple-gate FET assemblies. For example, FIG. 10 is a simplified circuit diagram of a multiple-gate FET assembly **1000** that may be used in place of some or all of the FETs (e.g., FETs **701-730**, **801-830**, FIGS. 7A, 7C, 8) in an RF switch, in accordance with another embodiment. The multiple-gate FET assembly **1000** includes a multiple-gate FET **1020** and a voltage leveling circuit **1030**. According to an embodiment, the multiple-gate FET assembly **1000** is monolithically and integrally formed in and on a semiconductor substrate.

(93) Multiple-gate FET **1020** includes a source terminal **1070** (e.g., source terminal **785**, FIG. 7A), a drain terminal **1080** (e.g., drain terminal **784**, FIG. 7A), a multiple-gate FET channel (depicted with dashed line **1090**) between the source and drain terminals **1070**, **1080**, and a multiple-gate assembly **1060** (e.g., analogous to gate terminal **783**, FIG. 7A) with a plurality of gate structures **1061**, **1062**, **1063** over the multiple-gate FET channel **1090**. The term “multiple-gate FET channel,” as used herein, refers to an entire variable-conductivity path between the source and drain terminals of a multiple-gate FET (e.g., between source and drain terminals **1070**, **1080**). As mentioned previously, utilization of multiple gates may enable better electrical control over the channel **1090**, when compared with single-gate FETs. This, in turn, may enable more effective suppression of “off-state” leakage current, and/or enhanced current in the “on” state (i.e., drive current). Although not shown in FIG. 10, a body bias terminal may be connected to the FET **1020** to enable a body bias voltage to be supplied to the FET **1020** from an external voltage source.

(94) The multiple-gate assembly **1060** is electrically coupled to a control terminal **1010** (e.g., terminal **783**, FIG. 7A) through a plurality of resistances **1012**. The source terminal **1070** is electrically coupled to a first node **1014** (e.g., directly or indirectly coupled to any of nodes **750-759**, FIG. 7C, or to the drain terminal of another FET), and the drain terminal **1080** is electrically coupled to a second node **1016** (e.g., directly or indirectly coupled to any of nodes **750-759**, FIG. 7C or to the source terminal of another FET).

(95) The voltage leveling circuit **1030** is electrically connected between the source terminal **1070**, the drain terminal **1080**, and the multiple-gate assembly **1060**. Circuit **1030** includes a plurality of channel contacts **1032**, **1033**, a plurality of capacitors **1034**, **1036**, **1037**, **1038**, **1043**, and a plurality of resistors **1041**, **1042**, according to an embodiment. Each of the channel contacts **1032**, **1033** may be, for example, an ohmic contact that is electrically coupled to the active surface of the semiconductor substrate over the multiple-gate FET channel **1080** between first and second pairs of adjacent gate structures **1061-1063**.

(96) Through various electrical connections, the channel contacts **1032**, **1033** are electrically coupled to capacitors **1034**, **1036-1038**, **1043**, and capacitors **1034**, **1036-1038**, **1043** are electrically coupled to the multiple-gate assembly **1060**, and to the source and drain terminals **1070**, **1080**, as shown in FIG. 10. Each of the capacitors **1034**, **1036-1038**, **1043** may be a metal-insulator-metal (MIM) capacitor that is integrally formed with the substrate (e.g., a first electrode formed from a portion of a first metal layer, a second electrode formed from a portion of a second metal layer, and an insulating layer (e.g., silicon nitride or other suitable insulating materials)

sandwiched between the first and second electrodes). In other embodiments, some or all of capacitors **1034**, **1036-1038**, **1043** may be discrete capacitors that are electrically coupled to the top surface of the semiconductor substrate.

(97) When implemented in a system with a stack of multiple-gate FETs, the voltage leveling circuit **1030** may result in a more uniform, off-state AC voltage distribution across the FETs of the stack. More specifically, by utilizing equalizing capacitors **1036-1038** connected as shown in FIG. **10**, AC voltage swing may be substantially equalized across all FETs in an off-state FET branch of an RF switch (or across multiple-gate FETs in a different type of circuit), thereby potentially preventing the first and/or first few multiple-gate FETs from experiencing the stack breakdown voltage before the rest of the multiple-gate FETs in the off-state branch. This may significantly improve the power handling capability of the switch branch.

(98) Circuit **1030** also includes relatively high-value resistors **1041**, **1042**, which are electrically connected in parallel with capacitors **1036** and **1038**, respectively, in an embodiment. Resistors **1041**, **1042** may be integrally formed with the semiconductor substrate (e.g., stripline resistors, polysilicon resistors, and so on), or may be discrete resistors that are coupled to the top surface of the substrate, in various embodiments. The resistors **1041**, **1042** of the voltage leveling circuit **1030** may result in a more uniform, off-state DC voltage distribution across the FETs of a stack. More specifically, the relatively high-value resistors **1041**, **1042** act as conductors for the DC signal, which is blocked by the capacitances, both intentional and parasitic, while most of the RF signal passes primarily through the capacitances. This balance is achieved by selecting appropriately valued resistors and capacitors in the parallel resistor/capacitor combinations.

(99) FIG. **11** is a flowchart of a method of operating an RF switch (e.g., RF switch **110**, **210**, **310**, **410**, **500**, **600**, **700**, **800**, FIGS. **1-8**) in an RF transceiver (e.g., transceiver **100**, **200**, FIGS. **1**, **2**), in accordance with an embodiment. The method may begin, in block **1102**, when a determination is made (e.g., by RF switch controller **150**, **250**, FIGS. **1**, **2**) whether the RF transceiver should be configured in a transmit (TX) mode or a receive (RX) mode. For example, this determination may be made based on a TX/RX control signal from a higher-level communication controller.

(100) When the transceiver is to be configured in a transmit mode configuration, then in block **1104**, the FET stacks in the TX series and RX shunt branches (e.g., branches **520**, **534**, **620**, **634**, FIGS. **5**, **6**, **7A**) simultaneously are turned on, while the FET stacks in the RX series and the TX shunt branches (e.g., branches **530**, **524**, **630**, **624**, FIGS. **5**, **6**, **7A**, **7C**) simultaneously are turned off. To achieve this, the drivers (e.g., drivers **151**, **152**, **251**, **252**, FIGS. **1**, **2**) of the RF switch controller provide control signals to the control nodes (e.g., terminals **732**, **735**, **736**, **741**, **742**, **745**, FIGS. **7A**, **7C**) of the various FET stacks of the RF switch to configure the RF switch in the transmit mode configuration. For example, to configure the RF switch **700** of FIG. **7A** into the transmit mode configuration, one or more drivers of the RF switch controller may send first control signals to control terminals **732** and **745** to simultaneously turn on branches **620** and **634** (i.e., to close switches **622**, **635** to establish low-impedance paths between nodes **628** and **648**, and between nodes **638** and **653**). At the same time, one or more drivers of the RF switch controller may send second control signals to control nodes **735**, **736**, **741**, **742** to simultaneously turn off branches **624** and **630** (i.e., to open switches **625**, **626**, **631**, **632** to establish high-impedance conditions between nodes **628** and **652** and between nodes **638** and **648**). Upon turning off branches **624** and **630**, the balancing capacitors (e.g., balancing capacitors **774-779**, **871**, **872**, **875**, **876**, **878**, **879**, FIGS. **7C**, **8**), if included in branches **624** and/or **630**, function to balance RF voltages across the FETs of the associated branch stack(s). The RF switch controller continues to send these control signals to the various control nodes until a determination is made (in block **1102**) that the transceiver is to be configured in a receive mode.

(101) When the transceiver is to be configured in a receive mode configuration, then in block **1106**, the FET stacks in the RX series and TX shunt branches (e.g., branches **530**, **534**, **630**, **624**, FIGS. **5**, **6**, **7A**, **7C**) simultaneously are turned on, while the FET stacks in the TX series and the RX shunt

branches (e.g., branches **520**, **534**, **620**, **634**, FIGS. **5**, **6**, **7A**) simultaneously are turned off. To achieve this, the drivers (e.g., drivers **151**, **152**, **251**, **252**, FIGS. **1**, **2**) of the RF switch controller provide control signals to the control nodes (e.g., terminals **732**, **735**, **736**, **741**, **742**, **745**, FIGS. **7A**, **7C**) of the various FET stacks of the RF switch to configure the RF switch in the receive mode configuration. For example, to configure the RF switch **700** of FIG. **7A** into the receive mode configuration, distinct drivers of the RF switch controller (e.g., drivers **151** and **152**, or drivers **251** and **252**) may simultaneously send first and second control signals, respectively, to control nodes **735**, **736**, **741**, **742** to simultaneously turn on branches **624** and **630** (i.e., to close switches **625**, **626**, **631**, **632** to establish low-impedance paths between nodes **638** and **648**, and between nodes **628** and **652**). Again, as discussed previously, separate drivers would be used to provide control signals to control nodes **741** and **742**, and separate drivers also would be used to provide control signals to control nodes **735** and **736**, according to an embodiment. At the same time, one or more drivers of the RF switch controller may send third control signals to control terminals **732** and **745** to simultaneously turn off branches **620** and **634** (i.e., to open switches **622**, **635** to establish high-impedance conditions between nodes **628** and **648** and between nodes **638** and **653**). Upon turning off branches **620** and **634**, the balancing capacitors, if included in branches **620** and/or **634**, function to balance RF voltages across the FETs of the associated branch stack(s). The RF switch controller continues to send these control signals to the various control nodes until a determination again is made (in block **1102**) that the transceiver is to be configured in a transmit mode.

(102) An embodiment of a switch circuit includes a first port, a second port, a first transistor stack coupled between the first and second ports, a first balancing capacitor, and a second transistor stack coupled in parallel with the first transistor stack between the first and second ports. The first transistor stack includes a first group of multiple first transistors and at least one additional first transistor coupled between the first and second ports. The multiple first transistors and the at least one additional first transistor all are connected together in series to provide a first variably-conductive path between the first and second ports. The first balancing capacitor has a first terminal coupled to an input of the first group of multiple first transistors, and a second terminal coupled to an output of the first group of multiple first transistors. According to a further embodiment, the second transistor stack includes a second group of multiple second transistors and at least one additional second transistor coupled between the first and second ports, and the multiple second transistors and the at least one additional second transistor all are connected together in series to provide a second variably-conductive path between the first and second ports.

(103) Another embodiment of a switch circuit includes a first port, a second port, a first transistor stack coupled between the first and second ports, a first balancing capacitor network, a second transistor stack coupled between the first and second ports, and a second balancing capacitor network. The first transistor stack includes a first plurality of transistors coupled in series between the first and second ports to provide a first variably-conductive path between the first and second ports. The first balancing capacitor network includes one or more first capacitors, and a first capacitor of the one or more first capacitors is coupled across a first group of multiple transistors of the first plurality of transistors. The second transistor stack includes a second plurality of transistors coupled in series between the first and second ports to provide a second variably-conductive path between the first and second ports. The second balancing capacitor network includes one or more second capacitors, wherein a first capacitor of the one or more second capacitors is coupled across a second group of multiple transistors of the second plurality of transistors.

(104) An embodiment of a transceiver includes a switch circuit. The switch circuit includes a first port, a second port, a first transistor stack coupled between the first and second ports, a first balancing capacitor, and a second transistor stack coupled in parallel with the first transistor stack between the first and second ports. The first transistor stack includes a first group of multiple first transistors and at least one additional first transistor coupled between the first and second ports. The multiple first transistors and the at least one additional first transistor all are connected together

in series to provide a first variably-conductive path between the first and second ports. The first balancing capacitor has a first terminal coupled to an input of the first group of multiple first transistors, and a second terminal coupled to an output of the first group of multiple first transistors.

(105) The foregoing detailed description is merely illustrative in nature and is not intended to limit the embodiments of the subject matter or the application and uses of such embodiments. As used herein, the words “exemplary” and “example” mean “serving as an example, instance, or illustration.” Any implementation described herein as exemplary or an example is not necessarily to be construed as preferred or advantageous over other implementations. Furthermore, there is no intention to be bound by any expressed or implied theory presented in the foregoing technical field, background, or detailed description.

(106) For the sake of brevity, conventional semiconductor fabrication techniques may not be described in detail herein. In addition, certain terminology may also be used herein for the purpose of reference only, and thus are not intended to be limiting, and the terms “first”, “second” and other such numerical terms referring to structures do not imply a sequence or order unless clearly indicated by the context.

(107) The foregoing description refers to elements or features being “connected” or “coupled” together. As used herein, unless expressly stated otherwise, “connected” means that one element is directly joined to (or directly communicates with) another element, and not necessarily mechanically. Likewise, unless expressly stated otherwise, “coupled” means that one element is directly or indirectly joined to (or directly or indirectly communicates with) another element, and not necessarily mechanically. Thus, although the schematic shown in the figures depict one exemplary arrangement of elements, additional intervening elements, devices, features, or components may be present in an embodiment of the depicted subject matter.

(108) While at least one exemplary embodiment has been presented in the foregoing detailed description, it should be appreciated that a vast number of variations exist. It should also be appreciated that the exemplary embodiment or embodiments described herein are not intended to limit the scope, applicability, or configuration of the claimed subject matter in any way. Rather, the foregoing detailed description will provide those skilled in the art with a convenient road map for implementing the described embodiment or embodiments. It should be understood that various changes can be made in the function and arrangement of elements without departing from the scope defined by the claims, which includes known equivalents and foreseeable equivalents at the time of filing this patent application.

Claims

1. A switch circuit comprising: a first port; a second port; a first transistor stack coupled between the first and second ports, wherein the first transistor stack comprises a first group of multiple first transistors and at least one additional first transistor coupled between the first and second ports, wherein the multiple first transistors and the at least one additional first transistor all are connected together in series between drains and sources of transistors of the multiple first transistors and at the least one additional transistor to provide a first variably-conductive path between the first and second ports; a first balancing capacitor having a fixed value with a first terminal directly coupled to an input of multiple transistors of the first group of multiple first transistors and a second terminal directly coupled to an output of the multiple transistors of the first group of multiple first transistors, wherein the first terminal and the second terminal of the first balancing capacitor are directly coupled across multiple transistors of the first group of multiple first transistors, and wherein the input of the first group of multiple first transistors is directly coupled to the first port; and a second transistor stack coupled between the first and second ports, wherein the second transistor stack comprises a second group of multiple second transistors and at least one additional

second transistor coupled between the first and second ports, wherein the multiple second transistors and the at least one additional second transistor all are connected together in series to provide a second variably-conductive path between the first and second ports; and a second balancing capacitor network that includes one or more second capacitors, wherein a second capacitor of the one or more second capacitors is directly coupled across a second group of multiple transistors of the second plurality of transistors.

2. The switch circuit of claim 1, wherein: each transistor of the first transistor stack has a gate terminal coupled to a first stack control terminal, each transistor of the second transistor stack has a gate terminal coupled to a second stack control terminal, and the switch circuit further comprises a first driver coupled to the first stack control terminal; and a second driver coupled to the second stack control terminal, where the first and second drivers are configured to simultaneously turn on or turn off the first and second pluralities of transistors.

3. The switch circuit of claim 1, wherein: the first group of multiple first transistors includes a first transistor with a first current-conducting terminal and a second current-conducting terminal, and a second transistor with a third current-conducting terminal and a fourth current-conducting terminal; the first terminal of the first balancing capacitor is connected to the first current-conducting terminal of the first transistor; the second current-conducting terminal of the first transistor is electrically coupled to the third current-conducting terminal of the second transistor; and the second terminal of the first balancing capacitor is connected to the fourth current-conducting terminal of the second transistor.

4. The switch circuit of claim 1, wherein the first group of multiple first transistors includes two transistors.

5. The switch circuit of claim 1, wherein the first group of multiple first transistors includes three or more transistors.

6. The switch circuit of claim 1, wherein the first and second transistor stacks form portions of a first branch between the first and second ports, and the switch circuit further comprises: a third port; a second branch coupled between the first and third ports; a third branch coupled between the second port and a ground reference node; and a fourth branch coupled between the third port and the ground reference node.

7. The switch circuit of claim 1, wherein each transistor of the first and second groups of transistors is a field effect transistor.

8. The switch circuit of claim 7, wherein each transistor of the first and second pluralities of transistors is a multiple-gate field effect transistor.

9. A switch circuit comprising: a first port; a second port; a third port; a first transistor stack coupled between the first and second ports, wherein the first transistor stack comprises a first group of multiple first transistors and at least one additional first transistor coupled between the first and second ports, wherein the multiple first transistors and the at least one additional first transistor all are connected together in series between drains and sources of transistors of the multiple first transistors and at the least one additional transistor to provide a first variably-conductive path between the first and second ports; a first balancing capacitor having a fixed value with a first terminal directly coupled to an input of multiple transistors of the first group of multiple first transistors and a second terminal directly coupled to an output of the multiple transistors of the first group of multiple first transistors, wherein the first terminal and the second terminal of the first balancing capacitor are directly coupled across multiple transistors of the first group of multiple first transistors, and wherein the input of the first group of multiple first transistors is directly coupled to the first port; a second transistor stack coupled between the first and second port; and a third transistor stack coupled between the first and third ports, wherein the third transistor stack comprises a third group of multiple third transistors coupled in series between the first and third ports, and wherein each transistor of the third group of multiple third transistors has a gate terminal coupled to a third control terminal.

10. The switch circuit of claim 9, further comprising: a fourth transistor stack coupled between the third port and a ground reference node, wherein the fourth transistor stack comprises a fourth group of multiple fourth transistors coupled in series between the third port and the ground reference node, and wherein each transistor of the fourth group of multiple fourth transistors has a gate terminal coupled to a fourth control terminal.
11. The switch circuit of claim 10, further comprising: a fifth transistor stack coupled between the third port and the ground reference node, wherein the fifth transistor stack comprises a fifth group of multiple fifth transistors coupled in series between the third port and the ground reference node, and wherein each transistor of the fifth group of multiple fifth transistors has a gate terminal coupled to a fifth control terminal.
12. A switch circuit comprising: a first port; a second port; a first transistor stack coupled between the first and second ports, wherein the first transistor stack comprises a first plurality of transistors connected in series between drains and sources of transistors of the first plurality of transistors and between the first and second ports to provide a first variably-conductive path between the first and second ports; a first balancing capacitor network that includes one or more first capacitors having fixed values, wherein a first capacitor of the one or more first capacitors is directly coupled across multiple transistors within a first group of multiple transistors of the first plurality of transistors, and wherein one or more of the first capacitors is directly coupled to the first port; a second transistor stack coupled between the first and second ports, wherein the second transistor stack comprises a second plurality of transistors coupled in series between the first and second ports to provide a second variably-conductive path between the first and second ports; and a second balancing capacitor network that includes one or more second capacitors, wherein a second capacitor of the one or more second capacitors is directly coupled across a second group of multiple transistors of the second plurality of transistors.
13. The switch circuit of claim 12, wherein: the first plurality of transistors includes two transistors; and the second plurality of transistors includes two transistors.
14. The switch circuit of claim 12, wherein: the first plurality of transistors includes three or more transistors; and the second plurality of transistors includes three or more transistors.
15. A transceiver comprising: a switch circuit that includes a first port, a second port, a first transistor stack coupled between the first and second ports, wherein the first transistor stack comprises a first group of multiple first transistors and at least one additional first transistor coupled between the first and second ports, wherein sources and drains of the multiple first transistors and the at least one additional first transistor all are connected together in series to provide a first variably-conductive path between the first and second ports, a first balancing capacitor having a fixed value with a first terminal directly coupled to an input of multiple transistors of the first group of multiple first transistors, and a second terminal directly coupled to an output of the multiple transistors of the first group of multiple first transistors, wherein the first terminal and the second terminal of the first balancing capacitor are directly coupled across multiple transistors of the first group of multiple first transistors, and wherein the input of the first group of multiple first transistors is directly coupled to the first port; and a second transistor stack coupled in parallel with the first transistor stack between the first and second ports, wherein the second transistor stack comprises a second group of multiple second transistors and at least one additional second transistor coupled between the first and second ports, wherein the multiple second transistors and the at least one additional second transistor all are connected together in series to provide a second variably-conductive path between the first and second ports; and a second balancing capacitor network that includes one or more second capacitors, wherein a second capacitor of the one or more second capacitors is directly coupled across a second group of multiple transistors of the second plurality of transistors.
-