

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267759

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

VOGEDES; Jerome et al.

eDRX ENHANCEMENT FOR REDUCED CAPABILITY DEVICE

Abstract

Methods, systems, and devices may assist in reducing the possibility that a reduced capability NR device misses a paging message due to the termination of PTW. Methods, systems, and devices may enable a UE to dynamically turn on and off eDRX mode of operation or change eDRX configuration based on its traffic profiles.

Inventors: VOGEDS; Jerome (Wilmington, DE), CHEN; Zhuo (Wilmington, DE), ADJAKPLE; Pascal (Wilmington, DE), MURRAY; Joseph (Wilmington, DE), LI; Yifan (Wilmington, DE), PAN; Kyle (Wilmington, DE), DI GIROLAMO; Rocco (Wilmington, DE), ZHANG; Guodong (Wilmington, DE), TSAI; Allan (Wilmington, DE), AWADIN; Mohamed (Wilmington, DE)

Applicant: IPLA HOLDINGS INC. (New York, NY)

Family ID: 1000008586953

Assignee: IPLA HOLDINGS INC. (New York, NY)

Appl. No.: 19/203207

Filed: May 09, 2025

Related U.S. Application Data

parent US continuation 17927016 20221122 PENDING US continuation PCT/US2021/044749
20210805 child US 19203207
us-provisional-application US 63061340 20200805

Publication Classification

Int. Cl.: H04W76/28 (20180101); H04W52/02 (20090101); H04W68/00 (20090101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. application Ser. No. 17/927,016, filed Nov. 22, 2022, which is based on PCT filing PCT/US2021/044749, filed Aug. 5, 2021, which claims the benefit of U.S. Provisional Patent Application No. 63/061,340, filed on Aug. 5, 2020, entitled “eDRX ENHANCEMENT FOR REDUCED CAPABILITY DEVICE,” the contents of each are hereby incorporated by reference herein.

BACKGROUND

[0002] Extended Discontinuous Reception (eDRX) is an extension of an existing LTE feature that can be used by IoT devices to reduce power consumption. eDRX can be used without PSM or in conjunction with PSM to obtain additional power savings.

[0003] This background information is provided to reveal information believed by the applicant to be of possible relevance. No admission is necessarily intended, nor should be construed, that any of the preceding information constitutes prior art.

SUMMARY

[0004] Disclosed herein are methods, systems, and devices that may assist in eDRX enhancement for reduced capability NR devices. In an example, methods may reduce the possibility that a reduced capability NR device misses a paging message due to the termination of PTW. Methods are disclosed for a UE to extend the length of its configured Paging Time Window implicitly without receiving an indication from gNB and explicitly after receiving an indication from gNB. A method is disclosed for a UE to use the max value of UE specific PTW length and cell specific PTW length as its PTW length, wherein the cell specific PTW is obtained from the gNB via system information and the UE specific PTW is obtained from AMF when the UE registers in the network. A method is disclosed for a gNB to assist the Core Network to optimize the configuration of UE's PTW. In the disclosed method, the AMF obtains gNB assistance information, e.g., beam sweeping information, of which the UE connected to and decides the UE's PTW based on the beam sweeping information.

[0005] In addition, methods may enable a UE to dynamically turn on and off eDRX mode of operation or change eDRX configuration based on its traffic profiles. A method is disclosed that a UE sends a mobility registration update to re-negotiate the eDRX cycle when its traffic profile changes. A method is disclosed that gNB assists the UE to dynamically turn on and off eDRX mode of operation or change eDRX configuration based on its traffic profiles.

[0006] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter. Furthermore, the claimed subject matter is not constrained to limitations that solve any or all disadvantages noted in any part of this disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] A more detailed understanding may be had from the following description, given by way of example in conjunction with the accompanying drawings wherein:

[0008] FIG. 1 illustrates an eDRX configuration procedure when a UE is in RRC_INACTIVE state;

[0009] FIG. 2 illustrates a Wake-up-Signal;

[0010] FIG. 3 illustrates a UE that missed the paging DCI due to termination of PTW;

[0011] FIG. 4 illustrates Implicit Paging Time Window extension wherein the UE monitors an incomplete PDCCH monitoring occasion, for example the UE monitors a PDCCH monitoring occasion that overlaps with the PTW but not fully contained within the PTW;

[0012] FIG. 5 illustrates Implicit Paging Time Window extension wherein the UE monitors a PDCCH monitoring occasion that is outside the PTW but belongs to a PO that overlaps with the PTW;

[0013] FIG. 6 illustrates Explicit Paging Time Window Extension;

[0014] FIG. 7 illustrates PTW configuration optimization using cell specified PTW;

[0015] FIG. 8 illustrates PTW configuration optimization using cell specified PTW for UE mobility;

[0016] FIG. 9 illustrates gNB Assisted PTW configuration optimization;

[0017] FIG. 10 illustrates gNB Assisted PTW configuration optimization using NAS message for UE mobility;

[0018] FIG. 11 illustrates gNB Assisted PTW configuration optimization using A S message for UE mobility;

[0019] FIG. 12 illustrates Mobility registration update procedure to re-negotiate the eDRX cycle;

[0020] FIG. 13 illustrates gNB assisted eDRX cycle re-configuration when a UE's traffic profile changed and in RRC_IDLE;

[0021] FIG. 14 illustrates gNB assisted eDRX cycle re-configuration when a UE's traffic profile changed and in RRC_INACTIVE;

[0022] FIG. 15 illustrates UE Configuration Update procedure to update eDRX configuration;

[0023] FIG. 16 illustrates gNB assisted eDRX cycle re-configuration initiated by the network;

[0024] FIG. 17 illustrates an exemplary display (e.g., graphical user interface) that may be generated based on the methods, systems, and devices of eDRX enhancement for reduced capability NR devices.

[0025] FIG. 18A illustrates an example communications system;

[0026] FIG. 18B illustrates an exemplary system that includes RANs and core networks;

[0027] FIG. 18C illustrates an exemplary system that includes RANs and core networks;

[0028] FIG. 18D illustrates an exemplary system that includes RANs and core networks;

[0029] FIG. 18E illustrates another example communications system;

[0030] FIG. 18F is a block diagram of an example apparatus or device, such as a WTRU; and

[0031] FIG. 18G is a block diagram of an exemplary computing system.

DETAILED DESCRIPTION

Paging for NR

[0032] Paging allows the network to reach UEs in RRC_IDLE and in RRC_INACTIVE state through Paging messages, and to notify UEs in RRC_IDLE, RRC_INACTIVE and RRC_CONNECTED state of system information change and ETWS/CMAS indications through Short Messages. Both Paging messages and Short Messages are addressed with P-RNTI on PDCCH, but while the former is sent on PCCH, the latter is sent over PDCCH directly.

[0033] The UE may use Discontinuous Reception (DRX) in RRC_IDLE and RRC_INACTIVE state in order to reduce power consumption. The UE monitors one Paging Occasion (PO) per DRX cycle. A PO is a set of PDCCH monitoring occasions and can consist of multiple time slots (e.g., subframe or OFDM symbol) where the paging DCI can be sent, per TS 38.213 [5]. One Paging Frame (PF) is one Radio Frame and may contain one or multiple PO(s) or starting point of a PO.

[0034] In multi-beam operations, the UE assumes that the same paging message and the same Short Message are repeated in all transmitted beams and thus the selection of the beam(s) for the

reception of the paging message and Short Message is up to UE implementation. The paging message is same for both RAN initiated paging and CN initiated paging.

[0035] The UE initiates RRC Connection Resume procedure upon receiving RAN initiated paging. If the UE receives a CN initiated paging in RRC_INACTIVE state, the UE moves to RRC_IDLE and informs NAS.

[0036] The PF and PO for paging are determined by the following formulae: [0037] SFN for the PF is determined by:

[00001] $(\text{SFN} + \text{PF_offset}) \bmod T = (T \text{div} N) * (\text{UE_ID} \bmod N)$ [0038] Index (i_s), indicating the index of the PO is determined by:

[00002] $i_s = \text{floor}(\text{UE_ID} / N) \bmod N_s$

[0039] The PDCCH monitoring occasions for paging are determined according to pagingSearchSpace as specified in TS 38.213 [5] and firstPDCCH-MonitoringOccasionOfPO if configured as specified in TS 38.331 [2]. When SearchSpaceId=0 is configured for pagingSearchSpace, the PDCCH monitoring occasions for paging are same as for RMSI as defined in clause 13 in TS 38.213 [5].

[0040] When SearchSpaceId=0 is configured for pagingSearchSpace, N_s is either 1 or 2. For $N_s=1$, there is only one PO which starts from the first PDCCH monitoring occasion for paging in the PF. For $N_s=2$, PO is either in the first half frame ($i_s=0$) or the second half frame ($i_s=1$) of the PF.

[0041] When SearchSpaceId other than 0 is configured for pagingSearchSpace, the UE monitors the (i_s+1) .sup.th PO. A PO is a set of ' $S*X$ ' consecutive PDCCH monitoring occasions where ' S ' is the number of actual transmitted SSBs determined according to ssb-PositionsInBurst in SIB1 and X is the nrofPDCCH-MonitoringOccasionPerSSB-InPO if configured or is equal to 1 otherwise. The $[x*S+K]$.sup.th PDCCH monitoring occasion for paging in the PO corresponds to the K .sup.th transmitted SSB, where $x=0, 1, \dots, X-1, K=1, 2, \dots, S$. The PDCCH monitoring occasions for paging which do not overlap with UL symbols (determined according to tdd-UL-DL-ConfigurationCommon) are sequentially numbered from zero starting from the first PDCCH monitoring occasion for paging in the PF. When firstPDCCH-MonitoringOccasionOfPO is present, the starting PDCCH monitoring occasion number of (i_s+1) .sup.th PO is the (i_s+1) .sup.th value of the firstPDCCH-MonitoringOccasionOfPO parameter; otherwise, it is equal to i_s*S*X . If $X>1$, when the UE detects a PDCCH transmission addressed to P-RNTI within its PO, the UE is not required to monitor the subsequent PDCCH monitoring occasions for this PO.

[0042] NOTE 1: A PO associated with a PF may start in the PF or after the PF.

[0043] NOTE 2: The PDCCH monitoring occasions for a PO can span multiple radio frames. When SearchSpaceId other than 0 is configured for pagingSearchSpace the PDCCH monitoring occasions for a PO can span multiple periods of the paging search space.

[0044] The following parameters are used for the calculation of PF and i_s above: [0045] T : DRX cycle of the UE (T is determined by the shortest of the UE specific DRX value(s), if configured by RRC and/or upper layers, and a default DRX value broadcast in system information. In RRC_IDLE state, if UE specific DRX is not configured by upper layers, the default value is applied). [0046] N : number of total paging frames in T [0047] N_s : number of paging occasions for a PF [0048]

PF_offset: offset used for PF determination [0049] UE_ID: 5G-S-TMSI mod 1024

[0050] Parameters N_s , nAndPagingFrameOffset, nrofPDCCH-MonitoringOccasionPerSSB-InPO, and the length of default DRX Cycle are signaled in SIB1. The values of N and PF_offset are derived from the parameter nAndPagingFrameOffset as defined in TS 38.331 [2]. The parameter first-PDCCH-MonitoringOccasionOfPO is signalled in SIB1 for paging in initial DL BWP. For paging in a DL BWP other than the initial DL BWP, the parameter first-PDCCH-MonitoringOccasionOfPO is signaled in the corresponding BWP configuration.

[0051] If the UE has no 5G-S-TMSI, for instance when the UE has not yet registered onto the network, the UE shall use as default identity UE_ID=0 in the PF and i_s formulas above.

[0052] 5G-S-TMSI is a 48 bit long bit string as defined in TS 23.501 [6]. 5G-S-TMSI shall in the

formulae above be interpreted as a binary number where the left most bit represents the most significant bit.

Extended DRX

[0053] eDRX (Extended DRX) is a feature which was introduced by 3GPP in Rel. 13. An enhancement of DRX was introduced to reduce power consumption of IoT devices. eDRX supports a longer DRX cycle than the legacy DRX. For example, in the RRC idle state the paging cycle is extended from 2.56 seconds to 44 minutes in LTE-M and 2.92 hours in NB-IoT.

[0054] The UE can request the use of idle eDRX during the initial attach procedure or tracking area update (TAU) by including the eDRX parameters IE. The network entity MME accepts the request from the UE by providing the eDRX parameters IE according to the network policy when accepting the attach or TAU procedure. The UE will then use the received eDRX parameters for the subsequent procedures. If the UE does not receive any eDRX values from the network, it effectively means that the network rejects the eDRX request, probably since the network does not have eDRX support. In that case, the eDRX parameter is not applied, and legacy DRX is used instead.

[0055] Starting with Rel. 13, 3GPP introduced a hyper system frame number (Hyper SFN or H-SFN) to extend the time span of the time parameters, e.g., the timer used for eDRX. One H-SFN consists of 1024 SFNs, and H-SFN rolls over to 0 after 1024 hyper frames (HF). This results in a maximum H-SFN duration of 29127 h ($1024 \times 10240 \text{ ms} = 10485769 \text{ ms} = 29.127 \text{ h}$). The introduction of H-SFN timing makes the longer paging cycle possible. The UE is reachable for paging in a paging hyperframe (PH), which is a specific set of H-SFN values. Within the PH, the UE monitors the PF and PO in the given Paging Time Window (PTW). PTW is the time period configured for a UE in the eDRX cycle during which the UE monitors paging occasions (PO) on the PDCCH. In the remaining cycle time, the UE does not monitor the PDCCH. Thus, the network considers the UE unreachable for paging until the next paging hyperframe (PH) comes along. A high-level summary of the PH, PF and PO calculation is explained as follows: [0056] The PH is the H-SFN satisfying the following equation: [0057] $\text{H-SFN} \bmod T_{\text{sub.eDRX,H}} = (\text{UE_ID_H} \bmod T_{\text{sub.eDRX,H}})$, where [0058] UE_ID_H: [0059] 10 most significant bits of the Hashed ID, if P-RNTI is monitored on PDCCH or M PDCCH [0060] 12 most significant bits of the Hashed ID, if P-RNTI is monitored on NPDCCH [0061] $T_{\text{sub.eDRX,H}}$: eDRX cycle of the UE in Hyper-frames, ($T_{\text{sub.eDRX,H}} = 1, 2, \dots, 256$ Hyper-frames) (for NB-IoT, $T_{\text{sub.eDRX,H}} = 2, \dots, 1024$ Hyper-frames) and configured by upper layers. [0062] PTW_start denotes the first radio frame of the PH that is part of the PTW and has SFN satisfying the following equation: [0063]

$\text{SFN} = 256 * i_{\text{sub.eDRX}}$, where $i_{\text{sub.eDRX}} = \text{floor}(\text{UE_ID_H} / T_{\text{sub.eDRX,H}}) \bmod 4$. [0064] PTW_end is the last radio frame of the PTW and has SFN satisfying the following equation: [0065] $\text{SFN} = (\text{PTW_start} + L * 100 - 1) \bmod 1024$, where [0066] L = Paging Time Window length (in seconds) configured by upper layers

[0067] For RAT types that support extended DRX for CM-CONNECTED with RRC Inactive state, the AMF passes the UE's accepted idle mode eDRX cycle length value to NG-RAN. If the UE supports eDRX in RRC inactive, based on its UE radio capabilities, NG-RAN configures the UE with an eDRX cycle in RRC-INACTIVE up to the value for the UE's idle mode eDRX cycle as provided by the AMF in "RRC Inactive Assistance Information" or up to 10.24 seconds (whichever is lower). See FIG. 1.

Wake-Up-Signal

[0068] A wake-up signal (WUS) was introduced in 3GPP Rel. 15 and at first glimpse, it looks like a repetition of the paging indicator channel introduced in 3GPP Rel. 99 (UM TS). With the paging indicator channel, the network sends physical layer information that indicates whether the UE should read the higher layer control information on the respective control channels. The advantage is that recognition of the paging indicator channel is based on a matched filter or correlation metric, a sort of low power receiver, and does not require more energy consuming demodulation and

decoding operations with the main baseband receiver. Without WUS, the UE would have to monitor the PDCCH for paging at each PO. With the WUS approach, the UE only needs to decode the PDCCH when WUS is detected, otherwise, the UE will stay in sleep mode.

[0069] WUS duration is the maximum time duration configured by the network for the UE to detect the WUS. The UE can expect WUS repetitions during “Configured maximum WUS duration” but the actual WUS transmission can be shorter, e.g., for UE in good coverage. After WUS is detected, the network leaves a time gap to allow the UE to resynchronize to the network and eventually switch from the low-power wake-up receiver to the main baseband circuitry in order to be ready to decode the PDCCH. If UE detects the WUS, the UE shall monitor the following N paging occasions ($N=1$ for non-extended DRX) unless it has received a paging message; For a UE configured with extended DRX, the WUS can be associated to one or multiple paging occasion(s) ($N \geq 1$) in a PTW; The paging operation in the CN (AMF/MME) is not aware of the use of the WUS in the RAN (gNB/eNB). See FIG. 2.

Support of Reduced Capability NR Devices

[0070] The use cases identified for 5G are Enhanced Mobile Broadband (eMBB), Massive Machine-Type Communication (mM TC) and Ultra-Reliable and Low Latency Communication (URLLC). Time Sensitive Communication (TSC) was also identified as a use case at the boundary between mM TC and URLLC.

[0071] Support for eMBB and URLLC were introduced in Release 15. URLLC was further enhanced in Release 16 with the enhanced URLLC (eURLLC) and Industrial IoT work items. Release 16 also introduced support for Time-Sensitive Networking (TSN) and 5G integration for TSC use cases. In the 3GPP study on “self-evaluation towards IMT-2020 submission” it was confirmed that NB IoT and LTE M fulfill the IMT-2020 requirements for mMTC and can be certified as 5G technologies.

[0072] In Release 17, a new set of use cases with requirements at the boundary of eMBB, URLLC and mM TC is being studied. These use cases include Industrial Wireless Sensor Networks (IWSN), smart cities and wearables.

[0073] IWSN use cases and requirements are described in TR 22.804 [7], TS 22.104 [8], TR 22.832 [9] and TS 22.261 [10]. Devices in such an environment include e.g., pressure sensors, humidity sensors, thermometers, motion sensors, accelerometers, actuators, etc. Connecting these types of devices to 5G networks and core will allow connected industries to improve flexibility, enhance productivity and efficiency, reduce maintenance cost, and improve operational safety.

[0074] The smart city use case and requirements are described in TS 22.804 [7]. The smart city vertical covers data collection and processing to more efficiently monitor and control city resources, and to provide services to city residents. Surveillance cameras are expected to be an essential part of a smart city.

[0075] The wearables use case includes smart watches, rings, eHealth related devices, and medical monitoring devices etc. Devices supporting the wearables use case are expected to be small in size and may also be constrained in terms of power.

[0076] The Release 17 SID on Support of Reduced Capability NR Devices defines generic requirements for these use cases as follows: [0077] Device Complexity: Main motivation for the new device type is to lower the device cost and complexity as compared to high-end eMBB and URLLC devices of Rel-15/Rel-16. This is especially the case for industrial sensors. [0078] Device Size: Requirement for most use cases is that the standard enables a device design with compact form factor. [0079] Deployment Scenarios: System should support all FR 1/FR 2 bands for FDD and TDD.

[0080] The Release 17 SID on Support of Reduced Capability NR Devices defines use case specific requirements as follows: [0081] Industrial Wireless Sensors: Communication service availability is 99.99% and end-to-end latency less than 100 ms. The reference bit rate is less than 2 M bps (potentially asymmetric e.g., UL heavy traffic) for all use cases and the device is stationary.

The battery should last at least few years. For safety related sensors, latency requirement is lower, 5-10 ms. [0082] Video Surveillance: The reference economic video bitrate would be 2-4 Mbps, latency <500 ms, reliability 99%-99.9%. High-end video e.g., for farming would require 7.5-25 Mbps. It is noted that traffic pattern is dominated by UL transmissions. [0083] Wearables: Reference bitrate for smart wearable application can be 10-50 M bps in DL and minimum 5 M bps in UL and peak bit rate of the device higher, 150 M bps for downlink and 50 M bps for uplink. Battery of the device should last multiple days (up to 1-2 weeks).

Issue Statement #1: PTW Configuration and Optimization

[0084] In LTE DRX, a UE is expected to wake up for a specific sub-frame called the Paging Occasion (PO) to monitor the Physical Downlink Control Channel (PDCCH) for paging. In NR, due to the beam sweeping feature, a PO is a set of 'S*X' consecutive PDCCH monitoring occasions where 'S' is the number of actual transmitted SSBs determined according to $\text{ssb-PositionsInBurst}$ in SIB 1 and X is the $\text{nrofPDCCH-MonitoringOccasionPerSSB-InPO}$ if configured or is equal to 1 otherwise. The $[x*S+K].\text{sup.th}$ PDCCH monitoring occasion for paging in the PO corresponds to the $K.\text{sup.th}$ transmitted SSB, where $x=0, 1, \dots, X-1$, $K=1, 2, \dots, S$ is a set of PDCCH monitoring occasions and can consist of multiple time slots (e.g., subframe or OFDM symbol) where paging DCI can be sent. When $\text{firstPDCCH-MonitoringOccasionOfPO}$ is present, the starting PDCCH monitoring occasion number of $(i_s+1).\text{sup.th}$ PO is the $(i_s+1).\text{sup.th}$ value of the $\text{firstPDCCH-MonitoringOccasionOfPO}$ parameter; otherwise, it is equal to i_s*S*X . Therefore, in multi-beam operations, a PO associated with a PF may start in the PF or after the PF. The PDCCH monitoring occasions for a PO can span multiple radio frames. When SearchSpaceId other than 0 is configured for paging-SearchSpace the PDCCH monitoring occasions for a PO can span multiple periods of the paging search space.

[0085] With reference to FIG. 3, in LTE eDRX, PTW_start denotes the first radio frame of the PH that is part of the PTW and PTW_end is the last radio frame of the PTW. The UE stop monitoring POs that are outside of PTW. The length of PTW is determined by the core network independent of RAN. However, there are several issues if NR reuses the same eDRX design as in LTE described in the conventional Wake-up-Signal section. In NR, the RAN determines the length of a PO by configuring the number of actual transmitted SSBs and the number of PDCCH Monitoring Occasions associated with an SSB. On the other hand, the length of PTW is configured by the core network independently. There is no coordination between RAN and the core network about the configuration of the PTW of a UE. Therefore, if a PTW of the UE is not configured properly, the PTW may end before the PO end and a UE cannot receive a Paging DCI. For example, as shown in FIG. 2, if a PO starts towards the end of PTW, the UE may miss the paging DCI due to termination of PTW. Once the paging is missed, the UE has to wait for the next eDRX cycle to receive the paging, which introduces at least 10 seconds delay. Therefore, there is a need for a mechanism that reduce the possibility that a UE misses a paging message due to the termination of PTW.

Issue Statement #2: Power Saving for Different Traffic Profiles

[0086] In LTE, devices negotiate eDRX configuration as part of initial power up attach procedure or during Tracking Area Update (TAU) procedure and never in between. A reduced capability device cannot dynamically turn on and off eDRX mode of operation or change eDRX configuration based on its traffic profiles. In one example, the upper layer has traffic A and traffic B. The traffic A is not delay tolerant and the UE cannot be in eDRX mode when the traffic is active. The traffic B is delay tolerant and the UE can be in eDRX mode when all other traffics on the node is delay tolerant. When both traffic A and traffic B are active, the UE cannot be in the eDRX mode. However, when traffic A is terminated, the UE cannot switch into eDRX mode immediately since it has can only turn on or off eDRX during next periodic TAU. In another example, both traffic A and traffic B are delay tolerant but have different delay tolerant requirements. For example, traffic A can tolerant 30 seconds delay and traffic B can tolerant 30 minutes delay. When only traffic A is active, the UE can choose an eDRX cycle length T_1 that is 20.48 seconds. When only traffic B is

active, the UE can choose an eDRX cycle length T2 that is 1310.72 seconds. When traffic A and traffic B are both active, the eDRX cycle length should be set up to T1. However, when traffic A is terminated, the UE continues using the eDRX cycle T1 until configured by the network during the next TAU. This is power inefficient for the UE that only has traffic B is running since it has to wake up and monitoring a paging every 20.48 seconds. Therefore, there is a need for a mechanism that the eDRX parameter of UE can be configured dynamically.

[0087] Moreover, Commercial Mobile Alert System (CMAS), Earthquake and Tsunami Warning System (ETWS), and Public Warning System (PWS) delivery requirements (e.g., delay requirements) may not be met when a UE is in eDRX in LTE or NR. UEs that support CMAS and PWS cannot use eDRX with longer values. Therefore, it is power inefficient for RedCap (Reduced Capability) devices, e.g., wearables, which support CMAS and PWS.

[0088] Shorter values for the eDRX cycles, such as 2.56 seconds, have also been studied for RedCap device. For the lower bound of the eDRX cycle, one motivation to support shorter DRX cycles is that at least some RedCap UEs should be able to support the reception of emergency broadcast services (e.g. CMAS, ETWS, PWS) within the required delay budget of 4 seconds while still achieving power saving. This requirement is not possible to be met with longer eDRX cycle lengths. Certain RedCap UEs may not be required to receive emergency alerts, e.g., CMAS, PWS, ETWS. Furthermore, some RedCap UEs are only required to receive these alerts periodically or when certain conditions or dynamic criteria for reception of these alerts apply. The network should have a method to identify these cases/devices and optimize power saving for these devices that need not receive the alerts.

[0089] If a RedCap UE is configured to use a shorter eDRX cycle such as 2.56 s for enabling broadcast emergency services (e.g., EWTS, CMAS, PWS), RedCap UEs do not need to monitor gNB configured default paging (and RAN paging) cycles which presents a potential risk of UE missing SI change indicator.

Disclosed Systems Associated with the Aforementioned Problems

Systems for Issue Statement #1

Paging Time Window Extension

[0090] Disclosed herein is a description of subject matter for a UE to extend the length of its configured Paging Time Window. In an example, a UE may extend its PTW implicitly without receiving an indication from gNB to extend its PTW. In another example, a UE may extend its PTW explicitly after receiving an indication from gNB to extend its PTW. Implicit Paging Time Window Extension

Disclosed herein is a description of subject matter for a UE **201** to extend its PTW implicitly without receiving an indication from gNB **202** to extend its PTW. In the first disclosed method in FIG. **4** that may include step **210**-step **213**, the UE **201** the UE monitors an incomplete PDCCH monitoring occasion, meaning the UE monitors a PDCCH monitoring occasion that overlaps with the PTW, but is not fully contained within the PTW. Additionally, in one embodiment, when a UE **201** is monitoring a PO, it may continue monitoring the PO beyond the PTW_end radio frame. In another embodiment, when the UE is monitoring a PDCCH monitoring occasion, it may continue monitoring the PDCCH monitoring occasion beyond the PTW_end radio frame. In yet another embodiment, a UE may not monitor an incomplete PDCCH monitoring occasion, i.e., the UE only monitors a complete PDCCH monitoring occasion, meaning a PDCCH monitoring occasion that is fully contained within the PTW. In another disclosed method in FIG. **5** that may include step **220**-step **223**, the UE monitors a PDCCH monitoring occasion that is outside the PTW but belongs to a PO that overlaps with the PTW. In one embodiment, the UE monitors all the PDCCH monitoring occasions outside PTW, that belongs to a PO that overlaps with the PTW. In another embodiment, the UE monitors only a predefined or preconfigured number of PDCCH monitoring occasions outside PTW, that belongs to a PO that overlaps with the PTW, for example the UE may monitor only the first PDCCH monitoring occasion outside PTW, that belongs to a PO that overlaps with

the PTW. In another embodiment, a UE may not monitor an incomplete PO, i.e., the UE only monitors a complete PO, meaning a PO that is fully contained with the PTW. Alternatively, the UE monitors PDCCH monitoring occasions until a page is received within the PO or until the PO ends. In yet another embodiment, when a UE **201** is not monitoring a PO at the end of PTW_end radio frame, a UE **201** may continue monitoring the next POs beyond the PTW_end radio frame if the PO is associated with a Paging Frame that overlaps with the PTW. For example, if PTW_end radio frame is a Paging Frame, and the PO does not start in the radio frame, the UE **201** continues monitoring the PO associated with the Paging Frame. In another example, if PTW_end radio frame is not a Paging frame and the PO associated with the previous Paging frame does not start, the UE continues monitoring the PO beyond the PTW_end radio frame. Furthermore, if at any point, the UE receives a page within the PO, the UE may stop monitoring additional PDCCH monitoring occasions, including prior to the PTW_end radio frame.

Explicit Paging Time Window Extension

[0091] Disclosed herein is a description of subject matter for a UE **201** to extend its PTW explicitly after receiving an indication from gNB **202** to extend its PTW. In the disclosed method in FIG. **6** that may include step **230**-step **234**, gNB **202** sends a PTW extension indication at step **233** before sending a paging DCI at step **234**. After receiving the PTW extension indication at step **233**, a UE **201** continues monitoring the next n POs which may be beyond the PTW_end radio frame. n is Number of consecutive Paging Occasions (PO) mapped to one PTW extension indication provided in system information where (n≥1). Alternatively, the value of n can be indicated in the paging extension indication message. Alternatively, the value n can be configured via RRC configuration. The PTW extension indication can be sent to a device whose receiver and signal detection is based on a matched filter or simple correlator with low power consumption, a sort of low power receiver, and does not require high energy-consuming demodulation and decoding processing with the main high-complex baseband receiver. In one example, the PTW extension indication can be a Wake-Up-Signal (WUS). When UE **201** detects WUS, the UE **201** monitors the subsequent n POs which may be beyond the PTW_end radio frame or until a paging message including the UE's NAS identity is received, whichever is earlier. In another example, the PTW extension indication may be a RS (e.g., DMRS, CSI-RS, TRS) or a pre-defined sequence.

PTW Configuration Optimization Using Cell Specified PTW

[0092] A method is disclosed to reduce the possibility that a UE **201** misses a paging message due to the termination of PTW. In this method as shown in FIG. **7** that may include step **241**-step **250**, the gNB **202** periodically broadcast in system information a cell specific PTW length which is determined by the gNB **202** based on the beam sweeping or SSB burst patterns. A UE **201** can obtain the cell specific PTW length in the system information. When a UE **201** registers in the network, it negotiates with the AMF **203** and obtains the UE specific PTW length determined by AMF **203**. The UE **201** uses the max value of UE specific PTW length and cell specific PTW length as its PTW length. The detailed description of the method is as follows.

[0093] Step **241** of FIG. **7**: gNB **202** periodically broadcasts the cell specific PTW length in the system information. In one example, the gNB **202** broadcast default PTW length in the PCCH-config in the DownlinkConfigCommonSIB information element. The PTW length value s1 corresponds to 1 unit which is 1.24 second, value s2 corresponds to 2 units which is 2.48 second and so on. See Table 1.

TABLE-US-00001 TABLE 1 DownlinkConfigCommonSIB ::= SEQUENCE {
frequencyInfoDL FrequencyInfoDL-SIB, initialDownlinkBWP BWP-
DownlinkCommon, bcch-Config BCCH-Config, pcch-Config PCCH-
Config, ... } PCCH-Config ::= SEQUENCE { defaultPagingCycle PagingCycle
defaultPTWLength PTWLength nAndPagingFrameOffset CHOICE {
oneT NULL, halfT INTEGER (0..1), quarterT
INTEGER (0..3), oneEighthT INTEGER (0..7), oneSixteenthT

INTEGER (0..15) }, ns ENUMERATED {four, two, one}, firstPDCCH-MonitoringOccasionOfPO CHOICE { sCS15KHzZoneT SEQUENCE (SIZE (1..4)) OF INTEGER (0..139), sCS30KHzZoneT-SCS15KHzhalfT SEQUENCE (SIZE (1..4)) OF INTEGER (0..279), sCS60KHzZoneT-SCS30KHzhalfT-SCS15KHzquarterT SEQUENCE (SIZE (1..4)) OF INTEGER (0..559), sCS120KHzZoneT-SCS60KHzhalfT-SCS30KHzquarterT-SCS15KHzZoneEighthT SEQUENCE (SIZE 1..4)) OF INTEGER (0..1119), sCS120KHzhalfT-SCS60KHzquarterT-SCS30KHzZoneEighthT-SCS15KHzZoneSixteenthT SEQUENCE (SIZE (1..4)) OF INTEGER (0..2239), sCS120KHzquarterT-SCS60KHzZoneEighthT-SCS30KHzZoneSixteenthT SEQUENCE (SIZE (1..4)) OF INTEGER (0..4479), sCS120KHzZoneEighthT-SCS60KHzZoneSixteenthT SEQUENCE (SIZE (1..4)) OF INTEGER (0..8959), sCS120KHzZoneSixteenthT SEQUENCE (SIZE (1..4)) OF INTEGER (0..17919) } OPTIONAL, -- Need R ... } PTWLength::= ENUMERATED (s1, s2, s3, s4, s5, s6, s7, s8, s9, s10, s11, s12, s13, s14, s15, s16, . . .)

[0094] Step **242** of FIG. 7: After receiving the system information, the UE **201** obtains the cell specific PTW and selects the cell to establish AS connections.

[0095] Step **243** of FIG. 7: The UE **201** establishes an AS connection with the gNB **202**.

[0096] Step **244** of FIG. 7: The UE **201** registers to the core network by sending a registration request to the AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE **201** is a RedCap UE and associated capabilities, requirements, and characteristics. In some embodiments, the RedCap capabilities or assistance may also include charging and energy characteristics. This may enable paging (re) configurations that are modified based on wireless power transfer and energy harvesting (e.g., RF charging, solar power), power dissipation or charging rates, and power level thresholds. Note that these energy/power methods may be variable and dynamic in nature, triggering paging configuration modifications to appropriately adapt power saving gains associated with e.g., longer eDRX cycles and shorter PTW or latency reductions with e.g., shorter DRX cycles and longer PTW. The registration request also includes the eDRX parameter information element for the UE **201** to enable eDRX. The eDRX parameter may include the cell specific PTW length of UE **201**.

[0097] Step **245** of FIG. 7: The AMF **203** decides whether to accept or reject the request of UE **201** for enabling eDRX. The AMF **203** also decides if the eDRX parameter(s) are acceptable, partially acceptable, or not acceptable. Determination of whether to accept or reject the request may be based on a number of factors including, e.g., requirements for delivering emergency alerts, identified device type (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity or traffic load of a network. Paging capacity can be directly impacted dependent upon duration of the configured paging timer windows.

[0098] Step **246** of FIG. 7: The AMF **203** sends a registration accept message to the UE **201**. If the AMF **203** accepts the request of UE **201** for enabling eDRX, the message contains the eDRX parameter information element for the UE to use eDRX. The eDRX parameter contains the eDRX cycle and the PTW length.

[0099] Step **247** of FIG. 7: The UE **201** starts monitoring Paging Occasions using the maximum value of UE specific and cell specific PTW length.

[0100] Step **248** of FIG. 7: The AMF **203** sends a paging request with eDRX and DRX parameter to the gNB **202** which includes the Paging eDRX parameters including paging eDRX Cycle and UE specific PTW length.

[0101] Step **249** of FIG. 7: If UE specific PTW length is included in the paging request, the gNB **202** uses the maximum value of UE specific and cell specific PTW length to determine whether it should send a paging DCI in the next PO associated with the UE **201**.

[0102] Step **250** of FIG. 7: The UE **201** receives a paging DCI- and then receives the paging message from the gNB **202**.

[0103] With regard to FIG. 8, when a UE 201 moves to another cell, the UE 201 can reselect the new cell and obtains the new cell specific PTW. FIG. 8 shows an example that a UE 201 moves to a new cell of gNB 204 from gNB 202 and obtains the new cell specific PTW. The detailed description of the method is as follows.

[0104] Step 260 of FIG. 8: The UE 201 establishes an AS connection with the gNB 202.

[0105] Step 261 of FIG. 8: The UE 201 registers to the core network configured eDRX parameter provided AMF 203. The registration process may include identification of the UE capabilities to determine whether or not the UE 201 is a RedCap UE and associated capabilities, requirements, and characteristics.

[0106] Step 262 of FIG. 8: The UE 201 releases the AS connection with the gNB 202.

[0107] Step 263 and Step 264 of FIG. 8: The UE 201 moves to a new cell. The UE performs cell reselection on the new cell and obtains the new cell specified PTW as part of the system information from gNB 204. The UE 201 starts monitoring Paging Occasions using the maximum value of UE specific and cell specific PTW length.

[0108] Step 265 of FIG. 8: The AMF 203 sends a paging request with eDRX and DRX parameter to the gNB 204 which includes the Paging eDRX parameters including paging eDRX Cycle and UE specific PTW length.

[0109] Step 266 of FIG. 8: If UE specific PTW length is included in the paging request, the gNB 204 uses the maximum value of UE specific and cell specific PTW length to determine whether it should send paging DCI in the next PO associated with the UE 201.

[0110] Step 267 of FIG. 8: The UE 201 receives a paging DCI from gNB 204 and then receives the paging message from the gNB 204.

gNB Assisted PTW Configuration Optimization

[0111] Methods are disclosed for a gNB 270 to assist the Core Network to configure UE's PTW to reduce the possibility that a UE 201 misses a paging message due to the termination of PTW. In the first disclosed method shown in FIG. 9 that may include step 270-step 275, after receiving the registration request from the UE 201, the AMF 203 sends a request to obtain gNB 202 assistance information, e.g., beam sweeping/SSB pattern of which the UE 201 is connected to. The AMF 203 decides the PTW based on the beam sweeping information. The detailed description of the method is as follows.

[0112] Step 270 of FIG. 9: The UE 201 establishes an AS connection with the gNB 202

[0113] Step 271 of FIG. 9: The UE 201 registers to the core network by sending a registration request to the AMF 203. The registration process may include identification of the UE capabilities to determine whether or not the UE 201 is a RedCap UE and associated capabilities, requirements, and characteristics (e.g., UE power/energy characteristics). The registration request also includes the eDRX parameter information element for the UE 201 to enable eDRX.

[0114] Step 272 of FIG. 9: The AMF 203 may send a request to the gNB 202 to obtain gNB 202 assistance information, e.g., beam sweeping information for the UE 201 if it does not know the beam sweeping information of the gNB 202. In one example, the AMF 203 requests to obtain the cell specific PTW of the gNB 202.

[0115] Step 273 of FIG. 9: The gNB 202 reports its gNB assistance information, e.g., beam sweeping information associated with the UE 201. In one example, the gNB 202 sends an NG SETUP REQUEST to the AMF 203 and includes the default PTW length it uses to send a paging DCI to the UE 201. In another embodiment, the gNB 202 sends a UE RADIO CAPABILITY INFO INDICATION to the AMF 203 and includes the supported PTW length it uses to send a paging DCI to the UE 201 in the UERadioCapabilityForPaging Information Element, which includes the RRC UERadioPagingInformation message as defined in [2]. See Table 2 and Table 3.

TABLE-US-00002 TABLE 2 -- NG SETUP REQUEST -- --

```
***** NGSetupRequest ::=
SEQUENCE{    protocolIEs    ProtocolIE-Container    { {NGSetupRequestEs} },    ... }
```

```

NGSetupRequestIEs NGAP-PROTOCOL-IES ::= { { ID id-GlobalRANNodeID
CRITICALITY reject TYPE GlobalRANNodeID PRESENCE mandatory }| { ID id-
RANNodeName CRITICALITY ignore TYPE RANNodeName PRESENCE
optional }| { ID id-SupportedTAList CRITICALITY reject TYPE SupportedTAList
PRESENCE mandatory }| { ID id-DefaultPagingDRX CRITICALITY ignore TYPE
PagingDRX PRESENCE mandatory }| { ID id-DefaultPTWLength CRITICALITY
ignore TYPE PTWLength PRESENCE mandatory }| { ID id-
UERetentionInformation CRITICALITY ignore TYPE UERetentionInformation
PRESENCE optional }| { ID id-NB-IoT-Default@PagingDRX CRITICALITY ignore TYPE
NB-IoT-DefaultPagingDRX PRESENCE optional }, ... } -- UE RADIO CAPABILITY INFO
INDICATION -- -- *****
UERadioCapabilityInfoIndication ::= SEQUENCE { protocolIEs ProtocolIE-Container
{ {UERadioCapabilityInfoIndicationIEs} }, ... } UERadioCapabilityInfoIndicationIEs
NGAP-PROTOCOL-IES ::= { { ID id-AMF-UE-NGAP-ID CRITICALITY reject TYPE
AMF-UE-NGAP-ID PRESENCE mandatory }| { ID id-RAN-UE-NGAP-ID
CRITICALITY reject TYPE RAN-UE-NGAP-ID PRESENCE mandatory }| { ID id-
UERadioCapability CRITICALITY ignore TYPE UERadioCapability PRESENCE
mandatory }| { ID id-UERadioCapabilityForPaging CRITICALITY ignore TYPE
UERadioCapabilityForPaging PRESENCE optional }| { ID id-UERadioCapability-
EUTRA-Format CRITICALITY ignore TYPE UERadioCapability PRESENCE
optional }, ... }
TABLE-US-00003 TABLE 3 UERadioPagingInformation message -- ASN1START
UERadioPagingInformation ::= SEQUENCE { criticalExtensions CHOICE {
c1 CHOICE ueRadioPagingInformation UERadioPagingInformation-IEs,
spare7 NULL, spare6 NULL, spare5 NULL, spare4 NULL, spare3
NULL, spare2 NULL, spare1 NULL }, criticalExtensionsFuture SEQUENCE {
} } UERadioPagingInformation-IEs ::= SEQUENCE { supportedBandListNRForPaging
SEQUENCE (SIZE (1..maxBands)) OF FreqBandIndicatorNR OPTIONAL,
supportedPTWForPaging OCTET STRING OPTIONAL, nonCriticalExtension
SEQUENCE { } OPTIONAL } -- ASN1STOP

```

[0116] Step **274** of FIG. **9**: The AMF **203** decides whether to accept or reject the UE's request for enabling eDRX. The AMF **203** also determines PTW based on beam sweeping information, e.g., the cell specific PTW. Determination of whether to accept or reject the eDRX request may be based on a number of factors including, e.g., requirements for delivering emergency alerts, identified device type (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity or traffic load of a network. Paging capacity can be directly impacted dependent upon duration of the configured paging timer windows.

[0117] Step **275** of FIG. **9**: The AMF **203** sends a registration accept message to the UE **201**. If the AMF **203** accepts the request of UE **201** for enabling eDRX, the message includes the eDRX parameter information element for the UE **201** to use eDRX. The eDRX parameter includes the eDRX cycle and the PTW length.

[0118] When a UE **201** moves to another cell, the UE **201** can reselect the new cell and needs to notify the core network about beam sweeping information of the new cell. FIG. **10** (step **280a**-step **286**) and FIG. **11** (step **290a**-step **296**) show examples of a UE **201** that moves to a new cell of gNB **204** from gNB **202** and re-negotiates the PTW. Re-negotiating the PTW requires the UE **201** to switch into RRC_Connected state, which consumes more power than RRC_Idle and RRC_Inactive states. Therefore, mechanisms are disclosed for a UE **201** to reduce the possibility of re-negotiating the PTW. In the first mechanism, a PTW validation area is disclosed which includes a group of cells that have the same or similar beam sweeping patterns. When a UE **201** is moving within a PTW validation area, the UE **201** does not need to re-negotiate the PTW with the AMF

203. In one example, the core network provides the list of cells that is in the PTW validation area when UE **201** registers to the network. In another example, the serving gNB **202** of the UE **201** provides the list of cells that is in the PTW validation area when bringing the UE **201** to RRC inactive state. In yet another example, the serving gNB **202** of the UE **201** provides the list of cells that is in the PTW validation area when bringing the UE **201** to RRC idle state. In the second mechanism, the UE **201** compares the beam sweeping pattern of the new cell with the previous cell. In one example, the UE **201** compares the `ssb-PositionsInBurst` in `SIB1 nrofPDCCH-MonitoringOccasionPerSSB-InPO` and `firstPDCCH-MonitoringOccasionOfPO` parameter of the previous cell. In another example, the UE **201** compares the cell specific PTW broadcasted by the new cell with the value of the previous cell. The UE **201** does not need to re-negotiate PTW if the new cell has the same beam sweeping patterns.

[0119] In the method described in FIG. **10**, if the UE **201** decides to update its PTW, the UE **201** sends a NAS message to the AMF **203** to obtain the new PTW configuration. The detailed description of the method is as follows.

[0120] Step **280a** of FIG. **10**: The UE establishes an AS connection with the gNB **202**.

[0121] Step **280b** of FIG. **10**: The UE registers to the core network configured eDRX parameter provided AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE is a RedCap UE and associated capabilities, requirements, and characteristics. During the eDRX configuration, the AMF **203** may provide the list of cells that is in the PTW validation area when the UE **201** registers to the network.

[0122] Step **280c** of FIG. **10**: The UE releases the AS connection with the gNB **202**. gNB **202** may provide the list of cells that is in the PTW validation area when bring the UE **201** to RRC inactive state.

[0123] Step **281** of FIG. **10**: The UE **201** moves to a new cell of gNB **204**. The UE **201** obtains the cell system information and reselects the new cell. Based on the system information, the UE **201** decides whether to re-negotiate the PTW. If the UE **201** decides to re-negotiate the PTW, it triggers the procedure in step **282**.

[0124] Step **282** of FIG. **10**: The UE sends a registration update request to the AMF.

[0125] Step **283** of FIG. **10**: The AMF **203** sends a request to the gNB **204** to obtain gNB assistance information, e.g., beam sweeping information for the UE **201**.

[0126] Step **284** of FIG. **10**: The gNB **204** reports its gNB assistance information, e.g., beam sweeping information associated with the UE **201**. In one example, the gNB **204** sends an NG SETUP REQUEST to the AMF **203** and includes the default PTW length it uses to send a paging DCI to the UE **201**. In another example, the gNB **204** sends a UE RADIO CAPABILITY INFO INDICATION to the AMF **203** and includes the default PTW length it uses to send a paging DCI to the UE **201** in the `UERadioCapabilityForPaging` Information Element.

[0127] Step **284**: The AMF **203** determines a new PTW based on beam sweeping information, e.g., the cell specific PTW.

[0128] Step **285** of FIG. **10**: The AMF **203** sends a registration update accept message to the UE **201** with the new PTW length.

[0129] In the method described in FIG. **11**, if the UE **201** decides to update its PTW, the UE **201** sends an AS message to the gNB **204** to obtain the new PTW configuration. The detailed description of the method is as follows.

[0130] Step **290a** of FIG. **11**: The UE **201** establishes an AS connection with the gNB **202**.

[0131] Step **290b** of FIG. **11**: The UE **201** registers to the core network configured eDRX parameter provided AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE **201** is a RedCap UE and associated capabilities, requirements, and characteristics. During the eDRX configuration, the AMF **203** may provide the list of cells that is in the PTW validation area when the UE **201** registers to the network.

[0132] Step **290c** of FIG. **11**: The UE **201** releases the AS connection with the gNB **202**. gNB **202**

may provide the list of cells that is in the PTW validation area when moving the UE **201** to RRC inactive state.

[0133] Step **291** of FIG. **11**: The UE **201** moves to a new cell of gNB **204**. The UE **201** obtains the cell system information and reselects the new cell. Based on the system information, the UE **201** decides whether to re-negotiate the PTW. If the UE **201** decides to re-negotiate the PTW, it triggers the procedure in step **292**.

[0134] Step **292** of FIG. **11**: The UE **201** sends an AS message to the gNB **204** indicating it intends to re-negotiate the new PTW. The UE **201** may include its previous PTW length in the message.

[0135] Step **293** of FIG. **11**: Based on the previous PTW length of UE **201**, the gNB **204** may decide whether to update the PTW value of the UE **201**. This decision may be further based on a number of factors including, e.g., requirements for delivering emergency alerts, identified device type or capabilities (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity or traffic load of the gNB **204**. Paging capacity can be directly impacted dependent upon duration of the configured paging timer windows. If the gNB **204** decides not to update the UE's PTW value, it sends the UE **201** to RRC_Idle or RRC_Inactive state. Otherwise, gNB **204** sends a request to the AMF **203** on behalf of the UE **201** to obtain a new PTW value. gNB **204** also reports its gNB assistance information, e.g., beam sweeping information associated with the UE **201**. In one example, the gNB **204** sends an NG SETUP REQUEST to the AMF **203** and includes the default PTW length it uses to send a paging DCI to the UE **201**. In another example, the gNB **204** sends a UE RADIO CAPABILITY INFO INDICATION to the AMF **203** and includes the default PTW length it uses to send a paging DCI to the UE **201** in the UERadioCapabilityForPaging Information Element.

[0136] Step **294** of FIG. **11**: The AMF **203** determines a new PTW based on beam sweeping information, e.g., the cell specific PTW. The AMF **203** may also determine a new PTW based on additional factors including, e.g., requirements for delivering emergency alerts, identified device type or capabilities (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity or traffic load of the network.

[0137] Step **295** of FIG. **11**: The AMF **203** sends an RRC assistance information message to the gNB **204**, which includes the new PTW length assigned to the UE **201**.

[0138] Step **296** of FIG. **11**: The gNB **204** sends an AS message to the UE **201** with the newly assigned PTW length.

Systems for Issue Statement #2

[0139] The eDRX parameter of the UE **201** can be configured dynamically. In an example, UE **201** initiated methods are disclosed for a UE **201** to dynamically turn on and off eDRX mode of operation or change eDRX configuration. In another example, network initiated methods are disclosed to dynamically turn on and off eDRX mode of operation or change eDRX configuration of a UE **201**.

UE Initiated Dynamic eDRX Configuration

[0140] Disclosed herein is a description of subject matter for a UE **201** to dynamically turn on and off eDRX mode of operation or change eDRX configuration. The UE **201** may request to change eDRX configurations based on its traffic profiles or triggered by its upper layer. In the first disclosed method in FIG. **12**, the UE **201** may send a mobility registration update to re-negotiate the eDRX cycle when requesting to change eDRX configurations. The detailed description of the method is as follows.

[0141] Step **300** of FIG. **12**: The UE **201** registers to the Core Network and obtains the initial DRX configuration from AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE **201** is a RedCap UE and associated capabilities, requirements, and characteristics. In one example, the UE **201** has an initial DRX configuration received from the AMF **203**, and the UE **201** has both traffic A and traffic B that are delay tolerant but have different delay tolerant requirements. Traffic A can tolerant 30 seconds delay and traffic B

can tolerant 30 minutes delay. When traffic A and traffic B are both active, the eDRX cycle length should be set up to 20.48 second in order to meet the delay requirement of Traffic A.

[0142] Step **301** of FIG. **12**: An event is triggered to update eDRX configuration. For example, when the traffic profiles or energy/power characteristics on the UE **201** changes, the UE **201** decides whether to re-negotiate its eDRX parameters, e.g., eDRX cycle, with the core network. As an example, when traffic A is terminated and only traffic B is active, the UE **201** can choose an eDRX cycle length that is 1310.72 seconds dependent upon e.g., delay tolerant traffic requirements. The UE **201** sends a registration update request to the AMF **203** to re-negotiate its eDRX cycle to reduce its power consumption in step **302**. In an another example, when the charging or battery power level reaches a configured threshold, the UE **201** sends a registration update request to the AMF **203** to re-negotiate its eDRX cycle to either reduce its power consumption or decrease latency with a shorter eDRX cycle in step **302**.

[0143] Step **302** of FIG. **12**: The UE **201** sends a registration update request to the AMF **203** to re-negotiate its eDRX cycle. In the request, the UE **201** may include the disclosed new eDRX cycle, e.g., 1310.72 seconds in the eDRX parameters information elements.

[0144] Step **303** of FIG. **12**: The AMF **203** decides whether to accept or reject the UE request for using the new eDRX parameter(s) and send a response to the UE **201**. Determination of whether to accept or reject the request may be based on a number of factors including, e.g., requirements for delivering emergency alerts, identified device type or capabilities (RedCap, RedCap type, or non-RedCap and UE power/energy characteristics), determined/calculated available paging capacity or traffic load of a network. Paging capacity can be directly impacted dependent upon duration of the configured paging timer windows.

[0145] Step **304** of FIG. **12**: The AMF **203** sends a registration update accept message with the new eDRX parameter to the UE **201**. The UE **201** uses the new eDRX cycle to monitor Paging Occasions.

[0146] In another disclosed method in FIG. **13** and FIG. **14**, the UE **201** sends a request to the gNB when an eDRX configuration update is triggered by the upper layers or a traffic profile change. The gNB **202** assists the UE **201** to dynamically turn on and off eDRX mode of operation or change eDRX configuration based on the information in the request, e.g. its traffic profiles. FIG. **13** shows an example procedure that eDRX configuration update is triggered by the change of UE traffic profile when the UE **201** is in RRC_Idle state. In the procedure, the UE **201** sends an AS message to the gNB **202** to update its eDRX parameter(s). The message may indicate the traffic profile change information. The message may also include the disclosed eDRX parameter in the message. The gNB **202** determines whether or not the eDRX parameter(s) of the UE **201** need to be changed based on information obtained from the core network. The detailed description of the method is as follows.

[0147] Step **310a** of FIG. **13**: The UE **201** registers to the Core Network and obtains the initial DRX configuration from AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE **201** is a RedCap UE and associated capabilities, requirements, and characteristics. In one example, the UE **201** has an initial DRX configuration received from the AMF **203**, and the UE **201** has traffic A and traffic B. The traffic A is not delay tolerant and the UE **201** cannot be in eDRX mode when the traffic is active. The traffic B is delay tolerant and the UE **201** can be in eDRX mode when all other traffic on the node is delay tolerant. When both traffic A and traffic B are active, the UE **201** cannot be in the eDRX mode. During the registration, the AMF **203** may know the characteristics of traffic A and traffic B.

[0148] Step **310b** of FIG. **13**: The AMF **203** sends assistance information to gNB **202** about the PTW associated with the traffic A and traffic B.

[0149] Step **311** of FIG. **13**: An event is triggered to update eDRX configuration. For example, when the traffic profiles on the UE **201** changes, or additionally, energy characteristics on the UE **201** changes. The UE sends an AS message to gNB to request an eDRX configuration update

including the traffic profile change information. For example, when traffic A is terminated and only traffic B is active, the UE can send an indication that traffic A is terminated. In another example, the UE sends an AS message to gNB to request an eDRX configuration update including the energy characteristic change information.

[0150] Step **312** of FIG. **13**: The UE **201** sends an AS message to the gNB **202** to request an eDRX configuration update including the traffic profile change information. For example, the UE **201** uses the RRCSetupRequest message when performing an RRC Connection Establishment procedure; using the RRCResumeRequest/RRCResumeRequest1 message when performing an RRC Connection Resume procedure; or using the UEAssistanceInformation message when performing a UE Assistance Information procedure.

[0151] Step **313** of FIG. **13**: The gNB **202** decides whether the eDRX parameter needs to be changed. If so, the gNB **202** sends a request to AMF **203** to assist UE **201** to update eDRX parameter. For example, after knowing the traffic A is terminated, the gNB **202** sends a request to AMF **203** to update the eDRX configuration. Additionally, the request may include, e.g., requirements for delivering emergency alerts, identified device type or capabilities (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity or traffic load.

[0152] Step **314** of FIG. **13**: The gNB **202** sends a request to AMF **203** to update the eDRX configuration.

[0153] Step **315** of FIG. **13**: AMF **203** decides whether to accept or reject the request for using the new eDRX parameter and sends a response to the gNB **202**. Determination of whether to accept or reject the request may be based on a number of factors including, e.g., requirements for delivering emergency alerts, identified device type (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity of a network. Paging capacity can be directly impacted dependent upon duration of the configured paging timer windows.

[0154] Step **316** of FIG. **13**: AMF **203** sends a response to the gNB **202** which includes the new eDRX parameter for the UE **201**.

[0155] Step **317** of FIG. **13**: The gNB **202** sends an AS message to the UE **201** to configure the new eDRX parameter. For example, using RRCReconfiguration message.

[0156] FIG. **14** shows an example procedure that the eDRX configuration update is triggered by the change of UE traffic profile when the UE **201** is in RRC_INACTIVE state. In the procedure, the UE **201** sends an AS message to gNB **202** to update its eDRX parameter. The message may indicate the traffic profile change information. The message may also include the disclosed eDRX parameter in the message. The gNB **202** determines whether the eDRX parameter(s) of the UE **201** need to be changed based on information obtained from the core network. The gNB **202** determines and configures the new eDRX parameter of the UE **201** and notifies the AMF **203** the new eDRX parameter associated with the UE **201**. The detailed description of the method is as follows.

[0157] Step **320a** of FIG. **14**: The UE **201** registers to the Core Network and obtains the initial DRX configuration from AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE **201** is a RedCap UE and associated capabilities, requirements, and characteristics. In one example, the UE **201** has an initial DRX configuration received from the AMF **203**, and the UE **201** has traffic A and traffic B. The traffic A is not delay tolerant and the UE **201** cannot be in eDRX mode when the traffic is active. The traffic B is delay tolerant and the UE **201** can be in eDRX mode when all other traffic on the node is delay tolerant. When both traffic A and traffic B are active, the UE **201** cannot be in the eDRX mode. During the registration, the AMF **203** may know the characteristics of traffic A and traffic B.

[0158] Step **320b** of FIG. **14**: The AMF **203** sends assistance information to the gNB **202** about the PTW associated with the traffic A and traffic B.

[0159] Step **321** of FIG. **14**: An event is triggered to update eDRX configuration. For example,

when the traffic profiles on the UE **201** changes, or additionally, energy characteristics on the UE **201** changes. The UE **201** sends an AS message to the gNB to request an eDRX configuration update including the traffic profile change information. For example, when traffic A is terminated and only traffic B is active, the UE **201** can send an indication that traffic A is terminated. In another example, the UE sends an AS message to gNB to request an eDRX configuration update including the energy characteristic change information.

[0160] Step **322** of FIG. **14**: The UE **201** sends an AS message to gNB **202** to request eDRX configuration update including the traffic profile change information. For example, the UE **201** uses the RRCSetupRequest message when performing an RRC Connection Establishment procedure; using the RRCResumeRequest/RRCResumeRequest1 message when performing an RRC Connection Resume procedure; or using the UEAssistanceInformation message when performing a UE Assistance Information procedure.

[0161] Step **323** of FIG. **14**: The gNB **202** decides whether the eDRX parameter(s) need to be changed based on the assistance information obtained in step **0b**. Factors such as, requirements for delivering emergency alerts, identified device type or capabilities (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity or traffic load of the gNB may be leveraged in the decision. If the eDRX parameter(s) need to be changed, the gNB **202** determines and configures the new eDRX parameter of the UE **201** and notifies the AMF **203** the new eDRX parameter associated with the UE **201**.

[0162] Step **324a** of FIG. **14** The gNB **202** sends a request to AMF **203** to update the eDRX configuration.

[0163] Step **324b** of FIG. **14**: The gNB **202** sends an AS message to the UE **201** to configure the new eDRX parameter, for example, using an RRCReconfiguration message.

Network Initiated Dynamic eDRX Configuration

[0164] Disclosed herein is a description of subject matter for the network to dynamically turn on and off eDRX mode of operation or change eDRX configuration of a UE **201**. The network may request to change eDRX configurations when the user plane information associated with the UE **201** changed. In the first disclosed method in FIG. **15**, the network may send a UE **201** configuration update command to update the new eDRX parameter of the UE **201**. The detailed description of the method is as follows.

[0165] Step **330** of FIG. **15**: The UE **201** registers to the Core Network and obtains the initial DRX configuration from AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE is a RedCap UE and associated capabilities, requirements, and characteristics.

[0166] Step **331** of FIG. **15**: An event is triggered for the network to update the eDRX configuration. For example, when user plane information associated with the UE **201** changed, the AMF **203** decides a new set of eDRX configuration to the UE **201**.

[0167] Step **332** of FIG. **15**: If the UE **201** is in RRC idle, the AMF **201** initiates a network triggered service request procedure to establish a connection with the UE **201**. During the procedure, the AMF **203** may send a NAS message which includes the new eDRX parameter associated with the UE **201**.

[0168] Step **333** of FIG. **15**: The AMF **203** sends a NAS Message which includes the new eDRX parameter associated with the UE **201**. In one example, the NAS message is a UE configuration update command.

[0169] Step **334** of FIG. **15**: The UE **201** may send a NAS message to response eDRX configuration. In one example, the NAS message is a UE configuration update complete message.

[0170] In another disclosed method in FIG. **16**, the network sends a request to the gNB **202** when an eDRX configuration update is triggered. The gNB **202** assists the AMF **203** to dynamically turn on and off eDRX mode of operation or change eDRX configuration based on the information in the request. The gNB **202** determines whether the eDRX parameters of the UE **201** need to be updated.

The detailed description of the method is as follows.

[0171] Step **340** of FIG. **16**: The UE **201** registers to the Core Network and obtains the initial DRX configuration from AMF **203**. The registration process may include identification of the UE capabilities to determine whether or not the UE **201** is a RedCap UE and associated capabilities, requirements, and characteristics.

[0172] Step **341**: of FIG. **16** An event is triggered for the network to update the eDRX configuration. For example, when user plane information associated with the UE **201** changed, the AMF **203** decides a new set of eDRX configuration information elements to the UE **201**.

[0173] Step **342**: of FIG. **16** The AMF **203** sends an RRC Assistance information message to the gNB **202**, which includes the new eDRX parameter(s) associated with the UE **201**.

[0174] Step **343** of FIG. **16**: The gNB **202** decides whether the eDRX parameter(s) need to be changed based on the assistance information obtained in step **342**. Factors such as, e.g., requirements for delivering emergency alerts, identified device type or capabilities (RedCap, RedCap type, or non-RedCap, and UE power/energy characteristics), determined/calculated available paging capacity or traffic load of the gNB **202** may be leveraged in the decision. If the eDRX parameter(s) need to be changed, the gNB **202** determines and configures the new eDRX parameter associated with the UE **201**.

[0175] Step **344** of FIG. **16**: The gNB **202** sends an AS message to the UE **201** to configure the new eDRX parameter, for example, using an RRCReconfiguration message.

[0176] It is understood that the entities performing the steps illustrated herein, such as FIG. **4**-FIG. **16**, may be logical entities. The steps may be stored in a memory of, and executing on a processor of, a device, server, or computer system such as those illustrated in FIG. **18F** or FIG. **18G**. Skipping steps, combining steps, or adding steps between exemplary methods disclosed herein (e.g., FIG. **4**-FIG. **16**) is contemplated. Table 4 provides exemplary abbreviations.

TABLE-US-00004 TABLE 4 Abbreviations and Definitions

Abbreviations	Definitions
AMF	Access and Mobility Management Function
BCH	Broadcast Channel
BR-P-RNTI	Bandwidth Reduced Paging Radio Network Temporary Identifier
BW	Bandwidth
BWP	Bandwidth Part
BR	Bandwidth Reduced
CMAS	Commercial Mobile Alert Service
CN	Core Network
DCI	Downlink Control Information
DL	Downlink
DL-SCH	DL Shared Channel
DRX	Discontinuous Reception
eDRX	Extended DRX
eMBB	Enhanced Mobile Broadband
ETWS	Earthquake & Tsunami Warning System
eURLLC	Enhanced Ultra-Reliable and Low Latency Communication
E-UTRA	Evolved Universal Terrestrial Radio Access
FDD	Frequency Division Duplex
FR1	Frequency 1
FR2	Frequency 2
gNB	NR NodeB
GPS	Global Positioning System
IMT	International Mobile Telecommunications
IWSN	Industrial Wireless Sensor Networks
LOS	Line of Sight
LTE	Long Term Evolution
MCS	Modulation and Coding Scheme
MHz	Mega-Hertz
MIB	Master Information Block
MME	Mobility Management Entity
MO	Monitoring Occasion
MTC	Machine Type Communication
NAS	Non-Access Stratum
NB	Narrowband
NB-IoT	Narrowband Internet of Things
NPDCCCH	Narrowband Physical Downlink Control Channel
NR	New Radio
NW	Network
IE	Information Element
IMSI	International Mobile Subscriber Identity
OAM	Operations, Administration and Maintenance
OFDM	Orthogonal Frequency Division Multiplexing
PBCH	Physical Broadcast Channel
PCCH	Paging Common Control Channel
PDCCH	Physical Downlink Control Channel
PDSCH	Physical Downlink Shared Channel
PF	Paging Frame
PNB	Paging Narrowband
PO	Paging Occasion
PRACH	Physical Random Access Channel
PRB	Physical Resource Block
P-RNTI	Paging Radio Network Temporary Identifier
PSM	Power Saving Mode
PTW	Paging Time Window
PWS	Public Warning System
RACH	Random Access Channel
RAN	Radio Access Network
RAT	Radio Access Technology
RB	Resource Block
RedCap	Reduced Capability
RMSI	Remaining Minimum System Information
RRC	Radio Resource Control
RX	Receive
SCS	Sub-Carrier Spacing
SFN	System Frame Number
SI	System Information
SID	Study Item Description
SI-RNTI	System Information Radio Network Temporary Identifier
SIB	System Information Block
SSB	Synchronization Signal Block
S-TMSI	Shortened-Temporary Mobile

Subscriber Identity TAU Tracking Area Update TB Transport Block TBS Transport Block Size
TDD Time Division Duplex WTRU Wireless Transmit/Receive Unit

[0177] FIG. 17 illustrates an exemplary display (e.g., graphical user interface) that may be generated based on the methods, systems, and devices of eDRX enhancement for reduced capability NR devices, as discussed herein. Display interface **901** (e.g., touch screen display) may provide text in block **902** associated with of eDRX enhancement for reduced capability NR devices, such as related parameters, method flows, and associated current conditions. Progress of any of the steps (e.g., sent messages or success of steps) discussed herein may be displayed in block **902**. In addition, graphical output **902** may be displayed on display interface **901**. Graphical output **903** may be the topology of the devices implementing the methods, systems, and devices of eDRX enhancement for reduced capability NR devices, a graphical output of the progress of any method or systems discussed herein, or the like.

[0178] The 3rd Generation Partnership Project (3GPP) develops technical standards for cellular telecommunications network technologies, including radio access, the core transport network, and service capabilities-including work on codecs, security, and quality of service. Recent radio access technology (RAT) standards include WCDMA (commonly referred as 3G), LTE (commonly referred as 4G), LTE-Advanced standards, and New Radio (NR), which is also referred to as “5G”. 3GPP NR standards development is expected to continue and include the definition of next generation radio access technology (new RAT), which is expected to include the provision of new flexible radio access below 7 GHz, and the provision of new ultra-mobile broadband radio access above 7 GHz. The flexible radio access is expected to consist of a new, non-backwards compatible radio access in new spectrum below 6 GHz, and it is expected to include different operating modes that may be multiplexed together in the same spectrum to address a broad set of 3GPP NR use cases with diverging requirements. The ultra-mobile broadband is expected to include cmWave and mmWave spectrum that will provide the opportunity for ultra-mobile broadband access for, e.g., indoor applications and hotspots. In particular, the ultra-mobile broadband is expected to share a common design framework with the flexible radio access below 7 GHz, with cmWave and mmWave specific design optimizations.

[0179] 3GPP has identified a variety of use cases that NR is expected to support, resulting in a wide variety of user experience requirements for data rate, latency, and mobility. The use cases include the following general categories: enhanced mobile broadband (eMBB) ultra-reliable low-latency Communication (URLLC), massive machine type communications (mMTC), network operation (e.g., network slicing, routing, migration and interworking, energy savings), and enhanced vehicle-to-everything (eV2X) communications, which may include any of Vehicle-to-Vehicle Communication (V2V), Vehicle-to-Infrastructure Communication (V2I), Vehicle-to-Network Communication (V2N), Vehicle-to-Pedestrian Communication (V2P), and vehicle communications with other entities. Specific service and applications in these categories include, e.g., monitoring and sensor networks, device remote controlling, bi-directional remote controlling, personal cloud computing, video streaming, wireless cloud-based office, first responder connectivity, automotive ecall, disaster alerts, real-time gaming, multi-person video calls, autonomous driving, augmented reality, tactile internet, virtual reality, home automation, robotics, and aerial drones to name a few. All of these use cases and others are contemplated herein.

[0180] FIG. 18A illustrates an example communications system **100** in which the methods and apparatuses of eDRX enhancement for reduced capability NR devices, such as the systems and methods illustrated in FIG. 1 through FIG. 16 described and claimed herein may be used. The communications system **100** may include wireless transmit/receive units (WTRUs) **102a**, **102b**, **102c**, **102d**, **102e**, **102f**, or **102g** (which generally or collectively may be referred to as WTRU **102** or WTRUs **102**). The communications system **100** may include, a radio access network (RAN) **103/104/105/103b/104b/105b**, a core network **106/107/109**, a public switched telephone network (PSTN) **108**, the Internet **110**, other networks **112**, and Network Services **113**. Network Services

113 may include, for example, a V2X server, V2X functions, a ProSe server, ProSe functions, IoT services, video streaming, or edge computing, etc.

[0181] It will be appreciated that the concepts disclosed herein may be used with any number of WTRUs, base stations, networks, or network elements. Each of the WTRUs **102a**, **102b**, **102c**, **102d**, **102e**, **102f**, or **102g** may be any type of apparatus or device configured to operate or communicate in a wireless environment. Although each WTRU **102a**, **102b**, **102c**, **102d**, **102e**, **102f**, or **102g** may be depicted in FIG. **18A**, FIG. **18B**, FIG. **18C**, FIG. **18D**, FIG. **18E**, or FIG. **18F** as a hand-held wireless communications apparatus, it is understood that with the wide variety of use cases contemplated for 5G wireless communications, each WTRU may comprise or be embodied in any type of apparatus or device configured to transmit or receive wireless signals, including, by way of example only, user equipment (UE), a mobile station, a fixed or mobile subscriber unit, a pager, a cellular telephone, a personal digital assistant (PDA), a smartphone, a laptop, a tablet, a netbook, a notebook computer, a personal computer, a wireless sensor, consumer electronics, a wearable device such as a smart watch or smart clothing, a medical or eHealth device, a robot, industrial equipment, a drone, a vehicle such as a car, bus, truck, train, or airplane, and the like.

[0182] The communications system **100** may also include a base station **114a** and a base station **114b**. In the example of FIG. **18A**, each base stations **114a** and **114b** is depicted as a single element. In practice, the base stations **114a** and **114b** may include any number of interconnected base stations or network elements. Base stations **114a** may be any type of device configured to wirelessly interface with at least one of the WTRUs **102a**, **102b**, and **102c** to facilitate access to one or more communication networks, such as the core network **106/107/109**, the Internet **110**, Network Services **113**, or the other networks **112**. Similarly, base station **114b** may be any type of device configured to wirelessly interface with at least one of the Remote Radio Heads (RRHs) **118a**, **118b**, Transmission and Reception Points (TRPs) **119a**, **119b**, or Roadside Units (RSUs) **120a** and **120b** to facilitate access to one or more communication networks, such as the core network **106/107/109**, the Internet **110**, other networks **112**, or Network Services **113**. RRHs **118a**, **118b** may be any type of device configured to wirelessly interface with at least one of the WTRUs **102**, e.g., WTRU **102c**, to facilitate access to one or more communication networks, such as the core network **106/107/109**, the Internet **110**, Network Services **113**, or other networks **112**.

[0183] TRPs **119a**, **119b** may be any type of device configured to wirelessly interface with at least one of the WTRU **102d**, to facilitate access to one or more communication networks, such as the core network **106/107/109**, the Internet **110**, Network Services **113**, or other networks **112**. RSUs **120a** and **120b** may be any type of device configured to wirelessly interface with at least one of the WTRU **102e** or **102f**, to facilitate access to one or more communication networks, such as the core network **106/107/109**, the Internet **110**, other networks **112**, or Network Services **113**. By way of example, the base stations **114a**, **114b** may be a Base Transceiver Station (BTS), a Node-B, an eNode B, a Home Node B, a Home eNode B, a Next Generation Node-B (gNode B), a satellite, a site controller, an access point (AP), a wireless router, and the like.

[0184] The base station **114a** may be part of the RAN **103/104/105**, which may also include other base stations or network elements (not shown), such as a Base Station Controller (BSC), a Radio Network Controller (RNC), relay nodes, etc. Similarly, the base station **114b** may be part of the RAN **103b/104b/105b**, which may also include other base stations or network elements (not shown), such as a BSC, a RNC, relay nodes, etc. The base station **114a** may be configured to transmit or receive wireless signals within a particular geographic region, which may be referred to as a cell (not shown). Similarly, the base station **114b** may be configured to transmit or receive wired or wireless signals within a particular geographic region, which may be referred to as a cell (not shown) for methods, systems, and devices of eDRX enhancement for reduced capability NR devices, as disclosed herein. Similarly, the base station **114b** may be configured to transmit or receive wired or wireless signals within a particular geographic region, which may be referred to as

a cell (not shown). The cell may further be divided into cell sectors. For example, the cell associated with the base station **114a** may be divided into three sectors. Thus, in an example, the base station **114a** may include three transceivers, e.g., one for each sector of the cell. In an example, the base station **114a** may employ multiple-input multiple output (MIMO) technology and, therefore, may utilize multiple transceivers for each sector of the cell.

[0185] The base stations **114a** may communicate with one or more of the WTRUs **102a**, **102b**, **102c**, or **102g** over an air interface **115/116/117**, which may be any suitable wireless communication link (e.g., radio frequency (RF), microwave, infrared (IR), ultraviolet (UV), visible light, cmWave, mmWave, etc.). The air interface **115/116/117** may be established using any suitable radio access technology (RAT).

[0186] The base stations **114b** may communicate with one or more of the RRHs **118a**, **118b**, TRPs **119a**, **119b**, or RSUs **120a**, **120b**, over a wired or air interface **115b/116b/117b**, which may be any suitable wired (e.g., cable, optical fiber, etc.) or wireless communication link (e.g., radio frequency (RF), microwave, infrared (IR), ultraviolet (UV), visible light, cmWave, mmWave, etc.). The air interface **115b/116b/117b** may be established using any suitable radio access technology (RAT).

[0187] The RRHs **118a**, **118b**, TRPs **119a**, **119b** or RSUs **120a**, **120b**, may communicate with one or more of the WTRUs **102c**, **102d**, **102e**, **102f** over an air interface **115c/116c/117c**, which may be any suitable wireless communication link (e.g., radio frequency (RF), microwave, infrared (IR), ultraviolet (UV), visible light, cmWave, mmWave, etc.). The air interface **115c/116c/117c** may be established using any suitable radio access technology (RAT).

[0188] The WTRUs **102a**, **102b**, **102c**, **102d**, **102e**, or **102f** may communicate with one another over an air interface **115d/116d/117d**, such as Sidelink communication, which may be any suitable wireless communication link (e.g., radio frequency (RF), microwave, infrared (IR), ultraviolet (UV), visible light, cmWave, mmWave, etc.). The air interface **115d/116d/117d** may be established using any suitable radio access technology (RAT).

[0189] The communications system **100** may be a multiple access system and may employ one or more channel access schemes, such as CDMA, TDMA, FDMA, OFDMA, SC-FDMA, and the like. For example, the base station **114a** in the RAN **103/104/105** and the WTRUs **102a**, **102b**, **102c**, or RRHs **118a**, **118b**, TRPs **119a**, **119b** and RSUs **120a**, **120b**, in the RAN **103b/104b/105b** and the WTRUs **102c**, **102d**, **102e**, **102f**, may implement a radio technology such as Universal Mobile Telecommunications System (UM TS) Terrestrial Radio Access (UTRA), which may establish the air interface **115/116/117** or **115c/116c/117c** respectively using wideband CDMA (WCDMA). WCDMA may include communication protocols such as High-Speed Packet Access (H SPA) or Evolved HSPA (HSPA+). HSPA may include High-Speed Downlink Packet Access (HSDPA) or High-Speed Uplink Packet Access (HSUPA).

[0190] In an example, the base station **114a** and the WTRUs **102a**, **102b**, **102c**, or RRHs **118a**, **118b**, TRPs **119a**, **119b**, or RSUs **120a**, **120b** in the RAN **103b/104b/105b** and the WTRUs **102c**, **102d**, may implement a radio technology such as Evolved UM TS Terrestrial Radio Access (E-UTRA), which may establish the air interface **115/116/117** or **115c/116c/117c** respectively using Long Term Evolution (LTE) or LTE-Advanced (LTE-A). In the future, the air interface **115/116/117** or **115c/116c/117c** may implement 3GPP NR technology. The LTE and LTE-A technology may include LTE D2D and V2X technologies and interfaces (such as Sidelink communications, etc.). Similarly, the 3GPP NR technology includes NR V2X technologies and interface (such as Sidelink communications, etc.).

[0191] The base station **114a** in the RAN **103/104/105** and the WTRUs **102a**, **102b**, **102c**, and **102g** or RRHs **118a**, **118b**, TRPs **119a**, **119b** or RSUs **120a**, **120b** in the RAN **103b/104b/105b** and the WTRUs **102c**, **102d**, **102e**, **102f** may implement radio technologies such as IEEE 802.16 (e.g., Worldwide Interoperability for Microwave Access (WiMAX)), CDMA 2000, CDMA 2000 1×, CDMA 2000 EV-DO, Interim Standard 2000 (IS-2000), Interim Standard 95 (IS-95), Interim Standard 856 (IS-856), Global System for Mobile communications (GSM), Enhanced Data rates

for GSM Evolution (EDGE), GSM EDGE (GERAN), and the like.

[0192] The base station **114c** in FIG. **18A** may be a wireless router, Home Node B, Home eNode B, or access point, for example, and may utilize any suitable RAT for facilitating wireless connectivity in a localized area, such as a place of business, a home, a vehicle, a train, an aerial, a satellite, a manufactory, a campus, and the like, for implementing the methods, systems, and devices of eDRX enhancement for reduced capability NR devices, as disclosed herein. In an example, the base station **114c** and the WTRUs **102**, e.g., WTRU **102e**, may implement a radio technology such as IEEE 802.11 to establish a wireless local area network (WLAN). Similarly, the base station **114c** and the WTRUs **102d**, may implement a radio technology such as IEEE 802.15 to establish a wireless personal area network (WPAN). In yet another example, the base station **114c** and the WTRUs **102**, e.g., WTRU **102e**, may utilize a cellular-based RAT (e.g., WCDMA, CDMA 2000, GSM, LTE, LTE-A, NR, etc.) to establish a picocell or femtocell. As shown in FIG. **18A**, the base station **114c** may have a direct connection to the Internet **110**. Thus, the base station **114c** may not be required to access the Internet **110** via the core network **106/107/109**.

[0193] The RAN **103/104/105** or RAN **103b/104b/105b** may be in communication with the core network **106/107/109**, which may be any type of network configured to provide voice, data, messaging, authorization and authentication, applications, or voice over internet protocol (VoIP) services to one or more of the WTRUs **102a**, **102b**, **102c**, **102d**. For example, the core network **106/107/109** may provide call control, billing services, mobile location-based services, pre-paid calling, Internet connectivity, packet data network connectivity, Ethernet connectivity, video distribution, etc., or perform high-level security functions, such as user authentication.

[0194] Although not shown in FIG. **18A**, it will be appreciated that the RAN **103/104/105** or RAN **103b/104b/105b** or the core network **106/107/109** may be in direct or indirect communication with other RANs that employ the same RAT as the RAN **103/104/105** or RAN **103b/104b/105b** or a different RAT. For example, in addition to being connected to the RAN **103/104/105** or RAN **103b/104b/105b**, which may be utilizing an E-UTRA radio technology, the core network **106/107/109** may also be in communication with another RAN (not shown) employing a GSM or NR radio technology.

[0195] The core network **106/107/109** may also serve as a gateway for the WTRUs **102a**, **102b**, **102c**, **102d**, **102e** to access the PSTN **108**, the Internet **110**, or other networks **112**. The PSTN **108** may include circuit-switched telephone networks that provide plain old telephone service (POTS). The Internet **110** may include a global system of interconnected computer networks and devices that use common communication protocols, such as the transmission control protocol (TCP), user datagram protocol (UDP) and the internet protocol (IP) in the TCP/IP internet protocol suite. The networks **112** may include wired or wireless communications networks owned or operated by other service providers. For example, the networks **112** may include any type of packet data network (e.g., an IEEE 802.3 Ethernet network) or another core network connected to one or more RANs, which may employ the same RAT as the RAN **103/104/105** or RAN **103b/104b/105b** or a different RAT.

[0196] Some or all of the WTRUs **102a**, **102b**, **102c**, **102d**, **102e**, and **102f** in the communications system **100** may include multi-mode capabilities, e.g., the WTRUs **102a**, **102b**, **102c**, **102d**, **102e**, and **102f** may include multiple transceivers for communicating with different wireless networks over different wireless links for implementing methods, systems, and devices of eDRX enhancement for reduced capability NR devices, as disclosed herein. For example, the WTRU **102g** shown in FIG. **18A** may be configured to communicate with the base station **114a**, which may employ a cellular-based radio technology, and with the base station **114c**, which may employ an IEEE 802 radio technology.

[0197] Although not shown in FIG. **18A**, it will be appreciated that a User Equipment may make a wired connection to a gateway. The gateway maybe a Residential Gateway (RG). The RG may provide connectivity to a Core Network **106/107/109**. It will be appreciated that much of the

subject matter included herein may equally apply to UEs that are WTRUs and UEs that use a wired connection to connect with a network. For example, the subject matter that applies to the wireless interfaces **115**, **116**, **117** and **115c/116c/117c** may equally apply to a wired connection.

[0198] FIG. **18B** is a system diagram of an example RAN **103** and core network **106** that may implement methods, systems, and devices of eDRX enhancement for reduced capability NR devices, as disclosed herein. As noted above, the RAN **103** may employ a UTRA radio technology to communicate with the WTRUs **102a**, **102b**, and **102c** over the air interface **115**. The RAN **103** may also be in communication with the core network **106**. As shown in FIG. **18B**, the RAN **103** may include Node-Bs **140a**, **140b**, and **140c**, which may each include one or more transceivers for communicating with the WTRUs **102a**, **102b**, and **102c** over the air interface **115**. The Node-Bs **140a**, **140b**, and **140c** may each be associated with a particular cell (not shown) within the RAN **103**. The RAN **103** may also include RNCs **142a**, **142b**. It will be appreciated that the RAN **103** may include any number of Node-Bs and Radio Network Controllers (RNCs.)

[0199] As shown in FIG. **18B**, the Node-Bs **140a**, **140b** may be in communication with the RNC **142a**. Additionally, the Node-B **140c** may be in communication with the RNC **142b**. The Node-Bs **140a**, **140b**, and **140c** may communicate with the respective RNCs **142a** and **142b** via an Iub interface. The RNCs **142a** and **142b** may be in communication with one another via an Iur interface. Each of the RNCs **142a** and **142b** may be configured to control the respective Node-Bs **140a**, **140b**, and **140c** to which it is connected. In addition, each of the RNCs **142a** and **142b** may be configured to carry out or support other functionality, such as outer loop power control, load control, admission control, packet scheduling, handover control, macro-diversity, security functions, data encryption, and the like.

[0200] The core network **106** shown in FIG. **18B** may include a media gateway (MGW) **144**, a Mobile Switching Center (MSC) **146**, a Serving GPRS Support Node (SGSN) **148**, or a Gateway GPRS Support Node (GGSN) **150**. While each of the foregoing elements are depicted as part of the core network **106**, it will be appreciated that any one of these elements may be owned or operated by an entity other than the core network operator.

[0201] The RNC **142a** in the RAN **103** may be connected to the MSC **146** in the core network **106** via an IuCS interface. The MSC **146** may be connected to the MGW **144**. The MSC **146** and the MGW **144** may provide the WTRUs **102a**, **102b**, and **102c** with access to circuit-switched networks, such as the PSTN **108**, to facilitate communications between the WTRUs **102a**, **102b**, and **102c**, and traditional land-line communications devices.

[0202] The RNC **142a** in the RAN **103** may also be connected to the SGSN **148** in the core network **106** via an IuPS interface. The SGSN **148** may be connected to the GGSN **150**. The SGSN **148** and the GGSN **150** may provide the WTRUs **102a**, **102b**, and **102c** with access to packet-switched networks, such as the Internet **110**, to facilitate communications between and the WTRUs **102a**, **102b**, and **102c**, and IP-enabled devices.

[0203] The core network **106** may also be connected to the other networks **112**, which may include other wired or wireless networks that are owned or operated by other service providers.

[0204] FIG. **18C** is a system diagram of an example RAN **104** and core network **107** that may implement methods, systems, and devices of eDRX enhancement for reduced capability NR devices, as disclosed herein. As noted above, the RAN **104** may employ an E-UTRA radio technology to communicate with the WTRUs **102a**, **102b**, and **102c** over the air interface **116**. The RAN **104** may also be in communication with the core network **107**.

[0205] The RAN **104** may include eNode-Bs **160a**, **160b**, and **160c**, though it will be appreciated that the RAN **104** may include any number of eNode-Bs. The eNode-Bs **160a**, **160b**, and **160c** may each include one or more transceivers for communicating with the WTRUs **102a**, **102b**, and **102c** over the air interface **116**. For example, the eNode-Bs **160a**, **160b**, and **160c** may implement MIMO technology. Thus, the eNode-B **160a**, for example, may use multiple antennas to transmit wireless signals to, and receive wireless signals from, the WTRU **102a**.

[0206] Each of the eNode-Bs **160a**, **160b**, and **160c** may be associated with a particular cell (not shown) and may be configured to handle radio resource management decisions, handover decisions, scheduling of users in the uplink or downlink, and the like. As shown in FIG. **18C**, the eNode-Bs **160a**, **160b**, and **160c** may communicate with one another over an X2 interface.

[0207] The core network **107** shown in FIG. **18C** may include a Mobility Management Gateway (MME) **162**, a serving gateway **164**, and a Packet Data Network (PDN) gateway **166**. While each of the foregoing elements are depicted as part of the core network **107**, it will be appreciated that any one of these elements may be owned or operated by an entity other than the core network operator.

[0208] The MME **162** may be connected to each of the eNode-Bs **160a**, **160b**, and **160c** in the RAN **104** via an S1 interface and may serve as a control node. For example, the MME **162** may be responsible for authenticating users of the WTRUs **102a**, **102b**, and **102c**, bearer activation/deactivation, selecting a particular serving gateway during an initial attach of the WTRUs **102a**, **102b**, and **102c**, and the like. The MME **162** may also provide a control plane function for switching between the RAN **104** and other RANs (not shown) that employ other radio technologies, such as GSM or WCDMA.

[0209] The serving gateway **164** may be connected to each of the eNode-Bs **160a**, **160b**, and **160c** in the RAN **104** via the S1 interface. The serving gateway **164** may generally route and forward user data packets to/from the WTRUs **102a**, **102b**, and **102c**. The serving gateway **164** may also perform other functions, such as anchoring user planes during inter-eNode B handovers, triggering paging when downlink data is available for the WTRUs **102a**, **102b**, and **102c**, managing and storing contexts of the WTRUs **102a**, **102b**, and **102c**, and the like.

[0210] The serving gateway **164** may also be connected to the PDN gateway **166**, which may provide the WTRUs **102a**, **102b**, and **102c** with access to packet-switched networks, such as the Internet **110**, to facilitate communications between the WTRUs **102a**, **102b**, **102c**, and IP-enabled devices.

[0211] The core network **107** may facilitate communications with other networks. For example, the core network **107** may provide the WTRUs **102a**, **102b**, and **102c** with access to circuit-switched networks, such as the PSTN **108**, to facilitate communications between the WTRUs **102a**, **102b**, and **102c** and traditional land-line communications devices. For example, the core network **107** may include, or may communicate with, an IP gateway (e.g., an IP Multimedia Subsystem (IMS) server) that serves as an interface between the core network **107** and the PSTN **108**. In addition, the core network **107** may provide the WTRUs **102a**, **102b**, and **102c** with access to the networks **112**, which may include other wired or wireless networks that are owned or operated by other service providers.

[0212] FIG. **18D** is a system diagram of an example RAN **105** and core network **109** that may implement methods, systems, and devices of eDRX enhancement for reduced capability NR devices, as disclosed herein. The RAN **105** may employ an NR radio technology to communicate with the WTRUs **102a** and **102b** over the air interface **117**. The RAN **105** may also be in communication with the core network **109**. A Non-3GPP Interworking Function (N3IWF) **199** may employ a non-3GPP radio technology to communicate with the WTRU **102c** over the air interface **198**. The N3IWF **199** may also be in communication with the core network **109**.

[0213] The RAN **105** may include gNode-Bs **180a** and **180b**. It will be appreciated that the RAN **105** may include any number of gNode-Bs. The gNode-Bs **180a** and **180b** may each include one or more transceivers for communicating with the WTRUs **102a** and **102b** over the air interface **117**. When integrated access and backhaul connection are used, the same air interface may be used between the WTRUs and gNode-Bs, which may be the core network **109** via one or multiple gNBs. The gNode-Bs **180a** and **180b** may implement MIMO, MU-MIMO, or digital beamforming technology. Thus, the gNode-B **180a**, for example, may use multiple antennas to transmit wireless signals to, and receive wireless signals from, the WTRU **102a**. It should be appreciated that the

RAN **105** may employ of other types of base stations such as an eNode-B. It will also be appreciated the RAN **105** may employ more than one type of base station. For example, the RAN may employ eNode-Bs and gNode-Bs.

[0214] The N3IWF **199** may include a non-3GPP Access Point **180c**. It will be appreciated that the N3IWF **199** may include any number of non-3GPP Access Points. The non-3GPP Access Point **180c** may include one or more transceivers for communicating with the WTRUs **102c** over the air interface **198**. The non-3GPP Access Point **180c** may use the 802.11 protocol to communicate with the WTRU **102c** over the air interface **198**.

[0215] Each of the gNode-Bs **180a** and **180b** may be associated with a particular cell (not shown) and may be configured to handle radio resource management decisions, handover decisions, scheduling of users in the uplink or downlink, and the like. As shown in FIG. **18D**, the gNode-Bs **180a** and **180b** may communicate with one another over an Xn interface, for example.

[0216] The core network **109** shown in FIG. **18D** may be a 5G core network (5GC). The core network **109** may offer numerous communication services to customers who are interconnected by the radio access network. The core network **109** comprises a number of entities that perform the functionality of the core network. As used herein, the term “core network entity” or “network function” refers to any entity that performs one or more functionalities of a core network. It is understood that such core network entities may be logical entities that are implemented in the form of computer-executable instructions (software) stored in a memory of, and executing on a processor of, an apparatus configured for wireless or network communications or a computer system, such as system **90** illustrated in FIG. **18G**.

[0217] In the example of FIG. **18D**, the 5G Core Network **109** may include an access and mobility management function (AMF) **172**, a Session Management Function (SMF) **174**, User Plane Functions (UPFs) **176a** and **176b**, a User Data Management Function (UDM) **197**, an Authentication Server Function (AUSF) **190**, a Network Exposure Function (NEF) **196**, a Policy Control Function (PCF) **184**, a Non-3GPP Interworking Function (N3IWF) **199**, a User Data Repository (UDR) **178**. While each of the foregoing elements are depicted as part of the 5G core network **109**, it will be appreciated that any one of these elements may be owned or operated by an entity other than the core network operator. It will also be appreciated that a 5G core network may not consist of all of these elements, may consist of additional elements, and may consist of multiple instances of each of these elements. FIG. **18D** shows that network functions directly connect with one another, however, it should be appreciated that they may communicate via routing agents such as a diameter routing agent or message buses.

[0218] In the example of FIG. **18D**, connectivity between network functions is achieved via a set of interfaces, or reference points. It will be appreciated that network functions could be modeled, described, or implemented as a set of services that are invoked, or called, by other network functions or services. Invocation of a Network Function service may be achieved via a direct connection between network functions, an exchange of messaging on a message bus, calling a software function, etc.

[0219] The AMF **172** may be connected to the RAN **105** via an N2 interface and may serve as a control node. For example, the AMF **172** may be responsible for registration management, connection management, reachability management, access authentication, access authorization. The AMF may be responsible forwarding user plane tunnel configuration information to the RAN **105** via the N2 interface. The AMF **172** may receive the user plane tunnel configuration information from the SMF via an N11 interface. The AMF **172** may generally route and forward NAS packets to/from the WTRUs **102a**, **102b**, and **102c** via an N1 interface. The N1 interface is not shown in FIG. **18D**.

[0220] The SMF **174** may be connected to the AMF **172** via an N11 interface. Similarly the SMF may be connected to the PCF **184** via an N7 interface, and to the UPFs **176a** and **176b** via an N4 interface. The SMF **174** may serve as a control node. For example, the SMF **174** may be

responsible for Session Management, IP address allocation for the WTRUs **102a**, **102b**, and **102c**, management and configuration of traffic steering rules in the UPF **176a** and UPF **176b**, and generation of downlink data notifications to the AMF **172**.

[0221] The UPF **176a** and UPF **176b** may provide the WTRUs **102a**, **102b**, and **102c** with access to a Packet Data Network (PDN), such as the Internet **110**, to facilitate communications between the WTRUs **102a**, **102b**, and **102c** and other devices. The UPF **176a** and UPF **176b** may also provide the WTRUs **102a**, **102b**, and **102c** with access to other types of packet data networks. For example, Other Networks **112** may be Ethernet Networks or any type of network that exchanges packets of data. The UPF **176a** and UPF **176b** may receive traffic steering rules from the SMF **174** via the N4 interface. The UPF **176a** and UPF **176b** may provide access to a packet data network by connecting a packet data network with an N6 interface or by connecting to each other and to other UPFs via an N9 interface. In addition to providing access to packet data networks, the UPF **176** may be responsible packet routing and forwarding, policy rule enforcement, quality of service handling for user plane traffic, downlink packet buffering.

[0222] The AMF **172** may also be connected to the N3IWF **199**, for example, via an N2 interface. The N3IWF facilitates a connection between the WTRU **102c** and the 5G core network **170**, for example, via radio interface technologies that are not defined by 3GPP. The AMF may interact with the N3IWF **199** in the same, or similar, manner that it interacts with the RAN **105**.

[0223] The PCF **184** may be connected to the SMF **174** via an N7 interface, connected to the AMF **172** via an N15 interface, and to an Application Function (AF) **188** via an N5 interface. The N15 and N5 interfaces are not shown in FIG. **18D**. The PCF **184** may provide policy rules to control plane nodes such as the AMF **172** and SMF **174**, allowing the control plane nodes to enforce these rules. The PCF **184**, may send policies to the AMF **172** for the WTRUs **102a**, **102b**, and **102c** so that the AMF may deliver the policies to the WTRUs **102a**, **102b**, and **102c** via an N1 interface. Policies may then be enforced, or applied, at the WTRUs **102a**, **102b**, and **102c**.

[0224] The UDR **178** may act as a repository for authentication credentials and subscription information. The UDR may connect with network functions, so that network function can add to, read from, and modify the data that is in the repository. For example, the UDR **178** may connect with the PCF **184** via an N36 interface. Similarly, the UDR **178** may connect with the NEF **196** via an N37 interface, and the UDR **178** may connect with the UDM **197** via an N35 interface.

[0225] The UDM **197** may serve as an interface between the UDR **178** and other network functions. The UDM **197** may authorize network functions to access of the UDR **178**. For example, the UDM **197** may connect with the AMF **172** via an N8 interface, the UDM **197** may connect with the SMF **174** via an N10 interface. Similarly, the UDM **197** may connect with the AUSF **190** via an N13 interface. The UDR **178** and UDM **197** may be tightly integrated.

[0226] The AUSF **190** performs authentication related operations and connect with the UDM **178** via an N13 interface and to the AMF **172** via an N12 interface.

[0227] The NEF **196** exposes capabilities and services in the 5G core network **109** to Application Functions (AF) **188**. Exposure may occur on the N33 API interface. The NEF may connect with an AF **188** via an N33 interface and it may connect with other network functions in order to expose the capabilities and services of the 5G core network **109**.

[0228] Application Functions **188** may interact with network functions in the 5G Core Network **109**. Interaction between the Application Functions **188** and network functions may be via a direct interface or may occur via the NEF **196**. The Application Functions **188** may be considered part of the 5G Core Network **109** or may be external to the 5G Core Network **109** and deployed by enterprises that have a business relationship with the mobile network operator.

[0229] Network Slicing is a mechanism that could be used by mobile network operators to support one or more ‘virtual’ core networks behind the operator's air interface. This involves ‘slicing’ the core network into one or more virtual networks to support different RANs or different service types running across a single RAN. Network slicing enables the operator to create networks customized

to provide optimized solutions for different market scenarios which demands diverse requirements, e.g. in the areas of functionality, performance and isolation.

[0230] 3GPP has designed the 5G core network to support Network Slicing. Network Slicing is a good tool that network operators can use to support the diverse set of 5G use cases (e.g., massive IoT, critical communications, V2X, and enhanced mobile broadband) which demand very diverse and sometimes extreme requirements. Without the use of network slicing techniques, it is likely that the network architecture would not be flexible and scalable enough to efficiently support a wider range of use cases need when each use case has its own specific set of performance, scalability, and availability requirements. Furthermore, introduction of new network services should be made more efficient.

[0231] Referring again to FIG. **18D**, in a network slicing scenario, a WTRU **102a**, **102b**, or **102c** may connect with an AMF **172**, via an N1 interface. The AMF may be logically part of one or more slices. The AMF may coordinate the connection or communication of WTRU **102a**, **102b**, or **102c** with one or more UPF **176a** and **176b**, SMF **174**, and other network functions. Each of the UPFs **176a** and **176b**, SMF **174**, and other network functions may be part of the same slice or different slices. When they are part of different slices, they may be isolated from each other in the sense that they may utilize different computing resources, security credentials, etc.

[0232] The core network **109** may facilitate communications with other networks. For example, the core network **109** may include, or may communicate with, an IP gateway, such as an IP Multimedia Subsystem (IMS) server, that serves as an interface between the 5G core network **109** and a PSTN **108**. For example, the core network **109** may include, or communicate with a short message service (SMS) service center that facilitates communication via the short message service. For example, the 5G core network **109** may facilitate the exchange of non-IP data packets between the WTRUs **102a**, **102b**, and **102c** and servers or applications functions **188**. In addition, the core network **170** may provide the WTRUs **102a**, **102b**, and **102c** with access to the networks **112**, which may include other wired or wireless networks that are owned or operated by other service providers.

[0233] The core network entities described herein and illustrated in FIG. **18A**, FIG. **18C**, FIG. **18D**, or FIG. **18E** are identified by the names given to those entities in certain existing 3GPP specifications, but it is understood that in the future those entities and functionalities may be identified by other names and certain entities or functions may be combined in future specifications published by 3GPP, including future 3GPP NR specifications. Thus, the particular network entities and functionalities described and illustrated in FIG. **18A**, FIG. **18B**, FIG. **18C**, FIG. **18D**, or FIG. **18E** are provided by way of example only, and it is understood that the subject matter disclosed and claimed herein may be embodied or implemented in any similar communication system, whether presently defined or defined in the future.

[0234] FIG. **18E** illustrates an example communications system **111** in which the systems, methods, apparatuses that implement eDRX enhancement for reduced capability NR devices, described herein, may be used. Communications system **111** may include Wireless Transmit/Receive Units (WTRUs) A, B, C, D, E, F, a base station gNB **121**, a V2X server **124**, and Road Side Units (RSUs) **123a** and **123b**. In practice, the concepts presented herein may be applied to any number of WTRUs, base station gNBs, V2X networks, or other network elements. One or several or all WTRUs A, B, C, D, E, and F may be out of range of the access network coverage **131**. WTRUs A, B, and C form a V2X group, among which WTRU A is the group lead and WTRUs B and C are group members.

[0235] WTRUs A, B, C, D, E, and F may communicate with each other over a Uu interface **129** via the gNB **121** if they are within the access network coverage **131**. In the example of FIG. **18E**, WTRUs B and F are shown within access network coverage **131**. WTRUs A, B, C, D, E, and F may communicate with each other directly via a Sidelink interface (e.g., PC5 or NR PC5) such as interface **125a**, **125b**, or **128**, whether they are under the access network coverage **131** or out of the access network coverage **131**. For instance, in the example of FIG. **18E**, WTRU D, which is outside

of the access network coverage **131**, communicates with WTRU F, which is inside the coverage **131**.

[0236] WTRUs A, B, C, D, E, and F may communicate with RSU **123a** or **123b** via a Vehicle-to-Network (V2N) **133** or Sidelink interface **125b**. WTRUs A, B, C, D, E, and F may communicate to a V2X Server **124** via a Vehicle-to-Infrastructure (V2I) interface **127**. WTRUs A, B, C, D, E, and F may communicate to another UE via a Vehicle-to-Person (V2P) interface **128**.

[0237] FIG. **18F** is a block diagram of an example apparatus or device WTRU **102** that may be configured for wireless communications and operations in accordance with the systems, methods, and apparatuses that implement eDRX enhancement for reduced capability NR devices, described herein, such as a WTRU **102** of FIG. **18A**, FIG. **18B**, FIG. **18C**, FIG. **18D**, or FIG. **18E**, or FIG. **1-16** (e.g., UEs). As shown in FIG. **18F**, the example WTRU **102** may include a processor **118**, a transceiver **120**, a transmit/receive element **122**, a speaker/microphone **124**, a keypad **126**, a display/touchpad/indicators **128**, non-removable memory **130**, removable memory **132**, a power source **134**, a global positioning system (GPS) chipset **136**, and other peripherals **138**. It will be appreciated that the WTRU **102** may include any sub-combination of the foregoing elements. Also, the base stations **114a** and **114b**, or the nodes that base stations **114a** and **114b** may represent, such as but not limited to transceiver station (BTS), a Node-B, a site controller, an access point (AP), a home node-B, an evolved home node-B (eNodeB), a home evolved node-B (HeNB), a home evolved node-B gateway, a next generation node-B (gNode-B), and proxy nodes, among others, may include some or all of the elements depicted in FIG. **18F** and may be an exemplary implementation that performs the disclosed systems and methods for device triggering described herein.

[0238] The processor **118** may be a general purpose processor, a special purpose processor, a conventional processor, a digital signal processor (DSP), a plurality of microprocessors, one or more microprocessors in association with a DSP core, a controller, a microcontroller, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Array (FPGAs) circuits, any other type of integrated circuit (IC), a state machine, and the like. The processor **118** may perform signal coding, data processing, power control, input/output processing, or any other functionality that enables the WTRU **102** to operate in a wireless environment. The processor **118** may be coupled to the transceiver **120**, which may be coupled to the transmit/receive element **122**. While FIG. **18F** depicts the processor **118** and the transceiver **120** as separate components, it will be appreciated that the processor **118** and the transceiver **120** may be integrated together in an electronic package or chip.

[0239] The transmit/receive element **122** of a UE may be configured to transmit signals to, or receive signals from, a base station (e.g., the base station **114a** of FIG. **18A**) over the air interface **115/116/117** or another UE over the air interface **115d/116d/117d**. For example, the transmit/receive element **122** may be an antenna configured to transmit or receive RF signals. The transmit/receive element **122** may be an emitter/detector configured to transmit or receive IR, UV, or visible light signals, for example. The transmit/receive element **122** may be configured to transmit and receive both RF and light signals. It will be appreciated that the transmit/receive element **122** may be configured to transmit or receive any combination of wireless or wired signals.

[0240] In addition, although the transmit/receive element **122** is depicted in FIG. **18F** as a single element, the WTRU **102** may include any number of transmit/receive elements **122**. More specifically, the WTRU **102** may employ MIMO technology. Thus, the WTRU **102** may include two or more transmit/receive elements **122** (e.g., multiple antennas) for transmitting and receiving wireless signals over the air interface **115/116/117**.

[0241] The transceiver **120** may be configured to modulate the signals that are to be transmitted by the transmit/receive element **122** and to demodulate the signals that are received by the transmit/receive element **122**. As noted above, the WTRU **102** may have multi-mode capabilities. Thus, the transceiver **120** may include multiple transceivers for enabling the WTRU **102** to

communicate via multiple RATs, for example NR and IEEE 802.11 or NR and E-UTRA, or to communicate with the same RAT via multiple beams to different RRHs, TRPs, RSUs, or nodes. [0242] The processor **118** of the WTRU **102** may be coupled to, and may receive user input data from, the speaker/microphone **124**, the keypad **126**, or the display/touchpad/indicators **128** (e.g., a liquid crystal display (LCD) display unit or organic light-emitting diode (OLED) display unit. The processor **118** may also output user data to the speaker/microphone **124**, the keypad **126**, or the display/touchpad/indicators **128**. In addition, the processor **118** may access information from, and store data in, any type of suitable memory, such as the non-removable memory **130** or the removable memory **132**. The non-removable memory **130** may include random-access memory (RAM), read-only memory (ROM), a hard disk, or any other type of memory storage device. The removable memory **132** may include a subscriber identity module (SIM) card, a memory stick, a secure digital (SD) memory card, and the like. The processor **118** may access information from, and store data in, memory that is not physically located on the WTRU **102**, such as on a server that is hosted in the cloud or in an edge computing platform or in a home computer (not shown). The processor **118** may be configured to control lighting patterns, images, or colors on the display or indicators **128** in response to whether the setup of the systems area in some of the examples described herein are successful or unsuccessful, or otherwise indicate a status of eDRX enhancement for reduced capability NR devices and associated components. The control lighting patterns, images, or colors on the display or indicators **128** may be reflective of the status of any of the method flows or components in the FIG.'s illustrated or discussed herein (e.g., FIG. 4-FIG. 16, etc.). Disclosed herein are messages and procedures of eDRX enhancement for reduced capability NR devices. The messages and procedures may be extended to provide interface/API for users to request resources via an input source (e.g., speaker/microphone **124**, keypad **126**, or display/touchpad/indicators **128**) and request, configure, or query eDRX enhancement for reduced capability NR devices related information, among other things that may be displayed on display **128**.

[0243] The processor **118** may receive power from the power source **134** and may be configured to distribute or control the power to the other components in the WTRU **102**. The power source **134** may be any suitable device for powering the WTRU **102**. For example, the power source **134** may include one or more dry cell batteries, solar cells, fuel cells, and the like. Additional considerations, especially for RedCap devices, power sources may be intermittent and vary with time. Wireless power transfer and energy harvesting (e.g., RF charging, solar power and the like), power dissipation or charging rates, and power level threshold information can be leveraged by the WTRU for triggering paging configuration updates.

[0244] The processor **118** may also be coupled to the GPS chipset **136**, which may be configured to provide location information (e.g., longitude and latitude) regarding the current location of the WTRU **102**. In addition to, or in lieu of, the information from the GPS chipset **136**, the WTRU **102** may receive location information over the air interface **115/116/117** from a base station (e.g., base stations **114a**, **114b**) or determine its location based on the timing of the signals being received from two or more nearby base stations. It will be appreciated that the WTRU **102** may acquire location information by way of any suitable location-determination method.

[0245] The processor **118** may further be coupled to other peripherals **138**, which may include one or more software or hardware modules that provide additional features, functionality, or wired or wireless connectivity. For example, the peripherals **138** may include various sensors such as an accelerometer, biometrics (e.g., finger print) sensors, an e-compass, a satellite transceiver, a digital camera (for photographs or video), a universal serial bus (USB) port or other interconnect interfaces, a vibration device, a television transceiver, a hands free headset, a Bluetooth® module, a frequency modulated (FM) radio unit, a digital music player, a media player, a video game player module, an Internet browser, and the like.

[0246] The WTRU **102** may be included in other apparatuses or devices, such as a sensor,

consumer electronics, a wearable device such as a smart watch or smart clothing, a medical or eHealth device, a robot, industrial equipment, a drone, a vehicle such as a car, truck, train, or an airplane. The WTRU **102** may connect with other components, modules, or systems of such apparatuses or devices via one or more interconnect interfaces, such as an interconnect interface that may comprise one of the peripherals **138**.

[0247] FIG. **18G** is a block diagram of an exemplary computing system **90** in which one or more apparatuses of the communications networks illustrated in FIG. **18A**, FIG. **18C**, FIG. **18D** and FIG. **18E** as well as eDRX enhancement for reduced capability NR devices, such as the systems and methods illustrated in FIG. **1** through FIG. **16** described and claimed herein may be embodied, such as certain nodes or functional entities in the RAN **103/104/105**, Core Network **106/107/109**, PSTN **108**, Internet **110**, Other Networks **112**, or Network Services **113**. Computing system **90** may comprise a computer or server and may be controlled primarily by computer readable instructions, which may be in the form of software, wherever, or by whatever means such software is stored or accessed. Such computer readable instructions may be executed within a processor **91**, to cause computing system **90** to do work. The processor **91** may be a general purpose processor, a special purpose processor, a conventional processor, a digital signal processor (DSP), a plurality of microprocessors, one or more microprocessors in association with a DSP core, a controller, a microcontroller, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Array (FPGAs) circuits, any other type of integrated circuit (IC), a state machine, and the like. The processor **91** may perform signal coding, data processing, power control, input/output processing, or any other functionality that enables the computing system **90** to operate in a communications network. Coprocessor **81** is an optional processor, distinct from main processor **91**, that may perform additional functions or assist processor **91**. Processor **91** or coprocessor **81** may receive, generate, and process data related to the methods and apparatuses disclosed herein for eDRX, such as receiving eDRX related messages.

[0248] In operation, processor **91** fetches, decodes, and executes instructions, and transfers information to and from other resources via the computing system's main data-transfer path, system bus **80**. Such a system bus connects the components in computing system **90** and defines the medium for data exchange. System bus **80** typically includes data lines for sending data, address lines for sending addresses, and control lines for sending interrupts and for operating the system bus. An example of such a system bus **80** is the PCI (Peripheral Component Interconnect) bus.

[0249] Memories coupled to system bus **80** include random access memory (RAM) **82** and read only memory (ROM) **93**. Such memories include circuitry that allows information to be stored and retrieved. ROMs **93** generally include stored data that cannot easily be modified. Data stored in RAM **82** may be read or changed by processor **91** or other hardware devices. Access to RAM **82** or ROM **93** may be controlled by memory controller **92**. Memory controller **92** may provide an address translation function that translates virtual addresses into physical addresses as instructions are executed. Memory controller **92** may also provide a memory protection function that isolates processes within the system and isolates system processes from user processes. Thus, a program running in a first mode may access only memory mapped by its own process virtual address space; it cannot access memory within another process's virtual address space unless memory sharing between the processes has been set up.

[0250] In addition, computing system **90** may include peripherals controller **83** responsible for communicating instructions from processor **91** to peripherals, such as printer **94**, keyboard **84**, mouse **95**, and disk drive **85**.

[0251] Display **86**, which is controlled by display controller **96**, is used to display visual output generated by computing system **90**. Such visual output may include text, graphics, animated graphics, and video. The visual output may be provided in the form of a graphical user interface (GUI). Display **86** may be implemented with a CRT-based video display, an LCD-based flat-panel display, gas plasma-based flat-panel display, or a touch-panel. Display controller **96** includes

electronic components required to generate a video signal that is sent to display **86**.

[0252] Further, computing system **90** may include communication circuitry, such as for example a wireless or wired network adapter **97**, that may be used to connect computing system **90** to an external communications network or devices, such as the RAN **103/104/105**, Core Network **106/107/109**, PSTN **108**, Internet **110**, WTRUs **102**, or Other Networks **112** of FIG. **18A**, FIG. **18B**, FIG. **18C**, FIG. **18D**, or FIG. **18E**, to enable the computing system **90** to communicate with other nodes or functional entities of those networks. The communication circuitry, alone or in combination with the processor **91**, may be used to perform the transmitting and receiving steps of certain apparatuses, nodes, or functional entities described herein.

[0253] It is understood that any or all of the apparatuses, systems, methods and processes described herein may be embodied in the form of computer executable instructions (e.g., program code) stored on a computer-readable storage medium which instructions, when executed by a processor, such as processors **118** or **91**, cause the processor to perform or implement the systems, methods and processes described herein. Specifically, any of the steps, operations, or functions described herein may be implemented in the form of such computer executable instructions, executing on the processor of an apparatus or computing system configured for wireless or wired network communications. Computer readable storage media includes volatile and nonvolatile, removable and non-removable media implemented in any non-transitory (e.g., tangible or physical) method or technology for storage of information, but such computer readable storage media do not include signals. Computer readable storage media include, but are not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other tangible or physical medium which may be used to store the desired information and which may be accessed by a computing system.

[0254] In describing preferred methods, systems, or apparatuses of the subject matter of the present disclosure-eDRX enhancement for reduced capability NR devices—as illustrated in the Figures, specific terminology is employed for the sake of clarity. The claimed subject matter, however, is not intended to be limited to the specific terminology so selected.

[0255] The various techniques described herein may be implemented in connection with hardware, firmware, software or, where appropriate, combinations thereof. Such hardware, firmware, and software may reside in apparatuses located at various nodes of a communication network. The apparatuses may operate singly or in combination with each other to effectuate the methods described herein. As used herein, the terms “apparatus,” “network apparatus,” “node,” “device,” “network node,” or the like may be used interchangeably. In addition, the use of the word “or” is generally used inclusively unless otherwise provided herein.

[0256] This written description uses examples for the disclosed subject matter, including the best mode, and also to enable any person skilled in the art to practice the disclosed subject matter, including making and using any devices or systems and performing any incorporated methods. The disclosed subject matter may include other examples that occur to those skilled in the art (e.g., skipping steps, combining steps, or adding steps between exemplary methods disclosed herein).

[0257] Methods, systems, apparatus, and the like may provide for eDRX enhancements for reduced capability NR devices. In an example, an apparatus may receive paging configuration information (e.g., PTW, WUS, DRX/eDRX, etc. configuration) from a 2nd apparatus to monitor a plurality of PDCCH monitoring occasions; receive paging configuration information from a 3rd apparatus to monitor a plurality of PDCCH monitoring occasions; determine when to monitor a set of PDCCH monitoring occasions based on the paging configuration information received from the second and third apparatuses; determine when to send a request to change when to monitor a set of PDCCH monitoring occasions; and send a request to change when to monitor a set of PDCCH monitoring occasions. There may be continued monitoring of a set of PDCCH monitoring occasions outside (e.g., after or end) of the configured Paging Time Window radio frame when monitoring a set of

PDCCH monitoring occasions outside of Paging Time Window radio frame. The apparatus may be identified as a Reduced Capabilities (RedCap) device or a particular type of RedCap device. The apparatus may receive paging configuration information from a 2nd apparatus (e.g., base station-nodeB) or 3rd apparatus (e.g., an AMF or other core network device) to monitor a plurality of PDCCH monitoring occasions specifically configured for the identified device type. The request to change when to monitor a set of PDCCH monitoring occasions may be triggered based on the change of a traffic profile. The traffic profiles may be associated with an RRC state or with an emergency alert (e.g., CMAS, PWS, or ETWS). The paging configuration information from a 2nd apparatus or a 3rd apparatus to monitor a plurality of PDCCH monitoring occasions is modified based on a change of a traffic profile, wherein the change in traffic profile may be planned, or predictive. The change in traffic profile or change in planned traffic profile or prediction of traffic profile may be reported from the device to the Network. The device (e.g., one of the apparatuses) receives paging configuration information inclusive of a common starting point for paging timing window information that is coordinated between the 2nd apparatus and the 3rd apparatus. The device receives paging configuration information inclusive of a paging timing window extension indication via one or more of the following: receive a paging request message from the second apparatus initiated by the third apparatus; receive prior to the 2nd apparatus transmitting a paging DCI; receive in a channel that is based on a matched filter or correlation metric; receive in a Wake-Up-Signal (WUS); receive in an RRC configuration message; or receive in a System Information Update message. In an example, a method may include determining paging timing window information for a plurality of PDCCH monitoring occasions based on receiving paging timing window information from a Core Network (e.g., AMF); transmitting to an apparatus, the paging timing window information for when to monitor a set of PDCCH monitoring occasions; and evaluating requests from one or more apparatus for changing when to monitor a set of PDCCH monitoring occasions. Based on the evaluating of the request, sending a response. The response may include an indication whether and when to change the set of PDCCH monitoring occasions. All combinations in this paragraph and the below paragraph (including the removal or addition of steps) are contemplated in a manner that is consistent with the other portions of the detailed description.

[0258] Methods, systems, apparatus, and the like may provide for eDRX enhancements for reduced capability NR devices. In an example, an apparatus may receive an event trigger to modify the paging configuration information; receiving a configuration update command to modify paging configuration information from a Core Network; and sending a configuration update complete message upon completion. The paging configuration information may be validated and reconfigured as determined by the gNB based on assistance information received from the Core Network. In an example, an apparatus may monitor PDCCH monitoring occasions, wherein the PDCCH monitoring occasions are associated with a paging occasion (PO) that overlaps with a paging timing window (PTW) and is not fully contained within the PTW, and the first apparatus is configured to perform one or more of the following: 1) monitor the PDCCH monitoring occasions outside the PTW (which may be all) that belongs to the PO that overlaps with the PTW; 2) monitor a preconfigured number of PDCCH monitoring occasions outside PTW that belong to the PO that overlaps with the PTW; 3) monitor only a complete PO that is fully contained with the PTW; or 4) monitor PDCCH monitoring occasions until a page is received within the PO or until the PO ends. In an example, an apparatus may receive paging configuration information from the second apparatus or a third apparatus to monitor a plurality of PDCCH monitoring occasions specifically configured for one or more of the following identified device types and characteristics: 1) Reduced Capabilities (RedCap) device; 2) particular type of RedCap device; or 3) power characteristics. The first apparatus may report to the second apparatus or the third apparatus a change in traffic profile or in planned or prediction of traffic profile, and receives from the second apparatus or the third apparatus as a result of reporting to the second apparatus or the third apparatus a change in traffic

profile or in planned or prediction of traffic profile, an update to the set of PDCCH monitoring occasions. The second apparatus or third apparatus may modify the paging configuration information in the first apparatus, based on a change of the available paging capacity of the network. The first apparatus may receive periodically in system information based on beam sweeping or SSB burst patterns, the paging configuration information including a paging timing window (PTW) from the second apparatus. All combinations in this paragraph (including the removal or addition of steps) are contemplated in a manner that is consistent with the other portions of the detailed description.

Claims

1. An apparatus for wireless communication, the apparatus comprising circuitry configured to: send a registration request for an extended discontinuous reception (eDRX) to a core network; receive, in response to the registration request, a first eDRX configuration from the core network, wherein the first eDRX configuration comprises first eDRX parameters associated with the apparatus; and receive a message indicating a second eDRX configuration from a gNB, wherein the second eDRX configuration is determined by the gNB based on an RRC assistance information received from the core network, wherein the RRC assistance information comprise second eDRX parameters associated with the apparatus.
2. The apparatus of claim 1, wherein the first eDRX parameters comprises a first eDRX cycle and a first paging time window (PTW) length.
3. The apparatus of claim 2, wherein the second eDRX parameters comprise at least one of a second eDRX cycle and a second PTW length.
4. The apparatus of claim 1, wherein the registration request indicates identification of capabilities of the apparatus to determine whether or not the apparatus is a RedCap UE.
5. The apparatus of claim 1, wherein the core network is configured to send the RRC assistance information to the gNB when user plane information associated with the apparatus have changed.
6. A method for a network system comprising gNB and a core network, the method comprising: receiving, at the core network, a registration request for an extended discontinuous reception (eDRX) from an apparatus; transmitting, from the core network in response to the registration request, a first eDRX configuration to the apparatus, wherein the first eDRX configuration comprises first eDRX parameters associated with the apparatus; and transmitting, from the gNB, a message indicating a second eDRX configuration to the apparatus, wherein the second eDRX configuration is determined by the gNB based on an RRC assistance information received from the core network, wherein the RRC assistance information comprise second eDRX parameters associated with the apparatus.
7. The method of claim 6, wherein the first eDRX parameters comprises a first eDRX cycle and a first paging time window (PTW) length.
8. The method of claim 7, wherein the second eDRX parameters comprise at least one of a second eDRX cycle and a second PTW length.
9. The method of claim 6, wherein the registration request indicates identification of capabilities of the apparatus to determine whether or not the apparatus is a RedCap UE.
10. The method of claim 6, wherein the core network is configured to send the RRC assistance information to the gNB when user plane information associated with the apparatus have changed.
11. A method for a core network, the method comprising: receiving a registration request for an extended discontinuous reception (eDRX) from an apparatus; transmitting, in response to the registration request, a first eDRX configuration to the apparatus, wherein the first eDRX configuration comprises first eDRX parameters associated with the apparatus; and transmitting a RRC assistance information to a gNB, wherein the RRC assistance information comprise second eDRX parameters associated with the apparatus, the gNB being configured to transmit a message

indicating a second eDRX configuration to the apparatus, wherein the second eDRX configuration is determined by the gNB based on the RRC assistance information.

12. The method of claim 11, wherein the first eDRX parameters comprises a first eDRX cycle and a first paging time window (PTW) length.

13. The method of claim 12, wherein the second eDRX parameters comprise at least one of a second eDRX cycle and a second PTW length.

14. The method of claim 11, wherein the registration request indicates identification of capabilities of the apparatus to determine whether or not the apparatus is a RedCap UE.

15. The method of claim 11, wherein the core network is configured to send the RRC assistance information to the gNB when user plane information associated with the apparatus have changed.
