

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250264977

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

SHIM; Jung-hyun et al.

### USER TERMINAL APPARATUS AND MANAGEMENT METHOD OF HOME NETWORK THEREOF

#### Abstract

An example user terminal apparatus includes communication circuitry configured to be connected to a home network comprising a plurality of devices; a display configured to display a UI screen for managing the home network; a sensor configured to sense a user manipulation of the UI screen; and processing circuitry configured to change the UI screen displayed on the display according to the user manipulation. The UI screen is one of a plurality of service pages that are changeable according to a user manipulation in a first direction, the plurality of service pages being pages for respectively providing different home network management services. At least one of the plurality of service pages comprises an area that is displayable on the display according to a user manipulation in a second direction.

**Inventors:** SHIM; Jung-hyun (Suwon-si, KR), KIM; Chang-won (Suwon-si, KR), JOO; Ga-hyun (Suwon-si, KR), KIM; Jin-sung (Suwon-si, KR), RYU; Jong-youb (Suwon-si, KR), LEE; Chang-hyun (Suwon-si, KR), LIM; Yong-hyun (Suwon-si, KR)

**Applicant:** SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

**Family ID:** 1000008586704

**Appl. No.:** 19/080866

**Filed:** March 16, 2025

#### Foreign Application Priority Data

KR

10-2014-0074580

Jun. 18, 2014

#### Related U.S. Application Data

parent US continuation 18100379 20230123 parent-grant-document US 12277302 child US 19080866

parent US continuation 17497957 20211010 parent-grant-document US 11592968 child US

18100379

parent US continuation 16723950 20191220 parent-grant-document US 11163425 child US 17497957

parent US continuation 14900082 20151218 parent-grant-document US 10564813 WO continuation PCT/KR2014/005385 20140618 child US 16723950  
us-provisional-application US 61836251 20130618

---

## Publication Classification

**Int. Cl.:** **G06F3/0483** (20130101); **G06F1/16** (20060101); **G06F3/0346** (20130101); **G06F3/04817** (20220101); **G06F3/0482** (20130101); **G06F3/04847** (20220101); **G06F3/04883** (20220101); **H04L12/28** (20060101)

**U.S. Cl.:**

**CPC** **G06F3/0483** (20130101); **G06F1/1694** (20130101); **G06F3/0346** (20130101); **G06F3/04817** (20130101); **G06F3/0482** (20130101); **G06F3/04847** (20130101); **G06F3/04883** (20130101); **H04L12/2803** (20130101); **H04L12/2809** (20130101); **H04L12/2816** (20130101); G06F2200/1614 (20130101); G06F2200/1637 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/100,379, filed Jan. 23, 2023, which is a continuation of U.S. application Ser. No. 17/497,957, filed Oct. 10, 2021, now U.S. Pat. No. 11,592,968, which is a continuation of U.S. application Ser. No. 16/723,950, filed Dec. 20, 2019, now U.S. Pat. No. 11,163,425, which is a continuation of U.S. application Ser. No. 14/900,082, filed on Dec. 18, 2015, now U.S. Pat. No. 10,564,813, which is a national stage application of International Patent Application No. PCT/KR2014/005385, filed on Jun. 18, 2014, which designates the United States, which claims the benefit of U.S. Provisional Application No. 61/836,251, filed Jun. 18, 2013, and which claims priority to Korean Patent Application No. 10-2014-0074580, filed Jun. 18, 2014. The contents of each of these applications are incorporated herein in their entirety.

### TECHNICAL FIELD

[0002] The present application generally describes a user terminal apparatus and a management method of a home network thereof, and more particularly, a user terminal apparatus that provides various user interface (UI) screens for managing a home network and a management method of a home network thereof.

### BACKGROUND AND SUMMARY

[0003] With the development of computer technologies, communication technologies, and home electronics technologies, a network management service for managing a home network to which apparatuses and systems in a home are connected has taken center stage as a future-oriented technology.

[0004] All types of information electronic appliances that are connected to one another through a home network in a home may transmit data to one another and communicate with various types of user terminal apparatuses. For example, a user may control all types of electronic appliances that are connected to one another through a home network in a home regardless of time and place, by using a UI installed in a user terminal apparatus such as a portable phone, a mobile phone, a smart phone or the like.

[0005] However, since ubiquitous service eXchanges (UXs), which are provided according to different types of businesses such as a manufacturer, a communication company, etc., are different, it is still difficult to provide a home network management service. For example, whenever a device is newly added to a home network, the user has no choice but to adapt to a new UI screen design or have the discomfort of a fixed UI screen that may not satisfy various tastes of the user.

[0006] Also, various services, such as controls, methods, energy management, and the like of home appliances, are provided in a home network system. However, it can be difficult for the user to check, in one view, various functions provided from various services through only an existing service UI screen.

[0007] The present application describes a user terminal apparatus that provides various user interface (UI) screens for managing a home network and a method of managing a home network thereof.

[0008] According to a non-limiting aspect of the technology described herein, there is provided a user terminal apparatus including: a communication unit configured to be connected to a home network comprising a plurality of devices; a display unit configured to display a UI screen for managing the home network; a sensing unit configured to sense a user manipulation of the UI screen; and a control unit configured to change the UI screen displayed on the display unit according to the user manipulation. The UI screen may be one of a plurality of service pages that are changeable according to a user manipulation in a first direction, and the plurality of service pages may be pages for respectively providing different home network management services, and at least one of the plurality of service pages may include an area that is displayable on the display unit according to a user manipulation in a second direction.

[0009] In response to one of the plurality of service pages being selected, the control unit may display a function area page subordinate to the service page on the display unit.

[0010] The first direction may be a horizontal direction, the second direction may be a vertical direction, and the control unit may sequentially display the plurality of service pages page by page in response to a flick or drag manipulation being input in the horizontal direction and display a function area included in the service page in response to a flick or drag manipulation being input in the vertical direction.

[0011] One of the plurality of service pages may be a main page, and the main page may include an information display area of the home network and at least one favorite function area that is displayable according to a user manipulation in the second direction.

[0012] In response to a new device being added to the home network, the control unit may add at least one of a new service page and a new function area.

[0013] The plurality of service pages may include at least one of a control service page providing a control menu for respectively controlling operations of the plurality of devices, an energy service page providing energy usage information of the plurality of devices, a monitoring service page providing a monitoring service by using a photographing device of the plurality of devices, a media service page providing a media service by using a media output device of the plurality of devices, and a mode service page for differently controlling the plurality of devices according to a home network mode.

[0014] A function area of the control service page may include the control menu, a function area of the energy service page may include periodical energy usage information of the plurality of devices, a function area of the monitoring service page may include data captured by one of the plurality of devices, a function area of the media service may include a menu for managing a file stored in at least one of the plurality of devices, a function area of the mode service page may include a mode execution menu for executing one mode, and in response to the mode execution menu being selected, the control unit may control devices included in a group corresponding to the mode execution menu at one time.

[0015] The plurality of service pages may respectively include service summary areas. In response

to a service summary area of one service page being displayed and a user manipulation in the second direction being performed, the control unit may move and display at least one function area connected to the service summary area onto the service summary area.

[0016] In response to the at least one function area being displayed on the display unit and an enlarge menu icon of one function area being selected, the control unit may enlarge the one function area to a detailed function area and display the detailed function area in a whole area of the display unit.

[0017] In response to the at least one function area being displayed on the display unit and a pinch gesture being input, the control unit may reduce the at least one function area to corresponding objects and display the corresponding objects and, in response to one of the objects being selected, change the selected object to a function area and display the function area.

[0018] The user terminal apparatus may further include a rotation sensing unit configured to sense a rotation of the user terminal apparatus. The control unit may display the main page according to a first layout in response to the display unit being oriented in the vertical direction and display the main page according to a second layout in response to the display unit being oriented in the horizontal direction.

[0019] The first layout may be a layout in which the information display area of the home network and at least one favorite function area are connected in a second axis direction based on the information display area of the home network, and the second layout may be a layout that includes a plurality of state information areas indicating state information of respective rooms included in an environment managed by the home network.

[0020] According to another non-limiting aspect of the technology described herein, a method of managing a home network of a user terminal apparatus includes, in response to an application for managing the home network including a plurality of devices, being executed, displaying a first service page of a plurality of service pages for managing the home network; in response to the first service page being displayed and a user manipulation in a first direction being input, displaying a second service page connected to the first service page; and in response to the first service page or the second service page being displayed and a user manipulation in a second direction, displaying a function area comprised in the first service page or the second service page. The plurality of service pages may be pages for respectively providing different home network management services.

[0021] The method may further include: in response to one of the plurality of service pages being selected, displaying a function area subordinate to the service page on a display unit.

[0022] The method may further include: in response to a new device being added to the home network, adding at least one of a new service page and a new function area.

[0023] The one of the plurality of service pages may be a main page, and the main page may include an information display area of the home network and at least one favorite function area that is displayable on a display unit according to a user manipulation in the second direction.

[0024] The plurality of service pages may respectively include service summary areas and at least one function area connected to the service summary areas. The displaying of the at least one function area may include: in response to the at least one function area being displayed and a user manipulation in the second direction being performed, moving and displaying the at least one function area onto the service summary areas.

[0025] The method may further include: in response to the at least one function area being displayed and an enlarge menu icon of one function area being selected, enlarging the one function area to a detailed function area and displaying the detailed function area.

[0026] The method may further include: in response to at least one function area being displayed and a pinch gesture being input, reducing the at least one function area to corresponding objects and displaying the corresponding objects, and in response to one of the reduced objects being selected, changing the selected object to a function area and displaying the function area.

[0027] The method may further include: in response to the main page being displayed and a display

unit of the user terminal apparatus being oriented in a vertical direction, displaying the main page according to a first layout, and in response to the display unit being oriented in a horizontal direction, displaying the main page according to a second layout.

[0028] According to various example embodiments as described above, a home network service user interface (UI) screen that reflects various needs of a user may be provided. Therefore, the user may further intuitively and efficiently use various services.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0029] FIG. 1 illustrates an example UI screen for managing a home network according to a non-limiting example embodiment.

[0030] FIGS. 2, 3 and 4 illustrate a layout of an example UI screen for managing a home network according to a non-limiting example embodiment.

[0031] FIGS. 5, 6, 7 and 8 illustrate an example home network system for providing a home network management service according to various non-limiting example embodiments.

[0032] FIG. 9 is a block diagram of an example user terminal apparatus according to a non-limiting example embodiment.

[0033] FIG. 10 illustrates a main page of an example UI screen for managing a home network according to a non-limiting example embodiment.

[0034] FIGS. 11A, 11B, 11C, 11D, 12A, 12B and 12C illustrate a function area that is included in an example home network management service page according to various non-limiting example embodiments.

[0035] FIG. 13 is a block diagram of a detailed structure of an example user terminal apparatus according to a non-limiting example embodiment.

[0036] FIGS. 14A, 14B, 14C, 15A, 15B, 16 and 17 illustrate an example main page according to various non-limiting example embodiments.

[0037] FIGS. 18, 19, 20, 21, 22, 23, 24 and 25 illustrate an example first service page according to various non-limiting example embodiments.

[0038] FIGS. 26, 27, 28A, 28B, 29, 30, 31, 32, 33 and 34 illustrate an example second service page according to various non-limiting example embodiments.

[0039] FIGS. 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47 and 48 illustrate an example third service page according to various non-limiting example embodiments.

[0040] FIGS. 49 and 50 illustrate an example fourth service page according to various non-limiting example embodiments.

[0041] FIGS. 51, 52, 53, 54 and 55 illustrate an example fifth service page according to various non-limiting example embodiments.

[0042] FIGS. 56, 57, 58 and 59 illustrate an example sixth service page according to various non-limiting example embodiments.

[0043] FIGS. 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72 and 73 illustrate an example setting screen according to various non-limiting example embodiments.

[0044] FIG. 74 is a flowchart of an example method of managing a home network of a user terminal apparatus according to a non-limiting example embodiment.

[0045] FIGS. 75 and 76 illustrate map information that is provided by an example user terminal apparatus according to a non-limiting example embodiment.

[0046] FIG. 77 illustrates a method of operating an example user terminal apparatus according to another non-limiting example embodiment.

[0047] FIGS. 78, 79, 80 and 81 illustrate an example user terminal apparatus that is realized as a TV according to another non-limiting example embodiment.

## DETAILED DESCRIPTION

[0048] Example embodiments are described in greater detail with reference to the accompanying drawings.

[0049] In the following description, the same drawing reference numerals are used for the same elements in different drawings. The matters defined in the description, such as detailed construction and elements, are provided to assist in a comprehensive understanding of the example embodiments. Thus, it is apparent that the example embodiments may be carried out without those specifically defined matters. Also, well-known functions or constructions are not described in detail to avoid obscuring the example embodiments with unnecessary detail.

[0050] FIG. 1 illustrates an operation of an example user terminal apparatus according to a non-limiting example embodiment. A user terminal apparatus **200** is an element that receives a user manipulation by using various types of input devices or units such as a touch screen, a mouse, a keyboard, a touchpad, a button, a microphone, a camera, etc. and performs a control operation corresponding to the user manipulation. In detail, the user terminal apparatus **200** may be realized as various types of devices or apparatuses such as a portable phone, a mobile phone, a smart phone, a laptop personal computer (PC), a tablet PC, a personal digital assistant (PDA), a PC, a TV, a home network control apparatus, etc. The user terminal apparatus **200** may be variously referred to as a management apparatus, a control apparatus, a display apparatus, etc. but is referred to herein as the user terminal apparatus **200**.

[0051] A user may manage a home network system **500** by using the user terminal apparatus **200**. The user terminal apparatus **200** displays a UI screen that is designed so as to enable the user to manage the home network system **500**. Home network management is a concept including control of devices connected to one another through a network in a home, analyses of states of the devices, sensing of dangerous situations in the home, information exchanges between family members, etc. and is possible through the user terminal apparatus **200**.

[0052] Referring to FIG. 1, a UI screen that is displayed through a display unit **220** of the user terminal apparatus **200** is a part of one of a plurality of service pages **100-1** through **100-7**.

[0053] A service page may refer to, for example, a page including a service summary area and at least one function area. The plurality of service pages are pages for respectively providing different home network management services. The plurality of service pages may be changed according to a user manipulation in a first direction. Also, at least one of the service pages may include a function area that is displayed according to a user manipulation in a second direction. The service pages may be connected to one another and may be separately displayed on the display unit **220** according to a user manipulation. Also, the first direction may correspond to a horizontal direction, and the second direction may correspond to a vertical direction, but the first and second directions are not necessarily limited in this respect.

[0054] A direction may be changed on the display unit **220** according to settings to display the UI screen. For example, the user terminal apparatus **200** may include a gravity sensor, and a control unit may change a direction of the UI screen so as to enable the UI screen to correspond to aspects of an orientation of the user terminal apparatus **200**. Therefore, the vertical direction and the horizontal direction may be determined according to a direction of a screen displayed on the display unit **220**. The horizontal direction may be a direction displayed from left to right or from right to left on the displayed screen, and the vertical direction may be a direction displayed from top to bottom or from bottom to top.

[0055] As shown in FIG. 1, a service summary area **110-1** of a main service **100-1** of a plurality of service pages is currently displayed on the display unit **220**. For example, if a user manipulation in a first direction is input, a service summary area **110-2** of a monitoring service page **100-2** connected to (or accessible via) the main page **100-1** may be displayed. As another example, if a user manipulation in a second direction is input when the service summary area **110-1** of the main page **100-1** is displayed, at least one favorite function area **120-1**, **122-1**, and **124-1** connected to

(or accessible via) the service summary area **110-1** may be displayed.

[0056] For convenience of description, respective service pages are designated as shown in FIG. **1**. However, the arrangement order and designation of service pages is not limited to that shown in FIG. **1**, and may involve other types of service pages, designs of service pages, etc.

[0057] UI screens having different characteristics may be arranged in the first and second directions. For example, service screens for managing a home network may be arranged in the first direction, and screens for controlling functions of devices included in the home network may be arranged in the second direction. Also, the screens for controlling the functions of the devices used for providing corresponding services on the service screens arranged in the first direction may be respectively arranged in the second direction.

[0058] FIG. **1** illustrates a whole structure of a UI screen provided by the user terminal apparatus **200** according to an example embodiment. The UI screen may provide various home network management services and includes screen designs, structures, information, etc. appropriate for service characteristics.

[0059] The display unit **220** of the user terminal apparatus **200** may display a part of the whole structure of the UI screen shown in FIG. **1** according to a user manipulation direction.

[0060] Referring to FIG. **1**, the example UI screen for managing the home network is a screen on which one of a plurality of service pages **100-2** through **100-7** is displayed. Here, the plurality of service pages **100-2** through **100-7** are arranged in the first direction relative to the main page **100-1**. In FIG. **1**, a horizontal direction may be the first direction based on the display unit **220** of the user terminal apparatus **200**, and a vertical direction may be the second direction. However, the first and second directions are not limited to this arrangement. For example, the vertical direction may be set to the first direction, and the horizontal direction may be set to the second direction. Alternatively, a third or fourth direction that is a diagonal direction may be additionally set.

[0061] The user inputs a user manipulation to directly touch a surface of the display unit **220** so as to perform flicking or dragging in the first or second direction. However, types of user manipulations are not limited thereto. For example, the user may change a screen by using a touch pen or may change the screen by using a direction button, a wheel button, or the like. Also, the user may manipulate a UI screen by using a motion (e.g. tilting the user terminal apparatus **200**) or a voice. Example embodiments where a UI is changed according to a touch manipulation method of directly touching a screen by a user will now be described.

[0062] If an icon corresponding to a home network function is selected so as to perform the home network function on the user terminal apparatus **200** or the user terminal apparatus **200** is turned on to be booted-up, the user terminal apparatus **200** may display the main page **100-1**. Alternatively, a currently used service page may be displayed.

[0063] The main page **100-1** is an initial page that is provided from a home network management service and may include a home network situation, environment information such as time, weather, etc., an external traffic situation, etc. Besides these, other types of information, such as various types of information released in relation to a home network management, news updates, a danger (e.g., extreme weather conditions) guide message, etc. may be displayed on the main page **100-1**. The main page **100-1** may alternatively be referred to as an initial page, a home page, a landing page, etc.

[0064] Referring to FIG. **1**, the main page **100-1** includes an information display area **110-1** for displaying information about a home network and the plurality of favorite function areas **120-1**, **122-1**, and **124-1** that are sequentially arranged in the second direction under the information display area **110-1**.

[0065] At least one or more service pages may be connected to the main page **100-1**. In FIG. **1**, the plurality of service pages **100-2** through **100-7** are connected to the main page **100-1** along the first direction. Information about various services for managing the home network may be respectively displayed on the service pages **100-2** through **100-7**.

[0066] In detail, referring to FIG. 1, the plurality of service pages **100-2** through **100-7** respectively include service summary areas **110-2** through **110-7** and a plurality of function areas **120-2**, **122-2**, **120-3**, **122-3**, **120-4**, **122-4**, **120-5**, **122-5**, **120-6**, **122-6**, **120-7**, and **122-7** that are sequentially arranged in the second direction under corresponding service summary areas **110-2** through **110-7**.

[0067] Here, function areas may refer, for example, to areas that may directly select or control functions respectively provided from service pages. For example, if a third service page **100-4** is used to display control services of devices in a home, an arbitrary function area included in the third service page **100-4** may be a function area for controlling a TV or an air conditioner. When a TV control function area is displayed on the display unit **220**, the user may immediately turn a TV on or off or control a volume, a channel, or the like through the TV control function area.

[0068] The plurality of service pages **100-2** through **100-7** may respectively further include additional menus (e.g., menus **124-2** and **124-3**). The user may select an additional menu to add a new function area into a corresponding service page.

[0069] The user of the user terminal apparatus **200** may perform a user interaction by using each UI screen arranged according to the first or second direction. In detail, the user may perform dragging or flicking along the first or second direction to change a UI screen. A user interaction method will now be described in detail.

[0070] When a summary area of a service page is displayed, the user may call a function area. A first service page **100-2** will be described by way of example and without limitation. A plurality of function areas included in the first service page **100-2** may sequentially go up onto and be displayed in a summary area **110-2** of a first service according to a user manipulation (e.g., a manipulation for performing dragging or flicking upwards after performing touching) in the second direction. In this case, according to example embodiments, summary areas may be maintained, and function areas may respectively overlap and be displayed on the summary areas or the summary areas may be pushed upwards to gradually display the function areas. Alternatively, a screen change may be immediately performed according to display sizes. In other words, if the user inputs a user manipulation upwards along the second direction when the summary area **110-2** is displayed, the summary area **110-2** may be changed into two function areas **120-2** and **122-2** right under the summary area **110-2**. Alternatively, a favorite function area or a function area may be displayed on the display unit **220** in the manner of a card taken out of a wallet. Therefore, a function area may be written as various terms such as a card, a tag, a function section, etc. The word “card” is used in FIG. 1 in consideration of a characteristic of such a function area.

[0071] If a user manipulation is input downwards along the second direction when a function area is displayed, the display unit **220** may re-display the summary area **110-2**.

[0072] A detailed operation performed according to a user input will now be described. For example, if a first user manipulation **10** in the first (horizontal) direction is input when the information display area **110-1** of the main page **100-1** is currently displayed on the display unit **220**, the display unit **220** displays a first summary area **110-2** of the first service page **100-2**. In this case, the information display area **110-1** may be immediately changed into the first service summary area **110-2** or may be changed to be pushed to the left so as to enable the first service summary area **110-2** to be gradually displayed from the left direction. Alternatively, a screen may be changed so as to enable the first service summary area **110-2** to be overlaid on the information display area **110-1**.

[0073] As another example, as shown in FIG. 1, if a second user manipulation **20** in the second direction is input when the information display area **110-1** of the home network of the main page **100-1** is currently displayed on the display unit **220**, the display unit **220** displays at least one of the plurality of favorite function areas **120-1**, **122-1**, and **124-1** of the main page **100-1**. Here, the plurality of favorite function areas **120-1**, **122-1**, and **124-1** correspond to function areas of function areas of respective service pages that are registered as bookmarks.

[0074] If a user manipulation is input in a left direction along the first direction when a plurality of



favorite function areas are displayed, the display unit **220** may immediately display the corresponding function areas **120-2** and **122-2** on the first service page **100-2** or may display the first service summary area **110-2**.

[0075] As shown in FIG. **1**, the main page **100-1** and the service pages **100-2** through **100-7** may be formed in larger sizes than a display size of the display unit **220**. Also, in the pages **100-1** through **100-7**, a size of the information display area **110-1** or sizes of service summary areas **110-2** through **110-7** may be equal to the display size of the display unit **220**. On the contrary, sizes of favorite function areas or function areas may be smaller than the display size of the display unit **220**.

Therefore, when favorite function areas or function areas are displayed, a plurality of favorite function areas or a plurality of function areas may be displayed within one screen.

[0076] The whole structure of the UI screen for managing the home network has been described above with reference to FIG. **1**, and a layout of each UI screen for managing a home network will now be described with reference to FIGS. **2** through **4**.

[0077] FIG. **2** illustrates a layout of a main page according to an example embodiment. Referring to FIG. **2**, a main page **100-1** may include a title area **130-1** and an information display area **110-1** of a home network.

[0078] A title of a home network may be displayed in the title area **130-1**. If a user does not input a particular profile, a default title may be displayed. For example, a title “Smart Home” may be displayed by default in the title area **130-1** of the main page. After that, if the user stores a particular profile, a title may be changed according to, for example, a user name. For example, if the user is a user AAA, a title “AAA’s Home” may be displayed in the title area **130-1**. Also, title area **130-1** of the main page may include a menu area **132-1**, and, if the menu area **132-1** of the main page is selected, a menu may be displayed, which may be provided on the main page **100-1**, or may be changed into a history screen. This will be described in more detail with reference to FIGS. **15** and **16**.

[0079] The information display area **110-1** of the home network may include a briefing area **112-1** that displays briefing contents, an information area **114-1** that displays information provided on the main page **100-1**, and a cue area **116-1** of a favorite function area for indicating that at least one of a plurality of favorite function areas **120-1**, **122-1**, and **124-1** is positioned at the bottom. If the cue area **116-1** of the favorite function area is touched for input of a user manipulation for performing upward dragging, the plurality of favorite function areas **120-1**, **122-1**, and **124-1** may be sequentially displayed in the information display area **110-1**.

[0080] FIG. **3** illustrates a layout of a first service page **100-2** of a plurality of service pages **100-2** through **100-7** according to an example embodiment. Layouts of the other service pages are similar to the layout of the first service page **100-2**.

[0081] Referring to FIG. **3**, the first service page **100-2** may include a title area **130-2** and a service summary area **110-2**.

[0082] The title area **130-2** of the first service page displays “Smart Home” by default and, if the user stores a profile, may be changed so that “User Name’s Home” is displayed. Also, the title area **130-2** of the first service page may include a menu area **132-2** and, if the menu area **132-2** of the first service page is selected, a menu may be provided on the first service page **100-2**.

[0083] The first service summary area **110-2** may include a first service title area **112-2** that displays a first service name, a first service description area **114-2** that displays description contents or a current state of a first service, and a first service information area **116-2** that displays main information provided on the first service page **100-2**. Here, a tip object **119-2** that calls a description of displayed information may be provided in the first service information area **116-2**. When the tip object **119-2** is selected, a description of a corresponding function may be displayed.

[0084] The first service summary area **110-2** may include an inter-service indicator **117-2** and a cue area **118-2** of a function area of the first service for indicating that at least one of a plurality of function areas **120-2**, **122-2**, and **124-2** of the first service is positioned below the service page **110-**

2. When the cue area **118-2** of the function area of the first service is touched to input the second manipulation **20** of the user for performing dragging in the second direction, the plurality of function areas **120-2** and **122-2** of the first service may be overlaid in the first service summary area **110-2** as shown in FIG. 4.

[0085] As shown in FIG. 4, the plurality of function areas **120-2** and **122-2** of the first service may include a title area **1** that provides a sub title if a title and an additional content of a function area are needed, an information area **4** that displays contents of the corresponding function area, a bookmark icon **2**, and an enlarge menu icon **3**. If the bookmark icon **2** is selected, the corresponding function area is added to a new favorite function area of the main page **100-1**. In other words, the user may check a function area, which is registered with a bookmark, on the main page **100-1** without passing through the first service page **100-2**.

[0086] If the enlarge menu icon **3** is selected, the corresponding function area is enlarged, and detailed information of the corresponding function area is displayed.

[0087] Also, the plurality of function areas **120-2** and **122-2** of the first service may be moved in the second direction according to a user manipulation in the second direction. Here, a scroll bar **6** may be displayed.

[0088] A UI screen according to various example embodiments as described above provides a unifying design of each service. Also, a change between service screens and a detailed function that is provided by a service may be intuitively called according to a user manipulation in the first or second direction.

[0089] A structure of a UI screen for managing a home network may be variously changed to be appropriate for a user taste or may be adaptively changed according to a change in an environment of a home network system. This example embodiment will now be described in more detail with reference to FIGS. 5 through 8.

[0090] FIGS. 5 and 6 illustrate a home network system according to various example embodiments.

[0091] Referring to FIG. 5, a home network system **500** is connected to a user terminal apparatus **200** and includes a home server **510** and a plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6** connected to the home server **510**.

[0092] The home server **510** may control and manage the client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6** connected to the home network, and may operate with the client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6**. In detail, the home server **510** may take charge of a service remote management function from an external network, audio, video, game, digital broadcasting server, energy management, home automation, and security server functions in a home, etc. The home server **510** may exist as an independent device or may be mounted on another device.

[0093] The user terminal apparatus **200** may communicate with the home server **510** to transmit a control command or the like for controlling the plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6** or receive various types of state information of the plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6**, danger situation sensing information of the home, or the like.

[0094] Also, the user terminal apparatus **200** may be provided with a new service page or a template of a new function area UI from the home server **510** to change a UI screen configuration according to a user taste.

[0095] According to another example embodiment, the home network system **500** may include a gateway and communicate with an external server apparatus **600**. Referring to FIG. 6, in detail, the home network system **500** may include a gateway **530** and a plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6** connected to the gateway **530**.

[0096] The gateway **530** is an apparatus that provides an interconnection between a network in a home and an external network and operates as a hub that connects and manages the plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6**. In detail, the gateway **530** may control and manage devices by using wired and/or wireless communication technology and access an external

network (e.g., the Internet) to provide various services such as video on demand (VOD), remote control, etc.

[0097] In particular, the gateway **530** may transmit a control command, which is provided from the external server apparatus **600**, to the plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6** or may collect state information from the plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6** and transmit the state information to the server apparatus **600**. In this case, the user terminal apparatus **200** may transmit a control command or the like for controlling the plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6** or may receive various types of state information or the like from the plurality of client devices **520-1**, **520-2**, **520-3**, . . . , and **520-6**.

[0098] The user terminal apparatus **200** may also be provided with a new service page or a UI template of a new function area from the server apparatus **600** to change a UI screen configuration according to a user taste. In this case, the UI template stored in the server apparatus **600** may be updated by a server manager.

[0099] Referring to FIG. **6**, the user terminal apparatus **200** may communicate with a second home network system **700** connected to the server apparatus **600**. For example, the user may check state information of a parent's home through the user terminal apparatus **200** and receive information such as a message or the like indicating, for example, that a gas range is turned on for a long time in the parent's home. A care report service as described above will be described later in more detail with reference to FIGS. **49** and **50**.

[0100] A new device that is added to a home network system will now be described with reference to FIG. **7**.

[0101] Referring to FIG. **7**, if a new device **520-7** is added, the user terminal apparatus **200** that communicates with the home network system **500** may provide device addition information to the user. For example, the home server **510** or the server apparatus **600** may collect meta information about a new device and transmit new device information to the user terminal apparatus **200**. Also, a new device may be registered in the home network system **500** according to user settings. In this case, the user terminal apparatus **200** may generate a new UI screen of a new device or change and display an existing UI screen configuration. In detail, the home server **510** or the server apparatus **600** may analyze meta information of a device to transmit a UI template appropriate for a function provided by the device to the user terminal apparatus **200**. The user terminal apparatus **200** may configure a new UI screen by using the received UI template.

[0102] In detail, referring to FIG. **8**, a new service page **100-8** corresponding to the new device **520-7** may be generated, and a plurality of function areas A-2, C-1, and C-2 of a plurality of functions that may be performed by the new device **520-7** may be included in existing service pages **100-2** and **100-3** or a new service page **100-8**.

[0103] For example, as shown in FIG. **7**, if the new device **520-7** is a camera, the home network system **500** may newly provide a monitoring service that displays an image captured by the camera **520-7**. Therefore, the user terminal apparatus **200** may add the new service page **100-8** associated with the monitoring service onto a UI screen. If a plurality of cameras **520-7** exist and are installed all over environment of a home, the user terminal apparatus **200** may provide images of areas where the cameras **520-7** are respectively installed. In this case, a plurality of function areas for controlling operation of cameras respectively installed in areas may be newly added. For example, a main room monitoring function area C-1 and a baby room monitoring function area C-2 may be included in the new service page **100-8**. In this case, if a service provided from a first service page **100-2** is a control service, a function area A-2 for controlling on/off switching of a monitoring camera may be added onto the first service page **100-2**.

[0104] If an existing device is deregistered on the home network system **500**, a service page or an associated function area associated with the existing device may be automatically deleted or a message for inquiring about whether to delete the service page or the associated function area may be displayed through the display unit **220**. In other words, a UI screen configuration displayed on

the user terminal apparatus **200** may be adaptively changed according to changes in an environment of the home network system **500**.

[0105] The user terminal apparatus **200** that provides a UI screen for managing a home network as described above will now be described in detail.

[0106] FIG. **9** is a block diagram of a structure of the user terminal apparatus **200** according to an example embodiment. Referring to FIG. **9**, the user terminal apparatus **200** includes a communication unit **210**, the display unit **220**, a sensing unit **230**, and a control unit **240**.

[0107] The communication unit **210** may, for example, be circuitry or some arrangement of hardware, software and firmware configured to enable wired and/or wireless communication with various types of external devices or external servers according to various types of communication methods. In particular, the communication unit **210** may be connected to the home network system **500** to receive information about client devices included in a home network or transmit a control command to the client devices.

[0108] If a new device is added to the home network, the communication unit **210** may receive information about the new device and receive a new UI template of the new device.

[0109] The display unit **220** may, for example, be one or more displays (e.g., CRT, LCD, OLED and the like) configured to display various types of UI screens as described above. A UI screen refers to a display screen that provides various types of information or menus to a user and performs a user interaction according to an action of the user for the various types of information or menus. As shown in FIG. **1**, if a UI screen is formed of various pages, and sizes of the pages are larger than a display size, the display unit **220** may display at least a part of the UI screen for managing a home network.

[0110] The sensing unit **230** may, for example, be one or more sensors configured to sense various manipulations such as a touch on the user terminal apparatus **200**, a rotation, a slope, and a pressure supplied to the user terminal apparatus **200**, an access to the user terminal apparatus **200**, etc. In particular, the sensing unit **230** may include a touch sensor (not shown) and a rotation sensor (not shown).

[0111] In detail, various touches of the user on the touch sensor may be associated with executions of various functions. For example, the various touches of the user may be classified into an operation (or tap) of pressing (or touching) and withdrawing from a screen, an operation (or a double tap) of consecutively pressing the screen two times and then withdrawing from the screen, an operation (or a long tap) of (long) pressing the screen for a preset time or more or withdrawing from the screen, an operation (or a drag) of pressing a point of the screen for a preset time or more and dragging the point to another point, an operation (or a swipe) of swiping the screen in a preset direction at a preset speed, an operation (pinch in) of pressing the screen with two fingers and closing the two fingers together, an operation (pinch out) of pressing the screen with two fingers and spreading the two fingers apart, etc.

[0112] The rotation sensor may include, for example, a geomagnetic sensor, an acceleration sensor, and/or the like for sensing aspects of a rotation state, a movement direction, etc. of the user terminal apparatus **200**.

[0113] The control unit **240** may, for example, include a processor (e.g., executing appropriate software), an application specific integrated circuit (ASIC), floating point gate array, and/dedicated circuitry configured to control an overall operation of the user terminal apparatus **200**. The control unit **240** may operate with elements such as the communication unit **210**, the sensing unit **230**, the display unit **220**, etc. to perform control operations described above according to various example embodiments.

[0114] If an application for managing the home network is executed, the control unit **240** controls the display unit **220** to display a UI screen as shown in FIG. **10**. If a user manipulation is sensed by the sensing unit **230** in this state, the control unit **240** may change the UI screen or control the home network according to the user manipulation. In detail, the control unit **240** may control the

display unit **240** to sequentially display the main page **100-1** and a plurality of service pages **100-2**, **100-3**, **100-4**, . . . , and **100-7** page by page according to the first user manipulation **10** performed sequentially in the first direction. The control unit **240** may also control the display unit **220** to display a plurality of function areas according to the second user manipulation **20** performed in the second direction.

[0115] If a home network management is started, the control unit **140** may first control display unit **220** to display the main page **100-1**. The main page **100-1** may provide various types of information. For example, the main page **100-1** may include a light button **114b-1**, a temperature button **114c-1**, and a standby power button **114d-1**. If an arbitrary button is selected from these buttons, a detail control window may be displayed in a pop-up form.

[0116] For example, if the standby power button **114d-1** is selected, a message window “Do you want to cut off standby power in your home (excluding a monitoring device and a refrigerator)?” may be displayed. Also, if a selection button included in the message window is selected, an operation of cutting off power in a home may be performed.

[0117] As another example, referring to FIG. **10**, the main page **100-1** may include a plurality of user icons **114e-1**, **114f-1**, and **114g-1** respectively corresponding to family members in a family member current state area. If one of the plurality of user icons **114e-1**, **114f-1**, and **114g-1** is selected, a message pop-up window **114h-1** for sending a message to a corresponding family member may be output. Here, if one of a phone button, a message button, and a chatting button is selected, the control unit **240** may place a phone call to a corresponding family member or output a window or a chatting window for sending a message based on a phone directory stored in a storage unit (not shown).

[0118] According to another example embodiment, if a vertical rotation of the user terminal apparatus **200** is sensed by the sensing unit **230** when the main page **100-1** is displayed, the control unit **240** displays the main page **100-1** according to a layout different from a layout of the displayed main page **100-1**.

[0119] For example, referring to FIG. **10**, when the display unit **220** is oriented in a portrait direction, the control unit **240** displays the main page **100-1** in a layout where the information display area **110-1** of the home network and the first favorite function area **120-1** are connected to each other in a second direction based on the information display area **110-1** of the home network. When the display unit **220** is oriented in a landscape direction, the control unit **240** may display the main page **100-1** in a layout so as to include a plurality of state information areas **30**, **40**, and **50** indicating state information about respective rooms included in an environment managed by the home network. A rotation operation of the user terminal apparatus **200** as described above may be sensed by the sensing unit **230**.

[0120] If the main page **100-1** is displayed in a second layout as shown in FIG. **10**, for example, the user may select a light button **31** of a first room to switch on/off lights in that room. If a light for a respective room is switched on or off, background colors of the corresponding state information areas **30**, **40**, and **50** may be changed. The user may also select a temperature button **32** of the first room to control temperature of that room. For example, if the temperature button **32** of the first room is selected, a screen may be changed into one for setting a temperature level. Here, an animation effect may be applied to turn the first state information area **30** corresponding to the first room from a front side to a back side.

[0121] Also, at least one favorite function area of the main page **100-1** corresponds to at least one of function areas registered with bookmarks, among function areas included in each service page. The bookmark registration may be performed through a selection of the bookmark menu icon **2** provided in each function area as described above with reference to FIG. **4**.

[0122] For example, if the second user manipulation **20** is input when the first service summary area **110-2** of the first service page **100-2** is displayed as shown in FIG. **11A**, the control unit **240** may move and display at least one function area connected to the first service summary area **110-2**

onto the first service summary area **110-2** as shown in FIG. **11B**. Here, the second user manipulation **20** may be an operation of dragging a cue area **118-2** of a function area of a first service for indicating that at least one of a plurality of function areas **120-2** and **122-2** exists, upwards.

[0123] If the cue area **118-2** of the function area of the first service is dragged upwards as shown in FIG. **11D**, the plurality of function areas **120-2** and **122-2** of the first service may be sequentially moved onto the first service summary area **110-2** along with the dragging operation. Here, if the enlarge menu icon **3** provided in each of the plurality of function areas **120-2** and **122-2** of the first service is selected, the control unit **240** may enlarge the first function area **120-2** of the corresponding first service into a first detailed function area **126-2** of the first service and display the first detailed function area **126-2** on a front surface of the display unit **220** as shown in FIG. **11D**.

[0124] According to another example embodiment, if a pinch gesture **30** is input in a state in which a plurality of function areas **120-2**, **122-2**, and **124-2** of a first service are displayed as shown in FIG. **12A**, the control unit **240** may reduce the plurality of function areas **120-2**, **122-2**, and **122-3** of the first service to a plurality of corresponding first function area objects **120'-2**, **122'-2**, **124'-2**, **126'-2**, **128'-2**, and **129'-2** and display the plurality of the corresponding first function area objects **120'-2**, **122'-2**, **124'-2**, **126'-2**, **128'-2**, and **129'-2** as shown in FIG. **12B**. If a method as described above is used, the user may check a plurality of function areas in one view.

[0125] Here, if one of the reduced first function area objects is selected as shown in FIG. **12B**, the control unit **240** may change the selected first function area object **120'-2** back into the first function area **120-2** of the first service and display the first function area **120-2** as shown in FIG. **12C**.

[0126] Also, if a new device is added to the home network, the control unit **240** may add at least one of a new service page and a new function area. As described above with reference to FIG. **8**, the control unit **240** may generate a new service page or a new function area by using a new UI template.

[0127] The user terminal apparatus **200** may be realized in various manners and types of devices to perform a method of managing a home network according to various example embodiments as described above.

[0128] FIG. **13** is a block diagram of a detailed structure of the user terminal apparatus **200** according to an example embodiment. Referring to FIG. **13**, the user terminal apparatus **200** includes a communication unit **210**, a display unit **220**, a touch sensor **231**, a rotation sensor **233**, a control unit **240**, and a storage unit **250**.

[0129] The communication unit **210** is an element for communicating with various types of external devices or external servers according to various types of communication methods. The communication unit **220** may include various types of communication chips (or integrated circuits) such as a WiFi chip **211**, a Bluetooth chip **212**, a wireless communication chip **213**, an NFC chip **214**, and the like. The WiFi chip **211**, the Bluetooth chip **212**, and the NFC chip **214** respectively perform communications according to a WiFi method, a Bluetooth method, and an NFC method. The NFC chip **214** refers to a chip that operates in a Near Field Communication (NFC) method using a band of 13.56 MHz among various types of RF-ID frequency bands such as 135 kHz, 13.56 MHz, 433 MHz, 860~960 MHz, 2.45 GHz, etc. If the WiFi chip **211** or the Bluetooth chip **212** is used, the communication unit **210** may transmit and receive various types of connection information such as an SSID, a session key, etc., and connect communications by using the various types of connection information, and transmit and receive various types of information. The wireless communication chip **213** refers to a chip that performs communications according to various types of communication standards such as IEEE, Zigbee, 3.sup.rd Generation (3G), 3.sup.rd Generation Partnership Project (3GPP), Long Term Evolution (LTE), and the like.

[0130] In particular, the communication unit **210** is connected to the home network system **500** to

receive information about client devices in a home network and/or transmit a control command to the client devices. Also, if a new device is added to the home network, the communication unit **210** may receive meta information about the new device or a new UI template appropriate for the new device.

[0131] The user terminal apparatus **200** may communicate with various types of external devices, such the home server **510**, the server apparatus **600**, etc., through the communication unit **210**.

[0132] The display unit **220** is one or more displays for displaying a screen including at least one object. Here, the screen refers to an image frame that is provided through the display unit **210** in the user terminal apparatus **200**. In detail, a home screen, an icon screen, a list screen, an application execution screen, a web browser screen, a content play screen, etc. may be included in the screen. Also, object icons refer to various shapes that are displayed in the screen like a text, a photo, a widget, etc. In particular, the display unit **220** may display various types of UI screens for managing a home network as described above.

[0133] The touch sensor **231** may sense a user manipulation that is performed on the display unit **220**. If the user touches the screen with a finger or a pen to perform drawing, the touch sensor **231** may sense a place where the drawing is performed and a trajectory of the drawing. The touch sensor **231** may be realized using various types of touch sensors such as a capacitive type, a decompressive type, a piezoelectric type, and the like. The capacitive type is a method of sensing micro-electricity excited into a body of the user to calculate touch coordinates by using a dielectric coated on a surface of the display unit **220** when a part of the body of the user touches the surface of the display unit **220**. The decompressive type is a method of sensing a current flowing due to a contact between upper and lower electrode plates of the display unit **220** at a point of the screen touched by the user to calculate touch coordinates.

[0134] The touch sensor **231** may sense a user manipulation that is performed by using an input unit such as a pen, in addition to a finger of the user. If the input unit is a stylus pen including a coil, the touch sensor **231** may include a magnetic field sensor that may sense a magnetic field changed by the coil of the stylus pen. Therefore, the touch sensor **231** may sense a touch manipulation and a proximity manipulation, i.e., hovering.

[0135] If a user manipulation is sensed, the touch sensor **231** provides the control unit **240** with the sensing result. For example, if the user touches a point of the screen with the finger or the pen, the touch sensor **231** provides the control unit **240** with x, y coordinate values of the touch point. If the user moves the touch point when touching the screen, the touch sensor **231** provides the control unit **240** with touch coordinate values, which are changing, in real time. As described above, the touch sensor **231** may sense a close approach rather than a direct touch.

[0136] The rotation sensor **230** senses aspects of a rotation state, a movement direction, orientation, and the like of the user terminal apparatus **200**. A geomagnetic sensor, an acceleration sensor, a gyro sensor, and/or the like may be used as a sensor for sensing the rotation state, the movement direction and/or the orientation. The acceleration sensor outputs a sensing value corresponding to acceleration changing according to an orientation of an apparatus or device to which the acceleration sensor is attached. The gyro sensor is a sensor that, if a rotation motion occurs, measures a Coriolis force acting in a speed direction of the rotation motion to sense an angular speed. The geomagnetic sensor is a sensor for sensing an azimuth angle. If the rotation sensor **230** senses the rotation state of the user terminal apparatus **200**, the control unit **240** may differently display a layout of the main page **100-1** according to the rotation state as described above with reference to FIG. **10**.

[0137] The storage unit **250** may store an O/S **255** or programs such as various types of applications and various types of data such as user setting data, data generated in a process of executing an application, a multimedia content, etc. In particular, the storage unit **250** may store an application **251** for managing a home network. In FIG. **13**, the application **251** is referred to as a smart home application. If the smart home application is selected by the user or automatically

executed according to a default setting value, the control unit **240** generates a UI screen as described in the above-described various example embodiments and displays the UI screen on the display unit **220**. The storage unit **240** may also store a plurality of templates **253-1**, **253-2**, . . . , and **253-n**. A template refers to data that defines a layout, a text, a menu, an icon, or the like for expressing a service page or a function area as described above.

[0138] The control unit **240** may generate various types of UI screens as described above by using the plurality of templates **253-1**, **253-2**, . . . , and **253-n**. For example, if a new device is connected to the home network system **500**, the control unit **240** may determine a new service that may be provided by the new device. If the new service is determined, the control unit **240** may generate a new service page UI corresponding to the new device by using the template **1** and generate a new function UI by using the template **2**. This is described in detail with reference to FIGS. **7** and **8**, and thus a repeated description is omitted.

[0139] The storage unit **250** may also store a template that is updated in the home server **510** or the server apparatus **600**. In detail, the control unit **240** may store a new template in the storage unit **250** or delete an existing template from the storage unit **250** by using received information so as to efficiently manage a storage space of the storage unit **250**.

[0140] The control unit **240** displays various types of UI screens for managing the home network on the display unit **220** by using the programs and the data stored in the storage unit **250**.

[0141] The control unit **240** includes a RAM **241**, a ROM **243**, a CPU **245**, a Graphic Processing Unit (GPU) **247**, and a bus **249**. The RAM **241**, the ROM **243**, the CPU **245**, and the Graphic Processing Unit (GPU) **247**, and the like may be connected to one another through the bus **249**.

[0142] The CPU **245** accesses the storage unit **250** to perform booting up by using the O/S **255** stored in the storage unit **250**. Also, various operations are performed by using the smart home application **251**, the plurality of templates **253-1**, **253-2**, . . . , and **253-n**, and the like stored in the storage unit **250**.

[0143] The ROM **243** stores a command set and the like for booting up a system. If a turn-on command is input to supply power, the CPU **245** copies the O/S **255** stored in the storage unit **250** into the RAM **241** and executes the O/S **255** to boot the system according to a command stored in the ROM **243**. If the booting up is completed, the CPU **245** copies various types of programs stored in the storage unit **250** into the RAM **241** and executes the programs copied into the RAM **241** to perform various types of operations.

[0144] If booting up of the user terminal apparatus **200** is completed, the GPU **247** displays a UI screen. In detail, the GPU **247** may generate a screen including various types of objects such as an icon, an image, a text, and the like by using an operator (not shown) and a renderer (not shown). The operator calculates attribute values, such as a coordinate values, shapes, sizes, colors, and/or the like, at which the objects are to be respectively displayed according to a layout of the screen. The renderer generates a screen having various layouts including objects based on the attribute values calculated by the operator. The screen generated by the renderer is provided to the display unit **220** to be displayed.

[0145] Besides this, although not shown in FIG. **13**, according to example embodiments, the user terminal apparatus **200** may further include various types of external input ports for connections to various types of external terminals such as a USB port into which a USB connector may be connected, a headset, a mouse, an LAN, etc., a DMB chip for receiving and processing a Digital Multimedia Broadcasting (DMB) signal, various types of sensors, etc.

[0146] As described above, the user terminal apparatus **200** may be realized in various shapes and structures. The control unit **240** of the user terminal apparatus **200** may display a UI screen for managing various types of home networks according to various example embodiments.

[0147] A UI screen for managing a home network according to various example embodiments will now be described in detail with reference to the drawings.



[0148] FIGS. **14A-14C** illustrate the main page **100-1** according to an example embodiment.

[0149] The main page **100-1** is an initial page that is provided from a home network management service and may include environment information, such as an overall home network situation, time, weather, etc., external traffic situations, etc.

[0150] For example, referring to FIGS. **14A** through **14C**, the main page **100-1** may include a briefing area **112-1** that provides various types of notifications of a home network management, a family user current state area **118-1** that displays whether each family member is at home or out, an area **114a-1** that provides notifications of abnormal situations occurring in a home such as a device abnormality occurrence, a security problem occurrence, an excessive energy usage, and the like, an indicator **117-1** for immediately moving onto a next service page, and the like.

[0151] If an abnormality occurs in a robot cleaner (R/C) that is a device as shown in FIG. **14B** as an example of a display state of the main page **100-1**, the control unit **240** may display an error message **1401** that includes a robot cleaner icon and an abnormality situation in the area **114a-1** that provides a notification of the abnormality situation. As another example, if a security problem and a device abnormality problem occur together, the control unit **240** may display an image **1401** captured from an intruder in the area **114a-1** providing a notification of an abnormality situation and alternately display a message **1403** such as “Sense Motion During Absence. Storing of Image is Completed” and “Abnormality occurs when using R/C” every n seconds.

[0152] FIGS. **15A** and **15B** illustrate a briefing area of a main page according to an example embodiment.

[0153] Referring to FIG. **15A**, if a briefing area **112-1** of the main page **100-1** is selected, a briefing list **112a-1** is displayed under the briefing area **112-1**. If a briefing close bar **112b-1** is dragged upwards, the briefing list **112a-1** is closed. Even if the briefing list **112a-1** is long, the briefing list **112a-1** may be displayed on a front surface of the display unit **220** as shown in FIG. **15B**. In this case, the briefing list **112a-1** may be scrolled up and down.

[0154] As shown in FIGS. **15A** and **15B**, the briefing list provides a menu of various types of notification messages and user selections such as a device control, a channel notification, an update notification, a job performance notification, etc. For example, as shown in FIG. **15B**, if an air conditioner operating selection **1501** is input in the briefing list **112a-1**, an air conditioner may be controlled to be turned on. If any selection of the briefing list **112a-1** is not input for a preset time, the briefing list **112a-1** may be automatically closed.

[0155] FIGS. **16** and **17** illustrate an output of a history screen on a main page according to an example embodiment.

[0156] Referring to FIG. **16**, if a history button **134-1** of the main page **100-1** is selected, the control unit **240** displays a history screen **1610** on which a list of use logs of all devices of a home network is arranged according to date. The history screen **1610** may be divided into various areas such as a display area **1611** displaying a device having a history of being used on the same day (i.e., today) and a display area **1612** displaying a device having a history of being used on another day (e.g., yesterday).

[0157] A user may select an object that the user wants to control on the history screen **1610**. As shown on **1610** of FIG. **16**, if a robot cleaner that has a history of being used today is selected (**1613**), the control unit **240** additionally displays (**1620**) various menu options **1621** within the screen **1610**. Here, if an execution menu option **1622** is selected, the robot cleaner may be controlled to be turned on. In this case, the robot cleaner may be executed in an auto mode that is used today (**1630**).

[0158] If the user selects a shortcut menu option **1623** on the history screen **1610**, a control service page or a detailed function area provided on all service pages may be displayed for the robot cleaner (**1640**). The detailed function area may provide various menus for controlling a corresponding device. The detailed function area will be described in more detail later.

[0159] If the user selects a delete menu option **1633** on the history screen **1610**, a corresponding

history list is deleted (**1650**). After deleting, a message for indicating that the history list is deleted may be displayed at a bottom of the history screen (**1660**).

[0160] A case where the history button **134-1** is selected on the main page **100-1** is described with reference to FIG. **17**.

[0161] Referring to FIG. **17**, if an Add to Mode button **1711** is selected on a history screen **1710**, the control unit **240** displays a screen **1720** for selecting a device that is to be included in a mode that is to be newly generated. The user may check a box provided beside a device icon of the screen **1720** to select a device that is to be included in a mode. If a preset “Going Away” mode is selected (**1721**), devices that are included in the mode so as to be controlled are all displayed in a checked state. Here, the user may cancel the check (**1722**). If a selection of a device to be included in a mode to be newly added is selected, the user may select a next button **1723**. Thereafter, a screen **1730** for inputting a name of the new mode may be displayed, and the user may input a desired mode name into a mode name input box **1731**. Also, the user may select an edit menu provided for each device to change a device state setting when executing a mode. For example, as shown with **1740** of FIG. **17**, if the edit menu **1741** for a TV01 is selected (**1741**), the control unit **240** may display an edit window **1751** in a middle of the display unit **220** (**1750**). If the user changes and stores settings for the TV01 through the edit window **1751** (**1752**), a message indicating that a mode is completely added may be displayed at bottom of a screen (**1760**).

[0162] “User mode 01” set as described above may be checked on a mode service page that will be described later. In detail, in an environment where a newly generated “User mode 01” is executed, TV01 located in a living room is turned on to CH15, an automatic cleaning function of a robot cleaner (R/C) located in the living room is executed, and TV02 located in the living room is turned on to CH15. In other words, controls of all these devices may be simultaneously performed with an execution of “User mode 01”. A mode service as described above will be described in more detail later with reference to FIGS. **26** through **34**.

[0163] The user may be provided with overall information about a home network through the main page **100-1** described above and may execute functions provided on each service page without entering each service page. The first service page **100-2** among a plurality of pages connected to the main page **100-1** in a first direction will now be described.

<First Service Page **100-2**-Monitoring>

[0164] Among a plurality of service pages, the first service page **100-2**, which provides a monitoring service by using a photographing apparatus of a plurality of devices included in a home network, will now be described. Hereinafter, a first service will be referred to as a monitoring service.

[0165] FIG. **18** illustrates a monitoring service page **100-2** according to an example embodiment.

[0166] Referring to FIG. **18**, messages having different contents may be provided at an upper end of a monitoring service summary area **110-2** of the monitoring service page **100-2** according to current monitoring states. For example, information about the number of monitoring cameras that are currently operating, positions of the monitoring cameras, a name of a room where an intruder is sensed, or the like may be displayed in message form at the upper end of the monitoring service summary area **110-2**.

[0167] According to an example embodiment, the monitoring service page **100-2** may provide an intruder sensing service. Hereinafter, this function will be referred to as a safety guard service. If a moving object is sensed or an outer forceful intrusion is sensed in the absence of a user, the safety guard service may provide an automatic recording service through a camera installed at a sensed position. This will be described in more detail later with reference to FIG. **19**.

[0168] Also, a lower end of the monitoring service summary area **110-2** includes an area that displays information about a frequently used camera(s). This will be described in more detail later with reference to FIG. **20**.

[0169] The monitoring service page **100-2** also includes a first function area **120-2** of a monitoring

service connected to the lower end of the monitoring service summary area **110-2**. When the monitoring service summary area **110-2** is displayed on the front surface of the display unit **220**, only a cue area **118-2** of a function area of the monitoring service, which indicates that the function area exists below, is displayed on the display unit **220** as shown in FIG. **19**. The first function area **120-2** of the monitoring service may be displayed above the monitoring service summary area **110-2** according to a user manipulation for dragging the cue area **118-2** of the function area of the monitoring onto the monitoring service summary area **110-2**. In this case, if other function areas exist under the first function area **120-2** of the monitoring service, the other function areas may be moved upwards together with the first function area **120-2** of the monitoring service.

[0170] A function area of the monitoring service may provide data captured by a device included in the home network. For example, a play menu of data, which is captured and stored by a CCTV installed in a room, may be provided in other function areas of respective rooms, and real-time captured data may be provided. In this case, menus for image recording and screen capturing may be provided in the function area.

[0171] Also, the function area may provide a menu for controlling a capturing direction of the CCTV and a menu for controlling a movement of a device that is a moveable device (e.g., a robot cleaner with a camera).

[0172] The safety guard function will now be described as an example of a service provided in a service summary area of a monitoring service in more detail with reference to FIG. **19**.

[0173] Referring to FIG. **19**, if the user selects a button **134-2** for executing the safety guard function when the safety guard function is currently canceled, a message displayed at an upper end of a monitoring service summary area may be changed. For example, as shown with **1920** of FIG. **19**, a message for indicating that the safety guard service is operating may be displayed at the top. If a monitoring camera senses a motion in the absence of the user, the corresponding camera may perform automatic recording or automatic capturing, and a captured picture or a recorded video may be stored to be displayed at the upper end of the monitoring service page **100-2** (**1940**). If the user selects a recorded video or a capture screen **1941** displayed at the upper end of the monitoring service page **100-2**, the control unit **240** changes a screen into a player screen according to a file format thereof (**1950**).

[0174] Referring to **1910** of FIG. **19**, the monitoring service page **100-2** may include a frequently used area **140-2** that displays a frequently used monitoring camera(s).

[0175] Referring to FIG. **20**, if a living room screen **141-2** is selected in the frequently used area **140-2**, the living room screen **141-2** may be changed into a detailed monitoring screen **150-2** of a living room and then displayed.

[0176] Alternatively, the detailed monitoring screen **150-2** may be immediately changed and displayed in a function area. For example, referring to FIG. **21**, if an enlarge menu icon **3** of the first function area **120-2** of the monitoring service is selected among a plurality of function areas of the monitoring service page **100-2**, the detailed monitoring screen **150-2** may be displayed on the front surface of the display unit **220**.

[0177] As another example, referring to FIG. **21**, if a bookmark menu icon **2** is selected in the first function area **120-2** of the monitoring service, the first function area **120-2** of the monitoring service may be registered in a favorite function area of the main page **100-1**. In a method as described above, a function area frequently used by the user may be included in the main page **100-1**, and thus the user may easily look for the function area frequently used by the user on the main page **100-1** without accessing an individual service page.

[0178] As another example, if a recording button **120a-2** is selected in the first function area **120-2** of the monitoring service, a recording function may be performed as shown in FIG. **21**.

[0179] FIG. **22** illustrates another function area of the monitoring service page **100-2**. Here, a second function area **120-4** of the monitoring service may provide a recorded file. If an enlarge menu icon **3** of the second function area **120-4** of the monitoring service is selected, the second

function area is enlarged and displayed as a detailed function area displaying a list of recorded files arranged in time order. If one of the recorded files is selected, a player screen may be displayed in a file form.

[0180] Returning to the display of the detailed monitoring screen **150-2**, referring to FIG. 23, if a rotation of the user terminal apparatus **200** is sensed, the detailed monitoring screen **150-2** may occupy the front surface of the display unit **220** to be displayed in a horizontal direction. If one of a plurality of direction keys **150a-2**, **150b-2**, and **150c-2** is selected on the detailed monitoring screen **150-2**, a camera may be moved in a selected direction.

[0181] FIG. 24 illustrates a detailed function of the detailed monitoring screen **150-2**. As shown in FIG. 24, if a power button A is selected, a command for turning off monitoring is transmitted to a client device, in this case, to a robot cleaner. If a capture button B is selected, a screen that is currently monitored is captured, and the captured screen is added into a recorded file list area **152-2** at a bottom. If a recording button C is selected, recording starts. If recording is completed, a recorded file is added into the recorded file list area **152-2**. A scroll bar **152b-2** provided in the recorded file list area **152-2** may be moved to check many more recorded files. If a more button **152a-2** is selected, a detailed recorded file list screen is output.

[0182] The detailed recorded file list screen **154-2** will be described with reference to FIG. 25. If a fold button **154a-2** is selected, an area “IP Cam in Living Room” is closed, and recorded files of an area “Porch IP Cam 1 in Room 1” may come up to be displayed. If a menu button **154b-2** is selected, refresh, sort by, and delete menu icons may be displayed in a pop-up window. The user may select the sort by menu icon to sort recorded files according to dates or device names. If the delete menu icon is selected, a check box may be generated in an area of a recorded file icon **154c-2**, and the user may select the check box corresponding to a recorded file to be deleted and then select a complete button (not shown) to delete a file.

[0183] Through the user terminal apparatus **200** providing the monitoring service page as described above, the user may check a situation of a home even from the outside and check an immediate notification provided to the user terminal apparatus **200** to effectively cope with an internal intruder.

<Second Service Page **100-3**-Mode>

[0184] Hereinafter, among a plurality of service pages, a second service page for differently controlling a plurality of devices included in a home network according to home network modes will be described. Hereinafter, a second service will be referred to as a mode service.

[0185] In the mode service, the user may directly select a plurality of modes and select a mode set by the user to control the plurality of devices of the home network. For example, if a particular mode is executed, a plurality of devices associated with the particular mode may be simultaneously turned on. If set values are differently set according to devices when setting a mode, the devices may operate according to the set values when executing the mode. An operation depending on an execution of a mode will be described in more detail according to detailed example embodiments.

[0186] According to an example embodiment, a smart home application stored in the storage unit **250** may provide a plurality of modes by default, and examples of default modes may include “Going Away”, “Coming Home”, “Sleep”, “Vacation”, etc. Besides the modes provided by default, the user may add one or more new modes.

[0187] FIG. 26 illustrates a mode service page **100-3** according to an example embodiment.

[0188] Referring to FIG. 26, a mode service summary area **110-3** of the mode service page **100-3** may include a scheduled mode area **2601** and a frequently used mode area **2602**. If a schedule check button **110a-3** is selected in the scheduled mode area **2601**, the control unit **240** may display a schedule check pop-up on the display unit **220**. If a mode execute button **110b-3** is selected, the control unit **240** may perform an execution of a corresponding mode. This will now be described in more detail with reference to FIG. 27.

[0189] The mode service page **100-3** includes a first function area **120-3** of a mode service

connected to a lower end of a mode service summary area **110-3**. When the mode service summary area **110-3** is displayed on the front surface of the display unit **220**, only a cue area **118-3** of a function area of the mode service for indicating that a function area exists below is displayed on the display unit **220** as shown in FIG. **26**. The first function area **120-3** of the mode service is displayed above the mode service summary area **110-3** according to a user manipulation for dragging the cue area **118-3** of the function area of the mode service into the mode service summary area **110-3**. In this case, if other function areas exist under the first function area **120-3** of the mode service, the other function areas are also moved upward together with the first function area **120-3** of the mode service.

[0190] FIG. **27** illustrates a UI for executing a mode provided by the user terminal apparatus **200** according to an example embodiment.

[0191] Referring to FIG. **27**, for example, if the user selects a “Going Away” mode execute button **110b-3** in the mode service summary area **110-3** of the mode service page **100-3**, a message for indicating that “Going Away” mode is executed may be displayed at a lower end of the mode service summary area **110-3** (**2720**). In this case, a selected mode is not immediately executed, and a mode execute cancel button **110c-3** is displayed for a preset time. If the mode execute cancel button **110c-3** is not selected from a preset time N sec, an execution of the selected mode may be completed, and the corresponding mode may be displayed in color, i.e., in a different display state from a display state of another mode. Therefore, the user may check that the mode is being executed. Also, the mode execute button is displayed in an inactivated state (**2701**).

[0192] In detail, if the mode is executed, control states of devices included in the corresponding mode may be changed into set states. For example, when executing the “Going Away” mode, the user may set the “Going Away” mode to turn off all devices except a refrigerator and a boiler in a home.

[0193] According to an example embodiment, if a device does not operate according to a set mode when executing a mode, other devices except the device may continuously operate according to the corresponding mode without stopping a whole part of the mode.

[0194] FIGS. **28A** and **28B** illustrate a UI that is provided by the user terminal apparatus **200** to add a new mode according to an example embodiment.

[0195] Referring to FIGS. **28A** and **28B**, if the user selects a menu button **132-3** on the mode service page **100-2**, a menu screen **2811** may be displayed under the menu button **132-3**. If the user selects a mode add menu **2812**, the control unit **240** may display a window **2821** for receiving a name of a new mode on the display unit **220**. If the user inputs a name of a new mode and selects a next button **2822**, the control unit **240** changes the menu screen **2811** into a detailed screen **2830** for adding a new mode and displays the detailed screen **2830**. The detailed screen **2830** is divided into two areas, a lower area **2832** is an area that displays a device usable in a new mode, and an upper area **2831** is an area that displays a selected device. In this case, an icon corresponding to a device selected in the lower area **2832** is displayed in the upper area **2831** and simultaneously is not displayed in the lower area **2832** anymore. If an icon **2847** of a device is selected in the upper area **2831**, the control unit **240** displays a window **2841** for inputting a set value of the device. The user may input a detailed set value through the window **2841** and store the detailed set value (**2842**). If a finish button **2843** is selected, an addition of a new mode is completed (**2860**).

[0196] Hereinafter, a function area of a mode service page will be described in more detail. The function area of the mode service page may include a mode execute menu for executing one mode, and the control unit **240** may simultaneously control devices included in a group corresponding to the mode execute menu.

[0197] FIG. **29** illustrates a function area of a service mode page according to an example embodiment. In detail, FIG. **29** illustrates one of a plurality of function areas respectively corresponding to modes provided on a mode service page.

[0198] Referring to FIG. **29**, if a bookmark menu icon **2** is selected in the first function area **120-3**

of the mode service, the first function area **120-3** of the mode service is registered in a favorite function area of the main page **100-1**. In other words, the first function area **120-3** of the mode service of the mode service page **100-3** may be looked for on the main page **100-1**.

[0199] Also, referring to FIG. **29**, if an enlarge menu icon **3** is selected in the first function area **120-3** of the mode service, the first function area **120-3** of the mode service is enlarged as a first detailed function area **126-3** of the mode service and then displayed on the front surface of the display unit **220**.

[0200] Also, whether to execute a set value of a set device may be set in the first function area **120-3** of the mode service. For example, referring to FIG. **29**, when the “Going Away” mode is executed, a TV is set to be turned off. If the user does not want to turn off the TV, the user may cancel the turning off of the TV.

[0201] Also, the user may execute the “Going Away” mode in the first function area **120-3** of the mode service. Referring to FIG. **30**, if a “Mode Execute” button is selected, the “Mode Execute” button is changed into a “Mode Cancel” button and then displayed for a preset time. If a preset time elapses, the “Going Away” mode is executed. Also, referring to FIG. **30**, if a reservation button is selected, a schedule reservation screen pops up and then provided in a turn-off state. Here, if turning-off is canceled, a schedule reservation set value may be input.

[0202] FIG. **31** illustrates a UI that is provided by the user terminal apparatus **200** to delete a mode according to an example embodiment. Referring to FIG. **31**, if the user selects a menu button **132-3** of the first detailed function area **126-3** of the mode service, a menu option **3121** is displayed under the menu button **132-3** (**3120**). If the user selects a Mode Delete button **3122** among these, the control unit **240** displays a window **3131** for inputting a final approval of a mode deletion. Here, if the delete approve button **3132** is selected, deleting is completed, and the control unit **240** displays a mode service summary area **110-3**.

[0203] Returning to the screen **3120** of FIG. **31**, if a mode rename button **3123** is selected, a window for inputting a new name of a corresponding mode may be displayed. Also, if a reset button **3124** is selected, the corresponding mode may be reset.

[0204] FIG. **32** illustrates a UI that is provided by the user terminal apparatus **200** to set a mode reservation according to an example embodiment. Referring to FIG. **32**, if a reservation set button **3211** is selected in the first detailed function area **126-3** of the mode service, the control unit **240** may display a schedule set screen **3221**. Thereafter, the user may change mode schedule setting through the schedule set screen **3221**. For example, the user may set a date, a time, a mode execution repeated cycle, etc. at which a mode will be automatically executed. If a set store button **3231** is selected after the user completes setting, a message for indicating that a schedule is stored may be displayed at a lower end of the first detailed function area **126-3** of the mode service (**3240**). For example, if a mode reservation is turned off as shown with **3240** of FIG. **32**, the control unit **240** may display “No Schedule” **3241** at an upper end of the first detailed function area **126-3** of the mode service.

[0205] FIG. **33** illustrates a UI for settings of devices included in a mode. Referring to FIG. **33**, if the user wants to change a setting of one of devices included in a mode, the user may select an icon **3311** of the device. In this case, the UI may be an operation of long pressing the icon **3311** of the device. If such a user input is sensed, the control unit **240** displays an option menu **3321** of a selected device. The option menu **3321** may include a device edit menu option **3322** and a device delete menu option **3323**. Here, if the device edit menu option **3322** is selected, an edit screen **3331** may be displayed. The user may change a set value of the corresponding device on the edit screen **3331**. For example, if a schedule on/off button **3332** is selected to turn off a schedule, an edit screen **3340** may be darkened (e.g., grayed) and displayed. Thereafter, if a button **3341** is selected, a screen **3350** to which a set value set by the user is applied is displayed. Referring to **3350** of FIG. **33**, a message **3351** for indicating that the schedule is turned off may be displayed under an icon of a corresponding device.

[0206] Referring to FIG. 33 again, if a device delete menu option 3323 is selected, a device may be deleted from a corresponding mode.

[0207] According to another example embodiment, referring to FIG. 34, if an add button 3411 is selected in the first detailed function area 126-3 of the mode service, a screen 3420, which includes a plurality of icons corresponding to a selectable device, is displayed. The screen 3420 includes an upper area 3421 that displays an icon of a device included in a current mode and a lower area 3422 that displays an icon of an addable device. If the user wants to add a device, the user may select an icon 3423 of a device to be added. In this case, an icon corresponding to a selected new device may be replaced and displayed in an area 3431 in which an existing add button is positioned. If the user selects an icon 3432, a screen 3441 for changing a mode set value of a device corresponding to the icon may be displayed. If a store button 3442 is selected after the user completes setting, setting is completed. Thereafter, a message, which is included in the area 3431 displaying the corresponding icon, is changed into set contents.

[0208] Through a mode service page as described above, the user may set a plurality of modes according to tastes of the user and execute only one mode to acquire an effect of executions of a plurality of devices without inputting individual settings of the plurality of devices.

<Third Service Page 100-4-Control>

[0209] Hereinafter, among a plurality of service pages, a third service page that provides a control menu for respectively controlling operations of a plurality of devices included in a home network will be described. Hereinafter, a third service will be referred to as a control service.

[0210] The control service provides a function of checking a state of a device of the home network and a function of turning power on/off.

[0211] FIG. 35 illustrates a control service page 100-4 according to an example embodiment.

[0212] Referring to FIG. 35, a control service summary area 110-4 of the control service page 100-4 includes a scheduled device area and a frequently used device area. If a schedule check button 110a-4 is selected in the scheduled device area, a schedule check pop-up is called. If a device power button 110b-4 is selected, a corresponding device is turned on or off. This will be described in more detail later with reference to FIG. 36.

[0213] Also, the control service page 100-4 includes a first function area 120-4 of a control service connected under a control service summary area 110-4. When the control service summary area 110-4 is displayed on the front surface of the display unit 220, only a cue area 118-4 of a function area of the control unit service for indicating that a function area exists below is displayed on the display unit 220 as shown in FIG. 35. The first function area 120-4 of the control service is displayed above the control service summary area 110-4 according to a user manipulation for dragging the cue area 118-4 of the function area of the control service into the control service summary area 110-4. In this case, if other function areas exist under the first function area 120-4 of the control service, the other function areas are also moved upwards together with the first function area 120-4 of the control service.

[0214] FIG. 36 illustrates editing of a reserved device that is performed on the control service page 100-4 provided by the user terminal apparatus 200 according to an example embodiment.

[0215] Referring to FIG. 36, if a schedule check button 110a-4 is selected, a screen 3621 for checking a schedule is displayed. Here, if a reset button 3622 is selected, a screen 3631 for setting operation scheduled date, time, repeated cycle, and the like of a corresponding device is displayed. Here, if a reservation cancel button 3623 is selected, a reservation of the corresponding device may be canceled. If the user selects a next button 3641 after setting is completed, a screen 3651 for setting a mode of a device is displayed. For example, if the device is a robot cleaner, an automatic mode for performing automatic cleaning, a spot mode for cleaning a determined spot, a max mode for maximum intensity cleaning, a manual mode for designating a cleaning place, a cleaning intensity, etc. by the user, or the like may be provided. If a store button 3652 is selected after a mode is set, a message for indicating that a schedule is stored may be displayed at a lower end of

the control service summary area **110-4**, and a changed setting item may be displayed in an area **3661** displaying a scheduled device.

[0216] The control service page **100-4** provides control UI screens for various types of devices. For example control UI screens for a TV, an air conditioner (A/C), a robot cleaner, a washer, a light, an oven, and a plug will now be described.

[0217] A function area of a control service page will now be described in more detail. The function area of a control service may include a control menu for controlling a device included in a home network.

[0218] FIG. **37** illustrates a first function area of a control service for controlling a TV according to an example embodiment. Hereinafter, for convenience of description, the first function area **120-4** of the control service will be referred to as a TV control card **120-4**, and a first detailed function area **130-4** of the control service will be referred to as a TV detailed control card **130-4**.

[0219] Referring to FIG. **37**, the TV control card **120-4** includes volume control, power, input (external input), home, and channel control buttons. If an enlarge menu icon **3** is selected, a change into the TV detailed control card **130-4** is performed, and the TV detailed control device **130-4** includes more many control buttons than the TV control card **130-4**. For example, if a Navigation tab is selected, a navigation touch pad area or the like is provided with reference to FIG. **38**. If a reservation list tab is selected, a reservation state of turning on and/or off of a TV may be checked, and a reservation may be added.

[0220] FIG. **39** illustrates a second function area of a control service for controlling an A/C according to an example embodiment. Hereafter, for convenience of description, a second function area **121-4** of the control service will be referred to as an A/C control card **121-4**, and a second detailed function area **131-4** of the control service will be referred to as an A/C detailed control card **131-4**.

[0221] Referring to FIG. **39**, the A/C control card **121-4** includes a current temperature area, a temperature control button, and a wind direction control button. Here, if a current temperature reaches a maximum or minimum temperature, + or – button may be inactivated. If the enlarge menu icon **3** is selected, a change into the A/C detailed control card **131-4** is performed, and the A/C detailed control card **131-4** includes more many control buttons than the A/C control card **131-4**. For example, if an operating tap is selected, an operation mode, such as subtropical pleasantness, air-conditioning, dehumidifying, cleaning, heating, or the like, may be selected. If a reservation list tap is selected, a reservation state of turning on and/or off an A/C may be checked, and a reservation may be added. If Vertical Swing is selected, a wind direction menu changing according to an operation mode may be displayed as shown in FIG. **40**.

[0222] FIG. **41** illustrates a third function area of a control service for controlling a robot cleaner according to an example embodiment. Hereinafter, for convenience of description, a third function area **122-4** of the control service will be referred to as a robot cleaner control card **122-4**, and a third detailed function area **132-4** of the control service will be referred to as a robot cleaner detailed control card **132-4**.

[0223] Referring to FIG. **41**, the robot cleaner control card **122-4** includes operation state, power buttons, and the like. If an enlarge menu icon **3** is selected, the robot cleaner control card **122-4** is changed to the robot cleaner detailed control card **132-4**, and the robot cleaner detailed control card **132-4** includes more many control buttons than the robot cleaner control card **132-4**. For example, if an operate tap is selected, an operation state button, a direction control button, a microphone, a light, a camera button, etc. are provided. For example, if the camera button is selected, an image that is captured through a camera installed in a robot cleaner may be checked.

[0224] FIG. **42** illustrates a fourth function area of the control service for controlling a washer according to an example embodiment. Hereinafter, for convenience of description, a fourth function area **123-4** of the control service will be referred to as a washer control card **123-4**, and a fourth detailed function area **133-4** of the control service will be referred to as a washer detailed



control card **133-4**.

[0225] Referring to FIG. **42**, the washer control card **123-4** includes an information screen, a state window, a start button, or the like. If an enlarge menu icon **3** is selected, the washer control card **123-4** is changed to the washer detailed control card **133-4**, and the washer detailed control card **133-4** includes many more control buttons than the washer control card **133-4**. Also, referring to FIG. **43**, if a state window **133a-4** is selected, a menu for changing washing elements, such as a water temperature, rinsing, dewatering, etc. is displayed.

[0226] FIG. **44** illustrates a fifth function area of the control service for controlling a light according to an example embodiment. Hereinafter, for convenience of description, a fifth function area **124-4** of the control service will be referred to as a light control card **124-4**, and a fifth detailed function area **134-4** of the control service will be referred to as a light detailed control card **134-4**.

[0227] Referring to FIG. **44**, the light control card **124-4** includes an information screen, a power button, etc. If an enlarge menu icon **3** is selected, the light control card **124-4** is changed to the light detailed control card **134-4**, the light detailed control card **134-4** includes many more control buttons than the light control card **124-4**. If a light intensity tab is selected in the light detailed control card **134-4**, a light intensity may be controlled. If a particular mood is selected, the light intensity may be automatically controlled according to the corresponding mood. Referring to FIG. **45**, if a Smart Care tab is selected in the light detailed control card **134-4**, various care modes are provided. For example, if baby crying is sensed in a Baby Care, a designated LED may automatically dim. If a motion of the user terminal apparatus **200** is sensed while asleep in a Night Care, a designated LED may automatically dim. If there is a missed call in the user terminal apparatus **200** in a Missed Call Care, an LED designated after a preset time may automatically flicker so as to enable the user to check the user terminal apparatus **200**.

[0228] FIG. **46** illustrates a sixth function area of the control service for controlling an oven according to an example embodiment. Hereinafter, for convenience of description, a sixth function area **125-4** of the control service will be referred to as an oven control card **125-4**, and a sixth detailed function area **135-4** of the control service will be referred to as an oven detailed control card **135-4**.

[0229] Referring to FIG. **46**, the oven control card **125-4** includes an information screen, a power button, and the like. If an enlarge menu icon **3** is selected, the oven control card **125-4** is changed to the oven detailed control card **135-4**, and the oven detailed control card **135-4** includes many more buttons than the oven control card **135-4**. If an operate tab is selected in the oven detailed control card **135-4**, a plurality of oven function buttons, temperature control and select start button, etc. are provided.

[0230] Referring to FIG. **47**, if a particular one is selected from a plurality of oven functions in the oven detailed control card **135-4**, a list **135a-4** that may be provided by the selected function is displayed.

[0231] FIG. **48** illustrates a seventh function area of the control service for controlling a power plug according to an example embodiment. Hereinafter, for convenience of description, a seventh function area **126-4** of the control service will be referred to as a plug control card **126-4**, and a seventh detailed function area **136-4** of the control service will be referred to as a plug detailed control card **136-4**.

[0232] Referring to FIG. **48**, the plug control card **126-4** includes an information screen, a power button, and the like. If an enlarge menu icon **3** is selected, the plug control card **126-4** is changed to the plug detailed control card **136-4**, and the plug detailed control card **136-4** includes many more control buttons than the plug control card **136-4**. The plug detailed control card **136-4** may provide a reservation list of on/off reservations.

[0233] Through the user terminal apparatus **200** providing a control service page as described above, the user may easily manipulate devices in a home through only the user terminal apparatus **200**.

<Fourth Service Page **100-5-Care Report**>

[0234] Among a plurality of service pages, a fourth service page that provides controls of devices included in another home network will now be described. Hereinafter, a fourth service will be referred to as a care report service.

[0235] The care report service is a service that checks and reports whether an abnormality occurs in a home registered as a care object, based on a device use log of the home.

[0236] FIG. **49** illustrates a care report service page **100-5** according to an example embodiment.

[0237] Referring to FIG. **49**, a care report service summary area **110-5** of the care report service page **100-5** provides a message having different contents according to a current monitoring state and includes a recently used device log information area of a home registered as a care object.

[0238] If a call button **110a-5** is selected in the recently used device log information area of the home registered as the care object, a call is made to the corresponding home.

[0239] Also, the care report service page **100-5** includes a first function area **120-5** of a care report service connected under the care report service summary area **110-5**. When the care report service summary area **110-5** is displayed on the front surface of the display unit **220**, only a cue area **118-5** of a function area of the care report service for indicating that a function area exists below is displayed on the display unit **220** as shown in FIG. **49**. The first function area **120-5** of the care report service is displayed above the care report service summary area **110-5** according to a user manipulation for dragging the cue area **118-5** of the function area of the care report service into the care report service summary area **110-5**. In this case, if other function areas exist under the first function area **120-5** of the care report service, the other function areas are moved upwards together with the first function area **120-5** of the care report service.

[0240] FIG. **50** illustrates a function area that is provided on a care report service page according to an example embodiment. In detail, FIG. **50** illustrates various states of the first function area **120-5** of the care report service.

[0241] Referring to FIG. **50**, for example, if an abnormality occurs in a home registered as a care object, and an enlarge menu icon **3** is selected, a first detailed function area **130-5** of the care report service is displayed on the front surface of the display unit **220**. Here, if a Call button is selected, a call is made to the home registered as the care object.

[0242] Through the user terminal apparatus **200** providing the care service page as described above, the user may be provided with situation information about a home of the user and another home through a user terminal apparatus of the user.

<Fifth Service Page **100-6-Energy**>

[0243] Among a plurality of service pages, a fifth service page that provides energy usage information about a plurality of devices included in a home network will now be described. Hereinafter, the fifth service will be referred to as an energy service.

[0244] The energy service provides a service of measuring and managing detailed energy usage of a device registered in a home network.

[0245] FIG. **51** illustrates an energy service page **100-6** according to an example embodiment.

[0246] Referring to FIG. **51**, an energy service summary area **110-6** of the energy service page **100-6** includes a description message of energy, a bar graph **110b-6** showing energy usage that is currently used and energy usage goal, and an area indicating information about three devices having most energy usage among devices registered in a home network.

[0247] Also, the energy service page **100-6** includes a first function area **120-6** of the energy service connected under the energy service summary area **110-6**. When the energy service summary area **110-6** is displayed on the front surface of the display unit **220**, only a cue area **118-6** of a function area of the energy service for indicating that a function area exists below is displayed on the display unit **220** as shown in FIG. **51**. The first function area **120-6** of the energy service is displayed above the energy service summary area **110-6** according to a user manipulation for dragging the cue area **118-6** of the energy service into the energy service summary area **110-6**. In

this case, if other function areas exist under the first function area **120-6** of the energy service, the other function areas are also moved upwards together with the first function area **120-6** of the energy service.

[0248] Referring to FIG. 52, if an edit menu **110a-6** provided in the energy service summary area **110-6** is selected, an energy goal value of each device of the home network may be edited. Also, if the bar graph **110b-6** provided in the energy service summary area **110-6** is selected, a screen, which displays energy usage that is currently used and energy usage goal, is output. The user swipes a monthly graph area displayed at a bottom of the screen from side to side to scroll the monthly graph area. Also, if a detail view button **110c-6** provided in the energy service summary area **110-6** is selected, three devices having most energy usage among devices registered in the home network are included so as to display energy usage detail information of other registered devices.

[0249] FIGS. 53 through 55 illustrate a function area that is provided on an energy service page according to various example embodiments. The energy service page provides a first function area **120-6** (Energy Goal Card) of the energy service page, a second function area **122-6** (Monthly Energy Usage Card) of the energy service page, and a third function area **124-6** (Energy Usage Rate Card) of the energy service page.

[0250] Referring to FIG. 53, if an enlarge menu icon **3** provided in the first function area **120-6** (Energy Goal Card) of the energy service is selected, a first detailed function area **130-6** of the energy service page is displayed as shown in FIG. 53. The first detailed function area **130-6** of the energy service page displays an energy goal value set by the user and information about an amount remaining to the goal value, an excess of the goal value, or the like.

[0251] Also, referring to FIG. 54, if an enlarge menu icon **3** provided in the second function area **122-6** (Monthly Energy Usage Card) of the energy service page is selected, a second detailed function area **132-6** of the energy service page is displayed as shown in FIG. 54. The second detailed function area **132-6** of the energy service page displays a monthly energy usage as a broken line graph in the second detailed function area **132-6** of the energy service page and monthly provides detailed information about power consumption. For example, information about a month where energy consumption increases fastest, and a monthly energy consumption difference calculation result may also be provided.

[0252] Also, referring to FIG. 55, if an enlarge menu icon **3** provided in the third function area **124-6** (Energy Usage Rate Card) of the energy service page is selected, a third detailed function area **134-6** of the energy service page is displayed as shown in FIG. 55. The third detailed function area **134-6** of the energy service page may provide detailed information about energy consumption of each device and information about monthly energy consumption of each device.

[0253] According to the user terminal apparatus **200** providing the energy service page as described above, the user may check an energy usage at one time and set an energy goal value. Therefore, an energy saving effect may increase.

<Sixth Service Page **100-7**-Media>

[0254] A sixth service page that provides a media service by using a media output device of a plurality of devices included in a home network will now be described. Hereinafter, a sixth service will be referred to as a media service. The media service refers to a service through which recently played content and recently updated content may be checked and played.

[0255] FIG. 56 illustrates a media service page **100-7** according to an example embodiment.

[0256] Referring to FIG. 56, a media service summary area **110-7** of the media service page **100-7** includes a recently played content information area and a recently updated file information area.

[0257] The media service page **100-7** also includes a first function area **120-7** of the media service connected under the media service summary area **110-7**. When the media service summary area **110-7** is displayed on the front surface of the display unit **220**, only a cue area **118-7** of a function area of the media service for indicating that a function area exists below is displayed on the display

unit **220** as shown in FIG. **56**. The first function area **120-7** of the media service is displayed above the media service summary area **110-7** according to a user manipulation for dragging the cue area **118-7** of the function area of the energy service into the media service summary area **110-7**. In this case, if other function areas exist under the first function area **120-7** of the media service, the other function areas are also moved upwards together with the first function area **120-7** of the media service.

[0258] According to an example embodiment, the user may select a play method of a content displayed in the media service summary area **110-7**. Referring to FIG. **57**, if an operation of long pressing a content icon **5711** by the user is sensed, the control unit **240** may display a playable device list **110a-7**. Also, the user may select one of playable devices according to an operation of dragging a movable content icon **5712**. With reference to **5730** of FIG. **57**, a device of the user may be selected as a device for playing content among the device (My Phone) of the user, a TV in a living room, a device (Den's) of another user, and a TV in a bedroom. With reference to **5740** of FIG. **57**, the user may select the device (Den's) of the other user, not the device of the user. In this case, the device of the other user may be a user terminal apparatus of the other user registered in the home network. Thereafter, a message **5751** indicating that a corresponding content is played in the selected device of the other user may be displayed.

[0259] A function area of the media service page **100-7** may include a menu for managing a file stored in at least one of a plurality of devices included in the home network. In detail, FIG. **58** illustrates function areas that may be provided on the media service page **100-7**.

[0260] Referring to FIG. **58**, a first function area **120-7** of the media service, a second function area **122-7** of the media service, a third function area **124-7** of the media service, and a fourth area **126-7** of the media service are illustrated. Respective function areas relate to "Movie", "Music", "Photo", and "Recently updated". If an enlarge menu icon **3** provided in each function area is selected, a corresponding detailed function area is displayed on the front surface of the display unit **220**.

[0261] FIG. **59** illustrates a detailed function area provided from a media service. Contents may be arranged and displayed in thumbnail form or in list form in the detailed function area as shown with **5910** of FIG. **59**. If a menu button **5911** is selected to select an option menu, an arrange menu icon **5921** may be displayed under the menu button **5911**. If the user selects the arrange menu icon **5921**, a screen **5931** for inputting an arrangement standard may be displayed. Contents may be arranged in order of date, size, alphabet, or the like. For example, if an alphabetic order arrangement is selected (**5932**), contents may be arranged in alphabetic order as shown with **5940** of FIG. **59**. The user may re-select the menu button **5911** to change the arrangement standard.

[0262] According to the media service page as described above, the user may easily manage stored contents and play the stored contents by using other devices connected to the home network.

[0263] A plurality of service pages that are provided from a home network service will now be described. Hereafter, various types of setting screens of a home network service will be described.

[0264] Referring to FIG. **60**, a setting UI screen **400** includes account management, device management, briefing setting, cleanliness guide setting, and card management menus.

[0265] Here, if an account manage menu **400a** is selected, an account management UI screen **410** is displayed. As shown in FIG. **61**, if a My Profile menu option **410a** is selected on the account management UI screen **420**, a screen for setting representative photo, name, etc. of my account is output. If a family list menu option **410b** is selected on the account management UI screen **410**, a registered family member list **430** is provided with reference to FIG. **62**. The user may set a name, a representative photo, etc. of each of registered family members and add or delete a family member as shown in FIG. **62**.

[0266] FIG. **63** illustrates adding of family members into the registered family member list **430**. Referring to FIG. **63**, if a device add menu **6311** is selected on the registered family member list **430**, the control unit **240** searches for a user located in the same network and displays that the user

is being searched (**6320**). Thereafter, if a check box provided in a list is selected (**6331**), and an add button **6341** for completing adding is selected after a family list searched by the user is displayed, a selected member may be added into the registered family member list **430** as shown with **6350** of FIG. **63**. According to another example embodiment, adding of a family member may be performed through a contact list stored in the storage unit **250** of the user terminal apparatus **200**.

[0267] Referring to FIG. **60** again, if a device manage menu **400b** is selected, a device management UI screen **420** is displayed. As shown in FIG. **64**, the user may set names of devices registered in the home network and locations of the devices on the device management UI screen **420**. Also, as shown in FIG. **65**, if “device add” is selected in the device manage menu **400b**, a list of searched devices and a list of unsearched devices are provided in the network. The user may select a device that is to be added into a provided list.

[0268] Also, as shown in FIG. **66**, an unsearched device may be added in the network. Referring to FIG. **66**, if a device add menu **6611** is selected, a screen **6630**, which provides adding of devices and includes an area **6631** displaying a searched device in the network and an area **6632** displaying an unsearched device in the network, may be displayed. The user may input Access Point (AP) information, etc. about devices unsearched in the network to register the devices in the home network system **500** (**6640**).

[0269] Referring to FIG. **60** again, if briefing setting **400c** is selected, a briefing setting UI screen **430** is displayed. Referring to FIG. **67**, various types of notifications that may be displayed in a briefing area **112-1** provided in the information display area **110-1** of the home network of the main page **100-1** may be set on the briefing setting UI screen **430**. For example, if selecting of “automatic temperature control” is canceled on the briefing setting UI screen **430**, a notification about a temperature is not displayed in the briefing area **112-1** (refer to FIG. **15**) of the main page **100-1** anymore.

[0270] Referring to FIG. **60** again, if cleanliness guide setting **400d** is selected, a cleanliness guide setting UI screen **440** is displayed. Referring to FIG. **68**, the user may set a cleanliness index or see cleanliness guide contents on the cleanliness guide setting UI screen **440**.

[0271] Referring to FIG. **60** again, if a manage card (function area) **400e** is selected, a card management UI screen **440** is displayed. As shown in FIG. **69**, the user may delete a function area (card) included in a plurality of service pages **100-2**, **100-3**, **100-4**, **100-5**, **100-6**, and **100-7** or restore a deleted function area (card) through the card management UI screen **440**.

[0272] A home network management service as described may be provided through various types of UI screens. The home network management service will now be described with reference to FIGS. **70** through **72**.

[0273] FIG. **70** illustrates a home network management service that is provided on a lock screen **800** of the user terminal apparatus **200** according to an example embodiment of the present invention. The lock screen **800** is a screen that is first displayed when the user terminal apparatus **200** is turned on. A user authentication process may be performed on the lock screen, and only if an authentication is performed, the user may use various functions of the user terminal apparatus **200**.

[0274] Referring to FIG. **70**, the lock screen **800** of the user terminal apparatus **200** includes brief information of the home network management service. In other words, the user may be simply provided with important information about the home network without executing a home network application. For example, as shown in FIG. **70**, a notification provided from a care service or a monitoring service may be provided on the lock screen **800**.

[0275] FIG. **71** illustrates a home network management service that is provided on a quick panel of the user terminal apparatus **200** according to an example embodiment. The quick panel refers to a screen that is displayed by an operation of touching and dragging down one of a plurality of edges by the user when a basic background screen of the user terminal apparatus **200** is displayed. The quick panel may display brief state information and the like of the user terminal apparatus **200**.

[0276] Referring to FIG. **71**, the quick panel may display at least one of function areas or main

notification information included in the plurality of service pages **100-2**, **100-3**, **100-4**, **100-5**, **100-6**, and **100-7**.

[0277] FIG. **72** illustrates a widget of the user terminal apparatus **200** according to an example embodiment. The widget is an object for a service shortcut that is provided on a basic background screen of the user terminal apparatus **200**.

[0278] Referring to FIG. **72**, a plurality of widgets **820a**, **820b**, **820c**, and **820d** are to be connected to a corresponding service page. As shown in FIG. **72**, widgets may be selected and registered in option menus provided on the plurality of service pages **100-2**, **100-3**, **100-4**, **100-5**, **100-6**, and **100-7**.

[0279] As shown in FIG. **73**, the present widget may apply layouts of function areas provided on the plurality of service pages **100-2**, **100-3**, **100-4**, **100-5**, **100-6**, and **100-7**.

[0280] According to various example embodiments as described above, the user may use various services provided from a home network service. A method of managing a home network of a user terminal apparatus according to an example embodiment will now be described in detail by using a flowchart.

[0281] FIG. **74** illustrates a method of managing a home network of a user terminal apparatus according to an example embodiment. Referring to FIG. **74**, if an application for managing a home network is executed, the control unit **240** displays a first service page of a plurality of service pages in operation **S7410**. The plurality of service pages are pages for providing a plurality of home network management services that may be provided by using the plurality of devices. Here, the first service page is a page that is first displayed when executing an application, i.e., may be a main page or a recently searched service. In detail, if there is a service page that is used by a user just before, and the application is re-executed, the service page that is used just before may be displayed.

[0282] If a user manipulation in a first direction is input when the first service page is displayed, the control unit **240** displays a second service page connected to the first service page in operation **S7420**. The second page is one of a plurality of service pages described above, for example, a service page that provides a monitoring service of each room, a mode service, a control service of a client device of the home network, etc. An order of arranging a plurality of services may depend on setting of the user, and a service page may be added and deleted according to user setting.

[0283] If a user manipulation in a second direction is input when the first service page or the second service page is displayed, the control unit **240** may display a function area included in the first service page or the second service page in operation **S7430**.

[0284] A service page and a function area as described above have been described in detail in the above-described various example embodiments, and thus their repeated descriptions are omitted.

[0285] In a plurality of example embodiments as described above, a UI screen including a plurality of services may be selectively displayed according to a user manipulation. In this case, map information may be provided so as to enable the user to intuitively check a structure of a whole page at one time. The map information refers to information that reduces the whole page, displays the reduced whole page, and indicates a location of a page that is currently being searched by the user within the whole page.

[0286] FIGS. **75** and **76** illustrate map information that is provided by a user terminal apparatus according to an example embodiment.

[0287] According to the present example embodiment, the user terminal apparatus **200** may provide location information of a particular area of a service page that is currently being searched by the user.

[0288] FIG. **75** illustrates a part of the control service page **100-4** that is currently being searched by the user within a UI screen including a total of seven service pages. In detail, the part of the control service page **100-4** is displayed on the display unit **220** of the user terminal apparatus **200**.

[0289] In this state, if a particular user manipulation is input, a structure of a whole UI screen is

reduced and then is all displayed within the display unit **220** as shown in FIG. **76**. Also, a graphic object **7600** that informs the user of a location of an area that is currently being searched within the whole UI screen is displayed together. The user may intuitively know that a current page is a function area (control card **1**) of a control service page, with seeing the map information. Thereafter, if the user deletes the map information, the control unit **240** displays the function area (control card **1**) of the control service page. In this state, if the user performs flicking or dragging to the left, the control unit **240** displays a mode service page. If the user performs flicking or dragging to the right, the control unit **240** displays a care service page.

[0290] A user manipulation for displaying the map information may be set by an arbitrary manipulation for calling the map information. For example, if the user terminal apparatus **200** rotates in a horizontal direction when the user searches for a service page with gripping the user terminal apparatus **200** in a vertical direction, map information displaying a location of an area that the user is searching for may be displayed as shown in FIG. **75**. Alternatively, even if an operation of moving or swinging the user terminal apparatus **200** at a preset speed or the like is sensed, the map information may be displayed. Alternatively, even if a menu for moving to the map information is selected when the user searches for a service page, the map information may be displayed. Whether to display the map information may be selectively performed according to an option setting state of the user.

[0291] In the above-described example embodiments, an arrangement direction of a service page is different from an arrangement direction of a function area, but the arrangement directions may be variously changed and set.

[0292] In detail, according to another example embodiment, a service page may be configured so as to have a different structure from that shown in FIG. **1**. This will be described in detail with reference to FIG. **77**.

[0293] FIG. **77** illustrates an operation of a user terminal apparatus according to another example embodiment. The present example embodiment may be easily understood in comparison of FIG. **77** with FIG. **11**.

[0294] In the above-described various example embodiments, function areas of service pages (favorite function areas in case of main page) are connected under service summary areas. According to the present example embodiment, function areas are arranged in the same directions as those of service summary areas. Therefore, since a function area is equal to a page that is arranged in one direction, the function area will be hereinafter referred to as a function area page.

[0295] Referring to FIG. **77**, for example, if a particular user manipulation is input when a service summary area **110-3** of a monitoring service page is displayed, a first function area page of a monitoring page may be generated on a side of a service summary area **110-3** and replace the service summary area **110-3** to be displayed on the display unit **220**. Here, if the display unit **220** is realized as a touch screen, the particular user manipulation may be set to various types of manipulations, such as a pinch to zoom (in or out) for simultaneously dragging two fingers, a double touch, etc. but is not limited thereto.

[0296] When a first function area **771** is displayed, a second function area page **772** is displayed according to a user manipulation, such as turning over of a page to a side. Only two function area pages are illustrated in FIG. **77**, but one function area page or two or more function area pages may be included as described with reference to FIG. **1**.

[0297] If a user manipulation for performing flicking or dragging in a direction where the pages are arranged when the second function area page **772** is displayed, a summary area **110-6** of an energy service page may be displayed.

[0298] If a manipulation, such as a pinch to zoom or the like, is input when the first function area page **771** or the second function area page **772** is displayed, the first function area page **771** or the second function area page **772** may return to a summary area **110-3** of a monitoring service page. In this case, an animation through which the first function area page **771** or the second function area

page **772** disappears or is reduced may be added.

[0299] If a user manipulation, such as flicking or dragging of the summary area **119-3** of the monitoring service page to the side, is input when the first function area page **771** or the second function area page **772** is closed, the summary area **110-6** of the energy service page may be displayed.

[0300] As in the present example embodiment, if a user manipulation of a function area is input, an operation corresponding to the input manipulation may be performed. A detailed example embodiment is equal to the example embodiments described with reference to FIGS. **1** through **74**, and thus repeated descriptions thereof are omitted.

[0301] The user terminal apparatus **200** may be realized as various types. In the above-described example embodiments, the user terminal apparatus **200** is realized as a smart phone, but may be realized, for example, as a TV.

[0302] FIG. **78** illustrates the main page **100-1** if a user terminal apparatus is realized as a TV.

[0303] Referring to FIG. **78**, the main page **100-1** may be displayed on a side of a display unit **900** of the TV. The user may select various menus of the main page **100-1** by using an input unit such a remote control unit.

[0304] If a user manipulation for flicking a touch pad of the remote control unit from side to side is input when the main page **100-1** is displayed, a plurality of service pages may be simultaneously displayed.

[0305] If the user terminal apparatus is realized as the TV, a limitation on a size of a display unit is smaller than if the user terminal apparatus is realized as a smartphone or the like. Therefore, if a full screen change menu **901** of the main page **100-1** is selected, a plurality of favorite function areas **120-1** and **122-1** may be horizontally arranged and displayed as shown in FIG. **79**. In this case, the user may navigate favorite function areas from side to side by using a direction key of the remote control unit.

[0306] Referring to FIG. **79**, situation information **902** inside a home may be displayed along with the plurality of favorite function areas **120-1** and **122-1**. Differently from if the user terminal apparatus is realized as a smartphone or the like, if a user manipulation of a category area **903** is input, a change into a screen displaying a function area of another service may be performed. For example, FIG. **80** illustrates a screen that displays a function area of a monitoring service. Through the category area **903**, the user may check whether a currently displayed screen is a service of which category.

[0307] In the previous example embodiment, if a change between service pages or a call of a function area is performed according to a user manipulation in a first or second direction, a similar manipulation may be performed through a touch pad provided in a remote control unit in the case of a TV. Alternatively, up, down, left, and right direction keys of the remote control unit may be used.

[0308] Even if the user terminal apparatus is realized as the TV, a plurality of service pages may be displayed as described with reference to FIGS. **1** through **73**, and as an example, a monitoring service page **100-2** is illustrated in FIG. **81**.

[0309] Even if a UI for managing a home network is realized as a TV, a principle of configuring various types of screens described above with reference to FIGS. **1** through **73** may be applied, and thus more repeated descriptions are omitted. Changes in some of layouts caused by an increase in a size of a display unit **900** may be sufficiently understood through FIGS. **78** through **81**, and modified example embodiments associated with a user manipulation performed through a remote control unit or the like will be apparent to those skilled in the art.

[0310] A user terminal apparatus according to various example embodiments as described above may provide various types of UIs for managing a home network. The various types of UIs may be designed according to characteristics of provided services and characteristics of provided information. Therefore, a user may easily use a home network service through only a simple



operation. In particular, the user terminal apparatus may flexibly change a UI for managing a home network according to environment changes in the home network or a manipulation of the user. Therefore, the user may be provided with an integrated home network management service appropriate for a lifestyle or a taste of the user.

[0311] A method of managing a home network by using various types of UI screens, which are arranged on a plurality of axes and have different attributes, has been described in detail in the above-described various example embodiments, but the above-described various example embodiments are not limited to a home network management. For example, a user terminal apparatus that may provide a plurality of services and a plurality of functions may provide UI screens having types as described above so as to enable the user to easily select the services and the functions. Alternatively, even in various environments for managing a plurality of devices (e.g., a printer, a scanner, a copier, a multi-function peripheral, etc.) connected through a network, a UI screen may be variously designed to be efficiently managed according to the above-described method. In other words, contents described in the above-described various example embodiments may be applied to display a UI screen in a home network system, various types of apparatuses, or a system.

[0312] A method of managing a home network of a user terminal apparatus, a method of displaying a UI screen, etc. according to the above-described example embodiments may be stored on a non-transitory readable medium. The non-transitory readable medium may be mounted and used on various types of apparatuses.

[0313] The non-transitory readable medium is readable by devices and includes compact disks (CDs), digital video disks (DVDs), hard disks, Blu-ray disks, universal serial buses (USBs), memory cards, and read-only memory (ROM).

[0314] The foregoing example embodiments and advantages are merely illustrative and should not be construed as limiting. The teachings described herein can be readily applied to other types of apparatuses. Also, the description of the example embodiments is intended to be illustrative, and not to limit the scope of the claims, and many alternatives, modifications, and variations will be apparent to those skilled in the art.

## Claims

1. A user terminal apparatus comprising, a communicator configured to communicate with a plurality of devices registered in the home network; a display; and a processor configured to: control the display to display an energy service page for providing energy usage information of the plurality of devices, the energy service page comprising an energy service summary area; and based on a user manipulation for dragging a function area corresponding to the energy service summary area being input, control the display to display the function area above the energy service summary area.
2. The user terminal apparatus of claim 1, wherein the processor is configured to: control the display to display a cue area of the function area for indicating that the function area exists, and based on a user manipulation for dragging the cue area of the function area into the energy service summary area being input, control the display to display the cue area of the function area above the energy service summary area.
3. The user terminal apparatus of claim 2, wherein the cue area of the function area is disposed below the energy service page.
4. The user terminal apparatus of claim 1, wherein the energy service summary area comprises: at least one of a first area indicating a description message of energy service, a second area indicating energy usage that is currently used and an energy usage goal, or a third area indicating information about at least one device having most energy usage among the plurality of devices registered in the home network.

5. The user terminal apparatus of claim 4, wherein the processor is configured to: based on a user manipulation for selecting an edit User Interface (UI) including the second area being input, control the display to display a screen for editing an energy usage goal of each device among the plurality of devices registered in the home network.
6. The user terminal apparatus of claim 4, wherein the processor is configured to: based on a user manipulation for selecting a detail view UI including the third area being input, control the display to display a screen for displaying energy usage detail information of the registered plurality of devices.
7. The user terminal apparatus of claim 1, wherein the function area comprises: at least one of a first function area indicating energy usage goal, a second function area indicating monthly energy usage or a third function area indicating energy usage rate.
8. The user terminal apparatus of claim 7, wherein the processor is configured to: based on a user manipulation for selecting the first function area being input, control the display to display a screen for displaying information about remaining amount corresponding to the energy usage goal or excess amount corresponding to the goal value.
9. The user terminal apparatus of claim 7, wherein the processor is configured to: based on a user manipulation for selecting the second function area being input, control the display to display a screen for displaying a graph of monthly energy usage.
10. The user terminal apparatus of claim 7, wherein the processor is configured to: based on a user manipulation for selecting the third function area being input, control the display to display a screen for displaying information about energy usage of each device among the plurality of devices registered in the home network.
11. A method for communicating with a plurality of devices registered in the home network by a user terminal apparatus, the method comprising: displaying an energy service page for providing energy usage information of the plurality of devices, the energy service page comprising an energy service summary area; and based on a user manipulation, for dragging a function area corresponding to the energy service summary area, being input, displaying the function area above the energy service summary area.
12. The method of claim 11, further comprising: displaying a cue area of the function area for indicating that a function area exists, based on a user manipulation for dragging the cue area of the function area into the energy service summary area being input, displaying the cue area of the function area above the energy service summary area.
13. The method of claim 12, wherein the cue area of the function area exists below the energy service page.
14. The method of claim 11, wherein the energy service summary area comprises: at least one of a first area indicating a description message of energy service, a second area indicating energy usage that is currently used and energy usage goal or a third area indicating information about at least one device having most energy usage among the plurality of devices registered in the home network.
15. The method of claim 14, further comprising: based on a user manipulation for selecting an edit User Interface (UI) including the second area being input, displaying a screen for editing energy usage goal of each device among the plurality of devices registered in the home network.
16. The method of claim 14, further comprising: based on a user manipulation for selecting a detail view UI including the third area being input, displaying a screen for displaying energy usage detail information of the registered plurality of devices.
17. The method of claim 11, wherein the function area comprises: at least one of a first function area indicating energy usage goal, a second function area indicating monthly energy usage or a third function area indicating energy usage rate.
18. The method of claim 17, further comprising: based on a user manipulation for selecting the first function area being input, displaying a screen for displaying information about remaining amount corresponding to the energy usage goal or excessing amount corresponding to the goal value.

**19.** The method of claim 17, further comprising: based on a user manipulation for selecting the second function area being input, displaying a screen for displaying a graph of monthly energy usage.

**20.** The method of claim 17, further comprising: based on a user manipulation for selecting the third function area being input, displaying a screen for displaying information about energy usage of each device among the plurality of devices registered in the home network.

---