

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12393304
Kind Code	B1
Date of Patent	August 19, 2025
Inventor(s)	Shih; Chia-Chien et al.

Touch circuit

Abstract

A touch circuit including an integrator circuit and a compensation circuit is provided. The integrator circuit includes a first terminal, a second terminal and an output terminal. The first terminal of the integrator circuit is coupled to a touch sensor, and the second terminal of the integrator circuit is coupled to a first voltage. The compensation circuit includes a first terminal and a second terminal. The first terminal of the compensation circuit is coupled to the first terminal of the integrator circuit, and the second terminal of the compensation circuit is coupled to a second voltage. When the touch circuit senses a sensing current from the touch sensor, the first voltage is increased and the second voltage is decreased.

Inventors: Shih; Chia-Chien (Hsinchu County, TW), Chen; Yu-Huang (Tainan, TW), Liu; I-Te (Hsinchu County, TW)

Applicant: Novatek Microelectronics Corp. (Hsinchu, TW)

Family ID: 1000007700636

Assignee: Novatek Microelectronics Corp. (Hsinchu, TW)

Appl. No.: 18/582655

Filed: February 21, 2024

Publication Classification

Int. Cl.: G06F3/041 (20060101); G06F3/044 (20060101)

U.S. Cl.:

CPC G06F3/0418 (20130101); G06F3/044 (20130101);

Field of Classification Search

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10082922	12/2017	Hanssen et al.	N/A	N/A
10572058	12/2019	Kim	N/A	H03K 21/08
10684726	12/2019	Chen	N/A	H03K 17/962
10976796	12/2020	Anantharaman	N/A	G06F 3/0418
11093090	12/2020	Larsson et al.	N/A	N/A
11853514	12/2022	Kim et al.	N/A	N/A
11861111	12/2023	Kim	N/A	G06F 3/04166
2010/0097345	12/2009	Jang	345/174	G06F 3/041661
2010/0110040	12/2009	Kim	345/174	G06F 1/3237
2010/0328252	12/2009	Chang	345/174	G06F 3/044
2012/0218020	12/2011	Erdogan	327/337	G06F 3/04166
2012/0287077	12/2011	Pant	345/174	G06F 3/0418
2014/0021966	12/2013	Shahrokhi	324/679	G01R 27/2605
2021/0173501	12/2020	Larsson et al.	N/A	N/A
2022/0360275	12/2021	Maharyta et al.	N/A	N/A
2023/0108545	12/2022	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
115395959	12/2021	CN	N/A
202123457	12/2020	TW	N/A
202314583	12/2022	TW	N/A

OTHER PUBLICATIONS

“Notice of allowance of Taiwan Counterpart Application”, issued on Sep. 27, 2024, p. 1-p. 3. cited by applicant

Primary Examiner: Chow; Doon Y

Attorney, Agent or Firm: JCIPRNET

Background/Summary

BACKGROUND

Technical Field

(1) The invention relates to an electronic circuit, more specifically, to a touch circuit.

Description of Related Art

(2) The touch circuit receives both the reference current and the sensing current generated by the touch sensor. The touch circuit then divides the current and sends it to the current integrator for processing. The touch circuit is to detect the sensing current. However, it is important to note that the reference current is significantly larger than the sensing current. An excessively large reference

current can easily cause the current integrator to saturate, rendering the touch circuit unable to detect the sensing current. To address this issue, a capacitive compensation circuit is utilized to generate a compensation current that can reduce the reference current.

(3) Traditionally, the compensation current is generated by a compensation voltage coupled to the compensation capacitor. However, when the voltage amplitude is limited, a large compensation capacitance is often necessary to reduce the reference current.

SUMMARY

(4) The invention is directed to a touch circuit, that can increase the compensation current of the compensation capacitor, thereby reducing the required capacitance value for the compensation circuit.

(5) An embodiment of the invention provides a touch circuit including an integrator circuit and a compensation circuit. The integrator circuit includes a first terminal, a second terminal and an output terminal. The first terminal of the integrator circuit is coupled to a touch sensor, and the second terminal of the integrator circuit is coupled to a first voltage. The compensation circuit includes a first terminal and a second terminal. The first terminal of the compensation circuit is coupled to the first terminal of the integrator circuit, and the second terminal of the compensation circuit is coupled to a second voltage. When the touch circuit senses a sensing current from the touch sensor, the first voltage is increased and the second voltage is decreased.

(6) An embodiment of the invention provides a touch circuit including an integrator circuit and a compensation circuit. The integrator circuit includes a first terminal, a second terminal and an output terminal. The first terminal of the integrator circuit is coupled to a touch sensor, and the second terminal of the integrator circuit is coupled to a first voltage. The switch circuit includes a first terminal, a second terminal and a third terminal. The first terminal of the switch circuit is coupled to the first terminal of the integrator circuit. The compensation circuit includes a first terminal and a second terminal. The first terminal of the compensation circuit is coupled to the second terminal of the switch circuit, and the second terminal of the compensation circuit is coupled to a second voltage. The third terminal of the switch circuit is coupled to a third voltage. The switch circuit is configured to switch many times to make the second voltage switch between a first level and a second level. The first level is larger than the second level.

(7) To make the aforementioned more comprehensible, several embodiments accompanied with drawings are described in detail as follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

(2) FIG. 1 is a block diagram illustrating a touch device according to an embodiment of the invention.

(3) FIG. 2 is a schematic diagram illustrating a touch circuit of FIG. 1 according to an embodiment of the invention.

(4) FIG. 3 is a waveform diagram illustrating voltage levels of the first voltage and the second voltage according to an embodiment of the invention.

(5) FIG. 4 is a schematic diagram illustrating a touch circuit according to another embodiment of the invention.

(6) FIG. 5 is a waveform diagram illustrating voltage levels of the second voltage and control signals of FIG. 4 according to an embodiment of the invention.

(7) FIG. 6A, FIG. 6B, FIG. 6C and FIG. 6D respectively show the different stages of operation of the touch circuit of FIG. 4 and its signal waveforms according to different embodiments of the invention.

DESCRIPTION OF THE EMBODIMENTS

(8) Embodiments are provided below to describe the disclosure in detail, though the disclosure is not limited to the provided embodiments, and the provided embodiments could be suitably combined. The term “coupling/coupled” or “connecting/connected” used in this specification (including claims) of the application may refer to any direct or indirect connection means. For example, “a first device is coupled to a second device” should be interpreted as “the first device is directly connected to the second device” or “the first device is indirectly connected to the second device through other devices or connection means.” In addition, the term “signal” could refer to a current, a voltage, a charge, a temperature, data, electromagnetic wave or any one or multiple signals.

(9) FIG. 1 is a block diagram illustrating a touch device according to an embodiment of the invention. FIG. 2 is a schematic diagram illustrating a touch circuit of FIG. 1 according to an embodiment of the invention. Referring to FIG. 1 and FIG. 2, the touch device **100** includes a touch sensor **110**, a touch circuit **120** and a signal processing circuit **130**. The touch sensor **110** is configured to sense a touch event and output a reference current **I1** and a sensing current **I2** to the touch circuit **120**, wherein the sensing current **I2** may be generated due to a user that touches the touch sensor **110**. The touch circuit **120** is configured to receive the reference current **I1** and the sensing current **I2** and output a sensing signal **S1** to the signal processing circuit **130**, and then the sensing signal **S1** is processed by the signal processing circuit **130**.

(10) Implementation for the structures of the touch sensor **110** and the signal processing circuit **130** could be obtained, taught and suggested with reference to common knowledge in the related art.

(11) The touch circuit **120** includes an integrator circuit **122** and a compensation circuit **124**. The integrator circuit **122** is configured to generate the sensing signal **S1** according to the reference current **I1** and the sensing current **I2** and output the sensing signal **S1** to the signal processing circuit **130**.

(12) To be specific, the integrator circuit **122** includes an operational amplifier AMP and a first capacitor **Cf**. The operational amplifier AMP includes an inverting terminal, a non-inverting terminal and an output terminal. The inverting terminal of the operational amplifier AMP serves as the first terminal of the integrator circuit **122** and is coupled to the touch sensor **110**. The non-inverting terminal of the operational amplifier AMP serves as the second terminal of the integrator circuit **122** and is coupled to a first voltage **V1**. The output terminal of the operational amplifier AMP serves as the output terminal of the integrator circuit **122** and is coupled to the signal processing circuit **130**. The touch sensing signal **S1** is outputted from the output terminal of the operational amplifier AMP to the signal processing circuit **130**.

(13) The first capacitor **Cf** includes a first terminal and a second terminal. The first terminal of the first capacitor **Cf** is coupled to the inverting terminal of the operational amplifier AMP. The second terminal of the first capacitor **Cf** is coupled to the output terminal of the operational amplifier AMP.

(14) On the other hand, the compensation circuit **124** includes a second capacitor **Cc** (a compensation capacitor). The second capacitor **Cc** includes a first terminal and a second terminal. The first terminal of the second capacitor **Cc** serves as the first terminal of the compensation circuit **124** and is coupled to the inverting terminal of the operational amplifier AMP. The second terminal of the second capacitor **Cc** serves as the second terminal of the compensation circuit **124** and is coupled to the second voltage **V2**.

(15) The main purpose of the touch circuit **120** is to detect the sensing current **I2**. However, the reference current **I1** is very large compared to the sensing current **I2**, and the excessively large reference current **I1** will easily cause the integrator circuit **122** to saturate, making the touch circuit **120** unable to detect the sensing current **I2**.

(16) In the present embodiment, the compensation circuit **124** generates a compensation current **I3** by switching the first voltage **V1** and the second voltage **V2** to reduce the reference current **I1**. For example, when the touch circuit **120** senses the sensing current **I2** from the touch sensor **110**, the first voltage **V1** is increased and the second voltage **V2** is decreased, so as to increase the equivalent cross voltage change of the second capacitor **Cc**.

(17) FIG. 3 is a waveform diagram illustrating voltage levels of the first voltage and the second voltage according to an embodiment of the invention. The voltage levels of the first voltage **V1** and the second voltage **V2** may be changed as illustrated in FIG. 3. When the touch circuit **120** senses the sensing current **I2** from the touch sensor **110**, the second voltage **V2** is decreased and the voltage level of the second voltage **V2** is changed from a first level **L1** to a second level **L2**, wherein the first level **L1** is larger than the second level **L2**. The decrement is the difference $\Delta V2$.

(18) In the meanwhile, when the touch circuit **120** senses the sensing current **I2** from the touch sensor **110**, the first voltage **V1** is increased and the voltage level of the first voltage **V1** is changed from a third level **L3** to a fourth level **LA**, wherein the fourth level **LA** is larger than the third level **L3**. The increment is the difference $\Delta V1$.

(19) Therefore, the compensation charge stored in the second capacitor **Cc** is increased due to the equivalent cross voltage change of $\Delta V1 + \Delta V2$. This increase in compensation charge results in an increase in the compensation capacity, such as the compensation current **I3**, of the compensation circuit **124**. As a result, the required capacitance value of the second capacitor **Cc** for the compensation circuit **124** is reduced.

(20) FIG. 4 is a schematic diagram illustrating a touch circuit according to another embodiment of the invention. FIG. 5 is a waveform diagram illustrating voltage levels of the second voltage and control signals of FIG. 4 according to an embodiment of the invention. Referring to FIG. 4 and FIG. 5, the touch circuit **420** further includes a switch circuit **426**. The switch circuit **426** is configured to switch many times to make the second voltage **V2** switch between a first level **L1** and a second level **L2**, wherein the first level **L1** is larger than the second level **L2**.

(21) The switch circuit **426** includes a first terminal, a second terminal and a third terminal. The first terminal of the switch circuit **426** is coupled to the inverting terminal of the operational amplifier **AMP**. The second terminal of the switch circuit **426** is coupled to the first terminal of the second capacitor **Cc**. The third terminal of the switch circuit **426** is coupled to a third voltage **V3**, wherein the first voltage **V1** is larger than or equal to the third voltage **V3**, and the first voltage **V1** and the third voltage **V3** are constant voltages.

(22) To be specific, the switch circuit **426** includes a first switch **SW1** and a second switch **SW2**. The first switch **SW1** includes a first terminal, a second terminal and a control terminal. The first terminal of the first switch **SW1** serves as the first terminal of the switch circuit **426** and is coupled to the inverting terminal of the operational amplifier **AMP**. The second terminal of the first switch **SW1** serves as the second terminal of the switch circuit **426** and is coupled to the first terminal of the second capacitor **Cc**. The control terminal of the first switch **SW1** is controlled by a first control signal **Ctrl_1**.

(23) The second switch **SW2** includes a first terminal, a second terminal and a control terminal. The first terminal of the second switch **SW2** is coupled to the second terminal of the first switch. The second terminal of the second switch **SW2** serves as the third terminal of the switch circuit **426** and is coupled to the third voltage **V3**. The control terminal of the second switch **SW2** is controlled by a second control signal **Ctrl_2**.

(24) The following section describes the different stages of operation of the touch circuit **420** and its signal waveforms.

(25) FIG. 6A, FIG. 6B, FIG. 6C and FIG. 6D respectively show the different stages of operation of the touch circuit of FIG. 4 and its signal waveforms according to different embodiments of the invention. Referring to FIG. 6A to FIG. 6D, in FIG. 6A, the touch circuit **420** operates in a first stage **T1**. When the touch circuit **420** operates in the first stage **T1**, the second voltage **V2** is

changed from the first level L1 to the second level L2. The first switch SW1 is conducted, and the second switch SW2 is not conducted, so that the first terminal of the second capacitor Cc is connected to the first voltage V1, and the compensation current I3_1 is generated to reduce the reference current I1.

(26) In FIG. 6B, the touch circuit 420 operates in a second stage T2. When the touch circuit 420 operates in the second stage T2 after the first stage T1, the second voltage V2 is changed from the second level L2 to the first level L1. The first switch SW1 is not conducted, and the second switch SW2 is conducted, so that the first terminal of the second capacitor Cc is connected to the third voltage V3. The purpose of this stage is to disconnect the compensation circuit 424 from the integrator circuit 422 when the second voltage V2 is back to the first level L1 to avoid current backflow to the integrator circuit 422.

(27) In FIG. 6C, the touch circuit 420 operates in a third stage T3. When the touch circuit 420 operates in the third stage T3 after the second stage T2, the second voltage V2 is maintained as the first level L1. The first switch SW1 is conducted, and the second switch SW2 is not conducted, so that the first terminal of the second capacitor Cc is connected to the first voltage V1 again, and the compensation current I3_3 is generated to reduce the reference current I1.

(28) In FIG. 6D, the touch circuit 420 operates in a fourth stage T4. When the touch circuit 420 operates in the fourth stage T4 after the third stage T3, the second voltage V2 is changed from the first level L1 to the second level L2. The first switch SW1 is conducted, and the second switch SW2 is not conducted, so that the first terminal of the second capacitor Cc is connected to the first voltage V1, and the compensation current I3_4 is generated to reduce the reference current I1.

(29) In the present embodiment, the switch circuit 426 switches many times to make the second voltage V2 switch between the first level L1 and the second level L2. FIG. 5 shows the example of switching the second voltage V2 twice, which will change the difference voltage $\Delta V2$ by 2 times. If switching n times, it will change the difference voltage $\Delta V2$ by a factor of n. In addition, the first terminal of the second capacitor Cc is connected to the third voltage V3, so that the second capacitor Cc can store additional compensation charge $Cc \times (V1 - V3)$.

(30) In summary, in the embodiments of the invention, the compensation charge stored in the second capacitor is increased due to the equivalent cross voltage change. This increase in compensation charge results in an increase in the compensation capacity, such as the compensation current, of the compensation circuit. As a result, the required capacitance value of the second capacitor for the compensation circuit is reduced.

(31) It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed embodiments without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the disclosure covers modifications and variations provided that they fall within the scope of the following claims and their equivalents.

Claims

1. A touch circuit, comprising: an integrator circuit comprising a first terminal, a second terminal and an output terminal, wherein the first terminal of the integrator circuit is coupled to a touch sensor, and the second terminal of the integrator circuit is coupled to a first voltage; and a compensation circuit comprising a first terminal and a second terminal, wherein the first terminal of the compensation circuit is coupled to the first terminal of the integrator circuit, and the second terminal of the compensation circuit is coupled to a second voltage, wherein when the touch circuit senses a sensing current from the touch sensor, the first voltage is increased and the second voltage is decreased.

2. The touch circuit of claim 1, wherein the output terminal of the integrator circuit is coupled to a signal processing circuit, and the integrator circuit is configured to generate a sensing signal according to the sensing current and output the sensing signal to the signal processing circuit.

3. The touch circuit of claim 1, wherein the integrator circuit comprises: an operational amplifier comprising an inverting terminal, a non-inverting terminal and an output terminal, wherein the inverting terminal of the operational amplifier serves as the first terminal of the integrator circuit, the non-inverting terminal of the operational amplifier serves as the second terminal of the integrator circuit, and the output terminal of the operational amplifier serves as the output terminal of the integrator circuit; and a first capacitor comprising a first terminal and a second terminal, wherein the first terminal of the first capacitor is coupled to the inverting terminal of the operational amplifier, and the second terminal of the first capacitor is coupled to the output terminal of the operational amplifier.
4. The touch circuit of claim 3, wherein the compensation circuit comprises: a second capacitor comprising a first terminal and a second terminal, wherein the first terminal of the second capacitor serves as the first terminal of the compensation circuit and is coupled to the inverting terminal of the operational amplifier, and the second terminal of the second capacitor serves as the second terminal of the compensation circuit and is coupled to the second voltage.
5. A touch circuit, comprising: an integrator circuit comprising a first terminal, a second terminal and an output terminal, wherein the first terminal of the integrator circuit is coupled to a touch sensor, and the second terminal of the integrator circuit is coupled to a first voltage; a switch circuit comprising a first terminal, a second terminal and a third terminal, wherein the first terminal of the switch circuit is coupled to the first terminal of the integrator circuit; and a compensation circuit comprising a first terminal and a second terminal, wherein the first terminal of the compensation circuit is coupled to the second terminal of the switch circuit, and the second terminal of the compensation circuit is coupled to a second voltage, wherein the third terminal of the switch circuit is coupled to a third voltage, and the switch circuit is configured to switch many times to make the second voltage switch between a first level and a second level, wherein the first level is larger than the second level.
6. The touch circuit of claim 5, wherein the switch circuit comprises: a first switch comprising a first terminal, a second terminal and a control terminal, wherein the first terminal of the first switch serves as the first terminal of the switch circuit and is coupled to the first terminal of the integrator circuit, the second terminal of the first switch serves as the second terminal of the switch circuit and is coupled to the first terminal of the compensation circuit, and the control terminal of the first switch is controlled by a first control signal; and a second switch comprising a first terminal, a second terminal and a control terminal, wherein the first terminal of the second switch is coupled to the second terminal of the first switch, the second terminal of the second switch serves as the third terminal of the switch circuit and is coupled to the third voltage, and the control terminal of the second switch is controlled by a second control signal.
7. The touch circuit of claim 6, wherein when the touch circuit operates in a first stage, the second voltage is changed from the first level to the second level, wherein the first switch is conducted, and the second switch is not conducted in the first stage.
8. The touch circuit of claim 7, wherein when the touch circuit operates in a second stage after the first stage, the second voltage is changed from the second level to the first level, wherein the first switch is not conducted, and the second switch is conducted in the second stage.
9. The touch circuit of claim 8, wherein when the touch circuit operates in a third stage after the second stage, the second voltage is maintained as the first level, wherein the first switch is conducted, and the second switch is not conducted in the third stage.
10. The touch circuit of claim 9, wherein when the touch circuit operates in a fourth stage after the third stage, the second voltage is changed from the first level to the second level, wherein the first switch is conducted, and the second switch is not conducted in the fourth stage.
11. The touch circuit of claim 5, wherein the first voltage and the third voltage are constant voltages.
12. The touch circuit of claim 5, wherein the first voltage is larger than or equal to the third voltage.

13. The touch circuit of claim 5, wherein the output terminal of the integrator circuit is coupled to a signal processing circuit, and the integrator circuit is configured to generate a sensing signal according to the sensing current and output the sensing signal to the signal processing circuit.

14. The touch circuit of claim 5, wherein the integrator circuit comprises: an operational amplifier comprising an inverting terminal, a non-inverting terminal and an output terminal, wherein the inverting terminal of the operational amplifier serves as the first terminal of the integrator circuit, the non-inverting terminal of the operational amplifier serves as the second terminal of the integrator circuit, and the output terminal of the operational amplifier serves as the output terminal of the integrator circuit; and a first capacitor comprising a first terminal and a second terminal, wherein the first terminal of the first capacitor is coupled to the inverting terminal of the operational amplifier, and the second terminal of the first capacitor is coupled to the output terminal of the operational amplifier.

15. The touch circuit of claim 14, wherein the compensation circuit comprises: a second capacitor comprising a first terminal and a second terminal, wherein the first terminal of the second capacitor serves as the first terminal of the compensation circuit and is coupled to the second terminal of the switch circuit, and the second terminal of the second capacitor serves as the second terminal of the compensation circuit and is coupled to the second voltage.
