

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12390064

Kind Code

B2

Date of Patent

August 19, 2025

Inventor(s)

Thorne; Jason B. et al.

Cleaning apparatus with combing unit for removing debris from cleaning roller

Abstract

A cleaning apparatus includes a combing unit including a series of spaced protrusions or teeth extending into a cleaning roller for preventing build up and removing debris (such as hair, string, and the like). The protrusions extend along a substantial portion of the cleaning roller and extend partially into the cleaning roller to intercept the debris as it passes around the roller. The protrusions have angled leading edges that are not aligned with a rotation center of the cleaning roller and are directed into or against a direction of rotation of the cleaning roller. The combing unit and protrusions have a shape and configuration designed to facilitate debris removal from the cleaning roller with minimal impact on the operation of the cleaning apparatus. The cleaning apparatus may include a surface cleaning head of an upright vacuum cleaner or sweeper or a robotic vacuum cleaner.

Inventors: Thorne; Jason B. (Wellesley Hills, MA), Ming; Yao (Newton, MA), Der Marderosian; Daniel R. (Westwood, MA), Meyer; Daniel (Boston, MA), Cleary; Patrick (Allston, MA), Howes; Gordon (Suzhou, CN), Wu; David (Newton, MA), Gao Wenxiu; Nancy (Suzhou, CN)

Applicant: SHARKNINJA OPERATING LLC (Needham, MA)

Family ID: 1000008762348

Assignee: SharkNinja Operating LLC (Needham, MA)

Appl. No.: 18/131247

Filed: April 05, 2023

Prior Publication Data

Document Identifier

US 20230240492 A1

Publication Date

Aug. 03, 2023

Related U.S. Application Data

continuation parent-doc US 15492320 20170420 US 11647881 child-doc US 18131247
continuation-in-part parent-doc WO PCT/US2016/058148 20161021 PENDING child-doc US 15492320
continuation-in-part parent-doc US 15331045 20161021 US 11278171 20220322 child-doc US 15492320
us-provisional-application US 62469853 20170310
us-provisional-application US 62313394 20160325
us-provisional-application US 62248813 20151030
us-provisional-application US 62244331 20151021

Publication Classification

Int. Cl.: **A47L9/04** (20060101); **A47L5/26** (20060101); **A47L5/30** (20060101); **A47L9/06** (20060101); **A47L9/30** (20060101)

U.S. Cl.:

CPC **A47L9/0477** (20130101); **A47L5/26** (20130101); **A47L5/30** (20130101); **A47L9/0488** (20130101); **A47L9/0613** (20130101); **A47L9/30** (20130101);

Field of Classification Search

CPC: A47L (9/0477); A47L (11/4041); A47L (5/30); A47L (9/0488)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2032345	12/1935	Cranon	N/A	N/A
2411488	12/1945	White	N/A	N/A
2607062	12/1951	Le Febvre	N/A	N/A
2785431	12/1956	Pardee	N/A	N/A
4138762	12/1978	Jost et al.	N/A	N/A
4173807	12/1978	Maier	N/A	N/A
4333205	12/1981	Woodward et al.	N/A	N/A
4334337	12/1981	Miller et al.	N/A	N/A
4372004	12/1982	Vermillion	N/A	N/A
4384386	12/1982	Dorner et al.	N/A	N/A
4627127	12/1985	Dupre	N/A	N/A
4662027	12/1986	Parker et al.	N/A	N/A
4912805	12/1989	Krasznai et al.	N/A	N/A
D348548	12/1993	Pino	N/A	N/A
5452490	12/1994	Brundula et al.	N/A	N/A
5495634	12/1995	Brundula et al.	N/A	N/A
5611109	12/1996	Worwag	N/A	N/A
5632060	12/1996	Steinberg et al.	N/A	N/A

5765258	12/1997	Melito et al.	N/A	N/A
5960514	12/1998	Miller et al.	N/A	N/A
6012200	12/1999	Murphy et al.	N/A	N/A
D440019	12/2000	Mehaffey et al.	N/A	N/A
6226832	12/2000	McCormick	N/A	N/A
6237188	12/2000	Takemoto et al.	N/A	N/A
6367781	12/2001	Flynn et al.	N/A	N/A
D473687	12/2002	Kaffenberger	N/A	N/A
6550099	12/2002	Worwag	N/A	N/A
7013528	12/2005	Parker et al.	N/A	N/A
D524498	12/2005	Luebbering et al.	N/A	N/A
7171723	12/2006	Kobayashi et al.	N/A	N/A
7200893	12/2006	Gerber et al.	N/A	N/A
7316050	12/2007	Worwag	N/A	N/A
7328479	12/2007	Willenbring	N/A	N/A
7329294	12/2007	Conrad	N/A	N/A
D566356	12/2007	Medema	N/A	N/A
D569564	12/2007	Labarbera	N/A	N/A
D594612	12/2008	Umeda	N/A	N/A
D597268	12/2008	Santiago et al.	N/A	N/A
7690079	12/2009	Boddy et al.	N/A	N/A
D619315	12/2009	Ayers	N/A	N/A
7769490	12/2009	Abramson et al.	N/A	N/A
D635728	12/2010	Fjellman	N/A	N/A
7979952	12/2010	Beskow et al.	N/A	N/A
8037571	12/2010	Butts et al.	N/A	N/A
D655468	12/2011	Karsan	N/A	N/A
D668010	12/2011	Stickney et al.	N/A	N/A
8316503	12/2011	Follows et al.	N/A	N/A
8402600	12/2012	Beskow et al.	N/A	N/A
8402601	12/2012	Fahlstrom	N/A	N/A
D681291	12/2012	Morgan et al.	N/A	N/A
8418303	12/2012	Kapoor et al.	N/A	N/A
8631541	12/2013	Tran	N/A	N/A
8726441	12/2013	Colasanti et al.	N/A	N/A
8745818	12/2013	Iles et al.	N/A	N/A
8776311	12/2013	Genn et al.	N/A	N/A
8782851	12/2013	Follows et al.	N/A	N/A
8800107	12/2013	Blouin	N/A	N/A
8806710	12/2013	Follows et al.	N/A	N/A
D720104	12/2013	Santiago et al.	N/A	N/A
9021655	12/2014	Owen et al.	N/A	N/A
9027198	12/2014	Conrad	N/A	N/A
D731130	12/2014	Dyson et al.	N/A	N/A
D731134	12/2014	Dyson et al.	N/A	N/A
D731136	12/2014	Yun et al.	N/A	N/A
D731720	12/2014	Gidwell et al.	N/A	N/A
D731724	12/2014	Cheon et al.	N/A	N/A
9066640	12/2014	Iles et al.	N/A	N/A
D738583	12/2014	Gidwell et al.	N/A	N/A

D738584	12/2014	Niedzwecki	N/A	N/A
9144356	12/2014	Yun	N/A	N/A
D741558	12/2014	Kerr	N/A	N/A
D742083	12/2014	Gidwell et al.	N/A	N/A
D743123	12/2014	Chu	N/A	N/A
D745231	12/2014	Niedzwecki	N/A	N/A
D747571	12/2015	Dyson	N/A	N/A
D747572	12/2015	Kerr	N/A	N/A
9295362	12/2015	Eriksson	N/A	N/A
9314140	12/2015	Eriksson	N/A	N/A
D761507	12/2015	Heck et al.	N/A	N/A
D762031	12/2015	Niedzwecki	N/A	N/A
9451853	12/2015	Conrad et al.	N/A	N/A
D770111	12/2015	Lee et al.	N/A	N/A
9456723	12/2015	Thorne et al.	N/A	N/A
9468346	12/2015	Rzepka	N/A	N/A
D771890	12/2015	Kim	N/A	N/A
D772512	12/2015	Yoon et al.	N/A	N/A
D773139	12/2015	Palladino	N/A	N/A
D774260	12/2015	Manning	N/A	N/A
D774264	12/2015	Bartram et al.	N/A	N/A
D779751	12/2016	Chu	N/A	N/A
D779752	12/2016	Johnson	N/A	N/A
D781014	12/2016	Wu et al.	N/A	N/A
D788393	12/2016	Canas et al.	N/A	N/A
D789007	12/2016	Jang et al.	N/A	N/A
D790785	12/2016	Courtney et al.	N/A	N/A
D792665	12/2016	Salagnac	N/A	N/A
D796134	12/2016	Labarbera	N/A	N/A
D796136	12/2016	Reynolds et al.	N/A	N/A
11759069	12/2022	Gacin et al.	N/A	N/A
2002/0124334	12/2001	Worwag	N/A	N/A
2003/0106183	12/2002	Frederick et al.	N/A	N/A
2003/0145424	12/2002	Stephens et al.	N/A	N/A
2003/0159240	12/2002	Mertes et al.	N/A	N/A
2004/0045125	12/2003	Park et al.	N/A	N/A
2005/0172447	12/2004	Roney et al.	N/A	N/A
2006/0037170	12/2005	Shimizu	N/A	N/A
2006/0191097	12/2005	Baumhake	N/A	N/A
2008/0052846	12/2007	Kapoor et al.	N/A	N/A
2009/0229075	12/2008	Eriksson	N/A	N/A
2010/0107359	12/2009	Yoo	N/A	N/A
2010/0287717	12/2009	Jang	15/41.1	A47L 9/009
2010/0306958	12/2009	Follows et al.	N/A	N/A
2011/0219571	12/2010	Dyson	15/344	A47L 5/24
2011/0296648	12/2010	Kah, Jr.	N/A	N/A
2012/0000030	12/2011	Conrad	N/A	N/A
2012/0011676	12/2011	Jung et al.	N/A	N/A
2012/0169497	12/2011	Schnittman	340/540	A47L 9/106
2012/0198644	12/2011	Iles	N/A	N/A

2012/0311802	12/2011	Hinnant	N/A	N/A
2012/0311813	12/2011	Gilbert, Jr. et al.	N/A	N/A
2013/0058635	12/2012	Vrdoljak	N/A	N/A
2013/0139349	12/2012	Lles	15/383	A47L 9/0488
2013/0152337	12/2012	Thorne	N/A	N/A
2013/0212831	12/2012	Follows et al.	N/A	N/A
2013/0298350	12/2012	Schnittman et al.	N/A	N/A
2014/0060577	12/2013	Bruders et al.	N/A	N/A
2014/0150201	12/2013	McGee et al.	N/A	N/A
2014/0150202	12/2013	Schultheis	N/A	N/A
2014/0196247	12/2013	Kasper et al.	N/A	N/A
2014/0237760	12/2013	Conrad	N/A	N/A
2014/0259475	12/2013	Doughty	N/A	N/A
2014/0259521	12/2013	Kowalski	N/A	N/A
2015/0013102	12/2014	Bilger	N/A	N/A
2015/0033498	12/2014	McVey	N/A	N/A
2015/0040340	12/2014	Bilger et al.	N/A	N/A
2015/0135474	12/2014	Gidwell	N/A	N/A
2015/0289735	12/2014	Van Der Kooi	15/383	A47L 9/02
2015/0297054	12/2014	Weeks et al.	N/A	N/A
2015/0351596	12/2014	Thorne	N/A	N/A
2015/0359396	12/2014	Yun	N/A	N/A
2016/0058257	12/2015	Ventress et al.	N/A	N/A
2016/0128530	12/2015	Thorne et al.	N/A	N/A
2016/0174793	12/2015	Burke et al.	N/A	N/A
2016/0220080	12/2015	Thorne	N/A	N/A
2016/0220081	12/2015	Xu et al.	N/A	N/A
2016/0220082	12/2015	Thorne et al.	N/A	N/A
2016/0324388	12/2015	Vrdoljak et al.	N/A	N/A
2016/0345795	12/2015	Manning	N/A	N/A
2016/0374533	12/2015	Innes et al.	N/A	N/A
2017/0042319	12/2016	Conrad et al.	N/A	N/A
2017/0079493	12/2016	Genn et al.	N/A	N/A
2017/0112343	12/2016	Innes et al.	N/A	N/A
2017/0127896	12/2016	Carter et al.	N/A	N/A
2017/0144810	12/2016	Birdsell	N/A	N/A
2017/0172363	12/2016	Eriksson et al.	N/A	N/A
2017/0209008	12/2016	Isley et al.	N/A	N/A
2017/0215667	12/2016	Thorne et al.	N/A	N/A
2017/0231445	12/2016	Kasper	N/A	N/A
2017/0280957	12/2016	Jeong et al.	N/A	N/A
2017/0332859	12/2016	Nam et al.	N/A	N/A
2017/0347848	12/2016	Carter et al.	N/A	N/A
2018/0035854	12/2017	Thorne	N/A	N/A
2018/0064301	12/2017	Cottrell et al.	N/A	N/A
2018/0068815	12/2017	Cottrell	N/A	N/A
2018/0070785	12/2017	Udy et al.	N/A	N/A
2018/0199784	12/2017	Schnittman et al.	N/A	N/A

2018/0255991	12/2017	Der Marderosian et al.	N/A	N/A
2018/0296046	12/2017	Thorne et al.	N/A	N/A
2018/0306432	12/2017	Ognjen et al.	N/A	N/A
2018/0325252	12/2017	Hopke et al.	N/A	N/A
2018/0338654	12/2017	Kelsey	N/A	N/A
2018/0338656	12/2017	Carter et al.	N/A	N/A
2019/0038098	12/2018	Thorne et al.	N/A	N/A
2019/0059668	12/2018	Thorne et al.	N/A	N/A
2019/0069740	12/2018	Thorne et al.	N/A	N/A
2019/0069744	12/2018	Liggett et al.	N/A	N/A
2019/0090701	12/2018	Tonderys et al.	N/A	N/A
2019/0090705	12/2018	Thorne et al.	N/A	N/A
2019/0191947	12/2018	Freese et al.	N/A	N/A
2019/0193120	12/2018	Brown et al.	N/A	N/A
2019/0246853	12/2018	Sardar et al.	N/A	N/A
2019/0274500	12/2018	Thorne et al.	N/A	N/A
2019/0274501	12/2018	Antonisami et al.	N/A	N/A
2019/0298123	12/2018	Conrad et al.	N/A	N/A
2019/0302793	12/2018	Leech et al.	N/A	N/A
2019/0307302	12/2018	Zheng et al.	N/A	N/A
2019/0320865	12/2018	Brown et al.	N/A	N/A
2019/0320866	12/2018	Thorne et al.	N/A	N/A
2019/0335968	12/2018	Harting et al.	N/A	N/A
2019/0343349	12/2018	Clare et al.	N/A	N/A
2019/0357740	12/2018	Thorne et al.	N/A	N/A
2020/0000298	12/2019	Brown et al.	N/A	N/A
2020/0022543	12/2019	Gill et al.	N/A	N/A
2020/0022544	12/2019	Gill et al.	N/A	N/A
2020/0022553	12/2019	Gill et al.	N/A	N/A
2020/0037833	12/2019	Niedzwecki et al.	N/A	N/A
2020/0037843	12/2019	Fiebig et al.	N/A	N/A
2020/0046184	12/2019	Freese et al.	N/A	N/A
2020/0077855	12/2019	Brown et al.	N/A	N/A
2020/0085267	12/2019	Liu	N/A	N/A
2020/0085269	12/2019	Thorne	N/A	N/A
2020/0121144	12/2019	Gacin et al.	N/A	N/A
2020/0121148	12/2019	Hoffman et al.	N/A	N/A
2020/0138260	12/2019	Sutter et al.	N/A	N/A
2020/0166949	12/2019	Leech et al.	N/A	N/A
2020/0170470	12/2019	Liggett et al.	N/A	N/A
2020/0201348	12/2019	Leech	N/A	N/A
2020/0205631	12/2019	Brown et al.	N/A	N/A
2020/0205634	12/2019	Sutter et al.	N/A	N/A
2020/0275812	12/2019	Burbank et al.	N/A	N/A
2020/0297172	12/2019	Tonderys et al.	N/A	N/A
2021/0169289	12/2020	Thorne et al.	N/A	N/A
2021/0254615	12/2020	Vrdoljak et al.	N/A	N/A
2021/0307581	12/2020	Thorne et al.	N/A	N/A
2022/0071459	12/2021	Gacin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201861563	12/2010	CN	N/A
201861563	12/2010	CN	N/A
102188197	12/2010	CN	N/A
203662686	12/2013	CN	N/A
104138238	12/2013	CN	N/A
104703525	12/2014	CN	N/A
205181249	12/2015	CN	N/A
205181249	12/2015	CN	N/A
206080407	12/2016	CN	N/A
206080407	12/2016	CN	N/A
106963290	12/2016	CN	N/A
10302525	12/2005	DE	N/A
102010017211	12/2010	DE	N/A
102010017258	12/2010	DE	N/A
0042370	12/1980	EP	N/A
0909547	12/1998	EP	N/A
1994869	12/2007	EP	N/A
2289381	12/2010	EP	N/A
2218385	12/2012	EP	N/A
2543301	12/2012	EP	N/A
2941994	12/2014	EP	N/A
3073881	12/2015	EP	N/A
3187083	12/2016	EP	N/A
360577	12/1930	GB	N/A
516291	12/1938	GB	N/A
583738	12/1945	GB	N/A
877778	12/1960	GB	N/A
2109224	12/1982	GB	N/A
228577	12/1994	GB	N/A
2476811	12/2010	GB	N/A
2509925	12/2013	GB	N/A
2529819	12/2015	GB	N/A
S507359	12/1974	JP	N/A
S59174143	12/1983	JP	N/A
03228721	12/1990	JP	N/A
05228083	12/1992	JP	N/A
H06284991	12/1993	JP	N/A
H07322981	12/1994	JP	N/A
2639155	12/1996	JP	N/A
H10127542	12/1997	JP	N/A
H10201682	12/1997	JP	N/A
H11028178	12/1998	JP	N/A
H11187997	12/1998	JP	N/A
2000033059	12/1999	JP	N/A
2000033059	12/1999	JP	N/A
2000139786	12/1999	JP	N/A
2001120473	12/2000	JP	N/A

2003339589	12/2002	JP	N/A
2004222912	12/2003	JP	N/A
2005046262	12/2004	JP	N/A
2006247229	12/2005	JP	N/A
2006312066	12/2005	JP	A47L 9/04
2007068835	12/2006	JP	N/A
2008000382	12/2007	JP	N/A
2008043351	12/2007	JP	N/A
2009045503	12/2008	JP	N/A
2010246848	12/2009	JP	N/A
2011050428	12/2010	JP	N/A
2011188951	12/2010	JP	N/A
2013013590	12/2012	JP	N/A
2013052238	12/2012	JP	N/A
2014033738	12/2013	JP	N/A
2014509211	12/2013	JP	N/A
2015000210	12/2014	JP	N/A
2015116414	12/2014	JP	N/A
2016504100	12/2015	JP	N/A
2017074258	12/2016	JP	N/A
2017121468	12/2016	JP	N/A
20040052092	12/2003	KR	N/A
20050099416	12/2004	KR	N/A
100593324	12/2005	KR	N/A
9210967	12/1991	WO	N/A
0141618	12/2000	WO	N/A
2009117383	12/2008	WO	N/A
2011083294	12/2010	WO	N/A
2013104886	12/2012	WO	N/A
2014131105	12/2013	WO	N/A
2014131106	12/2013	WO	N/A
2014177216	12/2013	WO	N/A
2015015166	12/2014	WO	N/A
2015015167	12/2014	WO	N/A
2015075481	12/2014	WO	N/A
2016034848	12/2015	WO	N/A
2017070492	12/2016	WO	N/A
2019139846	12/2018	WO	N/A

OTHER PUBLICATIONS

Chinese Second Office Action with English Summary issued May 10, 2023, received in Chinese Patent Application No. 202111186082.X, 17 pages. cited by applicant

Chinese Office Action with machine generated English translation issued May 27, 2023, received in Chinese Patent Application No. 202210128813.3, 19 pages. cited by applicant

Chinese Office Action with English Summary issued Jun. 19, 2023, received in Chinese Patent Application No. 201711405708.5, 10 pages. cited by applicant

Chinese Office Action with English Summary issued Jul. 15, 2023, received in Chinese Patent Application No. 202210063972X, 16 pages. cited by applicant

Japanese Office Action with English translation issued Apr. 22, 2022, received in Japanese Application No. 2021-521415, 13 pages. cited by applicant

Chinese Office Action with English translation, issued May 22, 2020, received in China Application No. 201810965394.2, 20 pgs. cited by applicant

Chinese Office Action with English translation, issued May 26, 2020, received in China Application No. 201810516731.X, 13 pgs. cited by applicant

Korean Office Action with English translation, issued Aug. 31, 2020, received in Korean Application No. 10-2020-7018384, 7 pgs. cited by applicant

Chinese Office Action with English translation, issued Oct. 15, 2020, received in China Application No. 201610921399.6, 21 pgs. cited by applicant

Australian Examination Report issued Jun. 11, 2020, received in Australian Application No. 2019246800, 7 pgs. cited by applicant

European Search Report issued Nov. 27, 2020, received in EP Application No. 18806820.9, 7 pgs. cited by applicant

US Office Action issued May 21, 2020, received in U.S. Appl. No. 15/331,045, 14 pgs. cited by applicant

US Office Action issued Nov. 2, 2020, received in U.S. Appl. No. 15/987,589, 15 pgs. cited by applicant

Japanese Office Action with English translation, issued Jan. 21, 2021, received in JP Application No. 2017-557189, 27 pgs. cited by applicant

UK Examination Report issued Sep. 20, 2022, received in UK Patent Application No. 1915155.4, 4 pages. cited by applicant

UK Examination Report issued Oct. 24, 2022, received in UK Patent Application No. 2212062.0, 4 pages. cited by applicant

US Office Action issued Oct. 20, 2022, received in U.S. Appl. No. 16/656,930, 11 pages. cited by applicant

Chinese Office Action with English translation issued Oct. 18, 2022, received in Chinese Patent Application No. 202210128813.3, 14 pages. cited by applicant

Australian Examination Report issued Nov. 15, 2022, received in Australian Patent Application No. 2021232679, 5 pages. cited by applicant

PCT Search Report and Written Opinion mailed Dec. 26, 2018, received in PCT Application No. PCT/US18/47525, 14 pgs. cited by applicant

Australian Examination Report issued Oct. 23, 2018, received in AU Application No. 2016341998, 5 pgs. cited by applicant

Australian Examination Report issued Oct. 16, 2018, received in AU Application No. 2016342001, 5 pgs. cited by applicant

EP Search Report issued Nov. 27, 2020, received in EP Application No. 18806820.9, 7 pgs. cited by applicant

Extended European Search Report issued Mar. 28, 2019, received in EP Application No. 16858305.2, 7 pgs. cited by applicant

English translation of Japanese Office Action mailed May 21, 2019, received in Japanese Application No. 2018-520541, 11 pgs. cited by applicant

English translation of Korean Office Action issued Apr. 30, 2019, received in Korean Application No. 10-2018-7014180, 11 pgs. cited by applicant

US Office Action mailed May 3, 2019, received in U.S. Appl. No. 15/331,045, 9 pgs. cited by applicant

Extended European Search Report issued Apr. 3, 2019, received in EP Application No. 16858308.6, 7 pgs. cited by applicant

English translation of Japanese Office Action mailed Apr. 1, 2019, received in Japanese Application No. 2017-557189, 6 pgs. cited by applicant

English translation of Japanese Office Action mailed Dec. 2, 2019, received in JP Application No. 2018-520541, 6 pgs. cited by applicant

English translation of Korean Office Action mailed Nov. 27, 2019, received in Korean Application No. 10-2018-7014180, 5 pgs. cited by applicant

US Office Action mailed Sep. 17, 2019, received in U.S. Appl. No. 15/685,456, 11 pgs. cited by applicant

Chinese Office Action with English translation issued Jan. 2, 2020, received in Chinese Patent Application No. 201680061488.6, 11 pgs. cited by applicant

English translation of Japanese Decision of Rejection mailed Jan. 6, 2020, received in Japanese Application No. 2017-557189, 5 pgs. cited by applicant

Chinese Office Action with English translation issued Feb. 25, 2020, received in Chinese Patent Application No. 201610921399.6, 18 pgs. cited by applicant

Chinese Office Action with English translation issued Mar. 2, 2020, received in Chinese Patent Application No. 201711481216.4, 16 pgs. cited by applicant

Korean Office Action with machine translation issued Jan. 18, 2022, received in Korean Patent Application No. 10-2019-7034239, 10 pages. cited by applicant

Chinese Office Action with English summary issued Dec. 26, 2022, received in Chinese Patent Application No. 202210063972X, 10 pages. cited by applicant

US Office Action mailed Feb. 23, 2023, received in U.S. Appl. No. 17/556,992, 14 pages. cited by applicant

Chinese Office Action with English translation issued Mar. 25, 2020, received in Chinese Patent Application No. 201711405708.5, 11 pgs. cited by applicant

US Office Action mailed Mar. 17, 2020, received in U.S. Appl. No. 15/768,879, 25 pgs. cited by applicant

Chinese Office Action with English translation issued Feb. 18, 2022, received in Chinese Application No. 202110712842.X, 13 pages. cited by applicant

UK Examination Report issued Mar. 30, 2022, received in UK Application No. GB191515.4, 5 pages. cited by applicant

Australian Examination Report issued Mar. 17, 2022, received in Australian Application No. 2019362030, 3 pages. cited by applicant

PCT Search Report and Written Opinion mailed Aug. 23, 2018, received in PCT Application No. PCT/US18/34320, 11 pgs. cited by applicant

PCT Search Report and Written Opinion mailed Jul. 18, 2018, received in PCT Application No. PCT/US18/28635, 16 pgs. cited by applicant

English translation of Korean Office Action dated May 31, 2019, received in Korean Application No. 10-2018-7014186, 8 pgs. cited by applicant

Extended European Search Report dated Jun. 17, 2022, received in European Patent Application No. 19872356.1, 6 pages. cited by applicant

Chinese Office Action with English Machine Translation dated Jun. 28, 2022, received in Chinese Patent Application No. 202111186082.X, 14 pages. cited by applicant

Chinese Office Action with English Translation issued Jun. 24, 2022, received in Chinese Patent Application No. 2019800688188, 16 pages. cited by applicant

Korean Office Action with English Machine Translation dated Aug. 1, 2022, received in Korean Patent Application No. 10-2021-7014906, 12 pages. cited by applicant

Chinese Office Action with English Machine Translation issued Aug. 10, 2022, received in Chinese Patent Application No. 202110712842.X, 20 pages. cited by applicant

Canadian Office Action issued Jul. 25, 2022, received in Canadian Patent Application No. 3,117,040, 3 pages. cited by applicant

US Office Action issued Feb. 27, 2024, received in U.S. Appl. No. 18/225,138, 9 pages. cited by applicant

Extended European Search Report issued Apr. 2, 2024, received in European Patent Application No. 21865202.2, 9 pages. cited by applicant

Chinese Decision of Rejection issued May 7, 2021, received in China Application No. 201680061488.6, 9 pgs. cited by applicant

Australian Examination Report issued Aug. 31, 2023, received in Australian Patent Application No. 2022202981, 4 pages. cited by applicant

Chinese Office Action with English translation, issued Jul. 31, 2020, received in China Application No. 201610921399.6, 21 pgs. cited by applicant

PCT International Search Report and Written Opinion mailed Mar. 31, 2016, received in corresponding PCT Application No. PCT/US16/15370, 15 pgs. cited by applicant

3rd Party Observation filed Jul. 13, 2020 in EP Application No. 20160744107, 7 pgs. cited by applicant

US Office Action mailed Feb. 22, 2016, received in related U.S. Appl. No. 14/744,438, 29 pgs. cited by applicant

International Search Report and Written Opinion issued on Mar. 17, 2017 in corresponding PCT Patent Application No. PCT/US 16/58155, 12 pgs. cited by applicant

International Search Report and Written Opinion issued on Mar. 24, 2017 in corresponding PCT Patent Application No. PCT/US 16/58148, 14 pgs. cited by applicant

US Office Action issued Jun. 7, 2024, received in U.S. Appl. No. 18/519,793, 9 pages. cited by applicant

US Office Action issued Jul. 11, 2024, received in U.S. Appl. No. 18/225,138, 10 pages. cited by applicant

US Office Action issued Jul. 16, 2024, received in U.S. Appl. No. 18/539,078, 13 pages. cited by applicant

Extended European Search Report dated Aug. 5, 2024, received in European Patent Application No. 23220030.3, 6 pages. cited by applicant

Canadian Examiner Report issued Feb. 8, 2021, received in Canada Patent Application No. 3,064,747, 4 pages. cited by applicant

Korean Office Action with English translation issued Mar. 19, 2021, received in Korean Patent Application No. 10-2020-7006909, 15 pages. cited by applicant

Japanese Office Action with English translation mailed Mar. 22, 2021, received in Japanese Patent Application No. 2020-510098, 15 pages. cited by applicant

Chinese Office Action with English translation issued Jan. 6, 2021, received in Chinese Patent Application No. 201711481216.4, 11 pages. cited by applicant

Japanese Office Action with English translation mailed Jan. 26, received in Japanese Patent Application No. 2019-564874, 9 pages. cited by applicant

Chinese Office Action with English translation issued Apr. 13, 2021, received in Chinese Patent Application No. 201810516731.X, 13 pages. cited by applicant

Japanese Office Action with English translation issued Jan. 26, 2021, received in Japanese Patent Application No. 2019-556824, 11 pages. cited by applicant

Australian Examination Report issued Jun. 24, 2021, received in Australian Patent Application No. 2021201452, 6 pages. cited by applicant

Chinese Decision of Rejection with English translation issued Jun. 8, 2021 received in Chinese Patent Application No. 201711405708.5, 6 pages. cited by applicant

Office Action issued May 3, 2021, received in Canadian Patent Application No. 3,073,677, 6 pages. cited by applicant

Japanese Office Action with English translation mailed Jul. 9, 2021, received in Japanese Patent Application No. 2020-080880, 8 pages. cited by applicant

Australian Examination Report issued May 5, 2021, received in Australian Patent Application No. 2021201726, 3 pages. cited by applicant

Chinese Office Action with English translation issued Aug. 31, 2021, received in Chinese Patent Application No. 202011084724.0, 8 pages. cited by applicant

European Extended Search Report issued Jul. 13, 2021, received in European Patent Application No. 18848114.7, 5 pages. cited by applicant
Korean Office Action with English translation issued Aug. 2, 2021, received in Korean Patent Application No. 10-2020-7006909, 14 pages. cited by applicant
Chinese Office Action with English translation issued Dec. 9, 2020, received in Chinese Patent Application No. 201711405708.5, 7 pages. cited by applicant
Australian Examination Report issued Nov. 3, 2023, received in Australian Patent Application No. 2021232679, 3 pages. cited by applicant
Australian Examination Report issued Nov. 17, 2023, received in Australian Patent Application No. 2022204276, 3 pages. cited by applicant
Korean Office Action with machine-generated English language translation issued Dec. 6, 2023, received in Korean Patent Application No. 10-2023-7011563, 13 pages. cited by applicant
US Office Action issued on Nov. 30, 2023, received in U.S. Appl. No. 16/921,350, 12 pages. cited by applicant
U.S. Office Action issued Jan. 13, 2025, received in U.S. Appl. No. 18/225,138, 10 pages. cited by applicant

Primary Examiner: Muller; Bryan R

Attorney, Agent or Firm: Grossman Tucker Perreault & Pflieger, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application claims the benefit of U.S. Provisional Application No. 62/469,853, filed Mar. 10, 2017 and is a continuation-in-part of U.S. patent application Ser. No. 15/331,045, filed Oct. 21, 2016, which claims the benefit of U.S. Provisional Patent Application Ser. No. 62/244,331 filed Oct. 21, 2015, U.S. Provisional Patent Application Ser. No. 62/248,813 filed Oct. 30, 2015, and U.S. Provisional Patent Application Ser. No. 62/313,394 filed Mar. 25, 2016, all of which are fully incorporated herein by reference. The present application is also a continuation-in-part of International Application No. PCT/US2016/058148, filed on Oct. 21, 2016, which is fully incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to cleaners with cleaning rollers and more particularly, to a cleaning apparatus, such as a surface cleaning head for a vacuum cleaner, with a combing unit for removing debris from a cleaning roller such as a leading roller.

BACKGROUND INFORMATION

(2) Vacuum cleaners generally include a suction conduit with an opening on the underside of a surface cleaning head for drawing air (and debris) into and through the surface cleaning head. One of the challenges with vacuum cleaner design is to control engagement of the suction conduit with a surface being cleaned to provide the desired amount of suction. If the suction conduit is spaced too far from a surface, the suction may be less because the air is flowing into the suction conduit through a greater surface area. If the suction conduit is directly engaged with the surface and thus scaled on all sides, air will stop flowing into the suction conduit and the suction motor may be damaged as a result.

(3) Vacuum cleaners also generally use agitation to loosen debris and facilitate capturing the debris in the flow of air into the suction conduit. Agitators are often used in the suction conduit of a surface cleaning head proximate a dirty air inlet to cause the agitated debris to flow into the dirty air inlet. If the agitator in the suction conduit is unable to loosen the debris or if the debris is too

small, the suction conduit may pass over the debris without removing the debris from the surface. In other cases, the surface cleaning head may push larger debris forward without ever allowing the debris to be captured in the flow into the suction conduit (sometimes referred to as snowplowing). (4) One example of an agitator is a cleaning roller such as a brush roll. A cleaning roller may be located within a suction conduit and/or may be located at a leading side of a suction conduit (e.g., a leading roller). One challenge with a leading roller in particular is the debris (e.g., hair) that becomes entangled around the roller. Projections may be used to engage the roller to facilitate removal of debris, but existing structures are often not effective and/or interfere with the operation of the surface cleaning head.

SUMMARY

(5) Consistent with an embodiment, a cleaning apparatus includes a housing defining an opening on an underside of the housing for receiving debris, a cleaning roller mounted in the housing for directing debris into the opening, and a combing unit extending a substantial length of a cleaning surface of the cleaning roller and in contact with the cleaning roller. The combing unit includes a series of spaced combing protrusions extending partially into the cleaning roller and having angled leading edges that are not aligned with a center of rotation of the cleaning roller. The angled leading edges are directed into a direction of rotation of the cleaning roller.

(6) Consistent with another embodiment, a surface cleaning head includes a housing having a front side and back side. The housing defines a suction conduit with an opening on an underside of the housing between the front side and the back side. A brush roll is rotatably mounted to the housing within the suction conduit and at least a portion of the brush roll is proximate the opening of the suction conduit. A leading roller is mounted to the housing in front of the brush roll and adjacent the opening of the suction conduit. A front portion of the leading roller is at least partially exposed at the front side of the housing. The surface cleaning head also includes a combing unit extending a substantial length of a cleaning surface of the leading roller and in contact with the leading roller. The combing unit includes a series of spaced combing protrusions extending partially into the leading roller and having angled leading edges that are not aligned with a center of rotation of the leading roller. The angled leading edges are directed toward a direction of rotation of the leading roller.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) These and other features and advantages will be better understood by reading the following detailed description, taken together with the drawings wherein:

(2) FIG. 1 is a perspective view of a surface cleaning head including dual agitators and combing protrusions, consistent with an embodiment of the present disclosure.

(3) FIG. 2 is a side cross-sectional view of the surface cleaning head shown in FIG. 1 showing a flow path through a suction conduit.

(4) FIG. 3 is an enlarged side cross-sectional view illustrating the leading roller and brush roll of the surface cleaning head shown in FIG. 1.

(5) FIG. 4 is an enlarged side cross-sectional view illustrating a leading roller and combing protrusions in the surface cleaning head shown in FIG. 1.

(6) FIG. 5 is a front perspective view of the front region of the surface cleaning head of FIG. 1 without the leading roller and illustrating the combing protrusions.

(7) FIG. 6 is an enlarged perspective view of one embodiment of a plurality of combing protrusions.

(8) FIG. 7 is a front bottom view of the front region of the surface cleaning head of FIG. 1 without the leading roller.

- (9) FIG. 8 is a front view the surface cleaning head of FIG. 1.
- (10) FIG. 9 is a bottom view the surface cleaning head of FIG. 1.
- (11) FIG. 10 is a perspective cross sectional view of combing protrusions engaging a cleaning roller, consistent with an embodiment of the present disclosure.
- (12) FIG. 11 is a side cross-sectional view of the combing protrusions engaging the cleaning roller.
- (13) FIG. 12 is a side perspective view of the combing protrusions shown in FIG. 10.
- (14) FIG. 13 is a top perspective view of a section of the combing protrusions shown in FIG. 10.
- (15) FIGS. 14A-14D are top, front, bottom and side views of the section of combing protrusions shown in FIG. 13.
- (16) FIG. 15A is a side cross-sectional view of the combing protrusions engaging a cleaning roller above an axis of rotation, consistent with another embodiment.
- (17) FIG. 15B is a side cross-sectional view of a combing protrusion having a curved leading edge engaging a cleaning roller, consistent with a further embodiment.
- (18) FIG. 16 is a perspective view of an upright vacuum cleaner including a surface cleaning head with dual rotating agitators and combing protrusions, consistent with embodiments of the present disclosure.
- (19) FIG. 17 is a perspective view of a stick type vacuum cleaner including a surface cleaning head with dual rotating agitators and combing protrusions, consistent with embodiments of the present disclosure.
- (20) FIG. 18 is a bottom perspective view of a robotic vacuum cleaner including a cleaning roller and combing protrusions, consistent with yet another embodiment of the present disclosure.

DETAILED DESCRIPTION

- (21) A cleaning apparatus, consistent with embodiments of the present disclosure, includes a combing unit (also referred to as a debriding unit or rib) including a series of spaced protrusions or teeth extending into a cleaning roller for preventing build up and removing debris (such as hair, string, and the like). The protrusions extend along a substantial portion of the cleaning roller and extend partially into the cleaning roller to intercept the debris as it passes around the roller. The protrusions have angled leading edges that are not aligned with a rotation center of the cleaning roller and are directed into or against a direction of rotation of the cleaning roller. The combing unit and protrusions have a shape and configuration designed to facilitate debris removal from the cleaning roller with minimal impact on the operation of the cleaning apparatus. The cleaning apparatus may include a surface cleaning head of an upright vacuum cleaner or sweeper or a robotic vacuum cleaner.
- (22) An embodiment of a surface cleaning head may include dual rotating agitators (e.g., a leading roller and a brush roll) and may be used to facilitate capturing of debris in the air flow into a suction conduit on the underside of the surface cleaning head. In this embodiment, the leading roller is generally positioned adjacent to and in advance of the opening of the suction conduit such that the leading roller engages debris and moves the debris toward the opening. At least a top half of the leading roller may be substantially outside of the flow path to the suction conduit and a bottom portion of the leading roller may be exposed to the flow path to the suction conduit. The rotating brush roll may be located in the suction conduit with the leading roller located in front of and spaced from the brush roll, forming an inter-roller air passageway between lower portions of the leading roller and the brush roll. In some embodiments, combing protrusions may contact the leading roller above the inter-roller air passageway to facilitate debris removal into the flow path. The surface cleaning head may also include a leading bumper that extends in front of the leading roller to protect a front portion of the leading roller and facilitate front edge cleaning.
- (23) Although specific embodiments of a surface cleaning head with a leading roller are shown, other embodiments of a cleaning apparatus with a combing unit are within the scope of the present disclosure. The cleaning apparatus with the combing unit may be used in different types of vacuum cleaners including, without limitation, an “all in the head” type vacuum, upright vacuum cleaners,

canister vacuum cleaners, stick vacuum cleaners, robotic vacuum cleaners and central vacuum systems, and may be used in sweepers (e.g., low or no suction). The surface cleaning head with a leading roller may also include removable agitators (e.g., brush rolls) in openable agitator chambers, such as the type described in greater detail in U.S. Pat. No. 9,456,723 and U.S. Patent Application Pub. No. 2016/0220082, which are commonly-owned and fully incorporated herein by reference. The leading roller may be similarly removable.

(24) As used herein, a “surface cleaning head” refers to a device configured to contact a surface for cleaning the surface by use of suction air flow, agitation, or a combination thereof. A surface cleaning head may be pivotably or steeringly coupled by a swivel connection to a wand for controlling the surface cleaning head and may include motorized attachments as well as fixed surface cleaning heads. A surface cleaning head may also be operable without a wand or handle. As used herein, “seal” or “sealing” refers to preventing a substantial amount of air from passing through to the suction conduit but does not require an air tight seal. As used herein, “agitator” refers to any element, member or structure capable of agitating a surface to facilitate movement of debris into a suction air flow in a surface cleaning head. As used herein, “soft” and “softer” refer to the characteristics of a cleaning element being more compliant or pliable than another cleaning element. As used herein, the term “flow path” refers to the path taken by air as it flows into a suction conduit when drawn in by suction. As used herein, the terms “above” and “below” are used relative to an orientation of the surface cleaning head on a surface to be cleaned and the terms “front” and “back” are used relative to a direction that a user pushes the surface cleaning head on a surface being cleaned (i.e., back to front). As used herein, the term “leading” refers to a position in front of at least another component but does not necessarily mean in front of all other components.

(25) Referring to FIGS. 1-9, an embodiment of a surface cleaning head **100** with dual agitators and a combing unit is shown and described. The surface cleaning head **100** includes a housing **110** with a front side **112**, and a back side **114**, left and right sides **116a**, **116b**, an upper side **118**, and a lower or under side **120**. The housing **110** defines a suction conduit **128** having an opening **127** on the underside **120** of the housing (shown in FIGS. 2 and 3). The suction conduit **128** is fluidly coupled to a dirty air inlet **129**, which leads to a suction motor (not shown) either in the surface cleaning head **100** or another location in the vacuum. The suction conduit **128** is the interior space defined by interior walls in the housing **110**, which receives and directs air drawn in by suction, and the opening **127** is where the suction conduit **128** meets the underside **120** of the housing **110**.

(26) The surface cleaning head **100** includes dual rotating agitators **122**, **124**, for example, a brush roll **122** and a leading roller **124**. The brush roll **122** and leading roller **124** may be configured to rotate about first and second rotating axes (RA1, RA2). The rotating brush roll **122** is at least partially disposed within the suction conduit **128** (shown in FIGS. 2 and 3). The leading roller **124** is positioned in front of and spaced from the brush roll **122** and at least substantially outside the suction conduit **128**. In some embodiments, at least an inside upper portion (e.g., upper half) of the leading roller **124** is not exposed to the primary air flow path (e.g., arrow **40**) into the opening **127** of the suction conduit **128** while at least an inside of the bottom portion of the leading roller **124** is exposed to the primary flow path into the opening **127** of the suction conduit **128**.

(27) Other variations are possible where different portions of the leading roller **124** may be exposed or not exposed to the flow path into the suction conduit **128**. In other embodiments, for example, a flow path may allow air to flow over the upper portion of the leading roller **124**. The leading roller **124** may rotate about the second rotation axis RA2 located within a leading roller chamber **126**. The leading roller chamber **126** may have a size and shape slightly larger than the cylindrical projection of the leading roller **124** when the leading roller **124** is rotating therein, for example, to form the flow path over the upper portion.

(28) The surface cleaning head **100** may include one or more wheels **130** for supporting the housing on the surface **10** to be cleaned. The brush roll **122** may be disposed in front of one or more wheels **130**, **132** (see FIGS. 1 and 9) for supporting the housing **110** on the surface **10** to be

cleaned. For example, one or more larger wheels **130** may be disposed along the back side **114** and/or one or more smaller middle wheels **132** may be provided at a middle section on the underside **116** of the housing **110** and/or along the left and right sides **116a**, **116b**. Other wheel configurations may also be used. The wheels **130**, **132** facilitate moving the surface cleaning head **100** along the surface **10** to be cleaned, and may also allow the user to easily tilt or pivot the surface cleaning head **100** (e.g., brush roll **122** and/or the leading roller **124**) off of the surface **10** to be cleaned. The rear wheel(s) **130** and the middle wheel(s) **132** may provide the primary contact with the surface being cleaned and thus primarily support the surface cleaning head **100**. When the surface cleaning head **100** is positioned on the surface **10** being cleaned, the leading roller **124** may also rest on the surface **10** being cleaned. In other embodiments, the leading roller **124** may be positioned such that the leading roller **124** sits just above the surface being cleaned.

(29) The rotating brush roll **122** may have bristles, fabric, or other cleaning elements, or any combination thereof around the outside of the brush roll **122**. Examples of brush rolls and other agitators are shown and described in greater detail in U.S. Pat. No. 9,456,723 and U.S. Patent Application Pub. No. 2016/0220082, which are fully incorporated herein by reference.

(30) The leading roller **124** may include a relatively soft material (e.g., soft bristles, fabric, felt, nap or pile) arranged in a pattern (e.g., a spiral pattern) to facilitate capturing debris, as will be described in greater detail below. The leading roller **124** may be selected to be substantially softer than that of the brush roll **122**. The softness, length, diameter, arrangement, and resiliency of the bristles and/or pile of the leading roller **124** may be selected to form a seal with a hard surface (e.g., but not limited to, a hard wood floor, tile floor, laminate floor, or the like), whereas the bristles of the brush roll **122** may be selected to agitate carpet fibers or the like. For example, the leading roller **124** may be at least 25% softer than the brush roll **122**, alternatively the leading roller **124** may be at least 30% softer than the brush roll **122**, alternatively the leading roller **124** may be at least 35% softer than the brush roll **122**, alternatively the leading roller **124** may be at least 40% softer than the brush roll **122**, alternatively the leading roller **124** may be at least 50% softer than the brush roll **122**, alternatively the leading roller **124** may be at least 60% softer than the brush roll **122**. Softness may be determined, for example, based on the pliability of the bristles or pile being used.

(31) The size and shape of the bristles and/or pile may be selected based on the intended application. For example, the leading roller **124** may include bristles and/or pile having a length of between 5 to 15 mm (e.g., 7 to 12 mm) and may have a diameter of 0.01 to 0.04 mm (e.g., 0.01-0.03 mm). According to one embodiment, the bristles and/or pile may have a length of 9 mm and a diameter of 0.02 mm. The bristles and/or pile may have any shape. For example, the bristles and/or pile may be linear, arcuate, and/or may have a compound shape. According to one embodiment, the bristles and/or pile may have a generally U and/or Y shape. The U and/or Y shaped bristles and/or pile may increase the number of points contacting the floor surface **10**, thereby enhancing sweeping function of leading roller **124**. The bristles and/or pile may be made on any material such as, but not limited to, Nylon 6 or Nylon 6/6.

(32) Optionally, the bristles and/or pile of leading roller **124** may be heat treated, for example, using a post weave heat treatment. The heat treatment may increase the lifespan of the bristles and/or pile of the leading roller **124**. For example, after weaving the fibers and cutting the velvet into rolls, the velvet may be rolled up and then run through a steam rich autoclave making the fibers/bristles more resilient fibers.

(33) The leading roller **124** may have an outside diameter D_{lr} that is smaller than the outside diameter D_{br} of the brush roll **122**. For example, the diameter D_{lr} may be greater than zero and less than or equal to $0.8D_{br}$, greater than zero and less than or equal to $0.7D_{br}$, or greater than zero and less than or equal to $0.6D_{br}$. According to example embodiments, the diameter D_{lr} may be in the range of $0.3D_{br}$ to $0.8D_{br}$, in the range of $0.4D_{br}$ to $0.8D_{br}$, in the range of $0.3D_{br}$ to $0.7D_{br}$, or in the range of $0.4D_{br}$ to $0.7D_{br}$. As an illustrative example, the brush roll **122** may have an outside diameter of 48 mm and the leading roller **124** may have an outside diameter of 30 mm. While the

leading roller **124** may have an outside diameter D_{lr} that is smaller than the outside diameter D_{br} of the brush roll **122**, the brush roll **122** may have bristles that are longer than the bristle and/or pile of the leading roller **122**.

(34) Positioning a leading roller **124** (having a diameter D_{lr} that is smaller than the diameter D_{br} of the brush roll **122**) in front of the brush roll **122** provides numerous benefits. For example, this arrangement decreases the height of the front side **112** of the surface cleaning head **100** (e.g., the housing **110**) from the surface **10** to be cleaned. The decreased height of the front of the surface cleaning head **100** provides a lower profile that allows the surface cleaning head **100** to fit under objects (e.g., furniture and/or cabinets). Moreover, the lower height allows for the addition of one or more light sources **111** (such as, but not limited to, LEDs), while still allowing the surface cleaning head **100** to fit under objects.

(35) Additionally, the smaller diameter D_{lr} of the leading roller **124** allows the rotating axis of the leading roller **124** to be placed closer to the front side **112** of the surface cleaning head **100**. When rotating, the leading roller **124** forms a generally cylindrical projection having a radius that is based on the overall diameter of the leading roller **124**. As the diameter of the leading roller **124** decreases, the bottom contact surface **140** (FIG. 3) of the leading roller **124** moves forward towards the front side **112** of the surface cleaning head **100**. In addition, when the surface cleaning head **100** contacts a vertical surface **12** (e.g., but not limited to, a wall, trim, and/or cabinet), the bottom contact surface **140** of the leading roller **124** is also closer to the vertical surface **12**, thereby enhancing the front edge cleaning of the surface cleaning head **100** compared to a larger diameter leading roller. Moreover, the smaller diameter D_{lr} of the leading roller **124** also reduces the load/drag on the motor driving the leading roller **124**, thereby enhancing the lifespan of the motor and/or allowing a smaller motor to be used to rotate both the brush roll **122** and leading roller **124**.

(36) The rotating brush roll **122** may be coupled to an electrical motor (either AC or DC) to cause the rotating brush roll **122** to rotate about the first rotating axis. The rotating brush roll may be coupled to the electrical motor by way of a gears and/or drive belts. The leading roller **124** may be driven from the same drive mechanism used to drive the rotating brush roll **122** or a separate drive mechanism. An example of the drive mechanism is described in U.S. patent application Ser. No. 15/331,045, filed Oct. 21, 2016, which is incorporated herein by reference. Other drive mechanisms are possible and within the scope of the present disclosure.

(37) In at least one embodiment, the brush roll **122** and the leading roller **124** rotate in the same direction directing debris toward the suction conduit **128**, for example, counter clockwise as shown in FIG. 3. This arrangement may reduce the number of parts (e.g., no clutch or additional gear train may be necessary), thereby making the surface cleaning head **100** lighter, reducing drivetrain loss (thereby allowing for smaller/less expensive motors), and less expensive to manufacture. Optionally, the brush roll **122** and the leading roller **124** may rotate at same speed, thereby reducing the number of parts (e.g., no additional gear train necessary) and reducing drivetrain loss (thus, smaller/less expensive motor) and making the surface cleaning head **100** lighter and less expensive to manufacture.

(38) As shown in FIG. 3, the leading roller **124** may be positioned within the housing **110** such that the bottom contact surface **140** is disposed closer to the surface **10** to be cleaned compared to the bottom contact surface **144** of the brush roll **122**. This arrangement allows the leading roller **124** to contact a surface **10** (e.g., a hard surface) without the brush roll **122** contacting the hard surface **10**. As may be appreciated, the leading roller **124** is intended to pick up debris from a hard surface **10** while the brush roll **122** is intended to primarily contact a carpet surface. This arrangement is therefore beneficial since it allows the leading roller **124** to form a seal between the front **112** of the surface cleaning head **100** with the hard surface **10**, thereby enhancing airflow and suction with the hard surface **10**. Additionally, this arrangement reduces the drag/torque on the drive motor(s) since the brush roll **122** (in some embodiments) does not have to contact the hard surface **10**. The reduced drag/torque may allow for a smaller, less expensive motor and/or may increase the lifespan

of the motor.

(39) According to some embodiments, as shown in FIG. 3, the leading roller **124** is spaced apart a distance **L1** (which is greater than 0 mm) from the brush roll **122** such that the leading roller **124** does not contact the brush roll **122**. The distance **L1** allows for an inter-roller vacuum passageway **146** between lower portions of the brush roll **122** and the leading roller **124**, which provides at least a portion of the flow path into the opening **127** of the suction conduit **128**. The inter-roller vacuum passageway **146** allows for debris that is either picked up by (and/or removed from) the leading roller **124** to be entrained in the vacuum flow generated by the surface cleaning head **100** and/or to be picked up by the brush roll **122**, thereby enhancing the cleaning efficiency of the surface cleaning head **100**. Additionally, the distance **L1** reduces the load/drag on the motor(s), thereby enhancing the lifespan of the motor(s) and/or allowing smaller motors to be used to rotate both the brush roll **122** and the leading roller **124**.

(40) One or both of the leading roller **124** and the brush roll **122** may be removable. The leading roller **124** may be removably coupled to the housing **110** of the surface cleaning head **100**. For example, a portion of the housing **110** (such as, but not limited to, a portion of the left and/or right side **116a**, **116b**) may be removably/hingedly coupled thereto. To remove the leading roller **124**, the removable portion may be unsecured/uncoupled from the rest of the housing **110**, thereby allowing the leading roller **124** to disengage from a drive wheel and allowing the leading roller **124** to be removed from the leading roller chamber **126**. Other ways of removably coupling the leading roller **124** within the housing **110** are also possible and within the scope of the present disclosure.

(41) In some embodiments, the housing **110** of the surface cleaning head **100** may include a removable and/or hinged panel that allows the brush roll **122** to be removed. As shown in FIGS. 1 and 8, for example, the surface cleaning head **100** includes a panel **119** that may be removably and/or hingedly coupled to the housing **110**. To remove the brush roll **122**, the panel **119** may be disengaged from the housing **110** (e.g., removed) to allow the user to have access to a brush roll chamber **121**. Examples of removable panels or covers and removable brush rolls are described in greater detail in U.S. Pat. No. 9,456,723 and U.S. patent application Pub. No. 2016/0220082, which are fully incorporated herein by reference. Alternatively or additionally, the leading roller **124** may be removable in the same way. Another example of a removable leading roller is described in U.S. patent application Ser. No. 15/331,045, filed Oct. 21, 2016, which is incorporated herein by reference.

(42) The ability to remove the brush roll **122** and/or the leading roller **124** from the surface cleaning head **100** allows the brush roll **122** and/or the leading roller **124** to be cleaned more easily and may allow the user to change the size of the brush roll **122** and/or the leading roller **124**, change type of bristles on the brush roll **122** and/or the leading roller **124**, and/or remove the brush roll **122** and/or the leading roller **124** entirely depending on the intended application.

(43) In some embodiments, the surface cleaning head **100** may also include a series of combing protrusions **150** (also referred to as debriding protrusions) in contact with the leading roller **124**, as shown in greater detail in FIGS. 4-7. The combing protrusions **150** may be configured to remove debris (such as, but not limited to, hair, string, and the like) that may be wrapped around and/or entrapped/entrained in/on the leading roller **124** as the surface cleaning head **100** is being used (e.g., without the user having to manually remove the debris from the leading roller **124**).

According to one embodiment, the combing protrusions **150** may contact only the leading roller **124** (e.g., the combing protrusions **150** may not contact the brush roll **122**). Some of the benefits of the combing protrusions **150** only contacting the leading roller **124** include increasing the lifespan of the leading roller **124**. Additionally, the combing protrusions **150** that only contact the leading roller **124** may reduce the load/drag on the motor, thereby allowing a smaller/less expensive motor to be used and making the surface cleaning head **100** lighter and less expensive to manufacture.

(44) In this embodiment, the combing protrusions **150** may include a plurality of spaced ribs **152** with angled edges **153** extending into contact with a surface of the leading roller **124**. The spaced

ribs **152** extend from a back support **151** with base portions **154** located between to reinforce the spaced ribs **152**. The back support **151** may be mounted within the leading roller chamber **126**. The angled edges **153** of the spaced ribs **152** may be arranged at an angle A (see FIGS. **4** and **6**) that is in the range of 15-20 degrees, for example, 20-25 degrees, such as 23.5 degrees. This example structure of the combing protrusions **150** may allow for increased strength and reduced frictional losses since less points may contact the leading roller **124**. Other shapes and configurations for the combing protrusions are also within the scope of the present disclosure.

(45) As shown in FIGS. **4** and **5**, the combing protrusions **150** may be disposed at a height H above the bottom contacting surface **140** of the leading roller **124** and on a side or lower half of the leading roller **124**. The placement of the combing protrusions **150** may help to prevent the combing protrusions **150** from contacting a carpet, thereby reducing drag on the surface cleaning head **100** and reducing the likelihood of the combing protrusions **150** damaging the carpet. This arrangement also allows the combing protrusions **150** to be exposed to the inter-roller vacuum passageway **146**, thereby enhancing the removal of debris from the leading roller **124** by the combing protrusions **150**. The combing protrusion **150** may also substantially prevent air from flowing through the combing protrusions **150** to the inside upper portion (e.g., upper half) of the leading roller **124**. In other embodiments, a space may be formed between the outer surface of the leading roller **124** and the back support **151** such that air flows downward through the combing protrusions **150** to force debris into the air flow through the inter-roller vacuum passageway **146**.

(46) As shown in FIG. **7**, an embodiment of the surface cleaning head **100** optionally includes an electrostatic discharge element (ESD) **156**. The ESD **156** may reduce and/or prevent the buildup of electrostatic charge on the surface cleaning head **100**. The ESD **156** may include any known device for discharging electrostatic charge. According to one embodiment, the ESD **156** may include Barnet fibers woven between the openings in the back of the leading roller chamber **126**. The Barnet fibers may be arranged in close proximity to the combing protrusions **150** and/or leading roller **124** for discharging. For example, the ESD **156** may be connected to a printed circuit board assembly (PCBA) that dumps charge out to the neutral AC line.

(47) In some embodiments, the housing **110** may further include a bumper **160** forming a top part of the front side **112** of the housing **110**, as shown in FIGS. **1**, **3**, **5**, and **8**. The bumper **160** may reduce potential damage to either the surface cleaning head **100** and/or other objects in the environment. A front portion of the leading roller **124** is exposed at the front side **112** of the housing **110**, and the bumper **160** may extend around at least a top of the leading roller **124**. In the example embodiment, the bumper **160** includes a lateral portion **162** extending laterally along the front side **112** of the housing **110** and side portions **164**, **168** extending downwardly along left and right sides of the front side **112** of the housing **110**. The side portions **164**, **168** may extend to a point at or below the second rotation axis RA2 of the leading roller **124**.

(48) The bumper **160** may optionally define one or more front edge vacuum passageways **168**, **169** providing at least a portion of the air flow path. As shown in FIG. **4**, the bumper **160** may therefore generally form a seal with a vertical surface **12** (e.g., wall or the like) to improve front edge cleaning. The front edge vacuum passageways **168**, **169** may allow for increased airspeed of the air being sucked into the surface cleaning head **100**, thereby enhancing front edge cleaning. The bumper **160** may also include one or more lateral air passageways disposed in the lateral portion **162**, which also allow for increased airflow along the front side **112**.

(49) The bumper **160** may also include one or more compression elements **161**, **163** (e.g., ribs) disposed on the lateral edge/section **162**. The compression elements **161**, **163** allow for increased resiliency and cushioning of the bumper **160**. When the bumper **160** is pushed against the vertical surface **12** (FIG. **4**), the compression elements **161**, **163** contact the surface **12** first and push the bumper **160** locally farther back than the rest of the bumper **160**, thereby forming a gap on either side of the compression elements **161**, **163**. The gaps on either side of the compression elements **161**, **163** form air paths allowing air to be drawn down in front of the leading roller **124**, which may

disturb dust and debris so that it can be directed into the air flow path toward the suction conduit.

(50) The bumper **160** may be formed as one piece with the housing **110** or may be formed as a separate piece secured within a groove and/or notch **165** formed between two or more pieces (e.g., an upper and lower portion **110a**, **110b**) of the housing **110**, as shown in FIG. 3. The groove and/or notch **165** may facilitate assembly of the housing **110** and the bumper **160** (e.g., between a headlight portion **110a** and main portion **110b** of the housing **110**).

(51) In some embodiments, the surface cleaning head **100** may further include one or more floor sealing strips **170**, **172** and side edge vacuum passageways **174** on an underside of the housing **110**, as shown in FIGS. 1 and 9. The floor sealing strip(s) **170**, **172** may include one or more sections extending outwardly from the housing **110** and having a length sufficient to at least partially contact the surface **10** to be cleaned. The floor seals strip(s) **170**, **172** may include soft bristles, fabric material, rubber material, or other material capable of contacting the surface being cleaned to substantially prevent air flow into the opening **127** of the suction conduit **128** from the rear side. The sealing strips **170**, **172** may also include a combination of elements or materials, such as bristles with a rubber strip extending along the strip between the bristles (e.g., with the bristles being longer than the rubber strip).

(52) In the example embodiment, a lateral floor sealing strip **170** extends along a rear lateral portion (e.g., behind the opening **127** of the suction conduit **128**) and side sealing strips **172** extend partially along the left and right sides **116a**, **116b**. The side sealing strips **172** extend, for example, along a substantial portion of the opening **127** of the suction conduit **128** and are spaced from the leading roller **124** to define one or more side edge vacuum passageways **174** extending back towards the opening **127** of the suction conduit **128**. Because the leading roller **124** itself forms a seal with the surface **10** being cleaned, additional sealing strips are unnecessary along the front side **112**. Although separate strips **170**, **172** are shown, one continuous sealing strip may be used. The floor sealing strips **170**, **172** may enhance scaling between the surface cleaning head **100** and the floor **10**, thereby enhancing the vacuum efficiency.

(53) The side edge vacuum passageways **174** may enhance the side edge cleaning efficiency of the surface cleaning head **100**. Side edge vacuum passageways **174** draw in air from the front **112** and the corner/sides **116a**, **116b** towards the suction conduit **128**, thereby enhancing edge cleaning as well as front cleaning. At least one of the side edge vacuum passageways **174** may also direct air into the inter-roller air passageway **146** between the leading roller **124** and the brush roll **122** to facilitate removal of debris from the leading roller **124**. As such, the side edge vacuum passageways **174** and the inter-roller air passageway **146** together provide at least a portion of the primary air flow path (e.g., as indicated by arrows **40**) into the suction conduit **128**.

(54) The side edge vacuum passageways **174** may be arranged at an approximately 45 degree angle with respect the longitudinal axis of the housing **110**. In other embodiments, the angle of the side edge vacuum passageways **174** may be within 30 to 60 degrees with respect the longitudinal axis of the housing **110**. Although the side edge passageways are shown as angled straight passageways, other shapes and configurations (e.g., S shaped or curved) are also possible and within the scope of the present disclosure.

(55) Referring to FIGS. 10-14D, a combing unit **1050** used for cleaning a cleaning roller **1024** in a cleaning apparatus is described in greater detail. The cleaning roller **1024** may be rotatably mounted in a housing, such as the surface cleaning head housing described above, with the combing unit **1050** engaging the cleaning roller **1024**. The combing unit **1050** includes a series of spaced combing protrusions or teeth **1052** extending from a back support **1051** and extending partially into the cleaning roller **1024**. Although the illustrated embodiment shows the combing unit **1050** with teeth **1052** extending from a single back support **1051**, the combing unit **1050** may also include teeth extending from multiple back supports.

(56) The combing unit **1050** may extend along a substantial portion of a length of the cleaning roller **1024** (i.e., more than half) such that the combing teeth **1052** remove debris from a substantial

portion of the cleaning surface of the cleaning roller **1024**. In an embodiment, the combing teeth **1052** may engage the cleaning surface of the cleaning roller **1024** along, for example, greater than 90% of a length of the cleaning surface of the cleaning roller **1024**. The combing unit **1050** works particularly well with cleaning rollers that are designed to move hair and other similar debris away from a center of the roller **1024**.

(57) The combing teeth **1052** have angled leading edges **1053** that are not aligned with a rotation center **1023** of the cleaning roller **1024**. The angled leading edges **1053** are the edges that an incoming portion of the rotating cleaning roller **1024** hits first and are directed toward or into a direction of rotation (i.e., into arrow **1002**) of the cleaning roller **1020**. More specifically, the leading edge **1053** of a combing tooth **1052** forms an acute angle α relative to a line **1004** extending from an intersection point **1025** where the leading edge **1053** intersects with an outer surface of the cleaning roller **1024** to the rotation center **1023**. In some embodiments, the angle α is in a range of 5° to 50° and more specifically in a range of 20° to 30° and even more specifically about 24° to 25° .

(58) In some embodiments, the combing teeth **1052** are positioned as close as possible to the bottom contact point **1040** of the cleaning roller **1024** but high enough to prevent being caught on a surface being cleaned (e.g., a carpet). The combing teeth **1052**, for example, may be positioned just above the lowest structure on the housing of a cleaning apparatus. Positioning the combing teeth **1052** closer to the bottom contact point **1040** of the cleaning roller **1024** allows debris to be intercepted and removed as soon as possible, thereby improving debris removal.

(59) In another embodiment, shown in FIG. 15A, the combing unit **1050** may have other orientations and positions relative to the cleaning roller **1024** (e.g., above the rotation center **1023**). In a robotic vacuum cleaner, for example, the combing unit **1050** may be positioned higher to prevent the combing teeth **1052** from interfering with the debris being deposited into a dust bin **1060**.

(60) The combing teeth **1052** may extend into the cleaning roller **1024** to a depth in a range of 0% to 50% of the cleaning roller radius for a soft roller and 0% to 30% of the cleaning roller radius for a tufted brush roll. In one embodiment, the cleaning roller **1024** is a soft roller (e.g., nylon bristles with a diameter less than or equal to 0.15 mm and a length greater than 3 mm) and the combing teeth **1052** extend into the soft cleaning roller **1024** in a range of 15% to 35%. The combing protrusions **1052** may be positioned to provide a root gap or spacing between the back support **1051** and the outer surface of the cleaning roller **1024** such that air may flow between the cleaning roller **1024** and the back support **1051** and through the roots of the combing teeth **1052**. The air flow through the roots of the combing teeth **1052** may help to dislodge debris that has been removed from the cleaning roller **1024** and to direct the debris into an air flow passageway toward a suction conduit of a cleaning apparatus. The root gap may have a width RG in a range of 1 to 3 mm and more specifically a range of 2 to 3 mm. The root gap RG may extend across an entire length of the combing unit **1050**, or a root gap RG may be formed only in one or more sections along the length of the combing unit **1050** to form air channels only at those sections. In other embodiments, the back support **1051** of the combing unit **1050** may contact the outer surface of the cleaning roller **1024** to provide sealing and force air to flow under the cleaning roller **1024**.

(61) In the illustrated embodiment (FIGS. 11 and 14D), the combing teeth **1052** have a triangular-shaped “tooth” profile with a wider base or root **1054** having a root width $W_{sub.r}$ and a tip **1056** having a diameter $D_{sub.r}$. In general, the base or root **1054** may be wide enough to prevent the tooth **1052** from bending upward when contacted by the rotating cleaning roller **1024** and the tip **1056** may be sharp enough to catch the debris. In some embodiments, the tip **1056** may be rounded with a diameter in the range of less than 3 mm and more specifically in the range of 1 to 2 mm and even more specifically about 1.6 mm. The root width $W_{sub.r}$ may be in a range of 5 to 6 mm.

(62) In another embodiment, shown in FIG. 15B, combing teeth **1052'** have a curved profile with curved leading edges **1053'** forming a concave curve. In this embodiment, a line **1006** extending

from the curved leading edge **1053'** at the tip **1056** forms an angle α with the line **1004** extending from the intersection point **1025** to the rotation center **1023**. The combing teeth **1052'** with curved edges may be positioned and spaced similar to the teeth **1052** with straight leading edges **1053** as described and shown herein.

(63) In some embodiments, the combing unit **1050** includes combing teeth **1052** spaced 4 to 16 teeth per inch and more specifically 7 to 9 teeth per inch. The combing teeth **1052** may be made of plastic or metal and may have a thickness that provides a desired rigidity to prevent bending when engaged with the rotating cleaning roller **1024**. In some embodiments, the combing teeth **1052** may have a thickness in a range of 0.5 to 2 mm depending upon the material. In one example, the combing teeth **1052** are made of plastic and have a thickness of 0.8 mm, a spacing *S* of about 2.4 mm, and a center-to-center spacing *Se* of about 3.3 mm.

(64) Although the combing unit **1050** is shown with combing teeth **1052** having an equal spacing, a combing unit **1050** may also include teeth **1052** with different spacings including, for example, groups of equally spaced teeth. The combing unit **1050** may include a section at the center of the cleaning roller **1024** with no teeth and groups of combing teeth **1052** proximate ends of the cleaning roller **1024** where the hair and similar debris migrates during rotation. Although the combing unit **1050** is shown with teeth **1052** having the same shape or tooth profile and dimensions, the combing unit **1050** may include teeth of different shapes, profiles dimensions and configurations at different locations along the combing unit **1050**.

(65) FIGS. **16** and **17** illustrate examples of two different types of vacuum cleaners **1600**, **1700** that may include a surface cleaning head **1602**, **1702** with dual agitators including a leading roller **1624**, **1724** and a combing unit (not shown), consistent with the embodiments described herein. The surface cleaning head **1602** with the leading roller **1624** may be used on an upright vacuum cleaner **1600** with a removable canister **1601** coupled to a wand **1604**, such as the type described in U.S. Patent Application Pub. No. 2015/0351596, which is commonly owned and fully incorporated herein by reference. The surface cleaning head **1702** with the leading roller **1724** may be used on a stick type vacuum cleaner **1700** with a removable handheld vacuum **1701** coupled at one end of a wand **1704**, such as the type described in U.S. Patent Application Pub. No. 2015/0135474, which is commonly owned and fully incorporated herein by reference.

(66) FIG. **18** illustrates a robotic vacuum cleaner **1800** that includes a housing **1810** and a cleaning roller **1824** with a combing unit (not shown) as disclosed herein. The robotic vacuum cleaner **1800** may also include one or more wheels **1830** for moving about a surface to be cleaned. An example of the combing unit used in a robotic vacuum cleaner is disclosed in greater detail in U.S. Provisional Application No. 62/469,853, filed Mar. 10, 2017, which is incorporated herein by reference.

(67) While the principles of the invention have been described herein, it is to be understood by those skilled in the art that this description is made only by way of example and not as a limitation as to the scope of the invention. Other embodiments are contemplated within the scope of the present invention in addition to the exemplary embodiments shown and described herein. Modifications and substitutions by one of ordinary skill in the art are considered to be within the scope of the present invention, which is not to be limited except by the following claims.

Claims

1. A cleaning apparatus comprising: a housing having a front side and back side, the housing including a suction conduit fluidly coupled to an opening on an underside of the housing between the front side and the back side, the suction conduit fluidly coupled to a suction motor; a brush roller rotatably mounted to the housing; a leading roller mounted in the housing in front of the brush roller and spaced from the brush roller such that a position of the leading roller relative to the housing is fixed and the leading roller and brush roller do not contact each other; one or more drive

mechanisms coupled to the brush roller and the leading roller configured to simultaneously drive the brush roller and the leading roller; a wall defining a portion of the suction conduit, the wall separating at least an inside upper portion of the leading roller from the suction conduit such that at least the inside upper portion of the leading roller is substantially outside of a flow path to the suction conduit; and a series of spaced combing protrusions extending from the wall, the combing protrusions configured to contact an outer surface of the lower portion of the leading roller between the rotation center of the leading roller and the bottom contact surface of the leading roller.

2. The cleaning apparatus of claim 1, wherein the combing protrusions have roots at the back support and the tips at an opposite end from the roots, the combing protrusions being wider at the roots than at the tips.

3. The cleaning apparatus of claim 1, wherein the combing protrusions include leading edges that form an acute angle relative to a line extending from an intersection point of the leading edge and the leading roller to a rotation center of the leading roller.

4. The cleaning apparatus of claim 1, wherein at least some of the combing protrusions have a curved profile with at least the leading edge forming a concave curve.

5. The cleaning apparatus of claim 1, wherein at least some of the combing protrusions have a triangular-shaped profile.

6. The cleaning apparatus of claim 1, wherein the combing unit is spaced across at least 90% of a length of the cleaning roller.

7. The cleaning apparatus of claim 1, wherein the housing defines an inter-roller air passageway between lower portions of the brush roller and the leading roller and below the combing protrusions, the inter-roller air passageway being in fluid communication with the suction conduit of the housing.

8. The cleaning apparatus of claim 7, wherein the debrising protrusions configured to contact the outer surface of the lower portion of the leading roller to remove debris from the leading roller, the debrising protrusions exposed to the inter-roller passageway such that the removed debris falls into the inter-roller passageway and into the flow path to the opening of the suction conduit.

9. The cleaning apparatus of claim 1, wherein an upper portion of the leading roller above the combing protrusions is outside of the suction conduit.

10. The cleaning apparatus of claim 1, wherein the cleaning apparatus is a robotic cleaner.

11. The cleaning apparatus of claim 1, wherein the apparatus is a sweeper and further comprises a wand coupled at one end to the cleaning apparatus.

12. The cleaning apparatus of claim 1, wherein the apparatus is a stick vacuum and further comprises a wand coupled at one end to the cleaning apparatus and a hand vacuum removably coupled to an opposite end of the wand.

13. The cleaning apparatus of claim 1, wherein the apparatus is a upright canister vacuum and further comprises a wand coupled at one end to the cleaning apparatus and a removable canister coupled to the wand.
