

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267428

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

de Barros Chapiewski; Guilherme et al.

User Intervention Based on Proximity Between Tracking Devices

Abstract

A tracking system can provide intervention notifications to a user to notify the user that a tracking device is potentially lost or is in a predicted state. The tracking system may notify the user that a tracking device is potentially lost or in a predicted state based on a number of factors, including: a proximity of a tracking device to other tracking devices or a user's mobile device, a movement of a tracking device to more than a threshold distance away from a mobile device or other tracking devices, a location of a tracking device relative to a geographic location or to geographic boundaries, a usage or movement behavior of the tracking device, a usage or movement behavior of a user or owner of a tracking device, information received from an external source, or information received from sensors within the tracking device or a user's mobile.

Inventors: de Barros Chapiewski; Guilherme (Cupertino, CA), Quintana; Melody (San Carlos, CA), Kumar; Mayank (San Francisco, CA), Lettau; Tyler (Hercules, CA), Patterson; Wayne (Burlingame, CA)

Applicant: Tile, Inc. (San Mateo, CA)

Family ID: 1000008586924

Appl. No.: 19/201928

Filed: May 08, 2025

Related U.S. Application Data

parent US continuation 18545170 20231219 parent-grant-document US 12323877 child US 19201928

parent US continuation 17864403 20220714 parent-grant-document US 11895558 child US 18545170

parent US continuation 17137177 20201229 parent-grant-document US 11425528 child US 17864403

parent US continuation 16810846 20200306 parent-grant-document US 10917746 child US 17137177

parent US continuation 16298951 20190311 parent-grant-document US 10631126 child US 16810846
parent US continuation 16184417 20181108 parent-grant-document US 10278021 child US 16298951
parent US continuation 15947209 20180406 parent-grant-document US 10158975 child US 16184417
parent US continuation 15339742 20161031 parent-grant-document US 9955305 child US 15947209
us-provisional-application US 62344392 20160601

Publication Classification

Int. Cl.: **H04W4/02** (20180101); **G06Q10/0631** (20230101); **G08B13/04** (20060101); **G08B13/14** (20060101); **G08B13/24** (20060101); **G08B21/24** (20060101); **G08B25/08** (20060101); **H04L67/12** (20220101); **H04L67/306** (20220101); **H04L67/50** (20220101); **H04L67/52** (20220101); **H04L67/55** (20220101); **H04W4/021** (20180101); **H04W4/029** (20180101); **H04W64/00** (20090101)

U.S. Cl.:

CPC **H04W4/023** (20130101); **G08B13/14** (20130101); **G08B13/1427** (20130101); **G08B13/2462** (20130101); **G08B21/24** (20130101); **G08B25/08** (20130101); **H04L67/52** (20220501); **H04L67/55** (20220501); **H04W4/021** (20130101); **H04W4/029** (20180201); **H04W64/006** (20130101); **G06Q10/063116** (20130101); **G08B13/04** (20130101); **H04L67/12** (20130101); **H04L67/306** (20130101); **H04L67/535** (20220501)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION [0001] This application is a continuation of U.S. application Ser. No. 18/545,170, filed Dec. 19, 2023, which is a continuation of U.S. application Ser. No. 17/864,403, filed Jul. 14, 2022, now U.S. Pat. No. 11,895,558, which is a continuation of U.S. application Ser. No. 17/137,177, filed Dec. 29, 2020, now U.S. Pat. No. 11,425,528, which is a continuation of U.S. application Ser. No. 16/810,846, filed Mar. 6, 2020, now U.S. Pat. No. 10,917,746, which is a continuation of U.S. application Ser. No. 16/298,951, filed Mar. 11, 2019, now U.S. Pat. No. 10,631,126, which is a continuation of U.S. application Ser. No. 16/184,417, filed Nov. 8, 2018, now U.S. Pat. No. 10,278,021, which is a continuation of U.S. application Ser. No. 15/947,209, filed Apr. 6, 2018, now U.S. Pat. No. 10,158,975, which application is a continuation of U.S. application Ser. No. 15/339,742, filed Oct. 31, 2016, now U.S. Pat. No. 9,955,305, which claims the benefit of U.S. Provisional Application No. 62/344,392, filed Jun. 1, 2016, the contents of which are incorporated by reference herein in their entirety.

BACKGROUND

[0002] This disclosure relates generally to tracking devices, and more specifically, to intervening on behalf of a user of a tracking device.

[0003] Users can attach tracking devices to one or more personal objects, such as keys, a phone, a car, a briefcase, and the like. The tracking device can communicatively couple to a mobile device of the user (or of a community member), and the mobile device can, in response to receiving a communication from the tracking device, determine a location of the mobile device (for instance, via a GPS receiver). The mobile device can then provide an identifier for the tracking device and

the determined location of the mobile device to a cloud server, which can associate the tracking device with the determined location of the mobile device.

[0004] When a user loses an object coupled to a tracking device, the user must classify the object as lost. In other words, the user must take an affirmative action before the cloud server can identify the tracking device as lost. Thus, there is a need to be able to identify a tracking device as lost or as unintentionally left behind before an affirmative action is taken by the user, or (in some cases) before the user even knows the object is lost or left behind. The cloud server can then inform the user that the object may be lost or left behind, beneficially improving the user's experience with the tracking device.

SUMMARY

[0005] A tracking system can provide intervention notifications to a user to notify the user that a tracking device is potentially lost, or to notify a user of a predicted state of a tracking device. A user can attach a tracking device to or enclose the tracking device within an object, such as a wallet, keys, a car, a bike, a pet, or any other object that the user wants to track. The user can then use a mobile device (e.g., by way of a software application installed on the mobile device) or other device or service to track the tracking device and corresponding object. For example, the mobile device can perform a local search for a tracking device attached to a near-by object. However, in situations where the user is unable to locate the tracking device using their own mobile device (e.g., if the tracking device is beyond a distance within which the mobile device and the tracking device can communicate), the user can leverage the capabilities of a community of users of a tracking device system.

[0006] A tracking system intervention can include the tracking system transmitting a notification to the mobile device of the user describing the intervention. For example, the notification may notify the user that a tracking device is potentially lost, meaning the user may have left the tracking device behind unintentionally. Additionally, the notification may notify the user that the tracking device is in a predicted state. An example predicted state can include a determination that an object coupled to the tracking device may be useful to the user, and the user does not currently possess the tracking device. The tracking system may allow the user to opt-in to the notifications and may configure a time and/or frequency of when the user receives notifications.

[0007] The tracking system can identify a tracking device as potentially lost or can predict a future state of the tracking device based on a number of factors, including but not limited to: a proximity of a tracking device to one or more additional tracking devices, a proximity of a tracking device to a user or the user's mobile device, a movement of a tracking device to more than a threshold distance away from a mobile device or one or more additional tracking devices, a location of a tracking device relative to a particular or pre-defined geographic location, a location of a tracking device relative to particular or pre-defined geographic boundaries, a usage or movement behavior of the tracking device, a usage or movement behavior of a user or owner of a tracking device, information received from an external source, information received from sensors within the tracking device or a user's mobile device, based on a current time or date, or based on any other suitable factors.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 illustrates an example tracking system environment in which a tracking device can operate, according to one embodiment.

[0009] FIG. 2 illustrates an example tracking system for use in a tracking system environment, according to one embodiment.

[0010] FIG. 3 illustrates an example user mobile device for use in a tracking system environment,

according to one embodiment.

[0011] FIG. 4 illustrates an example community mobile device for use in a tracking system environment, according to one embodiment.

[0012] FIG. 5 illustrates an example tracking device for use in a tracking system environment, according to one embodiment.

[0013] FIG. 6 illustrates a flowchart for a method of identifying a tracking device as potentially lost based on a threshold distance from a target device, according to one embodiment.

[0014] FIG. 7 illustrates a flowchart for a method of identifying a tracking device as potentially lost based on a threshold distance from a geographic location, according to one embodiment.

[0015] FIG. 8 illustrates a flowchart for a method of identifying a tracking device as potentially lost based on historical movement behavior, according to one embodiment.

[0016] FIG. 9 illustrates a flowchart for a method of identifying a tracking device as potentially useful to user based on external data, according to one embodiment.

[0017] FIG. 10 illustrates a flowchart for a method of identifying a tracking device as potentially lost based on sensor data, according to one embodiment.

[0018] FIG. 11 illustrates a flowchart for a method of generating an opt-in notification for identifying a tracking device as potentially lost, according to one embodiment.

[0019] The figures depict various embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention described herein.

DETAILED DESCRIPTION

Environment Overview

[0020] Embodiments described herein detail functionality associated with a tracking device. A user can attach a tracking device to or enclose the tracking device within an object, such as a wallet, keys, a car, a bike, a pet, or any other object that the user wants to track. The user can then use a mobile device (e.g., by way of a software application installed on the mobile device) or other device or service to track the tracking device and corresponding object. For example, the mobile device can perform a local search for a tracking device attached to a near-by object. However, in situations where the user is unable to locate the tracking device using their own mobile device (e.g., if the tracking device is beyond a distance within which the mobile device and the tracking device can communicate), the user can leverage the capabilities of a community of users of a tracking device system.

[0021] In particular, a tracking system (also referred to herein as a “cloud server” or simply “server”) can maintain user profiles associated with a plurality of users of the tracking device system. The tracking system can associate each user within the system with one or more tracking devices associated the user (e.g., tracking devices that the user has purchased and is using to track objects owned by the user). If the user's object becomes lost or stolen, the user can send an indication that the tracking device is lost to the tracking system, which is in communication with one or more mobile devices associated with the community of users in communication with the system. The tracking system can set a flag indicating the tracking device is lost. When one of a community of mobile devices that are scanning for nearby tracking devices and providing updated locations to the tracking system identifies a flagged tracking device, the tracking system can associate the received location with the flagged tracking device, and relay the location to a user of the tracking device, thereby enabling the user to locate the lost tracking device.

[0022] FIG. 1 illustrates an example tracking system environment in which a tracking device can operate, according to one embodiment. The environment of FIG. 1 includes a tracking system **100** communicatively coupled to a mobile device **102** associated with the user **103** via a first network **108**. The tracking system **100** is also communicatively coupled to a plurality of community mobile devices **104a** through **104n** (collectively referred to herein as “community mobile devices **104**”)

associated with a plurality of users **105a** through **105n** of the tracking system **100** (collectively referred to herein as “community users **105**”) via the first network **108**. As will be explained in more detail below, the tracking system **100** can allow the user **103** to manage and/or locate a tracking device **106** associated with the user **103**. In some embodiments, the tracking system **100** leverages the capabilities of community mobile devices **104** to locate the tracking device **106** if the location of the tracking device is unknown to the user **103** and beyond the capabilities of mobile device **102** to track. In some configurations, the user **103** may own and register multiple tracking devices **106**. Although FIG. 1 illustrates a particular arrangement of the tracking system **100**, mobile device **102**, community mobile devices **104**, and tracking device **106**, various additional arrangements are possible. FIG. 1 also illustrates an external data source **112** that is communicatively coupled to the tracking system **100** to provide additional, external data to the tracking system **100**, as is discussed further below. Examples of external data sources include: social networking systems, messaging systems, calendaring systems, banking systems, budgeting systems, vendor systems, online retailers, parking regulation databases, weather service, travel agency, transportation services, ride-sharing systems, geo-locating systems, contact management systems, and the like.

[0023] In some configurations, the user **103** may be part of the community of users **105**. Further, one or more users **105** may own and register one or more tracking devices **106**. Thus, any one of the users within the community of users **105** can communicate with tracking system **100** and leverage the capabilities of the community of users **105** in addition to the user **103** to locate a tracking device **106** that has been lost.

[0024] The tracking system **100**, mobile device **102**, and plurality of community mobile devices **104** may communicate using any communication platforms and technologies suitable for transporting data and/or communication signals, including known communication technologies, devices, media, and protocols supportive of remote data communications.

[0025] In certain embodiments, the tracking system **100**, mobile device **102**, and community mobile devices **104** may communicate via a network **108**, which may include one or more networks, including, but not limited to, wireless networks (e.g., wireless communication networks), mobile telephone networks (e.g., cellular telephone networks), closed communication networks, open communication networks, satellite networks, navigation networks, broadband networks, narrowband networks, the Internet, local area networks, and any other networks capable of carrying data and/or communications signals between the tracking system **100**, mobile device **102**, and community mobile devices **104**. The mobile device **102** and community of mobile devices **104** may also be in communication with a tracking device **106** via a second network **110**. The second network **110** may be a similar or different type of network as the first network **108**. In some embodiments, the second network **110** comprises a wireless network with a limited communication range, such as a Bluetooth or Bluetooth Low Energy (BLE) wireless network. In some configurations, the second network **110** is a point-to-point network including the tracking device **106** and one or more mobile devices that fall within a proximity of the tracking device **106**. In such embodiments, the mobile device **102** and community mobile devices **104** may only be able to communicate with the tracking device **106** if they are within a close proximity to the tracking device, though in other embodiments, the tracking device can use long-distance communication functionality (for instance, a GSM transceiver) to communicate with either a mobile device **102/104** or the tracking system **100** at any distance. In some configurations, the mobile device **102** and one or more community mobile devices **104** may each be associated with multiple tracking devices associated with various users.

[0026] As mentioned above, FIG. 1 illustrates the mobile device **102** associated with the user **103**. The mobile device **102** can be configured to perform one or more functions described herein with respect to locating tracking devices (e.g., tracking device **106**). For example, the mobile device **102** can receive input from the user **103** representative of information about the user **103** and

information about a tracking device **106**. The mobile device **102** may then provide the received user information, tracking device information, and/or information about the mobile device **102** to the tracking system **100**. Accordingly, the tracking system **100** is able to associate the mobile device **102**, the user **103**, and/or the tracking device **106** with one another. In some embodiments, the mobile device **102** can communicate with the tracking device **106** and provide information regarding the location of the tracking device to the user **103**. For example, the mobile device **102** can detect a communication signal from the tracking device **106** (e.g., by way of second network **110**) as well as a strength of the communication signal or other measure of proximity to determine an approximate distance (and/or a relative direction) between the mobile device **102** and the tracking device **106**. The mobile device **102** can then provide this information to the user **103** (e.g., by way of one or more graphical user interfaces) to assist the user **103** to locate the tracking device **106**. Accordingly, the user **103** can use the mobile device **102** to track and locate the tracking device **106** and a corresponding object associated with the tracking device **106**. If the mobile device **102** is located beyond the immediate range of communication with the tracking device **106** (e.g., beyond the second network **110**), the mobile device **102** can be configured to send an indication that a tracking device **106** is lost to the tracking system **100**, requesting assistance in finding the tracking device. The mobile device **102** can send an indication of a lost device in response to a command from the user **103**. For example, once the user **103** has determined that the tracking device **106** is lost, the user can provide user input to the mobile device **102** (e.g., by way of a graphical user interface), requesting that the mobile device **102** send an indication that the tracking device **106** is lost to the tracking system **100**. In some examples, the lost indication can include information identifying the user **103** (e.g., name, username, authentication information), information associated with the mobile device **102** (e.g., a mobile phone number), information associated with the tracking device (e.g., a unique tracking device identifier), or a location of the user (e.g., a GPS location of the mobile device **102** at the time the request is sent).

[0027] The tracking system **100** can be configured to provide a number of features and services associated with the tracking and management of a plurality of tracking devices and/or users associated with the tracking devices. For example, the tracking system **100** can manage information and/or user profiles associated with user **103** and community users **105**. In particular, the tracking system **100** can manage information associated with the tracking device **106** and/or other tracking devices associated with the user **103** and/or the community users **105**.

[0028] As mentioned above, the tracking system **100** can receive an indication that the tracking device **106** is lost from the mobile device **102**. The tracking system **100** can then process the indication in order to help the user **103** find the tracking device **106**. For example, the tracking system **100** can leverage the capabilities of the community mobile devices **104** to help find the tracking device **106**. In particular, the tracking system **100** may set a flag for a tracking device **106** to indicate that the tracking device **106** is lost and monitor communications received from the community mobile devices **104** indicating the location of one or more tracking devices **106** within proximity of the community mobile devices **104**. The tracking system **100** can determine whether a specific location is associated with the lost tracking device **106** and provide any location updates associated with the tracking device **106** to the mobile device **102**. In one example, the tracking system may receive constant updates of tracking device **106** locations regardless of whether a tracking device **106** is lost and provide a most recent updated location of the tracking device **106** in response to receiving an indication that the tracking device **106** is lost.

[0029] In some configurations, the tracking system **100** can send a location request associated with the tracking device **106** to each of the community mobile devices **104**. The location request can include any instructions and/or information necessary for the community mobile devices **106** to find the tracking device **102**. For example, the location request can include a unique identifier associated with the tracking device **106** that can be used by the community mobile devices **104** to identify the tracking device **106**. Accordingly, if one of the community mobile devices **104** detects

a communication from the tracking device **106** (e.g., if the community mobile device **104** is within range or moves within range of the communication capabilities of the tracking device **106** and receives a signal from the tracking device **106** including or associated with the unique identifier associated with the tracking device **106**), the community mobile device **104** can inform the tracking system **100**. Using the information received from the community mobile devices **104**, the tracking system **100** can inform the user (e.g., by way of the mobile device **102**) of a potential location of the tracking device **106**.

[0030] As shown in FIG. **1** and as mentioned above, the tracking system **100** can communicate with a plurality of community mobile devices **104** associated with corresponding community users **105**. For example, an implementation may include a first community mobile device **104a** associated with a first community user **105a**, a second community mobile device **104b** associated with a second community user **105b**, and additional communication mobile devices associated with additional community users up to an nth community mobile device **104n** associated with an nth community user **105n**. The community mobile devices **104** may also include functionality that enables each community mobile device **104** to identify a tracking device **106** within a proximity of the community mobile device **104**. In one example, a first community mobile device **104a** within proximity of a tracking device **106** can communicate with the tracking device **106**, identify the tracking device **106** (e.g., using a unique identifier associated with the tracking device **106**), and/or detect a location associated with the tracking device **106** (e.g., a location of the first mobile community device **104a** at the time of the communication with the tracking device **106**). This information can be used to provide updated locations and/or respond to a location request from the tracking system **100** regarding the tracking device **106**. In some embodiments, the steps performed by the first community mobile device **104a** can be hidden from the first community user **105a**. Accordingly, the first community mobile device **104a** can assist in locating the tracking device **106** without bother and without the knowledge of the first community user **105a**.

[0031] As mentioned above, the tracking system **100** can assist a user **103** in locating a tracking device **106**. The tracking device may be a chip, tile, tag, or other device for housing circuitry and that may be attached to or enclosed within an object such as a wallet, keys, purse, car, or other object that the user **103** may track. Additionally, the tracking device **106** may include a speaker for emitting a sound and/or a transmitter for broadcasting a beacon. In one configuration, the tracking device **106** may periodically transmit a beacon signal that may be detected using a nearby mobile device **102** and/or community mobile device **104**. In some configurations, the tracking device **106** broadcasts a beacon at regular intervals (e.g., one second intervals) that may be detected from a nearby mobile device (e.g., community mobile device **104**). The strength of the signal emitted from the tracking device **106** may be used to determine a degree of proximity to the mobile device **102** or community mobile device **104** that detects the signal. For example, a higher strength signal would indicate a close proximity between the tracking device **106** and the mobile device **102** and a lower strength signal would indicate a more remote proximity between the tracking device **106** and the mobile device **102**, though in some embodiments, the tracking device **106** can intentionally vary the transmission strength of the beacon signal. In some cases, the strength of signal or absence of a signal may be used to indicate that a tracking device **106** is lost.

System Overview

[0032] FIG. **2** illustrates an example tracking system for use in a tracking system environment, according to one embodiment. As shown, the tracking system **100** may include, but is not limited to, an association manager **204**, a tracking device location manager **206**, a tracking device intervention manager **207**, and a data manager **208**, each of which may be in communication with one another using any suitable communication technologies. It will be recognized that although managers **204-208** are shown to be separate in FIG. **2**, any of the managers **204-208** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

[0033] The association manager **204** may be configured to receive, transmit, obtain, and/or update information about a user **103** and/or information about one or more specific tracking devices (e.g., tracking device **106**). In some configurations, the association manager **204** may associate information associated with a user **103** with information associated with a tracking device **106**. For example, user information and tracking information may be obtained by way of a mobile device **102**, and the association manager **204** may be used to link the user information and tracking information. The association between user **103** and tracking device **106** may be used for authentication purposes, or for storing user information, tracking device information, permissions, or other information about a user **103** and/or tracking device **106** in a database.

[0034] The tracking system **100** also includes a tracking device location manager **206**. The tracking device location manager **206** may receive and process an indication that the tracking device **106** is lost from a mobile device (e.g., mobile device **102** or community mobile devices **104**). For example, the tracking system **100** may receive a lost indication from a mobile device **102** indicating that the tracking device **106** is lost. The tracking device location manager **206** may set a flag on a database (e.g., tracker database **212**) indicating that the tracking device **106** is lost. The tracking device location manager **206** may also query a database to determine tracking information corresponding to the associated user **103** and/or tracking device **106**. The tracking system **100** may obtain tracking device information and provide the tracking device information or other information associated with the tracking device **106** to a plurality of community mobile devices **104** to be on alert for the lost or unavailable tracking device **106**.

[0035] The tracking device location manager **206** may also receive a location from one or more community mobile devices **104** that detect the tracking device **106**, for instance in response to the community mobile device receiving a beacon signal transmitted by the tracking device **106**, without the tracking device **106** having been previously marked as lost. In such embodiments, a user corresponding to the mobile device **102** can request a most recent location associated with the tracking device from the tracking system **100**, and the location manager **206** can provide the location received from the community mobile device for display by the mobile device **102**. In some embodiments, the location manager **206** provides the location of the tracking device **106** received from a community mobile device either automatically (for instance if the tracking device **106** is marked as lost) or at the request of a user of the mobile device **102** (for instance, via an application on the mobile device **102**). The location manager **206** can provide a location of a tracking device **106** to a mobile device **102** via a text message, push notification, application notification, automated voice message, or any other suitable form of communication.

[0036] The tracking device location manager **206** may further manage providing indications about whether a tracking device **106** is lost or no longer lost. For example, as discussed above, the tracking device location manager **206** may provide a location request to the community of mobile devices **104** indicating that a tracking device **106** is lost. Additionally, upon location of the tracking device **106** by the user **103** or by one of the community of users **105**, the tracking device location manager **206** may provide an indication to the user **103**, community user **105**, or tracking system **100** that the tracking device **106** has been found, thus removing any flags associated with a tracking device and/or canceling any location request previously provided to the community of users **105**. For example, where a user **103** sends an indication that the tracking device **106** is lost to the tracking system **100** and later finds the tracking device **106**, the mobile device **102** may provide an indication to the tracking system **100** that the tracking device **106** has been found. In response, the tracking device location manager **206** may remove a flag indicating that the tracking device **106** is lost and/or provide an updated indication to the community of users **105** that the tracking device **106** has been found, thus canceling any instructions associated with the previously provided location request. In some configurations, the notification that the tracking device **106** has been found may be provided automatically upon the mobile device **102** detecting the tracking device **106** within a proximity of the mobile device **102**. Alternatively, the notification that the tracking device

106 has been found may be provided by the user **103** via user input on the mobile device **102**. In another example, a known user (e.g., a friend or family member) with whom the tracking device **106** has been shared may provide an indication that the tracking device **106** has been found.

[0037] The tracking system **100** additionally includes a tracking device intervention manager **207**. The tracking device intervention manager **207** can identify whether a tracking device is lost or has been left behind, or can predict a state of the tracking device based on, for instance, the location of a tracking device relative to other tracking devices, the location of a tracking device relative to a user's phone, and the location of a tracking device relative to historical user data. When a device is determined to be lost or left behind, or when a state of the tracking device has been predicted, the tracking device intervention manager **207** can notify a user, for instance via a notification sent to and displayed by a mobile device **102** of the user. The tracking device intervention manager **207** is described below in greater detail.

[0038] The tracking system **100** additionally includes a data manager **208**. The data manager **208** may store and manage information associated with users, mobile devices, tracking devices, permissions, location requests, and other data that may be stored and/or maintained in a database related to performing location services of tracking devices. As shown, the data manager **208** may include, but is not limited to, a user database **210**, a tracker database **212**, permissions data **214**, and location request data **216**. It will be recognized that although databases and data within the data manager **208** are shown to be separate in FIG. 2, any of the user database **210**, tracker database **212**, permissions data **214**, and location request data **216** may be combined in a single database or manager, or divided into more databases or managers as may serve a particular embodiment.

[0039] The data manager **208** may include the user database **210**. The user database **210** may be used to store data related to various users. For example, the user database **210** may include data about the user **103** as well as data about each user **105** in a community of users **105**. The community of users **105** may include any user that has provided user information to the tracking system **100** via a mobile device **102**, **104** or other electronic device. The user information may be associated with one or more respective tracking devices **106**, or may be stored without an association to a particular tracking device. For example, a community user **105** may provide user information and permit performance of tracking functions on the community mobile device **104** without owning or being associated with a tracking device **106**. The user database **210** may also include information about one or more mobile devices or other electronic devices associated with a particular user.

[0040] The data manager **208** may also include a tracker database **212**. The tracker database **212** may be used to store data related to tracking devices. For example, the tracker database **212** may include tracking data for any tracking device **106** that has been registered with the tracking system **100**. Tracking data may include unique tracker identifications (IDs) associated with individual tracking devices **106**. Tracker IDs may be associated with a respective user **103**. Tracker IDs may also be associated with multiple users. Additionally, the tracker database **212** may include any flags or other indications associated with whether a specific tracking device **106** has been indicated as lost and whether any incoming communications with regard to that tracking device **106** should be processed based on the presence of a flag associated with the tracking device **106**.

[0041] The data manager **208** may further include permissions data **214** and location request data **216**. Permissions data **214** may include levels of permissions associated with a particular user **103** and/or tracking device **106**. For example, permissions data **214** may include additional users that have been indicated as sharing a tracking device **106**, or who have been given permission to locate or receive a location of a tracking device **106**. Location request data **216** may include information related to a location request or a lost indication received from the user **103** via a mobile device **102**.

[0042] FIG. 3 illustrates an example user mobile device for use in a tracking system environment, according to one embodiment. As shown, the mobile device **102** may include, but is not limited to, a user interface manager **302**, a location request manager **304**, a database manager **306**, a tracking

manager **308**, and an intervention engine **340**, each of which may be in communication with one another using any suitable communication technologies. It will be recognized that although managers **302-308** are shown to be separate in FIG. 3, any of the managers **302-308** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

[0043] As will be explained in more detail below, the mobile device **102** includes the user interface manager **302**. The user interface manager **302** may facilitate providing the user **103** access to data on a tracking system **100** and/or providing data to the tracking system **100**. Further, the user interface manager **302** provides a user interface by which the user **103** may communicate with tracking system **100** and/or tracking device **106** via mobile device **102**. For example, the user interface manager **302** can facilitate the providing of power settings to the tracking device **106** for power management on the tracking device **106** by the user **103**.

[0044] The mobile device **102** may also include a location request manager **304**. The location request manager **304** may receive and process a request input to the mobile device **102** to send an indication that a tracking device **106** is lost to a tracking system **100**. For example, the user **103** may provide an indication that a tracking device **106** is lost, unreachable, or otherwise unavailable from the mobile device **102** via the user interface manager **302**, and the location request manager **304** may process the lost indication and provide any necessary data to the tracking system **100** for processing and relaying a location request to other users **105** over a network **108**. In some configurations, an indication that a tracking device **106** is lost is provided via user input. Alternatively, the indication may be transmitted automatically in response to the mobile device **102** determining that a tracking device **106** is lost.

[0045] In addition, the location request manager **304** can request a location of the tracking device **106** without the tracking device **106** being identified as lost. For instance, a user can access a tracking device location feature of an application running on the mobile device **102** (for example, via the user interface manager **302**), and the location request manager **304** can request a most recent location of the tracking device **106** from the tracking system **100**. The location request manager **304** can receive the most recent location from the tracking system **100**, and can display the most recent location via the user interface manager **302**.

[0046] The mobile device **102** may also include a database manager **306**. The database manager **306** may maintain data related to the user **103**, tracking device **106**, permissions, or other data that may be used for locating a tracking device **106** and/or providing a request to a tracking system **100** for locating one or more tracking devices **106** associated with the user **103**. Further, the database manager **306** may maintain any information that may be accessed using any other manager on the mobile device **102**.

[0047] The mobile device **102** may further include a tracking manager **308**. The tracking manager **308** may include a tracking application (e.g., a software application) for communicating with and locating a tracking device **106** associated with the user **103**. For example, the tracking manager **308** may be one configuration of a tracking application installed on the mobile device **102** that provides the functionality for locating a tracking device **106** and/or requesting location of a tracking device **106** using a tracking system **100** and/or a plurality of community mobile devices **104**. As shown, the tracking manager **308** may include, but is not limited to, a Bluetooth Low Energy (BLE) manager **310**, a persistence manager **312**, a local files manager **314**, a motion manager **316**, a secure storage manager **318**, a settings manager **320**, a location manager **322**, a network manager **324**, a notification manager **326**, a sound manager **328**, a friends manager **330**, a photo manager **332**, an authentication manager **334**, and a device manager **336**. Thus, the tracking manager **308** may perform any of the functions associated with managers **310-338**, described in additional detail below.

[0048] The BLE manager **310** may be used to manage communication with one or more tracking devices **106**. The persistence manager **312** may be used to store logical schema information that is

relevant to the tracking manager **308**. The local files manager **314** may be responsible for managing all files that are input or output from the mobile device **102**. The motion manager **316** may be responsible for all motion management required by the tracking manager **308**. The secure storage manager **318** may be responsible for storage of secure data, including information such as passwords and private data that would be accessed through this sub-system. The settings manager **320** may be responsible for managing settings used by the tracking manager **308**. Such settings may be user controlled (e.g., user settings) or defined by the tracking manager **308** for internal use (e.g., application settings) by a mobile device **102** and/or the tracking system **100**. The location manager **322** may be responsible for all location tracking done by the tracking manager **308**. For example, the location manager **322** may manage access to the location services of the mobile device **102** and works in conjunction with other managers to persist data. The network manager **324** may be responsible for all Internet communications from the tracking manager **308**. For example, the network manager **324** may mediate all Internet API calls for the tracking manager **308**. The notification manager **326** may be responsible for managing local and push notifications required by the tracking manager **308**. The sound manager **328** may be responsible for playback of audio cues by the tracking manager **308**. The friends manager **330** may be responsible for managing access to contacts and the user's social graph. The photo manager **332** may be responsible for capturing and managing photos used by the tracking manager **308**. The authentication manager **334** may be responsible for handling the authentication (e.g., sign in or login) of users. The authentication manager **334** may also include registration (e.g., sign up) functionality. The authentication manager **334** further coordinates with other managers to achieve registration functionality. The device manager **336** may be responsible for managing the devices discovered by the tracking manager **308**. The device manager **336** may further store and/or maintain the logic for algorithms related to device discovery and update.

[0049] The mobile device **102** may further include an intervention engine **340**. The intervention engine **340** is configured to, in response to a determination that a tracking device may be lost (or inadvertently left behind, misplaced, forgotten, stolen, etc.), notify a user that the tracking device may be lost or left behind. In some embodiments, the determination that the tracking device may be lost or left behind may be made by the tracking system **100** and communicated to the mobile device **102**, may be made by a different tracking device and communicated to the mobile device, or may be made by the intervention engine **340**. Likewise, the intervention engine **340** is configured to, in response to predicting a state of the tracking device, notify a user of the tracking device of the predicted state of the tracking device. The state of the tracking device can be predicted by the tracking system **100** and communicated to the mobile device **102**, or may be made by the intervention engine **340**. The intervention engine **340** can notify a user of the mobile device **102** that a tracking device may be lost or left behind, or can notify the user of the predicted state of the tracking device in a number of ways, for instance by displaying a notification within a graphical notification interface of the mobile device, by displaying a status or notification within an application interface of the mobile device, by emitting an alarm or notification audio, or the like.

[0050] FIG. 4 illustrates an example community mobile device for use in a tracking system environment, according to one embodiment. As shown, the community mobile device **104** may include, but is not limited to, a user interface manager **402**, a tracking device manager **404**, a database manager **406**, and a tracking manager **408**, each of which may be in communication with one another using any suitable communication technologies. The user interface manager **402**, database manager **406**, and tracking manager **408** illustrated in FIG. 4 may include similar features and functionality as the user interface manager **302**, database manager **306**, and tracking manager **308** described above in connection with FIG. 3. It will be recognized that although managers **402-408** are shown to be separate in FIG. 4, any of the managers **402-408** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

[0051] The community mobile device **104** may include a tracking device manager **404**. The tracking device manager **404** may facilitate scanning for nearby tracking devices **106**. In some configurations, the tracking device manager **404** can continuously or periodically scan (e.g., once per second) for nearby tracking devices **106**. The tracking device manager **404** may determine whether to provide an updated location of the nearby tracking device **106** to the tracking system **100**. In some configurations, the tracking device manager **404** provides a location of a nearby tracking device **106** automatically. Alternatively, the tracking device manager **404** may determine whether the location of the tracking device **106** has been recently updated, and may determine whether to provide an updated location based on the last time a location of the tracking device **106** has been updated (e.g., by the community mobile device **104**). For example, where the community mobile device **104** has provided a recent update of the location of a tracking device **106**, the tracking device manager **404** may decide to wait a predetermined period of time (e.g., 5 minutes) before providing an updated location of the same tracking device **106**.

[0052] In one configuration, the tracking device manager **404** may receive and process a location request or other information relayed to the community mobile device **104** by the tracking system **100**. For example, the tracking device manager **404** may receive an indication of a tracking device **106** that has been indicated as lost, and provide a location of the tracking device **106** if it comes within proximity of the community mobile device **104**. In some configurations, the community mobile device **104** is constantly scanning nearby areas to determine if there is a tracking device **106** within a proximity of the community mobile device **104**. Therefore, where a tracking device **106** that matches information provided by the tracking system **100** (e.g., from the location request) comes within proximity of the community mobile device **104**, the tracking device manager **404** may generate and transmit a response to the location request to the tracking system **100**, which may be provided to the user **103** associated with the tracking device **106**. Further, generating and transmitting the response to the tracking request may be conditioned on the status of the tracking device **106** being flagged as lost by the mobile device **102** and/or the tracking system **100**.

[0053] The tracking device manager **404** may additionally provide other information to the tracking system **100** in response to receiving the tracking request. For example, in addition to providing a location of the community mobile device **104**, the tracking device manager may provide a signal strength associated with the location to indicate a level of proximity to the location of the community mobile device **104** provided to the user **103**. For example, if a signal strength is high, the location provided to the user **103** is likely to be more accurate than a location accompanied by a low signal strength. This may provide additional information that the user **103** may find useful in determining the precise location of tracking device **106**.

[0054] As described above, the tracking device manager **404** may determine whether to send a location within the proximity of the tracking device **106** to the tracking system **100**. The determination of whether to send a location to the tracking system **100** may be based on a variety of factors. For example, a tracking device manager **404** may determine to send a location of the tracking device **106** to a tracking system **100** based on whether the detected tracking device **106** has been indicated as lost or if a tracking request has been provided to the community mobile device **104** for the particular tracking device **106**. In some configurations, the community mobile device **104** may send an update of a location of a tracking device **106** even if the tracking device **106** is not associated with a current tracking request or if the tracking device **106** is not indicated as lost. For example, where the location of a tracking device **106** has not been updated for a predetermined period of time, the community mobile device **104** may provide an update of a tracking device location to the tracking system **100**, regardless of whether a tracking request has been received.

[0055] In some configurations, the community mobile device **104** may include additional features. For example, the community mobile device **104** may allow a tracking system **100** to snap and download a photo using photo functionality of the community mobile device **104**. In some configurations, this may be an opt-in feature by which a community user **105** permits a tracking

system **100** to take a snap-shot and possibly provide a visual image of an area within a proximity of the tracking device **106**.

[0056] FIG. 5 illustrates an example tracking device for use in a tracking system environment, according to one embodiment. The tracking device **106** of FIG. 5 includes an interface **502**, a transceiver **504**, a controller **506**, and one or more sensors **508**. The transceiver **504** is a hardware circuit capable of both transmitting and receiving signals. It should be noted that in other embodiments, the tracking device **106** includes fewer, additional, or different components than those illustrated in FIG. 5.

[0057] The interface **502** provides a communicative interface between the tracking device **106** and one or more other devices, such as a mobile device **102**. For instance, the interface **502** can instruct the transceiver **504** to output beacon signals as described above (for example, periodically or in response to a triggering event, such as a detected movement of the tracking device **106**). The interface **502** can, in response to the receiving of signals by the transceiver **504** from, for instance, the mobile device **102**, manage a pairing protocol to establish a communicative connection between the tracking device **106** and the mobile device **102**. As noted above, the transceiver **504** can include a BLE receiver and transmitter, though in other embodiments, the transceiver **504** enables communications via other suitable wireless connection protocols (such as WiFi, Global System for Mobile Communications or “GSM”, LTE, and the like). It should be noted that while various examples herein describe the transceiver **504** as a GSM receiver and transmitter, this is done for the purposes of brevity, and it should be emphasized that the transceiver **504** can communicate over any other wireless communication protocol according to the embodiments described herein.

[0058] The controller **506** is a hardware chip that configures the tracking device **106** to perform one or more functions or to operate in one or operating modes or states. For instance, the controller **506** can configure the interval at which the transceiver broadcasts beacon signals, can authorize or prevent particular devices from pairing with the tracking device **106** based on information received from the devices and permissions stored at the tracking device, can increase or decrease the transmission strength of signals broadcasted by the transceiver, can configure the interface to emit a ringtone or flash an LED light, can enable or disable various tracking device sensors, can enable or disable communicative functionality of the tracking device **106**, can configure the tracking device into a sleep mode or awake mode, can configure the tracking device into a power preservation mode, and the like. The controller **506** can configure the tracking device to perform functions or to operate in a particular operating mode based on information or signals received from a device paired with or attempting to pair with the tracking device **106**, based on an operating state or connection state of the tracking device **106**, based on user-selected settings, based on information stored at the tracking device **106**, based on a detected location of the tracking device **106**, based on historical behavior of the tracking device **106** (such as a previous length of time the tracking device was configured to operate in a particular mode), based on information received from the sensors **508**, or based on any other suitable criteria.

[0059] The sensors **508** can include motion sensors (such as gyroscopes or accelerators), altimeters, GPS transceivers, orientation sensors, proximity sensors, communication sensors, light sensors, temperature sensors, pressure sensors, touch sensors, audio sensors, or any other suitable sensor configured to detect an environment of the tracking device **106**, a state of the tracking device **106**, a movement or location of the tracking device **106**, and the like. The sensors **508** are configured to provide information detected by the sensors to the controller **506**, which in turn can provide the information detected by the sensors to a mobile device **102** communicatively coupled to the tracking device **106**.

Tracking Device Collection Overview

[0060] Tracking devices can be organized into collections of tracking devices that are commonly co-located, that may move similarly, that are often kept close together, that are used similarly or for a common purpose, that are attached to related or similar objects, that are associated with a

common subject matter, or that behave in a similar way. As used herein, a “collection” refers to a pre-determined set of tracking devices. Collections of tracking devices can include one, two, or more tracking devices, and the identities of each collection and the identities of the tracking devices within each collection can be stored within the tracker database **212**, within a mobile device **102** of a user associated with the collection, or any other suitable location.

[0061] Tracking device collections can be defined by users. For instance, a user can create a collection via an application interface or other mobile device interface, via a web page interface associated with the tracking system **100**, or the like. The user can select a set of tracking devices owned or managed by the user, can associate with the selected tracking devices, and can name or otherwise identify the collection. For instance, the user can select tracking devices that are attached to objects needed by the user for the user's job, can create a collection of “work” tracking devices, and can name the collection, all via an application running on the user's mobile device **102**. The mobile device **102** can then communicate the defined collection to the tracking system **100** for storage.

[0062] Alternatively, tracking device collections can be defined by the tracking system **100**, based on common historical behavior/usage patterns associated with a set of tracking devices. For instance, if a set of tracking devices (e.g., a first tracking device coupled to a user's wallet, a second to a user's ID badge, and a third to a user's briefcase) commonly accompanies a user from a home location to a work location weekday mornings, and likewise from the work location to the home location weekday evenings, the set of tracking devices can be grouped together in a tracking device collection. As described above, tracking devices are coupled to objects, and the user can identify to the tracking system **100** (for instance, via the mobile device **102**) the identity of the objects to which the tracking devices are attached. Accordingly, the tracking system **100** can define collections of tracking devices based on the identified types of objects to which a set of tracking devices are coupled. For example, if a user identifies an object to which a first tracking device is coupled as “luggage”, and identifies an object to which a second tracking device is coupled as “passport”, the tracking system **100** can define a “travel” tracking device collection based on a pre-determined likelihood that a user's luggage and passport are likely to be used together.

[0063] In some embodiments, the tracking system **100** can identify a candidate tracking device collection (e.g., by identifying a set of tracking devices), and can present or suggest the candidate tracking device collection to a user (for instance, via the user's mobile device **102**). For example, the travel system **100** can identify a set of tracking devices that commonly move in conjunction with a user's car, and can suggest a candidate “car” tracking device collection to the user. If the user agrees to define a tracking device collection based on the presented candidate tracking device collection, the tracking system **100** can store the tracking device collection.

[0064] In some embodiments, the tracking system **100** can identify a candidate tracking device likely to be related to a defined tracking device collection, and can present or suggest the candidate tracking device to the user to add to the tracking device collection. For example, if a user has defined a “travel” collection of tracking devices including a passport tracking device and luggage tracking device, and the tracking system **100** determines that a tracking device coupled to a camera bag is commonly co-located with the passport and luggage (or moves in conjunction with the passport and luggage), then the tracking system can suggest to the user (for instance, via the user's mobile device **102**) that the user add the camera bag to the travel tracking device collection. If the user accepts the suggestion and adds the suggested tracking device to the tracking device collection, the tracking system **100** can update the stored tracking device collection to include the suggested tracking device.

[0065] In some embodiments, an interface of the user's mobile device (such as an application interface, a web page interface, and the like) can display one or more tracking device collections to the user. For instance, the mobile device can display a selectable icon, button, or display portion corresponding to the tracking device collection. When a user selects the tracking device collection,

the mobile device can identify tracking devices within the selected tracking device collection, and can display information associated with the identified tracking devices within the collection (such as location information, status information, information about the object to which the tracking device is coupled, and the like). For instance, the user can select a “work” tracking device collection from an interface of the application associated with the tracking system **100**, and the application can display information associated with a first tracking device coupled to a user's keys, a second tracking device coupled to the user's ID badge, and a third tracking device coupled to the user's briefcase.

[0066] Examples of tracking device collections include but are not limited to: [0067] Car accessory tracking devices: a wallet, glasses, spare tire, garage door remote control, parking pass, toll road/bridge payment sensor, keys, phone charger, jumper cables, car jack, auxiliary cable [0068] Travel tracking devices: luggage, phone charger, laptop charger, makeup/toiletry bag, passport, digital book/reader, computer, tablet, phone, camera, headphones, airpods, water bottle, jacket, pillow [0069] Purse tracking devices: purse, wallet, checkbook, keys, pillbox [0070] Work tracking devices: laptop, tablet, phone, ID badge, headphones, wallet, briefcase [0071] School tracking devices: backpack, lunch bag, laptop, books [0072] Home tracking devices: remote control, safe, jewelry box, tools, toolbox, artwork [0073] Camping tracking devices: tent, sleeping bags, headlamp, flashlight, lanterns, first aid kit [0074] Skiing/snowboarding tracking devices: skis, snowboard, coat, gloves, helmet, goggles, ski pass [0075] Golf tracking devices: clubs, bag, shoes, hat [0076] SCUBA tracking devices: fins, mask, tank, wetsuit, flashlight, weight belt, buoyancy compensator [0077] Art/antique tracking devices: tracking devices coupled to artwork or antiques [0078] Photography tracking devices: camera bag, camera, lenses, tripods, flash gear [0079] Public tracking devices: tracking devices coupled to buses, food trucks, and the like [0080] Computer/laptop accessories tracking devices: laptop, tablet, charger, dongle, mouse, keyboard, monitors, external hard drive, web camera [0081] Tool tracking devices: hammer, screwdriver, wrench, saw, safety glasses, tool box [0082] Emergency supplies tracking devices: fire extinguisher, water containers, canned foods, flashlights, emergency radio [0083] Baby/child tracking devices: baby bag, diapers, toys, baby powder, baby wipes, books, car seat, stroller, clothes [0084] Gym tracking devices: gym shoes, gym bag, extra clothes, towel, joint brace/support [0085] Beach tracking devices: towel, sunscreen, beach umbrella, water bottle, surfboard, cooler [0086] Rain-gear tracking devices: jacket, hat, poncho, umbrella, rain boots [0087] Snow-gear tracking devices: jacket, hat, ear muffs, scarf [0088] Warm-weather tracking devices: sunscreen, sunglasses, sandals, water bottle [0089] Valuable item tracking devices: Art, antique, television, jewelry/jewelry box, safe, monitor, computer

Tracking Device Intervention Overview

[0090] As used herein, a tracking device “intervention” can refer to notifying a user, owner, or manager of a tracking device that the tracking device may be lost, may be forgotten, or may be inadvertently left behind (collectively referred to as “potentially lost” hereinafter). In some embodiments, a tracking device intervention can refer to notifying a user of a predicted state or behavior of a tracking device (collectively referred to as “predicted state” hereinafter). In each case, a tracking device is either identified as potentially lost or a state of the tracking device is predicted, and in response, a notification is sent to a user of the tracking device.

[0091] During the performance of a tracking device intervention, a user can be notified of the predicted state of the tracking device or that the tracking device is potentially lost via a mobile device **102**, for instance via a notification displayed within a mobile device or application interface, via an audio signal or vibration signal, and the like. As also noted above, any of the tracking system **100**, the mobile device **102**, or a tracking device **106** can identify a tracking device is potentially lost or can predict a state of the tracking device, though the remainder of the description will refer to the tracking system identifying a tracking device as potentially lost for the purposes of simplicity.

[0092] A notification that a tracking device is potentially lost can include information about a last known location of the tracking device (for instance, displayed on a map displayed by a mobile device), can include information identifying the tracking device (such as a name of the tracking device, the identity of the object to which the tracking device is attached, or an icon corresponding to the tracking device), can include information identifying a tracking device collection to which the tracking device belongs (such as a name of the tracking device collection or an icon corresponding to the tracking device collection), and can include text indicating why the tracking device is thought to be lost or left behind (e.g., “you normally take your briefcase to work with you, and you left it behind today”). A notification of a predicted state of the tracking device can include information identifying the tracking device or a tracking device collection to which the tracking device belongs, can include information describing the predicted state of the tracking device (e.g., “you might want to bring this tracking device with you before you leave for work”), and can include information describing the circumstances under which the state of the tracking device is predicted (e.g., “it is warmer than normal outside today, don't forget to bring your water bottle”).

[0093] In some embodiments, a notification of a predicted state of the tracking device or identifying a tracking device as potentially lost can include an option to disregard the notification. For instance, if the notification indicates that a tracking device is potentially lost, the user can select an option displayed by or associated with the notification to identify the tracking device as not lost. Likewise, if the notification indicates a predicted state of the tracking device reminding a user to bring an object coupled to a particular tracking device, the user can select an option displayed by or associated with the notification to disregard the reminder. Likewise, in some embodiments, a notification that a tracking device is identified as potentially lost can include an option to confirm the tracking device as lost. In response to the selection of such an option by a user, the tracking system **100** can affirmatively classify the tracking device as lost according to the principles described herein.

[0094] The tracking system **100** can identify a tracking device **106** as potentially lost or can predict a future state of the tracking device based on a number of factors, including but not limited to: a proximity of a tracking device to one or more additional tracking devices, a proximity of a tracking device to a user's mobile device, a movement of a tracking device to more than a threshold distance away from a mobile device or one or more additional tracking devices, a location of a tracking device relative to a particular or pre-defined geographic location (such as GPS coordinates, a user's home, a user's place of employment, etc.), a location of a tracking device relative to particular or pre-defined geographic boundaries (such as boundaries within a map, property lines, and the like), based on a usage or movement behavior of the tracking device, based on a usage or movement behavior of a user or owner of a tracking device, based on information received from an external source (for instance, via an API corresponding to the API), based on information received from sensors within the tracking device or a user's mobile device (such as motion sensors), based on a current time or date, based on a low battery level, based on a malfunction of the tracking device or a tracking device component, or based on any other suitable factors. Circumstances in which the tracking system **100** can identify a tracking device **106** as potentially lost or can predict a state of the tracking device are described in greater detail below.

[0095] Tracking device proximity: The tracking system **100** can identify a tracking device **106** as potentially lost in response to determining that the tracking device is not located within a threshold distance (such as a wireless communicative range, a selected threshold distance, or a pre-determined distance) of a target device (such as a user's mobile device or of one or more additional tracking devices). For instance, if a tracking device is commonly located within a threshold distance of a user's mobile device, the tracking system **100** can flag the tracking device as potentially lost in response to a determination that the tracking device is located outside the threshold distance of the user's mobile device. In addition, if a tracking device is commonly located

within a threshold distance of a second tracking device, the tracking system can flag the tracking device as potentially lost in response to a determination that the tracking device is located more than a threshold distance away from the second tracking device. Likewise, if a tracking device is part of a tracking device collection, the tracking system **100** can flag the tracking device as potentially lost in response to a determination that the tracking device is located more than a threshold distance away from one or more additional tracking devices within the tracking device collection.

[0096] It should be noted that the determination that a tracking device is potentially lost in response to proximity to another tracking device, a tracking device collection, or a user's mobile device can be based on time. For instance, if two tracking devices are commonly located within a threshold distance of each other during normal work hours for a user, but aren't commonly located within the threshold distance of each other outside of work hours, the tracking system **100** may flag a first of the tracking devices as potentially lost only if the first tracking device is located more than the threshold distance from the second tracking device during work hours, and may not flag the first tracking device as potentially lost if the first tracking device is located more than the threshold distance from the second tracking device outside of work hours.

[0097] The tracking system **100** can determine that a tracking device **106** is not within a threshold proximity of a mobile device **102** by determining that the tracking device is outside of the transmission or communicative range of the mobile device. For instance, if the mobile device and the tracking device are configured to communicatively couple via the Bluetooth protocol, the tracking system **100** can determine that the tracking device **106** is outside of a threshold proximity of the mobile device **102** if the mobile device is unable to receive Bluetooth advertisements or communications from the tracking device. The tracking system **100** can determine that a first tracking device is not within a threshold proximity of one or more additional tracking devices by determining that the one or more additional tracking devices are within the transmission or communicative range of one or more mobile devices, and that the first tracking device is not within the transmission or communicative range of the one or more mobile devices. Likewise, the tracking system **100** can determine that a tracking device **106** is not within a threshold proximity of a mobile device **102** or one or more additional tracking devices by determining a location of the tracking device (e.g., from a community mobile device **104** different than the mobile device **102**, from a database storing a last known location of the tracking device, or from any other suitable source), and determining that the determined location of the tracking device is greater than a threshold distance away from the mobile device **102** or the one or more additional tracking devices.

[0098] In some embodiments, the tracking system **100** can flag a tracking device **106** as potentially lost in response to the movement of the tracking device from within a threshold distance of a mobile device **102** to greater than a threshold distance of the mobile device. In some embodiments, the tracking system **100** can flag a tracking device **106** as potentially lost in response to the severing of a communicative connection between the tracking device and a mobile device **102** (for instance, as a result of the movement of the tracking device and the mobile device away from each other). In some embodiments, a user can select the threshold distance used by the tracking system **100** to trigger a determination that the tracking device **106** is potentially lost, for instance via an interface of the mobile device **102**.

[0099] FIG. 6 illustrates a flowchart for a method of identifying a tracking device as potentially lost based on a threshold distance from a target device, according to one embodiment. Alternate embodiments may contain more, fewer, or different steps, or the steps may be performed in an order different from the one shown in FIG. 6.

[0100] The tracking system **100** receives **600** a location of a user's tracking device and receives **610** a location of a target device. In some embodiments, the tracking device location is received from a mobile device of a user different from the user to whom the tracking device belongs. The target device can be another tracking device, a user's mobile device, or any other suitable system. The

tracking system **100** determines **620** whether the tracking device location is more than a threshold distance from the target device location. If the tracking device location is determined to be more than the threshold distance from the target device location, the tracking system identifies **630** the tracking device as potentially lost. The tracking system **100** generates **640** a notification identifying the tracking device and indicating that the tracking device is potentially lost, and provides **650** the generated notification to the user's mobile device. The user's mobile device can be configured to display the notification to the user.

[0101] Examples: In some embodiments, the tracking system **100** notifies a user that a tracking device is potentially lost if the tracking device is not located with a threshold distance of the user's mobile device and if the tracking device is coupled with an object the user uses regularly. For example, the user may be notified as such if the tracking device is coupled to keys, a wallet, a phone, glasses, a watch, a laptop, a digital book/reader, or a tablet. The threshold distance can be selected by the user or the tracking system **100** such that the tracking device is on the user's person or within the user's immediate vicinity (e.g. ≤ 5 feet), or may be selected such that the user is reminded to bring the object when the user leaves an area (e.g. approximately 15 feet). In some embodiments, the user designates which tracking devices are coupled to objects the user uses regularly. The user may also designate time periods during which those designated tracking devices should be within a threshold distance of the user's mobile device. For example, the user may designate the user's work hours, workout hours, sleeping hours, dining hours, relaxation hours, traveling hours, class hours, or commuting hours.

[0102] In some embodiments, the tracking system may notify a user that a tracking device is potentially lost if a tracking device was located within the threshold distance of the user's mobile device when the user left a geographic location and the tracking device is not located within the threshold distance of the user's mobile device before the user returns to that geographic location. For example, if the tracking device is coupled to a tablet, if the user leaves home with the tablet and the tracking system **100** determines that the tablet tracking device is not within a threshold distance of the user's mobile device before the user returns home, the tracking system **100** may notify the user that the tablet tracking device is potentially lost. The threshold distance may be selected such that if the tracking device is near the user or in the user's car (e.g. 2-5 feet), the tracking device is not identified as potentially lost. Example geographic locations include the user's home, work, school, gym, or car.

[0103] In some embodiments, the tracking system **100** notifies the user that a tracking device coupled to car accessory may not be in the car based on whether the car accessory tracking device is located within a threshold distance of a tracking device coupled to the car. For example, if a tracking device coupled to the user's parking pass is not located within the threshold distance of a tracking device coupled to a car, the tracking system **100** may notify the user that the parking pass tracking device is not in the car. In such embodiments, the tracking system **100** may only notify the user if the user's mobile device is located within a threshold distance of the car tracking device. For example, the tracking system **100** may notify the user if a phone charger tracking device is not located within a first threshold distance of a car tracking device if the user is located within a second threshold distance of the car tracking device (e.g. if the user is in the car and about to leave).

[0104] In some embodiments, the tracking system **100** provides notifications to the user's mobile device if the user is traveling and based on whether the travel tracking device is located within a threshold distance of the user's mobile device. For example, if the user is on an airplane, the user may be notified that a travel tracking device (e.g. a luggage tracking device, a laptop tracking device, a phone tracking device) is not on the user's airplane if the travel tracking device is not located within a threshold distance of the user's mobile device or a tracking device coupled to the airplane. Additionally, the tracking system **100** may notify the user of a travel tracking device that is potentially lost if the travel tracking device is within a threshold distance of an airplane tracking

device and not within a threshold distance of the user's mobile device (e.g. the user left the travel tracking device on the airplane).

[0105] In some embodiments, the tracking system **100** notifies the user that the user's luggage was sent to the wrong airport. The tracking system **100** can notify the user of such a state if the user's mobile device is located within a threshold distance of one airplane tracking device, and a luggage tracking device is located within a threshold distance of another airplane tracking device (or a community member's mobile device) that is at a different airport from the airport of the first airplane.

[0106] In some embodiments, the tracking system **100** notifies the user if the user has potentially lost a tracking device coupled to the user's passport. If a passport tracking device is not located within a threshold distance of the user's mobile device or other travel tracking devices (such as a luggage tracking device, a travel bag tracking device, etc.) while the user's mobile device or the travel tracking devices are at a travel hub (e.g. airport, seaport, train station), the user may be notified that the passport tracking device is potentially lost.

[0107] In some embodiments, the tracking system **100** notifies the user that a tracking device may have been stolen from the user's car if the tracking device is not located within a threshold distance of a car tracking device. For example, if the user leaves a tracking device coupled to a laptop in a car, and the laptop tracking device is not located within a threshold distance of the car tracking device, the user may be notified that the laptop tracking device has left the car. The tracking system **100** may only notify the user that a tracking device is potentially stolen if the user's mobile device is not detected within a threshold distance of the car tracking device during the time period in which the potentially stolen tracking device was determined to be outside the threshold distance from the car. For example, a user may have left a laptop tracking device in a car, and as a result, the laptop tracking device may be within a threshold distance of a car tracking device. If the laptop tracking device is determined to be outside the threshold distance from the car tracking device before the user returns to the car (e.g. when the user's mobile device is within a threshold distance of the car tracking device), the user can be notified that the laptop tracking device has been stolen.

[0108] In some embodiments, the tracking system **100** notifies the user when a tracking device associated with a child is not located within a threshold distance of the user's mobile device. For example, a tracking device may be coupled to the child's phone, jacket, backpack, shoes, or toys. The user may configure the threshold distance of the child tracking device based on where the child is. For example, if the child is at the park, the threshold distance may be larger than if the child is at a theme park. In some embodiments, the user is notified when the child tracking device is not located within a threshold distance of another tracking device, such as a tracking device given to a baby sitter to locate the child tracking device. In these embodiments, if the child tracking device is not located within a threshold distance of the other tracking device, the tracking system **100** may notify the user through the user's mobile device that the child tracking device is outside the threshold distance of the user's mobile device or another tracking device.

[0109] In some embodiments, the tracking system **100** will notify the user of a potentially lost tracking device when the user's mobile device is at a particular geographic location/within a geographic boundary and when the tracking device is not located within a threshold distance of the user's mobile device. For example, if the user's mobile device is at a store, the tracking system **100** may notify the user of a potentially lost wallet tracking device if the wallet tracking device is not located within a threshold distance of the user's mobile device while the user is at the store. The tracking system **100** may flag one or more tracking devices from a particular collection of tracking devices depending on which geographic location or geographic boundary the mobile device is in. For example, if the mobile device is at the airport, the tracking system **100** may notify the user if a travel tracking device is not located within a threshold distance of the mobile device or another travel tracking device. If the mobile device is at the gym, the tracking system **100** may notify the user if a gym bag tracking device is not located within a threshold distance of the mobile device or

another workout tracking device. If the mobile device is at the beach, the tracking system **100** may notify the user if a beach gear tracking device is not located within a threshold distance of the mobile device or another beach tracking device. If the mobile device is at work, the tracking system **100** may notify the user if a work tracking device is not located within a threshold distance of the mobile device or another work tracking device. If the mobile device is at a campsite, the tracking system **100** may notify the user if a camping tracking device is not located within a threshold distance of the mobile device or another camping tracking device.

[0110] Geographic location: The tracking system **100** can identify a tracking device **106** as potentially lost in response to determining that the tracking device is more than a threshold distance from a selected geographic location (for instance, defined by geographic coordinates), or outside of an area defined by a selected geographic boundary (for instance, boundaries associated with a house or building, boundaries associated with property lines or a property lot, and the like). The geographic location or geographic boundary can be defined or selected by a user, for instance, via an interface of the mobile device **102** or of the tracking system **100**. For example, a user can define a set of GPS coordinates as a selected location, or can draw a set of geographic boundaries within a map interface. In some embodiments, a user can select a threshold distance or can change a pre-set threshold distance for use in conjunction with a selected geographic location (such that tracking devices located more than the selected threshold distance are identified as potentially lost).

[0111] The geographic location or geographic boundary can also be selected (for instance, by the tracking system **100**) based on historical location data associated with the tracking device **106**, a user, or a mobile device **102** associated with the user. For instance, if a tracking device **106** is commonly located within a geographic boundary associated with a user's work building during week day working hours, the geographic boundary can be selected by the tracking system **100** for use in determining if the tracking device is potentially lost. Likewise, if a tracking device **106** is commonly located within a threshold distance of a user's home on the weekend, a geographic location corresponding to the user's home (e.g., a set of GPS coordinates over which the user's home is located) can be selected by the tracking system **100** for use in determining if the tracking device is potentially lost.

[0112] In some embodiments, the tracking system **100** can identify a potential geographic location or geographic boundary for use in determining if a tracking device **106** is potentially lost based on historical location data associated with the tracking device, a user, or a mobile device of the user, and can present the potential geographic location or geographic boundary to the user. For instance, an application associated with the tracking system **100** can display a set of selectable potential geographic locations or geographic boundaries to the user, and can display information associated with the historical location data upon which each potential geographic location or geographic boundary is identified (for instance, the application can display a potential geographic location in conjunction with the text "recommended based on the location of this tracking device during weekdays between the hours of 9 am and 5 pm"). If the user selects the potential geographic location or geographic boundary, the tracking system **100** can store the geographic location or geographic boundary for future use in determining if the tracking device **106** is lost.

[0113] The tracking system **100** can determine that a tracking device **106** is not located within a threshold distance of a geographic location or is not located within a geographic boundary if 1) a location of the tracking device is received from a community mobile device **104** and 2) if the received location is more than a threshold distance away from the geographic location or is located outside of the geographic boundary. Alternatively, the tracking system **100** can determine that a tracking device **106** is located more than a threshold distance away from a geographic location or outside of a geographic boundary in response to 1) determining that a mobile device **102** of a user is located within the threshold distance of the geographic location or within the geographic boundary and 2) determining that the tracking device is not located within the communicative or transmission range of the mobile device (for instance, by determining that the mobile device cannot

communicatively couple to the tracking device). In such embodiments, the communicative or transmission range of the mobile device **102** can be greater than the range defined by the geographic location and the threshold distance, and greater than the range defined by the geographic boundary.

[0114] FIG. 7 illustrates a flowchart for a method of identifying a tracking device as potentially lost based on a threshold distance from a geographic location, according to one embodiment. Alternate embodiments may contain more, fewer, or different steps, or the steps may be performed in an order different from the one shown in FIG. 7.

[0115] The tracking system **100** receives **700** a location of a user's tracking device. In some embodiments, the tracking device location is received from a mobile device of a user different from the user to whom the tracking device belongs. The tracking system **100** determines **710** if the tracking device location is more than a threshold distance from a geographic location. As described above, in alternate embodiments, the tracking system determines if the tracking device location is outside of a geographic boundary. If the tracking system **100** determines that the tracking device location is more than the threshold distance from the geographic location (or outside the geographic boundary), the tracking system identifies **720** the tracking device as potentially lost. The tracking system **100** generates **730** a notification identifying the tracking device and indicating that the tracking device is potentially lost, and provides **740** the generated notification to the user's mobile device. The user's mobile device can be configured to display the notification to the user.

[0116] Examples: In some embodiments, the tracking system **100** notifies the user when a tracking device coupled to a set of keys leaves a geographic boundary. For example, if a business provides a set of keys to a temporary employee or a contractor, the tracking system **100** may notify the user when a keys tracking device is not located within a threshold distance of a geographic location or within a geographic boundary associated with an office of the business.

[0117] In some embodiments, a tracking device is coupled to a lifting weight or some other piece of exercise equipment and the tracking system **100** notifies the user when the lifting weight tracking device leaves a gym. Each lifting weight or piece of exercise equipment in a gym may be coupled to a tracking device and the notification to the mobile device may include information that identifies which lifting weight was not located within the gym.

[0118] In some embodiments, if the mobile device is located near a tourist destination and a tracking device coupled to a camera is located within a threshold distance of the mobile device, the tracking system **100** may notify the user through the mobile device that they may want to take out their camera and take pictures of the tourist destination.

[0119] In some embodiments, the tracking system **100** notifies the user that the user's car is potentially stolen if the car tracking device coupled to the user's car is located outside of a threshold distance from the geographic location where the user parked the car. The tracking system can determine a geographic location for where the user parked the car based on the geographic location of the car tracking device when the mobile device exceeded a threshold distance away from the car tracking device (e.g., when the user walked more than a threshold distance away from the car). If the car tracking device is located more than a threshold distance from the parking location, the tracking system **100** can notify the user that the car has potentially been stolen.

[0120] In some embodiments, the tracking system **100** notifies a user if a tracking device is not located within a room or a house. For example, if a tracking device is coupled to an object that is not supposed to leave a room (e.g. a remote control, reading glasses), the tracking system **100** may notify the user if the tracking device leaves the room/is not located within the room. The tracking system **100** may also notify the user that a tracking device coupled to a valuable item (such as a safe, a jewelry box, artwork, a television, a computer, etc.) may have been stolen from a house if the tracking device coupled to the valuable item is not located within the house.

[0121] In some embodiments, the tracking system **100** notifies the user if their child is not at a geographic location at which the child is supposed to be. If a tracking device associated with the

child (e.g., a tracking device coupled to the child's bag or jacket) is not located within a threshold distance of a geographic location or within certain geographic boundaries (e.g. home, school, art/performance/music lessons, sport practice, friend's house), the user may be notified that the child is not located where they are supposed to be and may be provided with the location of the child tracking device.

[0122] In some embodiments, the tracking system **100** notifies the user if a tracking device coupled to a pet is not located within a threshold distance of the user's home or within the geographic boundaries of the user's home. For example, if the user's pet escapes or is stolen, the tracking system **100** can notify the user that the pet tracking device is not located within the user's home and can provide the location of the pet tracking device. In some embodiments, the tracking system **100** notifies the user if the pet tracking device enters a particular part of the user's home. For example, if the pet is not supposed to be inside the house or not supposed to be in a particular room of the house, the tracking system can notify the user that the pet tracking device is not where it is supposed to be based on whether the pet tracking device is or is not located within a threshold distance of a geographic location or whether the pet is or is not located within a geographic boundary.

[0123] Tracking device behavior: The tracking system **100** can identify a tracking device **106** as potentially lost in response to a comparison of current tracking device behavior and location and historical tracking device behavior and location. For instance, the tracking system **100** can determine that a tracking device **106** commonly accompanies a user on the user's way to work based on an analysis of historical location data associated with the tracking device, and can flag the tracking device as potentially lost in response to determining that the tracking device is not accompanying the user on the user's way to work. Likewise, the tracking system **100** can determine that the tracking device **106** typically does not move between the hours of 10 am and 4 pm on weekdays based on an analysis of historical movement data associated with the tracking device, and can flag the tracking device as potentially lost in response to a determination that the motion of the tracking device exceeds a pre-determined motion threshold during this time interval. In addition, the tracking system **100** can determine that the tracking device **106** commonly communicatively connects with a mobile device **102** of a user after 10 pm on weekends based on an analysis of historical communication data associated with the tracking device, and can flag the tracking device as potentially lost in response to a determination that the tracking device has not communicatively connected to the mobile device on a weekend day after 10 pm after the passage of a threshold amount of time.

[0124] The tracking system **100** can predict a future state of the tracking device **106** based on a comparison of historical data associated with the tracking device. For instance, the tracking system **100** can determine that a tracking device **106** commonly travels between a first location and a second location between the hours of 5 pm and 6 pm, and can predict that the tracking device will be located at the second location after 6 pm in the event that the tracking device is outside the communicative range of a user's mobile device. Continuing with this example, the tracking system **100** can determine that the tracking device **106** commonly takes 30 minutes to reach the second location after leaving the first location, and can predict that the tracking device will reach the second location approximately 30 minutes after detecting that the tracking device has left the first location. Historical data analyzed by the tracking system **100** can include when, where, or how often the tracking device connects with the mobile device. In some embodiments, the tracking system **100** can analyze historical behavior of other tracking devices for use in predicting a state of the tracking device **106**. In such embodiments, historical location and movement patterns of other tracking devices can be used to predict a location and/or movement of the tracking device **106** in response to a determination that the tracking device is undergoing similar location and movement patterns.

[0125] Examples: In some embodiments, the tracking system **100** identifies collections of tracking

devices, as described above, for instance based on a history of the tracking devices tending to be located near each other or based on a collection definition from a user, and can notify the user that a tracking device of a collection is lost if the tracking device is not located near tracking devices in a collection. For example, the tracking system may determine that a keys tracking device and a wallet tracking device are typically located near each other, and thus may include the keys tracking device and the wallet tracking device in a collection. If the keys tracking device is subsequently not located near the wallet tracking device, the user may be notified that the keys tracking device or the wallet tracking device is potentially lost. In some embodiments, the tracking system **100** identifies tracking devices that are typically located near each other and may prompt the user to create a collection of the tracking devices or to add one or more of the tracking devices to an existing collection. For example, if the tracking system **100** determines that a toiletry bag tracking device is typically located near a suitcase tracking device, the tracking system **100** may prompt the user to add the toiletry bag tracking device to a travel tracking device collection.

[0126] In some embodiments, the tracking system **100** can notify the user that a car tracking device is potentially stolen based on the behavior of the car tracking device. For example, if the car tracking device is typically parked within a threshold distance of a geographic location during particular hours (e.g. while the user is typically home or asleep), the tracking system **100** may notify the user if the car tracking device is not located within that threshold distance. The tracking system may also determine that a keys tracking device is typically located near the car tracking device when the car tracking device is moving, and may notify the user that the car tracking device is potentially stolen if the car tracking device is moving when not near the keys tracking device.

[0127] In some embodiments, the tracking system **100** can notify the user that a car coupled to a tracking device has been in a car accident. The tracking system **100** may determine if the car tracking device stops suddenly or begins to move erratically and may identify that behavior as indicative of a car accident. The tracking system **100** may send a notification to the user about the potential car accident, and the notification may include an option to automatically send emergency assistance (e.g. an EMT, paramedic, fire fighters, the police) to the location of the car tracking device. If the mobile device is not located near the car tracking device, the notification may include the location of the car tracking device. If the mobile device is located near the car tracking device (e.g. within a threshold distance), the tracking system **100** may automatically notify an emergency assistance service (e.g. 911) of the car accident and may transmit the location of the car tracking device or the mobile device to the emergency assistance service.

[0128] In some embodiments, the tracking system **100** can notify the user with an estimate for how long it will take for the user's luggage to arrive at the luggage carousel from an airplane. The tracking system **100** may analyze the amount of time it takes luggage tracking devices of other users to arrive at the luggage carousel and provide an estimate based on those amounts of time. In some embodiments, the tracking system **100** determines an estimate for the amount of time will take for a luggage tracking device to arrive at the luggage carousel based on which airport the user has arrived at. The tracking system **100** may also analyze the paths luggage tracking devices take in an airport from an airplane to a luggage carousel and, based on those paths, provide a real-time time estimate to the user. For example, if the average wait time is 30 minutes and the luggage tracking device is half way to the luggage carousel from the airplane, the tracking system **100** may update the wait time estimate to 15 minutes.

[0129] In some embodiments, the tracking system **100** notifies the user if a tracking device typically does not move and the tracking device suddenly begins to move. For example, a tracking device may be coupled to an object that typically does not move, such as a piece of art, a safe, an unused car, a desktop computer, a passport, or a file cabinet. If the tracking device moves (e.g. is located in a location different from where it was originally, or a motion-detection sensor of the tracking device, such as an accelerometer, detects movement), the tracking system **100** may notify the user that the tracking device is potentially lost or stolen. In some embodiments, the tracking

system **100** only notifies the user that the tracking device has moved if the mobile device is not located within a threshold distance of the tracking device.

[0130] In some embodiments, the tracking system **100** notifies the user if a pet coupled to a pet tracking device is taken for a walk. The tracking system **100** may determine if a pet is being taken out for a walk if the pet tracking device is following a path that the pet tracking device follows regularly (e.g. weekly, when a pet walker comes to walk the pet). If the pet tracking device deviates from paths the pet tracking device has taken in the past, the tracking system **100** may notify the user that the pet is potentially lost rather than that the pet is on a walk. Additionally, if the tracking system **100** determines that the pet is on a walk but that the path taken by the pet tracking device is different from a typical path of a walk (e.g. significantly longer or shorter), the tracking system **100** may provide a notification describing the difference to the user.

[0131] User behavior: The tracking system **100** can identify a tracking device **106** as potentially lost in response to a comparison of current user location and behavior and historical user location and behavior. For instance, the tracking system **100** can determine that a user commonly brings a tracking device **106** with the user during particular times of the day (determined, for instance, based on historical communicative connections between the tracking device and a mobile device **102** of the user). In such instances, if the user is determined to not have the tracking device **106** during similar times of the day, the tracking system **100** can flag the tracking device as potentially lost. Likewise, the tracking system **100** can determine that when a mobile device **102** of a user is historically communicatively connected to a first tracking device in a collection of tracking devices, the user is historically commonly connected to the remaining tracking devices in the collection of tracking devices. In such instances, if the user's mobile device **102** is communicatively connected to the first tracking device in the collection but not the second tracking device in the collection, the tracking system **100** can flag the second tracking device as potentially lost.

[0132] The tracking system **100** can predict a state of a tracking device **106** based on historical user location and behavior. For instance, the tracking system **100** can determine that users commonly bring a particular type of object coupled to a tracking device when the users move from a first location to a second location. In such instances, the tracking system **100** can determine that the user of a tracking device **106** coupled to the particular type of object is in the first location, and can predict that the user will want to bring the object to the second location. Likewise, the tracking system **100** can determine that a user commonly drives a particular vehicle on weekend mornings, and can predict that the user will need to bring the user's wallet coupled to a tracking device **106** before the user drives the vehicle.

[0133] FIG. **8** illustrates a flowchart for a method of identifying a tracking device as potentially lost based on historical movement behavior, according to one embodiment. Alternate embodiments may contain more, fewer, or different steps, or the steps may be performed in an order different from the one shown in FIG. **8**.

[0134] The tracking system **100** determines **800** a current movement behavior of a user's tracking device, and determines **810** a historical movement behavior. The historical movement behavior can be historical movement behavior of the tracking device, the user, or the user's mobile device. It should also be noted that in some embodiments, the tracking system **100** can determine a current movement behavior of a user, or of a user's mobile device. The tracking system **100** determines if the current movement behavior differs from the historical movement behavior. If the current movement behavior differs from the historical movement behavior (e.g. by more than a threshold amount), the tracking system identifies **830** the tracking device as potentially lost. The tracking system **100** generates **730** a notification identifying the tracking device and indicating that the tracking device is potentially lost, and provides **740** the generated notification to the user's mobile device. The user's mobile device can be configured to display the notification to the user.

[0135] Examples: In some embodiments, the tracking system **100** notifies the user if the user has

potentially dropped a tracking device. For example, if the tracking system **100** detects that the user may have dropped a tracking device coupled to the user's keys or wallet, the tracking system **100** may notify the user that the tracking device was potentially dropped and provide the location of the tracking device to the user in the notification. The tracking system **100** may detect a dropped tracking device if the tracking device is moving similarly to and in conjunction with the mobile device and the tracking device stops moving while the mobile device keeps moving, or the movement of the tracking device differs by more than a threshold from the movement of the mobile device. In some embodiments, the tracking system **100** provides notifications to the user based on the user's routine. If the user regularly visits a location during a particular time period and brings one or more tracking devices while visiting the location, the tracking system **100** may provide notifications to the user that remind the user to bring the tracking devices or notify the user that they potentially forgot to bring one or more of the tracking devices. For example, if the user visits a gym every week, the tracking system **100** may provide notifications to the user to bring gym tracking devices (e.g. a gym shoes tracking device or a gym bag tracking device) to the gym. Similarly, if the user travels regularly, the tracking system **100** may notify the user to bring travel tracking devices (e.g. a passport tracking device or a luggage tracking device) before the user travels to the airport. If the user is a student and goes to class regularly, the tracking system **100** can provide a notification to bring tracking devices coupled to class supplies (e.g. textbooks, a laptop, pencil case, notebook, homework/homework folder), or may notify the user if the user has potentially forgotten a class supply tracking device. In some embodiments, the user can specify routine activities for which the tracking system **100** should provide notifications or can specify time ranges during which the tracking system **100** should provide notifications. For example, if the user goes to the gym on Tuesdays, the user may specify to the tracking system **100** to provide reminder notifications about gym tracking devices on Tuesdays or when the user is going to or at the gym.

[0136] In some embodiments, the tracking system **100** can provide reminder notifications to the user to use objects that the user needs to interact with regularly. The tracking system **100** may determine if the user is near a tracking device coupled to one of the objects and, if the user has not been near the tracking device within a certain time period, the tracking system **100** may notify the user to use the object coupled to the tracking device. For example, the user may be notified to use a pill box/medicine, a toothbrush, a mouth guard, or weights/exercise equipment. In some embodiments, the tracking device is coupled to an object that is related to a chore the user needs to perform on a regular basis, such as a pet food bowl, a mailbox, a washer/dryer, a dishwasher, a sink, or a trash can.

[0137] External data: The tracking system **100** can identify a tracking device **106** as potentially lost or can predict a state of the tracking device based on data received from an external data source **112**. The external data source **112** can be an external database, a website, a digital or network service, an external device or system, a communication, or any other suitable source. In some embodiments, data can be requested from the external data source **112** by the tracking system **100** or a mobile device **102**, for instance via an API associated with the external source. The data can be requested from the external data source **112** at the explicit request of a user of the mobile device **102**, periodically, or in response to the occurrence of an event (for instance, the movement of a tracking device **106**, the communicative coupling of the tracking device to the mobile device, locating the tracking device, the movement or location of the user, or any other suitable criteria).

[0138] FIG. **9** illustrates a flowchart for a method of identifying a tracking device as potentially useful to user based on external data, according to one embodiment. Alternate embodiments may contain more, fewer, or different steps, or the steps may be performed in an order different from the one shown in FIG. **9**.

[0139] The tracking system **100** determines **900** a location of a user's tracking device, where the tracking device is coupled to an object. The tracking system **100** determines **910** a location of a

user, and determines **920** whether the tracking device location is more than a threshold distance from the user's location. If the tracking device location is more than the threshold distance from the user location, the tracking system **100** accesses **930** external data from an external source, where the external data is associated with the object coupled to the tracking device. The tracking system **100** determines **940** that possession of the object is likely to be useful to the user based on the external data. The tracking system **100** generates **950** a notification identifying the tracking device and recommending that the user obtain the object, and provides **960** the generated notification to the user's mobile device. The user's mobile device can be configured to display the notification to the user.

[0140] Examples: In some embodiments, the tracking system **100** receives financial transaction information from a bank or a budgeting system to detect fraudulent charges to the user's account. The tracking system **100** may receive information identifying transactions charged to the user's credit card and identifying where the transactions occurred. If a transaction occurred at a store that the wallet tracking device has not been in or was not in at the time of the transaction, the tracking system **100** may notify the user that the transaction at the store is potentially fraudulent. In some embodiments, the notification of the potential fraudulent charge may include an option to notify the credit card company of the fraudulent charge.

[0141] In some embodiments, the tracking system **100** receives sales information from a vendor system regarding sales that are available near the user based on tracking devices near the user. If the tracking system **100** detects that a tracking device is near the user (e.g. within a threshold distance of the mobile device), and the tracking device is coupled to an object, the tracking system **100** may provide a notification with information about a sale that is relevant to the object. For example, if the user is carrying a gym bag tracking device and is walking through a store, the tracking system **100** may notify the user that there is a sale on energy drinks or water. In some embodiments, the tracking system **100** provides notifications with sales information based on a tracking device not being located near the user. For example, if the user is carrying a luggage tracking device, but a toiletry bag tracking device is not located near the user, the tracking system **100** may notify the user of sales to purchase toiletries in a nearby store.

[0142] In some embodiments, the tracking system **100** receives parking regulation information from a database. The parking regulation information may describe where a user can park a car and for how long the user can park the car there. The tracking system **100** can provide notifications to a user if the user has parked their car in a spot for too long. For example, if a car tracking device is located in a parking spot that has a two hour parking limit, the user may be notified after an hour and a half that the car tracking device needs to be moved soon. If the user paid a parking meter for the parking spot, the tracking system **100** may provide a notification to the user when the parking meter timer is getting low, and the notification may include an option to pay more money into the parking meter. In some embodiments, the tracking system **100** determines which parking meter is associated with the car tracking device based on the location of the car tracking device.

Additionally, the tracking system **100** may notify the user if the car tracking device is potentially parked in a parking spot that the car is not allowed to be parked in. For example, if street parking on a street is restricted on Mondays and the car tracking device is located on the restricted street on a Monday, the user may be notified that their car is potentially parked illegally.

[0143] In some embodiments, the tracking system **100** receives information about a user's schedule and provides notifications to the user based on the user's schedule. The schedule information can include information about a user's calendar from a calendaring system or a user's messages (e.g. emails, texts, instant messages) from a messaging system. The schedule information may describe events the user must attend, including what the events are, when they are, and where they are. The tracking system **100** may provide notifications to the user to remind the user to bring certain tracking devices to an event or to notify the user that they potentially left a tracking device behind. For example, the tracking system **100** may remind the user to bring a wallet tracking device, a keys

tracking device, a watch tracking device, or a glasses tracking device to events on the user's schedule. In some embodiments, the tracking system **100** provides a notification to the user based on what event is on the user's schedule. For example, if the schedule information shows that the user is going to class and does not have a class tracking device (e.g. a textbook tracking device, pencil case tracking device, notebook tracking device), the tracking system **100** may notify the user that they potentially forgot the class tracking device. In some embodiments, the schedule information includes the type of the class (e.g., Biology, English, History) the user needs to attend, and the tracking system **100** may identify the class tracking device as potentially lost based on the type of the class.

[0144] In some embodiments, the tracking system **100** receives travel information for the user from a travel agency or a transport service and provides notifications based on the travel information. The travel information can include the user's start location, destination, departure time, arrival time, or transportation hubs the user may be traveling through. In some embodiments, the travel information is determined based on the user's emails or calendar received by the tracking system **100**. The tracking system **100** may provide a notification to the user to pack certain objects based on the user's destination. For example, if the user is traveling to a cold place and a jacket tracking device is not located near a luggage tracking device, the tracking system **100** may notify the user that they should pack a jacket. The tracking system **100** can notify the user that their luggage is potentially lost if a luggage tracking device is not located at the correct transportation hub (determined based on information received from a travel system) when the user arrives at the transportation hub. For example, if a luggage tracking device is located at an airport that is different from the one the user arrived at, the user may be notified that the luggage tracking device is at the wrong airport.

[0145] In some embodiments, the tracking system **100** can notify a travel hub or a transportation service if a user's luggage takes a long time to reach a luggage carousel or if the user's luggage was lost. The tracking system **100** can determine if a user's luggage took a long time to reach a luggage carousel or if the user's luggage was lost based on the location of a luggage tracking device. If the tracking system **100** notifies the travel hub or transportation service about delayed or lost luggage, the tracking system **100** may receive a coupon, gift card, offer, or the like for the user from the travel hub or transportation service. For example, the travel hub or transportation service may provide the user with an offer for a free coffee or a discount on a future trip.

[0146] In some embodiments, the tracking system **100** receives weather information from a weather service and can provide notifications to the user based on the weather information. The weather information includes information about the weather in a geographic area, including high and low temperatures, rain/snow forecasts, wind forecasts, or humidity forecasts. The tracking system **100** may provide notifications to the user if the user is not located near a tracking device coupled to an object that will be necessary or helpful for the forecasted weather in the weather information. For example, if the weather information forecasts rain in the user's geographic area and a jacket tracking device is not located near the user, the tracking system **100** may notify the user that it will rain soon and that the user does not have their jacket. The user may receive a similar notification if the user is not located near an umbrella tracking device, a rain boot tracking device, or a hat tracking device. Similarly, if the weather information forecasts snow in the user's geographic area, the tracking system **100** may provide the user with a notification reminding them to bring a coat tracking device, an ear muff tracking device, or a scarf tracking device. If the weather information forecasts warm weather in the user's geographic area, the tracking system **100** may provide the user with a notification reminding them to bring a water bottle tracking device, a sunscreen tracking device.

[0147] In some embodiments, the tracking system **100** receives information about natural disasters or emergency situations near the user and may notify the user of the locations of tracking devices coupled to emergency supplies. Examples of natural disasters can include flooding, hurricanes,

tornados, earthquakes, and forest fires. Examples of emergency situations can include power outages, water outages, police activity, and building fires. The tracking system **100** can notify a user of the location of tracking supplies coupled to emergency supplies, including a fire extinguisher, extra water, extra food, and flashlights. In some embodiments, the tracking system **100** notifies the user of the location of a tracking device coupled to an object carried by the user's child if the tracking system receives information about a natural disaster or emergency situation.

[0148] Sensor data: The tracking system **100** can identify a tracking device **106** as potentially lost or can predict a state of the tracking device based on data received from one or more tracking device sensors. The tracking device sensors can include one or more of: movement sensors (such as accelerators, gyroscopes, and the like), location determination sensors (such as a GPS transceiver, altimeters, and the like), orientation sensors, proximity sensors, communication sensors (such as a Bluetooth antenna or a Wifi antenna), temperature sensors, pressure sensors, light sensors, touch sensors (such as a capacitive touch screen), audio sensors (such as a microphone), or any other suitable sensor. The tracking device **106** can obtain sensor data in response to requesting sensor data from the sensors, automatically (as the sensors receive/generate the data), in response to a request from a mobile device **102** or a user of the mobile device, in response to a request from the tracking system **100**, and the like. The tracking device **106** can forward the sensor data to a mobile device **102**, which in turn can forward the sensor data to the tracking system **100**.

[0149] The tracking system **100** can identify a tracking device **106** as potentially lost based on sensor data received from the tracking device. For instance, if a user leaves the tracking device **106** at home, and sensor data is received from the tracking device indicating that the tracking device has moved, the tracking system **100** can identify the tracking device as potentially lost (or in this case, potentially stolen). Likewise, if sensor data is received from a first tracking device indicating that a temperature has fallen below a particular threshold, the tracking system can predict that a user might need an object coupled to a second tracking device in order to stay warm.

[0150] FIG. **10** illustrates a flowchart for a method of identifying a tracking device as potentially lost based on sensor data, according to one embodiment. Alternate embodiments may contain more, fewer, or different steps, or the steps may be performed in an order different from the one shown in FIG. **10**.

[0151] The tracking system **100** determines **1000** a location of a user's tracking device that is coupled to an object. The tracking system **100** determines **1010** a location of a user, and determines **1020** whether the tracking device location is more than a threshold distance from the user's location. If the tracking device location is more than the threshold distance from the user location, the tracking system **100** accesses **1030** sensor data from one or more sensors within the tracking device. The tracking system **100** identifies **1040** identifies the tracking device as potentially lost based on the sensor data. The tracking system **100** generates **1050** a notification identifying the tracking device and identifying the tracking device as potentially lost, and provides **1060** the generated notification to the user's mobile device. The user's mobile device can be configured to display the notification to the user. Examples: In some embodiments, the tracking system **100** uses accelerometer data from an accelerometer in a tracking device to determine if the user has dropped the tracking device and may identify the tracking device as potentially lost. For example, if the accelerometer data describes a sudden downward acceleration of the tracking device and then a sudden deceleration as the tracking device reaches the ground, the tracking system **100** may notify the user that the user potentially dropped the tracking device. In some embodiments, the tracking system **100** only notifies the user that the tracking device is potentially lost if the tracking device is not located within a threshold distance of the user.

[0152] In some embodiments, the tracking system **100** uses thermometer data from a thermometer in a tracking device to notify a user if an area is too warm or too cold for an object coupled to the tracking device or if the tracking device is outside when it should not be. The tracking system **100** may notify the user that the tracking device is potentially lost or that the tracking device is outside.

For example, if the user leaves their pet outside on a cold day and thermometer data from a pet tracking device indicates that the temperature is below a threshold, the tracking system **100** may notify the user that it is potentially too cold outside for the pet. Similarly, if the user leaves a laptop tracking device outside, the tracking system **100** may notify the user that the laptop is potentially lost based on thermometer data from the tracking device that it is warm. Such a tracking device can be coupled to a laptop, a child, a pet, a book, a wallet, keys, or any other object a user may leave outside.

[0153] In some embodiments, the tracking system **100** uses altimeter data from an altimeter in a water bottle tracking device to notify the user to drink water to keep hydrated. If the tracking system **100** determines that the water bottle tracking device is located near the user, and the altimeter data from the water bottle tracking device indicates that the water bottle tracking device is at a high altitude, the tracking system **100** may provide a notification to the user to drink from the water bottle to keep hydrated. Similarly, if the user is at a high altitude and a water bottle tracking device is not located near the user, the user may be notified that the water bottle tracking device is lost or that the water bottle tracking device should be brought with the user when the user goes outside. If the user is at a high altitude, the tracking system **100** also may notify the user to use or find a tracking device coupled to sunscreen, a hat, a jacket, a backpack, sunglasses, or any other object that may be helpful in a high altitude environment. In some embodiments, the tracking system uses thermometer data from a thermometer in the water bottle tracking device to notify the user to drink water.

[0154] In some embodiments, the tracking system **100** receives barometer data from a barometer in a tracking device to determine if it is about to rain. If the barometer data indicates that it is about to rain (e.g. the barometric pressure begins to drop) and a rain-gear tracking device (e.g. a jacket tracking device) is not located near the user, the tracking system **100** may notify the user that the rain-gear tracking device is lost or that the user should bring the rain-gear tracking device when going outside.

[0155] In some embodiments, the tracking system **100** uses audio data from an audio sensor in a tracking device to determine if an object coupled to the tracking device is potentially being stolen. If the audio data from a tracking device indicates that a window or a door has been broken, the tracking system **100** may notify the user that someone may be breaking into their house and may identify the tracking device as potentially lost. The tracking system **100** also may use accelerometer data to determine if a tracking device coupled to an object has been stolen. For example, if audio data indicates that a window has been broken and/or accelerometer data indicates that the tracking device is moving, the tracking system **100** may notify the user that the tracking device has potentially been stolen and may identify the tracking device as potentially lost.

[0156] It should be emphasized that in some embodiments, identifying a tracking device as lost or predicting a state of a tracking device can be based on any combination of the above circumstances. For example, a tracking device can be identified as potentially lost based on a proximity of the tracking device to other tracking devices and based on historical behavior of the tracking device. Likewise, a state of the tracking device can be predicted based on a combination of a movement of the tracking device and based on sensor data received from the tracking device.

[0157] Examples: In some embodiments, the tracking system **100** uses audio data from an audio sensor in a tracking device and the tracking device's proximity to a geographic location to notify the user that the tracking device has potentially been stolen. If the audio data from a tracking device indicates that a window or a door has been broken, and the tracking device is not located within a threshold distance of a geographic location or within certain geographic boundaries (e.g. a user's home), the tracking system **100** may notify the user that the tracking device has potentially been stolen.

[0158] In some embodiments, the tracking system **100** can notify the user of potential fraudulent financial transaction based on the behavior of a wallet tracking device. The tracking system **100**

can receive financial transaction information from a bank or a budgeting system. If the financial transaction information describes a financial transaction at a store, but the historical behavior of the wallet tracking device suggests that the user has not been in the store, the tracking system **100** may notify the user of the potentially fraudulent financial transaction. For example, if the financial transaction information includes a credit card charge at a first restaurant on a Wednesday, however the wallet tracking device is typically located in another restaurant on Wednesdays, the tracking system **100** may notify the user of the potentially fraudulent charge at the first restaurant.

[0159] The tracking device system **100** can prompt a user of a mobile device **102** to opt-in to one or more types of interventions, for instance via a mobile device interface. For example, the tracking system **100** can determine that a tracking device **106** is part of a tracking device collection, and can suggest to a user of a mobile device **102** that the mobile device receive intervention notifications when the distance between the tracking device and other tracking devices in the tracking device collection exceeds a threshold. If the user opts-in to a suggested intervention, the tracking system **100** stores the opt-in and provides notifications associated with the intervention in response to the circumstances associated with the intervention being trigger. If the user does not opt-in to a suggestion intervention, the tracking system **100** will not provide notifications associated with the intervention, even if the circumstances associated with the intervention are triggered.

[0160] FIG. **11** illustrates a flowchart for a method of generating an opt-in notification for identifying a tracking device as potentially lost, according to one embodiment. Alternate embodiments may contain more, fewer, or different steps, or the steps may be performed in an order different from the one shown in FIG. **11**.

[0161] The tracking system **100** accesses **1100** criteria for identifying a user's tracking device as potentially lost. The criteria can be associated with one or more properties of the tracking device. The tracking system **100** accesses **1110** information associated with the one or more properties of the tracking device, and identifies **1120** the tracking device as potentially lost based on the accessed criteria and the accessed information associated with the one or more properties of the tracking device. The tracking system **100** generates **1130** an interface including an option to opt-in to notifications identifying the tracking device as potentially lost in response to the accessed criteria being satisfied, and provides **1140** the generated interface to the user's mobile device. The mobile device can be configured to display the interface to the user. In response to the user opting-in to receiving the notifications, the tracking system **100** generates **1150** a notification that the tracking device is potentially lost and provides the generated notification to the mobile device for display to the user.

[0162] In some embodiments, the tracking system **100** can prompt a user of a mobile device **102**, via a notification presented by the mobile device, to configure a tracking device **106** to operate in a particular mode based on a predicted state of the tracking device. For instance, if a tracking device **106** is predicted to be in motion or is predicted to move to an unfamiliar location, the tracking system **100** can instruct the mobile device **102** to display a notification including an option to configure the tracking device to operate in a high performance mode (e.g., the tracking device can increase a frequency of advertisements/communications broadcasted by the tracking device to increase the likelihood that the tracking device is able to communicatively couple to the mobile device or a community mobile device **104**). Likewise, if a tracking device **106** is predicted to be stationary for an interval of time, the tracking system **100** can instruct the mobile device **102** to display a notification including an option to configure the tracking device to operate in a power saving mode (e.g., the tracking device can decrease the frequency of advertisements/communications broadcasted by the tracking device in order to preserve power).

[0163] If the user selects to reconfigure the tracking device **106** to operate in a particular mode as suggested by the notification (for instance, by selecting a selectable option displayed by the notification), the mobile device **102** can reconfigure the tracking device, and can inform the tracking system **100** that the user reconfigured the tracking device. In the future, if the tracking

system **100** predicts a similar tracking device state, the tracking system can instruct the mobile device **102** to similarly configure the tracking device **106** without requiring the mobile device to display a similar notification and without requiring the user to affirmatively select to configure the tracking device to operate in the suggested mode.

[0164] Examples: In some embodiments, the tracking system **100** prompts the user to opt into notifications about a luggage tracking device if the tracking system **100** determines the user is traveling. The user can select to receive notifications about whether the luggage tracking device is on the correct airplane, whether the luggage tracking device arrived at the correct airport, or an estimate for how long it will take for the luggage tracking device to arrive at a luggage carousel.

[0165] In some embodiments, the tracking system **100** prompts the user to opt into or modify the circumstances under which the user is notified when a tracking device is not located within a threshold distance of the mobile device. For example, if the user leaves a wallet tracking device or a keys tracking device on a desk in the user's office and the user leaves the office without bringing the wallet tracking device or the keys tracking device, the user may not want a notification while the user is still within the office building. Thus, the tracking system **100** may prompt the user to adjust the threshold distance for which lost determinations are made for one or more tracking devices. Additionally, if the user does not want to receive notifications about a tracking device not being located within a threshold distance of the user, the user may be prompted to disable the notifications regarding that tracking device. For example, if a user lends their car to other people, the user may disable notifications about a car tracking device.

[0166] In some embodiments, the tracking system **100** prompts the user to configure a tracking device to operate in a particular mode. For example, the user may configure a tracking device to operate in a power saving mode if the tracking device is coupled to an object that is predicted to be stationary for a period of time, such as a safe, artwork, a desktop computer, a jewelry box, or a television. The user may also configure a tracking device to operate in a power saving mode if the tracking device is coupled to an object (such as a television remote, a pet, or weights/exercise equipment) that is predicted to be located within a geographic area, such as a home, an office, or a store. The user may configure a tracking device to operate in a high performance mode if the tracking device is coupled to an object that is predicted to be in an unknown/unfamiliar area or is predicted to move, such as a car, luggage, a wallet, or keys. In some embodiments, the user may configure a tracking device to operate in different modes based on where the tracking device is located. For example, a pet tracking device may operate in a power saving mode when the pet tracking device is located within a home and may operate in a high performance mode if the tracking device is located outside the home.

[0167] The tracking device interventions described herein can beneficially enable a user to know that a tracking device is lost before the user even realizes the tracking device is lost. Likewise, a tracking device intervention can remind a user to bring an object coupled to a tracking device with the user when the user moves from a first location to a second location (e.g., on the way to work) before the user gets too far away from the first location. In addition, a tracking device intervention can suggest a user take an action (such as bringing an object coupled to a tracking device) based on a predicted state of the tracking device (e.g., the object coupled to the tracking device is likely to be useful to the user). In each of these circumstances, the user is provided with important or useful information before the user realizes that such information would be important or useful, thereby beneficially improving a user's experience with the tracking device and the tracking system **100**.

Additional Considerations

[0168] The foregoing description of the embodiments of the invention has been presented for the purpose of illustration; it is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Persons skilled in the relevant art can appreciate that many modifications and variations are possible in light of the above disclosure.

[0169] Any of the devices or systems described herein can be implemented by one or more

computing devices. A computing device can include a processor, a memory, a storage device, an I/O interface, and a communication interface, which may be communicatively coupled by way of communication infrastructure. Additional or alternative components may be used in other embodiments. In particular embodiments, a processor includes hardware for executing computer program instructions by retrieving the instructions from an internal register, an internal cache, or other memory or storage device, and decoding and executing them. The memory can be used for storing data or instructions for execution by the processor. The memory can be any suitable storage mechanism, such as RAM, ROM, flash memory, solid state memory, and the like. The storage device can store data or computer instructions, and can include a hard disk drive, flash memory, an optical disc, or any other suitable storage device. The I/O interface allows a user to interact with the computing device, and can include a mouse, keypad, keyboard, touch screen interface, and the like. The communication interface can include hardware, software, or a combination of both, and can provide one or more interfaces for communication with other devices or entities.

[0170] Some portions of this description describe the embodiments of the invention in terms of algorithms and symbolic representations of operations on information. These algorithmic descriptions and representations are commonly used by those skilled in the data processing arts to convey the substance of their work effectively to others skilled in the art. These operations, while described functionally, computationally, or logically, are understood to be implemented by computer programs or equivalent electrical circuits, microcode, or the like. Furthermore, it has also proven convenient at times, to refer to these arrangements of operations as modules, without loss of generality. The described operations and their associated modules may be embodied in software, firmware, hardware, or any combinations thereof.

[0171] Any of the steps, operations, or processes described herein may be performed or implemented with one or more hardware or software modules, alone or in combination with other devices. In one embodiment, a software module is implemented with a computer program product comprising a computer-readable medium containing computer program code, which can be executed by a computer processor for performing any or all of the steps, operations, or processes described.

[0172] Embodiments of the invention may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, and/or it may comprise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a non-transitory, tangible computer readable storage medium, or any type of media suitable for storing electronic instructions, which may be coupled to a computer system bus. Furthermore, any computing systems referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

[0173] Embodiments of the invention may also relate to a product that is produced by a computing process described herein. Such a product may comprise information resulting from a computing process, where the information is stored on a non-transitory, tangible computer readable storage medium and may include any embodiment of a computer program product or other data combination described herein.

[0174] Finally, the language used in the specification has been principally selected for readability and instructional purposes, and it may not have been selected to delineate or circumscribe the inventive subject matter. It is therefore intended that the scope of the invention be limited not by this detailed description, but rather by any claims that issue on an application based hereon. Accordingly, the disclosure of the embodiments of the invention is intended to be illustrative, but not limiting, of the scope of the invention, which is set forth in the following claims.

Claims

- 1.** A method for locating a tracking device, comprising: receiving, at a central tracking system, a location of a tracking device coupled to a pet from a mobile device within a communicative range of the tracking device; determining, by the central tracking system, if the received location is within a geographic boundary associated with a home of an owner of the pet; in response to determining that the received location is outside the geographic boundary, flagging, by the central tracking system, the tracking device as lost and sending a notification to a device of the owner indicating that the pet has escaped; and in response to determining that the received location is within the geographic boundary, removing, by the central tracking system, any flags indicating that the tracking device is lost.
- 2.** The method of claim 1, wherein the mobile device receives a signal from the tracking device and, in response to receiving the signal, determines a location of the mobile device using a location-detection apparatus and provides the determined location to the central tracking device system in association with an identity of the tracking device.
- 3.** The method of claim 1, wherein the geographic boundary is set by the owner of the pet and includes a home of the owner of the pet.
- 4.** The method of claim 1, wherein the mobile device and the device are both owned by the owner of the pet.
- 5.** The method of claim 1, wherein the mobile device is not owned by the owner of the pet.
- 6.** The method of claim 1, wherein the notification includes the received location of the mobile device.
- 7.** The method of claim 1, wherein the notification additionally includes text describing a difference in behavior for the tracking device coupled to the pet.
- 8.** A non-transitory computer-readable storage medium storing executable instructions that, when executed by a processor, cause the processor to perform steps comprising: receiving, at a central tracking system, a location of a tracking device coupled to a pet from a mobile device within a communicative range of the tracking device; determining, by the central tracking system, if the received location is within a geographic boundary associated with a home of an owner of the pet; in response to determining that the received location is outside the geographic boundary, flagging, by the central tracking system, the tracking device as lost and sending a notification to a device of the owner indicating that the pet has escaped; and in response to determining that the received location is within the geographic boundary, removing, by the central tracking system, any flags indicating that the tracking device is lost.
- 9.** The non-transitory computer-readable storage medium of claim 8, wherein the mobile device receives a signal from the tracking device and, in response to receiving the signal, determines a location of the mobile device using a location-detection apparatus and provides the determined location to the central tracking device system in association with an identity of the tracking device.
- 10.** The non-transitory computer-readable storage medium of claim 8, wherein the geographic boundary is set by the owner of the pet and includes a home of the owner of the pet.
- 11.** The non-transitory computer-readable storage medium of claim 8, wherein the mobile device and the device are both owned by the owner of the pet.
- 12.** The non-transitory computer-readable storage medium of claim 8, wherein the mobile device is not owned by the owner of the pet.
- 13.** The non-transitory computer-readable storage medium of claim 8, wherein the notification includes the received location of the mobile device.
- 14.** The non-transitory computer-readable storage medium of claim 8, wherein the notification additionally includes text describing a difference in behavior for the tracking device coupled to the pet.
- 15.** A central tracking system for locating a tracking device, comprising a processor and a non-transitory computer-readable storage medium storing executable instructions that, when executed

by the processor, cause the processor to perform steps comprising: receiving, at the central tracking system, a location of a tracking device coupled to a pet from a mobile device within a communicative range of the tracking device; determining, by the central tracking system, if the received location is within a geographic boundary associated with a home of an owner of the pet; in response to determining that the received location is outside the geographic boundary, flagging, by the central tracking system, the tracking device as lost and sending a notification to a device of the owner indicating that the pet has escaped; and in response to determining that the received location is within the geographic boundary, removing, by the central tracking system, any flags indicating that the tracking device is lost.

16. The system of claim 15, wherein the mobile device receives a signal from the tracking device and, in response to receiving the signal, determines a location of the mobile device using a location-detection apparatus and provides the determined location to the central tracking device system in association with an identity of the tracking device.

17. The system of claim 15, wherein the geographic boundary is set by the owner of the pet and includes a home of the owner of the pet.

18. The system of claim 15, wherein the mobile device and the device are both owned by the owner of the pet.

19. The system of claim 15, wherein the mobile device is not owned by the owner of the pet.

20. The system of claim 15, wherein the notification includes the received location of the mobile device.
