

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386811
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Thuppanna; Nataraja et al.

Method, apparatus, and computer program product for improved tracking of state data

Abstract

A method, apparatus, and computer program product is provided for tracking state data of objects during a session, and saving the data to a database. The tracking may be performed by a reusable set of computer program code accessible by a plurality of user interface applications. Temporary data may be stored as insert objects, update objects, and delete objects and maintained during a session of a user interface application. The temporary data may be updated as additional data is manipulated by the user interface application, but does not need to be tracked by the user interface application. The user interface application indicates if data is to be deleted, or is current (e.g., new or modified). Upon completion of the session, calls are made to update the database based on the temporary data.

Inventors: Thuppanna; Nataraja (Morrisville, NC), Cruz; Ismael (Durham, NC), Sinclair; Debora (Durham, NC)

Applicant: HealthStream, Inc. (Nashville, TN)

Family ID: 64271867

Assignee: HealthStream, Inc. (Nashville, TN)

Appl. No.: 17/163078

Filed: January 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210149870 A1	May. 20, 2021

Related U.S. Application Data

continuation parent-doc US 15597403 20170517 US 10936572 child-doc US 17163078

Publication Classification

Int. Cl.: **G06F16/00** (20190101); **G06F16/17** (20190101); **G06F16/21** (20190101); **G06F16/23** (20190101); **G06F16/27** (20190101); **G06F16/951** (20190101); **G06F16/958** (20190101); G16H10/60 (20180101)

U.S. Cl.:

CPC **G06F16/23** (20190101); **G06F16/1727** (20190101); **G06F16/21** (20190101); **G06F16/2308** (20190101); **G06F16/2379** (20190101); **G06F16/27** (20190101); **G06F16/951** (20190101); **G06F16/958** (20190101); G16H10/60 (20180101)

Field of Classification Search

CPC: G06F (16/23); G06F (16/1727); G06F (16/958); G06F (16/2379); G06F (16/2308); G06F (16/951); G06F (16/27); G06F (16/21); G16H (10/60)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6301585	12/2000	Milne	N/A	N/A
6366954	12/2001	Traversat et al.	N/A	N/A
6493695	12/2001	Pickering et al.	N/A	N/A
6553392	12/2002	Mosher, Jr.	714/E11.107	G06F 11/2082
6553405	12/2002	Desrochers	N/A	N/A
6598057	12/2002	Synnestvedt et al.	N/A	N/A
7209970	12/2006	Everson et al.	N/A	N/A
7689565	12/2009	Gandhi	707/999.01	G06F 16/27
7814124	12/2009	De Jong et al.	N/A	N/A
7904487	12/2010	Ghatore	N/A	N/A
8352424	12/2012	Zunger et al.	N/A	N/A
8782736	12/2013	Thuppanna et al.	N/A	N/A
8821294	12/2013	McCaffrey	463/42	A63F 9/24
8910184	12/2013	Dixon et al.	N/A	N/A
9253154	12/2015	Gaitonde	N/A	H04L 63/0245
9798759	12/2016	Schreter	N/A	G06F 16/2308
9940403	12/2017	Chow et al.	N/A	N/A
2002/0147857	12/2001	Sanchez et al.	N/A	N/A
2003/0074227	12/2002	Yu	N/A	N/A
2003/0195904	12/2002	Chestnut	N/A	G06F 21/6227
2003/0200212	12/2002	Benson	N/A	G06F 9/466
2004/0139107	12/2003	Bachman	N/A	G06F 16/951

2004/0244012	12/2003	Massarenti	N/A	N/A
2006/0123046	12/2005	Doise et al.	N/A	N/A
2006/0218538	12/2005	Van Kesteren	N/A	N/A
2006/0277220	12/2005	Patrick et al.	N/A	N/A
2006/0282460	12/2005	Pandya et al.	N/A	N/A
2007/0237086	12/2006	Tulac	370/244	G06F 16/2477
2007/0239751	12/2006	Wei et al.	N/A	N/A
2007/0239798	12/2006	Shringi	N/A	G06F 16/2365
2007/0294308	12/2006	Megerian	N/A	G06F 16/21
2009/0037446	12/2008	Tonev et al.	N/A	N/A
2010/0049745	12/2009	Aebig et al.	N/A	N/A
2010/0050230	12/2009	Aebig et al.	N/A	N/A
2010/0191712	12/2009	Wolman	707/704	G06F 16/2379
2011/0196830	12/2010	Zunger et al.	N/A	N/A
2012/0078432	12/2011	Weatherhead et al.	N/A	N/A
2013/0111499	12/2012	Dixon et al.	N/A	N/A
2013/0117326	12/2012	De et al.	N/A	N/A
2013/0124667	12/2012	Chow et al.	N/A	N/A
2013/0191420	12/2012	Petri et al.	N/A	N/A
2013/0318117	12/2012	Abdul et al.	N/A	N/A
2014/0068423	12/2013	Nakashima	715/243	G06F 40/169
2014/0075501	12/2013	Srinivasan et al.	N/A	N/A
2014/0229947	12/2013	Daudel	718/1	G06F 11/3636
2014/0304825	12/2013	Gianniotis et al.	N/A	N/A
2015/0052108	12/2014	Volk	707/649	G06F 11/1446
2015/0088815	12/2014	Billapati	707/609	G06F 16/21
2015/0142854	12/2014	Seth et al.	N/A	N/A
2016/0094681	12/2015	Wu	N/A	N/A
2017/0076740	12/2016	Feast et al.	N/A	N/A
2017/0103127	12/2016	Hanson	N/A	G06F 16/958
2017/0293668	12/2016	Crabtree et al.	N/A	N/A
2018/0018428	12/2017	Coifman	N/A	G06F 16/27

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3026583	12/2015	EP	N/A
3438846	12/2021	EP	N/A
WO2009042941	12/2008	WO	N/A

OTHER PUBLICATIONS

Benoit Dageville et al., “The Snowflake Elastic Data Warehouse”, SIGMOD '16: Proceedings of the 2016 International Conference on Management of Data Jun. 2016, pp. 215-226. cited by examiner

Bi Li, Wenxuan Xie et al., “Learning to Update for Object Tracking With Recurrent Meta-Learner”, IEEE Transactions on Image Processing, vol. 28, No. 7, Jul. 2019, pp. 3624. cited by examiner

“Advanced Claim Management,” Change Healthcare, www.changehealthcare.com/solutions/medical-network/advanced-claim-management, last accessed Jun. 28, 2021. cited by applicant

“Ahi QA and Ahi Lobby,” Change Healthcare, www.changehealthcare.com/solutions/revenue-cycle-management/patient-access-financial-clearance/ahi-qa-ahi-lobby, last accessed Jun. 28, 2021. cited by applicant

“API & Services Connection for Healthcare,” Change Healthcare, www.changehealthcare.com/solutions/medical-network/api-services-connection, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Cardiology Analytics,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/cardiology/analytics, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Cardiology Cath,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/cardiology/cath, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Cardiology Charge Manager,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/cardiology/charge-manager, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Cardiology ECG Management,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/cardiology/ecg-management, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Cardiology EP Solutions,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/cardiology/ep-solutions, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Cardiology Hemo,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/cardiology/hemo, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Cardiology Nuclear Medicine Advanced Visualization,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/cardiology/nuclear-medicine-advanced-visualization, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Enterprise Imaging Network Archive,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/enterprise-imaging-network/archive, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Enterprise Viewer,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/enterprise-viewer, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Image Repository,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/image-repository, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Imaging Fellow,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/imaging-fellow, last accessed Jun. 28, 2021. cited by applicant

“Change Healthcare Imaging Share,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/imaging-share, last accessed Jun. 28,

2021. cited by applicant
“Change Healthcare Mammography Plus,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/radiology/mammography-plus, last accessed Jun. 28, 2021. cited by applicant
“Change Healthcare Radiology Collaboration,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/radiology/collaboration, last accessed Jun. 28, 2021. cited by applicant
“Change Healthcare Radiology Solutions,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/radiology/radiology-solutions, last accessed Jun. 28, 2021. cited by applicant
“Change Healthcare Study Share,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/radiology/study-share, last accessed Jun. 28, 2021. cited by applicant
“Change Healthcare Workflow Intelligence,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/workflow-intelligence, last accessed Jun. 28, 2021. cited by applicant
“Claiming & Remittance,” Change Healthcare, www.changehealthcare.com/solutions/medical-network/claiming-remittance, last accessed Jun. 28, 2021. cited by applicant
“Claims Automation,” Change Healthcare, www.changehealthcare.com/solutions/medical-network/claims-automation, last accessed Jun. 28, 2021. cited by applicant
“ConnectCenter,” Change Healthcare, www.changehealthcare.com/solutions/medical-network/connectcenter, last accessed Jun. 28, 2021. cited by applicant
“Credentialing Advocate Solution,” Change Healthcare, www.changehealthcare.com/solutions/dental-network/credentialing-advocate, last accessed Jun. 28, 2021. cited by applicant
“Dental Claim Attachments,” Change Healthcare, www.changehealthcare.com/solutions/dental-network/dental-claim-attachments, last accessed Jun. 28, 2021. cited by applicant
“Dental Practice Analytic Insights,” Change Healthcare, www.changehealthcare.com/solutions/dental-network/dental-practice-analytic-insights, last accessed Jun. 28, 2021. cited by applicant
“Enterprise Business Insight,” Change Healthcare, www.changehealthcare.com/solutions/revenue-cycle-management/revenue-cycle-analytics/enterprise-business-insight, last accessed Jun. 28, 2021. cited by applicant
“Enterprise Imaging Network Analytics,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/enterprise-imaging-network/analytics, last accessed Jun. 28, 2021. cited by applicant
“Enterprise Pharmacy System,” Change Healthcare, www.changehealthcare.com/solutions/pharmacy/management/enterprise-pharmacy-system, last accessed Jun. 28, 2021. cited by applicant
“Imaging Optimization,” Change Healthcare, www.changehealthcare.com/solutions/enterprise-imaging/medical-imaging-consulting/imaging-optimization, last accessed Jun. 28, 2021. cited by applicant
“InterQual Evidence-Based Development,” Change Healthcare, www.changehealthcare.com/solutions/clinical-decision-support/interqual/evidence-based-development, last accessed Jun. 28, 2021. cited by applicant
“Medical Claim Attachments,” Change Healthcare, www.changehealthcare.com/solutions/medical-network/medical-claim-attachments, last accessed Jun. 28, 2021. cited by applicant
“Part D Complete & Community Advocate,” Change Healthcare, www.changehealthcare.com/solutions/eligibility-enrollment/part-d-complete-community-advocate, last accessed Jun. 28, 2021. cited by applicant

“Payer Connectivity Services,” Change Healthcare, www.changehealthcare.com/solutions/medical-network/payer-connectivity-services, last accessed Jun. 28, 2021. cited by applicant
SoftwareArtist, Read and Write JSON with Python, 2015, gowrishankarnath.com (Year: 2015). cited by applicant

Primary Examiner: Channavajjala; Srirama

Attorney, Agent or Firm: Bradley Arant Boult Cummings LLP

Background/Summary

TECHNOLOGICAL FIELD

(1) Embodiments of the present invention relate generally to computer technology and, more particularly, to methods, apparatuses, and computer program products for improved tracking of state data in a session.

BACKGROUND

(2) Many web based systems and services provide user interfaces for users to enter data, manipulate the data, and perform various user configurations to enable the web application to function as intended by the user. Many of the interfaces span multiple pages, some of which are dependent on user inputs made to fields on previous pages.

(3) Data displayed by the applications is often retrieved from a database, and configurations of the data and new data records are transmitted to the database as directed by the user. In some systems, web applications update the database as the data is provided and retrieve data from the database as it is requested, resulting in near real-time updates to the database. However, numerous applications and users may access the data at a given time, and this approach could result in a large number of calls to the database. Some systems could therefore experience performance issues, including at the server and/or database level, due to the high volume of expensive database operations.

(4) As an alternative to making calls to the database on an as-needed basis, some web applications could track the data in the user interface application. However, the data provided by the user could result in cumbersome state tracking in the user interface portion of the application while the user navigates throughout the application and continues to manipulate the data. This approach would require extensive configuration and programming by application developers to track the data in each user interface application until the session is complete and the data can be transmitted to the database.

BRIEF SUMMARY

(5) Methods, apparatuses, and computer program products are therefore provided for improved tracking of state data in a session. Example embodiments provide a reusable interface such that various applications can access the interface and reuse the interface to handle the maintenance of data based on the user inputs provided during the session. When the user interface application indicates the data configuration is complete, example embodiments transmit the necessary calls to the database to provide the committed updates, additions, and deletions to the database. Example embodiments may therefore minimize or reduce the number of database operations in comparison to alternative implementations and further reduce the application code needed to be written by developers of applications that would otherwise be needed to track the state of data within the user interface application.

(6) A method is provided for tracking state data of objects during a session for updating a database. The method comprises receiving an indication of a user interface operation based on a user input to a user interface, processing the user interface operation to generate temporary data, wherein the

temporary data is categorized as at least one of an insert object, update object or delete object. The method further includes updating the temporary data according to subsequently received indications of user interface operations, receiving a commit indication indicating to commit the user interface operations to the database, and in response to the commit indication, transmitting data referenced by the temporary data to the database with operations associated with each of the respective insert objects, update objects and delete objects.

(7) In some embodiments, the tracking of the state data is performed by a reusable set of computer program instructions configured as an application program interface (API) compatible with a plurality of object types and a plurality of database tables.

(8) In some embodiments, processing the user interface operation comprise, in an instance the user interface operation indicates NewOrModified, and a referenced object comprises a record identifier, adding an associated reference as an update object. Processing the user interface operation may further comprise, in an instance the user interface operation indicates the referenced object is NewOrModified, and the referenced object does not comprise a unique record identifier, determining whether the referenced object is referenced in the temporary data and maintaining the temporary data accordingly.

(9) The method may therefore also include, in an instance the user interface operation indicates the referenced object is NewOrModified, the referenced object does not comprise a unique record identifier, and the referenced object is referenced in the temporary data, preventing duplicate references from being added to the temporary data.

(10) Further, the method may include, in an instance the user interface operation indicates the referenced object is NewOrModified, the referenced object does not comprise a unique record identifier, and the referenced object is not referenced in the temporary data, adding an insert object to the temporary data, wherein the insert object includes a reference to the referenced object as indicated by the user interface operation.

(11) In some embodiments, transmitting the data referenced by the temporary data to the database comprises minimizing a number of database calls.

(12) The method may further include maintaining a map that maps record identifiers recognizable by the database to associated objects in the temporary data.

(13) The user interface operation indicates referenced data is either (a) NewOrModified, or (b) Deleted. The user interface operation may indicate the referenced data is NewOrModified, but does not distinguish whether the referenced data is new or modified.

(14) An apparatus is provided for tracking state data of objects during a session for updating a database. The apparatus comprises at least one processor and at least one memory including computer program code, the at least one memory and the computer program code configured to, with the processor, cause the apparatus to at least receive an indication of a user interface operation based on a user input to a user interface, and process the user interface operation to generate temporary data, wherein the temporary data is categorized as at least one of an insert object, update object or delete object. The memory and computer program code may be further configured to update the temporary data according to subsequently received indications of user interface operations and receive a commit indication indicating to commit the user interface operations to the database. The memory and computer program code may be further configured to, in response to the commit indication, transmit data referenced by the temporary data to the database with operations associated with each of the respective insert objects, update objects and delete objects.

(15) A computer program product is provided for tracking state data of objects during a session for updating a database. The computer program product comprises at least one non-transitory computer-readable storage medium having computer-executable program code instructions stored therein, the computer-executable program code instructions comprising program code instructions to receive an indication of a user interface operation based on a user input to a user interface and process the user interface operation to generate temporary data, wherein the temporary data is

categorized as at least one of an insert object, update object or delete object. The computer-executable program code instructions may further comprise program code instructions to update the temporary data according to subsequently received indications of user interface operations, receive a commit indication indicating to commit the user interface operations to the database, and in response to the commit indication, transmit data referenced by the temporary data to the database with operations associated with each of the respective insert objects, update objects and delete objects.

(16) An apparatus is provided with means for tracking state data of objects during a session for updating a database. The apparatus further comprises means for receiving an indication of a user interface operation based on a user input to a user interface, means for processing the user interface operation to generate temporary data, wherein the temporary data is categorized as at least one of an insert object, update object or delete object. The apparatus further includes means for updating the temporary data according to subsequently received indications of user interface operations, means for receiving a commit indication indicating to commit the user interface operations to the database, and in response to the commit indication, means for transmitting data referenced by the temporary data to the database with operations associated with each of the respective insert objects, update objects and delete objects.

(17) The above summary is provided merely for purposes of summarizing some example embodiments of the invention so as to provide a basic understanding of some aspects of the invention. Accordingly, it will be appreciated that the above described example embodiments are merely examples and should not be construed to narrow the scope or spirit of the disclosure in any way. It will be appreciated that the scope of the disclosure encompasses many potential embodiments, some of which will be further described below, in addition to those here summarized.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) Having thus described embodiments of the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

(2) FIGS. 1 and 2 are overviews of example systems that can be used to practice some example embodiments described herein;

(3) FIG. 3 is a schematic diagram of an apparatus in accordance with some example embodiments; and

(4) FIG. 4 is a flowchart of operations that may be performed in accordance with some example embodiments.

DETAILED DESCRIPTION

(5) Some embodiments of the present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the invention are shown. Indeed, various embodiments of the invention may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like reference numerals refer to like elements throughout.

(6) As used herein, where a computing device is described herein to receive data from another computing device, it will be appreciated that the data may be received directly from the other computing device and/or may be received indirectly via one or more intermediary computing devices, such as, for example, one or more servers, relays, routers, network access points, and/or the like. Similarly, where a computing device is described herein to transmit data to other computing devices, it will be appreciated that the data may be sent directly to the other computing

device or may be sent to the other computing device via one or more interlinking computing devices, such as, for example, one or more servers, relays, routers, network access points, and/or the like.

(7) FIG. 1 is an overview of a system that can be used to practice certain embodiments described herein, and should not be considered limiting. As illustrated in FIG. 1, example embodiments may be implemented as or employed in a distributed system. The various depicted components may be configured to communicate over a network **10**, such as the Internet, for example, or any other communication interface as described in further detail hereinafter. In general, client device(s) **30** may be configured to communicate with a server **40** and/or database **50**. Client device **30** may include any computing device such as a personal computer, laptop, smart phone, tablet, and/or the like. In some examples, any number of user devices **30** may be configured to communicate with server **40**, which may be configured to host applications, process requests from the client device **30**, provide data and content to the client device **30**, and/or the like. The server **40** may be communicatively connected to database **50** which may be configured to store data, content, and/or the like. The client device **30**, server **40** and/or database **50** may be configured to perform any of the operations described herein.

(8) FIG. 2 is another overview of a system that can be used to practice certain embodiments described herein. As shown, multiple different user interface applications **100** may communicate with save wizard engine **110** to perform tracking of state data of objects manipulated by the respective user interface applications **100** during a session, and to save the data to the database **50**.

(9) The user interface applications **100** may generate objects for display by a browser or other similar application and allow the user to manipulate the data. The save wizard engine **110** may track the data manipulated by the user interface application **100** during a session, and save the relevant data to the database **50** when the session is complete. The save wizard engine **110** may therefore be implemented in a middle tier of a multi-tier architecture such that the save wizard engine **110** facilitates communication between a data-tier layer (e.g., database **50**) and the user interface applications **100**. In some examples, the user interface applications **100** and save wizard engine **110** may be implemented on server **40**. As another example, the user interface applications **100** and save wizard engine **110** may be implemented on various servers **40** configured to operate as a distributed system.

(10) Any of the operations described herein, such as those described with respect to FIG. 4, may be at least partially implemented as a reusable set of computer program instructions compatible with a plurality of object types. Any of the operations described herein may be provided by the save wizard engine **110** via an Application Program Interface (API) configured for reuse by a user interface application **100**, including user interface applications to be developed in the future. As additional user interface applications are implemented, such as on server **40**, and/or as additional database tables are added to database **50**, the API provided by example embodiments may continue to be utilized by application developers to track the state data during a session for subsequent saving to the database. Example embodiments therefore may minimize or reduce the application development needed to track the state data in each of the user interface applications.

(11) The systems of FIGS. 1 and 2 described above are provided merely as example implementations and it will be appreciated that the example embodiments provided herein may be implemented as or employed by any number of system architectures.

(12) Referring now to FIG. 3, apparatus **200** is a computing device(s) configured according to example embodiments for improved tracking of state data in a session. Apparatus **200** may at least partially or wholly embody any of the network **10**, client device **30**, server **40**, database **50**, user interface applications **100**, and/or save wizard engine **110** described above. Apparatus **200** may therefore implement any of the network **10**, client device **30**, server **40**, database **50**, user interface applications **100**, and/or save wizard engine **110**, in accordance with some example embodiments, or may be implemented as a distributed system that includes any of the network **10**, client device

30, server **40**, database **50**, user interface applications **100**, and/or save wizard engine **110**.

(13) It should be noted that the components, devices, and elements illustrated in and described with respect to FIG. 3 below may not be mandatory and thus some may be omitted in certain embodiments. For example, FIG. 3 illustrates a user interface **216**, as described in more detail below, which may be optional in the server **40**, database **50**, and/or save wizard engine **110**. Additionally, some embodiments may include further or different components, devices, or elements beyond those illustrated in and described with respect to FIG. 3.

(14) Continuing with FIG. 3, processing circuitry **210** may be configured to perform actions in accordance with one or more example embodiments disclosed herein. In this regard, the processing circuitry **210** may be configured to perform and/or control performance of one or more functionalities of apparatus **200** in accordance with various example embodiments. The processing circuitry **210** may be configured to perform data processing, application execution, and/or other processing and management services according to one or more example embodiments. In some embodiments apparatus **200**, or a portion(s) or component(s) thereof, such as the processing circuitry **210**, may be embodied as or comprise a circuit chip. The circuit chip may constitute means for performing one or more operations for providing the functionalities described herein.

(15) In some example embodiments, the processing circuitry **210** may include a processor **212**, and in some embodiments, such as that illustrated in FIG. 3, may further include memory **214**. The processing circuitry **210** may be in communication with or otherwise control a user interface **216**, and/or a communication interface **218**. As such, the processing circuitry **210** may be embodied as a circuit chip (e.g., an integrated circuit chip) configured (e.g., with hardware, software, or a combination of hardware and software) to perform operations described herein.

(16) The processor **212** may be embodied in a number of different ways. For example, the processor **212** may be embodied as various processing means such as one or more of a microprocessor or other processing element, a coprocessor, a controller, or various other computing or processing devices including integrated circuits such as, for example, an ASIC (application specific integrated circuit), an FPGA (field programmable gate array), or the like. Although illustrated as a single processor, it will be appreciated that the processor **212** may comprise a plurality of processors. The plurality of processors may be in operative communication with each other and may be collectively configured to perform one or more functionalities of apparatus **200** as described herein. The plurality of processors may be embodied on a single computing device or distributed across a plurality of computing devices collectively configured to function as network **10**, client device **30**, server **40**, database **50**, user interface applications **100**, save wizard engine **110** and/or apparatus **200**. In some example embodiments, the processor **212** may be configured to execute instructions stored in the memory **214** or otherwise accessible to the processor **212**. As such, whether configured by hardware or by a combination of hardware and software, the processor **212** may represent an entity (e.g., physically embodied in circuitry—in the form of processing circuitry **210**) capable of performing operations according to embodiments of the present invention while configured accordingly. Thus, for example, when the processor **212** is embodied as an ASIC, FPGA, or the like, the processor **212** may be specifically configured hardware for conducting the operations described herein. Alternatively, as another example, when the processor **212** is embodied as an executor of software instructions, the instructions may specifically configure the processor **212** to perform one or more operations described herein.

(17) In some example embodiments, the memory **214** may include one or more non-transitory memory devices such as, for example, volatile and/or non-volatile memory that may be either fixed or removable. In this regard, the memory **214** may comprise a non-transitory computer-readable storage medium. It will be appreciated that while the memory **214** is illustrated as a single memory, the memory **214** may comprise a plurality of memories. The plurality of memories may be embodied on a single computing device or may be distributed across a plurality of computing devices. The memory **214** may be configured to store information, data, applications, computer

program code, instructions and/or the like for enabling apparatus **200** to carry out various functions in accordance with one or more example embodiments. For example, when apparatus **200** is implemented as apparatus **200**, memory **214** may store data records associated with simulated requests and responses.

(18) The memory **214** may be configured to buffer input data for processing by the processor **212**. Additionally or alternatively, the memory **214** may be configured to store instructions for execution by the processor **212**. In some embodiments, the memory **214** may include one or more databases, such as database **50**, that may store a variety of files, contents, or data sets. Among the contents of the memory **214**, applications may be stored for execution by the processor **212** to carry out the functionality associated with each respective application. In some cases, the memory **214** may be in communication with one or more of the processor **212**, user interface **216**, and/or communication interface **218**, for passing information among components of apparatus **200**.

(19) The optional user interface **216** may be in communication with the processing circuitry **210** to receive an indication of a user input at the user interface **216** and/or to provide an audible, visual, mechanical, or other output to the user. As such, the user interface **216** may include, for example, a keyboard, a mouse, a joystick, a display, a touch screen display, a microphone, a speaker, and/or other input/output mechanisms. As such, the user interface **216** may, in some example embodiments, provide means for user control of managing data access operations and/or the like. In some example embodiments in which apparatus **200** is embodied as server **40**, database **50**, save wizard engine **110**, and/or the like, aspects of user interface **216** may be limited or the user interface **216** may not be present.

(20) The communication interface **218** may include one or more interface mechanisms for enabling communication with other devices and/or networks. In some cases, the communication interface **218** may be any means such as a device or circuitry embodied in either hardware, or a combination of hardware and software that is configured to receive and/or transmit data from/to a network and/or any other device or module in communication with the processing circuitry **210**. By way of example, the communication interface **218** may be configured to enable communication amongst client device **30**, server **40**, database **50**, apparatus **200**, and/or the like over a network.

Accordingly, the communication interface **218** may, for example, include supporting hardware and/or software for enabling wireless and/or wireline communications via cable, digital subscriber line (DSL), universal serial bus (USB), Ethernet, or other methods.

(21) The network, such as network **10**, in which apparatus **200** and/or any of the components described herein may operate may include a local area network, the Internet, any other form of a network, or in any combination thereof, including proprietary private and semi-private networks and public networks. The network may comprise a wired network and/or a wireless network (e.g., a cellular network, wireless local area network, wireless wide area network, some combination thereof, and/or the like).

(22) FIG. **4** is a flowchart illustrating example operations of an apparatus **200** according to some example embodiments. The operations of FIG. **4** may be performed by apparatus **200** (e.g., save wizard engine **110**) to track state data of objects in a session and save the data to the database **50**. In particular, example embodiments provide a reusable interface that can be accessed by various user interface applications **100**, such as those operative on server **40**. Example embodiments maintain the data as provided by the interfacing user interface application **100**, and transmit consolidated data to the database **50**.

(23) As used herein, a session may be considered a series of communications between a client device **30** and server **40**. The session may begin when the client device **30** initially accesses an application operative on server **40**, such as user interface application **100**. The session may end when the user initiates to commit the data to the database **50**, such as by selecting “save,” “submit,” or any similar input component. As another example, the session may end when a user closes the browser. In some examples, a session may include the exchange of data provided via a series of

user interface displays, and the user may navigate back and forth between displays, and make configure the data accordingly.

(24) As shown by operation **400**, apparatus **200** may include means, such as save wizard engine **110**, processor **212**, memory **214**, user interface **216**, communication interface **218**, and/or the like, for receiving an indication of a user interface operation based on a user input to a user interface. The user interface operation may be received from a user interface application **100** that invokes the save wizard engine **110**, and may include data to be added to, modified on, or deleted from a database. In particular, the user interface operation may pass as a parameter to the save wizard engine **110** a reference or pointer to a record or an object that represents a record. The referenced object may represent a record that is to be modified, added, or deleted in the database **50** as provided by the user interface application **100**. In this regard, the data referenced by the temporary data of the save wizard engine **110** may be referred to herein as records or objects. The objects or records may comprise data that when processed can be inserted into an associated database table.

(25) In some embodiments, the user interface operation may also pass as a parameter a flag indicating the type of operation to be performed on the referenced object. For example, the parameters may include a NewOrModified flag or a Deleted flag. Additionally or alternatively, in some embodiments, the user interface application **100** may invoke separate methods depending on whether the data is NewOrModified or Deleted. The NewOrModified and Deleted flags or operations are described in further detail below.

(26) The user interface operation and any parameters associated therewith may be communicated to example embodiments following user entry into or manipulation of fields displayed on the user interface **216**. For example, a user may enter data for input to an application, and select a “next” button or similar indicator to continue through various pages of the application. The user interface application **100** may invoke the save wizard engine **110** as the data is entered, and/or as the user continues to a different page or display.

(27) As shown by operation **402**, apparatus **200** may include means, such as save wizard engine **110**, processor **212**, memory **214**, user interface **216**, communication interface **218**, and/or the like, for processing the user interface operation to generate temporary data, wherein the temporary data is categorized as at least one of an insert object, update object or delete object and comprises a reference or pointer to an object or record that is to be added, modified or deleted from the database **50**. The term ‘temporary data’ is used to indicate that the reference or pointer to the data is stored or saved for local access by the save wizard engine **110** and/or apparatus **200**, such as in memory **214**, but is not yet saved to database **50**. In some embodiments, the records or objects referenced by the temporary data may not be available to other applications since it is not yet saved to the database. However, save wizard engine **110** may track and maintain the data for use within the session and may efficiently save the appropriate data to the database at the end of the session.

(28) As introduced above, the data transmitted by the user interface application **100** to the save wizard engine **110** via the user interface operation may include a Deleted flag or a NewOrModified flag. In this regard, the user interface application **100** does not need to track or indicate that the data is new or modified, but rather provides references to the current data, (e.g., currently known to the user interface application **100** taking into consideration the user configurations). Said differently, data flagged as NewOrModified may not yet exist in the database **50**, or maybe associated with an existing record in the database **50**, but the user interface application **110** does not need to distinguish between the two states of new or modified. The save wizard engine **110** handles the operations and state tracking of the data provided by the user interface application **110** relative to the state of the database.

(29) The save wizard engine **110** may process the operations and the references to data to determine any number of insert operations, update operations, and/or deletion operations that would be made to the database **50** if the data provided in the user interface operation were committed, or saved, to the database. To track the state data, the save wizard engine **110** may maintain a new bucket, update

bucket and/or delete bucket during the session, and update the temporary data comprising references or pointers to records or objects stored therein as additional user interface operations are performed in the session. Each of the buckets may be implemented as any data structure configured to store references to any type objects or records provided by the user interface application **100**.

(30) According to example embodiments, the referenced objects may comprise record identifiers (e.g., keys) used to uniquely identify the associated record in the database. Accordingly, an object or record referenced in the update and/or delete buckets may be associated with a record identifier linking the data to the database.

(31) In some examples, objects referenced in the new bucket may not have a record identifier associated with the object because the record does not yet exist in the database.

(32) Because the user interface application **100** only needs to flag data as Deleted or NewOrModified, the user interface application **100** may transmit a reference or pointer to any modified object to save wizard engine **110** whether the record is new to the save wizard engine **110** or already exists in one of the buckets. The user interface application **100** does not need to track whether the record is new or modified, but rather provides a reference to the complete record as currently provided in the user interface application **100** to the save wizard engine **110**.

(33) If the user interface operation indicates to the save wizard engine **110** that associated data is NewOrModified and the referenced object includes a record identifier linking the record to an existing record in the database, the save wizard engine **110** generates an update object to store in the update bucket. The update object may include a reference to the object which represents the record in the database. In some embodiments, the save wizard engine **110** may store a map that maps record identifiers recognized or recognizable by the database to the associated object in the temporary data. This may allow for improved efficiency so that the save wizard engine **110** does not need to check every object referenced in the temporary data to determine whether the temporary data already references the record. The save wizard engine **110** may instead access the map to determine whether the temporary data already references the associated record, and may only continue to check other objects referenced in temporary data, as described below, if the record is not referenced in the temporary data.

(34) If the user interface operation indicates to the save wizard engine **110** that associated data is NewOrModified, and the referenced object does not include a record identifier linking the record to the database, the save wizard engine **110** may compare the record or object referenced by the user interface operation to those already referenced by the temporary data maintained by the save wizard engine **110** to determine if the save wizard engine **110** already includes temporary data referencing the record. Based on the comparison, the user interface operations may be processed as follows.

(35) If the user interface operation indicates to the save wizard engine **110** that associated data is NewOrModified, and the associated object is not already referenced in the temporary data, (and does not have an associated record identifier linking it to the database), save wizard engine **110** adds an insert object to the new bucket. The insert object may include a reference or pointer to the object representing the new record to be inserted. In this regard, the save wizard engine **110** may generate an insert object which references data to be inserted in various fields of the database table in a new record when the session is complete, as described below with respect to operation **408**.

(36) If data received by the save wizard engine **110** is flagged as NewOrModified, does not have an associated record identifier recognized by the database, and it is not new to the save wizard engine **110** (e.g., is already referenced in the new bucket or update bucket) the save wizard engine **110** prevents addition of duplicate references to the temporary data. Said differently, the save wizard engine **110** may ignore the user interface operation, because the referenced object has already been modified by the user interface application **100** and the temporary data of the save wizard engine **110** already references the object. In this regard, as requests are received from the user interface application **100**, for a NewOrModified operation, the save wizard engine **110** determines existence

of a record in temporary data (e.g., a bucket) by comparing the record being provided against all records referenced in any of the buckets.

(37) In some embodiments, user interface application **100** can transmit a deleted object to the save wizard engine **110** without having to determine if the record exists in the database. If data received by the save wizard engine **110** is flagged as Delete, but the save wizard engine **110** determines the record was newly created in the session and does not yet exist in the database **50** (e.g., does not have an associated record identifier), the save wizard engine **110** may remove the reference to the associated insert object from the new bucket and ignore the associated record. In contrast, if the record does exist in the database (e.g., has an associated record identifier), the save wizard engine **110** may add a delete object to the delete bucket and remove an associated record from the update bucket, if one exists.

(38) In some examples, a user interface operation transmitted to the save wizard engine **110** may be processed such that more than one database operation would be initiated to complete the request. In this regard, references to multiple objects could be added to any of the temporary data buckets for a single user interface operation. For example, a user may provide data associated with the addition of several new database records, possibly in different database tables. As another example, a user may complete a task which results in user interface operations to add a new record, delete an existing record and/or update an existing record. These tasks may be completed on a single user interface display and transmitted to apparatus **200**.

(39) As shown by operation **404**, apparatus **200** may include means, such as save wizard engine **110**, processor **212**, memory **214**, user interface **216**, communication interface **218**, and/or the like, for updating the temporary data according to subsequently received indications of user interface operations. In this regard, user interface operations may be interpreted by the save wizard engine **110** and maintained accordingly so as to minimize or reduce database operations ultimately initiated by the save wizard engine **110**.

(40) In some embodiments, the save wizard engine **110** may identify that data passed from the user interface application **100** utilizes a different variable that actually points to the same record referenced by the temporary data stored by the save wizard engine **110**. In this regard, the following computer program code may return true if the two pointers or references point to the same object. "objectReference1==objectReference2." ObjectReference1 could be a reference provided by the user interface application **100** and objectReference2 could be a reference to the object in one of the buckets of temporary data. If a user is operating on a single object or record, the object pointer that the user interface application **100** passes to the save wizard engine **110** and the record already referenced in the temporary data are pointing to the same object.

(41) For example, consider that a user previously initiated creation of a new record for a patient with a first name of "John," last name of "Doe," and birth date of "mm/dd/yyyy." This data may be referenced by the save wizard engine **110** as an insert object in the new bucket. While entering additional detail on a subsequent page, such as address and phone number, the user may realize the patient's last name is spelled incorrectly. The user may return to the previous page to correct the spelling.

(42) In this regard, the save wizard engine **110** may ignore the subsequent request because the insert object in the new bucket already includes a reference to the same object. Example embodiments may therefore reduce unnecessary database calls to be subsequently made, in comparison to a system that would perform the database insert operation with the misspelled name, followed by an additional database update operation to correct the name.

(43) As another example, a user that creates data that could result in a new record, may ultimately cancel the transaction or delete the instance of the data in the session. In this regard, temporary data stored by the apparatus **200** in the new bucket may be deleted from the new bucket prior to committing the data to the database. In this example, an unnecessary insert and delete operation could be avoided.

(44) As another example, save wizard engine **110** may determine a user interface operation is indicative of a delete operation of a record associated with an object stored in the update bucket. In this regard, the save wizard engine **110** may remove the update object from the update bucket so that the data is not unnecessarily updated prior to deletion, and add a delete object to the delete bucket. If a delete request is associated with a new object (e.g., the object being deleted matches an object saved in the new bucket), the save wizard engine **110** may remove the new object and ignore the delete request, so that the data is not transmitted to the database and subsequently deleted. Instead, the data created and deleted within the session can be ignored by the save wizard engine **110**.

(45) In some examples, for each request from the user interface application, example embodiments may search the existing temporary data to determine if the existing temporary data needs to be updated instead of generating new instances of insert objects, update objects, and/or delete objects for every request by default. In some instances the save wizard engine **110** may ignore user interface operations if the object is already referenced by the temporary data

(46) As shown by operation **406**, apparatus **200** may include means, such as save wizard engine **110**, processor **212**, memory **214**, user interface **216**, communication interface **218**, and/or the like, for receiving a commit indication indicating to commit the user interface operations (e.g., the data associated with the referenced objects) to the database. The commit indication may be generated in response to a user selecting a “save,” or “submit” button. As another example, the commit indication may be generated by any other type of user input, such as the session ending.

(47) As shown by operation **408**, apparatus **200** may include means, such as save wizard engine **110**, processor **212**, memory **214**, communication interface **218**, and/or the like, for in response to the commit indication, transmitting data referenced by the temporary data to the database with operations associated with each of the respective insert objects, update objects and delete objects. In this regard, example embodiments may traverse the insert objects, update objects, and delete objects and generate database commands representing each of the objects. For example, the commands may be generating in a Structured Query Language (SQL) or other programming language configured to update a relational database such as database **50**.

(48) In some embodiments, save wizard engine **110** may therefore determine an order in which database operations will be performed based on dependencies of objects in the temporary data. Accordingly, some database operations may be dependent on other database operations. For example, a new record may be referenced in an update object relating to another record. This scenario may occur, for example, if a user could provide details of a new patient that is a family member of an existing patient and the two patients are to be linked. The save wizard engine **110** may first perform the insert operation relating to the new patient and receive a new record identifier from the database **50**. The save wizard engine **110** may then update the record of the existing patient to link to the new patient based on a record identifier returned from the database. In some embodiments, the save wizard engine **110** does not handle the ordering of the database operations, and another component or routine, such as one operative on server **40**, may perform other routines to ensure relational database integrity after the save wizard engine **110** transmits the data to the database **50**. For example, the user interface application **100** may perform data integrity verification.

(49) Example embodiments described herein provide many technical advantages to the various components of the respective systems. The operations provided above, such as those described with respect to FIG. **4**, may be provided by an API configured for reuse. In this regard, save wizard engine **110** may be implemented at least partially as a reusable set of computer program instructions compatible with a plurality of object types. Multiple different user interface applications **100** may therefore employ example embodiments to direct the save wizard engine **110** to track the state data of objects during a session and save the data to the database when the session is complete. As additional user interface applications are implemented, such as on server **40**, and/or

additional database tables are added to database **50**, the API provided by example embodiments may continue to be utilized by application developers to track the state data during a session for subsequent updating to the database.

(50) Further, example embodiments may minimize or reduce a number of database calls, in comparison to other implementations that do not track state data during the session, or those that make database calls as the user interface operations are processed throughout the session. The number of operations performed by server **40** and/or database **50** may therefore be limited or reduced such that processing resources are conserved. Accordingly, performance of the server **40** and/or database **50** may be improved in comparison to other implementations. Example embodiments may therefore minimize or reduce server load, database timeouts, and unnecessary network traffic, and improve performance on the server and database, and throughout the system.

(51) Similarly, due to the minimized or reduced number of database operations, example embodiments also provide for cleaner audit records relative to other implementations, such that clear and concise audit trails of updates to the database can be stored for subsequent review and audit.

(52) It will be appreciated that the figures are each provided as examples and should not be construed to narrow the scope or spirit of the disclosure in any way. In this regard, the scope of the disclosure encompasses many potential embodiments in addition to those illustrated and described herein. Numerous other configurations may also be used to implement embodiments of the present invention.

(53) FIG. **4** illustrates operations of a method, apparatus, and computer program product according to some example embodiments. It will be understood that each operation of the flowcharts or diagrams, and combinations of operations in the flowcharts or diagrams, may be implemented by various means, such as hardware and/or a computer program product comprising one or more computer-readable mediums having computer readable program instructions stored thereon. For example, one or more of the procedures described herein may be embodied by computer program instructions of a computer program product. In this regard, the computer program product(s) which embody the procedures described herein may comprise one or more memory devices of a computing device (for example, memory **214**) storing instructions executable by a processor in the computing device (for example, by processor **212**). In some example embodiments, the computer program instructions of the computer program product(s) which embody the procedures described above may be stored by memory devices of a plurality of computing devices. As will be appreciated, any such computer program product may be loaded onto a computer or other programmable apparatus (for example, apparatus **200**) to produce a machine, such that the computer program product including the instructions which execute on the computer or other programmable apparatus creates means for implementing the functions specified in the flowchart block(s). Further, the computer program product may comprise one or more computer-readable memories on which the computer program instructions may be stored such that the one or more computer-readable memories can direct a computer or other programmable apparatus to function in a particular manner, such that the computer program product may comprise an article of manufacture which implements the function specified in the flowchart block(s). The computer program instructions of one or more computer program products may also be loaded onto a computer or other programmable apparatus (for example, apparatus **200** and/or other apparatus) to cause a series of operations to be performed on the computer or other programmable apparatus to produce a computer-implemented process such that the instructions which execute on the computer or other programmable apparatus implement the functions specified in the flowchart block(s).

(54) Accordingly, blocks of the flowcharts support combinations of means for performing the specified functions and combinations of operations for performing the specified functions. It will also be understood that one or more blocks of the flowcharts, and combinations of blocks in the flowcharts, can be implemented by special purpose hardware-based computer systems which

perform the specified functions, or combinations of special purpose hardware and computer instructions.

(55) Many modifications and other embodiments of the inventions set forth herein will come to mind to one skilled in the art to which these inventions pertain having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the inventions are not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Moreover, although the foregoing descriptions and the associated drawings describe example embodiments in the context of certain example combinations of elements and/or functions, it should be appreciated that different combinations of elements and/or functions may be provided by alternative embodiments without departing from the scope of the appended claims. In this regard, for example, different combinations of elements and/or functions than those explicitly described above are also contemplated as may be set forth in some of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

Claims

1. A method for tracking state data of objects during a session for updating a database, the method comprising: receiving a first indication of a first user input to a user interface; based on the first user input, generating a first user interface operation that includes a first flag indicating the first user interface operation indicates a new data record or a modified data record, and a first reference to a first referenced object, wherein the first referenced object includes a record identifier; processing the first user interface operation to at least one of generate or update temporary data, wherein the temporary data includes an insert object based on the first user interface operation; receiving a second indication of a second user input to the user interface; based on the second user input, generating a second user interface operation that includes a second flag indicating the second user interface operation indicates deletion of a data record from the temporary data, and a second reference to a second referenced object; and processing the second user interface operation to update the temporary data, wherein the temporary data includes a delete object based on the second user interface operation, and wherein processing the second user interface operation comprises, determining whether the second reference to the second referenced object of the second user interface operation includes a reference to the first referenced object of the first user interface operation, responsive to a determination that the second reference to the second referenced object of the second user interface operation includes the reference to the first referenced object of the first user interface operation, removing the insert object from the temporary data prior to transmitting data referenced by the temporary data to the database; wherein the tracking of the state data is performed by a reusable set of computer program instructions configured as an application program interface (API) compatible with a plurality of object types and a plurality of database tables; and wherein processing the second user interface operation further comprises, determining whether the second referenced object includes a record identifier associated with the database, responsive to a determination that the second referenced object includes the record identifier associated with the database, removing an update object from the temporary data, wherein the update object includes a reference to a referenced object that includes the record identifier associated with the database.
2. The method of claim 1, wherein processing the second user interface operation further comprises removing an update object from the temporary data, wherein the update object includes a reference to the first referenced object of the first user interface operation.
3. The method of claim 1, wherein the temporary data including the insert object based on the first user interface operation comprises the temporary data including a plurality of insert objects based

on the first user interface operation.

4. The method of claim 1, further comprising: maintaining a map that maps record identifiers recognizable by the database to associated objects in the temporary data.

5. The method of claim 1, wherein the first flag does not distinguish whether the first referenced object is new or modified.

6. The method of claim 1, further comprising: updating the temporary data according to subsequently received indications of user interface operations; receiving a commit indication indicating to commit the first user interface operation, the second user interface operation, and the subsequently received user interface operations to the database; and in response to the commit indication, transmitting data referenced by the temporary data to the database with operations associated with each of the respective insert objects and delete objects.

7. The method of claim 6, wherein: transmitting the data referenced by the temporary data to the data with operations associated with each of the respective insert and delete objects comprises determining an order in which the database performs the operations; and determining the order in which the database performs the operations is based on dependencies of objects in the temporary data.

8. An apparatus for tracking state data of objects during a session for updating a database, the apparatus comprising at least one processor and at least one memory including computer program code, the at least one memory and the computer program code configured to, with the processor, cause the apparatus to at least: receive a first indication of a first user input to a user interface; based on the first user input, generate a first user interface operation that includes a first flag indicating the first user interface operation indicates a new data record or a modified data record, and a first reference to a first referenced object, wherein the first referenced object includes a record identifier; process the first user interface operation to at least one of generate or update temporary data, wherein the temporary data includes an insert object based on the first user interface operation; receive a second indication of a second user input to the user interface; based on the second user input, generate a second user interface operation that includes a second flag indicating the second user interface operation indicates deletion of a data record from the temporary data, and a second reference to a second referenced object; and process the second user interface operation to update the temporary data, wherein the temporary data includes a delete object based on the second user interface operation, and wherein processing the second user interface operation comprises, determining whether the second reference to the second referenced object of the second user interface operation includes a reference to the first referenced object of the first user interface operation, responsive to a determination that the second reference to the second referenced object of the second user interface operation includes the reference to the first referenced object of the first user interface operation, removing the insert object from the temporary data prior to transmitting data referenced by the temporary data to the database; wherein the tracking of the state data is performed by a reusable set of computer program instructions configured as an application program interface (API) compatible with a plurality of object types and a plurality of database tables; and wherein processing the second user interface operation further comprises, determining whether the second referenced object includes a record identifier associated with the database, responsive to a determination that the second referenced object includes the record identifier associated with the database, removing an update object from the temporary data, wherein the update object includes a reference to a referenced object that includes the record identifier associated with the database.

9. The apparatus of claim 8, wherein processing the second user interface operation further comprises removing an update object from the temporary data, wherein the update object includes a reference to the first referenced object of the first user interface operation.

10. The apparatus of claim 8, wherein the temporary data including the insert object based on the first user interface operation comprises the temporary data including a plurality of insert objects

based on the first user interface operation.

11. The apparatus of claim 8, the at least one memory and the computer program code are further configured to, with the processor, cause the apparatus to: maintain a map that maps record identifiers recognizable by the database to associated objects in the temporary data.

12. The apparatus of claim 8, wherein the first flag does not distinguish whether the referenced object is new or modified.

13. The apparatus of claim 8, the at least one memory and the computer program code are further configured to, with the processor, cause the apparatus to: update the temporary data according to subsequently received indications of user interface operations; receive a commit indication indicating to commit the first user interface operation, the second user interface operation, and the subsequently received user interface operations to the database; and in response to the commit indication, transmit data referenced by the temporary data to the database with operations associated with each of the respective insert objects and delete objects.

14. A computer program product for tracking state data of objects during a session for updating a database, the computer program product comprising at least one non-transitory computer-readable storage medium having computer-executable program code instructions stored therein, the computer-executable program code instructions comprising program code instructions to: receive a first indication of a first user input to a user interface; based on the first user input, generate a first user interface operation that includes a first flag indicating the first user interface operation indicates a new data record or a modified data record, and a first reference to a first referenced object, wherein the first referenced object includes a record identifier; process the first user interface operation to at least one of generate or update temporary data, wherein the temporary data includes an insert object based on the first user interface operation; receive a second indication of a second user input to the user interface; based on the second user input, generate a second user interface operation that includes a second flag indicating the second user interface operation indicates deletion of a data record from the temporary data, and a second reference to a second referenced object; and process the second user interface operation to update the temporary data, wherein the temporary data includes a delete object based on the second user interface operation, and wherein processing the second user interface operation comprises, determining whether the second reference to the second referenced object of the second user interface operation includes a reference to the first referenced object of the first user interface operation, responsive to a determination that the second reference to the second referenced object of the second user interface operation includes the reference to the first referenced object of the first user interface operation, removing the insert object from the temporary data prior to transmitting data referenced by the temporary data to the database; wherein the tracking of the state data is performed by a reusable set of computer program instructions configured as an application program interface (API) compatible with a plurality of object types and a plurality of database tables; and wherein processing the second user interface operation further comprises, determining whether the second referenced object includes a record identifier associated with the database, responsive to a determination that the second referenced object includes the record identifier associated with the database, removing an update object from the temporary data, wherein the update object includes a reference to a referenced object that includes the record identifier associated with the database.

15. The computer program product of claim 14, the computer-executable program code instructions further comprising program code instructions to: update the temporary data according to subsequently received indications of user interface operations; receive a commit indication indicating to commit the first user interface operation, the second user interface operation, and the subsequently received user interface operations to the database; and in response to the commit indication, transmit data referenced by the temporary data to the database with operations associated with each of the respective insert objects and delete objects.
