

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391454
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Wu; Jing-Feng

Vacuum container

Abstract

The invention discloses a vacuum container comprising a storage container, a connecting tray component, a top cap and two one-way exhausters. The connecting tray component air-tightly encloses a container opening of the storage container. The top cap has a pressing part, and the top cap encloses a tray opening of the connecting tray component in a manner that the pressing part is in a position corresponding to the tray opening. One of the one-way exhausters is inserted in a guiding hole of the connecting tray component to form a tray one-way exhaust passage. The other one-way exhauster is inserted in an exhausting hole to form a cap one-way exhaust passage.

Inventors:	Wu; Jing-Feng (Tainan, TW)
Applicant:	Wu; Jing-Feng (Tainan, TW)
Family ID:	1000008762582
Appl. No.:	18/588837
Filed:	February 27, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240317478 A1	Sep. 26, 2024

Foreign Application Priority Data

TW	112110818	Mar. 23, 2023
----	-----------	---------------

Publication Classification

Int. Cl.: B65D81/20 (20060101); B65D43/02 (20060101)

U.S. Cl.:

CPC **B65D81/2038** (20130101); **B65D43/0218** (20130101); B65D2543/00203 (20130101);
B65D2543/00231 (20130101); B65D2543/005 (20130101); B65D2543/00537
(20130101); B65D2543/00555 (20130101)

Field of Classification Search

CPC: B65D (81/2038); B65D (43/0218); B65D (2543/00203); B65D (2543/00231); B65D
(2543/005); B65D (2543/00537); B65D (2543/00555); B65B (31/047); F16J (13/24)

USPC: 220/231; 220/212; 220/240; 220/203.11; 220/367.1; 220/203.29; 220/203.01; 220/203.13;
215/228; 215/262; 215/260; 215/270; 215/311; 141/8; 141/65; 141/98; 206/524.8;
206/459.1; 99/472; 99/454

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1672904	12/1927	Randall	220/592.27	B65D 81/3818
3129835	12/1963	Collens	215/311	F04B 43/0063
4051971	12/1976	Saleri	99/476	B65D 81/2038
4083468	12/1977	Batchelor	220/234	B65D 39/12
4218967	12/1979	Batchelor	206/524.8	B65D 81/2038
4372096	12/1982	Baum	53/103	B67B 3/24
4807776	12/1988	Cortopassi	220/528	B65D 43/0212
4823968	12/1988	Handzlik	215/260	B65B 31/047
5390809	12/1994	Lin	220/592.27	F16K 15/1825
5398811	12/1994	Latella, Jr.	206/524.8	A47J 47/04
5406992	12/1994	Miramon	220/203.02	A47G 19/2272
5469979	12/1994	Chiou	220/625	B65D 81/2038
5546997	12/1995	Miramon	53/88	B65D 81/20
5558243	12/1995	Chu	220/240	B65D 81/2038
5564480	12/1995	Chen	220/203.02	A47J 47/06
5564581	12/1995	Lin	215/228	B65D 81/2038
5611376	12/1996	Chuang	215/311	B65B 31/047
5651470	12/1996	Wu	220/240	F16J 13/24
5692632	12/1996	Hsieh	220/240	B65D 81/20
5806575	12/1997	Tsay	141/192	B65D 81/2015
5944211	12/1998	Woodnorth	220/806	B65D 81/2038
5957317	12/1998	Lee	220/240	B65D 81/2038
6023915	12/1999	Colombo	426/106	B65D 77/225
6264054	12/2000	Miyake	220/23.91	B65D 81/2038
6619493	12/2002	Yang	220/203.11	B65D 51/1683
6644489	12/2002	Chang	215/311	B65D 81/2038
6789690	12/2003	Nieh	220/203.11	B65D 81/2015
6830081	12/2003	Chen	220/203.19	F04B 35/04
6877629	12/2004	Meyer	206/524.8	A47J 47/10
6994227	12/2005	Kwon	220/203.11	A47J 47/10
7048136	12/2005	Havens	222/509	B65D 51/1644
7296598	12/2006	Lin	220/240	B65D 81/2038

7299941	12/2006	McMahon, III	220/780	B65D 43/0222
7614522	12/2008	Hsu	220/784	A47J 36/027
8186527	12/2011	Liu	215/354	B65D 39/12
8590722	12/2012	Kim	277/530	B65D 81/2038
9108778	12/2014	Wang	N/A	B65D 51/165
9145242	12/2014	Wang	N/A	A47J 47/06
9731887	12/2016	Park	N/A	B65D 81/2015
9771200	12/2016	Sun	N/A	B65D 25/28
10597217	12/2019	Krus	N/A	B65D 81/2038
10968025	12/2020	Wei	N/A	B65D 81/2015
11021311	12/2020	Pace	N/A	A47J 41/02
11370592	12/2021	Wang	N/A	B65D 51/1644
2003/0116572	12/2002	Klock	220/373	A47J 36/027
2005/0051551	12/2004	Galletti	220/212	B65D 81/2038
2008/0078466	12/2007	Wang	141/65	B65D 81/2038
2008/0110911	12/2007	Chen	220/793	B65D 45/32
2010/0263328	12/2009	Dorsey	220/8	B65D 81/2015
2013/0146500	12/2012	Kim	206/524.8	B65D 81/2038
2020/0039724	12/2019	Park	N/A	B65D 43/0222
2021/0284398	12/2020	Valderrama	N/A	B65D 43/022

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2616493	12/2003	CN	N/A
WO-2012114277	12/2011	WO	A47J 36/027

Primary Examiner: Aviles; Orlando E

Assistant Examiner: Patel; Brijesh V.

Attorney, Agent or Firm: HESLIN, ROTHENBERG, FARLEY & MESITI, P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority to Taiwanese Application No. 112110818, filed on Mar. 23, 2023, which is incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

(2) The present invention relates to a vacuum container, and more particularly relates to a vacuum container which is simple in structure and easy to operate.

BACKGROUND OF THE INVENTION

(3) A conventional vacuum container for preserving foods is usually equipped with a vacuum pump to exhaust inside air to the outside of the vacuum container, thereby creating a vacuum state inside the vacuum container for food preservation. However, the disposing of the vacuum pump not only increases the assembly cost of the vacuum container but also complicates the whole structure by requiring the disposing of corresponding airtight flow paths to cause that the conventional vacuum container is not conducive to detachment and cleaning.

SUMMARY OF THE INVENTION

(4) Therefore, one objective of the present invention is to provide a vacuum container which is

conductive to detachment and cleaning and easy to operate to achieve/release the vacuum state.

(5) In order to achieve the above objective, the present invention provides a vacuum container, comprising: a storage container having a container opening and an accommodating space communicating with each other, wherein the container opening is formed on a top portion of the storage container such that an object to be preserved passes through the container opening to get into the accommodating space; a connecting tray component having a tray opening, a tray inside space and a guiding hole, wherein the tray opening is formed on a top portion of the connecting tray component and communicates with the tray inside space, the guiding hole is formed passing through the connecting tray component, and the connecting tray component air-tightly encloses the container opening to seal the accommodating space; a top cap having a pressing part, wherein the top cap is flexible such that the top cap is pressed to collapse and deform, the top cap encloses the tray opening to seal the tray inside space in a manner that the pressing part is in a position corresponding to the tray opening of the connecting tray component, and the top cap has an exhausting hole passing through the top cap; and two one-way exhausters, wherein one of the one-way exhausters is inserted in the guiding hole to mount in the connecting tray component thereby forming a tray one-way exhaust passage communicating the accommodating space of the storage container and the tray inside space of the connecting tray component, and another one-way exhauster is inserted in the exhausting hole to mount in the top cap thereby forming a cap one-way exhaust passage communicating the tray inside space and an outside space; wherein when the pressing part of the top cap is pressed to collapse and deform toward the tray inside space, the tray inside space is compressed by the pressing part and exhausts an exhaust air through the cap one-way exhaust passage to the outside space, and then the accommodating space is driven by a pressure difference between the tray inside space and the accommodating space to exhaust through the tray one-way exhaust passage to the tray inside space so that the accommodating space becomes in a state approaching vacuum, and the pressing part resiliently recovers due to an intake air to the tray inside space.

(6) In one embodiment of the present invention, a vacuum container is provided, wherein the connecting tray component has a connecting ring, a spacer tray and a top ring, the connecting ring is ring-shaped and has a down extending part and a receiving part, the down extending part is formed extending from a bottom portion of the connecting ring in a circular manner, the receiving part is arranged at a top portion of the connecting ring, the receiving part is in position corresponding to the top portion of the storage container, and the down extending part is in tight contact with an inner surface of the storage container so that the connecting ring is air-tightly mounted on the top portion of the storage container, the tray opening is formed on a top portion of the spacer tray, the tray inside space is formed inside the spacer tray, the guiding hole is formed passing through a bottom base of the spacer tray thereby mounting the one-way exhauster in the guiding hole, and the spacer tray has a contact part, the contact part is ring-shaped and disposed between the top portion of the spacer tray and the bottom base to form a stair like structure together with the top portion of the spacer tray and the bottom base, wherein the contact part is in tight contact with the receiving part of the connecting ring, and an outer surface of the spacer tray is arranged opposite to an inner surface of the connecting ring, and the outer surface of the spacer tray is arranged between the contact part and the bottom base, the top portion of the top ring is in tight contact with the top ring, and a bottom surface of the top cap is in tight contact with the top portion of the spacer tray, wherein the bottom portion of the connecting ring is in airtight contact with the top portion of the storage container to air-tightly enclose the container opening of the storage container with the spacer tray and the top ring, when the connecting ring is pulled in a manner away from the top portion of the storage container, an outside air from the outside space flows into the accommodating space.

(7) In one embodiment of the present invention, a vacuum container is provided, wherein the connecting ring of the connecting tray component further has a holding tab, the holding tab is

formed extending downward from an outer surface of the connecting ring, and the holding tab is provided to be held to facilitate pulling the connecting ring away from the top portion of the storage container.

(8) In one embodiment of the present invention, a vacuum container is provided, wherein the connecting ring of the connecting tray component further has a through hole, the through hole is formed passing through the down extending part so that two ends of the through hole are in a position corresponding to the inner surface of the storage container and the spacer tray, respectively so that the outside air in advance passes through the through hole to flow into the accommodating space of the storage container when the connecting ring is pulled upward slightly thereby preventing from pulling upward the connecting ring too high.

(9) In one embodiment of the present invention, a vacuum container is provided, wherein the top ring of the connecting tray component further has an extensional part, the extensional part is ring-shaped and formed extending downward from a bottom portion of the top ring to dispose in a top inner surface of the spacer tray, the top cap further has a bottom extending part, the bottom extending part is ring-shaped and is formed protruding from the bottom surface of the top cap, and the bottom extending part further has a plurality of transverse strips, the transverse strips are arranged to be spaced apart from each other and transversely protrude from an outer surface of the bottom extending part, wherein the bottom surface of the top cap, which abuts to a rim of the top cap, is in tight contact with a top surface of the top ring, the bottom extending part of the top cap is in tight contact with an inner surface of the top ring, and the transverse strips are in tight contact with the extensional part of the top ring thereby forming an airtight connection between the top ring and the top cap.

(10) In one embodiment of the present invention, a vacuum container is provided, wherein the spacer tray of the connection tray component has a plurality of guiding grooves, the guiding grooves are recessed from a bottom outer surface of the spacer tray in a radially spaced manner around the guiding hole, the guiding grooves communicate with the accommodating space of the storage container, the one-way exhauster mounted in the spacer tray has a cylinder, a bottom contact block, a top cover part and a membrane, the cylinder is inserted in the guiding hole of the spacer tray, a flowing clearance is formed between an outer surface of the cylinder and the bottom base of the spacer tray, and the flowing clearance communicates with the guiding grooves, the bottom contact block is arranged at a bottom portion of the cylinder and in contact with the bottom outer surface of the spacer tray to cover the guiding grooves, the top cover part is arranged at a top portion of the cylinder and disposed in the tray inside space of the spacer tray, the membrane is formed extending downward from a rim of the top cover part and at an inclined angle to the top cover part, and is in airtight contact with a bottom inner surface of the spacer tray, thereby forming, together with the spacer tray and the top cover part, a temporary chamber communicating with the flowing clearance, wherein the intake air from the accommodating space driven by the pressure difference between the tray inside space and the accommodating space flows through the guiding grooves, the flowing clearance and the temporary chamber and pushes the membrane away from the bottom inner surface of the spacer tray to open the tray one-way exhaust passage so that the intake air can flow to the tray inside space, after the intake air flows through the membrane, the membrane recovers to have an airtight contact with the bottom inner surface of the spacer tray to block the intake air from flowing back to the accommodating space.

(11) In one embodiment of the present invention, a vacuum container is provided, wherein the top cap has a plurality of exhausting grooves, the exhausting grooves are recessed from a bottom surface of the top cap in a radially spaced manner around the exhausting hole, the exhausting grooves communicate with the tray inside space of the spacer tray, the one-way exhauster mounted in the top cap has a cylinder, a bottom contact block, a top cover part and a membrane, the cylinder is inserted in the exhausting hole of the top cap, a flowing clearance is formed between an outer surface of the cylinder and the top cap, and the flowing clearance communicates with the

exhausting grooves, the bottom contact block is arranged at a bottom portion of the cylinder and in contact with the bottom surface of the top cap to cover the exhausting grooves, the top cover part is arranged at a top portion of the cylinder and disposed between the exhausting hole and the outside space, the membrane extends downward from a rim of the top cover part in an inclined angle with respect to the top cover part, and is in airtight contact with a top surface of the top cap, and the membrane is together with the top cap and the top cover part to form a temporary chamber communicating with the flowing clearance, wherein the exhaust air from the tray inside space compressed by the pressing part of the top cap flows through the exhausting grooves, the flowing clearance and the temporary chamber and pushes the membrane away from the top surface of the top cap to open the cap one-way exhaust passage so that the exhaust air can flow to the outside space, after the exhaust air flows through the membrane, the membrane recovers to have an airtight contact with the top surface of the top cap to block the outside air flowing back to the tray inside space.

(12) In one embodiment of the present invention, a vacuum container is provided, wherein the top cap further has a spacer groove, the spacer groove is recessed in the top cap and is formed to surround, together with the exhausting hole, the pressing part so that the pressing part of the top cap is easy to collapse and deform by pressing the pressing part.

(13) In one embodiment of the present invention, a vacuum container is provided, wherein the top cap has a vent hole, the vent hole is formed through the top cap and located in the pressing part, the vent hole communicates with the outside space and the tray inside space, wherein by pressing the top cap while blocking the vent hole, the top cap collapses to deform so as to exhaust the exhaust air to the outside space by compression of the tray inside space, after releasing the pressing operation of the pressing part, the vent hole is open and the tray inside space will have an atmospheric pressure the same as the outside space.

(14) The vacuum container of the present invention has the technical effects as follows. The vacuum container has a simple structure so that the vacuum container is easy to disassemble and assemble for cleaning. Moreover, it is easy to operate the vacuum container to achieve the vacuum state, and also easy to operate the vacuum container to release the vacuum state.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic diagram illustrating an appearance of a vacuum container according to one embodiment of the present invention;

(2) FIG. 2 is a schematic exploded view illustrating the vacuum container according to the embodiment of the present invention;

(3) FIG. 3 is a schematic sectional view illustrating the vacuum container according to the embodiment of the present invention along line 3-3 in FIG. 1;

(4) FIG. 4 is a schematic enlarged view illustrating the vacuum container according to the embodiment of the present invention in an area denoted by reference numeral 4 in FIG. 3;

(5) FIG. 5 is a schematic sectional view illustrating the vacuum container according to the embodiment of the present invention along line 5-5 in FIG. 1; and

(6) FIG. 6 is a schematic enlarged view illustrating the vacuum container according to the embodiment of the present invention in an area denoted by reference numeral 6 in FIG. 5.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(7) The preferred embodiments of the present invention are described in detail with reference to FIGS. 1 to 6. The description is used for explaining the embodiments of the present invention only, but not for limiting the scope of the claims.

(8) As shown in FIGS. 1 to 3, a vacuum container 100 according to one embodiment of the present

invention has a storage container **1**, a connecting tray component **2**, a top cap **3** and two one-way exhausters **4A**, **4B**. The vacuum container **100** of the present invention has a simple structure so that the vacuum container **100** is easy to disassemble and assemble for cleaning. Moreover, it is easy to operate the vacuum container **100** to achieve the vacuum state and to release the vacuum state, thus facilitating users to operate the vacuum container **100**.

(9) As shown in FIGS. **1** to **3**, the storage container **1** has a container opening **11** and an accommodating space **12** communicating with each other. The container opening **11** is formed on a top portion of the storage container **1** such that an object to be preserved passes through the container opening **11** to get into the accommodating space **12**.

(10) As shown in FIGS. **1** to **3**, the connecting tray component **2** has a tray opening **221**, a tray inside space **222** and a guiding hole **223**. The tray opening **221** is formed on a top portion of the connecting tray component **2** and communicates with the tray inside space **222**. The guiding hole **223** is formed passing through the connecting tray component **2**. The connecting tray component **2** air-tightly encloses the container opening **11** to seal the accommodating space **12**.

(11) As shown in FIGS. **1** to **3**, the top cap **3** has a pressing part **31**. The top cap **3** is flexible such that the top cap **3** is pressed to collapse and deform. The top cap **3** encloses the tray opening **221** to seal the tray inside space **222** in a manner that the pressing part **31** is in a position corresponding to the tray opening **221** of the connecting tray component **2**. Moreover, the top cap **3** has an exhausting hole **32** passing through the top cap **3**.

(12) As shown in FIGS. **1**, **5** and **6**, one of the one-way exhausters **4A** is inserted in the guiding hole **223** to mount in the connecting tray component **2** thereby forming a tray one-way exhaust passage. The tray one-way exhaust passage communicates the accommodating space **12** of the storage container **1** and the tray inside space **222** of the connecting tray component **2**.

(13) As shown in FIGS. **1**, **3** and **4**, the other one-way exhauster **4B** is inserted in the exhausting hole **32** to mount in the top cap **3** thereby forming a cap one-way exhaust passage. The cap one-way exhaust passage communicates the tray inside space **222** and an outside space.

(14) In the embodiment of the present invention, as shown in FIGS. **1**, **3** and **4**, when the pressing part **31** of the top cap **3** is pressed to collapse and deform toward the tray inside space **222**, the tray inside space **222** is compressed by the pressing part **31** and exhausts an exhaust air through the cap one-way exhaust passage to the outside space. With reference to FIGS. **1**, **5** and **6**, the accommodating space **12** is then driven by a pressure difference between the tray inside space **222** and the accommodating space **12** to exhaust through the tray one-way exhaust passage to the tray inside space **222** so that the accommodating space **12** becomes in a state approaching vacuum, and the pressing part **31** resiliently recovers due to an intake air to the tray inside space **222**.

(15) In detail, as shown in FIGS. **1** to **3**, according to the vacuum container **100** of the present invention, the connecting tray component **2** has a connecting ring **21**, a spacer tray **22** and a top ring **23**. The connecting ring **21** is ring-shaped and has a down extending part **211** and a receiving part **213**. The down extending part **211** is formed extending downward from a bottom portion of the connecting ring **21** in a circular manner. The receiving part **213** is arranged at a top portion of the connecting ring **21**. The receiving part **213** is in position corresponding to the top portion of the storage container **1**, and the down extending part **211** is in tight contact with an inner surface of the storage container **1** so that the connecting ring **21** is air-tightly mounted on the top portion of the storage container **1**. In detail, the bottom portion of the connecting ring **21** is in airtight contact with the top portion of the storage container **1** to air-tightly enclose the container opening **11** of the storage container **1** with the spacer tray **22** and the top ring **23**. When the connecting ring **21** is pulled in a manner away from the top portion of the storage container **1**, an outside air from the outside space flows into the accommodating space **12**.

(16) As shown in FIGS. **1**, **2**, **5** and **6**, the tray opening **221** is formed on a top portion of the spacer tray **22**, the tray inside space **222** is formed inside the spacer tray **22**, the guiding hole **223** is formed passing through a bottom base **224** of the spacer tray **22** thereby mounting the one-way

exhauster **4A** in the guiding hole **223**. Moreover, the spacer tray **22** has a contact part **220**, the contact part **220** is ring-shaped and disposed between the top portion of the spacer tray **22** and the bottom base **224** to form a stair like structure together with the top portion of the spacer tray **22** and the bottom base **224**. The contact part **220** is in tight contact with the receiving part **213** of the connecting ring **21**, and an outer surface of the spacer tray **22** is arranged opposite to an inner surface of the connecting ring **21**, wherein the outer surface of the spacer tray **22** is arranged between the contact part **220** and the bottom base **224**.

(17) As shown in FIGS. **1** to **3**, according to the vacuum container **100** of the present invention, the connecting ring **21** of the connecting tray component **2** further has a holding tab **212**. The holding tab **212** is formed extending downward from an outer surface of the connecting ring **21**. The holding tab **212** is provided to be held to facilitate pulling the connecting ring **21** away from the top portion of the storage container **1**.

(18) As shown in FIGS. **2** and **3**, the connecting ring **21** of the connecting tray component **2** further has a through hole **214**. The through hole **214** is formed passing through the down extending part **211** so that two ends of the through hole **214** are in position corresponding to the inner surface of the storage container **1** and the spacer tray **22**, respectively so that the outside air earlier passes through the through hole **214** to flow into the accommodating space **12** of the storage container **1** when the connecting ring **21** is pulled upward slightly thereby preventing from pulling upward the connecting ring **21** too high and causing damage to the connecting ring **21** due to tension.

Furthermore, the through hole **214** may be in position corresponding to the holding tab **212**.

(19) As shown in FIGS. **1** to **3**, the top portion of the top ring **23** is in tight contact with the top cap **3**, and a bottom surface of the top ring **23** is in tight contact with the top portion of the spacer tray **22**. According to the vacuum container **100** of the embodiment of the present invention, the top ring **23** of the connecting tray component **2** further has an extensional part **231**. The extensional part **231** is ring-shaped and formed extending downward from a bottom portion of the top ring **23** to dispose in a top inner surface of the spacer tray **22**.

(20) Furthermore, as shown in FIGS. **1** to **3**, the top cap **3** further has a bottom extending part **36**, the bottom extending part **36** is ring-shaped and is formed protruding from the bottom surface of the top cap **3**. Moreover, the bottom extending part **36** further has a plurality of transverse strips **361**, the transverse strips **361** are arranged to be spaced apart from each other and transversely protrude from an outer surface of the bottom extending part **36**. The bottom surface of the top cap **3**, which abuts to a rim of the top cap **3**, is in tight contact with a top surface of the top ring **23**, and the bottom extending part **36** of the top cap **3** is in tight contact with an inner surface of the top ring **23**. Furthermore, the transverse strips **361** are in tight contact with the extensional part **231** of the top ring **23** thereby forming an airtight connection between the top ring **23** and the top cap **3**.

(21) As shown in FIGS. **1**, **2**, **5** and **6**, according to the vacuum container **100** of the embodiment of the present invention, the spacer tray **22** of the connection tray component **2** has a plurality of guiding grooves **225**. The guiding grooves **225** are recessed from a bottom outer surface of the spacer tray **22** in a radially spaced manner around the guiding hole **223**. The guiding grooves **225** communicate with the accommodating space **12** of the storage container **1**.

(22) In detail, as shown in FIGS. **1**, **2**, **5** and **6**, the one-way exhauster **4A** mounted in the spacer tray **22** has a cylinder **41A**, a bottom contact block **42A**, a top cover part **43A** and a membrane **44A**. The cylinder **41A** is inserted in the guiding hole **223** of the spacer tray **22**, a flowing clearance is formed between an outer surface of the cylinder **41A** and the bottom base of the spacer tray **22**, and the flowing clearance communicates with the guiding grooves **225**. The bottom contact block **42A** is arranged at a bottom portion of the cylinder **41A** and in contact with the bottom outer surface of the spacer tray **22** to cover the guiding grooves **225**. The top cover part **43A** is arranged at a top portion of the cylinder **41A** and disposed in the tray inside space **222** of the spacer tray **22**. The membrane **44A** is formed extending downward from a rim of the top cover part **43A** and at an inclined angle to the top cover part **43A**, and is in airtight contact with a bottom inner surface of the

spacer tray **22**, thereby forming, together with the spacer tray **22** and the top cover part **43A**, a temporary chamber communicating with the flowing clearance.

(23) As shown in FIGS. **1**, **2**, **5** and **6**, the intake air from the accommodating space **12** driven by the pressure difference between the tray inside space **222** and the accommodating space **12** flows through the guiding grooves **225**, the flowing clearance and the temporary chamber and pushes the membrane **44A** away from the bottom inner surface of the spacer tray **22** to open the tray one-way exhaust passage so that the intake air can flow to the tray inside space **222**. After the intake air flows through the membrane **44A**, the membrane **44A** recovers to have an airtight contact with the bottom inner surface of the spacer tray **22** to block the intake air from flowing back to the accommodating space **12**.

(24) Furthermore, as shown FIGS. **1** to **4**, according to the vacuum container **100** of the embodiment of the present invention, the top cap **3** has a plurality of exhausting grooves **33**. The exhausting grooves **33** are recessed from a bottom surface of the top cap **3** in a radially spaced manner around the exhausting hole **32**. The exhausting grooves **33** communicate with the tray inside space **222** of the spacer tray **22**.

(25) As shown FIGS. **1** to **4**, the one-way exhauster **4B** mounted in the top cap **3** has a cylinder **41B**, a bottom contact block **42B**, a top cover part **43B** and a membrane **44B**. The cylinder **41B** is inserted in the exhausting hole **32** of the top cap **3**, a flowing clearance is formed between an outer surface of the cylinder **41B** and the top cap **3**, and the flowing clearance communicates with the exhausting grooves **33**. The bottom contact block **42B** is arranged at a bottom portion of the cylinder **41B** and in contact with the bottom surface of the top cap **3** to cover the exhausting grooves **33**. The top cover part **43B** is arranged at a top portion of the cylinder **41B** and disposed between the exhausting hole **32** and the outside space. The membrane **44B** extends downward from a rim of the top cover part **43B** in an inclined angle with respect to the top cover part **43B**, and is in airtight contact with a top surface of the top cap **3**, thereby forming, together with the top cap **3** and the top cover part **43B**, a temporary chamber communicating with the flowing clearance.

(26) As shown FIGS. **1** to **4**, the exhaust air from the tray inside space **222** compressed by the pressing part **31** of the top cap **3** flows through the exhausting grooves **33**, the flowing clearance and the temporary chamber and pushes the membrane **44B** away from the top surface of the top cap **3** to open the cap one-way exhaust passage so that the exhaust air can flow to the outside space. After the exhaust air flows through the membrane **44B**, the membrane **44B** recovers to have an airtight contact with the top surface of the top cap **3** to block the outside air flowing back to the tray inside space **222**.

(27) As shown FIGS. **1** to **3**, according to the vacuum container **100** of the embodiment of the present invention, the top cap **3** further has a spacer groove **34**. The spacer groove **34** is recessed in the top cap **3** and is formed to surround, together with the exhausting hole **32**, the pressing part **31** so that the pressing part **31** of the top cap **3** is easy to collapse and deform by pressing the pressing part **31**.

(28) As shown FIGS. **1**, **2** and **5**, according to the vacuum container **100** of the embodiment of the present invention, the top cap **3** has a vent hole **35**. The vent hole **35** is formed passing through the top cap **3** and located in the pressing part **31**. The vent hole **35** communicates with the outside space and the tray inside space **222**. In the embodiment of the present invention, by pressing the top cap **3** while blocking the vent hole **35**, the top cap **3** collapses to deform so as to exhaust the exhaust air to the outside space by compression of the tray inside space **222**. After releasing the pressing operation of the pressing part **31**, the vent hole **35** is open and the tray inside space **222** will have an atmospheric pressure the same as the outside space.

(29) The vacuum container **100** of the embodiment of the present invention only comprises the storage container **1**, the connecting tray component **2**, the top cap **3** and the two one-way exhausters **4A**, **4B** such that the overall assembly structure of the vacuum container **100** is relative simple, and thus easy to disassemble and assemble, which is conducive to cleaning of the vacuum container

100.

(30) Furthermore, by pressing the pressing part **31** of the top cap **3**, the exhaust air from the tray inside space **222** is exhausted through the cap one-way exhaust passage to the outside space, the intake air from the accommodating space **12** flows through the tray one-way exhaust passage to the tray inside space **222**, and therefore the accommodating space **12** of the storage container **1** becomes in the state approaching vacuum. In detail, the vacuum state of the accommodating space **12** can be released simply by holding the holding tab **212** to pull the connecting ring **21** away from the top portion of the storage container **1** to flow the outside air into the accommodating space **12**.

(31) The above description is merely the explanation of the preferred embodiment of the present invention. The ordinary person skilled in the art can apply other adjustments according to the claims below and the above description. However, the adjustments still belong to the technical concept of the present invention and fall into the claims of the present invention.

Claims

1. A vacuum container, comprising: a storage container having a container opening and an accommodating space communicating with each other, wherein the container opening is formed on a top portion of the storage container such that an object to be preserved passes through the container opening to get into the accommodating space; a connecting tray component having a tray opening, a tray inside space and a guiding hole, wherein the tray opening is formed on a top portion of the connecting tray component and communicates with the tray inside space, the guiding hole is formed passing through the connecting tray component, and the connecting tray component air-tightly encloses the container opening to seal the accommodating space; a top cap having a pressing part, wherein the top cap is flexible such that the top cap is pressed to collapse and deform, the top cap encloses the tray opening to seal the tray inside space in a manner that the pressing part is in a position corresponding to the tray opening of the connecting tray component, and the top cap has an exhausting hole passing through the top cap; and two one-way exhausters, wherein one of the one-way exhausters is inserted in the guiding hole to mount in the connecting tray component thereby forming a tray one-way exhaust passage communicating the accommodating space of the storage container and the tray inside space of the connecting tray component, and another one-way exhauster is inserted in the exhausting hole to mount in the top cap thereby forming a cap one-way exhaust passage communicating the tray inside space and an outside space; wherein when the pressing part of the top cap is pressed to collapse and deform toward the tray inside space, the tray inside space is compressed by the pressing part and exhausts an exhaust air through the cap one-way exhaust passage to the outside space, and then the accommodating space is driven by a pressure difference between the tray inside space and the accommodating space to exhaust through the tray one-way exhaust passage to the tray inside space so that the accommodating space becomes in a state approaching vacuum, and the pressing part resiliently recovers due to an intake air to the tray inside space.

2. The vacuum container as claimed in claim 1, wherein the connecting tray component has a connecting ring, a spacer tray and a top ring, the connecting ring is ring-shaped and has a down extending part and a receiving part, the down extending part is formed extending from a bottom portion of the connecting ring in a circular manner, the receiving part is arranged at a top portion of the connecting ring, the receiving part is in position corresponding to the top portion of the storage container, and the down extending part is in tight contact with an inner surface of the storage container so that the connecting ring is air-tightly mounted on the top portion of the storage container, the tray opening is formed on a top portion of the spacer tray, the tray inside space is formed inside the spacer tray, the guiding hole is formed passing through a bottom base of the spacer tray thereby mounting the one-way exhauster in the guiding hole, and the spacer tray has a contact part, the contact part is ring-shaped and disposed between the top portion of the spacer tray

and the bottom base to form a stair like structure together with the top portion of the spacer tray and the bottom base, wherein the contact part is in tight contact with the receiving part of the connecting ring, and an outer surface of the spacer tray is arranged opposite to an inner surface of the connecting ring, and the outer surface of the spacer tray is arranged between the contact part and the bottom base, the top portion of the top ring is in tight contact with the top cap, and a bottom surface of the top ring is in tight contact with the top portion of the spacer tray, wherein the bottom portion of the connecting ring is in airtight contact with the top portion of the storage container to air-tightly enclose the container opening of the storage container with the spacer tray and the top ring, when the connecting ring is pulled in a manner away from the top portion of the storage container, an outside air from the outside space flows into the accommodating space.

3. The vacuum container as claimed in claim 2, wherein the connecting ring of the connecting tray component further has a holding tab, the holding tab is formed extending downward from an outer surface of the connecting ring, and the holding tab is provided to be held to facilitate pulling the connecting ring away from the top portion of the storage container.

4. The vacuum container as claimed in claim 2, wherein the connecting ring of the connecting tray component further has a through hole, the through hole is formed passing through the down extending part so that two ends of the through hole are in a position corresponding to the inner surface of the storage container and the spacer tray, respectively so that the outside air in advance passes through the through hole to flow into the accommodating space of the storage container when the connecting ring is pulled upward slightly thereby preventing from pulling upward the connecting ring too high.

5. The vacuum container as claimed in claim 2, wherein the top ring of the connecting tray component further has an extensional part, the extensional part is ring-shaped and formed extending downward from a bottom portion of the top ring to dispose in a top inner surface of the spacer tray, the top cap further has a bottom extending part, the bottom extending part is ring-shaped and is formed protruding from the bottom surface of the top cap, and the bottom extending part further has a plurality of transverse strips, the transverse strips are arranged to be spaced apart from each other and transversely protrude from an outer surface of the bottom extending part, wherein the bottom surface of the top cap, which abuts to a rim of the top cap, is in tight contact with a top surface of the top ring, the bottom extending part of the top cap is in tight contact with an inner surface of the top ring, and the transverse strips are in tight contact with the extensional part of the top ring thereby forming an airtight connection between the top ring and the top cap.

6. The vacuum container as claimed in claim 2, wherein the spacer tray of the connection tray component has a plurality of guiding grooves, the guiding grooves are recessed from a bottom outer surface of the spacer tray in a radially spaced manner around the guiding hole, the guiding grooves communicate with the accommodating space of the storage container, the one-way exhauster mounted in the spacer tray has a cylinder, a bottom contact block, a top cover part and a membrane, the cylinder is inserted in the guiding hole of the spacer tray, a flowing clearance is formed between an outer surface of the cylinder and the bottom base of the spacer tray, and the flowing clearance communicates with the guiding grooves, the bottom contact block is arranged at a bottom portion of the cylinder and in contact with the bottom outer surface of the spacer tray to cover the guiding grooves, the top cover part is arranged at a top portion of the cylinder and disposed in the tray inside space of the spacer tray, the membrane is formed extending downward from a rim of the top cover part and at an inclined angle to the top cover part, and is in airtight contact with a bottom inner surface of the spacer tray, thereby forming, together with the spacer tray and the top cover part, a temporary chamber communicating with the flowing clearance, wherein the intake air from the accommodating space driven by the pressure difference between the tray inside space and the accommodating space flows through the guiding grooves, the flowing clearance and the temporary chamber and pushes the membrane away from the bottom inner surface of the spacer tray to open the tray one-way exhaust passage to flow the air to the tray inside

space, after the intake air flows through the membrane, the membrane recovers to have an airtight contact with the bottom inner surface of the spacer tray to block the intake air from flowing back to the accommodating space.

7. The vacuum container as claimed in claim 2, wherein the top cap has a plurality of exhausting grooves, the exhausting grooves are recessed from a bottom surface of the top cap in a radially spaced manner around the exhausting hole, the exhausting grooves communicate with the tray inside space of the spacer tray, the one-way exhauster mounted in the top cap has a cylinder, a bottom contact block, a top cover part and a membrane, the cylinder is inserted in the exhausting hole of the top cap, a flowing clearance is formed between an outer surface of the cylinder and the top cap, and the flowing clearance communicates with the exhausting grooves, the bottom contact block is arranged at a bottom portion of the cylinder and in contact with the bottom surface of the top cap to cover the exhausting grooves, the top cover part is arranged at a top portion of the cylinder and disposed between the exhausting hole and the outside space, the membrane extends downward from a rim of the top cover part in an inclined angle with respect to the top cover part, and is in airtight contact with a top surface of the top cap, and the membrane is together with the top cap and the top cover part to form a temporary chamber communicating with the flowing clearance, wherein the exhaust air from the tray inside space compressed by the pressing part of the top cap flows through the exhausting grooves, the flowing clearance and the temporary chamber and pushes the membrane away from the top surface of the top cap to open the cap one-way exhaust passage to flow the air to the outside space, after the exhaust air flows through the membrane, the membrane recovers to have an airtight contact with the top surface of the top cap to block the outside air flowing back to the tray inside space.

8. The vacuum container as claimed in claim 1, wherein the top cap further has a spacer groove, the spacer groove is recessed in the top cap and is formed to surround, together with the exhausting hole, the pressing part so that the pressing part of the top cap is easy to collapse and deform by pressing the pressing part.

9. The vacuum container as claimed in claim 1, wherein the top cap has a vent hole, the vent hole is formed through the top cap and located in the pressing part, the vent hole communicates with the outside space and the tray inside space, wherein by pressing the top cap while blocking the vent hole, the top cap collapses to deform so as to exhaust the exhaust air to the outside space by compression of the tray inside space, after releasing the pressing operation of the pressing part, the vent hole is open and the tray inside space will have an atmospheric pressure same as the outside space.

10. The vacuum container as claimed in claim 1, wherein the top cap has a vent hole, the vent hole is formed through the top cap and located in the pressing part, the vent hole communicates with the outside space and the tray inside space.
