

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12391374
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Hayes; Alexander et al.

---

### Aircraft hydraulic braking system including hydraulic accumulator and a brake actuator

---

#### Abstract

An aircraft hydraulic braking system having at least one hydraulic accumulator and a brake actuator. The at least one hydraulic accumulator is the sole source of pressurised hydraulic fluid in the aircraft hydraulic braking system for operating the brake actuator and thereby apply a braking force to a wheel on an aircraft.

---

**Inventors:** Hayes; Alexander (Bristol, GB), Ibrahim; Yasser (Bristol, GB), Palitta; Marica (Bristol, GB), Siegel; Romain (Bristol, GB)

**Applicant:** Airbus Operations Limited (Bristol, GB)

**Family ID:** 1000008763232

**Assignee:** AIRBUS OPERATIONS LIMITED (Bristol, GB)

**Appl. No.:** 17/956697

**Filed:** September 29, 2022

#### Prior Publication Data

Document Identifier	Publication Date
US 20230101767 A1	Mar. 30, 2023

#### Foreign Application Priority Data

GB	2114023	Sep. 30, 2021
----	---------	---------------

---

#### Publication Classification

**Int. Cl.:** B64C25/42 (20060101)

**U.S. Cl.:**

CPC                    **B64C25/42** (20130101);

## **Field of Classification Search**

**CPC:**                B64C (25/42)

---

## **References Cited**

### **U.S. PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Issued Date</b>	<b>Patentee Name</b>	<b>U.S. Cl.</b>	<b>CPC</b>
2502152	12/1949	Hudson	188/106R	B60T 13/141
3948569	12/1975	Gentet et al.	N/A	N/A
4121874	12/1977	Knox et al.	N/A	N/A
4251115	12/1980	Knox	303/113.1	B60T 8/445
4264109	12/1980	Knox	303/68	B64C 25/42
4792192	12/1987	Tveitane	N/A	N/A
5397173	12/1994	Bourguet	N/A	N/A
5411323	12/1994	Takahashi et al.	N/A	N/A
5456523	12/1994	Boehringer	N/A	N/A
8038094	12/2010	Oyama	N/A	N/A
2002/0057012	12/2001	Bourguet et al.	N/A	N/A
2009/0242694	12/2008	Oyama	N/A	N/A
2014/0014447	12/2013	O'Connell	74/483PB	B64C 25/44
2014/0117151	12/2013	Fox et al.	N/A	N/A
2016/0016575	12/2015	Howell	701/3	B60T 13/662
2019/0106095	12/2018	Burte	N/A	B60T 13/66
2020/0391856	12/2019	Knudsen	N/A	B64D 27/02

### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
108284947	12/2017	CN	N/A
1072103	12/1958	DE	N/A
3466780	12/2018	EP	N/A
598383	12/1947	GB	N/A
1166481	12/1968	GB	N/A
2563675	12/2017	GB	N/A
2602157	12/2021	GB	N/A

### **OTHER PUBLICATIONS**

Extended European Search Report in EP 22 19 9137 (May 23, 2023)(13 pages). cited by applicant  
EP Search Report in EP 23 15 4209 (Jun. 13, 2023)(6 pages). cited by applicant  
European Search Report cited in EP 22199137.5 mailed Jan. 25, 2023, 20 pages. cited by applicant

---

*Primary Examiner:* Sinaki; Arfan Y.

*Attorney, Agent or Firm:* Nixon & Vanderhye P.C.

---

## Background/Summary

### RELATED APPLICATION

(1) This application incorporates by reference in its entirety and claims priority to United Kingdom patent application GB 2114023-1, filed Sep. 30, 2021.

### TECHNICAL FIELD

(2) The present invention relates to braking systems for aircraft, particularly aircraft hydraulic braking systems, methods of and controllers for controlling the same, and aircraft comprising the braking systems and/or hydraulic braking systems.

(3) Aircraft braking systems typically comprise one or more primary energy sources, such as pumps, for operating plural brakes of an aircraft, such as to slow the aircraft during a landing event on a runway.

### BACKGROUND

(4) Some aircraft braking systems also comprise backup, or alternative, sources of pressurised hydraulic fluid for operating the brakes, such as hydraulic accumulators. These may be used to operate the brakes in the event of a failure of the one or more primary energy sources.

(5) The present invention aims to provide improved aircraft braking systems which are lighter, less complex and/or more efficient than known aircraft braking systems.

### SUMMARY

(6) A first aspect of the present invention provides an aircraft hydraulic braking system comprising at least one hydraulic accumulator and a brake actuator. The at least one hydraulic accumulator is the sole source of pressurised hydraulic fluid in the aircraft hydraulic braking system for operating the brake actuator.

(7) Providing the at least one hydraulic accumulator as the sole source of hydraulic fluid for operating the brake actuator may reduce a weight and/or complexity of the aircraft hydraulic braking system, such as by reducing a number of components and/or fluid connections in the aircraft hydraulic braking system, or between the aircraft hydraulic braking system and other hydraulic systems of the aircraft. For example, the aircraft hydraulic braking system need not be fluidically connected or connectable to a centralised hydraulic system of the aircraft. Indeed, such a centralised hydraulic system could be omitted from the aircraft.

(8) Optionally, the aircraft hydraulic braking system is free from plural hydraulic accumulators fluidically connected in series. This may similarly reduce a weight and/or complexity of the aircraft hydraulic braking system, such as by reducing a number of components and/or fluid connections in the aircraft hydraulic braking system.

(9) Optionally, the aircraft hydraulic braking system comprises at least one inlet for receiving hydraulic fluid to charge the at least one hydraulic accumulator, wherein the aircraft hydraulic braking system is configured so that in-flight charging of the at least one hydraulic accumulator via the at least one inlet is precluded.

(10) This may improve an in-flight reliability of the aircraft hydraulic braking system, such as by reducing a number of components and/or fluid connections that would otherwise be required to charge the at least one hydraulic accumulator in-flight, and/or by reducing a number of operations performed in-flight, such operations including charging the at least one hydraulic accumulator. Moreover, precluding in-flight charging of the at least one hydraulic accumulator may avoid a need to certify a charging system for operation during a flight.

(11) Optionally, the aircraft hydraulic braking system is free from any hydraulic fluid source for charging the at least one accumulator via the at least one inlet. This may reduce a number of components and/or fluid connections required to operate the hydraulic braking system, reducing a weight of the aircraft.

(12) Specifically, such a hydraulic fluid source may be free from any pump and/or hydraulic fluid reservoir for supplying hydraulic fluid to charge the at least one hydraulic accumulator. In this way, the brake actuator may be operated using fewer, or no, moving and/or electrical power-consuming components, thereby reducing a complexity of, and improving a reliability and efficiency of, the aircraft hydraulic braking system. Moreover, omitting a pump and/or hydraulic fluid reservoir may reduce a weight of the aircraft hydraulic braking system significantly.

(13) Optionally, the aircraft hydraulic braking system comprises a hydraulic fluid source for charging the at least one accumulator via the at least one inlet between flights. In this way, the at least one accumulator may be charged when the aircraft is on the ground, such as during taxiing or loading, without requiring connection to an external source of hydraulic fluid.

(14) Optionally, the hydraulic fluid source comprises a hydraulic fluid reservoir and a pump for pumping hydraulic fluid from the hydraulic fluid reservoir to the at least one accumulator via the at least one inlet to charge the at least one accumulator. Optionally, the pump is precluded from pumping hydraulic fluid from the hydraulic fluid reservoir to the at least one accumulator via the at least one inlet during flight of the aircraft.

(15) The hydraulic fluid reservoir may be configured to receive hydraulic fluid from the brake actuator during actuation of the actuator. This may be by the hydraulic braking system comprising one or more return lines and/or valves configured to return fluid from the brake actuator to the hydraulic fluid reservoir. This may allow the hydraulic fluid to be re-used following a braking event, such as to re-charge the at least one accumulator on the ground following a landing event of the aircraft during which the brake actuator is operated. This may reduce a requirement for ground crew to re-charge and/or top-up the aircraft hydraulic braking system following the braking event.

(16) Optionally, the aircraft hydraulic braking system comprises an isolator for isolating the pump from the at least one inlet and the at least one accumulator during flight of the aircraft.

Alternatively, or additionally, the aircraft hydraulic braking system is configured so that the pump is precluded from operating during flight of the aircraft.

(17) Providing an isolator may prevent accidental in-flight charging of the at least one accumulator, and/or may ensure that no fluid is passable back to the hydraulic fluid source, such as to the pump and/or the reservoir, during operation of the brake actuator. Optionally, there is no such hydraulic fluid source in the aircraft hydraulic braking system, and the inlet, and/or isolator, is connectable to a ground-based hydraulic fluid source to charge the at least one accumulator between flights.

(18) Precluding operation of the pump may reduce an in-flight power consumption of the aircraft hydraulic braking system, and/or may allow a smaller pump to be used, thereby reducing weight. Additionally, in this way, the hydraulic fluid system may require fewer additional components, such as additional pumps and/or valves, which may otherwise be required for improved redundancy. Moreover, precluding in-flight operation of the pump may avoid a need to certify the pump for in-flight operation.

(19) Optionally, the pump and the reservoir are configured to provide hydraulic fluid exclusively to the aircraft hydraulic braking system. In other words, the hydraulic fluid source is a local hydraulic fluid source exclusive to the aircraft hydraulic braking system. That is, the hydraulic fluid source may be separate from, and/or isolated from, any other hydraulic fluid system of the aircraft, such as a hydraulic fluid system for operating flight surfaces of the aircraft, and/or for extending and retracting landing gear of the aircraft. That is, the brake actuator may be operated without receiving pressurised hydraulic fluid from a centralised hydraulic fluid source, or centralised hydraulic fluid system, of the aircraft. This may reduce a weight and/or complexity of the aircraft hydraulic braking system, such as by reducing a number of fluid connections between different components of the aircraft. Optionally, the hydraulic fluid source, such as the pump and/or the reservoir, is a centralised hydraulic fluid source, such as by being configured to supply hydraulic fluid to another hydraulic system of the aircraft, such as to a landing gear extension/retraction system.

Alternatively, such a centralised hydraulic fluid source may be omitted from the aircraft.

(20) Optionally, the aircraft hydraulic braking system is configured so that the at least one hydraulic accumulator is precluded from being charged during at least partial discharge of the at least one hydraulic accumulator, such as to operate the brake actuator. Optionally, the pump is precluded from pumping hydraulic fluid from the hydraulic fluid reservoir to the at least one accumulator via the at least one inlet during a braking event of the aircraft.

(21) The braking event may be in-flight, such as when performing a pre-landing test of the brakes, or at the end of a flight, such as during a landing event of the aircraft. Precluding operation of the pump during the braking event may improve a reliability of the aircraft hydraulic braking system while reducing a number of components required for redundancy purposes, as outlined above.

(22) Optionally, the at least one hydraulic accumulator comprises a first hydraulic accumulator and a second hydraulic accumulator. Optionally, the aircraft hydraulic braking system is configured to be operable in a first mode, in which the first accumulator is fluidically coupled to the brake actuator to operate the brake actuator, and a second mode, in which the second accumulator is fluidically coupled to the brake actuator to operate the brake actuator.

(23) The first accumulator may be a primary hydraulic accumulator, and the first mode may be a primary operating mode. The second hydraulic accumulator may be either an alternative or a backup or “emergency” hydraulic accumulator, and the second mode may be either an alternative or backup operating mode. In this way, the second hydraulic accumulator may provide alternative and/or backup braking to the first brake actuator, improving a flexibility and/or reliability of the aircraft hydraulic braking system.

(24) Optionally, the aircraft hydraulic braking system comprises a second brake actuator. Optionally, in the first mode, the second hydraulic accumulator is fluidically coupled to the second brake actuator to operate the second brake actuator. Optionally, in the second mode, the second hydraulic accumulator is fluidically coupled to the second brake actuator to operate the second brake actuator.

(25) In this way, the first and second hydraulic accumulators may be configured in the first mode, such as during “normal” operation, to brake respective first and second brake actuators, which may be brake actuators of the same or different landing gears of the aircraft. In the second mode, the first hydraulic accumulator may be configured to brake one or both of the first and second brake actuators, such as in the event of a failure of the second hydraulic accumulator. The second hydraulic accumulator may be larger than the first hydraulic accumulator, such as to provide sufficient energy to brake both the first and second brake actuators. This may improve a reliability of the system without requiring additional hydraulic accumulators, thereby reducing a weight and complexity of the aircraft.

(26) A second aspect of the present invention provides a method of controlling a hydraulic braking system of an aircraft, the hydraulic braking system comprising a brake actuator and at least one hydraulic accumulator. The at least one hydraulic accumulator is the sole source of pressurised hydraulic fluid in the hydraulic braking system for operating the brake actuator. The method comprises precluding charging of, or not charging, the at least one hydraulic accumulator during a flight of the aircraft, and causing at least partial discharge of the at least one hydraulic accumulator to operate the brake actuator during the flight or during a landing event at an end of the flight.

(27) By not charging the at least one hydraulic accumulator during the flight of the aircraft, a complexity and/or weight of the hydraulic braking system may be reduced, and/or a reliability of the hydraulic braking system may be improved, in any way as described above. Moreover, this may avoid a need to certify a charging system for charging the at least one accumulator during the flight.

(28) In this aspect, the aircraft hydraulic braking system may comprise, or may be free from, plural hydraulic accumulators fluidically connected in series.

(29) Optionally, the method comprises causing charging of the at least one hydraulic accumulator while the aircraft is on the ground before the flight. The at least one hydraulic accumulator may be

fully, or only partially, charged, in order to provide at least sufficient power to brake the aircraft during the landing event at the end of the flight.

(30) Optionally, the causing charging comprises causing charging of the at least one hydraulic accumulator from a hydraulic fluid source of the hydraulic braking system. In this way, the charging of the accumulator may be performed without requiring connection to an external source of hydraulic fluid.

(31) Optionally, the hydraulic fluid source comprises a hydraulic fluid reservoir and a pump for pumping hydraulic fluid from the hydraulic fluid reservoir to the at least one accumulator to charge the at least one accumulator. This may provide any of the advantages discussed above in relation to the first aspect.

(32) Optionally, the hydraulic braking system comprises an isolator for isolating the pump from the at least one accumulator during the flight, or during flight of the aircraft. Alternatively, or additionally, the hydraulic braking system is configured so that the pump is precluded from operating during the flight, or during flight of the aircraft. This may provide any of the advantages discussed above in relation to the first aspect.

(33) Optionally, the pump and the reservoir are configured to provide hydraulic fluid exclusively to the hydraulic braking system. This may provide any of the advantages discussed above in relation to the first aspect.

(34) Optionally, the method comprises precluding charging of, or not charging, the at least one hydraulic accumulator during the causing at least partial discharge of the hydraulic accumulator. The method may comprise precluding charging of, or not charging, the at least one hydraulic accumulator during the whole landing event. This may improve a reliability of the aircraft hydraulic braking system, optionally while reducing a number of components required for redundancy purposes, as outlined above.

(35) Optionally, the method comprises precluding in-flight charging of the at least one hydraulic accumulator. That is, the at least one hydraulic accumulator may not be charged during any flight of the aircraft. Alternatively, the accumulators may be charged during one or more flights of the aircraft. In such a case, a charging system for the accumulator, such as a charging system comprising the hydraulic fluid source, may require certification, such as by certifying a pump and/or other component(s) of the hydraulic fluid source.

(36) A third aspect of the present invention provides an aircraft braking system controller configured to perform the method of the second aspect.

(37) The controller may be supplied in isolation. Alternatively, the controller may be a part of the aircraft hydraulic braking system, or any other suitable control system of the aircraft. The controller may provide any of the optional features and/or advantages of the second aspect.

(38) A fourth aspect of the present invention provides an aircraft hydraulic braking system according to the first aspect, comprising the aircraft braking system controller of the third aspect.

(39) A fifth aspect of the present invention provides a non-transitory computer-readable storage medium storing instructions that, when executed by a processor of an aircraft braking system controller, such as the controller of the third aspect, cause the processor to perform the method of the second aspect.

(40) A sixth aspect of the present invention provides a braking system for an aircraft, the braking system comprising a first hydraulic braking system and a second hydraulic braking system. The first hydraulic braking system comprises a first supply of hydraulic fluid and is configured to brake a first wheel of the aircraft, and the second hydraulic braking system comprises a second supply of hydraulic fluid and is configured to brake a second wheel of the aircraft. The braking system is free from any fluidic connection between the first and second hydraulic braking systems.

(41) Optionally, the first and second supplies of hydraulic fluid are exclusive to the respective first and second hydraulic braking systems. Optionally, the first and second supplies of hydraulic fluid are de-centralised, so that they are unable to provide pressurised hydraulic fluid to any other

hydraulic fluid system of the aircraft, such as a hydraulic fluid system for operating flight surfaces and/or landing gear extension or retraction.

(42) Optionally, the braking system is free from any fluid connections between the braking system and other hydraulic fluid systems of the aircraft. Omitting any fluid connections between the first and second hydraulic braking systems, and optionally between the braking system and other hydraulic fluid systems of the aircraft, may reduce a weight of the aircraft. Providing local hydraulic fluid sources may reduce a complexity and/or weight of the aircraft braking system, such as by reducing an amount of hydraulic fluid present in fluid connections between components of the aircraft.

(43) Optionally, the first wheel is a wheel of a first landing gear, and the second wheel is a wheel of a second landing gear. That is, the first and second hydraulic braking systems may be local to respective first and second landing gears. This may reduce a number of, or eliminate any, fluid connections between hydraulic braking systems of landing gears on opposite sides of an aircraft, thereby reducing a weight of the aircraft braking system, while reducing complexity and increasing reliability.

(44) Optionally, the first hydraulic braking system and/or the second hydraulic braking system comprises the aircraft hydraulic braking system of the first or fourth aspects. As such, the first and/or second hydraulic braking systems may benefit from any of the advantages provided by the first or fourth aspects, and optional features thereof.

(45) A seventh aspect of the present invention provides an aircraft comprising the aircraft hydraulic braking system of the first or fourth aspect, the aircraft braking system controller of the third aspect, the non-transitory computer-readable storage medium of the fifth aspect, or the braking system of the sixth aspect. The aircraft may benefit from any of the advantages provided by the first, third, fourth, fifth, and sixth aspects, or optional features thereof.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

(2) FIG. 1 shows a schematic view of an aircraft according to an example;

(3) FIG. 2 shows a schematic view of a hydraulic braking system of the aircraft of FIG. 1;

(4) FIG. 3 shows an example method of controlling the hydraulic braking system of FIG. 2; and

(5) FIG. 4 shows a schematic view of a non-transitory computer-readable storage medium according to an example.

### DETAILED DESCRIPTION

(6) The present disclosure describes an aircraft hydraulic braking system for braking at least one wheel of an aircraft, such as the aircraft **1** shown in FIG. 1. The aircraft **1** comprises plural landing gears **10a** to **10c**, specifically first and second main landing gears **10a**, **10b** located on opposite sides of a fuselage **12** of the aircraft, and a nose landing gear **10c** aligned with the fuselage. Each landing gear comprises respective sets of wheels **11a** to **11c**. The aircraft **1** comprises a braking system comprising first and second hydraulic braking systems **100a**, **100b**, each configured to brake a subset of the wheels **11a**, **11b** of the aircraft **10**. In the illustrated example, this is by each hydraulic braking system **100** being configured to brake the wheels **11a**, **11b** of a respective one of the landing gears **10a**, **10b**. In other examples, this is by each hydraulic braking system **100** being configured to brake a subset of wheels **11a** **11b** of one or both of the main landing gears **10a**, **10b**. In other examples, as described below, the aircraft comprises an aircraft hydraulic braking system **100** configured to brake the wheels **11a**, **11b** of both the first and second main landing gears **10a**, **10b**. The wheels **11c** of the nose landing gear are unbraked, but could alternatively be braked by

one of the aircraft hydraulic braking systems **100a**, **100b**, or another suitable braking system. In other examples, the aircraft **1** comprises any other suitable number of main landing gears, each comprising any suitable number of wheels, braked or unbraked.

(7) FIG. 2 shows an example of an aircraft hydraulic braking system **100** (or “braking system **100**”), which is an exemplary one of the first and second hydraulic braking systems **100a**, **100b**. The aircraft hydraulic braking system **100** comprises two subsystems, specifically a primary subsystem **110** and a secondary subsystem **210**. The primary subsystem **110** comprises a primary hydraulic accumulator **150** (or “accumulator **150**”), while the secondary subsystem **210** comprises a secondary hydraulic accumulator **250** (or “accumulator **250**”). The primary and secondary subsystems **110**, **210** are couplable to first to fourth brakes actuators **15a** to **15b** for braking respective first to fourth wheels **13a** to **13d** of the aircraft **1**. Each of the first to fourth wheels **13a** to **13d** are on a single one of the main landing gears. In other examples, the first and second wheels **13a** to **13b** are wheels **11a** of the first main landing gear **10a**, while the third and fourth wheels **13c**, **13d** are wheels **11b** of the second main landing gear **10b**. The brake actuators **15a** to **15d** are configured to brake a single respective wheel **13a** to **13d** of the aircraft **1**, but may alternatively be configured to brake any number of wheels **13a** to **13d**.

(8) Each of the first to fourth brake actuators **15a** to **15d** is couplable, by a respective one of first to fourth shuttle valves **14a** to **14d**, to either the primary subsystem **110** or the secondary subsystem **210**, specifically to receive pressurised hydraulic fluid from either the primary accumulator **150** or the secondary accumulator **250** to operate the respective brake **15a** to **15d**. The first to fourth shuttle valves **14a** to **14d** are each coupled, or couplable, to the primary and secondary subsystems **110**, **210** so that hydraulic fluid is passed through the shuttle valve from the subsystem **110**, **210** providing the highest pressure hydraulic fluid to the respective shuttle valve **14a**, **14d**. In other words, each shuttle valve **14a** to **14d** is passively operable by providing pressurised hydraulic fluid from one of the subsystems **110**, **210** of the hydraulic braking system **100** to one opening of the shuttle valve **14a** to **14d**, and providing pressurised hydraulic fluid at a lower pressure, or providing no hydraulic fluid, from the other subsystem **110**, **210** of the braking system **100** to another opening of the shuttle valve **14a** to **14d**. In other examples, the shuttle valves **14a** to **14d** may be replaced by any other suitable valves, such as electromechanical valves, for passing hydraulic fluid to the brake actuators **15a** to **15b** from either the primary subsystem **110** or the secondary subsystem **210**.

(9) The braking system **100** comprises first and second primary servo valves **120a**, **120b** and first and second secondary servo valves **220a**, **220b**, which may herein be referred to as primary and secondary “pairs” of servo valves **120a**, **120b** and **220a**, **220b**. The primary and secondary pairs of servo valves **120a**, **120b** and **220a**, **220b** are located in the respective first and second subsystems **110**, **210** of the braking system, and are fluidically couplable to the respective primary and secondary hydraulic accumulators **150**, **250** by respective primary and secondary selector valves **130**, **230**.

(10) A first side of each of the first and second shuttle valves **14a**, **14b** is coupled, or couplable, to the first primary servo valve **120a**, and a second, opposing, side of each of the first and second shuttle valves **14a**, **14b** is coupled, or couplable, to the first secondary shuttle valve **220a**, so that hydraulic fluid is passable from the respective primary and secondary subsystems **110**, **210** to the respective first and second sides of the first and second shuttle valves **14a**, **14b**. Similarly, a first side of each of the third and fourth shuttle valves **14c**, **14d** is coupled, or couplable, to the second primary servo valve **120b**, and a second, opposing, side of each of the third and fourth shuttle valves **14c**, **14d** is coupled, or couplable, to the second secondary shuttle valve **220b**, so that hydraulic fluid is passable from the respective primary and secondary subsystems **110**, **210** to the respective first and second sides of the third and fourth shuttle valves **14c**, **14d**. The primary and secondary pairs of servo valves are individually operable, such as by a controller as described below, to control an amount of pressurised hydraulic fluid that is passed from the respective primary and secondary subsystems **110**, **210** to the first to fourth shuttle valves **14a** to **14d**, and



thereby to the brake actuators **15a** to **15d**, to brake the wheels **13a** to **13d**. In some examples, the first and second primary and secondary servo valves **120a**, **220a** are operable to control braking of wheels **13a** to **13d** of a single one of the main landing gears **10a**, **10b**. In other examples, the first primary and secondary servo valves **120a**, **220a** are operable to control braking of wheels **13a**, **13b** of the first main landing gear **10a**, while the second primary and secondary servo valves **120b**, **220b** are operable to control braking of wheels **13c**, **13d** of the second main landing gear **10b**. Alternatively, there may be any other number of servo valves **120a**, **120b** and **220a**, **220b** operable to cause braking of any other number of wheels **13a** to **13d**.

(11) The primary and secondary selector valves **130**, **230** are operable, such as by a controller as described below, to selectively permit pressurised hydraulic fluid to pass from the respective primary and secondary accumulators **150**, **250** to the respective primary and secondary pairs of servo valves **120a**, **120b** and **220a**, **220b**. In other words, the primary and secondary selector valves **130**, **230** are operable to isolate the respective primary and/or secondary accumulators from the brake actuators **15a** to **15d**. This may provide improved redundancy, such in the event of a failure of any one of the primary and secondary selector valves **120a**, **120b** and **220a**, **220b**.

(12) In the present example, the secondary subsystem **210** is a “backup”, or “emergency” subsystem, such as to provide redundancy braking in the event of a failure in the primary subsystem **110**. That is, the braking system **100** is operable in a primary mode, in which the primary accumulator **150** is fluidically coupled to each of the brake **15a** to **15d** to operate the brake actuators **15a** to **15d**, and a secondary mode, in which the secondary accumulator **250** is fluidically coupled to each of the brake actuators **15a** to **15d** to operate the brake actuators **15a** to **15d**. That is, the secondary mode in the present example is a backup mode. As such, the secondary accumulator **250** is smaller than the primary accumulator **150**, but in other examples the primary and secondary hydraulic accumulators **150**, **250** may be the same size as each other, or the secondary hydraulic accumulator **250** may be larger than the primary hydraulic accumulator **150**.

(13) In another example, in a first mode, the first subsystem **110** is coupled to provide pressurised hydraulic fluid to operate one or more of the brake actuators **15a** to **15d**, such as the first and second brake actuators **15a**, **15b**, while the second subsystem is coupled to provide pressurised hydraulic fluid to one or more other brake actuators **15a** to **15d**, such as the third and fourth brake actuators **15c**, **15d**. The braking system **100** may be operated in the second mode for instance in the event of a failure of the secondary hydraulic accumulator **250**. In such an example, the primary accumulator **150** may be larger than the secondary accumulator **250**, and indeed may be “oversized”, so that it is able to provide sufficient pressurised hydraulic fluid to operate each of the first to fourth brake actuators **15a** to **15d**.

(14) In any event, in the example shown in FIG. 2, the primary and secondary hydraulic accumulators **150**, **250** are the sole sources of hydraulic fluid in the hydraulic braking system **100** for operating the brake actuators **15a** to **15d**. That is, pressurised hydraulic fluid for operating the brake actuators **15a** to **15d** can only be received from one or both of the first and second hydraulic accumulators **150**, **250**, regardless of any operating state. For example, in a primary operating mode, the pressurised hydraulic fluid is receivable from the primary hydraulic accumulator **150**, while in a secondary operating mode, and/or a backup mode, the pressurised hydraulic fluid is receivable from the secondary hydraulic accumulator **250**. There are no other sources of pressurised hydraulic fluid for operating the brake actuators **15a** to **15d**. In some examples, there is only one accumulator **150**, **250**, being the sole source of pressurised hydraulic fluid for operating the brake actuators **15a** to **15d**, while in other examples there are more than two accumulators **150**, **250**, together being the sole sources of pressurised hydraulic fluid for operating the brake actuators **15a** to **15d**. Moreover, the hydraulic braking system **100** of the present example is free from plural hydraulic accumulators fluidically connected in series.

(15) The illustrated hydraulic braking system **100** comprises a primary inlet **140** for receiving hydraulic fluid to charge the primary hydraulic accumulator **150**, and a secondary inlet **240** for

receiving hydraulic fluid to charge the secondary hydraulic accumulator **250**. The aircraft hydraulic braking system **100** is, however, configured so that in-flight charging of the primary and secondary accumulators **150**, **250** through the respective primary and secondary inlets **140**, **240** is precluded. (16) As shown using dashed lines in FIG. 2, the aircraft hydraulic braking system **100** of the illustrated example comprises a hydraulic fluid source **160** for charging the first and second hydraulic accumulators **150**, **250** via the respective first and second inlets. The hydraulic fluid source **160** comprises a hydraulic fluid reservoir **120** and a pump P for pumping hydraulic fluid from the hydraulic fluid reservoir **120** to the primary and secondary hydraulic accumulators **150**, **250** via the primary and secondary inlets **140**, **240**.

(17) In some examples, the hydraulic fluid reservoir **120** is configured to receive hydraulic fluid from the brake actuators **15a** to **15b** following a braking event. Specifically, as shown with dashed lines in FIG. 2, in some examples, the hydraulic braking system **100** comprises return fluid lines from the first and second primary and secondary servo valves **120a**, **120b** and **220a**, **220b**, to the hydraulic reservoir **120**. In some such examples, the brake actuators **15a** to **15b** comprise return biasing members, such as return springs, to cause the brake actuators **15a** to **15b** to return to an unbraked position following a braking event when pressurised fluid is no longer being supplied to operate the brake actuators **15a** to **15d**. This may be by the first and second primary and secondary servo valves **120a**, **120b** and **220a**, **220b** being operable to isolate the brake actuators **15a** to **15d** from the first and second hydraulic fluid sources **150**, **250** and couple the brake actuators **15a** to **15d** to the hydraulic fluid reservoir **120** via respective return lines.

(18) It will be appreciated that the pump P and reservoir **120** are not sources of pressurised hydraulic fluid for operating the brake actuators **15a** to **15d**. They are instead sources of hydraulic fluid for charging the accumulators **150**, **250**, and are precluded from in-flight operation, and/or are isolated from the accumulators **150**, **250** and the brake actuators **15a** to **15d**, during any flight of the aircraft **10**, including during braking events of the aircraft **10**, which may be performed as pre-landing tests, or during landing events at the ends of flights of the aircraft **10**. That is, as noted above, the primary and secondary hydraulic accumulators are the sole sources of pressurised hydraulic fluid for operating the brake actuators **15a** to **15d**, regardless of the presence of the hydraulic fluid source **160**.

(19) In some examples, the primary and secondary inlets **140**, **240** comprise, and/or are defined by, respective primary and secondary isolators **141**, **241**. In some examples, the primary and secondary isolators are configured, and/or are operable, to isolate the pump P from the primary and secondary accumulators **150**, **250** during flight of the aircraft **10**, in order to preclude in-flight charging of the primary and secondary hydraulic accumulators **150**, **250**.

(20) In other examples, in-flight charging of the primary and secondary accumulators **150**, **250** is precluded instead by the aircraft hydraulic braking system being free from any hydraulic fluid source **160** for charging the first and second accumulators **150**, **250** via the respective first and second inlets **140**, **240**. That is, in some examples, the pump P and reservoir **120** are not present, and the accumulators **150**, **250** can only be charged using fluid supplied from an external hydraulic fluid source, such as a ground-based hydraulic fluid source, when the aircraft is on the ground.

(21) Turning now to FIG. 3, shown is an example method **300** of controlling the hydraulic braking system **100**. The method comprises precluding **320** charging of, or not charging, the primary and secondary hydraulic accumulators **150**, **250** during a flight of the aircraft **10**. The method further comprises causing **330** at least partial discharge of the primary and/or secondary hydraulic accumulator **150**, **250** to operate one or more of the brake actuators **15a** to **15d** during a landing event at an end of the flight, and/or during the flight such as during an in-flight pre-landing test of the hydraulic braking system **100**.

(22) In some examples, the method also comprises causing **310** charging of the primary and/or secondary hydraulic accumulator **150**, **250** while the aircraft **10** is on the ground before the flight. This may comprise fully or only partially charging the primary and/or secondary hydraulic

accumulator **150, 250**, as suited to the needs of the flight.

(23) In some examples, the causing **310** charging of the primary and/or secondary hydraulic accumulator **150, 250** comprises causing **311** charging of the respective primary and/or secondary hydraulic accumulator **150, 250** from the hydraulic fluid source **160**, such as by operating the pump **P** of the hydraulic braking system **100** while the aircraft is on the ground. In other examples, the causing **310** the charging is performed by ground crew, such as by connecting an external hydraulic fluid supply to the respective primary and secondary inlets **140, 240**.

(24) In some examples, the method comprises precluding **331** charging of, or not charging, the primary and secondary hydraulic accumulators **150, 250** during the causing **330** at least partial discharge of either or both of the primary and secondary hydraulic accumulators **150, 250** to operate the brake actuator during the flight or during the landing event at the end of the flight.

(25) In some examples, the precluding **320** the charging of the primary and secondary hydraulic accumulators during the flight, and/or the precluding **331** the charging of the primary and secondary hydraulic accumulators **150, 250** during the causing **330** at least partial discharge of the primary and/or secondary hydraulic accumulator **150, 250**, is achieved by precluding in-flight charging of the primary and secondary hydraulic accumulators **150, 250**. That is, in some examples, as described above, the primary and secondary hydraulic accumulators **150, 250** are precluded from charging during any flight of the aircraft **10**.

(26) In the illustrated example, the aircraft **10** comprises an aircraft braking system controller **500** (or “controller **500**”). The controller **500**, and/or a processor (not shown) thereof, is configured to perform the method **300** of controlling the hydraulic braking system **100**. In the present example, the controller **500** is a part of the hydraulic braking system **100**, but in other examples, the controller **500** may be remote from the hydraulic braking system **100** and communicatively coupled to the hydraulic braking system **100**. In some such examples, the controller **500** may be a part of a braking system (not shown) of the aircraft **10**, the braking system comprising plural hydraulic braking systems **100**, and the controller **500** may be communicatively coupled to each of the plural hydraulic braking systems **100**. In other examples, the controller **500** is any other suitable controller of the aircraft **10**, or is a remote from the aircraft, such as in a cloud-based computing network to which the hydraulic braking system **100** is coupled, and/or is a part of a ground station, such as a ground station of a runway.

(27) In any event, the controller **500** is configured to operate any one or more of the components of the hydraulic braking system **100** to achieve the functionality described above with reference to the method **300** of FIG. 3 and/or the hydraulic braking control system **100** of FIG. 2. For example, the controller **500** may be configured to operate any one or more of: the pump **P**; first and/or second isolators coupled to, or comprising, the respective primary or secondary inlets **140, 240**; the primary and/or secondary selector valves **130, 230**; the primary and/or secondary pairs of servo valves **120a, 120b** and **220a, 220b**; and the first to fourth shuttle valves **14a** to **14d**, to provide the desired functionality, as will be understood.

(28) FIG. 4 shows a schematic diagram of a non-transitory computer-readable storage medium **400** according to an example. The non-transitory computer-readable storage medium **400** stores instructions **430** that, if executed by a processor **420** of a controller **410** or system **410**, cause the processor **420** to perform a method according to an example. In some examples, the controller **410** or system **410** is the aircraft braking system controller **500**, and/or the hydraulic braking system **100**. In some examples, the processor **420** is the processor as described above with reference to the controller **500**, or any variation thereof discussed herein.

(29) The instructions **420** comprise precluding **431** charging of, or not charging, the primary and secondary hydraulic accumulators **150, 250** during a flight of the aircraft **10**, and causing **432** at least partial discharge of the primary and/or secondary hydraulic accumulator **150, 250** to operate one or more of the brake actuators **15a** to **15d** during the flight or during a landing event at an end of the flight. In some examples, the computer readable storage medium **400** stores instructions that,

if executed by the processor **420**, cause the processor **420** to perform the method **300** described above with reference to FIG. **3** or any variant thereof discussed herein.

(30) It will be understood that while the above description is illustrative of an example hydraulic system **100**, other arrangements may be possible without departing from the scope of the invention, which is defined by the appended claims. For instance, it will be appreciated that the arrangement of valves shown in FIG. **2** is exemplary only, and that the hydraulic accumulators **150**, **250** may be coupled, or couplable, to the brake actuators **15a** to **15d** using any other suitable combination of valves known to the skilled person. Similarly, there may be any number of such hydraulic accumulators **150**, **250** coupled to any number of brake actuators **15a** to **15d** for braking any number of wheels **13a** to **13d** of any number of landing gears **10a** to **10c**.

(31) Additionally, as noted briefly above, the aircraft **10** comprises a braking system comprising first and second hydraulic braking systems **100a**, **100b**, each configured to brake a subset of the wheels **11a**, **11b** of the main landing gears **10a**, **10b**. In some such examples, this is by each hydraulic braking system **100** being configured to brake the wheels **11a**, **11b** of a respective one of the landing gears **10a**, **10b**. In such cases, the hydraulic braking systems **100a**, **100b** are self-contained. That is, they each comprise their own, local, hydraulic accumulators **150**, **250**. In some examples, the primary and secondary hydraulic accumulators **150**, **250** are exclusive to the respective hydraulic braking systems **100**. It will be understood that, for this to be the case, the braking system is free from any fluidic connections between any of the plural hydraulic braking systems **100**. Alternatively, however, as noted above, the aircraft **1** may comprise only a single one of the hydraulic braking systems **100a**, **100b**. In some such examples, the hydraulic braking system **100** is configured to brake wheels **11a**, **11b** on both the first and the second main landing gears **10a**, **10b**.

(32) While at least one exemplary embodiment of the present invention(s) is disclosed herein, it should be understood that modifications, substitutions and alternatives may be apparent to one of ordinary skill in the art and can be made without departing from the scope of this disclosure. This disclosure is intended to cover any adaptations or variations of the exemplary embodiment(s). In addition, in this disclosure, the terms “comprise” or “comprising” do not exclude other elements or steps, the terms “a” or “one” do not exclude a plural number, and the term “or” means either or both, unless the this application states otherwise. Furthermore, characteristics or steps which have been described may also be used in combination with other characteristics or steps and in any order unless the disclosure or context suggests otherwise. This disclosure hereby incorporates by reference the complete disclosure of any patent or application from which it claims benefit or priority.

## Claims

1. An aircraft hydraulic braking system configured to be onboard an aircraft, the aircraft hydraulic braking system comprising: at least one hydraulic accumulator and a brake actuator, wherein the at least one hydraulic accumulator is the sole source of pressurized hydraulic fluid in the aircraft hydraulic braking system for operating the brake actuator; at least one inlet configured to receive pressurized hydraulic fluid from a hydraulic fluid source, wherein the aircraft hydraulic braking system is configured with a first mode of operation in which the at least one hydraulic accumulator is isolated from the hydraulic fluid source, wherein the aircraft hydraulic braking system is configured to operate in the first mode while the aircraft is in flight to prevent hydraulic fluid from flowing via the at least one inlet from the hydraulic fluid source to the at least one hydraulic accumulator, wherein the aircraft hydraulic braking system is configured with a second mode of operation in which the at least one hydraulic accumulator is in fluid communication with the pressurized fluid source via the at least one inlet, and wherein the aircraft hydraulic braking system is configured to operate in the second mode during a period while the aircraft is on the ground.

2. The aircraft hydraulic braking system of claim 1, wherein the aircraft braking system is in the first mode during a braking event of the aircraft.
  3. The aircraft hydraulic braking system of claim 1, wherein the at least one accumulator comprises a first accumulator and a second accumulator; and wherein the aircraft hydraulic braking system is configured to be operable in a third mode, in which the first accumulator is fluidically coupled to the brake actuator to operate the brake actuator, and a fourth mode, in which the second accumulator is fluidically coupled to the brake actuator to operate the brake actuator.
  4. The aircraft hydraulic braking system of claim 3, further comprising a second brake actuator, wherein, in the third mode, the second accumulator is fluidically coupled to the second brake actuator to operate the second brake actuator.
  5. The aircraft hydraulic braking system of claim 3, further comprising a second brake actuator, wherein, in the fourth mode, the second accumulator is fluidically coupled to the second brake actuator to operate the second brake actuator.
  6. The aircraft hydraulic braking system of claim 1, further comprising a controller configured to: preclude charging of the at least one hydraulic accumulator during the flight of the aircraft; and cause at least partial discharge of the at least one hydraulic accumulator to operate the at least one brake actuator during the flight or during a landing event at an end of the flight.
  7. The aircraft hydraulic braking system of claim 6, wherein the controller is further configured to cause charging of the at least one hydraulic accumulator while the aircraft is on the ground before the flight.
  8. The aircraft hydraulic braking system of claim 7, wherein the charging of the at least one hydraulic accumulator is from the hydraulic fluid source.
  9. The aircraft hydraulic braking system of claim 6, wherein the preclusion of the charging of the at least one hydraulic accumulator is performed during the causing the at least partial discharge of the hydraulic accumulator.
  10. An aircraft comprising the aircraft hydraulic braking system of claim 1.
  11. The aircraft hydraulic braking system of claim 1, wherein the hydraulic fluid source comprises a hydraulic fluid reservoir, and the hydraulic braking system further comprises a pump configured to pump hydraulic fluid from the hydraulic fluid reservoir to the at least one accumulator via the at least one inlet to charge the at least one accumulator while the aircraft hydraulic braking system is in the second mode of operation.
  12. A braking system configured to be mounted onboard an aircraft, the braking system comprising: a first hydraulic braking system including first accumulator of hydraulic fluid and a first brake actuator, wherein the first hydraulic braking system is configured to brake a first wheel of the aircraft and the first accumulator is the sole source of pressurized hydraulic fluid for operating the first brake actuator, and a second hydraulic braking system includes a second accumulator of hydraulic fluid and a second brake actuator, wherein the second hydraulic braking system is configured to brake a second wheel of the aircraft and the second accumulator is the sole source of pressurized hydraulic fluid for operating the second brake actuator; wherein the first hydraulic braking system is isolated from and devoid of fluidic connection with the second hydraulic braking system.
-