

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12393611
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Ploegert; Justin J. et al.

Building data platform with graph based capabilities

Abstract

A building system of a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to identify a capability of an entity in a building graph, the building graph including a plurality of nodes and a plurality of edges, the plurality of nodes representing entities of the building including the entity and the capability, the plurality of edges representing relationships between the entities of the building and the capability. The instructions cause the one or more processors to receive a command to perform an operation associated with the entity, the operation associated with the capability of the entity and provide the command to perform the operation associated with the entity to an operating system.

Inventors: Ploegert; Justin J. (Cudahy, WI), O'Dierno; Dominick James (Mt Pleasant, WI), Otto; Brian Scott (Menomonee Falls, WI)

Applicant: Tyco Fire & Security GmbH (Schaffhausen, CH)

Family ID: 1000008766698

Assignee: TYCO FIRE & SECURITY GMBH (Neuhausen am Rheinfall, CH)

Appl. No.: 18/483430

Filed: October 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240121131 A1	Apr. 11, 2024

Related U.S. Application Data

continuation parent-doc US 17833407 20220606 US 11968059 child-doc US 18483430
continuation parent-doc US 17134664 20201228 US 11356292 20220607 child-doc US 17833407
us-provisional-application US 62955856 20191231
us-provisional-application US 63005841 20200406
us-provisional-application US 63105754 20201026

Publication Classification

Int. Cl.: G05B15/02 (20060101); G05B13/02 (20060101); G05B13/04 (20060101); G05B17/02 (20060101); G05B19/042 (20060101); G06F9/54 (20060101); G06F16/21 (20190101); G06F16/23 (20190101); G06F16/2452 (20190101); G06F16/2457 (20190101); G06F16/25 (20190101); G06F16/27 (20190101); G06F16/28 (20190101); G06F16/901 (20190101); G06F21/60 (20130101); G06F30/13 (20200101); G06Q30/04 (20120101); G06Q50/00 (20120101); G06Q50/06 (20120101); H04L12/28 (20060101); H04L67/12 (20220101); H04L67/561 (20220101); H04L43/062 (20220101)

U.S. Cl.:

CPC G06F16/288 (20190101); G05B13/0265 (20130101); G05B13/041 (20130101); G05B13/047 (20130101); G05B15/02 (20130101); G05B17/02 (20130101); G05B19/0428 (20130101); G06F9/542 (20130101); G06F9/547 (20130101); G06F16/212 (20190101); G06F16/2358 (20190101); G06F16/24526 (20190101); G06F16/24575 (20190101); G06F16/258 (20190101); G06F16/27 (20190101); G06F16/9024 (20190101); G06F21/60 (20130101); G06F30/13 (20200101); G06Q30/04 (20130101); G06Q50/00 (20130101); G06Q50/06 (20130101); H04L12/282 (20130101); H04L12/2827 (20130101); H04L67/12 (20130101); H04L67/561 (20220501); G05B2219/163 (20130101); G05B2219/25011 (20130101); G05B2219/2614 (20130101); G05B2219/2642 (20130101); G05B2219/2652 (20130101); H04L12/2803 (20130101); H04L12/2807 (20130101); H04L43/062 (20130101)

Field of Classification Search

CPC: H04L (12/2827); H04L (12/282); H04L (43/04); G06F (16/9024); G06F (16/288); G05B (15/02); G05B (2219/2652); G05B (2219/25011); G06N (3/006)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5301109	12/1993	Landauer et al.	N/A	N/A
5446677	12/1994	Jensen et al.	N/A	N/A
5581478	12/1995	Cruse et al.	N/A	N/A
5812962	12/1997	Kovac	N/A	N/A
5960381	12/1998	Singers et al.	N/A	N/A
5973662	12/1998	Singers et al.	N/A	N/A
6014612	12/1999	Larson et al.	N/A	N/A
6031547	12/1999	Kennedy	N/A	N/A
6134511	12/1999	Subbarao	N/A	N/A
6157943	12/1999	Meyer	N/A	N/A
6285966	12/2000	Brown et al.	N/A	N/A
6363422	12/2001	Hunter et al.	N/A	N/A
6385510	12/2001	Hoog et al.	N/A	N/A
6389331	12/2001	Jensen et al.	N/A	N/A
6401027	12/2001	Xu et al.	N/A	N/A
6437691	12/2001	Sandelman et al.	N/A	N/A
6477518	12/2001	Li et al.	N/A	N/A
6487457	12/2001	Hull et al.	N/A	N/A
6493755	12/2001	Hansen et al.	N/A	N/A
6577323	12/2002	Jamieson et al.	N/A	N/A

6626366	12/2002	Kayahara et al.	N/A	N/A
6646660	12/2002	Patty	N/A	N/A
6704016	12/2003	Oliver et al.	N/A	N/A
6732540	12/2003	Sugihara et al.	N/A	N/A
6764019	12/2003	Kayahara et al.	N/A	N/A
6782385	12/2003	Natsumeda et al.	N/A	N/A
6813532	12/2003	Eryurek et al.	N/A	N/A
6816811	12/2003	Seem	N/A	N/A
6823680	12/2003	Jayanth	N/A	N/A
6826454	12/2003	Sulfstede	N/A	N/A
6865511	12/2004	Frerichs et al.	N/A	N/A
6925338	12/2004	Eryurek et al.	N/A	N/A
6986138	12/2005	Sakaguchi et al.	N/A	N/A
7031880	12/2005	Seem et al.	N/A	N/A
7401057	12/2007	Eder	N/A	N/A
7552467	12/2008	Lindsay	N/A	N/A
7627544	12/2008	Chkodrov et al.	N/A	N/A
7716685	12/2009	Schechter et al.	N/A	N/A
7818249	12/2009	Lovejoy et al.	N/A	N/A
7822708	12/2009	Mathew et al.	N/A	N/A
7889051	12/2010	Billig et al.	N/A	N/A
7996488	12/2010	Casabella et al.	N/A	N/A
8078330	12/2010	Brickfield et al.	N/A	N/A
8104044	12/2011	Scofield et al.	N/A	N/A
8229470	12/2011	Ranjan et al.	N/A	N/A
8265979	12/2011	Golani et al.	N/A	N/A
8401991	12/2012	Wu et al.	N/A	N/A
8495745	12/2012	Schrecker et al.	N/A	N/A
8516016	12/2012	Park et al.	N/A	N/A
8532808	12/2012	Drees et al.	N/A	N/A
8532839	12/2012	Drees et al.	N/A	N/A
8600556	12/2012	Nesler et al.	N/A	N/A
8635182	12/2013	Mackay	N/A	N/A
8682921	12/2013	Park et al.	N/A	N/A
8731724	12/2013	Drees et al.	N/A	N/A
8737334	12/2013	Ahn et al.	N/A	N/A
8738334	12/2013	Jiang et al.	N/A	N/A
8738414	12/2013	Nagar et al.	N/A	N/A
8751487	12/2013	Byrne et al.	N/A	N/A
8788097	12/2013	Drees et al.	N/A	N/A
8805995	12/2013	Oliver	N/A	N/A
8843238	12/2013	Wenzel et al.	N/A	N/A
8874071	12/2013	Sherman et al.	N/A	N/A
8941465	12/2014	Pineau et al.	N/A	N/A
8990127	12/2014	Taylor	N/A	N/A
9070113	12/2014	Shafiee et al.	N/A	N/A
9116978	12/2014	Park et al.	N/A	N/A
9185095	12/2014	Moritz et al.	N/A	N/A
9189527	12/2014	Park et al.	N/A	N/A
9189567	12/2014	Goldman et al.	N/A	N/A
9196009	12/2014	Drees et al.	N/A	N/A
9219736	12/2014	Lewis et al.	N/A	N/A
9229966	12/2015	Aymeloglu et al.	N/A	N/A
9286582	12/2015	Drees et al.	N/A	N/A

9311807	12/2015	Schultz et al.	N/A	N/A
9344751	12/2015	Ream et al.	N/A	N/A
9354968	12/2015	Wenzel et al.	N/A	N/A
9507686	12/2015	Horn et al.	N/A	N/A
9524594	12/2015	Ouyang et al.	N/A	N/A
9558196	12/2016	Johnston et al.	N/A	N/A
9652813	12/2016	Gifford et al.	N/A	N/A
9753455	12/2016	Drees	N/A	N/A
9811249	12/2016	Chen et al.	N/A	N/A
9817383	12/2016	Sinha et al.	N/A	N/A
9838844	12/2016	Emeis et al.	N/A	N/A
9870413	12/2017	Saulpaugh et al.	N/A	N/A
9886478	12/2017	Mukherjee	N/A	N/A
9948359	12/2017	Horton	N/A	N/A
10055114	12/2017	Shah et al.	N/A	N/A
10055206	12/2017	Park et al.	N/A	N/A
10095756	12/2017	Park et al.	N/A	N/A
10116461	12/2017	Fairweather et al.	N/A	N/A
10169454	12/2018	Ait-Mokhtar et al.	N/A	N/A
10169486	12/2018	Park et al.	N/A	N/A
10171297	12/2018	Stewart et al.	N/A	N/A
10171586	12/2018	Shaashua et al.	N/A	N/A
10187258	12/2018	Nagesh et al.	N/A	N/A
10417245	12/2018	Park et al.	N/A	N/A
10417451	12/2018	Park et al.	N/A	N/A
10505756	12/2018	Park et al.	N/A	N/A
10514963	12/2018	Shrivastava et al.	N/A	N/A
10515098	12/2018	Park et al.	N/A	N/A
10534326	12/2019	Sridharan et al.	N/A	N/A
10536295	12/2019	Fairweather et al.	N/A	N/A
10564993	12/2019	Deutsch et al.	N/A	N/A
10678866	12/2019	Ranganathan et al.	N/A	N/A
10684033	12/2019	Sinha et al.	N/A	N/A
10705492	12/2019	Harvey	N/A	N/A
10708078	12/2019	Harvey	N/A	N/A
10739029	12/2019	Sinha et al.	N/A	N/A
10747183	12/2019	Sinha et al.	N/A	N/A
10760815	12/2019	Janakiraman et al.	N/A	N/A
10762475	12/2019	Song et al.	N/A	N/A
10798175	12/2019	Knight et al.	N/A	N/A
10824120	12/2019	Ahmed	N/A	N/A
10845771	12/2019	Harvey	N/A	N/A
10853146	12/2019	Talayco	N/A	N/A
10854194	12/2019	Park et al.	N/A	N/A
10859984	12/2019	Park	N/A	N/A
10862928	12/2019	Badawy et al.	N/A	N/A
10901373	12/2020	Locke et al.	N/A	N/A
10921760	12/2020	Harvey	N/A	N/A
10921972	12/2020	Park et al.	N/A	N/A
10969133	12/2020	Harvey	N/A	N/A
10986121	12/2020	Stockdale et al.	N/A	N/A
11016998	12/2020	Park et al.	N/A	N/A
11024292	12/2020	Park et al.	N/A	N/A
11038709	12/2020	Park et al.	N/A	N/A

11041650	12/2020	Li et al.	N/A	N/A
11042144	12/2020	Park et al.	N/A	N/A
11054796	12/2020	Holaso	N/A	N/A
11070390	12/2020	Park et al.	N/A	N/A
11073976	12/2020	Park et al.	N/A	N/A
11108587	12/2020	Park et al.	N/A	N/A
11113295	12/2020	Park et al.	N/A	N/A
11229138	12/2021	Harvey et al.	N/A	N/A
11238065	12/2021	Tang	N/A	N/A
11314726	12/2021	Park et al.	N/A	N/A
11314788	12/2021	Park et al.	N/A	N/A
11556105	12/2022	Cooley et al.	N/A	N/A
11561522	12/2022	Cooley et al.	N/A	N/A
11561523	12/2022	Cooley et al.	N/A	N/A
11573551	12/2022	Cooley et al.	N/A	N/A
11586167	12/2022	Cooley et al.	N/A	N/A
11663375	12/2022	Brett et al.	N/A	N/A
2002/0010562	12/2001	Schleiss et al.	N/A	N/A
2002/0016639	12/2001	Smith et al.	N/A	N/A
2002/0059229	12/2001	Natsumeda et al.	N/A	N/A
2002/0123864	12/2001	Eryurek et al.	N/A	N/A
2002/0147506	12/2001	Eryurek et al.	N/A	N/A
2002/0177909	12/2001	Fu et al.	N/A	N/A
2003/0005486	12/2002	Ridolfo et al.	N/A	N/A
2003/0014130	12/2002	Grumelart	N/A	N/A
2003/0073432	12/2002	Meade, II	N/A	N/A
2003/0158704	12/2002	Triginai et al.	N/A	N/A
2003/0171851	12/2002	Brickfield et al.	N/A	N/A
2003/0200059	12/2002	Ignatowski et al.	N/A	N/A
2004/0068390	12/2003	Saunders	N/A	N/A
2004/0128314	12/2003	Katibah et al.	N/A	N/A
2004/0133314	12/2003	Ehlers et al.	N/A	N/A
2004/0199360	12/2003	Friman et al.	N/A	N/A
2004/0210348	12/2003	Imhof et al.	N/A	N/A
2005/0055308	12/2004	Meyer et al.	N/A	N/A
2005/0108262	12/2004	Fawcett et al.	N/A	N/A
2005/0154494	12/2004	Ahmed	N/A	N/A
2005/0278703	12/2004	Lo et al.	N/A	N/A
2005/0283337	12/2004	Sayal	N/A	N/A
2006/0095521	12/2005	Patinkin	N/A	N/A
2006/0140207	12/2005	Eschbach et al.	N/A	N/A
2006/0184479	12/2005	Levine	N/A	N/A
2006/0200476	12/2005	Gottumukkala et al.	N/A	N/A
2006/0248573	12/2005	Pannu et al.	N/A	N/A
2006/0265751	12/2005	Cosquer et al.	N/A	N/A
2006/0271589	12/2005	Horowitz et al.	N/A	N/A
2007/0028179	12/2006	Levin et al.	N/A	N/A
2007/0203693	12/2006	Estes	N/A	N/A
2007/0261062	12/2006	Bansal et al.	N/A	N/A
2007/0273497	12/2006	Kuroda et al.	N/A	N/A
2007/0273610	12/2006	Baillot	N/A	N/A
2008/0034425	12/2007	Overcash et al.	N/A	N/A
2008/0094230	12/2007	Mock et al.	N/A	N/A
2008/0097816	12/2007	Freire et al.	N/A	N/A

2008/0186160	12/2007	Kim et al.	N/A	N/A
2008/0249756	12/2007	Chaisuparasmikul	N/A	N/A
2008/0252723	12/2007	Park	N/A	N/A
2008/0281472	12/2007	Podgorny et al.	N/A	N/A
2009/0195349	12/2008	Frader-Thompson et al.	N/A	N/A
2009/0287736	12/2008	Shike et al.	N/A	N/A
2010/0045439	12/2009	Tak et al.	N/A	N/A
2010/0058248	12/2009	Park	N/A	N/A
2010/0070981	12/2009	Hadar et al.	N/A	N/A
2010/0131533	12/2009	Ortiz	N/A	N/A
2010/0274366	12/2009	Fata et al.	N/A	N/A
2010/0281387	12/2009	Holland et al.	N/A	N/A
2010/0286937	12/2009	Hedley et al.	N/A	N/A
2010/0324962	12/2009	Nesler et al.	N/A	N/A
2011/0015802	12/2010	Imes	N/A	N/A
2011/0047418	12/2010	Drees et al.	N/A	N/A
2011/0061015	12/2010	Drees et al.	N/A	N/A
2011/0071685	12/2010	Huneycutt et al.	N/A	N/A
2011/0077950	12/2010	Hughston	N/A	N/A
2011/0087650	12/2010	Mackay et al.	N/A	N/A
2011/0087988	12/2010	Ray et al.	N/A	N/A
2011/0088000	12/2010	Mackay	N/A	N/A
2011/0093424	12/2010	Zimmermann et al.	N/A	N/A
2011/0125737	12/2010	Pothering et al.	N/A	N/A
2011/0137853	12/2010	Mackay	N/A	N/A
2011/0153603	12/2010	Adiba et al.	N/A	N/A
2011/0154363	12/2010	Karmarkar	N/A	N/A
2011/0157357	12/2010	Weisensale et al.	N/A	N/A
2011/0178977	12/2010	Drees	N/A	N/A
2011/0191343	12/2010	Heaton et al.	N/A	N/A
2011/0205022	12/2010	Cavallaro et al.	N/A	N/A
2011/0218777	12/2010	Chen et al.	N/A	N/A
2011/0270853	12/2010	Curbera et al.	N/A	N/A
2012/0011126	12/2011	Park et al.	N/A	N/A
2012/0011141	12/2011	Park et al.	N/A	N/A
2012/0022698	12/2011	Mackay	N/A	N/A
2012/0062577	12/2011	Nixon	N/A	N/A
2012/0064923	12/2011	Imes et al.	N/A	N/A
2012/0083930	12/2011	Ilic et al.	N/A	N/A
2012/0100825	12/2011	Sherman et al.	N/A	N/A
2012/0101637	12/2011	Imes et al.	N/A	N/A
2012/0135759	12/2011	Imes et al.	N/A	N/A
2012/0136485	12/2011	Weber et al.	N/A	N/A
2012/0158633	12/2011	Eder	N/A	N/A
2012/0221581	12/2011	Narayanan et al.	N/A	N/A
2012/0259583	12/2011	Noboa et al.	N/A	N/A
2012/0272228	12/2011	Marndi et al.	N/A	N/A
2012/0278051	12/2011	Jiang et al.	N/A	N/A
2013/0007063	12/2012	Kalra et al.	N/A	N/A
2013/0038430	12/2012	Blower et al.	N/A	N/A
2013/0038707	12/2012	Cunningham et al.	N/A	N/A
2013/0060820	12/2012	Bulusu et al.	N/A	N/A
2013/0086497	12/2012	Ambuhl et al.	N/A	N/A
2013/0097706	12/2012	Titonis et al.	N/A	N/A

2013/0103221	12/2012	Raman et al.	N/A	N/A
2013/0167035	12/2012	Imes et al.	N/A	N/A
2013/0170710	12/2012	Kuoch et al.	N/A	N/A
2013/0204836	12/2012	Choi et al.	N/A	N/A
2013/0246916	12/2012	Reimann et al.	N/A	N/A
2013/0247205	12/2012	Schrecker et al.	N/A	N/A
2013/0262035	12/2012	Mills	N/A	N/A
2013/0275174	12/2012	Bennett et al.	N/A	N/A
2013/0275908	12/2012	Reichard	N/A	N/A
2013/0297050	12/2012	Reichard et al.	N/A	N/A
2013/0298244	12/2012	Kumar et al.	N/A	N/A
2013/0331995	12/2012	Rosen	N/A	N/A
2013/0332387	12/2012	Mirra et al.	N/A	N/A
2013/0332862	12/2012	Mirra et al.	N/A	N/A
2013/0338970	12/2012	Reggetti	N/A	N/A
2014/0032506	12/2013	Hoey et al.	N/A	N/A
2014/0059483	12/2013	Mairs et al.	N/A	N/A
2014/0081652	12/2013	Klindworth	N/A	N/A
2014/0129660	12/2013	Vaynblat et al.	N/A	N/A
2014/0135952	12/2013	Maehara	N/A	N/A
2014/0152651	12/2013	Chen et al.	N/A	N/A
2014/0172184	12/2013	Schmidt et al.	N/A	N/A
2014/0189861	12/2013	Gupta et al.	N/A	N/A
2014/0207282	12/2013	Angle et al.	N/A	N/A
2014/0258052	12/2013	Khuti et al.	N/A	N/A
2014/0269614	12/2013	Maguire et al.	N/A	N/A
2014/0277765	12/2013	Karimi et al.	N/A	N/A
2014/0278461	12/2013	Artz	N/A	N/A
2014/0327555	12/2013	Sager et al.	N/A	N/A
2015/0019174	12/2014	Kiff et al.	N/A	N/A
2015/0042240	12/2014	Aggarwal et al.	N/A	N/A
2015/0105917	12/2014	Sasaki et al.	N/A	N/A
2015/0145468	12/2014	Ma et al.	N/A	N/A
2015/0156031	12/2014	Fadell et al.	N/A	N/A
2015/0168931	12/2014	Jin	N/A	N/A
2015/0168977	12/2014	Oswald et al.	N/A	N/A
2015/0172300	12/2014	Cochenour	N/A	N/A
2015/0178421	12/2014	Borrelli et al.	N/A	N/A
2015/0185261	12/2014	Frader-Thompson et al.	N/A	N/A
2015/0186777	12/2014	Lecue et al.	N/A	N/A
2015/0202962	12/2014	Habashima et al.	N/A	N/A
2015/0204563	12/2014	Imes et al.	N/A	N/A
2015/0235267	12/2014	Steube et al.	N/A	N/A
2015/0241895	12/2014	Lu et al.	N/A	N/A
2015/0244730	12/2014	Vu et al.	N/A	N/A
2015/0244732	12/2014	Golshan et al.	N/A	N/A
2015/0261863	12/2014	Dey et al.	N/A	N/A
2015/0263900	12/2014	Polyakov et al.	N/A	N/A
2015/0286969	12/2014	Warner et al.	N/A	N/A
2015/0295796	12/2014	Hsiao et al.	N/A	N/A
2015/0304193	12/2014	Ishii et al.	N/A	N/A
2015/0316918	12/2014	Schleiss et al.	N/A	N/A
2015/0324422	12/2014	Elder	N/A	N/A
2015/0341212	12/2014	Hsiao et al.	N/A	N/A

2015/0348417	12/2014	Ignaczak et al.	N/A	N/A
2015/0379080	12/2014	Jochimski	N/A	N/A
2016/0011753	12/2015	McFarland et al.	N/A	N/A
2016/0014070	12/2015	Adkins	N/A	N/A
2016/0019228	12/2015	Hong et al.	N/A	N/A
2016/0033946	12/2015	Zhu et al.	N/A	N/A
2016/0035246	12/2015	Curtis	N/A	N/A
2016/0065601	12/2015	Gong et al.	N/A	N/A
2016/0070736	12/2015	Swan et al.	N/A	N/A
2016/0078229	12/2015	Gong et al.	N/A	N/A
2016/0090839	12/2015	Stolarczyk	N/A	N/A
2016/0119434	12/2015	Dong et al.	N/A	N/A
2016/0127712	12/2015	Alfredsson et al.	N/A	N/A
2016/0139752	12/2015	Shim et al.	N/A	N/A
2016/0147243	12/2015	Micali et al.	N/A	N/A
2016/0163186	12/2015	Davidson et al.	N/A	N/A
2016/0170390	12/2015	Xie et al.	N/A	N/A
2016/0171862	12/2015	Das et al.	N/A	N/A
2016/0173816	12/2015	Huenerfauth et al.	N/A	N/A
2016/0179315	12/2015	Sarao et al.	N/A	N/A
2016/0179342	12/2015	Sarao et al.	N/A	N/A
2016/0179990	12/2015	Sarao et al.	N/A	N/A
2016/0180557	12/2015	Yousaf et al.	N/A	N/A
2016/0195856	12/2015	Spero	N/A	N/A
2016/0212165	12/2015	Singla et al.	N/A	N/A
2016/0234186	12/2015	Leblond et al.	N/A	N/A
2016/0239660	12/2015	Azvine et al.	N/A	N/A
2016/0239756	12/2015	Aggour et al.	N/A	N/A
2016/0247129	12/2015	Song et al.	N/A	N/A
2016/0255139	12/2015	Rathod	N/A	N/A
2016/0260063	12/2015	Harris et al.	N/A	N/A
2016/0292303	12/2015	Hong et al.	N/A	N/A
2016/0313751	12/2015	Risbeck et al.	N/A	N/A
2016/0313752	12/2015	Przybylski	N/A	N/A
2016/0313902	12/2015	Hill et al.	N/A	N/A
2016/0320758	12/2015	Park	N/A	N/A
2016/0335865	12/2015	Sayavong et al.	N/A	N/A
2016/0342906	12/2015	Shaashua et al.	N/A	N/A
2016/0350364	12/2015	Anicic et al.	N/A	N/A
2016/0357521	12/2015	Zhang et al.	N/A	N/A
2016/0357828	12/2015	Tobin et al.	N/A	N/A
2016/0358432	12/2015	Branscomb et al.	N/A	N/A
2016/0363336	12/2015	Roth et al.	N/A	N/A
2016/0370258	12/2015	Perez	N/A	N/A
2016/0378306	12/2015	Kresl et al.	N/A	N/A
2016/0379326	12/2015	Chan-Gove et al.	N/A	N/A
2017/0006135	12/2016	Siebel	N/A	N/A
2017/0011318	12/2016	Vigano et al.	N/A	N/A
2017/0017221	12/2016	Lamparter et al.	N/A	N/A
2017/0039255	12/2016	Raj et al.	N/A	N/A
2017/0052536	12/2016	Warner et al.	N/A	N/A
2017/0053441	12/2016	Nadumane et al.	N/A	N/A
2017/0063894	12/2016	Muddu et al.	N/A	N/A
2017/0068409	12/2016	Nair	N/A	N/A

2017/0070775	12/2016	Taxier et al.	N/A	N/A
2017/0075984	12/2016	Deshpande et al.	N/A	N/A
2017/0084168	12/2016	Janchookiat	N/A	N/A
2017/0090437	12/2016	Veeramani et al.	N/A	N/A
2017/0093700	12/2016	Gilley et al.	N/A	N/A
2017/0098086	12/2016	Hoernecke et al.	N/A	N/A
2017/0103327	12/2016	Penilla et al.	N/A	N/A
2017/0103403	12/2016	Chu et al.	N/A	N/A
2017/0123389	12/2016	Baez et al.	N/A	N/A
2017/0134415	12/2016	Muddu et al.	N/A	N/A
2017/0177715	12/2016	Chang et al.	N/A	N/A
2017/0180147	12/2016	Brandman et al.	N/A	N/A
2017/0188216	12/2016	Koskas et al.	N/A	N/A
2017/0212482	12/2016	Boettcher et al.	N/A	N/A
2017/0212668	12/2016	Shah et al.	N/A	N/A
2017/0214646	12/2016	Longo et al.	N/A	N/A
2017/0220641	12/2016	Chi et al.	N/A	N/A
2017/0230930	12/2016	Frey	N/A	N/A
2017/0235817	12/2016	Deodhar et al.	N/A	N/A
2017/0251182	12/2016	Siminoff et al.	N/A	N/A
2017/0270124	12/2016	Nagano et al.	N/A	N/A
2017/0272458	12/2016	Muddu et al.	N/A	N/A
2017/0277769	12/2016	Pasupathy et al.	N/A	N/A
2017/0278003	12/2016	Liu	N/A	N/A
2017/0286572	12/2016	Hershey et al.	N/A	N/A
2017/0294132	12/2016	Colmenares	N/A	N/A
2017/0300593	12/2016	Inoue	N/A	N/A
2017/0315522	12/2016	Kwon et al.	N/A	N/A
2017/0315697	12/2016	Jacobson et al.	N/A	N/A
2017/0322534	12/2016	Sinha et al.	N/A	N/A
2017/0323389	12/2016	Vavrasek	N/A	N/A
2017/0329289	12/2016	Kohn et al.	N/A	N/A
2017/0336770	12/2016	MacMillan	N/A	N/A
2017/0345287	12/2016	Fuller et al.	N/A	N/A
2017/0351957	12/2016	Lecue et al.	N/A	N/A
2017/0357225	12/2016	Asp et al.	N/A	N/A
2017/0357490	12/2016	Park et al.	N/A	N/A
2017/0357908	12/2016	Cabadi et al.	N/A	N/A
2017/0364618	12/2016	Gardner	N/A	N/A
2018/0012159	12/2017	Kozloski et al.	N/A	N/A
2018/0013579	12/2017	Fairweather et al.	N/A	N/A
2018/0024520	12/2017	Sinha et al.	N/A	N/A
2018/0039238	12/2017	Gartner et al.	N/A	N/A
2018/0048485	12/2017	Pelton et al.	N/A	N/A
2018/0069932	12/2017	Tiwari et al.	N/A	N/A
2018/0113897	12/2017	Donlan et al.	N/A	N/A
2018/0114140	12/2017	Chen et al.	N/A	N/A
2018/0137288	12/2017	Polyakov	N/A	N/A
2018/0150753	12/2017	Farrell et al.	N/A	N/A
2018/0157930	12/2017	Rutschman et al.	N/A	N/A
2018/0159756	12/2017	Matthews et al.	N/A	N/A
2018/0159876	12/2017	Park et al.	N/A	N/A
2018/0162400	12/2017	Abdar	N/A	N/A
2018/0176241	12/2017	Manadhata et al.	N/A	N/A

2018/0195749	12/2017	Sinha et al.	N/A	N/A
2018/0198627	12/2017	Mullins	N/A	N/A
2018/0203961	12/2017	Aisu et al.	N/A	N/A
2018/0232459	12/2017	Park et al.	N/A	N/A
2018/0238575	12/2017	Park et al.	N/A	N/A
2018/0239982	12/2017	Rutschman et al.	N/A	N/A
2018/0246988	12/2017	Johnson et al.	N/A	N/A
2018/0260442	12/2017	Vaidhyanathan et al.	N/A	N/A
2018/0275625	12/2017	Park et al.	N/A	N/A
2018/0276962	12/2017	Butler et al.	N/A	N/A
2018/0292797	12/2017	Lamparter et al.	N/A	N/A
2018/0313561	12/2017	Sinha et al.	N/A	N/A
2018/0331916	12/2017	DaMaggio et al.	N/A	N/A
2018/0336785	12/2017	Ghannam et al.	N/A	N/A
2018/0356775	12/2017	Harvey	N/A	N/A
2018/0359111	12/2017	Harvey	N/A	N/A
2018/0364654	12/2017	Locke et al.	N/A	N/A
2019/0005025	12/2018	Malabarba	N/A	N/A
2019/0013023	12/2018	Pourmohammad et al.	N/A	N/A
2019/0017719	12/2018	Sinha et al.	N/A	N/A
2019/0025771	12/2018	Park et al.	N/A	N/A
2019/0026359	12/2018	Park et al.	N/A	N/A
2019/0026710	12/2018	Chow et al.	N/A	N/A
2019/0037135	12/2018	Hedge	N/A	N/A
2019/0042988	12/2018	Brown et al.	N/A	N/A
2019/0050264	12/2018	Chintalapally et al.	N/A	N/A
2019/0074011	12/2018	Saxena	N/A	H04L 12/282
2019/0088106	12/2018	Grundstrom	N/A	N/A
2019/0094824	12/2018	Xie et al.	N/A	N/A
2019/0095259	12/2018	Nakamura	N/A	N/A
2019/0095644	12/2018	Park et al.	N/A	N/A
2019/0095820	12/2018	Pourmohammad	N/A	N/A
2019/0095821	12/2018	Pourmohammad	N/A	N/A
2019/0096014	12/2018	Pourmohammad et al.	N/A	N/A
2019/0096212	12/2018	Pourmohammad et al.	N/A	N/A
2019/0096213	12/2018	Pourmohammad et al.	N/A	N/A
2019/0096214	12/2018	Pourmohammad	N/A	N/A
2019/0096217	12/2018	Pourmohammad et al.	N/A	N/A
2019/0102840	12/2018	Perl et al.	N/A	N/A
2019/0109821	12/2018	Clark et al.	N/A	N/A
2019/0121801	12/2018	Jethwa et al.	N/A	N/A
2019/0138333	12/2018	Deutsch et al.	N/A	N/A
2019/0138512	12/2018	Pourmohammad et al.	N/A	N/A
2019/0138662	12/2018	Deutsch et al.	N/A	N/A
2019/0138970	12/2018	Deutsch et al.	N/A	N/A
2019/0147883	12/2018	Mellenthin et al.	N/A	N/A
2019/0155238	12/2018	Srivastava et al.	N/A	N/A
2019/0158309	12/2018	Park et al.	N/A	N/A
2019/0163152	12/2018	Worrall et al.	N/A	N/A
2019/0182119	12/2018	Ratkovic et al.	N/A	N/A
2019/0182273	12/2018	Walsh et al.	N/A	N/A
2019/0220546	12/2018	Cohen et al.	N/A	N/A
2019/0243813	12/2018	Pourmohammad et al.	N/A	N/A
2019/0253427	12/2018	Kling et al.	N/A	N/A

2019/0260831	12/2018	Milev et al.	N/A	N/A
2019/0268178	12/2018	Fairweather et al.	N/A	N/A
2019/0281010	12/2018	Teverovsky et al.	N/A	N/A
2019/0288866	12/2018	Smith et al.	N/A	N/A
2019/0289038	12/2018	Li et al.	N/A	N/A
2019/0294978	12/2018	Sachs	N/A	N/A
2019/0310979	12/2018	Masuzaki et al.	N/A	N/A
2019/0325329	12/2018	Rais-Ghasem et al.	N/A	N/A
2019/0354544	12/2018	Hertz et al.	N/A	N/A
2019/0354922	12/2018	Berti et al.	N/A	N/A
2019/0361411	12/2018	Park et al.	N/A	N/A
2019/0361412	12/2018	Park	N/A	G06N 3/006
2019/0370671	12/2018	Martinez Canedo et al.	N/A	N/A
2019/0377306	12/2018	Harvey	N/A	N/A
2020/0004216	12/2019	Park et al.	N/A	N/A
2020/0050605	12/2019	Tung et al.	N/A	N/A
2020/0064007	12/2019	Escapa et al.	N/A	N/A
2020/0090085	12/2019	Martinez Canedo et al.	N/A	N/A
2020/0097493	12/2019	Gawrys et al.	N/A	N/A
2020/0128036	12/2019	Sarzynski et al.	N/A	N/A
2020/0137119	12/2019	Jin et al.	N/A	N/A
2020/0142365	12/2019	Sharma et al.	N/A	N/A
2020/0184792	12/2019	Pourmohammad et al.	N/A	N/A
2020/0210481	12/2019	Niebielski et al.	N/A	N/A
2020/0226156	12/2019	Borra et al.	N/A	N/A
2020/0285203	12/2019	Thakur et al.	N/A	N/A
2020/0336328	12/2019	Harvey	N/A	N/A
2020/0348632	12/2019	Harvey	N/A	N/A
2020/0366697	12/2019	Vittal	N/A	N/A
2020/0387576	12/2019	Brett et al.	N/A	N/A
2020/0393157	12/2019	Turney et al.	N/A	N/A
2020/0396208	12/2019	Brett et al.	N/A	N/A
2020/0409931	12/2019	Zang et al.	N/A	N/A
2020/0412810	12/2019	Knight	N/A	H04L 43/04
2021/0034357	12/2020	Kesavan et al.	N/A	N/A
2021/0042299	12/2020	Migliori	N/A	N/A
2021/0043221	12/2020	Yelchuru et al.	N/A	N/A
2021/0055944	12/2020	Hinton et al.	N/A	N/A
2021/0133670	12/2020	Cella et al.	N/A	N/A
2021/0173969	12/2020	Abbey et al.	N/A	N/A
2021/0191826	12/2020	Duraisingh et al.	N/A	N/A
2021/0200764	12/2020	Ploegert et al.	N/A	N/A
2021/0325070	12/2020	Endel et al.	N/A	N/A
2021/0342961	12/2020	Winter et al.	N/A	N/A
2021/0381711	12/2020	Harvey et al.	N/A	N/A
2021/0381712	12/2020	Harvey et al.	N/A	N/A
2021/0382445	12/2020	Harvey et al.	N/A	N/A
2021/0383041	12/2020	Harvey et al.	N/A	N/A
2021/0383042	12/2020	Harvey et al.	N/A	N/A
2021/0383200	12/2020	Harvey et al.	N/A	N/A
2021/0383219	12/2020	Harvey et al.	N/A	N/A
2021/0383235	12/2020	Harvey et al.	N/A	N/A
2021/0383236	12/2020	Harvey et al.	N/A	N/A
2021/0405629	12/2020	Malakuti et al.	N/A	N/A

2022/0066402	12/2021	Harvey et al.	N/A	N/A
2022/0066405	12/2021	Harvey	N/A	N/A
2022/0066432	12/2021	Harvey et al.	N/A	N/A
2022/0066434	12/2021	Harvey et al.	N/A	N/A
2022/0066528	12/2021	Harvey et al.	N/A	N/A
2022/0066722	12/2021	Harvey et al.	N/A	N/A
2022/0066754	12/2021	Harvey et al.	N/A	N/A
2022/0066761	12/2021	Harvey et al.	N/A	N/A
2022/0067226	12/2021	Harvey et al.	N/A	N/A
2022/0067227	12/2021	Harvey et al.	N/A	N/A
2022/0067230	12/2021	Harvey et al.	N/A	N/A
2022/0069863	12/2021	Harvey et al.	N/A	N/A
2022/0070293	12/2021	Harvey et al.	N/A	N/A
2022/0121965	12/2021	Chatterji et al.	N/A	N/A
2022/0138684	12/2021	Harvey	N/A	N/A
2022/0147000	12/2021	Cooley et al.	N/A	N/A
2022/0150124	12/2021	Cooley et al.	N/A	N/A
2022/0165143	12/2021	Pourmohammad	N/A	N/A
2022/0215264	12/2021	Harvey et al.	N/A	N/A
2022/0223023	12/2021	Pourmohammad et al.	N/A	N/A
2022/0284362	12/2021	Bellinger et al.	N/A	N/A
2022/0335184	12/2021	Wesley et al.	N/A	N/A
2022/0391373	12/2021	Pourmohammad et al.	N/A	N/A
2022/0413460	12/2021	Park et al.	N/A	N/A
2023/0010757	12/2022	Preciado	N/A	N/A
2023/0071312	12/2022	Preciado et al.	N/A	N/A
2023/0076011	12/2022	Preciado et al.	N/A	N/A
2023/0083703	12/2022	Meiners	N/A	N/A
2023/0110131	12/2022	Smith et al.	N/A	N/A
2023/0169220	12/2022	Ramanasankaran et al.	N/A	N/A
2023/0214555	12/2022	Harvey et al.	N/A	N/A
2023/0252205	12/2022	Harvey et al.	N/A	N/A
2023/0334200	12/2022	Meiners	N/A	N/A
2023/0419807	12/2022	Pourmohammad	N/A	N/A
2024/0338002	12/2023	Park et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019226217	12/2019	AU	N/A
2019226264	12/2019	AU	N/A
101415011	12/2008	CN	N/A
102136099	12/2010	CN	N/A
102136100	12/2010	CN	N/A
102650876	12/2011	CN	N/A
104040583	12/2013	CN	N/A
104603832	12/2014	CN	N/A
104919484	12/2014	CN	N/A
106204392	12/2015	CN	N/A
106406806	12/2016	CN	N/A
106960269	12/2016	CN	N/A
107077476	12/2016	CN	N/A
107147639	12/2016	CN	N/A
107598928	12/2017	CN	N/A
110622139	12/2018	CN	N/A

2 528 033	12/2011	EP	N/A
3 268 821	12/2017	EP	N/A
3 324 306	12/2017	EP	N/A
4 226 263	12/2022	EP	N/A
H10-049552	12/1997	JP	N/A
2003-162573	12/2002	JP	N/A
2007-018322	12/2006	JP	N/A
4073946	12/2007	JP	N/A
2008-107930	12/2007	JP	N/A
2013-152618	12/2012	JP	N/A
2014-044457	12/2013	JP	N/A
6959164	12/2020	JP	N/A
2016/0102923	12/2015	KR	N/A
WO-2009/020158	12/2008	WO	N/A
WO-2011/100255	12/2010	WO	N/A
WO-2013/050333	12/2012	WO	N/A
WO-2015/106702	12/2014	WO	N/A
WO-2015/145648	12/2014	WO	N/A
WO-2017/035536	12/2016	WO	N/A
WO-2017/192422	12/2016	WO	N/A
WO-2017/194244	12/2016	WO	N/A
WO-2017/205330	12/2016	WO	N/A
WO-2017/213918	12/2016	WO	N/A
WO-2018/132112	12/2017	WO	N/A
WO-2020/061621	12/2019	WO	N/A
WO 2021/067731	12/2020	WO	N/A
WO-2022/042925	12/2021	WO	N/A
WO-2022/103812	12/2021	WO	N/A
WO-2022/103813	12/2021	WO	N/A
WO-2022/103820	12/2021	WO	N/A
WO-2022/103822	12/2021	WO	N/A
WO-2022/103824	12/2021	WO	N/A
WO-2022/103829	12/2021	WO	N/A
WO-2022/103831	12/2021	WO	N/A

OTHER PUBLICATIONS

Adiono et al., “Design of Database and Secure Communication Protocols for Internet-of-Things-Based Smart Home System,” 2017 IEEE Region 10 Conference (TENCON), Malaysia, Nov. 5-8, 2017, pp. 1273-1278. cited by applicant

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, 2018 (20 pages). cited by applicant

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, Sep. 15, 2018, 3 pages, (Abstract). cited by applicant

Balaji et al, “Demo Abstract: Portable Queries Using the Brick Schema for Building Applications,” BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (2 pages). cited by applicant

Balaji, B. et al., “Brick: Towards a Unified Metadata Schema For Buildings.” BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (10 pages). cited by applicant

Bhattacharya et al., “Short Paper: Analyzing Metadata Schemas for Buildings—The Good, The Bad and The Ugly,” BuildSys '15, Seoul, South Korea, Nov. 4-5, 2015 (4 pages). cited by applicant

Bhattacharya, A., “Enabling Scalable Smart-Building Analytics,” Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2016-201, Dec. 15, 2016 (121 pages). cited by applicant

Brick, “Brick Schema: Building Blocks for Smart Buildings,” URL: chrome-extension://efaidnbmninnibpcapjpcglclefindmkaj/https://www.memoori.com/wp-

content/uploads/2016/06/Brick_Schema_Whitepaper.pdf, Mar. 2019 (17 pages). cited by applicant

Brick, “Brick: Towards a Unified Metadata Schema For Buildings,” URL: chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://brickschema.org/papers/Brick_BuildSys_Presentation.pdf, Presented at BuildSys '16, Nov. 2016 (46 pages). cited by applicant

Brick, “Metadata Schema for Buildings,” URL: https://brickschema.org/docs/Brick-Leaflet.pdf, retrieved from internet Dec. 24, 2019 (3 pages). cited by applicant

Chinese Office Action on CN Appl. Ser. No. 201780003995.9 dated Apr. 8, 2021 (21 pages with English language translation). cited by applicant

Chinese Office action on CN Appl. Ser. No. 201780043400.2 dated Apr. 25, 2021 (15 pages with English language translation). cited by applicant

Curry, E. et al., “Linking building data in the cloud: Integrating cross-domain building data using linked data.” Advanced Engineering Informatics, 2013, 27 (pp. 206-219). cited by applicant

Digital Platform Litigation Documents Part 1, includes cover letter, dismissal of case DDE-1-21-cv-01796, IPR2023-00022 (documents filed Jan. 26, 2023-Oct. 7, 2022), and IPR2023-00085 (documents filed Jan. 26, 2023-Oct. 20, 2022) (748 pages total). cited by applicant

Digital Platform Litigation Documents Part 10, includes DDE-1-21-cv-01796 (documents filed Nov. 1, 2022-Dec. 22, 2021 (1795 pages total). cited by applicant

Digital Platform Litigation Documents Part 2, includes IPR2023-00085 (documents filed Oct. 20, 2022) (172 pages total). cited by applicant

Digital Platform Litigation Documents Part 3, includes IPR2023-00085 (documents filed Oct. 20, 2022) and IPR2023-00170 (documents filed Nov. 28, 2022-Nov. 7, 2022) (397 pages total). cited by applicant

Digital Platform Litigation Documents Part 4, includes IPR2023-00170 (documents filed Nov. 7, 2022) and IPR2023-00217 (documents filed Jan. 18, 2023-Nov. 15, 2022) (434 pages total). cited by applicant

Digital Platform Litigation Documents Part 5, includes IPR2023-00217 (documents filed Nov. 15, 2022) and IPR2023-00257 (documents filed Jan. 25, 2023-Nov. 23, 2022) (316 pages total). cited by applicant

Digital Platform Litigation Documents Part 6, includes IPR2023-00257 (documents filed Nov. 23, 2022) and IPR2023-00346 (documents filed Jan. 3, 2023-Dec. 13, 2022) (295 pages total). cited by applicant

Digital Platform Litigation Documents Part 7, includes IPR 2023-00346 (documents filed Dec. 13, 2022) and IPR2023-00347 (documents filed Jan. 3, 2023-Dec. 13, 2022) (217 pages total). cited by applicant

Digital Platform Litigation Documents Part 8, includes IPR2023-00347 (documents filed Dec. 13, 2022), EDTX-2-22-cv-00243 (documents filed Sep. 20, 2022-Jun. 29, 2022), and DDE-1-21-cv-01796 (documents filed Feb. 3, 2023-Jan. 10, 2023 (480 pages total). cited by applicant

Digital Platform Litigation Documents Part 9, includes DDE-1-21-cv-01796 (documents filed Jan. 10, 2023-Nov. 1, 2022 (203 pages total). cited by applicant

El Kaed, C. et al., “Building management insights driven by a multi-system semantic representation approach,” 2016 IEEE 3rd World Forum on Internet of Things (WF-IoT), Dec. 12-14, 2016, (pp. 520-525). cited by applicant

Ellis, C. et al., “Creating a room connectivity graph of a building from per-room sensor units.” BuildSys '12, Toronto, ON, Canada, Nov. 6, 2012 (7 pages). cited by applicant

European Office Action EP Appl. No. 20845822.4 dated May 25, 2023 (9 pages). cited by applicant

European Office Action on EP Appl. No. 19707156.6 dated Jul. 5, 2022 (9 pages). cited by applicant

Extended European Search Report on EP Application No. 18196948.6 dated Apr. 10, 2019 (9 pages). cited by applicant

Fierro et al., “Beyond a House of Sticks: Formalizing Metadata Tags with Brick,” BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (10 pages). cited by applicant

Fierro et al., “Dataset: An Open Dataset and Collection Tool for BMS Point Labels,” DATA'19, New York, NY, USA, Nov. 10, 2019 (3 pages). cited by applicant

Fierro et al., “Design and Analysis of a Query Processor for Brick,” ACM Transactions on Sensor Networks, Jan. 2018, vol. 1, No. 1, art. 1 (25 pages). cited by applicant

Fierro et al., “Design and Analysis of a Query Processor for Brick,” BuildSys '17, Delft, Netherlands, Nov. 8-9, 2017 (10 pages). cited by applicant

Fierro et al., “Mortar: An Open Testbed for Portable Building Analytics,” BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Fierro et al., “Why Brick is a Game Changer for Smart Buildings,” URL:

https://brickschema.org/papers/Brick_Memoori_Webinar_Presentation.pdf, Memoori Webinar, 2019 (67 pages). cited by applicant

Fierro, “Writing Portable Building Analytics with the Brick Metadata Schema,” UC Berkeley, ACM E-Energy, 2019 (39 pages). cited by applicant

Fierro, G., “Design of an Effective Ontology and Query Processor Enabling Portable Building Applications,” Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2019-106, Jun. 27, 2019 (118 pages). cited by applicant

File History for U.S. Appl. No. 12/776,159, filed May 7, 2010 (722 pages). cited by applicant

Final Conference Program, ACM BuildSys 2016, Stanford, CA, USA, Nov. 15-17, 2016 (7 pages). cited by applicant

Gao et al., “A large-scale evaluation of automated metadata inference approaches on sensors from air handling units,” Advanced Engineering Informatics, 2018, 37 (pp. 14-30). cited by applicant

Harvey, T., “Quantum Part 3: The Tools of Autonomy, How PassiveLogic's Quantum Creator and Autonomy Studio software works,” URL: <https://www.automatedbuildings.com/news/jan22/articles/passive/211224010000passive.html>, Jan. 2022 (7 pages). cited by applicant

Harvey, T., “Quantum: The Digital Twin Standard for Buildings,” URL: <https://www.automatedbuildings.com/news/feb21/articles/passivelogic/210127124501passivelogic.html>, Feb. 2021 (6 pages). cited by applicant

Hu, S. et al., “Building performance optimisation: A hybrid architecture for the integration of contextual information and time-series data,” Automation in Construction, 2016, 70 (pp. 51-61). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/013831 dated Mar. 31, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/035524 dated Jul. 24, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion on PCT Appl. No. PCT/US2022/034101 dated Oct. 10, 2022 (21 pages). cited by applicant

International Search Report and Written Opinion on PCT/US2017/052060, mailed Oct. 5, 2017, 11 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052633, mailed Oct. 23, 2017, 9 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052829, mailed Nov. 27, 2017, 24 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/024068, mailed Jun. 15, 2018, 22 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052971, dated Mar. 1, 2019, 19 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052974, mailed Dec. 19, 2018, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052975, mailed Jan. 2, 2019, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052994, mailed Jan. 7, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2019/015481, dated May 17, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2020/058381, dated Jan. 27, 2021, 30 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2020/067130, dated Apr. 30, 2021, 33 pages. cited by applicant

Japanese Office Action on JP Appl. Ser. No. 2018-534963 dated May 11, 2021 (16 pages with English language translation). cited by applicant

Koh et al., “Plaster: An Integration, Benchmark, and Development Framework for Metadata Normalization Methods,” BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., “Scrabble: Transferrable Semi-Automated Semantic Metadata Normalization using Intermediate

Representation,” BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., “Who can Access What, and When?” BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (4 pages). cited by applicant

Li et al., “Event Stream Processing with Out-of-Order Data Arrival,” International Conferences on Distributed Computing Systems, 2007, (8 pages). cited by applicant

Maryasin, O., “Home Automation System Ontology for Digital Building Twin,” 2019 XXI International Conference Complex Systems: Control and Modeling Problems (CSCMP), IEEE, Sep. 2019 (pp. 70-74). cited by applicant

Microsoft, “Azure Digital Twins: Next-generation IoT solutions that model the real world,” URL: <https://azure.microsoft.com/en-us/services/digital-twins/>, Retrieved Jan. 8, 2021, 12 pages. cited by applicant

Nissin Electric Co., Ltd., “Smart power supply system (SPSS),” Outline of the scale verification plan, Nissin Electric Technical Report, Japan, Apr. 23, 2014, vol. 59, No. 1 (23 pages with English language abstract). cited by applicant

Passivelogic, “Explorer: Digital Twin Standard for Autonomous Systems. Made interactive.” URL: <https://passivelogic.com/software/quantum-explorer/>, retrieved from internet Jan. 4, 2023 (13 pages). cited by applicant

Passivelogic, “Quantum: The Digital Twin Standard for Autonomous Systems, A physics-based ontology for next-generation control and AI.” URL: <https://passivelogic.com/software/quantum-standard/>, retrieved from internet Jan. 4, 2023 (20 pages). cited by applicant

Quantum Alliance, “Quantum Explorer Walkthrough,” 2022, (7 pages) (screenshots from video). cited by applicant

Results of the Partial International Search for PCT/US2018/052971, dated Jan. 3, 2019, 3 pages. cited by applicant

Sinha, Sudhi and Al Huraimel, Khaled, “Reimagining Businesses with AI” John Wiley & Sons, Inc., Hoboken, NJ, USA, First ed. published 2020 (156 pages). cited by applicant

Sinha, Sudhi R. and Park, Youngchoon, “Building an Effective IoT Ecosystem for Your Business,” Johnson Controls International, Springer International Publishing, 2017 (286 pages). cited by applicant

Sinha, Sudhi, “Making Big Data Work For Your Business: A guide to effective Big Data analytics,” Impact Publishing LTD., Birmingham, UK, Oct. 2014 (170 pages). cited by applicant

The Virtual Nuclear Tourist, “Calvert Cliffs Nuclear Power Plant,” URL: <http://www.nucleartourist.com/us/calvert.htm>, Jan. 11, 2006 (2 pages). cited by applicant

University of California at Berkeley, EECS Department, “Enabling Scalable Smart-Building Analytics,” URL: <https://www2.eecs.berkeley.edu/Pubs/TechRpts/2016/EECS-2016-201.html>, retrieved from internet Feb. 15, 2023 (7 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,661 dated Oct. 25, 2022 (54 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,661 dated Sep. 29, 2023 (50 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,671 dated Jan. 20, 2023 (62 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,671 dated Mar. 17, 2022 (48 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,691 dated Feb. 23, 2023 (60 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,691 dated Oct. 19, 2023 (67 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,973 dated May 26, 2022 (48 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/134,999 dated Apr. 28, 2023 (36 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/135,023 dated Aug. 10, 2022 (15 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/135,056 dated Nov. 17, 2022 (15 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 17/833,407 dated Jun. 23, 2023 (28 pages). cited by applicant

US Final Office Action on U.S. Appl. No. 18/098,554 dated Aug. 17, 2023 (9 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,691 dated Jun. 6, 2023 (62 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/135,056 dated Jun. 14, 2022 (15 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,659 dated Mar. 8, 2021 (11 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,661 dated Dec. 30, 2021 (35 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,661 dated Jul. 27, 2022 (62 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,661 dated May 31, 2023 (52 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,664 dated Mar. 12, 2021 (21 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,664 dated Nov. 29, 2021 (22 pages). cited by applicant

US Non-Final Office Action on U.S. Appl. No. 17/134,671 dated Apr. 13, 2023 (33 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/134,671 dated Aug. 16, 2022 (51 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/134,671 dated Oct. 27, 2021 (47 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/134,691 dated Aug. 16, 2022 (56 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/134,973 dated Jan. 6, 2022, (47 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/134,973 dated Mar. 12, 2021 (28 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/134,999 dated Jan. 11, 2023 (35 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/134,999 dated Sep. 18, 2023 (29 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/135,023 dated Dec. 7, 2022 (16 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/135,023 dated Mar. 25, 2022 (27 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 17/833,407 dated May 2, 2023 (27 pages). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 18/098,554 dated Jun. 22, 2023 (13 pages). cited by applicant
US Notice of Allowance for U.S. Appl. No. 17/135,009 dated May 25, 2022 (9 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/134,659 dated Jun. 16, 2021 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/134,664 dated Mar. 24, 2022 (12 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/134,671 dated Aug. 17, 2023 (25 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/135,009 dated May 3, 2023 (5 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/135,009 dated Sep. 16, 2022 (5 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/135,023 dated May 9, 2023 (16 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/135,056 dated Jun. 27, 2023 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/135,056 dated Mar. 1, 2023 (8 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/504,121 dated Feb. 4, 2022 (12 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/678,260 dated Jun. 5, 2023 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/678,260 dated Mar. 14, 2023 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/678,260 dated May 24, 2022 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/678,260 dated Sep. 2, 2022 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/828,887 dated Jun. 6, 2023 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/828,887 dated Mar. 14, 2023 (7 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/833,407 dated Aug. 16, 2023 (11 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/853,352 dated Sep. 22, 2023 (13 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 18/098,554 dated Nov. 17, 2023 (5 pages). cited by applicant
US Office Action on U.S. Appl. No. 17/134,664 dated Jun. 25, 2021 (24 pages). cited by applicant
US Office Action on U.S. Appl. No. 17/134,973 dated Jul. 26, 2021 (44 pages). cited by applicant
Valtolina et al., "Ontology-Based Consistent Specification of Sensor Data Acquisition Plans in Cross-Domain IoT Platforms," IEEE Access, Dec. 2019, vol. 7 (pp. 176141-176169). cited by applicant
Van Hoof, Bert, "Announcing Azure Digital Twins: Create digital replicas of spaces and infrastructure using cloud, AI and IoT," URL: <https://azure.microsoft.com/en-us/blog/announcing-azure-digital-twins-create-digital-replicas-of-spaces-and-infrastructure-using-cloud-ai-and-iot/>, Sep. 24, 2018 (11 pages). cited by applicant
W3C, "SPARQL: Query Language for RDF," located on The Wayback Machine, URL: <https://web.archive.org/web/20161230061728/http://www.w3.org/TR/rdf-sparql-query/>), retrieved from internet Nov. 15, 2022 (89 pages). cited by applicant
Wang et al., "Linking energy-cyber-physical systems with occupancy prediction and interpretation through WiFi probe-based ensemble classification," Applied Energy, 2019, vol. 236 (pp. 55-69). cited by applicant
Wei et al., "Development and Implementation of Software Gateways of Fire Fighting Subsystem Running on EBI," Control, Automation and Systems Engineering, IITA International Conference on, IEEE, Jul. 2009 (pp. 9-12). cited by applicant
White et al., "Reduce building maintenance costs with AWS IoT TwinMaker Knowledge Graph," The Internet of Things on AWS—Official Blog, URL: <https://aws.amazon.com/blogs/iot/reduce-building-maintenance-costs-with-aws-iot-twinmaker-knowledge-graph/>, Nov. 18, 2022 (10 pages). cited by applicant
Yao et al., "State of the art review on model predictive control (MPC) in Heating Ventilation and Air-conditioning (HVAC) field," Building and Environment, 2021, vol. 200 (18 pages). cited by applicant
Zhou, Q. et al., "Knowledge-infused and Consistent Complex Event Processing over Real-time and Persistent Streams," Further Generation Computer Systems, 2017, 76 (pp. 391-406). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/134,691 dated Jan. 16, 2024 (6 pages). cited by applicant

US Notice of Allowance on U.S. Appl. No. 18/375,823 dated May 7, 2024 (8 pages). cited by applicant
Australian Office Action on AU Appl. No. 2019304871 dated Feb. 19, 2024 (4 pages). cited by applicant
Chinese Office Action on CN Appl. No. 202080097068.X dated Feb. 21, 2024 (23 pages with English language translation). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/134,661 dated Mar. 8, 2024 (8 pages). cited by applicant
US Final Office Action on U.S. Appl. No. 17/134,999 dated Jan. 29, 2024 (31 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/853,359 dated Feb. 21, 2024 (12 pages). cited by applicant
Chinese Office Action on CN Appl. No. 202080097068.X dated Jul. 17, 2024 (20 pages with English language translation). cited by applicant
US Non-Final Office Action on U.S. Appl. No. 18/543,290 dated Jul. 31, 2024 (13 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 18/375,850 dated Jul. 31, 2024 (9 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 17/134,999 dated Sep. 5, 2024 (18 pages). cited by applicant
Australian Examination Report No. 1 on AU Appl. No. 2024219353 dated Sep. 20, 2024 (3 pages). cited by applicant
US Notice of Allowance on U.S. Appl. No. 18/543,290 dated Dec. 5, 2024 (10 pages). cited by applicant
Extended European Search Report on EP Appl. No. 24194840.5 dated Feb. 10, 2025 (9 pages). cited by applicant
Office Action on Canadian Appl. No. 3106434 dated Mar. 19, 2025 (5 pages). cited by applicant

Primary Examiner: Vu; Tuan A

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/833,407 filed Jun. 6, 2022, which is a continuation of U.S. patent application Ser. No. 17/134,664 filed Dec. 28, 2020, which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/955,856 filed Dec. 31, 2019, U.S. Provisional Patent Application No. 63/005,841 filed Apr. 6, 2020, and U.S. Provisional Patent Application No. 63/105,754 filed Oct. 26, 2020. The entirety of each of these applications are incorporated by reference herein.

BACKGROUND

(1) The present disclosure relates generally to the management of building systems of a building. The present disclosure relates more particularly to the control of building systems through a cloud based system. A building can include various types of building subsystems, e.g., heating, ventilation, and air conditioning (HVAC) systems, security systems, fire response systems, etc. Discrete predefined controlling systems may operate each subsystem individually without knowledge of the building. However, discrete predefined controlling systems may not allow for dynamic, scalable, and adjustable solutions that can provide holistic management of a building.

SUMMARY

(2) Event Enrichment with Contextual Information

(3) One implementation of the present disclosure is a building system including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive an event from an event source, the event indicating a data value associated with the piece of building equipment occurring at a particular time. The instructions cause the one or more processors to identify contextual data of a database that provides a contextual description of the event, generate an enriched event by enriching the event with the contextual data, the enriched event including the data value, the particular time, and the contextual data, and provide the enriched event to a consuming application configured to operate based on the enriched event.

(4) In some embodiments, the instructions cause the one or more processors to retrieve one or more schemas from a schema database, the one or more schemas indicating available schema formats for events, determine whether a schema that the event is formatted in matches the one or more schemas, generate the enriched event in response to determining that the schema that the event is formatted in matches the one or

more schemas, and perform at least one of adding the event into a dead letter storage in response to a determination that the schema that the event is formatted in does not match the one or more schemas or adding the schema that the event is formatted in into the schema database in response to determining that the schema that the event is formatted in does not match the one or more schemas and in response to determining that the building system is operating in a discovery mode to discover new schemas.

(5) In some embodiments, the instructions cause the one or more processors cause the enriched event to be added to a topic subscribed to by the consuming application.

(6) In some embodiments, the instructions cause the one or more processors to persist the enriched event in an event database.

(7) In some embodiments, the instructions cause the one or more processors to identify the contextual data based on one or more enrichment rules associated with the consuming application. In some embodiments, the instructions cause the one or more processors to identify second contextual data of the database based on one or more second enrichment rules associated with a second consuming application, generate a second enriched event by enriching the event with the second contextual data, the data value, and the particular time, and provide the second enriched event to the second consuming application.

(8) In some embodiments, the event is received from a piece of building equipment of a building. In some embodiments, the instructions cause the one or more processors to identify the contextual data by searching a graph projection that includes the contextual description of the piece of building equipment.

(9) In some embodiments, the graph projection includes nodes and edges. In some embodiments, the nodes represent entities of the building and the edges represent relationships between the entities of the building. In some embodiments, the nodes include a node representing the piece of building equipment. In some embodiments, the instructions cause the one or more processors to identify the contextual data by identifying one or more nodes of the nodes related to the node representing the piece of building equipment based on one or more edges of the edges between the node representing the piece of building equipment and the one or more nodes.

(10) In some embodiments, the contextual data includes one or more capabilities of the piece of building equipment.

(11) In some embodiments, the contextual description includes at least one of a location where the piece of building equipment is located, another piece of building equipment related to the piece of building equipment, a point of the piece of building equipment, and a person associated with the piece of building equipment.

(12) In some embodiments, the location is at least one of the building that the piece of building equipment is located in or a space that the piece of building equipment is located in.

(13) Another implementation of the present disclosure is a method including receiving, by a processing circuit, an event from a piece of building equipment of a building, the event indicating a data value associated with the piece of building equipment occurring at a particular time. The method further includes identifying, by the processing circuit, contextual data of a database that provides a contextual description of the event, generating, by the processing circuit, an enriched event by enriching the event with the contextual data, the enriched event including the data value, the particular time, and the contextual data, and providing, by the processing circuit, the enriched event to a consuming application configured to operate based on the enriched event.

(14) In some embodiments, the method includes retrieving, by the processing circuit, one or more schemas from a schema database, the one or more schemas indicating available schema formats for events, determining, by the processing circuit, whether a schema that the event is formatted in matches the one or more schemas, and generating, by the processing circuit, the enriched event in response to determining that the schema that the event is formatted in matches the one or more schemas. In some embodiments, the method includes performing, by the processing circuit, at least one of adding the event into a dead letter storage in response to a determination that the schema that the event is formatted in does not match the one or more schemas or adding the schema that the event is formatted in into the schema database in response to determining that the schema that the event is formatted in does not match the one or more schemas and in response to determining that the building system is operating in a discovery mode to discover new schemas.

(15) In some embodiments, the method includes causing, by the processing circuit, the enriched event to be added to a topic subscribed to by the consuming application.

- (16) In some embodiments, the method includes persisting, by the processing circuit, the enriched event in an event database.
- (17) In some embodiments, the method includes identifying, by the processing circuit, the contextual data is based on one or more enrichment rules associated with the consuming application. In some embodiments, the method further includes identifying, by the processing circuit, second contextual data of the database based on one or more second enrichment rules associated with a second consuming application, generating, by the processing circuit, a second enriched event by enriching the event with the second contextual data, the data value, and the particular time, and providing, by the processing circuit, the second enriched event to the second consuming application.
- (18) In some embodiments, the method further includes identifying, by the processing circuit, the contextual data by searching a graph projection that includes the contextual description of the piece of building equipment.
- (19) In some embodiments, the graph projection includes nodes and edges. In some embodiments, the nodes represent entities of the building and the edges represent relationships between the entities of the building. In some embodiments, the nodes include a node representing the piece of building equipment. In some embodiments, the method includes identifying, by the processing circuit, the contextual data includes identifying one or more nodes of the nodes related to the node representing the piece of building equipment based on one or more edges of the edges between the node representing the piece of building equipment and the one or more nodes.
- (20) In some embodiments, the contextual data includes one or more capabilities of the piece of building equipment.
- (21) In some embodiments, the contextual description includes at least one of a location where the piece of building equipment is located, another piece of building equipment related to the piece of building equipment, a point of the piece of building equipment, and a person associated with the piece of building equipment.
- (22) Another implementation of the present disclosure is a building system including one or more memory devices having instructions thereon and one or more processors configured to execute the instructions causing the one or more processors to receive an event from a piece of building equipment of a building, the event indicating a data value associated with the piece of building equipment occurring at a particular time, identify contextual data of a database that provides a contextual description of the event, generate an enriched event by enriching the event with the contextual data, the enriched event including the data value, the particular time, and the contextual data, and provide the enriched event to a consuming application configured to operate based on the enriched event.
- (23) Building Graph Change Feed
- (24) One implementation of the present disclosure is a building system of a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive a modification to a graph, the graph including nodes and edges between the nodes, the nodes representing entities of the building and the edges representing relationships between the entities of the building. The instructions cause the one or more processors to generate a change feed event, the change feed event recording the modification to the graph and add the change feed event to a change feed including change feed events representing modifications to the graph at different times.
- (25) In some embodiments, the entities of the building are at least one of building equipment, locations of the building, users of the building, and events of the building.
- (26) In some embodiments, the instructions cause the one or more processors to construct the graph at points in time including a first time and a second time by selecting a first set of the change feed events occurring up to the first time, generating the graph at the first time based on the first set of the change feed events, selecting a second set of the change feed events occurring up to the second time, and generating the graph at the second time based on the second set of the change feed events.
- (27) In some embodiments, the modification is at least one of adding a new node to the nodes of the graph, adding a new edge to the edges of the graph, deleting an existing node of the nodes of the graph, deleting an existing edge of the edges of the graph, modifying the existing node of the nodes of the graph, or modifying the existing edge of the edges of the graph.
- (28) In some embodiments, the instructions cause the one or more processors to communicate the change feed event of the change feed to one or more consuming applications.

(29) In some embodiments, the instructions cause the one or more processors to add the change feed event to a change feed topic, wherein the one or more consuming applications are subscribed to the change feed topic and receive the change feed event in response to the change feed event being added to the change feed topic.

(30) In some embodiments, the one or more consuming applications update the graph stored by the one or more consuming applications based on the change feed event.

(31) Another implementation of the present disclosure is a method including receiving, by a processing circuit, a modification to a graph, the graph including nodes and edges between the nodes, the nodes representing entities of a building and the edges representing relationships between the entities of the building. The method includes generating, by the processing circuit, a change feed event, the change feed event recording the modification to the graph and adding, by the processing circuit, the change feed event to a change feed including change feed events representing modifications to the graph at different times.

(32) In some embodiments, the entities of the building are at least one of building equipment, locations of the building, users of the building, and events of the building.

(33) In some embodiments, the method includes constructing, by the processing circuit, the graph at points in time including a first time and a second time by selecting a first set of the change feed events occurring up to the first time, generating the graph at the first time based on the first set of the change feed events, selecting a second set of the change feed events occurring up to the second time, and generating the graph at the second time based on the second set of the change feed events.

(34) In some embodiments, the modification is at least one of adding a new node to the nodes of the graph, adding a new edge to the edges of the graph, deleting an existing node of the nodes of the graph, deleting an existing edge of the edges of the graph, modifying the existing node of the nodes of the graph, or modifying the existing edge of the edges of the graph.

(35) In some embodiments, the method further includes communicating, by the processing circuit, the change feed event of the change feed to one or more consuming applications.

(36) In some embodiments, the method further includes adding, by the processing circuit, the change feed event to a change feed topic, wherein the one or more consuming applications are subscribed to the change feed topic and receive the change feed event in response to the change feed event being added to the change feed topic.

(37) In some embodiments, the one or more consuming applications update the graph stored by the one or more consuming applications based on the change feed event.

(38) Another implementation of the present disclosure is one or more memory devices having instructions thereon and one or more processors configured to execute the instructions causing the one or more processors to receive a modification to a graph, the graph including nodes and edges between the nodes, the nodes representing entities of the building and the edges representing relationships between the entities of the building. The instructions cause the one or more processors to generate a change feed event, the change feed event recording the modification to the graph and add the change feed event to a change feed including change feed events representing modifications to the graph at different times.

(39) In some embodiments, the entities of the building are at least one of building equipment, locations of the building, users of the building, and events of the building.

(40) In some embodiments, the instructions cause the one or more processors to construct the graph at points in time including a first time and a second time by selecting a first set of the change feed events occurring up to the first time, generating the graph at the first time based on the first set of the change feed events, selecting a second set of the change feed events occurring up to the second time, and generating the graph at the second time based on the second set of the change feed events.

(41) In some embodiments, the modification is at least one of adding a new node to the nodes of the graph, adding a new edge to the edges of the graph, deleting an existing node of the nodes of the graph, deleting an existing edge of the edges of the graph, modifying the existing node of the nodes of the graph, or modifying the existing edge of the edges of the graph.

(42) In some embodiments, the instructions cause the one or more processors to communicate the change feed event of the change feed to one or more consuming applications.

(43) In some embodiments, the instructions cause the one or more processors to add the change feed event to a change feed topic, wherein the one or more consuming applications are subscribed to the change feed topic and receive the change feed event in response to the change feed event being added to the change

feed topic.

(44) Building Graph Based Capabilities

(45) One implementation of the present disclosure is a building system of a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to identify a capability of an entity in a building graph, the building graph including nodes and edges, the nodes representing entities of the building including the entity and the capability, the edges representing relationships between the entities of the building and the capability, wherein a first node of the nodes represents the entity and a second node of the nodes related to the first node by one or more edges of the edges represents the capability. The instructions cause the one or more processors to receive a command to perform an operation associated with the entity, the operation associated with the capability of the entity and provide the command to perform the operation associated with the entity to an operating system.

(46) In some embodiments, the instructions cause the one or more processors to identify the capability of the entity by identifying the first node of the nodes of the building graph representing the entity and identifying at least one of one or more nodes or the one or more edges between the first node and the second node representing the capability of the entity.

(47) In some embodiments, the entity is a piece of building equipment of the building. In some embodiments, the capability is a control operation that the piece of building equipment is configured to perform.

(48) In some embodiments, the entity is a user of the building. In some embodiments, the capability is an action associated with the user that a system is configured to perform.

(49) In some embodiments, the instructions cause the one or more processors to receive the command to perform the operation associated with the entity from a requesting system. In some embodiments, the instructions cause the one or more processors to identify whether the requesting system has a policy to make the command to perform the operation based on the building graph, wherein the building graph indicates the policy to make the command. In some embodiments, the instructions cause the one or more processors to provide the command to perform the operation associated with the entity to the operating system in response to identifying that the requesting system has the policy to make the command.

(50) In some embodiments, the instructions cause the one or more processors to identify whether a requesting system has a policy to make the command to perform the operation based on the building graph by identifying a third node of the nodes representing the requesting system and identifying one or more particular edges of the edges between the third node and a fourth node of the nodes representing the policy to make the command.

(51) In some embodiments, the instructions cause the one or more processors to determine that the operating system is a piece of building equipment of the building, identify a device hub configured to facilitate messaging between the building system and the piece of building equipment based on the building graph, wherein the nodes includes a node representing the device hub, and send the command to the piece of building equipment through the device hub.

(52) In some embodiments, the entity is a piece of building equipment. In some embodiments, the instructions cause the one or more processors to determine that the operating system is an external system separate from the building system, identify a connection broker configured to facilitate a connection between the building system and the external system, wherein the nodes includes a node representing the connection broker and the external system, and send the command to the piece of building equipment through the connection broker.

(53) Another implementation of the present disclosure is a method including identifying, by a processing circuit, a capability of an entity in a building graph of a building, the building graph including nodes and edges, the nodes representing entities of the building including the entity and the capability, the edges representing relationships between the entities of the building and the capability, wherein a first node of the nodes represents the entity and a second node of the nodes related to the first node by one or more edges of the edges represents the capability. The method includes receiving, by the processing circuit, a command to perform an operation associated with the entity, the operation associated with the capability of the entity and providing, by the processing circuit, the command to perform the operation associated with the entity to an operating system.

(54) In some embodiments, identifying, by the processing circuit, the capability of the entity includes

identifying the first node of the nodes of the building graph representing the entity and identifying at least one of one or more nodes or the one or more edges between the first node and the second node representing the capability of the entity.

(55) In some embodiments, the entity is a piece of building equipment of the building. In some embodiments, the capability is a control operation that the piece of building equipment is configured to perform.

(56) In some embodiments, the entity is a user of the building. In some embodiments, the capability is an action associated with the user that a system is configured to perform.

(57) In some embodiments, the method includes receiving, by the processing circuit, the command to perform the operation associated with the entity includes receiving the command from a requesting system. In some embodiments, the method includes identifying, by the processing circuit, whether the requesting system has a policy to make the command to perform the operation based on the building graph, wherein the building graph indicates the policy to make the command. In some embodiments, the method includes providing, by the processing circuit, the command to perform the operation associated with the entity to the operating system in response to identifying that the requesting system has the policy to make the command.

(58) In some embodiments, the method includes identifying, by the processing circuit, whether a requesting system has a policy to make the command to perform the operation based on the building graph by identifying a third node of the nodes representing the requesting system and identifying one or more particular edges of the edges between the third node and a fourth node of the nodes representing the policy to make the command.

(59) In some embodiments, the method includes determining, by the processing circuit, that the operating system is a piece of building equipment of the building, identifying, by the processing circuit, a device hub configured to facilitate messaging between the processing circuit and the piece of building equipment based on the building graph, wherein the nodes includes a node representing the device hub, and sending, by the processing circuit, the command to the piece of building equipment through the device hub.

(60) In some embodiments, the entity is a piece of building equipment. In some embodiments, the method includes determining, by the processing circuit, that the operating system is an external system separate from the building system, identifying, by the processing circuit, a connection broker configured to facilitate a connection between the building system and the external system, wherein the nodes includes a node representing the connection broker and the external system, and sending, by the processing circuit, the command to the piece of building equipment through the connection broker.

(61) One implementation of the present disclosure is one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to identify a capability of an entity in a building graph of a building, the building graph including nodes and edges, the nodes representing entities of the building including the entity and the capability, the edges representing relationships between the entities of the building and the capability, wherein a first node of the nodes represents the entity and a second node of the nodes related to the first node by one or more edges of the edges represents the capability. The instructions cause the one or more processors to receive a command to perform an operation associated with the entity, the operation associated with the capability of the entity and provide the command to perform the operation associated with the entity to an operating system.

(62) In some embodiments, the instructions cause the one or more processors to identify the capability of the entity by identifying the first node of the nodes of the building graph representing the entity and identifying at least one of one or more nodes or the one or more edges between the first node and the second node representing the capability of the entity.

(63) In some embodiments, the entity is a piece of building equipment of the building. In some embodiments, the capability is a control operation that the piece of building equipment is configured to perform.

(64) In some embodiments, the entity is a user of the building. In some embodiments, the capability is an action associated with the user that a system is configured to perform.

(65) Building Graph Based Communication Actions

(66) One implementation of the present disclosure is a building system of a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive a command to perform an action for an entity. The instructions cause the

one or more processors to identify a service configured to perform the action based on a building graph, the building graph including nodes and edges, wherein the nodes represent entities of the building, the service, and one or more other services, wherein the edges represent relationships between the entities and communication actions of the service with the one or more other services and cause the service to perform the action by causing the service to perform one or more communication actions with the one or more other services indicated by the building graph.

(67) In some embodiments, the communication actions are application programming interface (API) calls to the one or more other services.

(68) In some embodiments, the entities of the building are at least one of building equipment, locations of the building, users of the building, and events of the building.

(69) In some embodiments, a first node of the nodes represents the service and a second node of the nodes represents a second service of the one or more other services. In some embodiments, an edge of the edges relates the first node to the second node and indicates a communication action that the service can make to the second service.

(70) In some embodiments, the service is a connection broker configured to broker a connection between the building system and an external system separate from the building system. In some embodiments, the action is an operation performed by the external system. In some embodiments, the one or more communication actions are API calls that the connection broker makes with the one or more other services to cause the external system to perform the operation.

(71) In some embodiments, the service is a device hub configured to handle messages between the building system and a piece of building equipment. In some embodiments, the action is an operation performed by the piece of building equipment. In some embodiments, the one or more communication actions are API calls that the device hub makes with the one or more other services to cause the piece of building equipment to perform the operation.

(72) In some embodiments, the instructions cause the one or more processors to identify a capability of the entity in the building graph, the capability indicating that the entity can perform the action and cause the service to perform the action based on the one or more communication actions indicated by the building graph responsive to identifying the capability of the entity.

(73) In some embodiments, the instructions cause the one or more processors to receive the command to perform the action from a requesting system. In some embodiments, the instructions cause the one or more processors to identify whether the requesting system has a policy to make the command to perform the action based on the building graph, wherein the building graph indicates the policy to make the command. In some embodiments, the instructions cause the one or more processors to cause the service to perform the action in response to identifying the policy to make the command.

(74) In some embodiments, the instructions cause the one or more processors to identify whether a requesting system that the building system receives the request to perform the command from has a policy to make the command by identifying a first node of the nodes representing the requesting system in the building graph and identifying one or more edges between the first node and a second node of the nodes representing the policy to make the command.

(75) Another implementation of the present disclosure is a method including receiving, by a processing circuit, a command to perform an action for an entity, identifying, by the processing circuit, a service configured to perform the action based on a building graph, the building graph including nodes and edges, wherein the nodes represent entities of the building, the service, and one or more other services, wherein the edges represent relationships between the entities and communication actions of the service with the one or more other services, and causing, by the processing circuit, the service to perform the action by causing the service to perform one or more communication actions with the one or more other services indicated by the building graph.

(76) In some embodiments, the communication actions are application programming interface (API) calls to the one or more other services.

(77) In some embodiments, the entities of the building are at least one of building equipment, locations of the building, users of the building, and events of the building.

(78) In some embodiments, a first node of the nodes represents the service and a second node of the nodes represents a second service of the one or more other services. In some embodiments, an edge of the edges relates the first node to the second node and indicates a communication action that the service can make to

the second service.

(79) In some embodiments, the service is a connection broker configured to broker a connection between the building system and an external system separate from the building system. In some embodiments, the action is an operation performed by the external system. In some embodiments, the one or more communication actions are API calls that the connection broker makes with the one or more other services to cause the external system to perform the operation.

(80) In some embodiments, the service is a device hub configured to handle messages between the building system and a piece of building equipment. In some embodiments, the action is an operation performed by the piece of building equipment. In some embodiments, the one or more communication actions are API calls that the device hub makes with the one or more other services to cause the piece of building equipment to perform the operation.

(81) In some embodiments, the method includes identifying, by the processing circuit, a capability of the entity in the building graph, the capability indicating that the entity can perform the action and causing, by the processing circuit, the service to perform the action based on the one or more communication actions indicated by the building graph responsive to identifying the capability of the entity.

(82) In some embodiments, the method includes receiving, by the processing circuit, the command to perform the action from a requesting system. In some embodiments, the method includes identifying, by the processing circuit, whether the requesting system has a policy to make the command to perform the action based on the building graph, wherein the building graph indicates the policy to make the command. In some embodiments, the method includes causing, by the processing circuit, the service to perform the action in response to identifying the policy to make the command.

(83) In some embodiments, the method includes identifying, by the processing circuit, whether a requesting system that the building system receives the request to perform the command from has a policy to make the command includes identifying a first node of the nodes representing the requesting system in the building graph and identifying one or more edges between the first node and a second node of the nodes representing the policy to make the command.

(84) Another implementation of the present disclosure is one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive a command to perform an action for an entity. The instructions cause the one or more processors to identify a service configured to perform the action based on a building graph, the building graph including nodes and edges, wherein the nodes represent entities of the building, the service, and one or more other services, wherein the edges represent relationships between the entities and communication actions of the service with the one or more other services and cause the service to perform the action by causing the service to perform one or more communication actions with the one or more other services indicated by the building graph.

(85) In some embodiments, the communication actions are application programming interface (API) calls to the one or more other services.

(86) Building Graph Based Policies

(87) One implementation of the present disclosure is a building system of a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive a request to access a portion of a building graph of the building from a system, the building graph including nodes and edges, the nodes representing entities of the building and the edges representing relationships between the entities of the building. The instructions cause the one or more processors to determine whether the system has access to the portion of the building graph based on a policy indicated by the nodes and edges of the building graph and provide the portion of the building graph to the system in response to a determination that the system has access to the portion of the building graph.

(88) In some embodiments, the building graph includes a first node representing the policy. In some embodiments, the building graph includes a second node indicating a read policy to read events related to the first node by a first edge of the edges. In some embodiments, the building graph includes a third node indicating a command policy to send commands related to the first node by a second edge of the edges.

(89) In some embodiments, the instructions cause the one or more processors to determine whether the system has access to the portion of the building graph based on the policy by identifying a first node of the nodes representing the system and identifying an edge of the edges between the first node and a second

node representing the policy to access the portion of the building graph.

(90) In some embodiments, the policy to access the portion of the building graph is an access policy to access events associated with a particular entity. In some embodiments, the nodes include a first node representing the policy and a second node representing the particular entity. In some embodiments, an edge of the edges links the first node to the second node.

(91) In some embodiments, the policy to access the events associated with the particular entity is a particular access policy to access other events of other entities, the other entities related to the particular entity. In some embodiments, the nodes include other nodes representing the other entities. In some embodiments, the edges include one or more edges relating the other nodes to the second node representing the particular entity.

(92) In some embodiments, the instructions cause the one or more processors to receive a command to perform an action for an entity from a requesting system and identify whether the system has a command policy to make the command to perform the action based on the building graph by identifying a first node of the nodes representing the requesting system and identifying one or more edges between the first node and a second node of the nodes representing the command policy to make the command.

(93) In some embodiments, the instructions cause the one or more processors to identify a capability of the entity in the building graph and provide the command to perform the action associated with the entity to an operating system in response to identifying the capability.

(94) In some embodiments, the instructions cause the one or more processors to identify the capability of the entity by identifying a node of the nodes of the building graph representing the entity and identifying at least one of one or more nodes or one or more particular edges between the node and a third node representing the capability of the entity.

(95) In some embodiments, the entity is a piece of building equipment of the building. In some embodiments, the capability is an operation that the piece of building equipment is configured to perform.

(96) Another implementation of the present disclosure is a method including receiving, by a processing circuit, a request to access a portion of a building graph of a building from a system, the building graph including nodes and edges, the nodes representing entities of the building and the edges representing relationships between the entities of the building. The method includes determining, by the processing circuit, whether the system has access to the portion of the building graph based on a policy indicated by the nodes and edges of the building graph and providing, by the processing circuit, the portion of the building graph to the system in response to a determination that the system has access to the portion of the building graph.

(97) In some embodiments, the building graph includes a first node representing the policy. In some embodiments, the building graph includes a second node indicating a read policy to read events related to the first node by a first edge of the edges. In some embodiments, the building graph includes a third node indicating a command policy to send commands related to the first node by a second edge of the edges.

(98) In some embodiments, determining, by the processing circuit, whether the system has access to the portion of the building graph based on the policy includes identifying a first node of the nodes representing the system and identifying an edge of the edges between the first node and a second node representing the policy to access the portion of the building graph.

(99) In some embodiments, the policy to access the portion of the building graph is an access policy to access events associated with a particular entity. In some embodiments, the nodes include a first node representing the policy and a second node representing the particular entity. In some embodiments, an edge of the edges links the first node to the second node.

(100) In some embodiments, the policy to access the events associated with the particular entity is a particular access policy to access other events of other entities, the other entities related to the particular entity. In some embodiments, the nodes include other nodes representing the other entities. In some embodiments, the edges include one or more edges relating the other nodes to the second node representing the particular entity.

(101) In some embodiments, the method includes receiving, by the processing circuit, a command to perform an action for an entity from a requesting system and identifying, by the processing circuit, whether the system has a command policy to make the command to perform the action based on the building graph by identifying a first node of the nodes representing the requesting system and identifying one or more edges between the first node and a second node of the nodes representing the command policy

to make the command.

(102) In some embodiments, the method includes identifying, by the processing circuit, a capability of the entity in the building graph and providing, by the processing circuit, the command to perform the action associated with the entity to an operating system in response to identifying the capability.

(103) In some embodiments, the method includes identifying, by the processing circuit, the capability of the entity by identifying a node of the nodes of the building graph representing the entity and identifying at least one of one or more nodes or one or more particular edges between the node and a third node representing the capability of the entity.

(104) In some embodiments, the entity is a piece of building equipment of the building. In some embodiments, the capability is an operation that the piece of building equipment is configured to perform.

(105) One implementation of the present disclosure is one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive a request to access a portion of a building graph of a building from a system, the building graph including nodes and edges, the nodes representing entities of the building and the edges representing relationships between the entities of the building, determine whether the system has access to the portion of the building graph based on a policy indicated by the nodes and edges of the building graph, and provide the portion of the building graph to the system in response to a determination that the system has access to the portion of the building graph.

(106) In some embodiments, the building graph includes a first node representing the policy. In some embodiments, the building graph includes a second node indicating a read policy to read events related to the first node by a first edge of the edges. In some embodiments, the building graph includes a third node indicating a command policy to send commands related to the first node by a second edge of the edges.

(107) Building Graph Projections

(108) One implementation of the present disclosure is a building system of a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to retrieve projection rules for generating a building graph projection. The instructions cause the one or more processors to retrieve entities representing elements of the building and relationships between the entities representing relationships between the entities, construct the building graph projection including nodes and edges based on the entities, the relationships, and the projection rules, and perform one or more operations based on the building graph projection.

(109) In some embodiments, the instructions cause the one or more processors to construct the building graph projection by generating one node of the nodes for each of the entities, generate an edge of the edges for each relationship of the relationships, and connecting the edge from a first node of the nodes to a second node of the nodes to illustrate a particular relationship of the relationships between a first entity of the entities and a second entity of the entities.

(110) In some embodiments, the projection rules indicate permissions for a subscriber, wherein the permissions identify a set of the entities and a set of the relationships. In some embodiments, the instructions cause the one or more processors to construct the building graph projection based on the set of the entities and the set of the relationships.

(111) In some embodiments, the projection rules indicate an ontology indicating allowed relationships between types of entities. In some embodiments, the instructions cause the one or more processors to construct the building graph projection based on the types of entities and the allowed relationships between the types of entities.

(112) In some embodiments, the instructions cause the one or more processors to retrieve, for a subscriber, the projection rules for generating the building graph projection from graph projection rules stored in a database, wherein the graph projection rules associated with subscribers.

(113) In some embodiments, the instructions cause the one or more processors to retrieve second projection rules for a second subscriber of the subscribers, construct a second building graph projection including a second plurality of nodes and a second plurality of edges based on the at least some of the entities, at least some of the relationships, and the second projection rules, and store the building graph projection and the second building graph projection in a graph projection database.

(114) In some embodiments, the instructions cause the one or more processors to receive a modification to the building graph projection, generate a change feed event, the change feed event recording the modification to the building graph projection, and add the change feed event to a change feed including

change feed events representing modifications to the building graph projection at different times.

(115) In some embodiments, the modification is at least one of adding a new node to the nodes of the building graph projection, adding a new edge to the edges of the building graph projection, deleting an existing node of the nodes of the building graph projection, deleting an existing edge of the edges of the building graph projection, modifying the existing node of the nodes of the building graph projection, or modifying the existing edge of the edges of the building graph projection.

(116) In some embodiments, the instructions cause the one or more processors to, receive an event from a piece of building equipment of the building, the event indicating a data value associated with the piece of building equipment occurring at a particular time, identify contextual data of a database that provides a contextual description of the event, generate an enriched event by enriching the event with the contextual data, the enriched event including the data value, the particular time, and the contextual data, and provide the enriched event to a consuming application configured to operate based on the enriched event.

(117) In some embodiments, the instructions cause the one or more processors to identify the contextual data by searching the building graph projection that includes the contextual description of the piece of building equipment.

(118) In some embodiments, the nodes represent the entities and the edges represent relationships between the entities. In some embodiments, the nodes include a node representing the piece of building equipment. In some embodiments, the instructions cause the one or more processors to identify the contextual data by identifying one or more nodes of the nodes related to the node representing the piece of building equipment based on one or more edges of the edges between the node representing the piece of building equipment and the one or more nodes.

(119) Another implementation of the present disclosure is a method including retrieving, by a processing circuit, projection rules for generating a building graph projection. The method includes retrieving, by the processing circuit, entities representing elements of a building and relationships between the entities representing relationships between the entities, constructing, by the processing circuit, the building graph projection including nodes and edges based on the entities, the relationships, and the projection rules, and performing, by the processing circuit, one or more operations based on the building graph projection.

(120) In some embodiments, the method includes generating, by the processing circuit, one node of the nodes for each of the entities, generating, by the processing circuit, an edge of the edges for each relationship of the relationships, and connecting, by the processing circuit, the edge from a first node of the nodes to a second node of the nodes to illustrate a particular relationship of the relationships between a first entity of the entities and a second entity of the entities.

(121) In some embodiments, the projection rules indicate permissions for a subscriber, wherein the permissions identify a set of the entities and a set of the relationships. In some embodiments, the method further includes constructing, by the processing circuit, the building graph projection based on the set of the entities and the set of the relationships.

(122) In some embodiments, the projection rules indicate an ontology indicating allowed relationships between types of entities. In some embodiments, the method further includes constructing, by the processing circuit, the building graph projection based on the types of entities and the allowed relationships between the types of entities.

(123) In some embodiments, the method further includes retrieving, by the processing circuit, for a subscriber, the projection rules for generating the building graph projection from graph projection rules stored in a database, wherein the graph projection rules associated with subscribers.

(124) In some embodiments, the method further includes retrieving, by the processing circuit, second projection rules for a second subscriber of the subscribers. In some embodiments, the method further includes constructing, by the processing circuit, a second building graph projection including a second plurality of nodes and a second plurality of edges based on the at least some of plurality of entities, at least some of the relationships, and the second projection rules and storing, by the processing circuit, the building graph projection and the second building graph projection in a graph projection database.

(125) In some embodiments, the method further includes receiving, by the processing circuit, a modification to the building graph projection, generating, by the processing circuit, a change feed event, the change feed event recording the modification to the building graph projection, and adding, by the processing circuit, the change feed event to a change feed including change feed events representing modifications to the building graph projection at different times.

(126) In some embodiments, the modification is at least one of adding a new node to the nodes of the building graph projection, adding a new edge to the edges of the building graph projection, deleting an existing node of the nodes of the building graph projection, deleting an existing edge of the edges of the building graph projection, modifying the existing node of the nodes of the building graph projection, or modifying the existing edge of the edges of the building graph projection.

(127) Another implementation of the present disclosure is one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to retrieve projection rules for generating a building graph projection, retrieve entities representing elements of a building and relationships between the entities representing relationships between the entities, construct the building graph projection including nodes and edges based on the entities, the relationships, and the projection rules, and perform one or more operations based on the building graph projection.

(128) Event Based Building Graph Queries

(129) One implementation of the present disclosure is a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive a query for information of a building graph of the building from a system, the query including an indication of an entity and an indication of an event associated with the entity. The instructions cause the one or more processors to query the building graph with the indication of the entity and the indication of the event associated with the entity for the information of the building graph, the building graph including nodes and edges, the nodes representing entities and events including the entity and the event, the edges representing relationships between the entities and the events and generate a query response based on the information and provide the query response to the system.

(130) In some embodiments, the indication of the entity is an indication of an entity type of the entity. In some embodiments, the instructions cause the one or more processors to query the building graph with the indication of the entity and the event by identifying a node of the nodes corresponding to the entity type of the entity, the node representing the entity and identifying one or more edges between the node representing the entity and a second node of the nodes representing the event. In some embodiments, the instructions cause the one or more processors to generate the query response by causing the query response to include the entity in response to identifying the node and identifying the one or more edges between the node and the second node.

(131) In some embodiments, the system includes a user application. In some embodiments, the instructions cause the one or more processors to receive the query from the user application where a user provides a request for the information to the user application and the user application generates and provides the query to the building system.

(132) In some embodiments, the instructions cause the one or more processors to provide the query response to the user application. In some embodiments, the user application generates a display indicating the information of the query response.

(133) In some embodiments, one or more edges of the edges between a first node representing a particular event and a second node representing a particular building entity indicates that the particular event is associated with the particular building entity.

(134) In some embodiments, the particular building entity is a piece of building equipment that generates the particular event.

(135) In some embodiments, the instructions cause the one or more processors to determine whether the system has access to the information of the building graph based on a policy indicated by the nodes and edges of the building graph and provide the information of the building graph to the system in response to a determination that the system has access to the information of the building graph.

(136) In some embodiments, the instructions cause the one or more processors to determine whether the system has access to the information of the building graph based on the policy by identifying a first node of the nodes representing the system and identifying an edge of the edges between the first node and a second node representing the policy to access the information of the building graph.

(137) In some embodiments, the instructions cause the one or more processors to receive a request from the system for a capability of the entity responsive to providing the query response to the system, identify the capability of the entity in the building graph, receive a command to perform an operation associated with the entity, the command performing an action associated with the capability of the entity, and provide the command to perform the operation associated with the entity to an operating system.

(138) In some embodiments, the instructions cause the one or more processors to identify the capability of the entity by identifying a first node of the nodes of the building graph representing the entity and identifying at least one of one or more nodes or one or more edges between the first node and a second node representing the capability of the entity.

(139) Another implementation of the present disclosure is a method including receiving, by a processing circuit, a query for information of a building graph of a building from a system, the query including an indication of an entity and an indication of an event associated with the entity. The method includes querying, by the processing circuit, the building graph with the indication of the entity and the indication of the event associated with the entity for the information of the building graph, the building graph including nodes and edges, the nodes representing entities and events including the entity and the event, the edges representing relationships between the entities and the events and generating, by the processing circuit, a query response based on the information and provide the query response to the system.

(140) In some embodiments, the indication of the entity is an indication of an entity type of the entity. In some embodiments, querying, by the processing circuit, the building graph with the indication of the entity and the event includes identifying a node of the nodes corresponding to the entity type of the entity, the node representing the entity and identifying one or more edges between the node representing the entity and a second node of the nodes representing the event. In some embodiments, generating, by the processing circuit, the query response includes causing the query response to include the entity in response to identifying the node and identifying the one or more edges between the node and the second node.

(141) In some embodiments, the method includes receiving, by the processing circuit, a request from the system for a capability of the entity responsive to providing the query response to the system. In some embodiments, the method includes identifying, by the processing circuit, the capability of the entity in the building graph, receiving, by the processing circuit, a command to perform an operation associated with the entity, the command performing an action associated with the capability of the entity, and providing, by the processing circuit, the command to perform the operation associated with the entity to an operating system.

(142) In some embodiments, the method include receiving, the query from a user application where a user provides a request for the information to the user application and the user application generates and provides the query to a building system.

(143) In some embodiments, the method includes providing, by the processing circuit, the query response to the user application. In some embodiments, the user application generates a display indicating the information of the query response.

(144) In some embodiments, one or more edges of the edges between a first node representing a particular event and a second node representing a particular building entity indicates that the particular event is associated with the particular building entity.

(145) In some embodiments, the particular building entity is a piece of building equipment that generates the particular event.

(146) In some embodiments, the method includes determining, by the processing circuit, whether the system has access to the information of the building graph based on a policy indicated by the nodes and edges of the building graph and providing, by the processing circuit, the information of the building graph to the system in response to a determination that the system has access to the information of the building graph.

(147) In some embodiments, the method includes determining, by the processing circuit, whether the system has access to the information of the building graph based on the policy by identifying a first node of the nodes representing the system and identifying an edge of the edges between the first node and a second node representing the policy to access the information of the building graph.

(148) Another implementation of the present disclosure is one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to receive a query for information of a building graph of a building from a system, the query including an indication of an entity and an indication of an event associated with the entity. The instructions cause the one or more processors to query the building graph with the indication of the entity and the indication of the event associated with the entity for the information of the building graph, the building graph including nodes and edges, the nodes representing entities and events including the entity and the event, the edges representing relationships between the entities and the events and generate a query response based on the

information and provide the query response to the system.

(149) Zone Based Tenant Entitlement Model

(150) One implementation of the present disclosure is a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to manage entitlements for subscriptions of one or more buildings with a building entitlement model, wherein a first subscription of the subscriptions is linked to first zone via the building entitlement model and a second subscription of the subscriptions is linked to a second zone via the building entitlement model. The instructions cause the one or more processors to receive a first request to perform a first operation for the first subscription and a second request to perform a second operation for the second subscription, determine, based on the building entitlement model, whether the first subscription has a first entitlement for the first operation and whether the second subscription has a second entitlement for the second operation, and implement the first operation on first computing resources of the first zone based on the building entitlement model in response to a first determination that the first subscription has the first entitlement and implement the second operation on second computing resources of the second zone based on the building entitlement model in response to a second determination that the second subscription has the second entitlement.

(151) In some embodiments, the entitlements indicate whether the subscriptions have authorization to utilize functional resources of the building system.

(152) In some embodiments, the instructions cause the one or more processors to receive first operational data associated with the first subscription, the first operational data indicating actions of the first subscription utilizing first computing resources, determine a resource utilization metric of the first subscription based on the first operational data, determine to throttle the actions of the first subscription in response to determining that the resource utilization metric exceeds a level, and throttle the actions of the first subscription to reduce an amount of the actions of the first subscription in response to determining that the resource utilization metric exceeds the level.

(153) In some embodiments, the instructions cause the one or more processors to receive first operational data associated with the first subscription, the first operational data indicating first actions of the first subscription utilizing first computing resources, receive second operational data associated with the second subscription, the second operational data indicating second actions of the second subscription utilizing the second computing resources, determine first resource utilization metrics of the first subscription based on the first operational data, and determine second resource utilization metrics of the second subscription based on the second operational data.

(154) In some embodiments, the instructions cause the one or more processors to generate a first bill in an amount proportional to first resource utilization of the first subscription based on the first resource utilization metrics and generate a second bill in a second amount proportional to a second resource utilization of the second subscription based on the second resource utilization metrics.

(155) In some embodiments, the first zone represents a first geographic boundary and the first computing resources are located within the first geographic boundary. In some embodiments, the second zone represents a second geographic boundary and the second computing resources are located within the second geographic boundary.

(156) In some embodiments, the first computing resources include computational resources and storage resources. In some embodiments, the second computing resources include second computational resources and second storage resources.

(157) In some embodiments, the building entitlement model includes a tenant, wherein the tenant represents an entity associated with a billing boundary. In some embodiments, the tenant is linked to the subscriptions by the building entitlement model.

(158) In some embodiments, the building entitlement model includes a second tenant, wherein the second tenant represents a second entity associated with a second billing boundary. In some embodiments, the second tenant is linked, by the building entitlement model, to a second plurality of subscriptions of the building entitlement model.

(159) Another implementation of the present disclosure is a method including managing, by a processing circuit, entitlements for subscriptions of one or more buildings with a building entitlement model, wherein a first subscription of the subscriptions is linked to first zone via the building entitlement model and a second subscription of the subscriptions is linked to a second zone via the building entitlement model. The

method includes receiving, by the processing circuit, a first request to perform a first operation for the first subscription and a second request to perform a second operation for the second subscription, determining, by the processing circuit, based on the building entitlement model, whether the first subscription has a first entitlement for the first operation and whether the second subscription has a second entitlement for the second operation, and implementing, by the processing circuit, the first operation on first computing resources of the first zone based on the building entitlement model in response to a first determination that the first subscription has the first entitlement and implement the second operation on second computing resources of the second zone based on the building entitlement model in response to a second determination that the second subscription has the second entitlement.

(160) In some embodiments, the entitlements indicate whether the subscriptions have authorization to utilize functional resources of a building system.

(161) In some embodiments, the method further includes receiving, by the processing circuit, first operational data associated with the first subscription, the first operational data indicating actions of the first subscription utilizing first computing resources and determining, by the processing circuit, a resource utilization metric of the first subscription based on the first operational data. In some embodiments, the method further includes determining, by the processing circuit, to throttle the actions of the first subscription in response to determining that the resource utilization metric exceeds a level and throttling, by the processing circuit, the actions of the first subscription to reduce an amount of the actions of the first subscription in response to determining that the resource utilization metric exceeds the level.

(162) In some embodiments, the method includes receiving, by the processing circuit, first operational data associated with the first subscription, the first operational data indicating first actions of the first subscription utilizing first computing resources, receiving, by the processing circuit, second operational data associated with the second subscription, the second operational data indicating second actions of the second subscription utilizing the second computing resources, determining, by the processing circuit, first resource utilization metrics of the first subscription based on the first operational data, and determining, by the processing circuit, second resource utilization metrics of the second subscription based on the second operational data.

(163) In some embodiments, the method further includes generating, by the processing circuit, a first bill in an amount proportional to first resource utilization of the first subscription based on the first resource utilization metrics and generating, by the processing circuit, a second bill in a second amount proportional to a second resource utilization of the second subscription based on the second resource utilization metrics.

(164) In some embodiments, the first zone represents a first geographic boundary and the first computing resources are located within the first geographic boundary. In some embodiments, the second zone represents a second geographic boundary and the second computing resources are located within the second geographic boundary.

(165) In some embodiments, the first computing resources include computational resources and storage resources. In some embodiments, the second computing resources include second computational resources and second storage resources.

(166) In some embodiments, the building entitlement model includes a tenant, wherein the tenant represents an entity associated with a billing boundary. In some embodiments, the tenant is linked to the subscriptions by the building entitlement model.

(167) In some embodiments, the building entitlement model includes a second tenant, wherein the second tenant represents a second entity associated with a second billing boundary. In some embodiments, the second tenant is linked, by the building entitlement model, to a second plurality of subscriptions of the building entitlement model.

(168) Another implementation of the present disclosure is one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to manage entitlements for subscriptions of one or more buildings with a building entitlement model, wherein a first subscription of the subscriptions is linked to first zone via the building entitlement model and a second subscription of the subscriptions is linked to a second zone via the building entitlement model. The instructions cause the one or more processors to receive a first request to perform a first operation for the first subscription and a second request to perform a second operation for the second subscription, determine, based on the building entitlement model, whether the first subscription has a first entitlement for the first operation and whether the second subscription has a second entitlement for the second

operation, and implement the first operation on first computing resources of the first zone based on the building entitlement model in response to a first determination that the first subscription has the first entitlement and implement the second operation on second computing resources of the second zone based on the building entitlement model in response to a second determination that the second subscription has the second entitlement.

(169) In some embodiments, the entitlements indicate whether the subscriptions have authorization to utilize functional resources of a building system.

(170) Edge Based Event Enrichment

(171) One implementation of the present disclosure is an edge platform of a building communicatively coupled to a cloud system, the edge platform including one or more memory devices having instructions stored thereon, the one or more memory devices located on-premises within the building and one or more processors located on-premises within the building, the one or more processors executing the instructions causing the one or more processors to receive an event from a piece of building equipment of the building, the event indicating a data value associated with the piece of building equipment occurring at a particular time. The instructions cause the one or more processors to identify contextual data of a data structure that provides a contextual description of the event, generate an enriched event by enriching the event with the contextual data, the enriched event including the data value, the particular time, and the contextual data, and communicate the enriched event to the cloud system configured to operate based on the enriched event.

(172) In some embodiments, the instructions cause the one or more processors to train one or more machine learning models stored locally by the edge platform based on the enriched event and perform one or more operations with the piece of building equipment based on the one or more machine learning models.

(173) In some embodiments, the instructions cause the one or more processors to identify the contextual data based on one or more enrichment rules. In some embodiments, the instructions cause the one or more processors to identify second contextual data of the data structure based on one or more second enrichment rules, generate a second enriched event by enriching the event with the second contextual data, the data value, and the particular time, and provide the second enriched event to the cloud system.

(174) In some embodiments, the data structure is a graph. In some embodiments, the instructions cause the one or more processors to identify the contextual data by searching the graph that includes the contextual description of the event.

(175) In some embodiments, the graph includes nodes and edges. In some embodiments, the nodes represent entities of the building and the edges represent relationships between the entities of the building. In some embodiments, the nodes include a node representing the piece of building equipment. In some embodiments, the instructions cause the one or more processors to identify the contextual data by identifying one or more nodes of the nodes related to the node representing the piece of building equipment based on one or more edges of the edges between the node representing the piece of building equipment and the one or more nodes.

(176) In some embodiments, the data structure is a digital twin stored by the edge platform. In some embodiments, the digital twin of the edge platform is updated based on changes made to a second digital twin stored by the cloud system to synchronize the second digital twin stored by the cloud system with the digital twin of the edge platform.

(177) In some embodiments, the instructions cause the one or more processors to receive a change feed of change feed events indicating the changes to the second digital twin and update the digital twin stored by the edge platform with the change feed by making the changes to the digital twin stored by the edge platform.

(178) In some embodiments, the second digital twin is a graph including nodes represent entities of the building and plurality of edges represent relationships between the entities of the building. In some embodiments, the changes include at least one of adding a new node to the nodes of the graph, adding a new edge to the edges of the graph, deleting an existing node of the nodes of the graph, deleting an existing edge of the edges of the graph, modifying the existing node of the nodes of the graph, or modifying the existing edge of the edges of the graph.

(179) In some embodiments, the instructions cause the one or more processors to read the change feed events from a change feed topic, wherein the edge platform is subscribed to the change feed topic and

receives the change feed events in response to the change feed events being added to the change feed topic by the cloud system.

(180) Another implementation of the present disclosure is a method including receiving, by an edge platform, an event from a piece of building equipment of a building, the event indicating a data value associated with the piece of building equipment occurring at a particular time, the edge platform located on-premises within the building and communicatively coupled to a cloud system, identifying, by the edge platform contextual data of a data structure that provides a contextual description of the event, generating, by the edge platform an enriched event by enriching the event with the contextual data, the enriched event including the data value, the particular time, and the contextual data, and communicating, by the edge platform, the enriched event to the cloud system configured to operate based on the enriched event.

(181) In some embodiments, the method includes training, by the edge platform one or more machine learning models stored locally by the edge platform based on the enriched event and performing, by the edge platform one or more operations with the piece of building equipment based on the one or more machine learning models.

(182) In some embodiments, the method includes identifying, by the edge platform, the contextual data based on one or more enrichment rules, identifying, by the edge platform, second contextual data of the data structure based on one or more second enrichment rules, generating, by the edge platform, a second enriched event by enriching the event with the second contextual data, the data value, and the particular time, and providing, by the edge platform, the second enriched event to the cloud system.

(183) In some embodiments, the data structure is a graph. In some embodiments, the method further includes identifying, by the edge platform, the contextual data by searching the graph that includes the contextual description of the event.

(184) In some embodiments, the graph includes nodes and edges. In some embodiments, the nodes represent entities of the building and the edges represent relationships between the entities of the building. In some embodiments, the nodes include a node representing the piece of building equipment. In some embodiments, the method further includes identifying, by the edge platform, the contextual data by identifying one or more nodes of the nodes related to the node representing the piece of building equipment based on one or more edges of the edges between the node representing the piece of building equipment and the one or more nodes.

(185) In some embodiments, the data structure is a digital twin stored by the edge platform. In some embodiments, the method further includes updating the digital twin of the edge platform based on changes made to a second digital twin stored by the cloud system to synchronize the second digital twin stored by the cloud system with the digital twin of the edge platform.

(186) In some embodiments, the method includes receiving, by the edge platform, a change feed of change feed events indicating the changes to the second digital twin and updating, by the edge platform, the digital twin stored by the edge platform with the change feed by making the changes to the digital twin stored by the edge platform.

(187) In some embodiments, the second digital twin is a graph including nodes represent entities of the building and plurality of edges represent relationships between the entities of the building. In some embodiments, the changes include at least one of adding a new node to the nodes of the graph, adding a new edge to the edges of the graph, deleting an existing node of the nodes of the graph, deleting an existing edge of the edges of the graph, modifying the existing node of the nodes of the graph, or modifying the existing edge of the edges of the graph.

(188) In some embodiments, the method includes reading, by edge platform, the change feed events from a change feed topic, wherein the edge platform is subscribed to the change feed topic and receives the change feed events in response to the change feed events being added to the change feed topic by the cloud system.

(189) Another implementation of the present disclosure is an edge platform of a building communicatively coupled to a cloud system, the edge platform including one or more memory devices having instructions stored thereon and one or more processors, the one or more processors executing the instructions causing the one or more processors to receive an event from a piece of building equipment of the building, the event indicating a data value associated with the piece of building equipment occurring at a particular time. The instructions cause the one or more processors to identify contextual data of a data structure that provides a contextual description of the event, generate an enriched event by enriching the event with the

contextual data, the enriched event including the data value, the particular time, and the contextual data, and communicate the enriched event to the cloud system configured to operate based on the enriched event.

(190) In some embodiments, the data structure is a graph. In some embodiments, the instructions cause the one or more processors to identify the contextual data by searching the graph that includes the contextual description of the event.

(191) Digital Twin Synchronization with External Systems

(192) One implementation of the present disclosure is a building system of a building including one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to store a digital twin of the building including a graph data structure, the graph data structure including nodes representing entities of the building and edges between the nodes representing relationships between the entities of the building. The instructions cause the one or more processors to receive an modification to the digital twin of the building, the update modifying at least one of the nodes or the edges, generate a change feed event of a change feed, the change feed event recording the modification to the graph data structure, the change feed including change feed events representing modifications to the graph data structure at different times, and synchronize, based on the change feed event, an external digital twin of the building of an external system with the digital twin of the building by communicating with the external system.

(193) In some embodiments, the entities of the building are at least one of building equipment, locations of the building, users of the building, and events of the building.

(194) In some embodiments, the instructions cause the one or more processors to receive the modification to the digital twin of the building by receiving an event from a piece of building equipment of the building and determining, based on the event, the modification to the digital twin of the building.

(195) In some embodiments, the instructions cause the one or more processors to synchronize, based on the change feed event, the external digital twin of the building of the external system with the digital twin of the building by communicating the change feed event to the external system, wherein the external system updates the external digital twin of the building based on the change feed event.

(196) In some embodiments, the instructions cause the one or more processors to receive the modification to the digital twin of the building from a second external system, wherein the modification to the digital twin of the building is based on a second modification made by the second external system to a second external digital twin of the building stored by the second external system.

(197) In some embodiments, the modification is at least one of adding a new node to the nodes of the graph data structure, adding a new edge to the edges of the graph data structure, deleting an existing node of the nodes of the graph data structure, deleting an existing edge of the edges of the graph data structure, modifying the existing node of the nodes of the graph data structure, or modifying the existing edge of the edges of the graph data structure.

(198) In some implementations, the instructions cause the one or more processors to add the change feed event to a change feed topic, wherein the external system is subscribed to the change feed topic and receives the change feed event in response to the change feed event being added to the change feed topic.

(199) In some implementations, the instructions cause the one or more processors to synchronize, based on the change feed event, the external digital twin of the building of the external system with the digital twin of the building by communicating with the external system, wherein the external digital twin of the building is in a first format different than a format of the digital twin of the building.

(200) In some implementations, the instructions cause the one or more processors to synchronize, based on the change feed event, a second external digital twin of a second external system, the second external digital twin in a second format different than the first format of the external digital twin and the format of the digital twin of the building.

(201) In some implementations, the instructions cause the one or more processors to generate a first update for the external digital twin of the building in the first format for the external digital twin of the building of the external system based on the change feed event, generate a second update for the second external digital twin of the building in the second format for the second external digital twin of the building of the second external system based on the change feed event, communicate the first update for the external digital twin of the building to the external system, wherein the external system updates the external digital twin of the building based on the first update, and communicate the second update for the second external

digital twin of the building to the second external system, wherein the second external system updates the external digital twin of the building based on the second update.

(202) Another implementation of the present disclosure is a method including storing, by a processing circuit, a digital twin of the building including a graph data structure, the graph data structure including nodes representing entities of the building and edges between the nodes representing relationships between the entities of the building. The method includes receiving, by the processing circuit, an modification to the digital twin of the building, the update modifying at least one of the nodes or the edges, generating, by the processing circuit, a change feed event of a change feed, the change feed event recording the modification to the graph data structure, the change feed including change feed events representing modifications to the graph data structure at different times, and synchronizing, by the processing circuit, based on the change feed event, an external digital twin of the building of an external system with the digital twin of the building by communicating with the external system.

(203) In some embodiments, the entities of the building are at least one of building equipment, locations of the building, users of the building, and events of the building.

(204) In some embodiments, receiving, by the processing circuit, the modification to the digital twin of the building includes receiving an event from a piece of building equipment of the building and determining, based on the event, the modification to the digital twin of the building.

(205) In some embodiments, synchronizing, by the processing circuit, based on the change feed event, the external digital twin of the building of the external system with the digital twin of the building includes communicating the change feed event to the external system, wherein the external system updates the external digital twin of the building based on the change feed event.

(206) In some embodiments, the method includes receiving, by the processing circuit, the modification to the digital twin of the building from a second external system, wherein the modification to the digital twin of the building is based on a second modification made by the second external system to a second external digital twin of the building stored by the second external system.

(207) In some embodiments, the modification is at least one of adding a new node to the nodes of the graph data structure, adding a new edge to the edges of the graph data structure, deleting an existing node of the nodes of the graph data structure, deleting an existing edge of the edges of the graph data structure, modifying the existing node of the nodes of the graph data structure, or modifying the existing edge of the edges of the graph data structure.

(208) In some embodiments, the method further includes adding, by the processing circuit, the change feed event to a change feed topic, wherein the external system is subscribed to the change feed topic and receives the change feed event in response to the change feed event being added to the change feed topic.

(209) In some embodiments, synchronizing, by the processing circuit, based on the change feed event, the external digital twin of the building of the external system with the digital twin of the building includes communicating with the external system, wherein the external digital twin of the building is in a first format different than a format of the digital twin of the building.

(210) In some embodiments, the method includes synchronizing, by the processing circuit, based on the change feed event, a second external digital twin of a second external system, the second external digital twin in a second format different than the first format of the external digital twin and the format of the digital twin of the building.

(211) Another implementation of the present disclosure is one or more memory devices having instructions thereon, that, when executed by one or more processors, cause the one or more processors to store a digital twin of a building including a graph data structure, the graph data structure including nodes representing entities of the building and edges between the nodes representing relationships between the entities of the building. The instructions cause the one or more processors to receive an modification to the digital twin of the building, the update modifying at least one of the nodes or the edges, generate a change feed event of a change feed, the change feed event recording the modification to the graph data structure, the change feed including change feed events representing modifications to the graph data structure at different times, and synchronize, based on the change feed event, an external digital twin of the building of an external system with the digital twin of the building by communicating with the external system.

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Various objects, aspects, features, and advantages of the disclosure will become more apparent and better understood by referring to the detailed description taken in conjunction with the accompanying drawings, in which like reference characters identify corresponding elements throughout. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.
- (2) FIG. 1 is a block diagram of a building data platform including an edge platform, a cloud platform, and a twin manager, according to an exemplary embodiment.
- (3) FIG. 2 is a block diagram of the cloud platform and the twin manager of FIG. 1 processing an event received from the edge platform of FIG. 1, according to an exemplary embodiment.
- (4) FIG. 3 is a block diagram of the cloud platform of FIG. 1 processing events shown in greater detail, according to an exemplary embodiment.
- (5) FIG. 4 is a block diagram of the twin manager of FIG. 1 generating projections and operating with components of the cloud platform of FIG. 1 to enrich events, according to an exemplary embodiment.
- (6) FIG. 5 is a flow diagram of a preprocessing workflow performed by the cloud platform of FIG. 1 to preprocess events, according to an exemplary embodiment.
- (7) FIG. 6 is a flow diagram of a discovery workflow discovering new entities from metadata and a device tree that is performed by the cloud platform of FIG. 1, according to an exemplary embodiment.
- (8) FIG. 7 is a flow diagram of a projection workflow performed by the twin manager of FIG. 1 generating a projection, according to an exemplary embodiment.
- (9) FIG. 8 is a flow diagram of an enrichment workflow performed by the cloud platform of FIG. 1 enriching events with contextual information, according to an exemplary embodiment.
- (10) FIG. 9 is a flow diagram of a command processing workflow performed by the cloud platform of FIG. 1 where commands are sent to devices or are communicated to an external system via a connection broker, according to an exemplary embodiment.
- (11) FIG. 10 is a flow diagram of a messaging workflow performed by the cloud platform of FIG. 1 where messages of building systems are received via the edge platform of FIG. 1 and commands for the building systems are communicated to the building subsystems via the edge platform, according to an exemplary embodiment.
- (12) FIG. 11 is a graph projection of the twin manager of FIG. 1 including application programming interface (API) data, capability data, policy data, and services, according to an exemplary embodiment.
- (13) FIG. 12 is another graph projection of the twin manager of FIG. 1 including application programming interface (API) data, capability data, policy data, and services, according to an exemplary embodiment.
- (14) FIG. 13 is a graph projection of the twin manager of FIG. 1 including equipment and capability data for the equipment, according to an exemplary embodiment.
- (15) FIG. 14 is a block diagram of a user interaction manager that handles user queries and requests, according to an exemplary embodiment.
- (16) FIG. 15 is a flow diagram of a process of a security dashboard communicating with the building data platform of FIG. 1 to review information about equipment and command the equipment, according to an exemplary embodiment.
- (17) FIG. 16 is a flow diagram of a process where an event of building equipment is enriched with contextual information of a graph that can be performed by the cloud platform of FIG. 1, according to an exemplary embodiment.
- (18) FIG. 17 is a flow diagram of a process where a change feed of events that record modifications to a graph that can be performed by the twin manager of FIG. 1, according to an exemplary embodiment.
- (19) FIG. 18 is a flow diagram of a process where a graph identifying capabilities of a piece of equipment is used to operate the piece of equipment that can be performed by the cloud platform of FIG. 1, according to an exemplary embodiment.
- (20) FIG. 19 is a flow diagram of a process where the cloud platform of FIG. 1 operates different services related by a graph, according to an exemplary embodiment.
- (21) FIG. 20 is a flow diagram of a process where a user or service is provided with information and control abilities based on policies stored within a graph that can be performed by the cloud platform of FIG. 1, according to an exemplary embodiment.

- (22) FIG. 21 is a flow diagram of a process where a graph projection is constructed for a system based on projection rules, according to an exemplary embodiment.
- (23) FIG. 22 is a flow diagram of a process where a graph is queried based on entity and event, according to an exemplary embodiment.
- (24) FIG. 23 is a block diagram of a platform manager of the cloud platform of FIG. 1 managing tenant and subscription entitlements with a tenant entitlement model, according to an exemplary embodiment.
- (25) FIG. 24 is a block diagram of the tenant entitlement model in greater detail, according to an exemplary embodiment.
- (26) FIG. 25 is a flow diagram of a process of managing tenant and subscription entitlements with the tenant entitlement model, according to an exemplary embodiment.
- (27) FIG. 26 is a block diagram of the edge platform of FIG. 1 performing event enrichment at the edge before the events are communicated to the cloud, according to an exemplary embodiment.
- (28) FIG. 27 is a flow diagram of a process of performing event enrichment at the edge by the edge platform of FIG. 1 before the events are communicated to the cloud, according to an exemplary embodiment.
- (29) FIG. 28 is a block diagram of the twin manager of FIG. 1 synchronizing a digital twin of the twin manager with digital twins of other external systems, according to an exemplary embodiment.
- (30) FIG. 29 is a flow diagram of a process of synchronizing a digital twin of the twin manager with digital twins of other external system, according to an exemplary embodiment.

DETAILED DESCRIPTION

(31) Overview

- (32) Referring generally to the FIGURES, a building data platform is shown, according to various exemplary embodiments. The building data platform described herein can be configured to facilitate the management and control of a building. The building data platform can provide agility, flexibility, and scalability for building management, enabling buildings to be dynamic spaces.
- (33) The building data platform can allow users to be able to manage operations systemically with buildings that have memory, intelligence, and unique identities. The building data platform can be configured to perform energy and space optimization, predictive maintenance, and/or remote operations. Although the building data platform is described for a building, e.g., for building subsystems of a building (e.g., for HVAC systems, security systems, access control systems, elevator systems, fire response systems, etc.), the building data platform can be applied to other industries, e.g., motor vehicles, airports, manufacturing systems, transit systems, airplanes, and/or any other type of system where the management of devices is desired. The building data platform can provide seamless integration of devices regardless of brand, make, model, or subsystem.
- (34) The building data platform can include multiple components, e.g., an edge platform, a cloud platform, and a twin manager. The edge platform can be configured to facilitate connection for the building data platform directly to the building systems. The edge platform can facilitate receiving, collecting, and/or retrieving data from the building subsystems. In some embodiments, the edge platform can facilitate the command and control of the building systems for the building data platform.
- (35) The cloud platform can be configured to facilitate message control for the building data platform. The cloud platform can be configured to receive messages of the building subsystems through the edge platform and manage the messages. The cloud platform can route messages around the building data platform. Furthermore, the cloud platform can facilitate directing operational commands for the building subsystems to the building subsystems through the edge platform. In some embodiments, the cloud platform is configured to enrich messages received from the building subsystems. The cloud platform can be configured to add contextual information to event messages received from the building subsystems via the edge platform. The contextual information can be utilized by applications that consume the event messages and can allow for the applications to immediately have access to the contextual information instead of requiring the applications to query another system to receive contextual information.
- (36) The twin manager can facilitate the management of a digital twin of the building, e.g., the building subsystems. Digital twins can be digital replicas of physical entities that enable an in-depth analysis of data of the physical entities and provide the potential to monitor systems to mitigate risks, manage issues, and utilize simulations to test future solutions. Digital twins can play an important role in helping technicians find the root cause of issues and solve problems faster, in supporting safety and security

protocols, and in supporting building managers in more efficient use of energy and other facilities resources. Digital twins can be used to enable and unify security systems, employee experience, facilities management, sustainability, etc.

(37) The twin manager can be configured to track the building subsystems by storing entities (e.g., data representing equipment, buildings, spaces, floors, software services, policies, etc.), relationships (e.g., relationships between equipment and their locations, API calls between software services, etc.), and events (e.g., data that has occurred, measurements, commands, statuses, etc.). The twin manager can create graph projections, e.g., a graph with nodes for the entities and events of the building and edges for the relationships between the entities and/or events. The graph projections can be built on particular policies (e.g., what entities, events, and/or relationships should be included within the graph) and/or ontologies (the types of relationships that should be made with different types of entities and/or events). In this regard, particular graph projections can be generated for particular subscribers, users, systems, etc.

(38) Referring now to FIG. 1, a building data platform **100** including an edge platform **102**, a cloud platform **106**, and a twin manager **108** are shown, according to an exemplary embodiment. The edge platform **102**, the cloud platform **106**, and the twin manager **108** can each be separate services deployed on the same or different computing systems. In some embodiments, the cloud platform **106** and the twin manager **108** are implemented in off premises computing systems, e.g., outside a building. The edge platform **102** can be implemented on-premises, e.g., within the building.

(39) The building data platform **100** includes applications **110**. The applications **110** can be various applications that operate to manage the building subsystems **122**. The applications **110** can be remote or on-premises applications that run on various computing systems. The applications **110** can include an alarm application **168** configured to manage alarms for the building subsystems **122**. The applications **110** include an assurance application **170** that implements assurance services for the building subsystems **122**. In some embodiments, the applications **110** include an energy application **172** configured to manage the energy usage of the building subsystems **122**. The applications **110** include a security application **174** configured to manage security systems of the building.

(40) In some embodiments, the applications **110** and/or the cloud platform **106** interacts with a user device **176**. In some embodiments, a component or an entire application of the applications **110** runs on the user device **176**. The user device **176** may be a laptop computer, a desktop computer, a smartphone, a tablet, and/or any other device with an input interface (e.g., touch screen, mouse, keyboard, etc.) and an output interface (e.g., a speaker, a display, etc.).

(41) The applications **110**, the twin manager **108**, the cloud platform **106**, and the edge platform **102** can be implemented on one or more computing systems, e.g., on processors and/or memory devices. For example, the edge platform **102** includes processor(s) **118** and memories **120**, the cloud platform **106** includes processor(s) **124** and memories **126**, the applications **110** include processor(s) **164** and memories **166**, and the twin manager **108** includes processor(s) **148** and memories **150**.

(42) The processors can be a general purpose or specific purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. The processors may be configured to execute computer code and/or instructions stored in the memories or received from other computer readable media (e.g., CDROM, network storage, a remote server, etc.).

(43) The memories can include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. The memories can include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. The memories can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. The memories can be communicably connected to the processors and can include computer code for executing (e.g., by the processors) one or more processes described herein.

(44) The edge platform **102** can be configured to provide connection to the building subsystems **122**. The edge platform **102** can receive messages from the building subsystems **122** and/or deliver messages to the building subsystems **122**. The edge platform **102** includes one or multiple gateways, e.g., the gateways **112-116**. The gateways **112-116** can act as a gateway between the cloud platform **106** and the building

subsystems **122**. The gateways **112-116** can be the gateways described in U.S. Provisional Patent Application No. 62/951,897 filed Dec. 20, 2019, the entirety of which is incorporated by reference herein. In some embodiments, the applications **110** can be deployed on the edge platform **102**. In this regard, lower latency in management of the building subsystems **122** can be realized.

(45) The edge platform **102** can be connected to the cloud platform **106** via a network **104**. The network **104** can communicatively couple the devices and systems of building data platform **100**. In some embodiments, the network **104** is at least one of and/or a combination of a Wi-Fi network, a wired Ethernet network, a ZigBee network, a Bluetooth network, and/or any other wireless network. The network **104** may be a local area network or a wide area network (e.g., the Internet, a building WAN, etc.) and may use a variety of communications protocols (e.g., BACnet, IP, LON, etc.). The network **104** may include routers, modems, servers, cell towers, satellites, and/or network switches. The network **104** may be a combination of wired and wireless networks.

(46) The cloud platform **106** can be configured to facilitate communication and routing of messages between the applications **110**, the twin manager **108**, the edge platform **102**, and/or any other system. The cloud platform **106** can include a platform manager **128**, a messaging manager **140**, a command processor **136**, and an enrichment manager **138**. In some embodiments, the cloud platform **106** can facilitate messaging between the building data platform **100** via the network **104**.

(47) The messaging manager **140** can be configured to operate as a transport service that controls communication with the building subsystems **122** and/or any other system, e.g., managing commands to devices (C2D), commands to connectors (C2C) for external systems, commands from the device to the cloud (D2C), and/or notifications. The messaging manager **140** can receive different types of data from the applications **110**, the twin manager **108**, and/or the edge platform **102**. The messaging manager **140** can receive change on value data **142**, e.g., data that indicates that a value of a point has changed. The messaging manager **140** can receive timeseries data **144**, e.g., a time correlated series of data entries each associated with a particular time stamp. Furthermore, the messaging manager **140** can receive command data **146**. All of the messages handled by the cloud platform **106** can be handled as an event, e.g., the data **142-146** can each be packaged as an event with a data value occurring at a particular time (e.g., a temperature measurement made at a particular time).

(48) The cloud platform **106** includes a command processor **136**. The command processor **136** can be configured to receive commands to perform an action from the applications **110**, the building subsystems **122**, the user device **176**, etc. The command processor **136** can manage the commands, determine whether the commanding system is authorized to perform the particular commands, and communicate the commands to the commanded system, e.g., the building subsystems **122** and/or the applications **110**. The commands could be a command to change an operational setting that control environmental conditions of a building, a command to run analytics, etc.

(49) The cloud platform **106** includes an enrichment manager **138**. The enrichment manager **138** can be configured to enrich the events received by the messaging manager **140**. The enrichment manager **138** can be configured to add contextual information to the events. The enrichment manager **138** can communicate with the twin manager **108** to retrieve the contextual information. In some embodiments, the contextual information is an indication of information related to the event. For example, if the event is a timeseries temperature measurement of a thermostat, contextual information such as the location of the thermostat (e.g., what room), the equipment controlled by the thermostat (e.g., what VAV), etc. can be added to the event. In this regard, when a consuming application, e.g., one of the applications **110** receives the event, the consuming application can operate based on the data of the event, the temperature measurement, and also the contextual information of the event.

(50) The enrichment manager **138** can solve a problem that when a device produces a significant amount of information, the information may contain simple data without context. An example might include the data generated when a user scans a badge at a badge scanner of the building subsystems **122**. This physical event can generate an output event including such information as “DeviceBadgeScannerID,” “BadgeID,” and/or “Date/Time.” However, if a system sends this data to a consuming application, e.g., Consumer A and a Consumer B, each customer may need to call the building data platform knowledge service to query information with queries such as, “What space, build, floor is that badge scanner in?” or “What user is associated with that badge?”

(51) By performing enrichment on the data feed, a system can be able to perform inferences on the data. A

result of the enrichment may be transformation of the message “DeviceBadgeScannerId, BadgeId, Date/Time,” to “Region, Building, Floor, Asset, DeviceId, BadgeId, UserName, EmployeeId, Date/Time Scanned.” This can be a significant optimization, as a system can reduce the number of calls by $1/n$, where n is the number of consumers of this data feed.

(52) By using this enrichment, a system can also have the ability to filter out undesired events. If there are 100 building in a campus that receive 100,000 events per building each hour, but only 1 building is actually commissioned, only $1/10$ of the events are enriched. By looking at what events are enriched and what events are not enriched, a system can do traffic shaping of forwarding of these events to reduce the cost of forwarding events that no consuming application wants or reads.

(53) An example of an event received by the enrichment manager **138** may be:

(54) TABLE-US-00001 { “id”: “someguid”, “eventType”: “Device_Heartbeat”, “eventTime”: “2018-01-27T00:00:00+00:00” “eventValue”: 1, “deviceId”: “someguid” }

(55) An example of an enriched event generated by the enrichment manager **138** may be:

(56) TABLE-US-00002 { “id”: “someguid”, “eventType”: “Device_Heartbeat”, “eventTime”: “2018-01-27T00:00:00+00:00” “eventValue”: 1, “deviceId”: “someguid”, “buildingName”: “Building-48”, “buildingID”: “SomeGuid”, “panelID”: “SomeGuid”, “panelName”: “Building-48-Panel-13”, “cityID”: 371, “cityName”: “Milwaukee”, “stateID”: 48, “stateName”: “Wisconsin (WI)”, “countryID”: 1, “countryName”: “United States” }

(57) By receiving enriched events, an application of the applications **110** can be able to populate and/or filter what events are associated with what areas. Furthermore, user interface generating applications can generate user interfaces that include the contextual information based on the enriched events.

(58) The cloud platform **106** includes a platform manager **128**. The platform manager **128** can be configured to manage the users and/or subscriptions of the cloud platform **106**. For example, what subscribing building, user, and/or tenant utilizes the cloud platform **106**. The platform manager **128** includes a provisioning service **130** configured to provision the cloud platform **106**, the edge platform **102**, and the twin manager **108**. The platform manager **128** includes a subscription service **132** configured to manage a subscription of the building, user, and/or tenant while the entitlement service **134** can track entitlements of the buildings, users, and/or tenants.

(59) The twin manager **108** can be configured to manage and maintain a digital twin. The digital twin can be a digital representation of the physical environment, e.g., a building. The twin manager **108** can include a change feed generator **152**, a schema and ontology **154**, a projection manager **156**, a policy manager **158**, an entity, relationship, and event database **160**, and a graph projection database **162**.

(60) The graph projection manager **156** can be configured to construct graph projections and store the graph projections in the graph projection database **162**. Examples of graph projections are shown in FIGS. **11-13**. Entities, relationships, and events can be stored in the database **160**. The graph projection manager **156** can retrieve entities, relationships, and/or events from the database **160** and construct a graph projection based on the retrieved entities, relationships and/or events. In some embodiments, the database **160** includes an entity-relationship collection for multiple subscriptions. Subscriptions can be subscriptions of a particular tenant as described in FIG. **24**.

(61) In some embodiment, the graph projection manager **156** generates a graph projection for a particular user, application, subscription, and/or system. In this regard, the graph projection can be generated based on policies for the particular user, application, and/or system in addition to an ontology specific for that user, application, and/or system. In this regard, an entity could request a graph projection and the graph projection manager **156** can be configured to generate the graph projection for the entity based on policies and an ontology specific to the entity. The policies can indicate what entities, relationships, and/or events the entity has access to. The ontology can indicate what types of relationships between entities the requesting entity expects to see, e.g., floors within a building, devices within a floor, etc. Another requesting entity may have an ontology to see devices within a building and applications for the devices within the graph.

(62) The graph projections generated by the graph projection manager **156** and stored in the graph projection database **162** can be a knowledge graph and is an integration point. For example, the graph projections can represent floor plans and systems associated with each floor. Furthermore, the graph projections can include events, e.g., telemetry data of the building subsystems **122**. The graph projections can show application services as nodes and API calls between the services as edges in the graph. The

graph projections can illustrate the capabilities of spaces, users, and/or devices. The graph projections can include indications of the building subsystems **122**, e.g., thermostats, cameras, VAVs, etc. The graph projection database **162** can store graph projections that keep up a current state of a building.

(63) In some embodiments the enrichment manager **138** can use a graph projection of the graph projection database **162** to enrich events. In some embodiments, the enrichment manager **138** can identify nodes and relationships that are associated with, and are pertinent to, the device that generated the event. For example, the enrichment manager **138** could identify a thermostat generating a temperature measurement event within the graph. The enrichment manager **138** can identify relationships between the thermostat and spaces, e.g., a zone that the thermostat is located in. The enrichment manager **138** can add an indication of the zone to the event.

(64) Furthermore, the command processor **136** can be configured to utilize the graph projections to command the building subsystems **122**. The command processor **136** can identify a policy for a commanding entity within the graph projection to determine whether the commanding entity has the ability to make the command. For example, the command processor **136**, before allowing a user to make a command, determine, based on the graph projection database **162**, to determine that the user has a policy to be able to make the command.

(65) In some embodiments, the policies can be conditional based policies. For example, the building data platform **100** can apply one or more conditional rules to determine whether a particular system has the ability to perform an action. In some embodiments, the rules analyze a behavioral based biometric. For example, a behavioral based biometric can indicate normal behavior and/or normal behavior rules for a system. In some embodiments, when the building data platform **100** determines, based on the one or more conditional rules, that an action requested by a system does not match a normal behavior, the building data platform **100** can deny the system the ability to perform the action and/or request approval from a higher level system.





(66) For example, a behavior rule could indicate that a user has access to log into a system with a particular IP address between 8 A.M. through 5 P.M. However, if the user logs in to the system at 7 P.M., the building data platform **110** may contact an administrator to determine whether to give the user permission to log in.



(67) The change feed generator **152** can be configured to generate a feed of events that indicate changes to the digital twin, e.g., to the graph. The change feed generator **152** can track changes to the entities, relationships, and/or events of the graph. For example, the change feed generator **152** can detect an addition, deletion, and/or modification of a node or edge of the graph, e.g., changing the entities, relationships, and/or events within the database **160**. In response to detecting a change to the graph, the change feed generator **152** can generate an event summarizing the change. The event can indicate what nodes and/or edges have changed and how the nodes and edges have changed. The events can be posted to a topic by the change feed generator **152**.

(68) The change feed generator **152** can implement a change feed of a knowledge graph. The building data platform **100** can implement a subscription to changes in the knowledge graph. When the change feed generator **152** posts events in the change feed, subscribing systems or applications can receive the change feed event. By generating a record of all changes that have happened, a system can stage data in different ways, and then replay the data back in whatever order the system wishes. This can include running the changes sequentially one by one and/or by jumping from one major change to the next. For example, to generate a graph at a particular time, all change feed events up to the particular time can be used to construct the graph.

(69) The change feed can track the changes in each node in the graph and the relationships related to them, in some embodiments. If a user wants to subscribe to these changes and the user has proper access, the user can simply submit a web API call to have sequential notifications of each change that happens in the graph. A user and/or system can replay the changes one by one to reinstitute the graph at any given time slice. Even though the messages are “thin” and only include notification of change and the reference “id/seq id,” the change feed can keep a copy of every state of each node and/or relationship so that a user and/or system can retrieve those past states at any time for each node. Furthermore, a consumer of the change feed could also create dynamic “views” allowing different “snapshots” in time of what the graph looks like from a particular context. While the twin manager **108** may contain the history and the current state of the graph based upon schema evaluation, a consumer can retain a copy of that data, and thereby

create dynamic views using the change feed.

(70) The schema and ontology **154** can define the message schema and graph ontology of the twin manager **108**. The message schema can define what format messages received by the messaging manager **140** should have, e.g., what parameters, what formats, etc. The ontology can define graph projections, e.g., the ontology that a user wishes to view. For example, various systems, applications, and/or users can be associated with a graph ontology. Accordingly, when the graph projection manager **156** generates an graph projection for a user, system, or subscription, the graph projection manager **156** can generate a graph projection according to the ontology specific to the user. For example, the ontology can define what types of entities are related in what order in a graph, for example, for the ontology for a subscription of “Customer A,” the graph projection manager **156** can create relationships for a graph projection based on the rule: Regioncustom characterBuildingcustom characterFloorcustom characterSpacecustom characterAsset

(71) For the ontology of a subscription of “Customer B,” the graph projection manager **156** can create relationships based on the rule: Buildingcustom characterFloorcustom characterAsset

(72) The policy manager **158** can be configured to respond to requests from other applications and/or systems for policies. The policy manager **158** can consult a graph projection to determine what permissions different applications, users, and/or devices have. The graph projection can indicate various permissions that different types of entities have and the policy manager **158** can search the graph projection to identify the permissions of a particular entity. The policy manager **158** can facilitate fine grain access control with user permissions. The policy manager **158** can apply permissions across a graph, e.g., if “user can view all data associated with floor **1**” then they see all subsystem data for that floor, e.g., surveillance cameras, HVAC devices, fire detection and response devices, etc.

(73) Referring now to FIG. **2**, the cloud platform **106** and the twin manager **108** processing an event received from the edge platform **102** is shown, according to an exemplary embodiment. The cloud platform **106** includes a preprocessor **202**, topics **204**, the enrichment manager **138**, and enriched events **208**. The twin manager **108** is shown to include the entity, relationship, and event database **160**, the schema and ontology **154**, and the projection manager **156**. The projection manager **156** includes the policy manager **158**, a graph projection generator **210**, and the graph projection database **162**.

(74) Data received from the edge platform **102**, or any other system described herein, can be converted into an event if the data is not already formatted as an event by the messaging manager **140**. The messaging manager **140** can provide events to the preprocessor **202**. The preprocessor **202** can analyze the events to make sure the events are formatted properly. For example, the preprocessor **202** can make a call to the schema and ontology **154** of the twin manager **108** to identify the schema for the event. The preprocessor **202** can determine whether the format of the event is correct based on the schema.

(75) Furthermore, the preprocessor **202** can identify what topic the event belongs to, e.g., whether the event relates to a change for the graph projection database **162** or whether the event relates to telemetry data of a building. The preprocessor **202** can provide the event to the appropriate topics of the topics **204**.

(76) The enrichment manager **138** can be configured to enrich the events of one or more particular topics of the topics **204**. The enrichment manager **138** can receive a schema for enrichment and a graph projection for enrichment. In some embodiments, the ontology received by the enrichment manager **138** can define enrichment rules for particular types of events, e.g., what information should be shown for particular events. For example, for an event of a thermostat, the rules may define that location and equipment being controlled by the thermostat should be enriched into the event.

(77) The graph projection including all of the nodes and edges that define the contextual information associated with the event can be received by the enrichment manager **138** from the graph projection database **162**. The received projection can include the information that is added into the events as part of the enrichment. The enriched events **208** are then provided to the applications **110** for processing where the applications **110** operate based on the original data of the event as well as the contextual information enriched into the event.

(78) The graph projection generator **210** is shown to receive data from the entity, relationship, and event database **160**. Furthermore, the graph projection generator **210** can receive an ontology from the schema and ontology **154**. The graph projection generator **210** can generate a graph projection based on the ontology and the data received from the database **160**. The graph projection can be stored in the graph projection database **162**. Furthermore, the policy manager **158** can select different ontologies to provide to

the graph projection generator **210** and/or the enrichment manager **138**. In this regard, based on the entity (e.g., application or system) that will be consuming a graph projection and/or receiving an enriched event, the policy manager **158** can select an ontology specific to the entity.

(79) Referring now to FIG. **3**, the cloud platform **106** processing events is shown, according to an exemplary embodiment. The preprocessor **202** receives events and processes the events through a consumer feed filter. The consumer feed filter can filter events into particular topics for consumption by various consumers, e.g., for particular event topics **324**. In this regard, a particular application or system can create a subscription in the topic to subscription map **302** and the corresponding events of a topic can be added to the topic of the event topics **324**.

(80) The preprocessor **202** includes a schema validator **306**. The schema validator can make a call to the schema and ontology **154** and receive a schema or set of schemas for validating the events to determine whether the event is formatted in an allowed schema and/or includes the minimum fields. If the event is properly formatted (e.g., matches an approved schema of the schema and ontology **154**), the event can be provided to a router **308**. If the event is not properly formatted, the event can be added to the malformed device tree **336**. A user and/or analysis system can review the malformed device tree **336** to determine system configuration errors. For example, the cloud platform **106** could identify improper graph configurations where nodes or relationships are missing within the graph.

(81) The router **308** can add the event to one or more topics of the topic **204**. One topic of the topics **310** is a change feed topic **310**. Graph change feed events are created by the change feed generator **152** and added to the change feed topic **310**. The topics **204** further include raw events topic **312**, metadata topic **314**, and device tree topic **316**. The router can fan the event into various topics based on a type of the event.

(82) The metadata topic **314** can include metadata **320**. The metadata may be data describing entities (e.g., equipment) and/or capabilities and/or policies associated with the entities. During a discovery phase that the cloud platform **106** can be configured to operate in, where equipment is discovered by the cloud platform **106**, or during a normal operating mode of the cloud platform **106**, metadata events can be added to the metadata topic **314** to update the entities, relationships, and events of the database **160**, e.g., build up the graph projections.

(83) In some embodiments, all events are added into the raw event topic. In some embodiments, if an event relates to how the graph is represented, the event is added into the metadata topic **314**. In some embodiments, if the event represents a new device or set of devices, the device is added to the device tree topic **316**. In some embodiments, the device tree data of the device tree topic **316** can be a type of event that describes an object or asset discovered by the cloud platform **106** that contains the relationship of that object to other objects of similar context

(84) A raw event **318** of the raw events topic **312** can be provided to the enrichment manager **206** for enrichment. The enrichment manager **206** can receive a graph projection from the graph projection database **162** and enrich the raw event **318** based on context of the graph projection. In some embodiments, the enrichment manager **206** can enrich the raw event **318** based on one or more user rules. For example, the rules could be to enrich indications of assets shown within a field of view of a camera where the event is a frame or set of frames captured by the camera. The enriched events can be enriched based on destination. For example, the event can be enriched according to the system that will be receiving the event. In this regard, the event can be enriched multiple different times for multiple different receiving systems.

(85) Enrichment may help systems operate quickly. For example, a person may scan a badge at a door. An application may look up the user of the badge with the badge number. Furthermore, the application may look up what equipment and what place the scanner is associated with. However, by performing multiple searches, the processing of the applications may be slow. However, with the enrichment of the enrichment manager **206**, a telemetry event such as scanning a door badge can add floor indications, user identifications, etc. so that the receiving application can operate on the event and contextual information without needing to search for and/or retrieve the contextual information.

(86) The enriched event can be added to the event topics **324**. The event topics **324** can be subscribed to by various systems. For example, a graph projection processor **326** can make updates to projections of the graph projection database **162** based on the enriched event. For examples telemetry data could be added to the graph projection database **162**, statuses of equipment could be added to the graph projection database **162**, etc. The persist service **328** can persist the enriched events in an events database **332**. Furthermore, a

publisher **330** can provide the enriched events to the applications **110**, e.g., to particular applications subscribed to the enriched events.

(87) Referring now to FIG. **4**, the twin manager **108** generating projections and operating with components of the cloud platform **106** to enrich events is shown, according to an exemplary embodiment. The twin manager **108** includes an event manager **404**. The event manager can receive data from a user device and/or another system. The event manager **404** can receive an addition of an event type, an addition of an event stream, a new event, and/or a new event subscription. Based on the received information, the event manager **404** can be configured to update the topic to subscription map **408**. Furthermore, if the received information indicates changes to the graph projections of the graph projection database **162**, the event manager **404** can be configured to generate a change event for a change feed.

(88) The twin manager **108** includes a query manager **402**. The query manager **402** can receive a query or a post from a user device or another system. The query manager **402** can be configured to query the entity, relationship, and/or event database **160** based on the query. An ontology received from the schema and ontology **154** can define the query that the query manager **402** makes to the database **160**. In some embodiments, the query manager **402** can be configured to upsert new entities, relationships, and/or events into the database **160**. In some embodiments, the query manager **402** constructs a query or determines whether to upsert information to the database **160** based on an access control list received from the policy manager **158**. In this regard, the entity requesting information through a query or sending a post of new information can be verified for having the proper access policy by the policy manager **158** and the query manager **402**.

(89) The policy manager **158** is shown to receive projections from the graph projection generator **210**. In some embodiments, the policy manager **158** can receive the projections from the graph projection database **162**. The policy manager **158** can be configured to receive a request for access to information and can review the graph to determine whether the requesting entity has the proper access to the information. The policy manager **158** can serve access control lists determined from the graph projections to the query manager **402**. The policy manager **158** can serve the access control list to the schema and ontology **154** for use in providing an ontology to the enrichment manager **206** and/or for user in determining projection rules for the graph projection generator **210**.

(90) Referring now to FIG. **5**, a preprocessing workflow **500** performed by the cloud platform **106** to preprocess events is shown, according to an exemplary embodiment. Events can be received by the platform **106**. The cloud platform **106** can filter the events in step **502**. The events can be filtered into schema discovery, e.g., a new message schema, for filtering into an existing schema message category. Furthermore, in step **502**, the cloud platform **106** can add subscription identifier and entity information to the event. For example, the subscription identifier can be looked up in step **504** via the topic to subscription map **408**. The entity information can indicate the entity related to the event, e.g., the entity that created the event. For example, a thermostat, the entity, may have generated a temperature measurement, the event.

(91) If the message is for a schema discovery (step **506**), the cloud platform **106** can post the schema used in the message in the schema and ontology **154** or alternatively proceed to step **512**. In step **508**, the cloud platform **106** can lookup valid message schemas from the schema and ontology **154**. In step **512**, the cloud platform **106** can determine whether the schema of the event is valid or invalid based on the valid message schemas. In step **514**, if the schema is invalid, the event can be added to an invalid schema deadletter where invalid schema events are stored. If the schema is valid, the event can be routed to message topics based on a type of the message in step **516**, e.g., whether the event is metadata, a raw event, etc.

(92) Referring now to FIG. **6**, a discovery workflow **600** discovering new entities from metadata **314** and a device tree **322** that is performed by the cloud platform **106** is shown, according to an exemplary embodiment. The cloud platform **106** can receive the metadata **314** and start a process timer in step **602**. In step **604**, the cloud platform **106** can transform and map device, type, and capabilities. The cloud platform **106** can reference a missing type to schema mapping. In step **610**, the cloud platform **106** can look up a reference mapping for the metadata, definitions of entities for the metadata, a tenant associated with the metadata, and/or other information of an entity relationship collection. In step **608**, the new device types can be persisted as metadata **616** and added to a metadata device table **614**.

(93) In step **628**, the cloud platform **106** can start a process timer in response to receiving the device tree **322**. The device tree **322** can be analyzed to determine what action, e.g., verb, operation, or subject

included within the device tree **322** is to be performed. The action may be an insert, update, or delete command for the graph projections. In step **618**, the cloud platform **106** can transform or map the device tree based on metadata stored in the device metadata **616**. In step **634**, the cloud platform **106** can evaluate the process and determine if a message has already been processed. In step **620** the processor cost can be calculated and in step **622** the event can be logged in the processing log **613**. In step **636** the new data for insertion, updating, and/or deletion can be posted.

(94) In response to receiving the device tree **322**, the cloud platform **106** can start a process timer in step **628**. The cloud platform **106** can analyze the device tree **322** for a verb, operation, and/or subject to construct an insert command, an update command, and/or a delete command **632**.

(95) Referring now to FIG. 7, a projection workflow **700** performed by the twin manager **108** is shown, according to an exemplary embodiment. In step **702**, the twin manager **108** can receive a change feed event from the change feed generator **152**. Based on the change feed event, in step **704**, the twin manager **108** can generate a graph projection and store the graph projection. The twin manager **108** can edit existing graph projections of the graph projection database **162** based on the change feed event. The twin manager **108** can replace an existing graph projection of the graph projection database **162** with a new graph projection created responsive to receiving the change feed event.

(96) The twin manager **108** can receive a query from the query manager **706**. The query may be a query for information of a graph projection and/or a query for a graph projection itself. The query can originate from a requesting application, system, or user device. The twin manager **108** can, in step **708**, retrieve a graph projection based on a policy for the requesting system.

(97) The twin manager **108** can retrieve policies from a policy database **161** to determine which graph projection the querying system has access to. In response to retrieving the appropriate graph projection from the graph projection database **162**, the twin manager **108** can construct a query response including the specific information from the graph projection and/or the graph projection itself. The twin manager **108** can return the query response to the query manager **706**.

(98) Referring now to FIG. 8, an enrichment workflow **800** performed by the cloud platform **106** enriching events with contextual information is shown, according to an exemplary embodiment. The cloud platform **106** receives an internal event **802**, metadata **320**, a device tree **322**, and a raw event **314**. The internal event **802** may be an event created by the building data platform **100** requiring enrichment. Each data element received can be enriched according to the workflow **800**.

(99) In step **806**, in response to receiving an event, a process timer can be started. In step **808**, the cloud platform **106** can get an event type for the event from an event type storage **812** and a projection type from a projection type storage **814**. In this regard, a projection type specific to the event can be retrieved. The specific projection identified can be retrieved in step **810** and entities and relationships specific for enriching the event can be retrieved from the graph projection. Based on the entities and relationships, a custom enrichment can be generated in step **816** for the event.

(100) In some embodiments, some events may not be associated with any event type and/or projection type. In response to identifying an event that cannot be enriched, the cloud platform **106** can add the event to a dead letter **820**. The dead letter **820** can be reviewed by users and/or systems to identify errors in the operation of the cloud platform **106** and/or issues with the systems creating the events.

(101) Referring now to FIG. 9, a command processing workflow **900** performed by the cloud platform **106** where commands are sent to devices or are communicated to an external system via a connection broker is shown, according to an exemplary embodiment. The cloud platform **106** can receive an internal command **902** and/or an external command **904**. The internal command **902** can be a command generated by a component of the building data platform **100**. The external command **904** can be a command generated by an external device or system, e.g., the user device **176**.

(102) In step **906**, the internal command **902** and/or the external command **904** can be received and a process timer started. In step **908**, the cloud platform **106** can authorize the command to determine whether the entity requesting the command is authorized to perform the command. For example, the cloud platform **106** can search a graph projection of the graph projection database **162** for policies and capabilities to determine whether the requesting entity has access to make the command that the entity is making.

(103) If the command is not authorized, in step **910** the event can be logged in a processing log **912**. In step **914**, the cloud platform **106** can determine whether the command is a command for a device of the

building subsystems **122**, e.g., a command to device (C2D) command or a command for an external system that will be handled via a connector, a command to connector (C2C) command. In response to the command being a C2D command, the cloud platform **106** can enqueue the message to be sent to a device via a device hub in step **916**. The cloud platform **106** can consult a graph projection to identify the device hub responsible for handling commands for the device.

(104) If the command is a C2C command, the cloud platform **106** can select a connection broker **918** in step **922**. The connection broker **918** can be a component configured to communicate and integrate with external systems, e.g., the external system **920**. For example, an office program suite, a virtual meeting platform, an email server, etc. can all integrate with the building data platform **100** via the connection broker **918**. The cloud platform **106** can select the appropriate connection broker for the command by searching a graph projection of the graph projection database **162**.

(105) Referring now to FIG. **10**, a messaging workflow **1000** performed by the cloud platform **106** where messages of building subsystems **122** are received via the edge platform **102** and commands for the building subsystems **122** are communicated to the building subsystems **122** via the edge platform **102** is shown, according to an exemplary embodiment. The cloud platform **106** can receive data events from building subsystems **122** via an edge platform **102** through device hubs **1002** and **1004** specific to devices of the building subsystems **122**.

(106) The device hubs **1002** and **1004** can post events into topics **1006** and **1008**. A source identifier **1010** subscribed to the topics **1006** and **1008** can look up an identifier of the device hub based on an identifier of the device and post the event into a data feed topic **1011** associated with the device hub in a device hub identifier mapping to device identifier **1012**. An event handler **1018** can provide the event to the preprocessor **202**.

(107) The C2D command of the command processing workflow **900**. The command can be posted in a C2D message topic **1014**. A command processor **1016** subscribed to the C2D message topic **1014** can read the C2D messages and provide the C2D commands to the appropriate device topics, e.g., topic **1006** or topic **1008**. The device hubs **1002** and/or **1004** can pick up the C2D commands and operate the building subsystems **122** via the C2D command.

(108) Referring now to FIG. **11**, a graph projection **1100** of the twin manager **108** including application programming interface (API) data, capability data, policy data, and services is shown, according to an exemplary embodiment. The graph projection **1100** includes nodes **1102-1140** and edges **1150-1172**. The nodes **1102-1140** and the edges **1150-1172** are defined according to the key **1101**. The nodes **1102-1140** represent different types of entities, devices, locations, points, persons, policies, and software services (e.g., API services). The edges **1150-1172** represent relationships between the nodes **1102-1140**, e.g., dependent calls, API calls, inferred relationships, and schema relationships (e.g., BRICK relationships).

(109) The graph projection **1100** includes a device hub **1102** which may represent a software service that facilitates the communication of data and commands between the cloud platform **106** and a device of the building subsystems **122**, e.g., door actuator **1114**. The device hub **1102** is related to a connector **1104**, an external system **1106**, and a digital asset “Door Actuator” **1108** by edge **1150**, edge **1152**, and edge **1154**.

(110) The cloud platform **106** can be configured to identify the device hub **1102**, the connector **1104**, the external system **1106** related to the door actuator **1114** by searching the graph projection **1100** and identifying the edges **1150-1154** and edge **1158**. The graph projection **1100** includes a digital representation of the “Door Actuator,” node **1108**. The digital asset “Door Actuator” **1108** includes a “DeviceNameSpace” represented by node **1108** and related to the digital asset “Door Actuator” **1108** by the “Property of Object” edge **1156**.

(111) The “Door Actuator” **1114** has points and timeseries. The “Door Actuator” **1114** is related to “Point A” **1116** by a “has_a” edge **1160**. The “Door Actuator” **1114** is related to “Point B” **1118** by a “has_A” edge **1158**. Furthermore, timeseries associated with the points A and B are represented by nodes “TS” **1120** and “TS” **1122**. The timeseries are related to the points A and B by “has_a” edge **1164** and “has_a” edge **1162**. The timeseries “TS” **1120** has particular samples, sample **1110** and **1112** each related to “TS” **1120** with edges **1168** and **1166** respectively. Each sample includes a time and a value. Each sample may be an event received from the door actuator that the cloud platform **106** ingests into the entity, relationship, and event database **160**, e.g., ingests into the graph projection **1100**.

(112) The graph projection **1100** includes a building **1134** representing a physical building. The building includes a floor represented by floor **1132** related to the building **1134** by the “has_a” edge from the

building **1134** to the floor **1132**. The floor has a space indicated by the edge “has_a” **1170** between the floor **1132** and the space **1130**. The space has particular capabilities, e.g., is a room that can be booked for a meeting, conference, private study time, etc. Furthermore, the booking can be canceled. The capabilities for the floor **1132** are represented by capabilities **1128** related to space **1130** by edge **1180**. The capabilities **1128** are related to two different commands, command “book room” **1124** and command “cancel booking” **1126** related to capabilities **1128** by edge **1184** and edge **1182** respectively.

(113) If the cloud platform **106** receives a command to book the space represented by the node, space **1130**, the cloud platform **106** can search the graph projection **1100** for the capabilities for the **1128** related to the space **1128** to determine whether the cloud platform **106** can book the room.

(114) In some embodiments, the cloud platform **106** could receive a request to book a room in a particular building, e.g., the building **1134**. The cloud platform **106** could search the graph projection **1100** to identify spaces that have the capabilities to be booked, e.g., identify the space **1130** based on the capabilities **1128** related to the space **1130**. The cloud platform **106** can reply to the request with an indication of the space and allow the requesting entity to book the space **1130**.

(115) The graph projection **1100** includes a policy **1136** for the floor **1132**. The policy **1136** is related set for the floor **1132** based on a “To Floor” edge **1174** between the policy **136** and the floor **1132**. The policy **1136** is related to different roles for the floor **1132**, read events **1138** and send command **1140**. The policy **1136** is set for the entity **1103** based on has edge **1151** between the entity **1103** and the policy **1136**.

(116) The twin manager **108** can identify policies for particular entities, e.g., users, software applications, systems, devices, etc. based on the policy **1136**. For example, if the cloud platform **106** receives a command to book the space **1130**. The cloud platform **106** can communicate with the twin manager **108** to verify that the entity requesting to book the space **1130** has a policy to book the space. The twin manager **108** can identify the entity requesting to book the space as the entity **1103** by searching the graph projection **1100**. Furthermore, the twin manager **108** can further identify the edge has **1151** between the entity **1103** and the policy **1136** and the edge **1178** between the policy **1136** and the command **1140**.

(117) Furthermore, the twin manager **108** can identify that the entity **1103** has the ability to command the space **1130** based on the edge **1174** between the policy **1136** and the edge **1170** between the floor **1132** and the space **1130**. In response to identifying the entity **1103** has the ability to book the space **1130**, the twin manager **108** can provide an indication to the cloud platform **106**.

(118) Furthermore, if the entity makes a request to read events for the space **1130**, e.g., the sample **1110** and the sample **1112**, the twin manager **108** can identify the edge has **1151** between the entity **1103** and the policy **1136**, the edge **1178** between the policy **1136** and the read events **1138**, the edge **1174** between the policy **1136** and the floor **1132**, the “has_a” edge **1170** between the floor **1132** and the space **1130**, the edge **1168** between the space **1130** and the door actuator **1114**, the edge **1160** between the door actuator **1114** and the point A **1116**, the “has_a” edge **1164** between the point A **1116** and the TS **1120**, and the edges **1168** and **1166** between the TS **1120** and the samples **1110** and **1112** respectively.

(119) Referring now to FIG. **12**, a graph projection **1200** of the twin manager **108** including application programming interface (API) data, capability data, policy data, and services is shown, according to an exemplary embodiment. The graph projection **1200** includes the nodes and edges described in the graph projection **1100** of FIG. **11**. The graph projection **1200** includes a connection broker **1254** related to capabilities **1128** by edge **1298a**. The connection broker **1254** can be a node representing a software application configured to facilitate a connection with another software application. In some embodiments, the cloud platform **106** can identify the system that implements the capabilities **1128** by identifying the edge **1298a** between the capabilities **1128** and the connection broker **1254**.

(120) The connection broker **1254** is related to an agent that optimizes a space **1256** via edge **1298b**. The agent represented by the node **1256** can book and cancel bookings for the space represented by the node **1130** based on the edge **1298b** between the connection broker **1254** and the node **1256** and the edge **1298a** between the capabilities **1128** and the connection broker **1254**.

(121) The connection broker **1254** is related to a cluster **1208** by edge **1298c**. Cluster **1208** is related to connector B **1201** via edge **1298e** and connector A **1206** via edge **1298d**. The connector A **1206** is related to an external subscription service **1204**. A connection broker **1210** is related to cluster **1208** via an edge **1211** representing a rest call that the connection broker represented by node **1210** can make to the cluster represented by cluster **1208**.

(122) The connection broker **1210** is related to a virtual meeting platform **1212** by an edge **1254**. The node

1212 represents an external system that represents a virtual meeting platform. The connection broker represented by node **1210** can represent a software component that facilitates a connection between the cloud platform **106** and the virtual meeting platform represented by node **1212**. When the cloud platform **106** needs to communicate with the virtual meeting platform represented by the node **1212**, the cloud platform **106** can identify the edge **1254** between the connection broker **1210** and the virtual meeting platform **1212** and select the connection broker represented by the node **1210** to facilitate communication with the virtual meeting platform represented by the node **1212**.

(123) A capabilities node **1218** can be connected to the connection broker **1210** via edge **1260**. The capabilities **1218** can be capabilities of the virtual meeting platform represented by the node **1212** and can be related to the node **1212** through the edge **1260** to the connection broker **1210** and the edge **1254** between the connection broker **1210** and the node **1212**. The capabilities **1218** can define capabilities of the virtual meeting platform represented by the node **1212**. The capabilities may be an invite bob command represented by node **1216** and an email bob command represented by node **1214**. The capabilities **1218** can be linked to a node **1220** representing a user, Bob. The cloud platform **106** can facilitate email commands to send emails to the user Bob via the email service represented by the node **1204**. Furthermore, the cloud platform **106** can facilitate sending an invite for a virtual meeting via the virtual meeting platform represented by the node **1212**.

(124) The node **1220** for the user Bob can be associated with the policy **1136** via the “has” edge **1264**. Furthermore, the node **1220** can have a “check policy” edge **1266** with a portal node **1224**. The portal node **1224** has an edge **1268** to the policy node **1136**. The portal node **1224** has an edge **1223** to a node **1226** representing a user input manager (UIM). The UIM node **1226** has an edge **1223** to a device API node **1228**. The door actuator node **1114** has an edge **1274** to the device API node **1228**. The door actuator **1114** has an edge **1235** to the connector virtual object **1234**. The device API node **1228** can be an API for the door actuator **1114**.

(125) The device API node **1228** is related to a transport connection broker **1230** via an edge **1229**. The transport connection broker **1230** is related to a device hub **1232** via an edge **1278**. The device hub represented by node **1232** can be a software component that hands the communication of data and commands for the door actuator **1114**. The cloud platform **106** can identify where to store data within the graph projection **1200** received from the door actuator by identifying the nodes and edges between the points **1116** and **1118** and the device hub node **1232**. Similarly, the cloud platform **1208** can identify commands for the door actuator that can be facilitated by the device hub represented by the node **1232**, e.g., by identifying edges between the device hub node **1232** and an open door node **1252** and an lock door node **1250**. The door actuator **114** has an edge “has mapped an asset” **1180** between the node **1114** and a capabilities node **1248**. The capabilities node **1248** and the nodes **1252** and **1250** are linked by edges **1296** and **1294**.

(126) The device hub **1232** is linked to a cluster **1236** via an edge **1284**. The cluster **1236** is linked to connector A **1240** and connector B **1238** by edges **1286** and the edge **1288**. The connector A **1240** and the connector B **1238** is linked to an external system **1244** via edges **1288** and **1290**. The external system **1244** is linked to a door actuator **1242** via an edge **1292**.

(127) Referring now to FIG. 13, a graph projection **1300** of the twin manager **108** including equipment and capability data for the equipment is shown, according to an exemplary embodiment. The graph projection **1300** includes nodes **1302-1356** and edges **1260-1398f**. The cloud platform **106** can search the graph projection **1300** to identify capabilities of different pieces of equipment.

(128) A building **120** node **1304** represents a particular building that includes two floors. A floor **1** node **1302** is linked to the building **120** node **1304** via edge **1360** while a floor **2** node **1306** is linked to the building **120** node **1304** via edge **1362**. The floor **2** includes a particular room **2023** represented by edge **1364** between floor **2** node **1306** and room **2023** node **1308**. Various pieces of equipment are included within the room **2023**. A light represented by light node **1316**, a bedside lamp node **1314**, a bedside lamp node **1312**, and a hallway light node **1310** are related to room **2023** node **1308** via edge **1366**, edge **1372**, edge **1370**, and edge **1368**.

(129) The light represented by light node **1316** is related to a light connector **1326** via edge **1384**. The light connector **1326** is related to multiple commands for the light represented by the light node **1316**. The commands may be a brightness setpoint **1324**, an on command **1326**, and a hue setpoint **1328**. The cloud platform **106** can receive a request to identify commands for the light represented by the light **1316** and

can identify the nodes **1324-1328** and provide an indication of the commands represented by the node **1324-1328** to the requesting entity. The requesting entity can then send commands for the commands represented by the nodes **1324-1328**.

(130) The bedside lamp node **1314** is linked to a bedside lamp connector **1381** via an edge **1313**. The connector **1381** is related to commands for the bedside lamp represented by the bedside lamp node **1314** via edges **1392**, **1396**, and **1394**. The command nodes are a brightness setpoint node **1332**, an on command node **1334**, and a color command **1340**. The hallway light **1310** is related to a hallway light connector **1346** via an edge **1398d**. The hallway light connector **1346** is linked to multiple commands for the hallway light node **1310** via edges **1398g**, **1398f**, and **1398e**. The commands are represented by an on command node **1352**, a hue setpoint node **1350**, and a light bulb activity node **1348**.

(131) The graph projection **1300** includes a name space node **1322** related to a server A node **1318** and a server B node **1320** via edges **1374** and **1376**. The name space node **1322** is related to the bedside lamp connector **1381**, the bedside lamp connector **1344**, and the hallway light connector **1346** via edges **1382**, **1380**, and **1378**.

(132) Referring now to FIG. **14**, a block diagram of a user interaction manager **1402** that handles user queries and requests is shown, according to an exemplary embodiment. The user interaction manager **1402** can be a component of the cloud platform **106**. The user interaction manager **1402** in some embodiments, is a system separate from the cloud platform **106**. The user interaction manager **1402** includes processor(s) **1404** and memories **1406**. The processor(s) **1404** and the memories **1406** can be similar to, or the same as, the processors and memories described with reference to FIG. **1**.

(133) The user interaction manager **1402** receives an APPLE query from the user device **176**. The user interaction manager **1402** can be configured to query the graph based on the APPLE query and generate a query response based on the APPLE query and return the query response to the user device **176**. Although the user device **176** is shown in FIG. **14** to send the APPLE query to the user interaction manager **1402** and receive the query response, any computing system can send a query and receive a query response from the user interaction manager **1402**, e.g., the applications **110**, the building subsystems **122**, etc.

(134) The APPLE query can include an asset parameter **1410**, a point parameter **1412**, a people parameter **1414**, a location parameter **1416**, and an event parameter **1418** that a query parser **1408** of the user interaction manager **1402** can utilize in querying a graph projection. The graph parser **1408** can query the graph with entities **1420** and/or relationships **1426** which can indicate capabilities **1434**, commands **1436**, schema type **1438** and/or entity relationship history **1440**.

(135) The user interaction manager **1402** can analyze event type registration **1422**, subscriptions to events **1424**, filtering for relevant events **1428**, validating events **1430**, identifying event history **1442**, and perform event enrichment **1444**. For example, events received at an ingress **1454** from a device hub **1452** can be validated according to a schema. If the validator **1430** determines that the entity is not of a valid schema, the validator **1430** can add the event to a dead letter **1456**.

(136) A policy evaluator **1432** of the user interaction manager **1402** can determine whether the user of the user device **176** (or another system or application) has the appropriate policies to view information of the graph and/or make the commands indicated by the user device **176**. The policy evaluator **1432** can determine whether or not to implement a command based on command policies for the user device **176** which may be indicated by a graph projection. Furthermore, the policy evaluator **1432** can determine whether or not to respond to a query based on whether the user device **176** has access to view the queried information. The policy evaluator **1432** can be configured to generate a policy projection **1476**. Data access **1446** and **1448** can provide access to assets, points, people, locations, and events. The data access **1446** and/or **1448** can retrieve data of the building subsystems **122** via the connector **1474** and/or via the database **1468** including entities **1472** and relationships **1470**. A data retention layer **1450** can retain a record of all queries and query responses.

(137) The user interaction manager **1402** can provide a UI for the provisioning service **130** to provision tenants. A tenant management system can provide tenant and/or subscription services for generating new customer subscriptions, e.g., subscriptions for a tenant of a building. Similarly, the provisioning service **130** can receive policies and/or device management commands from the tenant management system **1478** for creating a graph projection for the customer subscription.

(138) Referring now to FIG. **15**, a process **1500** of a security dashboard **1502** communicating with the building data platform **100** to review information about equipment and command the equipment is shown,

according to an exemplary embodiment. The process **1500** can be performed by the building data platform **100**. In some embodiments, the twin manager **108**, the applications **110**, and/or the cloud platform **106** can perform the process **1500**. In FIG. **15**, a security dashboard **1502**, the user interaction manager **1402**, a cache **1504**, a device interface manager **1506**, the policy manager **158**, and a transport manager **1510** are shown to perform the process **1500**. The aforementioned components can be components of the applications **110**, the twin manager **108**, and the cloud platform **106**.

(139) In step **1512**, the security dashboard **1502** can receive a command from a user to look at doors with active alarms on a particular floor, a second floor of a building. In some embodiments, the security dashboard **1502** is an application run by the applications **110**. In some embodiments, the user interacts with the security dashboard **1502** via the user device **176**.

(140) In step **1514**, the security dashboard **1502** queries the user interaction manager **1402** for assets and events, in particular, doors (assets) with an active alarm (event) on a second floor (asset). In step **1516**, the user interaction manager **1402** can get read permissions to an entity and relationship collection from the policy manager **158**. The policy manager **158** can determine which entities and/or events the user has access to based on policies indicated by a graph projection of the graph projection database **162**. The policy manager **158** can determine whether the user has access to read entities and/or relationships.

(141) In response to the user having access to read the entities and/or relationships, the policy manager **158** can send a granted indication in step **1518** to the user interaction manager **1402**. In step **1520**, the user interaction manager can get read permissions for events on the second floor from the policy manager **158**. The policy manager **158** can determine whether the user has access to the events of the second floor by searching a graph projection and can respond to the user interaction manager **1402** with a granted message in step **1522** in response to determining that the user has access to the events of the second floor.

(142) Responsive to receiving the access to read the entities, relationships, and events of the second floor, the user interaction manager **1402** can read the entities relationships, and events from the cache **1504**. In some embodiments, the user interaction manager **1402** can read the entities, relationships, and events from a graph projection in step **1524**.

(143) In step **1526**, the cache **1504** can return the requested data of the step **1534** to the user interaction manager **1402**. In step **1528**, the user interaction manager **1402** can return the filtered assets with capabilities of the assets. For example, all doors on the second floor can be returned in step **1528** along with a capability to command each door to lock or unlock. In step **1530**, the security dashboard **1502** can display doors with active alarms on the second floor along with capabilities of the doors.

(144) In step **1532**, a user can click a particular door displayed in the step **1530**, e.g., a door **13**, and select the command to lock the door. In step **1534**, the security dashboard **1502** can send a lock door command for door **13** to the user interaction manager **1402**. The user interaction manager **1402** can get a send command permission for the door **13** from the policy manager **158** in step **1536**. The policy manager **158** can determine, based on a graph projection, whether the user has access to command the door **13** to lock. In response to detecting that the user does have a policy to lock the door **13**, the policy manager **158** can send a granted message to the device interface manager **1506** in step **1538**. The device manager **1506** can send the command to lock the door **13** to a transport manager **1510** in steps **1540-1546**. The transport manager **1510** can facilitate the command to lock the door **13**. Before implementing the command, the device interface manager **1506** can communicate with the policy manager **158** to verify that the permission to command the door and the policy manager **158** can send a granted message in step **1544** to the device interface manager **1506** in response to determining that that the permission exists.

(145) An acknowledge message can be sent to the device interface manager **1506** in step **1548** by the transport manager **1510** indicating that the command has been sent. The device interface manager **1506** can send a success message **1550** to the user interaction manager **1402**. The user interaction manager **1402** can send a success message to the security dashboard **1502** in step **1552**. The security dashboard **1502** can display a message to the user that the command has been successfully sent to the door **13** in step **1554**.

(146) Referring now to FIG. **16**, a flow diagram of a process **1600** where an event of building equipment is enriched with contextual information of a graph that can be performed by the cloud platform **106** is shown, according to an exemplary embodiment. In some embodiments, the cloud platform **106** can be configured to perform the process **1600**. Furthermore, any computing device or system described herein can be configured to perform the process **1600**.

(147) In step **1602**, the cloud platform **106** receives an event from building equipment or services. In some

embodiments, the cloud platform **106** receives non-event data, e.g., a stream of timeseries data, a message, etc. and normalizes the data into event data. The event can include one or more parameters, e.g., a data value (e.g., a temperature, an equipment status, etc.), a time at which the event occurred, etc. In some embodiments, the cloud platform **106** receives the event from an event source, for example, cloud data, NC4, a weather data service, the cloud platform **106** itself (e.g., an event, an enriched event, etc.), and/or any other system or device.

(148) In step **1604**, the cloud platform **106** can identify one or more entities and/or one or more relationships of a graph related to the event. The entities could be an indication of a location of the event (e.g., what room, what floor, what building the event occurred in), the building entities that consume the data of the event, other entities affected by the event (e.g., a temperature setpoint change of one room affecting the temperature of an adjacent room), etc. The relationships can indicate how the event is related to the entities. For example, a relationship, “isLocatedIn,” could be added to indicate that the sensor producing the event is located in a specific space.

(149) In some embodiments, the cloud platform **106** identifies the one or more entities and the one or more relationships from a graph projection. The graph projection can be a graph projection specific to a particular subscriber (e.g., user or organization) of the cloud platform **106**. In some embodiments, the cloud platform **106** receives the graph projection from the graph projection database **162**.

(150) In step **1606**, the cloud platform **106** generates an enriched event with the event and the one or more entities and the one or more relationships of the step **1604**. The cloud platform **106** can add multiple attributes to the event based on the entities and the relationships. In some embodiments, the cloud platform **106** generates an enriched event package including all of the data of the enriched event and the one or more entities and one or more relationships identified in the step **1604**.

(151) In step **1608**, the cloud platform **106** can provide the enriched event of the step **1606** to one or more applications configured to operate based on the enriched event. In some embodiments, the applications **110** can receive the enriched event and operate based on the data of the event and the contextual information (e.g., the entities and relationships) enriching the event. For example, for an application that controls the temperature of a space, an enriched event can include a temperature measurement of the space in addition to an identification of the space and the VAV box for the space. The application can generate a command for the VAV box based on the temperature measurement and communicate the temperature measurement to the identified VAV box of the enriched event.

(152) Referring now to FIG. **17**, a process **1700** where a change feed of events that record modifications to a graph that can be performed by the twin manager **108** is shown, according to an exemplary embodiment. The twin manager **108** can be configured to perform the process **1700**. In some embodiments, components of the twin manager **108** are configured to perform the process **1700**, for example, the change feed generator **152** and/or the graph projection database **162**. In some embodiments, any computing device described herein is configured to perform the process **1700**.

(153) In step **1702**, the twin manager **108** receives one or more changes to a graph. The changes may modify one or more nodes or one or more edges of the graph. For example, the changes may be to add a new node or edge, delete an existing node or edge, or modify an existing node or edge of the graph. In some embodiments, the modification is received by the twin manager **108** from the user device **176**, e.g., the user provides the twin manager **108** with a modification to a graph. In some embodiments, the modification is received as an event indicating a change to the graph, e.g., event is metadata **320** or the device tree **322**.

(154) In step **1704**, the twin manager **108** generates a change feed event recording the changes modifying the one or more nodes and/or the one or more edges. The event can be a data package of information including an event time, a time at which the event occurred. In some embodiments, the event includes an indication of how the graph has changed, e.g., what nodes and/or edges of the graph have changed and how those nodes and/or edges have changed. The twin manager **108** can implement the changes of step **1702** to the graph and also generate an event recording the change to the graph.

(155) In step **1706**, the twin manager **108** can add the event to a change feed. The change feed can include multiple change events for different changes to the graph. The change feed may be a topic that some applications and/or systems subscribe to, e.g., the applications **110**. In step **1706**, one or more applications that operate based on the graph can receive the change feed. In this regard, the applications and/or systems can receive the change feed event and update their storage of the graph based on the change feed. This can

allow the application and/or system to update their graph without receiving the entire graph, just an indication of the change. Furthermore, the twin manager **108** and/or any other system can generate the graph at one or more different times based on the events of the change feed to track the configuration of the graph at multiple different times.

(156) Referring now to FIG. **18**, a flow diagram of a process **1800** where a graph identifying capabilities of a piece of equipment is used to operate the piece of equipment that can be performed by the cloud platform **106** is shown, according to an exemplary embodiment. In some embodiments, the cloud platform **106** is configured to perform the process **1800**. In some embodiments, a component of the cloud platform **106**, e.g., the command processor **136** is configured to perform the process **1800**. Any computing device described herein can be configured to perform the process **1800**.

(157) In step **1802**, the cloud platform **106** can identify a capability of a piece of equipment based on a graph of nodes and edges where a first node of the nodes represents the capability and a second node of the nodes represents the piece of equipment where one or more edges relate the first node and the second node. In some embodiments, the cloud platform **106** may receive a request for information about the capabilities of a piece of equipment, e.g., from a user request via the user device **176** or from a device of the building subsystems **122** (e.g., a thermostat may request to control a VAV box). The cloud platform **106** can identify the capabilities, the operational commands that the piece of equipment can perform by identifying capability nodes related to a node of the piece of equipment through one or more edges and/or nodes between the nodes for the capabilities and the node for the piece of equipment. The cloud platform **106** can analyze a graph projection received from the twin manager **108** to identify the capabilities.

(158) In some embodiments, an entity can have capabilities originating from different systems. For example, a room could be an entity with a capability for temperature control, based on HVAC systems for the room. The room could also have a booking capability to reserve the room based on a room booking and/or meeting scheduling system.

(159) In step **1804**, the cloud platform **106** can receive a command to operate the piece of equipment based on the capability identify from the graph in the step **1802**. In some embodiments, the cloud platform **106** communicates the capability to the requesting entity, e.g., the user device **176**, the applications **110**, a device of the building subsystems **122**, etc. The requesting entity can review the capability and issue a command for the capability.

(160) In step **1806**, the cloud platform **106** can provide the command to the piece of equipment. In some embodiments, the cloud platform **106** identifies a software component configured to manage messaging for the piece of equipment. The cloud platform **106** may identify the software component from the graph. For example, a node of the graph may represent the software component and one or more edges or nodes may relate the software component node and the node representing the piece of equipment. The cloud platform **106** can identify the software component by identifying the edges and/or nodes relating the software component node and the node representing the piece of equipment. The cloud platform **106** can provide the command to the software component to handle commanding the piece of equipment.

(161) Referring now to FIG. **19**, a process **1900** where the cloud platform **106** operates different services related by a graph is shown, according to an exemplary embodiment. In some embodiments, the process **1900** is performed by the cloud platform **106**. In some embodiments, any computing device described herein is configured to perform the process **1900**.

(162) In step **1902**, the cloud platform **106** receives an indication to perform an action for an entity. The action could be controlling a piece of building equipment. Implementing a command with an external system, e.g., generating a virtual meeting via a virtual meeting platform, send an email via an email service, etc.

(163) In step **1904**, the cloud platform **106** can identify a service configured to perform the action based on a graph including nodes and edges. For example, if the command is to send an email, the cloud platform **106** may identify an email service by identifying an email service node of the graph. If the action is to command a piece of building equipment to operate, the cloud platform **106** could identify a node of the graph representing a device hub that handles messages for the piece of building equipment.

(164) The nodes of the graph can represent various devices or software components. The edges can represent communication actions between the various devices or software components. For example, the edges could represent API calls between the various software components. Referring to FIG. **12**, API calls may exist for a device hub **1232** to implement a control command for a door actuator **1242**. The API calls

may be between other connecting software components, e.g., cluster **1236**, connector A **1240**, connector B **1238**, and external system **1244**. To implement a control command for door actuator **1242**, the device hub **1232** may make an API call **1284** to the cluster **1236** which may in turn make API calls **1286** and/or **1288** to connectors A **1240** and connector B **1238**. Connector A **1240** may make an API call to external system **1244**, API call **1288**. Similarly, connector B **1238** may make an API call **1290** to external system **1244**. External system **1244** may make an API call **1292** to the door actuator **1242** to implement the requested command.

(165) Similarly, if the command is to send an email via the email service **1204**, a connection broker **1254** may broker the connection for the cloud platform **106** with the email service **1204** and may make one or more API calls to implement the email command. The connection broker **1254** may make an API call **1298c** to the cluster **1208** which may make an API call **1298d** to a connector A that makes an API call **1298f** with the email service **1204** to send an email.

(166) In step **1906**, the cloud platform **106** causes the service identified in step **1904** to perform the operation based on the communication actions represented by the edges. For example, the cloud platform **106** can identify a set of API calls that implement the action. The API calls can be identified in part based on the graph. For example, to implement sending an email, the cloud platform **106** can identify API call **1298c** made by connection broker **1254**, API call **1298d** made by cluster **1208**, and API call **1298f** made by connector A **1206**. The cloud platform **106** can cause each service (i.e., connection broker **1254**, cluster **1208**, and connector A **1206**) to make the appropriate API call to implement the action.

(167) Referring now to FIG. **20**, a process **2000** where a user or service is provided with information and control abilities based on policies stored within a graph that can be performed by the cloud platform **106** is shown, according to an exemplary embodiment. The cloud platform **106** can be configured to perform the process **2000**. In some embodiments, any computing device or system described herein can be configured to perform the process **2000**.

(168) In step **2002**, the cloud platform **106** receives a request to view a portion of a graph of nodes and edges from a user and/or service. The nodes can represent entities of a building while the edges can represent relationships between the entities of the building. The request can be received from a user via the user device **176**. The request can be received from the applications **110** and/or the building subsystems **122**, in some embodiments.

(169) In step **2004**, the cloud platform **106** can determine whether the user and/or service has access to view the portion of the graph based on a policy indicated by one or more nodes and/or relationships of the graph. For example, the graph can indicate a policy for viewing information of the graph. For example, referring to FIG. **11**, an entity **1103** has **1151** the policy **1136** to read events **1138** to the floor **1132**. In this regard, if the user and/or service is the entity with a policy to read events, the user and/or service could view the events **110** and/or **1112**.

(170) The policy of the user and/or service could cascade through the graph, for example, if the user and/or service has a policy to read information for a higher level node, lower level nodes are also available to the user and/or service. For example, the cloud platform **106** could identify that the entity **1103** has **1151** the policy **1136** to the floor **1132** via edge **1174**. Because the door actuator **1114** is an asset of the space **1130** indicated by the edge **1168** and that the space **1130** is a space of the floor **1132** indicated by the edge **1170**, the cloud platform **106** can identify that the entity **1103** has access to the events of the door actuator **1114**.

(171) In step **2006**, the cloud platform **106** can provide a user and/or service an indication of the portion of the graph in response to determining that the policy indicates that the user and/or service has access to view the portion of the graph. The cloud platform **106** can cause a display device of the user device **176** to display the indication of the portion of the graph in some embodiments. In step **2008**, the cloud platform **106** can receive a command for a piece of equipment. The command may be a command to operate the piece of equipment, in some embodiments. In some embodiments, the command is a command to perform an action on behalf of a user, e.g., send an email to a user, schedule a meeting with the user, etc.

(172) In step **2010**, the cloud platform **106** can determine whether the user or service has access to perform the command based on a policy indicated by one or more nodes and/or edges of the graph. For example, a policy of the graph can indicate that the user and/or service has access to operate the piece of equipment.

(173) For example, referring to FIG. **12**, the user bob **1220** has a send command policy for a particular floor, e.g., Bob **1220** has **1264** policy **1136** for the send command **1140** via the edge **1178**. The policy **1136** is set for the floor **1132** via the edge **1174**. Because the entity **1103** has a send command policy for the

floor **1132**, any piece of equipment on the floor can be commanded by the entity **1103**. For example, the door actuator **1114** is a piece of equipment of a space **1130** indicated by edge **1168**. The space **1130** is a space of the floor **1132** indicated by the edge **1170**. The door actuator **1114** has a capability **1248** indicated by edge **1180**, the command can be an open door command **1252** or a lock door command **1250** related to the capabilities **1248** of the door actuator **1114** via the edges **1296** and **1294**.

(174) The cloud platform **106** can determine that the user Bob **1220** has the ability to command the door actuator **1114** via the relationships between the door actuator **1114** and the floor **1132** that the policy **1136** is set for. Because the user Bob **1220** has the ability to make commands for the floor **1132**, all components related to the floor **1132**, e.g., are located on the floor **1132**, can be available to the user, e.g., the door actuator **1114** being a device of the space **1130** via the edge **1168** and the space **1130** being an area of the floor **1132** via the edge **1170**.

(175) In step **2012**, the cloud platform **106** can operate the piece of equipment to perform the command. The cloud platform **106** can, in some embodiments, identify the services and/or communication actions to implement the command as described in FIG. **19**. For example, the cloud platform **106** can utilize the graph to identify the services that handle messaging for the devices and can identify the communication actions that the service performs to implement the command.

(176) Referring now to FIG. **21**, a process **2100** where a graph projection is constructed by the twin manager **108** is shown, according to an exemplary embodiment. In some embodiments, the twin manager **108** is configured to perform the process **2100**. In some embodiments, components of the twin manager **108**, e.g., the graph projection manager **156**, is configured to perform the process **2100**. In some embodiments, any computing device described herein is configured to perform the process **2100**.

(177) In step **2102**, the twin manager **108** can receive a request for a graph projection from a system. For example, a user via the user device **176** may request a graph projection be generated. In some embodiments, the cloud platform **106** receives an indication of a new subscribing customer and the cloud platform **106** provides a request to the twin manager **108** to generate a new projection for the subscribing customer. In some embodiments, the twin manager **108** receives a request from the applications **110** for a graph projection to be generated for a specific application of the applications **110**.

(178) In step **2104**, the twin manager **108** retrieves projection rules for the system for generating the graph projection. The projection rules can be an ontology specific for the system. For example, the ontology can define what types of nodes can be related in what particular ways. For example, one ontology may indicate that one type of node (e.g., thermostat) should be related to another type of node (e.g., a space). The ontology can indicate each type of node and what second types of nodes that each type of node can be related to. Furthermore, the projection rules can indicate policies for the system. For example, the projection rules can identify what nodes and/or edges that the system has access to view.

(179) In step **2106**, the twin manager **108** can retrieve entities and/or relationships representing entities of a building and relationships between the entities of the building. The twin manager **108** can retrieve all entities and/or relationships from the entity, relationship, and event database **160**. In some embodiments, the twin manager **108** retrieves only the entities and/or relationships that the projection rules indicate should be included within the projection graph, e.g., only entities and/or relationships that correspond to the ontology or only entities and/or relationships that the system has an access policy to.

(180) In step **2108**, the twin manager **108** can construct the graph projection based on the entities and relationships retrieved in the step **2106** and the projection rules retrieved in the step **2104**. In some embodiments, the twin manager **108** can construct the graph projection by generating nodes for the entities and generating edges between the nodes to represent the relationships between the entities.

(181) In some embodiments, the twin manager **108** generates the graph projection based on the ontology. For example, the ontology may indicate that building nodes should have an edge to room nodes. Another ontology may indicate that building nodes should have an edge to floor nodes and floor nodes should have an edge to room nodes. Therefore, for entity data that indicates a building A has a floor A and that floor A has a room A, with the first ontology, a node for the building A can be generated along with an edge from the building A node to a room A node. For the second ontology, a building A node with an edge to a floor A node can be generated. Furthermore, the floor A node can have an edge to a room A node.

(182) In step **2110**, the building data platform **100** can perform one or more operations based on the graph projection. In some embodiments, the building data platform **100** can perform event enrichment with contextual information of the graph projection (e.g., as described in FIG. **16**). In some embodiments, the

building data platform **100** can generate a change feed based on changes to the graph projection (e.g., as described in FIG. **17**). In some embodiments, the building data platform **100** can utilize the graph projection to command and control entities represented by the graph projection (e.g., as described in FIG. **20**). In some embodiments, the building data platform **100** can utilize the graph projection to identify services and/or communication commands to implementations (e.g., as described in FIG. **19**).

(183) Referring now to FIG. **22**, a process **2200** where a graph is queried based on an entity and an event is shown, according to an exemplary embodiment. The cloud platform **106** can be configured to perform the process **2200**. In some embodiments, any computing device described herein can be configured to perform the process **2200**.

(184) In step **2202**, the cloud platform **106** receives a query for information of a graph, the query including an entity and an event. The query can be formed from parameters for an asset, point, place, location, and event (“APPLE”). The query can indicate an entity, one of an asset, point, place, and location while the query can further indicate an event. In this regard, the query can search for certain entities with a particular event, for example, a floor (type of asset) with an active door alarm (event), a door (type of asset) with an active door alarm (event), a building (type of asset) with a temperature measurement exceeding a particular amount (event), etc.

(185) In step **2204**, the cloud platform **106** queries the graph for information based on the query received in the step **2202** where the graph includes nodes and edges, the nodes representing entities and events and the edges representing relationships between the entities and the events. For example, the query can be run against the graph to identify an entity associated with a particular event.

(186) For example, referring now to FIG. **11**, if the query is to find a space with a door actuator value of 1 at a particular time, “a,” the cloud platform **106** can be configured to search the edges and nodes to first all spaces within the graph. Next, the cloud platform **106** can select spaces of the graph that are linked to an event node for a door actuator with a value of 1 at a particular time, “a.” For example, the cloud platform **106** can determine that the space **1130** has an edge **1168** to the door actuator **1114** and that the door actuator **1114** has an edge **1160** to a point A **1116** and that the point A **1116** has an edge to the TS **1120** which in turn has an edge **1168** to the event node **1110** which has a value of 1 at a time “a.”

(187) In step **2206**, the cloud platform **106** can generate a query response based on the information queried in the step **2204**. The query response can include one or more nodes and/or edges of the graph selected by the query. For example, the query response could identify the entity of the query. Furthermore, the query response could identify the entity of the query and one or more nodes and/or edges relating the entity to the event of the query. The cloud platform **106** can return the query response to a system that originally made the query, e.g., to the user device **176**, the applications **110**, the building subsystems **122**, etc.

(188) Referring now to FIG. **23**, the platform manager **128** of the cloud platform **106** managing tenant and subscription entitlements with a tenant entitlement model **2300** is shown, according to an exemplary embodiment. The platform manager **128** can be configured to manage entitlements of various tenants and/or tenant subscriptions for the building data platform **100**. The provisioning service **130** can receive data from a user device **176** to create, end, or update a tenant and/or tenant subscription. The provisioning service **130** can cause the subscription service **132** to update the tenant entitlement model **2300** appropriately.

(189) In some embodiments, the provisioning service **130** is configured to handle license purchases and/or license activation for a tenant and/or tenant subscription. A user, via the user device **176**, can purchase a license for a particular tenant subscription through the provisioning service **130**. Responsive to the purchase of the license, the provisioning service **130** can add the entitlement for the tenant subscription to the tenant entitlement model **2300**, activating the license purchased.

(190) The tenant entitlement model **2300** can indicate tenants, each tenant indicating a billing boundary. Each tenant can further include one or multiple subscriptions, particular implementations of the building data platform **100** for the tenant. For example, a retail chain that includes multiple stores could be a tenant while each store could have a particular subscription. Each subscription can be tied to a particular geographic operating zone, e.g., an indication of computing resources within the geographic operating zone that the subscription utilizes. Each subscription can further indicate entitlements for the subscription, e.g., services, data, or operations of the building data platform **100** that the subscription is authorized to utilize.

(191) The entitlement service **134** can receive requests for entitlements from systems **2302** (e.g., the edge

platform **102**, the twin manager **108**, and/or applications **110**). The request may be a question whether a particular subscription has authorization for a particular entitlement, for example, the question could be whether a particular subscription has access to make a command responsive to systems **2302** requesting to make the command. In some embodiments, while the systems **2302** are operating (e.g., processing a control command, enriching an event, generating a user interface, performing a control algorithm), they may encounter an action that requires an entitlement. Responsive to encountering the action requiring the entitlement, the systems **2302** can communicate with the entitlement service **134** to determine whether the particular subscription that the systems **2302** are performing the action for has an entitlement for the action.

(192) The platform manager **128** includes a throttle manager **2304** configured to perform throttling operations for particular tenants and/or tenant subscriptions. For example, a particular tenant may have an entitlement to make a certain number of commands per minute, receive a certain amount of event data from building systems a minute, utilize a particular amount of processing power to run applications, etc. The throttle manager **2304** can receive operating data from the systems **2302**, in some embodiments through a meter **2306** of the platform manager **128**. In some embodiments, the meter **2306** receives the operating data, analyzes the operating data to determine metrics (e.g., commands per minute, storage utilized, etc.) for particular tenant subscriptions.

(193) The throttle manager **2304** can communicate a resource throttling command for particular customer subscriptions to the systems **2302**. For example, if a customer subscription has an entitlement for a particular number of event enrichment operations and the operating data indicates that the particular number of event enrichment operations have been performed, the throttle manager **2304** can send a throttle command for event enrichment (e.g., stop all enrichment for the tenant subscription, cause the enrichment to be slowed, etc.). In some embodiments, the throttle manager **2303** could slow down operating commands of a particular tenant subscription in response to receiving more than a particular number of requests to perform operating commands in a particular time period (e.g., 1,000 requests in a minute).

(194) The meter **2306** can be configured to generate metrics indicating the operations of the systems **2302** for the tenant subscriptions and/or for the tenants. The meter **2306** can receive the operating data from the systems **2302** and determine which tenant subscription the operating data is associated with. For example, the systems **2302** may record which tenant subscription is associated with the operating data and provide an indication of the tenant subscription to the meter **2306**. The operating data can be a control command, an amount of events received by the systems **2302** from building systems of a building, etc. The metrics generated by the meter **2306** can indicate computational resources used by particular tenant subscriptions, storage resources used by particular tenant subscriptions, number of computing request or commands made, etc. In some embodiments, the meter **2306** is configured to generate a bill for particular tenants and/or tenant subscriptions based on the metrics to scale bills of tenant subscriptions based on their usage of the systems **2302**.

(195) In some embodiments, the meter **2306** generates metrics for one or multiple tenant subscriptions. The metrics can be API request per second, day, month, and total amount of data transferred. The metrics can indicate number of messages processed and/or computational cycles used. The metrics can indicate amount data storage used and/or amount of data persisted. The metrics can indicate events per second, per day, and/or per month. Furthermore, the metrics can indicate event subscriptions per second, per day, and/or per month. A tenant may have one or multiple event subscriptions indicating how the data platform **100** handles and/or enriches particular events.

(196) Referring now to FIG. **24**, the tenant entitlement model **2200** shown in greater detail, according to an exemplary embodiment. In some embodiments, the tenant entitlement model **2200** is a graph data structure, one or more tables, or other data storage structures. The tenant can be a billing boundary. The tenants can have multiple subscriptions, e.g., multiple sites of a single entity, multiple floors of a building rented to various companies, etc. The tenant **2400** is shown to include three separate subscriptions, subscription A **2402**, subscription B **2404**, and subscription C **2406**. The tenant **2400** can be a particular account associated with a globally unique identifier (GUID) linked to particular subscription identifiers.

(197) Each of the subscriptions **2402-2406** can be associated with a particular geographic zone, e.g., zone **2408** and zone **2410**. The zones can be particular geographic regions such as cities, counties, states, countries, continents, country groupings (e.g., Asia Pacific (APAC), Europe, the Middle East and Africa (EMEA), etc.), etc. Each of the subscriptions **2402-2406** can be linked to one of the zones **2408** and **2410**.

Each of the geographic zones **2408** and **2410** can be associated with computational resources (e.g., servers, processors, storage devices, memory, networking infrastructure, etc.) located within each of the zones for implementing the building data platform **100**. The computational resources within each zone can be shared amount subscriptions for the zone.

(198) In some embodiments, the building data platform **100** can implement DNS style data routing to the computational resources of the zones based on subscription identifiers for the subscriptions **2402-2406**. The zones **2408** and **2410** can resolve data residency concerns, e.g., that data of a particular subscription does not leave a particular geographic district, e.g., leave a country.

(199) Each of the zones **2408** and **2410** can indicate entitlements for subscriptions linked to the zones **2408** and **2410**. For example, a table **2414** can indicate entitlements for the subscription A **2402** and the subscription B **2404** linked to the zone **2408**. A table **2412** can indicate entitlements for subscriptions of the zone **2410**, e.g., the subscription C **2406**. The tables **2414** and **2412** can indicate all entitlements offered by the building data platform **100** for the particular zone and whether each subscription has authorization for the particular entitlement. The entitlements can indicate what services, resources, and/or what computing, storage, and/or networking usage levels the subscriptions **2402-2406** are entitled to.

(200) For example, the building data platform **100** includes platform resources **2413** and **2418** for the zones **2408** and **2410** respectively. In the zone **2408**, the platform resources **2413** include computing resources **2414** and storage resources **2416**. In the zone **2410**, the platform resources **2418** include computing resources **2420** and storage **2422**. The building data platform **100** can facilitate resource scaling providing the subscription A **2402** and the subscription B **2404** various amounts of the platform resources **2413** according to entitlements for the subscription A **2402** and the subscription B **2404** respectively. Each subscription can be assigned an amount of resource based on whether the subscription is assigned, via the entitlements, a premium resource usage tier or a lower level resource usage tier.

(201) The entitlements can be a set of available capabilities within one of the zones **2408** and **2410** that the subscriptions **2402-2406** are assigned or are not assigned. The entitlements can be availability of the graph, events, commands, event subscriptions, gateway operations, and/or gateway cloud to device (C2D) communication. In some embodiments, the ability to create an event subscription, e.g., an ER collection, graph, and/or enrichment rule for a particular event or type of events can be available to some subscriptions but not to others. The platform manager **128** can provide an API, e.g., through the provisioning service **130**, the subscription service **132**, and/or the entitlement service **134**, for managing the entitlements of the tenant entitlement model **2300**.

(202) Referring now to FIG. **25**, a process **2500** of managing tenant and subscription entitlements with the tenant entitlement model **2300** is shown, according to an exemplary embodiment. In some embodiments, the platform manager **128** is configured to perform the process **2500**. Any computing device or system described herein can be configured to perform the process **2500**, in some embodiments.

(203) In step **2502**, the platform manager **128** is configured to receive one or more tenant and/or subscription management requests from the user device **176**. For example, the requests can be to create a new tenant and/or new subscription for a tenant, remove an existing tenant and/or existing subscription, update entitlements for subscriptions, etc. In some embodiments, the requests are associated with purchases, e.g., purchasing an entitlement for a particular subscription. In some embodiments, the request can indicate management of subscription zone relationships, e.g., a management of what zone an existing or new subscription is set for. In some embodiments, the entitlements set for the subscription are limited to the entitlements available for a particular zone that the subscription is linked to. In step **2504**, the platform manager **128** can update the tenant entitlement model **2300** based on the request received in the step **2502**.

(204) In step **2506**, the platform manager **128** receives a request to perform an operation for a subscription for a zone from one of the systems **2302**. For example, one of the systems **2302** can provide the request to the platform manager **128** to determine whether an operation is available for a subscription. For example, the twin manager **108** may process a command request to command a particular piece of equipment of the building subsystems **122** for a particular subscription. The twin manager **108** can send a request to the platform manager **128** for confirmation of whether the subscription has a command entitlement for a particular zone.

(205) In response to receiving the request of the step **2508**, the platform manager **128** can determine whether the subscription has the entitlement for the operation for the zone based on the tenant entitlement model **2200**. For example, the platform manager **128** can search entitlements for the particular zone that

the subscription is linked to in order to determine whether the subscription has the entitlement for the operation. The platform manager **128** can respond to the system with an indication of whether or not the subscription has the entitlement.

(206) In step **2510**, the building data platform **100** can implement the operation with computing resources for the zone linked to the subscription by the tenant entitlement model. For example, the platform manager **128** can respond to the system where the system is a component of the building data platform **100** with an indication that the subscription has the entitlement. The system can proceed with performing the operation. Furthermore, the subscription may be tied to a zone which is linked to computing resources of the building data platform **100**. The operation can be performed on the computing resources tied to the zone.

(207) In step **2512**, the platform manager **128** can perform metering and/or throttling for the subscription based on the operation and/or one or more additional operations. The platform manager **128** can track all operational data associated with the subscription and build operation metrics via the meter **2306**. The metrics can indicate resource usage of the subscription. Based on the metrics, the platform manager **128** can generate bills based on the metrics to charge the subscription an amount according to the resource usage. Furthermore, based on the metrics the platform manager **128** can implement resource throttling to control the amount of computing and/or storage resources used by the subscription.

(208) Referring now to FIG. **26**, a system **2600** including the edge platform **100** performing event enrichment at the edge platform **102** before the events are communicated to the cloud platform **106** is shown, according to an exemplary embodiment. The system **2600** includes the building subsystems **122**, the edge platform **102**, the cloud platform **106**, the applications **110**, and the twin manager **108**. The edge platform **102** can receive events from the building subsystems **122** and enrich the events before passing the events on to the cloud platform **106**. Because the edge platform **102** is located on-premises, e.g., on the edge, the events can be enriched before being passed on to other cloud systems and/or used in edge based analytics run on the edge platform **102**. In some embodiments, processors, memory devices, and/or networking devices of the edge platform **102** are located on-premises within a building.

(209) The edge platform **102** can receive events from the building subsystems **122**. The events can be data packages describing an event that has occurred with a timestamp of when the event occurred. The events can be raw events that are composed of content that is emitted from a producing system. However, the event may not include any intent or knowledge of the system that consumes it. The event can be of a particular event type. An enrichment manager **2602** of the edge platform **102** can receive the events from the building subsystems **122**. The enrichment manager **2602** can be the same as, or similar to, the enrichment manager **138**.

(210) The enrichment manager **2602** can enrich the events received from the building subsystems **122** based on event context received and/or retrieved from a lite digital twin **2608** of the edge platform **102**. For example, the enrichment manager **2602** can add entity and/or entity relationship information associated with the event to the event to generate the enriched events **2604**. The event enrichment can be the same as or similar to the enrichment described with referenced to FIGS. **1-3** and FIG. **8**. The enriched events **2604** can be an event with additional added properties or attributes that provide context regarding the event.

(211) In some embodiments, the enrichment manager **2602** includes multiple event streams. The event streams can be data enrichment processing streams for particular events and/or particular types of events. Each event stream can be linked to a tenant and/or tenant subscription. Each event stream can indicate one or more rules for enriching an event, e.g., an indication of the information to add to the event. In this regard, one event can be applied to multiple event streams and receive different enrichments to generate multiple enriched events. Each enriched event can be provided to a different application or end system.

(212) The edge platform **102** includes edge applications **2610**. The edge applications **2610** can be similar to or the same as the applications **110**. While the applications **110** may be run on a cloud system, the edge applications **2610** can be run locally on the edge platform **102**. The edge applications **2610** can operate based on the enriched events **2604** and may not need to consult a digital twin to acquire context regarding an event since the enriched events **2604** may already include the needed context. In some embodiments, the edge application **2610** perform analytics (e.g., aggregation, data monitoring, etc.), control algorithms, etc. for the building subsystems **122**.

(213) For example the edge applications **2610** can generate control decisions for the building subsystems **122** based on the enriched events **2604**, e.g., temperature setpoints for zones, fan speed settings for fans,

duct pressure setpoints, ventilation commands, etc. In some embodiments, the edge applications **2610** include models, e.g., machine learning models for predicting characteristics and/or conditions and/or for operating the building subsystems **122**. In some embodiments, the machine learning is performed at the edge platform **102** which results in higher scores than machine learning performed in the cloud since a greater amount of data can be collected faster and used for training at the edge.

(214) In some embodiments, the enrichment manager **2602** only operates when the twin manager **108** is not operating and enriching events. For example, the edge platform **102** can receive an indication that there is an error with cloud systems, e.g., network issues, computing issues, etc. In this regard, the edge platform **102** can take over enriching the events with the enrichment manager **2602** and operating on the events with the edge applications **2610**. In this regard, the enrichment and application operation can dynamically move between the edge platform **102** and the cloud. Furthermore, load balancing can be implemented so that some events are enriched and operated on by edge applications **2610** while other events are passed to the cloud platform **106** and/or the twin manager **108** for enrichment and provided to the applications **110** for operation.

(215) In some embodiments, by performing enrichment at the edge platform **102**, analytics can be performed at the edge platform **102** based on the enriched events. In this regard, lower latencies can be realized since analytics and/or control algorithms can be performed quickly at the edge platform **102** and data does not need to be communicated to the cloud. In some embodiments, the edge applications **2610** and/or machine learning models of the edge applications **2610** can be built in the cloud and communicated to the edge platform **102** and additional learning can be performed at the edge platform **102**.

(216) The edge platform **102** includes the lite digital twin **2608**. The lite digital twin **2608** can be a version of a digital twin **2610** of the twin manager **108**. The digital twins **2610** and/or **2608** can be virtual representations of a building and/or the building subsystem **122** of the building. The digital twin **2610** and/or the digital twin **2608** can be or can include the graph projection database **162**, e.g., one or more graph data structures. The digital twin **2610** and/or the lite digital twin **2608** can be the graphs shown in FIGS. **11-13**. In some embodiments, the lite digital twin **2608** is a projection that does not include all nodes and edges of a full projection graph. The lite digital twin **2608** may only include the nodes or edges necessary for enriching the events and can be built on projection rules that define the information needed that will be used to enrich the events.

(217) In some embodiments, the lite digital twin **2608** can be synchronized, in whole or in part, with the digital twin **2610**. The lite digital twin **2608** can include less information than the digital twin **2610**, e.g., less nodes or edges. The lite digital twin **2608** may only include the nodes and/or edges necessary for enriching events of the building subsystems **122**. In some embodiments, changes or updates to the digital twin **2610** can be synchronized to the lite digital twin **2608** through a change feed of change feed events. The change feed can indicate additions, removals, and/or reconfigurations of nodes or edges to the graph projection database **162**. Each change feed event can indicate one update to the digital twin **2610**.

(218) A digital twin updater **2606** can receive the events of the change feed from the change feed generator **152** and update the lite digital twin **2608** based on each change feed event. The updates made to the lite digital twin **2608** can be the same updates as indicated by the events of the change feed. In some embodiments, the digital twin updater **2606** can update the lite digital twin **2608** to only include the nodes and edges necessary for enrichment of the events, and thus include less nodes and edges than the digital twin **2610**.

(219) In some embodiments, the digital twin updater **2606** filters out change feed events if the change feed events do not pertain to information needed to enrich the events. In this regard, the digital twin updater **2606** can store a list of information needed for enrichment, e.g., the digital twin updater **2606** can include all event subscriptions or enrichment rules. The digital twin updater **2606** can determine whether a change feed event updates information pertaining to event enrichment and only update the lite digital twin **2608** responsive to determining that the change feed event updates information needed for enrichment. In some embodiments, when a new event subscription and/or new enrichment rule is created, the digital twin updater **2606** can communicate with the digital twin **2610** to retrieve nodes or edges needed for the new event subscription and/or enrichment rules.

(220) Referring now to FIG. **27**, a process **2700** of performing event enrichment at the edge by the edge platform **102** before the events are communicated to the cloud is shown, according to an exemplary embodiment. In some embodiments, the edge platform **102** is configured to perform the process **2700**.

Furthermore, any computing system or device as described herein can be configured to perform the process **2700**.

(221) In step **2702**, the twin manager **108** can receive a change to the digital twin **2610** managed by the twin manager **108**. The change can be an addition, removal, or reconfiguration of an edge and/or node. In step **2704**, the twin manager **108** can update the digital twin **2610** based on the change. Furthermore, in step **2706**, the twin manager **108** can generate a change feed event for a change feed representing the change to the digital twin. In some embodiments, the change feed event can summarize the change. In step **2708**, the twin manager **108** can communicate the change feed to the edge platform **102** for synchronizing the digital twin **2610** with the lite digital twin **2608** of the edge platform **102**.

(222) In step **2710**, the edge platform **102** can receive the change feed from the twin manager **108**. The edge platform **102** can be subscribed to the change feed and can receive all change feed events posed to the change feed by the twin manager **108**. In step **2712**, the edge platform **102** can update the lite digital twin **2608** based on the change feed event. In some embodiments, the edge platform **102** can determine, responsive to receiving the change feed event, whether the change feed event affects enrichment performed by the edge platform **102**. Responsive to determining that the change feed event affects nodes or edges of the lite digital twin **2608** used in enrichment, the edge platform **102** can update the lite digital twin **2608** based on the change feed event.

(223) In step **2714**, the edge platform **102** can receive one or more events from building systems of a building. For example, the building subsystems **122** can generate events, e.g., data collection events, operational command decisions, etc. The events can describe information created for the building subsystems **122** and include a timestamp indicating when the information was created.

(224) In step **2716**, the edge platform **102** can retrieve event context from the lite digital twin **2608** for the one or more events. The event context can indicate attributes describing the event. In step **2718**, the edge platform **102** can generate the enriched events **2604** by enriching the one or more events with the event context retrieved in the step **2718**. Enriching the events can include adding additional attributes (the event context) to the events. In step **2720**, the edge platform can communicate the one or more enriched events **2604** to the cloud, e.g., the cloud platform **106**.

(225) Referring now to FIG. **28**, a system **2800** including the twin manager **108** synchronizing the digital twin **2610** of the twin manager **108** with digital twins of other external systems is shown, according to an exemplary embodiment. The twin manager **108** can act as a master record of a digital twin of a building and/or building subsystems and use a change feed to update digital twins of other systems, e.g., an external system **2806** and **2816**. Furthermore, in some embodiments, the twin manager **108** can receive updates to the digital twin of one external system, e.g., the external system **2806** and synchronize the changes to other external systems, e.g., the external system **2816**. This synchronization can allow for data sharing between all of the digital twins since each digital twin is up-to-date.

(226) The twin manager **108** includes the digital twin **2619** and the change fee generator **152**. Furthermore, the twin manager **108** includes a twin updater **2802** and a change synchronizer **2804**. The twin updater **2802** can receive updates to the graph projection database **162**, e.g., updates to nodes or edges of the graph, e.g., insertion, deletion, or reconfiguration of nodes or edges. The updates can be received from the cloud platform **106** as part of the event processing shown in FIG. **3** where updates to the graph are learned from events. In some embodiments, the updates can originate from other systems, e.g., the external system **2806** or **2816**. For example, the external system **2806** could make an update to a digital twin **2808** in a first format stored by the external system **2806** and communicate the change to the twin updater **2802**. In some embodiments, the external system **2806** can use a change feed to communicate the update to the twin manager **108**.

(227) The change synchronizer **2804** can synchronize the digital twin **2610** with the digital twin **2808** of the external system **2806** and a digital twin **2814** of the external system **2816**. The change synchronizer **2804** can make updates to the digital twin **2808** and the digital twin **2814**. In some embodiments, the change synchronizer **2804** makes different types of updates based on the format of the digital twins **2808** and **2814**. For example, the change synchronizer **2804** can make a twin update in a first format for the digital twin **2808** and a twin update in a second format for the digital twin **2814** to make the same update across the twins **2808** and **2814**.

(228) In some embodiments, the change synchronizer **2804** uses a change feed of change feed events to update the digital twin **2808** and the digital twin **2814**. In some embodiments, the change synchronizer

2804 receives a change feed of change feed events from the change feed generator **152**. Responsive to receiving a new change feed event, the change synchronizer **2804** can make the change indicated by the change feed event in the digital twin **2808** and the digital twin **2814**. In some embodiments, the change synchronizer **2804** communicates the change feed to the external system **2806** and/or the external system **2814** causing the external system **2806** and the external system **2816** to update the digital twins **2808** and **2814**.

(229) The external system **2806** can receive updates from the change synchronizer **2804** and update the digital twin **2808** according to the updates. Similarly, a twin updater **2812** of the external system **1816** can receive updates from the change synchronizer **2804** and update the digital twin **2814**. In some embodiments, the updates received from the change synchronizer **2804** are in a format associated with the digital twin stored by the external systems **2806** and/or **2816**. In some embodiments, the update is a change feed event and/or a change feed of change feed events.

(230) In some embodiments, the building data platform **100** can generate lite graph projection of the digital twin **2610** and the digital twin in the first format **2808** and the digital twin in the second format **2814**. The projections can be built based on projection rules and therefore may not include all of the nodes and edges as a full graph projection. The same projection rules can be used for the twin manager **108** and the external system **2806** and/or the external system **2816**. The building data platform **100** can compare the projections against each other to confirm that the twins of the twin manager **108** and the external system **2806** and/or **2816** are the same. By comparing the projections instead of the full twins, an easier feasible comparison can be performed.

(231) Referring now to FIG. **29**, a process **2900** of synchronizing the digital twin **2610** of the twin manager **108** with digital twins **2808** and **2814** of other external systems **2806** and **2816** is shown, according to an exemplary embodiment. In some embodiments, the twin manager **108** is configured to perform the process **2900**. Any computing device or system described herein can be configured to perform the process **2900**, in some embodiments.

(232) In step **2902**, the twin manager **108** receives an update to the digital twin **2610**. The update can be received from an internal system, e.g., a component of the building data platform **100**. For example, events processed by the cloud platform **106** can be analyzed to derive updates to the digital twin **2610** as described in FIG. **3**. Similarly, in some embodiments, a user via the user device **176** can provide the update to the digital twin **2610** to the twin manager **108**. In some embodiments, an external system can provide the update, e.g., the external system **2806** and/or the external system **2816**. In this regard, the external system **2806** can make an update to the digital twin **2808** and communicate the update made to the digital twin **2808** to the twin manager **108**.

(233) In step **2904**, the twin manager **108** updates the digital twin **2610** based on the update received in the step **2902**. In step **2906**, the twin manager **108** generates a change feed event of a change feed based on the update. The change feed event represents the changes made to the digital twin **2610**. In some embodiments, the change feed is a topic where multiple change feed events are posted for consuming systems to receive.

(234) In step **2908**, the twin manager **108** generates a first update in a first format for the digital twin **2808** based on the change feed event. Furthermore, the twin manager **108** generates a second update in a second format for the digital twin **2814** based on the change feed event. In step **2910**, the twin manager **108** can synchronize the digital twin **2808** of the external system **2806** with the update in the first format by communicating with the external system **2806**. In step **2912**, the twin manager **108** can synchronize the digital twin **2814** of the external system **2816** with the update in the second format by communicating with the external system **2816**.

(235) Configuration of Exemplary Embodiments

(236) The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments.

Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

(237) The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a machine, the machine properly views the connection as a machine-readable medium. Thus, any such connection is properly termed a machine-readable medium. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(238) Although the figures show a specific order of method steps, the order of the steps may differ from what is depicted. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule based logic and other logic to accomplish the various connection steps, processing steps, comparison steps and decision steps.

(239) In various implementations, the steps and operations described herein may be performed on one processor or in a combination of two or more processors. For example, in some implementations, the various operations could be performed in a central server or set of central servers configured to receive data from one or more devices (e.g., edge computing devices/controllers) and perform the operations. In some implementations, the operations may be performed by one or more local controllers or computing devices (e.g., edge devices), such as controllers dedicated to and/or located within a particular building or portion of a building. In some implementations, the operations may be performed by a combination of one or more central or offsite computing devices/servers and one or more local controllers/computing devices. All such implementations are contemplated within the scope of the present disclosure. Further, unless otherwise indicated, when the present disclosure refers to one or more computer-readable storage media and/or one or more controllers, such computer-readable storage media and/or one or more controllers may be implemented as one or more central servers, one or more local controllers or computing devices (e.g., edge devices), any combination thereof, or any other combination of storage media and/or controllers regardless of the location of such devices.

Claims

1. A building system of a building comprising one or more memory devices having instructions stored thereon, that, when executed by one or more processors, cause the one or more processors to: post an event to a topic based on data received from a piece of building equipment, the event indicating a command that the piece of building equipment is capable of performing; responsive to the event being posted to the topic, insert at least a first node storing the command that the piece of building equipment is capable of performing into a building graph data structure including a plurality of nodes and a plurality of edges between the plurality of nodes, the plurality of nodes representing entities of the building and the plurality of edges representing relationships between the entities of the building, wherein the building graph data

structure includes: a second node of the plurality of nodes representing the piece of building equipment, and an edge of the plurality of edges between the first node and the second node indicating that the piece of building equipment has a capability to perform the command; execute a software application to query the building graph data structure to dynamically detect the inserted first node indicating that the piece of building equipment has the capability to perform the command by identifying the second node representing the piece of building equipment, the first node storing the command, and the edge between the first node and the second node indicating that the piece of building equipment has the capability to perform the command; and transmit the command to the piece of building equipment to execute the command responsive to identifying the first node, the second node, and the edge between the first node and the second node.

2. The building system of claim 1, wherein the instructions cause the one or more processors to: generate a graphical user interface element comprising the command retrieved from the first node responsive to identifying that the piece of building equipment has the capability to perform the command; and transmit, responsive to an interaction with the graphical user interface element, the command to the piece of building equipment.

3. The building system of claim 1, wherein the building graph data structure includes: a third node representing a capability set and a plurality of fourth nodes representing capabilities of the capability set, the capability set including the capability, wherein the first second node of the plurality of nodes representing the piece of building equipment is linked via a first edge of the plurality of edges to the third node of the plurality of nodes representing the capability set, wherein the third node representing the capability set is related via a plurality of second edges of the plurality of edges to the plurality of fourth nodes representing the capabilities, the plurality of fourth nodes including the first node representing the capability, the plurality of second edges including the edge; wherein the instructions cause the one or more processors to: identify, based on the building graph data structure, that the piece of building equipment has the capability by identifying the first edge relating the second node to the third node and identifying the edge of the plurality of second edges relating the third node to the first node representing the capability.

4. The building system of claim 1, wherein the capability is the command to execute a control operation that the piece of building equipment is configured to perform.

5. The building system of claim 1, wherein the instructions cause the one or more processors to: identify whether a requesting system has a permission to make the command indicated by the capability by: identifying a third node of the plurality of nodes representing the requesting system; and identifying one or more particular edges of the plurality of edges between the third node and a fourth node of the plurality of nodes representing the permission to make the command.

6. The building system of claim 1, wherein the instructions cause the one or more processors to: identify a device hub configured to facilitate messaging between the building system and the piece of building equipment based on the building graph data structure, wherein the plurality of nodes include a node representing the device hub; and send the command indicated by the capability to the piece of building equipment through the device hub.

7. The building system of claim 1, wherein the instructions cause the one or more processors to: identify a connection broker configured to facilitate a connection between the building system and the piece of building equipment, wherein the plurality of nodes include a node representing the connection broker; and send the command indicated by the capability to the piece of building equipment through the connection broker.

8. The building system of claim 1, wherein the entities include a user of the building; wherein the command is associated with the user and the piece of building equipment is configured to perform the command responsive to a reception of an input from a system associated with the user of the building.

9. The building system of claim 1, wherein the instructions cause the one or more processors to: receive an input from a system associated with a user; identify a node of the plurality of nodes representing the user; identify a node of the plurality of nodes representing a permission of the user to perform the command; identify an edge of the plurality of edges between the node representing the user and the node representing the permission; and cause the piece of building equipment to perform the command responsive to an identification of the edge between the node representing the user and the node representing the permission.

10. A method, comprising: posting, by one or more processing circuits, an event to a topic based on data received from a piece of building equipment, the event indicating a command that the piece of building

equipment is capable of performing; responsive to the event being posted to the topic, inserting, by the one or more processing circuits, at least a first node storing the command that the piece of building equipment is capable of performing into a building graph data structure including a plurality of nodes and a plurality of edges between the plurality of nodes, the plurality of nodes representing entities of a building and the plurality of edges representing relationships between the entities of the building, wherein the building graph data structure includes: a second node of the plurality of nodes representing the piece of building equipment, and an edge of the plurality of edges between the first node and the second node indicating that the piece of building equipment has a capability to perform the command; executing, by the one or more processing circuits, a software application to query the building graph data structure to dynamically detect the inserted first node indicating that the piece of building equipment has the capability to perform the command by identifying the second node representing the piece of building equipment, the first node storing the command, and the edge between the first node and the second node indicating that the piece of building equipment has the capability to perform the command; and transmitting, by the one or more processing circuits, the command to the piece of building equipment to execute the command responsive to identifying the first node, the second node, and the edge between the first node and the second node.

11. The method of claim 10, comprising: generating, by the one or more processing circuits, a graphical user interface element comprising the command retrieved from the first node responsive to identifying that the piece of building equipment has the capability to perform the command; and transmitting, by the one or more processing circuits, responsive to an interaction with the graphical user interface element, the command to the piece of building equipment.

12. The method of claim 10, wherein the building graph data structure includes: a third node representing a capability set and a plurality of fourth nodes representing capabilities of the capability set, the capability set including the capability, wherein the second node of the plurality of nodes representing the piece of building equipment is linked via a first edge of the plurality of edges to the third node of the plurality of nodes representing the capability set, wherein the third node representing the capability set is related via a plurality of second edges of the plurality of edges to the plurality of fourth nodes representing the capabilities, the plurality of fourth nodes including the first node representing the capability, the plurality of second edges including the edge; where the method includes: identifying, by the one or more processing circuits, based on the building graph data structure, that the piece of building equipment has the capability by identifying the first edge relating the first node to the third node and identifying the edge of the plurality of second edges relating the third node to the first node representing the capability.

13. The method of claim 10, wherein the capability is the command to execute a control operation that the piece of building equipment is configured to perform.

14. The method of claim 10, comprising: identifying, by the one or more processing circuits, whether a requesting system has a permission to make the command indicated by the capability by: identifying a third node of the plurality of nodes representing the requesting system; and identifying one or more particular edges of the plurality of edges between the third node and a fourth node of the plurality of nodes representing the permission to make the command.

15. The method of claim 10, comprising: identifying, by the one or more processing circuits, a device hub configured to facilitate messaging between the one or more processing circuits and the piece of building equipment based on the building graph data structure, wherein the plurality of nodes include a node representing the device hub; and sending, by the one or more processing circuits, the command indicated by the capability to the piece of building equipment through the device hub.

16. The method of claim 10, comprising: identifying, by the one or more processing circuits, a connection broker configured to facilitate a connection between the one or more processing circuits and the piece of building equipment, wherein the plurality of nodes include a node representing the connection broker; and sending, by the one or more processing circuits, the command indicated by the capability to the piece of building equipment through the connection broker.

17. The method of claim 10, wherein the entities include a user of the building; wherein the command is associated with the user and the piece of building equipment is configured to perform the command responsive to a reception of an input from a system associated with the user of the building.

18. The method of claim 10, comprising: receive an input from a system associated with a user; identify a node of the plurality of nodes representing the user; identify a node of the plurality of nodes representing a permission of the user to perform the command; identify an edge of the plurality of edges between the

node representing the user and the node representing the permission; and cause the piece of building equipment to perform the command responsive to an identification of the edge between the node representing the user and the node representing the permission.

19. One or more non-volatile storage media storing instructions thereon, that, when executed by one or more processors, cause the one or more processors to: post an event to a topic based on data received from a piece of building equipment, the event indicating a command that the piece of building equipment is capable of performing; responsive to the event being posted to the topic, insert at least a first node storing the command that the piece of building equipment is capable of performing into a graph data structure including a plurality of nodes and a plurality of edges between the plurality of nodes, the plurality of nodes representing entities of an environment and the plurality of edges representing relationships between the entities of the environment, wherein the building graph data structure includes: a first node of the plurality of nodes representing the piece of equipment, and an edge of the plurality of edges between the first node and the second node indicating that the piece of equipment has a capability to perform the command; execute a software application to query the graph data structure to dynamically detect the inserted first node indicating that the piece of equipment has the capability to perform the command by identifying the second node representing the piece of equipment, the first node storing the command, and the edge between the first node and the second node indicating that the piece of equipment has the capability to perform the command; and transmit the command to the piece of equipment to execute the command responsive to identifying the first node, the second node, and the edge between the first node and the second node.

20. The one or more non-volatile storage media of claim 19, wherein the instructions cause the one or more processors to: generate a graphical user interface element comprising the command retrieved from the second node responsive to identifying that the piece of equipment has the capability to perform the command; and transmit, responsive to an interaction with the graphical user interface element, the command to the piece of equipment.
