

US Patent & Trademark Office

Patent Public Search | Text View

| | |
|----------------------|-----------------------|
| United States Patent | 12388296 |
| Kind Code | B2 |
| Date of Patent | August 12, 2025 |
| Inventor(s) | Jung; Chun-Kil et al. |

Non-contact power reception apparatus for non-contact charging and electronic settlement performed in a single portable terminal

Abstract

A non-contact power reception apparatus is provided, in which a power reception coil for a charging system and a loop antenna for an electronic settlement system are mounted on a battery pack and a cover case of a portable terminal such that the power reception coil is arranged in the center thereof and the loop antenna is disposed outside the power reception coil, so that a mode of receiving a wireless power signal and a mode of transmitting and receiving data are selectively performed, thereby preventing interference from harmonic components and enabling non-contact charging and electronic settlement using a single portable terminal. A jig for fabricating a core to be mounted to the non-contact power reception apparatus is provided.

| | |
|-------------------|---|
| Inventors: | Jung; Chun-Kil (Seoul, KR), Kuk; Yoon-Sang (Seoul, KR) |
| Applicant: | GE Hybrid Technologies, LLC (Niskayuna, NY) |
| Family ID: | 42243239 |
| Assignee: | GE Hybrid Technologies, LLC (Niskayuna, NY) |
| Appl. No.: | 18/178326 |
| Filed: | March 03, 2023 |

Prior Publication Data

| | |
|----------------------------|-------------------------|
| Document Identifier | Publication Date |
| US 20230208192 A1 | Jun. 29, 2023 |

Foreign Application Priority Data

| | | |
|----|-----------------|---------------|
| KR | 10-2008-0126269 | Dec. 12, 2008 |
| KR | 10-2009-0051316 | Jun. 10, 2009 |
| KR | 10-2009-0084388 | Sep. 08, 2009 |

Related U.S. Application Data

continuation parent-doc US 17371874 20210709 US 11601014 child-doc US 18178326
continuation parent-doc US 16996327 20200818 US 11095163 20210817 child-doc US 17371874
continuation parent-doc US 16298659 20190311 US 10804745 20201013 child-doc US 16996327
continuation parent-doc US 15499906 20170428 US 10277075 20190430 child-doc US 16298659
continuation parent-doc US 15142738 20160429 US 9673660 20170606 child-doc US 15499906
continuation parent-doc US 14094665 20131202 US 9356660 20160531 child-doc US 15142738
continuation parent-doc US 12741679 US 8624546 20140107 WO PCT/KR2009/007431
20091211 child-doc US 14094665

Publication Classification

Int. Cl.: **H02J7/00** (20060101); **H01F41/098** (20160101); **H02J7/04** (20060101); **H02J50/00** (20160101); **H02J50/10** (20160101); **H02J50/12** (20160101); **H02J50/80** (20160101); **H04B5/79** (20240101); H01F27/28 (20060101); H01F38/14 (20060101)

U.S. Cl.:

CPC **H02J50/005** (20200101); **H01F41/098** (20160101); **H02J7/00304** (20200101); **H02J7/00308** (20200101); **H02J7/04** (20130101); **H02J50/10** (20160201); **H02J50/12** (20160201); **H02J50/80** (20160201); **H04B5/79** (20240101); H01F27/2871 (20130101); H01F38/14 (20130101); H02J7/00034 (20200101); Y10T29/49071 (20150115); Y10T29/53265 (20150115)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

| Patent No. | Issued Date | Patentee Name | U.S. Cl. | CPC |
|------------|-------------|-----------------|----------|-----|
| 5850135 | 12/1997 | Kuki et al. | N/A | N/A |
| 6002320 | 12/1998 | Uda et al. | N/A | N/A |
| 6967462 | 12/2004 | Landis | N/A | N/A |
| 7180265 | 12/2006 | Naskali et al. | N/A | N/A |
| 8022804 | 12/2010 | Pilniak | N/A | N/A |
| 8041227 | 12/2010 | Holcombe et al. | N/A | N/A |
| 8073488 | 12/2010 | Yoneda | N/A | N/A |
| 8111042 | 12/2011 | Bennett | N/A | N/A |
| 8129942 | 12/2011 | Park et al. | N/A | N/A |
| 8624546 | 12/2013 | Jung et al. | N/A | N/A |
| 9356660 | 12/2015 | Jung et al. | N/A | N/A |
| 9673660 | 12/2016 | Jung et al. | N/A | N/A |
| 10277075 | 12/2018 | Jung et al. | N/A | N/A |
| 10804745 | 12/2019 | Jung et al. | N/A | N/A |
| 10992184 | 12/2020 | Jung et al. | N/A | N/A |

| | | | | |
|--------------|---------|-----------------|---------|-----------------|
| 11095163 | 12/2020 | Jung et al. | N/A | N/A |
| 2002/0142195 | 12/2001 | Ehara | N/A | N/A |
| 2004/0004460 | 12/2003 | Fitch et al. | N/A | N/A |
| 2004/0145342 | 12/2003 | Lyon | N/A | N/A |
| 2004/0250744 | 12/2003 | Garcia | 116/63C | E01F 9/629 |
| 2005/0127866 | 12/2004 | Hamilton et al. | N/A | N/A |
| 2005/0127867 | 12/2004 | Calhoon et al. | N/A | N/A |
| 2005/0162125 | 12/2004 | Yu et al. | N/A | N/A |
| 2005/0189910 | 12/2004 | Hui | N/A | N/A |
| 2005/0283971 | 12/2004 | Erpelding | 29/605 | H02K 41/0358 |
| 2006/0040171 | 12/2005 | Lee | N/A | N/A |
| 2006/0113955 | 12/2005 | Nunally | N/A | N/A |
| 2007/0069687 | 12/2006 | Suzuki | N/A | N/A |
| 2008/0079394 | 12/2007 | Kim et al. | N/A | N/A |
| 2008/0111518 | 12/2007 | Toya | N/A | N/A |
| 2008/0211455 | 12/2007 | Park et al. | N/A | N/A |
| 2008/0238364 | 12/2007 | Weber et al. | N/A | N/A |
| 2009/0261778 | 12/2008 | Kook | N/A | N/A |
| 2010/0036773 | 12/2009 | Bennett | N/A | N/A |
| 2011/0025264 | 12/2010 | Mochida et al. | N/A | N/A |
| 2011/0316475 | 12/2010 | Jung et al. | N/A | N/A |
| 2014/0084861 | 12/2013 | Jung et al. | N/A | N/A |
| 2016/0248272 | 12/2015 | Jung et al. | N/A | N/A |
| 2017/0338683 | 12/2016 | Jung et al. | N/A | N/A |
| 2019/0273398 | 12/2018 | Jung et al. | N/A | N/A |
| 2020/0381953 | 12/2019 | Jung et al. | N/A | N/A |
| 2020/0381954 | 12/2019 | Jung et al. | N/A | N/A |
| 2021/0336488 | 12/2020 | Jung et al. | N/A | N/A |

FOREIGN PATENT DOCUMENTS

| Patent No. | Application Date | Country | CPC |
|-----------------|------------------|---------|-----|
| 0982869 | 12/1999 | EP | N/A |
| 2429372 | 12/2006 | GB | N/A |
| H05199146 | 12/1992 | JP | N/A |
| 11-332135 | 12/1998 | JP | N/A |
| 2000200725 | 12/1999 | JP | N/A |
| 2001238372 | 12/2000 | JP | N/A |
| 2002078247 | 12/2001 | JP | N/A |
| 2002270437 | 12/2001 | JP | N/A |
| 2002299138 | 12/2001 | JP | N/A |
| 3794267 | 12/2005 | JP | N/A |
| 2008236888 | 12/2007 | JP | N/A |
| 20040008248 | 12/2003 | KR | N/A |
| 100819604 | 12/2007 | KR | N/A |
| 100819753 | 12/2007 | KR | N/A |
| 20080084628 | 12/2007 | KR | N/A |
| 10-2009-0091440 | 12/2008 | KR | N/A |
| 2008056415 | 12/2007 | WO | N/A |

OTHER PUBLICATIONS

U.S. Appl. No. 16/298,659, Jung, et al. cited by applicant
U.S. Appl. No. 16/996,317, Jung, et al. cited by applicant
U.S. Appl. No. 16/996,327, Jung, et al. cited by applicant
U.S. Appl. No. 17/371,874, Jung, et al. cited by applicant
“CN Application No. 200980101002.7 First Office Action”, Sep. 2, 2013, 9 pages. cited by applicant
“CN Application No. 200980101002.7 Second Office Action”, Apr. 1, 2014, 13 pages. cited by applicant
“CN Application No. 200980101002.7 Third Office Action”, Dec. 23, 2014, 4 pages. cited by applicant
“European Application No. 09825621 European Search Report and Opinion”, Mar. 4, 2014, 9 pages. cited by applicant
“Japanese Office Action dated Dec. 3, 2012, issued in corresponding Japanese Patent Application No. 2011-540609”, Dec. 3, 2012, 7 pages. cited by applicant
“Japanese Office Action dated Feb. 29, 1962, issued in corresponding Japanese Patent Application No. 2011-540609.”, Feb. 29, 1962. cited by applicant
“KR Application No. KR20080126269 Written Opinion”, Mar. 16, 2010, 4 pages. cited by applicant
“KR Application No. KR20090051316 Written Opinion”, Mar. 19, 2010, 4 pages. cited by applicant
“KR Application No. KR20090084388 Written Opinion”, Mar. 19, 2010, 4 pages. cited by applicant
“KR Application No. KR20090084388 Written Opinion”, Jul. 26, 2010, 6 pages. cited by applicant
“PCT Application No. PCT/KR2009/007431 International Preliminary Report on Patentability”, Jun. 23, 2011, 8 pages. cited by applicant
“PCT Application No. PCT/KR2009/007431 International Search Report”, Jul. 30, 2010, 5 pages. cited by applicant
“PCT Application No. PCT/KR2009/007431 Written Opinion”, Jul. 30, 2010, 10 pages. cited by applicant
“Qi System Description Wireless Power Transfer”, Wireless Power Consortium, vol. 1:Low Power, Part 1:Interface Definition, Version 1.0.1, Oct. 2010, 88 pages. cited by applicant
“U.S. Appl. No. 12/741,649 Office Action”, Nov. 15, 2012, 7 pages. cited by applicant
“U.S. Appl. No. 12/741,679 Final Office Action”, Apr. 18, 2013, 6 pages. cited by applicant
“U.S. Appl. No. 14/094,665 Final Office Action”, Jan. 6, 2016, 12 pages. cited by applicant
“U.S. Appl. No. 14/094,665 Office Action”, Aug. 4, 2015, 11 pages. cited by applicant
“U.S. Appl. No. 15/142,738 Office Action”, Sep. 23, 2016, 9 pages. cited by applicant
“U.S. Appl. No. 15/499,906 Office Action”, Jun. 29, 2018, 7 pages. cited by applicant
“U.S. Appl. No. 16/298,659 Office Action”, Jan. 27, 2020, 10 pages. cited by applicant
“U.S. Appl. No. 16/996,317 Office Action”, Oct. 27, 2020, 13 pages. cited by applicant
“U.S. Appl. No. 16/996,327 Office Action”, Dec. 21, 2020, 14 pages. cited by applicant
“U.S. Appl. No. 17/371,874 Final Office Action”, Feb. 28, 2022, 12 pages. cited by applicant
“U.S. Appl. No. 17/371,874 Non Final Office Action”, Jul. 14, 2022, 14 pages. cited by applicant
“U.S. Appl. No. 17/371,874 Office Action”, Nov. 10, 2021, 11 pages. cited by applicant

Primary Examiner: Williams; Arun C

Attorney, Agent or Firm: DeLizio, Peacock, Lewin & Guerra, LLP

Background/Summary

RELATED MATTERS (1) This application is a continuation of U.S. patent application Ser. No. 17/371,874, filed Jul. 9, 2021, which is a continuation of U.S. patent application Ser. No. 16/996,327, filed Aug. 18, 2020, which is a continuation of U.S. patent application Ser. No. 16/298,659, filed on Mar. 11, 2019, which is a continuation of U.S. patent application Ser. No. 15/499,906, filed on Apr. 28, 2017, which is a continuation of U.S. patent application Ser. No. 15/142,738, filed on Apr. 29, 2016, which is a continuation of U.S. patent application Ser. No. 14/094,665, filed on Dec. 2, 2013, issued as U.S. Pat. No. 9,356,660 on May 31, 2016, which is a continuation of U.S. patent application Ser. No. 12/741,679, filed on May 6, 2010, issued as U.S. Pat. No. 8,624,546 on Jan. 7, 2014, which is a National Stage Entry of International Patent Application Serial No. PCT/KR2009/007431, filed on Dec. 11, 2009, which claims the priority benefit of Korean Application No. 10-2009-0084388, filed on Sep. 8, 2009, Korean Application No. 10-2009-0051316, filed Jun. 10, 2009 and Korean Application No. 10-2008-0126269, filed on Dec. 12, 2008, all of which were filed in the Korean Intellectual Property Office and the disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to a non-contact power reception apparatus and a jig for fabricating a core for the non-contact power reception apparatus, and more particularly to a non-contact power reception apparatus, in which a power reception coil for a charging system and a loop antenna for an electronic settlement system are mounted on a battery pack and a cover case of a portable terminal such that the power reception coil is arranged in the center thereof and the loop antenna is disposed outside the power reception coil, so that a mode of receiving a wireless power signal and a mode of transmitting and receiving data are selectively performed, thereby preventing interference from harmonic components and enabling non-contact charging and electronic settlement using a single portable terminal, and a jig for fabricating a core to be mounted to the non-contact power reception apparatus.

BACKGROUND

(2) Generally, a battery pack is a kind of power supply that is charged with power (electric energy) received from an external charger and supplies the power so that portable electronic devices, such as cellular phones, personal digital assistants (PDAs) and the like can be operated, and consists of a battery cell which is charged with electric energy and circuits for charging and discharging the battery cell (supplying electric energy to portable terminals).

(3) The electrical connection between the battery pack, which is used in the portable terminals, and the charger for charging electric energy to the battery pack may be achieved using a connector supply system, which receives the power from a regular power source and converts the voltage and current thereof to correspond to those of the battery pack, and supplies the electric power to the battery pack via a connector of the corresponding battery pack.

(4) However, when the charger and the batteries are connected or disconnected to replenish the electric power of the batteries using such a connector supply system, there may be drawbacks, such as instant discharge owing to the difference in potential between the charger connector and the battery connector, the risk of fire and concomitant damage due to fire caused by the presence of foreign substances gathered on both connectors, and the like.

(5) Further, accumulated humidity will cause the discharge of the battery through the battery connector and other problems will occur, such as the reduction in the life and performance of the battery pack, and the like.

(6) To solve the above-mentioned problems, a non-contact charging system using a wireless power transmission and reception system was recently proposed.

(7) Meanwhile, portable terminals that have recently proliferated include an electronic settlement system using a Local Area Network (LAN), so that settlement is carried out by bringing the portable terminals into proximity with electronic settlement devices and conducting a settlement process.

(8) Such an electronic settlement system essentially includes a loop antenna, an absorber, an impedance matching circuit and the like in the portable terminal.

(9) In order to mount, in a single portable terminal, both the non-contact charging system using the wireless power transmission and reception technology and the settlement system using the LAN, a power reception coil of the charging system and the loop antenna of the electronic settlement system should be mounted in the portable terminal and operated.

(10) However, due to interference from harmonic components (n times a fundamental wave), which is produced in the frequency band (e.g., 13.56 MHz) of the electronic settlement system and the frequency band (e.g., hundreds kHz) of the charging system, problems such as the unstable transmission of signals occur, therefore failing to perform desired functions.

(11) The information disclosed in this Background section is only for the enhancement of understanding of the background and should not be taken as an acknowledgment or any form of suggestion that this information forms the prior art that would already be known to a person skilled in the art.

BRIEF SUMMARY

(12) To solve the above-mentioned problem, the present disclosure is directed to a non-contact power reception apparatus, in which a power reception coil for a charging system and a loop antenna for an electronic settlement system are mounted on a battery pack and a cover case of a portable terminal while interference from harmonic components is prevented, thereby enabling non-contact charging and electronic settlement using a single portable terminal.

(13) Another object of the present disclosure is to provide a non-contact power reception apparatus having the power reception coil arranged in the center thereof and the loop antenna disposed outside the power reception coil, so that a mode of receiving a wireless power signal and a mode of transmitting and receiving data are selectively performed.

(14) A further object of the present disclosure is to provide a jig for fabricating a double-structure core which is mounted in the non-contact power reception apparatus.

(15) In accordance with an aspect of the present disclosure, the non-contact power reception apparatus may include a common transmission and reception block selectively performing a mode of receiving a wireless power signal and a mode of transmitting and receiving data, a rectification block rectifying the power signal received by the common transmission and reception block in the mode of receiving the wireless power signal, a received-power control block controlling the power signal rectified by the rectification block, a charging control block controlling charging of a battery pack using electric energy of the power signal controlled by the received-power control block, and a data processing block transmitting and receiving data for electronic settlement with an external electronic device via the common transmission and reception block in the mode of transmitting and receiving data.

(16) The common transmission and reception block may include a power reception coil receiving the wireless power signal, a loop antenna for the transmission and reception of data, a mode switching unit selecting either one of the power reception coil and the loop antenna and allowing electrical connection to either one of the rectification block and the data processing block, and a mode control unit detecting a received-voltage of the power reception coil and controlling a switching operation of the mode switching unit.

(17) The mode control unit may perform a control operation so that, if the detected received-voltage is higher than a reference voltage, the mode switching unit performs the switching operation to electrically connect the power reception coil and the rectification block, and if the detected received-voltage is lower than the reference voltage, the mode switching unit performs the

switching operation to electrically connect the loop antenna and the data processing block.

(18) The mode control unit may include a voltage detector for detecting the received-voltage of the power reception coil, comparing the detected received-voltage with the reference voltage and outputting the comparison result.

(19) In accordance with another aspect of the present disclosure, the non-contact power reception apparatus may include, in a portable terminal, a common transmission and reception block selectively performing a mode of receiving a wireless power signal and a mode of transmitting and receiving data, a rectification block rectifying the power signal received by the common transmission and reception block in the mode of receiving the wireless power signal, a received-power control block controlling the power signal rectified by the rectification block, a charging control block controlling charging of a battery pack using electric energy of the power signal controlled by the received-power control block, and a data processing block transmitting and receiving data for electronic settlement with an external electronic device via the common transmission and reception block in the mode of transmitting and receiving data. The portable terminal may include a terminal body capable of performing wireless communication, a rechargeable battery pack supplying electric energy to the terminal body, a cover case for protection of the battery pack, and at least one connector module electrically connecting the respective terminal body, the battery pack and the cover case, in which a first connector module of the battery pack is connected with a second connector module of the terminal body, in which the common transmission and reception block is arranged in the battery pack in such a manner as to be connected with the first connector module of the battery pack and a third connector module of the terminal body, in which the rectification block, the reception power control block and the charging block are sequentially arranged in the terminal body to extend from the third connector module to the second connector module, and in which the data processing block is arranged between the third connector module and the received-power control module.

(20) In accordance with further another aspect of the present disclosure, the non-contact power reception apparatus may include, in a portable terminal, a common transmission and reception block selectively performing a mode of receiving a wireless power signal and a mode of transmitting and receiving data, a rectification block rectifying the power signal received by the common transmission and reception block in the mode of receiving the wireless power signal, a received-power control block controlling the power signal rectified by the rectification block, a charging control block controlling charging of a battery pack using electric energy of the power signal controlled by the received-power control block, and a data processing block transmitting and receiving data for electronic settlement with an external electronic device via the common transmission and reception block in the mode of transmitting and receiving data. The portable terminal may include a terminal body capable of performing wireless communication, a rechargeable battery pack supplying electric energy to the terminal body, a cover case for protection of the battery pack, and at least one connector module electrically connecting the terminal body, the battery pack and the cover case, in which a first connector module of the battery pack is connected with a second connector module of the terminal body, in which the common transmission and reception block is arranged in the cover case in such a manner as to be connected with a fourth connector module of the cover case, the fourth connector module being connected with a third connector of the terminal body, in which the rectification block, the reception power control block and the charging block are sequentially arranged in the terminal body to extend from the third connector module to a second connector module, and in which the data processing block is arranged between the third connector module and the received-power control module, the second connector module being connected with a first connector module of the battery pack.

(21) A connector of the fourth connector module, which is connected with the common transmission and reception block arranged in the cover case, may have a shape of a leaf spring, and be electrically connected with a connector of the first connector module of the battery pack via a

through-hole provided in a cover of the cover case.

(22) The common transmission and reception block may include a power reception coil receiving the wireless power signal, a loop antenna for transmission and reception of data, a mode switching unit selecting any one of the power reception coil and the loop antenna and allowing electrical connection to any one of the rectification block and the data processing block, and a mode control unit detecting a received-voltage of the power reception coil and controlling a switching operation of the mode switching unit.

(23) The mode control unit may perform a control operation so that if the detected received-voltage is higher than a reference voltage, the mode switching unit performs the switching operation to electrically connect the power reception coil and the rectification block, and if the detected received-voltage is lower than the reference voltage, the mode switching unit performs the switching operation to electrically connect the loop antenna and the data processing block.

(24) The mode control unit may include a voltage detector for detecting the received-voltage of the power reception coil, comparing the detected received-voltage with the reference voltage and outputting the comparison result.

(25) In accordance with still another aspect of the present disclosure, the jig for fabricating a core for a non-contact power reception apparatus may include a lower planar disk having a center winding protrusion thereon, an upper planar disk placed on the lower disk and having at least one slide hole therein, and at least one guide unit inserted into the slide hole so as to be vertically movable.

(26) The lower disk may have a through-hole adjacent to the winding protrusion.

(27) The guide unit may have a shape corresponding to a rectangular corner and an inner curved section.

(28) In accordance with yet another aspect of the present disclosure, the method of fabricating a double-structure core using the jig for the non-contact power reception apparatus may include steps of: a) inserting a coil wire into the through-hole of the lower disk from a lower side thereof and drawing the coil wire upwards, b) winding the drawn coil wire about the winding protrusion to form a first coil, c) after the completion of formation of the first coil, sliding and lowering a plurality of guide units disposed in the upper disk, d) winding a coil wire around an outer surface of the guide unit to form a second coil, and e) separating the first and second coils from a jig for winding a coil.

(29) The step b) includes b-1) winding the coil wire about the winding protrusion to extend the diameter of the first coil, and b-2), if the diameter of the first coil matches that of an imaginary circle formed by the curved surface of the guide unit, completing the formation of the first coil.

(30) The step d) includes d-1) winding the coil wire extending from the first coil about an imaginary rectangle defined by the outer surface of the guide unit to form the second coil, and d-2), if the size of the second coil matches the size of the lower or upper disk, completing the formation of the second coil.

(31) According to the above-mentioned construction, the present disclosure has at least the following advantageous effects:

(32) The power reception coil of the charging system and the loop antenna of the electronic settlement system are mounted in the battery pack and the cover case of the portable terminal, so that non-contact charging and electronic settlement are both performed in the single portable terminal.

(33) Particularly, the non-contact charging system and the electronic settlement system, which use different respective frequency bands, are operated at the same time and interference between the two systems is prevented, so that the reliability is improved.

(34) The control modules of the non-contact charging system using the wireless power transmission and reception technology and the electronic settlement system using LAN are arranged in diverse forms, so that non-contact charging and electronic settlement can be carried out for battery packs

having diverse structures.

(35) In fabricating the core for the non-contact reception apparatus using the jig, the corresponding core is configured to have the shape of both a circle and a rectangle, so that the mobility and transmission efficiency of the corresponding core (secondary side) can be advantageously improved at the same time, by combining the advantages of a circular coil and a rectangular coil.

(36) Thus, adaptability to various kinds of portable terminals and the like can be considerably improved.

(37) The jig for winding a coil, which facilitates fabricating the core, and the method of easily fabricating the core using the jig are further provided, thereby having effects of improved productivity, reduced cost, increased production and the like in fabricating the double-structure core.

(38) Thus, the reliability of the non-contact charging system that includes the non-contact power reception apparatus and the non-contact power transmission apparatus can be improved, as can the competitiveness of related products, such as portable terminals, battery packs, and the like.

(39) The methods and apparatuses of the present disclosure have other features and advantages which will be apparent from or are set forth in more detail in the accompanying drawings, which are incorporated herein, and the following Detailed Description, which together serve to explain certain principles of the present disclosure.

(40) The methods and apparatuses of the present disclosure have other features and advantages which will be apparent from or are set forth in more detail in the accompanying drawings, which are incorporated herein, and the following Detailed Description, which together serve to explain certain principles of the present disclosure.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIG. 1 is a schematic circuit diagram of an example non-contact power reception apparatus in accordance with the present disclosure;

(2) FIG. 2 is a schematic block diagram of another example non-contact power reception apparatus in accordance with the present disclosure;

(3) FIG. 3 is a schematic circuit diagram of an example common transmission and reception block of FIG. 2;

(4) FIG. 4 is a schematic circuit diagram of another example non-contact power reception apparatus in accordance with the present disclosure;

(5) FIG. 5 is a schematic circuit diagram of another example non-contact power reception apparatus in accordance with the present disclosure;

(6) FIG. 6 is an exploded perspective view of an example battery pack for portable terminals in accordance with the present disclosure;

(7) FIG. 7 is an exploded perspective view of an example battery pack and a cover case for portable terminals;

(8) FIG. 8 is a partially cut away perspective view of an example jig for fabricating a core for the non-contact power reception apparatus in accordance with the present disclosure;

(9) FIG. 9 is an exploded perspective view of the jig of FIG. 8;

(10) FIGS. 10 and 11 are perspective views illustrative of a procedure of fabricating a double-structure core using the jig of FIG. 8;

(11) FIG. 12 is a perspective view of the double-structure core fabricated using the jig of FIG. 8; and

(12) FIG. 13 is a cross-sectional view illustrative of the procedure shown in FIGS. 10 and 11.

DETAILED DESCRIPTION

(13) Reference will now be made in detail to various embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings and described below. While the disclosure will be described in conjunction with example embodiments, it will be understood that the present description is not intended to limit the disclosure to those example embodiments. On the contrary, the disclosure is intended to cover not only the example embodiments, but also various alternatives, modifications, equivalents and other embodiments, which may be included within the spirit and scope of the disclosure as defined by the appended claims.

(14) A non-contact power reception apparatus and a jig for fabricating a core for the power reception apparatus according to the present disclosure are variously applicable, and example embodiments thereof will now be described in detail with reference to the accompanying drawings.

(15) FIG. 1 is a schematic circuit diagram of an example non-contact power transmission system in accordance with the present disclosure, which includes a non-contact power transmission apparatus **100** for sending out a wireless power signal and a non-contact power reception apparatus **200** receiving the wireless power signal and charging a battery cell with it.

(16) The non-contact power transmission apparatus **100** includes a primary core **110**, an identifier **120**, a wireless power transmission controller **130**, a switching controller **140**, an operating driver **150**, a series resonance converter **160**, and a feedback circuit **170**.

(17) The primary core **110** consists of a plurality of power transmission cores **111** and is connected in parallel with the series resonance converter **160**.

(18) The identifier **120** detects a change in the load of the primary core **110** and determines whether the change is induced by the non-contact power reception apparatus **200** or not. Thus, the identifier serves both to detect the change in the load and to analyze and process a data signal code of an AC signal of the signals transmitted from the non-contact power reception apparatus **200**.

(19) The wireless power transmission controller **130** receives and checks the determination result from the identifier **120**, and, if the change in the load is induced by the non-contact power reception apparatus **200**, sends out a power control signal to the operating driver **150** via the primary core **110** to transmit the wireless power signal.

(20) Then, the controller **130** analyzes and processes the data signal filtered by the identifier **120** and correspondingly controls the operating driver **150**. In addition, the controller creates a data signal (e.g., an ID asking signal) and transmits it to the non-contact power reception apparatus **200** via the primary core **110**.

(21) The switching controller **140** controls the switching operation of a plurality of switches (not shown), which are provided between the series resonance circuit **160** and the power transmission cores **111**.

(22) The operating driver **150** controls the operation of the series resonance converter **160** depending upon the intensity of the wireless power signal that is to be transmitted.

(23) The series resonance converter **160** creates a transmission power source for creating a wireless power signal to be transmitted under the control of the operating driver **150**, and supplies it to the primary core **110**.

(24) That is, when the wireless power transmission controller **130** transmits a power control signal for transmitting a wireless power signal, which may have a required power value, to the operating driver **150**, the operating driver **150** controls the operation of the series resonance converter **160** to correspond to the transmitted power control signal, and the series resonance converter **160** applies to the primary core **110** a transmission power source, which may correspond to the required power value, under the control of the operating driver **150**, thereby transmitting a wireless power signal having the required intensity.

(25) When the primary core **110** receives the code data of an AC signal, the feedback circuit **170** extracts the code data of the AC signal from a DC signal applied to the primary core **110**. The feedback circuit **170** includes an RC filter circuit section (not shown), which is electrically connected with ends of the power transmission cores **111** of the primary core **110** to remove a DC

signal component (low frequency component), and an amplifying circuit section (not shown), which has an OP-AMP that is electrically connected with the RC filter circuit section.

(26) That is, the low frequency signal, which is a DC signal component, is removed by the RC filter circuit section and the extracted AC signal component is amplified by the amplifying circuit section.

(27) Thus, it is possible to transmit and receive a low-amplitude signal.

(28) The non-contact power reception apparatus **200** to be supplied with power by receiving the wireless power signal includes a power reception coil **211** of a secondary core **220**, which creates induced power using the transmitted wireless power signal, a rectifier **230**, which rectifies the induced power, and a battery cell module (not designated), which charges a battery cell **270** with the rectified power.

(29) This battery module includes a protection circuit, such as an overvoltage and overcurrent prevention circuit, a temperature detecting circuit and the like, and a charging management module, which collects and processes information such as the charged state of the battery cell and the like.

(30) The non-contact power reception apparatus **200** further includes a wireless power receiver controller, which checks the current induced to the power reception coil **211** of the secondary core **220** and requests the control of the intensity of a wireless power signal based on the information on the charging of the battery cell, which is collected and processed by the battery cell module, and an ID transmitter, which, via the secondary core **220**, transmits and receives the code data of an AC signal modulated in an AC modulation manner.

(31) The non-contact power reception apparatus **200** further includes a capacitor C, which is connected in parallel with the power reception coil **211** of the secondary core **220** to remove a DC signal component, and a MOSFET, in which a drain terminal is serially connected with the capacitor.

(32) The MOSFET performs on/off control under the control of the ID transmitter. The ID transmitter inputs the operation voltage of the MOSFET to the gate terminal of the MOSFET in correspondence with a duty rate, which is set to correspond to the control request for the intensity of the wireless power signal by the wireless power receiver controller.

(33) That is, when the ID transmitter inputs an on-signal and an off-signal, which correspond to the operation voltage, to the gate terminal, the MOSFET creates and outputs a pulse width modulated (PWM) signal corresponding to voltage input to the gate terminal, and the PWM signal is transmitted to the non-contact power transmission apparatus **100** via the power reception core **211**.

(34) The non-contact power transmission apparatus **100** is supplied with power via a power supply port **181** from an adapter supplied with a regular power source, a power source of a USB port of a portable terminal such as a notebook, or the like.

(35) The apparatus **100** further includes a current detector **191**, which detects the internal current of the apparatus **100**, and a temperature detector **192**, which detects the internal temperature of the apparatus **100** during the charging process, so that if overheating, overvoltage or overcurrent occurs, the operation can be stopped.

(36) The battery cell module **230** of the non-contact power reception apparatus **200** further includes a charging circuit **231** for charging a battery cell, a gauge circuit **232** for checking the charged quantity, and a charging monitoring circuit **233** for monitoring the charging state.

(37) A display **193** is further provided to display the state of operation of the non-contact power transmission apparatus **100** and the charging state of the non-contact power reception apparatus **200**.

(38) With regard to the fabrication of the power reception coil **211** of the secondary side core **220** of the non-contact power reception apparatus **200**, a description thereof will be made later.

(39) Hereinafter, reference will be made to the embodiment of the non-contact power reception apparatus **200** that is provided with both a charging coil and a communication loop antenna at the same time.

(40) FIG. 2 is a schematic block diagram of an example non-contact power reception apparatus illustrative of non-contact charging and a control module of data communication in the portable terminals in accordance with the present disclosure. The non-contact power reception apparatus includes a common transmission and reception block **210**; a rectification block **220**, rectifying an AC wireless power signal and converting the same to a DC wireless power signal; a received-power control block **230**, controlling the DC signal converted by the rectification block **220** to be converted into chargeable voltage and current (which can be used in the following construction); a charging control block **240**, supplying, to a battery cell block **270**, electric energy output from the received-power control block **230**; a data processing block **250**, analyzing and processing transmitted/received data and performing an electronic settlement process; and the battery cell block **270**.

(41) Here, the battery cell block **270** consists of a rechargeable battery cell **273**, a temperature detecting module **272**, and a charging monitoring block **271** for protection.

(42) The common transmission and reception block **210** serves to selectively perform a mode of receiving a wireless power signal to operate the non-contact charging system and a mode of transmitting and receiving data to operate the electronic settlement system, and includes a power reception coil **211**, a loop antenna **212**, a mode switching unit **213**, and a mode control unit **214**.

(43) The power reception coil **211** serves to receive the wireless power signal from the non-contact charging system, and, as shown in FIG. 3, one end side thereof is connected, at a common contact point, with the loop antenna **212** and output outside the block and another end side thereof is connected with the mode switching unit **213**.

(44) The loop antenna **212** serves to transmit and receive data, such as information on settlement by the electronic settlement system, and as shown in FIG. 3, one end side thereof is connected, at a common contact point, with the power reception coil **211** and output outside the block, and another end side thereof is connected with the mode switching unit **213**.

(45) The mode switching unit **213** serves to select either one of the power reception coil **211** and the loop antenna **212** and perform a switching operation to allow electrical connection to either one of the rectification block **230** and the data processing block **250**. In a state of allowing the loop antenna **212** and the data processing block **250** to be connected, the power reception coil **211** and the rectification block **230** are operated to be connected under the control of the mode control unit **214**.

(46) The mode control unit **214** serves to detect a voltage of the power received by the power reception coil **211** and control the switching operation of the mode switching unit **213**. Then, the mode control unit compares the detected received-voltage with a reference voltage (a minimum voltage capable of determining a power signal supplied by a non-contact charging system), and outputs the comparison result to the mode switching unit **213**.

(47) That is, after detecting a voltage received by the power reception coil **211**, the mode control unit **214** performs the control operation so that, if the detected received-voltage is higher than the reference voltage, the mode switching unit **213** performs the switching operation to electrically connect the power reception coil **211** and the rectification block **220**, and, if the detected received-voltage is lower than the reference voltage, the mode switching unit **213** performs the switching operation to electrically connect the loop antenna **212** and the data processing block **250**.

(48) The mode control unit **214**, as shown in FIG. 3, includes a voltage detector **214** that is connected to a common contact point between the power reception coil **211** and the loop antenna **212**, so as to detect a voltage induced to the power reception coil **211**.

(49) As shown in FIGS. 4 and 5, reference will now be made to an example in which non-contact charging and the control module of data communication in the portable terminals have been adapted according to the present disclosure.

(50) FIG. 4 is a schematic circuit diagram of an example non-contact power reception apparatus in accordance with the present disclosure. Referring also to FIG. 6, the apparatus is configured so that

the common transmission and reception module **210** is arranged in a battery pack A such that the module **210** is electrically connected with a first connector module **261** of the battery pack A, and the rectification block **220**, the received-power control block **230**, the charging control block **240**, and the data processing block **250** are arranged in a terminal body B of the portable terminal.

(51) Here, the terminal body B is configured such that a second connector module **252**, which is to be electrically connected with the charging control block **240**, is provided so as to be connected with the first connector module **261** of the battery pack A, and such that a third connector module **263** is provided so as to allow the wireless power signal received by the power reception coil **211** to be supplied to the rectification block **220**.

(52) The data that is transmitted/received via the loop antenna **212** communicates with the data processing block **250** via the third connector module **263**, and the data processing block **250** analyzes and processes the communicated data and performs a process such as settlement or the like.

(53) Meanwhile, as shown in FIG. 6, the battery pack A is configured to include a battery cell **273**, a temperature detecting module **272**, and a charging monitoring module **271** in the battery pack A, which consists of an upper case Aa and a lower case Ab.

(54) The power reception coil **211** and the loop antenna **212** are mounted on one side of the battery cell **273** such that a shield plate **211a** is disposed between the power reception coil **211** and the battery cell **273**, and an absorber **212a** is arranged between the loop antenna **212** and the battery cell **273**.

(55) That is, the power reception coil **211** and the loop antenna **212** are provided on different pieces of shielding material on the same plane, thereby minimizing the thickness of the battery pack A.

(56) Here, the power reception coil **211** has a structure in which a plurality of windings is wound around it, and the loop antenna **212** has a loop type structure, so that, as shown in FIG. 6, the power reception coil **211** may be provided in the center of the apparatus, and the loop antenna **212** may be provided outside the power reception coil.

(57) Thus, according to the arrangement shown in FIGS. 4 and 6, the power reception coil **211**, which receives a non-contact wireless power signal and charges a battery, and the loop antenna **212** for data communication for electronic settlement are arranged on the same plane, and the common transmission and reception block **212**, which includes the power reception coil **211** and the loop antenna **212**, is mounted in the battery pack A, so that the thickness of the battery pack A can be minimized, fabricating costs can be reduced, and the rectification module **220**, the received-power control block **230**, the charging control block **240**, and the data processing block **250** can also use modules mounted in the portable terminal body B.

(58) The detailed electrical connection between the respective elements of FIG. 6 or the like is modifiable into various forms by persons skilled in the art, so that it is not limited to the specific construction of FIG. 7, which is to be described later.

(59) FIG. 5 is a schematic circuit diagram of an example non-contact power reception apparatus in accordance with the present disclosure. Referring also to FIG. 7, the apparatus is configured so that the common transmission and reception module **210** is arranged in a cover case C such that the module **210** is electrically connected with a fourth connector module **264** of the cover case C, the fourth connector module **264** is connected with a third connector module **263** of the terminal body B, and the rectification block **220**, the received-power control block **230**, the charging control block **240**, and the data processing block **250** are arranged between the third connector module **263** and the second connector module **262** in the terminal body B.

(60) The second connector module **262** of the terminal body B is connected with the first connector module **261** of the battery pack A.

(61) Meanwhile, the cover case C is configured so that, as shown in FIG. 7, space (not designated) for the common transmission and reception block **210** is formed in the cover case C, and the power reception coil **211** and the loop antenna **212** are mounted in the space such that a shield plate **211a**

is disposed on the power reception coil **211**, and an absorber **212a** is arranged on the loop antenna **212**.

(62) In some implementations, as shown in FIG. 7, the cover case includes the power reception coil **211** in the center thereof and the loop antenna **212** outside the power reception coil.

(63) Thus, according to the arrangement shown in FIGS. 5 and 7, the power reception coil **211**, which receives a non-contact wireless power signal and charges a battery, and the loop antenna **212** for data communication for electronic settlement are arranged on the same plane, and the common transmission and reception block **212**, which includes the power reception coil **211** and the loop antenna **212**, is mounted in the cover case C, so that the thickness of the cover case C can be minimized, and the rectification module **220**, the received-power control block **230**, the charging control block **240**, and the data processing block **250** are mounted in the terminal body B, so that traditional battery packs can continue to be used.

(64) Meanwhile, in order to minimize the size of the non-contact power transmission apparatus and the non-contact power reception apparatus, the power reception cores **211** according to the above embodiments may be fabricated to be thin. Thus, a coil is used in which a coil wire, which comprises a plurality of thin metal wires, is wound around itself in the winding diameter.

(65) In non-contact charging, a shielding sheet is generally provided on one side of a secondary coil in order to protect electric circuit elements from electromagnetic waves.

(66) Here, if the secondary coil is circular, there is no coil near the four corners of the rectangular shield sheet, so that an eddy current is generated, thus raising the temperature.

(67) Due to the non-contact power transmission nature, the positions of the primary core and the secondary core are variable, so that the mobility and transmission efficiency for the secondary core may be an evaluating reference for the reliability of products.

(68) Generally, the coil may be shaped so that a transmitter and a receiver are circular windings, or otherwise so that the transmitter is circular windings and the receiver is rectangular windings.

(69) Here, if the coil of the receiver is circular, mobility is excellent, whereas power transmission efficiency suffers because area is decreased compared to the rectangular coil. If the coil is rectangular, relative to the circular coil, power transmission efficiency is excellent, but mobility suffers.

(70) According to the present disclosure, a jig is provided which facilitates fabricating the secondary core for the non-contact reception apparatus, the secondary core is configured to have the shape of both a circle and a rectangle, so that the mobility and transmission efficiency for the secondary core can be advantageously improved at the same time, by combining the advantages of a circular coil and a rectangular coil.

(71) FIG. 8 is a partially cut away perspective view of an example jig for fabricating the non-contact power reception apparatus, showing a double-structure core **320** wound around the coil-winding jig **310**, the double-structure core consisting of circular and rectangular core portions.

(72) The coil-winding jig **310** includes a lower disk **311**, an upper disk **312**, and a guide unit **313** guiding the double-structure core **320** so that the circular and rectangular core portions are separately wound around the coil-winding jig **310**.

(73) The lower disk **311** is formed in a planar form as shown in FIG. 9, and has a winding protrusion **311a**, about which the double-structure core is wound, in the center of the upper surface thereof.

(74) In some implementations, the height of the winding protrusion **311a** may be greater than the height (diameter) of the coil wire.

(75) A through-hole **311b** is formed adjacent to the winding protrusion **311a**, as shown in FIG. 3.

(76) The through-hole **311b** passes through the lower disk **311**, and is formed at an incline, as shown in FIG. 13. The inclined through-hole **311b** prevents the coil wire from being drawn up towards the upper portion of the lower disk **311** when the double-structure core **320** is wound.

(77) The upper disk **312** is placed above the lower disk at a certain distance therefrom, and is

formed in a planar form, like the lower disk **311**, as shown in FIG. **9**.

(78) Here, various methods of separating and fixing the lower and upper disks **311** and **312** can be adopted, without being limited to a specific one, as desired by persons skilled in the art.

(79) For example, a separate holder holds and fixes one side (opposite corner or the like) of the upper disk **312**, so that the upper disk can be separated from the lower disk **311**.

(80) The upper disk **312** has at least one slide hole **312a** and, in some implementations, has at least four slide holes.

(81) The guide unit **313** is inserted into the slide hole **312a** in the upper disk **312** so that the guide unit is movable in a vertical direction. In some implementations, as shown in FIG. **9**, if the outer surface extends, an imaginary rectangle may be formed, and if the inner surface extends, an imaginary circle may be formed.

(82) That is, the guide unit **313** has a shape corresponding to the corners of a rectangle (such as a rectangular plane having a certain thickness) and an inner curved section **313a** corresponding to a circle.

(83) Hereinafter, a method of fabricating a double-structure core **320** using the jig **310** for the non-contact power reception apparatus will be described with reference to FIGS. **10** and **11**.

(84) Here, various kinds of separate devices for controlling the construction of the present disclosure, such as a separator for separating the upper disk **312**, a winder for coiling wire, and the like, may be adopted, without being limited to a specific one, as desired by those skilled in the art.

(85) First, a coil wire (not designated) as a basic unit of the double-structure core **320** is inserted into the through-hole **311b** of the lower disk **311** from a lower side thereof and drawn upwards.

(86) Here, as desired by a person skilled in the art, the coil wire may of course be inserted into the through-hole from the upper side thereof and drawn downwards.

(87) The drawn coil wire is circularly wound about the winding protrusion **311a** to form a first coil **321**.

(88) Here, in the case where the winding protrusion **311a** is provided to have the same height as the thickness (height) of the coil wire and the undersurface of the upper disk **312** is separated by the height of the winding protrusion **311a**, winding the coil wire is of course easily performed.

(89) If the diameter of the first coil **321** increases to reach an imaginary circular diameter by the inner curved section **313a** of the guide unit **313** as the coil wire is wound, winding the coil wire stops and the formation of the first coil **321** is completed.

(90) After the completion of the formation of the first coil **321**, the guide units **313** provided in the upper disk **321** are slid and lowered.

(91) In some implementations, the curved section **313a** of the guide unit **313** may come close to the outer circumference of the first coil **321**.

(92) When the lower surface of the guide unit **313** has come close to the upper surface of the lower disk **312** through the above process, the coil wire is wound around the outer surface of the guide unit **313** to form a second coil **322**.

(93) Here, the coil wire for forming the second coil **322** may be different from that for the first coil **321**, but in some implementations, the coil wire forming the first coil **321** be continuously used while extending from the first coil.

(94) If the second coil **322** formed by the coil wire corresponds to the area (size) of the lower or upper disk **311** or **312**, as shown in FIG. **11**, the formation of the second coil **322** is completed.

(95) After the double-structure core **320** has been completely fabricated through the above process, the double-structure core **320**, consisting of first and second coils **321** and **322**, is removed from the coil-winding jig **310**.

(96) Thus, the wireless power transmission double-structure core is fabricated such that the first circular coil **321** is provided in the center thereof and the second rectangular coil **322** is provided outside the first coil, so that the core with advantageous circular and rectangular coils have can be accomplished.

(97) As set forth above, non-contact charging, the data communication control module and its arrangement in the portable terminal have been described above. It is understood that the technical construction of the present disclosure may be modified to have different forms without departing from the spirit and features of the present disclosure by those skilled in the art.

(98) Therefore, the above-mentioned embodiments are provided only for illustrative purposes in all aspects, and the disclosure is not limited thereto. The scope of the present disclosure is defined not by the above detailed description, but by the appended claims, and that the described embodiments and all variations or modifications that can be deduced from equivalents interpreted from the claims fall within the scope of the present disclosure.

Claims

1. An apparatus of a non-contact charging system, the apparatus comprising: a battery; a wireless power transfer coil configured to receive a wireless power signal for charging the battery; and a communication antenna, wherein the wireless power transfer coil and the communication antenna are arranged in a plane at a first side of the battery in the apparatus, wherein the wireless power transfer coil and the communication antenna are configured to use different respective frequency bands and are capable of being operated at a same time.
2. The apparatus of claim 1, wherein the wireless power transfer coil is arranged within a center of a loop formed by the communication antenna.
3. The apparatus of claim 1, wherein the wireless power transfer coil is positioned in a center area of the apparatus at the first side of the battery, and wherein the communication antenna forms a loop type structure outside the wireless power transfer coil.
4. The apparatus of claim 1, wherein the wireless power transfer coil includes a first wire that coils around a winding diameter, and wherein the communication antenna includes a second wire that loops outside the first wire.
5. The apparatus of claim 1, further comprising: a case, wherein the wireless power transfer coil and the communication antenna are positioned substantially at one side of the case.
6. The apparatus of claim 1, wherein the wireless power transfer coil and the communication antenna are formed as a double-structure core and have a substantially circular arrangement.
7. The apparatus of claim 1, wherein the communication antenna is capable of transmitting or receiving a wireless data signal.
8. The apparatus of claim 7, wherein the wireless data signal includes information related to an electronic payment.
9. The apparatus of claim 1, further comprising: shielding material to protect electrical circuit elements in the apparatus from electromagnetic waves, wherein the shielding material is disposed between at least the wireless power transfer coil and the electrical circuit elements of the apparatus.
10. The apparatus of claim 9, wherein the wireless power transfer coil and the communication antenna are positioned on different pieces of the shielding material.
11. The apparatus of claim 9, wherein different pieces of the shielding material provide spatial decoupling of the wireless power transfer coil and the communication antenna on the same plane to minimize an overall height of the wireless power transfer coil and the communication antenna in the apparatus.
12. The apparatus of claim 1, further comprising: shielding material disposed between the wireless power transfer coil and at least one other electrical circuit component of the apparatus; and an absorber disposed between the communication antenna and the at least one other electrical circuit component.
13. The apparatus of claim 1, wherein the wireless power transfer coil has a circular shape and the communication antenna has a substantially rectangular shape.
14. The apparatus of claim 1, wherein the wireless power transfer coil and the communication

antenna are arranged in a common module of the apparatus.

15. An apparatus of a non-contact charging system, comprising: one or more electrical circuits of a portable terminal; a battery; a wireless power transfer coil; a communication antenna, wherein the wireless power transfer coil and the communication antenna are arranged in a plane at a first side of the battery, wherein the wireless power transfer coil and the communication antenna are configured to use different respective frequency bands and are capable of being operated at a same time; shielding material disposed between the wireless power transfer coil and the one or more electrical circuits; and an absorber disposed between the communication antenna and the one or more electrical circuits.

16. The apparatus of claim 15, further comprising: a case configured to house at least the battery, the wireless power transfer coil, and the communication antenna, wherein the wireless power transfer coil and the communication antenna are arranged within the case at the first side of the battery.

17. The apparatus of claim 15, wherein the wireless power transfer coil includes a first wire that coils around a winding diameter, and wherein the communication antenna includes a second wire that loops outside the first wire, and wherein the wireless power transfer coil and the communication antenna are formed as a double-structure core and have a substantially circular arrangement.

18. The apparatus of claim 15, wherein the wireless power transfer coil is positioned in a center area of the apparatus at the first side of the battery, and wherein the communication antenna forms a loop type structure outside the wireless power transfer coil.

19. The apparatus of claim 15, wherein the shielding material and the absorber provide spatial decoupling of the wireless power transfer coil and the communication antenna positioned substantially in the same plane.
