

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392900
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Li; Yueming

Distance measuring device

Abstract

A distance measuring device, including a first housing having an accommodating space; and a laser ranging device provided in the accommodating space of the first housing; a tapeline structure, the tapeline structure integrated with the laser ranging device into one piece, wherein the laser ranging device is arranged along a radial direction or an axial direction of the tapeline structure.

Inventors:	Li; Yueming (Hangzhou, CN)
Applicant:	Hangzhou Great Star Industrial Co., Ltd. (Hangzhou, CN)
Family ID:	1000008762499
Assignee:	Hangzhou Great Star Industrial Co., Ltd. (Hangzhou, CN)
Appl. No.:	18/133823
Filed:	April 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230296775 A1	Sep. 21, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 18098636 20230215 PENDING child-doc US 18133823
reissue parent-doc US 16334648 20190319 US 11156444 WO PCT/CN2016/103242 20161025
child-doc US 18098636

Publication Classification

Int. Cl.: **G01B3/1041** (20200101); **G01B3/1069** (20200101); **G01B3/1092** (20200101);
G01S17/86 (20200101)

U.S. Cl.:CPC **G01S17/86** (20200101); **G01B3/1069** (20200101);**Field of Classification Search****CPC:** G01B (3/1041); G01B (3/1092); G01B (11/026); G01S (17/08)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5182863	12/1992	Rando	N/A	N/A
5760392	12/1997	Hisamoto et al.	N/A	N/A
5777899	12/1997	Kumagai	N/A	N/A
5815251	12/1997	Ehbets et al.	N/A	N/A
6093928	12/1999	Ohtomo	250/231.13	G01D 5/36
6209219	12/2000	Wakefield	33/227	G01C 15/008
6928029	12/2004	Rickman	33/760	G01S 17/86
7036241	12/2005	Williams et al.	N/A	N/A
7119533	12/2005	Tamura et al.	N/A	N/A
7454840	12/2007	Delfini et al.	N/A	N/A
7456936	12/2007	Gogolla	356/5.01	G01C 15/002
7690124	12/2009	Henry	N/A	N/A
8094291	12/2011	Zimmermann	356/4.01	G01S 7/4818
8269951	12/2011	Courchesne	356/5.01	G01C 15/002
8356419	12/2012	Lord	33/763	G01D 7/00
D680888	12/2012	Ranieri	D10/72	N/A
D726043	12/2014	Cook	D10/72	N/A
9046340	12/2014	Li	N/A	G01S 17/88
D787347	12/2016	Wortelboer	D10/72	N/A
D788611	12/2016	Anderson	D10/72	N/A
11143494	12/2020	Li	N/A	G01S 7/4813
11156444	12/2020	Li	N/A	G01C 3/00
11460284	12/2021	Reed	N/A	G01B 3/1069
2004/0040170	12/2003	Sanoner	33/762	G01B 3/11
2004/0223164	12/2003	Gogolla	356/601	G01C 15/002
2005/0111301	12/2004	Rickman	N/A	N/A
2006/0010706	12/2005	Williams et al.	N/A	N/A
2006/0021244	12/2005	Oura	N/A	N/A
2007/0101593	12/2006	Jang	N/A	N/A
2007/0107248	12/2006	Jones	33/760	G01B 3/1041
2008/0007711	12/2007	Liu	N/A	N/A

2009/0273771	12/2008	Gittinger et al.	N/A	N/A
2010/0088914	12/2009	Cerwin	N/A	N/A
2010/0103406	12/2009	Zimmermann	N/A	N/A
2014/0090264	12/2013	Li	33/760	G01B 3/10
2016/0069658	12/2015	Klein	33/760	G01B 3/1003
2019/0234723	12/2018	Li	N/A	G01B 3/1043

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1123573	12/1995	CN	N/A
2350725	12/1998	CN	N/A
2779424	12/2005	CN	N/A
101713826	12/2009	CN	N/A
202837547	12/2012	CN	N/A
203012137	12/2012	CN	N/A
203224628	12/2012	CN	N/A
103412312	12/2012	CN	N/A
203287522	12/2012	CN	N/A
105627857	12/2015	CN	N/A
205484804	12/2015	CN	N/A
206274346	12/2016	CN	N/A
107976682	12/2017	CN	N/A
20-2014005479	12/2013	DE	N/A
2015101446	12/2015	DE	N/A
H-08327737	12/2000	JP	N/A
2004-233106	12/2003	JP	N/A
2005148037	12/2004	JP	N/A
3185168	12/2012	JP	N/A
M447982	12/2012	TW	N/A

OTHER PUBLICATIONS

Decision of Refusal for JP-2019522486, dated Feb. 2, 2010, 3 pgs. cited by applicant
International Search Report and Written Opinion for PCT/CN2016/103242, dated Jul. 26, 2017.
cited by applicant
Decision of Refusal and English-language Translation for JP-2021105032, dated May 11, 2023, 7
pgs. cited by applicant
Chinese Office Action Issued in Corresponding Chinese Patent Application No. 201610938229.9,
mailed on Nov. 27, 2024, 20 pages. cited by applicant

Primary Examiner: Hughes; Deandra M

Assistant Examiner: Leung; Christina Y

Attorney, Agent or Firm: Blank Rome LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a Continuation-In-Part of reissue application Ser. No. 18/098,636 (our ref. 164830.00102), filed Jan. 18, 2023, which is a reissue of Ser. No. 16/334,648, filed Mar. 19, 2019, now U.S. Pat. No. 11,156,444, issued Oct. 26, 2021, which is a national phase application of PCT/CN2016/103242, filed Oct. 25, 2016. The disclosures of these applications are hereby incorporated by reference.

FIELD OF THE INVENTION

(1) The present invention relates to the field of distance measuring tools and in particular to a distance measuring device.

DESCRIPTION OF THE PRIOR ART

(2) Tapelines and laser ranging devices are common distance measuring tools, which can be used in construction, interior decoration, handling of traffic accidents and other fields. In the prior art, when a tapeline is in use, the tape end part and the measuring terminal end of the tape need to be respectively leveled with the starting end and the terminal end of the object to be measured, so the measurer needs to use his/her hands or other auxiliary equipment to keep the tape to be fitted onto the object to be measured. Under certain circumstances, a regular tapeline is not convenient to operate and has lower measurement accuracy. For example, in the field of measurement in danger zone, the applicability of a regular tapeline is poor.

(3) Again, in the construction industry for example, tapelines are often used to measure the length of a transverse object hung up from the ground or the distance from the object to a vertical object of reference. Since there is no attaching point for the tapeline, the measurement can only rely on ocular estimation of the start point or the terminal point to be measured from a distance. Therefore, the error of the measured value is large and the measurement accuracy is poor, which will adversely affect the following construction work. If more accurate data of measurement at a height are desired to be acquired by using a tapeline, the measurer needs to establish a supporting frame or use a long ladder to climb high up, to attach the tapeline onto the object to be measured to complete the measurement. If the object to be measured has a great length, two or more workers are then needed to climb high up to complete the measurement, which is troublesome and expensive in labor cost while it is dangerous due to the risk of falling of the measurer from high up.

(4) Moreover, due to the limit of the length of the tapeline, the applications are limited thereby, and the measurement range is relatively limited which can only be used in scenes of smaller space rather than scenes of larger space. The measurement range of a regular tapeline is generally around 5 meters, 7.5 meters or 10 meters. Some specially made tapelines may even have a measurement range up to 15 meters or 20 meters. However, the larger the measurement range of the tapeline is, the larger the volume thereof is and thus the tapeline is inconvenient for carrying and use by the measurer.

(5) Although laser ranging devices in the prior art have higher measurement accuracy, they have larger volumes and higher cost, and are inconvenient for carrying and use. Some of the portable laser ranging devices have smaller volumes and are easy for carrying, but after being used over a long time, the light emitting surface of the laser source and the light receiving surface of the light sensor device will experience relatively large abrasions, such that the light feedback sensitivity and distance measurement accuracy are affected. Moreover, the laser ranging devices have larger errors when detecting short distances, and are quite limited in the field of interior decoration and are difficult to achieve large-scale applications.

SUMMARY OF THE INVENTION

(6) It is an object of the present invention to provide a distance measuring device which solves the technical problems residing in the prior art, such as inconvenience of operation, low measurement accuracy, inconvenience for carrying, etc.

(7) In order to solve the above technical problems, the present invention provides a distance measuring device, including a shell, and a laser ranging device provided at the inside and/or the

outer surface of the shell. The laser ranging device comprises a laser generating means, a photoelectric conversion means, a circuit board and a power supply. The laser generating means is used for emitting measurement beam to the object to be measured; the object to be measured reflects the measurement beam, generating reflected light; the photoelectric conversion means is used for capturing all or part of the reflected light and converting the optical signal of the captured reflected light into at least one feedback electrical signal; the power supply is connected to the laser generating means, the photoelectric conversion means and the circuit board. At least one processor is provided on the circuit board; the processor is connected to the laser generating means for controlling the laser generating means; the processor is connected to the photoelectric conversion means for acquiring the feedback electrical signal and calculating a distance from the object to be measured to the distance measuring device.

(8) Further, the laser generating means comprises a light emitting surface; the photoelectric conversion means comprises a light receiving surface provided beside the light emitting surface; the light emitting surface and the light receiving surface are disposed in a side by side arrangement or in an up and down arrangement on the outer surface of the shell. Or, the laser generating means comprises a light emitting surface; the photoelectric conversion means comprises a light receiving surface provided beside the light emitting surface; the outer surface of the shell is provided with a laser beam emitting port directly facing the light emitting surface and a light receiving hole directly facing the light receiving surface and provided beside the laser beam emitting port; the laser beam emitting port and the light receiving hole are disposed in a side by side arrangement or in an up and down arrangement; the light emitting surface emits the measurement beam through the laser beam emitting port; and the light receiving surface captures the reflected light through the light receiving hole.

(9) Further, the center point of the light receiving surface is located on the same straight line as the center point of the light emitting surface; and the area of the light receiving surface is 3 to 10 times the area of the light emitting surface.

(10) Further, the distance measuring device also includes a tapeline structure disposed within the shell.

(11) Further, the laser generating means and the photoelectric conversion means are both located above or below the tapeline structure; and the power supply is provided on the left or right side of the tapeline structure.

(12) Further, the power supply, the laser generating means and the photoelectric conversion means are all located in front of or behind the tapeline structure; and the laser generating means and the photoelectric conversion means are both located above or below the power supply, or on the left or on the right side of the power supply.

(13) Further, the power supply is located in front of or behind the tapeline structure; and the laser generating means and the photoelectric conversion means are located on the left or on the right side of the tapeline structure.

(14) Further, the circuit board is disposed horizontally above the tapeline structure; or the circuit board is vertically disposed on the left or right side of the tapeline structure.

(15) Further, the tapeline structure comprises a tapeline wheel, a tape, a tape outlet, a pressure piece and a locking key. The tapeline wheel is disposed within the shell; all or part of the tape is wound on the tapeline wheel; one end of the tape is fixedly connected to the tapeline wheel and the other end is provided with a tape end portion; the tape outlet is provided at the lower end of the outer side wall of the shell, and the tape end portion extends out of the shell through the tape outlet; the pressure piece is provided in the shell and adjacent to the tape outlet, for pressing the tape so that the length of the tape outside the shell remains unchanged; and the locking key is provided on an outer surface of the shell, for controlling the pressure piece to press or loosen the tape.

(16) Further, the distance measuring device also includes a second tapeline structure disposed within the second shell; and the second shell is detachably connected to the shell.

(17) Further, the shell is L-shaped; the shell includes a horizontal portion located at an upper portion of the shell and a vertical portion located at a lower portion of the shell; wherein the second shell is detachably connected to the lower left of the shell.

(18) Further, the shell includes at least one first snap slot recessed on a left side face of the vertical portion of the shell; the second shell includes at least one first strip protruding from a right side face of the second shell; when the second shell is connected to the shell, the first strip is snap-fitted to the first snap slot.

(19) Further, the shell includes at least one connecting member, each of which projects downwardly from a bottom surface of the horizontal portion of the shell, the connecting member is adjacent to a left side face of the shell, each connecting member is provided with a nut in the horizontal direction, and the nut faces a left side of the shell; the second shell includes at least one connecting through hole, at least one screw hole and at least one screw, each connecting through hole extends perpendicularly through a top surface of the second shell, the position thereof is corresponding to the position of the connecting member; the screw hole horizontally extends through a left side face of the second shell; when the second shell is connected to the shell, the connecting member passes through the connecting through hole, each nut corresponds to a screw hole, and the corresponding nut and screw hole are located on the same straight line; and each screw passes through a screw hole and is fixed on a nut corresponding to the screw hole.

(20) Further, the second tapeline structure includes a second tapeline wheel, a second tape, a second tape outlet, a second pressure piece and a second locking key. The second tapeline wheel is disposed within the second shell; all or part of the second tape is wound on the second tapeline wheel; one end of the second tape is fixedly connected to the second tapeline wheel, and the other end is provided with a second tape end portion; and the second tape outlet is provided at a lower end of the outer side wall of the second shell, the second tape end portion extends out of the second shell through the second tape outlet. The second pressure piece is provided in the second shell and adjacent to the second tape outlet, for pressing the second tape so that the length of the second tape outside the second shell remains unchanged; and the second locking key is provided on an outer surface of the second shell, for controlling the second pressure piece to press or loosen the second tape.

(21) Further, the second shell includes a rectangular through hole vertically extending through a top surface of the second shell and positioned above the second tapeline wheel. The shell includes an arcuate groove recessed on a bottom surface of the shell and located above the rectangular through hole; when the second shell is connected to the shell, an upper portion of the second tape wound on the second tapeline wheel passes through the rectangular through hole and is disposed within the arcuate groove.

(22) The distance measuring device further includes an outer casing of shell, which is a transverse U-shape; when the second shell is connected to the shell, the outer casing of shell is coated on an outer surface of the shell and the second shell.

(23) The shell includes at least one second snap slot recessed on a front side face and a back side face of the vertical portion of the shell; the outer casing of shell includes at least one second strip protruding from an inner side face of the outer casing of shell and corresponding to the second snap slot; when the outer casing of shell is coated on the outer surface of the shell, the second strip is snap-fitted to the second snap slot.

(24) The outer casing of shell comprises a first outer casing through hole, a second outer casing through hole, a third outer casing through hole, a first outer casing notch and a second outer casing notch. The first outer casing through hole extends through a top surface of the outer casing of shell, corresponding to the display means; the second outer casing through hole extends through a right side face of the outer casing of shell, corresponding to the power supply; the third outer casing through hole extends through a bottom surface of the outer casing of shell, corresponding to the locking key; the first outer casing notch is provided on a left side face of an upper portion of the

outer casing of shell; and the second outer casing notch is provided on a left side face of a lower portion of the outer casing of shell.

(25) Further, the distance measuring device also includes a display means connected to the processor, for displaying the distance from the object to be measured to the distance measuring device. The display means is provided on the outer surface of the shell, preferably, an upper surface, a front surface or a rear surface of the shell.

(26) Further, the distance measuring device also includes an operating means connected to the processor, for transmitting at least one control instruction to the laser ranging device. The operating means comprises an operation panel and an operation circuit board, the operation panel is provided on an upper surface, a front surface or a rear surface of the shell, for inputting at least one control action, and each of the control actions corresponds to a control instruction; and the operation circuit board is disposed below the operation panel and is connected to the processor, for converting the at least one control action into at least one electrical signal and transmitting the electrical signal to the processor; each of the electrical signals corresponds to a control instruction; and the control instructions comprise, but are not limited to, start instructions, close instructions, and store instructions.

(27) Further, the circuit board is provided with a memory connected to the processor, for storing the distance from the object to be measured to the distance measuring device.

(28) Further, the laser generating means comprises, but is not limited to, a laser tube; the photoelectric conversion means comprises, but is not limited to, a photoelectric sensor; the power supply comprises, but is not limited to, a button battery, a rectangular battery or a cylindrical battery.

(29) In order to improve assembly efficiency, of the distance measuring device of the present invention, simplify its structure and impart to it other functions than long distance ranging and short distance ranging, the present invention provides another distance measuring device comprising: a first housing having an accommodating space; and a laser ranging device provided in the accommodating space of the first housing; a tapeline structure, the tapeline structure integrated with the laser ranging device into one piece, wherein the laser ranging device is arranged along a radial direction or an axial direction of the tapeline structure.

(30) Further, the laser ranging device comprises: a laser generating means for emitting a measurement beam to an object to be measured; a photoelectric conversion means for receiving a reflected beam reflected from the object to be measured and converting it into at least one feedback electric signal; a circuit board provided thereon with at least one processor; and a power supply connected to the laser generating means, the photoelectric conversion means and the circuit board.

(31) Further, the power supply is a rechargeable battery, the laser ranging device is provided thereon with a charging port, the first housing provided therein with a through hole matching the charging port.

(32) Further, the tapeline structure is provided in the first housing, a laser module made up of the laser generating means, the photoelectric conversion means and the power supply is provided at an edge in the radial direction or on an end face in the axial direction of the tapeline structure.

(33) Further, the tapeline structure comprises: a tapeline wheel provided in the first housing; a tape entirely or partially wound on the tapeline wheel, one end of the tape fixedly connected to the tapeline wheel, the other end thereof provided with a tape end portion; a first tape outlet provided in a side wall of the first housing, the tape end portion extending out of the first housing through the first tape outlet; a pressure piece for pressing the tape so that a length of the tape outside the first housing is kept constant; and a locking key provided on an outer surface of the first housing and used to control the pressure piece to press or loosen the tape.

(34) Further, the tapeline structure further comprises a tapeline casing, which is provided in the first housing, and in which the tapeline wheel is provided; the tape successively passes through a second tape outlet in the tapeline casing and the first tape outlet; the pressure piece is provided near the

second tape outlet or the first tape outlet.

(35) Further, the first housing is provided therein with a locating post, the locating post connected to the tapeline casing so that the tapeline casing is located within the first housing.

(36) Further, the tapeline structure further comprises: a locating member, which is located in the first housing, and to which a rotating shaft of the tapeline wheel is connected; the locating member comprising at least one locating portion, the locating portion provided at a circular circumferential edge of the tapeline wheel.

(37) Further, the locating member comprises a first locating portion and a second locating portion.

(38) Further, the locating member comprises an engagement portion, the engagement portion engaged in the rotating shaft of the tapeline wheel.

(39) Further, the locating member comprises three locating portions.

(40) Further, the housing is provided therein with a shaft shank, the shaft shank located at the middle of the locating member, the tapeline wheel is rotatably connected to the shaft shank.

(41) Further, the shaft shank is integrally formed with the first housing.

(42) Further, one end of the shaft shank is restricted in position by a stepped shaft with respect to the first housing, the other end of the shaft shank is fixedly connected to the locating member.

(43) Further, the laser ranging device further comprises: a display means and an operating means, the display means and the operating means both disposed on the end face in the axial direction or at the edge in the radial direction of the tapeline structure.

(44) Further, the laser ranging device further comprises a display means, the display means provided on a side wall of the first housing, one end of the display means rotatably connected to the first housing through a first rotating shaft, the other end of the display means defining a push end; the pressure piece is provided near the first tape outlet; the push end is connected to the pressure piece through a transmission mechanism.

(45) Further, the transmission mechanism comprises a first rotating element and a connecting rod, the first rotating element rotatably connected to the first housing through a second rotating shaft, one end of the first rotating element connected to the push end so as to move with the push end, the other end connected to one end of the pressure piece through the connecting rod; the pressure piece rotatably connected to the first housing through a third rotating shaft, the other end of the pressure piece configured to press the tape or loosen the tape.

(46) Further, the first housing comprises a first housing portion and a second housing portion, the first housing portion joined to the second housing portion to form the first housing defining the accommodating space.

(47) Further, the distance measuring device further comprises a second housing; the tapeline structure is provided in the second housing; the first housing is detachably connected to the second housing through a connecting structure.

(48) Further, the first housing is provided on a side thereof facing toward the second housing with an arcuate recessed portion, the second housing is provided on a side thereof facing toward the first housing with an arcuate raised portion in engagement with the arcuate recessed portion.

(49) Further, the connecting structure comprises a connecting protrusion provided on the side of the first housing facing toward the second housing and a connecting recess provided on the side of the second housing facing toward the first housing, the connecting protrusion inserted in the connecting recess.

(50) Further, a first side surface of the first housing facing toward the second housing is a flat surface, a second side surface of the second housing facing toward the first housing is a flat surface.

(51) Further, the connecting structure comprises a connecting slide channel provided on the first side surface and a fin which is provided on the second side surface and slidable into the connecting slide channel.

(52) Further, the distance measuring device comprises a laser module, one end of the laser module

provided with the laser ranging device, the other end of the laser module provided with a second device, wherein the second device is any one or more selected from a laser spot projector, a laser line projector, a laser cross projector and a temperature measuring device.

(53) Further, the laser module is provided on the end face in the axial direction of the tapeline structure, the first housing is provided with a raised portion, the raised portion defining a second accommodating space, the laser module is located within the second accommodating space.

(54) Further, the tapeline structure comprises a sensing component, the sensing component configured to detect a displacement distance of the tape in the tapeline structure.

(55) Further, the distance measuring device further comprises a display means, the display means configured to display a measurement of the laser ranging device and/or a measurement of the tapeline structure.

(56) Further, the display means is configured so that, when the distance measuring device is switched to distance measuring by the laser ranging device, the display means displays the measurement of the laser ranging device, and when the distance measuring device is switched to distance measuring by the tapeline structure, the display means displays the measurement of the tapeline structure.

(57) Further, the display means is configured so that, when the tape in the tapeline structure is moving, the display means displays a measurement of the tapeline structure, and when the distance measuring device is switched to distance measuring by the laser ranging device, the display means displays the measurement of the laser ranging device.

(58) Further, the display means is configured to display both the measurement of the laser ranging device and the measurement of the tapeline structure.

(59) Further, the distance measuring device comprises a communication component, the communication component configured to communicate with a terminal to transmit measurement data.

(60) Further, the sensing component comprises a Hall sensing device, a sensing component of the Hall sensing device is always in contact with the tape.

(61) Further, the Hall sensing device comprises a roller, a connecting member and a resilient member, the roller disposed at one end of the connecting member and located at a radial edge location of the tapeline structure, the roller kept in contact with the tape wound on the tapeline wheel in the tapeline structure, the other end of the connecting member connected to the resilient member, the resilient member configured to apply a torque to the connecting member to bias the roller toward the tapeline structure.

(62) Further, the sensing component comprises a marking code identification component, the tape is provided thereon with marking codes, the marking code identification component configured to identify the marking codes.

(63) The present invention is advantageous in providing a distance measuring device, which is effectively improved over conventional laser ranging devices to have an extended service life and not show degraded light feedback sensitivity or measurement accuracy even after long-term use. Combining a tapeline with a laser ranging device, the present invention provides both short distance ranging and long distance ranging functions and a range of advantages including ease of operation, convenience of carrying, low cost and high measurement accuracy. It is suitable to be widely promoted and applied in building and construction, interior decoration, measurement in dangerous areas and other fields. The present invention modularizes the tapeline and thereby allows it to be conveniently mounted within the single housing along with a laser ranging device, resulting in increased assembly efficiency. Alternatively, the tapeline and the laser ranging device may be provided in separate housings. Moreover, the two can be conveniently integrated, or separated for individual use, achieving convenience of both carrying and use. Further, the present invention extends the functionality of the laser ranging device. In addition to laser-based long distance ranging, laser spot projection, line projection, temperature measuring and other functions can be

imparted to it as actually needed. According to the present invention, the sensing component may be provided to sense a displacement length of the tape, from which a numerical measurement of the tapeline can be derived. Compared with manual measurement reading of the tapeline, higher accuracy can be achieved. Furthermore, the present invention allows the distance measuring device to communicate with the terminal and store data in the terminal, facilitating data analysis and storage.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an overall schematic structural view of Embodiment 1 of the invention;
- (2) FIG. 2 is a schematic structural view of Embodiment 1 of the invention after the front side face of the shell is opened;
- (3) FIG. 3 is a schematic structural view of Embodiment 1 of the invention after the back side face of the shell is opened;
- (4) FIG. 4 is a schematic structural view of Embodiment 1 of the invention after the shell is removed;
- (5) FIG. 5 is a structural block diagram of the circuit in Embodiment 1 of the invention;
- (6) FIG. 6 is an overall schematic structural view of Embodiment 2 of the invention;
- (7) FIG. 7 is a schematic structural view of Embodiment 2 after the front side face of the shell is opened;
- (8) FIG. 8 is a schematic structural view of Embodiment 2 of the invention viewed from another angle after the front side face of the shell is opened;
- (9) FIG. 9 is an overall schematic structural view of Embodiment 3 of the invention;
- (10) FIG. 10 is a schematic structural view of Embodiment 3 of the invention after the front side face of the shell is opened;
- (11) FIG. 11 is a schematic structural view of Embodiment 3 of the invention viewed from another angle after the front side face of the shell is opened;
- (12) FIG. 12 is an overall schematic structural view of Embodiment 4 of the invention;
- (13) FIG. 13 is a schematic structural view of Embodiment 4 of the invention after the front side face of the shell is opened;
- (14) FIG. 14 is a schematic structural view of Embodiment 4 of the invention after the shell is removed;
- (15) FIG. 15 is an overall schematic structural view of Embodiment 5 of the invention;
- (16) FIG. 16 is an exploded schematic structural view of Embodiment 5 of the invention;
- (17) FIG. 17 is a schematic structural view of Embodiment 5 after the back side face of the shell is opened;
- (18) FIG. 18 is a schematic structural view of the left lower side face of the shell in Embodiment 5 of the invention;
- (19) FIG. 19 is a schematic structural view of the second shell in Embodiment 5 of the invention;
- (20) FIG. 20 is a schematic structural view of Embodiment 5 of the invention after the front side face of the second shell is opened;
- (21) FIG. 21 is a schematic structural view of the outer casing of the shell in Embodiment 5 of the invention;
- (22) FIG. 22 is a schematic structural view of the outer casing of the shell in Embodiment 5 of the invention viewed from another angle;
- (23) FIG. 23 is an overall schematic structural view of a distance measuring device according to Embodiment 6 of the present invention;
- (24) FIG. 24 is a side view of the distance measuring device according to Embodiment 6 of the

present invention;

(25) FIG. **25** is a schematic structural view of a backside of the distance measuring device according to Embodiment 6 of the present invention;

(26) FIG. **26** is an exploded schematic view of the distance measuring device according to Embodiment 6 of the present invention;

(27) FIG. **27** is a schematic structural view of a laser module according to Embodiment 6 of the present invention;

(28) FIG. **28** is a schematic structural view of the interior of the distance measuring device according to Embodiment 6 of the present invention;

(29) FIG. **29** is an exploded schematic view of a tapeline structure according to Embodiment 6 of the present invention;

(30) FIG. **30** is a schematic view of the interior of a distance measuring device according to Embodiment 7 of the present invention;

(31) FIG. **31** is a schematic structural view of a tapeline structure according to Embodiment 7 of the present invention;

(32) FIG. **32** is a front view of the tapeline structure according to Embodiment 7 of the present invention;

(33) FIG. **33** is a schematic cross-sectional view of the tapeline structure according to Embodiment 7 of the present invention;

(34) FIG. **34** is a schematic structural view of a distance measuring device according to Embodiment 8 of the present invention;

(35) FIG. **35** is a schematic structural view of the interior of the distance measuring device according to Embodiment 8 of the present invention;

(36) FIG. **36** is a schematic structural plan view of the interior of the distance measuring device according to Embodiment 8 of the present invention;

(37) FIG. **37** is a schematic structural view of a distance measuring device according to Embodiment 9 of the present invention;

(38) FIG. **38** is an exploded schematic view of the distance measuring device according to Embodiment 9 of the present invention, showing an arcuate recessed portion and an arcuate raised portion;

(39) FIG. **39** is an exploded schematic view of the distance measuring device according to Embodiment 9 of the present invention, showing connecting slide channels;

(40) FIG. **40** is a schematic view of a second shell in the distance measuring device according to Embodiment 9 of the present invention, showing fins;

(41) FIG. **41** is a schematic structural view of a distance measuring device according to Embodiment 10 of the present invention, showing a laser ranging device;

(42) FIG. **42** is a schematic structural view of the distance measuring device according to Embodiment 10 of the present invention viewed from another angle, showing a second device;

(43) FIG. **43** is a schematic structural view of a distance measuring device according to Embodiment 11 of the present invention;

(44) FIG. **44** is an exploded schematic view of FIG. **43**;

(45) FIG. **45** is a schematic view of FIG. **44** viewed from another angle;

(46) FIG. **46** is a schematic structural view of a distance measuring device according to Embodiment 12 of the present invention;

(47) FIG. **47** is a top view of FIG. **46**;

(48) FIG. **48** is a schematic cross-sectional view of FIG. **47** taken along A-A;

(49) FIG. **49** is a schematic structural view of the interior of Embodiment 12;

(50) FIG. **50** schematically illustrates measurements displayed on a display means in Embodiment 12;

(51) FIG. **51** schematically illustrates communication carried out between the distance measuring

device and a terminal in Embodiment 12;

(52) FIG. 52 is a schematic structural view of the interior of Embodiment 13;

(53) FIG. 53 is a schematic view of a tape in Embodiment 13;

(54) FIG. 54 is a schematic structural view of a distance measuring device according to Embodiment 14; and

(55) FIG. 55 shows the structure of a shaft shank in Embodiment 14.

LIST OF REFERENCE NUMERALS IN DRAWINGS

(56) **1** shell, **2** laser ranging device, **3** tapeline structure, **4** second shell, **5** second tapeline structure, **6** outer casing of the shell, **7** clip; **11** front side face, **12** back side face, **13** left side face, **14** right side face, **15** top face, **16** bottom face, **17** laser beam emitting port, **18** light receiving hole; **21** laser generating means, **22** photoelectric conversion means, **23** circuit board, **24** display means, **25** operating means, **26** power supply; **31** tapeline wheel, **32** tape, **33** tape outlet, **34** pressure piece, **35** locking key, **36** tape end portion; **51** second tapeline wheel, **52** second tape, **53** second tape outlet, **54** second pressure piece, **55** second locking key, **56** second tape end portion; **101** horizontal portion, **102** vertical portion, **103** first snap slot, **104** connecting member, **105** nut, **106** arcuate groove, **107** second snap slot; **211** light emitting surface, **221** light receiving surface, **231** processor, **232** memory; **251** operation panel, **252** operation circuit board, **253** press button; **401** first strip, **402** connecting through hole, **403** screw hole, **404** screw, **405** rectangular through hole; **601** second strip, **602** first outer casing through hole, **603** second outer casing through hole, **604** third outer casing through hole, **605** first outer casing notch, **606** second outer casing notch; **610** housing, **611** accommodating space, **612** first housing portion, **613** second housing portion, **614** first tape outlet, **615** second tape outlet, **616** first through hole, **617** locating post, **620** third tapeline structure, **621** tapeline casing, **20** laser module, **631** charging port, **632** battery; **720** fourth tapeline structure, **721** locating member, **722** first locating portion, **723** second locating portion, **724** rotating shaft, **725** engagement portion; **810** housing, **811** first side wall, **812** second side wall, **820** fifth tapeline structure, **821** pressure piece, **822** third rotating shaft, **823** resilient element, **830** display means, **831** push end, **832** first rotating shaft, **833** transmission line, **840** transmission mechanism, **841** first rotating element, **842** connecting rod, **843** extension, **844** second rotating shaft; **910** first housing, **911** second housing, **912** arcuate recessed portion, **913** arcuate raised portion, **920** sixth tapeline structure, **930** connecting structure, **931** connecting protrusion, **932** stud, **934** connecting slide channel, **935** fin, **936** first connecting sheet, **937** second connecting sheet; **1001** laser ranging device, **1002** second device; **1110** housing, **1111** raised portion, **1112** second accommodating space, **1113** light receiving hole, **1114** laser beam emitting port, **1115** battery hatch, **1120** seventh tapeline structure, **1121** spacer, **1122** base portion, **1123** annular portion; **1210** housing, **1211** tape exit port, **1220** eighth tapeline structure, **1221** support frame, **1222** tapeline wheel, **1223** tape, **1224** tape locking button, **1225** pressure piece, **1230** sensing component, **1231** connecting member, **1232** roller, **1233** resilient member; **241** laser ranging measurement, **242** tapeline-based distance measuring measurement, **1240** terminal; **1330** marking code identification component, **1331** marking code; **1420** ninth tapeline structure, **1421** locating member, **1422** locking means, **1423** locating portion, **1424** body, **1425** screw, **1426** shaft shank.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(57) Five preferred embodiments of the present invention will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown, for the purpose of clarity and better understanding of the techniques. This invention may be embodied in various different forms and the invention should not be construed as being limited to the embodiments set forth herein.

(58) In the description, elements with identical structure are marked with the same reference numerals, and like elements with similar structure or function are marked throughout with like reference numerals, respectively. The dimension and thickness of each element in the accompanying drawings are arbitrarily shown, and the invention does not define the dimension and

thickness of each element. Certain parts may be shown somewhat exaggerated in thickness in the interest of clarity.

(59) Directional terms described by the present invention, such as upper, lower, front, back, left, right, inner, outer, side, etc., are only directions by referring to the accompanying drawings, and are thus used to explain and describe the present invention, but the present invention is not limited thereto.

(60) It will be understood that when an element is referred to as being “on/above” another element, it can be directly placed on the other element, or there may be an intermediate element on which it is placed, and the intermediate element is placed on the other element. When an element is referred to as being “mounted to” or “connected to” another element, either one can be understood as being directly “mounted” or “connected”, or via an intermediate element to be indirectly “mounted to” or “connected to” the other element.

Embodiment 1

(61) As shown in FIGS. 1-3, Embodiment 1 provides a distance measuring device that can independently implement laser ranging, which includes a shell **1** and a laser ranging device **2**. The laser ranging device **2** is provided in the interior of the shell and/or on the outer surface thereof.

(62) As shown in FIG. 1, the shell **1** is an irregular cuboid having the width thereof equal to or approximately equal to the height thereof, and the thickness thereof is about 25% to 40% of the width thereof. The shell **1** has six faces, namely the front side face **11**, the rear side face **12**, the left side face **13**, the right side face **14**, the top face **15**, and the bottom face **16**.

(63) As shown in FIGS. 2 and 3, the laser ranging device **2** includes a laser generating means **21**, a photoelectric conversion means **22**, a circuit board **23**, a display means **24**, an operating means **25**, and a power supply **26**. The laser generating means **21** is preferably a laser tube, that is, a glass sealed-off CO₂ laser, but is not limited to a laser tube, and may be other means for generating a laser beam. The photoelectric conversion means **22** is preferably a photoelectric sensor, but is not limited to a photoelectric sensor, or may be other means for capturing light and converting the optical signal into an electrical signal. The laser generating means **21** and the photoelectric conversion means **22** may be arranged in a side by side arrangement or in an up and down arrangement. In this embodiment, the laser generating means **21** is integrated with the photoelectric conversion means **22**.

(64) As shown in FIG. 4, the laser generating means **21** includes a light emitting surface **211**, and the photoelectric conversion means **22** includes a light receiving surface **221**. The light receiving surface **221** is disposed beside the light emitting surface **211** and is adjacent to the light emitting surface **211**. The two may be provided in a side by side arrangement or in an up and down arrangement.

(65) As shown in FIG. 5, at least one processor **231** is provided on the circuit board **23**. The processor **231** is connected to the laser generating means **21** for controlling the normal operation of the laser generating means **21**. The processor **231** is connected to the photoelectric conversion means **22** for acquiring the feedback electric signal and calculating the distance from the object to be measured to the distance measuring device of the present embodiment. Alternatively, a memory **232** may be provided on the circuit board **23**, the memory **232** is connected to the processor **231** for storing the distance from the object to be measured to the distance measuring device so that the user can check the reading record again from the display means **24** when the user forgets the reading.

(66) In the present embodiment, the processor **231** issues a control signal instructing the laser generating means **21** to emit a laser beam as a measurement beam to the object to be measured. The measurement beam forms a reflection on the surface of the object to be measured, producing reflected light and a portion of the reflected light parallel to the measurement beam can be captured by the photoelectric conversion means **22** and converted into an electrical signal to be fed back to the processor **231**. The inside of the processor **231** may be provided with a timer for recording the

time point at which the laser beam is emitted from the laser generating means **21** and the time point at which the feedback electric signal is obtained. Based on the time difference between the two time points, it is possible to calculate the distance between the object to be measured and the distance measuring device. During the above mentioned time period, the laser beam travels back and forth between the object to be measured and the distance measuring device at the speed of light, and the half of the product of the time difference and the speed of light is the distance to be measured between the object to be measured and the distance measuring device.

(67) In the present embodiment, the light emitting surface of the laser generating means and the light receiving surface of the photoelectric conversion means may be both provided on the outer surface of the shell (such as the left side face **13** of the shell), the laser generating means **21** emits a laser beam as a measurement beam from the light emitting surface **211**, and photoelectric conversion means **22** captures the external reflected light through the light receiving surface **221**. Since the laser beam is always perpendicular to the plane where the light emitting surface **211** is located, the light emitting surface **211** can be used to assist the user in aiming at the object to be measured; thus the laser beam can be directly irradiated to the object to be measured. In order to ensure the reflection effect, the laser beam is preferably directly irradiated to the plane on the object to be measured, and making the laser beam be vertically irradiated to the plane as much as possible, so that more light can be reflected back to the distance measuring device, making the measurement results more accurate.

(68) If the light emitting surface and the light receiving surface are provided on the outer surface of the shell, it is prone to be worn during transportation, use and storage. After long-term use, the light feedback sensitivity and measurement accuracy of the rangefinder is reduced due to the wear, and the service life is reduced. For this reason, the present embodiment also provides the following technical solutions.

(69) As shown in FIGS. **1** to **4**, the shell **1** is provided with a laser beam emitting port **17** and a light receiving hole **18**, and the laser beam emitting port **17** directly faces the light emitting surface **211**, and the light receiving hole **18** directly faces the light receiving surface **221**. Since the light emitting surface **211** and the light receiving surface **221** are adjacent to each other, the laser beam emitting port **17** and the light receiving hole **18** are also disposed adjacent to each other. In the present embodiment, the laser beam emitting port **17** and the light receiving hole **18** are both provided on the left side face **5** of the shell.

(70) The light emitting surface **211** and the light receiving surface **221** are completely disposed inside the shell **1** instead of on the surface of the shell **1**. The light emitting surface **211** and the light receiving surface **221** can be protected from abrasion, and the influences on the electrical device caused by the dust and the moisture in the surrounding environment can be reduced. It is possible to further improve the service life of the light emitting surface **211** and the light receiving surface **221** without affecting normal operations of the laser generating means **21** and the photoelectric conversion means **22**, and to ensure the light feedback sensitivity and the measurement accuracy of the distance measuring device.

(71) The laser generating means **21** emits a laser beam as a measurement beam through the laser beam emitting port **17**, and the photoelectric conversion means **22** captures external reflected light through the light receiving hole **18**. Since the laser beam is always perpendicular to the plane where the laser beam emitting port **17** is located, the laser beam emitting port **17** is used to assist the user in aiming at the object to be measured, so that the laser beam can be directly irradiated to the object to be measured, and in order to ensure the reflection effect, the laser beam is preferably directly irradiated to a plane on the object to be measured, and making the laser beam be vertically irradiated to the plane as much as possible, so that more light can be reflected back to the distance measuring device, making the measurement results more accurate.

(72) In the present embodiment, the center point of the light emitting surface **211** is located on the same straight line as the center point of the light receiving surface **221**, and the closer the distance

between the light emitting surface **211** and the light receiving surface **221** and between the light receiving hole **18** and the laser beam emitting port **17** is, the smaller the error is. Theoretically speaking, if the center point of the light emitting surface **211** completely coincides with the center point of the light receiving surface **221**, the error is minimum, but it is currently difficult to realize. (73) In the conventional case, the area of the light receiving surface **221** is 3 to 10 times the area of the light emitting surface **211**. Since the laser beam that is emitted can be kept along a straight line, after the laser beam is reflected by the surface of the object to be measured, it is difficult to ensure sufficient intensity and amount of the light that can be returned along the original path back to the vicinity of the light emitting surface **211** if the object to be measured is not a mirror surface with excellent reflection effect, even if the laser beam can be irradiated vertically onto the object to be measured. Therefore, the area of the light receiving surface **221** may be appropriately enlarged to further improve the measurement accuracy and improve the feedback sensitivity.

(74) Since the light emitting surface **211** and the light receiving surface **221** may be disposed in a side by side arrangement or in an up and down arrangement, the laser beam emitting port **17** and the light receiving hole **18** may thus also be disposed in a side by side arrangement or in an up and down arrangement. The laser beam emitting port **17** is slightly larger than the light emitting surface **211**, and the light receiving hole **18** is slightly larger than the light receiving surface **221**. Since the area of the light receiving surface **221** is normally 3 to 10 times the area of the light emitting surface **211**, the area of the light receiving hole **18** is also 3 to 10 times the area of the laser beam emitting port **17**.

(75) In the present embodiment, the display means **24** is preferably a display screen provided on the outer surface of the shell **1** and connected to the processor **231** for displaying the distance from the object to be measured to the distance measuring device.

(76) In the present embodiment, the operating means **25** is provided on the outer surface of the shell **1** and is connected to the processor **231** for transmitting at least one control instruction to the laser ranging device **21**.

(77) The operating means **25** includes an operation panel **251** and an operation circuit board **252**. The operation panel **251** is preferably provided on the upper surface of the shell **1**, or on the front surface or the rear surface of the shell **1**. The operation panel **251** is used for inputting at least one control action, and each of the control actions corresponds to a control instruction. The operation circuit board **252** is disposed below the operation panel **251** and is connected to the processor **231**. The operation circuit board **252** converts the at least one control action into at least one electrical signal and sends the electrical signal to the processor **231**. Each of the electrical signals corresponds to a control instruction. In the present embodiment, the operation panel **251** is provided with three keys **253** corresponding to three control instructions respectively, namely, a start instruction, a close instruction, a storage instruction for starting the distance measuring device, closing the distance measuring device or storing the distance from the object to be measured to the distance measuring device. The user operates the operation panel **251**, presses a certain button to input a control instruction, and the operation panel **251** simultaneously records a control action, and the operation circuit board **252** converts the control instruction inputted by the user using the key into an electric signal, and according to the key that is pressed, an electrical signal containing a control instruction is transmitted to the processor **231**. The operation panel **251** may also be provided with other keys **253** to input more control instructions.

(78) In order to facilitate user operation and use, the display means **24** and the operating means **25** of the present embodiment are preferably provided on the upper surface of the shell **1** (the outer surface of the top surface **15**), and the user looks down and can readily see the operation panel **251** and operate the distance measuring means as well as read the readings of the distance to be measured. The display means **24** and the operating means **25** can be integrally designed, that is, adopting a touch screen, and an operation control function and a reading display function are realized at the same time. Due to the high cost of the touch screen, this scheme is still more or less

limited in applications.

(79) In the present embodiment, the power supply **26** may be a button battery, a rectangular battery or two parallel-arranged cylindrical batteries. The size of a button battery is small, taking up small space, and the distance measuring device can be provided in a smaller size. Rectangular cells, cylindrical batteries have greater battery power than the button battery, needing less times of battery replacement, which can reduce the cost in use, but the size thereof are larger, which makes it inconvenient to carry. Both of the rectangular battery and the cylindrical battery may be a rechargeable battery, thereby further reducing the cost in use.

(80) The present embodiment also provides a fixed mounting plate (not shown), which can be connected and fixed to the shell **1** by means of a screw nut or the like, and the laser generating means **21**, the photoelectric conversion means **22**, the circuit board **23**, the tapeline structure **3**, etc. can be all mounted on the fixed mounting plate.

(81) The technical effect of the first embodiment is to provide a laser ranging device capable of independently realizing the ranging function, which can effectively protect the light emitting surface of the laser generating means and the light receiving surface of the photoelectric conversion device as compared with conventional laser ranging device, reducing unnecessary wear, having good dustproof and waterproof effect, effectively prolonging the service life of components, and ensuring relatively high light feedback sensitivity and higher measurement accuracy even after long-term use.

Embodiment 2

(82) The distance measuring device according to Embodiment 1 only has a laser ranging function and is more suitable for long distance ranging, and in a case where the distance to be measured is shorter, for example, when the distance to be measured is less than 1 m or 2 m, the error of the laser ranging device will be quite large and the measurement accuracy will be lower.

(83) In view of this, Embodiment 2 provides another technical solution, which includes all the technical solutions of Embodiment 1, and the distinguishing technical feature is characterized in that, as shown in FIGS. **6-8**, a tapeline structure **3** is also provided in the shell **1**. In the shell **1**, the laser ranging device **2** and the tapeline structure **3** are provided at the same time, and the gap of the shell can be reduced to enhance the dustproof and waterproof effects.

(84) As shown in FIGS. **6-8**, the tapeline structure **3** includes a tapeline wheel **31**, a tape **32**, a tape outlet **33**, a pressure piece **34**, and a locking key **35**. The tapeline wheel **31** is provided in the shell **1**; the tape **32** is wound on the tapeline wheel **31** in whole or in part; one end of the tape **32** is fixedly connected to the tapeline wheel **31** and the other end is provided with a tape end portion **36**. The tape outlet **33** is provided at the lower end of the outside wall of the shell **1**, and the tape end portion **36** extends beyond the shell **1** through the tape outlet **33**, and the pressure piece **34** is provided inside the shell **1** and near the tape outlet **33**. When the tape **32** is pulled out of the shell **1**, the pressure piece **34** can be used to press the tape **32** so that the length of the tape **32** outside the shell **1** is kept constant. The locking key **35** is provided on the outer surface of the shell **1** for controlling the pressure piece **34** to press or loosen the tape **33**.

(85) The tapeline structure **3** may also be any of the prior art tapelines. In the work, the tape **32** is pulled out of the shell **1** by the tape end portion **36** to perform the measurement. After the measurement, it is necessary to press down the locking key **35**, in which the pressure piece **34** presses the tape **32** so that the length of the tape **32** outside the shell **1** remains constant so as to allow reading of the length of the tape **32**. In the present embodiment, the locking key **35** is a key provided on the bottom surface **16** of the shell **1**, and after the first pressing, the pressure piece **34** presses the tape **32**; after reading the length value, and after pressing again, the pressure piece **34** releases the tape **32**, and after the length of the tape **32** is read, the tape **32** is retracted into the interior of the shell **1**.

(86) The tapeline structure **3** is preferably as the following scheme: the width of the tape **32** is less than or equal to 2 cm, preferably 1 cm; the length of the tape **32** is less than or equal to 2 m, and the

volume of the tape **32** wound on the tapeline wheel **31** is effectively reduced, the space occupied by the tape **32** in the distance measuring device is reduced, and the width of the distance measuring device is reduced. For the combination of the laser generating means **21** and the photoelectric conversion means **22**, the measurement accuracy will be relatively higher, if the object to be measured is 2 m or more, so the tape length of the tape reaching 2 m will make the present embodiment applicable in various situations.

(87) In the present embodiment, the circuit board **23** is located above the tapeline structure **3** and near the top portion of the shell **1**, which can prevent the circuit board from being pressed by other components in the tapeline structure **3**, and prevent the various components on the circuit board **23** from being damaged caused by being pressed.

(88) As shown in FIGS. **6** to **7**, in the present embodiment, the laser generating means **21** and the photoelectric conversion means **22** are located above the tapeline structure **3**, and the laser generating means **21** and the photoelectric conversion means **22** are disposed in a side by side arrangement to appropriately increase the overall height of the distance measuring device. If the laser generating means **21** and the photoelectric conversion means **22** are disposed in an up and down arrangement, the distance measuring device would be too tall and inconvenient to carry. The laser generating means **21** and the photoelectric conversion means **22** may also be both located below the tapeline structure **3**, which will not be further described here.

(89) As shown in FIGS. **7-8**, the power supply **26** is preferably two cylindrical or rectangular batteries having a thickness less than the shell **1**, either vertically or obliquely provided on the left or right side of the tapeline structure **3**, so as to appropriately increase the overall width of the distance measuring device. If the cylindrical batteries are provided above or below the tapeline structure **3**, the height of the distance measuring device is further increased, so that the appearance of the distance measuring device is incongruous, making it inconvenient to carry and use the device.

(90) In this embodiment, in order for full utilization of the interior space of the tapeline, the laser generating means **21**, the photoelectric conversion means **22**, the circuit board **23** and the power supply **26** are arranged along a radial edge of the tapeline structure **3**. As shown, a tape width of the tapeline structure **3** is chosen as L . Preferably, $L \geq 18$ mm. Preferably, L is 18-33 mm. In this way, in the laser ranging device, a laser module made up of the laser generating means **21** and the photoelectric conversion means **22** has a width (measured along an axis of the tapeline structure) that is substantially the same as a width of the tapeline structure. In this way, the laser ranging device **2** coincides with the tapeline structure **3** in a vertical direction (a radial direction of the tapeline wheel **31** in the tapeline structure **3**), rather than at opposing axial ends of the tapeline wheel **31** in the tapeline structure **3**, resulting in a reduced overall width of the distance measuring device.

(91) As shown in FIG. **6**, the front side face **11** of the shell **1** is also provided with a clip **7** which allows the user to attach the distance measuring device on the belt on the waist by means of the clip **7** for easy carrying.

(92) The technical effect of the second embodiment is to provide a distance measuring device in which the laser ranging device and the tapeline structure are arranged inside the same shell so that the distance measuring device has both a long distance ranging and a short distance ranging function, effectively enhancing the dustproof and waterproof effect at the same time. The thickness of the distance measuring device according to the second embodiment is similar to that of the conventional tapeline, and is convenient for hand gripping, and is convenient for the user to operate and use in the work.

Embodiment 3

(93) The distance measuring device according to the second embodiment increases the height and the width of the distance measuring device to a certain extent, so that the occupancy area of the distance measuring device is relatively large and the device is inconvenient to carry.

(94) For this reason, Embodiment 3 provides another technical solution. Embodiment 3 includes most of the technical solutions of Embodiment 2, and the distinguishing technical feature is characterized in that, as shown in FIGS. 9-11, the power supply 26, together with the laser generating means 21 and the photoelectric conversion means 22, are simultaneously located in front of the tapeline structure 3, increasing the thickness of the distance measuring device to a certain extent and effectively reducing the height and width of the distance measuring device.

(95) Another distinguishing technical feature of Embodiment 3 relative to Embodiment 2 is that, as shown in FIGS. 10-11, the laser generating means 21 and the photoelectric conversion means 22 are located below the power supply 26, the power supply 26 is a cylindrical battery or a rectangular battery, the thickness of which is relatively small, so that the thickness of the distance measuring device will not be too large. Similarly, alternatively, the laser generating means 21 and the photoelectric conversion means 22 may also be located above the power supply 26.

(96) Another distinguishing technical feature of Embodiment 3 relative to Embodiment 2 is characterized in that, as shown in FIGS. 10 to 11, the laser generating means 21 and the photoelectric conversion means 22 are disposed in an up and down arrangement, and the laser generating means 21 is located directly below the photoelectric conversion means 22, thereby appropriately increasing the overall thickness of the distance measuring device so that the thickness of the distance measuring device is not so large. If the laser generating means 21 and the photoelectric conversion means 22 are disposed in a side by side arrangement, the thickness of the distance measuring device will be too large, and it is difficult to be gripped by a hand and the operation is inconvenient.

(97) Similarly, the power supply 26 together with the laser generating means 21 and the photoelectric conversion means 22 may be simultaneously located behind the tapeline structure 3, and the principle thereof is similar to that in the foregoing case and will not be described here.

(98) As shown in FIGS. 9 and 10, the locking key 35 is a sliding key provided on the left side face 13 or the right side face 14 of the shell 1. The locking key 35 can be slid back and forth to effect the pressing or releasing of the tape 32. The locking key 35 may also be a key provided on the bottom surface 16 of the shell 1 in Embodiment 2.

(99) The display means 24 and the operating means 25 of the present embodiment are preferably provided on the upper surface of the shell 1 (the outer surface of the top surface 15) in order to facilitate the operation and use by the user. Once looking down, the user can readily operate the device, and read the distance to be measured. Since the thickness of the distance measuring device described in Embodiment 1 is larger than that of the distance measuring device described in Embodiment 2, the display means 24 can be wider and larger, the display of font is larger and clearer, which further improves the user experience of the reading process.

(100) The technical effect of Embodiment 3 is to provide such a distance measuring device that the distance measuring device has both a long distance ranging and a short distance ranging function, and the laser ranging device and the tapeline structure are arranged in the same shell, further reducing the overall volume, the height and the width of the product. The height and width of the distance measuring device described in Embodiment 3 are similar to those of the conventional tapelines, making it easier for the user to carry, and to operate and use in the work.

Embodiment 4

(101) The distance measuring device according to Embodiment 2 increases the height and the width of the distance measuring device to a certain extent, so that the distance measuring device occupies a relatively large area and is inconvenient to carry. The distance measuring device according to Embodiment 3 increases, to a certain degree, the thickness of the distance device, and the users will hold it in their hands, making the operation inconvenient.

(102) For this reason, Embodiment 4 provides another technical solution. Embodiment 4 includes most of the technical solutions of Embodiment 3, and the distinguishing technical feature is characterized in that, as shown in FIGS. 12 to 14, the power supply 26 is located behind the

tapeline structure **3** to reduce the height or width of the distance measuring device.

(103) Another distinguishing technical feature of Embodiment 4 relative to Embodiment 3 is characterized in that, as shown in FIGS. **13** to **14**, the laser generating means **21** and the photoelectric conversion means **22** are located on the left side of the tapeline structure **3**; the power supply **26** is a cylindrical battery or a rectangular battery of a smaller diameter, having a relatively smaller thickness, so that the thickness of the distance measuring device is not so large.

(104) Another distinguishing technical feature of Embodiment 4 relative to Embodiment 3 is characterized in that, as shown in FIGS. **13** to **14**, the circuit board **23** and the display means **24** are vertically disposed on the left side of the tapeline structure **3**; the laser generating means **21** and the photoelectric conversion means **22** are located behind the circuit board **23**, and the display means **24** is located in front of the circuit board **23**.

(105) The display screen in the display means **24** and the operation panel **251** of the operating means **25** are provided on the front surface of the shell **1** (outer surface of the front side face **11**). Since the area of the front side face **11** and the rear side face **12** of the display means are relatively large, the display screen of the display means **24** and the keys of the operating means **25** can be provided larger, making the operation more convenient and the display clearer. Circuit board **23** and the display means **24** are vertically provided to save more space and reduce the width of the distance measuring device.

(106) The laser generating means **21** and the photoelectric conversion means **22** are disposed in an up and down arrangement, and the laser generating means **21** is located just below the photoelectric conversion means **22**, thereby limiting the thickness of the entire distance measuring device. If the laser generating means **21** and the photoelectric conversion means **22** are disposed in a side by side arrangement, the thickness of the distance measuring device will be too large, and it is difficult to be gripped by hands and the operation is inconvenient.

(107) Similarly, alternatively, the power supply **26** may be located in front of the tapeline structure **3**, the laser generating means **21** and the photoelectric conversion means **22** may be located on the right side of the power supply **26**, and the circuit board **23** and the display means **24** may be vertically provided on the right side of the tapeline structure **3**. The display screen in the display means **24** and the operation panel **215** of the operating means **25** may be provided on the rear surface of the shell **1** (outer surface of the rear side face **12**).

(108) The technical effect of Embodiment 4 is to provide a distance measuring device having functions of long distance ranging and short distance ranging; and setting the laser ranging device and the tapeline structure in the same shell further reduces the overall volume, the height and the thickness of the product; the height and the thickness of the distance measuring device described in Embodiment 4 may be smaller than the ordinary tapeline, making it more convenient to be carried by users; and the display means and the operating means of the distance measuring device described in Embodiment 4 are relatively large, facilitating operation and reading by users.

Embodiment 5

(109) In Embodiments 2-4, the laser ranging device and the tapeline structure are arranged in the same shell, and the volume is significantly larger than that of the ordinary tapeline, the space occupied is relatively large, and it is inconvenient to be carried to a certain extent. For the user, in some special occasions, the user only needs to use the tapeline function or laser ranging function, without the need to use multi-functional laser ranging device. In addition, in Embodiments 2-4, the number of components in the shell is larger, the assembly line is long, the process is difficult, and the production efficiency is low.

(110) In view of this, Embodiment 5 provides another solution, where Embodiment 5 includes all the technical solutions of Embodiment 1 and the distinguishing technical feature is characterized in that, as shown in FIGS. **15** to **16**, the present embodiment may also include a second tapeline structure **5** provided inside the second shell **4**, and the second shell **4** is detachably connected to the shell **1**.


(111) The connection between the second shell **4** and the shell **1** may be respectively provided with connecting means corresponding to each other, for example, a plurality of bayonets are designed on one side of the shell **1**, a plurality of buckles corresponding to the bayonets are designed on one side of the second shell **4**; when they are engaged with each other, they can be integrally fixed together and can have both short distance measurement and long distance measurement functions. The second shell **4** and the shell **1** may be connected in an up and down, left and right or front and rear relation.

(112) As shown in FIGS. **19-20**, the second tapeline structure **5** includes a second tapeline wheel **51**, a second tape **52**, a second tape outlet **53**, a second pressure piece **54**, and a second locking key **55**. The second tapeline wheel **51** is provided inside the second shell **4**, the second tape **52** is entirely or partially wound on the second tapeline wheel **51**, and one end of the second tape **52** is fixedly connected to the second tapeline wheel **51**, and a second tape end **56** is provided at the other end. The second tape outlet **53** is provided at the lower end of the outer side wall of the second shell **4**, the second tape end **56** extends beyond the second shell **4** through the second tape outlet **53**, and the second pressure piece **54** is provided inside the second shell **4** and near the second tape outlet **53**. When the second tape **52** is pulled out of the second shell **4**, the second pressure piece **54** may be used to press the second tape **52** such that the length of the second tape **52** outside the second shell **4** is kept constant; and the second locking key **55** is provided on the outer surface of the second shell **4** for controlling the second pressure piece **54** to press or loosen the second tape **53**.

(113) The interior of the second tapeline structure **5** may be any of the prior art tapelines. In the work, the second tape **52** is pulled out of the second shell **4** by means of the second tape end **56** to complete the measurement, and after the measurement, the second locking key **55** needs to be pressed or toggled, the second pressure piece **54** therein presses the second tape **52** so that the length of the second tape **52** outside of the second shell **4** remains constant so as to facilitate reading the indicated number of the length of the second tape **52**.

(114) The second locking key **55** may be a sliding key provided on the left side face or the right side face of the second shell **4**, and the second tape **52** may be pressed or loosened by sliding the second locking key **55** forward and backward. The second locking key **55** may be a button (not shown) provided on the bottom surface of the second shell **4**, and after the first pressing, the second pressure piece **54** presses the second tape **52**; after reading the indicated number of the length, the second pressure piece **54** loosens the second tape **52** after the button is pressed again.

(115) As shown in FIG. **16**, the front side face of the second shell **4** is provided with a clip **7** which allows the user to attach the distance measuring device on the belt on the waist by means of the clip **7** for easy carrying.

(116) As shown in FIGS. **16 to 18**, in the present embodiment, the shell **1** is an approximately inverted L-shape, similar to the “custom character” shape, the front side face **11** and the rear side face **12** of the shell **1** are approximately inverted L-shape. The shell **1** includes a horizontal portion **101** and a vertical portion **102**, the horizontal portion **101** is horizontally provided on the upper portion of the shell **1**; the vertical portion **102** is located at the lower portion of the shell **1**, and the upper end of the vertical portion **102** is the right end of the horizontal portion **101**; the shell **1** is an inverted L-shape, and there is a certain space at the lower left of the shell, which can accommodate the second shell **4**, and the second shell **4** is detachably connected to the lower left of the shell **1**.

(117) The shell **1** includes at least one first snap slot **103** which is recessed on the left side face of the vertical portion **102** of the shell **1**; the second shell **4** includes at least one first strip **401**, and the first strip **401** protrudes from the right side face of the second shell **4**; when the second shell **4** is connected to the shell **1**, the first strip **401** is engaged with the first snap slot **103**. In the present embodiment, two vertically-provided first snap slots **103** and two vertically-provided first strips **401** are preferred. When the second shell **4** is connected to the lower left of the shell **1**, the first strip **401** is engaged with the first snap slot **103** and acts as a stopper, so that the second shell **4** and

the shell **1** remain relatively fixed.

(118) The shell **1** includes at least one connecting member **104**, each of which projects downwardly from the bottom surface of the horizontal portion **101** of the shell **1**; the connecting member **104** is located near the left side face of the shell **1**; each connecting member **104** is provided with a horizontally oriented nut **105**, and the nut **105** faces the left side of the shell **1**. The second shell **4** includes at least one connecting through hole **402**, at least one screw hole **403** and at least one screw **404**. Each connecting through hole **402** is vertically penetrated through the top surface of the second shell **4** and its position is corresponding to the position of the connecting member **104**. The screw hole **403** is horizontally penetrated through the left side face of the second shell **4**. When the second shell **4** is connected to the shell **1**, the connecting member **104** passes through the connecting through hole **402**; each nut **105** corresponds to a screw hole **403**, and the nuts **105** and the screw holes **403** corresponding to each other are located on the same straight line; each screw **404** is passed through a screw hole **403** and is fixed to the nut **105** corresponding to the screw hole **403**. In the present embodiment, two connecting members **104** and two connecting through holes **402** are preferred. When the second shell **4** is connected to the lower left of the shell **1**, the two connecting members **104** are inserted into the two connecting through holes **402**, the two nuts **105** are opposed to the two screw holes **403**, the two screws **404** are inserted into the nut **105** from the screw holes **403** on the left side face of the second shell **4**, so that the two are fixed to each other.

(119) The second shell **4** includes a rectangular through hole **405** vertically extending through the top surface of the second shell **4** and located above the second tapeline wheel. The shell **1** comprises an arcuate groove **106** recessed on the bottom surface of the shell **1** and located above the rectangular through hole **405**. When the second shell **4** is connected to the shell **1**, the upper portion of the second tape **52** wound on the second tapeline wheel **51** passes through the rectangular through hole **405** and is placed in the arcuate groove **106**. When the second tape **52** is fully wound on the second tapeline wheel **51**, a tapeline disk is formed with a relatively large volume, and the rectangular through hole **405** and the arcuate groove **106** are provided so as to minimize the volume of the distance measuring device to facilitate carrying and use.

(120) In the present embodiment, the shell **1** and the second shell **4** can be relatively fixed only by two sets of screws and nuts as a connecting member, and the advantage is that the removal and installation are convenient and the user can easily detach the two as desired and can only carry or use a part of or the assembled whole part therein; the deficiency lies in that the shell **1** and the second shell **4** are relatively fixed only by the two sets of screws and nuts, and the connection structure is simple and not strong and reliable enough, and it is possible to cause damage to the connection structure upon hitting or dropping, making the two separate and cannot be connected again. For this reason, the present embodiment further provides the following technical solutions.

(121) As shown in FIG. **15**, the distance measuring device according to the present embodiment may further include a shell outer casing **6** which is a “concave” shape in a transverse direction; when the second shell **4** is connected to the shell **1**, the shell outer casing **6** is coated on the outer surface of the shell **1** and the second shell **4**. The shell outer casing **6** may be made of hard material (such as hard plastic, stainless steel, etc.), or elastic material (such as rubber, etc.) may be used so that the combination of the second shell **4** and the shell **1** is more stable, so that the two are not easily separated from each other and at the same time can also play a protective role.

(122) As shown in FIG. **18**, the shell **1** includes at least one second snap slot **107** which is recessed into the front side face and the rear side face of the vertical portion **102** of the shell **1**. As shown in FIGS. **21** and **22**, the shell outer casing **6** includes at least one second strip **601** projecting from the inner side face of the shell outer casing **1** and corresponding to the second snap slot **107**. When the shell outer casing **6** is coated on the outer surface of the shell **1**, the second strip **601** is engaged to the second snap slot **107** so that the shell **1** and the shell outer casing **6** are relatively fixed.

(123) The shell **1** and the shell outer casing **6** are provided with a plurality of corresponding screw holes (not shown) respectively. After the shell outer casing **6** is coated on the outer surface of the

shell **1**, the shell outer casing **6** is fixed to the shell **1** by means of a plurality of screws so that the second shell **4** and the shell **1** are less likely to be disengaged from each other, so that the combination of the two is more stable. This structure can protect the shell **1** and the shell outer casing **6** better because of the large number of fasteners, but it is generally not advisable for the user to separate the shell **1** and the second shell **4** to use due to the inconvenience of detaching. (124) As shown in FIGS. **21** and **22**, the shell outer casing **6** includes a first outer casing through hole **602**, a second outer casing through hole **603**, a third outer casing through hole **604**, a first outer casing notch **605**, and a second outer casing notch **606**. The first outer casing through hole **602** passes through the top surface of the shell outer casing **6**, corresponding to the display means **24** and the operating means **25**, whereby the user can perform the control operation and the data reading. The second outer casing through hole **603** penetrates through the right side face of the shell outer casing **6**, corresponding to the power supply **26**, and the box cover of the battery box is located where the power supply **26** is exposed at the outer wall of the shell **1**, and whereby the battery can be replaced by the user. The third outer casing through hole **604** passes through the bottom surface of the shell outer casing **6** corresponding to second locking key **55**, whereby the user can lock the tape. The first outer casing notch **605** is provided on the left side face of the upper portion of the shell outer casing **6** and corresponds to the laser generating means **21** and the photoelectric conversion means **22**; the second outer casing notch **606** is provided on the left side face of the lower portion of the shell outer casing **6**, corresponding to the second tape outlet **53** so as to ensure that the shell outer casing **6** does not affect the normal operation and use of the laser ranging device and the tapeline structure.

(125) The technical effect of Embodiment 5 is to provide a distance measuring device comprising a detachable laser ranging device and a tapeline structure, both of which can be operated independently, and the user can separate the two or combine them into one as needed to carry or use. When the two are fixed to each other as a whole, it can be applied to both long distance ranging and short distance ranging. The distance measuring device according to Embodiment 5 designs the product as two modules: a laser ranging device and a tapeline structure, which can be produced separately and then assembled into a whole. Such a modular design can effectively improve the production efficiency of the product.

Embodiment 6

(126) As shown in FIGS. **23** to **29**, Embodiment 6 provides a distance measuring device with laser ranging and tapeline-based distance measuring functions, in which a laser ranging device **2** and a third tapeline structure **620** are mounted within a single housing **610**. The third tapeline structure **620** is separately assembled in the housing **610** as a standalone component.

(127) As shown in FIGS. **23** and **26**, the distance measuring device of Embodiment 6 includes the housing **610**, which defines an accommodating space **611** therein. The laser ranging device **2** and the third tapeline structure **620** are arranged in the accommodating space **611**. As shown in FIGS. **26** and **27**, the laser ranging device **2** includes a laser generating means **21**, a photoelectric conversion means **22**, a circuit board **23**, a display means **24**, an operating means **25** and a power supply. The laser ranging device **2** may be implemented as the same as that of Embodiment 1. In some implementations, the power supply is integrated in a laser module **20** made up of the laser generating means **21** and the photoelectric conversion means **22**. The power supply may be implemented as a rechargeable battery **632**. The laser module **20** is provided with a charging port **631**, which may be chosen as a USB or type-C charging port. In some implementations, wireless charging may be provided, for example, using an induction coil.

(128) The third tapeline structures **620** includes the features of those of Embodiments 2 to 5, except that, in each of the tapeline structures of Embodiments 2 to 5, the various components are separately mounted in the shell **1** or **4**, while in Embodiment 6, as shown in FIGS. **28** and **29**, the third tapeline structure **620** is integrated in a tapeline casing **621**, and they are together assembled as a whole in the accommodating space **611** in the housing **610**. As shown in FIGS. **23** and **29**, the

third tapeline structure **620** includes a tapeline wheel **31**, a tape **32**, a pressure piece **34** and a locking key **35**. The tapeline wheel **31** is disposed in the tapeline casing **621**, and the tape **32** is entirely or partially wound on the tapeline wheel **31**. One end of the tape **32** is fixedly connected to the tapeline wheel **31**, and the other end defines a tape end portion **36**. The tapeline casing **621** is provided therein with a first tape outlet **614**, and the housing **610** is provided therein with a second tape outlet **615**. The tape end portion **36** extends out of the tapeline casing **621** through the first tape outlet **614**, and extends out of the housing **610** through the second tape outlet **615**. The locking key **35** is provided on an outer surface of the housing **610** and used to control the pressure piece **34** to press or release the tape **32**. In some implementations, the locking key **35** is provided around the pressure piece **34**, as in the tapeline structures of Embodiments 2 to 4. In some implementations, the locking key **35** is provided at a location of the housing **610** in opposition to the pressure piece **34**. The locking key **35** is connected to the pressure piece **34** through a transmission mechanism. When the locking key **35** is pressed down, the motion is transmitted to the transmission mechanism, causing the transmission mechanism to actuate the pressure piece **34** to press or release the tape **32**.

(129) The third tapeline structure **620** is mounted within the housing **610**, and the laser ranging device **2** is disposed in a space delimited between an edge of the third tapeline structure **610** and an inner side of the housing **610**. This can maximize reasonable spatial utilization of the housing **610** and reduce the overall size of the distance measuring device. In some implementations, as shown in FIG. **28**, the laser module **20** of the laser ranging device **2** is provided at a radial edge location of the third tapeline structure **620** (in a radial direction of the tapeline wheel **31**), and in the outer surface of the housing **610**, there are provided a laser beam emitting port **17** aligned with a light emitting surface **211** of the laser generating means **21**, a light receiving hole **18** aligned with a light receiving surface **221** of the photoelectric conversion means **22** and a first through hole **616** matching the charging port **631** (see FIG. **25**). The display means **24** and the operating means **25** are provided on an axial end face of the third tapeline structure **620** (in an axial direction of the tapeline wheel **31**), and a second through hole and a third through hole are provided in a side wall of the housing **610** opposing the display means. The second through hole is aligned with the display means **24**, and the third through hole is aligned with the operating means **25**. This can facilitate a user's viewing of the display means and operation. Preferably, a transparent protective plate for protecting the display means **24** is disposed over the second through hole. The operating means **25** is implemented as a press button passing through the third through hole.

(130) Referring to FIG. **26**, at least one locating post **617** is provided in the housing **610**. The locating post **617** may extend through the tapeline casing **621** of the third tapeline structure **620**. This enables rapid location of the third tapeline structure **620** during its mounting, followed by fixing the third tapeline structure **620** in the housing **610** using fasteners.

(131) In some implementations, referring to FIG. **26**, the housing **610** includes a first housing portion **612** and a second housing portion **613**. When joined together, the first housing portion **612** and the second housing portion **61** make up the housing **610** defining the accommodating space **611**. The first housing portion **612** and the second housing portion **613** may be joined together using fasteners along an axial direction of the third tapeline structure **620**, or along a radial direction of the third tapeline structure **620**.

(132) In this embodiment, since the tapeline structure is mounted in the housing **610** as a whole, it may be pre-fabricated and then assembled with the distance measuring device, resulting in increased assembly efficiency of the distance measuring device. Through arranging the laser ranging device and the third tapeline structure in the housing in a reasonable manner, the distance measuring device is capable of both long distance ranging and short distance ranging and can be conveniently carried and easily operated and used in work by the user.

Embodiment 7

(133) As shown in FIGS. **30** to **33**, Embodiment 7 provides a distance measuring device with both

laser ranging and tapeline-based distance measuring functions, in which a laser ranging device **2** and a fourth tapeline structure **720** are mounted within a single housing.

(134) As shown in FIG. **30**, the fourth tapeline structure **720** is substantially the same as the tapeline structures of Embodiments 2 to 4 and also includes a tapeline wheel **31**, a tape **32**, a tape outlet **33**, a pressure piece **34** and a locking key **35**. The tapeline wheel **31** is disposed in the housing, and the tape **32** is entirely or partially wound on the tapeline wheel **31**. One end of the tape **32** is fixedly connected to tapeline wheel **31**, and the other end defines a tape end portion **36**. The tape outlet **33** is provided in a lower portion of an outer side wall of the housing, and the tape end portion **36** extends out of the housing through the tape outlet **33**. The pressure piece **34** is disposed in the housing in the vicinity of the tape outlet **33**. When the tape **32** is pulled out of the housing, the pressure piece **34** can be used to press the tape **32** so that the length of the tape **32** outside the housing is kept constant. The locking key **35** is provided on an outer surface of the housing in order to control the pressure piece **34** to press or release the tape **33**.

(135) Referring to FIGS. **30** and **31**, Embodiment 7 differs from Embodiments 2 to 4 in that the fourth tapeline structure **720** further includes a locating member **721**. A rotating shaft **724** of the tapeline wheel **31** is connected to the locating member **721**, and the locating member **721** further includes at least one locating portion arranged at a circular circumferential edge of the tapeline wheel **31**. The locating member **721** is fixed in the housing, and the tapeline wheel **31** is connected to the locating member **721** so that the tapeline wheel **31** is rotatably fixed in the housing. In some implementations, the locating member **721** includes a first locating portion **722** and a second locating portion **723**. A line connecting the first locating portion **722** and the rotating shaft **724** forms an angle of greater than 90° with a line connecting the second locating portion **723** and the rotating shaft **724**. In some implementations, as shown in FIGS. **32** and **33**, the locating member **721** is provided thereon with a raised engagement portion **724**, which is inserted into the rotating shaft **725** of the tapeline wheel **31**, thereby coupling the locating member **721** to the tapeline wheel **31**. The locating member **721** enables rapid assembly of the fourth tapeline structure **720**.

(136) The laser ranging device **2** may be disposed at a radial edge location of the fourth tapeline structure **720**, as in Embodiment 6. Reference can be made to the description of Embodiment 6 for more structural details. It would be appreciated that Embodiments 2 to 4 may alternatively adopt the tapeline structure arrangement of this embodiment.

Embodiment 8

(137) As shown in FIGS. **34** to **36**, Embodiment 8 provides a distance measuring device with both laser ranging and tapeline-based distance measuring functions, in which a laser ranging device **2** and a fifth tapeline structure **820** are mounted within a single housing **810**. In this embodiment, a display means **830** can also serve as a locking key of the tapeline structure.

(138) As shown in FIGS. **35** and **36**, the distance measuring device includes a fifth tapeline structure **820** and a laser ranging device **2**, both mounted in the housing **810**. The fifth tapeline structure **820** includes a tapeline wheel **31**, a tape **32**, a tape outlet **33** and a pressure piece **821**. The tapeline wheel **31** is rotatably disposed in the housing **820**, and the tape **32** is entirely or partially wound on the tapeline wheel **31**. One end of the tape **32** is fixedly connected to tapeline wheel **31**, and the other end defines a tape end portion **35**. The tape outlet **33** is provided in an outer side wall of the housing **810**, and the tape end portion **35** extends out of the housing **810** through the tape outlet **33**. The pressure piece **821** is disposed in the housing **810** in the vicinity of the tape outlet **33**. When the tape **32** is pulled out of the housing **810**, the pressure piece **821** can be used to press the tape **32** so that the length of the tape **32** outside the housing **810** is kept constant. The display means **830** is disposed on the outer side wall of the housing **810**. One end of the display means serve as a push end **831**, which is coupled to the pressure piece **821** through a transmission mechanism **840**. When the push end **831** is pressed down, the pressure piece **821** will be driven to move to cause the pressure piece **821** to unlock the tape **32**. That is, the pressure piece **821** does not press the tape **32** any longer, and the tape **32** can therefore be stowed.

(139) Another end of the display means **830** opposing the push end **831** is pivotably coupled to the housing **810** through a first rotating shaft **832**. When the push end **831** is pressed, the display means **830** can pivot about the first rotating shaft **832** relative to the housing **810**. The push end **831** is connected to the pressure piece **821** through the transmission mechanism **840**.

(140) In some implementations, the location of the display means **830** on the housing **810** opposes that of the tape outlet **33**. That is, the display means **830** is located on a first side wall **811** of the housing **810** which extends along a radial direction of the tapeline wheel **31**, and the tape outlet **33** is located on a second side wall **812** opposing the first side wall **811**. The transmission mechanism **840** includes a first rotating element **841** and a connecting rod **842**. The first rotating element **841** is fixedly connected at one end thereof to the push end **831** so as to be movable therewith. Preferably, an extension **843** is provided at the push end **831** such as to extend from the push end **831** to the first rotating element **841**, thereby connecting the first rotating element **841** to the push end **831**. The other end of the first rotating element **841** is hinged to one end of the connecting rod **842**. A middle portion of the first rotating element **841** is rotatably connected to the housing **810** through a second rotating shaft **844**. The other end of the connecting rod **842** is coupled to the pressure piece **821**. When pressed, the push end **831** actuates the first rotating element **841**. As a result, one end of the first rotating element **841** rotates, and the other end of the first rotating element **841** rotates in the opposite direction, thus pulling the connecting rod **842**. Thus, the pressure piece **821** is caused to move away from and thus unlock the tape **32**.

(141) In some implementations, a middle portion of the pressure piece **821** is movably connected to the housing **810** through a third rotating shaft **822**. One end of the pressure piece **821** is hinged to the connecting rod **842**, and the other end may be brought into contact with the tape **32**. When pulled by the connecting rod **842** at one end, the pressure piece **821** pivots about the third rotating shaft **822** so that the other end thereof moves away from and unlocks the tape **32**. In some implementations, a resilient element **823** is disposed within the housing in order to apply a resilient force to the pressure piece **821**, which biases the pressure piece **821** in a direction allowing it to lock the tape **32**. After the push end **831** is not pressed any longer, the external force exerted by the connecting rod **842** on the pressure piece **821** disappears, and the pressure piece **821** then returns, under the action of the resilient element **823**, to the position where it locks the tape **32**. Preferably, the resilient element **823** is a torsion spring disposed over the third rotating shaft **822**. It would be appreciated that another resilient element such as a tension spring, a compression spring, a resilient tab or the like may be alternatively used.

(142) In this embodiment, under normal circumstances, the pressure piece **821** locks the tape under the action of the resilient element **823**. In this way, self-locking is provided. Unlocking can be achieved by pressing the push end **831**. Moreover, the display means **830** serves as a push component for unlocking the tape. That is, the push component and the display means **830** are integrated as a single piece, resulting in a reduction in the number of components.

(143) The laser ranging device **2** may be arranged in the housing **810** in a reasonable way, as actually needed. For example, it may be arranged in the same manner as in any of Embodiments 2 to 4 and Embodiments 6 to 7. However, it is to be noted that the display means **830** is arranged according to this embodiment. A transmission line **833** for signal communication is provided between the display means **830** and a circuit board **23**. For example, as shown, a laser module in the laser ranging device **2** is disposed at a radial edge location of the fifth tapeline structure **820**, preferably on the same side as the tape outlet **33** and on the opposite side to the display means **830**. The transmission line **833** is disposed between the display means **830** and the laser module to connect the circuit board **23** in the laser ranging device **2** to the display means **830**.

Embodiment 9

(144) In Embodiments 2 to 4 and 6 to 8, the laser ranging device and the tapeline structure are arranged within a single housing. In Embodiment 5, the laser ranging device and the tapeline structure are arranged in separate housings, which are then joined together. As shown in FIGS. 37

to **40**, in this embodiment, a laser ranging device and a tapeline structure are disposed in separate housings, which are joined together, however, in a different manner from that of Embodiment 5. (145) As shown in FIG. **37**, the laser ranging device **2** is provided in a first housing **910**, and the sixth tapeline structure **920** in a second housing **911**. The laser ranging device **2** is implemented in the same way as in Embodiment 1 or 6, and the sixth tapeline structure **920** may be implemented as the tapeline structure in any of Embodiments 2 to 8. Therefore, further description thereof is omitted here.

(146) The first housing **910** and the second housing **911** are detachably joined together into a single assembly by a connecting structure **930**. Moreover, the first housing **910** and the second housing **911** may be separated as actually needed, allowing the laser ranging device or the tapeline structure to be used individually.

(147) In some implementations, as shown in FIG. **38**, the second housing **911** has an arcuate raised portion **913** on its side facing the first housing **910**. A radius of the arcuate raised portion **913** matches a radius of a tapeline wheel **31** in the second housing **911**. The first housing **910** has an arcuate recessed portion **912** on its side facing the second housing **911**. The size of the arcuate recessed portion **912** matches that of the arcuate raised portion **913**. When the first housing **910** is joined to the second housing **911**, the arcuate raised portion **913** snugly fits in the arcuate recessed portion **912**. In some implementations, the connecting structure **930** includes a connecting protrusion **931** projecting from the first housing **910** toward the second housing **911** and a connecting recess recessed downwardly from an outer surface of the second housing **911**. The first housing **910** and the second housing **911** can be joined together by inserting the connecting protrusion **931** into the connecting recess. At least one arcuate stud **932** may be provided on a side surface of the connecting protrusion **931**, and a hole for mating with the stud **932** may be defined in a side surface of the connecting recess. The stud **932** may be received in and engage with the hole, enhancing connection strength between the connecting protrusion **931** and the connecting recess and making the joint between the first housing **910** and the second housing **911** firmer.

(148) In some implementations, as shown in FIGS. **39** and **40**, both the second housing **911** and the first housing **910** have flat joint surfaces. A connecting slide channel **934** is provided on a side surface of the first housing **910** facing the second housing **911**, and a fin **935** is provided on a corresponding side surface of the second housing **911**. The fin **935** can slide into the connecting slide channel **934**, thereby joining the first housing **910** and the second housing **911** together. Specifically, on the side surface of the first housing **910** facing the second housing **911**, at least one elongate first connecting sheet **936** is provided so as to define the connecting slide channel **934** together with the side surface of the first housing **910** therebetween. On the corresponding side surface of the second housing **911**, a second connecting sheet **937** is provided along a lengthwise direction thereof. The second connecting sheet **937** defines, on at least one side thereof, the fin **936** that can slide into the connecting slide channel **934** from one end thereof. Preferably, two first connecting sheets **936** are provided and placed in opposition to each other to define a pair of connecting slide channels **934**, and the second connecting sheet **937** defines fins **936** at both sides, which can slide into the respective connecting slide channels **934**.

(149) In this embodiment, the laser ranging device and the tapeline structure can be conveniently assembled together or disassembled from each other. Thus, as actually needed, the laser ranging function and the tapeline function can be performed independently from each other, or the two are assembled to be carried and used together. When the two are secured to each other, the device can be suitably used for both long distance ranging and short distance ranging. The distance measuring device of Embodiment 9 is designed as the two modules: the laser ranging device and the tapeline structure. The modules can be fabricated separately and then assembled together. Such a modular design allows the product to be produced with effectively increased efficiency. In comparison with Embodiment 5, the connecting structure **930** employed in Embodiment 9 enables easier assembly and disassembly.

Embodiment 10

(150) In each of the distance measuring devices of Embodiments 1 to 9, the laser ranging device has only the laser ranging function. As shown in FIGS. **41** to **42**, Embodiment 10 provides a distance measuring device including a laser ranging device and a tapeline structure, which are joined together. The laser ranging device of Embodiment 10 has the same laser ranging function as that of each of the distance measuring devices of Embodiments 1 to 9. In addition, it has a second function, which may be a cross projection function, a line projection function or the like. As the laser ranging function is implemented in the same way as in Embodiments 1 to 9, it needs not be described in further detail here.

(151) As shown in FIGS. **41** and **42**, the laser ranging function is provided at one end of a laser module in Embodiment 10. That is, the laser module includes the laser ranging device **1001**, which is implemented in the same way as in Embodiments 1 to 9. At the other end of the laser module, there is provided a second device **1002** capable of providing a second function. For example, the second device may be implemented as any one or more of a laser spot projector, a laser line projector or a laser cross projector. In this way, the laser module has multiple functions. It would be appreciated that other functions may also be integrated, such as an infrared temperature measuring function. That is, the second device may be implemented as a temperature measuring device for providing a temperature measuring function. The second device may incorporate other functional modules, as actually needed. These functional modules may be implemented as conventional ones known in the art.

Embodiment 11

(152) As shown in FIGS. **43** to **45**, Embodiment 11 provides a distance measuring device with laser ranging and tapeline-based distance measuring functions, in which a laser ranging device **2** and a seventh tapeline structure **1120** are mounted in a single housing **1110**. The seventh tapeline structure **1120** may be structured in the same as in any of Embodiments 2 to 4, 6, 7 and 8, and mounted in the housing **1110** in the same manner as in any of Embodiments 2 to 4, 6, 7 and 8. For example, as in Embodiments 2 to 4, components of the seventh tapeline structure **1120** may be separately mounted in the housing **1110**. Alternatively, as in Embodiment 6, the seventh tapeline structure **1120** may be mounted as a whole in the housing **1110**. Still alternatively, as in Embodiment 7, it may be mounted in the housing **1110** with the aid of a locating member.

(153) As in any of the preceding embodiments, the laser ranging device **2** includes a laser generating means **21**, a photoelectric conversion means **22**, a circuit board **23**, a display means **24**, an operating means **25** and a power supply. However, differing from the foregoing embodiments, the laser generating means **21**, the photoelectric conversion means **22** and the circuit board **23** are provided as a single laser module on an axial end face of the seventh tapeline structure **1120**, and the power supply is also provided on the axial end face of the seventh tapeline structure **1120** either above or under the laser generating means **21** and the photoelectric conversion means **22**. Between the seventh tapeline structure **1120** and the laser module, there is provided a spacer **1121**, which separates the seventh tapeline structure **1120** from the laser module. Preferably, the spacer **1121** includes a base portion **1122** and an annular portion **1123** projecting from an edge of the base portion **1122**. The annular portion **1123** and the base portion **1122** delimit an accommodating space, in which the seventh tapeline structure **1120** is received. The laser module and the power supply are provided on a side surface of the base portion **1122** facing away from the seventh tapeline structure **1120**. The housing **1110** defines, on a side wall thereof facing the laser generating means **21** and the photoelectric conversion means **22**, a raised portion **1111** which is raised outwardly and defines a second accommodating space **1112** for holding the laser module. As in the preceding embodiments, a light receiving hole **1113** and a laser beam emitting port **1114** are provided at one end of the raised portion **1111**.

(154) The operating means **25** is provided on another side wall of the raised portion **1111**.

Preferably, the operating means **25** includes a press button, and a press button slot is provided in a

side wall of the raised portion **1111** facing away from the housing **1110**. The press button passes through the press button slot and is then connected to the circuit board **23**.

(155) The display means **24** is provided at a radial edge location of the seventh tapeline structure **1120**. Preferably, the display means **24** is supported by the annular portion **1123** of the spacer **1121**. A slot for passage of the display means **24** therethrough is provided in a corresponding side wall of the housing **1110**.

(156) The power supply may be selected as a cylindrical batter, and a side wall portion of the housing **1110** corresponding to the power supply defines a battery hatch **1115**. Through opening the battery hatch **1115**, the battery can be replaced rapidly. It would be appreciated that a rechargeable battery may be alternatively used, and accordingly, the battery hatch **1115** may be replaced with a charging port. Alternatively, a battery having a different shape may be used, such as a square battery, a button-shaped battery or the like.

Embodiment 12

(157) With the distance measuring device of each of Embodiments 2 to 11, when using the tapeline structure to measure a distance, the operator has to read a numerical value marked on the tape as a measurement of the distance. In contrast, according to this embodiment, a tapeline structure is provided with a sensing component for obtaining a distance measurement of the tapeline structure and then outputting it to a display means, on which the measurement is then displayed. This can increase measurement accuracy of the tapeline structure. According to this embodiment, the sensing component may be provided on any of the tapeline structures of Embodiments 2 to 11, rather than only on that shown in FIGS. **46** to **49**.

(158) How the distance measuring device of this embodiment operates will be described in detail below in the context of the sensing component being provided on the tapeline structure shown in FIGS. **46** to **49** as an example.

(159) As shown in FIGS. **46**, **48** and **49**, the distance measuring device of this embodiment includes a laser ranging device **2** and the eighth tapeline structure **1220**. As shown in FIG. **48**, the laser ranging device **2** and the eighth tapeline structure **1220** are mounted in a single housing **1210**. The eighth tapeline structure **1220** includes a support frame **1221**, on which a tapeline wheel **1222** is disposed. A tape **1223** is entirely or partially wound on tapeline wheel **1222**. The laser ranging device **2** is disposed at a radial edge location of the tapeline structure **1220**. The housing **1210** is provided with a tape locking button **1224** and a tape exit port **1211**. The tape **1223** extends at one end out of the tape exit port **1211**, and the tape locking button **1224** is configured to be pressed to lock the tape **1223**. The tape locking button **1223** may be arranged at a proper location of the housing **1210**. For example, as shown in FIG. **49**, the tape locking button **1224** is provided on a side of the housing **1210** opposing the tape exit port **1211** and is connected to a pressure piece **1225**. When the tape locking button **1224** is pressed, the pressure piece **1225** is driven to move toward and lock the tape **1223**. The sensing component **1230** is provided at a radial edge location of the support frame **1221** and electrically connected to the display means **24**. As a result of pulling the tape **1223** out, the tapeline wheel **1221** rotates, and the sensing component **1230** can sense a displacement distance of the tape **1223**, from which a length of the tape **1223** that has been pulled out can be derived by calculation as a measurement of the tapeline structure **1220**. Preferably, the sensing component **1230** may be chosen as a Hall sensing component. Specifically, the Hall sensing component includes a connecting member **1231** and a roller **1232** for sensing a displacement distance of the tape **1223**. The roller **1232** is disposed at one end of the connecting member **1231** so as to be in contact with the tape **1223** wound on the tapeline wheel **1222**. The other end of the connecting member **1231** is connected to the housing **1210** by a resilient member **1233**. The resilient member **1233** is configured to apply a torque to the connecting member **1231**, which biases the roller **1232** toward the tapeline wheel **1222**, thereby ensuring that the roller **1231** is always in contact with the tape **1223** wound on the tapeline wheel **1222**. As the tape **1223** is being increasingly pulled out, a length of the tape **1223** wound on the tapeline wheel **1222**, and

hence a diameter of the tapeline wheel **1222**, increasingly decreases. At this time, under the action of the resilient member **1233**, the roller **1232** is always kept in contact with the tape **1223** wound on the tapeline wheel **1222**, so it can accurately sense a displacement distance of the tape **1223**, enabling the tapeline structure **1220** to obtain an accurate measurement. Examples of the resilient member **1233** may include, but are not limited to, torsion springs, tension springs, compression springs and resilient tabs. The sensing component **1230** may be arranged at another location where it can be brought into contact with the tape **1223** than that shown in FIG. **49**.

(160) It would be appreciated that the sensing device of this embodiment is not limited to being used only in the distance measuring device of FIGS. **46** to **49**. Instead, it may also be integrated in the tapeline structure of any of Embodiments 2 to 11.

(161) One or two display means **24** may be provided. In case of two display means, one of the display means is used to display a measurement of the laser ranging device **2** thereon, and the other is used to display a measurement of the tapeline structure **1220** thereon. The two display means may be integrated as a single piece.

(162) In some other implementations, only one display means **24** may be included. This display means **24** displays both a measurement of the laser ranging device **2** and a measurement of the tapeline structure **1220** thereon. Specifically, in case of one display means **24** being used, the distance measuring device may have multiple operating modes.

(163) In a first operating mode, a switch (not shown) of the distance measuring device can be used to switch it between laser ranging and distance measuring by the tapeline structure. When the distance measuring device is switched to laser ranging, a measurement of the tapeline structure is not displayed on the display means **24**, and only a laser ranging measurement is displayed thereon. When the distance measuring device is switched to tapeline-based distance measuring, a laser ranging measurement is not displayed on the display means **24**, and only a measurement of the tapeline structure is displayed thereon.

(164) In a second operating mode, the distance measuring device may be configured so that, when it is ON or OFF, a measurement of the tapeline **1223** is displayed on the display means **24** in response to the tape **1223** being pulled out. If laser ranging is desired, the switch may be manipulated to switch the device to the laser ranging. As a result, a laser ranging measurement is displayed on the display means **24**. When the distance measuring device is low in power, the tapeline structure **1220** can be still used normally for measuring.

(165) In a third operating mode, both laser ranging and tapeline-based distance measuring measurements can be displayed on a single display means **24**. That is, as shown in FIG. **50**, a screen of the display means **24** may be divided into two sections, with the laser ranging measurement **241** being displayed on one section and the tapeline's measurement **242** on the other.

(166) It would be appreciated that, according to this embodiment, operating modes may be configured as actually needed, rather than limited to the above three.

(167) Further, as shown in FIG. **51**, the distance measuring device of this embodiment further includes a communication module (not shown), which is able to communicate with a terminal **1240** in a wireless way to transmit measurements of the distance measuring device to the terminal **1240**. The measurements may be displayed and stored on the terminal **1240**. The terminal **1240** may be implemented as a mobile phone, a computer or another device. For example, a mobile phone running a corresponding application may be used as the terminal, and a Bluetooth connection may be established between the distance measuring device and the mobile phone. Measurements including laser ranging and tapeline-based distance measuring measurements may be displayed on an interface of the application.

(168) Data transmission between the distance measuring device and the terminal may be either conducted in real time or triggered by a press button. That is, a trigger press-button may be provided on the distance measuring device, and data transmission may be carried out between the distance measuring device and the terminal when the trigger press-button is pressed down.

(169) This embodiment not only enables accurate reading of measurements of the tapeline structure, without possible numerical errors that may arise from manual reading, but also allows the measurements to be transmitted to and stored in a terminal for numerical analysis.

Embodiment 13

(170) This embodiment has a structure that is essentially the same as that of Embodiment 12, except that a different sensing component from that of Embodiment 12 is used in this embodiment. As shown in FIGS. 52 and 53, the sensing component of this embodiment includes marking codes **1331** provided on a tape **1223** and a marking code identification component **1330** arranged within a housing. Preferably, the marking code identification component **1330** is disposed around a tape exit port **1211**, and the marking codes **1331** are uniformly arranged on the tape **1223** along a lengthwise direction thereof. As the tape **1223** is being increasingly pulled out through the tape exit port **1211**, the marking code identification component **1330** can obtain a length of the tape **1223** that has been pulled out through identifying the marking codes **1331** thereon, which is then converted to a measurement of the tapeline structure. It would be appreciated that, similar to Embodiment 12, the marking codes **1331** and the marking code identification component **1330** of this embodiment may also be applicable to any of Embodiments 2 to 11.

(171) The tape **1223** may be graduated with numerical values as is conventional, which can be read by an operator. In order to extend the life span of the tape, its surface may be covered with a film (not shown), which protects the marking codes **1331** against abrasion and wearing.

(172) Preferably, the marking code **1331** and the marking code identification component **1330** of this embodiment may be provided along with the Hall sensing component of Embodiment 12. In this way, two numerical values can be obtained and then corrected, and a value obtained from the correction may be taken as a measurement of the tape **1223**, resulting in even higher reading accuracy.

Embodiment 14

(173) This embodiment is a modification of Embodiment 7. In Embodiment 7, as shown in FIG. 31, the tapeline wheel **31** is mounted on the locating member **721** in the fourth tapeline structure **720** and the locating member **721** is then mounted within the housing, thus achieving the mounting of the tapeline structure. Moreover, the locating member **721** includes the first locating portion **722** and the second locating portion **723**. This embodiment modifies the locating member **721** of FIG. 31 by adding a locating portion thereto, as detailed below.

(174) As shown in FIGS. 54 to 55, this embodiment provides a distance measuring device with both laser ranging and tapeline-based distance measuring functions, in which a laser ranging device **2** and a ninth tapeline structure **1420** are mounted in a single housing. Except for a locating member **1421**, the ninth tapeline structure **1420** is the same as that of each preceding embodiment. That is, the ninth tapeline structure may include a tapeline wheel **31**, a tape **32**, a tape outlet **33**, a pressure piece **34** and a locking means **1422**. The tapeline wheel **31** is disposed within the housing, and the tape **32** is entirely or partially wound on the tapeline wheel **31**. The tape **32** is fixedly connected to the tapeline wheel **31** at one end and defines a tape end portion **36** at the other end. The tape outlet **33** is provided in a lower portion of an outer side wall of the housing, and the tape end portion **36** extends out of the housing through the tape outlet **33**. The pressure piece **34** is disposed in the housing around the tape outlet. When the tape **32** is pulled out from the housing, the pressure piece **34** can be used to tightly press the tape **32** so that a length of the tape **32** outside the housing is kept constant. The locking means **1422** is disposed on an outer surface of the housing and is used to cause the pressure piece **34** to press or release the tape **32**. It would be appreciated that the locking means may be implemented either as the locking key **35** of Embodiment 7, or as the locking structure of Embodiment 8 (the structure that utilizes the display means to unlock the tape).

(175) As shown, the locating member **1421** is fixed in the housing, and the tapeline wheel **31** is rotatably coupled to the locating member **1421**. The locating member **1421** includes three locating

portions **1423**, each extending outwardly from a body **1424** of the locating member **1421** and connected to the housing by a fastener. For example, one end of each locating portion **1423** is fixed to the housing by a screw **1425**. In this way, the locating member **1421** is fixed within the housing. (176) As in Embodiment 7, the tapeline wheel **31** may be connected to the locating member **1421** through an engagement portion **724** and thereby mounted within the housing. In some implementations, as shown in FIG. 55, a protruding shaft shank **1426** is provided on the housing at a central location of the locating member **1421**, but is not directly connected to the locating member **1421**. The tapeline wheel **31** is fitted over the shaft shank **1426** as to be rotatable around the shaft shank **1426**. The shaft shank **1426** may be integrally formed with the housing. That is, the shaft shank **1426** may form part of the housing. In other words, the shaft shank **1426** and the housing constitute a single piece. As shown in FIG. 55, the shaft shank **1426** may be alternatively implemented as a separate component in the form of a stepped shaft. In this case, one end of the shaft shank **1426** is restricted with respect to the housing through a portion of the stepped shaft, and the other end of the shaft shank **1426** is coupled to the locating member **1421** by a screw. (177) It would be appreciated that the number of locating portions **1423** in the locating member **1421** may be determined as actually needed. It may be any number that is at least one and is not limited to two as in Embodiment 7, or three as in this embodiment. (178) With the locating member **1421**, the tapeline structure can be quickly assembled in the housing while ensuring robust operation of the tapeline. (179) The laser ranging device **2** may be disposed at a radial edge location as in Embodiments 6 to 7. Reference can be made to the above description of Embodiment 6 for more details in this regard. It would be appreciated that the arrangement for the tapeline structure may also be employed in any of Embodiments 2 to 4. (180) Presented above are merely a few preferred embodiments of the present invention. Those of ordinary skill in the art can make many improvements and modifications to the foregoing embodiments without departing from the spirit of the present invention. Accordingly, all and any such improvements and modifications are intended to also fall within the scope of the present invention.

Claims

1. A distance measuring device, comprising: a first housing having an accommodating space; and a laser ranging device provided in the accommodating space of the first housing; and a tapeline structure, the tapeline structure integrated with the laser ranging device into one piece, wherein the laser ranging device comprises a laser module and a power supply connected to the laser module; wherein the laser module comprises: a laser generating means for emitting a measurement beam to an object to be measured; a photoelectric conversion means for receiving a reflected beam reflected from the object to be measured and converting it into at least one feedback electric signal; and a circuit board provided thereon with at least one processor; wherein the tapeline structure is provided in the first housing, and the laser module is provided on an end face in an axial direction of the tapeline structure; wherein a raised portion is provided on the end face in the axial direction, and the raised portion defines a second accommodating space for accommodating the laser module.
2. The distance measuring device of claim 1, wherein the power supply is a rechargeable battery, the laser ranging device is provided thereon with a charging port, the first housing provided therein with a through hole matching the charging port.
3. The distance measuring device of claim 1, wherein the tapeline structure comprises: a tapeline wheel provided in the first housing; a tape entirely or partially wound on the tapeline wheel, one end of the tape fixedly connected to the tapeline wheel, the other end thereof provided with a tape end portion; a first tape outlet provided in a side wall of the first housing, the tape end portion extending out of the first housing through the first tape outlet; a pressure piece for pressing the tape

- so that a length of the tape outside the first housing is kept constant; and a locking key provided on an outer surface of the first housing and used to control the pressure piece to press or loosen the tape.
4. The distance measuring device of claim 1, wherein the laser ranging device further comprises: a display means and an operating means, the display means and the operating means both disposed on the end face in the axial direction or at an edge in a radial direction of the tapeline structure.
5. The distance measuring device of claim 1, wherein the first housing comprises a first housing portion and a second housing portion, the first housing portion joined to the second housing portion to form the first housing defining the accommodating space.
6. The distance measuring device of claim 1, wherein the laser ranging device further comprises a second device, wherein the second device is any one or more selected from a laser spot projector, a laser line projector, a laser cross projector and a temperature measuring device.
7. A distance measuring device, comprising: a first housing having a first accommodating space; a second housing having a second accommodating space; a laser ranging device provided in the first accommodating space; and a tapeline structure provided in the second accommodating space; the first housing is detachably connected to the second housing through a connecting structure, wherein a first side of the first housing facing toward the second housing is an arcuate recessed portion, a second side of the second housing facing toward the first housing is an arcuate raised portion in engagement with the arcuate recessed portion; the connecting structure comprises a connecting protrusion provided on the first side and a connecting recess provided on the second side, and the connecting protrusion is inserted in the connecting recess; or a first side surface of the first housing facing toward the second housing is a flat surface, a second side surface of the second housing facing toward the first housing is a flat surface; the connecting structure comprises a connecting slide channel provided on the first side surface and a fin which is provided on the second side surface and slidable into the connecting slide channel.
8. The distance measuring device of claim 7, wherein the laser ranging device comprises a laser module and a power supply connected to the laser module; the laser module comprises: a laser generating means for emitting a measurement beam to an object to be measured; a photoelectric conversion means for receiving a reflected beam reflected from the object to be measured and converting it into at least one feedback electric signal; and a circuit board provided thereon with at least one processor.
-