

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12383344
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kang; Hyosig et al.

---

### Surgical system with occlusion detection

---

#### Abstract

A method includes controlling a robotic system using a virtual boundary and based on optical tracking of a tracker, detecting a condition in which an optical detection device is occluded from detecting the tracker, and maintaining the virtual boundary if the condition persists for shorter than a predetermined period of time.

---

**Inventors:** Kang; Hyosig (Weston, FL), Moses; Dennis (Doral, FL), Quaid; Arthur (Ft. Lauderdale, FL)

**Applicant:** MAKO Surgical Corp. (Weston, FL)

**Family ID:** 38646620

**Assignee:** MAKO Surgical Corp. (Weston, FL)

**Appl. No.:** 18/106150

**Filed:** February 06, 2023

#### Prior Publication Data

Document Identifier	Publication Date
US 20230172671 A1	Jun. 08, 2023

#### Related U.S. Application Data

continuation parent-doc US 17395668 20210806 US 11712308 child-doc US 18106150  
continuation parent-doc US 16509651 20190712 US 11123143 child-doc US 17395668  
continuation parent-doc US 15288769 20161007 US 10350012 child-doc US 16509651  
continuation parent-doc US 11750815 20070518 US 9492237 child-doc US 15288769  
us-provisional-application US 60801378 20060519

---

## Publication Classification

**Int. Cl.:** **A61B34/20** (20160101); **A61B17/00** (20060101); **A61B17/17** (20060101); **A61B34/00** (20160101); **A61B34/10** (20160101); **A61B34/30** (20160101); **A61B90/00** (20160101)

**U.S. Cl.:**

**CPC** **A61B34/20** (20160201); **A61B17/1764** (20130101); **A61B34/10** (20160201); **A61B34/30** (20160201); **A61B34/71** (20160201); **A61B34/76** (20160201); **A61B90/03** (20160201); A61B2017/00119 (20130101); A61B2017/00694 (20130101); A61B2017/00712 (20130101); A61B2017/00725 (20130101); A61B2034/102 (20160201); A61B2034/107 (20160201); A61B2034/108 (20160201); A61B2034/2055 (20160201); A61B2034/2059 (20160201); A61B2034/2065 (20160201); A61B2034/2068 (20160201); A61B2034/207 (20160201); A61B2034/2072 (20160201); A61B34/25 (20160201); A61B2034/305 (20160201); A61B2090/363 (20160201); A61B2090/364 (20160201); A61B2090/3983 (20160201)

## Field of Classification Search

**CPC:** A61B (34/20); A61B (34/10); A61B (34/30); A61B (34/71); A61B (34/76); A61B (90/03); A61B (17/1764); A61B (2034/102); A61B (2034/107); A61B (2034/108); A61B (2034/2055); A61B (2034/2059); A61B (2034/2065); A61B (2034/2068); A61B (2034/207); A61B (2034/2072); A61B (2034/305); A61B (34/25); A61B (2090/363); A61B (2090/364); A61B (2090/3983); A61B (2017/00119); A61B (2017/00694); A61B (2017/00712); A61B (2017/00725)

**USPC:** 702/150

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4903536	12/1989	Salisbury et al.	N/A	N/A
4979949	12/1989	Matsen et al.	N/A	N/A
5046375	12/1990	Salisbury et al.	N/A	N/A
5086401	12/1991	Glassman et al.	N/A	N/A
5142930	12/1991	Allen et al.	N/A	N/A
5154717	12/1991	Matsen et al.	N/A	N/A
5207114	12/1992	Salisbury et al.	N/A	N/A
5230338	12/1992	Allen et al.	N/A	N/A
5236432	12/1992	Matsen et al.	N/A	N/A
5299288	12/1993	Glassman et al.	N/A	N/A
5343385	12/1993	Joskowicz et al.	N/A	N/A
5383901	12/1994	McGregor et al.	N/A	N/A
5388480	12/1994	Townsend	N/A	N/A
5399951	12/1994	Lavallee et al.	N/A	N/A
5408409	12/1994	Glassman et al.	N/A	N/A
5445144	12/1994	Wodicka et al.	N/A	N/A
5445166	12/1994	Taylor	N/A	N/A

5452941	12/1994	Halse et al.	N/A	N/A
5551429	12/1995	Fitzpatrick et al.	N/A	N/A
5572999	12/1995	Funda et al.	N/A	N/A
5576727	12/1995	Rosenberg et al.	N/A	N/A
5587937	12/1995	Massie et al.	N/A	N/A
5611353	12/1996	Dance et al.	N/A	N/A
5625576	12/1996	Massie et al.	N/A	N/A
5630431	12/1996	Taylor	N/A	N/A
5638819	12/1996	Manwaring et al.	N/A	N/A
5676673	12/1996	Ferre et al.	N/A	N/A
5682886	12/1996	Delp et al.	N/A	N/A
5688280	12/1996	Booth et al.	N/A	N/A
5694013	12/1996	Stewart et al.	N/A	N/A
5695500	12/1996	Taylor et al.	N/A	N/A
5701140	12/1996	Rosenberg et al.	N/A	N/A
5704791	12/1997	Gillio	N/A	N/A
5727554	12/1997	Kalend et al.	N/A	N/A
5792147	12/1997	Evans et al.	N/A	N/A
5799055	12/1997	Peshkin et al.	N/A	N/A
5806518	12/1997	Mittelstadt	N/A	N/A
5831408	12/1997	Jacobus et al.	N/A	N/A
5855553	12/1998	Tajima et al.	N/A	N/A
5871018	12/1998	Delp et al.	N/A	N/A
5887121	12/1998	Funda et al.	N/A	N/A
5888220	12/1998	Felt et al.	N/A	N/A
5898599	12/1998	Massie et al.	N/A	N/A
5928137	12/1998	Green	N/A	N/A
5950629	12/1998	Taylor et al.	N/A	N/A
5971997	12/1998	Guthrie et al.	N/A	N/A
5976156	12/1998	Taylor et al.	N/A	N/A
5978696	12/1998	Vomlehn et al.	N/A	N/A
5980535	12/1998	Barnett et al.	N/A	N/A
5984930	12/1998	Maciunas et al.	N/A	N/A
5987960	12/1998	Messner et al.	N/A	N/A
6002859	12/1998	DiGioia, III et al.	N/A	N/A
6006126	12/1998	Cosman	N/A	N/A
6006127	12/1998	Van Der Brug et al.	N/A	N/A
6017305	12/1999	Bonutti	N/A	N/A
6033415	12/1999	Mittelstadt et al.	N/A	N/A
6084587	12/1999	Tarr et al.	N/A	N/A
6104158	12/1999	Jacobus et al.	N/A	N/A
6109270	12/1999	Mah et al.	N/A	N/A
6111577	12/1999	Zilles et al.	N/A	N/A
6147674	12/1999	Rosenberg et al.	N/A	N/A
6161032	12/1999	Acker	N/A	N/A
6161033	12/1999	Kuhn	600/407	A61B 90/36
6188728	12/2000	Hurst	N/A	N/A
6191796	12/2000	Tarr	N/A	N/A
6205411	12/2000	DiGioia, III et al.	N/A	N/A

6219032	12/2000	Rosenberg et al.	N/A	N/A
6223100	12/2000	Green	N/A	N/A
6226566	12/2000	Funda et al.	N/A	N/A
6228089	12/2000	Wahrburg	N/A	N/A
6231526	12/2000	Taylor et al.	N/A	N/A
6233504	12/2000	Das et al.	N/A	N/A
6259806	12/2000	Green	N/A	N/A
6285902	12/2000	Kienzle et al.	N/A	N/A
6288705	12/2000	Rosenberg et al.	N/A	N/A
6292174	12/2000	Mallett et al.	N/A	N/A
6300936	12/2000	Braun et al.	N/A	N/A
6322467	12/2000	Hook et al.	N/A	N/A
6322567	12/2000	Mittelstadt et al.	N/A	N/A
6325808	12/2000	Bernard et al.	N/A	N/A
6337994	12/2001	Stoianovici et al.	N/A	N/A
6366273	12/2001	Rosenberg et al.	N/A	N/A
6369834	12/2001	Zilles et al.	N/A	N/A
6377011	12/2001	Ben-Ur	N/A	N/A
6377839	12/2001	Kalfas et al.	N/A	N/A
6385475	12/2001	Cinquin et al.	N/A	N/A
6385509	12/2001	Das et al.	N/A	N/A
6393340	12/2001	Funda et al.	N/A	N/A
6405072	12/2001	Cosman	N/A	N/A
6405158	12/2001	Massie et al.	N/A	N/A
6417638	12/2001	Guy et al.	N/A	N/A
6421048	12/2001	Shih et al.	N/A	N/A
6424885	12/2001	Niemeyer et al.	N/A	N/A
6430434	12/2001	Mittelstadt	N/A	N/A
6434416	12/2001	Mizoguchi et al.	N/A	N/A
6443894	12/2001	Sumanaweera et al.	N/A	N/A
6466815	12/2001	Saito et al.	N/A	N/A
6468265	12/2001	Evans et al.	N/A	N/A
6484118	12/2001	Govari	N/A	N/A
6493608	12/2001	Niemeyer	N/A	N/A
6494039	12/2001	Pratt et al.	N/A	N/A
6522906	12/2002	Salisbury et al.	N/A	N/A
6533737	12/2002	Brosseau et al.	N/A	N/A
6546277	12/2002	Franck et al.	N/A	N/A
6547782	12/2002	Taylor	N/A	N/A
6551325	12/2002	Neubauer et al.	N/A	N/A
6552722	12/2002	Shih et al.	N/A	N/A
6583161	12/2002	Medina	N/A	N/A
6642686	12/2002	Ruch	N/A	N/A
6671651	12/2002	Goodwin et al.	N/A	N/A
6674916	12/2003	Deman et al.	N/A	N/A
6690964	12/2003	Bieger et al.	N/A	N/A
6692485	12/2003	Brock et al.	N/A	N/A
6701174	12/2003	Krause et al.	N/A	N/A
6704694	12/2003	Basdogan et al.	N/A	N/A
6711431	12/2003	Sarin et al.	N/A	N/A

6711432	12/2003	Krause et al.	N/A	N/A
6748819	12/2003	Maeguchi et al.	N/A	N/A
6750877	12/2003	Rosenberg et al.	N/A	N/A
6757582	12/2003	Brisson et al.	N/A	N/A
6778850	12/2003	Adler et al.	N/A	N/A
6785572	12/2003	Yanof et al.	N/A	N/A
6786896	12/2003	Madhani et al.	N/A	N/A
6801801	12/2003	Sati	N/A	N/A
6810281	12/2003	Brock et al.	N/A	N/A
6816148	12/2003	Mallett et al.	N/A	N/A
6831640	12/2003	Shih et al.	N/A	N/A
6845691	12/2004	Hsien	N/A	N/A
6850794	12/2004	Shahidi	N/A	N/A
6853965	12/2004	Massie et al.	N/A	N/A
6859661	12/2004	Tuke	N/A	N/A
6877239	12/2004	Leitner et al.	N/A	N/A
6894678	12/2004	Rosenberg et al.	N/A	N/A
6920347	12/2004	Simon et al.	N/A	N/A
6985133	12/2005	Rodomista et al.	N/A	N/A
6987504	12/2005	Rosenberg et al.	N/A	N/A
7001346	12/2005	White	N/A	N/A
7035716	12/2005	Harris et al.	N/A	N/A
7039866	12/2005	Rosenberg et al.	N/A	N/A
7131073	12/2005	Rosenberg et al.	N/A	N/A
7168042	12/2006	Braun et al.	N/A	N/A
7199790	12/2006	Rosenberg et al.	N/A	N/A
7206626	12/2006	Quaid, III	N/A	N/A
7206627	12/2006	Abovitz et al.	N/A	N/A
7331436	12/2007	Pack et al.	N/A	N/A
7491198	12/2008	Kockro	N/A	N/A
7660623	12/2009	Hunter et al.	N/A	N/A
7717932	12/2009	McFarlin et al.	N/A	N/A
7742804	12/2009	Faul	N/A	N/A
7747311	12/2009	Quaid, III	N/A	N/A
7774044	12/2009	Sauer et al.	N/A	N/A
7831292	12/2009	Quaid et al.	N/A	N/A
8010180	12/2010	Quaid et al.	N/A	N/A
8095200	12/2011	Quaid, III	N/A	N/A
8391954	12/2012	Quaid, III	N/A	N/A
8571628	12/2012	Kang et al.	N/A	N/A
8911499	12/2013	Quaid et al.	N/A	N/A
9002426	12/2014	Quaid et al.	N/A	N/A
9492237	12/2015	Kang	N/A	A61B 34/76
9724165	12/2016	Arata et al.	N/A	N/A
10028789	12/2017	Quaid et al.	N/A	N/A
10231790	12/2018	Quaid et al.	N/A	N/A
10350012	12/2018	Kang	N/A	A61B 90/03
10952796	12/2020	Arata et al.	N/A	N/A

11123143	12/2020	Kang	N/A	A61B 34/71
11529198	12/2021	Wu	N/A	A61B 34/30
11712308	12/2022	Kang	606/130	A61B 90/03
11771504	12/2022	Kang	606/130	A61B 34/30
11937884	12/2023	Kang et al.	N/A	N/A
2001/0034530	12/2000	Malackowski et al.	N/A	N/A
2001/0037064	12/2000	Shahidi	N/A	N/A
2001/0039422	12/2000	Carol et al.	N/A	N/A
2001/0041838	12/2000	Holupka et al.	N/A	N/A
2002/0035321	12/2001	Bucholz et al.	N/A	N/A
2002/0062177	12/2001	Hannaford et al.	N/A	N/A
2002/0082498	12/2001	Wendt et al.	N/A	N/A
2002/0087274	12/2001	Alexander et al.	N/A	N/A
2002/0107521	12/2001	Petersen et al.	N/A	N/A
2002/0108054	12/2001	Moore et al.	N/A	N/A
2002/0120188	12/2001	Brock et al.	N/A	N/A
2003/0093103	12/2002	Malackowski et al.	N/A	N/A
2003/0112281	12/2002	Sriram et al.	N/A	N/A
2003/0187351	12/2002	Franck et al.	N/A	N/A
2003/0195664	12/2002	Nowlin et al.	N/A	N/A
2003/0209096	12/2002	Pandey et al.	N/A	N/A
2004/0009459	12/2003	Anderson et al.	N/A	N/A
2004/0012806	12/2003	Murata	N/A	N/A
2004/0024311	12/2003	Quaid, III	N/A	N/A
2004/0034282	12/2003	Quaid et al.	N/A	N/A
2004/0034283	12/2003	Quaid	N/A	N/A
2004/0034302	12/2003	Abovitz et al.	N/A	N/A
2004/0097952	12/2003	Sarin et al.	N/A	N/A
2004/0102866	12/2003	Harris et al.	N/A	N/A
2004/0106916	12/2003	Quaid et al.	N/A	N/A
2004/0115606	12/2003	Davies	N/A	N/A
2004/0127788	12/2003	Arata	N/A	N/A
2004/0128026	12/2003	Harris et al.	N/A	N/A
2004/0143243	12/2003	Wahrburg	N/A	N/A
2004/0157188	12/2003	Luth et al.	N/A	N/A
2004/0167654	12/2003	Grimm et al.	N/A	N/A
2004/0171924	12/2003	Mire et al.	N/A	N/A
2004/0172044	12/2003	Grimm et al.	N/A	N/A
2004/0236424	12/2003	Berez et al.	N/A	N/A
2004/0242993	12/2003	Tajima	N/A	N/A
2005/0001831	12/2004	Shih et al.	N/A	N/A
2005/0053200	12/2004	Sukovic et al.	N/A	N/A
2005/0062738	12/2004	Handley et al.	N/A	N/A
2005/0093821	12/2004	Massie et al.	N/A	N/A
2005/0107801	12/2004	Davies et al.	N/A	N/A
2005/0113677	12/2004	Davies et al.	N/A	N/A

2005/0154471	12/2004	Aram et al.	N/A	N/A
2005/0165489	12/2004	Michelson	N/A	N/A
2005/0193451	12/2004	Quistgaard et al.	N/A	N/A
2005/0197800	12/2004	Goodwin et al.	N/A	N/A
2005/0203384	12/2004	Sati et al.	N/A	N/A
2005/0215879	12/2004	Chuanggui	N/A	N/A
2005/0215888	12/2004	Grimm et al.	N/A	N/A
2005/0217394	12/2004	Langley et al.	N/A	N/A
2005/0222830	12/2004	Massie et al.	N/A	N/A
2006/0033707	12/2005	Rodomista et al.	N/A	N/A
2006/0058616	12/2005	Marquart et al.	N/A	N/A
2006/0084867	12/2005	Tremblay et al.	N/A	N/A
2006/0109266	12/2005	Itkowitz et al.	N/A	N/A
2006/0133827	12/2005	Becouarn et al.	N/A	N/A
2006/0142657	12/2005	Quaid et al.	N/A	N/A
2006/0207419	12/2005	Okazaki et al.	N/A	N/A
2006/0265179	12/2005	Jansen et al.	N/A	N/A
2006/0293598	12/2005	Fraser	N/A	N/A
2007/0142751	12/2006	Kang et al.	N/A	N/A
2007/0260140	12/2006	Solar et al.	N/A	N/A
2007/0270685	12/2006	Kang et al.	N/A	N/A
2008/0004633	12/2007	Arata et al.	N/A	N/A
2008/0010705	12/2007	Quaid et al.	N/A	N/A
2008/0010706	12/2007	Moses et al.	N/A	N/A
2008/0058945	12/2007	Hajaj et al.	N/A	N/A
2008/0125637	12/2007	Geist et al.	N/A	N/A
2009/0000626	12/2008	Quaid et al.	N/A	N/A
2009/0000627	12/2008	Quaid et al.	N/A	N/A
2009/0012531	12/2008	Quaid et al.	N/A	N/A
2009/0012532	12/2008	Quaid et al.	N/A	N/A
2010/0137882	12/2009	Quaid, III	N/A	N/A
2010/0170362	12/2009	Bennett et al.	N/A	N/A
2010/0198219	12/2009	McFarlin et al.	N/A	N/A
2010/0225209	12/2009	Goldberg et al.	N/A	N/A
2011/0130761	12/2010	Plaskos et al.	N/A	N/A
2011/0270120	12/2010	McFarlin et al.	N/A	N/A
2012/0176306	12/2011	Lightcap et al.	N/A	N/A
2013/0096573	12/2012	Kang et al.	N/A	N/A
2013/0096574	12/2012	Kang et al.	N/A	N/A
2014/0350571	12/2013	Maillet et al.	N/A	N/A
2016/0097676	12/2015	Kurasawa et al.	N/A	N/A
2016/0124022	12/2015	Tadano	N/A	N/A
2016/0153777	12/2015	Ni et al.	N/A	N/A
2016/0155097	12/2015	Venkatesha	N/A	N/A
2019/0290367	12/2018	Andersson et al.	N/A	N/A
2021/0128253	12/2020	Kang et al.	N/A	N/A
2022/0031404	12/2021	Kang et al.	N/A	N/A

## FOREIGN PATENT DOCUMENTS

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
1684729	12/2004	CN	N/A
1 059 067	12/1999	EP	N/A
1 184 684	12/2001	EP	N/A
1 380 266	12/2003	EP	N/A
0 957 803	12/2003	EP	N/A
1 574 186	12/2007	EP	N/A
1 871 267	12/2017	EP	N/A
08-215211	12/1995	JP	N/A
09-330016	12/1996	JP	N/A
2000-279425	12/1999	JP	N/A
2002-102251	12/2001	JP	N/A
3342969	12/2001	JP	N/A
2003-053684	12/2002	JP	N/A
2004-513684	12/2003	JP	N/A
2005506616	12/2004	JP	N/A
WO-95/01757	12/1994	WO	N/A
WO-96/17552	12/1995	WO	N/A
WO-00/35336	12/1999	WO	N/A
WO-02/24051	12/2001	WO	N/A
WO-02/060653	12/2001	WO	N/A
WO-02/061371	12/2001	WO	N/A
WO-03/007101	12/2002	WO	N/A
WO-03/077101	12/2002	WO	N/A
WO-2004/069036	12/2003	WO	N/A
WO-2004/069040	12/2003	WO	N/A
WO-2004/069041	12/2003	WO	N/A
WO-2004/070573	12/2003	WO	N/A
WO-2004/070577	12/2003	WO	N/A
WO-2004/070580	12/2003	WO	N/A
WO-2004/070581	12/2003	WO	N/A
WO-2004/075987	12/2003	WO	N/A
WO-2005/009215	12/2004	WO	N/A
WO-2005/013841	12/2004	WO	N/A
WO-2005/072629	12/2004	WO	N/A
WO-2005/120380	12/2004	WO	N/A
WO-2005/122916	12/2004	WO	N/A
WO-2006/004894	12/2005	WO	N/A
WO-2006/091494	12/2005	WO	N/A
WO-2007/117297	12/2006	WO	N/A

## **OTHER PUBLICATIONS**

English translation of JP 2005506616, Mar. 3, 2005. (Year: 2005). cited by examiner  
Abovitz et al., “The Future Use of Networked Haptic Learning Information Systems in Computer-Assisted Surgery,” CAOS 2001, Jul. 6-8, 2001, pp. 337-338. cited by applicant  
Abovitz, “Digital surgery: the future of medicine and human-robot symbiotic interaction,” Industrial Robot: An International Journal, Oct. 2001, vol. 28, Issue 5, pp. 401-406 (abstract only). cited by applicant  
Abovitz, “Human-Interactive Medical Robotics,” CAOS 2000, Jun. 15-17, 2000, pp. 71-72. cited



by applicant

Abovitz, “Human-Interactive Medical Robotics,” CAOS 2001, Jul. 6-8, 2001, pp. 81-82. cited by applicant

Acosta, et al., “Development of a Haptic Virtual Environment”, Computer-Based Medical Systems, Proceedings 12th IEEE Symposium. pp. 35-39, 1999. cited by applicant

Bennett et al., “Autonomous Calibration Of Single-Loop Kinematic Chains Formed By Manipulators With Passive End-Point Constraints,” IEEE Transactions On Robotics And Automation, vol. 7, pp. 597-606, 1991. cited by applicant

Bettini et al., “Vision assisted control for manipulation using virtual fixtures: Experiments at macro and micro scales,” in Proc. 2002 IEEE Intl. Conf. on Robotics and Automation, (Washington, DC), May 2002, 8 pages. cited by applicant

Chapter II Demand and Response to Written Opinion for PCT/US2006/005700, submitted Dec. 15, 2006, 16 pages. cited by applicant

Chapter II Demand and Response to Written Opinion for PCT/US2006/049216, submitted Jul. 15, 2008, 19 pages. cited by applicant

Chen et al., “Force Feedback for Surgical Simulation,” Proceedings of the IEEE, New York, US, vol. 86, No. 3, Mar. 1, 1998. pp. 524-530. cited by applicant

Cobb et al., “A robotic system for TKR surgery,” in Third Annual North American Program on Computer Assisted Orthopaedic Surgery, (Pittsburgh, PA), pp. 70-74, Jun. 1999. cited by applicant

Colgate, J. Edward, et al., “Cobots: Robots for Collaboration with Human Operators,” proceedings of International Mechanical Engineering Congress & Exhibition, DSC—vol. 58, 1996, pp. 433-439. cited by applicant

Davies et al, “Acrobot-using Robots and Surgeons Synergistically in Knee Surgery”, 1997 British Crown Copyright, pp. 173-178. cited by applicant

Davies et al., “The use of force control in robot assisted knee surgery,” in Proceedings of the First Annual Symposium on Medical Robotics and Computer Assisted Surgery, vol. 2, (Pittsburgh, PA), pp. 258-262, Sep. 1994. cited by applicant

Decision to Refuse a European Patent Application for EP Application No. 07756266.8 dated Aug. 3, 2016, 32 pages. cited by applicant

Definition of devices, web thesaurus, printers Mar. 4, 2021. (Year: 2021). cited by applicant

Definition of Object, web dictionary, printed Mar. 4, 2021 (Year: 2021). cited by applicant

Examination report for EP 04757075.9, dated Jan. 12, 2011, 5 pages. cited by applicant

Fritz, et al., “Design of a Haptic Data Visualization System for People with Visual Impairments”, IEEE Trans. on Rehabilitation Engineering, vol. 7, No. 3, Sep. 1999, 13 pages. cited by applicant

Germano et al., Clinical Use of the Optical Digitizer for Intracranial Neuronavigation, Neurosurgery, vol. 45(2), Aug. 1999, 15 pages. cited by applicant

Goswami, et al., “Identifying Robot Parameters Using Partial Pose Information,” IEEE Control Systems Magazine, vol. 13, No. 5, Oct. 1993, 11 pages. cited by applicant

Ho, S.C. et al., “Robot Assisted Knee Surgery Establishing a Force Control Strategy Incorporating Active Motion Constraint,” IEEE Engineering in Medicine and Biology Magazine, vol. 14, No. 3, May 1, 1995, col. 2-3, p. 293. cited by applicant

Hollerbach, J.M. & D. E. Johnson. Virtual Environment Rendering. To appear in Human and Machine Haptics, M. Cutkosky, R. Howe, K. Salisbury, and M. Srinivasan (eds.), MIT Press, 2000 (available at <http://www.cs.ubc.ca/labs/spin/publications/related/hollerbach00.pdf>), 25 pages. cited by applicant

International Preliminary Examination Report for PCT/US2003/007063, dated Sep. 2, 2004 (2 pages). cited by applicant

International Preliminary Report on Patentability for PCT/US2004/022978 including International Search Report and Written Opinion, dated Feb. 13, 2007 (6 pages). cited by applicant

International Preliminary Report on Patentability for PCT/US2006/005700, dated May 8, 2007 (7

pages). cited by applicant

International Preliminary Report on Patentability for PCT/US2006/049216, dated Sep. 10, 2008, 9 pages. cited by applicant

International Search Report and Written Opinion for corresponding PCT Application No. PCT/US2006/049216, dated May 8, 2008 (15 pgs.). cited by applicant

International Search Report and Written Opinion for PCT/US2006/005700, dated Jun. 27, 2006, 10 pages. cited by applicant

International Search Report for PCT/US2003/007063, dated Apr. 16, 2004 (7 pages). cited by applicant

Kanazides, Peter et al., "An Integrated System for Cementless Hip Replacement", Integrated Surgical Systems Department of Orthopedic Surgery, Sutter General Hospital, May/Jun. 1995, pp. 307-313. cited by applicant

Leeser et al., "Computerassisted teach and play: Novel user-friendly robot teach mode using gravity compensation and backdrivability," in Proceedings of the Robotics International/SME Fifth World Conference on Robotics Research, (Cambridge, MA), Sep. 1994, 7 pages. cited by applicant

Leeser, Karl, et al., "Control and Exploitation of Kinematic Redundancy in Torque-Controllable Manipulators via Multiple-Jacobian Superposition," to the International Conf. on Field & Service Robotics, Dec. 8-10, 1997, 7 pages. cited by applicant

London Press Services, "'Acrobot' capable of delicate knee surgery," Can. Med. Assoc. J., Jun. 15, 1997, 156(12), p. 1690. cited by applicant

Matsuoka, Yoky, et al., "Design of Life-Size Haptic Environments," Experimental Robotics VII, 2001, pp. 461-470. cited by applicant

Meggiolaro, et al., "Manipulator calibration using a single endpoint contact constraint," in 26th ASME Biennial Mechanisms Conference, (Baltimore, MD), 2000, 9 pages. cited by applicant

Moore, Carl A., et al., "Cobot Implementation of 3D Virtual Surfaces," proceedings of the 2002 Institute of Electrical and Electronics Engineers International Conference on Robotics & Automation, May 2002, pp. 3242-3247. cited by applicant

Niki, et al., "Simple Haptic Display and Object Data Design", Proceedings of the 2000 IEEE/RSJ International Conference on Intelligent Robots and Systems, pp. 967-972, 2000. cited by applicant

Otmane, S., et al., "Active Virtual Guides as an Apparatus for Augmented Reality Based Telemanipulation System on the Internet," presented at Institute of Electrical and Electronics Engineers Computer Society 33rd Annual Simulation Symposium ANSS 2000, held Apr. 16-20, 2000, pp. 185-191. cited by applicant

Park et al., "Virtual fixtures for robotic cardiac surgery," in Proc. Medical Image Computing and Computer-Assisted Intervention, (Utrecht, Netherlands), Oct. 2001, 2 pages. cited by applicant

PCT/US2006/049216, Partial Intl. Search Report, Jan. 18, 2008 (2 pgs.). cited by applicant

Press Release, "The Acrobot Company Wins Best Surgical Innovation Award," Acrobot Precision Surgical Systems, May 24, 2002, 1 page. cited by applicant

Provision of the Minutes in Accordance with Rule 124(4) EPC for EP Application No. 07756266.8 dated Aug. 2, 2016, 5 pages. cited by applicant

Quaid et al., "Haptic Information Displays for Computer-Assisted Surgery," Proceedings of the 2002 IEEE International Conference on Robotics & Automation, May 2002, pp. 2092-2097. cited by applicant

Quaid, Arthur E., et al., "FGS WAM: First Cadaver Trial," Z-Kat, Inc. Confidential Material, Sep. 28, 2001, pp. 1-7. cited by applicant

Quaid, Arthur E., et al., "FGS WAM: Integration of Fluorotactic Guidance with the Whole-Arm Manipulator," Z-Kat, Inc. Confidential Material, Dec. 28, 2000, pp. 1-6. cited by applicant

Quaid, et al., "The Use of Haptic Information Displays for Assisting in the Execution of Image-Guided Surgery Plans," Syllabus of the Computer Assisted Orthopaedic Surgery Meeting, Jul. 2001, pp. 338-340. cited by applicant

Roche, "Changing the way surgeons plan and execute minimally invasive unicompartmental knee surgery," Orthopaedic Product News, pp. 16-18, Jul./Aug. 2006. cited by applicant

Rosenberg, "Virtual Fixtures: Perceptual Tools for Telerobotic Manipulation", 1993 IEEE, 76-82. cited by applicant

Rosenberg, Virtual Fixtures: Perceptual overlays enhance operator performance in telepresence tasks. PhD thesis, Stanford University, Aug. 1994, 7 pages. cited by applicant

Sayers, Craig P., et al., "An Operator Interface for Teleprogramming Employing Synthetic Fixtures," to appear in Presence, Special Issue on Networked Virtual Environments and Teleoperation, Jun. 1994, pp. 1-27. cited by applicant

Schneider, O., et al., "Synergistic Robotic Assistance to Cardiac Procedures," presented to Computer Assisted Radiology and Surgery on Jun. 23-26, 1999, 5 pages. cited by applicant

Sensible Technologies, Inc., "Freeform Feel the Difference", 2001, 4 pages. cited by applicant

Sensible Technologies, Inc., "FreeForm Modeling—Technical Features," 2003, 2 pages. cited by applicant

Staecker et al., "Use of the LandmarX (tm) Surgical Navigation System in Lateral Skull Base and Temporal Bone Surgery", SkullBase, vol. 11, No. 4, 2001, pp. 245-255; Thieme Medical Publishers, Inc. 11 pages. cited by applicant

Taylor, Russell et al., "An Image-Directed Robotic System for Precise Orthopaedic Surgery", IEEE Transactions on Robotics and Automation, vol. 10, No. 3, Jun. 1994, pp. 261-275. cited by applicant

Taylor, Russell et al., "Redundant Consistency Checking in a Precise Surgical Robot", Annual International Conference of the IEEE Engineering in Medicine and Biology Society, vol. 12, No. 5, 1990, pp. 1933-1935. cited by applicant

Taylor, Russell et al., "Robotic Joint Replacement Surgery", NSF Engineering Research Center for Computer-Integrated Surgical Systems and Technology, 2000, 2001, 2004, 71 pages. cited by applicant

Tognetti, Lawrence Joseph, "Actuator Design for a Passive Haptic Display," Georgia Institute of Technology, Jun. 1999, 33 pages. cited by applicant

Townsend et al., "Teleoperator slave—WAM design methodology," Industrial Robot, vol. 26, No. 3, pp. 167-177, 1999. cited by applicant

World Wide Web, <http://haptics.me.jhu.edu/r.sub.--hapt.html>, "Haptic Interfaces and Virtual Environments," printed on Jun. 12, 2003, 2 pages. cited by applicant

World Wide Web, <http://haptics.me.jhu.edu/r.sub.--kine.html>, "Robot Design and Kinematics," printed on Jun. 12, 2003, 2 pages. cited by applicant

World Wide Web, <http://www.acrobot.co.uk/background.html>, "The Acrobot Company Limited—Background," printed on Jul. 10, 2002, 1 page. cited by applicant

World Wide Web, <http://www.acrobot.co.uk/home.html>, "The Acrobot Company Limited—Precision Surgical Systems," printed on Jul. 10, 2002, 1 page. cited by applicant

World Wide Web, <http://www.acrobot.co.uk/meetings.html>, "The Acrobot Company Limited—Meetings and Publications," printed on Jul. 10, 2002, pp. 1-3. cited by applicant

World Wide Web, <http://www.acrobot.co.uk/products.html>, "The Acrobot Company Limited—Products," printed on Jul. 10, 2002, pp. 1-6. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/assistance.htm>, "Surgical Assistance," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/design.htm>, "Virtual Design, Assembly & Maintenance," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/endeffectors.htm>, "End effectors," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/hapticmaster.htm>, "HapticMASTER", printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/reality.htm>, "Virtual Reality," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/rehabilitation.htm>, "Rehabilitation," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/research.htm>, "Research," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/simulation.htm>, "Simulation & Training," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.fcs-cs.com/robotics/content/software.htm>, "Software," printed on Jun. 12, 2003, 1 page. cited by applicant

World Wide Web, <http://www.merl.com/projects/surgSim99/>, "Knee Arthroscopy Simulation," printed on Jun. 12, 2003, 2 pages. cited by applicant

Written Opinion for PCT/US2006/049216, dated May 8, 2008, 12 pages. cited by applicant

Zilles, et al., "A Constraint-Based God-object Method for Haptic Display", IEEE Proceedings, pp. 146-151, 1995. cited by applicant

---

*Primary Examiner:* Nghiem; Michael P

*Attorney, Agent or Firm:* FOLEY & LARDNER LLP

---

## **Background/Summary**

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/395,668, filed Aug. 6, 2021, now U.S. patent Ser. No. 11/712,308, which is a continuation of U.S. application Ser. No. 16/509,651, filed Jul. 12, 2019, now U.S. patent Ser. No. 11/123,143, which is a continuation of U.S. application Ser. No. 15/288,769, filed Oct. 7, 2016, now U.S. patent Ser. No. 10/350,012, which is a continuation of U.S. application Ser. No. 11/750,815, filed May 18, 2007, now U.S. Pat. No. 9,492,237, which claims the benefit of and priority to U.S. Provisional Application No. 60/801,378, filed May 19, 2006, all of which are hereby incorporated by reference herein in their entireties.

### **BACKGROUND**

(1) The invention relates to a surgical system and, more particularly, to method and apparatus for controlling a haptic device.

(2) Minimally invasive surgery (MIS) is the performance of surgery through incisions that are considerably smaller than incisions used in traditional surgical approaches. For example, in an orthopedic application such as total knee replacement surgery, an MIS incision length may be in a range of about 4 to 6 inches whereas an incision length in traditional total knee surgery is typically in a range of about 6 to 12 inches. As a result of the smaller incision length, MIS procedures are generally less invasive than traditional surgical approaches, which minimizes trauma to soft tissue, reduces post-operative pain, promotes earlier mobilization, shortens hospital stays, and speeds rehabilitation.

(3) MIS presents several challenges for a surgeon. For example, in minimally invasive orthopedic joint replacement, the small incision size reduces the surgeon's ability to view and access the anatomy, which increases the complexity of sculpting bone and assessing proper implant position. As a result, accurate placement of implants may be difficult. Conventional techniques for counteracting these problems include, for example, surgical navigation, positioning the leg for optimal joint exposure, and employing specially designed, downsized instrumentation and complex surgical techniques. Such techniques, however, typically require a large amount of specialized

instrumentation, a lengthy training process, and a high degree of skill. Moreover, operative results for a single surgeon and among various surgeons are not sufficiently predictable, repeatable, and/or accurate. As a result, implant performance and longevity varies among patients.

(4) Conventional efforts to facilitate the performance and improve the outcome of minimally invasive and traditional orthopedic joint procedures may include the use of a robotic surgical system. For example, some conventional techniques include autonomous robotic systems, such as the ROBODOC system (formerly available from Integrated Surgical Systems, Inc., Sacramento, California). Such systems, however, typically serve primarily to enhance bone machining by performing autonomous cutting with a high speed burr. Although such systems enable precise bone resections for improved implant fit and placement, they act autonomously (rather than cooperatively with the surgeon) and thus require the surgeon to cede a degree of control to the robot. Additional drawbacks of autonomous systems include the large size of the robot, poor ergonomics, increased incision length for adequate robot access, and limited acceptance by surgeons and regulatory agencies due to the autonomous nature of the system. Such systems also typically require rigid clamping of the bone during registration and cutting and thus lack real-time adaptability to the dynamic intraoperative scene.

(5) Other conventional robotic systems include non-autonomous robots that cooperatively interact with the surgeon, such as the ACROBOT system (The Acrobot Company Limited, London, Great Britain). One drawback of conventional interactive robotic systems, however, is that such systems lack the ability to adapt surgical navigation in real-time to a dynamic intraoperative environment. For example, U.S. Pat. No. 7,035,716, which is hereby incorporated by reference herein in its entirety, discloses an interactive robotic system programmed with a three-dimensional virtual region of constraint that is registered to a patient. The robotic system includes a three degree of freedom (3 DOF) arm having a handle that incorporates force sensors. The surgeon utilizes the handle to manipulate the arm and move the cutting tool. Moving the arm via the handle is required so that the force sensors can measure the force being applied to the handle by the surgeon. The measured force is then used to control motors to assist or resist movement of the cutting tool. For example, during a knee replacement operation, the femur and tibia of the patient are fixed in position relative to the robotic system. As the surgeon applies force to the handle to move the cutting tool, the interactive robotic system applies an increasing degree of resistance to resist movement of the cutting tool as the tool approaches a boundary of the virtual region of constraint. In this manner, the robotic system guides the surgeon in preparing the bone by maintaining the tool within the virtual region of constraint. As with the above-described autonomous systems, however, the interactive robotic system functions primarily to enhance bone machining. Additionally, the 3 DOF configuration of the arm and the requirement that the surgeon manipulate the arm using the force handle results in limited flexibility and dexterity, making the robotic system unsuitable for certain MIS applications. The interactive robotic system also requires the anatomy to be rigidly restrained and the robotic system to be fixed in a gross position and thus lacks real-time adaptability to the intraoperative scene.

(6) Although some interactive robotic systems may not require fixation of the anatomy, such as the VECTORBOT system (BrainLAB, Inc., Westchester, Illinois), such systems do not enable bone sculpting but instead merely function as intelligent tool guides. For example, such systems may control a robotic arm to constrain movement of a drill along a pre-planned drilling trajectory to enable a surgeon to drill a hole in a vertebra for placement of a pedicle screw. Similarly, other robotic systems, such as the BRIGIT system (Zimmer, Inc., Warsaw, Indiana), simply position a mechanical tool guide. For example, the robotic system disclosed in International Pub. No. WO 2005/0122916, and hereby incorporated by reference herein in its entirety, discloses a robotic arm that positions a mechanical tool guide. Using the robot-positioned tool guide, the surgeon manually manipulates a conventional surgical tool, such as a saw or drill, to make cuts to the patient's anatomy while the robot constrains movement of the tool guide. Although such systems may

increase the accuracy and repeatability of the bone cuts, they are limited to performing the functions of a conventional tool guide and thus lack the ability to enable the surgeon to sculpt complex shapes in bone, as may be required for minimally invasive modular implant designs.

(7) Some non-robotic conventional surgical tools useful for bone sculpting do not require fixation of the relevant anatomy, such as the Precision Freehand Sculptor (Blue Belt Technologies, Inc., Pittsburgh, Pennsylvania). One drawback of such tools, however, is that they do not function in a manner that is transparent to the user. For example, U.S. Pat. No. 6,757,582, which is hereby incorporated by reference herein in its entirety, discloses a handheld surgical tool that can be used for sculpting a target shape into a bone. The handheld tool is a freehand cutting tool that is manipulated by the surgeon to grind away portions of the bone to form a desired target shape in the bone. The target shape is defined, for example, by a voxel-based model that is registered to the physical bone. During cutting, both the bone and the cutting tool are tracked to enable a controller to determine whether the cutting tool is impinging on the boundaries of the target shape and therefore cutting away bone that should be left intact. If so, the controller may shut off or retract the cutting tool to protect the bone. Although the bone is protected, the operation of the surgical tool is interrupted during the surgical procedure and the length of time to perform the procedure may increase. Further, interruption of cutting may also result in a rough surface cut. Additionally, such systems merely disable the cutting tool based on a position of the tool relative to the target shape but do not actually constrain the surgeon's manipulation of the cutting tool, for example, to prevent contact between the cutting tool and sensitive anatomy, or address other adverse situations, such as when rapid motion of the anatomy is detected. Thus, such systems may not include adequate safeguards to protect the patient. Moreover, a handheld tool that incorporates a shutoff mechanism may be bulky and heavier than a normal freehand tool or a gravity compensated interactive arm. Thus, it may be difficult for a surgeon to maneuver such a handheld tool to produce fine cutting motions, which makes such tools unsuited for applications that require complex shapes to be sculpted in bone, especially in a minimally invasive surgical environment such as when cutting in the gap between the femur and the tibia in a knee replacement operation without dislocating or distracting the joint.

(8) In view of the foregoing, a need exists for a surgical system that is able to cooperatively interact with a surgeon to enable the surgeon to sculpt complex shapes in bone in a minimally invasive manner and that has the ability to dynamically compensate for motion of objects in the intraoperative environment in a manner that safeguards the patient and is substantially transparent to the surgeon.

## SUMMARY

(9) According to an aspect of the present invention, a method for calibrating a surgical device includes acquiring first data including a position and/or an orientation of a first object disposed on the surgical device at a first location; acquiring second data including a position and/or an orientation of a second object disposed on the surgical device at a second location; determining third data including a position and/or an orientation of the first object relative to the second location; and determining a position and/or an orientation of the second object relative to the second location based at least in part on the first data, the second data, and the third data.

(10) According to another aspect, a system for calibrating a surgical device includes a first object configured to be disposed on the surgical device, a second object configured to be disposed on the surgical device, and a computing system. The computing system is programmed to determine first data including a position and/or an orientation of the first object when the first object is disposed on the surgical device at a first location; determine second data including of a position and/or an orientation of the second object when the second object is disposed on the surgical device at a second location; determine third data including a position and/or an orientation of the first object relative to the second location; and determine a position and/or an orientation of the second object

relative to the second location based at least in part on the first data, the second data, and the third data.

---

## Description

### BRIEF DESCRIPTION OF THE FIGURES

- (1) The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain principles of the invention.
- (2) FIG. 1 is a perspective view of an embodiment of a surgical system according to the present invention.
- (3) FIG. 2A is a perspective view of an embodiment of a haptic device according to the present invention.
- (4) FIG. 2B is a perspective view of an embodiment of a haptic device according to the present invention.
- (5) FIG. 2C is a perspective view of the haptic device of FIG. 2A showing a user operating the haptic device.
- (6) FIG. 3A is a perspective view of an embodiment of an end effector according to the present invention.
- (7) FIG. 3B is a side perspective view of the end effector of FIG. 3A.
- (8) FIG. 4 is a perspective view of an embodiment of an anatomy tracker according to the present invention.
- (9) FIG. 5 is a perspective view of an embodiment of a haptic device tracker according to the present invention.
- (10) FIG. 6A is a perspective view of an embodiment of an end effector tracker according to the present invention.
- (11) FIG. 6B is a perspective view of the end effector tracker of FIG. 6A attached to the end effector of FIG. 3A.
- (12) FIG. 7 is a perspective view of an embodiment of an instrument tracker according to the present invention.
- (13) FIG. 8 is a perspective view of a femur and a tibia showing an embodiment of a graphical representation of a haptic object according to the present invention.
- (14) FIG. 9 shows an embodiment of a display of a CAS system according to the present invention.
- (15) FIG. 10 is a block diagram of an embodiment of a haptic rendering process according to the present invention.
- (16) FIG. 11 is a representation of an embodiment of a 3D geometric haptic object according to the present invention.
- (17) FIGS. 12A-B show a block diagram of an embodiment of a haptic rendering process according to the present invention.
- (18) FIG. 13 is a pictorial representation illustrating coordinate systems and transformations according to the present invention.
- (19) FIGS. 14A-B show a block diagram of an embodiment of an occlusion detection algorithm according to the present invention.
- (20) FIG. 15 is a view of an embodiment of a mechanical tracking system according to the present invention.

### DETAILED DESCRIPTION

- (21) Presently preferred embodiments are illustrated in the drawings. An effort has been made to use the same or like reference numbers to refer to the same or like parts.
- (22) FIG. 1 shows an embodiment of a surgical system 10. The surgical system 10 includes a

computing system **20**, a haptic device **30**, and a tracking system **40**. In one embodiment, the surgical system **10** is a robotic surgical system as disclosed in U.S. patent application Ser. No. 11/357,197, Pub. No. US 2006/0142657, filed Feb. 21, 2006, and incorporated by reference herein in its entirety. In a preferred embodiment, the surgical system **10** is the HAPTIC GUIDANCE SYSTEM™ available from MAKO SURGICAL CORP.® in Ft. Lauderdale, Florida.

(23) The computing system **20** includes hardware and software for operation and control of the surgical system **10** and may comprise a computer **21**, a computer **31**, a display device **23**, an input device **25**, and a cart **29**. The computing system **20** is adapted to enable the surgical system **10** to perform various functions related to surgical planning, navigation, image guidance, and/or haptic guidance. The computer **21** is preferably customized for surgical planning and navigation and includes algorithms, programming, and software utilities related to general operation, data storage and retrieval, computer aided surgery (CAS), and/or any other suitable functionality. In contrast, the computer **31** is preferably customized for controlling performance, stability, and/or safety of the haptic device **30** and includes haptic control utilities and programs that enable the haptic device **30** to utilize data from the tracking system **40**.

(24) The haptic device **30** is a surgical device configured to be manipulated by a user (such as a surgeon) to move a surgical tool **50** to perform a procedure on a patient, such as sculpting a surface of a bone to receive an implant. During the procedure, the haptic device **30** provides haptic guidance to the surgeon, for example, to maintain the tool **50** within a predefined virtual boundary. As disclosed in the above-referenced Pub. No. US 2006/0142657, the virtual boundary may be defined by a virtual haptic object that is generated by the computing system **20** and registered to (associated with) the anatomy of the patient. The haptic object establishes a desired relationship between the anatomy and the tool **50**, such as a desired position, orientation, velocity, and/or acceleration of the tool **50** relative to the anatomy. In operation, when the surgeon moves the tool **50** in a manner that violates the desired relationship (such as when the tool **50** contacts a virtual boundary), the haptic device **30** provides haptic guidance in the form of tactile feedback (e.g., vibration) and/or force feedback (e.g., force and/or torque) to the surgeon. The haptic guidance may be experienced by the surgeon, for example, as resistance to further tool movement in the direction of the virtual boundary. As a result, the surgeon may feel as if the tool **50** has encountered a physical object, such as a wall. In this manner, the virtual boundary functions as a virtual cutting guide. Thus, the surgical system **10** limits the surgeon's ability to physically manipulate the haptic device **30** (e.g., by providing haptic guidance and/or a limit on user manipulation of the haptic device **30**) by implementing control parameters based on a relationship between the anatomy and a position, an orientation, a velocity, and/or an acceleration of a portion of the haptic device **30**, such as the tool **50**. In addition to haptic objects, the relationship may be based on predefined parameters, such as a predefined depth that limits total travel of the tool **50**.

(25) Guidance from the haptic device **30** coupled with computer aided surgery (CAS) enables a surgeon to actively and accurately control surgical actions, such as bone cutting, and delivery of localized therapies (e.g., in the brain). In orthopedic applications, the haptic device **30** can be applied to the problems of inaccuracy, unpredictability, and non-repeatability in bone preparation by guiding the surgeon in proper sculpting of bone to thereby enable precise, repeatable bone resections while maintaining intimate involvement of the surgeon in the bone preparation process. Moreover, because the haptic device **30** guides the surgeon during cutting, the skill level of the surgeon is less critical. Thus, surgeons of varying skill degree and experience are able perform accurate, repeatable bone resections.

(26) The haptic device **30** may be robotic, non-robotic, or a combination of robotic and non-robotic systems. In one embodiment, the haptic device **30** is a robotic system as disclosed in the above-referenced Pub. No. US 2006/0142657. In a preferred embodiment, the haptic device is the HAPTIC GUIDANCE SYSTEM™ available from MAKO SURGICAL CORP.® in Ft. Lauderdale, Florida. As shown in FIG. 2A, the haptic device **30** includes a base **32**, an arm **33**, an



end effector **35**, a user interface **37**, and a platform **39**.

(27) The base **32** provides a foundation for the haptic device **30**. The base **32** supports the arm **33** and may also house other components, such as, for example, controllers, amplifiers, actuators, motors, transmission components, clutches, brakes, power supplies, sensors, computer hardware, and/or any other well-known robotic component.

(28) The arm **33** is disposed on the base **32** and is adapted to enable the haptic device **30** to be manipulated by the user. The arm **33** may be an articulated linkage such as serial device, a parallel device, or a hybrid device (i.e., a device having both serial and parallel elements). In a preferred embodiment, the arm **33** is a serial device having four or more degrees of freedom (axes of movement), such as, for example, a robotic arm known as the “Whole-Arm Manipulator” or WAM™ currently manufactured by Barrett Technology, Inc. The arm **33** includes a proximal end disposed on the base **32** and a distal end that includes the end effector **35** to which the surgical tool **50** is coupled. To manipulate the haptic device **30**, a user **160** simply grasps and moves the arm **33** (as shown in FIG. 2C), which results in movement of the tool **50**. In one embodiment, the arm **33** includes a first segment **33a**, a second segment **33b**, and a third segment **33c** as shown in FIG. 2A. The first segment **33a** and the second segment **33b** are connected at a first joint **33d** (e.g., a shoulder joint), and the second segment **33b** and the third segment **33c** are connected at a second joint **33e** (e.g., an elbow joint). As shown in FIG. 2B, the arm **33** has a first degree of freedom DOF.sub.1, a second degree of freedom DOF.sub.2, a third degree of freedom DOF.sub.3, and a fourth degree of freedom DOF.sub.4. Dexterity of the arm **33** may be enhanced by adding additional degrees of freedom. For example, the arm **33** may include a wrist **36** disposed on the third segment **33c** as shown in FIG. 2A. The wrist **36** includes one or more degrees of freedom, such as a degree of freedom DOF.sub.5, to augment the degrees of freedom DOF.sub.1, DOF.sub.2, DOF.sub.3, and DOF.sub.4. The wrist **36** may be, for example, a one or three degree of freedom WAM™ wrist manufactured by Barrett Technology, Inc. or a one degree of freedom direct drive wrist.

(29) To enable the haptic device **30** to provide haptic guidance to the user, the arm **33** incorporates a drive system, such as the drive system disclosed in the above-referenced Pub. No. US 2006/0142657. The drive system includes actuators (e.g., motors) and a mechanical transmission. In an exemplary embodiment, the drive system includes a high-speed cable transmission and zero backlash, low friction, cabled differentials. The cable transmission may be, for example, a cable transmission used in the WAM™ robotic arm currently manufactured by Barrett Technology, Inc. and/or a cable transmission as described in U.S. Pat. No. 4,903,536, which is hereby incorporated by reference herein in its entirety.

(30) The arm **33** also includes position sensors (not shown) for determining a position and an orientation (i.e., pose) of the arm **33**, such as encoders and/or resolvers mounted on the joints **33d** and **33e** and/or encoders and/or resolvers mounted on a shaft of each motor.

(31) The end effector **35** comprises a working end of the haptic device **30**. As shown in FIG. 2A, the end effector **35** includes a proximal portion connected to the arm **33** and a distal portion that includes the tool **50** and a tool holder **51**. The tool **50** may be, for example, a surgical tool (such as a burr, drill, probe, saw, etc.). In one embodiment, the tool **50** and the tool holder **51** comprise an electric, air cooled surgical tool currently manufactured by ANSPACH® and having product numbers EMAX2 (motor), L-2SB (2 mm fluted ball), L-4B (4 mm fluted ball), L-6B (6 mm fluted ball), and L-1R (12) (1.2 mm×12.8 mm fluted router). The surgical tool may also include additional components such as a user input device (e.g., a foot pedal such as ANSPACH® product number EMAX2-FP), a control console (e.g., ANSPACH® product number SC2000), and the like. Further, the tool **50** may be integrated into the surgical system **10** such that cutting information (e.g., velocity, torque, temperature, etc.) is available to the surgical system **10** and/or such that the surgical system **10** can control operation of the tool **50**.

(32) In one embodiment, the tool holder **51** includes a holding device **151** configured to couple the

surgical tool **50** to the haptic device **30**. As shown in FIG. 3B, the holding device **151** comprises a first member **151a** and a second member **151b**. The first member **151a** is configured to receive at least a portion of the tool **50** (e.g., a shaft **50a** of the tool **50**) and to engage the second member **151b**. The second member **151b** is configured to couple the first member **151a** and the surgical tool **50** to the end effector **35** of the haptic device **30**, to maintain the tool **50** in a desired position when the tool **50** is coupled to the end effector **35**, and to substantially prevent movement of the tool **50** relative to the end effector **35**. As shown in FIGS. 3A and 3B, the first member **151a** of the holding device **151** may be a sleeve or sheath sized to receive a shaft **50a** of the tool **50** and to be inserted into the second member **151b**. For example, in one embodiment, the first member **151a** has a diameter in a range of about 5.9 mm to about 6.1 mm at a first end (i.e., an end into which the shaft **50a** is inserted) and a diameter of about 11.38 mm to about 11.48 mm at a second end (i.e., an end that is inserted into the second member **151b**). The second member **151b** of the holding device **151** may be any connector suitable for coupling a first object (e.g., a tool or work piece) to a second object (e.g., a machine or robot) in a manner that is secure, stable, and enables repeatable positioning of the first object relative to the second object. In one embodiment, the second member **151b** includes a collet. In other embodiments, the second member **151b** may include threads, clamping devices, set screws, and the like.

(33) In one embodiment, the holding device **151** is configured so that an axis of the holding device **151** corresponds to a desired axis of the tool **50** when the holding device **151** is disposed on the haptic device **30**. For example, in one embodiment (shown in FIGS. 3A and 3B), the second member **151b** of the holding device **151** includes a connector comprising a collet **151c**, a collet knob **151d**, and a collar nut **151e**. In this embodiment, the collet **151c** includes a male morse taper feature, and the aperture **52** of the end effector **35** includes a corresponding female morse taper feature. The collet **151c** is mated to the aperture **52** and tightened onto the end effector **35** with the collar nut **151e**. This taper connection establishes an axis H-H that corresponds to the desired axis of the surgical tool **50**. As shown in FIG. 3B, when the tool **50** is coupled to the end effector **35** via the holding device **151**, an axis of the tool **50** aligns with the axis H-H. In this manner, the holding device **151** aligns the tool **50** in a desired configuration relative to the end effector **35**. After the collet **151c** is mated with the end effector **35**, the first member **151a** is inserted into the collet **151c**. The shaft **50a** of the tool **50** is inserted into the first member **151a** until a tip **50b** of the tool **50** is in a desired position. Once the tip **50b** is properly positioned, the collet knob **151d** is tightened down onto the fingers or tangs of the collet **151a**. The clamping force exerted on the first member **151a** and the tool **50** by the collet fingers secures the first member **151a** and the tool **50** in place. In this manner, the holding device **151** substantially prevents movement of the first member **151a** and the tool **50** relative to the end effector **35**. Once installed on the end effector **35**, a portion **50c** (shown in FIG. 3B) of the tool **50** projects from the end effector **35** and can be attached to a motor for driving the tool **50**. Additionally, because the holding device **151** and the tool **50** can be decoupled from the end effector **35**, the components can be removed as necessary for replacement, sterilization, and the like.

(34) The user interface **37** enables physical interaction between the user and the haptic device **30**. The interface **37** is configured so that the user can grasp the interface **37** and manipulate the tool **50** while simultaneously receiving haptic guidance from the haptic device **30**. The interface **37** may be a separate component affixed to the haptic device **30** (such as a handle or hand grip) or may simply be part of the existing structure of the haptic device **30** (such as the arm **33**). Because the interface **37** is affixed to or is an integral part of the haptic device **30**, any haptic feedback output by the haptic device **30** is transmitted directly to the user when the user is in contact with the interface **37**. Thus, the interface **37** advantageously enables the haptic device **30** to hold the tool **50** cooperatively with the surgeon (as shown in FIG. 2C) and to simultaneously provide haptic guidance.

(35) The tracking system **40** of the surgical system **10** is configured to track one or more objects

during a surgical procedure to detect movement of the objects. As described in the above-referenced Pub. No. US 2006/0142657. The tracking system **40** includes a detection device that obtains a pose (i.e., position and orientation) of an object with respect to a coordinate frame of reference of the detection device **41**. As the object moves in the coordinate frame of reference, the detection device tracks the object. A change in the pose of the object indicates that the object has moved. In response, the computing system **20** can make appropriate adjustments to the control parameters for the haptic device **30**. For example, when the anatomy moves, the computing system **20** can make a corresponding adjustment to a virtual haptic object (e.g., a virtual cutting boundary) that is registered to the anatomy. Thus, the virtual cutting boundary moves along with the anatomy. (36) Pose data from the tracking system **40** is also used to register (i.e., map or associate) coordinates in one space to those in another space to achieve spatial alignment, for example, using a coordinate transformation process. Registration may include any known registration technique, such as, for example, image-to-image registration; image-to-physical space registration; and/or combined image-to-image and image-to-physical-space registration. In one embodiment, the anatomy and the tool **50** (in physical space) are registered to a representation of the anatomy (such as an image **614** in image space) as disclosed in the above-referenced Pub. No. US 2006/0142657 and shown in FIG. **9**. Based on registration and tracking data, the surgical system **10** can determine (a) a spatial relationship between the anatomy and the image **614** and (b) a spatial relationship between the anatomy and the tool **50** so that the computing system **20** can superimpose, and continually update, a virtual representation **616** of the tool **50** on the image **614**. The relationship between the virtual representation **616** and the image **614** is substantially identical to the relationship between the tool **50** and the actual anatomy.

(37) The tracking system **40** may be any tracking system that enables the surgical system **10** to continually determine (or track) a pose of the relevant anatomy of the patient and a pose of the tool **50** (and/or the haptic device **30**). For example, the tracking system **40** may comprise a non-mechanical tracking system, a mechanical tracking system, or any combination of non-mechanical and mechanical tracking systems suitable for use in a surgical environment.

(38) In one embodiment, the tracking system **40** includes a non-mechanical tracking system as shown in FIG. **1**. The non-mechanical tracking system is an optical tracking system that comprises a detection device **41** and a trackable element (or tracker) that is configured to be disposed on a tracked object and is detectable by the detection device **41**. In one embodiment, the detection device **41** includes a visible light-based detector, such as a micron tracker, that detects a pattern (e.g., a checkerboard pattern) on a tracking element. In another embodiment, the detection device **41** includes a stereo camera pair sensitive to infrared radiation and positionable in an operating room where the surgical procedure will be performed. The tracker is configured to be affixed to the tracked object in a secure and stable manner and includes an array of markers (e.g., an array **S1** in FIG. **4**) having a known geometric relationship to the tracked object. As is well known, the markers may be active (e.g., light emitting diodes or LEDs) or passive (e.g., reflective spheres, a checkerboard pattern, etc.) and have a unique geometry (e.g., a unique geometric arrangement of the markers) or, in the case of active, wired markers, a unique firing pattern. In operation, the detection device **41** detects positions of the markers, and the surgical system **10** (e.g., the detection device **41** using embedded electronics) calculates a pose of the tracked object based on the markers' positions, unique geometry, and known geometric relationship to the tracked object. The tracking system **40** includes a tracker for each object the user desires to track, such as an anatomy tracker **43** (to track patient anatomy), a haptic device tracker **45** (to track a global or gross position of the haptic device **30**), an end effector tracker **47** (to track a distal end of the haptic device **30**), and an instrument tracker **49** (to track an instrument held manually by the user).

(39) The anatomy tracker **43** is disposed on the patient's anatomy and enables the anatomy to be tracked by the detection device **41**. The anatomy tracker **43** includes a fixation device for attachment to the anatomy, such as a bone pin, surgical staple, screw, clamp, intramedullary rod, or

the like. In one embodiment, the anatomy tracker **43** is configured for use during knee replacement surgery to track a femur **F** and a tibia **T** of a patient. In this embodiment, as shown in FIG. **1**, the anatomy tracker **43** includes a first tracker **43a** adapted to be disposed on the femur **F** and a second tracker **43b** adapted to be disposed on the tibia **T**. As shown in FIG. **4**, the first tracker **43a** includes a fixation device comprising bone pins **P**, a clamp **400**, and a unique array **S1** of markers (e.g., reflective spheres). The second tracker **43b** is identical to the first tracker **43a** except the second tracker **43b** is installed on the tibia **T** and has its own unique array of markers. When installed on the patient, the first and second trackers **43a** and **43b** enable the detection device **41** to track a position of the femur **F** and the tibia **T**.

(40) The haptic device tracker **45** is disposed on the haptic device **30** and enables the surgical system **10** to monitor a global or gross position of the haptic device **30** in physical space so that the surgical system **10** can determine whether the haptic device **30** has moved relative to other objects in the surgical environment, such as the patient, or whether the detection device **41** has moved relative to the haptic device **30**. Such information is important because the tool **50** is attached to the haptic device **30**. For example, if the user repositions or inadvertently bumps the haptic device **30** while cutting the femur **F** with the tool **50**, the tracking system **40** will detect movement of the haptic device tracker **45**. In response, the surgical system **10** can make appropriate adjustments to programs running on the computing system **20** to compensate for movement of the haptic device **30** (and the attached tool **50**) relative to the femur **F**. As a result, integrity of the bone preparation process is maintained.

(41) The haptic device tracker **45** includes a unique array **S3** of markers (e.g., reflective spheres) and is adapted to be mounted on the base **32** of the haptic device **30** in a manner that enables the tracker **45** to be secured in a fixed position relative to the base **32**. The fixed position is calibrated to the haptic device **30** during a haptic device registration calibration (discussed below) so that the surgical system **10** knows where the tracker **45** is located relative to the base **32**. Once calibrated, the fixed position is maintained during the surgical procedure. In one embodiment, as shown in FIGS. **2A** and **5**, the tracker **45** is mounted on an arm **34** having a proximal end connected to the base **32** (e.g., via screws, rivets, welding, clamps, magnets, etc.) and a distal end that carries the array **S3** of markers. The arm **34** may include one or more support members (e.g., brackets, struts, links, etc.) having a rigid structure so that the haptic device tracker **45** is fixed in a permanent position with respect to the haptic device **30**. Preferably, however, the arm **34** is adapted for adjustability so that the array **S3** is moveable relative to the haptic device **30**. Thus, the array **S3** can be positioned independently of the base **32** before being secured in a fixed position. As a result, a position of the array **S3** can be customized for each surgical case (e.g., based on patient size, operating table height, etc.) and set so as not to impede the surgeon during a surgical procedure.

(42) Adjustability may be imparted to the arm **34** in any known manner (e.g., an articulating linkage, a flexible neck, etc.). For example, in the embodiment of FIG. **5**, the arm **34** includes a ball joint **34b** on which the haptic device tracker **45** is disposed. The ball joint **34b** includes a locking mechanism actuated by a handle **34a**. In operation, the user may unscrew the handle **34a** to release the ball joint **34b**, manipulate the ball joint **34b** until the tracker **45** is in a desired position, and tighten the handle **34a** until the ball joint **34b** is fixedly secured. In this manner, the tracker **45** may be fixed in the desired position. As an alternative to securing the tracker **45** in a fixed position and calibrating the fixed position to the haptic device **30**, the arm **34** may include position sensors (e.g., encoders) similar to the position sensors of the arm **33** to provide measurements of a pose of the arm **34** relative to the base **32**. When position sensors are incorporated into the arm **34**, the haptic device registration calibration (discussed below) may be eliminated because the surgical system **10** can determine the location of the tracker **45** with respect to the base **32** based on the pose of the arm **34** provided by the position sensors.

(43) The end effector tracker **47** enables the surgical system **10** to determine a pose of a distal end of the haptic device **30**. The tracker **47** is preferably configured to be disposed on the haptic device

**30** at a distal end of the arm **33** (e.g., on the segment **33c**, the end effector **35**, the tool **50**, and/or the tool holder **51**). In one embodiment (shown in FIG. **6B**), the tracker **47** is disposed on the tool holder **51**. As shown in FIG. **6A**, the tracker **47** may include a unique array **S4** of markers (e.g., reflective spheres) and may be adapted to be affixed to the haptic device **30** in any known manner, such as, for example, with a clamping device, threaded connection, magnet, or the like. In the embodiment of FIG. **6A**, the tracker **47** is affixed to the haptic device **30** with a clamp **1500**. The clamp **1500** may be formed integrally with the array **S4** or affixed to the array **S4** in any conventional manner, such as with mechanical hardware, adhesive, welding, and the like. The clamp **1500** includes a first portion **1505**, a second portion **1510**, and a thumbscrew **1515**. The first and second portions **1505** and **1510** are shaped to receive a portion of the haptic device **30**, such as a cylindrical portion of the tool **50** and/or the tool holder **51**. In one embodiment, the cylindrical portion is the first member **151a** of the holding device **151** of the tool holder **51** (shown in FIGS. **3A** and **3B**). To enable the clamp **1500** to grasp the cylindrical portion, the first portion **1505** may have a V-shaped groove (shown in FIG. **6A**) and the second portion **1510** may have a planar surface so that the first and second portions **1505** and **1510** can securely receive the cylindrical portion when tightened together. In one embodiment, the clamp **1500** is configured so that the surgical system **10** can determine a point and/or an axis of the haptic device **30** at a location where the tracker **47** is disposed on the haptic device **30**. For example, when the tracker **47** is secured to the cylindrical portion with the clamp **1500**, the surgical system **10** is able to determine a point and/or an axis of the cylindrical portion (e.g., an axis H-H shown in FIG. **3B**) based on the geometry of the tracker **47**, specifically, the geometric relationship between the reflective spheres on the array **S4** and the V-shaped groove on the first portion **1505** of the clamp **1500**.

(44) To install the end effector tracker **47** on the haptic device **30**, the first and second portions **1505** and **1510** of the clamp **1500** are disposed around a cylindrical portion of the tool **50** or the tool holder **51** and tightened together using the thumbscrew **1515**. The effector **47** may include a feature configured to aid in positioning the tracker **47** relative to the end effector **35**. For example, the tracker **47** may include one or more surfaces **1503** (shown in FIG. **6B**) that are adapted to abut corresponding surfaces on the haptic device **30**. In one embodiment, the surfaces **1503** are configured to abut a portion of the tool holder **51**, such as fingers or tangs of the collet **151c** as shown in FIG. **6B**. In operation, the user slides the clamp **1500** along the cylindrical portion of the tool holder **51** until the surfaces **1503** abut the fingers or tangs of the collet **151c** and then tightens the thumb screw **1515**. The tracker **47** may be removed by loosening the thumbscrew **1515** and sliding the tracker **47** off the cylindrical portion. In this manner, the tracker **47** may be removably and repeatably secured in a known position relative to the end effector **35**. The tracker **47** may also include a feature, such as a divot **47a** shown in FIG. **6B**, to facilitate orientation of the tracker **47** relative to the end effector **35**, for example, to avoid installing the tracker **47** upside down. After installation of the tracker **47**, the user may reorient the tracker **47** (if desired) by loosening the clamp **1500** and swiveling the tracker **47** around the cylindrical portion. Thus, the clamp **1500** enables adjustability of the tracker **47** relative to the end effector **35**. Adjustability is particularly useful during the haptic device registration calibration (described below) to orient the tracker **47** to face the detection device **41** to thereby improve tracking accuracy and visibility.

(45) Alternatively, instead of a separate end effector tracker **47**, the haptic device **30** may incorporate fiducials on the end effector **35**. The fiducials may be similar to the unique array **S4** of markers and may include, for example, reflective spheres. In contrast to the end effector tracker **47**, the fiducials are not removed from the end effector **35** prior to surgery. One disadvantage of not removing the fiducials is that blood and debris may contaminate the fiducials during surgery, which occludes the fiducials and degrades their ability to reflect light to the detection device **41**. Thus, the fiducials preferably include a smooth plastic coating so that any surface contamination can be easily removed. The fiducials should be mounted in a location on the end effector **35** that is visible to the detection device **41** during the haptic device registration calibration (described below) but

that will not impede the surgeon during the surgical procedure. For example, the fiducials may be mounted on an underside of the end effector **35**. Alternatively, the fiducials may be mounted on an adjustable linkage that can be positioned in a registration calibration position where there is a clear line of site between the fiducials and the detection device **41** and a stowed position where the fiducials will not hamper the surgeon during the surgical procedure.

(46) In one embodiment, the end effector tracker **47** is used only during the haptic device registration calibration (discussed below) and is removed prior to performance of the surgical procedure. In this embodiment, the end effector tracker **47** is disposed on the end effector **35** and the haptic device tracker **45** is mounted to the base **32** (e.g., via the adjustable arm **34**) so that a position of the haptic device tracker **45** with respect to the haptic device **30** is adjustable. Because the position of the haptic device tracker **45** is adjustable, the surgical system **10** does not know the location of the haptic device tracker **45** relative to the haptic device **30**. To determine the geometric relationship between the haptic device **30** and the haptic device tracker **45**, the registration calibration process utilizes the end effector tracker **47** (as described below). Although the end effector tracker **47** may remain on the haptic device **30** for the surgical procedure and can be continuously monitored, it is advantageous to remove the end effector tracker **47** when the registration calibration is complete to prevent the tracker **47** from impeding the surgeon during the surgical procedure. Another advantage of removing the tracker **47** is that movement of the tracker **47** during the surgical procedure may result in degraded performance of the surgical system **10** due to delays or limited bandwidth as the tracking system **40** detects and processes movement of the tracker **47**.

(47) In an alternative embodiment, the end effector tracker **47** may be eliminated. In this embodiment, the haptic device tracker **45** is fixed in a permanent position on the haptic device **30**. Because the haptic device tracker **45** is permanently fixed on the haptic device **30**, the relationship between the haptic device tracker **45** and the coordinate frame of the haptic device **30** is known. Accordingly, the surgical system **10** does not need the end effector tracker **47** for the registration calibration to establish a relationship between the haptic device tracker **45** and the coordinate frame of the haptic device **30**. In this embodiment, the haptic device tracker **45** may be rigidly mounted on the haptic device **30** in any position that permits the tracking system **40** to see the array **S3** of the haptic device tracker **45**, that is close enough to the surgical site so as not to degrade accuracy, and that will not hinder the user or interfere with other personnel or objects in the surgical environment.

(48) In another alternative embodiment, the haptic device **30** is firmly locked in position. For example, the haptic device **30** may be bolted to a floor of the operating room or otherwise fixed in place. As a result, the global or gross position of the haptic device **30** does not change substantially so the surgical system **10** does not need to track the global or gross position of the haptic device **30**. Thus, the haptic device tracker **45** may be eliminated. In this embodiment, the end effector tracker **47** may be used to determine an initial position of the haptic device **30** after the haptic device **30** is locked in place. One advantage of eliminating the haptic device tracker **45** is that the surgical system **10** does not need to include monitoring data for the haptic device tracker **45** in the control loop. As a result, noise and errors in the control loop are reduced. Alternatively, the haptic device tracker **45** may be retained but is monitored only for detecting excessive motion of the base **32** or the tracking system **40** rather than being included in the control loop.

(49) In another alternative embodiment, the tracking system **40** is attached to the haptic device **30** in a permanently fixed position. For example, the tracking system **40** (including the detection device **41**) may be mounted directly on the haptic device **30** or connected to the haptic device **30** via a rigid mounting arm or bracket so that the tracking system **40** is fixed in position with respect to the haptic device **30**. In this embodiment, the haptic device tracker **45** and the end effector tracker **47** may be eliminated because a position of the tracking system **40** relative to the haptic device **30** is fixed and can be established during a calibration procedure performed, for example,

during manufacture or set up of the haptic device **30**.

(50) In another alternative embodiment, the tracking system **40** is attached to the haptic device **30** in an adjustable manner. For example, the tracking system **40** (including the detection device **41**) may be connected to the haptic device **30** with an arm, such as the adjustable arm **34** (described above in connection with the haptic device tracker **45**) so that the tracking system **40** is moveable from a first position to a second position relative to the haptic device **30**. After the arm and the tracking system **40** are locked in place, a calibration can be performed to determine a position of the tracking system **40** relative to the haptic device **30**. A calibration to determine the position of the tracking system **40** relative to the haptic device **30** may be performed, for example, by viewing the end effector tracker **47** with the tracking system **40**.

(51) The instrument tracker **49** is adapted to be coupled to an instrument **150** that is held manually in the hand of the user. The instrument **150** may be, for example, a probe, such as a registration probe. As shown in FIG. 7, the instrument tracker **49** may comprise a unique array **S5** of markers (e.g., reflective spheres) formed integrally with the instrument **150** or affixed to the instrument **150** in any known manner, such as with mechanical hardware, adhesive, welding, a threaded connection, a clamping device, a clip, or the like. When the instrument tracker **49** is removably connected to the instrument **150**, such as with a clip or a clamping device, the instrument tracker **49** should be calibrated to the instrument **150** to determine a relationship between the instrument tracker **49** and a geometry of the instrument **150**. Calibration may be accomplished in any suitable manner, such as with a tool calibrator having a divot or a V-groove (e.g., as described in U.S. Patent Application Pub. No. US 2003/0209096, which is hereby incorporated by reference herein in its entirety). Knowing a geometric relationship between the array **S5** and the instrument **150**, the surgical system **10** is able to calculate a position of a tip of the instrument **150** in physical space. Thus, the instrument **150** can be used to register an object by touching a tip of the instrument **150** to a relevant portion of the object. For example, the instrument **150** may be used to register a bone of the patient by touching landmarks or points on the surface of the bone.

(52) The tracking system **40** may additionally or alternatively include a mechanical tracking system. In contrast to the non-mechanical tracking system (which includes a detection device **41** that is remote from the trackers **43**, **45**, **47**, and **49**), a mechanical tracking system may be configured to include a detection device (e.g., an articulating linkage having joint encoders) that is physically connected to the tracked object. The tracking system **40** may include any known mechanical tracking system, such as a mechanical tracking system as described in U.S. Pat. Nos. 6,033,415, 6,322,567, and/or Pub. No. US 2006/0142657, each of which is hereby incorporated by reference herein in its entirety, or a fiber optic tracking system.

(53) For example, as described in U.S. Pub. No. 2006/0142657, the tracking system **40** includes a mechanical tracking system having a jointed mechanical arm **241** (e.g., an articulated arm having six or more degrees of freedom) adapted to track a bone of the patient. As shown in FIG. 15, the arm **241** has a proximal end affixed to the base **32** of the haptic device **30** and a freely moveable distal end fixed to the femur **F** of the patient. Alternatively, the proximal end may be affixed to any other suitable location (such as, for example, to a rail of an operating table, a leg holder, etc.) but is preferably connected (e.g., directly or via a bracket) to the base **32** of the haptic device **30** so that the arm **241** moves globally with the haptic device **30**. The distal end of the arm **241** includes an fixation device **245** adapted for rigid fixation to the femur **F**, such as, for example, a bone pin, bone screw, clamp, wearable device, surgical staple, or the like. The arm **241** is configured to have multiple degrees of freedom. For example, in one embodiment, as shown in FIG. 15, the arm **241** includes a plurality of links **242** connected at joints **244**. Each joint **244** incorporates one or more position sensors (not shown) to track a pose of the arm **241**. The position sensors may include any suitable sensor, such as, for example, the position sensors described above in connection with the arm **33** of the haptic device **30**. In operation, as the femur **F** moves, the distal end of the arm travels with the femur **F**. The position sensors (and appropriate software) produce measurements of a pose

of the distal end of the arm relative to the proximal end of the arm fixed to the haptic device **30**. In this manner, motion of the femur **F** relative to the haptic device **30** is captured. The mechanical tracking system may also include a second arm that is identical to the arm **241** but is rigidly affixed to the tibia **T** to enable the tracking system to track motion of the tibia **T**. In this manner, the mechanical tracking system may be used to track the femur **F** and the tibia **T** so that the surgical system **10** can detect bone motion in real time during surgery. Using bone motion data in conjunction with appropriate software, the surgical system **10** can compensate for the bone motion in real time during surgery.

(54) In operation, the computing system **20**, the haptic device **30**, and the tracking system **40** cooperate to enable the surgical system **10** to provide haptic guidance to the user during a surgical procedure. The haptic guidance manifests as a result of the user's interaction with a virtual environment generated by a haptic rendering process. The haptic rendering process may include any suitable haptic rendering process, such as, for example, a haptic rendering process as described in U.S. Pat. No. 6,111,577, which is hereby incorporated by reference herein in its entirety. In a preferred embodiment, the haptic rendering process includes a haptic rendering algorithm as disclosed in the above-referenced Pub. No. US 2006/0142657 and/or U.S. patent application Ser. No. 11/646,204, filed Dec. 27, 2006, and incorporated by reference herein in its entirety. In the preferred embodiment, the surgical system **10** employs point-based haptic interaction where only a virtual point, or haptic interaction point (HIP), interacts with virtual objects in the virtual environment. The HIP corresponds to a physical point on the haptic device **30**, such as, for example, a tip of the tool **50**. The HIP is coupled to the physical point on the haptic device **30** by a virtual spring/damper model. The virtual object with which the HIP interacts may be, for example, a haptic object **705** (shown in FIG. **11**) having a surface **707** and a haptic force normal vector  $F_n$ . A penetration depth  $d_i$  is a distance between the HIP and the nearest point on the surface **707**. The penetration depth  $d_i$  represents the depth of penetration of the HIP into the haptic object **705**.

(55) One embodiment of a haptic rendering process is represented generally in FIG. **10**. In operation, position sensors (block **2502**) of the haptic device **30** (block **2500**) provide data to a forward kinematics process (block **2504**). Output of the forward kinematics process is input to a coordinate transformation process (block **2506**). A haptic rendering algorithm (block **2508**) receives data from the coordinate transformation process and provides input to a force mapping process (block **2510**). Based on the results of the force mapping process, actuators (block **2512**) of the haptic device **30** are actuated to convey an appropriate haptic wrench (i.e., force and/or torque) to the user.

(56) In one embodiment, the surgical system **10** includes a haptic rendering process as shown in FIGS. **12A-B**. The dashed lines of FIGS. **12A-B** correspond to the blocks of FIG. **10**. As shown in FIGS. **12A-B**, the coordinate transformation process **2506** utilizes registration and tracking information for the anatomy and the haptic device **30** and input from the forward kinematics process **2504** to determine coordinate transformations (or transforms) that enable the surgical system **10** to calculate a location of an endpoint of the haptic device **30** relative to specified portions of the anatomy. For example, the coordinate transformation process **2506** enables the surgical system **10** to calculate a location of the tip of the tool **50** relative to desired cut surfaces on the anatomy.

(57) As shown in FIG. **13**, the coordinate transformation process **2506** includes defining various coordinate systems, including a first coordinate system  $X_{sub.1}$  associated with the detection device **41** of the tracking system **40**, a second coordinate system  $X_{sub.2}$  associated with the anatomy (e.g., a bone or an anatomy tracker **43a** or **43b** affixed to the bone), a third coordinate system  $X_{sub.3}$  associated with the haptic device tracker **45**, a fourth coordinate system  $X_{sub.4}$  associated with the haptic device **30** (e.g., the base **32** of the haptic device), and a fifth coordinate system  $X_{sub.5}$  associated with a virtual environment (e.g., a representation of the anatomy including a virtual (or haptic) object defining desired cut surfaces for installation of an implant).



Coordinate transformations are then determined that enable coordinates in one coordinate system to be mapped or transformed to another coordinate system.

(58) A first coordinate transformation T.sub.1 (shown in FIGS. 12A-B and 13) is a transformation from the coordinate system of the anatomy (the second coordinate system X.sub.2) to the coordinate system of the virtual environment (the fifth coordinate system X.sub.5). Thus, in embodiments where the virtual environment includes a virtual object defining a shape of an implant, the transformation T.sub.1 relates the physical anatomy to the desired cut locations for installation of the implant. As represented by block 4500 in FIG. 12A, the transformation T.sub.1 may be determined by registering the physical anatomy of the patient to a representation of the anatomy (as described below) and positioning the virtual object relative to the representation of the anatomy. Positioning the virtual object relative to the representation of the anatomy may be accomplished, for example, using any suitable planning process, such as an implant planning process as disclosed in the above-referenced Pub. No. US 2006/0142657. For example, a virtual model that defines a virtual cutting boundary (such as a model of an implant to be implanted in the bone) may be positioned relative to the representation of the anatomy (such as an image of the anatomy) displayed on the display device 23.

(59) A second coordinate transformation T.sub.2 (shown in FIGS. 12A-B and 13) is a transformation from the coordinate system of the detection device 41 (the coordinate system X.sub.1) to the coordinate system of the anatomy (the coordinate system X.sub.2). As represented by block 4502 in FIG. 12A, the tracking system 40 outputs the transformation T.sub.2 during a surgical procedure as the detection device 41 monitors motion of the anatomy. Because the detection device 41 continuously monitors the anatomy, the transformation T.sub.2 is regularly updated to reflect motion of the anatomy.

(60) A third coordinate transformation T.sub.3 (shown in FIGS. 12A-B and 13) is a transformation from the coordinate system of the haptic device tracker 45 (the third coordinate system X.sub.3) to the coordinate system of the haptic device 30 (the fourth coordinate system X.sub.4). In this embodiment, the haptic device tracker 45 is coupled to the base 32 of the haptic device 30 via the arm 34 (as shown in FIG. 2A). Thus, the transformation T.sub.3 relates the location of the haptic device tracker 45 to the base 32 of the haptic device 30. As represented by block 4504 in FIG. 12A, the transformation T.sub.3 may be determined, for example, by performing the haptic device registration calibration as described below.

(61) A fourth coordinate transformation T.sub.4 (shown in FIGS. 12A-B and 13) is a transformation from the coordinate system of the detection device 41 (the coordinate system X.sub.1) to the coordinate system of the haptic device tracker 45 (the coordinate system X.sub.3). As represented by block 4506 in FIG. 12A, the tracking system 40 outputs the transformation T.sub.4 during a surgical procedure as the detection device 41 monitors motion of the haptic device tracker 45. Because the detection device 41 continuously monitors the haptic device tracker 45, the transformation T.sub.4 is regularly updated to reflect motion of the haptic device tracker 45.

(62) A fifth coordinate transformation T.sub.5 (shown in FIGS. 12A-B and 13) is a transformation that results from the forward kinematics process 2504. The forward kinematics process 2504 computes a Cartesian endpoint position of the arm 33 of the haptic device 30 as a function of joint angle. As represented by blocks 4508 and 4510 in FIG. 12A, the forward kinematics process 2504 receives input from position sensors in the joints of arm 33. Based on this input, the forward kinematics process 2504 computes a position of a distal end of the arm 33 relative to the base 32 of the haptic device 30. Based on a known geometric relationship between the tool 50 and the distal end of the arm 33, a position of the tip of the tool 50 relative to the base 32 of the haptic device 30 can then be computed. Because the position sensors continuously monitor joint position, the transformation T.sub.5 is regularly updated to reflect motion of the arm 33.

(63) A sixth coordinate transformation T.sub.6 (shown in FIGS. 12A-B and 13) is obtained by multiplying the first through fifth coordinate transformations together in an appropriate sequence.

In one embodiment,  $T_{sub.6} = T_{sub.1}^{sup.} - 1T_{sub.2}^{sup.} - 1T_{sub.4}T_{sub.3}^{sup.} - 1T_{sub.5}$ . The result of the transformation  $T_{sub.6}$  (represented by a variable  $x$  in FIG. 12B) is a location of a virtual point, or haptic interaction point (HIP), relative to the virtual environment. In this embodiment, the HIP corresponds to a location of a physical point on the haptic device 30 (e.g., the tip of the tool 50) relative to the desired cut surfaces defined by the virtual object. Because motion of the anatomy, the haptic device tracker 45, and the arm 33 of the haptic device 30 are continuously monitored, the transformation  $T_{sub.6}$  is regularly updated to reflect motion of the anatomy, the base 32 of the haptic device 30, and the arm 33 of the haptic device 30. In this manner, the surgical system 10 compensates for motion of objects during a surgical procedure.

(64) One advantage of the present invention is that the surgical system 10 is able to compensate for motion of objects during the surgical procedure in a dynamic manner that is transparent to the user. Specifically, the surgical system 10 operates synchronously by continually monitoring motion of the anatomy, the haptic device tracker 45, and the arm 33 and continually updating the transformations  $T_{sub.2}$ ,  $T_{sub.4}$ , and  $T_{sub.5}$  without interrupting operation of the haptic device 30. In contrast, conventional surgical systems typically operate asynchronously, for example, by requiring the user to stop and reset the system or reregister tracked objects when movement of a tracked object is detected. As a result, with conventional systems, the operation of the system may be interrupted or impeded when motion of a tracked object is detected. Although the present invention can operate synchronously without interrupting the operation of the haptic device 30, it is advantageous to occasionally restrict operation of the haptic device 30, for example, when the surgical system 10 detects abnormal motion, such as when a tracked object moves too fast and/or too far.

(65) In one embodiment, a method of compensating for motion of objects during a surgical procedure includes (a) determining a pose of the anatomy; (b) determining a pose of the tool 50; (c) determining at least one of a position, an orientation, a velocity, and an acceleration of the tool 50; (d) associating the pose of the anatomy, the pose of the tool 50, and a relationship between the pose of the anatomy and the at least one of the position, the orientation, the velocity, and the acceleration of the tool 50; and (e) updating the association in response to motion of the anatomy and/or motion of the tool 50 without interrupting operation of the surgical device during the surgical procedure. The method may also include the step of providing haptic guidance, based on the relationship, to the user to constrain the user's manipulation of the surgical tool. The relationship may be based, for example, on a desired interaction between the anatomy and a position, an orientation, a velocity, and/or an acceleration of the tool 50. In one embodiment, the relationship is defined by a virtual object or parameter positioned relative to the anatomy and representing a desired location of an implant and/or cut surfaces for installing the implant. The step of associating the pose of the anatomy, the pose of the tool 50, and the relationship may be accomplished, for example, using registration processes, coordinate transformation processes (e.g., block 2506 of FIG. 10), and implant planning processes (e.g., as described in the above-reference Pub. No. US 2006/0142657). In one embodiment, the step of associating includes (a) defining a first transformation for transforming a coordinate system of the anatomy to a coordinate system of a representation of an anatomy; (b) defining a second transformation for transforming a coordinate system of the tool 50 to a coordinate system of the representation of the anatomy; and (c) associating the relationship with the coordinate system of the representation of the anatomy. To associate the relationship with the coordinate system of the representation of the anatomy, the user may, for example, position a virtual object relative to an image of the anatomy (e.g., as described in the above-reference Pub. No. US 2006/0142657). To enable the surgical system 10 to compensate for motion of objects during the surgical procedure, the step of updating the association may include updating the first transformation and/or the second transformation in response to motion of the anatomy and/or motion of the tool 50.

(66) In this embodiment, the pose of the tool 50 is determined by determining a pose of a first

portion of the haptic device **30** to which the tool **50** is coupled, determining a pose of a second portion of the haptic device **30**, and calculating the pose of the tool **50** based at least in part on the poses of the first and second portions of the haptic device **30** and a known geometric relationship between the tool **50** and the first portion of the haptic device **30**. In one embodiment, the first portion of the haptic device **30** comprises the distal end of the arm **33**, and the second portion of the haptic device **30** comprises the base **32** of the haptic device **30**. In another embodiment, the second portion of the haptic device **30** comprises an intermediate portion of the arm **33** (e.g., the segments **33a**, **33b**, or **33c**). In one embodiment, rather than mounting the end effector tracker **35** to a distal end of the arm, the end effector tracker **35** could be mounted to an intermediate portion of the arm, such as the elbow. The step of determining the pose of the second portion of the haptic device **30** includes determining a pose of the haptic device tracker **45** (which is mounted on the second portion of the haptic device **30**, e.g., to the base **32** or an intermediate portion of the arm **33**). Because the pose of the tool **50** is determined based on the poses of the first and second portions of the haptic device **30** and because the surgical system **10** continually updates the poses of the first and second portions (e.g., based on joint encoder data and a position of the haptic device tracker **45**), the pose of the tool **50** is updated to account for motion of the first and second portions. As a result, motion to the tool **50** is determined based on motion of the first and second portions. In this manner, the surgical system **10** is able to compensate for motion of objects during a surgical procedure.

(67) In one embodiment, the tracking system **40** is a non-mechanical tracking system (e.g., as described above in connection with the tracking system **40**) that operates at a different update rate than the haptic device **30**. For example, the haptic device **30** may update at 2000 Hz while the tracking system **40** updates at 15-30 Hz. The lower update rate of the tracking system **40** limits the dynamic performance of the motion compensation because the 15-30 Hz updates are separated by 1/15 to 1/30 seconds during which time no tracking information is available. Additionally, higher frequency motions of a tracked object will not be present in the output data of the tracking system **40**. One disadvantage of poor dynamic performance is that the surgical system **10** may not have sufficient data to move the haptic object precisely in sync with the physical anatomy. As a result, any cuts the surgeon makes may have reduced accuracy. For example, when the surgical system **10** is providing haptic guidance to guide the surgeon in cutting a planar bone surface with a spherical burr, momentary motion of one of the tracked objects combined with poor dynamic performance may result in divots or peaks in the final cut surface. The worse the dynamic performance, the larger the divots and peaks will be. If the bone cuts are for a cemented implants, small divots are acceptable because cement will simply fill the divots. For press fit implants, however, divots cause gaps between the implant and the bone that may potentially inhibit full in-growth of the bone into the implant. Peaks are less critical than divots because they can be easily removed with the burr but will increase the amount of time required to complete bone preparation.

(68) For motion compensation applications, several techniques are beneficial in maximizing performance from tracking systems with dynamic performance issues. First, because of the different update rates, if the coordinate transformation process **2506** uses data directly from the tracking system **40**, the desired cut surfaces defined by the virtual object move in abrupt steps in response to detected motion of the anatomy. As a result, a user manipulating the haptic device **30** may experience a rough or “jumpy” feeling when interacting with a haptic object. To address this problem, the surgical system **10** may include an interpolation or other appropriate filter (represented by the blocks **4512** in FIG. 12A). The filter also acts to reduce the output noise of the tracking system, which would otherwise result in the user feeling a vibration when interacting with a haptic object, or result in the cut having a rough surface. In a preferred embodiment, the filter is a 3rd order Butterworth filter with a cutoff frequency in a range of 5-10 Hz that samples data from the tracking system **40** at 2000 Hz and produces a filtered output. The filtered output reduces “jumpiness” of the cut surfaces relative to the anatomy from both the “stairstep” output from the

tracking system and the noise inherent in the tracking system output updates. The Butterworth filter is characterized by a flat frequency in the passband and is easily designed using commonly available filter design software, such as Mathwork's Matlab Signal Processing Toolbox "butter" function, which outputs digital or analog filter coefficients based on the desired order and cutoff frequency. Using a higher order will result in sharper rolloff characteristics but require additional computation. A lower cutoff frequency will improve the filtering of the discrete tracking system updates and the tracking system noise but degrade the dynamic performance of the tracking. Alternatively, a Chebychev, Inverse Chebychev, Elliptic, Bessel (Thomson), or other filter can be used instead of a Butterworth filter. In another embodiment, a finite impulse response (FIR) filter can be used. An FIR filter can be designed to be "linear phase" so that all frequencies are delayed by the same amount, which makes compensation for filter delay easier. FIR filters are also well suited to "multi-rate" applications. For the tracking application of the present invention, interpolation would be used to convert the low frequency tracking signal to the high frequency rate of the haptic device **30**. FIR filters are better than infinite impulse response (IIR) filters for multi-rate applications because FIR filters do not have feedback, i.e., their outputs are only a function of the input signal, not the output of the filter. Also, computation is only required for the low frequency signal samples, not for every high frequency sample.

(69) In their traditional implementation, all of the above filters are designed for scalar input signals. However, the tracking system **40** will generally output multiple position and orientation signals. In a preferred embodiment, the filter **4512** receives the tracking system output, expressed as a homogenous transformation four by four size matrix that contains the position and orientation information. It is not desirable to filter the elements of this matrix directly because the result will not be a valid homogenous matrix and the orientation will not be filtered properly. Instead, the homogenous transformation is first converted to a three element position vector and a quaternion, which is a four element vector that represents the orientation information. For the small motions between samples, these seven values can then be independently filtered. The quaternion may be normalized before taking the filtered values and converting them back to a homogenous transformation, which is then output from the filter **4512**.

(70) In most cases, the position output of the tracking system **40** represents the position of the relevant tracked object at some point in the past. The latency is the time interval between the time when the tracking system **40** samples the tracked object's position and the time when the surgical system **10** receives this position output. This time interval may include processing time of the tracking system **40**, communication delays, and a fraction or multiple of the sampling time of the tracking system **40**. The filter **4512** adds additional latency based on the phase delay of the particular filter selected. These latency sources all combine to degrade the dynamic tracking performance and cause the haptic surfaces to lag behind the motion of their associated tracked objects. However, these latency values are usually known or can be measured or estimated fairly accurately. Thus, the latency effect can be partially compensated for. For example, if the combined latency of the tracking system **40** and the filter **4512** is  $t_{sub.1}$ , then the filtered position output  $p$  may be corrected by  $\Delta p = v \cdot t_{sub.1}$ . The velocity value  $v$  can be computed by a (possibly filtered) difference of successive position values or with a washout filter, as described below. In another embodiment, as is well known to those skilled in the art of control theory, a state estimator, state observer, or Kalman filter, which include a simple simulated model of the anatomy and/or the base **32** of the haptic device **30** and internally compute both the position and velocity of the tracked object, could be used to eliminate the latency of the filter **4512**. Alternatively, the filter **4512** could be eliminated by utilizing a higher frequency tracking system, such as an encoder-based mechanical tracking system or high speed optical tracking system.

(71) Some tracking systems, notably optical tracking systems, may not produce accurate outputs when tracked objects are moving relative to the camera (i.e., the detection device **41**). Errors may result, for example, from motion blur caused by the exposure time or scanning rate of the camera.

If the velocity of the tracked object is computed using one of the methods described above and an error model of the tracking system as a function of velocity and/or position is known or determined, these errors may be corrected by adding this error value to the filtered position output.

(72) Dynamic performance of the tracking system **40** is only relevant if the haptic device **30** is capable of rendering a moving haptic object effectively. The haptic rendering capabilities of the haptic device **30** are impacted by the type of haptic control scheme used. The haptic device **30** may utilize any suitable haptic control scheme, such as, for example, admittance control, impedance control, or hybrid control. In an admittance control mode, the haptic device **30** accepts force input and yields position (or motion) output. For example, the haptic device **30** measures or senses a wrench at a particular location on the haptic device **30** (e.g., the user interface **37**) and acts to modify a position of the haptic device **30**. In an impedance control mode, the haptic device **30** accepts position (or motion) input and yields wrench output. For example, the haptic device **30** measures, senses, and/or calculates a position (i.e., position, orientation, velocity, and/or acceleration) of the tool **50** and applies an appropriate corresponding wrench. In a hybrid control mode, the haptic device **30** utilizes both admittance and impedance control. For example, a workspace of the haptic device **30** may be divided into a first subspace in which admittance control is used and a second subspace in which impedance control is used and/or both position and force inputs may be used to compute a force or position output. For example, in a substantially impedance controlled device, force inputs may be used to cancel out some of the natural friction of the system. In a preferred embodiment, the haptic device **30** is designed for impedance control, where the haptic device **30** reads the position and/or orientation of the user-manipulated surgical tool **50** and outputs an appropriate force and/or torque. Impedance control devices have the advantage of simplicity (no force sensor is required), better stability properties when the tool contacts physical objects (such as when cutting bone), and better performance when moving in free space. Admittance control devices, however, have an advantage in that they can render haptic objects with very stiff walls more easily than impedance control devices. With regard to motion tracking, impedance control devices are advantageous in that their performance is related to the open-loop force bandwidth and physical system dynamics. In contrast, the performance of an admittance control device depends on the closed-loop position control performance, which tends to be slower than the open-loop force and physical system dynamics.

(73) Returning to the haptic rendering algorithm of FIG. **10**, the HIP location,  $x$ , determined by the coordinate transformation process **2506** is provided as input to the haptic rendering algorithm **2508** as shown in FIG. **12B**. A collision detection/proxy location haptic rendering process (represented by block **4515** in FIG. **12B**) receives the HIP location,  $x$ , as input and outputs a desired location,  $x_{sub.d}$ . The HIP location,  $x$ , is subtracted from the desired location,  $x_{sub.d}$ , and the result,  $\Delta x$ , is multiplied by a haptic stiffness,  $K_{sub.p}$ , to determine a position-dependent force command,  $F_{sub.spring}$ . A desired velocity is also determined by taking the derivative,  $\dot{z}_{sub.d}$ , of the desired location,  $x_{sub.d}$ . The desired velocity is used in the computation of a damping force,  $F_{sub.damping}$ .

(74) As shown in FIG. **12B**, the damping force,  $F_{sub.damping}$ , is computed by subtracting the desired velocity,  $\{\dot{x}\}_{sub.d}$ , from a Cartesian endpoint velocity,  $\{\dot{x}\}$ , of the haptic device **30** and multiplying the result by a damping gain,  $K_{sub.D}$ . The Cartesian endpoint velocity,  $\{\dot{x}\}$ , is computed using data from position sensors in motors of the arm **33**. As discussed above in connection with the haptic device **30**, the arm **33** of the haptic device **30** preferably includes a cable transmission and position sensors in the motors and joints of the arm **33**. In a preferred embodiment, joint encoders (represented by block **4508** of FIG. **12A**) are used to obtain joint position measurements, and motor encoders (represented by block **4516** of FIG. **12A**) are used to compute velocity measurements. The joint position measurements are used in the forward kinematics process **2504** to determine the transformation  $T_{sub.5}$  and are also provided as input to a gravity compensation algorithm (represented by block **4518** in FIG. **12A**). The gravity

compensation algorithm computes gravity torques,  $\tau_{\text{sub.grav\_comp}}$ , required to counteract gravity loads on the segments of the arm **33** as a function of joint angle. In contrast, the motor position measurements are differenced and filtered to compute a motor velocity measurement. A washout filter (as represented by block **4520** in FIG. **12A**) combines the differentiating and smoothing into one filter. The washout filter may be represented in the Laplace domain as:

$$(75) F_{\text{WOF}}(s) = \frac{s}{p+1}$$

where  $s$  is the Laplace transform variable, and where  $p$  determines the location of poles and in general should be located about two to three times faster than the fastest system pole. In one embodiment, the pole is placed at about 80 Hz. The filtered velocity is then multiplied by a Jacobian matrix,  $J$ , to obtain the Cartesian endpoint velocity,  $\{\dot{x}\}$ , of the haptic device **30**.

(76) The washout filter limits the high-frequency gain thereby limiting the amplification of noise inherent in a derivative or differencing operation and removing sampling-rate artifacts. The washout filter has a single parameter,  $p$ , which simplifies design and tuning of the filter, compared with separate velocity differencing and smoothing operations. The Laplace domain representation given above can be transformed into a discrete-time representation that is suitable for implementation on a digital computer using the well-known bilinear transform or z-transform. In an alternative embodiment to the washout filter, a simple differenced position signal can be filtered with a Butterworth or other filter described above to provide a velocity measure. Alternatively, a filtered position signal can be differenced and possibly filtered again using any of the filters described above.

(77) As shown in FIG. **12B**,  $F_{\text{sub.damping}}$  and  $F_{\text{sub.spring}}$  are summed in the force mapping process **2510** to obtain a desired haptic force,  $F_{\text{sub.haptic}}$ . The desired haptic force is multiplied by a transposed Jacobian matrix,  $J_{\text{sup.T}}$ , to compute motor torques,  $\tau_{\text{sub.haptic}}$ , required to generate the desired haptic force. The gravity torques,  $\tau_{\text{sub.grav\_comp}}$ , are added to the motor torques,  $\tau_{\text{sub.haptic}}$ , to obtain a total torque,  $\tau_{\text{sub.total}}$ . The haptic device **30** is commanded to apply the total torque,  $\tau_{\text{sub.total}}$ , to the motors of the arm **33**. In this manner the haptic rendering process enables the surgical system **10** to control the haptic device **30**, which then responds to the commanded torques, user interaction, and interaction with the anatomy.

(78) The haptic device **30** is preferably configured to operate in various operating modes. For example, the haptic device **30** may be programmed to operate in an input mode, a hold mode, a safety mode, a free mode, an approach mode, a haptic (or burring) mode, and/or any other suitable mode. The operating mode may be selected manually by the user (e.g., using a selection button represented graphically on the display device **23** or a mode switch located on the haptic device **30** and/or the computing system **20**) and/or automatically by a controller or software process. In the input mode, the haptic device **30** is enabled for use as an input device to input information to the surgical system **10**. When the haptic device **30** is in the input mode, the user may operate the haptic device **30** as a joystick or other input device, for example, as described above in connection with the end effector **35** and/or in U.S. patent application Ser. No. 10/384,078 (Pub. No. US 2004/0034282), which is hereby incorporated by reference herein in its entirety.

(79) In the hold mode, the arm **33** of the haptic device **30** may be locked in a particular pose. For example, the arm **33** may be locked using brakes, control servoing techniques, and/or any other appropriate hardware and/or software for stabilizing the arm **33**. The user may desire to place the haptic device **30** in the hold mode, for example, during an activity such as bone cutting to rest, confer with a colleague, allow cleaning and irrigation of the surgical site, and the like. In the safety mode, the tool **50** coupled to the haptic device **30** may be disabled, for example, by shutting off power to the tool **50**. In one embodiment, the safety mode and the hold mode may be executed simultaneously so that the tool **50** is disabled when the arm **33** of the haptic device **30** is locked in position.

(80) In the free mode, the end effector **35** of the haptic device **30** is freely moveable within the

workspace of the haptic device **30**. Power to the tool **50** is preferably deactivated, and the haptic device **30** may be adapted to feel weightless to the user. A weightless feeling may be achieved, for example, by computing gravitational loads acting on the segments **33a**, **33b**, and **33c** of the arm **33** and controlling motors of the haptic device **30** to counteract the gravitational loads (e.g., as described below in connection with block **4518** of FIG. **12A**). As a result, the user does not have to support the weight of the arm. The haptic device **30** may be in the free mode, for example, until the user is ready to direct the tool **50** to a surgical site on the patient's anatomy.

(81) In the approach mode, the haptic device **30** is configured to guide the tool **50** to a target object, such as, for example, a surgical site, feature of interest on the patient's anatomy, and/or haptic object registered to the patient, while avoiding critical structures and anatomy. For example, in one embodiment, the approach mode enables interactive haptic positioning of the tool **50** as described in U.S. patent application Ser. No. 10/384,194 (Pub. No. US 2004/0034283), which is hereby incorporated by reference herein in its entirety. In another embodiment, the haptic rendering application may include a haptic object defining an approach volume (or boundary) that constrains the tool **50** to move toward the target object while avoiding sensitive features such as blood vessels, tendons, nerves, soft tissues, bone, existing implants, and the like. For example, as shown in FIG. **1**, the approach volume may include the haptic object **300**, which is substantially cone-shaped, funneling from a large diameter to a small diameter in a direction toward the target object (e.g., a proximal end of the tibia **T** or a distal end of the femur **F**). In operation, the user may freely move the tool **50** within the boundaries of the approach volume. As the user moves the tool **50** through the approach volume, however, the tapering funnel shape constrains tool movement so that the tool **50** does not penetrate the boundaries of the approach volume. In this manner, the tool **50** is guided directly to the surgical site.

(82) Another embodiment of the approach mode is shown in FIG. **8**, which illustrates a haptic object **208** corresponding to a femoral component of a knee prosthesis and a haptic object **208** corresponding to a tibial component of the knee prosthesis. In this embodiment, the haptic rendering application creates a virtual object that represents a pathway from a first position to a second position. For example, the virtual object may include a haptic object **310**, which is a virtual guide wire (e.g., a line) defining a pathway from a first position (e.g., a position of the tool **50** in physical space) to a second position that includes a target (e.g., a target object such as the haptic object **206** or **208**). In the approach mode, the haptic object **310** is activated so that movement of the tool **50** is constrained along the pathway defined by the haptic object **310**. The surgical system **10** deactivates the haptic object **310** when the tool **50** reaches the second position and activates the target object (e.g., the haptic object **206** or **208**). The tool **50** may be automatically placed in the haptic (or burring) mode when the haptic object **206** or **208** is activated. In a preferred embodiment, the haptic object **310** may be deactivated to enable the tool **50** to deviate from the pathway. Thus, the user can override the haptic guidance associated with the haptic object **310** to deviate from the guide wire path and maneuver the tool **50** around untracked objects (e.g., retractors, lamps, etc.) the cannot be accounted for when the virtual guide wire is generated. Thus, the approach mode enables the user to quickly deliver the tool **50** to a target object while avoiding critical structures and anatomy. In the approach mode, power to the tool **50** is preferably deactivated so that the tool is not accidentally energized, for example, when the user is inserting the tool through an incision or navigating soft tissue in a joint. The approach mode generally precedes the haptic mode.

(83) In the haptic (or burring) mode, the haptic device **30** is configured to provide haptic guidance to the user during a surgical activity such as bone preparation. In one embodiment, as shown in FIG. **8**, the haptic rendering application may include the haptic object **206** defining a cutting volume on the tibia **T**. The haptic object **206** may have a shape that substantially corresponds to a shape of a surface of a tibial component. The haptic device **30** may enter the haptic mode automatically, for example, when the tip of the tool **50** approaches a predefined point related to a feature of interest. In the haptic mode, the haptic object **206** may also be dynamically modified

(e.g., by enabling and disabling portions of a haptic surface) to improve performance of the haptic device **30** when sculpting complex shapes or shapes with high curvature as described, for example, in U.S. patent application Ser. No. 10/384,194 (Pub. No. US 2004/0034283), which is hereby incorporated by reference herein in its entirety. In the haptic mode, power to the tool **50** is activated, and the tip of the tool **50** is constrained to stay within the cutting volume to enable a precise bone resection. In another embodiment, an orientation constraint may be implemented, for example, by generating a slowly increasing force to draw the user inside the haptic volume if the user is in proximity to the haptic volume. Additionally, in this embodiment, the tool **50** can be disabled whenever the tool **50** is outside the haptic volume. In another embodiment, the tool **50** can be disabled unless the haptic device **30** is generating haptic feedback forces.

(84) In operation, the surgical system **10** may be used for surgical planning and navigation as disclosed in the above-referenced Pub. No. US 2006/0142657. The surgical system **10** may be used, for example, to perform a knee replacement procedure or other joint replacement procedure involving installation of an implant. The implant may include any implant or prosthetic device, such as, for example, a total knee implant; a unicondylar knee implant; a modular knee implant; implants for other joints including hip, shoulder, elbow, wrist, ankle, and spine; and/or any other orthopedic and/or musculoskeletal implant, including implants of conventional materials and more exotic implants, such as orthobiologics, drug delivery implants, and cell delivery implants. Prior to performance of the procedure, the haptic device **30** is initialized, which includes a homing process, a kinematic calibration, and a haptic device registration calibration.

(85) The homing process initializes the position sensors (e.g., encoders) in the arm **33** of the haptic device **30** to determine an initial pose of the arm **33**. Homing may be accomplished in any known manner such as by manipulating the arm **33** so that each joint encoder is rotated until an index marker on the encoder is read. The index marker is an absolute reference on the encoder that correlates to a known absolute position of the joint. Thus, once the index marker is read, the control system of the haptic device **30** knows that the joint is in an absolute position. As the arm **33** continues to move, subsequent positions of the joint are calculated based on the absolute position and subsequent displacement of the encoder.

(86) The kinematic calibration identifies errors in the kinematic parameters of the forward kinematics process **2504** (shown in FIG. **10**). The forward kinematics process **2504** calculates a Cartesian position and orientation of the end effector **35** based on the measured joint angles of the arm **33** and the as-designed geometric properties of the haptic device **30** (e.g., length and offset of the segments **33a**, **33b**, and **33c** of the arm **33**). Due to manufacturing inaccuracies, however, the actual geometric properties of the haptic device **30** may deviate from the as-designed geometric properties, which results in error in the output of the forward kinematics process **2504**. To determine the error, a kinematic calibration fixture is attached to the haptic device **30**. In one embodiment, the fixture is a calibration bar having a fixed, known length. To perform the kinematic calibration, the end effector **35** is replaced with a calibration end effector having one or more ball joints (e.g., four ball joints arranged to form a cross, where a ball joint is located on each endpoint of the cross), and the arm **34** (on which the haptic device tracker **45** mounts) is removed and remounted in a horizontal configuration. A first end of the calibration bar is magnetically engaged with a ball joint on the arm **34**, and a second end of the calibration bar is magnetically engaged with one of the ball joints on the calibration end effector. The calibration end effector is then moved to a plurality of positions (manually or automatically) as data is captured by the surgical system **10**. After sufficient data has been collected (e.g., 100 data points), the second end of the calibration bar is magnetically engaged with a different ball joint on the calibration end effector. The process is repeated until data is captured for each ball joint on the calibration end effector. Using the existing kinematic parameters and measured joint angles, the data is used to calculate the length of the calibration bar. The computed length of the calibration bar is compared with the known actual length. The difference between the computed length and the known length is the error. Once the



error is determined, the kinematic parameters can be adjusted to minimize aggregate error in the forward kinematics process **2504** using, for example, a numerical nonlinear minimization algorithm such as Levenberg-Marquardt.

(87) The haptic device registration calibration establishes a geometric relationship or transformation between a coordinate system of the haptic device tracker **45** (e.g., the coordinate system X.sub.3 shown in FIG. **13**) and the coordinate system of the haptic device **30** (e.g., the coordinate system X.sub.4 shown in FIG. **13**). If the haptic device tracker **45** is fixed in a permanent position on the haptic device **30**, the registration calibration is unnecessary because the geometric relationship between the tracker **45** and the haptic device **30** is fixed and known (e.g., from an initial calibration performed during manufacture or setup). In contrast, if the tracker **45** can move relative to the haptic device **30** (e.g., if the arm **34** on which the tracker **45** is mounted is adjustable), the registration calibration must be performed to determine the geometric relationship between the tracker **45** and the haptic device **30**.

(88) The registration calibration involves securing the haptic device tracker **45** in a fixed position on the haptic device **30** and temporarily affixing the end effector tracker **47** to the end effector **35**, for example, with the clamp **1500** shown in FIG. **6A**. To register the haptic device tracker **45** to the haptic device **30**, the end effector **35** (and thus the end effector tracker **47**) is moved to various positions in a vicinity of the anatomy (e.g., positions above and below the knee joint, positions medial and lateral to the knee joint) while the tracking system **40** acquires pose data for the trackers **45** and **47** relative to the tracking system **40** in each of the positions. Multiple data points are collected and averaged to minimize the effects of sensor noise and other measurement errors. Acquisition of the pose data during the registration calibration may be automatic. Alternatively, the user can initiate the collection of data using an input device such as a foot pedal.

(89) In one embodiment, the user manually moves the end effector **35** to the various positions while the end effector **35** is in the free mode. In another embodiment, the surgical system **10** controls the haptic device **30** to automatically move the end effector **35** to the various positions. In yet another embodiment, the haptic device **30** provides haptic guidance to guide the user in moving the end effector **35** to predefined points in the workspace of the haptic device **30**. To improve the accuracy of the registration calibration, the predefined points are preferably located in a vicinity of the surgical site (e.g., close to the actual bone preparation site). The predefined points may include, for example, vertices of a shape, such as a two or three dimensional polytope (e.g., a polygon or polyhedron). In one embodiment, the shape is a cube centered at the relevant anatomy, such as the knee joint. The vertices are preferably displayed on the display device **23** along with an arrow indicating an allowable direction of motion for the end effector **35**. One advantage of utilizing haptic guidance to guide the user in moving the end effector **35** to predefined points is that the user is able to move the end effector **35** to a plurality of positions in a repeatable fashion, which improves the accuracy of the registration calibration.

(90) In addition to capturing data relating the pose of the trackers **45** and **47** to the tracking system **40**, the surgical system **10** determines a pose of the end effector **35** relative to the haptic device **30** (e.g., relative to a reference point fixed in relation to the base **32** of the haptic device **30**) based on data from the position sensors (e.g., joint encoders) in the arm **33**. The surgical system **10** uses the data obtained during the registration calibration to calculate the geometric relationship between the haptic device tracker **45** and the coordinate frame of reference of the haptic device **30** (e.g., the coordinate system X.sub.4 shown in FIG. **13**, which has its origin at a reference point **300** fixed in relation to the base **32** of the haptic device **30**).

(91) In one embodiment, a transformation, T.sub.R.sup.B, of the haptic device tracker **45** relative to the base **32** of the haptic device **30** (e.g., relative to a reference point fixed in relation to the base **32** of the haptic device **30**) is calculated as follows. As the end effector **35** is moved to the various positions, the surgical system **10** records (a) a position of the end effector tracker **47** (e.g., a known position on the end effector **35**) relative to the tracking system **40**, P.sub.C.sup.E, which is obtained

from the tracking system **40**; (b) a position and an orientation of the haptic device tracker **45** relative to the tracking system **40**,  $T_{sub.C.sup.B}$ , which is obtained from the tracking system **40**; and (c) a position of the end effector tracker **47** relative to the base of the haptic device **30**,  $r$ , which is obtained from the joint encoders of the haptic device **30**. If noise is present in the tracking system output, multiple samples can be taken for each end effector position. In the event the haptic device **30** moves during data sampling, the surgical system **10** can alert the user. Additionally, any affected data points should be thrown out because there will be latency between the data from the tracking system **40** and the data from the joint encoders of the haptic device **30**. A position of the end effector tracker **47** relative to the haptic device tracker **45** is computed as  $b_{sub.i} = T_{sub.B,i.sup.CP.sub.C,i.sup.E}$  for each test location,  $i$ . A position of the end effector tracker **47** relative to the base **32** of the haptic device **30** at each test location,  $i$ , is denoted by  $r_{sub.i}$ .

(92) After data collection is complete, the transformation of the haptic device tracker **45** relative to the base **32** of the haptic device **30** (i.e., relative to a reference point on the base **32** of the haptic device **30**),  $T_{sub.R.sup.B}$ , is separated into orientation and position terms,

$$(93) T_R^B = \begin{bmatrix} R_R^B & P_R^B \\ 0 & 1 \end{bmatrix}.$$

The orientation component  $R_{sub.R.sup.B}$  is found by solving the equation

$R_{sub.R.sup.B} b_{sub.i} = r_{sub.i}$ . For this equation, the position error vectors  $b_{sub.i}$  and  $r_{sub.i}$  are computed according to  $b_{sub.i} = b_{sub.i} - b_{sub.m}$  and  $r_{sub.i} = r_{sub.i} - r_{sub.m}$ , where

$$(94) b_m = \frac{\sum_{k=1}^n b_k}{n} \text{ and } r_m = \frac{\sum_{k=1}^n r_k}{n}.$$

A least-squares estimator using singular value decomposition is used to solve for  $R_{sub.R.sup.B}$ .

The position vector  $P_{sub.R.sup.B}$  can then be found from the equation

$P_{sub.R.sup.B} = r_{sub.m} - R_{sub.R.sup.B} b_{sub.m}$ . The transformation of the haptic device tracker **45** relative to the base **32** of the haptic device **30**,  $T_{sub.R.sup.B}$ , can then be reconstructed according to

$$(95) T_R^B = \begin{bmatrix} R_R^B & P_R^B \\ 0 & 1 \end{bmatrix}.$$

(96) After the registration calibration is complete, the end effector tracker **47** is removed from the haptic device **30**. During surgery, the surgical system **10** can determine a pose of the tool **50** based on (a) a known geometric relationship between the tool **50** and the end effector **35**, (b) a pose of the end effector **35** relative to the haptic device **30** (e.g., from the position sensors in the arm **33**), (c) the geometric relationship between the haptic device **30** and the haptic device tracker **45** determined during the registration calibration, and (d) the global or gross position of the haptic device **30** (e.g., from the pose of the haptic device tracker **45** relative to the tracking system **40**). The registration calibration need not be performed if the haptic device tracker **45** has not moved with respect to the haptic device **30** since the previous registration calibration and the previously acquired registration calibration data is still reliable.

(97) In one embodiment, a method for performing the registration calibration includes (a) acquiring first data including at least one of a position and an orientation of a first object disposed on the haptic device **30** at a first location; (b) acquiring second data including at least one of a position and an orientation of a second object disposed on the haptic device **30** at a second location; (c) determining third data including at least one of a position and an orientation of the first object relative to the second location; and (d) determining at least one of a position and an orientation of the second object relative to the second location based at least in part on each of the first data, the second data, and the third data. The method may also include (e) moving the first object (e.g., the end effector tracker **47** disposed on the arm **33** of the haptic device **30**) to a plurality of positions; (f) providing haptic guidance (e.g., force feedback) to guide the user in moving the first object to at

least one of the plurality of positions; (g) acquiring the first data or the second data when the first object is in each of the plurality of positions; and (h) alerting the user if the first object, the second object, the first location, and/or the second location moves during acquisition of the first data, the second data, and/or the third data.

(98) In one embodiment, the first object is the end effector tracker **47**, and the second object is the haptic device tracker **45**. In this embodiment, the steps of acquiring the first data and the second data include detecting the trackers **45** and **47** with the detection device **41**. Alternatively, the second object may comprise one or more components of the tracking system **40**, such as the detection device **41**. As described above in connection with the end effector tracker **47**, the end effector tracker **47** may be disposed at a location (e.g., the first location) on the haptic device **30** that includes a locating feature, such as a cylindrical feature of the tool **50** or the tool holder **51**. In this case, the step of acquiring the first data may include determining a position and/or an orientation of a point and/or an axis of the cylindrical feature (e.g., the axis H-H shown in FIG. **3B** or any point thereon). As described above in connection with the haptic device tracker **45**, the haptic device tracker **45** (or the detection device **41**) may be disposed at a location (e.g., the second location) on the haptic device **30**, such as the base **32** (e.g., via the arm **34**) on which the proximal end of the arm **33** is disposed. Alternatively, the haptic device tracker **45** (or the end effector tracker **47**) may be located on an intermediate portion of the arm **33**. During the haptic device registration calibration, the position and/or the orientation of the first object and the second object are fixed relative to the first and second locations, respectively. Fixation may be accomplished, for example, by clamping the end effector tracker **47** to the end effector **35** with the clamp **1500** and by fixing the position of the arm **34** on which the haptic device tracker **47** (or the detection device **41**) is mounted. To determine the position and orientation of the first object relative to the second location (i.e., the third data), the surgical system **10** determines a configuration of the arm **33**, for example, based on data from the joint encoders.

(99) After the haptic device **30** is initialized, the surgeon can register the patient and the surgical tool **50** to a representation of the anatomy (such as a CT image) and perform a surgical procedure, such as preparing a bone to receive an implant based on a surgical plan. Registration, implant planning, and surgical navigation may be accomplished, for example, as described in the above-referenced Pub. No. US 2006/0142657. Throughout the surgical procedure, the surgical system **10** monitors a position of the bone to detect movement of the bone and makes corresponding adjustments to programs running on the computer **21** and/or the computer **31**. For example, the surgical system **10** can adjust a representation (or image) of the bone in response to detected movement of the bone. Similarly, the surgical system **10** can adjust a representation (or image) of the surgical tool **50** in response to detected movement of the surgical tool **50**. Thus, images of the bone and the surgical tool on the display device **23** move dynamically in real-time as the bone and the surgical tool **50** move in physical space. The surgical system **10** can also adjust a virtual object associated with the bone in response to detected movement of the bone. For example, the virtual object may define a virtual cutting boundary corresponding to a shape of a surface of the implant. As the bone moves, the surgical system **10** adjusts the virtual object so that the virtual cutting boundary moves in correspondence with the physical bone. In this manner, the surgeon can make accurate bone cuts even when the bone is moving. Additionally, adjustment of the images and the haptic object are transparent to the surgeon so that the surgeon's operation of the haptic device **30** is not interrupted during the surgical procedure.

(100) To improve the safety of the surgical system **10**, the surgical system **10** may include a safety feature adapted to constrain the user's operation of the tool **50** when an unsafe condition exists. For example, if an unsafe condition is detected, the surgical system **10** may issue a fault signal. A fault condition may exist if there is a system problem (e.g., a problem with the hardware or software), if an occlusion detection algorithm (e.g., as described below) detects an occluded condition, if a tracked object is moving too fast for the tracking system to process (e.g., when the patient's leg or

the haptic device tracker **45** suddenly drops), when the tracking data is questionable, when the user is pushing too hard on the interface **37**, and/or if the tool **50** is in an undesirable location. In one embodiment, the surgical system **10** is programmed to issue a fault if a relationship between the anatomy and a position, an orientation, a velocity, and/or an acceleration of the tool **50** does not correspond to a desired relationship and/or if the detection device **41** is unable to detect the position of the anatomy or the position of the surgical tool **51**. In response to the fault signal, the surgical system **10** may impose a constraint on the haptic device **30**. The constraint may include, for example, providing haptic guidance to the user (e.g., to prevent the user from moving the tool **50** in an unsafe manner) or changing the mode of the haptic device **30** (e.g., from a haptic mode to a free mode). In the preferred embodiment, the constraint is applied to the interface **37**, which is both manipulated by the user and is proximal to the surgical site. For a teleoperated haptic device, which includes a “master” device that is operated by the surgeon and is typically remote from the surgical site and a “slave” device that holds the surgical tool proximal to the surgical site and is controlled by the master device, the constraint may be applied to the master device, the slave device, or both.

(101) In one embodiment, a fault signal may be issued if the haptic rendering algorithm determines that a penetration depth of the tool **50** into a haptic boundary exceeds a predetermined threshold. The predetermined threshold may be, for example, a penetration depth in a range of about 1 mm to about 1.25 mm. In one embodiment, the haptic rendering algorithm determines whether the predetermined threshold is exceeded based on the haptic wrench (i.e., force and/or torque) being applied by the haptic device **30** to the user. For example, the haptic rendering algorithm may include a linear force versus position curve where the haptic force is set to about 20,000 N/m (or 20 N/mm). Thus, if the user moves the tip of the tool **50** to a penetration depth of 1 mm, the haptic device **30** outputs a haptic force of about 20 N. Similarly, if the user moves the tip of the tool **50** to a penetration depth of 1.25 mm, the haptic device **30** outputs a haptic force of about 25 N. In this embodiment, the fault signal is triggered when the haptic force reaches about 22.5 N, which corresponds to a penetration depth of about 1.125 mm. Additionally, a threshold haptic force value can be used to protect against the haptic device **30** generating excessively high forces. For example, haptic objects can be designed as independent primitives (e.g., simple geometric shapes) and combined during haptic rendering. If the cumulative effect of the primitives is undesirable (e.g., the total haptic force is too high), a fault signal can be issued.

(102) In another embodiment, a fault signal may issue if rapid motion of the anatomy is detected as indicated, for example, by a velocity of the anatomy trackers **43a** and **43b**. Rapid motion may be caused, for example, when the anatomy shifts or a tracking element or the detection device **41** is bumped. In one embodiment, the fault signal issues if a velocity of the anatomy tracker **43a** is greater than about 40 mm/s or a velocity of the anatomy tracker **43b** is greater than about 26 mm/s. The indication of rapid motion may also be based on position (as opposed to velocity) such as when a position of the anatomy tracker **43a** or **43b** abruptly changes significantly. An abrupt change may be indicated, for example, if a change from the last known good position reported by the tracking system **40** to the current position reported by the tracking system **40** is greater than a predetermined threshold. In addition to rapid motion of the anatomy, the fault signal may issue if rapid motion of the haptic device tracker **45** is detected, such as when the haptic device tracker **45** has a high velocity or an abrupt change in position, which may indicate that the tracker **45** has been bumped or is not securely secured to the arm **34**.

(103) The surgical system **10** may have different levels or stages of faults. For example, in one embodiment, there are three stages of faults. The first fault stage applies when the tip of the tool **50** penetrates too deeply into or beyond a haptic boundary. The second fault stage applies when rapid motion of the anatomy is detected. The third fault stage applies when a system fault is present. The surgical system **10** responds to the fault stages by imposing a constraint on the haptic device **30**. For example, the surgical system **10** may respond to the first fault stage by disabling the tool **50**. The surgical system **10** may respond to the second fault stage by disabling both the tool **50** and the

haptic guidance. Disabling the haptic guidance when rapid motion of the anatomy is detected (e.g., when the patient's leg slips off the operating table) advantageously prevents the virtual haptic surfaces that define the haptic cutting volume from moving with the falling bone and dragging the tool **50** along. In contrast, if the haptic surfaces are not disabled when the bone moves rapidly, the haptic surfaces will follow the bone and the haptic device **30** will exert a large force on the arm **33** to maintain the tool **50** within the falling haptic volume. As a result, the arm **33** will be dragged downward as the bone falls. Disabling the haptic guidance avoids this dangerous situation. The surgical system **10** may respond to the third fault stage by disabling the tool **50**, shutting off power to the arm **33**, and locking the brakes of the arm **33**. In one embodiment, the surgical system **10** responds to a fault signal by disabling the tool **50** and placing the haptic device **30** in the free mode (rather than applying the brakes) so that the arm **33** does not pull or apply stress to the anatomy. In this manner, the surgical system **10** avoids damaging the anatomy by preventing the user from operating the tool **50** and/or the arm **33** when an unsafe condition exists.

(104) In one embodiment, a safety feature of the surgical system **10** includes a tool disabling feature. For example, if the tool **50** is an electric tool, the surgical system **10** may include a relay disposed along an electrical connection between the tool **50** and a user input device for controlling the tool **50**. For example, the relay may be located between a foot pedal and a tool control console (e.g., the ANSPACH® foot pedal and console described above in connection with the tool **50**). Alternatively, the relay could be disposed along a control cable for a handheld instrument. In the case of a pneumatic tool, a pneumatic shutoff valve may be disposed in an air connection between the user input device and the tool motor. In lieu of a relay, the surgical system **10** could supply a digital or analog signal to a “disable input” port on the tool control console. In one embodiment, the surgical system **10** includes a relay that is closed under normal operating conditions so that the tool **50** is activated when the user depresses the foot pedal. If a fault condition is detected, the surgical system **10** issues a fault signal and commands the relay to open so that the tool **50** cannot be activated even when the user depresses the foot pedal. In another embodiment, the relay is a “normally open” relay so that the tool **50** will remain shut off or disabled unless the tool **50** is specifically enabled by the surgical system **10**. One advantage of a “normally open” relay is that if the haptic device **30** completely shuts down, the tool **50** will be disabled. Alternatively or in addition to disabling the tool **50** by commanding a relay or shut off valve, a fault condition may trigger the surgical system **10** to disable the tool **50** by commanding a power shutoff to the console or to the power supplies or amplifiers that drive the tool **50**.

(105) In one embodiment, a method of controlling the haptic device **30** based on the tool disabling features includes (a) enabling operation of the haptic device **30**; (b) manipulating the haptic device **30** to perform a procedure on a patient; (c) determining whether a relationship between the anatomy of the patient and a position, an orientation, a velocity, and/or an acceleration of the tool **50** of the haptic device **30** corresponds to a desired relationship; and (d) issuing a fault signal and/or imposing a constraint on the haptic device **30** if the relationship does not correspond to the desired relationship or if the detection device **41** is unable to detect the anatomy or the tool **50**. The relationship may be based, for example, on a desired interaction between the anatomy and the tool **50**. In one embodiment, the relationship is defined by a virtual object positioned relative to the anatomy and representing a desired location of an implant and/or cut surfaces for installing the implant. The method may further include implementing control parameters for controlling the haptic device **30** to provide at least one of haptic guidance to the user and a limit on user manipulation of the surgical device based on the relationship. In one embodiment, in response to the fault signal, the surgical system **10** disables operation of the haptic device **30**, locks a portion of the haptic device **30** in position, and/or places the haptic device **30** in a safety mode. In the safety mode, operation of and/or manipulation of the haptic device **30** may be impeded or constrained. To determine whether the relationship corresponds to the desired relationship, the surgical system **10** may, for example, determine whether a penetration depth of the tool **50** into a virtual boundary

associated with the anatomy exceeds a desired penetration depth, determine whether the haptic device **30** has violated an operational constraint (e.g., a parameter generated by the haptic rendering algorithm), and/or determine whether the detection device **41** is able to detect a position of the anatomy and/or a position of the tool **50**.

(106) In another embodiment, a safety feature of the surgical system **10** includes an occlusion detection algorithm adapted to mitigate risk during a cutting operation in the event tracking elements (e.g., the trackers **43a**, **43b**, **45**) associated with the haptic device **30** and/or the anatomy become occluded. An occluded state may exist, for example, when the detection device **41** is unable to detect a tracking element (e.g., when a person or object is interposed between the tracking element and the detection device **41**), when a lens of the detection device **41** is occluded (e.g., by dust), and/or when reflectivity of markers on a tracking element is degraded (e.g., by blood, tissue, dust, bone debris, etc.). If an occluded state is detected, the occlusion detection algorithm alerts the user, for example, by causing a warning message to be displayed on the display device **23**, an audible alarm to sound, and/or the generation of tactile feedback (e.g., vibration). The occlusion detection algorithm may also issue a control signal, such as a command to the surgical system **10** to shut off power to or otherwise disable the tool **50** or to impose a constraint on the haptic device **30** (e.g., providing haptic guidance, changing a mode of the haptic device **30**, etc.). In this manner, the occlusion detection algorithm prevents the tool **50** from damaging the anatomy when the tracking system **40** is not able to accurately determine relative positions of the tool **50** and the anatomy.

(107) In one embodiment, the occlusion detection algorithm considers a position of the tool **50** relative to a haptic boundary. In this embodiment, if the occlusion detection algorithm detects an occluded state, the surgical system **10** determines whether the tool **50** is touching a haptic boundary of a haptic object. If the tool **50** is not in contact with a haptic boundary at the time of an occlusion event, the occlusion detection algorithm disables the tool **50** and places the haptic device **30** in the free mode so that the tool **50** will move with the patient and, if necessary, can be withdrawn from the patient. When the occluded state ends (e.g., when all occluded trackers become visible), the surgical system **10** places the haptic device **30** in the approach mode so that the user may resume the procedure. In this manner, the occlusion detection algorithm permits the haptic boundary to be deactivated if the user isn't pushing against the haptic wall at the time of the occlusion event. In contrast, if the surgical system **10** determines that the tool **50** is touching the haptic boundary and/or exceeding the haptic boundary at the time of the occlusion event, the occlusion detection algorithm waits for a predetermined period of time (e.g., 1 second) to see if the occluded tracker(s) become visible. During this time, the tool **50** is disabled, and the user is alerted that the tracker(s) are occluded (e.g., via a visual, audible, or tactile signal). If the haptic device tracker **45** and the anatomy trackers **43a** and **43b** all become visible within the predetermined period of time, the haptic (or burring) mode is resumed. Otherwise, the haptic device **30** is placed in the free mode so that the tool **50** will move with the patient and, if necessary, can be withdrawn from the patient. As before, when the occluded state ends (e.g., when all occluded trackers again become visible), the surgical system **10** places the haptic device **30** in the approach mode so that the user may resume the procedure. One advantage of utilizing the predetermined period of time (or time interval) is that the occlusion detection algorithm allows the haptic wall to remain active during momentary occlusion events. Additionally, sudden removal of the haptic walls, which might result in sudden motion from the surgeon during cutting, is avoided. Additionally, if the occluded condition ceases to exist within the predetermined period of time, the low pass filter utilized for dynamic tracking (motion compensation) is reset to prevent the tracking system **40** from perceiving small motions as discontinuous motion.

(108) FIGS. **14A-B** show a diagram of an embodiment of an occlusion detection algorithm. In step **S3500**, the haptic device **30** is in the haptic (or burring) mode. In step **S3502**, the algorithm determines whether the haptic device tracker **45** and the relevant anatomy tracker are both visible

(i.e., not occluded) to the detection device **41**. The relevant anatomy tracker is the anatomy tracker associated with the bone of interest. Thus, for a knee replacement procedure, if the surgeon is preparing the femur F, the relevant anatomy tracker is the anatomy tracker **43a**. Similarly, if the surgeon is preparing the tibia T, the relevant anatomy tracker is the anatomy tracker **43b**. Although additional anatomy trackers may also be monitored, the occlusion detection algorithm preferably monitors only the relevant anatomy tracker to avoid unnecessary false triggers (e.g., triggers based on occlusion of trackers associated with portions of the anatomy other than the bone of interest). If both the haptic device tracker **45** and the relevant anatomy tracker are visible, the algorithm proceeds to step **S3504** and enables the surgical tool **50**. The surgical tool **50** may be enabled, for example, by providing power to the tool **50** so that the tool **50** can be activated by the user, such as by depressing a foot pedal. As shown in the loop of FIG. **14** (steps **S3500**, **S3502**, and **S3504**), as long as both trackers are visible, the haptic device **30** continues in the haptic mode with the surgical tool **50** enabled.

(109) In contrast, if the detection device **41** in step **S3502** is unable to detect the haptic device tracker **45** and/or the relevant anatomy tracker, the algorithm concludes that at least one of the trackers is occluded and proceeds to step **S3506**. The surgical tool **50** may be disabled, for example, by shutting off power to the tool **50** so that the tool **50** cannot be activated by the user even if the user attempts to activate the tool **50**, such as by depressing a foot pedal. After the tool **50** is disabled, the algorithm proceeds to step **S3508** and provides an indication to the user that an occluded state exists. The indication may be any suitable signal, such as a visual signal on the display device **23**, an audible signal (e.g., a beep, alarm, or other warning sound), a tactile signal (e.g., vibration), and/or a control signal (e.g., a control signal that commands the haptic device **30** to lock the arm **33** in position). In step **S3510**, the algorithm determines whether a haptic force is detected. A haptic force is detected, for example, when the haptic device **30** is providing force feedback to the user (e.g., haptic guidance and/or a limit on user manipulation of the arm **33**). If a haptic force is not detected in step **S3510**, the algorithm proceeds to step **S3518**, deactivates the haptic mode, and enables the free mode. When the haptic device **30** is in the free mode, the tool **50** will move with the patient and, if necessary, can be withdrawn from the patient. When the occluded state ends, the surgical system **10** places the haptic device **30** in the approach mode so that the surgeon may resume the procedure.

(110) In contrast, if a haptic force is detected, the algorithm proceeds to step **S3512** and maintains the haptic device **30** in the haptic mode. In step **S3514**, the algorithm determines whether the haptic device tracker **45** and/or the relevant anatomy tracker is still occluded. If the trackers are not occluded, the algorithm returns to step **S3500** where the haptic device **30** is maintained in the haptic mode so that the surgeon may continue the procedure. In contrast, if at least one of the trackers is still occluded, the algorithm proceeds to step **S3516** and determines whether a time  $t$  has elapsed since the occluded state was detected. The time  $t$  may be chosen based on the application. In one embodiment, the time  $t$  is about 1 second. If the time  $t$  has not elapsed, the algorithm returns to step **S3514**. If the time  $t$  has elapsed, the algorithm proceeds to step **S3518**, deactivates the haptic mode, and enables the free mode. When the haptic device **30** is in the free mode, the tool **50** will move with the patient and, if necessary, can be withdrawn from the patient. When the occluded state ends, the surgical system **10** places the haptic device **30** in the approach mode so that the surgeon may resume the procedure. In this manner, the occlusion detection algorithm advantageously limits the user's ability to activate the tool **50** when the surgical system **10** is not able to determine the relative positions of the haptic device **30** and the anatomy. As a result, the risk of damaging the anatomy is mitigated.

(111) Another embodiment of the occlusion detection algorithm includes a method for controlling the haptic device **30** comprising the following steps: (a) detecting with the detection device **41** a first object comprising at least one of the anatomy and a tracking element associated with the anatomy; (b) detecting with the detection device **41** a second object comprising at least one of the

haptic device **30** and a tracking element associated with the haptic device **30**; and (c) providing an indication to the user if the detection device **41** is unable to detect the first object and/or the second object. The indication may be, for example, a signal, such as a visual, an audible, a tactile, and/or a control signal, or may be provided by disabling at least a portion of the haptic device **30**, such as the tool **50**. In one embodiment, the method includes imposing a constraint on the haptic device **30**, such as limiting movement of at least a portion of the haptic device **30** (e.g., the arm **33**, the tool **50**) or limiting operation of the haptic device **30** (e.g., shutting off power to or otherwise disabling the tool **50**, changing a mode of the haptic device, etc.). The constraint is preferably removed after a predetermined time interval (e.g., 1 second as discussed above in connection with step **S3516** of FIG. **14B**). The method may also include enabling the haptic device **30** only if the detection device **41** is able to detect both the first object and the second object.

(112) In one embodiment, the occlusion detection algorithm determines whether the haptic device **30** is providing haptic guidance to the user and/or a limit on user manipulation of the haptic device **30**. The haptic guidance and/or the limit on user manipulation may be based, for example, on a virtual boundary associated with the anatomy. If haptic guidance and/or a limit on user manipulation is being provided, the haptic guidance and/or the limit on user manipulation is preferably maintained to avoid damage to the anatomy (e.g., damage caused by sudden removal of the virtual boundary or haptic wall when the user is pushing against the virtual boundary with the tool **50**). Accordingly, the virtual boundary is preferably maintained if a portion of the haptic device **30** (e.g., the tip of the tool **50**) is proximate to, in contact with, or exceeding the virtual boundary. The method may also include deactivating the virtual boundary if the portion of the haptic device **30** is not interacting with the virtual boundary (e.g., if the tool **50** is not in contact with the virtual boundary or haptic wall). In this situation, because the user is not pushing against the virtual boundary with the tool **50**, the tool **50** is not likely to damage the anatomy if the virtual boundary is suddenly removed. As a result, the risk of damaging the anatomy is reduced.

(113) Thus, embodiments of the present invention provide a surgical system that is able to cooperatively interact with a surgeon to enable the surgeon to sculpt complex shapes in bone in a minimally invasive manner and that has the ability to dynamically compensate for motion of objects in the intraoperative environment in a manner that safeguards the patient and is substantially transparent to the surgeon.

(114) A system and method for verifying calibration of a surgical device is disclosed in U.S. patent application Ser. No. 11/750,807, entitled System and Method for Verifying Calibration of a Surgical Device, by Louis Arata, Sherif Aly, Robert Van Vorhis, Sandi Glauser, Timothy Blackwell, Rony Abovitz, and Maurice R. Ferre, filed on May 18, 2007, the disclosure of which is hereby incorporated herein by reference in its entirety.

## Claims

1. A surgical system, comprising a surgical tool configured to interact with an anatomy; a robotic system coupled to the surgical tool; a tracking system comprising: a tracker coupled to the robotic system, the surgical tool, or the anatomy; and an optical detection device that is configured to detect the tracker; and a computing system that: controls the robotic system using a virtual boundary; detects existence of a condition wherein the optical detection device is occluded from detecting the tracker; maintains the virtual boundary in response to the condition ceasing to exist before expiration of a predetermined period of time; places the robotic system in a free mode in response to the condition persisting for at least the predetermined period of time; and generates a fault signal in response to a determination that a movement of the tracker violates a limit.
2. The surgical system of claim 1, wherein the computing system maintains the virtual boundary during the predetermined period of time.
3. The surgical system of claim 1, wherein the computing system disables the surgical tool during



the predetermined period of time.

4. The surgical system of claim 3, wherein the computing system re-enables the surgical tool if the condition ceases to exist before the expiration of the predetermined period of time.

5. The surgical system of claim 1, wherein the computing system provides a visual or audible alert relating to the condition to a user during the predetermined period of time.

6. The surgical system of claim 1, wherein the computing system resets, in response to the condition ceasing to exist before the expiration of the predetermined period of time, a low pass filter used by the tracking system.

7. The surgical system of claim 1, wherein the predetermined time period is one second.

8. A method, comprising: controlling a robotic system using a virtual boundary and based on optical tracking of a tracker; detecting a condition in which an optical detection device is occluded from detecting the tracker; maintaining the virtual boundary in response to the condition persisting for shorter than a predetermined period of time; and providing an audible alert during the predetermined period of time in response to the condition.

9. The method of claim 8, further comprising maintaining the virtual boundary during the predetermined period of time.

10. The method of claim 8, further comprising placing the robotic system in a free mode in response to the condition persisting for at least the predetermined period of time.

11. The method of claim 8, further comprising: disabling a tool of the robotic system in response to the condition; and re-enabling the tool in response to the condition persisting for shorter than the predetermined period of time.

12. The method of claim 8, further comprising generating a fault signal in response to a determination that a movement of the tracker violates a limit.

13. One or more non-transitory computer-readable media storing program instructions that, when executed by one or more processors, cause the one or more processors to perform operations comprising: controlling a robotic system using a virtual boundary and based on optical tracking of a tracker; determining existence of a condition in which an optical detection device is occluded from detecting the tracker; disabling a tool in response to existence of the condition and re-enabling the tool in response to the condition ceasing to exist before expiration of a predetermined period of time; maintaining the virtual boundary in response to the condition ceasing to exist before expiration of the predetermined period of time; and generating a fault signal in response to a determination that a movement of the tracker violates a limit.

14. The one or more non-transitory computer-readable media of claim 13, wherein the operations further comprise maintaining the virtual boundary during the predetermined period of time.

15. The one or more non-transitory computer-readable media of claim 13, wherein the operations further comprise stopping, in response to the fault signal, power to a tool interfacing with the robotic arm.

---