

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12390254
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Tiongson; Christina M. et al.

---

### Bone stabilization systems

---

#### Abstract

An aiming guide system configured for connection to a bone plate including an aiming arm and a connection assembly. The aiming arm has a rigid body extending from a proximal end to a distal end with a plurality of aiming holes defined through the rigid body between the proximal end and the distal end thereof. The distal end defines an attachment slot through the body. The connection assembly is configured to engage an attachment screw hole of the bone plate and the attachment slot such that the aiming arm is fixed in position relative to the bone plate with each of the aiming holes aligned with a respective hole along the bone plate.

---

**Inventors:** Tiongson; Christina M. (Norristown, PA), Lueth; Jeffrey S. (Collegeville, PA), Shiner; Zachary C. (Philadelphia, PA), Jansen; David R. (Glenmoore, PA), Gray; Lauren E. (West Grove, PA)

**Applicant:** GLOBUS MEDICAL, INC. (Audubon, PA)

**Family ID:** 1000008763010

**Assignee:** Globus Medical Inc. (Audubon, PA)

**Appl. No.:** 18/413327

**Filed:** January 16, 2024

#### Prior Publication Data

Document Identifier	Publication Date
US 20240148420 A1	May. 09, 2024

#### Related U.S. Application Data

continuation parent-doc US 17388116 20210729 US 11871970 child-doc US 18413327  
continuation-in-part parent-doc US 15925846 20180320 US 10856920 20201208 child-doc US 16031066

## Publication Classification

**Int. Cl.:** **A61B17/80** (20060101); **A61B17/17** (20060101); **A61B17/34** (20060101); **A61B17/84** (20060101); **A61B17/86** (20060101); A61B17/68 (20060101); A61B90/00 (20160101)

**U.S. Cl.:**

**CPC** **A61B17/8061** (20130101); **A61B17/1728** (20130101); **A61B17/3468** (20130101); **A61B17/3496** (20130101); **A61B17/8014** (20130101); **A61B17/8057** (20130101); **A61B17/808** (20130101); **A61B17/84** (20130101); **A61B17/846** (20130101); **A61B17/86** (20130101); **A61B17/8665** (20130101); **A61B17/8695** (20130101); A61B2017/347 (20130101); A61B2017/681 (20130101); A61B2090/0808 (20160201)

## Field of Classification Search

**CPC:** A61B (17/17); A61B (17/80); A61B (17/808); A61B (17/8004); A61B (17/1728)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1105105	12/1913	Sherman	N/A	N/A
2486303	12/1948	Longfellow	N/A	N/A
3716050	12/1972	Johnston	N/A	N/A
4493317	12/1984	Klaue	N/A	N/A
4524765	12/1984	de Zbikowski	N/A	N/A
4651724	12/1986	Berentey et al.	N/A	N/A
4683878	12/1986	Carter	N/A	N/A
4781183	12/1987	Casey et al.	N/A	N/A
4867144	12/1988	Karas et al.	N/A	N/A
4923471	12/1989	Morgan	N/A	N/A
5002544	12/1990	Klaue et al.	N/A	N/A
5041114	12/1990	Chapman et al.	N/A	N/A
5151103	12/1991	Tepic et al.	N/A	N/A
5259398	12/1992	Vrespa	N/A	N/A
5364399	12/1993	Lowery et al.	N/A	N/A
5372598	12/1993	Luhr et al.	N/A	N/A
5423826	12/1994	Coates et al.	N/A	N/A
5468242	12/1994	Reisberg	N/A	N/A
D365634	12/1994	Morgan	N/A	N/A
5489305	12/1995	Morgan	N/A	N/A
5527311	12/1995	Procter et al.	N/A	N/A
5578036	12/1995	Stone et al.	N/A	N/A
5601553	12/1996	Trebing et al.	N/A	N/A
5676667	12/1996	Hausman	N/A	N/A
5690631	12/1996	Duncan et al.	N/A	N/A

5709686	12/1997	Talos et al.	N/A	N/A
5709687	12/1997	Pennig	N/A	N/A
5718704	12/1997	Medoff	N/A	N/A
5718705	12/1997	Sammarco	N/A	N/A
5746742	12/1997	Runciman et al.	N/A	N/A
5766175	12/1997	Martinotti	N/A	N/A
5785712	12/1997	Runciman et al.	N/A	N/A
5797914	12/1997	Leibinger	N/A	N/A
5814048	12/1997	Morgan	N/A	N/A
5925048	12/1998	Ahmad et al.	N/A	N/A
5938664	12/1998	Winqvist et al.	N/A	N/A
5961519	12/1998	Bruce et al.	N/A	N/A
6001099	12/1998	Huebner	N/A	N/A
6093201	12/1999	Cooper et al.	N/A	N/A
6096040	12/1999	Esser	N/A	N/A
6152927	12/1999	Farris et al.	N/A	N/A
6206881	12/2000	Frigg et al.	N/A	N/A
6283969	12/2000	Grusin et al.	N/A	N/A
6309393	12/2000	Tepic et al.	N/A	N/A
6322562	12/2000	Wolter	N/A	N/A
6364882	12/2001	Orbay	N/A	N/A
6533786	12/2002	Needham et al.	N/A	N/A
6623486	12/2002	Weaver et al.	N/A	N/A
6669700	12/2002	Farris et al.	N/A	N/A
6669701	12/2002	Steiner et al.	N/A	N/A
6712820	12/2003	Orbay	N/A	N/A
6719759	12/2003	Wagner et al.	N/A	N/A
6730091	12/2003	Pfefferle et al.	N/A	N/A
6866665	12/2004	Orbay	N/A	N/A
6955677	12/2004	Dahners	N/A	N/A
6974461	12/2004	Wolter	N/A	N/A
7001387	12/2005	Farris et al.	N/A	N/A
7063701	12/2005	Michelson	N/A	N/A
7128744	12/2005	Weaver et al.	N/A	N/A
7137987	12/2005	Patterson et al.	N/A	N/A
7153309	12/2005	Huebner et al.	N/A	N/A
7179260	12/2006	Gerlach et al.	N/A	N/A
7250053	12/2006	Orbay	N/A	N/A
7294130	12/2006	Orbay	N/A	N/A
7322983	12/2007	Harris	N/A	N/A
7341589	12/2007	Weaver et al.	N/A	N/A
7354441	12/2007	Frigg	N/A	N/A
7604657	12/2008	Orbay et al.	N/A	N/A
7632277	12/2008	Woll et al.	N/A	N/A
7635381	12/2008	Orbay	N/A	N/A
7637928	12/2008	Fernandez	N/A	N/A
7655029	12/2009	Niedernberger et al.	N/A	N/A
7695472	12/2009	Young	N/A	N/A
7717946	12/2009	Oepen et al.	N/A	N/A
7722653	12/2009	Young et al.	N/A	N/A

7740648	12/2009	Young et al.	N/A	N/A
7776076	12/2009	Grady, Jr. et al.	N/A	N/A
7857838	12/2009	Orbay	N/A	N/A
7867260	12/2010	Meyer et al.	N/A	N/A
7867261	12/2010	Sixto, Jr. et al.	N/A	N/A
7875062	12/2010	Lindemann et al.	N/A	N/A
7905910	12/2010	Gerlach et al.	N/A	N/A
7909858	12/2010	Gerlach et al.	N/A	N/A
7951178	12/2010	Jensen	N/A	N/A
7951179	12/2010	Matityahu	N/A	N/A
7976570	12/2010	Wagner et al.	N/A	N/A
D643121	12/2010	Millford et al.	N/A	N/A
D646785	12/2010	Milford	N/A	N/A
8043297	12/2010	Grady, Jr. et al.	N/A	N/A
8057520	12/2010	Ducharme et al.	N/A	N/A
8062296	12/2010	Orbay et al.	N/A	N/A
8100953	12/2011	White et al.	N/A	N/A
8105367	12/2011	Austin et al.	N/A	N/A
8114081	12/2011	Kohut et al.	N/A	N/A
8118846	12/2011	Leither et al.	N/A	N/A
8162950	12/2011	Digeser et al.	N/A	N/A
8167918	12/2011	Strnad et al.	N/A	N/A
8177820	12/2011	Anapliotis et al.	N/A	N/A
8246661	12/2011	Beutter et al.	N/A	N/A
8252032	12/2011	White et al.	N/A	N/A
8257403	12/2011	Den Hartog et al.	N/A	N/A
8257405	12/2011	Haidukewych et al.	N/A	N/A
8257406	12/2011	Kay et al.	N/A	N/A
8262707	12/2011	Huebner et al.	N/A	N/A
8267972	12/2011	Gehlert	N/A	N/A
8317842	12/2011	Graham et al.	N/A	N/A
8323321	12/2011	Gradl	N/A	N/A
8337535	12/2011	White et al.	N/A	N/A
8343155	12/2012	Fisher et al.	N/A	N/A
8382807	12/2012	Austin et al.	N/A	N/A
8394098	12/2012	Orbay et al.	N/A	N/A
8394130	12/2012	Orbay et al.	N/A	N/A
8398685	12/2012	McGarity et al.	N/A	N/A
8403966	12/2012	Ralph et al.	N/A	N/A
8419775	12/2012	Orbay et al.	N/A	N/A
8435272	12/2012	Dougherty et al.	N/A	N/A
8439918	12/2012	Gelfand	N/A	N/A
8444679	12/2012	Ralph et al.	N/A	N/A
8491593	12/2012	Prien et al.	N/A	N/A
8506608	12/2012	Cerny et al.	N/A	N/A
8512385	12/2012	White et al.	N/A	N/A
8518090	12/2012	Huebner et al.	N/A	N/A
8523862	12/2012	Murashko, Jr.	N/A	N/A
8523919	12/2012	Huebner et al.	N/A	N/A
8523921	12/2012	Horan et al.	N/A	N/A

8540755	12/2012	Whitmore	N/A	N/A
8551095	12/2012	Fritzinger et al.	N/A	N/A
8568462	12/2012	Sixto, Jr. et al.	N/A	N/A
8574268	12/2012	Chan et al.	N/A	N/A
8597334	12/2012	Mocanu	N/A	N/A
8603147	12/2012	Sixto, Jr. et al.	N/A	N/A
8617224	12/2012	Kozak et al.	N/A	N/A
8632574	12/2013	Kortenbach et al.	N/A	N/A
8641741	12/2013	Murashko, Jr.	N/A	N/A
8641744	12/2013	Weaver et al.	N/A	N/A
8663224	12/2013	Overes et al.	N/A	N/A
8728082	12/2013	Fritzinger et al.	N/A	N/A
8728126	12/2013	Steffen	N/A	N/A
8740905	12/2013	Price et al.	N/A	N/A
8747442	12/2013	Orbay et al.	N/A	N/A
8764751	12/2013	Orbay et al.	N/A	N/A
8764808	12/2013	Gonzalez-Hernandez	N/A	N/A
8777998	12/2013	Daniels et al.	N/A	N/A
8790376	12/2013	Fritzinger et al.	N/A	N/A
8790377	12/2013	Ralph et al.	N/A	N/A
8808333	12/2013	Kuster et al.	N/A	N/A
8808334	12/2013	Strnad et al.	N/A	N/A
8834532	12/2013	Velikov et al.	N/A	N/A
8834537	12/2013	Castanada et al.	N/A	N/A
8852246	12/2013	Hansson	N/A	N/A
8852249	12/2013	Ahrens et al.	N/A	N/A
8864802	12/2013	Schwager et al.	N/A	N/A
8870931	12/2013	Dahners et al.	N/A	N/A
8888825	12/2013	Batsch et al.	N/A	N/A
8906076	12/2013	Mocanu et al.	N/A	N/A
8911482	12/2013	Lee et al.	N/A	N/A
8926675	12/2014	Leung et al.	N/A	N/A
8940026	12/2014	Hilse et al.	N/A	N/A
8940028	12/2014	Austin et al.	N/A	N/A
8940029	12/2014	Leung et al.	N/A	N/A
8951291	12/2014	Impellizzeri	N/A	N/A
8968368	12/2014	Tepic	N/A	N/A
9011457	12/2014	Grady, Jr. et al.	N/A	N/A
9023052	12/2014	Lietz et al.	N/A	N/A
9050151	12/2014	Schilter	N/A	N/A
9072555	12/2014	Michel	N/A	N/A
9072557	12/2014	Fierlbeck et al.	N/A	N/A
9107678	12/2014	Murner et al.	N/A	N/A
9107711	12/2014	Hainard	N/A	N/A
9107713	12/2014	Horan et al.	N/A	N/A
9107718	12/2014	Isch	N/A	N/A
9113970	12/2014	Lewis et al.	N/A	N/A
9149310	12/2014	Fritzinger et al.	N/A	N/A
9161791	12/2014	Frigg	N/A	N/A
9161795	12/2014	Chasbrummel et al.	N/A	N/A

9168075	12/2014	Dell'Oca	N/A	N/A
9179950	12/2014	Zajac et al.	N/A	N/A
9179956	12/2014	Cerynik et al.	N/A	N/A
9180020	12/2014	Gause et al.	N/A	N/A
9211151	12/2014	Weaver et al.	N/A	N/A
9259217	12/2015	Fritzinger et al.	N/A	N/A
9259255	12/2015	Lewis et al.	N/A	N/A
9271769	12/2015	Batsch et al.	N/A	N/A
9283010	12/2015	Medoff et al.	N/A	N/A
9295506	12/2015	Raven, III et al.	N/A	N/A
9314284	12/2015	Chan et al.	N/A	N/A
9320554	12/2015	Greenberg et al.	N/A	N/A
9322562	12/2015	Takayama	N/A	N/A
9370388	12/2015	Globerman et al.	N/A	N/A
9433407	12/2015	Fritzinger et al.	N/A	N/A
9433452	12/2015	Weiner et al.	N/A	N/A
9468479	12/2015	Marotta et al.	N/A	N/A
9480512	12/2015	Orbay	N/A	N/A
9486262	12/2015	Andermahr et al.	N/A	N/A
9492213	12/2015	Orbay	N/A	N/A
9510878	12/2015	Nanavati et al.	N/A	N/A
9510880	12/2015	Terrill et al.	N/A	N/A
9526543	12/2015	Castaneda et al.	N/A	N/A
9545277	12/2016	Wolf et al.	N/A	N/A
9549819	12/2016	Bravo et al.	N/A	N/A
9566097	12/2016	Fierlbeck et al.	N/A	N/A
9622799	12/2016	Orbay et al.	N/A	N/A
9636157	12/2016	Medoff	N/A	N/A
9649141	12/2016	Raven, III et al.	N/A	N/A
9668794	12/2016	Kuster et al.	N/A	N/A
9801670	12/2016	Hashmi et al.	N/A	N/A
11096730	12/2020	Tiongson et al.	N/A	N/A
2002/0045901	12/2001	Wagner et al.	N/A	N/A
2003/0040752	12/2002	Kitchens	N/A	N/A
2004/0097937	12/2003	Pike et al.	N/A	N/A
2005/0049594	12/2004	Wack et al.	N/A	N/A
2005/0107796	12/2004	Gerlach et al.	N/A	N/A
2005/0131413	12/2004	O'Driscoll et al.	N/A	N/A
2005/0159753	12/2004	Kitchens	N/A	N/A
2005/0187551	12/2004	Orbay et al.	N/A	N/A
2006/0095044	12/2005	Grady, Jr.	606/96	A61B 17/1728
2006/0149265	12/2005	James et al.	N/A	N/A
2006/0241607	12/2005	Myerson et al.	N/A	N/A
2007/0162016	12/2006	Matityahu	N/A	N/A
2007/0173840	12/2006	Huebner	N/A	N/A
2007/0270849	12/2006	Orbay et al.	N/A	N/A
2007/0288022	12/2006	Lutz	N/A	N/A
2008/0021477	12/2007	Strnad et al.	N/A	N/A
2008/0195240	12/2007	Martin et al.	N/A	N/A
2008/0234749	12/2007	Forstein	N/A	N/A

2008/0275510	12/2007	Schonhardt et al.	N/A	N/A
2009/0024172	12/2008	Pizzicara	N/A	N/A
2009/0024173	12/2008	Reis, Jr.	N/A	N/A
2009/0118773	12/2008	James et al.	N/A	N/A
2009/0198285	12/2008	Raven, III	N/A	N/A
2009/0228010	12/2008	Gonzalez-Hernandez et al.	N/A	N/A
2009/0228047	12/2008	Derouet et al.	N/A	N/A
2009/0248084	12/2008	Hintermann	N/A	N/A
2009/0281543	12/2008	Orbay et al.	N/A	N/A
2009/0299369	12/2008	Orbay et al.	N/A	N/A
2009/0312760	12/2008	Forstein et al.	N/A	N/A
2010/0057086	12/2009	Price et al.	N/A	N/A
2010/0114097	12/2009	Siravo et al.	N/A	N/A
2010/0121326	12/2009	Woll et al.	N/A	N/A
2010/0137873	12/2009	Grady, Jr.	N/A	N/A
2010/0274247	12/2009	Grady, Jr. et al.	N/A	N/A
2011/0106086	12/2010	Laird	N/A	N/A
2011/0137314	12/2010	Kuster et al.	N/A	N/A
2011/0166573	12/2010	Wenk	606/71	A61B 17/1728
2011/0218580	12/2010	Schwager et al.	N/A	N/A
2012/0010667	12/2011	Eglseder	N/A	N/A
2012/0059424	12/2011	Epperly et al.	N/A	N/A
2012/0203227	12/2011	Martin	N/A	N/A
2012/0232599	12/2011	Schoenly et al.	N/A	N/A
2012/0323284	12/2011	Baker et al.	N/A	N/A
2013/0018426	12/2012	Tsai et al.	N/A	N/A
2013/0046347	12/2012	Cheng et al.	N/A	N/A
2013/0060291	12/2012	Petersheim	N/A	N/A
2013/0123841	12/2012	Lyon	N/A	N/A
2013/0138156	12/2012	Derouet	N/A	N/A
2013/0150902	12/2012	Leite	N/A	N/A
2013/0165981	12/2012	Clasbrummet et al.	N/A	N/A
2013/0211463	12/2012	Mizuno et al.	N/A	N/A
2013/0289630	12/2012	Fritzinger	N/A	N/A
2014/0005728	12/2013	Koay et al.	N/A	N/A
2014/0018862	12/2013	Koay et al.	N/A	N/A
2014/0031879	12/2013	Sixto, Jr. et al.	N/A	N/A
2014/0066998	12/2013	Martin	N/A	N/A
2014/0094856	12/2013	Sinha	N/A	N/A
2014/0121710	12/2013	Weaver et al.	N/A	N/A
2014/0180345	12/2013	Chan et al.	N/A	N/A
2014/0243901	12/2013	Mebarak et al.	N/A	N/A
2014/0277178	12/2013	O'Kane et al.	N/A	N/A
2014/0277181	12/2013	Garlock	N/A	N/A
2014/0316473	12/2013	Pfeffer	N/A	N/A
2014/0330320	12/2013	Wolter	N/A	N/A
2014/0378975	12/2013	Castaneda et al.	N/A	N/A
2015/0005831	12/2014	Sands	N/A	N/A
2015/0051650	12/2014	Verstreken et al.	N/A	N/A

2015/0051651	12/2014	Terrill et al.	N/A	N/A
2015/0073486	12/2014	Marotta et al.	N/A	N/A
2015/0105829	12/2014	Laird	N/A	N/A
2015/0112355	12/2014	Dahners et al.	N/A	N/A
2015/0134011	12/2014	Medoff	N/A	N/A
2015/0142065	12/2014	Schonhardt et al.	N/A	N/A
2015/0157337	12/2014	Wolf et al.	N/A	N/A
2015/0190185	12/2014	Koay et al.	N/A	N/A
2015/0209091	12/2014	Sixto, Jr. et al.	N/A	N/A
2015/0216571	12/2014	Impellizzeri	N/A	N/A
2015/0223824	12/2014	Mebarak	N/A	N/A
2015/0223852	12/2014	Lietz et al.	N/A	N/A
2015/0272638	12/2014	Langford	N/A	N/A
2015/0282851	12/2014	Michel	N/A	N/A
2015/0313653	12/2014	Ponce et al.	N/A	N/A
2015/0313654	12/2014	Horan et al.	N/A	N/A
2015/0327898	12/2014	Martin	N/A	N/A
2015/0351816	12/2014	Lewis et al.	N/A	N/A
2015/0374421	12/2014	Rocci et al.	N/A	N/A
2016/0022336	12/2015	Bateman	N/A	N/A
2016/0030035	12/2015	Zajac et al.	N/A	N/A
2016/0045237	12/2015	Cerynik et al.	N/A	N/A
2016/0045238	12/2015	Bohay et al.	N/A	N/A
2016/0074081	12/2015	Weaver et al.	N/A	N/A
2016/0166297	12/2015	Mighell et al.	N/A	N/A
2016/0166298	12/2015	Mighell et al.	N/A	N/A
2016/0183990	12/2015	Koizumi et al.	N/A	N/A
2016/0262814	12/2015	Wainscott	N/A	N/A
2016/0278828	12/2015	Ragghianti	N/A	N/A
2016/0310183	12/2015	Shaw et al.	N/A	N/A
2016/0310185	12/2015	Sixto et al.	N/A	N/A
2016/0324552	12/2015	Baker et al.	N/A	N/A
2016/0354122	12/2015	Montello et al.	N/A	N/A
2017/0035478	12/2016	Andermahr et al.	N/A	N/A
2017/0042592	12/2016	Kim	N/A	N/A
2017/0042596	12/2016	Mighell et al.	N/A	N/A
2017/0049493	12/2016	Gauneau et al.	N/A	N/A
2017/0065312	12/2016	Lauf et al.	N/A	N/A
2017/0105775	12/2016	Ricker et al.	N/A	N/A
2017/0215931	12/2016	Cremer et al.	N/A	N/A
2018/0289402	12/2017	Lueth et al.	N/A	N/A
2019/0076174	12/2018	Tiongson	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
2933020	12/2015	CA	N/A
201987653	12/2010	CN	N/A
202313691	12/2011	CN	N/A
202821574	12/2012	CN	N/A
202821575	12/2012	CN	N/A



203506858	12/2013	CN	N/A
203815563	12/2013	CN	N/A
105982727	12/2015	CN	N/A
1661525	12/2005	EP	N/A
2730244	12/2013	EP	N/A
2846870	12/2003	FR	N/A
2928259	12/2008	FR	N/A
2236010	12/1989	JP	N/A
2003210478	12/2002	JP	N/A
2008-518690	12/2007	JP	N/A
2009-513268	12/2008	JP	N/A
3177020	12/2011	JP	N/A
2016-539737	12/2015	JP	N/A
2020-11062	12/2019	JP	N/A
201316942	12/2012	TW	N/A
2007050796	12/2006	WO	N/A
2007109302	12/2006	WO	N/A
2016079504	12/2015	WO	N/A

---

*Primary Examiner:* Bates; David W

---

## **Background/Summary**

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/388,116, filed on Jul. 29, 2021, which is a division of U.S. patent Ser. No. 16/031,066 filed on Jul. 10, 2018, which is a continuation-in-part of U.S. patent application Ser. No. 15/925,846, filed Mar. 20, 2018, which is a continuation-in-part of U.S. patent application Ser. No. 15/703,345 filed Sep. 13, 2017, all of which are incorporated by reference herein in their entireties for all purposes.

### **FIELD OF THE INVENTION**

(1) The present disclosure relates to surgical devices, and more particularly, stabilization systems including plates, for example, for trauma applications.

### **BACKGROUND OF THE INVENTION**

(2) Bone fractures can be healed using plating systems. During treatment, one or more screws are placed on either side of a fracture, thereby causing compression and healing of the fracture. There is a need for improved plating systems as well as mechanisms for accurate use of the plating systems.

(3) Full open reduction and internal fixation (ORIF) of distal femur plates often requires an incision that would span much of the length of the femur, increasing the potential for excessive stripping of the soft tissue and/or periosteum and a higher chance of wound complications. Lateral distal femur plates are often inserted with an aiming guide assembly to assist in performing a minimally invasive (MIS) surgical approach. With an aiming guide, a surgeon can place and direct a plate through one small incision at the knee as well as target the location of shaft holes with small incisions up the femur. However, there is a need for a guide system that provides an easy to use, distal connection with the plate.

### **SUMMARY OF THE INVENTION**

(4) In accordance with the application, in some embodiments, a system is provided for treating a fracture in a bone. The system comprises a bone plate configured to engage the bone, the bone

plate comprising a proximal portion, a shaft and a distal portion, wherein the proximal portion comprises a tapered tip, wherein the shaft comprises one or more holes, and wherein the distal portion comprises one or more distal holes and a posterior side and an anterior side, wherein the posterior side of the distal portion is raised relative to the anterior side of the distal portion. The system further comprises at least one fastener received through the one or more holes of the shaft and at least one fastener received through the one or more distal holes of the distal portion.

(5) In other embodiments, a system is provided for treating a fracture in a bone. The system comprises a bone plate configured to engage the bone, the bone plate comprising a proximal portion, a shaft and a distal portion, wherein the proximal portion comprises a tapered tip, wherein the shaft comprises one or more holes, and wherein the distal portion comprises one or more distal holes and a posterior side and an anterior side, wherein the one or more holes in the shaft are fixed holes while the one or more distal holes in the distal shaft are polyaxial locking holes. The system further includes at least one fastener received through the one or more holes of the shaft and at least one fastener received through the one or more distal holes of the distal portion.

(6) In yet another embodiment, a system for treating a fracture in a bone includes a bone plate configured to engage the bone, the bone plate extending along a longitudinal axis and comprising a proximal portion, a shaft, and a distal portion, the shaft comprises a plurality of holes (e.g., polyaxial holes), the plurality of holes include a first repeating pattern of holes and a second repeating pattern of holes, the first repeating pattern of holes having a first virtual line segment connecting center points of all of the first repeating pattern of holes, the second repeating pattern of holes having a second virtual line segment connecting center points of all of the second repeating pattern of holes, wherein the first virtual line segment and the second virtual line segment are parallel, and the first virtual line segment and the second virtual line segment are angled relative to the longitudinal axis, and the distal portion comprises a plurality of distal holes and a posterior side and an anterior side, wherein the posterior side of the distal portion is raised relative to the anterior side of the distal portion.

(7) According to yet another embodiment, a system for treating a fracture in a bone includes a bone plate configured to engage the bone, the bone plate extending along a longitudinal axis and comprising a proximal portion, a shaft, and a distal portion, the shaft comprises a plurality of holes (e.g., polyaxial holes), the plurality of holes include a first repeating pattern of holes and a second repeating pattern of holes, the first repeating pattern of holes having a first virtual line segment connecting center points of all of the first repeating pattern of holes, the second repeating pattern of holes having a second virtual line segment connecting center points of all of the second repeating pattern of holes, wherein the first virtual line segment and the second virtual line segment are parallel, and the first virtual line segment and the second virtual line segment are angled relative to the longitudinal axis, and wherein the first repeating pattern includes a first center hole and the second repeating pattern includes a second center hole, and the center point of the first and second center holes are aligned generally along the longitudinal axis of the plate.

(8) Also provided are kits including plates of varying shapes and sizes, bone anchors, fasteners, insertion tools, and components for installing the same.

(9) Also provided are aiming guide systems configured for connection to a bone plate. In at least one embodiment, the aiming guide system includes an aiming arm and a connection assembly. The aiming arm has a rigid body extending from a proximal end to a distal end with a plurality of aiming holes defined through the rigid body between the proximal end and the distal end thereof. The distal end defines an attachment slot through the body. The connection assembly is configured to engage an attachment screw hole of the bone plate and the attachment slot such that the aiming arm is fixed in position relative to the bone plate with each of the aiming holes aligned with a respective hole along the bone plate.

(10) In at least one embodiment, the aiming guide system includes an aiming arm and a connection assembly. The aiming arm has a rigid body extending from a proximal end to a distal end with a

plurality of aiming holes defined through the rigid body between the proximal end and the distal end thereof. The distal end defines an attachment slot through the body. The connection assembly is configured to engage an attachment screw hole of the bone plate and the attachment slot such that the aiming arm is fixed in position relative to the bone plate with each of the aiming holes aligned with a respective hole along the bone plate. The connection assembly includes an attachment post having a first end with an orienting boss extending from a mating surface. The orienting boss is configured to be received in the attachment slot such that the aiming arm rests on the mating surface and is maintained in a proper orientation. A second end of the attachment post has an attachment block having a distal surface which defines a plurality of ball end pins. Each ball end pin is configured to be received in a respective indentation on the plate surface about the attachment screw hole. A threaded shaft extends through a through bore of the attachment post with threads of at least one end of the shaft body configured to threadably engage the attachment screw hole. A fastener is configured to threadably engage threads on an opposite end of the threaded shaft to secure the attachment post between the aiming arm and bone plate.

(11) Also provided is a method of connecting an aiming guide arm to a bone plate wherein the aiming guide arm has a rigid body extending from a proximal end to a distal end with a plurality of aiming holes defined through the rigid body between the proximal end and the distal end thereof and the distal end defining an attachment slot through the body. The bone plate extends along a longitudinal axis and includes a proximal portion, a shaft, and a distal portion, the bone plate defining a plurality of first screw holes along shaft, a plurality of second screw holes at the distal portion, an attachment screw hole proximate the distal portion and a plurality of indentations about the attachment screw hole. The method includes threadably engaging a first end of a threaded shaft in the attachment screw hole such that the threaded shaft extends from the bone plate at an oblique angle; sliding an attachment post over the threaded shaft such that ball end pins extending from an attachment block on one end of the attachment post seat within the indentations on the bone plate, the opposite end of the attachment post having an orienting boss extending from a mating surface; positioning the aiming guide arm with the orienting boss extending through the attachment slot with a first surface of the aiming guide arm seated on the mating surface; and securing a fastener to the second end of the threaded shaft, the fastener engaging a second surface of the aiming guide body opposite the first surface to secure the aiming guide body relative to the bone plate in a fixed orientation.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A more complete understanding of the present invention, and the attendant advantages and features thereof, will be more readily understood by reference to the following detailed description when considered in conjunction with the accompanying drawings, wherein:
- (2) FIG. 1 is a view of a bone plate on bone in accordance with some embodiments of the present application.
- (3) FIG. 2 is an alternate view of the bone plate on bone in FIG. 1.
- (4) FIG. 3 is a top perspective view of a narrow bone plate in accordance with some embodiments of the present application.
- (5) FIG. 4 is a top perspective view of a broad bone plate in accordance with some embodiments of the present application.
- (6) FIG. 5 is a view of an alternative bone plate on bone in accordance with some embodiments of the present application.
- (7) FIG. 6 is a top view of a lengthened, narrow bone plate in accordance with some embodiments of the present application.

- (8) FIG. 7 is a top view of a lengthened, broad bone plate in accordance with some embodiments of the present application.
- (9) FIG. 8 is a top view of a medial plate in accordance with some embodiments of the present application.
- (10) FIG. 9 is a top perspective view of a representative plate including a twist up its shaft.
- (11) FIG. 10 is a cross-sectional view of a section of a representative plate showing an arced contour of an underside.
- (12) FIG. 11 is a cross-sectional view of a different section of a representative plate showing an arced contour of an underside.
- (13) FIG. 12 is a top perspective view of another embodiment of a narrow bone plate.
- (14) FIG. 13 is a top perspective view of another embodiment of a broad bone plate.
- (15) FIG. 14 is a close-up view of the geometry of the broad bone plate of FIG. 13.
- (16) FIG. 15 is a top view of another embodiment of a narrow bone plate.
- (17) FIG. 16 is a top view of another embodiment of a broad bone plate.
- (18) FIG. 17 is a perspective view of another embodiment of a medial locking plate.
- (19) FIG. 18 is a perspective view of the epicondylar ridge on the end of a femur.
- (20) FIG. 19 illustrates the distal portion of the medial plate shown in FIG. 17.
- (21) FIG. 20 is a side view of a portion of the medial plate shown in FIG. 17.
- (22) FIG. 21 is a perspective view of an aiming guide system in accordance with an embodiment of the disclosure shown attached to an illustrative bone plate.
- (23) FIG. 22 is a perspective view of the aiming arm of the aiming guide system of FIG. 21.
- (24) FIGS. 23 and 24 are cross-sectional views of aiming holes of narrow and broad aiming arms, respectively.
- (25) FIG. 25 is a perspective view of an illustrative threaded shaft of the connecting assembly of the aiming guide system of FIG. 21.
- (26) FIG. 26 is a perspective view of an illustrative attachment post of the connecting assembly of the aiming guide system of FIG. 21.
- (27) FIG. 27 is a top plan view illustrating an alternative embodiment of the attachment slot and orienting boss.
- (28) FIG. 28 is a perspective view of the distal attachment block of the attachment post of FIG. 26.
- (29) FIG. 29 is a side elevation view illustrating connection of the connecting assembly with the aiming arm.
- (30) FIG. 30 is a cross-sectional view illustrating the connecting assembly fully assembled between the aiming arm and the bone plate.
- (31) FIG. 31 is a perspective view of an aiming guide system in accordance with another embodiment of the disclosure shown attached to an illustrative bone plate.
- (32) FIG. 32 is a perspective view of the fixed axis fastener of the aiming guide system of FIG. 31.
- (33) FIG. 33 is a perspective view of an illustrative tissue protection sleeve according to an embodiment of the disclosure.
- (34) FIG. 34 is an expanded elevation view of the proximal portion of the tissue protection sleeve of FIG. 33 engaged within an aiming hole of the aiming arm.
- (35) FIG. 35 is a perspective view of an illustrative drill sleeve according to an embodiment of the disclosure.
- (36) FIG. 36 is a cross-sectional view of the distal portion of the drill sleeve of FIG. 35 extending into a bone plate hole.
- (37) FIG. 37 is a cross-sectional view of an illustrative hole marker engaged within an aiming hole of the aiming arm.

#### DETAILED DESCRIPTION OF THE INVENTION

(38) Embodiments of the present application are generally directed to devices, systems and methods for bone stabilization. In particular, embodiments are directed to bone plates that extend

across bone members to treat one or more fractures.

(39) The plates described herein may be adapted to contact one or more of a femur, a distal tibia, a proximal tibia, a proximal humerus, a distal humerus, a clavicle, a fibula, an ulna, a radius, bones of the foot, bones of the hand, or other suitable bone or bones. The bone plates may be curved, contoured, straight, or flat. The plates may have a head portion that is contoured to match a particular bone surface, such as a condylar region, metaphysis or diaphysis. In addition, the plates may have a shaft portion that is contoured to match a particular surface that flares out in the form of an L-shape, T-shape, Y-shape. The plates may be adapted to secure small or large bone fragments, single or multiple bone fragments, or otherwise secure one or more fractures. In particular, the systems may include a series of trauma plates and screws designed for the fixation of fractures and fragments in diaphyseal and metaphyseal bone. Different bone plates may be used to treat various types and locations of fractures.

(40) The bone plates may be comprised of titanium, stainless steel, cobalt chrome, carbon composite, plastic or polymer—such as polyetheretherketone (PEEK), polyethylene, ultra-high molecular weight polyethylene (UHMWPE), resorbable polylactic acid (PLA), polyglycolic acid (PGA), combinations or alloys of such materials or any other appropriate material that has sufficient strength to be secured to and hold bone, while also having sufficient biocompatibility to be implanted into a body. Similarly, the bone plates may receive one or more screws or fasteners may be comprised of titanium, cobalt chrome, cobalt-chrome-molybdenum, stainless steel, tungsten carbide, combinations or alloys of such materials or other appropriate biocompatible materials. Although the above list of materials includes many typical materials out of which bone plates and fasteners are made, it should be understood that bone plates and fasteners comprised of any appropriate material are contemplated.

(41) The bone plates described herein can include a combination of locking holes and non-locking holes, only locking holes, or only non-locking holes. Locking holes comprise one or more openings that accept one or more locking fasteners. The one or more openings can be partially or fully threaded, thread-forming, or otherwise configured to allow locking attachment of the fastener to the hole. In some embodiments, the holes comprise stacked or polyaxial locking holes, which can accept both locking and non-locking fasteners. In some embodiments, the locking fasteners include heads that are at least partially threaded. The locking fasteners can be monoaxial or polyaxial. One non-limiting example of a locking fastener (among others) is shown in FIG. 6 of U.S. Ser. No. 15/405,368, filed Jan. 13, 2017, which is (along with any subsequent publication of the same application) hereby incorporated by reference in its entirety.

(42) Non-locking holes comprise one or more openings for accepting one or more non-locking fasteners. The one or more openings are at least in part non-threaded. In some embodiments, these openings include non-threaded or stacked openings, which can accept both locking and non-locking fasteners. In some embodiments, the holes comprise stacked or polyaxial locking holes, which can accept both locking and non-locking fasteners. The non-locking fasteners can be monoaxial or polyaxial. One non-limiting example of a non-locking fastener (among others) is shown in FIG. 4 of U.S. Ser. No. 15/405,368, filed Jan. 13, 2017, which is (along with any subsequent publication of the same application) hereby incorporated by reference in its entirety. In some embodiments, the non-locking fasteners can include dynamic compression screws, which enable dynamic compression of an underlying bone.

(43) In some embodiments, one or more of the plates described below include both locking and non-locking holes. Locking holes and locking fasteners may be useful for patients that have weaker bone. In addition, these may be helpful to prevent screw backout. Non-locking plates may be useful for patients that have strong bone.

(44) In some embodiments, one or more of the plates described below can comprise improved distal femoral plates. These plates can be used by a surgeon as an internal fixation device for a variety of fracture patterns in the condylar region of the distal femur. Typical indications can

include buttressing of comminuted/multi-fragmentary fractures, metaphyseal and supracondylar fractures, intra-articular and extra-articular femur fractures, periprosthetic fractures, fractures in osteopenic bone, osteotomies of the femur, and nonunions and malunions.

(45) The one or more plates can provide a number of advantages, as will be discussed further below. In particular, the plates are designed to better accommodate anatomical features. For example, one or more plates can include a raised posterior sideline that accommodates an epicondylar protuberance. In addition, the plates have various holes or openings for receiving various types of screws or fasteners, such as one or more kickstand screws, fixed screws, and/or polyaxial screws, that provide excellent fixation while minimizing the risk of various deformities.

(46) FIG. 1 is a view of a bone plate on bone in accordance with some embodiments of the present application. The bone plate **100** comprises a distal femur plate that is attached to a femur bone **5**. The femur bone **5** comprises a distal condylar region **7** and a shaft **17** having a lateral side **11** and a medial side **13**. The condylar region **7** includes a pair of medial and lateral condyles and a pair of medial and lateral epicondyles **9** positioned near the posterior edge of the condyles.

(47) The bone plate **100** comprises a distal femur plate that comprises a proximal portion **102** and a distal portion **104**. The proximal portion **102** comprises a tapered insertion end that transitions into a shaft **110**. The distal end of the shaft **110** flares out into a wider portion that forms the head or distal portion **104** of the bone plate **100**. While the proximal portion **102** and shaft **110** of the bone plate **100** reside along the shaft **17** of the femur, the head or distal portion **104** of the bone plate **100** resides along the condylar region **7** of the femur.

(48) The proximal portion **102** and shaft **110** of the bone plate **100** are configured to receive one or more screws or fasteners **50**. Likewise, the distal portion **104** of the bone plate **100** is configured to receive one or more screws or fasteners **52**. In some embodiments, the fasteners **50** on the proximal portion **102** and shaft **110** of the bone plate **100** comprise fixed angle fasteners, while the fasteners **52** on the distal portion **104** of the bone plate **100** comprise polyaxial fasteners. It has been found that while fixed angle fasteners are often stronger than polyaxial fasteners and provide greater stiffness to a bone plate attached to bone, at times, bone plate stiffness can be too great, thereby impeding proper bone healing. Accordingly, the present application provides a novel bone plate **100** that can accommodate both fixed angle fasteners **50** and polyaxial fasteners **52**, thereby providing a balance between adequate stiffness and proper healing. In other embodiments, the bone plate **100** can receive only fixed angle fasteners, thereby providing a bone plate of increased stiffness. In other embodiments, the bone plate **100** can receive only variable angle fasteners, thereby providing a bone plate of less stiffness. Moreover, polyaxial locking holes provide an opportunity to place a fastener at a variety of different angles relative to the bone plate, permitting the avoidance of other fasteners and/or implants that may already be in the bone. Therefore, the polyaxial locking holes provide more options for a surgical user. FIG. 2 is an alternate view of the bone plate on bone in FIG. 1. From this view, one can see the bone plate **100** and its fasteners **50**, **52** through the femur **5**. As noted above, in some embodiments, fasteners **50** comprise fixed fasteners that enter through the shaft **17** of the femur **5**. These fasteners **50** are shorter relative to fasteners **52** and provide increased stiffness. In some embodiments, fasteners **52** comprise variable angle fasteners that enter through the condylar region **7** of the femur **5**. These fasteners **52** are longer relative to fasteners **50**. While these fasteners **52** can provide decreased stiffness relative to the other fasteners **50**, they also have more variability in their angle of placement relative to one another and the bone plate to provide more options for a surgical user.

(49) FIG. 3 is a top perspective view of the narrow bone plate in accordance with some embodiments of the present application. The bone plate **100** comprises a proximal portion **102** and a distal portion **104**. In between the proximal portion **102** and distal portion **104** is a shaft **110** having an anterior sidewall **106** and a posterior sidewall **108**. Along the length of the bone plate **100** are a series of holes or openings for receiving screws or fasteners therein.

(50) The proximal portion **102** of the bone plate **100** comprises a tapered tip **120**. In some

embodiments, the tapered tip **120** serves as the lead portion of the bone plate **100** to enter into an incision. In some embodiments, the tapered tip **120** allows for simplified submuscular plate insertion to minimize incision length. The proximal portion **102** further comprises a k-wire hole **122** for receiving a k-wire therein to guide bone plate **100** to a desired surgical site. The k-wire hole **122** allows for temporary fixation of the bone plate **100** to bone via a k-wire. In some embodiments, the k-wire hole **122** is unthreaded. In addition, the proximal portion **102** further comprises an articulated tensioning device (ATD) slot **124**. The ATD slot **124** is configured to receive a portion of a tension or compression device (not shown) that can help to bring bone fragments together for healing. In some embodiments, the ATD slot **124** is composed of a through hole and a cylindrical shaped undercut on the bottom of the plate **100**.

(51) The proximal portion **102** transitions into the shaft portion **110**. The shaft portion **110** comprises multiple holes or openings **130a**, **130b**, **130c**, **130d**, **130e**, **130f** that are configured to receive fasteners therein. In some embodiments, holes **130a-130f** are configured to be fixed angle, stacked locking holes that can accommodate screws (e.g., between 3.5-7.5 mm screws, such as 4.5 mm screws). The fixed angle, stacked locking holes advantageously allow for mono-axial insertion of fasteners that lock to the bone plate **100**. In some embodiments, these holes can also accommodate non-locking fasteners. In some embodiments, the holes **130a-130f** are arranged in series such that no two holes **130a-130f** overlap along a width of the shaft portion **110**.

(52) In addition, the shaft portion **110** comprises one or more bi-directional dynamic compression slots **132a**, **132b** interspersed between the holes **130a-130f**. The slots **132a**, **132b** are elongated in length relative to the holes **130a-130f**, and are configured to receive one or more non-locking fasteners therein. While the present embodiment illustrates two dynamic compression slots **132a**, **132b**, in some embodiments, there can be three or more compression slots. In some embodiments, the dynamic compression slots **132a**, **132b** allow for static insertion of non-locking screws into the shaft portion **110** of the bone. In some embodiments, they also allow for compression (e.g., between 0.5-2 mm, such as 1 mm, of compression) along the shaft portion **110** of the bone through eccentric insertion of a non-locking screw. In some embodiments, the locations of the dynamic compression slots **132a**, **132b** are optimized for typical intercondylar splits and osteotomies.

(53) In addition to the holes **130a-130f** and the compression slots **132a**, **132b**, the shaft **110** further comprises a kickstand hole **135**. In some embodiments, the kickstand hole **135** comprises a polyaxial locking hole for receiving a locking fastener therein. The kickstand hole **135** is advantageously designed to receive a fastener that targets the strong cortical bone in the posteromedial cortex of the condylar region, thereby promoting angular stability. Additionally, the kickstand hole is useful for providing enhanced fixation for comminuted fractures in the metaphyseal region of the bone, due to its oblique angle relative to the upper surface of the plate. In some embodiments, the kickstand hole **135** is angled between 23-33 degrees, or in some embodiments between 27-29 degrees, upwards from a normal plane of the upper surface of the plate.

(54) The shaft portion **110** comprises an anterior side **106** and a posterior side **108** that form the edges of the shaft portion **110**. The anterior side **106** and posterior side **108** can include one or more waisted edge scallops **136**. Advantageously, the one or more waisted edge scallops **136** permit some bending of the shaft portion **110** without deforming the holes, thereby promoting uniform load transfer. In some embodiments, the shaft portion **110** can have a pre-contoured geometry. Advantageously, the pre-contoured geometry can allow an optimal fit along an entire lateral aspect of a femur. In lengthier versions of the plate **100**, there can be an anterior bow and slight shaft twist to mate with proximal femoral anatomy. In addition, in some embodiments, the underside of the bone plate **100** can be arced to mate with the cylindrical nature of the femoral shaft.

(55) The distal end of the shaft portion **110** transitions into the wider, distal portion **104** of the bone plate **100**. The distal portion **104** of the bone plate **100** is configured to reside at or near the condylar region of the femur **5**. The distal portion **104** comprises holes or openings **140a**, **140b**,

**140c, 140d, 140e, 140f, 140g, 140h** that are configured to receive one or more fasteners or screws therein. In some embodiments, the holes **140a-140h** comprise polyaxial locking holes that can accommodate screws (e.g., between 3.5-7.5 mm screws, such as 4.5 mm screws). The locking holes may be thread-forming such that a thread is formed within the locking hole as the fastener is inserted therein. In some embodiments, the polyaxial locking holes **140a-140h** can have a cone of angulation of up to between 30 to 50 degrees, and more particularly 40 degrees, according to some embodiments. The polyaxial locking holes **140a-140h** thus accommodate fasteners of different angles. Advantageously, in some embodiments, the polyaxial locking holes are designed to accommodate multi-planar diverging trajectories to allow a surgeon to select optimal screw trajectories to avoid any existing hardware in the condylar region. In other words, fasteners inserted into the condylar region will avoid other similarly inserted fasteners or other pre-existing hardware that may have been inserted previously in the region. While the present embodiment includes eight polyaxial holes **140a-140h**, one skilled in the art will appreciate that the bone plate **100** can include less than eight polyaxial holes or greater than eight polyaxial holes. Furthermore, as the bone plate **100** can include both fixed angle fasteners (e.g., in the shaft **110** of the bone plate **100**) and polyaxial fasteners (e.g., in the distal portion **104** of the bone plate **100**), the bone plate **100** can be provided relative to an underlying with just enough stiffness to accommodate adequate healing.

(56) In some embodiments, the holes **140a-140h** can include one or more holes that are nominally angled so that they are parallel to a knee joint. These holes can receive one or more fasteners or screws that are parallel to the knee joint, thereby helping in proper alignment of the bone plate **100** relative to bone. In the present embodiment, holes **140b, 140d, 140e** can be parallel to a knee joint and can be considered to be condylar realignment holes. Advantageously, these condylar realignment holes can help to restore the anatomic alignment of the articular block to prevent varus/valgus deformities and post-traumatic arthritis. In other words, holes **140b, 140d, 140e** (which are a subset of the polyaxial holes **140a-140h**) can help guide one or more fasteners therethrough that are parallel to the knee joint, thereby helping to ensure proper alignment between the bone plate and underlying bone. By providing proper alignment, this advantageously helps to prevent varus/valgus deformities and post-traumatic arthritis. One skilled in the art will appreciate that while holes **140b, 140d, 140e** can be formed as condylar realignment holes, other holes in the distal end can also be used for similar purposes.

(57) In addition to the holes **140a-140h**, the distal portion **104** of the plate **100** further comprises a distal pair of k-wire holes **142**. Like the proximal k-wire hole **122**, the k-wire holes **142** allow temporary fixation of the bone plate **100** to bone with k-wires.

(58) In addition to the holes **140a-140h** and k-wire holes **142**, the distal portion **104** of the plate **100** further comprises three indentations **144**. In some embodiments, the indentations **144** are rounded or spherical. The purpose of the indentations **144** is to help accommodate a portion of an instrument (e.g., an attachment post of an associated aiming instrument, for example, as described with reference to FIGS. 21-34). The instrument can be used to accurately guide fasteners or screws into respective holes in the bone plate **100**. The instrument can rest against one or more of the indentations **144**, thereby ensuring proper alignment and orientation between the instrument and the plate **100**. Unlike the holes **140a-140h** and k-wire holes **142**, the indentations **144** do not extend through the upper surface to the lower surface of the bone plate **100**. Rather, they are formed partially along the height of the bone plate **100**.

(59) The distal portion **104** of the plate **100** can have a distinct contour. In particular, the distal portion **104** of the plate **100** can comprise a concave cutout or lag screw groove **148**. Screws or fasteners can sometimes be placed externally to the bone plate **100** to lag fragments of the articular block prior to plate placement. The lag screw groove **148** advantageously accommodates and/or permits placement of these external lag/compression screws.

(60) In some embodiments, the distal portion **104** of the plate **100** further comprises a variable chamfered surface **149**. The variable chamfered surface **149** advantageously has different amounts



of material removed from a top surface of the bone plate **100** at the distal end, thereby permitting a thinner surface in an area where soft tissue cover is minimal. This desirably helps to prevent irritation around the knee region.

(61) In some embodiments, the distal portion **104** of the bone plate **100** further comprises an anterior side and a posterior side, wherein the posterior side has a raised contour relative to the anterior side in a vertical direction along the height of the bone plate **100**. As shown in FIG. 3, the bone plate **100** comprises a raised posterior side **146** that can be between 2-10 mm higher than an anterior side. In some embodiments, the raised posterior side **146** has an underside that is between 2-10 mm higher than an underside of an opposing anterior side of the bone plate **100**. The purpose of the raised posterior side **146** is that it advantageously accommodates an anatomical ridge on the posterior side of the femoral condyle known as the epicondyle. The raised posterior side **146** is advantageously designed to reside or sit on the epicondyle, thereby providing a mechanism by which a surgeon can key the bone plate **100** into place on the condylar surface. Furthermore, the raised posterior side **146** helps to stabilize the bone plate **100** over a bone, which would likely be unsteady without the raised feature. In addition to the raised contour, the bone plate **100** also includes condylar contouring around its distal perimeter to mimic the metaphyseal and epiphyseal anatomy to guide plate placement.

(62) In some embodiments, the overall height or thickness of the bone plate **100** can be variable along its length. In some embodiments, the height or thickness of the bone plate **100** can be greater in the shaft **110** than in the distal portion **104**. In some embodiments, the thickness in the shaft **110** can be between 3.0-6.0 mm, while the thickness in the distal portion **104** can be between 1.5-4.5 mm. The variable thickness advantageously provides ideal stiffness to the bone plate **100**, while also balancing the need to be careful around surrounding tissue around the bone plate. For example, a less thick distal portion **104** can help reduce unnecessary contact with adjacent tissue, thereby reducing irritation around a knee region.

(63) FIG. 4 is a top perspective view of a broad bone plate in accordance with some embodiments of the present application. The broad bone plate **200** includes many similar features as the narrower bone plate **100**, but is wider than the narrower bone plate **100**. In some embodiments, a distal portion **204** of the bone plate **200** can be between 7-11 mm, or approximately 9 mm, wider than the narrower bone plate **100**. This additional width permits space for additional (e.g., two or more) polyaxial locking holes **240**, as well as one or more k-wire holes **242**. In some embodiments, a shaft portion **210** of the bone plate **200** can be between 5.5-9.5 mm, or approximately 7.5 mm, wider than the narrower bone plate **100**. This additional width permits space for additional fixed angle, stacked locking holes **230**. In some embodiments, the additional width of the shaft **210** provides space for two, three or more locking holes **230** along its width.

(64) The bone plate **200** comprises a proximal portion **202** and a distal portion **204**. In between the proximal portion **202** and distal portion **204** is a shaft **210** having an anterior sidewall **206** and a posterior sidewall **208**. Along the length of the bone plate **200** are a series of holes or openings for receiving screws or fasteners therein.

(65) The proximal portion **202** of the bone plate **200** comprises a tapered tip **220**. In some embodiments, the tapered tip **220** serves as the lead portion of the bone plate **200** to enter into an incision. In some embodiments, the tapered tip **220** allows for simplified submuscular plate insertion to minimize incision length. The proximal portion **202** further comprises a k-wire hole **222** for receiving a k-wire therein to guide bone plate **200** to a desired surgical site. The k-wire hole **222** allows for temporary fixation of the bone plate **200** to bone via a k-wire. In some embodiments, the k-wire hole **222** is unthreaded. In addition, the proximal portion **202** further comprises an articulated tensioning device (ATD) slot **224**. The ATD slot **224** is configured to receive a portion of a tension or compression device (not shown) that can help to bring bone fragments together for healing. In some embodiments, the ATD slot **224** is composed of a through hole and a cylindrical shaped undercut on the bottom of the plate **200**.

(66) The proximal portion **202** transitions into the shaft portion **210**. The shaft portion **210** comprises multiple holes or openings **230a**, **230b**, **230c**, **230d**, **230e**, **230f**, **230g**, **230h**, **230i**, **230j** that are configured to receive fasteners therein. In some embodiments, holes **230a-230j** are configured to be fixed angle, stacked locking holes that can accommodate screws (e.g., between 3.5-7.5 mm screws, such as 4.5 mm screws). The fixed angle, stacked locking holes advantageously allow for mono-axial insertion of fasteners that lock to the bone plate **200**. In some embodiments, these holes can also accommodate non-locking fasteners. In some embodiments, the holes **230a-230j** are distributed such that no two holes **230a-230j** overlap along a width of the shaft portion **110**. However, one skilled in the art will appreciate that the shaft portion **210** is wide enough to accommodate two or more holes **230a-230j** side-by-side. In the present embodiment, the shaft includes distinct groups of three holes **230a-230j** side-by-side along the entire length of the plate.

(67) In addition, the shaft portion **210** comprises one or more bi-directional dynamic compression slots **232a**, **232b** interspersed between the holes **230a-230j**. The slots **232a**, **232b** are elongated in length relative to the holes **230a-230j**, and are configured to receive one or more non-locking fasteners therein. While the present embodiment illustrates two dynamic compression slots **232a**, **232b**, in some embodiments, there can be three or more compression slots. In some embodiments, the dynamic compression slots **232a**, **232b** allow for static insertion of non-locking screws into the shaft portion **210** of the bone. In some embodiments, they also allow for compression (e.g., between 0.5-2 mm, such as 1 mm, of compression) along the shaft portion **210** of the bone through eccentric insertion of a non-locking screw. In some embodiments, the locations of the dynamic compression slots **232a**, **232b** are optimized for typical intercondylar splits and osteotomies. In the present embodiments, each of the dynamic compression slots **232a**, **232b** is positioned adjacent to a pair of locking holes **230**.

(68) In addition to the holes **230a-230f** and the compression slots **232a**, **232b**, the shaft **210** further comprises a kickstand hole **235**. In some embodiments, the kickstand hole **235** comprises a polyaxial locking hole for receiving a locking fastener therein. The kickstand hole **235** is advantageously designed to receive a fastener that targets the strong cortical bone in the posteromedial cortex of the condylar region, thereby promoting angular stability. Additionally, the kickstand hole is useful for providing enhanced fixation for comminuted fractures in the metaphyseal region of the bone, due to its oblique angle relative to the upper surface of the plate.

(69) The shaft portion **210** comprises an anterior side **206** and a posterior side **208** that form the edges of the shaft portion **210**. The anterior side **206** and posterior side **208** can include one or more waisted edge scallops **236**. Advantageously, the one or more waisted edge scallops **236** permit some bending of the shaft portion **210** without deforming the holes, thereby promoting uniform load transfer. The waisted edge scallops **236** are slightly larger than the waisted edge scallops **136** to take into account the wider shaft. In some embodiments, the shaft portion **210** can have a pre-contoured geometry. Advantageously, the pre-contoured geometry can allow an optimal fit along an entire lateral aspect of a femur. In lengthier versions of the plate **200**, there can be an anterior bow and slight shaft twist to mate with proximal femoral anatomy. In addition, in some embodiments, the underside of the bone plate **200** can be arced to mate with the cylindrical nature of the femoral shaft.

(70) The distal end of the shaft portion **210** transitions into the wider, distal portion **204** of the bone plate **200**. The distal portion **204** of the bone plate **200** is configured to reside at or near the condylar region of the femur **5**. The distal portion **204** comprises holes or openings **240a**, **240b**, **240c**, **240d**, **240e**, **240f**, **240g**, **240h**, **240i**, **240j** that are configured to receive one or more fasteners or screws therein. In some embodiments, the holes **240a-240j** comprise polyaxial locking holes that can accommodate screws (e.g., between 3.5-7.5 mm screws, such as 4.5 mm screws). In some embodiments, the polyaxial locking holes **240a-240j** can have a cone of angulation of up to between 30 to 50 degrees, and more particularly 40 degrees, according to some embodiments. The

polyaxial locking holes **240a-240j** thus accommodate fasteners of different angles. Advantageously, in some embodiments, the polyaxial locking holes are designed to accommodate several multi-planar diverging trajectories to allow a surgeon to select optimal screw trajectories to avoid any existing hardware in the condylar region. In other words, fasteners inserted into the condylar region will avoid other similarly inserted fasteners or other pre-existing hardware that may have been inserted previously in the region. While the present embodiment includes ten polyaxial holes **240a-240j**, one skilled in the art will appreciate that the bone plate **200** can include less than ten polyaxial holes or greater than ten polyaxial holes. Furthermore, as the bone plate **200** can include both fixed angle fasteners (e.g., in the shaft **210** of the bone plate **200**) and polyaxial fasteners (e.g., in the distal portion **204** of the bone plate **200**), the bone plate **200** can be provided relative to an underlying with just enough stiffness to accommodate adequate healing.

(71) In some embodiments, the holes **240a-240j** can include one or more holes that are nominally angled so that they are parallel to a knee joint. These holes can receive one or more fasteners or screws that are parallel to the knee joint, thereby helping in proper alignment of the bone plate **200** relative to bone. In the present embodiment, holes **240b**, **240e**, **240f** can be parallel to a knee joint and can be considered to be condylar realignment holes. Advantageously, these condylar realignment holes can help to restore the anatomic alignment of the articular block to prevent varus/valgus deformities and post-traumatic arthritis. In other words, holes **240b**, **240e**, **240f** (which are a subset of the polyaxial holes **240a-240j**) can help guide one or more fasteners therethrough that are parallel to the knee joint, thereby helping to ensure proper alignment between the bone plate and underlying bone. By providing proper alignment, this advantageously helps to prevent varus/valgus deformities and post-traumatic arthritis. One skilled in the art will appreciate that while holes **240b**, **240e**, **240f** are considered condylar realignment holes, these are only representative, and other holes in the distal portion can also be considered condylar realignment holes.

(72) In addition to the holes **240a-240j**, the distal portion **204** of the plate **200** further comprises a distal pair of k-wire holes **242**. Like the proximal k-wire hole **222**, the k-wire holes **242** allow temporary fixation of the bone plate **200** to bone with k-wires.

(73) In addition to the holes **240a-240j** and k-wire holes **242**, the distal portion **204** of the plate **200** further comprises three indentations **244**. In some embodiments, the indentations **244** are rounded or spherical. The purpose of the indentations **244** is to help accommodate a portion of an instrument (e.g., an attachment post of an associated aiming instrument). The instrument can be used to accurately guide fasteners or screws into respective holes in the bone plate **200**. The instrument can rest against one or more of the indentations **244**, thereby ensuring proper alignment and orientation between the instrument and the plate **200**. Unlike the holes **240a-240j** and k-wire holes **242**, the indentations **244** do not extend through the upper surface to the lower surface of the bone plate **200**. Rather, they are formed partially along the height of the bone plate **200**.

(74) In some embodiments, the distal portion **204** of the plate **200** further comprises a variable chamfered surface **249**. The variable chamfered surface **249** advantageously has different amounts of material removed from a top surface of the bone plate **200** at the distal end, thereby permitting a thinner surface in an area where soft tissue cover is minimal. This desirably helps to prevent irritation around the knee region.

(75) In some embodiments, the distal portion **204** of the bone plate **200** further comprises an anterior side and a posterior side, wherein the posterior side has a raised contour relative to the anterior side. As shown in FIG. 4, the bone plate **200** comprises a raised posterior side **246** that can be between 2-10 mm higher than an anterior side. In some embodiments, the raised posterior side **246** has an underside that is between 2-10 mm higher than an underside of an opposing anterior side of the bone plate **200**. The purpose of the raised posterior side **246** is that it advantageously accommodates an anatomical ridge on the posterior side of the femoral condyle known as the epicondyle. The raised posterior side **246** is advantageously designed to reside or sit on the

epicondyle, thereby providing a mechanism by which a surgeon can key the bone plate **200** into place on the condylar surface. Furthermore, the raised posterior side **246** helps to stabilize the bone plate **200** over a bone, which would likely be unsteady without the raised feature. In addition to the raised contour, the bone plate **200** also includes condylar contouring around its distal perimeter to mimic the metaphyseal and epiphyseal anatomy to guide plate placement.

(76) FIG. **5** is a view of an alternative bone plate on bone in accordance with some embodiments of the present application. The bone plate **300** comprises a plate that is lengthier than the bone plates **100**, **200** in prior embodiments. The bone plate **300** is designed to extend along a majority of the length of a femur **5**. In some embodiments, as shown in FIG. **5**, the bone plate **300** extends from the distal condylar region **7** close to the proximal region **15** of the bone plate **300**. By spanning the extending length, the bone plate **300** may help heal and prevent fractures that are higher up the femur and near the proximal region **15**. Additionally, a lengthier bone plate can assist in providing a longer working length, which helps to modulate the stiffness of the plate and screw construct to promote faster healing.

(77) FIG. **6** is a top view of a lengthened, narrow bone plate in accordance with some embodiments of the present application. While the bone plate **300** has a number of similar features to bone plates **100**, **200**, the bone plate **300** is much longer. In some embodiments, the bone plate **300** has a length of between 400 and 500 mm, such as approximately 460 mm.

(78) The bone plate **300** can include three distinct regions, identified by the perforated lines. These regions include a proximal region **302**, a medial region **306** and a distal region **304**.

(79) The proximal region **302** comprises a tapered distal end that includes a tapered tip **320**, k-wire hole **322** and ATD slot **324**. In addition, the proximal region **302** comprises a series of proximal holes **328**. In some embodiments, these proximal holes **328** are polyaxial and nominally angled toward the outer edge of the bone plate **300** in order to assist in dodging a hip stem in the proximal femur. While the present embodiment shows ten proximal holes **328**, in other embodiments, the proximal region **302** includes less than ten or greater than ten proximal holes **328**. In addition, while the present embodiment shows ten proximal holes **328** that are similar to one another (e.g., polyaxial), in some embodiments, the proximal holes **328** can be a combination of monoaxial and polyaxial locking holes, or just monoaxial holes.

(80) The medial region **306** comprises a shaft region having a series of holes or openings for receiving fasteners or screws therein. As shown in FIG. **6**, some of the holes can be stacked holes **330** that can accept locking or non-locking screws, while some of the holes can be elongated dynamic compression slots **332** that can accept non-locking screws. In the present embodiments, the medial region **306** comprises twelve stacked holes **330** and two dynamic compression slots **332**. However, one skilled in the art will appreciate that in some embodiments, the medial region **306** can include less than or greater than twelve stacked holes **330** and two dynamic compression slots **332**.

(81) The distal region **304** of the bone plate **300** comprises a flared out, wider region that resides on a condylar region of bone. In some embodiments, the distal region **304** includes a pair of distal k-wire holes **342** for receiving guiding k-wires therein. The distal region **304** further includes three indentations **344** that are configured to engage a portion of an instrument (e.g., an alignment post of an aiming guide). The distal region **304** further includes a series of holes or openings for receiving one or more fasteners or screws therein. These include one kickstand hole **335** and eight polyaxial locking holes **340**, which are advantageously designed such that fasteners that are inserted therethrough do not interfere with one another. In addition to these features, the distal region **304** can further include a lag screw groove **348** and a raised posterior side **346** that can accommodate an epicondylar flare.

(82) As shown in FIG. **6**, the bone plate **300** comprises different types of holes in the three distinct regions—proximal region **302**, medial region **306** and distal region **304**. In some embodiments, the distal region **304**, which encompasses the condylar region, comprises polyaxial locking holes **328**.

In the medial region **306**, the polyaxial locking holes **328** can transition into non-polyaxial or fixed holes **330**. In some embodiments, the fixed holes **330** can be stacked holes. In the proximal region **302**, the fixed holes **330** can transition into polyaxial locking holes **340**.

(83) FIG. 7 is a top view of a lengthened, broad bone plate in accordance with some embodiments of the present application. Like the bone plate **300**, bone plate **400** has a number of similar features to bone plates **100**, **200**, but is much longer. In some embodiments, the bone plate **400** has a length of between 400 and 500 mm, such as approximately 460 mm. The bone plate **400** is also wider than the bone plate **300**, thereby accommodating a number of distinct hole patterns along its length.

(84) The bone plate **400** can include three distinct regions, identified by the perforated lines. These regions include a proximal region **402**, a medial region **406** and a distal region **404**. All three regions (**402**, **404**, and **406**) can contain groups of two or more holes side-by-side along the length of the plate. In the present embodiments, the shaft includes distinct groups of three holes side-by-side along the entire length of the plate.

(85) The proximal region **402** comprises a tapered distal end that includes a k-wire hole **422** and ATD slot **424**. In addition, the proximal region **402** comprises a series of proximal holes. In some embodiments, these proximal holes comprise polyaxial locking holes **428** that are nominally angled toward the outer edge of the bone plate **400** in order to assist in dodging a hip stem in the proximal femur. In between pairs of polyaxial locking holes **428** are stacked holes **426**. In some embodiments, both the polyaxial locking holes **428** and stacked holes **426** can receive locking or non-locking fasteners. In the present embodiment, the proximal region **402** comprises five sets of holes, whereby each set comprises a pair of polyaxial locking holes **428** and a stacked hole **426**.

(86) The medial region **406** comprises a shaft region having a series of holes or openings for receiving fasteners or screws therein. As shown in FIG. 7, some of the holes can be stacked holes **430** that can accept locking or non-locking screws, while some of the holes can be elongated dynamic compression slots **432** that can accept non-locking screws. In the present embodiments, the medial region **406** comprises seven sets of holes, whereby each set comprises two or more stacked holes **430**. In some of the sets, at least one dynamic compression slot **432** is provided between the two or more stacked holes.

(87) The distal region **404** of the bone plate **400** comprises a flared out, wider region that resides on a condylar region of bone. In some embodiments, the distal region **404** includes a pair of distal k-wire holes **442** for receiving guiding k-wires therein. The distal region **404** further includes three indentations **444** that are configured to engage a portion of an instrument (e.g., an alignment post of an aiming guide). The distal region **404** further includes a series of holes or openings for receiving one or more fasteners or screws therein. These include one kickstand hole **435** and ten polyaxial locking holes **440**, which are advantageously designed such that fasteners that are inserted therethrough do not interfere with one another. In addition to these features, the distal region **404** can further include a raised posterior side **446** that can accommodate an epicondylar flare.

(88) FIG. 8 is a top view of a medial plate in accordance with some embodiments of the present application. The medial plate **500** is inserted through an incision over the anteromedial of the distal femur or an S-shaped incision on the posterior side of the knee joint. The medial plate **500** includes similar features as the narrow and broad locking plates **100**, **200**. In some embodiments, the longest length of the medial plate will sit no less than 8 cm below the lesser trochanter in order to preserve the vessels and nerve pathways on the medial side of the femur. In some embodiments, the thickness of the plate **500** varies along a length of the plate **500**. For example, the plate **500** can be thicker in a proximal region (e.g., between 2.0-4.0 mm, such as approximately 3.0 mm) than in a distal region (e.g., between 1.5-3.0 mm, such as approximately 2.25 mm).

(89) The medial plate **500** comprises a proximal portion **502** and a distal portion **504** and a shaft **510** therebetween **510**. The proximal portion **502** comprises a tapered insertion tip **520**. Along the proximal portion **502** and shaft **510** are a series of holes **530** for receiving fasteners therein. In some embodiments, the holes **530** are polyaxial locking holes. In other embodiments, the holes **530**

are fixed angled stacked locking holes. In some embodiments, the holes **530** are a combination of polyaxial locking holes or fixed angle stacked locking holes. In some embodiments, the holes **530** accommodate screws of various sizes, such as between 3.5-7.5 mm screws, such as approximately 4.5 mm. The shaft **510** further includes waisted edge scallops **536**.

(90) The distal portion **504** of the medial plate **500** comprises similar features as in prior embodiments, including a pair of distal k-wire holes **542** and six polyaxial locking holes **540**. The polyaxial locking holes **540** can accommodate fasteners or screws that are between 3.0 and 6.0 mm, or approximately 4.5 mm. Furthermore, the distal portion **504** comprises a raised posterior side **546** to accommodate an epicondylar flare, as well as condylar contouring **506** to accommodate distinct anatomy. In some embodiments, the distal portion **504** also comprises a variable chamfered surface **549**.

(91) FIG. **9** is a top perspective view of a representative plate including a twist up its shaft. From this view, one can see how the proximal portion of the representative shaft **300** can have an upward twist from a more medial section of the plate. The advantage of the upward twist is that the plate is a better anatomical fit with bone.

(92) FIG. **10** is a cross-sectional view of a section of a representative plate showing an arced contour of an underside. FIG. **11** is a cross-sectional view of a different section of a representative plate showing an arced contour of an underside. From these views, one can see how the arced surface varies in radius and centrality along the length of the plate. For example, the underside in FIG. **10** has a radius of R1, while the underside in FIG. **11** has a radius of R2, wherein R1 is different from R2. By having different arced contours along different sections of the plate, this also helps to give the plate a better anatomical fit to bone. In some embodiments, R1 and R2 can have a dimension between about 25 mm to 250 mm, whereby R1 is different from R2.

(93) Turning now to FIG. **12**, a top perspective view of a narrow bone plate **600** according to yet another embodiment is shown. The narrow bone plate **600** is similar to narrow bone plate **100** shown in FIG. **3** and like elements are labeled the same. Similar to plate **100**, bone plate **600** comprises proximal portion **102** and distal portion **104** with shaft **110** extending therebetween having anterior sidewall **106** and posterior sidewall **108**.

(94) Similar to holes or openings **130a-130f** in plate **100**, plate **600** includes a plurality of holes or openings **130a-130g** that are configured to receive fasteners therein. In some embodiments, holes **130a-130g** may be configured as locking holes, which may be able to accept locking or non-locking screws. The openings **130a-130g** may be in the form of 4.5 mm polyaxial locking holes. The openings **130a-130g** may be staggered to prevent new linear fracture lines in the metaphyseal and diaphyseal regions.

(95) Similar to plate **100**, the shaft portion **110** of plate **600** comprises one or more bi-directional dynamic compression slots **132a**, **132b**. These slots **132a**, **132b** may be configured to receive one or more non-locking fasteners therein and may allow for compression along the shaft portion **110** of the bone. The bi-directional dynamic compression slots **132a**, **132b** may allow for static insertion of non-locking screws into the shaft of the bone and/or may allow for 1 mm of compression along the shaft of the bone through eccentric insertion of a non-locking screw. The locations of the dynamic compression slots **132a**, **132b** were optimized for typical intercondylar splits and osteotomies.

(96) The articulated tensioning device (ATD) hole **124** is composed of a through hole in the tip of the plate **600** and a cylindrical shaped undercut on the bottom surface of the plate **600**. The hole mates with an ATD and allows for compression or tensioning of fracture fragments.

(97) Plate **600** further includes a plurality of kickstand holes **135**. For example, in this embodiment, the shaft portion **110** may include two kickstand holes **135** separated from one another and oriented in different directions. The kickstand holes **135** may each comprise a polyaxial locking hole for receiving a locking fastener therein. In the metaphyseal region of the lateral plates, the two kickstand strut screws permit fixation in the anteromedial and posteromedial cortices of the medial

femoral condyle in the lateral plates. The screw targets the strong cortical bone of the posteromedial cortex in order to enhance screw fixation, prevent pull-out, and promote angular stability via triangular fixation.

(98) The anterior side **106** and posterior side **108** can include one or more waisted edge scallops **136**. Advantageously, the one or more waisted edge scallops **136** permit some bending of the shaft portion **110** without deforming the holes, thereby promoting uniform load transfer.

(99) The distal end of the shaft portion **110** transitions into the wider, distal portion **104** of the bone plate **600**. Similar to plate **100**, plate **600** includes holes or openings **140a-140h** that are configured to receive one or more fasteners or screws therein, including locking or non-locking screws. The holes **140a-140h** may comprise polyaxial locking holes, for example, with a cone of angulation. The cluster of holes **140a-140h** may be nominally targeted in several multi-planar diverging trajectories to allow the surgeon to select optimal screw trajectories to avoid any existing hardware in the condyle.

(100) The distal portion **104** of the plate **600** may further comprises a distal pair of k-wire holes **142**. Like the proximal k-wire hole **122**, the k-wire holes **142** allow temporary fixation of the bone plate **600** to bone with k-wires.

(101) The distal portion **104** of the plate **600** may include three indentations **144**, for example, or blind openings being rounded or spherical, to help accommodate a portion of an instrument (e.g., an attachment post of an associated aiming instrument).

(102) In this embodiment, plate **600** further includes a dedicated aiming arm attachment hole **602**. The dedicated aiming arm attachment hole **602** may be a threaded hole, for example, for attaching the attachment post of an associated aiming instrumentation for the system.

(103) The thickness of the plate **600** may vary from about 4.5 mm proximally to 3.6 mm distally, varying through the metaphyseal and epiphyseal regions. The transition in thickness may begin about 129 mm from the most distal edge of the plate **600**. The width of the plate **600** may vary from about 33 mm wide in the head of the plate **600** to about 17.5 mm wide in the shaft of the plate **600**. The transition in width may also begin about 129 mm from the most distal edge of the plate **600**.

(104) Turning now to FIGS. **13** and **14**, a broad lateral bone plate **700** according to yet another embodiment is shown. The broad lateral bone plate **700** is similar to broad bone plate **200** shown in FIG. **4** and like elements are labeled the same. Similar to plate **200**, bone plate **700** comprises proximal portion **202** and distal portion **204** with shaft **210** extending therebetween having anterior sidewall **206** and posterior sidewall **208**. The broad lateral locking plate **700** may be inserted through an incision over the lateral aspect of the distal femur and may provide some of the same types of features as the narrow version **600**.

(105) The shaft portion **210** comprises a plurality of holes or openings **230a, 230a1, 230b, 230c, 230d, 230e, 230f, 230g, 230h, 230i, 230i1, 230j, 230k, 230l** that are configured to receive fasteners therein. As compared to plate **200**, plate **700** replaces dynamic compression slots **232a, 232b** with openings **230a1** and **230i1** and additional openings **230K** and **230l** are added. The plurality of openings **230a-230l** may be 4.5 mm polyaxial locking holes in the distal cluster that may be nominally targeted in several multi-planar diverging trajectories to allow the surgeon to select optimal screw trajectories to avoid any existing hardware in the condyle. The plurality of openings **230a-230l** may accept locking or non-locking screws. The plurality of openings **230a-230l** in the shaft **210** of the plate **700** may be staggered to prevent new linear fracture lines in the metaphyseal and diaphyseal regions. In particular, the plurality of openings **230a-230l** may be a repeating pattern of three holes (e.g., **230a, 230a1, 230b**).

(106) As best seen in FIG. **14**, a first virtual line segment **L1** connecting a repeating pattern of three holes (e.g., **230c-230e**) through their respective center points may be angled relative to the longitudinal axis **A** of the plate **700**. Similarly, a second virtual line segment **L2** connecting a repeating pattern of three holes (e.g., **230f-230h**) through their respective center points may be

angled relative to the longitudinal axis A of the plate **700**. Although two virtual line segments L1, L2 are shown it is evident that the same repeating pattern of three holes repeats along the length of the plate **700**. Each line segment L1, L2 connecting a repeating pattern of three holes through their respective center points may be generally aligned substantially parallel to one another.

(107) The center point of the center hole **230d**, **230g** of each repeating pattern may be aligned generally along the longitudinal axis A of the plate **700**. In addition, indentations **238** of the scallop **236** along the anterior and posterior sidewalls **206**, **208** may be generally aligned with the center hole **230d**, **230g** of each repeating pattern. As best seen in FIG. **14**, the center of the scallops **236** on both of the side surfaces **206**, **208** are aligned with the center of the middle row of shaft holes. The indentations **238** of the scallop **236** along the side surfaces **206**, **208** lie on an axis which is perpendicular to the centered longitudinal axis A along the length of the shaft **210**. In particular, a virtual line segment L3 connecting a center point for the radius of a first indentation **238** on anterior sidewall **206** to a center point for the radius of a second indentation **238** on the posterior sidewall **208** are generally aligned with the center of the center hole **230d**. Similarly, a virtual line segment L4 connecting a center point for the radius of a third indentation **238** on anterior sidewall **206** to a center point for the radius of a fourth indentation **238** on the posterior sidewall **208** are generally aligned with the center of the center hole **230g**. It will again be appreciated that although two virtual line segments L3, L4 are shown it is evident that the same repeating pattern of three holes repeats along the length of the plate **700**. The undulating scallops **236** result in a shaft profile which continually varies in overall width.

(108) Plate **700** further includes a plurality of kickstand holes **235**. For example, in this embodiment, the shaft portion **210** may include two kickstand holes **235** separated from one another and oriented in different directions. The kickstand holes **235** may each comprise a polyaxial locking hole for receiving a locking fastener therein. The polyaxial locking kickstand strut holes **235** are designed to target the strong cortical bone in the anteromedial and posteromedial cortices of the medial condyle and promote angular stability.

(109) Similar to plate **600**, plate **700** includes a dedicated aiming arm attachment hole **702** and a plurality of indentations **244** surrounding the attachment hole **702**. The dedicated aiming arm attachment hole **702** may be a threaded hole, for example, for attaching the attachment post of an associated aiming instrumentation for the system. As shown, the three indentations **244** or blind openings may be rounded or spherical, to help accommodate a portion of an instrument (e.g., an attachment post of an associated aiming instrument).

(110) The distal portion **204** of the bone plate **700**, configured to reside at or near the condylar region of the femur **5**, may include a plurality of holes or openings **240a**, **240b**, **240c**, **240d**, **240e**, **240f**, **240g**, **240h**, **240i**, such as polyaxial locking holes, that are configured to receive one or more fasteners or screws therein. This is substantially similar to plate **200** except hole **240j** is omitted. One or more k-wire holes **242** may also be positioned in the distal portion **204** of the plate **700**.

(111) The thickness of the plate **700** may vary from about 4.5 mm proximally to about 3.6 mm distally varying through the metaphyseal and epiphyseal regions. Like the narrow plate **600**, the transition in thickness may begin about 129 mm from the most distal edge of the plate. The width of the plate may vary from about 39 mm wide in the head of the plate **700** to about 24 mm wide in the shaft **210** of the plate **700**. The transition in width also begins about 129 mm from the most distal edge of the plate **700**.

(112) The main differentiating qualities between the broad plate **700** and the narrow plate **600** are the overall size of the plates and the total number of each type of feature. The distal portion of the plate **700** is about 6 mm wider than that of the narrow plate **600**, thereby permitting space for one additional 4.5 mm polyaxial locking hole resulting in a total of 9 polyaxial holes in the distal cluster. As this plate **700** is designed to fill the majority of the lateral femoral condyle and/or abut against the femoral component of a total knee arthroplasty, the lag screw groove is eliminated in the broad plate **700**.



(113) The shaft **210** of the broad plate **700** is about 6.5 mm wider than that of the narrow plate **600**. With more space, the alternating pattern of polyaxial locking holes in the shaft is increased from 2-wide to 3-wide. Additionally, the waisted edge scallops **236** are slightly larger to take into account the wider shaft **210**.

(114) FIGS. **15** and **16** show the longest lengths for each of the two lateral plates **800**, **900**. These plates **800**, **900** are substantially the same as those shown in FIGS. **6** and **7**, respectively, and like elements are labeled the same. In these embodiments, the plates **800**, **900** further include an additional kickstand opening, **335**, **435**, respectively, and the associated indentations or blind openings **144**, **244**, respectively, to help accommodate a portion of an instrument (e.g., an attachment post of the associated aiming instrument). The total length of these plates **800**, **900** is about 458 mm and the radius of curvature (i.e. anterior bow) is about 1200 mm. Plate lengths decrease by approximately 31-33 mm, resulting in 11 lengths of each lateral plate and a shortest length of about 137 mm.

(115) The pattern of staggered polyaxial holes **330**, **430** occurs in the shaft of both lateral plates. The staggered hole pattern in the shaft provides increased pull-out resistance and helps to prevent new linear fracture lines in the metaphyseal and diaphyseal regions. Two DCP slots **332** break the stacked hole pattern at the 1st and 6th holes in the narrow plate (FIG. **15**), which may be useful in non-unions and osteotomies.

(116) In the broad plate **900**, the polyaxial holes **430** follow the three-hole diagonal pattern, described with reference to FIG. **14**, along the entire length of the shaft, nominally angled parallel to the center row of holes **430** but can be targeted inwards or outwards in order to dodge other implants such as total hip or knee arthroplasties.

(117) Turning now to FIG. **17**, the medial locking plate **1000** is similar to plate **500** shown in FIG. **8** and like elements are numbered the same. Medial locking plate **1000** may be advantageous in that the bottom surface **508** of the plate **1000** in contact with bone is anatomically contoured to abut the corresponding contours of the adjacent bone. For example, FIG. **18** illustrates the epicondylar ridge **1002** of the medial condyle, which is a bony protrusion located on the medial side of the femur's distal end. In order to accommodate the epicondylar ridge **1002**, the plate **1000** may include one or more of a raised posterior edge H1, an anterior radius R3, and a raised height H2. As shown in FIG. **19**, the posterior edge **546** may be raised relative to the anterior edge **548** to conform to the average height of the epicondylar ridge **1002** of the medial condyle. For example, the posterior edge **546** may be higher than anterior edge **548** by a height H1. Height H1 of the raised posterior edge **546** may be about 10-14 mm, or about 12 mm, as compared to the anterior edge **548**. Turning to FIG. **20**, the bottom surface **508** of the plate **1000** may include an anterior radius R3. The anterior radius R3, for example, along the anterior edge **548**, may be contoured to the distal end of the femur. For example, the radius R3 may range from about 28-32 mm, or about 30 mm. In addition, the height H2 of the distal portion **504** may be raised relative to the shaft **510** of the plate **1000**. For example, the height H2 may be about 9-10 mm, or about 9.5 mm. The anterior radius R3 and raised height H2 relative to the plate shaft **510** are designed to conform to the average size of the anteromedial third of the medial condyle. These unique anatomic features provide for a better fit to the bone and may provide better patient outcomes.

(118) Plate **1000** may include holes **530**, **540**, kickstand holes **535**, articulated tensioning device (ATD) hole **524**, and k-wire holes **522**, **542** as already described herein. The holes **530**, **540** may be locking holes, such as polyaxial locking holes. In particular, the locking holes may be thread-forming holes such that the fastener locks to the plate **1000** when inserted therein. The locking holes **530**, **540**, for example, provided in all portions of the plate **1000**, permit the creation of a fixed angle construct which helps to prevent both varus collapse and screw backout, even in cases of osteoporosis.

(119) The medial locking plate **1000** may be inserted through an incision over the anteromedial aspect of the distal femur or an S-shaped incision on the posterior side of the knee joint. The plate

**1000** is designed to sit on the most anterior third of the medial condyle, directly on top of the medial epicondyle. Plate **1000** may provide the same types of features as the narrow and broad lateral plates including all polyaxial locking holes **540** in the distal cluster and polyaxial locking holes **530** along the shaft **510** and two polyaxial locking kickstand strut holes **535** designed to target the strong cortical bone in the posterolateral cortex of the condyle and promote angular stability. The thickness of the plate **1000** may vary from about 3.0 mm proximally to about 2.25 mm distally with the transition occurring in the metaphyseal region of the plate **1000**.

(120) Unlike other plates that may lead to misplacement or are improperly contoured, the plates described in embodiments herein may have raised contours on their respective posterior sides to sit more flush on the condylar anatomy and provide surgeons with a way to key in the plate in the correct location. By having a large number of options for fixation along the plates, helps in preventing varus collapse and loss of fixation in poor bone quality. Many options for points of fixation become even more important in highly comminuted articular blocks or when other existing implants may need to be avoided.

(121) Referring to FIGS. **21-37**, an aiming guide system **1100** in accordance with an embodiment of the disclosure will be described. Generally, the aiming guide system **1100** includes an aiming arm **1102** that attaches to the bone plate **300** via a connection assembly **1128** that includes a single attachment post **1140** and threaded shaft **1130** engaged with the plate **300**. While the aiming guide system **1100** is shown and described with respect to bone plate **300**, it is understood that the system **1100** may be sized and configured to be utilized with various bone plates including the other plates described herein. The angle of the attachment post **1140** relative to the top surface of the plate **300** is designed such that the post **1140** and subsequent assembly items do not block access to the distal cluster of screw holes **340** in the plate. The aiming arm **1102** keys into place on the attachment post **1140** and is oriented with the proper side facing up (for a left femur procedure, the surface label “LEFT” should be facing up). A two-piece fastener completes the assembly of the aiming arm **1102** to the plate **300**, including a washer **1160** which lays flush against the upper surface of the aiming arm **1102** and a spherical nut **1170** that tightens onto the threaded shaft **1130**.

(122) Referring to FIG. **21**, the aiming arm **1102** accepts tissue protection sleeves **1180**. The sleeves **1180** provide a portal into small incisions through which trocars **1245**, drill sleeves **1210**, k-wire sleeves **1236**, dynamic compression sleeves **1250**, drills **1230**, drivers, and screws may pass. The sleeves **1180** clip into place on either surface of the aiming arm **1102** (depending on whether the procedure is being performed on a right or left femur). The accurate and rigid interface of the sleeves **1180** with the aiming arm **1102** functions to properly align the sleeves **1180** to provide the nominal (0°) angle of the holes **328**, **330**, **332** in the shaft of the plate **300**. The kickstand sleeve **1180'** is another type of tissue protection sleeve, providing a similar portal for trocars, drill sleeves, and the like, but is designed to align with the two oblique “kickstand” screw holes **335** in the plate **300**.

(123) Having generally described the aiming guide system **1100**, illustrative components, along with assembly and operation thereof, will be described. Referring to FIG. **22**, the aiming arm **1102** has a generally rigid body **1104** extending from a proximal end **1103** to a distal end **1105**. The arm body **104** has a length shorter than the plate **300** such that the proximal end **1103** thereof is slightly distal of the proximal end **302** of the plate **300** and the distal end **1105** is proximal of the distal end **304** of the plate **300** such that the screw holes **340** remain unobstructed. An attachment area **1106** extends from the distal end **1105** of the arm body **1104** and defines an attachment slot **1108** extending through the arm body **1104**. The attachment slot **1108** is configured to receive the orienting boss **1146** on the attachment post **1140** as will be described in more detail hereinafter. As illustrated in FIG. **21**, upon connection of the aiming arm **1102** to the plate **300**, the attachment area **1106** is offset to the side of plate **300** and does not obstruct the plate **300**.

(124) The arm body **1104** may be manufactured from a radiolucent material to prevent obstructing lateral imaging during the procedure. The aiming arm **1102** may be configured to be reversible, i.e.

when one surface is facing upward, the arm **1102** is configured for a lefthanded plate and when the opposite surface is facing upward, the arm **1102** is configured for a righthanded plate. Additionally, the arm body **1104** may have different configurations for narrow lateral plates versus broad lateral plates. In at least one embodiment, there is one left-right reversible arm for the narrow lateral plate and one left-right reversible arm for the broad lateral plate. A plate identifier **1107** may be printed on each surface to identify to the user the arm configuration and orientation. Additionally or alternatively, in at least one embodiment, the attachment location of the aiming arm **1102** to the attachment post **1140** may include a rounded groove or slot to accept a ball-end pin or the like in the orienting boss **1146** of the attachment post **1140** only when the aiming arm **1102** is assembled in the correct orientation, as described hereinafter with respect to FIG. 27.

(125) Referring to FIGS. 22-24, a plurality of aiming holes **1110** are defined through the aiming arm **1102**. Each aiming hole **1110** has a through bore **1112** which extends through the arm body **1104** and aligns with a respective screw hole **328**, **330**, **332** of the plate **300** when the aiming arm **1102** is attached relative to the plate **300**. The aiming holes **1110** may be numbered with indicators **1118** on the side and/or each surface of the arm body **1104** to indicate the associated targeted hole **328**, **330**, **332** in the plate **300**.

(126) Each aiming hole **1110** includes, on each surface of the arm body **1104**, a recess **1114** about the through bore **1112**. The recesses **1114** are configured to receive a portion of the head member **1186** of a tissue protection sleeve **1180**. The recess **1114** preferably has a non-round shape which complements the shape of the head member **1186** such that the head member **1186** is received and retained in a fixed position. An undercut **1116** is defined within each recess **1114** to receive a locking tab **1196** on the tissue protection sleeve **1180**, as will be described in more detail hereinafter.

(127) In both the narrow and broad aiming arms, the recess **1114** and undercut **1116** features are mirrored about the mid-plane of the aiming arm **1102** such that tissue protection sleeves **1180** can be inserted from either side of the reversible embodiment of the aiming arm **1102**. The undercuts **1116** meet at the mid-plane of each bore **1112**, resulting in a continuous groove in which the retention ledge **1198** of the locking tab **1196** will sit. In the narrow aiming arm as illustrated in FIG. 23, the undercut **1116** is fully circumferential about the central axis of each bore **1112**. In the broad aiming arm as illustrated in FIG. 24, the axis of revolution of the undercut **1116** is offset by 2 mm, resulting in an undercut which only consumes about 35% of the circumference of each bore **1112**.

(128) Referring again to FIG. 22, a projection **1120** extends outwardly from each side of the arm body **1104**. Each projection **1120** defines upper and lower sloped surfaces **1122**. A kickstand targeting hole **1124** is through each sloped surface **1122** and has an axis generally perpendicular to the sloped surface **1122**. Each kickstand targeting hole **1124** exits the projection on the opposite surface of the arm body **1104** at an exit hole **1126**. The kickstand targeting holes **1124** permit nominal targeting of the two oblique kickstand screw holes **335** in the distal cluster of the plate **300**. Each kickstand targeting hole **1124** may have a visual indicator **1118** next to the hole. For example, the holes may be labeled A for anterior and P for posterior.

(129) A connection assembly **1128** in accordance with an embodiment of the disclosure will be described with reference to FIGS. 25-30. The connection assembly **1128** a threaded shaft **1130**, a single attachment post **1140**, and a two-piece fastener including a washer **1160** and a spherical nut **1170**. Referring to FIG. 25, the threaded shaft **1130** includes a shaft body **1132** extending between ends **1131** and **1133**. Each end **1131**, **1133** includes threads **1134**, **1136**, respectively, and a driver-receiving bore **1135**, for example, configured to receive a hexalobe screwdriver. The threaded shaft **1130** is preferably reversible, with identical threads **1134**, **1136** at each end. In at least one embodiment, the tips of the threaded shaft contain a blunted first thread **1137** to promote self-centering of the shaft **1130** and help prevent cross-threading in the plate **300**. While not illustrated, it is recognized that the threaded shaft **1130** may be cannulated through its long central axis to permit the placement of a k-wire through the attachment slot **1108** of the aiming arm **1102** for

preliminary fixation.

(130) The attachment post **1140** includes a hollow tube **1142** extending from a proximal end **1141** to a distal end **1143**. A radial mating surface **1148** extends outwardly from the proximal end **1141** of the tube **1142** and the orienting boss **1146** extends upwardly from the mating surface **1148**. The mating surface **1148** extends at an acute angle relative to the axis of the hollow tube **1142**. The mating surface **1148** is oriented such that the aiming arm **1102** will lie flat on the mating surface **1148** when slid over the orienting boss **1146**. The orienting boss **1146** preferably has a configuration which dictates the orientation of the aiming arm **1102**. For example, in the illustrated embodiment, the orienting boss **1146** has a rectangular configuration such that when the orienting boss **1146** is engaged within the attachment slot **1108** of the aiming arm **1102**, the aiming arm **1102** must be properly aligned with the bone plate **300**. The orienting boss **1146** is not limited to a rectangular configuration, but may have other configurations, for example, oval shaped, trapezoidal, pentagonal.

(131) Additionally, or alternatively, a keying feature may be provided between the attachment slot and the orienting boss. In the embodiment illustrated in FIG. 27, one face of the orienting boss **1146'**, for example, the proximal side, includes a ball-end pin **1147** or other keying member extending therefrom. The ball-end pin **1147** is positioned some distance away from the center plane of the boss **1146'**. The attachment area **1106'** of the arm body **1104'** defines an attachment slot **1108'** with a corresponding groove **1109** positioned to receive the keying member **1147** provided the aiming arm **1102** is in the proper orientation. Since the keying member **1147** is off center, if the arm body **1104'** illustrated in FIG. 27 was flipped over, the groove **1109** would no longer align with the keying member **1147** and the orienting boss **1146'** would not be receivable in the attachment slot **1108'**.

(132) An attachment block **1150** extends from the distal end **1143** of the hollow tube **1142**. The distal surface **1152** of the attachment block **1150** is offset and contoured to match the contour of the plate **300** at the attachment location. A plurality of ball end pins **1154** extend from the distal surface **1152**. The ball end pins **1154** are configured to align with and engage the indentations **344** in the plate **300** (see FIG. 6). The engagement of the ball end pins **1154** in the indentations **344** ensures a proper orientation of the attachment post **1140** with the plate **300**, and thereby, a proper orientation of the aiming arm **1102** with the plate **300**. A continuous through bore **1144** extends through the attachment post **1140** from the orienting boss **1146**, through the hollow tube **1142** and through the attachment block **1150** such that the attachment post **1140** may be slid over the threaded shaft **1130**. The cannulation through the post **1140** matches the angle of the shaft **1130** relative to the top of the plate **300** as shown in FIG. 30. As such, once assembled, the trajectories of the holes **1110** in the aiming arm **1102** will align with the trajectories of the holes **328, 330, 332** in the shaft of the plate **300**.

(133) Referring to FIGS. 29 and 30, the two-piece fastener includes the washer **1160** and the spherical nut **1170**. The purpose of the two-piece fastener is to provide a simplified, streamlined assembly mechanism that permits lagging of the plate **300**, post **1140**, and aiming arm **1102** together in one step. As the axis A1 of the threaded shaft **1130** and the plane P1 of the aiming arm's mating surface are not normal to one another, the fastener required to lag the guide system together must be able to be oriented to the shaft **1130** and the aiming arm **1102** individually. The washer **1160** and spherical nut **1170** described herein achieve such individual orientation. The pre-determined orientation would be fixed such that the bottom surface of the washer would lie flush with the top surface of the aiming arm and the central axis of the nut would lie co-axial with the central axis of the threaded shaft. The washer **1160** includes a base member **1162** with a contact surface **1164**. A hole **1163** extends through the base member **1162** such that the threaded shaft **1130** may pass therethrough. A plurality of fingers **1166** extend upward from the base member **1162**. The fingers **1166** along with the base member **1162** define a semi-spherical seat **1168** for the spherical nut **1170**.

(134) The spherical nut **1170** includes a shaft **1172** extending between a ball portion **1174** and a handle member **1176**. The ball portion **1174** has a semi-spherical configuration which complements that of the seat **1168**. The fingers **1166** are configured to allow the ball portion **1174** of the spherical nut **1170** to be snapped into the seat **1168** and thereafter retain the ball portion **1174** within the seat **1168**. With such a configuration, the spherical nut **1170** can move freely within the washer **1160** but remains contained to avoid additional parts. A distal end of the ball portion **1174** defines an opening **1175** into a threaded bore **1178**. The threaded bore **1178** is configured to threadably engage the threads **1134**, **1136** at either end **1131**, **1133** of the threaded shaft **1130**. When the spherical nut **1170** is oriented with the threaded shaft **1130** and tightened, the washer **1160** self-aligns with the mating surface of the aiming arm **1102**, completing the rigid connection of the arm **1102** to the plate **300**.

(135) Referring to FIGS. **31** and **31**, a guide assembly with an alternative embodiment of the connection assembly **1128'** will be described. In the present embodiment, the two-piece fastener is replaced with a fixed axis fastener including a washer **1160'** and nut **1170'** which are fixed together such that the nut **1170'** is rotatable about a singular axis **A2**. The angle of axis **A2** is selected to match the angle of the axis **A1** of the attachment post **1140**. The washer **1160'** includes a base member **1162'** which defines a contact surface **1164**. A nut attachment shaft **1165** extends from the base member **1162'** and is configured to receive and rotatably retain the shaft **1172'** of the nut **1170'**. The nut shaft **1172'** may be connected to the nut attachment shaft **1165** via radial tabs engaging a rim within the nut attachment shaft **1165** or any other suitable means for rotatably connecting the nut shaft **1172'** to the nut attachment shaft **1165**. The fixed orientation of the nut attachment shaft **1165**, only permits rotational motion of the nut **1170'** about the nut's central axis. The nut shaft **1172'** includes internal threads configured to threadably engage the threads **1134**, **1136** at either end **1131**, **1133** of the threaded shaft **1130**. With the angle of the axis **A2** of the nut **1170'** matching that of the attachment post axis **A1**, the contact surface **1164** of the washer **1160'** will be parallel to and lie against the surface of the arm body **1104**.

(136) Having generally described the components of the connection assembly **1128**, attachment of the aiming arm **1102** to the plate **300** will be described with reference to FIGS. **29** and **30**. As a first step, the threaded shaft **1130** is assembled onto the plate **300**. The threads **1136** threadably engage the threads of one of the holes **340** in the plate **300**. The threaded shaft **1130** can be final tightened with a hexalobe screwdriver or the like engaged with the driver-engagement bore **1135**. The attachment post **1140** is slid over the threaded shaft **1130** and the ball end pins **1154** align with and engage the indentations **344** in the plate **300**. The aiming arm **1102** is then positioned such that the orienting boss **1146** is received in the attachment slot **1108**. The two-piece fastener is then positioned such that the contact surface **1164** of the washer **1160** sits on the upper surface of the aiming arm **1102** and the threaded shaft **1130** is received into the threaded bore **1178** of the spherical nut **1170**. The handle **1176** is then used to tighten the nut **1170** as the threaded bore **1178** engages the threads **1134**. As the spherical nut **1170** is tightened, the washer **1160** self-aligns with the mating surface of the aiming arm **1102**, completing the rigid connection of the arm **1102** to the plate **300**. As can be seen from FIGS. **29** and **30**, upon connection, the plane **P1** of the mating surface **1148** of the attachment post **1140** and the plane **P2** of the contact surface **1164** of the washer **1160** are parallel to one another. Accordingly, the trajectories of the holes **1110** in the aiming arm **1102** will align with the trajectories of the holes **328**, **330**, **332** in the shaft of the plate **300**.

(137) Referring to FIGS. **33** and **34**, an embodiment of a tissue protection sleeve **1180** will be described. The tissue protection sleeve **1180** is configured to be inserted into one of the aiming holes **1110** with a 1-to-1 association with the holes **328**, **330**, **332** in either the narrow or broad lateral plates **300**. The tissue protection sleeve **1180** includes a shaft **1182** extending from a proximal end **1181** to a distal end **1183**. A through bore **1184** extends through the shaft **1182** from the proximal end **1181** to the distal end **1183**. The distal end **1183** may have a slight taper thereto to minimize tissue disruption.

(138) As described above, a head member **1186** configured to seat in a desired orientation within the recess **1114** of one of the aiming holes **1110** is defined at the proximal end **1181** of the shaft **1182**. Additionally, the proximal end **1181** of the shaft **1182** defines the locking tab **1196** which is configured to engage in the undercut **1116** of the aiming hole **1110**. The locking tab **1196** is releasable such that the sleeve **1180** is removable from the aiming hole **1110**. To facilitate such, a slot **1194** is defined in the shaft **1182** such that a pivotal locking arm **1190** is defined. The free end of the pivotal locking arm **1190** defines an unlocking button **1192**. The locking tab **1196** is positioned along the locking arm **1190** distally of the unlocking button **1192**. The locking tab **1196** has a sloped surface extending to the retention ledge **1198**. Accordingly, as the tissue protection sleeve **1180** is inserted into the aiming hole **1110**, the sloped surface of the locking tab **1196** will contact the through bore **1112** and the locking arm **1190** will pivot radially inward, allowing the locking tab **1196** to pass through the bore **1112**. Once the locking tab **1196** passes the bore **1112** and is aligned with the undercut **1116**, the pivotal locking arm **1190** will automatically return to its initial position, with the retention ledge **1198** engaging the undercut **1116**, as shown in FIG. 34. In at least one embodiment, when inserted properly, an audible click is heard as the retention ledge **1198** engages the aiming hole's undercut **1116**. To remove the tissue protection sleeve **1180**, the unlocking button **1192** is squeezed toward the head portion **1186** of the sleeve **1180**, releasing the ledge **1198** from the undercut **1116**. The sleeve **1180** can then be pulled free from the aiming arm **1102**. With reference to FIG. 21, the tissue protection sleeve **1180** may receive instruments directly, for example, trocar **1245**, or may receive additional sleeves, for example, drilling sleeve **1200** or dynamic compression sleeve **1250**, which in turn receive instruments.

(139) In the illustrated embodiment, the kickstand tissue protection sleeve **1180'** is substantially the same as the tissue protection sleeves **1180** described above except at the proximal end **1181'** thereof. Instead of a head member **1186** and locking arm **1190**, a handle **1255** extends radially from the proximal end **1181'**. The handle **1255** facilitates greater control and rotation of the kickstand tissue protection sleeve **1180'** as it is inserted at an angle relative to the bone plate **300**. In other aspects, the sleeve **1180'** is the same as in the previous embodiment and facilitates passage of drill sleeves, screws and the like as described herein.

(140) Referring to FIGS. 35 and 36, an embodiment of a drill sleeve **1200** positionable within one of the tissue protection sleeves **1180**, **1180'** will be described. The drill sleeve **1200** includes an outer sleeve body **1202** extending from a proximal end **1201** to a distal end **1203**. A through bore **1204** extends through the outer body sleeve **1202** from the proximal end **1201** to the distal end **1203**. A collet **1206** is defined at the distal end **1203** of the outer sleeve body **1202**. Slots **1208** on either side of the outer sleeve body **1202** allow the collet **1206** to collapse and return to its natural expanded position. The drill sleeve **1200** also includes an inner drill sleeve body **1210** which extends from a proximal end **1211** to a distal end **1213**. A through bore **1214** extends through the inner body sleeve **1210** from the proximal end **1211** to the distal end **1213**. The distal end **1213** of the inner drill sleeve **1210** is sized to be positioned within the bore **1204** of the outer sleeve body **1202**. The proximal end **1211** of the inner drill sleeve body **1210** includes a grippable head member **1216** and a rotation tab **1218**. In an initial position, the inner sleeve body **1210** is only partially inserted into the outer sleeve body **1202** such that the distal end **1213** thereof is clear of the collapsible collet **1206**.

(141) The drill sleeve **1200** may be inserted into one of the tissue protection sleeves **1180**, **1180'** with the inner sleeve body **1210** in the initial position. The drill sleeve **1200** is advanced through the tissue protection sleeve **1180**, **1180'** until the collet **1206** of the outer sleeve body **1202** compresses and snaps into any of the holes **328**, **330**, **332**, **335** of the plate **300**. Once the outer sleeve body **1202** is fully seated, the collet **1206** is held in the expanded position by depressing the inner sleeve body **1210** until the distal end **1213** thereof is aligned with the collet **1206**, as illustrated in FIG. 36. In the illustrated embodiment, the inner sleeve body **1210** is depressed by rotating the tab **1218**. In other embodiments of the drill sleeve, this can be achieved by pressing

axially, rotating a nut, depressing a lever, or the like. With the drill sleeve **1200** locked in place, the inner sleeve through bore **1214** is configured to receive various instruments, for example, as shown in FIG. **21**, a drill **1230**, a k-wire **1235**, or a positioning pin **1240**.

(142) Alternatively, a dynamic compression sleeve **1250** can be inserted into the tissue protection sleeve **1180** to allow off-axis predrilling and permit compression through a dynamic compression hole **332** in either direction in the long axis of the plate **300**. The dynamic compression sleeve has a bore **1252** with an axis that is offset a given distance, for example, by about 1 mm, from the central axis of the sleeve **1250**. With the sleeve **1250** in a first orientation, the off axis bore **1252** is offset the given distance in the proximal direction of the plate **300** and when rotated 180°, is offset the given distance in the distal direction of the plate **300**. The sleeve **1250** has a tab **1254** which is aligned and press-fit into a tab in the head member **1186** of the tissue protection sleeve **1180** to properly clock its orientation. The holes **1110** in the aiming arm **1102** that align with dynamic compression holes **332** in the plate **300** may be marked, for example, outlined with white paint **1119** on the aiming arm.

(143) Referring to FIGS. **21** and **37**, a hole marker **1220** may also press-fit into one of the aiming holes **1110** to allow marking either the last hole in a plate being targeted or a hole which has already been filled with a screw. In the illustrated embodiment, the hole marker **1220** has a handle portion **1222** with a pair of legs **1224** depending therefrom. The legs **1224** are separated from one another by a gap **1227**. A circular cut **1226** adjacent the handle portion **1222** allows the legs **1224** to pivot toward one another upon application of an inward force, but then automatically return to the initial position upon removal of such force. The outer sides **1229** of each leg **1224** have a taper such that as the legs **1224** are moved into the through bore **1112** of one of the aiming holes **1110**, the legs **1224** will pivot toward one another and pass through. Each leg **1224** also has an outer notch defined therein **1228**. When the hole marker **1220** is completely seated in the recess **1114** of the aiming hole **1110**, the notch **1228** will receive and engage the wall of the through bore **1112** as the legs **1224** move back toward the initial position. The notches **1228** are sloped such that a sufficient removal force on the handle portion **1222** will cause the leg **1224** to again pivot toward one another and pass in the reverse direction through the through bore **1112**.

(144) The aiming guide system **1100** described herein allows for improved lateral imaging and visualization of the fracture. Due to the oblique angle of the threaded shaft **1130**, fracture lines are clearly visible in the metaphyseal region of the femur, and access to the distal holes **340** in the head of the plate **300** is maintained. The system **1100** also has fewer components and fewer total assembly steps, allowing for simpler operation and a more streamlined procedure than some of the other available guides.

(145) Attachment of the aiming arm **1102** to the plate **300** is achieved via a smaller rigid connection to the plate than most others on the market. This smaller connection is also located more distally in the plate than other competitive options. Therefore, a smaller incision placed more distally (closer to the articular surface of the knee) can be achieved. With a smaller MIS incision, excessive stripping of the soft tissue and/or periosteum can be avoided and there is a lower chance of wound complications.

(146) Oblique “kickstand” screw holes in a distal femur plate are a unique way to engage the strong bone on the medial condyle of the femur and promote stabilization of the construct through triangular, off-axis fixation. Providing a way to target the nominal axis of the kickstand holes through the guide system allows an easier, MIS approach to placing locking or non-locking screws in these oblique holes.

(147) One skilled in the art will appreciate that the embodiments discussed above are non-limiting. While bone plates may be described as suitable for a particular approach (e.g., medial or lateral), one skilled in the art will appreciate that the bone plates can be used for multiple approaches. In addition, while bone plates are described as having particular holes (e.g., locking or non-locking), one skilled in the art will appreciate that any of the bone plates can include locking, non-locking or

a combination of locking and non-locking holes. In addition to the bone plates, screws and instruments described above, one skilled in the art will appreciate that these described features can be used with a number of trauma treatment instruments and implants, including external fixators, ring fixators, rods, and other plates and screws. It will also be appreciated that one or more features of one embodiment may be partially or fully incorporated into one or more other embodiments described herein.

## Claims

1. An aiming guide system configured for connection to a bone plate, the bone plate extending along a longitudinal axis and comprising a proximal portion, a shaft, and a distal portion, the bone plate defining a plurality of first screw holes along shaft, a plurality of second screw holes at the distal portion, and an attachment screw hole proximate the distal portion, the guide system comprising: an aiming arm having a rigid body extending from a proximal end to a distal end with a plurality of aiming holes defined through the rigid body between the proximal end and the distal end thereof, the distal end defining an attachment slot through the body; and a connection assembly configured to engage the attachment screw hole and the attachment slot such that the aiming arm is fixed in position relative to the bone plate with each of the plurality of aiming holes aligned with a respective one of the first screw holes, wherein the connection assembly includes: an attachment post having a first end with an orienting boss extending from a mating surface, the orienting boss configured to be received in the attachment slot such that the aiming arm rests on the mating surface and is maintained in a proper orientation, wherein the orienting boss and the attachment slot have complementary configurations such that they mate only when the aiming arm is in the proper orientation, wherein the attachment post includes an attachment block at a second end, the attachment block having a distal surface which defines a plurality of ball end pins, each ball end pin configured to be received in a respective indentation on the plate surface about the attachment screw hole, wherein positioning of the ball end pins within the indentations properly aligns the attachment post relative to the plate.
2. The system of claim 1, wherein the orienting boss has a keying member extending therefrom and the attachment slot has a groove configured to receive the keying member when the aiming arm is in the proper orientation.
3. The system of claim 1, wherein the attachment post is configured to extend at an oblique angle with respect to the bone plate such that the attachment post and the aiming arm do not overlie the second screw holes.
4. The system of claim 1, wherein the connection assembly further includes a threaded shaft having a shaft body extending between first and second ends, each end including a plurality of threads, the threaded shaft extending through a through bore of the attachment post with the threads of at least one of the first and second ends of the shaft body configured to threadably engage the attachment screw hole.
5. The system of claim 4, wherein the connection assembly further comprises a fastener configured to threadably engage the threads on at least one of the threaded shaft to secure the attachment post between the aiming arm and bone plate.
6. The system of claim 5, wherein the fastener includes a washer, the washer having a contact surface defined on one side thereof and a semi-spherical seat defined on the opposite side thereof, and a spherical nut, the spherical nut has a ball portion having a semi-spherical configuration which complements that of the seat, the ball portion defining a threaded bore configured to threadably receive at least one end of the threaded shaft.
7. The system of claim 6, wherein during tightening of the threaded nut, engagement between the ball portion and the semi-spherical seat causes the washer to self-align with the contact surface generally parallel to the mating surface of the attachment post.



8. The system of claim 1, wherein a projection extends from at least one side surface of aiming arm body, the projection defines an angled aiming hole configured to align with a kickstand screw hole of the bone plate.
  9. The system of claim 1, further comprising at least one tissue protection sleeve configured to be positioned through one of the plurality of aiming holes such that the tissue protection sleeve defines a through bore from the aiming guide to a respective one of the first screw holes.
  10. The system of claim 1, wherein the aiming arm is reversible.
  11. An aiming guide system configured for connection to a bone plate, the bone plate extending along a longitudinal axis and comprising a proximal portion, a shaft, and a distal portion, the bone plate defining a plurality of first screw holes along shaft, a plurality of second screw holes at the distal portion, and an attachment screw hole proximate the distal portion, the guide system comprising: an aiming arm having a rigid body extending from a proximal end to a distal end with a plurality of aiming holes defined through the rigid body between the proximal end and the distal end thereof, the distal end defining an attachment slot through the body, and; a connection assembly configured to engage the attachment screw hole and the attachment slot such that the aiming arm is fixed in position relative to the bone plate with each of the plurality of aiming holes aligned with a respective one of the first screw holes, wherein the connection assembly includes: an attachment post having at a first end a mating surface such that the aiming arm rests on the mating surface in a proper orientation and an attachment block at a second end, the attachment block having a distal surface which defines a plurality of ball end pins, each ball end pin configured to be received in a respective indentation on the plate surface about the attachment screw hole, wherein positioning of the ball end pins within the indentations properly aligns the attachment post relative to the plate wherein the attachment post has an orienting boss extending from the mating surface and the orienting boss is configured to be received in the attachment slot such that the aiming arm rests on the mating surface and is maintained in the proper orientation wherein the orienting boss has a keying member extending therefrom and the attachment slot has a groove configured to receive the keying member when the aiming arm is in the proper orientation.
  12. The system of claim 11, wherein the attachment post is configured to extend at an oblique angle with respect to the bone plate such that the attachment post and the aiming arm do not overlie the second screw holes.
  13. The system of claim 11, wherein the connection assembly further includes a threaded shaft having a shaft body extending between first and second ends, each end including a plurality of threads, the threaded shaft extending through a through bore of the attachment post with the threads of at least one of the first and second ends of the shaft body configured to threadably engage the attachment screw hole.
  14. The system of claim 13, wherein the connection assembly further comprises a fastener configured to threadably engage the threads on at least one of the threaded shaft to secure the attachment post between the aiming arm and bone plate.
  15. The system of claim 14, wherein the fastener includes a washer, the washer having a contact surface defined on one side thereof and a semi-spherical seat defined on the opposite side thereof, and a spherical nut, the spherical nut has a ball portion having a semi-spherical configuration which complements that of the seat, the ball portion defining a threaded bore configured to threadably receive at least one end of the threaded shaft.
  16. The system of claim 15, wherein during tightening of the threaded nut, engagement between the ball portion and the semi-spherical seat causes the washer to self-align with the contact surface generally parallel to the mating surface of the attachment post.
  17. The system of claim 16, wherein a projection extends from at least one side surface of the aiming arm body, the projection defining an angled aiming hole configured to align with a kickstand screw hole of the bone plate.
-

