

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12392374
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Khan; Arman Mohammad et al.

---

### Methods and apparatus for thermal management of sumps using oleophilic and oleophobic coatings

---

#### Abstract

Oleophobic and/or oleophilic coatings to reduce heat loads on a gas turbine engine thermal management system are disclosed herein. An example method to reduce heat load in a gas turbine engine, the method including applying an oleophobic coating to an internal wall of a sump, the sump located in proximity to a heat generating element of the gas turbine engine, and applying an oleophilic coating to the heat generating element of the gas turbine engine.

---

**Inventors:** Khan; Arman Mohammad (Bengaluru, IN), Math; Souvik (Bengaluru, IN), Ganiger; Ravindra Shankar (Bengaluru, IN), Sengupta; Arundhati (Bengaluru, IN), Prasad; Santosh (Bengaluru, IN), Anstead; Duane H (Evendale, OH)

**Applicant:** General Electric Company (Schenectady, NY)

**Family ID:** 1000008765188

**Assignee:** GENERAL ELECTRIC COMPANY (Evendale, OH)

**Appl. No.:** 18/680506

**Filed:** May 31, 2024

#### Prior Publication Data

Document Identifier	Publication Date
US 20240352974 A1	Oct. 24, 2024

#### Related U.S. Application Data

continuation parent-doc US 18305139 20230421 US 12018722 child-doc US 18680506

---

#### Publication Classification

**Int. Cl.: F16C33/66** (20060101); **F01M11/00** (20060101); **F02C7/06** (20060101)

**U.S. Cl.:**

**CPC** **F16C33/6685** (20130101); **F01M11/0004** (20130101); **F02C7/06** (20130101);  
F01M2011/0091 (20130101); F16C2360/23 (20130101)

## Field of Classification Search

**CPC:** F02C (7/06); F01M (2011/0091); F16C (33/6685); F16C (2360/23)

**USPC:** 184/6.11

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4046223	12/1976	McHugh	384/313	F01D 25/125
4384725	12/1982	Nenov	277/944	F16J 15/43
4820948	12/1988	Rogelein	310/90	F16C 33/103
6470666	12/2001	Przytulski et al.	N/A	N/A
8783959	12/2013	Haag et al.	N/A	N/A
10024362	12/2017	Diener	N/A	F16C 33/664
10233934	12/2018	Marya et al.	N/A	N/A
10451211	12/2018	Herring et al.	N/A	N/A
10801408	12/2019	Dierksmeier et al.	N/A	N/A
10947925	12/2020	Singh et al.	N/A	N/A
11459952	12/2021	Rendina et al.	N/A	N/A
12018722	12/2023	Khan	N/A	F16C 33/6685
2004/0197212	12/2003	Roby	N/A	N/A
2006/0121315	12/2005	Myli	428/702	C23C 14/08
2013/0147123	12/2012	Davies et al.	N/A	N/A
2015/0030274	12/2014	Adane	384/469	F16C 33/60
2016/0177959	12/2015	Marya et al.	N/A	N/A
2017/0219010	12/2016	Diener	N/A	F16C 33/32
2020/0309032	12/2019	Mason	N/A	N/A
2020/0400094	12/2019	Singh et al.	N/A	N/A
2022/0120191	12/2021	Sato	N/A	F02B 37/00
2022/0282177	12/2021	Heise et al.	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103380306	12/2012	CN	N/A
111734529	12/2019	CN	N/A
102009053002	12/2010	DE	N/A
102011088232	12/2012	DE	N/A
102013213615	12/2014	DE	N/A
102020131655	12/2021	DE	N/A
2019081166	12/2018	JP	N/A

### OTHER PUBLICATIONS

Jackson et al., "Effect of Surface Wettability on Carbon Nanotube Water-Based Nanofluid Droplet Impingement Heat Transfer," Journal of Physics: Conference Series, published Jun. 2014, vol. 525, retrieved from <https://iopscience.iop.org/article/10.1088/1742-6596/525/1/012024>. cited by applicant

Ye et al., "Electrothermally Tunable Graphene Resonators Operating at very High Temperature up to 1200K," Nano Letters, published on Jan. 31, 2018, pp. 1678-1685, vol. 18, No. 3, retrieved from <https://pubs.acs.org/doi/pdf/10.1021/acs.nanolett.7b04685>. cited by applicant

Bonanno et al., "Use of Nanostructured Coating to Improve Heat Exchanger Efficiency," Factories of the Future, published on Feb. 15, 2019, pp. 275-292, retrieved from [https://doi.org/10.1007/978-3-319-94358-9\\_13](https://doi.org/10.1007/978-3-319-94358-9_13). cited by applicant

Solfiti et al., "A Review on Thermophysical Properties of Flexible Graphite," Procedia Structural Integrity, published Jun. 30, 2020, pp. 187-198, vol. 26, retrieved from <https://www.sciencedirect.com/science/article/pii/S2452321620304303>. cited by applicant

United States Patent and Trademark Office, "Notice of Allowance," in connection with U.S. Appl. No. 18/305,139, on Feb. 22, 2024, 7 pages. cited by applicant

The State Intellectual Property Office of People's Republic of China, "First Search," mailed in connection with Chinese Patent Application No. 202410476286.4, dated Jan. 7, 2025, 2 pages. cited by applicant

The State Intellectual Property Office of People's Republic of China, "First Office Action," mailed in connection with Chinese Patent Application No. 202410476286.4, dated Jan. 7, 2025, 10 pages (English Translation included). cited by applicant

---

*Primary Examiner:* Momper; Anna M

*Assistant Examiner:* Buse; Mark K

*Attorney, Agent or Firm:* Venable LLP

---

## **Background/Summary**

RELATED APPLICATIONS (1) This patent arises from a continuation of U.S. patent application Ser. No. 18/305,139, now U.S. Pat. No. 12,018,722, filed on Apr. 21, 2023. U.S. patent application Ser. No. 18/305,139 is hereby incorporated herein by reference in its entirety.

### **FIELD OF THE DISCLOSURE**

(1) This disclosure relates generally to thermal management of engine components, and, more particularly, to thermal management of sumps.

### **BACKGROUND**

(2) Aircraft typically include various accessory systems supporting the operation of the aircraft and/or its gas turbine engine(s). For example, such accessory systems may include a lubrication system that lubricates components of the engine(s), an engine cooling system that provides cooling air to engine components, an environmental control system that provides cooled air to the cabin of the aircraft, and/or the like. As such, heat is added or removed from a fluid (e.g., oil, air, etc.) during operation of these accessory systems.

---

## **Description**

## BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A full and enabling disclosure of the present technology, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended Figures, in which:
- (2) FIG. 1 is a cross-sectional view of a gas turbine engine in which examples disclosed herein may be implemented.
- (3) FIG. 2A illustrates an example sump positioned in the gas turbine engine of FIG. 1.
- (4) FIG. 2B illustrates example oleophilic and oleophobic coating(s) applied to the sump of FIG. 1.
- (5) FIG. 3A illustrates example heat dissipation resulting from oleophobic-coated sump walls.
- (6) FIG. 3B illustrates example oleophilic coating of sump walls as shown in an example cross-section of the gas turbine engine of FIG. 1.
- (7) FIG. 4 illustrates an example oleophobic coating with a high heat transfer coefficient (HTC) of cold sump walls in connection with the gas turbine engine of FIG. 1.
- (8) FIG. 5 illustrates an example oleophobic coating with a low heat transfer coefficient (HTC) of hot sump walls in connection with the gas turbine engine of FIG. 1.
- (9) In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. The figures are not substantially to scale.

## DETAILED DESCRIPTION

- (10) “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc., may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, or (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.
- (11) As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” object, as used herein, refers to one or more of that object. The terms “a” (or “an”), “one or more”, and “at least one” are used interchangeably herein. Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., the same entity or object. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

(12) As used herein, unless otherwise stated, the term “above” describes the relationship of two parts relative to Earth. A first part is above a second part if the second part has at least one part between Earth and the first part. Likewise, as used herein, a first part is “below” a second part when the first part is closer to the Earth than the second part. As noted above, a first part can be above or below a second part with one or more of: other parts therebetween, without other parts therebetween, with the first and second parts touching, or without the first and second parts being in direct contact with one another.

(13) As used in this application, stating that any part (e.g., a layer, film, area, region, or plate) is in any way on (e.g., positioned on, located on, disposed on, or formed on, etc.) another part, indicates that the referenced part is either in contact with the other part, or that the referenced part is above the other part with one or more intermediate part(s) located therebetween.

(14) As used herein, connection references (e.g., attached, coupled, connected, and joined) may include intermediate members between the elements referenced by the connection reference and/or relative movement between those elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and/or in fixed relation to each other. As used herein, stating that any part is in “contact” with another part is defined to mean that there is no intermediate part between the two parts.

(15) Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc., are used herein without imputing or otherwise indicating any meaning of priority, physical order, arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly that might, for example, otherwise share a same name.

(16) Approximating language, as used herein throughout the specification and claims, is applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “about”, “approximately”, and “substantially”, are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value, or the precision of the methods or machines for constructing or manufacturing the components and/or systems. For example, the approximating language may refer to being within a ten percent margin.

(17) The terms “forward” and “aft” refer to relative positions within a gas turbine engine, pump, or vehicle, and refer to the normal operational attitude of the gas turbine engine, pump, or vehicle. For example, with regard to a gas turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust. Further, with regard to a pump, forward refers to a position closer to a pump inlet and aft refers to a position closer to an end of the pump opposite the inlet.

(18) The terms “upstream” and “downstream” refer to the relative direction with respect to a flow in a pathway. For example, with respect to a fluid flow, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(19) A turbine engine, also referred to herein as a gas turbine engine, is a type of internal combustion engine that uses atmospheric air as a moving fluid. The gas turbine engine is a turbofan engine that includes a fan section upstream of a low-pressure compressor section and a bypass airflow passage. During operation, a volume of air enters an inlet of the engine and passes into the fan section. A first portion of air is directed or routed into the bypass airflow passage, and a second portion of air is directed or routed into the low-pressure compressor section where the pressure of the air is increased. The pressure of the second portion of air is further increased as it is routed through a high-pressure compressor section and into a combustion chamber where the pressurized

air is mixed with fuel and burned to provide combustion gases. Subsequently, the combustion gases are routed through a high-pressure turbine section and a low-pressure turbine section, where a portion of thermal and/or kinetic energy from the combustion gases is extracted.

(20) The combustion gases are then routed through a jet exhaust nozzle section of the gas turbine engine to provide propulsive thrust. Simultaneously, the pressure of the first portion of air is substantially increased as the first portion of air is routed through the bypass airflow passage before it is exhausted from a fan nozzle exhaust section of the turbofan engine, also providing propulsive thrust. The combination of propulsive thrusts from the first and second portions of air determines an overall thrust that the turbofan engine generates to propel the aircraft in flight. In this sense, the power of the gas turbine engine can be defined as a product of the overall thrust and the cruising speed of the aircraft.

(21) The gas turbine engine includes one or more shafts which are mounted for rotation in several bearings, usually of the rolling-element type. The bearings are enclosed in enclosures known as sumps, which are pressurized and provided with an oil flow for lubrication and cooling. A sump is a container (e.g., a lower part of a crankcase of an internal-combustion engine) into which liquids can drain and be reused. For example, oil drains into the sump to avoid a build-up in the crankcase. The sump can provide multiple functions, including physical mounting of bearing races, location of oil and air seals, supply of lubricating oil to the bearings, scavenging spent oil, pressurization of the sump, and/or ventilation. In some examples, a sump housing includes numerous tubes, internal passages, and/or structural elements. For example, the sump housing incorporates a radial array of service tubes, which serve different functional purposes and have different internal flowpaths. In aeroengines, multiple structures such as bearings, seals and/or gear box components generate heat. As such, oil is supplied to lubricate and cool the components. In some examples, oil heat pickup is a heat load to coolers and one of the factors contributing to sizing of thermal management system (TMS) components. In particular, improved thermal management of sumps located in the gas turbine engine would permit reduction of heat loads.

(22) Methods and apparatus disclosed herein use oleophobic and/or oleophilic coatings to reduce heat loads on TMS components. In examples disclosed herein, oleophobic and/or oleophilic coatings are used at select locations in and/or on sumps to provide thermal management of the sumps. More specifically, oleophobic coatings with a high heat transfer coefficient (HTC) on internal walls of a sump can drive oil flow towards scavenge ports at an increased speed to enhance heat transfer from sump walls to the oil. Alternatively or additionally, oleophilic coatings on areas near the bearings and/or seals spread the oil and result in efficient transfer of heat from hot surface(s) near the bearings and/or seals to the oil. Furthermore, aero/oleo phobic coatings with low HTC on sump external walls (e.g., especially on hot sumps) can act as a heat shield and reduce the sump heat retained from hot surroundings.

(23) For the figures disclosed herein, identical numerals indicate the same elements throughout the figures. Referring now to the drawings, FIG. 1 is a schematic cross-sectional view of an example high-bypass turbofan-type gas turbine engine **110** (“turbofan engine **110**”). While the illustrated example is a high-bypass turbofan engine, the principles of the present disclosure are also applicable to other types of engines, such as low-bypass turbofans, turbojets, turboprops, propfans, etc. As shown in FIG. 1, the turbofan engine **110** defines a longitudinal or axial centerline axis **112** extending therethrough for reference. FIG. 1 also includes an annotated directional diagram with reference to an axial direction A, a circumferential direction C, and a radial direction R.

(24) In general, the turbofan engine **110** includes a core turbine **114** of gas turbine engine **110** disposed downstream from a fan section **116**. The core turbine **114** includes a substantially tubular outer casing **118** that defines an annular inlet **120**. The outer casing **118** can be formed from a single casing or multiple casings. The outer casing **118** encloses, in serial flow relationship, a compressor section having a booster or low-pressure compressor **122** (“LP compressor **122**”) and a high pressure compressor **124** (“HP compressor **124**”), a combustion section **126**, a turbine section

having a high pressure turbine **128** (“HP turbine **128**”) and a low-pressure turbine **130** (“LP turbine **130**”), and an exhaust section **132**. A high pressure shaft or spool **134** (“HP shaft **134**”) drivingly couples the HP turbine **128** and the HP compressor **124**. A low-pressure shaft or spool **136** (“LP shaft **136**”) drivingly couples the LP turbine **130** and the LP compressor **122**. The LP shaft **136** can also couple to a fan spool or shaft **138** of the fan section **116**. In some examples, the LP shaft **136** is coupled directly to the fan shaft **138** (e.g., a direct-drive configuration). In alternative configurations, the LP shaft **136** can couple to the fan shaft **138** via a reduction gear **139** (e.g., an indirect-drive or geared-drive configuration).

(25) As shown in FIG. **1**, the fan section **116** includes a plurality of fan blades **140** coupled to and extending radially outwardly from the fan shaft **138**. An annular fan casing or nacelle **142** circumferentially encloses the fan section **116** and/or at least a portion of the core turbine **114**. The nacelle **142** can be supported relative (e.g., partially supported, etc.) to the core turbine **114** by a plurality of circumferentially-spaced apart outlet guide vanes **144**. Furthermore, a downstream section **146** of the nacelle **142** can enclose an outer portion of the core turbine **114** to define a bypass airflow passage **148** therebetween.

(26) As illustrated in FIG. **1**, air **150** enters an inlet portion **152** of the turbofan engine **110** during operation thereof. A first portion **154** of the air **150** flows into the bypass airflow passage **148**, while a second portion **156** of the air **150** flows into the inlet **120** of the LP compressor **122**. One or more sequential stages of LP compressor stator vanes **170** and LP compressor rotor blades **172** coupled to the LP shaft **136** progressively compress the second portion **156** of the air **150** flowing through the LP compressor **122** en route to the HP compressor **124**. Next, one or more sequential stages of HP compressor stator vanes **174** and HP compressor rotor blades **176** coupled to the HP shaft **134** further compress the second portion **156** of the air **150** flowing through the HP compressor **124**. This provides compressed air **158** to the combustion section **126** where it mixes with fuel and burns to provide combustion gases **160**.

(27) The combustion gases **160** flow through the HP turbine **128** where one or more sequential stages of HP turbine stator vanes **166** and HP turbine rotor blades **168** coupled to the HP shaft **134** extract a first portion of kinetic and/or thermal energy therefrom. This energy extraction supports operation of the HP compressor **124**. The combustion gases **160** then flow through the LP turbine **130** where one or more sequential stages of LP turbine stator vanes **162** and LP turbine rotor blades **164** coupled to the LP shaft **136** extract a second portion of thermal and/or kinetic energy therefrom. This energy extraction causes the LP shaft **136** to rotate, thereby supporting operation of the LP compressor **122** and/or rotation of the fan shaft **138**. The combustion gases **160** then exit the core turbine **114** through the exhaust section **132** thereof. A turbine frame **161** with a fairing assembly is located between the HP turbine **128** and the LP turbine **130**. The turbine frame **161** acts as a supporting structure, connecting a high-pressure shaft's rear bearing with a turbine housing **163** and forming an aerodynamic transition duct between the HP turbine **128** and the LP turbine **130**. Fairings form a fluid pathway between the high-pressure and low-pressure turbines and can be formed using metallic castings (e.g., nickel-based cast metallic alloys, etc.).

(28) Along with the turbofan engine **110**, the core turbine **114** serves a similar purpose and is exposed to a similar environment in land-based gas turbines, turbojet engines in which the ratio of the first portion **154** of the air **150** to the second portion **156** of the air **150** is less than that of a turbofan, and unducted fan engines in which the fan section **116** is devoid of the nacelle **142**. In each of the turbofan, turbojet, and unducted engines, a speed reduction device (e.g., the reduction gear **139**) can be included between any shafts and spools. For example, the reduction gear **139** is disposed between the LP shaft **136** and the fan shaft **138** of the fan section **116**.

(29) As described above with respect to FIG. **1**, the turbine frame **161** is located between the HP turbine **128** and the LP turbine **130** to connect the high-pressure shaft's rear bearing with the turbine housing **163** and form an aerodynamic transition duct between the HP turbine **128** and the LP turbine **130**. As such, air flows through the turbine frame **161** between the HP turbine **128** and the

LP turbine **130**.

(30) In FIG. **1**, the gas turbine engine **110** includes a first sump **178** and a second sump **180**, which include cavities that contain oil. The oil of the first sump **178** and the second sump **180** lubricate and cool the components of the gas turbine engine **110**, including the bearings and rotating components associated with the HP shaft **134**, the LP shaft **136** and the fan shaft **138**. In FIG. **1**, the first sump **178** is associated with the fan shaft **138** and the second sump **180** is disposed in the LP shaft **136**. It should be appreciated that the gas turbine engine **110** can include sumps in addition to the first sump **178** and the second sump **180** (e.g., one or more other sumps associated with the LP shaft **136**, one or more other sumps associated with the fan shaft **138**, one or more sumps associated with the HP shaft **134**, etc.).

(31) FIG. **2A** illustrates an example bearing sump system **200** positioned in the gas turbine engine **110** of FIG. **1**. The example bearing sump system **200** can be a wet-sump lubrication system or a dry-sump lubrication system. A wet-sump lubrication system is generally used in aviation-based gas turbine engines (e.g., as opposed to a dry-sump lubrication system). In a wet-sump lubrication system, sump elements are close to hot regions of the gas turbine engine **110**. Engine sump systems (e.g., such as bearing sump system **200**) contain oil used to lubricate and cool gas turbine engine **110** components, such as bearings used to support the spools of the gas turbine engine **110**. For example, lubrication oil is stored in the engine cavities. Further increasing the shaft speed of engines results in larger oil requirements of the gas turbine engine **110**.

(32) To ensure continued operation of the gas turbine engine **110** and to conserve oil, the oil present in the bearing sump system **200** is separated from air entering the gas turbine engine **110**. In the example of FIG. **2A**, the oil is distributed to the bearing sump system **200** from an oil jet **202**. For example, the oil is provided directly from the oil jet **202** to one or more heat-generating elements **204** (e.g., metal sleeves encircling the rotating components of the gas turbine engine **110**, particularly the heat-generating elements **204** that can include bearing housing and/or seal runners, etc.) in connection with a rotating shaft **203**. The bearing sump system **200** includes an example air seal **205** (e.g., sump air housing) and an example oil seal **206** to prevent oil leakage from the bearing sump system **200**. An example first cavity **208** includes regions of the bearing sump system **200** at which oil is ejected from the oil jet **202**, while an example second cavity **210** includes injection of compressed air using an example pressurizing port **212**. In some examples, the first cavity **208** is bounded by heat generating element(s) **204** (e.g., bearings) and an internal wall **232** of the sump. In some examples, the second cavity **210** is bounded by the air seal **205** and an external wall **234** of the sump. For example, the second cavity **210** is positioned between the air seal **205** and the oil seal **206** and can be pressurized by air ejectors (e.g., eighth-stage air ejectors, not shown), such that the pressure in the second cavity **210** is greater than the pressure in the first cavity **208** of the bearing sump system **200**.

(33) As air (e.g., bleed air from a compressor stage) flows from the second cavity **210** and across the oil seal **206**, the oil is prevented from leaking across the oil seal **206**. Furthermore, if oil does escape the first cavity **208**, the pressure of the air coming from the second cavity **210** contains the escaped oil on the other side of the oil seal **206**. Subsequently, scavenge oil is drawn from the bearing sump system **200** into a pump (not shown) via an example oil drain **214**. The oil can be circulated using pumps (e.g., driven by rotation of the gas turbine engine **110**), with one pump used to supply the oil and another pump used to scavenge the oil. Pump(s) used for oil scavenging can include a higher capacity to prevent oil from accumulating in the bearing sump system **200**. In some examples, oil extracted from the oil drain **214** can be disposed of overboard or returned to an oil tank. The oil serves to lubricate the bearings and gears of the gas turbine engine **110** while also removing heat generated by the engine components.

(34) In the example of FIG. **2A**, the bearing sump system **200** includes a sump vent **218** in connection with the first cavity **208** and a cavity drain **220** in connection with the air seal **205** enclosing the second cavity **210**. The first cavity **208** of the bearing sump system **200** surrounding



the rotating shaft **203** includes an example windback seal **222** to prevent oil migration from the first cavity **208** as part of shaft sealing. Additionally, an example chopper **224** provides grooves to create a counter-pressure with the rotating shaft **203**, further reducing oil leakage from the first cavity **208**. Higher mechanical rotor speeds place a higher burden on the oil system (not shown) to lubricate and cool the rotating components. Methods and apparatus disclosed herein permit for sump system-based heat load management using oleophilic and/or oleophobic coatings, which are described in more detail in connection with FIG. 2B. For example, an oleophobic coating **228** with a high heat transfer coefficient (HTC) can be added to the internal walls (e.g., an internal wall **232**) of the bearing sump system **200** (e.g., enclosing the first cavity **208**), driving the oil flow originating from the oil jet **202** towards the oil drain **214**, resulting in an enhanced transfer of heat from the sump's first cavity **208** walls to the oil. Conversely, an example oleophilic coating **226** on areas near heat-generating elements (e.g., bearings, seals, etc.) will cause the oil to spread and result in efficient transfer of heat from hot surfaces (e.g., side faces of cage, carbon seal runner, etc.) to the oil. In some examples, aero/oleo phobic coatings with a low heat transfer coefficient (HTC) on the sump's external walls (e.g., an external wall **234**) act as a heat shield and reduce sump-based heat pick up from hot surroundings (e.g., in the first cavity **208**). As such, examples disclosed herein introduce novel sump wall surface engineering with a combination of oil dispersion oleophilic surfaces and oil contraction/oil skidding phobic surfaces. In some examples, the surface engineering methodology (e.g., oleophilic/phobic deposition) disclosed herein can be defined for a sump depending on sump components. For example, oleophilic surface deposition near the bearing/heat-generating elements **204** permits efficient transfer of heat to oil, while phobic surface deposition on sump walls (e.g., inner walls of the oil seal **206** facing the first cavity **208**) reduces oil residence time, resulting in lower viscous heat generation. Additionally, oleophobic surface deposition on hot sump walls reduces coking.

(35) FIG. 2B illustrates an example schematic **250** of oleophilic and oleophobic coating(s) **226**, **228** applied to the bearing sump system **200** of FIG. 2A (e.g., including the oil seal **206** walls and the bearing/heat-generating elements **204**). For example, a surface **252** can be modified (e.g., using an oleophilic coating **226** on heat-generation element(s) **204**) to absorb nonpolar liquids (e.g., oil) or modified (e.g., using an oleophobic coating **228** on the oil seal **206**) to repel nonpolar liquids (e.g., oil). As shown in the example of FIG. 2B, oleophilic and oleophobic surfaces can be characterized based on a contact angle of an example oil droplet **255** with the oleophilic and oleophobic surface. In the example of the oleophilic coating **226** applied to the surface **252**, the oil droplet **255** spreads out on the oleophilic coating **226**, resulting in a minimum contact angle **258** (e.g., less than 5 degrees). In the example of the oleophobic coating **228** applied to the surface **252**, the oil droplet **255** is repelled by the oleophobic coating **228**, resulting in a maximum contact angle **260** (e.g., greater than 90 degrees). In examples disclosed herein, the use of oleophilic and oleophobic coating(s) **226**, **228** for thermal management of bearings and/or sumps results in lubrication oil durability and the improvement of bearing service life, with an up to 30% improvement in heat management. As such, improved reliability of heat generating elements (e.g., bearings) through a longer service life contributes to a significant weight reduction with the use of more compact heat exchangers. For example, depending on the chemistry of the coatings used, oleophobic coatings can increase the HTC, allowing improved efficiency of heat exchangers in the gas turbine engine **110**.

(36) In the example of FIG. 2A, heat-generating elements **204** can include bearing housing and/or seal runners. Using oleophilic-based coatings (e.g., graphite, graphene, and/or carbon nanotube-based sponges) as disclosed herein (e.g., oleophilic coating **226**) results in near zero oil-based contact angles driven by very high oil dispersion. Increases in oil dispersion using oleophilic coatings contributes to high thermal conductivity (K) (e.g., K=3,500 Watts per meter-Kelvin (W/mK), up to an 80% increase in thermal conductivity). Furthermore, application of oleophilic-based coatings near heat generating elements contributes to higher surface oil contact for effective

heat extraction (e.g., a dispersion of approximately 200-300%). As such, a reduction in the temperature of heat-generating elements **204** (e.g., bearing housing, etc.) is further achieved based on the application of the oleophilic coating (e.g., a 5% reduction in metal temperatures). As a result, oil provided via the oil jet **202** protects and prolongs the life of the machined parts (e.g., preventing metal from touching other metallic surfaces while in motion).

(37) In some examples, oleophobic coating **228** can be applied to cold sumps and/or hot sumps (e.g., internal and/or external sump walls surrounding the first cavity **208**), as described in more detail in connection with FIGS. **4** and **5**. For example, hot and cold sumps can be identified based on a temperature of air in the pressurizing port of the sump ( $T_{sub.przn}$ ) (e.g., pressurizing port **212**) and an internal sump temperature ( $T_{sub.sump}$ ), where a cold sump can be defined based on a temperature ratio of  $T_{sub.sump}/T_{sub.przn} \geq 1$  and a hot sump can be defined based on a temperature ratio of  $T_{sub.sump}/T_{sub.przn} < 1$ . Using examples disclosed herein, oleophobic coating of a cold sump (e.g., internal wall **232** surfaces of a cold sump) can contribute to an increase of ~7% heat dissipation (e.g., using oleophobic coating including perfluoroalkoxy alkane, perfluoroalkyl silane functionalized ceramics, etc.). Overall, an oleophobic coating on a cold sump results in very low oil dispersion (e.g., a contact angle of greater than 90 degrees), reduces the residence time of oil (e.g., by up to 25%), and contributes to a reduction in viscous heat generation (e.g., by up to 27%). Heat dissipation also increases due to the use of an oleophobic coating with a high heat transfer coefficient (HTC) (e.g., heat dissipation increase by 30-80%).

(38) Likewise, an oleophobic coating in a hot sump can include a reduction of sump wall heating by ~20% (e.g., using oleophobic coating materials such as polybenzimidazole or carbon-based materials that are fluoro-modified or nano/micro-textured, etc.). For example, the oleophobic coating **228** on internal and external sump wall **232**, **234** surfaces results in very low oil dispersion (e.g., with a contact angle of greater than 90 degrees), reduces residence time of oil (e.g., by 25%), and contributes to a reduction in the generation of viscous heat (e.g., by 27%). Furthermore, insulation of the sump walls (e.g., external and internal wall **232** surfaces) using an oleophobic coating with a low HTC results in decreased sump wall heating. Overall, the surface treatment of cold sumps (e.g., internal wall **232** surfaces) and/or hot sumps (e.g., internal wall **232** and external wall **234** surfaces) results in a significant reduction of viscous heat generation (e.g., by approximately 30%).

(39) FIG. **3A** illustrates example heat dissipation diagram(s) **300**, **350** resulting from oleophobic-coated sump walls. In some examples, coating locations within the bearing sump system **200** can be determined based on the location of the sump in the gas turbine engine **110** (FIG. **1**) (e.g., hot sump, cold sump, vented sump, non-vented sump, etc.). For example, oleophobic coating **228** on one side of a sump wall (e.g., between the first cavity **208** and the oil seal **206** of FIG. **2A**) results in heat convection (e.g., heat ( $Q$ ) dissipation), from an internal region **306** of the bearing sump system **200**, through a sump wall **304**, and towards an external region **302** of the bearing sump system **200** (e.g., towards the second cavity **210** of FIG. **2A**). As shown in the example of FIG. **3A**, a difference in a temperature of a sump's internal region ( $T_{sub.S}$ ) **310** and a temperature of a sump's external region ( $T_{sub.P}$ ) **312**, corresponding to an area of pressurization (e.g., including the pressurizing port **212** of FIG. **2A**), results in  $T_{sub.S} > T_{sub.P}$ , due to a direction **314** of the heat dissipation from the sump's internal region **306** to the sump's external region **302**. Conversely, oleophobic coating **228** on both sides of the sump wall **304**, as shown in heat dissipation diagram **350**, results in insulation rather than heat convection, where the temperature of the sump's internal region ( $T_{sub.S}$ ) **310** is less than the temperature of the sump's external region ( $T_{sub.P}$ ) **312** ( $T_{sub.S} < T_{sub.P}$ ). For example, heat dissipation **352** is retained within the sump's internal region **310** and/or the sump's external region **302**. In the example of the heat dissipation diagram **300**, an initial baseline of heat dissipation (e.g., 134 British thermal units per minute (BTU/min)) increases as a result of the use of oleophobic coating **228** on the sump wall **304** (e.g., 144 BTU/min), contributing to an approximately 7% increase in heat dissipation when using coatings with a high

HTC. In the example of the heat dissipation diagram **350**, an initial heat load baseline on the sump wall **304** (e.g., 184 BTU/min) is decreased as a result of oleophobic coatings **228** on the sump walls **304** (e.g., 148 BTU/min), contributing to an approximately 20% reduction in heat pick up.

(40) FIG. **3B** illustrates an example diagram **375** of oleophilic coating **226** as shown in an example cross-section of the gas turbine engine **110** of FIG. **1**. For example, the diagram **375** includes oleophilic high HTC coating **226** in oil wetted areas of the gas turbine engine **110**, including a first location **378** and a second location **380**. The first location **378** and the second location **380** baseline temperatures (e.g., base metal temperatures without coating) decrease as a result of oleophilic coating **226**. For example, the first location **378** temperature decreases from a baseline of 384 degrees Fahrenheit (F) to 368 degrees F. (e.g., a change of 16 degrees F.), whereas the second location **380** temperature decreases from a baseline of 283 degrees F. to 273 degrees F. (e.g., a change of 10 degrees F.), contributing to reduced temperatures of the gas turbine engine **110** metal components following oleophilic-based coatings applied in the first location **378** and the second location **380**.

(41) FIG. **4** illustrates an example diagram **400** showing oleophobic coating **228** with high heat transfer coefficient (HTC) applied to sump walls and oleophilic coating **226** applied to heat-generating elements (e.g., bearing housing, seal runners, etc.) in connection with the gas turbine engine **110** of FIG. **1**. For example, oleophilic coating **226** near heat-generating elements (e.g., the heat-generating elements **204** of FIG. **2A**) spreads the oil more efficiently. In some examples, the oleophilic coating **226** used for gas turbine engine components can include carbon-based oleophilic materials with high thermal conductivity (e.g.,  $K=3500 \text{ W/mK}$ ), the high thermal conductivity assisting in the effective redistribution of heat. In the example of FIG. **4**, the oleophobic coating **228** is applied between the sump wall **304** and the sump's internal region **306**. The location of the oleophobic coating **228** in the gas turbine engine **110** is shown with respect to the scavenge oil port (e.g., oil drain **214** of FIG. **2A**). Oleophobic coatings with a high HTC decrease the residence time of oil on sump internal wall(s) (e.g., the sump internal wall(s) **232** of FIG. **2A**) and enhance heat transfer from sump walls to the oil. As shown in diagram **450**, the oleophobic coating **228** results in the dissipation of heat towards the sump's external region **302**, such that temperature in the external region **302** is lower than the temperature in the internal region **306** (e.g., shown using a relationship **452**, where  $T_{\text{sub.out}} \ll T_{\text{sub.in}}$ ), as described in connection with FIG. **3A**.

(42) FIG. **5** illustrates an example diagram **500** showing the oleophobic coating **228** with a low heat transfer coefficient (HTC) applied to hot sump walls in connection with the gas turbine engine **110** of FIG. **1**. In the example of FIG. **5**, the oleophobic coating **228** is applied to both sides of the sump wall **304** (e.g., on a sump wall **228a** facing the sump's internal region **306** and on a sump wall **228b** facing the sump's external region **302**). As such, heat dissipation occurs from the sump's external region **302** to the sump's internal region **306**, as shown in connection with diagram **550** (e.g., where  $T_{\text{sub.in}} \ll T_{\text{sub.out}}$  in accordance with relationship **552**). In some examples, prolonged carbon-based or dust-based deposits on the sumps affect sump heat transfer. However, the introduction of oleophobic coating **228** reduces such deposition. In some examples, oleophobic coating(s) **228** and their corresponding maximum operating temperatures can include perfluoroalkyl alkane ( $\sim 500^\circ \text{ F.}$ ), perfluoroalkyl silane functionalized ceramic oxides ( $\sim 600^\circ \text{ F.}$ ), fluoro functionalized polymethylsilsesquioxane ( $\sim 450^\circ \text{ F.}$ ), and/or polybenzimidazole based compositions ( $\sim 900^\circ \text{ F.}$ ). In some examples, oleophilic coating(s) **226** and their corresponding maximum operating temperatures can include functionalized polymeric sponges (e.g., melamine-formaldehyde based sponge) ( $\sim 530^\circ \text{ F.}$ ), carbon (e.g., graphite ( $\sim 1000^\circ \text{ F.}$ ), graphene ( $\sim 1650^\circ \text{ F.}$ ), carbon nanotube (CNT) ( $\sim 1800^\circ \text{ F.}$ )) based sponges, and/or cellulosic fibers ( $\sim 400^\circ \text{ F.}$ ). In some examples, the oleophobic and oleophilic chemistries can be applied to a smooth or textured surface, the application on textured surfaces enhancing the effect of the chemistry (e.g., increasing or decreasing the contact angle), whereas re-entrant and/or inverse trapezoidal textures can help with improving oleophobicity.

(43) From the foregoing, it can be appreciated that oleophobic and/or oleophilic coatings can be used to reduce heat loads on gas turbine engine thermal management system (TMS) components. In examples disclosed herein, oleophobic coatings with a high heat transfer coefficient (HTC) on sump internal walls can drive the oil flow towards scavenge ports in a faster manner and enhance heat transfer from sump walls to oil. In examples disclosed herein, oleophilic coatings on areas near the bearings and/or seals spread the oil and result in efficient transfer of heat from a hot surface to the oil. Residence time of oil on the sump internal walls can be reduced, improving overall efficiency. Furthermore, coating of bearings and/or sumps results in lubrication oil durability and the improvement of bearing service life, with an up to 30% improvement in heat management. As such, improved reliability of heat generating elements (e.g., bearings) through a longer service life contributes to a significant weight reduction with the use of more compact heat exchangers. Increased heat loads resulting from changes to gas turbine engine components (e.g., changes in the reduction gear box, presence of additional bearings, higher high-pressure and/or low-pressure turbine speeds, higher air pressurization temperatures, etc.) can be mitigated using the oleophobic and/or oleophilic coatings disclosed herein.

(44) The following claims are hereby incorporated into this Detailed Description by this reference. Although certain example systems, methods, apparatus, and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all systems, methods, apparatus, and articles of manufacture fairly falling within the scope of the claims of this patent.

(45) Example oleophilic and oleophobic coatings for thermal management of sumps are disclosed herein. Further aspects of the present disclosure are provided by the subject matter of the following clauses.

(46) A method to reduce heat load in a gas turbine engine, the method comprising applying an oleophobic coating to an internal wall of a sump, the sump located in proximity to a heat generating element of the gas turbine engine and applying an oleophilic coating to the heat generating element of the gas turbine engine, the heat generating element positioned in a cavity of the sump.

(47) The method of any preceding clause, wherein the heat generating element includes at least one of a bearing housing or a seal runner.

(48) The method of any preceding clause, wherein the internal wall of the sump is located within the cavity of the sump, the cavity in connection with an oil drain.

(49) The method of any preceding clause, wherein the heat generating element receives oil ejected from an oil jet located in the cavity of the sump.

(50) The method of any preceding clause, wherein the oleophilic coating on the heat generating element lowers a temperature of a metal of the heat generating element from a baseline temperature.

(51) The method of any preceding clause, further including applying the oleophobic coating to an external wall of the sump to lower heating of the external wall.

(52) The method of any preceding clause, further including applying the oleophobic coating to a hot sump, the oleophobic coating including a low heat transfer coefficient.

(53) A sump of a gas turbine engine, the sump comprising a heat generating element and an internal wall of the sump forming a first cavity, the heat generating element including an oleophilic coating and an air seal and an external wall of the sump forming a second cavity, at least one of the internal wall of the sump or the external wall of the sump including an oleophobic coating.

(54) The sump of any preceding clause, wherein the heat generating element includes at least one of a bearing housing or a seal runner.

(55) The sump of any preceding clause, wherein the oleophobic coating applied to the internal wall of the sump includes a low heat transfer coefficient.

(56) The sump of any preceding clause, wherein the oleophobic coating applied to the external wall of the sump includes a high heat transfer coefficient.

- (57) The sump of any preceding clause, wherein the heat generating element receives an ejection of oil from an oil jet.
- (58) The sump of any preceding clause, wherein the oleophilic coating includes at least one of graphite, graphene, or a carbon nanotube-based sponge.
- (59) The sump of any preceding clause, wherein oleophobic coating of a cold sump includes coating of the internal wall of the sump.
- (60) The sump of any preceding clause, wherein in a cold sump a ratio of (1) an internal sump temperature to (2) a temperature of air in a pressurizing port of the sump is greater than or equal to one.
- (61) The sump of any preceding clause, wherein oleophobic coating of a hot sump includes coating of the internal wall of the sump and the external wall of the sump.
- (62) The sump of any preceding clause, wherein in a hot sump the ratio of (1) the internal sump temperature to (2) the temperature of air in the pressurizing port of the sump is less than one.
- (63) The sump of any preceding clause, wherein the oleophobic coating includes a perfluoroalkyl alkane, perfluoroalkyl silane functionalized ceramic oxide, fluoro functionalized polymethylsilsequioxane, or a polybenzimidazole-based composition.
- (64) The sump of any preceding clause, wherein the oleophilic coating includes a functionalized polymeric sponge, carbon, graphene, a carbon nanotube-based sponge, or cellulosic fibers.
- (65) A sump system of a gas turbine engine, the sump system comprising an oleophilic coating applied to a heat generating element of the sump system, the heat generating element at least one of a bearing housing or a seal runner, and an oleophobic coating applied to an internal wall of a sump surrounding the heat generating element.
- (66) The sump system of any preceding clause, wherein the sump system is a cold sump system or a hot sump system, the oleophobic coating applied based on positioning of the sump system in the gas turbine engine.
- (67) The sump system of any preceding clause, wherein oleophobic coating of the hot sump system includes coating of the internal wall of the sump and an external wall of the sump.
- (68) The sump system of any preceding clause, wherein the oleophobic coating applied to the external wall of the sump includes a high heat transfer coefficient.
- (69) The sump system of any preceding clause, wherein the oleophobic coating applied to the internal wall of the sump includes a low heat transfer coefficient.

## Claims

1. A method to reduce heat load in a gas turbine engine, the method comprising: applying an oleophobic coating to an internal wall of a sump, the sump located in proximity to a heat generating element of the gas turbine engine; and applying an oleophilic coating to the heat generating element of the gas turbine engine.
2. The method of claim 1, wherein a heat generating element includes at least one of a bearing housing or a seal runner.
3. The method of claim 1, wherein the internal wall of the sump is located within a cavity of the sump, the cavity in connection with an oil drain.
4. The method of claim 3, wherein the heat generating element receives oil ejected from an oil jet located in the cavity of the sump.
5. The method of claim 1, wherein the oleophilic coating on the heat generating element lowers a temperature of a metal of the heat generating element from a baseline temperature.
6. The method of claim 1, further including applying the oleophobic coating to an external wall of the sump to lower heating of the external wall.
7. The method of claim 6, further including applying the oleophobic coating to a hot sump, the oleophobic coating including a low heat transfer coefficient.

8. A sump of a gas turbine engine, the sump comprising: a heat generating element and an internal wall of the sump forming a first cavity, the heat generating element including an oleophilic coating, wherein an oleophobic coating applied to the internal wall of the sump includes a low heat transfer coefficient.
  9. The sump of claim 8, wherein the heat generating element includes at least one of a bearing housing or a seal runner.
  10. The sump of claim 8, wherein the oleophobic coating applied to an external wall of the sump includes a high heat transfer coefficient.
  11. The sump of claim 8, wherein the heat generating element receives an ejection of oil from an oil jet.
  12. The sump of claim 8, wherein the oleophilic coating includes at least one of graphite, graphene, or a carbon nanotube-based sponge.
  13. The sump of claim 8, wherein the oleophobic coating of a cold sump includes coating of the internal wall of the sump.
  14. The sump of claim 8, wherein the oleophobic coating of a hot sump includes coating of the internal wall of the sump and an external wall of the sump.
  15. A sump system of a gas turbine engine, the sump system comprising: an oleophilic coating applied to a heat generating element of the sump system; and an oleophobic coating applied to an internal wall of a sump surrounding the heat generating element.
  16. The sump system of claim 15, wherein the sump system is a cold sump system or a hot sump system, the oleophobic coating applied based on positioning of the sump system in the gas turbine engine.
  17. The sump system of claim 16, wherein oleophobic coating of the hot sump system includes coating of the internal wall of the sump and an external wall of the sump.
  18. The sump system of claim 17, wherein the oleophobic coating applied to the external wall of the sump includes a high heat transfer coefficient.
  19. The sump system of claim 15, wherein the oleophobic coating applied to the internal wall of the sump includes a low heat transfer coefficient.
-