

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12393226
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Heath; Hamish

Detachable modular console for aircraft cockpit

Abstract

Disclosed herein is a detachable modular console for an aircraft cockpit. The detachable modular console comprises a housing configured to receive one or more modular electronic components, a plurality of hardpoint fasteners for detachably fastening the housing to hardpoints in a floor of the aircraft cockpit, a leveling foot to engage the floor to stabilize the console and a display screen supported by the housing. The detachable modular console can house various modular electronic components. A rail enables rapid replacement of other electronic components. The hardpoints enable the console to be secured to the floor of the cockpit.

Inventors:	Heath; Hamish (Monavale, AU)
Applicant:	COULSON AVIATION AUSTRALIA PTY LTD (Bankstown Aerodrome, AU); COULSON AIRCANE LTD. (Port Alberni, CA)
Family ID:	1000008765107
Assignee:	COULSON AVIATION AUSTRALIA PTY LTD (Bankstown Aerodrome, AU); COULSON AIRCANE LTD. (Port Alberni, CA)
Appl. No.:	18/266474
Filed (or PCT Filed):	December 09, 2021
PCT No.:	PCT/CA2021/051765
PCT Pub. No.:	WO2022/120483
PCT Pub. Date:	June 16, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240043136 A1	Feb. 08, 2024

Related U.S. Application Data

us-provisional-application US 63124045 20201210

Publication Classification

Int. Cl.: G06F1/16 (20060101); B64D43/00 (20060101); H05K5/02 (20060101)

U.S. Cl.:

CPC G06F1/1628 (20130101); B64D43/00 (20130101); H05K5/0234 (20130101)

Field of Classification Search

CPC: G06F (1/1628); B64D (43/00); H05K (5/0234)

USPC: 361/600

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11483942	12/2021	Lawhon	N/A	H05K 7/1434
2010/0140397	12/2009	Van Wassenhove	244/118.5	B64D 11/0689
2011/0270469	12/2010	Bopp	361/679.01	G06F 1/163
2012/0075120	12/2011	Barbieri	340/946	B64D 43/00
2014/0230641	12/2013	Isola	89/37.17	F41A 23/24
2014/0291444	12/2013	Baudry	244/118.5	B64D 11/0689
2018/0009532	12/2017	Cazals	N/A	B64D 11/0602
2021/0039805	12/2020	Tentinger	N/A	H05K 7/1412
2021/0235593	12/2020	Bousquet	N/A	H05K 7/1412
2022/0017204	12/2021	Helou, Jr.	N/A	B64C 1/22

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2010069923	12/2009	WO	N/A

Primary Examiner: Feng; Zhengfu J

Attorney, Agent or Firm: Flaster Greenberg P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is the 371 National Stage of International Application No. PCT/CA2021/051765, filed Dec. 9, 2021, which claims priority to U.S. Provisional Patent Application No. 63/124,045, filed Dec. 10, 2020, the disclosures of each of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

(1) The present invention relates generally to aircraft cockpits and, more particularly, to consoles for aircraft cockpits.

BACKGROUND

(2) For multi-role aircraft it is sometimes desirable to change the electronic equipment in the aircraft cockpit to provide the crew with the electronic equipment they require for a particular mission. To install or remove electronic components from an aircraft cockpit may be time-consuming and require specialized technicians to ensure that the components are properly and safely installed.

(3) There is accordingly a need in the aircraft industry for a new or improved console that would enable rapid and efficient changing of onboard electronic components.

SUMMARY

(4) The following presents a simplified summary of some aspects or embodiments of the invention in order to provide a basic understanding of the invention. This summary is not an extensive overview of the invention. It is not intended to identify key or critical elements of the invention or to delineate the scope of the invention. Its sole purpose is to present some embodiments of the invention in a simplified form as a prelude to the more detailed description that is presented later.

(5) The present specification discloses a detachable modular console for an aircraft cockpit. The detachable modular console comprises a housing configured to receive one or more modular electronic components, a plurality of hardpoint fasteners for detachably fastening the housing to hardpoints in a floor of the aircraft cockpit, a leveling foot to engage the floor to stabilize the console and a display screen supported by the housing. The detachable modular console can house various modular electronic components. A rail enables rapid replacement of other electronic components. The hardpoints enable the console to be secured to the floor of the cockpit.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) These and other features of the disclosure will become more apparent from the description in which reference is made to the following appended drawings.

(2) FIG. 1 is an isometric view of a detachable modular console for an aircraft cockpit in accordance with an embodiment of the present invention.

(3) FIG. 2 is a side view of the console.

(4) FIG. 3 is a front view of the console.

(5) FIG. 4 is a rear view of the console.

(6) FIG. 5 is a front isometric view of the console.

(7) FIG. 6 is a bottom isometric view of the console.

(8) FIG. 7 is a rear isometric view of the console.

DETAILED DESCRIPTION OF EMBODIMENTS

(9) The following detailed description contains, for the purposes of explanation, numerous specific embodiments, implementations, examples and details in order to provide a thorough understanding of the invention. It is apparent, however, that the embodiments may be practiced without these specific details or with an equivalent arrangement. In other instances, some well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring the embodiments of the invention. The description should in no way be limited to the illustrative implementations, drawings, and techniques illustrated below, including the exemplary designs and implementations illustrated and described herein, but may be modified within the scope of the appended claims along with their full scope of equivalents.

(10) In the embodiment of the present invention illustrated in FIGS. 1-7, a detachable modular

console is designed to be detachably mounted to the floor of an aircraft cockpit, such as for example to the floor of a helicopter cockpit. Although the console has been designed initially for use in a helicopter, the console may also be used in a fixed-wing aircraft. The console which is generally denoted by reference numeral **10** includes a housing **12** configured to receive one or more modular electronic components **14**. The housing has a top surface **13**, a front face **15**, and a rear face **17** that is spaced-apart and generally parallel to the front face. The one or more modular electronic components **14** are accessible through the front face, i.e. to enable the pilot or co-pilot to select buttons, toggles, switches or other controls of the one or more modular electric components. (11) The housing also has a pair of side faces **26** that are spaced-apart and parallel to each other. In this embodiment, the housing **12** has a height greater than its width. In this embodiment, the housing has a depth (length) greater than the height.

(12) The detachable modular console **10** includes a plurality of hardpoint fasteners **16** for detachably fastening the housing to hardpoints in a floor of the aircraft cockpit, i.e. hardpoints that are secured to the floor of the aircraft cockpit. There are three hardpoint fasteners in the illustrated embodiment although it will be appreciated that the number of hardpoint fasteners may be varied. In this specific example implementation, the hardpoint fasteners are threaded studs. Preferably, the hardpoint fasteners are three 12-jaw threaded studs. Any other suitable fastener may be used depending on the hardpoints available in the floor of the aircraft cockpit.

(13) The detachable modular console **10** as illustrated by way of example in FIGS. **1-7** includes a leveling foot **18** extending from a bottom of the housing to engage the floor to stabilize the console and to minimize vibrations in the console. The leveling foot **18** has a threaded rod that is threadedly attached to a correspondingly threaded socket or bore in a flange-like extension **24** of the housing **12**. The leveling foot **18** is adjusted by rotating the threaded rod relative to the bore. The leveling foot **18** may be made of, or may include, an elastomeric or other resilient material to absorb vibrations. The flange-like extension **24** in this particular embodiment extends laterally from a bottom face of the housing while also extending forwardly from a corner of the bottom face and the rear face. As shown in the figures, in this embodiment, this flange-like extension **24** diverges outwardly toward the front face **15** to form a laterally protruding angled plate having a rounded forward end. This flange-like extension **24** supports both the leveling foot **18** and one of the two forward hardpoint fasteners **16** as shown by way of example in the figures. The flange-like extension **24** extends laterally from a bottom of the left side of the housing **12**. This flange-like extension **24** provides a means to offset or counterbalance the asymmetrically mounted display screen **20**.

(14) The detachable modular console **10** includes a display screen **20**, e.g. a touch screen, supported by the housing **12**. A movable support arm **22** is connected to the housing **12** and to the display screen **20** to support the display screen **20** above the housing **12**. The display screen **20** is designed to be visible by the pilot or co-pilot when seated in the aircraft cockpit. In the illustrated embodiment, the movable support arm **22** extends from a top surface **13** of the housing **12** from an attachment point that is near the front face **15** of the housing **12**. In the specific embodiment, this attachment point is closer to the front face **15** of the housing **12** than to a vertical midplane of the housing **12** (where the vertical midplane bisects the housing **12** lengthwise through its depth, i.e. the midplane divides the housing lengthwise in half from front to rear). In the illustrated embodiment, the attachment point is asymmetrically disposed on the housing **12**. For example, as shown in this embodiment, the attachment point is on the right side of the top surface **13** of the housing **12**. The display screen **20** in this embodiment extends forward such that a forward-most portion of the display screen protrudes beyond the plane defined by the front face of the housing. In this illustrated embodiment, the right-most portion of the display screen **20** protrudes beyond a right-side face of the housing.

(15) In the illustrated embodiment, the top surface **13** of the housing **12** is a solid top surface. The front face **15** is a partially open front face to enable access to the one or more electronic

components that are inserted into the housing **12**. The side faces **26** are partially open sides having generally X-shaped cross-braces **28** for structural support while permitting heat to dissipate from the one or more electronic components.

(16) The one or more electronic components **14** may comprise a mission computer providing an augmented reality mapping system, a video encoding device, and/or a multi-cellular downlink device. Other electronic components may be housed in the console. The housing comprises a Dzus rail to interchange the one or more modular electronic components.

(17) The console **10** illustrated has a housing **12** and hardpoint fasteners that are specifically designed in this particular example to mount into the existing hardpoints of a Bell **412** helicopter. Using existing hardpoints avoids the need to make any modifications to the airframe for installation of the console. In this specific example, the three fasteners are 12-jaw threaded studs (PN 33115), also known as 12-jaw stud fittings with threaded studs, to attach the console to three mounting positions (hardpoints) within the airframe. A tensioned levelling foot is then screwed down to the floor to minimize or attenuate vibrations. The tensioned levelling foot also enables rapid removal and installation of the console. As illustrated in FIG. 2, when viewed from the side, the leveling foot **18** is disposed between the two front hardpoint fasteners **16** and the rearward hardpoint fastener **16** along a depth of the housing from the front to the rear. Specifically, in this embodiment, the leveling foot **18** is disposed between the two front hardpoint fasteners **16** and the rearward hardpoint fastener **16** at a point between the front and rear hardpoint fasteners that is between halfway to three-quarters backward from the two front hardpoint fasteners in a depth-wise direction toward the rear hardpoint fastener.

(18) It will be appreciated that in other helicopters or other fixed-wing aircraft, the hardpoint fasteners may be spaced differently to fit the geometry of the hardpoints in any given aircraft cockpit. The illustrated console shown in the drawings is an integrated mission system that includes a touch screen interface for the operator, a mission computer, e.g. the Churchill navigation ARS-700 mission computer, video encoding and multi-cellular downlink. The mission console in this example implementation also interfaces with the Star Safire 380HDC gyro stabilized gimbal. The specific type of helicopter and the specific electronic components mentioned above are not meant to limit the invention but merely to illustrate one very specific example implementation.

(19) The operator (e.g. pilot or co-pilot) interfaces with the electronic components in the console via the touch screen display of the console and push button switches or other such human-machine interface elements that control the electronic component and systems.

(20) The console has been designed to be highly modular in order to allow for rapid changes of internal componentry. A Dzus rail has been utilised on the front of the console to enable the use of modular components. All the power and communication mount to configurable plates in the interior of the housing. The console has a common interface connector that allows for sensors to be easily changed without a complete redesign of the interface.

(21) It is to be understood that the singular forms “a”, “an” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a device” includes reference to one or more of such devices, i.e. that there is at least one device. The terms “comprising”, “having”, “including”, “entailing” and “containing”, or verb tense variants thereof, are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of examples or exemplary language (e.g. “such as”) is intended merely to better illustrate or describe embodiments of the invention and is not intended to limit the scope of the invention unless otherwise claimed.

(22) While several embodiments have been provided in the present disclosure, it should be understood that the disclosed systems and methods might be embodied in many other specific forms without departing from the scope of the present disclosure. The present examples are to be considered as illustrative and not restrictive, and the intention is not to be limited to the details

given herein. For example, the various elements or components may be combined or integrated in another system or certain features may be omitted, or not implemented.

(23) In addition, techniques, systems, subsystems, and methods described and illustrated in the various embodiments as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods without departing from the scope of the present disclosure. Other items shown or discussed as coupled or directly coupled or communicating with each other may be indirectly coupled or communicating through some interface, device, or intermediate component whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and could be made without departing from the inventive concept(s) disclosed herein.

Claims

1. A detachable modular console for an aircraft cockpit of an aircraft, the detachable modular console comprising: a housing configured to receive one or more modular electronic components, the housing having a front face through which the one or more modular electronic components are accessible; a plurality of hardpoint fasteners for detachably fastening the housing to hardpoints secured to a floor of the aircraft cockpit; a leveling foot extending from a bottom of the housing, the leveling foot being configured to engage the floor to stabilize the detachable modular console; and a display screen supported by the housing, wherein the display screen is visible to a pilot or co-pilot of the aircraft when sitting in the aircraft cockpit of the aircraft.
 2. The detachable modular console of claim 1, wherein the one or more electronic components comprises a mission computer providing an augmented reality mapping system.
 3. The detachable modular console of claim 1, wherein the one or more electronic components comprises a video encoding device.
 4. The detachable modular console of claim 1, wherein the one or more electronic components comprises multi-cellular downlink device.
 5. The detachable modular console of claim 1, wherein the housing comprises a Dzus rail to interchange the one or more modular electronic components.
 6. The detachable modular console of claim 1, comprising a movable support arm connected to the housing and to the display screen to support the display screen above the housing.
 7. The detachable modular console of claim 1, wherein the hardpoint fasteners are three 12-jaw threaded studs.
 8. The detachable modular console of claim 1, comprising a flange-like extension that extends laterally from a bottom of the housing.
 9. The detachable modular console of claim 1, comprising a flange-like extension that extends laterally from a bottom of a left side of the housing, and wherein the display screen is mounted to an attachment point on a right side of the housing.
 10. The detachable modular console of claim 9, wherein the flange-like extension receives the leveling foot.
 11. The detachable modular console of claim 10, wherein the flange-like extension diverges outwardly toward the front face of the housing to form a laterally protruding angled plate having a rounded forward end.
-