

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12395831
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Mohajeri; Shahram

---

### Dynamically generating application function-specific user endpoint identifiers

---

#### Abstract

In one example, the present disclosure describes a device, computer-readable medium, and method for dynamically generating an application function-specific user endpoint identifier. For instance, in one example, a method performed by a processing system including at least one processor includes receiving, from a network exposure function of a communications network, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application function residing externally to the communications network, querying a unified data repository for the application function-specific user endpoint identifier, determining, based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository, dynamically generating the application function-specific user endpoint identifier, and forwarding the application function-specific user identifier, as dynamically generated, to the network exposure function.

---

<b>Inventors:</b>	<b>Mohajeri; Shahram (Kirkland, WA)</b>
<b>Applicant:</b>	<b>AT&amp;T Intellectual Property I, L.P. (Atlanta, GA)</b>
<b>Family ID:</b>	<b>1000008764829</b>
<b>Assignee:</b>	<b>AT&amp;T Intellectual Property I, L.P. (Atlanta, GA)</b>
<b>Appl. No.:</b>	<b>18/059416</b>
<b>Filed:</b>	<b>November 28, 2022</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240179510 A1	May. 30, 2024

---

#### Publication Classification

**Int. Cl.:** H04W8/18 (20090101); H04W8/08 (20090101)

**U.S. Cl.:**

**CPC** H04W8/183 (20130101); H04W8/08 (20130101);

## Field of Classification Search

**CPC:** H04W (8/183); H04W (8/08)

**USPC:** 455/550.1; 455/418; 455/423; 455/435.1; 455/410

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
12273705	12/2024	Gundavelli	N/A	H04W 12/03
2022/0046752	12/2021	Lee	N/A	H04W 76/40
2023/0051733	12/2022	Shah	N/A	H04W 72/56
2023/0164641	12/2022	Purkayastha	370/331	H04W 36/0022

### OTHER PUBLICATIONS

Mohajeri et al., “Internet Protocol Version 4-to-Version 6 Redirect for Application Function-Specific User Endpoint Identifiers,” U.S. Appl. No. 18/059,418, filed Nov. 28, 2022, 30 pages. cited by applicant

---

*Primary Examiner:* Ly; Nghi H

---

## Background/Summary

(1) The present disclosure relates generally to digital privacy, and relates more particularly to devices, non-transitory computer-readable media, and methods for dynamically generating an application function-specific user endpoint identifier (UEId).

### BACKGROUND

(2) In the Third Generation Partnership Project (3GPP), each subscriber identity module (SIM) card may be allocated a unique identifier or UEId. For instance, in generations up to fourth generation (4G) mobile networks, the UEId may comprise an international mobile subscriber identity (IMSI); in fifth generation (5G) mobile networks, the UEId may comprise a subscription permanent identifier (SUPI) or a generic public subscription identifier (GPSI). An application function-specific UEId is like a GPSI in the form of an External Identifier (as opposed to a phone number, or MSISDN, form) that is generated for a device specifically for use with a particular application function. The use of different AF-specific UEIds in the form of External Identifiers (i.e., opaque identifiers) for different application functions has two main benefits: (1) AF-specific UEIds allows users to, if need be, avoid divulging their phone numbers (which are considered privacy-sensitive pieces of information) to application functions (i.e., such that the users are identified by the application functions in an anonymous manner); and (2) AF-specific UEIds prevent correlation and tracking of UEIds (and, thus, users) across applications.

### SUMMARY

- (3) In one example, the present disclosure describes a device, computer-readable medium, and method for dynamically generating an application function-specific user endpoint identifier. For instance, in one example, a method performed by a processing system including at least one processor includes receiving, from a network exposure function of a communications network, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application function residing externally to the communications network, querying a unified data repository for the application function-specific user endpoint identifier, determining, based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository, dynamically generating the application function-specific user endpoint identifier, and forwarding the application function-specific user identifier, as dynamically generated, to the network exposure function.
- (4) In another example, a non-transitory computer-readable medium stores instructions which, when executed by a processing system including at least one processor, cause the processing system to perform operations. The operations include receiving, from a network exposure function of a communications network, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application function residing externally to the communications network, querying a unified data repository for the application function-specific user endpoint identifier, determining, based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository, dynamically generating the application function-specific user endpoint identifier, and forwarding the application function-specific user identifier, as dynamically generated, to the network exposure function.
- (5) In another example, a system includes a processing system including at least one processor and a non-transitory computer-readable medium storing instructions which, when executed by the processing system, cause the processing system to perform operations. The operations include receiving, from a network exposure function of a communications network, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application function residing externally to the communications network, querying a unified data repository for the application function-specific user endpoint identifier, determining, based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository, dynamically generating the application function-specific user endpoint identifier, and forwarding the application function-specific user identifier, as dynamically generated, to the network exposure function.
- 

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The teachings of the present disclosure can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 illustrates an example system in which examples of the present disclosure for providing an application function-specific user endpoint identifier management function may operate;
- (3) FIG. 2 illustrates a call flow diagram that shows a more detailed view of the operations of the network exposure function, a binding support function, a unified data management element/application function-specific user endpoint identifier management function, and a unified data repository of FIG. 1;
- (4) FIG. 3 illustrates a flowchart of an example method for dynamically generating an application function-specific user endpoint identifier;
- (5) FIG. 4 illustrates call flow diagram that shows a view of operations of a user application, a mobile network operator portal, a basic service set, a unified data management element/application

function-specific user endpoint identifier management function, and a unified data repository; and (6) FIG. 5 depicts a high-level block diagram of a computing device specifically programmed to perform the functions described herein.

(7) To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures.

#### DETAILED DESCRIPTION

(8) In one example, the present disclosure provides a system, method, and non-transitory computer readable medium for dynamically generating an application function-specific user endpoint identifier (UEId). As discussed above, in the Third Generation Partnership Project (3GPP), each subscriber identity module (SIM) card may be allocated a unique identifier or UEId. For instance, in generations up to fourth generation (4G) mobile networks, the UEId may comprise an international mobile subscriber identity (IMSI); in fifth generation (5G) mobile networks, the UEId may comprise a subscription permanent identifier (SUPI) or a generic public subscription identifier (GPSI). An application function-specific UEId is like a GPSI in the form of an External Identifier (as opposed to a phone number, or MSISDN) that is generated for a device specifically for use with a particular application function. The use of different AF-specific UeIds in the form of External Identifiers (i.e., opaque identifiers) for different application functions has two main benefits: (1) AF-specific UeIds allows users to, if need be, avoid divulging their phone numbers (which are considered privacy-sensitive pieces of information) to application functions (i.e., such that the users are identified by the application functions in an anonymous manner); and (2) AF-specific UeIds prevent correlation and tracking of UeIds (and, thus, users) across applications.

(9) Currently, to enable application function-specific UeIds, 3GPP has defined the Nnef\_UEId\_Get service operation (i.e., 3GPP 23.502). The Nnef\_UEId\_Get service operation is invoked by an application function (e.g., a social media application, a streaming media application, or the like), which sends a Nnef\_UEId\_Get request including the IP address of a user endpoint device to a network exposure function (NEF). The NEF authorizes the request and then sends a management discovery request to a binding support function (BSF). In response to the management discovery request, the BSF determines the subscription permanent identifier (SUPI) that corresponds to the IP address specified in the Nnef\_UEId\_Get request and returns the SUPI to the NEF. The NEF then sends the SUPI to a unified data management element (UDM), which uses the SUPI to query a unified data repository (UDR) for an application function-specific UEId corresponding to the SUPI and the AFId (the identity of the application function, which the NEF determined through the authorization step), which is ultimately returned to the application function via the UDM and the NEF.

(10) The Nnef\_UEId\_Get service operation assumes that application function-specific UeIds have been provisioned in advance for a user endpoint. However, this is not always the case. For instance, the user endpoint may be a user's mobile phone, and the user may have just newly downloaded an application onto the mobile phone. If the newly downloaded application through its associated application function (which is an untrusted server residing outside of the mobile communications network) attempts to invoke the Nnef\_UEId\_Get service operation, an error will be generated, because there will be no application function-specific UEId defined in the UDR for the newly downloaded application on the mobile phone. Moreover, some users may delete application function-specific UeIds that have been provisioned in advance, for privacy reasons (e.g., to force a "forget me" effect). When the application functions associated with the deleted UeIds subsequently attempt to invoke the Nnef\_UEId\_Get service operation, errors will be generated.

(11) Examples of the present disclosure provide an application function-specific UEId management function that can generate application function-specific UeIds on the fly for application functions and user endpoints. The disclosed approach circumvents the generation of errors when application function-specific UeIds are not provisioned in advance and/or when users have deleted previously generated application function-specific UeIds.

(12) The disclosed management function may utilize GPSIs in the form of external identifiers (e.g., as defined by 3GPP) in order to uniquely and anonymously identify user endpoints. The GPSIs are specific to given application functions in order to prevent the user endpoints behavior from being tracked across application functions. These and other aspects of the present disclosure are discussed in further detail with reference to FIGS. 1-5, below.

(13) To further aid in understanding the present disclosure, FIG. 1 illustrates an example system **100** in which examples of the present disclosure for dynamically generating an application function-specific user endpoint identifier (UEId) may operate. The system **100** may include any one or more types of communication networks, such as a traditional circuit switched network (e.g., a public switched telephone network (PSTN)) or a packet network such as an Internet Protocol (IP) network (e.g., an IP Multimedia Subsystem (IMS) network), an asynchronous transfer mode (ATM) network, a wired network, a wireless network, and/or a cellular network (e.g., 2G-5G, a long term evolution (LTE) network, and the like) related to the current disclosure. It should be noted that an IP network is broadly defined as a network that uses Internet Protocol to exchange data packets. Additional example IP networks include Voice over IP (VOIP) networks, Service over IP (SoIP) networks, the World Wide Web, and the like.

(14) In one example, the system **100** may comprise a core network **102**. The core network **102** may be in communication with one or more access networks such as access network **120** and with the Internet **124**. In one example, the core network **102** may functionally comprise a fixed mobile convergence (FMC) network, e.g., an IP Multimedia Subsystem (IMS) network. In addition, the core network **102** may functionally comprise a telephony network, e.g., an Internet Protocol/Multi-Protocol Label Switching (IP/MPLS) backbone network utilizing Session Initiation Protocol (SIP) for circuit-switched and Voice over Internet Protocol (VoIP) telephony services. In one example, the core network **102** may include a plurality of network elements, including at least a network exposure function (NEF) **112**, a binding support function (BSF) **114**, a unified data management (UDM) element/application function-specific UEId management function (AUMF) **104**, and a unified data repository (UDR) **106**. Although the NEF **112**, BSF **114**, UDM/AUMF **104**, and UDR **106** are illustrated as separate elements in FIG. 1, in one example one or more of the NEF **112**, BSF **114**, UDM/AUMF **104**, and UDR **106** may be integrated in a single element (e.g., a single application server or the like). For instance, a single application server may perform the functions of the NEF **112**, BSF **114**, and UDM/AUMF **104** and may communicate with the UDR **106**. Additionally, the core network **102** may include a plurality of edge routers, including edge router **128**. For ease of illustration, various additional elements of the core network **102** are omitted from FIG. 1.

(15) In one example, the access network **120** may comprise a Digital Subscriber Line (DSL) network, a public switched telephone network (PSTN) access network, a broadband cable access network, a Local Area Network (LAN), a wireless access (e.g., an IEEE 802.11/Wi-Fi network and the like), a cellular access network, a 3rd party network, and the like. For example, the operator of the core network **102** may provide a cable television service, an IPTV service, a streaming service, or any other types of telecommunication services to subscribers via access network **120**. In one example, the core network **102** may be operated by a telecommunication network service provider (e.g., an Internet service provider, or a service provider who provides Internet services in addition to other telecommunication services). The core network **102** and the access network **120** may be operated by different service providers, the same service provider or a combination thereof, or the access network **120** may be operated by an entity having core businesses that are not related to telecommunications services, e.g., corporate, governmental, or educational institution LANs, and the like.

(16) In one example, the access network **120** may be in communication with one or more user endpoint devices **108** and **110**. The access network **120** may transmit and receive communications between the user endpoint devices **108** and **110**, between the user endpoint devices **108** and **110**,

the application function(s) (AF(s) **126** (e.g., application server(s)), the NEF **112**, other components of the core network **102**, devices reachable via the Internet in general, and so forth. In one example, each of the user endpoint devices **108** and **110** may comprise any single device or combination of devices that may comprise a user endpoint device, such as computing system **500** depicted in FIG. 5, and may be configured as described below. For example, the user endpoint devices **108** and **110** may each comprise a mobile device, a cellular smart phone, a gaming console, a set top box, a laptop computer, a tablet computer, a desktop computer, an application server, a wearable device (e.g., a smart watch or fitness tracker), an augmented reality (AR)/virtual reality (VR) headset, customer premises equipment (e.g., gateway devices), a bank or cluster of such devices, and the like.

(17) In one example, any one of the user endpoint devices **108** and **110** may run an application client (AC), such as AC **130**. The AC **130** may communicate with the AFs **126** or other application servers in the system **100** in order to provide a service to the user endpoint devices **108** and **110**, as discussed in greater detail below.

(18) In one example, one or more AFs **126** and one or more databases **132** may be accessible to user endpoint devices **108** and **110** via Internet **124** in general. The AF(s) **126** and DBs **132** may be associated with Internet software applications that may exchange data with the user endpoint devices **108** and **110** over the Internet **124**. Thus, some of the AFs **126** and DBs **132** may host applications including video conferencing applications, extended reality (e.g., virtual reality, augmented reality, mixed reality, and the like) applications, streaming media applications, social networking applications, immersive gaming applications, and the like.

(19) In accordance with the present disclosure, the NEF **112**, BSF **114**, UDM/AUMF **104**, and UDR **106** may be collectively configured to provide one or more operations or functions in connection with examples of the present disclosure for dynamically generating an application function-specific user endpoint identifier (UEId), as described herein. It should be noted that as used herein, the terms “configure,” and “reconfigure” may refer to programming or loading a processing system with computer-readable/computer-executable instructions, code, and/or programs, e.g., in a distributed or non-distributed memory, which when executed by a processor, or processors, of the processing system within a same device or within distributed devices, may cause the processing system to perform various functions. Such terms may also encompass providing variables, data values, tables, objects, or other data structures or the like which may cause a processing system executing computer-readable instructions, code, and/or programs to function differently depending upon the values of the variables or other data structures that are provided. As referred to herein a “processing system” may comprise a computing device including one or more processors, or cores (e.g., as illustrated in FIG. 4 and discussed below) or multiple computing devices collectively configured to perform various steps, functions, and/or operations in accordance with the present disclosure.

(20) In one example, the NEF **112**, BSF **114**, and UDM/AUMF **104** may cooperate, as discussed in further detail below, to query the UDR **106** for application function-specific UEIds/GPSIs and to dynamically generate an application function-specific UEId/GPSI for a user endpoint device **108** or **110** and application function **126** if an application function-specific UEId/GPSI for the user endpoint device **108** or **110** and application function **126** does not already exist. Thus one or more of the NEF **112**, BSF **114**, and UDM/AUMF **104** may comprise an individual application server. Alternatively, as discussed above, a single application server may perform the functions of two or more of the NEF **112**, BSF **114**, and UDM/AUMF **104**.

(21) The UDR **106** may store a plurality of application function-specific UEIds for user endpoint devices and application functions that have already been generated. In one example, the UDR **106** may comprise a physical storage device integrated with the NEF **112**, BSF **114**, and UDM/AUMF **104** (e.g., a database server or a file server), or attached or coupled to the UDM/AUMF **104**, in accordance with the present disclosure.

(22) It should be noted that the system **100** has been simplified. Thus, those skilled in the art will realize that the system **100** may be implemented in a different form than that which is illustrated in FIG. **1**, or may be expanded by including additional endpoint devices, access networks, network elements, application servers, etc. without altering the scope of the present disclosure. In addition, system **100** may be altered to omit various elements, substitute elements for devices that perform the same or similar functions, combine elements that are illustrated as separate devices, and/or implement network elements as functions that are spread across several devices that operate collectively as the respective network elements.

(23) For example, the system **100** may include other network elements (not shown) such as border elements, routers, switches, policy servers, security devices, gateways, a content distribution network (CDN) and the like. For example, portions of the core network **102**, access network **120**, and/or Internet **124** may comprise a content distribution network (CDN) having ingest servers, edge servers, and the like. Similarly, although only one access network **120** is shown, in other examples, access network **120** may comprise a plurality of different access networks that may interface with the core network **102** independently or in a chained manner. For example, UE devices **108** and **110** may communicate with the core network **102** via different access networks. Thus, these and other modifications are all contemplated within the scope of the present disclosure.

(24) To further aid in understanding the present disclosure, FIG. **2** illustrates call flow diagram **200** that shows a more detailed view of the operations of the network exposure function (NEF) **112**, the binding support function (BSF) **114**, the unified data management (UDM) element/application function-specific UEId management function (AUMF) **104**, and the unified data repository (UDR) **106** of FIG. **1**. In particular, FIG. **2** illustrates the process by which an application function-specific UEId for a user endpoint device and application function **126** may be retrieved or generated dynamically.

(25) As illustrated in FIG. **2**, the AF **126** may first invoke a Nnef\_UEId\_POST\_Retrieve service operation, by sending a Nnef\_UEId\_POST\_Retrieve request message to the NEF **112**. The Nnef\_UEId\_POST\_Retrieve request message requests an application function-specific UEId which can be used by the AF **126** (which is untrusted and resides externally to the communications network) to refer to the user of the user endpoint device anonymously over application programming interface (API) interactions the AF **126** has with the communications network. As such, the Nnef\_UEId\_POST\_Retrieve request message may include at least the IP address of the user endpoint device (UE\_IP) and an identifier of the application function **126** (AF\_Id).

(26) The NEF **112** may authorize the Nnef\_UEId\_POST\_Retrieve request and then send a management discovery request message (Nbsf\_Management\_Discovery Request) to the BSF **114**. The management discovery request may request the subscription permanent identifier (SUPI) for the user endpoint device on which the AC **130** resides. As such, the management discovery request may include the IP address of the user endpoint device on which the AC **130** resides (UE\_IP).

(27) The BSF **114** may respond to the management discovery request message with a management discovery response message (Nbsf\_Management\_Discovery Response) that provides the SUPI that corresponds to the IP address of the user endpoint device on which the AC **130** resides (UE\_IP). The management discovery response message may be sent back to the NEF **112**.

(28) Once the NEF **112** has acquired the SUPI for the user endpoint device on which the AC **130** resides, the NEF **112** may send a Nudm\_SDM\_POST\_Retrieve request message to the UDM/AUMF **104**. The Nudm\_SDM\_POST\_Retrieve request message may include the SUPI for the user endpoint device on which the AC **130** resides and the identifier of the AF **126** (AF\_Id). The Nudm\_SDM\_POST\_Retrieve request message may request the application function-specific UEId (e.g., external identifier) for the AF **126** and the user endpoint device on which the AC **130** resides.

(29) The UDM/AUMF **104** may next send a Nudr\_DataRepository\_GET\_UE\_External\_Id request message to the UDR **106**. The Nudr\_DataRepository\_GET\_UE\_External\_Id request message may

include the SUPI for the user endpoint device on which the AC **130** resides and the identifier of the AF **126** (AF\_Id) and may ask the UDR **106** for the AF-specific UEId (e.g., external identifier) that corresponds to the SUPI and AF\_Id.

(30) If an AF-specific UEId corresponding to the SUPI and the AF\_Id already exists in the UDR **106**, then the UDR **106** may return the AF-specific UEId to the UDM/AUMF **104** in a Nudr\_DataRepository\_GET response message. However, if an AF-specific UEId corresponding to the SUPI and the AF\_Id does not exist in the UDR **106**, then the Nudr\_DataRepository\_GET response message may indicate to the UDM/AUMF **104** that the requested UDM/AUMF **104** does not exist (i.e., the request is NULL).

(31) If a NULL response is received from the UDR **106**, then the UDM/AUMF **104** may dynamically generate an application function-specific UEId for the AF **126** and the user endpoint device on which the AC **130** resides (UE\_External\_Id). The UDM/AUMF **104** may then store the dynamically generated application function-specific UEId for the AF **126** and the user endpoint device on which the AC **130** resides (UE\_External\_Id) in the UDR **106** (e.g., via a Nudr\_DataRepository\_PUT service operation).

(32) Once the UDR **106** acknowledges storage of the dynamically generated application function-specific UEId for the AF **126** and the user endpoint device on which the AC **130** resides (UE\_External\_Id) (e.g., via a Nudr\_DataRepository\_PUT response message), the UDM/AUMF **104** may send the dynamically generated application function-specific UEId for the AF **126** and the user endpoint device on which the AC **130** resides (UE\_External\_Id) to the NEF **112** (e.g., via a Nudm\_SDM\_POST\_Retrieve response message). The NEF **112** may then forward the dynamically generated application function-specific UEId for the AF **126** and the user endpoint device on which the AC **130** resides (UE\_External\_Id) to the AC **130** (e.g., via a Nnef\_UEId\_POST\_Retrieve response message).

(33) The AF **126** may then proceed accordingly using the application function-specific UEId.

(34) FIG. 3 illustrates a flowchart of an example method **300** for dynamically generating an application function-specific user endpoint identifier (UEId). In one example, the method **300** may be performed by the UDM/AUMF **104** illustrated in FIGS. 1 and 2. However, in other examples, the method **300** may be performed by another device, such as the computing system **500** of FIG. 5, discussed in further detail below. For the sake of discussion, the method **300** is described below as being performed by a processing system (where the processing system may comprise a component of the UDM/AUMF **104**, the computing system **500**, or another device).

(35) The method **300** begins in step **302**. In step **304**, the processing system may receive, from a network exposure function of a communications network, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application function residing externally to the communications network (which may communicate with an application client residing locally on the user endpoint device).

(36) In one example, the user endpoint device may comprise a mobile device (e.g., a mobile phone, a tablet computer, a wearable device, or the like). The application function may comprise a software application that is supported by a local application client communicating with a remote application server that resides externally to the communications network. In one example, the request from the network exposure function may be received upon a first time that the user endpoint device executes or launches the software application.

(37) As discussed above, the application function-specific UEId may be an identifier (e.g., an external identifier) that is unique to the combination of the user endpoint device and the application function residing externally to the communications network. That is, each application function with which the user endpoint device communicates may be associated with a different application function-specific UEId. Moreover, other instances of the application function communicating with other user endpoint devices may be associated with different application function-specific UEIds that are unique to those other user endpoint devices.



(38) In one example, the request from the network exposure function may specify at least an identifier associated with the application function (AF\_Id) and a unique identifier or UEId associated with the SIM card of the user endpoint device, such as a subscription permanent identifier (SUPI).

(39) In step **306**, the processing system may query a unified data repository for the application function-specific user endpoint identifier. In one example, the processing system may specify the identifier associated with the application function (e.g., AF\_Id) and the unique identifier associated with the SIM card of the user endpoint device (e.g., SUPI). The AF\_Id and the SUPI may be indexed to an application function-specific UEId in the unified data repository, if an application function-specific UEId has previously been provisioned for the AF\_Id and the SUPI.

(40) In step **308**, the processing system may determine, based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository. For instance, if the application function-specific UEId has already been provisioned and exists in the unified data repository at the time of the query, then the unified data repository may respond to the query with the application function-specific UEId. However, if the application function-specific UEId has not been provisioned (or has been provisioned but then subsequently deleted by a user) and does not exist in the unified data repository at the time of the query, then the unified data repository may respond to the query with a NULL response.

(41) If the processing system concludes, in step **308**, that the application function-specific user endpoint identifier does exist in the unified data repository, then the method **300** may proceed to step **310**. In step **310**, the processing system may forward the application function-specific user endpoint identifier, as stored in the unified data repository, to the network exposure function.

(42) In one example, the application function-specific UEId comprises an external identifier for the UE. The processing system may retrieve the external identifier from the unified data repository and forward the external identifier to the network exposure function.

(43) If, on the other hand, the processing system concludes in step **308** that the application function-specific user endpoint identifier does not exist in the unified data repository, then the method **300** may proceed to step **312**. In step **312**, the processing system may dynamically generate the application function-specific user endpoint identifier.

(44) In one example, the processing system dynamically generates the application function-specific UEId in the form of an external identifier. In one example, the application function-specific UEId may be generated according to any known method for generating application function-specific UEs.

(45) In optional step **314** (illustrated in phantom), the processing system may store the application function-specific user endpoint identifier in the unified data repository. Thus, the next time the application function-specific UEId is required by the application function, the application specific UEId can be retrieved from the unified data repository.

(46) In step **316**, the processing system may forward the application function-specific user identifier, as dynamically generated by the processing system, to the network exposure function. For instance, the processing system may forward the UEId in the form of an external identifier to the network exposure function.

(47) Having forwarded either an application function-specific user endpoint identifier previously stored in the unified data repository (e.g., as in step **310**) or a dynamically generated application function-specific user endpoint identifier (e.g., as in steps **312-316**) to the network exposure function, the method **300** may end in step **318**.

(48) Although not expressly specified above, one or more steps of the method **300** may include a storing, displaying, and/or outputting step as required for a particular application. In other words, any data, records, fields, and/or intermediate results discussed in the method can be stored, displayed and/or outputted to another device as required for a particular application. Furthermore, operations, steps, or blocks in FIG. **3** that recite a determining operation or involve a decision do

not necessarily require that both branches of the determining operation be practiced. In other words, one of the branches of the determining operation can be deemed as an optional step. Furthermore, operations, steps or blocks of the above described method(s) can be combined, separated, and/or performed in a different order from that described above, without departing from the examples of the present disclosure.

(49) Thus, examples of the present disclosure provide an application function-specific UEId management function that can generate application function-specific UeIds on the fly for application functions and user endpoints. The disclosed approach circumvents the generation of errors when application function-specific UeIds are not provisioned in advance and/or when users have deleted previously generated application function-specific UeIds. The disclosed management function may utilize GPSIs in the form of external identifiers (e.g., as defined by 3GPP) in order to uniquely and anonymously identify user endpoints. The GPSIs are specific to given application functions in order to prevent the user endpoints behavior from being tracked across application functions.

(50) Examples of the present application function-specific UEId management function may be extended to enable further functionalities, including allowing users to manage (e.g., view and/or delete) application function-specific UeIds associated with the users' user endpoint devices.

(51) In another example, the present application function-specific UEId management function may allow a third party application that receives a user's MSISDN to exchange the MSISDN with an application-function specific static UEId over a NEF application programming interface (API), where the NEF API may in turn use the present application function-specific UEId management function on a southbound operation. The third party application in this case may prefer not to use MSISDN to target a user over the NEF API. For instance, an MSISDN change operation requested by the user may not be known to third party applications, and, as a result, any subsequent API calls onto a 3GPP network after a change in MSISDN may target the wrong user (to whom the MSISDN may have been reassigned).

(52) However, a third party application that has received the MSISN from the user can subscribe to NEF notifications for MSISDN change events for a user who is identified by an application function-specific static UEId. Thus, the third party application will no longer be in the dark if/when the user changes the MSISDN without letting the third party application know about the change. In one example, a new NEF event type for a change in MSISDN can be enabled through the usage of an UMF API notification service. In this case, the AUMF may only notify (through the NEF) the application functions that have been identified and authorized by the user to receive MSISDN changes.

(53) FIG. 4 illustrates call flow diagram 400 that shows a view of operations of a user application (APP) 430, a mobile network operator (MNO) portal 412, a basic service set (BSS) 414, a unified data management (UDM) element/application function-specific UEId management function (AUMF) 404, and a unified data repository (UDR) 406. In particular, FIG. 4 illustrates the process by which an application function-specific UEId for a user application 430 may be deleted from the UDR 406.

(54) As illustrated in FIG. 4, the user application 430 may send a request message (GET\_AF-specific\_UEId\_List Request) to the MNO portal 412. The request message may request a list of application function-specific UeIds.

(55) The MNO portal 412 may authenticate the user associated with the user application 430, and, assuming that the user is authenticated, may subsequently perform a user account lookup in the BSS 414. The MNO portal may use a UserId associated with the user of the user application 430 to perform the user account lookup.

(56) The BSS 414 may return a response to the MNO portal 412 in response to the user account lookup. The response from the BSS 414 may include a SUPI associated with a user endpoint device on which the user application 430 resides.

(57) Once the MNO portal **412** has the SUPI of the user endpoint device, the MNO portal **412** may send a subscriber data management request to the UDM/AUMF **404**. The subscriber data management request may include the SUPI and may request a list of external identifiers associated with the SUPI.

(58) Once the UDM/AUMF **404** has the SUPI, the UDM/AUMF **404** may use the SUPI to query the UDR **406**. For instance, the SUPI may be indexed in the UDR **406** to a list of external identifiers associated with the user endpoint device on which the user application **430** resides. The UDR **406** may return this list of external identifiers (UE\_External\_Id\_List) to the UDM/AUMF **404**.

(59) The UDM/AUMF **404** may forward the list of external identifiers (UE\_External\_Id\_List) to the MNO portal **412**. Based on the list of external identifiers, the MNO portal **412** may return a list of application function-specific UEIds for the user endpoint device (AF-specific\_UEId\_List) to the user application **430**.

(60) The user application **430** may, under the direction of a human user, request deletion of at least one selected application function-specific UEId in the list of application function-specific UEIds. The request for deletion may be sent by the user application **430** to the MNO portal **412**.

(61) The MNO portal **412** may send a request to delete the selected application function-specific UEId(s) (Nudm\_SDM\_DELETE Request) to the UDM/AUMF **404**. The request to delete the selected application function-specific UEId(s) may specify the selected application function-specific UEId(s) to be deleted and the SUPI associated with the user endpoint device on which the user application **430** resides.

(62) The UDM/AUMF **404** may send a request to delete the selected application function-specific UEId(s) from the UDR **406** (Nudr\_DataRepository\_DELETE Request) to the UDR **406**. The request to delete the selected application function-specific UEId(s) from the UDR **406** may specify the selected application function-specific UEId(s) to be deleted and the SUPI associated with the user endpoint device on which the user application **430** resides.

(63) The UDR **406** may send a response to the UDM/AUMF **404** indicating that the selected application function-specific UEId(s) have been deleted from the UDR **406**. The UDM/AUMF **404** may forward the response indicating that the selected application function-specific UEId(s) have been deleted from the UDR **406** to the MNO portal **412**, which may, in turn, forward the response to the user application **430**.

(64) Thus, the MNO portal **412** and BSS **414** may utilize the available APIs of the AUMF portion of the UDM/AUMF **404** (e.g., operations such as GET and DELETE) in order to provide a means for users to easily view and remove any application function-specific UEIds assigned to the user's user endpoint device from the UDR **406**.

(65) FIG. 5 depicts a high-level block diagram of a computing device specifically programmed to perform the functions described herein. For example, any one or more components or devices illustrated in FIG. 1 or described in connection with the method **300** may be implemented as the system **500**. For instance, the UDM/AUMF **104** of FIG. 1 (such as might be used to perform the method **300**) could be implemented as illustrated in FIG. 5. In another example, the NEF **112**, the BSF **114**, and/or one of the user endpoint devices **108** or **110** of FIG. 1 could be implemented as illustrated in FIG. 5.

(66) As depicted in FIG. 5, the system **500** comprises a hardware processor element **502**, a memory **504**, a module **505** for dynamically generating an application function-specific user endpoint identifier, and various input/output (I/O) devices **506**.

(67) The hardware processor **502** may comprise, for example, a microprocessor, a central processing unit (CPU), or the like. The memory **504** may comprise, for example, random access memory (RAM), read only memory (ROM), a disk drive, an optical drive, a magnetic drive, and/or a Universal Serial Bus (USB) drive. The module **505** for dynamically generating an application function-specific user endpoint identifier may include circuitry and/or logic for performing special

purpose functions relating to estimating available bandwidth ranges and/or modifying settings for data transfers according to available bandwidth ranges. The input/output devices **506** may include, for example, storage devices (including but not limited to, a tape drive, a floppy drive, a hard disk drive or a compact disk drive), a receiver, a transmitter, a fiber optic communications line, an output port, or a user input device (such as a keyboard, a keypad, a mouse, and the like).

(68) Although only one processor element is shown, it should be noted that the computer may employ a plurality of processor elements. Furthermore, although only one specific-purpose computer is shown in the Figure, if the method(s) as discussed above is implemented in a distributed or parallel manner for a particular illustrative example, i.e., the steps of the above method(s) or the entire method(s) are implemented across multiple or parallel specific-purpose computers, then the specific-purpose computer of this Figure is intended to represent each of those multiple specific-purpose computers. Furthermore, one or more hardware processors can be utilized in supporting a virtualized or shared computing environment. The virtualized computing environment may support one or more virtual machines representing computers, servers, or other computing devices. In such virtualized virtual machines, hardware components such as hardware processors and computer-readable storage devices may be virtualized or logically represented.

(69) It should be noted that the present disclosure can be implemented in software and/or in a combination of software and hardware, e.g., using application specific integrated circuits (ASIC), a programmable logic array (PLA), including a field-programmable gate array (FPGA), or a state machine deployed on a hardware device, a computer or any other hardware equivalents, e.g., computer readable instructions pertaining to the method(s) discussed above can be used to configure a hardware processor to perform the steps, functions and/or operations of the above disclosed method(s). In one example, instructions and data for the present module or process **505** for dynamically generating an application function-specific user endpoint identifier (e.g., a software program comprising computer-executable instructions) can be loaded into memory **504** and executed by hardware processor element **502** to implement the steps, functions or operations as discussed above in connection with the example method **300**. Furthermore, when a hardware processor executes instructions to perform “operations,” this could include the hardware processor performing the operations directly and/or facilitating, directing, or cooperating with another hardware device or component (e.g., a co-processor and the like) to perform the operations.

(70) The processor executing the computer readable or software instructions relating to the above described method(s) can be perceived as a programmed processor or a specialized processor. As such, the present module **505** for dynamically generating an application function-specific user endpoint identifier (including associated data structures) of the present disclosure can be stored on a tangible or physical (broadly non-transitory) computer-readable storage device or medium, e.g., volatile memory, non-volatile memory, ROM memory, RAM memory, magnetic or optical drive, device or diskette and the like. More specifically, the computer-readable storage device may comprise any physical devices that provide the ability to store information such as data and/or instructions to be accessed by a processor or a computing device such as a computer or an application server.

(71) While various examples have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of a preferred example should not be limited by any of the above-described example examples, but should be defined only in accordance with the following claims and their equivalents.

## Claims

1. A method comprising: receiving, from a network exposure function of a communications network by a processing system including at least one processor, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application

function residing externally to the communications network; querying, by the processing system, a unified data repository for the application function-specific user endpoint identifier; determining, by the processing system based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository; dynamically generating, by the processing system, the application function-specific user endpoint identifier; and forwarding, by the processing system, the application function-specific user endpoint identifier, as dynamically generated, to the network exposure function.

2. The method of claim 1, wherein the user endpoint device comprises a mobile device.

3. The method of claim 1, wherein the application function is one of a plurality of application functions with which the user endpoint device communicates, and each application function of the plurality of application functions is associated with a different application function-specific user endpoint identifier.

4. The method of claim 1, wherein the request specifies at least an identifier associated with the application function and a unique identifier associated with a subscriber identity module card of the user endpoint device.

5. The method of claim 4, wherein the unique identifier comprises a subscription permanent identifier.

6. The method of claim 4, wherein the querying attempts to index the identifier associated with the application function and the unique identifier associated with the subscriber identity module card of the user endpoint device to the application function-specific user endpoint identifier.

7. The method of claim 4, wherein the network exposure function acquires the unique identifier associated with the subscriber identity module card of the user endpoint device from a binding support function of the communications network.

8. The method of claim 7, wherein the binding support function indexes the unique identifier associated with the subscriber identity module card of the user endpoint device to an internet protocol address of the user endpoint device.

9. The method of claim 1, wherein the determining comprises receiving a null response from the unified data repository to the querying.

10. The method of claim 9, wherein the null response is an indication that the application function-specific user endpoint identifier has either not been provisioned previously or has been provisioned but subsequently deleted by a user.

11. The method of claim 1, wherein the application function-specific user endpoint identifier is an external identifier.

12. The method of claim 1, further comprising: storing, by the processing system, the application function-specific user endpoint identifier, as dynamically generated, in the unified data repository.

13. The method of claim 1, wherein the communications network is a fifth generation mobile network.

14. The method of claim 1, wherein the processing system is part of a unified data management element of the communications network.

15. The method of claim 14, wherein the unified data management element comprises an application function-specific user endpoint identifier management function.

16. A non-transitory computer-readable medium storing instructions which, when executed by a processing system including at least one processor, cause the processing system to perform operations, the operations comprising: receiving, from a network exposure function of a communications network, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application function residing externally to the communications network; querying a unified data repository for the application function-specific user endpoint identifier; determining, based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository; dynamically generating the application function-specific user endpoint identifier; and forwarding

the application function-specific user identifier, as dynamically generated, to the network exposure function.

17. The non-transitory computer-readable medium of claim 16, wherein the request specifies at least an identifier associated with the application function and a unique identifier associated with a subscriber identity module card of the user endpoint device.

18. The non-transitory computer-readable medium of claim 17, wherein the unique identifier comprises a subscription permanent identifier.

19. The non-transitory computer-readable medium of claim 16, wherein the operations further comprise: storing the application function-specific user endpoint identifier, as dynamically generated, in the unified data repository.

20. A system comprising: a processing system including at least one processor; and a non-transitory computer-readable medium storing instructions which, when executed by the processing system, cause the processing system to perform operations, the operations comprising: receiving, from a network exposure function of a communications network, a request for an application function-specific user endpoint identifier that is unique to a user endpoint device and an application function residing externally to the communications network; querying a unified data repository for the application function-specific user endpoint identifier; determining, based on a response from the unified data repository, whether the application function-specific user endpoint identifier exists in the unified data repository; dynamically generating the application function-specific user endpoint identifier; and forwarding the application function-specific user identifier, as dynamically generated, to the network exposure function.

---