

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250263243

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Mook; Dean et al.

Shelf with Integrated Roller Securement

Abstract

A conveyor system includes one or more conveyor units each including a base extending from a first end to a second end and a first side attached to the base and having a (i) first side coupler including a first pair of ribs disposed adjacent to the first end of the base and spaced apart from each other by a first distance and (ii) a second side coupler including a second pair of ribs disposed adjacent to the second end of the base and spaced apart from each other by a second distance that is less than the first distance.

Inventors: Mook; Dean (Medina, OH), Walker; William H. (Fairlawn, OH), Eden; Keith C. (Rockford, IL), Dyavarasegowda; Ashok Kumara (Bangalore, IN), Obitts; Shane (North Ridgeville, OH)

Applicant: Fasteners for Retail, Inc. (Twinsburg, OH)

Family ID: 1000008575322

Assignee: Fasteners for Retail, Inc. (Twinsburg, OH)

Appl. No.: 19/198901

Filed: May 05, 2025

Related U.S. Application Data

parent US continuation 18184844 20230316 parent-grant-document US 12291402 child US 19198901

us-provisional-application US 63269479 20220317

Publication Classification

Int. Cl.: B65G21/20 (20060101); B65G13/11 (20060101); B65G39/12 (20060101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application claims priority under 35 U.S.C. § 120 from patent application Ser. No. 18/184,844, filed Mar. 16, 2023, which claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Application 63/269,479, filed on Mar. 17, 2022. The disclosures of the prior applications are considered part of the disclosure of this application and are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

[0002] This disclosure relates to retail shelving with integrated roller securement.

BACKGROUND

[0003] Gravity-fed shelving systems are commonly used in retail environments as an efficient means of ensuring that products are continuously presented at the front-most area of a shelving system. For instance, when a retail customer or user removes a product from the front of the shelving system, a subsequent product that is stocked on the shelf automatically transitions to the front of the shelf under the influence of gravity. Such shelving ensures that product inventory is always presented for purchase.

[0004] Conventional gravity-fed shelving systems sometimes utilize a conveying system that allows the products to translate along the shelving under the influence of gravity. For instance, some shelving systems may include a support bed having a series of rollers arranged along a length of the support bed. Retail products are loaded into the shelving system such that the rollers facilitate natural translation of the retail products along the length of the support bed towards a lower end of the shelving system.

[0005] Over a period of use, rollers used in gravity-fed shelving systems may need to be removed for maintenance or replacement as the condition of the bearings and other components of each roller deteriorate. Accordingly, there exists a need in the art for a gravity-fed shelving system that allows for convenient replacement or maintenance of rollers while ensuring that the rollers remain securely installed within the shelving system during use.

SUMMARY

[0006] An aspect of the disclosure provides a conveyor system for a retail shelf. The conveyor system includes a conveyor frame having a frame base and a pair of parallel frame sidewalls. Each sidewall extend from a top side of the base to a distal end defining a plurality of sockets. The sockets include a socket bearing configured to support a corresponding roller shaft and a lip element extending across the opening at the distal end.

[0007] Implementations of the disclosure may include one or more of the following optional features. In some examples, the conveyor frame includes at least one end coupler attached at an end of the conveyor frame. In these examples, the end coupler includes at least one coupler ear integrally formed with one of the sidewalls and coupler base integrally formed with the frame base, with the coupler ear being independent from the coupler base. The conveyor system may additionally include a track system including a track member slidably couples to the end coupler. In some configurations, the conveyor frame includes a plurality of frame segments each defining a portion of a length of the conveyor frame. The plurality of segments may include a first end segment extending from a first end including the end coupler to a second end defined by the frame base and the frame sidewall and a second end segment extending from a third end including a frame coupler configured to overlap the second end of the first end segment when the conveyor

frame is in an assembled state.

[0008] In some implementations, the conveyor system includes the lip element that is recessed from an inner sidewall surface of each of the sidewalls. In these implementations, the lip element may be arcuate. In some examples, the conveyor frame includes a first end including a first track coupling member. In some configurations, the conveyor system includes a plurality of roller units that each include a first roller shaft at a first end and a second roller shaft at an opposite second end. The length from the first end to the second end is greater than a distance between a first lip element on a first one of the frame sidewalls and a second lip element on the other one of the frame sidewalls.

[0009] Another aspect of the disclosure provides a conveyor system for a retail shelf including a conveyor chassis with a base and a chassis sidewall extending a first height from the base. The conveyor system also includes a frame sidewall formed separately from the chassis and including a proximal end defining a sidewall channel configured to receive the chassis sidewall and an opposite distal end including a plurality of sockets.

[0010] Implementations of the disclosure may include one or more of the following optional features. In some examples, the conveyor chassis includes a plurality of receptacles formed in at least one of the base and the chassis sidewall. In these examples, the frame sidewall may have a plurality of tabs configured to be at least partially received within the receptacles when the channel of the frame sidewall receives the chassis sidewall. The tabs may have a sidewall retainer configured to engage the chassis at one of the receptacles. In some examples, the chassis includes a base retainer configured to interface with the sidewall retainer. In some implementations, the base retainer includes a flange extending from a top side of the base.

[0011] In some configurations, the conveyor system includes a base that is a metallic material and the frame sidewall includes a polymeric material. In some implementations, the frame includes at least one end coupler attached at an end of the conveyor frame. In these implementations, the end coupler includes at least one coupler ear integrally formed with one of the sidewalls and coupler base integrally formed with the frame base, with the coupler ear being independent from the coupler base. The conveyor system may also have a track system including a track member slidably coupled to the end coupler.

[0012] Another aspect of the disclosure provides a conveyor system for a retail shelf. The conveyor system includes a conveyor frame having a first sidewall. The first sidewall includes a distal end defining a plurality of sockets. The conveyor system further includes a first wing operable between an open configuration, wherein the sockets of the first sidewall are exposed, and a closed configuration, wherein the sockets of the first sidewall are covered by the first wing.

[0013] Implementations of the disclosure may include one or more of the following optional features. In some implementations, the first wing includes a lower end coupled to the first sidewall and an upper end operable to selectively cover the sockets of the first sidewall when the first wing is moved between the open configuration and the closed configuration. In some examples, the upper end of the first wing includes a flange configured to engage the distal end of the first sidewall in the closed configuration. In some configurations, the flange is configured to receive the distal end of the first sidewall. In some examples, the lower end of the first wing is hingedly coupled to the first sidewall. In some implementations, the lower end of the first wing is coupled to the first sidewall by a living hinge.

[0014] In some configurations the first sidewall and the first wing are integrally formed. In some implementations, the first wing includes an outer surface configured to face away from the first sidewall in the closed configuration, the outer surface including at least one rib extending parallel to the distal end of the first sidewall. In some examples, the conveyor frame includes a first end, including a first track coupling member. In some configurations, a plurality of roller units each including a first roller shaft received by one of the sockets of the first sidewall, wherein the first roller shaft is disposed between the first wing and the first sidewall when the first wing is in the

closed configuration.

[0015] Another aspect of the disclosure provides a shelf divider system. The shelf divider system, including a divider track, including a first slot extending along a length of the divider track. The shelf divider system further includes a track insert received within the first slot and including an inner core defining a lower socket and a plurality of stabilizers extending outwardly from the inner core.

[0016] This aspect may include one or more of the following optional features. In some configurations, each of the stabilizers extends to a distal end contacting an inner surface of the first slot. In some examples, the inner core includes a first material and the stabilizers include a second material that is different than the first material. In some implementations, the second material has at least one of a greater coefficient of friction or a lower stiffness than the first material.

[0017] In some configurations, the first slot includes a first slot opening formed in a top side of the first divider track. In some examples, the lower socket includes a lower socket opening exposed through the first slot opening. In some implementations, the lower socket has a first width and the lower socket opening has a second width that is less than the first width. In some configurations, a divider including a divider wall and a divider coupling tab extending from a bottom side of the divider wall, the divider coupling tab configured to selectively engage with the lower socket of the track insert through the first slot. In some examples, the divider coupling tab includes a distal end having a third width that is greater than a width of the lower socket.

[0018] In some implementations, the track insert is configured to expand within the first slot when the divider coupling tab is engaged with the lower socket of the track insert.

[0019] The details of one or more implementations of the disclosure are set forth in the accompanying drawings and the description below. Other aspects, features, and advantages will be apparent from the description and drawings, and from the claims.

Description

DESCRIPTION OF DRAWINGS

[0020] FIG. 1 is perspective view of an example shelving system according to the principles of the present disclosure.

[0021] FIG. 2 is a perspective view of an example conveyor unit for use according to the principles of the present disclosure.

[0022] FIG. 3 is an exploded perspective view of the conveyor unit of FIG. 2.

[0023] FIG. 4A is a cross-sectional view of the conveyor unit shown in FIG. 2, taken along Line 4A-4A in FIG. 2.

[0024] FIG. 4B is a cross-sectional view of the conveyor unit shown in FIG. 2, taken along Line 4B-4B in FIG. 2.

[0025] FIG. 5A is a cross-sectional view of the conveyor unit shown in FIG. 2, taken along Line 5A-5A in FIG. 2.

[0026] FIG. 5B is a cross-sectional view of the conveyor unit shown in FIG. 2, taken along Line 5B-5B in FIG. 2.

[0027] FIG. 6 is a first side elevation view of the conveyor unit of FIG. 2.

[0028] FIG. 7 is a second side elevation view of the conveyor unit of FIG. 2.

[0029] FIG. 7A is an enlarged view of a first end of the conveyor unit of FIG. 2, taken at Area 7A of FIG. 7.

[0030] FIG. 7B is an enlarged view of the conveyor unit of FIG. 2, taken at Area 7B of FIG. 7.

[0031] FIG. 8 is a perspective view of a divider system and track system according to the principles of the present disclosure.

[0032] FIG. 9 is an exploded perspective view of the divider system and track system of FIG. 8.

[0033] FIG. **10** is a side elevation view of the divider system and track system of FIG. **8**.
[0034] FIG. **11A** is an enlarged fragmentary view of the divider system and track system of FIG. **8**, taken at Area **11A**.
[0035] FIG. **11B** is an enlarged fragmentary view of the divider system and track system of FIG. **8**, taken at Area **11B**.
[0036] FIG. **12** is a perspective view of an example divider of the divider system of FIG. **8**.
[0037] FIG. **13** is a perspective view of another example of a shelving system according to the principles of the present disclosure.
[0038] FIG. **14** is an enlarged, partial, exploded view of the shelving system of FIG. **13**.
[0039] FIG. **15** is a fragmentary perspective view of a conveyor unit of the shelving system of FIG. **13**, showing an intermediate frame segment of the conveyor unit.
[0040] FIG. **16** is a perspective view of a conveyor frame of the shelving system of FIG. **13**. FIG. **17** is a partial perspective view of the conveyor frame of FIG. **16**.
[0041] FIG. **18** is a perspective view of an intermediate frame segment of the conveyor frame of FIG. **16**.
[0042] FIG. **19** is a cross-sectional view of the intermediate frame segment of FIG. **18**, taken at Line **19-19** of FIG. **18**.
[0043] FIG. **20A** is cross-sectional view of the intermediate frame segment of FIG. **18**, taken at Line **20-20** of FIG. **18**.
[0044] FIGS. **20B** and **20C** are cross-sectional views taken along Line **20-20** of FIG. **18**, showing steps for installing a roller into the intermediate frame segment of FIG. **18**.
[0045] FIG. **21** is an enlarged view of a first end of the conveyor, taken at Area **21** of FIG. **13**.
[0046] FIG. **22** is a perspective view of another example of a shelving system according to the principles of the present disclosure.
[0047] FIG. **23** is a perspective view of a conveyor frame of the shelving system of FIG. **22**.
[0048] FIG. **24** is an enlarged, partial view of the conveyor frame of FIG. **23**.
[0049] FIG. **25** is an exploded perspective view of the conveyor frame of FIG. **23**.
[0050] FIG. **26** is a cross-sectional view of the intermediate frame segment of FIG. **23**, taken at Line **26-26** of FIG. **23**.
[0051] FIG. **27A** is cross-sectional view of the intermediate frame segment of FIG. **23**, taken at Line **27-27** of FIG. **23**.
[0052] FIGS. **27B** and **27C** are cross-sectional views taken along Line **27-27** of FIG. **23**, showing steps for installing a roller into the intermediate frame segment of FIG. **23**.
[0053] FIG. **28** is a perspective view of another example of a shelving system according to the principles of the present disclosure.
[0054] FIG. **29** is an exploded perspective view of the shelving system of FIG. **28**.
[0055] FIG. **30** is an exploded perspective view of a conveyor unit of the shelving system of FIG. **28**.
[0056] FIG. **31** is an inner perspective view of a frame sidewall of the shelving system of FIG. **28**.
[0057] FIG. **32** is an outer perspective view of the frame sidewall of FIG. **31**.
[0058] FIG. **33** is a cross-sectional view of the conveyor unit of FIG. **30**, taken at Line **33-33** of FIG. **29**.
[0059] FIG. **34** is a cross-sectional view of the conveyor unit of FIG. **30**, taken at Line **34-34** of FIG. **29**.
[0060] Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

[0061] Referring to FIG. **1**, a shelving system **10** is shown including a track system **100**, a conveyor system **200**, and a divider system **300** according to an example of the present disclosure. As described throughout the application, the shelving system **10** and components thereof may be described with reference to a front side **12** corresponding to a product dispensing location that may

face a store aisle and a rear side **14** formed on the opposite side of the shelving system **10** from the front side **12**. Furthermore, the shelving system **10** and components thereof may be described relative to a longitudinal direction or axis extending from the front side **12** to the rear side **14** or a lateral direction or axis extending perpendicular to the longitudinal direction.

[0062] The shelving system **10** may be provided as a standalone unit for use in a retail environment, or may be provided in combination with a plurality of the shelving systems **10**. Furthermore, the shelving system **10** may be configured for direct attachment to one or more shelving support members (not shown), such as uprights or walls, or alternatively, may be installed on existing shelves. Optionally, the shelving system **10** may be provided as a gravity-fed shelving system **10**, whereby the shelving system **10** is oriented at an oblique angle relative to level such that a support bed **16** of the shelving system forms a decline from the rear side **14** of the shelving system **10** to the front side **12** of the shelving system **10**.

[0063] Generally, the track system **100** includes a pair of track members **102** each defining one or more of a conveyor track **104**, a divider track **106**, and/or an accessory track **108** (FIG. **11A**). The conveyor system **200** of the shelving system **10** includes one or more conveyor units **202** collectively defining the support bed **16** of the shelving system **10**. In the illustrated example, the conveyor system **200** includes a plurality of the conveyor units **202** attached to the track system **100** such that the conveyor units **202** cooperate to define the support bed **16** of the shelving system **10**. The divider system **300** includes at least one divider unit **304** selectively coupled to the divider track **106** of each of the track members **102**. As described in greater detail below, the divider system **300** includes an attachment interface between each divider track **106** and a respective one of the divider units **304** to allow each of the divider units **304** to be selectively attached to and adjusted along each divider track **106**. Thus, divider units **304** can be added, removed, or repositioned along the divider tracks **106** to define a plurality of independent product bays **18** for arranging and separating products.

[0064] With reference to FIG. **1**, the shelving system **10** includes the track system **100** generally configured to facilitate attachment and lateral translation of the various components of the conveyor system **200** and the divider system **300**. Here, the track system **100** includes a pair of the track members **102**, with a first track member **102** extending along the front side **12** and a second track member **102** extending along the rear side **14**. While the track members **102** of the present disclosure are shown as being identical, in some examples one of the track members **102** may be different. For example, one of the track members **102** may be provided without the accessory track **108**.

[0065] Referring to FIGS. **10-11B**, each track member **102** includes the conveyor track **104**, the divider track **106**, and the accessory track **108**. For the sake of description, each track member **102** and elements thereof may be described relative to a bottom side **110**, a top side **112**, an inner side **114** configured to face inward (i.e., towards the opposite track member **102**) and an outer side **116** configured to face outward (i.e., away from the opposite track member **102**). While the track members **102** illustrated in the figures are provided as integral units including all of the tracks **104**, **106**, **108** formed of a single piece, one or more of the tracks **104**, **106**, **108** may be provided as a detachable element. Furthermore, the track member **102** may be formed with any one of or any combination of the tracks **104**, **106**, **108**. For example, the track member **102** may be provided with just the conveyor track **104** or just the divider track **106**.

[0066] The track member **102** includes a base member **120** disposed along the bottom side **110** and a plurality of track walls **122**, **124**, **126** extending from the top side of the base member **120**. The track walls **122**, **124**, **126** cooperate with each other to define the respective conveyor track **104**, divider track **106**, and accessory track **108**. For example, the track walls **122**, **124**, **126** include an inner track wall **122** extending from the base member **120** adjacent to the inner side **114** of the track member **102** and partly defining the conveyor track **104**, an intermediate track wall **124** spaced apart from and cooperating with the inner track wall **122** to define the divider track **106**, and an

outer track wall **126** extending from the base member **120** at the outer side **116** and cooperating with the intermediate track wall **124** to define the accessory track **108**. Each of track walls **122**, **124**, **126** may include a respective end cap or retainer **128**, **130**, **132** formed at the distal end of the track wall **122**, **124**, **126** and configured to partially define the geometry of one of the respective tracks **104**, **106**, **108**.

[0067] The conveyor track **104** of the track member **102** is formed as a T-slot configured to receive a corresponding T-shaped coupler rail **282** of the conveyor system **200** along the inner side **114** of the track member **102**. Here, the T-slot includes a head portion **134** having a first height and a narrowed neck portion **136** having a second height that is less than the first height of the head portion **134**. The neck portion **136** defines an opening of the T-slot and faces toward the inner side **114** of the track member **102**. Here, the neck portion **136** is defined between an opposing pair of ribs **138** including a first rib **138** extending upwardly from the top side of the base member **120** and a second rib **138** extending downwardly from a distal end of an inner track wall retainer **128** formed at the distal end of the inner track wall **122**.

[0068] The divider track **106** is disposed in an intermediate portion of the track member **102** and is defined by the base member **120**, the inner track wall **122**, the intermediate track wall **124**, and the respective retainers **128**, **130** of the inner track wall **122** and the outer track wall **124**. Here, the divider track **106** is also formed as a T-slot along the top side **112** of the track member **102**. The divider track **106** includes a head portion **140** having a first width formed between the inner track wall **122** and the intermediate track wall **124** and a neck portion **142** having a second width defined between opposing ends of the retainers **128**, **130** that is less than the first width. As discussed in greater detail below, the divider track **106** is configured to receive and retain a divider coupling tab **332** in the head portion **140** while allowing the divider coupling tab **332** to be selectively inserted through an opening defined by the neck portion **142**.

[0069] The accessory track **108** is formed adjacent to the outer side **116** of the track member **102** and is defined by the base member **120**, the intermediate track wall **124**, the outer track wall **126**, and the retainers **130**, **132** formed on the respective track walls **124**, **126**. The accessory track **108** is optional and may be configured to accept various shelving accessories, such as label holders, security devices, product displays, or the like. In the illustrated example, the accessory track **108** includes an opening formed along the top side **112** of the track member **102**. The accessory track **108** may include one or more ribs or other features configured to interface with corresponding features of an accessory (e.g., a label holder) and to allow the accessory to translate along the lateral direction within the accessory track **108**.

[0070] Referring now to FIG. 2, an example of one of the conveyor units **202** of the conveyor system **200** is provided. Each conveyor unit **202** may be described as having a longitudinal axis extending from a first end **204** to a second end **206**. Thus, a length of each conveyor unit **202** is defined by a distance from the first end **204** to the second end **206**. Additionally, each conveyor unit **202** includes a first side **208** extending between the first end **204** and the second end **206** and a second side **210** formed on an opposite side from the first side **208** and extending between the first end **204** and the second end **206**. A width of each conveyor unit **202** is defined by the distance from the first side to the second side.

[0071] The conveyor unit **202** includes a conveyor frame **212** extending along the lengthwise direction of the conveyor unit **202** and a plurality of rollers **214** attached to the conveyor frame **212**. Generally, the plurality of rollers **214** are arranged in series between the first end **204** and the second end **206** of the conveyor unit **202** such that rotational axes of the rollers **214** are parallel to each other and extend between the first side **208** and the second side **210**, thereby defining a continuous support bed **16**. The conveyor unit **202** further includes a first end coupler **216** attached to the conveyor frame **212** at the first end **204** and a second end coupler **218** attached to the conveyor frame **212** at the second end **206**. As discussed in greater detail below, the first end coupler **216** and the second end coupler **218** extend different lengths from the ends **204**, **206** of the

conveyor system **200** such that the conveyor frame **212** is offset (i.e., not centered) towards the first end **204** of the conveyor unit **202**.

[0072] Referring to FIGS. 3-5B, the conveyor frame **212** includes a base **220**, a first sidewall **221** extending from a first side of the base **220**, and a second sidewall **222** extending from a second side of the base **220** on an opposite side of the conveyor frame **212** than the first sidewall **221**. The base **220** and each of the sidewalls **221**, **222** extend continuously along a length of the conveyor unit **202** from the first end **204** to the second end **206**. The conveyor frame **212** further includes a first wing **224a** attached to the conveyor frame **212** on the first side **208** and a second wing **224b** attached to the conveyor frame **212** on the second side **210**. As described below, each of the wings **224a**, **224b** are operable between a first position (FIG. 2) and a second configuration (FIG. 3) to selectively secure the rollers **214** within the conveyor frame **212**.

[0073] Referring to FIG. 4A, the base **220** includes a top side **226** and a bottom side **228** formed on an opposite side of the base **220** from the top side **226**. Optionally, the bottom side **228** of the base **220** may include a network of lower support ribs **232** extending from the bottom side **228**. The lower ribs **232** serve as both a bottom support structure for the conveyor unit **202** and a stiffening structure for the conveyor unit **202**. In some examples, the ribs **232** may be arranged as a grid pattern including longitudinal ribs **232** extending from the first end **204** to the second end **206** and lateral ribs **232** extending between the first side **208** and the second side **210** and connecting the longitudinal ribs **232**. The base **220** may further include a plurality of openings **234** formed through a thickness of the base **220** from the top side **226** to the bottom side **228**. When included, the openings **234** may be arranged in series along the length of the conveyor frame **212**.

[0074] Each of the sidewalls **221**, **222** extends from a proximal or lower end **236** attached to the base **220** to an upper or distal end **238** extending away from the base **220**. In other words, each sidewall **221**, **222** has a height extending from the top side **226** of the base **220** to the distal end **238**. Generally, the distal end **238** of each sidewall **221**, **222** is configured to receive the rollers **214** and to engage or interface with a corresponding one of the wings **224a**, **224b** to secure the rollers **214** in the conveyor frame **212**. Each sidewall **221**, **222** may be further described as having a width or thickness extending from an inner sidewall surface **240** (i.e., facing the other sidewall **221**, **222**) and an outer sidewall surface **242** formed on an opposite side from the inner sidewall surface **240**.

[0075] Referring still to FIG. 3, the distal end **238** of each sidewall **221**, **222** includes a plurality of lower sockets **244** arranged in series from the first end **204** to the second end **206** of the conveyor unit **202**. Each of the lower sockets **244** is generally configured to receive a shaft **215** or axle of one of the rollers **214** when the rollers **214** are installed in the conveyor frame **212** (FIG. 4A). In the illustrated example, each of the lower sockets **244** defines a rectangular notch in the distal end **238** of the sidewall **221**, **222**. More specifically, each lower socket **244** includes a bottom surface **250** parallel to the top side **226** of the base **220** and an opposing pair of side surfaces **252** extending from the bottom surface **250** to the distal end **238**. The rectangular configuration of the lower sockets **244** provides a universal fit capable of accommodating rollers **214** having different axle shapes (e.g., round, polygonal). In the illustrated example, the lower sockets **244** are evenly spaced along the length of each sidewall **221**, **222** and the spacing is selected to provide a desired spacing between adjacent ones of the rollers **214**.

[0076] As best shown in FIGS. 4A-5B, the distal end **238** of each sidewall **221**, **222** has a generally tapered profile between adjacent ones of the lower sockets **244**. Here, the distal end **238** is configured to interface with a corresponding profile of one of the wings **224a**, **224b** when the wing **224a**, **224b** is in the closed configuration (FIGS. 4A and 4B). As shown in FIG. 4A, the sidewall **221**, **222** has a substantially constant first thickness $T_{sub.221-1}$ between the lower end **236** and the distal end **238** and a second thickness $T_{sub.221-2}$ at the distal end **238**. In the illustrated example, the distal end **238** includes a taper from the first thickness $T_{sub.221-1}$ of the sidewall **221**, **222** to the second thickness $T_{sub.221-2}$. Optionally, the taper may include a compound taper defining an

inner shoulder **246** having a first taper rate extending from the first thickness T.sub.221-1 and a neck **248** extending from the inner shoulder **246** and having a second taper rate between the inner shoulder **246** and the second thickness T.sub.221-1. The tapered profile, and more specifically the compound taper advantageously provides a gradual transition from the first thickness T.sub.221-1 to the second thickness T.sub.221-2 and minimizes localized stresses. However, in some examples, the distal end **238** could be formed with a stepped profile (i.e., no taper) from the first thickness T.sub.221-1 to the second thickness T.sub.122.

[0077] With continued reference to FIG. **3**, the first wing **224a** is attached to the outer sidewall surface **242** of the first sidewall **221** and the second wing **224b** is attached to the outer sidewall surface **242** of the second sidewall **222**. Each of the wings **224a**, **224b** is operable between a closed configuration (FIGS. **4A-4B**) wherein the wing **224a**, **224b** captures or secures the rollers **214** within the lower sockets **244** and an open configuration (FIGS. **5A-5B**) wherein the lower sockets **244** are exposed for installation and removal of the rollers **214**.

[0078] Each wing **224a**, **224b** includes a lower end **254** attached to the conveyor frame **212** and an upper end **256** operable to move between a first position in the closed configuration and a second position in the open configuration. For example, the lower end **254** may be hingedly coupled to the outer sidewall surface **242** of one of the sidewalls **221**, **222** such that the wing **224a**, **224b** pivots about the lower end **254** to allow the upper end **256** to move between the first position and the second position. Each wing **224a**, **224b** further includes an inner wing surface **258** that faces the outer sidewall surface **242** when the wing **224a**, **224b** is in the closed configuration and an outer wing surface **260** formed on an opposite side of the wing **224a**, **224b** from the inner wing surface **258**. Each of the inner wing surface **258** and the outer wing surface **260** generally extend from the lower end **254** to the upper end **256** such that a distance between the inner wing surface **258** and the outer wing surface **260** defines a thickness T.sub.224 of the wings **224a**, **224b**.

[0079] The conveyor frame **212** may include a hinge **262** connecting the lower end **254** of each wing **224a**, **224b** to the outer sidewall surface **242**. As best shown in FIGS. **4A-5B**, the hinge **262** is provided as a living hinge **262** integrally formed with the sidewall **221**, **222** and the corresponding wing **224a**, **224b**. Here, the hinge **262** includes a reduced thickness T.sub.262 relative to the thickness T.sub.224 of the wings **224a**, **224b**. Accordingly, the hinge **262** facilitates movement of the wing **224a**, **224b** between the open configuration and the closed configuration by flexing or bending along the longitudinal direction of the conveyor frame **212**.

[0080] With continued reference to FIGS. **4A-5B**, the upper end **256** of each wing **224a**, **224b** includes a closure **264** configured to interface with or engage the distal end **238** of the corresponding sidewall **221**, **222** when the wing **224a**, **224b** is in the closed configuration. Additionally, when the wing **224a**, **224b** is in the closed configuration, the closure **264** is configured to cover each of the lower sockets **244** formed in the distal end **238** of the sidewall **221**, **222** such that the closure **264** captures a portion of one of the rollers **214** within the respective lower socket **244**.

[0081] The closure **264** includes an arm **266** extending inwardly from the inner wing surface **258** to a distal end including a rib or tooth **268** that extends away from the arm **266** towards the lower end **254** of the wing **224a**, **224b**. Accordingly, the inner wing surface **258**, the arm **266**, and the tooth **268** cooperate to define a recess **270** having an opening facing the lower end **254** of the wing **224a**, **224b**. In the illustrated example, the closure **264** includes a plurality of the teeth **268** arranged in series along a length of the wing **224a**, **224b**. The longitudinal spacing of the teeth **268** corresponds to the spacing of the lower sockets **244** formed in the distal end **238** of the sidewall **221**, **222** such that each tooth **268** is positioned between an adjacent pair of the lower sockets **244** and is configured to engage the neck **248** formed at the distal end **238**. Accordingly, adjacent or subsequent ones of the teeth **268** may be separated from each other by an upper socket **273** configured to cooperate with the lower socket **244** when the wing is in the closed configuration to capture the shaft **215** of the roller **214** within the conveyor frame **212**.

[0082] Each wing **224a**, **224b** may further include a plurality of spacers **272** and one or more longitudinal ribs **274** formed on the inner wing surface **258**. The plurality of spacers **272** are arranged in series along the inner wing surface **258** between the first end **204** and the second end **206**. Here, the longitudinal spacing of the spacers **272** is configured such that each spacer **272** contacts the outer sidewall surface **242** between adjacent ones of the lower sockets **244** when the wing **224a**, **224b**. The longitudinal ribs **274** include a pair of parallel longitudinal ribs **274** each extending along the direction from the first end **204** to the second end **206**. A first one of the longitudinal ribs **274** is disposed adjacent to the lower end **254** of the wing **224a**, **224b** and a second one of the ribs **274** is positioned between the first longitudinal rib **274** and the upper end **256** of the wing **224a**, **224b**. The longitudinal ribs **274** and the spacers **272** may cooperate to maintain a desired alignment between the wings **224a**, **224b** and the corresponding sidewalls **221**, **222** and to prevent overextension of the hinge **262** when the wings **224a**, **224b** are moved to the closed configuration.

[0083] As best shown in FIGS. **6** and **7**, the outer wing surfaces **260** of the wings **224a**, **224b** include a plurality of side couplers **276a-276d** generally configured for coupling adjacent ones of the conveyor units **202** together when assembled as part of the conveyor system **200**. In FIG. **6**, the outer wing surface **260** of the first wing **224a** includes a first side coupler **276a** adjacent to the first end **204** and a second side coupler **276b** adjacent to the second end **206**. In FIG. **7**, the outer wing surface **260** of the second wing **224b** includes a third side coupler **276c** adjacent to the first end **204** and a fourth side coupler **276d** adjacent to the second end **206**.

[0084] In the illustrated example, each of the side couplers **276a-276d** includes a pair of longitudinal ribs **278** that are spaced apart from each other by a distance $D_{sub.276a-D_{sub.276d}}$. The longitudinal ribs **278** of each side coupler **276.sub.a-276d** are spaced apart in a manner that allows the first side coupler **276a** of a first conveyor unit **202** to interface or mate with the second side coupler **276b** of a second conveyor unit **202** when the conveyor units **202** are assembled side-by-side with alternating orientations (i.e., the first side **208** of the first conveyor unit **202** faces the first side **208** of the second conveyor unit **202** or vice versa). Likewise, the longitudinal ribs **278** of the third side coupler **276c** are configured to mate or interface with the longitudinal ribs **278** of the fourth side coupler **276d** when the conveyor units **202** are assembled.

[0085] Additionally, the side couplers **276a-276d** are configured to prevent improper assembly (i.e., not alternating) of the conveyor units **202**. For example, the distances $D_{sub.276a-D_{sub.276d}}$ between the longitudinal ribs **278** of the side couplers **276a-276d** are configured such that the longitudinal ribs **278** of the first side coupler **276a** and the second side coupler **276b** will abut or interfere with the longitudinal ribs **278** of the third side coupler **276c** and the fourth side coupler **276d** if the conveyor units **202** are assembled in a non-alternating manner (i.e., first side **208** of first conveyor unit **202** facing the second side **210** of second conveyor unit **202**). This unique spacing between the longitudinal ribs **278** of the various side couplers **276a-276d** acts as a poka-yoke to ensure proper assembly (i.e., alternating) of the conveyor units **202**.

[0086] With continued reference to FIGS. **2**, **6**, and **7**, each conveyor unit **202** includes the first end coupler **216** disposed at the first end **204** and the second end coupler **218** disposed at the second end **206**. Here, each end coupler **216**, **218** is attached to a respective end of the conveyor frame **212**. In some examples, the end couplers **216**, **218** may be integrally formed with the conveyor frame **212**. Each of the end couplers **216**, **218** includes a coupler base **280a**, **280b** attached to the end of the conveyor frame **212** and a coupler rail **282** extending from the coupler base **280a**, **280b** in a direction away from the conveyor frame **212**. As discussed below, the coupler rails **282** are generally configured to interface with the track members **102** when the shelving system **10** is assembled.

[0087] Referring to FIGS. **6** and **7**, the coupler bases **280a**, **280b** each have a generally rectangular cross section extending from a proximal first side **284** attached to base **220** and the sidewalls **221**, **222** of the conveyor frame **212**, and a distal second side **286** formed on an opposite side from the

first side **284**. A distance between the first side **284** of the coupler base **280a**, **280b** and the second side **286** of the coupler base defines a length $L_{sub.280a}$, $L_{sub.280b}$ of the coupler base.

[0088] Each of the coupler rails **282** forms a first coupling element of a coupling system for securing the end **204**, **206** of the conveyor unit **202** to the track member **102**. Here, the coupler rail **282** includes a neck portion **288** having a proximal end attached to the second side **286** of the coupler base **280a**, **280b** and a head portion **290** attached to a distal end of the neck portion **288** and having a greater thickness $T_{sub.290}$ than the neck portion **288**. In the illustrated example, the coupling system is configured as a T-slot whereby each of the coupler rails **282** defines the male portion of the T-slot interface while the conveyor track **104** defines the corresponding female portion (i.e., the T-slot). However, the coupling system may be inverted such that the male portion of the interface is provided on the conveyor track **104** and the female portion of the interface is provided on the coupler rail **282**.

[0089] Optionally, the coupler bases **280a**, **280b** may have different lengths $L_{sub.280a}$, $L_{sub.280b}$ such that the first end coupler **216** extends from the first end **204** of the conveyor frame **212** a different distance than the second end coupler **218**. For example, the first coupler base **280a** of the first end coupler **216** may have a shorter length $L_{sub.280a}$ than the length $L_{sub.280b}$ of the second coupler base **280b** of the second end coupler **218**. By providing the coupler bases **280a**, **280b** with different lengths $L_{sub.280a}$, $L_{sub.280b}$, the conveyor units **202** are offset along the longitudinal direction of the conveyor system **10** towards the first end **204**. When the conveyor units **202** are installed in an alternating manner, this offset towards the first end **204** provides a corresponding offset in the alignments of the rollers **214** of adjacent ones of the conveyor units **202**. Thus, the rollers **214** of a first one of the conveyor units **202** are offset towards the front side **12** while the rollers **214** of an adjacent second one of the conveyor units **202** are offset towards the rear side **14**. Offsetting the rollers **214** of adjacent conveyor units **202** increases the overall support provided by the support bed **16** by increasing the number contact points along the length of the conveyor system **200**. In other words, offsetting the rollers **214** provides twice as many contact points for supporting merchandise compared to having the rollers **214** of adjacent conveyor units **202** aligned with each other.

[0090] Referring now to FIGS. 8-12, the divider system **300** includes a pair of divider track inserts **302** and one or more of the divider units **304**. The track inserts **302** are each configured to be disposed in the divider track **106** of one of the track members **102**. Generally, the divider system **300** is configured such that the divider units **304** can be selectively attached to each of the divider track inserts **302** by snapping the divider unit **304** into the divider track insert **302** from the top side **112** of the track member **102**. As shown in FIG. 9, each of the divider track inserts **302** is configured to be inserted into the divider track **106** from an open end of one of the track members **102**. As best shown in FIGS. 11A and 11B, the divider track insert **302** includes a receiver **310** configured to interface with one of the divider units **304** and a plurality of stabilizers **312a-312c** extending outwardly from an outer surface of the receiver **310**.

[0091] The receiver **310** of the divider track insert **302** is configured as a U-shaped body including an arcuate lower portion **314** and a pair of legs **316** extending from opposite sides of the lower portion **314**. The legs **316** and the lower portion **314** cooperate to define a lower socket **318** having an opening **320** aligned with the opening defined by the neck portion **142** of the divider track **106**. One or both of the legs **316** may include one or more protuberances **319** formed adjacent to a distal end of the leg **316** such that the opening **320** has a lesser width than a width of the lower socket **318**.

[0092] In the illustrated example, each of the stabilizers **312a-312c** extends outwardly from a proximal end **322** attached to an outer surface of the receiver **310** to a distal end **324** configured to interface with an inner surface of the divider track **106**. Particularly, the stabilizers **312a-312c** include a pair of lower stabilizers **312a** extending from an intersection between the lower portion **314** and one of the legs **316** to a distal end **324** received in a corner formed by an intersection

between the base member **120** and a respective one of the inner track wall **122** and the intermediate track wall **124**. The stabilizers **312a-312c** further include a pair of upper stabilizers **312b** extending from the distal ends of the legs **316** to distal ends **324** received in corners formed between each of the track walls **122**, **124** and the retainer **128**, **130** of the respective track wall **122**, **124**. Thus, the lower stabilizers **312a** and the upper stabilizers **312b** are vertically and longitudinally captured at each corner of the head portion **140** of the divider track **106**. Optionally, the stabilizers **312a-312c** may include any number of intermediate stabilizers **312c** extending outwardly from the receiver **310** between the lower stabilizers **312a** and the upper stabilizers **312b** such that the distal ends **324** contact one of the inner track wall **122** and the intermediate track wall **124** to further secure a position of the divider track insert **302** within the divider track **106**.

[0093] In some configurations, the divider track insert **302** may be formed as a composite structure, whereby the receiver **310** includes a first material having a first stiffness and/or coefficient of friction and the stabilizers **312a-312c** include a second material having a second stiffness and/or coefficient of friction that is different than the first material. For example, the receiver **310** may form a relatively rigid core having a first stiffness that is greater than a second stiffness of the stabilizers **312a-312c**. In other words, the stabilizers **312a-312c** may be more resilient than the core defined by the receiver **310** to allow the stabilizers **312a-312c** to flex within the divider track **106**. Additionally or alternatively, the second material of the stabilizers **312a-312c** may have a greater coefficient of friction than the first material of the receiver **310** to provide a gripping interface between the divider track insert **302** and the interior surfaces of the divider track **106**.

[0094] Optionally, the stabilizers **312a-312c** may be integrally formed with an outer shell **326** that attaches to the outer surface of the receiver **310**. The outer shell **326** and the stabilizers **312a-312c** are integrally formed with each other and may be co-extruded or co-molded with the receiver **310**.

[0095] Referring to FIG. **12**, each of the dividers **302** includes a divider wall **330** and a pair of divider coupling tabs **332** disposed at opposite ends of the divider wall **330**. Each of the divider walls **330** has a length and a height configured to provide separation between adjacent bays **18** of the shelving system **10**. Optionally, the divider wall **330** may include one or more reinforcing ribs **334** extending along a length of the divider wall **330**. In the illustrated example, the reinforcing ribs **334** are formed as distended portions of the divider wall **330** having an arcuate cross section extending along the length of the divider wall **330**. The divider wall **330** may further include a clearance notch **336** formed along the bottom side of the divider wall **330** and configured to provide a relief through which the rollers **214** can pass beneath the divider wall **330** as the divider wall is translated along the shelving system **10**.

[0096] The divider coupling tabs **332** are attached to a bottom side of the divider wall **330** at opposite ends. Particularly, the divider coupling tabs **332** include a first leg **340** attached to the bottom side of the divider wall **330** and a second leg **342** extending from the first leg **340** in a direction away from the bottom side of the divider wall **330**. Here, the first leg **340** may be described as being a “horizontal” leg configured rest atop the inner track wall retainer **128**, while the second leg **342** may be described as a “vertical” leg configured to extend downwardly and engage the receiver **310**. Thus, each of the first leg **340** and the second leg **342** may be configured with respect lengths and widths to provide a stable interface between the divider unit **304** and the track system **100**. The second leg **342** of the divider coupling tab **332** includes a projection **344** disposed adjacent to a lower, distal end of the second leg **342**. In the illustrated example, the projection **344** includes a distended portion of the second leg **340** that provides a lower portion of the second leg **342** with a thickness $T_{sub.342}$ that is greater than the width of the opening **320** of the lower socket **318**. Thus, to insert the divider coupling tab **332** into the receiver **310**, the distal end of the second leg **340** must be “snapped” into the lower socket **318** by biasing the projection **344** between the protuberances **319** of the receiver **310**.

[0097] A depth $D_{sub.344}$ of the projection **344** extends from a front surface the second leg **342** to a distal end surface **346** of the projection **344**. Optionally, the depth $D_{sub.344}$ of the projection

may be greater than a distance from the front surface of the second leg **342** to an opposing interior surface of the lower socket **318** when the lower leg **340** is fully seated within the receiver **310**. Accordingly, as shown in FIG. **11A**, a distal end surface **346** of the projection **344** may contact the interior surface of the lower socket **318** to provide a frictional interface between the second leg **342** and the receiver **310**. This frictional interface is configured to define a threshold lateral force that must be applied to the divider unit **304** to facilitate lateral movement thereof. Thus, the projection **344** may be dimensionally tuned (i.e., greater height, width, depth) or provided with frictional properties (e.g., high-friction materials) to define the desired adjustment threshold. For example, a greater adjustment threshold may be provided by increasing the friction between the projection **344** and the lower socket **318** where it is desired to make it more difficult to translate the divider unit **304** along the divider track **106**. Different adjustment thresholds may be utilized for different product types (e.g., heavy products use dividers with greater adjustment threshold).

[0098] By utilizing the continuous frictional interface provided by the receiver **310** and the divider coupling tabs **332**, the divider units **304** can be easily installed onto the shelving system **10** by snapping each of the divider coupling tabs **332** into a respective one of the divider tracks **106**. The continuous lower sockets **318** accommodate lateral misalignment of the divider coupling tabs **332** of the divider unit **304** by allowing the divider coupling tabs **332** at each end of the divider unit **304** to be snapped into the receiver **310** and then translated after installation to align the ends of the divider unit **304**. In contrast, conventional dividers utilize a locking means to prevent lateral movement or misalignment, which requires perfect lateral alignment to allow assembly of the system. This is particularly challenging in a store environment, where a user may not have clear access or visibility to the rear portion of the shelf.

[0099] With particular reference to FIGS. **13-21**, another example of a shelving system **10a** is provided. In view of the substantial similarity in structure and function of the components associated with the shelving system **10** with respect to the shelving system **10a**, like reference numerals are used hereinafter and in the drawings to identify like components while like reference numerals containing letter extensions are used to identify those components that have been modified.

[0100] Referring to FIG. **13**, a track system **100a** and a conveyor system **200a** according to another example of the disclosure are provided. As used previously, shelving system **10a** and components thereof may be described with reference to a front side **12** corresponding to a product dispensing location that may face a store aisle and a rear side **14** formed on the opposite side of the shelving system **10a** from the front side **12**. Furthermore, the shelving system **10a** and components thereof may be described relative to a longitudinal direction or axis extending from the front side **12** to the rear side **14** or a lateral direction or axis extending perpendicular to the longitudinal direction.

[0101] The shelving system **10a** may be provided as a standalone unit for use in a retail environment, or may be provided in combination with a plurality of the shelving systems **10a**. Furthermore, the shelving system **10a** may be configured for direct attachment to one or more shelving support members (not shown), such as uprights or walls, or alternatively, may be installed on existing shelves. Optionally, the shelving system **10a** may be provided as a gravity-fed shelving system **10a**, whereby the shelving system **10a** is oriented at an oblique angle relative to level such that a support bed **16** of the shelving system forms a decline from the rear side **14** of the shelving system **10a** to the front side **12** of the shelving system **10a**.

[0102] Generally, the track system **100a** includes a pair of track members **102a** each defining one or more of a conveyor track **104a** and an accessory track **108a** (FIG. **21**). The conveyor system **200a** of the shelving system **10a** includes one or more conveyor units **202a** collectively defining the support bed **16** of the shelving system **10**. In the illustrated example, the conveyor system **200a** includes a plurality of the conveyor units **202a** attached to the track system **100a** such that the conveyor units **202a** cooperate to define the support bed **16** of the shelving system **10**. With reference to FIG. **13**, the shelving system **10a** includes the track system **100a** generally configured

to facilitate attachment and lateral translation of the various components of the conveyor system **200a** and various accessories. Here, the track system **100a** includes a pair of the track members **102a**, with a first track member **102a** extending along the front side **12** and a second track member **102a** extending along the rear side **14**. While the track members **102a** of the present disclosure are shown as being identical, in some examples one of the track members **102a** may be different. For example, one of the track members **102a** may be provided without the accessory track **108a**. Alternatively, the shelving system **10a** may utilize a track system including a divider track, similar to the track system **100** provided above.

[0103] Referring to FIG. **21**, each track member **102a** includes the conveyor track **104a** and the accessory track **108a**. For the sake of description, each track member **102a** and elements thereof may be described relative to a bottom side **110**, a top side **112**, an inner side **114** configured to face inward (i.e., towards the opposite track member **102a**) and an outer side **116** configured to face outward (i.e., away from the opposite track member **102a**). While the track members **102a** illustrated in the figures are provided as integral units including both of the tracks **104a**, **108a** formed of a single piece, one or more of the tracks **104a**, **108a** may be provided as a detachable element. Furthermore, the track member **102a** may be formed with any one of or any combination of the tracks **104a**, **108a**. For example, the track member **102a** may be provided with just the conveyor track **104a** or just the accessory track **108**.

[0104] The track member **102a** includes a base member **120a** disposed along the bottom side **110** and a plurality of track walls **122a**, **126a** extending from the top side of the base member **120**. The track walls **122a**, **126a** cooperate with each other to define the respective conveyor track **104a** and accessory track **108a**. For example, the track walls **122a**, **126a** include an inner track wall **122a** extending from the base member **120a** adjacent to the inner side **114** of the track member **102a** and partly defining the conveyor track **104a** and an outer track wall **126a** extending from the base member **120a** at the outer side **116** and cooperating with the inner track wall **122a** to define the accessory track **108a**. One or both of the track walls **122a**, **126a** may include a respective end cap or retainer **128a** formed at the distal end of the track wall **122a**, **126a** and configured to partially define the geometry of one of the respective tracks **104a**, **108a**.

[0105] The conveyor track **104a** of the track member **102a** is formed as a T-slot configured to receive a corresponding T-shaped coupler element **283a**, **283b** of the conveyor system **200a** along the inner side **114** of the track member **102a**. Here, the T-slot includes a head portion **134a** having a first height and a narrowed neck portion **136a** having a second height that is less than the first height of the head portion **134a**. The neck portion **136a** defines an opening of the T-slot and faces toward the inner side **114** of the track member **102a**. Here, the neck portion **136a** is defined between an opposing pair of ribs **138a** including a first rib **138a** extending upwardly from the top side of the base member **120a** and a second rib **138a** extending downwardly from a distal end of an inner track wall retainer **128a** formed at the distal end of the inner track wall **122a**.

[0106] The accessory track **108a** is formed adjacent to the outer side **116** of the track member **102a** and is defined by the base member **120a**, the inner track wall **122a**, the outer track wall **126a**, and the retainer **128a** formed on the inner track wall **122a**. The accessory track **108a** is optional and may be configured to accept various shelving accessories, such as label holders, security devices, product displays, or the like. In the illustrated example, the accessory track **108a** includes an opening formed along the top side **112** of the track member **102a**. The accessory track **108a** may include one or more ribs or other features configured to interface with corresponding features of an accessory (e.g., a label holder) and to allow the accessory to translate along the lateral direction within the accessory track **108**.

[0107] Referring again to FIG. **13**, an example of the conveyor system **200a** is provided. As shown, the conveyor system **200a** includes a pair of conveyor units **202a** attached to the track system **100a**. However, any width of track system **100a** may be utilized to include any number of conveyor units **202a**. Each conveyor unit **202a** may be described as having a longitudinal axis extending from a

first end **204a** to a second end **206a**. Thus, a length of each conveyor unit **202a** is defined by a distance from the first end **204a** to the second end **206a**. Additionally, as indicated in FIG. 15, each conveyor unit **202a** includes a first side **208a** extending between the first end **204a** and the second end **206a** and a second side **210a** formed on an opposite side from the first side **208** and extending between the first end **204a** and the second end **206a**. A width of each conveyor unit **202a** is defined by the distance across the conveyor unit **202a** from the first side **208a** to the second side **210a**.

[0108] The conveyor unit **202a** includes a conveyor frame **212a** extending along the lengthwise direction of the conveyor unit **202a** and a plurality of the rollers **214** attached to the conveyor frame **212a**. Generally, the plurality of rollers **214** are arranged in series between the first end **204a** and the second end **206a** of the conveyor unit **202a** such that rotational axes of the rollers **214** are parallel to each other and extend between the first side **208a** and the second side **210a**, thereby defining a continuous support bed **16**.

[0109] As shown in FIG. 14, the conveyor units **202a** further include a first end coupler **216a** disposed at the first end **204a** of the conveyor frame **212a** and a second end coupler **218a** disposed at the second end **206a** of the conveyor frame **212a**. As discussed in greater detail below and illustrated in FIG. 14, the first end coupler **216a** and the second end coupler **218a** extend different lengths from the ends **204a**, **206a** of the conveyor frame **212a** such that the conveyor frame **212a** is offset (i.e., not centered) towards the first end **204a** of the conveyor unit **202a**.

[0110] Referring to FIGS. 16-18 the conveyor frame **212a** includes a base **220a**, a first frame sidewall **221a** extending from a first side of the base **220**, and a second frame sidewall **222a** extending from a second side of the base **220a** on an opposite side of the conveyor frame **212a** than the first frame sidewall **221a**. The base **220a** and each of the frame sidewalls **221a**, **222a** extend continuously along a length of the conveyor unit **202a** from the first end **204a** to the second end **206a**.

[0111] Referring to FIGS. 18 and 19, the base **220a** includes a top side **226a** and a bottom side **228a** formed on an opposite side of the base **220a** from the top side **226a**. Optionally, the base includes a central rib **233a** that extends continuously from the first end **204a** to the second end **206a**. In some examples, the base **220a** including the central rib **233a** includes a constant thickness $T_{\text{sub.220a}}$ measured from the top side **226a** to the bottom side **228a**. Thus, the central rib **233a** is defined by a portion of the base **220a** that protrudes from the top side **226a** and defines an elongate channel along the bottom side **228a** from the first end **204a** to the second end **206a**. The base **220a** may further include a plurality of openings **234a** formed through a thickness of the base **220a** on either side of the central rib **233a**. When included, the openings **234a** may be arranged in series along the length of the conveyor frame **212**.

[0112] Each of the frame sidewalls **221a**, **222a** extends from a proximal or lower end **236a** attached to the base **220a** to an upper or distal end **238a** extending away from the base **220a**. In other words, each frame sidewall **221a**, **222a** has a height extending from the top side **226a** of the base **220a** to the distal end **238a**. Generally, the distal end **238a** of each frame sidewall **221a**, **222a** is configured to receive and secure the rollers **214**. Each frame sidewall **221a**, **222a** may be further described as having a width or thickness extending from an inner sidewall surface **240a** (i.e., facing the other frame sidewall **221a**, **222a**) and an outer sidewall surface **242a** formed on an opposite side from the inner sidewall surface **240**.

[0113] Referring to FIG. 15, the distal end **238a** of each frame sidewall **221a**, **222a** includes a plurality of sockets **244a** arranged in series from the first end **204a** to the second end **206a** of the conveyor unit **202a**. Each of the sockets **244a** is generally configured to receive a shaft **215** or axle of one of the rollers **214** when the rollers **214** are installed in the conveyor frame **212a** (FIGS. 15 and 20C). In the illustrated example, each of the sockets **244a** defines cylindrical aperture extending through the thickness of the frame sidewall **221a**, **222a** (i.e., from the inner sidewall surface **240a** to the outer sidewall surface **242a**) adjacent to the distal end **238a** of the frame sidewall **221a**, **222a**. In the illustrated example, each the sockets **244a** are evenly spaced along the

length of each frame sidewall **221a**, **222a** and the spacing is selected to provide a desired spacing between adjacent ones of the rollers **214**. Optionally, each of the sockets **244a** may include a socket bearing **245a** formed on the frame sidewall **221a**, **222a**. Generally, the socket bearing **245a** is configured to provide additional bearing surface for supporting a roller shaft **215**. The socket bearing **245a** is configured to support the roller shaft **215** for rotation within the socket **244a**. As shown, the sockets bearings **245a** are defined by annular rims surrounding each socket **244a** on the outer sidewall surface **242a**. Thus, the socket bearings **245a** may correspond to a portion of the sidewall **211a**, **222b** that protrudes or has an increased thickness. As discussed below, the socket bearings **245a** may be integrally formed with the frame sidewalls **221a**, **222a** during a stamping process, whereby the socket bearings **245a** and the sidewalls **221a**, **222a** include the same materials.

[0114] As best shown in FIGS. **14**, **15**, and **19-20C**, the distal end **238a** of each frame sidewall **221a**, **222a** includes a plurality of lip elements **247a** each enclosing an upper portion of a respective one of the sockets **244a**. The lip elements **247a** are generally configured to guide the rollers **214** into the sockets **244a**. As best shown in FIG. **18**, each of the lip elements **247a** defines a recess along the inner sidewall surface **240a** at the distal end **238a**, which is configured to interface with an axle **215** of the roller **214** when each roller **214** is initially engaged with the sidewall **221a**, **222a**. While the illustrated example provides an arcuate lip element **247a** defining a concave recess relative to the inner sidewall surface **240a**, other geometries may be utilized to accommodate particular roller shaft **215** shapes. Thus, the lip element **247a** is configured to accommodate passage of the roller shaft **215** between the frame sidewalls **221a**, **222a** and into the corresponding sockets **244a** on each frame sidewall **221a**, **222b**. In some examples, a width $W_{sub.247a}$ (FIG. **19**) between opposing lip elements **247a** (i.e., laterally aligned across the conveyor frame **212a**) may be less than an overall length of the roller shafts **215**, whereby the rollers **214** must be press fit between the lip elements **247a** and into the sockets **244a**.

[0115] As best shown in FIGS. **17-20B**, the conveyor frame **212a** includes a plurality of side couplers **277a**, **277b** generally configured for coupling adjacent ones of the conveyor units **202a** together when assembled as part of the conveyor system **200a**. In FIG. **18**, an intermediate segment of the conveyor frame **212a** is illustrated and includes a first side coupler **277a** and a second side coupler **277b** spaced longitudinally from the first side coupler **277a** along each of the frame sidewalls **221a**, **222a**. Generally, the first side coupler **277a** of a first conveyor unit **202a** is configured to interface or mate with a second side coupler **277b** of an adjacent second conveyor unit **202a** when the conveyor system **200a** is assembled. This interfacing relationship between the side couplers **277a**, **277b** maintains longitudinal alignment between adjacent ones of the conveyor units **202a**.

[0116] With reference to FIGS. **18** and **19**, an opposing pair of the side couplers **277a**, **277b** is shown. Each of the side couplers **277a**, **277b** is formed adjacent to an intersection of the base **220a** and one of the frame sidewalls **221a**, **222b**. Particularly, the side couplers **277a**, **277b** may be formed during a stamping process, whereby material of each frame sidewall **221a**, **222b** is formed into each of the respective side couplers **277a**, **277b**. For example, each of the side couplers **277a**, **277b** may define a tab **277a**, **277b** that is cut from the material of the sidewall **221a**, **222b**, whereby when the frame sidewall **221a**, **222b** is folded upwardly relative to the base **220a**, the material defining each tab **277a**, **277b** remains substantially flat (i.e., parallel to the base **220a**) and a corresponding cut-out or aperture **279a**, **279b** is formed in the frame sidewall **221a**, **222a**.

[0117] With continued reference to FIG. **19**, the first side coupler **277a** extends a first length $L_{sub.277a}$ from the first frame sidewall **221a** and is substantially flush with top side **226a** of the base **220a** of the conveyor frame **212a**. Conversely, the second side coupler **277b** extends a second length $L_{sub.277b}$ from the second sidewall **222a** that is greater than the first length $L_{sub.277a}$ of the first side coupler **277a**. As shown, the second side coupler **277b** is vertically offset from the base **220a**, whereby a lower surface of the second side coupler **277b** is vertically offset from the

bottom side **228a** of the base **220a** by a distance **D.sub.227b** corresponding to a thickness **T.sub.227a** of the first side coupler **277a**. Accordingly, when adjacent conveyor units **202a** assembled, the second side coupler **277b** of one of the conveyor units **202a** overlaps the first side coupler **277a** of an adjacent conveyor unit **202a**, whereby a distal end of the second side coupler **277b** at least partially extends into the aperture **279a** associated with the first side coupler **277a**. [0118] In addition to maintaining alignment, the side couplers **277a**, **277b** are configured to prevent improper assembly (i.e., not alternating) of the conveyor units **202a**. Adjacent ones of the conveyor units **202a** are configured to be assembled in an alternating arrangement, whereby a first end **204a** of the first conveyor unit **202a** is aligned with (i.e., couples to the same track member **102a**) as a second end **206a** of an adjacent conveyor unit **202a**. The side couplers **277a**, **277b** prevent improper assembly by creating an interference if adjacent ones of the conveyor units **202a** are oriented in the same direction. For example, if assembled improperly, a distal end of one of the second side couplers **277b** will abut an outer sidewall surface **240a** of an adjacent conveyor unit **202a** rather than being received within the corresponding aperture **279a**, thereby preventing the conveyor units **202a** from being fully assembled and resulting in a gap between adjacent conveyor units **202a**.

[0119] With continued reference to FIG. **14**, each conveyor unit **202a** includes the first end coupler **216a** disposed at the first end **204a** and the second end coupler **218a** disposed at the second end **206a**. Here, each end coupler **216a**, **218a** is integrally formed with the conveyor frame **212a** at a respective end of the conveyor frame **212a**. Each of the end couplers **216a**, **218a** includes a coupler base **281a**, **281b** extending from the base **220a** of the frame **212a** and a pair of coupler ears **283a**, **283b** extending from one of the frame sidewalls **221a**, **222b**. As discussed below, the coupler bases **281a**, **281b** are formed integrally with the base **220a** of the frame **212a** and the coupler ears **283a**, **283b** are formed integrally with the respective sidewalls **221a**, **222b**, but the coupler ears **283a**, **283b** are independent of or disconnected from the coupler bases **281a**, **281b**. This configuration allows the couplers bases **281a**, **281b** to be formed using a stamping process, whereby the coupler elements **281a**, **281b**, **283a**, **283b** are cut or stamped from a common sheet of material and then formed into the conveyor frame **212a**.

[0120] As shown, each coupler base **281a**, **281b** includes a vertical neck portion extending from the base **220a** and a coupler lip extending horizontally (i.e., parallel to the base **220a**) from a distal end of the neck portion. The coupler lip defines a length **L.sub.281a**, **L.sub.281b** of the respective coupler bases **281a**, **281b** formed at each end **204a**, **206a**. For example, as shown in FIG. **14**, the length **L.sub.281a** of the coupler base **281a** formed at the first end **204a** is greater than the length **L.sub.281b** of the coupler base **281b** formed at the second end **206a**, whereby when adjacent conveyor units **202a** are assembled to the track member **102a**, the lips of the coupler base **281a**, **281b** interface with a corresponding coupler channels **143** formed in the track member **102a**.

[0121] Each of the coupler ears **283a**, **283b** forms a first coupling element of a coupling system for securing the end **204a**, **206a** of the conveyor unit **202a** to the track member **102a**. Here, the each of coupler ears **283a**, **283b** includes a neck portion **288a** having a proximal end attached to one of the frame sidewalls **221a**, **222a** and a head portion **290a** attached to a distal end of the neck portion **288** and having a greater thickness **T.sub.290** than the neck portion **288**. In the illustrated example, the coupling system is configured as a T-slot whereby each of the coupler ears **283a**, **283b** defines the male portion of the T-slot interface while the conveyor track **104a** defines the corresponding female portion (i.e., the T-slot). However, the coupling system may be inverted such that the male portion of the interface is provided on the conveyor track **104a** and the female portion of the interface is provided on end coupler **216a**, **218a**. Lengths that each of the coupler ears **283a**, **283b** extend from each end **204a**, **206a** of the conveyor frame **212a** correspond to the lengths **L.sub.281a**, **L.sub.281b** of the coupler bases **281a**, **281b**, whereby respective pairs of coupler bases **281a**, **281b**, and coupler ears **283a**, **283b** corresponding to each end **204a**, **206a** cooperate to provide adjacent ones of the conveyor units **202a** with offset longitudinal positions when

assembled to the track members **102a**. Offsetting the rollers **214** of adjacent conveyor units **202a** increases the overall support provided by the support bed **16** by increasing the number contact points along the length of the conveyor system **200a**. In other words, offsetting the rollers **214** provides twice as many contact points for supporting merchandise compared to having the rollers **214** of adjacent conveyor units **202a** aligned with each other.

[0122] With reference to FIGS. **16-18**, the conveyor frame **212a** may be formed as a modular structure including a first end segment **291a**, one or more intermediate segments **291b**, and a second end segment **291c**. As described in greater detail below with respect to FIG. **18**, the segments **291a-291c** are coupled to each other at segment joints defined by a female segment end **292** on a first one of the frame segments **291a-291c** and a male segment end **293** on another one of the frame segments **291a-291c**. Particularly, the first end segment **291a** extends from the first end **204a** including the first end coupler **216a** to an opposite end defining a female segment end **292**. Conversely, the second end segment **291c** extends from the second end **206a** including the second end coupler **218a** to an opposite end defining a male segment end **293**. The intermediate segment **291b** extends from a first end defining a female segment end **292** to a second end defining a male segment end **293**. Thus, the female segment end **292** of the intermediate segment **291b** is configured to interface with the male segment end **293** of the second end segment **291c** and the male segment end **293** of the intermediate segment **291b** is configured to interface with the female segment end **292** of the first end segment **291a**. Additional intermediate segments **291b** may be added between the first end segment **291a** and the second end segment **291c** to modify an overall length of the conveyor frame **212a**.

[0123] Turning to FIG. **18**, one of the intermediate segments **291b** is shown and includes a female segment end **292** and a male segment end **293**. The female segment end **292** is defined by terminal ends of the base **220a** and each of the frame sidewalls **221a**, **222a**. At the opposite end, the male segment end **293** includes one or more frame couplers **294**, **295** configured to overlap the female segment end **293** of an adjacent segment **291a**, **291b**, **291c** (FIG. **17**). The frame couplers **294**, **295** include one or more segment lips **294** extending from the base **220a** and a pair of segment ears **295** extending from the frame sidewalls **221a**, **222a**. As shown in FIG. **17**, the male segment end **293** includes a pair of the segment lips **294**, whereby one of the segment lips extends from the base **220a** along the longitudinal direction on each side of the central rib **233a**. The segment lips **294** extend horizontal to the base **220a**, but are offset in a vertical direction relative to the base **220a** so as to overlap the top side **226a** of a base **220a** of a corresponding female segment end **292** when assembled. Particularly, the segment lips **294** may be offset by the same distance $D_{sub.277b}$ as the second side couplers **277b** previously described.

[0124] In addition to the segment lips **294**, the male segment ends **293** include the segment ears **295** extending from each frame sidewall **221a**, **222a**. In the illustrated example, each of the segment ears **295** extends along the longitudinal direction from the respective frame sidewall **221a**, **222a** and is offset outwardly from the outer sidewall surface **242a** by a distance corresponding to the thickness of the frame sidewall **221a**, **222a**. Thus, the segment ears **295** are configured to overlap the outer sidewall surfaces **242a** of an adjacent segment **291a**, **291b** when the conveyor frame **212a** is assembled. An upper edge of each of the segment ears **295** includes a recess configured to engage one of the socket bearings **245a** of the mating segment **291a**, **291b** when the conveyor frame **212a** is assembled. For example, as shown in FIG. **17**, when the conveyor frame **212a** is assembled, a socket bearing **245a** of the front end segment **291a** rests within the recess **295a** of the segment ear **295** of the intermediate segment **291b** to secure the two segments **291a**, **291b** in the assembled state.

[0125] Each of the frame segments **291a-291c** may be manufactured as a unitary body. For example, all of the features of the frame segments **291a**, **291c**, socket bearings **245a**, the side couplers **277a**, **277b**, the segment lips **294**, and the segment ears **295** may be formed in a one or more stamping processes from a single blank or sheet of material. Thus, in addition to providing

improved functionality, the design of the frame segments **291a-291c** improves manufacturing efficiencies in comparison to systems requiring subsequent assembly steps.

[0126] With particular reference to FIGS. **22-27C**, another example of a conveyor system **200b** is provided. In view of the substantial similarity in structure and function of the components associated with the conveyor systems **200**, **200a** with respect to the conveyor system **200b**, like reference numerals are used hereinafter and in the drawings to identify like components while like reference numerals containing letter extensions are used to identify those components that have been modified.

[0127] In the illustrated example, the conveyor system **200b** includes a pair of generic conveyor units **202b** for the sake of illustrating the unique features of the conveyor system **200b** relative to the other examples of conveyor systems described herein. Thus, each of the conveyor frames **212b** is provided without any form of end couplers for attaching to a track member. However, the conveyor system **200b** may be configured with end couplers according to any of the examples provided herein.

[0128] The conveyor frame **212b** is provided as a modular structure including a conveyor chassis **219b** and a pair of frame sidewalls **221b** detachably coupled (i.e., can be detached and reattached without permanent damage to the structure) to the conveyor chassis **219b** on opposite sides. As best shown in FIGS. **23-25**, the chassis **219b** includes the base **220b** and a pair of chassis sidewalls **223b** extending along a length of the base **220a** on opposite sides. Particularly, a first one of the chassis sidewalls **223b** extends from the top side **226b** of the base **220b** along a left side and a second one of the sidewalls **223b** extends from the top side **226b** of the base along a right side. As shown, the chassis sidewalls **223b** are parallel to each other and each have a height $H_{sub.223b}$ extending to a distal end of the chassis sidewall **223b**.

[0129] The base **220b** includes a plurality of receptacles **296** configured to interface with a corresponding portion each frame sidewall **221b**. In the illustrated example, the receptacles include apertures formed through a thickness of the base **220b** adjacent to each chassis sidewall **223b**. For example, the base **220b** is shown with three receptacles **296** formed along the left chassis sidewall **223b** and three receptacles **296** formed along the right chassis sidewall **223b**. One or more of the receptacles **296** may include a base retainer **297** configured to interface with a corresponding sidewall retainer **253** of the frame sidewall **221b** to secure the frame sidewall **221b** to the base **220b**. In the illustrated example, the base retainer **297** includes a flange **297** formed adjacent to an inner side (i.e., closer to the longitudinal axis $A_{sub.219b}$) of the receptacle **296**. As shown in FIG. **27A**, the flange **297** is vertically offset from the bottom side **228b** of the base **220b** such that a bottom edge of the flange **297** is spaced apart from a shelf support surface when the base **220b** is installed a shelf support bed **16**. This space or gap between the bottom of the flange **297** and the the shelf provides an area in which the sidewall retainer **253** is received to engage the bottom of the flange **297**. Optionally, the flange **297** may be unitarily formed with the base **220a** (e.g., via stamping or molding).

[0130] With continued reference to FIGS. **24** and **25**, each of the frame sidewalls **221b** is configured to be selectively attached to the base **220b** along one of the chassis sidewalls **223b**. Generally, the frame sidewalls **221b** may be described as having a height extending in a vertical direction from the distal end **238b** at the top to a proximal end **239b**. The distal end **238b** is generally configured to receive the rollers **214** and the proximal end **239b** is generally configured for attaching to the base **220b**.

[0131] As shown in FIG. **25**, the proximal end **239b** includes a plurality of tabs **251a**, **251b** arranged along a length of the frame sidewall **221b**. The tabs **251a**, **251b** are configured to interface with the chassis sidewalls **223b** and the receptacles **296** to attach and secure the frame sidewalls **221b** to the base **220b**. The tabs **251a**, **251b** include a plurality of outer tabs **251a** and a plurality of inner tabs **251b**. As best shown in FIG. **26**, the inner tabs **251b** are spaced inwardly from the outer tabs **251a** to define a sidewall channel **255b** configured to mate with the chassis sidewall **223b**. In

the illustrated example, the outer tabs **251a** are substantially flush with and define a portion of the outer sidewall surface **242b**, while the inner tabs **251b** are inwardly offset from the inner sidewall surface **241b** to define the channel **255b**.

[0132] When the frame sidewalls **221b** are assembled to the base **220b**, the outer tabs **251a** and the inner tabs **251b** are alternately arranged along opposite sides of each chassis sidewall **223b**, whereby the tabs **251a**, **251b** straddle the chassis sidewall **223b**. The inner tabs **251b** have a length $L_{sub.251b}$ that corresponds to the height $H_{sub.223b}$ of the chassis sidewall **223b**, whereby a distal end of each inner tab **251b** extends into one of the receptacles **296** and below the flange **297**. The inner tabs **251b** may include the sidewall retainer **253** configured to engage the flange **297** adjacent to each receptacle **296**. As shown, the sidewall retainer **253** includes a tooth **253** formed on an inner surface (i.e., facing the center of the base **220b**) at the distal end of inner tab **251b**, whereby the tooth **253** is configured to “catch” the bottom edge of the flange **297** when the frame sidewall **221b** is fully engaged with the base **220b**.

[0133] With continued reference to FIG. **25**, the frame sidewalls **221b** may define an inner shoulder **249b** extending along a length of the frame sidewall **221b**. The inner shoulder **249b** is formed along the inner sidewall surface **240a** and provides a structural interface between the inner sidewall surface **240a** and the inner tabs **251b**. Namely, the inner tabs **251b** depend from a bottom side of the inner shoulder **249b** while an upper surface of the inner shoulder **249b** converges with the inner sidewall surface **240a**. Optionally, the inner shoulder **249b** may include a plurality of recesses **298** each configured to receive an end portion of an outer circumference of a roller **214**.

[0134] Referring to FIG. **24**, the frame sidewalls **221b** include a plurality of sockets **244b** arranged in series along the lengthwise direction. Each of the sockets **244b** defines an opening at the distal end **238b** of the frame sidewall **221b** for receiving one of the shafts **215** of one of the rollers **214**. In the illustrated example, each socket **244b** includes an elongate lip element **247b** extending across the opening of the socket **244b** at the distal end **238b**. The lip element **247b** is offset towards and flush with the outer sidewall surface **242b** whereby an inner guide surface **299** of the lip element **247b** is offset or recessed from the inner sidewall surface **240b**. Furthermore, the inner guide surface **299** is formed at an oblique angle relative to the inner sidewall surface **240b** and defines a ramp or biasing surface for guiding and retaining a roller shaft **215** into the socket **244**. For example, as shown in FIGS. **27A-27C**, when the frame sidewalls **221b** are installed on the base **220b**, a distance between the lip elements **247b** of the opposite sidewalls **221b** may be less than an overall length of the roller **214**, whereby the shafts **215** of the roller cannot freely drop into the sockets **244b**. Thus, a roller **214** may be installed by applying a downward force F to press the shafts **215** of the roller **214** between the lip elements **247b**, whereby the ends of the roller shafts **215** bias against the angled inner guide surface **299** of the lip element **247b** to bias or flex the distal ends **238** of the frame sidewalls **221b** outwardly in the direction $D_{sub.221b}$ (FIG. **27B**). Once the roller shafts **215** are seated within the sockets **244**, the resiliency of the frame sidewalls **221b** causes the distal ends **238** to return inwardly, whereby the shafts **215** of the rollers are captured within the sockets **244b** by a bottom side of the lip elements **247b**. In this example, the sockets **244b** have a substantially constant width $W_{sub.244b}$ that is sized to provide a slip fit with the roller shafts **215**.

[0135] With particular reference to FIGS. **28-34**, another example of a shelving system **10c** is provided. In view of the substantial similarity in structure and function of the components associated with the shelving systems **10**, **10a**, **10b** with respect to the shelving system **10c**, like reference numerals are used hereinafter and in the drawings to identify like components while like reference numerals containing letter extensions are used to identify those components that have been modified.

[0136] In the illustrated example, the shelving system **10c** includes a conveyor system **200c** including one or more conveyor units **202c** assembled to a track system **100a** in a similar manner as in the shelving system **10a** described previously. Here, each conveyor unit extends from a first

end **204c** to a second end **206c**. As shown, the conveyor system **200c** includes a pair of conveyor units **202c** for the sake of illustrating the unique features of the conveyor system **200c** relative to the other examples of conveyor systems described herein. Thus, each of the conveyor frames **212c** is provided within any form of end couplers for attaching to a track member. However, the conveyor system **200c** may be configured with end couplers according to any of the examples provided here.

[0137] The conveyor frame **212c** is provided as a modular structure including a base **220c** and a pair of frame sidewalls **221c**, **221d** detachably coupled (i.e., can be detached without permanent damage to the structure) to the base **220c** on opposite sides. As best shown in FIG. **30**, the base **220c** may be incorporated in a chassis **219c** including a pair of chassis sidewalls **223c** extending along a length of the base **220c** on opposite sides. Particularly, a first one of the chassis sidewalls **223c** extends from the top side **226c** of the base **220c** along a left side and a second one of the chassis sidewalls **223c** extends from the top side **226c** of the base along a right side. As shown, the chassis sidewalls **223c** are parallel to each other and each have a height $H_{sub.223c}$ extending to a distal end of the chassis sidewall **223c**.

[0138] The base **220c** includes a plurality of receptacles **296c** configured to interface with a corresponding portion each frame sidewall **221c**, **221d**. In the illustrated example, the receptacles **296c** include apertures formed through a thickness of the base **220c** adjacent to each chassis sidewall **223c**. Particularly, each of the receptacles **296c** includes a first portion formed through the base **220c** and a second portion formed through the chassis sidewall **223c**, whereby an upper edge of the receptacle **296c** formed in the chassis sidewall **223c** defines a base retainer **297c** (FIG. **33**) configured to interface with a corresponding retainer **253c**, **253d** of one of the frame sidewalls **221c**.

[0139] With continued reference to FIGS. **30-32**, each of the frame sidewalls **221c**, **221d** is configured to be selectively attached to the base **220c** along one of the chassis sidewalls **223c**. In the illustrated example, the frame sidewalls **221c**, **221d** include primary frame sidewalls **221c** and secondary frame sidewalls **221d** having a different length than the primary frame sidewalls **221c**. For example, the secondary frame sidewalls **221d** may have a shorter length than the primary frame sidewalls **221c**. While the lengths of the frame sidewalls **221c**, **221d** are different, the features and functions of the sidewalls **221c**, **221d** are substantially the same. Generally, a height of the frame sidewalls **221c**, **221d** may be described as extending in a vertical direction from the distal end **238c**, **238d** at the top to a proximal end **239c**, **239d** at the bottom. The distal end **238c**, **238d** is generally configured to receive the rollers **214** and the proximal end **239c**, **239d** is generally configured for attaching to the chassis **219c**.

[0140] As shown in FIGS. **30-32**, the proximal ends **239c**, **239d** of the frame sidewalls **221c**, **221d** include a plurality of tabs **251c-251e** arranged along a length of the frame sidewall **221c**, **221d**. The tabs **251c-251e** are configured to interface with the chassis sidewalls **223c** and the receptacles **296c** to attach the frame sidewalls **221c** to the base **220c**. Each frame sidewall **221c**, **221d** includes one or more outer tabs **251c**, **251e** and one or more inner tabs **251d**, **251f**. As best shown in FIG. **32** with respect to the secondary frame sidewall **221d**, the inner tabs **251d**, **251f** are spaced inwardly from the outer tabs **251c**, **251e** to define a sidewall channel **255c**, **255d** configured to mate with the chassis sidewall **223c**. In the illustrated example, the outer tabs **251c**, **251e** are substantially flush with and define a portion of the outer sidewall surface **242c**, **242d**, while the inner tabs **251d**, **251f** are inwardly offset from the inner sidewall surface **241b** to define the channel **255c**, **255d**.

[0141] When the frame sidewalls **221c**, **221d** are assembled to the base **220c**, the outer tabs **251c**, **251e** and the inner tabs **251d**, **251f** are alternatingly arranged along opposite sides of each chassis sidewall **223c**, whereby the respective pairs of tabs **251c-251f** of each frame sidewall **221c**, **221d** straddle the chassis sidewall **223c**. The outer tabs **251c**, **251e** may include one or more sidewall retainers **253c**, **253d** configured to engage the base retainer **297c** defined by the receptacle **296c**. With reference to FIG. **32**, an example of the outer tab **251e** of the secondary frame sidewall **221d**

is provided for illustration. As shown, the sidewall retainers **253c**, **253d** include a plurality of teeth **253c**, **253d** formed on an outer surface (i.e., facing away from the center of the base **220c**) at the distal end of inner tab **251e**, whereby the tooth **253c**, **253d** is configured to “catch” the base retainer **297c** (i.e., the bottom edge of the chassis sidewall **223c**, **253d** at the receptacle **296c**) when the frame sidewall **221c**, **221d** is fully engaged with the base chassis **219c**. As shown in FIG. **32**, the outer tabs **251d**, **251f** include notches or reliefs **400** that are aligned with each of the teeth **253c**, **253d**. Thus, when the frame sidewalls **221c**, **221d** are assembled to the base (FIG. **30**) and the teeth **253c**, **253d** are engaged with the receptacles **296c**, the teeth **253c**, **253d** remain exposed and accessible via the notches or reliefs **400** formed in the inner tabs **251d**, **221f**, whereby the teeth **253c**, **253d** can be disengaged from the receptacles **296c** through the notches to detach the frame sidewalls **221c**, **221d** from the base **220c**.

[0142] The frame sidewalls **221c**, **221d** may define an inner shoulder **249c**, **249d** extending along a length of the frame sidewall **221c**, **221d**. The inner shoulder **249c**, **249d** is formed along the inner sidewall surface **240c**, **240d** and provides an attachment interface between the inner sidewall surface **240c**, **240d** and the inner tabs **251d**, **251e**. Namely, the inner tabs **251d**, **251e** depend from a bottom side of the inner shoulder **249c**, **249d** while an upper surface of the inner shoulder **249c**, **249d** converges with the inner sidewall surface **240c**, **240d**. Optionally, the inner shoulder **249c**, **249d** may include a plurality of recesses **298** each configured to receive an end portion of an outer circumference of a roller **214**.

[0143] Referring to FIGS. **30-34**, the frame sidewalls **221c**, **221d** include a plurality of the sockets **244b** as previously described with respect to the frame sidewalls **221b**. Thus, a roller **214** may be installed by applying a downward force **F** to press the shafts **215** of the roller **214** between the lip elements **247b**, whereby the ends of the roller shafts **215** bias against the angled inner guide surface **299** of the lip element **247b** to bias or flex the distal ends **238** of the frame sidewalls **221c** outwardly in the direction. Once the roller shafts **215** are seated within the sockets **244b**, the resiliency of the frame sidewalls **221c** causes the distal ends **238** to return inwardly, whereby the shafts **215** of the rollers are captured within the sockets **244b** by a bottom side of the lip elements **247b**. In this example, the sockets **244b** have a substantially constant width **W.sub.244b** that is sized to provide a slip fit with the roller shafts **215**.

[0144] The conveyor units **202a** are assembled by initially aligning the channels **255c**, **255d** formed in the proximal ends **239c**, **239d** of the frame sidewalls **221c**, **221d** with the distal ends of the chassis sidewalls **223c**. Additionally, the sidewall retainers **253c**, **253d** are vertically aligned with the respective receptacles **296c**. The sidewalls **221c**, **221d** are then lowered onto the chassis sidewalls **223c** such that the chassis sidewalls **223c** are received within the channels **255c**, **255d** and the sidewall retainers **253c**, **253d** “snap” into the receptacles **296c**. Here, a top edge of the sidewall retainer **253c**, **253c** engages the lower edge defining the base retainer **297c** to secure a vertical position of the frame sidewall **221c**, **221d**. The rollers **214** are then assembled to the conveyor unit in the manner described above.

[0145] The frame chassis **219c** may include a first material, such as a metal, and the frame sidewalls **221c**, **221d** may include a second material, such as a polymeric material. Thus, the features of the frame chassis **219c** may be formed using metal stamping processes and the features of the frame sidewalls **221c**, **221d** may be formed using polymer molding processes, such as injection molding. By providing a hybrid structure including metal and polymers, material properties and manufacturing processes are improved by providing the chassis **219c** with increased strength and simplified manufacturing while still allowing the frame sidewalls **221c**, **221d** to be formed with more complex geometries permitted by polymer molding.

[0146] Example configurations are provided so that this disclosure will be thorough, and will fully convey the scope of the disclosure to those of ordinary skill in the art. Specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of configurations of the present disclosure. It will be apparent to those of ordinary

skill in the art that specific details need not be employed, that example configurations may be embodied in many different forms, and that the specific details and the example configurations should not be construed to limit the scope of the disclosure.

[0147] The terminology used herein is for the purpose of describing particular exemplary configurations only and is not intended to be limiting. As used herein, the singular articles “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. Additional or alternative steps may be employed.

[0148] When an element or feature is referred to as being “on,” “engaged to,” “connected to,” “attached to,” or “coupled to” another element or layer, it may be directly on, engaged, connected, attached, or coupled to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly engaged to,” “directly connected to,” “directly attached to,” or “directly coupled to” another element or layer, there may be no intervening elements or layers present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.). As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0149] The terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections. These elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another region, layer or section. Terms such as “first,” “second,” and other numerical terms do not imply a sequence or order unless clearly indicated by the context. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the example configurations.

Claims

1. A conveyor system for a retail shelf, the conveyor system comprising: one or more conveyor units each including: a base extending from a first end to a second end; and a first side attached to the base and having a (i) first side coupler including a first pair of ribs disposed adjacent to the first end of the base and spaced apart from each other by a first distance and (ii) a second side coupler including a second pair of ribs disposed adjacent to the second end of the base and spaced apart from each other by a second distance that is less than the first distance.
2. The conveyor system of claim 1, wherein each of the one or more conveyor units includes a second side attached to an opposite side of the base from the first side and having (i) a third side coupler including a third pair of ribs disposed adjacent to the first end of the base and spaced apart from each other by a third distance and (ii) a fourth side coupler including a fourth pair of ribs disposed adjacent to the second end of the base and spaced apart from each other by a fourth distance that is greater than the first distance.
3. The conveyor system of claim 2, wherein the third distance is less than the first distance and greater than the second distance.
4. The conveyor system of claim 2, wherein the fourth distance is greater than the first distance.
5. The conveyor system of claim 1, wherein the first side coupler of a first one of the one or more conveyor units is configured to mate with the second side coupler of a second one of the one or

more conveyor units.

6. The conveyor system of claim 5, wherein the first side coupler of the first one of the one or more conveyor units is configured to interfere with the third side coupler of the second one of the one or more conveyor units.

7. The conveyor system of claim 2, wherein the first side includes a first plurality of sockets arranged in series between the first end and the second end.

8. The conveyor system of claim 7, wherein the second side includes a second plurality of sockets arranged in series between the first end and the second end.

9. The conveyor system of claim 8, wherein at least one of the first plurality of sockets or the second plurality of sockets is enclosed.

10. The conveyor system of claim 1, further comprising a plurality of roller units each including a first roller shaft at a first end and a second roller shaft at an opposite second end.

11. A conveyor system for a retail shelf, the conveyor system comprising: a conveyor chassis formed of a first material and including a base and a chassis sidewall extending a first height from the base; and a frame sidewall formed separately from the conveyor chassis of a second material and including a proximal end defining a sidewall channel configured to receive the chassis sidewall and an opposite distal end including a plurality of sockets.

12. The conveyor system of claim 11, wherein the frame sidewall includes one or more tabs cooperating to define the sidewall channel at the proximal end of the frame sidewall.

13. The conveyor system of claim 12, wherein the one or more tabs includes one or more inner tabs extending from a first side of the frame sidewall and one or more outer tabs extending from an opposite second side of the frame sidewall and separated from the inner tabs by the sidewall channel.

14. The conveyor system of claim 11, wherein the conveyor chassis includes at least one end coupler attached at an end of the conveyor chassis.

15. The conveyor system of claim 14, wherein the end coupler includes at least one coupler ear integrally formed with one of the sidewalls and coupler base integrally formed with the base, the coupler ear being independent from the coupler base.

16. A conveyor system for a retail shelf, the conveyor system comprising: a base, a first sidewall extending from the base to a first distal end including a first plurality of sockets defining an aperture extending through a thickness of the first sidewall; and a second sidewall extending from the base to a second distal end and including a second plurality of sockets each defining an aperture extending through a thickness of the second sidewall.

17. The conveyor system of claim 16, wherein at least one of the first plurality of sockets or the second plurality of sockets includes enclosed sockets.

18. The conveyor system of claim 17, wherein at least one of the first plurality of sockets or the second plurality of sockets includes a lip element disposed adjacent to or along the socket.

19. The conveyor system of claim 18, further comprising a plurality of rollers each including a first shaft at a first end configured to engage one of the first plurality of sockets and a second shaft at a second end configured to engage a one of the second plurality of sockets.

20. The conveyor system of claim 19, wherein the first plurality of the sockets include lip elements and a length of the roller from the first shaft to the second shaft is greater than a distance from the lip elements to the second sidewall.
