

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250263980

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Kolste; Tyler et al.

---

### BEARING ASSEMBLIES, APPARATUSES, AND METHODS INCLUDING BEARING ELEMENTS

---

#### Abstract

Bearing assemblies, apparatuses, systems, and methods include bearing assemblies where one of the bearing assemblies may include bearing surfaces defining an at least partially conical surface.

---

**Inventors:** Kolste; Tyler (American Fork, UT), Wise; Daryl (Provo, UT), Peterson; S. Barrett (Orem, UT)

**Applicant:** US Synthetic Corporation (Orem, UT)

**Family ID:** 1000008586920

**Appl. No.:** 19/203072

**Filed:** May 08, 2025

#### Related U.S. Application Data

parent US continuation 18502624 20231106 parent-grant-document US 12297716 child US 19203072

parent US continuation 18126259 20230324 parent-grant-document US 11814902 child US 18502624

parent US continuation 17318365 20210512 parent-grant-document US 11619099 child US 18126259

---

#### Publication Classification

**Int. Cl.:** E21B4/00 (20060101); F16C17/10 (20060101); F16C33/04 (20060101)

**U.S. Cl.:**

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/502,624, filed Nov. 6, 2023, for “BEARING ASSEMBLIES, APPARATUSES, AND METHODS INCLUDING BEARING ELEMENTS,” which application is a continuation of U.S. patent application Ser. No. 18/126,259, filed Mar. 24, 2023, for “BEARING ASSEMBLIES, APPARATUSES, AND METHODS INCLUDING BEARING ELEMENTS,” which application is a continuation of U.S. patent application Ser. No. 17/318,365, filed May 12, 2021, for “BEARING ASSEMBLIES, APPARATUSES, AND METHODS INCLUDING BEARING ELEMENTS,” the disclosure of each of which is incorporated herein in its entirety by reference.

## TECHNICAL FIELD

[0002] This application relates to bearings assemblies including bearing elements and related assemblies, apparatuses, and methods.

## BACKGROUND

[0003] Thrust and bearing apparatuses are commonly used in a variety of mechanical applications. For example, subterranean drilling systems, turbomachinery, hydroelectric plants, windmills, cranes, turbine generators, pumps, and power plant machinery may utilize bearing assemblies.

[0004] A subterranean drilling system may include one or more thrust-bearing and/or bearing apparatuses that are operably coupled to the downhole drilling motor for carrying loads generated during drilling operations. Bearing apparatuses utilized in such drilling systems may each include a stator that does not rotate and a rotor that is surrounded by the stator and that is attached to the output shaft to rotate with the output shaft. The stator and rotor may each include a plurality of superhard bearing elements or inserts.

[0005] Wear-resistant, superhard materials may be utilized for bearing elements utilized in bearing assemblies. A polycrystalline diamond compact (PDC) bearing assembly may include steel rotor and stator bearing rings that are each configured to accept a number of superhard bearing elements. Each superhard bearing element may include a polycrystalline diamond (PCD) layer formed on a substrate, such as a cemented tungsten carbide substrate. One or more superhard bearing elements may be attached to a bearing rotor or stator by press-fitting, brazing, or through other suitable methods of attachment. Typically, bearing elements attached to a bearing rotor have superhard bearing surfaces configured and oriented radially outward to bear against opposing superhard bearing surfaces of bearing elements attached to a bearing stator that radially surrounds the bearing rotor.

[0006] During drilling operations, an output shaft that transfers rotational torque from a drilling motor to a drill bit may be deflected at various angles relative to the rotational axis of a bearing apparatus. Over time, such repeated deflection of the output shaft may cause a bearing rotor attached to the output shaft to become axially misaligned with respect to a bearing stator surrounding the bearing rotor. Axial misalignment of the bearing rotor from the bearing stator may result in a decrease in bearing performance or bearing failure.

## SUMMARY

[0007] Embodiments of the instant disclosure may be directed to bearing assemblies systems, and bearing apparatuses. According to some embodiments, a bearing apparatus may comprise an inner bearing assembly and an outer bearing assembly. The inner bearing assembly may comprise an inner support ring positioned about an inner bearing axis and one or more inner bearing elements

coupled to the inner support ring. The one or more inner bearing elements may each have an outward-facing bearing surface exhibiting a partially spherical convex shape. The outer bearing assembly may comprise an outer support ring positioned about an outer bearing axis and outer bearing elements coupled to the outer support ring. The outer bearing elements may each have an inward-facing bearing surface exhibiting a partially cylindrical concave shape, where the cylindrical concave shape of each of the outer bearing elements collectively define an at least partially conical inner surface substantially centered about the inner bearing axis. The at least partially conical inner surface of the outer bearing elements may be configured to engage with the outward-facing bearing surface of each of the one or more inner bearing elements.

[0008] According to some embodiments, a bearing apparatus may comprise a first bearing assembly and a second bearing assembly. The first bearing assembly may comprise a first support ring positioned circumferentially around a first bearing axis and one or more first bearing elements coupled to the first support ring. The one or more first bearing elements may each have an outward-facing bearing surface. The second bearing assembly may comprise a second support ring positioned circumferentially around a second bearing axis and second bearing elements coupled to the second support ring. The second bearing elements may each have an inward-facing bearing surface collectively defining an at least partially conical surface substantially centered about the second bearing axis. The at least partially conical surface of the second bearing elements may be configured to engage with the outward-facing bearing surface of each of the one or more first bearing elements.

[0009] According to some embodiments a method of forming a bearing assembly may comprise forming an inner bearing assembly comprising coupling one or more inner bearing elements to an inner support ring; and orienting the one or more inner bearing elements to each define an outward-facing bearing surface. The method may further include forming an outer bearing assembly comprising coupling outer bearing elements to an outer support ring; orienting the outer bearing elements to define an inward-facing bearing surface; collectively defining an at least partially conical inner surface with the outer bearing elements; and positioning the inner bearing assembly at least partially within the outer bearing assembly such that the at least partially conical inner surface of the outer bearing elements engage with the outward-facing bearing surface of each of the one or more inner bearing elements.

[0010] Features from any of the above-mentioned embodiments may be used in combination with one another in accordance with the general principles described herein. These and other embodiments, features, and advantages will be more fully understood upon reading the following detailed description in conjunction with the accompanying drawings and claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The accompanying drawings illustrate a number of exemplary embodiments and are a part of the specification. Together with the following description, these drawings demonstrate and explain various principles of the instant disclosure.

[0012] FIG. 1 is a perspective view of a bearing apparatus according to an embodiment of the disclosure.

[0013] FIG. 2 is a cross-sectional view of the bearing apparatus shown in FIG. 1.

[0014] FIG. 3 is a perspective view of a bearing assembly according to an embodiment of the disclosure.

[0015] FIG. 4 is a cross-sectional view of a portion of the bearing apparatus shown in FIG. 3.

[0016] FIG. 5 is a perspective view of a bearing assembly according to an embodiment of the disclosure.

[0017] FIG. **6** is a cross-sectional view of a portion of the bearing apparatus shown in FIG. **5**.  
[0018] FIG. **7** is another cross-sectional view of a portion of the bearing apparatus shown in FIG. **5**.  
[0019] FIG. **8** is a cross-sectional view of a portion of a bearing apparatus according to an embodiment of the disclosure.  
[0020] FIG. **9** is a cross-sectional view of a portion of a bearing apparatus according to an embodiment of the disclosure.  
[0021] FIG. **10** is a partial cut-away perspective view of a subterranean drilling system including one or more bearing apparatus according to an embodiment of the disclosure.

#### DETAILED DESCRIPTION

[0022] The instant disclosure is directed to exemplary bearing assemblies and bearing apparatuses including superhard bearing elements. These bearing apparatuses may include radial bearings, thrust bearings, and other bearing apparatuses without limitation. Such bearing apparatuses may be used in a variety of applications, including subterranean drilling systems, directional drilling systems, turbine generators, windmills, cranes, machinery, pumps, and any other suitable applications, without limitation.

[0023] The terms “superabrasive” and “superhard,” as used herein, may refer to any material having a hardness that is at least equal to a hardness of tungsten carbide. For example, a superhard article may represent an article of manufacture, at least a portion of which may exhibit a hardness that is equal to or greater than the hardness of tungsten carbide.

[0024] As used herein, relational terms, such as “first,” “second,” “top,” “bottom,” etc., are generally used for clarity and convenience in understanding the disclosure and accompanying drawings and do not connote or depend on any specific preference, orientation, or order, except where the context clearly indicates otherwise.

[0025] As used herein, the term “and/or” means and includes any and all combinations of one or more of the associated listed items.

[0026] As used herein, the terms “vertical,” “lateral,” and “radial” refer to the orientations as depicted in the figures.

[0027] As used herein, the term “substantially” or “about” in reference to a given parameter means and includes to a degree that one skilled in the art would understand that the given parameter, property, or condition is met with a small degree of variance, such as within acceptable manufacturing tolerances. For example, a parameter that is substantially met may be at least 90% met, at least 95% met, at least 99% met, or even 100% met.

[0028] FIG. **1** is a perspective view of a bearing apparatus **100** (e.g., in a primarily thrust bearing configuration) according to at least one embodiment and FIG. **2** is a cross-sectional view of the bearing apparatus **100**. As illustrated in FIGS. **1** and **2**, the bearing apparatus **100** may be configured as a thrust bearing to primarily support axial loads. For example, the bearing apparatus **100** may be configured to support a load where a majority of the load is applied in an axial direction and where a lesser amount of load is applied in a lateral or radial direction. In additional embodiments, and as discussed below, the bearing apparatus **100** may be configured as radial bearing configured to primarily support radial loads. For example, the bearing apparatus **100** may be configured to support a load where a majority of the load is applied in a lateral or radial direction and where a lesser amount of load is applied in an axial direction.

[0029] As depicted in FIG. **3**, bearing apparatus **100** may comprise a first bearing assembly **102** (e.g., an inner race or assembly) having bearing elements **104** (e.g., superhard bearing elements) coupled to a first support structure **106** and arranged about a central point or inner bearing axis **107**. The bearing elements **104** may be positioned in the first support structure **106** at a substantially similar or the same oblique angle relative to the inner bearing axis **107**.

[0030] As shown in FIG. **5**, bearing apparatus **100** may additionally comprise a second bearing assembly **108** (e.g., an outer race or assembly) having bearing elements **110** (e.g., superhard bearing elements) coupled to a second support structure **112** and arranged about a central point or

outer bearing axis **113**. As depicted, a portion of the first support structure **106** of the first bearing assembly **102** may be received in the second support structure **112** of the second bearing assembly **108**. The bearing elements **110** may be positioned in the second support structure **112** at a substantially similar or the same oblique angle relative to the outer bearing axis **113**.

[0031] In some embodiments, either of first bearing assembly **102** and second bearing assembly **108** may be configured as a rotor or a stator. For example, if second bearing assembly **108** is configured to remain stationary, second bearing assembly **108** may be referred to as the stator and the first bearing assembly **102** may be referred to as the rotor that moves (e.g., rotates, pivots, oscillates, swivels, etc.) relative to second bearing assembly **108**. Additionally, the first bearing assembly **102** may be a stator configured to remain stationary and second bearing assembly **108** may be a rotor configured to move (e.g., rotates, pivots, oscillates, swivels, etc.) relative to first bearing assembly **102**. In some embodiments, both the first bearing assembly **102** and the second bearing assembly **108** may move (e.g., rotates, pivots, oscillates, swivels, etc.) relative to each other.

[0032] First bearing assembly **102** and second bearing assembly **108** may each be arranged circumferentially around a central bearing axis (e.g., longitudinal axis **114**). The longitudinal axis **114** may comprise a rotational axis about which first bearing assembly **102** or second bearing assembly **108** rotates. However, a rotational axis of first bearing assembly **102** and/or second bearing assembly **108** may not be aligned with longitudinal axis **114** at all times during operation. For example, during a drilling operation, second bearing assembly **108** may be circumferentially centered about longitudinal axis **114** while the first bearing assembly **102** is circumferentially centered about and/or rotates about a rotational axis that is oriented at an angle with respect to the longitudinal axis **114**.

[0033] While the assemblies **102**, **108** are discussed as rotating (e.g., one relative to the other and/or both together), some embodiments may involve additional and/or differing types of movement. For example, the first bearing assembly **102** and the second bearing assembly **108** may define a revolute and/or spheroid joint (e.g., a hip joint and/or a ball joint) that enables the first bearing assembly **102** and the second bearing assembly **108** to rotate about differing axes (e.g., radial axes), pivot, oscillate, and/or swivel relative to each other. In some embodiments, a shaft coupled to the first bearing assembly **102** may pivot as the first bearing assembly **102** moves with the second bearing assembly **108** while partially rotating or substantially not rotating relative to the second bearing assembly **108** or vice versa. By way of further example, the first bearing assembly **102** may move (e.g., slide) about a radial axis within a bowl defined by the second bearing assembly **108** (e.g., as the first bearing assembly **102** partially moves into and back out of the bowl).

[0034] First support structure **106** may comprise an outer surface **116** facing radially outward that opposes an inner surface **118** of the second support structure **112** that faces radially inward with respect to the longitudinal axis **114**.

[0035] Bearing apparatus **100** may include a central aperture **120** defined the first support structure **106** and/or the second support structure **112** that may receive a shaft (e.g., a rotational motor shaft). As depicted, aperture **120** may be generally centered about longitudinal axis **114**.

[0036] First support structure **106** may be configured to receive multiple bearing elements **104** that may each be attached within a corresponding recess **122** defined in first support structure **106**. Second support structure **112** may be configured to receive multiple bearing elements **110** that may each be attached within a corresponding recess **124** defined in second support structure **112**. Each bearing element **104** may extend beyond outer surface **116** of first support structure **106** by a selected distance and/or profile. Each bearing element **110** may extend beyond inner surface **118** of second support structure **112** by a selected distance and/or profile. Each of bearing elements **104** and bearing elements **110** may be fixedly secured within a corresponding recess **122**, **124**, respectively, through brazing, press-fitting, threaded attachment, pin attachment, bonding, frictional

engagement, and/or by any other suitable attachment mechanism, without limitation.

[0037] Any suitable number of bearing elements **104** and bearing elements **110** may be secured, respectively, to first support structure **106** and second support structure **112**. For example, each bearing element **104** may be secured within the corresponding recess **122** defined in first support structure **106**. Additionally, each bearing element **110** may be secured within the corresponding recess **124** defined in second support structure **112**. First bearing assembly **102** may comprise the same number or a different number of bearing elements **104** in comparison with the number of bearing elements **110** included in second bearing assembly **108**. Additionally, bearing elements **104** may have substantially the same size/dimension (e.g., diameters) as bearing elements **110** or different size/dimension than bearing elements **110**.

[0038] First support structure **106** and second support structure **112** may each be made from a variety of different materials. For example, first support structure **106** and/or second support structure **112** may comprise a metallic material (e.g., carbon steel, titanium or titanium alloys, tungsten or tungsten alloys, aluminum or aluminum alloys, or stainless steel, etc.), a carbide material (e.g., tungsten carbide, silicon carbide, etc.), or any other suitable material. In some embodiments, first support structure **106** and/or second support structure **112** may be made of a material with relatively high thermal conductivity (e.g., a thermal conductivity equal to or exceeding tungsten carbide or cobalt-cemented tungsten carbide). Bearing elements **104**, **110** may each abut or contact a respective support structure **106**, **112** over a selected (e.g., a substantial) surface area of the bearing element **104**, **110** in order to promote heat transfer from the bearing element **104**, **110** to support structure **106**, **112**.

[0039] In some embodiments, first support structure **106** and/or second support structure **112** may include an erosion-resistant and/or abrasion-resistant coating applied thereto. For example, an erosion-resistant and abrasion resistant coating may include a coating including, for example, a urethane rubber or other suitable coating, without limitation. In other embodiments, a hardfacing coating (e.g., tungsten carbide hardfacing) may be applied to first support structure **106** and/or second support structure **112** by any suitable method, including, without limitation, flame spraying, welding HVOF (high velocity oxy-fuel coating spraying), and/or laser cladding.

[0040] In some embodiments, bearing elements **104** may be positioned and oriented on first support structure **106** and bearing elements **110** may be positioned and oriented on second support structure **112** such that bearing surfaces of one or more of bearing elements **104** contact opposing bearing surfaces of one or more of bearing elements **110**, respectively. When first bearing assembly **102** and second bearing assembly **108** are assembled together (e.g., in a ball-and-socket-type configuration), bearing surfaces of bearing elements **104** and the opposing bearing surfaces of bearing elements **110** may bear against each other and move relative to each other as first bearing assembly **102** rotates relative to second bearing assembly **108**. As will be described in greater detail below, bearing elements **104** and bearing elements **110** may comprise various surface shapes and configurations for achieving desired contact and freedom of movement between opposing bearing surfaces.

[0041] As depicted, an interface between the bearing elements **104** and bearing elements **110** may define a selected angle  $\theta_{sub.1}$  with respect to the longitudinal axis **114**. For example, operating primarily as a thrust bearing, the angle  $\theta_{sub.1}$  of the interface between the bearing elements **104**, **110** may be 45 degrees or more (e.g., 45 to 90 degrees, 60 degrees, 50 to 70 degrees, etc.) relative to the longitudinal axis **114**.

[0042] FIG. 3 is a perspective view of a bearing assembly including bearing elements on a support structure (e.g., first bearing assembly **102**). As illustrated in FIG. 3, bearing elements **104** may be mounted within the first support structure **106**. Bearing elements **104** may each extend radially outward from the first support structure **106** such that at least a portion of the bearing element **104** extends past an outer surface **116** of first support structure **106**. A portion of bearing element **104** extending from first support structure **106** may comprise a bearing surface **126** (e.g., a superhard

bearing surface).

[0043] Bearing surface **126** may comprise any suitable shape, without limitation (e.g., a planar shape, a rounded or curved shape (e.g., a partially ovoid, partially ellipsoid, partially spheroid, or otherwise elliptical shape), a convex shape, a concave shape, a conical shape, a cylindrical shape, combinations thereof, etc.). For example, bearing surface **126** may comprise an at least partially rounded or ellipsoidal convex surface (e.g., where the surface is rounded or curved in at least two traverse axes of direction). In some embodiments, bearing surface **126** may comprise a partially ellipsoidal, a partially cylindrical surface (e.g., a convex cylindrical surface), and/or partially spherical shape.

[0044] As depicted by the dashed lines in FIG. 3, the bearing surfaces **126** and/or the angular orientation of the first support structure **106** that positions the bearing elements **104** may collectively define a convex, partially spherical shape. Where the individual bearing surfaces **126** each exhibit partial spherical convex surface, at least a portion of each of the individual bearing surfaces **126** may define (e.g., fall within) the overall or collective convex, partially spherical shape of the first bearing assembly **102** (e.g., defined by the plurality of the spherical bearing surfaces **126**, a majority of the bearing surfaces **126**, and/or a substantial entirety of the bearing surfaces **126**, without limitation).

[0045] FIG. 4 is a cross-sectional view of a portion of the bearing assembly **102** shown in FIG. 3. As shown in FIG. 4, bearing element **104** may comprise a superhard table **128** affixed to or formed upon a substrate **130**. Superhard table **128** may be affixed to substrate **130** at interface **132**.

[0046] Bearing element **104** may also include a chamfer **134** between a side surface and bearing surface **126**. Chamfer **134** may comprise an angular, sloped, and/or rounded edge formed at the intersection of superhard side surface and bearing surface **126**. Any suitable surface shape may be formed at the intersection of superhard side surface and bearing surface **126**, such as those disclosed in U.S. Pat. No. 8,708,564, the disclosure of which is incorporated herein in its entirety by this reference. Any other suitable surface shape may also be formed between superhard side surface and bearing surface **126**, including, without limitation, an arcuate surface (e.g., a radius, an ovoid shape, or any other rounded shape), a sharp edge, multiple chamfers/radii, a honed edge, and/or combinations of the foregoing.

[0047] Bearing element **104** may comprise any suitable size, shape, and/or geometry, without limitation. As depicted, bearing surface **126** may comprise a convex, partial-ellipsoidal or substantially partial-ellipsoidal surface shape. A cross-sectional view of bearing element **104** taken along a plane parallel to the central element axis may have a convex, partial-circular or substantially partial-circular profile for bearing surface **126** as shown in FIG. 4. In some embodiments, bearing surface **126** may comprise a partial-spherical shape or a substantially partial-spherical surface shape. In such embodiments, each cross-sectional view of bearing element **104** taken along a plane intersecting a central element axis of the bearing element **104** may have substantially the same or similar profile.

[0048] In some embodiments, the individual bearing surfaces **126** of the bearing elements **104** may each exhibit a convex shape that, taken together, collectively define a substantially partial-spherical or frusto-spherical shape.

[0049] Substrate **130** may comprise any suitable material on which superhard table **128** may be formed. In at least one embodiment, substrate **130** may comprise a cemented carbide material, such as a cobalt-cemented tungsten carbide material and/or any other suitable material. In some embodiments, substrate **130** may include a suitable metal-solvent catalyst material, such as, for example, cobalt, nickel, iron, and/or alloys thereof. Substrate **130** may also include any suitable material including, without limitation, cemented carbides such as titanium carbide, tungsten carbide, niobium carbide, tantalum carbide, vanadium carbide, chromium carbide, and/or combinations of any of the preceding carbides cemented with iron, nickel, cobalt, and/or alloys thereof. Superhard table **128** may be formed of any suitable superabrasive and/or superhard

material or combination of materials, including, for example PCD. Any of the superhard tables disclosed herein may also comprise polycrystalline diamond materials, such as those disclosed in U.S. Pat. No. 7,866,418, the disclosure of which is incorporated herein, in its entirety, by this reference. According to additional embodiments, superhard table **128** may comprise cubic boron nitride, silicon carbide, polycrystalline diamond, and/or mixtures or composites including one or more of the foregoing materials, without limitation.

[0050] Superhard table **128** of bearing element **104** may be formed using any suitable technique. According to some embodiments, superhard table **128** may comprise a PCD table fabricated by subjecting a plurality of diamond particles to a high pressure, high temperature (HPHT) sintering process in the presence of a metal-solvent catalyst (e.g., cobalt, nickel, iron, or alloys thereof) to facilitate intergrowth between the diamond particles and form a PCD body comprised of bonded diamond grains that exhibit diamond-to-diamond bonding therebetween. For example, the metal-solvent catalyst may be mixed with the diamond particles, infiltrated from a metal-solvent catalyst foil or powder adjacent to the diamond particles, infiltrated from a metal-solvent catalyst present in a cemented carbide substrate, or combinations of the foregoing. The bonded diamond grains (e.g., sp<sup>3</sup>-bonded diamond grains), so-formed by HPHT sintering the diamond particles, define interstitial regions with the metal-solvent catalyst disposed within the interstitial regions of the as-sintered PCD body. The diamond particles may exhibit a selected diamond particle size distribution or mixture.

[0051] Following sintering, various materials, such as a metal-solvent catalyst, remaining in interstitial regions within the as-sintered PCD body may reduce the thermal stability of superhard table **128** at elevated temperatures. In some examples, differences in thermal expansion coefficients between diamond grains in the as-sintered PCD body and a metal-solvent catalyst in interstitial regions between the diamond grains may weaken portions of superhard table **128** that are exposed to elevated temperatures, such as temperatures developed during bearing operation. The weakened portions of superhard table **128** may become excessively worn and/or damaged during bearing operation.

[0052] Removing the metal-solvent catalyst and/or other materials from the as-sintered PCD body may improve the heat resistance and/or thermal stability of superhard table **128**, particularly in situations where the PCD material may be exposed to elevated temperatures. A metal-solvent catalyst and/or other materials may be removed (e.g., at least partially removed) from the as-sintered PCD body using any suitable technique, including, for example, leaching. In at least one embodiment, a metal-solvent catalyst, such as cobalt, may be removed from regions of the as-sintered PCD body, such as regions adjacent to the working surfaces of superhard table **128**. Removing a metal-solvent catalyst from the as-sintered PCD body may reduce damage to the PCD material of superhard table **128** caused by expansion of the metal-solvent catalyst.

[0053] At least a portion of a metal-solvent catalyst, such as cobalt, as well as other materials, may be removed from at least a portion of the as-sintered PCD body using any suitable technique, without limitation. For example, chemical and/or gaseous leaching may be used to remove a metal-solvent catalyst from the as-sintered PCD body up to a desired depth from a surface thereof. The as-sintered PCD body may be leached by immersion in an acid, such as aqua regia, nitric acid, hydrofluoric acid, or subjected to another suitable process to remove at least a portion of the metal-solvent catalyst from the interstitial regions of the PCD body and form superhard table **128** comprising a PCD table. For example, the as-sintered PCD body may be immersed in or exposed to the acid for about 2 to about 7 days (e.g., about 3, 5, or 7 days) or for a few weeks (e.g., about 4 weeks) depending on the process employed.

[0054] Even after leaching, a residual, detectable amount of the metal-solvent catalyst may be present in the at least partially leached superhard table **128**. It is noted that when the metal-solvent catalyst is infiltrated into the diamond particles from a cemented tungsten carbide substrate including tungsten carbide particles cemented with a metal-solvent catalyst (e.g., cobalt, nickel,



iron, or alloys thereof), the infiltrated metal-solvent catalyst may carry tungsten and/or tungsten carbide therewith and the as-sintered PCD body may include such tungsten and/or tungsten carbide therein disposed interstitially between the bonded diamond grains. The tungsten and/or tungsten carbide may be at least partially removed by the selected leaching process or may be relatively unaffected by the selected leaching process.

[0055] In some embodiments, only selected portions of the as-sintered PCD body may be leached, leaving remaining portions of resulting superhard table **128** in an unleached state. For example, some portions of one or more surfaces of the as-sintered PCD body may be masked or otherwise protected from exposure to a leaching solution and/or gas mixture while other portions of one or more surfaces of the as-sintered PCD body may be exposed to the leaching solution and/or gas mixture. Other suitable techniques may be used for removing a metal-solvent catalyst and/or other materials from the as-sintered PCD body or may be used to accelerate a chemical leaching process. For example, exposing the as-sintered PCD body to heat, pressure, electric current, microwave radiation, and/or ultrasound may be employed to leach or to accelerate a chemical leaching process, without limitation. Following leaching, at least a portion of superhard table **128** may comprise a volume of PCD material that is substantially free of a metal-solvent catalyst.

[0056] The plurality of diamond particles used to form superhard table **128** comprising the PCD material may exhibit one or more selected sizes. The one or more selected sizes may be determined, for example, by passing the diamond particles through one or more sizing sieves or by any other method. In an embodiment, the plurality of diamond particles may include a relatively larger size and at least one relatively smaller size. As used herein, the phrases “relatively larger” and “relatively smaller” refer to particle sizes determined by any suitable method, which differ by at least a factor of two (e.g., 40  $\mu\text{m}$  and 20  $\mu\text{m}$ ). More particularly, in various embodiments, the plurality of diamond particles may include a portion exhibiting a relatively larger size (e.g., 100  $\mu\text{m}$ , 90  $\mu\text{m}$ , 80  $\mu\text{m}$ , 70  $\mu\text{m}$ , 60  $\mu\text{m}$ , 50  $\mu\text{m}$ , 40  $\mu\text{m}$ , 30  $\mu\text{m}$ , 20  $\mu\text{m}$ , 15  $\mu\text{m}$ , 12  $\mu\text{m}$ , 10  $\mu\text{m}$ , 8  $\mu\text{m}$ ) and another portion exhibiting at least one relatively smaller size (e.g., 30  $\mu\text{m}$ , 20  $\mu\text{m}$ , 15  $\mu\text{m}$ , 12  $\mu\text{m}$ , 10  $\mu\text{m}$ , 8  $\mu\text{m}$ , 4  $\mu\text{m}$ , 2  $\mu\text{m}$ , 1  $\mu\text{m}$ , 0.5  $\mu\text{m}$ , less than 0.5  $\mu\text{m}$ , 0.1  $\mu\text{m}$ , less than 0.1  $\mu\text{m}$ ). In another embodiment, the plurality of diamond particles may include a portion exhibiting a relatively larger size between about 40  $\mu\text{m}$  and about 15  $\mu\text{m}$  and another portion exhibiting a relatively smaller size between about 12  $\mu\text{m}$  and 2  $\mu\text{m}$ . Of course, the plurality of diamond particles may also include three or more different sizes (e.g., one relatively larger size and two or more relatively smaller sizes) without limitation.

[0057] FIG. 5 is a perspective view of a bearing assembly including a plurality of bearing elements attached to a support structure (e.g., second bearing assembly **108**). As illustrated in FIG. 5, bearing elements **110** may be mounted within the second support structure **112**. Bearing elements **110** may each extend radially inward from the second support structure **112** such that at least a portion of the bearing element **110** extends past an inner surface **118** of the second support structure **112**. A portion of bearing element **110** extending from second support structure **112** may comprise a bearing surface **136**.

[0058] The bearing surface **136** of one or more of the bearing elements **110** (e.g., each bearing element **110**) may comprise an at least partially concave rounded shape that is at least partially complementary to the shape of the bearing surface **126** of the bearing elements **104** of the first bearing assembly **102**. For example, the bearing surfaces **136** of the bearing elements **110** may comprise a concave partial conical surface (e.g., a portion of a conical concave surface, a frustoconical surface). As discussed in greater detail below, the bearing surface **136** may exhibit a ramped or tapered shape (when viewed in a cross-sectional view) with a central lower portion that extends along a substantial portion of the diameter of the bearing surface **136** and is bordered by two higher portions positioned at or near two outer radial sections of the bearing elements **110**.

[0059] In some embodiments, when compared to bearing surface **126**, bearing surface **136** may not comprise a partial spherical surface shape. Rather, the bearing surface **136** may exhibit a curvature

(e.g., a major or maximal curvature that is greater than zero) substantially along only one reference axis (as opposed to a spherical surface that exhibits a similar curvature along more than one reference axis). In such an embodiment, another reference axis along the bearing surface **136** that is transverse (e.g., perpendicular) to the one reference axis with the curvature may exhibit minimal curvature (e.g., approaching or equal to zero curvature).

[0060] As depicted by the dashed lines in FIG. 5, the bearing surfaces **136** and/or the angular orientation of the second support structure **112** that positions the bearing elements **110** may collectively define a concave, at least partially conical shape (e.g., tapering smoothly with respect to a pointed apex or vertex). For example, the individual bearing surfaces **136** of the bearing elements **110** may each exhibit a concave partial conical shape where a majority (e.g., a substantial entirety) of the bearing surfaces **136** of the bearing elements **110** collectively, when taken together, define (e.g., lie within or upon) a frustoconical shape. As depicted, a portion (e.g., a majority, a substantial entirety) of each of the individual bearing surfaces **136** may be configured to accommodate the overall convex shape of the overall first bearing assembly **102** (e.g., when first bearing assembly **102** is assembled with second bearing assembly **108**). The overall convex conical shape of the support structure **106** of first bearing assembly **102** may exhibit a gradually decreasing radius with an end portion including a pointed or rounded radially innermost wall that is discontinuous with the remainder of the conical shape (e.g., extending horizontally/radially inward). In some embodiments, the overall convex conical shape of the support structure **106** may be substantially conical in that it approximates a portion of a cone to define an overall partially conical bearing surface on which the second bearing assembly **108** may travel. Similarly, the bearing surfaces **136** may each be substantially cylindrical such that, when fixed at an oblique angle relative to the outer bearing axis **113**, each of the bearing surfaces **136** approximate a portion of cone or conical shape.

[0061] FIG. 6 is a cross-sectional view of a portion of the bearing apparatus (e.g., the second bearing assembly **108**) shown in FIG. 5. As depicted in FIG. 6, the bearing elements **110** may each include may exhibit a ramped or tapered shape with a central lower portion **138** that extends along a diameter of the bearing surface **136** (e.g., from a first lateral side to a second opposing lateral side). The central lower portion **138** (e.g., central curved portion) is bordered on opposing lateral sides by two opposing higher portions **140** (e.g., two ramp portions) positioned at two outer lateral sections of the bearing elements **110**. For example, the four outer quadrants of the bearing surface **136** include two opposing radially outward sections of the central lower portion **138** that are interspersed between the opposing higher portions **140** about the circumference of the bearing surface **136**.

[0062] As further shown in FIG. 6, the cross section is taken in a first direction along a line that is tangential to the elliptical shape of the second bearing assembly **108**. Along this tangential cross section, the bearing surface **136** may exhibit a curvature (e.g., a major or maximal curvature that is greater than zero). Where the overall shape of the bearing surface **136** substantially exhibits a concave partially conical shape, the tangential cross section shown in FIG. 6 taken at any point along the diameter of the bearing element **110** that is tangent to the curvature of the overall second bearing assembly **108** may exhibit substantially the same curvature (e.g., as depicted in the figure, into or out of the drawing paper).

[0063] FIG. 7 is another cross-sectional view of a portion of the second bearing assembly **108** shown in FIG. 5 that is taken substantially perpendicular (e.g., approximately 90 degrees) to the view in FIG. 6. As shown in FIG. 7, the cross section is taken in a second direction along a radial axis of the second bearing assembly **108** (e.g., a line normal to the curved (e.g., ellipsoid, conical, etc.) shape of the second bearing assembly **108**). As depicted, the bearing surface **136** may comprise a substantially planar line exhibiting minimal (e.g., no) curvature (e.g., a curvature approaching or equal to zero). Where the overall shape of the bearing surface **136** substantially exhibits a concave conical shape, the normal or radial cross section shown in FIG. 7 taken at any

point along the diameter of the bearing element **110** that is normal to the curvature of the overall second bearing assembly **108** may exhibit substantially the same geometrical characteristics (e.g., as depicted in the figure, into or out of the drawing paper).

[0064] Similar to bearing element **104** discussed above, bearing element **110** may comprise a superhard table **142** affixed to or formed upon a substrate **144** at an interface **146** with a chamfer **148**. The components of bearing element **110** (e.g., the superhard table **142** and the substrate **144**) may be formed from similar and/or identical materials in similar and/or identical configurations to those discussed above with respect to bearing element **104**.

[0065] In some embodiments, the bearing surfaces **126**, **136** may be machined (e.g., by a grinding process, laser ablation, and/or electro-discharge machining) after or prior to being assembled with each respective support structure **106**, **112** so that bearing surfaces **126**, **136** exhibits a center of curvature that is substantially coincident with each other and with an intended path of rotation. However, as the substantially conical concave bearing surfaces **136** may be relatively less complex to form (e.g., as compared to the convex spherical shape of the bearing surfaces **126**), such a configuration may require relatively less processing to machine (e.g., grind) into the bearing elements **110**.

[0066] FIG. **8** is a cross-sectional view of a portion of a bearing apparatus (e.g., bearing apparatus **100** arranged in a primarily thrust bearing configuration). As shown in FIG. **8**, the bearing element **104** of the first bearing assembly **102** includes bearing surfaces **126** that at least portions of which oppose and bear against at least portions of respective bearing surfaces **136** of the bearing elements **110** of a second bearing assembly **108** during use. As shown in FIG. **8**, bearing surfaces **126** of the bearing elements **104** may comprise a convex (e.g., partial-ellipsoidal, partial-spherical or partial-cylindrical) surface that opposes and at least partially bears against the bearing surfaces **136** of bearing elements **110** having the partial concave conical bearing surface **136**. For example, the bearing surfaces **136** of the bearing elements **110** may exhibit a concave conical shape with a curvature conforming to the ellipsoidal surface shape of the bearing surface **126** on the first bearing assembly **102**. Collectively, the bearing surfaces **136** of the bearing elements **110** may define a partially conical shape (e.g., frustoconical) conforming to at least a portion of the collective ellipsoidal surface shape of the bearing surfaces **126** on the first bearing assembly **102**.

[0067] As discussed above, the bearing surface **136** comprising the concave conical shape may only exhibit a major curvature in one only direction. For example, the curvature of the bearing surface **136** may extend along only a path of rotation between the first bearing assembly **102** and the second bearing assembly **108** (e.g., in a tangential direction to a circular shape of either the first bearing assembly **102** or the second bearing assembly **108**). The bearing surface **136** may exhibit minimal to no curvature along a selected reference direction (e.g., a direction normal to the path of rotation). The curvature of the bearing surface **136** may be variable. In one embodiment, the curvature of the bearing surface **136** may decrease and increase, respectively, with respect to a reference axis of the bearing surfaces **136** or with respect to another geometrical feature, without limitation.

[0068] Such a configuration may provide an elliptical (e.g., circular) path on which the spherical bearing surfaces **126** of the first bearing assembly **102** may travel in a direction of rotation and also allow for inner bearing axis **107** to be misaligned with outer bearing axis **113** (e.g., form an angle and/or offset between bearing axis **107** and bearing axis **113**), while maintaining sufficient contact between bearing surfaces **126** and bearing surfaces **136**. In one embodiment, first bearing assembly **102** may be tilted (relative to second bearing assembly **108**) (or vice versa) in a direction transverse (e.g., perpendicular) to the direction of rotation. In some embodiments, the shape of the bearing surfaces **136** may enable at least some axial movement of the bearing elements **104** to compensate for one or more of axial misalignment, tilt, and/or axial deflection (e.g., shaft deflection). For example, the bearing surfaces **136** may allow for some axial translation and/or lateral movement resulting from rotation of the shaft to which the bearing apparatus **100** is coupled.

[0069] The elliptical path defined by the bearing surfaces **136** of the second bearing assembly **108** may substantially conform to a central portion (e.g., along the direction of rotation) of the spherical bearing surfaces **126** of the first bearing assembly **102** such that a majority of the central portion of the spherical bearing surfaces **126** is in contact with the bearing surfaces **136** of the second bearing assembly **108**. However, upper and lower portions relative on either side of the central portion of the spherical bearing surfaces **126** may curve away, and be spaced from, the conical concave bearing surfaces **136** of the second bearing assembly **108**.

[0070] FIG. **9** is a cross-sectional view of a portion of a bearing apparatus (e.g., bearing apparatus **200** arranged in a primarily radial bearing configuration). Bearing apparatus **200** may include one or more feature which is similar or identical to the bearing apparatus **100** discussed above and may include one or more similar or identical component of the bearing apparatus **100** discussed above. As shown in FIG. **9**, an interface between the bearing elements **204** and bearing elements **210**, as positioned by first support structure **206** and second support structure **212**, may define a relatively shallower angle  $\theta_{sub.2}$  with respect to a longitudinal axis or centerline **214** of the bearing apparatus **200**. For example, operating primarily as a radial bearing, the angle  $\theta_{sub.2}$  of the interface between the bearing elements **204**, **210** may be 45 degrees or less (e.g., 0 to 45 degrees, 30 degrees, 10 to 50 degrees, etc.) relative to the longitudinal axis **214**.

[0071] FIG. **10** is a partial cross-sectional perspective view of an exemplary subterranean system **300** that includes a bearing apparatus (e.g., bearing apparatus **100**, bearing apparatus **200**). As shown in FIG. **10**, subterranean system **300** may include a housing **302** enclosing a downhole drilling motor (e.g., a motor, turbine, or any other suitable device capable of rotating an output shaft, without limitation) that is operably connected to an output shaft **306**.

[0072] Bearing apparatus **100**, **200** may be operably coupled to downhole output shaft **306** such that the rotor or assembly of the bearing apparatus **100**, **200** rotates in conjunction with output shaft **306**, while the stator or another assembly of the bearing apparatus **100**, **200** remains stationary with respect to output shaft **306**. A downhole tool (e.g., a rotary drill bit **304**) configured to engage a subterranean formation may be connected to output shaft **306**. As illustrated in FIG. **10**, rotary drill bit **304** may be a roller cone bit comprising a plurality of roller cones **308**. According to additional embodiments, rotary drill bit **304** may comprise any suitable type of rotary drill bit, such as, for example, a so-called fixed-cutter drill bit. As a borehole is drilled using rotary drill bit **304**, pipe sections may be connected to subterranean drilling system **300** to form a drill string capable of progressively drilling the borehole to a greater depth within a subterranean formation. Any of the bearing assemblies disclosed herein may be used in subterranean drilling system **300**, without limitation.

[0073] According to various embodiments, drilling fluid may be circulated through the downhole drilling motor to generate torque and effect rotation of output shaft **306** and rotary drill bit **304** attached thereto so that a borehole may be drilled. A portion of the drilling fluid may also be used to lubricate opposing bearing surfaces of superabrasive elements on individual bearing assemblies of the bearing apparatus **100**.

[0074] Embodiments of the present disclosure may provide bearing assemblies that enable at least some axial movement to compensate for one or more of axial misalignment, tilt, and/or axial deflection (e.g., shaft deflection) while still conforming to an elliptical rotational path of travel between the bearing assemblies of the bearing apparatus. For example, bearing surfaces (e.g., tapered, cylindrical concave bearing surfaces) of one of the bearing assemblies may define a substantially conical overall shape enabling the other bearing assembly to freely rotate at least partially within the conical shape even with some shaft displacement. Further, the tapered bearing surfaces of at least one of the bearing assemblies may exhibit a topology that is relatively less difficult to produce) as compared to a spherical bearing surface.

[0075] Terms of degree (e.g., “about,” “substantially,” “generally,” etc.) indicate structurally or functionally insignificant variations. In an example, when the term of degree is included with a

term indicating quantity, the term of degree is interpreted to mean  $\pm 10\%$ ,  $\pm 5\%$ , or  $\pm 2\%$  of the term indicating quantity. In an example, when the term of degree is used to modify a shape, the term of degree indicates that the shape being modified by the term of degree has the appearance of the disclosed shape. For instance, the term of degree may be used to indicate that the shape may have rounded corners instead of sharp corners, curved edges instead of straight edges, one or more protrusions extending therefrom, is oblong, is the same as the disclosed shape, et cetera.

[0076] While the present disclosure has been described herein with respect to certain illustrated embodiments, those of ordinary skill in the art will recognize and appreciate that it is not so limited. Rather, many additions, deletions, and modifications to the illustrated embodiments may be made without departing from the scope of the disclosure as hereinafter claimed, including legal equivalents thereof. Further, the words “including,” “having,” and variants thereof (e.g., “includes” and “has”) as used herein, including the claims, shall be open ended and have the same meaning as the word “comprising” and variants thereof (e.g., “comprise” and “comprises”). In addition, features from one embodiment may be combined with features of another embodiment while still being encompassed within the scope of the disclosure as contemplated by the inventors.

## Claims

1. A bearing assembly, comprising; a first bearing assembly comprising one or more first bearing elements coupled to a first support structure; and a second bearing assembly comprising one or more second bearing elements coupled to a second support structure, the one or more second bearing elements oriented at an oblique angle relative to an axis of rotation to define an open bowl for receiving the first bearing assembly; wherein the one or more first bearing elements are located and configured relative to the one or more second bearing elements for relative rotation about the axis of rotation to slide the one or more first bearing elements along the one or more second bearing elements in the open bowl defined by the second bearing assembly to define a ball and socket-type joint between the first bearing assembly and the second bearing assembly.
2. The bearing assembly of claim 1, wherein the second bearing assembly comprises a generally conical bearing surface collectively defined by the one or more second bearing elements.
3. The bearing assembly of claim 1, wherein each of the one or more first bearing elements of the first bearing assembly comprises a partially spherical convex shape.
4. The bearing assembly of claim 1, wherein the first bearing assembly is coupled to a shaft having a rotational axis configured to be positioned in an orientation that is angularly offset relative to a centerline of the second support structure.
5. A bearing assembly, comprising; a first bearing assembly comprising one or more first bearing elements coupled to a first support structure and defining a convex partial spherical structure; and a second bearing assembly comprising one or more second bearing elements coupled to a second support structure defining an open concave structure; wherein the convex partial spherical structure of the first bearing assembly is configured to be located at least partially within the open concave structure of the second bearing assembly with the one or more first bearing elements being in contact with the one or more second bearing elements.
6. The bearing assembly of claim 5, wherein the one or more second bearing elements collectively define a generally conical bearing surface.
7. The bearing assembly of claim 6, wherein bearing surfaces of the one or more second bearing elements have two discrete ramp portions positioned on either side of a base portion.
8. The bearing assembly of claim 5, wherein at least some of the one or more first bearing elements and/or the one or more second bearing elements comprise a superhard table coupled to a substrate.
9. The bearing assembly of claim 5, wherein the first bearing assembly and the second bearing assembly collectively define a ball and socket-type structure.
10. A bearing assembly, comprising; a support ring; and bearing elements coupled to the support

ring, each of the bearing elements defining an open bowl exhibiting a partially conical shape, the partially conical shape of each of the bearing elements collectively defining an inward facing at least partially conical bearing surface.

**11.** The bearing assembly of claim 10, wherein the bearing assembly comprises an outer bearing assembly, and wherein the inward facing at least partially conical bearing surface is configured to engage with an outward facing bearing surface of an inner bearing assembly.

**12.** The bearing assembly of claim 11, wherein the partially conical shape of each of the bearing elements comprises a partially concave conical shape.

**13.** The bearing assembly of claim 12, wherein each of the bearing elements further comprises two discrete ramp portions positioned on either lateral side of a base portion.

**14.** The bearing assembly of claim 13, wherein the two discrete ramp portions of each of the bearing elements are positioned adjacent to one of the two discrete ramp portions of an adjacent bearing element of the bearing elements.

**15.** The bearing assembly of claim 11, further comprising an inner bearing assembly, the inner bearing assembly comprising: an inner support ring; and inner bearing elements coupled to the inner support ring, each of the inner bearing elements having an outward-facing bearing surface configured to engage with the at least partially conical bearing surface of the outer bearing assembly.

**16.** The bearing assembly of claim 15, wherein each of the outward-facing bearing surface exhibits a partially spheroid convex shape.

**17.** The bearing assembly of claim 15, wherein the bearing assembly is configured to enable the inner bearing assembly to move into and out of the open bowl defined by the bearing assembly.

**18.** The bearing assembly of claim 11, wherein at least a majority of each of the at least partially conical bearing surface defines and lies within the at least partially conical bearing surface.

**19.** The bearing assembly of claim 10, wherein the bearing assembly is configured as a rotor or a stator.

**20.** The bearing assembly of claim 10, wherein each of the bearing elements comprise a superhard table coupled to a substrate.

---