

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12393726
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Weast; John C. et al.

---

### Technologies for presenting public and private images

---

#### Abstract

Technologies for displaying public and private images includes a display device and one or more user viewing devices. The display device is configured to display or generate a personalized image or video that is viewable by an authorized user viewing device and not viewable by unauthorized viewing devices. To facilitate the display of the personalized images, the display device and the user viewing device(s) may negotiate a display protocol to be used by the display device to display the personalized image in a private manner. In some embodiment, the display device may also display a public image or video that is viewable by unauthorized viewing devices and/or individuals without viewing devices.

---

<b>Inventors:</b>	<b>Weast; John C. (Portland, OR), Boelter; Joshua (Portland, OR)</b>
<b>Applicant:</b>	<b>Intel Corporation (Santa Clara, CA)</b>
<b>Family ID:</b>	<b>1000008765367</b>
<b>Assignee:</b>	<b>INTEL CORPORATION (Santa Clara, CA)</b>
<b>Appl. No.:</b>	<b>18/463870</b>
<b>Filed:</b>	<b>September 08, 2023</b>

#### Prior Publication Data

Document Identifier	Publication Date
US 20240070320 A1	Feb. 29, 2024

#### Related U.S. Application Data

continuation parent-doc US 18062219 20221206 US 11853458 child-doc US 18463870  
continuation parent-doc US 16412845 20190515 ABANDONED child-doc US 18062219  
division parent-doc US 14551911 20141124 US 10380375 20190813 child-doc US 16412845

---

## Publication Classification

**Int. Cl.:** **G06F21/62** (20130101); **G06F3/14** (20060101); **G06F21/35** (20130101); **G06F21/84** (20130101); **G09G3/00** (20060101)

**U.S. Cl.:**

**CPC** **G06F21/6245** (20130101); **G06F3/14** (20130101); **G06F21/35** (20130101); **G06F21/84** (20130101); **G09G3/001** (20130101); G09G2354/00 (20130101); G09G2356/00 (20130101); G09G2358/00 (20130101)

## Field of Classification Search

**CPC:** G06F (21/35); G06F (21/6245); G06F (21/84); G06F (3/14); G09G (2354/00); G09G (2356/00); G09G (2358/00); G09G (3/001)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8692930	12/2013	Rolston	N/A	N/A
2002/0101988	12/2001	Jones	N/A	N/A
2008/0004950	12/2007	Huang	N/A	N/A
2009/0059103	12/2008	Azor et al.	N/A	N/A
2009/0061901	12/2008	Arrasvuori	N/A	N/A
2011/0191432	12/2010	Layson	N/A	N/A
2012/0054001	12/2011	Zivkovic	N/A	N/A
2012/0179527	12/2011	Ball	N/A	N/A
2012/0194420	12/2011	Osterhout	345/156	G06F 3/013
2013/0038702	12/2012	Schweitzer	N/A	N/A
2013/0103943	12/2012	Hirsch	N/A	N/A
2013/0143651	12/2012	Harrison et al.	N/A	N/A
2013/0254039	12/2012	Kim	N/A	N/A
2013/0307870	12/2012	Ashbrook	N/A	N/A
2014/0103104	12/2013	Jover	N/A	N/A
2014/0188616	12/2013	Badenhop	N/A	N/A
2015/0026708	12/2014	Ahmed	N/A	N/A
2016/0042602	12/2015	Phan	N/A	N/A
2016/0171220	12/2015	Yu	N/A	N/A
2018/0232769	12/2017	Barak	N/A	N/A
2019/0295551	12/2018	White	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103365657	12/2012	CN	N/A
103425119	12/2012	CN	N/A
107077312	12/2016	CN	N/A
3224795	12/2016	EP	N/A
2016/085601	12/2015	WO	N/A

## OTHER PUBLICATIONS

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for PCT Application No.

PCT/US2015/057166, mailed Feb. 5, 2016, 14 pages. cited by applicant

First Office Action for Chinese Application No. 201580056371.4, dated May 23, 2019, 2 pages. cited by applicant

Extended European Search Report for EP Application No. 15862598.8, mailed 08.05.2018, 9 pages. cited by applicant

Apr. 21, 2017, FESPA, "Turning the whole world into an interactive billboard with AR",

<https://www.fespa.com/en/news-media/features/turning-the-whole-world-into-an-interactive-billboard-with-ar>. cited by applicant

Noyola et al., Spring 2015, Stanford University,

<https://web.stanford.edu/class/cs231m/projects/final-report-noyola-stanko.pdf>. cited by applicant

Third Office Action for Chinese Application No. 201580056371.4. dated Jun. 1, 2020, including machine translation (27 pages). cited by applicant

European Office Action for European Application No. 15862598.8, dated Sep. 4, 2020 (6 pages). cited by applicant

Second Office Action for Chinese Application No. 201580056371.4, dated Feb. 3, 2020, including machine translation (29 pages). cited by applicant

European Office Action for European Application No. 15862598.8, dated Sep. 26, 2019 (6 pages). cited by applicant

---

*Primary Examiner:* Parsons; Theodore C

*Attorney, Agent or Firm:* JAFFERY WATSON HAMILTON & DESANCTIS LLP

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of and claims the benefit of and priority to U.S. application Ser. No. 18/062,219, entitled TECHNOLOGIES FOR PRESENTING PUBLIC AND PRIVATE IMAGES, by John C. Weast, et al., filed Dec. 6, 2022, now allowed, which is a continuation of and claims the benefit of and priority to U.S. application Ser. No. 16/412,845, entitled TECHNOLOGIES FOR PRESENTING PUBLIC AND PRIVATE IMAGES, by John C. Weast, et al., filed May 15, 2019, now abandoned, which is a divisional (and claims the benefit of and priority under 35 U.S.C. § 120) of U.S. patent application Ser. No. 14/551,911 entitled TECHNOLOGIES FOR PRESENTING PUBLIC AND PRIVATE IMAGES, by John C. Weast, et al., filed Nov. 24, 2014, now issued as U.S. Pat. No. 10,380,375, the entire contents of which are incorporated herein by reference.

## BACKGROUND

(1) Display devices are used to display information and entertainment content to viewers in the vicinity of the display. Display devices may be public or private. Public displays, such as crowd displays at sporting events, advertisement displays, and other displays in public areas typically display images and information for consumption by the general public. Private displays, such as computer displays, personal televisions, personal mobile device displays, and other displays controlled by a private entity are generally used to display personal images or information intended for consumption by the user of such devices or a select group of authorized individuals.

(2) Display devices, both public and private, are becoming ubiquitous in the everyday life of many

people. Additionally, as display technology improves, displays are increasingly being integrated and/or embedded in other devices or articles. For example, display technology is currently being incorporated into transparent windows, clothing, personal accessory items, and other devices. Such proliferation of display devices creates difficulties in communicating targeted information to individuals while maintaining a degree of privacy over such information.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The concepts described herein are illustrated by way of example and not by way of limitation in the accompanying figures. For simplicity and clarity of illustration, elements illustrated in the figures are not necessarily drawn to scale. Where considered appropriate, reference labels have been repeated among the figures to indicate corresponding or analogous elements.

(2) FIG. 1 is a simplified diagram of at least one embodiment of a system for displaying personalized image(s) to a viewer in a private manner;

(3) FIG. 2 is a simplified block diagram of at least one embodiment of a personalization public display device of the system of FIG. 1;

(4) FIG. 3 is a simplified block diagram of at least one embodiment of a user viewing device of the system of FIG. 1;

(5) FIG. 4 is a simplified block diagram of at least one embodiment of an environment of the personalization public display device of FIG. 2;

(6) FIG. 5 is a simplified block diagram of at least one embodiment of an environment of the user viewing device of FIG. 3;

(7) FIGS. 6 and 7 are a simplified flow diagram of at least one embodiment of a method for displaying personalized images to a viewer in a private manner that may be executed by the personalizing public display of FIGS. 2 and 4; and

(8) FIG. 8 is a simplified flow diagram of at least one embodiment of a method for viewing a personalized image that may be executed by the user viewing device of FIGS. 3 and 5.

### DETAILED DESCRIPTION OF THE DRAWINGS

(9) While the concepts of the present disclosure are susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and will be described herein in detail. It should be understood, however, that there is no intent to limit the concepts of the present disclosure to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives consistent with the present disclosure and the appended claims.

(10) References in the specification to “one embodiment,” “an embodiment,” “an illustrative embodiment,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may or may not necessarily include that particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described. Additionally, it should be appreciated that items included in a list in the form of “at least one A, B, and C” can mean (A); (B); (C); (A and B); (B and C); (A and C); or (A, B, and C). Similarly, items listed in the form of “at least one of A, B, or C” can mean (A); (B); (C); (A and B); (B and C); (A or C); or (A, B, and C).

(11) The disclosed embodiments may be implemented, in some cases, in hardware, firmware, software, or any combination thereof. The disclosed embodiments may also be implemented as instructions carried by or stored on one or more transitory or non-transitory machine-readable (e.g.,

computer-readable) storage medium, which may be read and executed by one or more processors. A machine-readable storage medium may be embodied as any storage device, mechanism, or other physical structure for storing or transmitting information in a form readable by a machine (e.g., a volatile or non-volatile memory, a media disc, or other media device).

(12) In the drawings, some structural or method features may be shown in specific arrangements and/or orderings. However, it should be appreciated that such specific arrangements and/or orderings may not be required. Rather, in some embodiments, such features may be arranged in a different manner and/or order than shown in the illustrative figures. Additionally, the inclusion of a structural or method feature in a particular figure is not meant to imply that such feature is required in all embodiments and, in some embodiments, may not be included or may be combined with other features.

(13) Referring now to FIG. 1, a system **100** for displaying personalized image(s) to a viewer includes a personalization public display device **102** and one or more user viewing devices **104**, which may be worn or otherwise operated by a corresponding user **112**. In use, as discussed in more detail below, the display device **102** is configured to display a personalized image or images (e.g., video) to a user, or group of users, of a particular user viewing device **104** (e.g., smart glasses, a smart phone, or other viewing device) in a private manner. In particular, the display device **102** displays or presents the personalized image(s) such that the personalized image(s) are viewable via use of an authorized user viewing device(s) **104** and not viewable by other unauthorized user viewing devices **104** and/or users without a user viewing devices **104**. To do so, the display device **102** and the targeted user viewing device **104** communicate with each other to establish one or more display protocols, which are used by the personalization public display device **102** to display or otherwise present the personalized image(s) in the private manner. The personalized images may be displayed by the display device **102** itself (e.g., in an encrypted or obscured format) or provided to the authorized user viewing device **104** by the display device **102** or an associated cloud service. For example, in some embodiments, the display device **102** may display the personalized image on a local display using any suitable display protocol capable of obscuring or encrypting the personalized image on the local display such as, for example, a polarization display protocol, a color filtering display protocol, a view segmentation display protocol, a layered depth variation display protocol, a pixel obfuscation display protocol, a pixel encoding display protocol, or other display protocol that allows the display device **102** to display the personalized image in an obscured or encrypted manner, while also allowing the targeted user viewing device **104** to properly view the personalized image. Alternatively, in other embodiments, the display device **102** (or an associated cloud service) may transmit the personalized image(s) to the authorized user viewing device **104** for display or presentation on a local display, projection surface, or lens of the user viewing device **104**. In such embodiments, the personalized images may be embodied as still image(s) or streamed images/video/audio (e.g., a video according to a Moving Picture Experts Group (MPEG) standard). In some embodiments, the display device **102** overlay the personalized images/video over a viewable area of the display or projection surface to provide an augmented reality view as discussed in more detail below.

(14) To view the personalized image, the user viewing device **104** also utilizes the established display protocol by, for example, decrypting a received or viewable encrypted personalized image, operating a local display according to the display protocol, controlling visual characteristics of a viewer lens, or other viewing technique based on the established display protocol. In some embodiments, the display protocol used to display and view the personalized image may be modified over time based on, for example, the user's location relative to the display device **102**, security timeouts, bandwidth or throughput considerations, and/or other criteria.

(15) An example of the operation of the system **100** is depicted in FIG. 1. A user **110** is shown viewing a display of the personalization public display device **102**. However, because the user **110** does not have a user viewing device **104**, the user **110** sees a public image **120** that is displayed on

the display by the display device **102**. The public image **120** (e.g., a cartoon character) is viewable by the general public, e.g., by anyone viewing the display device **102** without an authorized user viewing device **104**. Conversely, a user **112a** is viewing the display of the display device **102** with an authorized user viewing device **104** that has established a display protocol with the display device **102**. As such, the user **112a** sees a personalized image **130**, such as a targeted advertisement for a shirt. Depending on the display protocol used, the user **112a** may view the personalized image by looking at a local display of the user's **112a** viewing device **104** or by looking at the display of the display device **102**. Similarly, another user **112b** is viewing the display of the display device **102** with a different authorized user viewing device **104** that has established a different display protocol with the display device **102**. As such, the user **112b** sees a different personalized image **132**, such as a targeted advertisement for a new computer. Again, the user **112b** may view the personalized image by looking at a local display of the user's **112b** viewing device **104** or by looking at the display of the display device **102** depending on the particular display protocol used. In this way, the display protocols used by the personalization public display device **102** and the authorized user viewing device(s) **104** may be used to establish a private viewing modality between the two devices **102**, **104**. Of course, a group of users may be authorized to view the same personalized image by implementing the same display protocol in some embodiments.

(16) Referring now to FIG. 2, the personalization public display device **102** may be embodied as any type of display device capable of displaying, streaming, or otherwise presenting images, video and/or audio to a viewer and performing the functions described herein. For example, the display device **102** may be embodied as a crowd display, an advertisement display, an information display, a television, a smart appliance, a computer device, or other device or display surface having display capabilities. In some embodiments, the personalization public display device **102** may be incorporated into other devices or articles such as “smart” clothing, appliances, or other devices or objects.

(17) In the illustrative embodiment, the display device **102** includes a processor **200**, an input/output subsystem **202**, a memory **204**, one or more displays **208**, a communication circuit **206**, and a data storage **210**. Of course, the display device **102** may include other or additional components, such as those commonly found in a display device or other computing device (e.g., various input/output devices), in other embodiments. Additionally, in some embodiments, one or more of the illustrative components may be incorporated in, or otherwise form a portion of, another component. For example, the memory **204**, or portions thereof, may be incorporated in the processor **200** in some embodiments.

(18) The processor **200** may be embodied as any type of processor capable of performing the functions described herein. For example, the processor **200** may be embodied as a single or multi-core processor(s), digital signal processor, microcontroller, or other processor or processing/controlling circuit. Similarly, the memory **204** may be embodied as any type of volatile or non-volatile memory or data storage capable of performing the functions described herein. In operation, the memory **204** may store various data and software used during operation of the display device **102** such as operating systems, applications, programs, libraries, and drivers. The memory **204** is communicatively coupled to the processor **200** via the I/O subsystem **202**, which may be embodied as circuitry and/or components to facilitate input/output operations with the processor **200**, the memory **204**, and other components of the display device **102**. For example, the I/O subsystem **202** may be embodied as, or otherwise include, memory controller hubs, input/output control hubs, firmware devices, communication links (i.e., point-to-point links, bus links, wires, cables, light guides, printed circuit board traces, etc.) and/or other components and subsystems to facilitate the input/output operations. In some embodiments, the I/O subsystem **202** may form a portion of a system-on-a-chip (SoC) and be incorporated, along with the processor **200**, the memory **204**, and other components of the display device **102**, on a single integrated circuit chip.

(19) The communication circuit **206** of the display device **102** may be embodied as any communication circuit, device, or collection thereof, capable of enabling communications between the display device **102** and the user viewing devices **104** as discussed in more detail below. The communication circuit **206** may be configured to use any one or more communication technology and associated protocols (e.g., Ethernet, Bluetooth®, Wi-Fi®, WiMAX, etc.) to effect such communication.

(20) The display **208** may be embodied a display local to the display device **102** or remote therefrom, but communicatively thereto. For example, in some embodiments, the display **208** may be located at one location, while the remaining components of the display device **102** are located at another location remote from the display **208** but communicatively coupled thereto (e.g., via an interconnection, network, etc.) Although shown in FIG. 1 as a single display, it should be appreciated that the display **208** may be embodied as multiple, individual displays in other embodiments. For example, the display **208** may be embodied as an arrangement of displays located in, for example, a shopping mall or similar retail location. Alternatively, the display **208** may be embodied as a single display in some implementations. The individual display(s) **208** may be embodied as any type of display capable of displaying digital information such as a liquid crystal display (LCD), a light emitting diode (LED), a plasma display, a cathode ray tube (CRT), or other type of display device. Additionally, the display(s) **128** may be of any size or shape and have any suitable resolution, color, and/or have any other feature or quality commonly found in a display. In some embodiments, the display **208** may be attached to, embedded in, or otherwise incorporated into other devices or structures in some embodiments. For example, the display **208** may be incorporated in a transparent window, in clothing, in a smart device, or other device or article in which the display **128** is generally viewable by a public population.

(21) The data storage **210** may be embodied as any type of device or devices configured for short-term or long-term storage of data such as, for example, memory devices and circuits, memory cards, hard disk drives, solid-state drives, or other data storage devices. In some embodiments, the display device **102** may also store the personalized images displayed on the display **208** and/or transmitted to the user viewing device **104**. Additionally, the display device **102** may store the various display protocols and viewer policies in the data storage **210** which are used to select and display the personalized images as discussed in more detail below.

(22) In some embodiments, the display device **102** may also include one or more viewer detection sensors **212**. The viewer detection sensors **212** may be embodied as any type of sensor and/or circuit capable of sensing, detecting, or otherwise generating sensor data indicative of the presence of a user viewing device **104** within the proximity or vicinity of the display device **102**. For example, the viewer detection sensor **212** may be embodied as a communication circuit (e.g., the communication circuit **206** or portion thereof) configured to sense or detect communications from a user viewing device **104**, proximity sensors and associated circuitry configured to detect the presence of a user viewing device **104**, camera or image sensors and associated circuitry to detect the presence of a user viewing device **104** based on capture images, or other sensor or sensor circuitry capable of detecting the presence of a user viewing device **104** in proximity to the display device. As discussed in more detail below, upon detecting the presence of a user viewing device **104** within the vicinity, the display device **102** may initiate a negotiating procedure to establish the display protocols used to display the personalized image to a user of the authorized user viewing device **104**.

(23) In some embodiments, the display device **102** may further include one or more peripheral devices. Such peripheral devices may include any type of peripheral device commonly found in a display device or other computer device such as, for example, a hardware keyboard, input/output devices, peripheral communication devices, and/or other peripheral devices.

(24) Referring now to FIG. 3, the user viewing device **104** may be embodied as any type of device capable of viewing a personalized image displayed or transmitted by the personalization public

display device **102** (or an associated cloud service). For example, the user viewing device **104** may be embodied as a pair of smart glasses, electronic corneal implants, a smart phone or tablet, or other viewing device. Depending on the type of display device **102** and/or implementation of the system **100**, the user viewing device **104** may be configured to view the personalized images by providing real-world augmentation, visual filtering, and/or displaying of the personalized images locally. For example, the user viewing device **104** may be embodied as a pair of smart glasses configured to project or overlay an image of the personalized images onto a viewing lens of the glasses or configured to control a visual filter or shutter embedded in the viewing lens of the glasses. As an alternative example, the user viewing device **104** may be embodied as smart phone, camera, or other device having a local display onto which the personalized image may be displayed (e.g., overlaid onto a real-time image of the real-world to provide an augmented reality). As such, the user viewing device **104** may be embodied as any type of device usable by a user to view the personalized images.

(25) In the illustrative embodiment, the user viewing device **104** includes a processor **300**, an input/output subsystem **302**, a memory **304**, a display **308**, a communication circuit **306**, and a data storage **310**. Of course, the user viewing device **104** may include other or additional components, such as those commonly found in a viewing device or other computing device (e.g., various input/output devices), in other embodiments. Additionally, in some embodiments, one or more of the illustrative components may be incorporated in, or otherwise form a portion of, another component. For example, the memory **304**, or portions thereof, may be incorporated in the processor **300** in some embodiments.

(26) Similar to the processor **200** of the display device **102**, the processor **300** may be embodied as any type of processor capable of performing the functions described herein. For example, the processor **300** may be embodied as a single or multi-core processor(s), digital signal processor, microcontroller, or other processor or processing/controlling circuit. Similarly, the memory **304** may be embodied as any type of volatile or non-volatile memory or data storage capable of performing the functions described herein. In operation, the memory **304** may store various data and software used during operation of the display device **102** such as operating systems, applications, programs, libraries, and drivers. The memory **304** is communicatively coupled to the processor **300** via the I/O subsystem **302**, which may be embodied as circuitry and/or components to facilitate input/output operations with the processor **300**, the memory **304**, and other components of the user viewing device **104**. For example, the I/O subsystem **302** may be embodied as, or otherwise include, memory controller hubs, input/output control hubs, firmware devices, communication links (i.e., point-to-point links, bus links, wires, cables, light guides, printed circuit board traces, etc.) and/or other components and subsystems to facilitate the input/output operations. In some embodiments, the I/O subsystem **302** may form a portion of a system-on-a-chip (SoC) and be incorporated, along with the processor **300**, the memory **304**, and other components of the user viewing device **104**, on a single integrated circuit chip.

(27) The communication circuit **306** of the user viewing device **104** may be embodied as any communication circuit, device, or collection thereof, capable of enabling communications between the user viewing device **104** and the display device **102**. The communication circuit **306** may be configured to use any one or more communication technology and associated protocols (e.g., Ethernet, Bluetooth®, Wi-Fi®, WiMAX, etc.) to effect such communication.

(28) The display **308** may be embodied as any type of display on which a personalized image may be projected or displayed. For example, the display **308** may be embodied as a liquid crystal display (LCD), a light emitting diode (LED), a plasma display, a cathode ray tube (CRT), or other type of display device. Additionally or alternatively, the display **308** may be embodied as, or otherwise include, a viewing lens **320** (e.g., the transparent viewing glass of a pair of smart glasses, a retinal implant, etc.). In such embodiments, the user viewing device **104** may be configured to project the personalized image onto the viewing lens **320** in an augmented reality manner as



discussed above. Alternatively, in some embodiments, the user viewing device **104** may be configured to control the viewing lens **320** to adjust visual filtering, shuttering, or other visual quality or characteristic of the viewing lens **320**. For example, the viewing lens **320** may include an adjustment mechanism (e.g., shutter, iris, segmented view adjustment, etc.) operable to control a visual characteristic of the viewing lens. In such embodiments, the display protocol may be embodied as a control protocol for the adjustment mechanism.

(29) The data storage **310** may be embodied as any type of device or devices configured for short-term or long-term storage of data such as, for example, memory devices and circuits, memory cards, hard disk drives, solid-state drives, or other data storage devices. In some embodiments, the user viewing device **104** may store a local viewer policy in the data storage **310**, which is transmitted to the display device **102** to facilitate the selection of a personalized image.

(30) In some embodiments, the user viewing device **104** may also include one or more display detection sensors **312**. Similar to the viewer detection sensor(s) **212**, the display detection sensors **312** may be embodied as any type of sensor capable of sensing, detecting, or otherwise generating sensor data indicative of the presence of a personalization public display device **102** within the proximity or vicinity of the user viewing device **104**. For example, the display detection sensor **312** may be embodied as a communication circuit (e.g., the communication circuit **306** or portion thereof) configured to sense or detect communications from the display device, respond to such communications, and/or transmit an announcement of the presence of the user viewing device **104**. Alternatively or additionally, the display detection sensors **312** may be embodied as or otherwise include sensors capable of detecting that the user is presently viewing the local display **308**. For example, the user viewing device **104** may infer the presence of a display device **102** based on the user's interactions with the display **308** and/or other components of the user viewing device **104**.

(31) The user viewing device **104** may also further include one or more peripheral devices in some embodiments. Such peripheral devices may include any type of peripheral device commonly found in a viewing device or other computer device such as, for example, a hardware keyboard, input/output devices, peripheral communication devices, and/or other peripheral devices.

(32) Referring back to FIG. **1**, in some embodiments, the system **100** may also include a remote display server **106**, which is accessible by the display device **102** over a network **108**. In such embodiments, the personalization public display device **102** may be embodied as a “low featured” display operated by the remote display server **106** over the network **108**. For example, the personalized images may be stored on the remote display server **106**, and the server **106** may select which personalized images to display as discussed in more detail below. In such embodiments, the network **108** may be embodied as any type of communication network capable of facilitating communication between the display device **102** and the remote display server **106**. As such, the network **108** may include one or more networks, routers, switches, computers, and/or other intervening devices. For example, the network **108** may be embodied as or otherwise include one or more local or wide area networks, cellular networks, publicly available global networks (e.g., the Internet), an ad hoc network, a short-range communication network or link, or any combination thereof.

(33) Referring now to FIG. **4**, in use, the personalization public display device **102** establishes an environment **400**. The illustrative environment **400** includes a viewer detection module **402**, a display personalization module **404**, and a display control module **406**. The various modules of the environment **400** may be embodied as hardware, firmware, software, or a combination thereof. For example, the various modules, logic, and other components of the environment **400** may form a portion of, or otherwise be established by, the processor **200** or other hardware components of the display device **102**.

(34) The viewer detection module **402** is configured to detect the presence of a user viewing device **104** within proximity to the display device **102**. To do so, the viewer detection module **402** may analyze the sensor data generated by the viewer detection sensors **212**. For example, in some

embodiments, the viewer detection module **402** may monitor a local network for communications from a user viewing device **104**. Additionally or alternatively, the viewer detection module **402** may transmit or broadcast a discovery request to prompt a response from nearby user viewing device **104**. Further, in some embodiments, the viewer detection module **402** may analyze image or other data generated by the viewer detection sensors **212** to determine the presence of a user viewing device **104**. For example, the viewer detection module **402** may analyze images of the local vicinity to identify individuals in the images (e.g., via facial recognition, video analytics, etc.) and determine whether the individuals are carrying or using user viewing devices **104**. The viewer detection module **402** may pair the identified individuals with the detected user viewing devices **104**. As such, it should be appreciated that the viewer detection module **402** may utilize any suitable methodology and/or technology to detect and establish communication's with a user viewing device **104**.

(35) The display personalization module **404** is configured to negotiate with the target user viewing device **104** to establish the display protocol(s) to be used to display the personalized image. To do so, the display personalization module **404** utilize a viewer policy database **410**, which may include data or policies dictating or identifying criteria on which the display protocol(s) may be selected. For example, the viewer policy database **410** may include data that identifies which display protocol(s) a particular user viewing device **104** is capable of implementing (e.g., whether the user viewing device **104** is capable of visual filtering). Additionally or alternatively, the viewer policy database **410** may include data indicative of a display protocol preference of a user of a particular user viewing device **104**. The viewer policy database **410** may be updated over time based on, for example, historical interactions with the authorized user viewing device **104**. Additionally or alternatively, the user viewing device **104** may provide or update the viewer policy to the display device **102** as discussed in more detail below.

(36) The display personalization module **404** also manages the selection of images, videos, and/or other digital content (e.g., applications or other interactive experiences) to be displayed or otherwise presented by the display device **102**. To do so, the display personalization module **404** includes an image selection module **408** configured to determine or select public and/or personalized image(s), video, and/or other media to be presented by the display device **102**. For example, the image selection module **408** may select or determine one or more public images **420** to be displayed or presented by the display device **102**. As discussed above, the public images **420** are viewable by the general public (e.g., individuals without a user viewing device **104** and/or unauthorized user viewing devices **104**). Additionally, the image selection module **408** may select a personalized image **422** for display or presentation to a user of an authorized user viewing device **104** using the established display protocol.

(37) Depending on the particular implementation, the image selection module **408** may utilize any suitable criteria or data to select the personalized image **422**. For example, the image selection module **408** may select a personalized image **422** based on criteria related to the personalized image **422** itself and/or based on criteria related to a user of the targeted user viewing device **104**. In one illustrative example, the image selection module **408** may select a personalized image **422** based on a current advertisement campaign, the time of day, local environment conditions, in response to detected or identified events, and/or other criteria that is not directly related to the user of the user viewing device **104**. Additionally or alternatively, the image selection module **408** may select the personalized image **422** based on aspects or characteristics of the user of the user viewing device **104** such as, for example, physical characteristics of the user, past purchasing behavior, personal preferences, and/or the like. Such user preferences or characteristics may be included in the viewer policy database **410**, which may be used by the image selection module **408** to select the personalized image **422**. As discussed above, the user viewing device **104** may transmit or otherwise provide the viewer policies on which the personalized image selection is based to facilitate some control or filtering by the user over the selection process (e.g., the type of

advertisements, brands, or content the user is interested in).

(38) The personalized images **422** may be embodied as pre-generated images, video with or without associated audio, or other content, which are selected by the image selection module **408** based on a viewer policy or other data. Alternatively, in some embodiments, the personalized images **422** may be generated in real-time or near real-time based on the viewer policy or other data. Although shown in FIG. **4** as being stored on the personalization public display device **102**, the public images **420** and the personalized images **422** may be stored on the remote display server **106** in some embodiments. As such, the display device **102** may retrieve the public images **420** and/or personalized images **422** as needed. In such embodiments, the environment **400** may include an image retrieval module **430** to retrieve the public images **420** and/or personalized images **422** from the remote display server **106**.

(39) The display control module **406** is configured to control the display(s) **208** to present the selected personalized image(s) **422**, as well as any public image **420**. As discussed in more detail below, the display control module **406** may display or otherwise present the selected personalized image **422** based on the established display protocol. For example, the display control module **406** may control the display **208** to display or present a personalized image in an encrypted or obscured manner, which may be subsequently decrypted or unobscured by the user viewing device **104**. Depending on the established display protocol, the display control module **406** may be configured to control aspects of the display itself to display the personalized image **422** in an encrypted or obscured manner. For example, the display control module **406** may be configured to control a visual filter, shuttering, colorization, pixelization, or other aspect of the display **208** to display the personalized image **422**.

(40) Referring now to FIG. **5**, in use, the user viewing device **104** establishes an environment **500**. The illustrative environment **500** includes a display detection module **502**, a viewer personalization module **504**, and a viewer display module **506**. The various modules of the environment **500** may be embodied as hardware, firmware, software, or a combination thereof. For example, the various modules, logic, and other components of the environment **500** may form a portion of, or otherwise be established by, the processor **300** or other hardware components of the user viewing device **104**.

(41) The display detection module **502** is configured to detect the presence of a display device **102** in the local vicinity. To do so, in some embodiments, the viewer detection module **402** may be configured to communicate with the display device **102** to announce the presence of the user viewing device **104**. For example, the display detection module **502** may respond to discovery requests or similar communications received from the display device **102** and/or initiate communications with the display device **102** to indicate that the user viewing device **104** is nearby.

(42) The viewer personalization module **504** is configured to negotiate with the display device **102** to establish the display protocol(s). Similar to the display personalization module **404**, the viewer personalization module **504** may utilize a local viewer policy database **510** to establish the display protocols. The viewer policy database **510** may include, for example, policies or other data that indicate which display protocols the user viewing device **104** is capable of implementing. As such, the viewer personalization module **504** may transmit such data to the display device **102** during the display protocol negotiations.

(43) The viewer policy database **510** may also include policies or other data useable to identify or select a personalized image **422** for presentation to a user of the user viewing device **104**. For example, the viewer policy database **510** may include policies or data that identify personal preferences or characteristics of the user of the user viewing device **104** such as, for example, physical characteristics of the user, past purchasing behavior, likes, dislikes, and/or the like. Again, the viewer personalization module **502** may transmit such data to the display device **102** for use in selecting the personalized image(s) **422**.

(44) The viewer display module **506** is configured to control the local display **308** and/or viewing lens **320** to allow viewing of the personalized image(s) presented by the display device **102**.

Depending on the particular display protocol used, the viewer display module **506** may locally display the personalized image **422** or control the viewing lens **320** to allow viewing of the personalized image **422** displayed by the display device **102**. For example, in some embodiments, the viewer display module **506** may be configured to decrypt or unobscure a personalized image **422** displayed, presented, or transmitted by the display device **102** and locally display or project the decrypted/unobscured personalized image **422** on the local display **308**. In doing so, the viewer display module **506** may locally display the personalized image **422** in an augmented reality manner (e.g., overlaid on the display **208** of the display device **102**). Additionally or alternatively, the viewer display module **506** may control aspects of the viewing lens **320** to allow viewing of the personalized image **422** on the display **208** of the display device **102**. For example, the viewer display module **506** may control an adjustment mechanism of the viewing lens **320** to control visual filtering, shuttering, or other visual quality of the viewing lens **320** to facilitate the viewing of the personalized image **422**.

(45) Referring now to FIGS. **6** and **7**, in use, the personalization public display device **102** may execute a method **600** for personalizing display of images to a viewer. The method **600** begins with block **602** in which the display device **102** monitors for user viewing devices **104**, and/or users of user viewing devices **104**, in proximity to the display device **102**. As discussed above, the display device **102** may use any suitable technology or methodology to discover local user viewing devices **104**. For example, in block **604**, the display device **102** may monitor communication traffic of a local network (e.g., a local ad hoc network) for announcements or other communications from a new user viewing device **104**. Additionally or alternatively, in block **606**, the display device **102** may transmit discovery requests and monitor responses to such signals. For example, in some embodiments, the display device **102** may periodically broadcast a discovery request to detect new user viewing devices **104** within the vicinity. Further, in some embodiment, the display device **102** may receive queries from a user viewing device **104** in block **608**. In such embodiments, the user viewing device **104** may be configured to periodically broadcast queries searching for local display devices **102** as discussed below.

(46) In block **610**, the display device **102** determines whether a new user viewing device **104** has been detected in local proximity to the display device **102**. It should be appreciated that the range of detection (i.e., the proximity threshold) used by the display device **102** to determine the presence, or lack thereof, of a user viewing device **104** may vary depending on the implementation and/or the methodology used to detect the user viewing device **104**. For example, in some embodiments, a user may pre-register with an advertisement service or other display service to receive the personalized images from a network of displays **102**. In such embodiments, the location of the user relative to a nearby display **102** may be tracked based on the location of the user viewing device **104** or other mobile device (e.g., via global positioning system (GPS) tracking). Of course, other methods for determining the location of the user relative to a local display device **102** may be used in other embodiments.

(47) If no user viewing device **104** is detected within the proximity threshold, the method **600** advances to block **612** in which the display device displays or presents a public image **420**. As discussed above, the public image **420** may be embodied as a default image that is viewable by the general public. Alternatively, in some embodiments, the display device **102** may not display a public image **420** but rather obscure the display and/or any personalized images **422** displayed on the display in block **620**, such that the personalized image(s) **422** is not viewable by an unauthorized user viewing device **104**. Additionally or alternatively, the display device **102** may display or present a default personalized image in block **612**. The default personalized image may be selected based on known or expected users or user viewing devices **104** known or expected to be within the vicinity (e.g., based on an instruction from an associated cloud display service or otherwise inferred to be near the display device **102**, even though the user or user viewing device **104** was not successfully detected). Regardless, the method **600** subsequently loops back to block

**602** in which the display device **102** continues to monitor for user viewing devices **104**.

(48) If, however, the display device **102** determines that a new user viewing device **104** is present, the method **600** advances to block **616**. In block **616**, the display device **102** authorizes the detected user viewing device **104** to view personalized images. To do so, the display device **102** may authorize the user viewing device **104** based on any suitable criteria. For example, in block **618**, the display device **102** may receive identification data from the user viewing device **104**. The identification data may be embodied as any type of data that provides an identification of the user viewing device **104** and/or the user **112** of the user viewing device **104**. For example, the identification data may include a model number, serial number, globally unique identification (GUID) number, or other identity data associated with the user viewing device **104**. Additionally or alternatively, the identification data may include data that identifies the user **112**. In such embodiments, the identification data may form a portion of the viewer policy **410**. Further, in some embodiments, the display device **102** may authorize the user viewing device **104** based on the display capabilities of the user viewing device **104**. For example, the display device **102** may authorize the user viewing device **104** to view personalized images **422** based on which display protocols are useable by the user viewing device **104**.

(49) In block **620**, the display device **102** determines whether the detected user viewing device **104** is authorized. If not, the method **600** advances to block **612** in which the display device **102** display the public image **420** (or default personalized image) as discussed above. The method **600** subsequently loops back to block **602** in which the display device **102** continues to monitor for user viewing devices **104**.

(50) If, however, the display device **102** determines that the detected user viewing device **104** is authorized to view a personalized image, the method **600** advances to block **622**. In block **622**, the display device **102** establishes one or more display protocols with the detected user viewing device **104**. To do so, in some embodiments, the display device **102** may be configured to determine or select the display protocol based on the viewer policies stored in the database **410** and/or received from the user viewing device **104**. In such embodiments, the display device **102** may transmit the selected display protocol(s) to the user viewing device **104** in block **624**. Additionally or alternatively, the user viewing device **104** may select or request the display protocol and transmit the selected/requested display protocol, which is received by the display device in block **626**. Of course, in some embodiments, the display device **102** and user viewing device **104** may participate in a more complex negotiation based on other criteria and using any suitable negotiation methodology to arrive at a suitable display protocol.

(51) The method **600** subsequently advances to block **628** of FIG. 7 in which the display device **102** determines the personalized image(s) **422** to be displayed or presented to the authorized user viewing device **104**. As discussed above, the display device **102** may utilize any suitable criteria or data to select the personalized image **422** for display or presentation. For example, in some embodiments, the display device **102** may select the personalized image **422** based on a viewer policy retrieved from the local viewer policy database **410** in block **630**. Additionally or alternatively, the display device may select the personalized image **422** based on a viewer policy received from the user viewing device **104** in block **632**. In some embodiments, the block **634**, the display device **102** may infer a viewer policy on which to select the personalized image **422**. For example, the display device **102** may select the personalized image **422** based on the current time of day, environmental conditions, current sales, advertisement restrictions or conditions, and/or other criteria or data.

(52) After the display device **102** has determined or selected a personalized image(s) **422** for presentation to a user of the authorized user viewing device **104**, the method **600** advances to block **636**. In block **636**, the display device **102** controls the display **208** to display or present the selected personalized image **422**. As discussed above, the display device **102** displays or presents the personalized image **422** in a private manner using the negotiated display protocol such that the

personalized image **422** is viewable by the authorized user viewing device **104** and not viewable by unauthorized user viewing devices **104** or other unauthorized viewers. For example, in block **638**, the display device **102** may display an encrypted or obscured personalized image **422** using the negotiated display protocol. The encrypted/obscured personalized image **422** is not discernable or otherwise viewable by unauthorized user viewing devices **104**. However, user viewing devices **104** employing the negotiated display protocol can decrypt (e.g., via corresponding decryption keys) or otherwise unobscure (e.g. via controlling operation of the viewing lens **320**) the personalized image **422** to allow viewing of the personalized image **422** by the user(s) of the authorized user viewing device **104**. In other embodiments, the display device **102** may transmit the personalized images(s) **422** directly to the user viewing device(s) **104** for presentation thereon. Further, in some embodiments, the display device **102** may be configured to update or periodically change the personalized image **422** displayed or presented to the authorized user viewing device **104**. For example, the display device **102** may change the personalized image **422** in response to interaction from a user of the user viewing device **104** on the user viewing device **104** and/or on the display device **102** itself.

(53) It should be appreciated that the display device **102** may utilize multiple, different display protocols contemporaneously with each other to provide different personalized images **422** to different authorized user viewing devices **104**. In such embodiments, only those personalized images **422** displayed according to the determined display protocol would be viewable by the corresponding authorized user viewing device **104**. That is, personalized images displayed or presented by the display device **102** using another display protocol would not be viewable by an authorized user viewing device **104** configured to use a different display protocol. In this way, the display device **102** may manage multiple personalized images **422** while maintaining privacy between the various personalized images **422**.

(54) In some embodiments, the method **600** may advance to block **640** after presentation of the personalized images **422**. In block **640**, the display device **102** determines whether to track the authorized user viewing device **104** (or user thereof). If not, the method **600** loops back to block **602** in which the display device **102** continues to monitor for additional user viewing devices **104**. If, however, the display device **102** determines to track the authorized user viewing device **104**, the method **600** advances to block **644**.

(55) In block **644**, the display device **102** determines the location of the user viewing device **104** or user thereof. To do so, the display device **102** may utilize any suitable technology or methodology to track the user viewing device **104**. For example, the display device **102** may track the user viewing device **104** using proximity sensors, global positioning system data, image devices, and/or other devices useful in monitoring the location of the user viewing device **104** relative to the display device **102**. Subsequently, in block **646**, the display device **102** controls the display **208** to display or present the personalized image **422** based on the relative location of the user viewing device **104**. For example, in block **648**, the display device **102** may modify or update the display protocol used to display or present the personalized image **422** based on the present location of the user viewing device **104** relative to the display device **102**. In this way, the display device **102** may maintain a level of privacy of the personalized images **422** while the user of the authorized user viewing device **104** moves around. The modification of the display protocol may be particularly useful in those embodiments in which the display protocol adjusts the visual characteristics or properties of the display **208** itself, such as polarization, color filtering, and/or view segmentation.

(56) Referring now to FIG. **8**, in use, the user viewing devices **104** may execute a method **800** for viewing a personalized image. The method **800** begins with block **802** in which the user viewing device **104** monitors for display devices **102** in the local vicinity. Similar to the display device **102**, the user viewing device **104** may use any suitable technology or methodology to discover a nearby display device **102**. For example, in block **804**, the user viewing device **104** may monitor communication traffic of a local network (e.g., a local ad hoc network) for announcements or other

communications from a display device **102**. Additionally or alternatively, in block **806**, the user viewing device **104** may receive and respond to discovery request received from a local display device **102**. Further, in some embodiments, the user viewing device **104** may periodically or responsively transmit queries to nearby display devices **102** in block **808**.

(57) In block **810**, the user viewing device **104** determines whether a display device **102** has been detected nearby. If not, the method **800** loops back to block **802** in which the user viewing device **104** continues monitoring for a display device **102**. If, however, a display device **102** has been detected in the local proximity, the method **800** advances to block **812** in which the user viewing device **104** attempts to authorize itself to the display device **102**. To do so, the user viewing device **104** may utilize any authorization mechanism. For example, in some embodiments, the user viewing device **104** may transmit identification data to the display device **102** in block **814**. As discussed above, the identification data may identify the user viewing device **104** (e.g., a serial number, GUID, or other identification data) and/or a user of the user viewing device **104** (e.g., a user number, account number, name, or other identification data).

(58) In block **816**, the user viewing device **104** determines whether the display device **102** has authorized it to view personalized image(s). If not, the method **800** advances to block **818** in some embodiments. In block **818**, the user viewing device **104** may display or present a public image **420** transmitted or otherwise presented by the display device **102**. For example, in some embodiments, the display device **102** may transmit a public image **420** for display (e.g., via an overlay in an augmented reality manner) to the user viewing device **104**. In such embodiments, if the user viewing device **104** is not authorized, the user viewing device **104** may simply display the received public image on the local display **308**. Regardless, the method **800** subsequently loops back to block **802** in which the user viewing device **104** continues monitoring for a display device **102**.

(59) If, however, the user viewing device **104** has been authorized, the method **800** advances to block **820**. In block **820**, the user viewing device **104** establishes the display protocol(s) with the display device **102**. To do so, the user viewing device **104** may be configured to transmit a suggested, preferred, or required display protocol to the display device **102** in block **822**. As discussed above, the display protocol may be embodied as a portion of the viewer protocol stored in the viewer policy database **510**. Of course, rather than identifying a display protocol specifically, the user viewing device **104** may simply transmit data, on which the display device **102** may select or determine the display protocol. For example, as discussed above, the user viewing device **104** may transmit a viewer policy that includes data identifying the capabilities or features of the user viewing device **104**. In block **824**, the user viewing device **104** may receive the selected or identified display protocol from the display device **102**. Of course, the display protocol may be embodied as features or functions inherent in the user viewing device **104** and, in such case, the user viewing device **104** may simply receive identification data in block **824** that identifies the selected display protocol. Further, in some embodiments, the user viewing device **104** and the display device **102** may not negotiate the display protocol. Rather, the display device **102** may display a personalized image **422** using a predetermined or default display protocol, and the user of the user viewing device **104** may decide whether to not to implement the display protocol on the user viewing device **104** to allow viewing of the personalized image **422**. In this way, the user of the user viewing device **104** may filter which personalized images **422** are to be viewed (and the display device **102** may filter the type, content, brands, or other characteristic of the personalized images based on the display protocol used).

(60) After the display protocol(s) has been established between the user viewing device **104** and the display device **102** in block **820**, the method **800** advances to block **826** in which the user viewing device **104** facilitates the viewing of the personalized image **422** using the established display protocol. Depending on the particular display protocol used, the user viewing device **104** may display the personalized image **422** on the local display **308**, project the personalized image **422** on the viewing lens **320**, and/or control operation of visual features of the viewing lens **320** to allow

viewing of the personalized image **422** displayed on the display **208** of the display device **102**. As such, it should be appreciated that the viewable personalized image **422** may be displayed on either the display device **102** and/or the user viewing device **104** depending on the particular display protocols used. For example, in block **828**, the display device **102** may display the personalized image **422** in an obscured manner on the display **208** using a suitable display protocol (e.g., polarization, color filtering, or view segmentation), and the user viewing device **104** may control operation of the visual characteristics of the viewing lens **320** based on the established display protocol to enable a user of the user viewing device **104** to view the personalized image **422** on the display **208**. Additionally or alternatively, in block **830**, the display device may transmit an encrypted personalized image **422** to the user viewing device **104**, which decrypts the encrypted personalized image **422** in block **830** and displays the decrypted personalized image **422** on the local display **308** or projects the decrypted personalized image **422** on the viewing lens **320** (e.g., in an augmented reality manner).

(61) As discussed above, the display device **102** may be configured to adjust or update the display protocols based on the location of the user viewing device **104** relative to the display device **102**. In such embodiments, the user viewing device **104** may display, project, or otherwise present the personalized image **422** to the user of the user viewing device **104** based on the present location of the user viewing device **104**. That is, in such embodiments, the user viewing device **104** may be configured to update or adjust the display protocol consistent with the display device **102**.

Additionally, in some embodiments, the display device **102** and/or user viewing device **104** may update the display protocol and/or personalized image(s) based on the user's interaction with the user viewing device **104** and/or the display device **102**. For example, the user of the user viewing device **104** may interact with the displayed or presented personalized image **422** on the user viewing device **104** or the display device **102** to cause the display device **102** to display or present other personalized images in response to the user's interaction (e.g., a subsequent advertisement based on the user's interaction with an initial advertisement or image). Subsequently, the method **800** loops back to block **802** in which the user viewing device **104** continues monitoring for a display device **102**.

(62) Although the system **100** has been described above in regard to the display or presentation of personalized images or video, it should be appreciated that the system **100** may be utilized to disseminate additional or other content in a private manner in other embodiments. For example, the technologies and techniques disclosed herein may be utilized to present personalized audio or other digital content using a negotiated audio protocol, similar to the video protocol described above.

## EXAMPLES

(63) Illustrative examples of the devices, systems, and methods disclosed herein are provided below. An embodiment of the devices, systems, and methods may include any one or more, and any combination of, the examples described below.

(64) Example 1 includes a display device for displaying personalized images, the display device comprising a viewer detection module to determine whether a user viewing device is in a proximity to the display device; a display personalization module to (i) authorize the user viewing device to view a personalized image in response to a determination that the user viewing device is in the proximity and (ii) establish a display protocol with the user viewing device in response to authorization of the user viewing device, wherein the display protocol is useable by the display device to display the personalized image; and a display control module to control a display to display the personalized image to a user of the user viewing device based on the display protocol, wherein the personalized image is (i) viewable by the user viewing device and (ii) is not viewable by unauthorized viewing devices.

(65) Example 2 includes the subject matter of Example 1, and wherein to control the display of the display device comprises to display the personalized image in an encrypted or obfuscated format on the display.



(66) Example 3 includes the subject matter of any of Examples 1 and 2, and wherein to control the display of the display device comprises to display the personalized image and a public image on the display, the public image viewable by unauthorized viewing devices.

(67) Example 4 includes the subject matter of any of Examples 1-3, and wherein the display protocol is (i) usable by the display device to obscure the personalized image on the display device and (ii) usable by the user viewing device to unobscure the personalized image on the user viewing device.

(68) Example 5 includes the subject matter of any of Examples 1-4, and wherein the display protocol comprises an encryption protocol (i) usable by the display device to encrypt the personalized image on the display device and (ii) usable by the user viewing device to decrypt the personalized image on the user viewing device.

(69) Example 6 includes the subject matter of any of Examples 1-5, and wherein the display protocol comprises at least one of a polarization display protocol, a color filtering display protocol, a view segmentation display protocol, a layered depth variation display protocol, a pixel obfuscation display protocol, or a pixel encoding display protocol.

(70) Example 7 includes the subject matter of any of Examples 1-6, and wherein to authorize the user viewing device comprises to receive identification data from the user viewing device, the identification data identifying at least one of the user viewing device or the user of the user viewing device.

(71) Example 8 includes the subject matter of any of Examples 1-7, and wherein to authorize the user viewing device comprises to determine the personalized image based on a viewer policy associated with the user of the user viewing device.

(72) Example 9 includes the subject matter of any of Examples 1-8, and wherein to determine the personalized image comprises to determine the personalized image based on a viewer policy that defines a characteristic of at least one of the user viewing device or the user of the user viewing device.

(73) Example 10 includes the subject matter of any of Examples 1-9, and wherein to determine the personalized image comprises to determine the personalized image based on an analysis of an image of the user of the user viewing device.

(74) Example 11 includes the subject matter of any of Examples 1-10, and further including a local storage, wherein the viewer policy is stored in the local storage and the display personalization module is further to retrieve the viewer policy from the local storage.

(75) Example 12 includes the subject matter of any of Examples 1-11, and wherein the display personalization module is further to receive the viewer policy from the user viewing device.

(76) Example 13 includes the subject matter of any of Examples 1-12, and further including a sensor to generate sensor data indicative of a characteristic of at least one of the user viewing device or the user of the user viewing device, wherein the display personalization module is to infer the viewer policy based on the sensor data.

(77) Example 14 includes the subject matter of any of Examples 1-13, and wherein to determine whether the user viewing device is in the proximity comprises to monitor a network connection to which the display device is connected for network communication from the user viewing device.

(78) Example 15 includes the subject matter of any of Examples 1-14, and wherein the viewer detection module is to transmit a discovery request to the user viewing device; and receive a response from the user viewing device in response to the discovery request.

(79) Example 16 includes the subject matter of any of Examples 1-15, and wherein to determine whether the user viewing device is in the proximity comprises to receive a query communication from the user viewing device.

(80) Example 17 includes the subject matter of any of Examples 1-16, and wherein the display personalization module is further to track a position of the user viewing device relative to the display device, and the display control module is to control the display to display the personalized

image to the user of the user viewing device based on the display protocol and the position of the user viewing device relative to the display device.

(81) Example 18 includes the subject matter of any of Examples 1-17, and wherein the display personalization module is further to detect an interaction of a user of the user viewing device with the display device or the user viewing device, and the display control module is to control the display to display the personalized image to the user of the user viewing device based on the display protocol and the detected interaction.

(82) Example 19 includes the subject matter of any of Examples 1-18, and wherein the display personalization module is further to track a position of the user viewing device relative to the display device; and update the display protocol based on the position of the user viewing device relative to the display device.

(83) Example 20 includes the subject matter of any of Examples 1-19, and wherein the display control module is further to generate an audio signal associated with the personalized image, wherein the audio signal is (i) playable by the user viewing device and (ii) not playable by unauthorized viewing devices.

(84) Example 21 includes a user viewing device usable to view a personalized image generated by a display device, the user viewing device comprising a display detection module to determine whether the display device is in a proximity to the user viewing device; a viewer personalization module to (i) communicate with the display device to authorize the user viewing device to view a personalized image generated by the display device in response to a determination that the display device is in the proximity and (ii) establish, with the display device, a display protocol usable by the user viewing device to view the personalized image; and a viewer display module to facilitate the viewing of the personalized image by a user of the user viewing device based on the display protocol.

(85) Example 22 includes the subject matter of Example 21, and wherein to facilitate the viewing of the personalized image comprises to decrypt an encrypted personalized image based on the display protocol.

(86) Example 23 includes the subject matter of any of Examples 21 and 22, and further including a display, and wherein to facilitate the viewing of the personalized image comprises to control the display of the user viewing device to display the personalized image on the user viewing device based on the display protocol.

(87) Example 24 includes the subject matter of any of Examples 21-23, and further including a viewing lens, and wherein to facilitate the viewing of the personalized image comprises to control the viewing lens of the user viewing device based on the display protocol to enable the user to view the personalized image displayed by the display device.

(88) Example 25 includes the subject matter of any of Examples 21-24, and wherein to facilitate the viewing of the personalized image comprises to facilitate the viewing of the personalized image by the user of the user viewing device based on the display protocol and a location of the user viewing device relative to the display device.

(89) Example 26 includes the subject matter of any of Examples 21-25, and wherein the viewer display module is to facilitate the viewing of the personalized image by the user of the user viewing device based on the display protocol and an interaction of the user with the user viewing device or the display device.

(90) Example 27 includes the subject matter of any of Examples 21-26, and wherein the viewer personalization module is to receive the personalized image from the display device.

(91) Example 28 includes the subject matter of any of Examples 21-27, and wherein the display protocol comprises a display protocol (i) usable by the display device to obscure the personalized image on the display device and (ii) usable by the user viewing device to unobscure the personalized image on the user viewing device.

(92) Example 29 includes the subject matter of any of Examples 21-28, and wherein the display

protocol comprises an encryption protocol (i) usable by the display device to encrypt the personalized image on the display device and (ii) usable by the user viewing device to decrypt the personalized image on the user viewing device.

(93) Example 30 includes the subject matter of any of Examples 21-29, and wherein the display protocol comprises at least one of a polarization display protocol, a color filtering display protocol, a view segmentation display protocol, a layered depth variation display protocol, a pixel obfuscation display protocol, or a pixel encoding display protocol.

(94) Example 31 includes the subject matter of any of Examples 21-30, and further including a viewing lens, wherein the viewing lens comprises an adjustment mechanism to adjust a visual characteristic of the lens, and wherein the display protocol comprises a control protocol to control the adjustment mechanism of the viewing lens.

(95) Example 32 includes the subject matter of any of Examples 21-31, and wherein to communicate with the display device to authorize the user viewing device comprises to transmit, to the display device, identification data that identifies least one of the user viewing device or the user of the user viewing device.

(96) Example 33 includes the subject matter of any of Examples 21-32, and wherein to communicate with the display device to authorize the user viewing device comprises to transmit, to the display device, a user viewing policy associated with the user of the user viewing device.

(97) Example 34 includes the subject matter of any of Examples 21-33, and wherein the viewer policy defines a characteristic of at least one of the user viewing device or the user of the user viewing device.

(98) Example 35 includes the subject matter of any of Examples 21-34, and wherein to determine whether the display device is in a proximity comprises to monitor a network connection to which the user viewing device is connected for network communication from the display device.

(99) Example 36 includes the subject matter of any of Examples 21-35, and wherein to determine whether the display device is in a proximity comprises to receive a discovery request transmitted by the display device; and transmit a response to the display device in response to the discovery request.

(100) Example 37 includes the subject matter of any of Examples 21-36, and wherein to determine whether the display device is in a proximity comprises to transmit a query communication to the display device.

(101) Example 38 includes a method for displaying personalized images on a display device, the method comprising determining, by the display device, whether a user viewing device is in a proximity to the display device; authorizing, by the display device, the user viewing device to view a personalized image in response to a determination that the user viewing device is in the proximity; establishing, by the display device and with the user viewing device, a display protocol useable to display the personalized image in response to authorizing the user viewing device; and controlling a display to display the personalized image to a user of the user viewing device based on the display protocol such that the personalized image is (i) viewable by the user viewing device and (ii) is not viewable by unauthorized viewing devices.

(102) Example 39 includes the subject matter of Example 38, and wherein controlling the display of the display device comprises displaying the personalized image in an encrypted or obfuscated format on the display.

(103) Example 40 includes the subject matter of any of Examples 38 and 39, and wherein controlling the display of the display device comprises displaying the personalized image on the display while displaying a public image on the display, the public image viewable by unauthorized viewing devices.

(104) Example 41 includes the subject matter of any of Examples 38-40, and wherein establishing the display protocol comprises establishing a display protocol (i) usable by the display device to obscure the personalized image on the display device and (ii) usable by the user viewing device to

unobscured the personalized image on the user viewing device.

(105) Example 42 includes the subject matter of any of Examples 38-41, and wherein establishing the display protocol comprises establishing an encryption protocol (i) usable by the display device to encrypt the personalized image on the display device and (ii) usable by the user viewing device to decrypt the personalized image on the user viewing device.

(106) Example 43 includes the subject matter of any of Examples 38-42, and wherein establishing the display protocol comprises establishing at least one of a polarization display protocol, a color filtering display protocol, a view segmentation display protocol, a layered depth variation display protocol, a pixel obfuscation display protocol, or a pixel encoding display protocol.

(107) Example 44 includes the subject matter of any of Examples 38-43, and wherein authorizing the user viewing device comprises receiving identification data from the user viewing device, the identification data identifying at least one of the user viewing device or the user of the user viewing device.

(108) Example 45 includes the subject matter of any of Examples 38-44, and wherein authorizing the user viewing device comprises determining the personalized image based a viewer policy associated with the user of the user viewing device.

(109) Example 46 includes the subject matter of any of Examples 38-45, and wherein determining the personalized image comprises determining the personalized image based on a viewer policy that defines a characteristic of at least one of the user viewing device or the user of the user viewing device.

(110) Example 47 includes the subject matter of any of Examples 38-46, and determining the personalized image comprises determining the personalized image based on an analysis of an image of the user of the user viewing device.

(111) Example 48 includes the subject matter of any of Examples 38-47, and further including retrieving the viewer policy from a local storage.

(112) Example 49 includes the subject matter of any of Examples 38-48, and further including receiving the viewer policy from the user viewing device.

(113) Example 50 includes the subject matter of any of Examples 38-49, and further including generating, by a sensor of the display device, sensor data indicative of a characteristic of at least one of the user viewing device or the user of the user viewing device; and inferring the viewer policy based on the sensor data.

(114) Example 51 includes the subject matter of any of Examples 38-50, and wherein detecting the user viewing device comprises monitoring a network connection to which the display device is connected for network communication from the user viewing device.

(115) Example 52 includes the subject matter of any of Examples 38-51, and wherein detecting the user viewing device comprises transmitting, by the display device, a discovery request to the user viewing device; and receiving, by the display device, a response from the user viewing device in response to the discovery request.

(116) Example 53 includes the subject matter of any of Examples 38-52, and wherein detecting the user viewing device comprises receiving a query communication from the user viewing device.

(117) Example 54 includes the subject matter of any of Examples 38-53, and further including tracking a position of the user viewing device relative to the display device; and wherein controlling the display of the display device comprises controlling the display of the display device to display the personalized image to the user of the user viewing device based on the display protocol and the position of the user viewing device relative to the display device.

(118) Example 55 includes the subject matter of any of Examples 38-54, and further including detecting an interaction of a user of the user viewing device with the display device or the user viewing device, and wherein controlling the display of the display device comprises controlling the display of the display device to display the personalized image to the user of the user viewing device based on the display protocol and the detected interaction.

(119) Example 56 includes the subject matter of any of Examples 38-55, and further including tracking a position of the user viewing device relative to the display device; and updating the display protocol based on the position of the user viewing device relative to the display device.

(120) Example 57 includes the subject matter of any of Examples 38-56, and, further including generating an audio signal associated with the personalized image, wherein the audio signal is (i) playable by the user viewing device and (ii) not playable by unauthorized viewing devices.

(121) Example 58 includes a display device for displaying personalized images, the display device comprising a display; a processor; and a memory having stored therein a plurality of instructions that when executed by the processor cause the display device to perform the method of any of Examples 34-51.

(122) Example 59 includes one or more machine readable storage media comprising a plurality of instructions stored thereon that in response to being executed result in a display device performing the method of any of Examples 34-51.

(123) Example 60 includes a method for viewing a personalized image generated by a display device, the method comprising determining, by a user viewing device, whether a display device is in a proximity to the user viewing device; communicating, by the user viewing device, with the display device to authorize the user viewing device to view a personalized image generated by the display device in response to a determination that the display device is in the proximity; establishing, by the user viewing device and with the display device, a display protocol usable by the user viewing device to view the personalized image; and facilitating, by the user viewing device, the viewing of the personalized image by a user of the user viewing device based on the display protocol.

(124) Example 61 includes the subject matter of Example 60, and wherein facilitating the viewing of the personalized image comprises decrypting an encrypted personalized image based on the display protocol.

(125) Example 62 includes the subject matter of any of Examples 60 and 61, and wherein facilitating the viewing of the personalized image comprises controlling a display of the user viewing device to display the personalized image on the user viewing device based on the display protocol.

(126) Example 63 includes the subject matter of any of Examples 60-62, and wherein facilitating the viewing of the personalized image comprises controlling a viewing lens of the user viewing device based on the display protocol to enable the user to view the personalized image displayed by the display device.

(127) Example 64 includes the subject matter of any of Examples 60-63, and wherein facilitating the viewing of the personalized image comprises receiving, by the user viewing device, the personalized image from the display device.

(128) Example 65 includes the subject matter of any of Examples 60-64, and wherein facilitating the viewing of the personalized image comprises facilitating, by the user viewing device, the viewing of the personalized image by the user of the user viewing device based on the display protocol and a location of the user viewing device relative to the display device.

(129) Example 66 includes the subject matter of any of Examples 60-65, and wherein facilitating the viewing of the personalized image comprises facilitating, by the user viewing device, the viewing of the personalized image by the user of the user viewing device based on the display protocol and an interaction of the user with the user viewing device or the display device.

(130) Example 67 includes the subject matter of any of Examples 60-66, and wherein establishing the display protocol comprises a display protocol (i) usable by the display device to obscure the personalized image on the display device and (ii) usable by the user viewing device to unobscure the personalized image on the user viewing device.

(131) Example 68 includes the subject matter of any of Examples 60-67, and wherein establishing the display protocol comprises establishing an encryption protocol (i) usable by the display device

to encrypt the personalized image on the display device and (ii) usable by the user viewing device to decrypt the personalized image on the user viewing device.

(132) Example 69 includes the subject matter of any of Examples 60-68, and wherein establishing the display protocol comprises establishing at least one of a polarization display protocol, a color filtering display protocol, a view segmentation display protocol, a layered depth variation display protocol, a pixel obfuscation display protocol, or a pixel encoding display protocol.

(133) Example 70 includes the subject matter of any of Examples 60-69, and wherein communicating with the display device to authorize the user viewing device comprises transmitting, by the user viewing device and to the display device, identification data that identifies least one of the user viewing device or the user of the user viewing device.

(134) Example 71 includes the subject matter of any of Examples 60-70, and wherein communicating with the display device to authorize the user viewing device comprises transmitting, by the user viewing device and to the display device, a user viewing policy associated with the user of the user viewing device.

(135) Example 72 includes the subject matter of any of Examples 60-71, and wherein the viewer policy defines a characteristic of at least one of the user viewing device or the user of the user viewing device.

(136) Example 73 includes the subject matter of any of Examples 60-72, and wherein detecting the display device comprises monitoring a network connection to which the user viewing device is connected for network communication from the display device.

(137) Example 74 includes the subject matter of any of Examples 60-73, and wherein detecting the display device comprises receiving, by user viewing device, a discovery request transmitted by the display device; and transmitting, by the user viewing device, a response to the display device in response to the discovery request.

(138) Example 75 includes the subject matter of any of Examples 60-74, and wherein detecting the display device comprises transmitting a query communication to the display device.

(139) Example 76 includes a user viewing device usable to view a personalized image generated by a display device, the user viewing device comprising a processor; and a memory having stored therein a plurality of instructions that when executed by the processor cause the user viewing device to perform the method of any of Examples 54-68.

(140) Example 77 includes one or more machine readable storage media comprising a plurality of instructions stored thereon that in response to being executed result in a user viewing device performing the method of any of Examples 54-68.

## Claims

1. An apparatus comprising: processing circuitry coupled to a memory, the processing circuitry to: monitor for display devices and user viewing devices within a vicinity; establish display protocol between a user viewing device and a display device if the user viewing device and the display device are found in the vicinity and within a proximity of each other, wherein the user viewing device includes an authorized user viewing device; and facilitate viewing of one or more personalized images using the user viewing device, wherein the one or more personalized images are displayed using the display device or one or more local display devices associated with the user viewing device, wherein the display protocol is modifiable with changes to locations of a user having access to the user viewing device, wherein the display protocol to define levels of accessibility associated with the one or more personalized images.
2. The apparatus of claim 1, wherein the one or more personalized images are displayed based on the display protocol such that the one or more personalized images are not accessible to one or more unauthorized user viewing devices.
3. The apparatus of claim 1, wherein the processing circuitry is further to locate the user viewing

device and authenticate the user viewing device prior to establishing the display protocol between the user viewing device and the display device, wherein the one or more personalized images are displayed controlled through encryption or obfuscation.

4. The apparatus of claim 1, wherein the processing circuitry is further to exchange identifying data between the user viewing device and the display device based on query requests or discovery requests, and wherein the user viewing device and the display device are placed in communication with each other via a communication network.

5. The apparatus of claim 1, wherein the processing circuitry is further to facilitate viewing of one or more public images using the user viewing device, wherein the one or more public images are viewable by one or more unauthorized user viewing devices, wherein the processing circuitry comprises one or more of application processing circuitry or graphics processing circuitry.

6. The apparatus of claim 1, wherein the processing circuitry is further to: track a position of the user viewing device relative to the display device; and update the display protocol based on the position of the user viewing device relative to the display device, wherein the user viewing device comprises a mobile computing device.

7. A method comprising: monitoring, by a computing device, for display devices and user viewing devices within a vicinity; establishing display protocol between a user viewing device and a display device if the user viewing device and the display device are found in the vicinity and within a proximity of each other, wherein the user viewing device includes an authorized user viewing device; and facilitating viewing of one or more personalized images using the user viewing device, wherein the one or more personalized images are displayed using the display device or one or more local display devices associated with the user viewing device, wherein the display protocol is modifiable with changes to locations of a user having access to the user viewing device, wherein the display protocol to define levels of accessibility associated with the one or more personalized images.

8. The method of claim 7, wherein the one or more personalized images are displayed based on the display protocol such that the one or more personalized images are not accessible to one or more unauthorized user viewing devices.

9. The method of claim 7, further comprising locating the user viewing device and authenticating the user viewing device prior to establishing the display protocol between the user viewing device and the display device, wherein the one or more personalized images are displayed controlled through encryption or obfuscation.

10. The method of claim 7, further comprising exchanging identifying data between the user viewing device and the display device based on query requests or discovery requests, and wherein the user viewing device and the display device are placed in communication with each other via a communication network.

11. The method of claim 7, further comprising facilitating viewing of one or more public images using the user viewing device, wherein the one or more public images are viewable by one or more unauthorized user viewing devices, wherein the computing device comprises processing circuitry coupled to a memory, the processing circuitry having one or more of application processing circuitry or graphics processing circuitry.

12. The method of claim 7, further comprising: tracking a position of the user viewing device relative to the display device; and updating the display protocol based on the position of the user viewing device relative to the display device, wherein the user viewing device comprises a mobile computing device.

13. At least one non-transitory computer-readable medium having stored thereon instructions which, when executed, cause a computing device to perform operations comprising: monitoring for display devices and user viewing devices within a vicinity; establishing display protocol between a user viewing device and a display device if the user viewing device and the display device are found in the vicinity and within a proximity of each other, wherein the user viewing device

includes an authorized user viewing device; and facilitating viewing of one or more personalized images using the user viewing device, wherein the one or more personalized images are displayed using the display device or one or more local display devices associated with the user viewing device, wherein the display protocol is modifiable with changes to locations of a user having access to the user viewing device, wherein the display protocol to define levels of accessibility associated with the one or more personalized images.

14. The non-transitory computer-readable medium of claim 13, wherein the one or more personalized images are displayed based on the display protocol such that the one or more personalized images are not accessible to one or more unauthorized user viewing devices.

15. The non-transitory computer-readable medium of claim 13, wherein the operations further comprise locating the user viewing device and authenticating the user viewing device prior to establishing the display protocol between the user viewing device and the display device, wherein the one or more personalized images are displayed controlled through encryption or obfuscation.

16. The non-transitory computer-readable medium of claim 13, wherein the operations further comprise exchanging identifying data between the user viewing device and the display device based on query requests or discovery requests, and wherein the user viewing device and the display device are placed in communication with each other via a communication network.

17. The non-transitory computer-readable medium of claim 13, wherein the operations further comprise facilitating viewing of one or more public images using the user viewing device, wherein the one or more public images are viewable by one or more unauthorized user viewing devices, wherein the computing device comprises processing circuitry coupled to a memory, the processing circuitry having one or more of application processing circuitry or graphics processing circuitry.

18. The non-transitory computer-readable medium of claim 13, wherein the operations further comprise: tracking a position of the user viewing device relative to the display device; and updating the display protocol based on the position of the user viewing device relative to the display device, wherein the user viewing device comprises a mobile computing device.

---